Question 1

Not yet answered

Marked out of 1.00

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;

class Base
{
public:
virtual void print() const = 0;
};

class DerivedOne : virtual public Base
{
public:
void print() const
{
cout << "1";
}
};

class DerivedTwo : virtual public Base
{
public:
void print() const
{
cout << "2";
}
};

class Multiple : public DerivedOne, DerivedTwo
{
public:
void print() const
{
DerivedTwo::print();
}
};

int main()
{
Multiple both;
DerivedOne one;
DerivedTwo two;
Base *array[ 3 ];
array[ 0 ] = &both;
array[ 1 ] = &one;
array[ 2 ] = &two;
for ( int i = 0; i < 3; i++ )
array[ i ] -> print();
return 0;
}
```

Select one:

- **a. 212**
- **b. 215**
- **c. 121**

d. 12

Question 2

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int main()
{
cout<<(int i=5) << (int j=6);
}
```

Select one:

a. Prints 5 6

b. Compilation fails

c. Segmentation fault

d. None of these

Question **3**

Not yet answered

Marked out of 1.00

Given:

```
interface Hungry<E> { void munch(E x); }
interface Carnivore<E extends Animal> extends Hungry<E> {}
interface Herbivore<E extends Plant> extends Hungry<E> {}
abstract class Plant {}
class Grass extends Plant {}
abstract class Animal {}
class Sheep extends Animal implements Herbivore<Sheep> {
public void munch(Sheep x) {}
}
class Wolf extends Animal implements Carnivore<Sheep> {
public void munch(Sheep x) {}
}
```

Which of the following changes (taken separately) would allow this code to compile?
(Choose all that apply.)

Select one or more:

- ☐ **a. Change the Herbivore interface to**
  `interface Herbivore<E extends Animal> extends Hungry<E> {}`
- ☐ **b. Change the Sheep class to**
  `class Sheep extends Plant implements Carnivore<Wolf> {`
  `public void munch(Wolf x) {}`
  `}`
- ☐ **c. Change the Sheep class to**
  `class Sheep extends Animal implements Herbivore<Plant> {`
  `public void munch(Grass x) {}`
  `}`
- ☐ **d. No changes are necessary**
- ☐ **e. Change the Wolf class to**
  `class Wolf extends Animal implements Herbivore<Grass> {`
  `public void munch(Grass x) {}`
  `}`
- ☐ **f. Change the Carnivore interface to**
  `interface Carnivore<E extends Plant> extends Hungry<E> {}`

Question **4**

Not yet answered

Marked out of 1.00

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;

class sample
{
public:
virtual void example() = 0;
};

class Ex1:public sample
{
public:
void example()
{
cout << "hello ";
}
};

class Ex2:public sample
{
public:
void example()
{
cout << "world";
}
};

int main()
{
sample* arra[2];
Ex1 e1;
Ex2 e2;
arra[0]=&e1;
arra[1]=&e2;
arra[0]->example();
arra[1]->example();
}
```

Select one:

- **a. hello**
- **b. Compilation fails**
- **c. world**
- **d. hello world**

Question 5

Not yet answered

Marked out of 1.00

Given:

```
class Boo {
Boo(String s) { }
Boo() { }
}
class Bar extends Boo {
Bar() { }
Bar(String s) {super(s);}
void zoo() {
// insert code here
}
}
```

Which create an anonymous inner class from within class Bar? (Choose all that apply.)

Select one or more:

- ☐ **a. Bar f = new Boo(String s) { };**
- ☐ **b. Boo f = new Boo(24) { };**
- ☐ **c. Boo f = new Boo.Bar(String s) { };**
- ☐ **d. Boo f = new Bar() { };**
- ☐ **e. Boo f = new Boo() {String s; };**

Question 6

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include<stdio.h>
void foo(void)
{
static int staticVar;
staticVar++;
printf("foo: %d\n",staticVar);
}

void bar(void)
{
static int staticVar;
staticVar++;
printf("bar: %d\n",staticVar);
}

int main()
{
foo(), bar(), foo();
return 0;
}
```

Select one:

- **a. No compile error and separate copies of staticVar would be used in both the functions.**
  That's why staticVar in foo() would be 2 while staticVar in bar() would be 1.
- **b. Compile error because semicolon isn't used while calling foo() and bar() in side main function.**
- **c. Compile error because same static variable name is used in both foo and bar.**
  Since these static variables retain their values even after function is over, same name can't be used in both the functions.
- **d. No compile error and only one copy of staticVar would be used across both the functions and that's why final value of that single staticVar would be 3.**

Question 7

Not yet answered

Marked out of 1.00

The following block of code creates a Thread using a Runnable target:

```
Runnable target = new MyRunnable();
Thread myThread = new Thread(target);
```

Which of the following classes can be used to create the target, so that the preceding code compiles correctly?

Select one:

- **a. public class MyRunnable implements Runnable{public void run(){}}**
- **b. public class MyRunnable extends Object{public void run(){}}**
- **c. public class MyRunnable extends Runnable{public void run(){}}**
- **d. public class MyRunnable implements Runnable{public void start(){}}**
- **e. public class MyRunnable implements Runnable{void run(){}}**

Question 8

Not yet answered

Marked out of 1.00

What will be the order of execution of base class constructors in the following method of inheritance?

class A: public B, virtual public C {….};

Select one:

- **a. B(); A(); C();**
- **b. C(); B(); A();**
- **c. A(); B(); C();**
- **d. B(); C(); A();**

Question **9**

Not yet answered

Marked out of 1.00

Given:

```
import java.util.*;
class MapEQ {
public static void main(String[] args) {
Map<ToDos, String> m = new HashMap<ToDos, String>();
ToDos t1 = new ToDos("Monday");
ToDos t2 = new ToDos("Monday");
ToDos t3 = new ToDos("Tuesday");
m.put(t1, "doLaundry");
m.put(t2, "payBills");
m.put(t3, "cleanAttic");
System.out.println(m.size());
} }
class ToDos{
String day;
ToDos(String d) { day = d; }
public boolean equals(Object o) {
return ((ToDos)o).day == this.day;
}
// public int hashCode() { return 9; }
}
```

Which is correct? (Choose all that apply.)

Select one or more:

- ☐ **a. As the code stands it will not compile**
- ☐ **b. If the hashCode() method is uncommented the code will not compile**
- ☐ **c. If the hashCode() method is uncommented the output will be 2**
- ☐ **d. As the code stands the output will be 2**
- ☐ **e. If the hashCode() method is uncommented the output will be 3**
- ☐ **f. As the code stands the output will be 3**

Question **10**

Not yet answered

Marked out of 1.00

A process executes the following code

```
for (i = 0; i < n; i++)
fork();
```

The total number of child processes created is

Select one:

- ○ **a. n**
- ○ **b. 2n - 1**
- ○ **c. 2(n+1) - 1**
- ○ **d. 2n**

Question **11**

Not yet answered

Marked out of 1.00

Given:

```
12. public class AccountManager {
13. private Map accountTotals = new HashMap();
14. private int retirementFund;
15.
16. public int getBalance(String accountName) {
17. Integer total = (Integer) accountTotals.get(accountName);
18. if (total == null)
19. total = Integer.valueOf(0);
20. return total.intValue();
21. }
23. public void setBalance(String accountName, int amount) {
24. accountTotals.put(accountName, Integer.valueOf(amount));
25. } }
```

This class is to be updated to make use of appropriate generic types, with no changes in behavior (for better or worse).

Which of these steps could be performed? (Choose three.)

Select one or more:

- ☐ **a. Replace line 24 with**
  accountTotals.put(accountName, amount.intValue());
- ☐ **b. Replace line 13 with**
  private Map<String<Integer>> accountTotals = new HashMap<String<Integer>>();
- ☐ **c. Replace lines 17–20 with**
  int total = accountTotals.get(accountName);
  if (total == null) total = 0;
  return total;
- ☐ **d. Replace line 24 with**
  accountTotals.put(accountName, amount);
- ☐ **e. Replace line 13 with**
  private Map<String, Integer> accountTotals = new HashMap<String, Integer>();
- ☐ **f. Replace lines 17–20 with**
  Integer total = accountTotals.get(accountName);
  if (total == null) total = 0;
  return total;
- ☐ **g. Replace line 13 with**
  private Map<String, int> accountTotals = new HashMap<String, int>();
- ☐ **h. Replace lines 17–20 with**
  return accountTotals.get(accountName);

Question 12

Not yet answered

Marked out of 1.00

Output of the following in C Language

Suppose a, b, c and d are int variables. For ternary operator in C (? :), pick the best statement.

Select one:

- **a. a>b ? : ; is valid statement i.e. 2nd and 3rd operands can be empty and they are implicitly replaced with non-zero value at run-time.**
- **b. All of these are valid statements for ternary operator.**
- **c. a>b ? c=10 : d=10; is valid statement. Based on the value of a and b, either c or d gets assigned the value of 10.**
- **d. a>b ? (c=10,d=20) : (c=20,d=10); is valid statement. Based on the value of a and b, either c=10,d=20 gets executed or c=20,d=10 gets executed.**

Question 13

Not yet answered

Marked out of 1.00

Which are true about a static nested class? (Choose all that apply.)

Select one or more:

- **a. Its variables and methods must be static**
- **b. It does not have access to non-static members of the enclosing class**
- **c. You must have a reference to an instance of the enclosing class in order to instantiate it**
- **d. If the outer class is named MyOuter, and the nested class is named MyInner, it can be instantiated using new MyOuter.MyInner();**
- **e. It must extend the enclosing class**

Question 14

Not yet answered

Marked out of 1.00

Which of the following is correct with respect to "Jump Statements" in C?

Select one:

- **a. continue**
- **b. return**
- **c. break**
- **d. goto**
- **e. All of these**

Question **15**

Not yet answered

Marked out of 1.00

output of the following CPP Code

```
#include<iostream>
using namespace std;
class signal1
{
public:
int a:20;
int b:10;
};
int main()
{
signal1 s = {5,7};
cout<<s.a<<" "<<s.b;
}
```

Select one:

- **a. prints 5 7**
- **b. compilation fails**
- **c. prints 5 followed by garbage value**
- **d. Segmentation fault**
- **e. prints 5 followed by 5**

Question **16**

Not yet answered

Marked out of 1.00

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;

class stu
{
protected:
int rno;
public:
void get_no(int a)
{
rno = a;
}
void put_no(void)
{
}
};

class test:public stu
{
protected:
float part1,part2;
public:
void get_mark(float x, float y)
{
part1 = x;
part2 = y;
}
void put_marks()
{
}
};

class sports
{
protected:
float score;
public:
void getscore(float s)
{
score = s;
}
void putscore(void)
{
}
};

class result: public test, public sports
{
float total;
public:
void display(void);
};
void result::display(void)
{
total = part1 + part2 + score;
```

```
put_no();
put_marks();
putscore();
cout << "Total Score=" << total << "\n";
}
int main()
{
result stu;
stu.get_no(123);
stu.get_mark(27.5, 33.0);
stu.getscore(6.0);
stu.display();
return 0;
}
```

Select one:

- **a. 64.5**
- **b. 60.5**
- **c. 66.5**
- **d. 62.5**

Question **17**

Not yet answered

Marked out of 1.00

What's going to happen when we compile and run the following C program?

```
#include<stdio.h>

int main()
{
int i = 1, j;
for ( ; ; )
{
if (i)
j = --i;
if (j < 10)
printf("helloWorld", j++);
else
break;
}
return 0;
}
```

Select one:

- **a. it'll print helloWorld 10 times.**
- **b. it'll print helloWorld 9 times.**
- **c. it will run into infinite loop printing helloWorld.**
- **d. Compile Error.**

Question **18**

Not yet answered

Marked out of 1.00

Consider the following C function:

```
int f(int n)
{
static int i = 1;
if (n >= 5)
return n;
n = n+i;
i++;
return f(n);
}
```

The value returned by f(1) is

Select one:

- **a. 6**
- **b. 7**
- **c. 8**
- **d. 5**

Question **19**

Not yet answered

Marked out of 1.00

Suppose that in a C program snippet, followings statements are used.

i) sizeof(int);
ii) sizeof(int*);
iii) sizeof(int**);

Assuming size of pointer is 4 bytes and size of int is also 4 bytes, pick the most correct answer from the given options.

Select one:

- **a. i), ii) and iii) would compile successfully but the size of each would be different and would be decided at run time.**
- **b. ii) and iii) would result in compile error but i) would compile and result in size as 4.**
- **c. i), ii) and iii) would compile successfully and size of each would be same i.e. 4**
- **d. Only i) would compile successfully and it would return size as 4.**

Question **20**

Not yet answered

Marked out of 1.00

Virtual memory is

Select one:

- **a. Large main memory**
- **b. Illusion of large main memory**
- **c. None of the above**
- **d. Large secondary memory**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11544)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2