

---

# Expressive DSP for Audio Applications in C++

Tobias Pisani, 201809111

---

Bachelor Report (15 ECTS) in Computer Science

Department of Computer Science

June 8, 2021

Advisor: Aslan Askarov



AARHUS  
UNIVERSITY

DEPARTMENT OF COMPUTER SCIENCE

## Abstract

This thesis explores using an embedded domain specific language to write audio signal processing programs modelled as block diagrams. Building on existing research on an algebra to describe block diagrams, it provides the basis of a C++ library that implements such an EDSL. It goes on to explore real-world usage of said library by implementing an audio plugin, as well as expanding the library with support for multirate DSP algorithms. Using these techniques, the characteristics and advantages of an EDSL are shown.

*Tobias Pisani,  
Aarhus, June 8, 2021.*

## **Acknowledgements**

*A special thank you to Jonatan Midtgaard for his continuous help, guidance and support throughout the project, and to the Baadsmand family for feeding me for the last five days.*

# Contents

Abstract . . . . .	i
<b>1 Introduction</b>	<b>1</b>
1.1 Audio Processing . . . . .	1
<b>2 Related Work</b>	<b>4</b>
2.1 FAUST . . . . .	4
2.2 Eigen . . . . .	4
2.3 C++20 Ranges . . . . .	5
<b>3 Block Diagrams</b>	<b>6</b>
3.1 Algebra of Blocks . . . . .	6
<b>4 The C++ Library</b>	<b>11</b>
4.1 Blocks . . . . .	11
4.2 Block Compositions . . . . .	13
4.3 Literals and References . . . . .	14
4.4 Operator overloading and shorthand syntax . . . . .	15
4.5 Evaluating Signal Processors . . . . .	17
4.6 Extra features . . . . .	20
4.7 Compilation Errors . . . . .	21
4.8 Conclusion & Further Work . . . . .	22
<b>5 Using the Library</b>	<b>23</b>
5.1 The Effect . . . . .	23
5.2 Comparison with FAUST . . . . .	26
5.3 The Plugin . . . . .	26
5.4 Performance Testing . . . . .	29
5.5 Conclusion . . . . .	29
<b>6 Multirate DSP Algorithms</b>	<b>30</b>
6.1 Aliasing . . . . .	30
6.2 Oversampling for Alias reduction . . . . .	32
6.3 Multirate in the Algebra of Blocks . . . . .	34
6.4 Multirate in the EDA Library . . . . .	35
6.5 Conclusion . . . . .	37
<b>7 Conclusion &amp; Further Work</b>	<b>38</b>
<b>Bibliography</b>	<b>39</b>

<b>A</b>	<b>Code</b>	<b>41</b>
A.1	EDA Library Code . . . . .	41
A.2	Example code . . . . .	62

# Chapter 1

## Introduction

### 1.1 Audio Processing

Digital Signal Processing consists of working with continuous signals broken into discrete samples, usually at a fixed sample rate. In the case of audio, the signals are eventually converted either from or to an analog signal, being for example played through speakers. In this thesis the focus is on audio processing, but most of the subjects covered would be applicable in other DSP domains.

Digital audio processing is used in many areas, and on a wide range of hardware. In music production on desktop systems, audio editors called Digital Audio Workstations (DAWs) typically have plugin systems, of which there exist a few standards, with VST<sup>1</sup> being the most popular. These audio plugins, be it effects or synthesizers are a large industry of very specialized and artistic tools that are a big part of modern music production. The same goes for digital audio effects embedded in hardware systems, where digital guitar effects especially has been a large industry for many decades, along with live concert equipment, or even applications on smartphones and other portable devices.

In most of these contexts, predictable performance is a requirement, as they are hard realtime systems, where failure to process a signal in time can at best result in unpleasant noise, and at worst damage equipment or the hearing of users or audience. Thus, audio processing usually follows a fixed signal path, i.e. algorithms that work in constant time, independently of the characteristics of the input. In practice, this means little to no branching, no loops of a non-constant size, and often system-level constraints such as avoiding memory allocation and arbitrary system calls.

#### 1.1.1 Characteristics and Terminology

Digital Audio is represented as a stream of samples, each either a floating or fixed point number, and for processing, the stream is split up into buffers of a fixed size. In most normal applications, the samples are 32 bit floats, at sample rates of anywhere from 44.1kHz to 192kHz. Buffer sizes vary a lot depending on the realtime requirements, from as low as 16 samples up to 4096. Larger buffers usually allow for better performance, while increasing the processing latency. Low latency is often an important requirement, especially when the processing in question is being used by live musicians, or in other real-time processing situations.

When dealing with multiple channels in one stream, such as would be the case for stereo or surround sound, the samples from each channel are usually interleaved, forming buffers of frames of samples (see [Figure 1.1](#)). These buffers are then passed to a processing callback one at a time by the host audio system, whether that is the OS directly, or in the case of audio plugins, the plugin host application. This asynchronous callback-based model is

---

<sup>1</sup><https://www.steinberg.net/en/company/technologies/vst3.html>

```

int process(float* input, float* output, unsigned nframes) {
    for (int i = 0; i < nframes; i++) {
        output[i * 2] = input[i];
        output[i * 2 + 1] = input[i];
    }
}

```

Listing 1.1: An example asynchronous audio processing function that sends one input channel to two output channels. Numbers of channels are determined before registering the process function.




Figure 1.1: A stereo audio signal broken into buffers of 8 frames of two samples each.

what is used by most real time audio frameworks, such as ALSA<sup>2</sup>, JACK<sup>3</sup> and VST. An example of using such an interface can be seen in [Listing 1.1](#).

### 1.1.2 Constraints & Problems

The area of digital audio signal processing poses some interesting problems from a programming language perspective, because of especially two primary constraints:

Firstly, as mentioned earlier, high and predictable performance and integration with embedded systems is very important, which is why DSP is usually implemented in a low-level systems programming language such as C or C++. As an example, when processing a stereo signal at the standard CD sample rate of 44.1 kHz, one has to be able to process 88 200 samples per second, which leaves around 11.3  $\mu$ s per sample.

Secondly, audio effects and synthesizers are often designed by people who are not primarily programmers, but creative sound designers who compose low-level DSP algorithms into new tools to be used by musicians. And even when being developed by a programmer with experience in writing low-latency high-performance code, DSP programs are inherently compositional, often resembling an electronic circuit in structure more than an imperative program.

For these reasons, various Domain Specific Languages have been developed that try to solve these issues. One

<sup>2</sup><https://alsa-project.org>

<sup>3</sup><https://jackaudio.org>

such DSL is FAUST[1], which will be further introduced in [section 2.1](#), but is especially notable for being the product of a lot of research for the past 20 years. FAUST addresses these issues as a functional language based on an algebra developed to describe signal processors as block diagrams, and compiles to C++ to be easily integrable in existing systems.

Domain specific languages however, while providing syntax and semantics that are tailored to the domain, bring the inherent trade-off of ease of integration and expansion, compared to using a library in a general purpose language.

### 1.1.3 Contributions

In this project, I will use the basic research on which FAUST is built to develop a C++ library that instead constitutes an *Embedded Domain Specific Language*, or EDSL for audio DSP. I will show the advantages of staying within a general purpose language, and specifically how using operator overloading and expression templates in C++ allows for syntax that closely resembles that of FAUST, while staying easy to extend and integrate with existing systems and technologies.

In [chapter 2](#) I look at existing solutions in this domain, including more detail about FAUST, as well as a few similar solutions in other domains.

In [chapter 3](#) I introduce the block algebra originally developed for FAUST, along with a few extensions and changes applied for this project.

In [chapter 4](#) I use this block algebra to develop a C++ library which implements an EDSL with syntax and semantics based on the previously introduced block algebra.

In [chapter 5](#) I use this library to implement an audio effect plugin, and demonstrate how it can be used in a real-world scenario.

Finally, in [chapter 6](#), I delve into multirate DSP as an example of how the library can easily be extended with even a fairly complex feature that remains unimplemented by FAUST, and in this process cover some interesting intricacies of DSP.



## Chapter 2

# Related Work

This chapter will briefly introduce FAUST, along with two examples of C++ libraries from other domains that use techniques applied in this project to solve similar issues.

### 2.1 FAUST

As already mentioned in the introduction, this project builds largely on the research performed by the FAUST authors. It was first developed Orlarey, Fober and Letz at Grame, Centre National de Creation Musciale, Lyon, France in 2002[2], and has for the past 20 years been the basis of a lot of research in the area of expressive DSP programming languages[3, 4, 5, 6, 7].

The design of FAUST is based on block diagrams, and thus models a functional pipeline, abstracting away all implementation details regarding buffers, sample rates etc, and instead represents the operations performed on the signal, as opposed to the individual samples. This means the language is closer to the specification of DSP algorithms, resulting in code that is both easier to write initially and to modify when changing the specification.

FAUST programs can be compiled to various targets, including C++, JAVA, WebAssembly etc., and in addition to targeting multiple languages, the user has a lot of control over the generated code, allowing for integration with most frameworks. Going further, FAUST provides a lot of related tooling[[faustweb](#)], such as generating visualizations of the block diagram of a program, along with live-coding environments and automatic UI generation.

Even with all of the tooling and integration options provided, FAUST still presents some issues. Firstly, stateful components and algorithms must themselves be written in FAUST, which means that the vast amount of existing, and often highly optimized C++ algorithms for DSP[8] cannot easily be used from within FAUST, often resulting in FAUST programs eventually being rewritten in C++ when certain requirements are met. Along the same vein, FAUST does not support multirate algorithms (see [chapter 6](#)), which makes an important set of programs impossible to implement efficiently.

During the following chapters, I will present a solution that attempts to address these issues, while preserving the syntax and semantics of FAUST.

### 2.2 Eigen

Eigen is *"a C++ template library for linear algebra: matrices, vectors, numerical solvers, and related algorithms"*[9]. It is often used as the canonical example of EDSLs in C++, and is notable for being one of the oldest

and most well-tested cases of this technology. It is currently used by projects like Google’s Tensorflow[10] and MIRA, a middleware for robotics[11].

The Library provides, amongst other things, a simple and efficient interface for matrix operations, which are implemented using operator overloading and expression templates. This means syntax that closely represents the mathematical operators, but can be evaluated lazily and using optimizations based on the entire expression. Thus, Eigen shows the viability of highly optimized EDSLs in C++.

Since Eigen was first released in 2006, C++ has gone through a lot of changes, but for backwards compatibility reasons it still targets C++98. Especially in the metaprogramming areas of C++ a lot of new features have been introduced to simplify and improve the programming experience, meaning the specific internals of Eigen are not as applicable in a modern context.

## 2.3 C++20 Ranges

C++20[12] merged the long anticipated ranges proposal[13], which was significant in a number of ways. First of all, it added a lot of fairly simple utility functions and quality of life improvements to working with containers and algorithms, most notably range-based versions of all standard algorithms. This means that functions like `std::sort` can now be called with any *range* (i.e. container-like ) as its first and only argument, instead of the interface being based on separate begin and end iterators.

The most notable part of the C++ ranges library in this context however, is that it contains composable *views*, and was the first major part of the standard library to be designed around concepts and constraints[14]. The views provided by the ranges library are a simple case of using operator overloading to build expression trees embedded in the type system, and using these to provide features like lazy evaluation transparently. Thus, parts of the C++20 Ranges library can be used as an example of how to implement an EDSL in C++20.

## Chapter 3

# Block Diagrams

Block diagrams are used to describe many kinds of systems in various engineering fields, and are also the primary specification language for DSP algorithms[15, 16, 17, 18, 19]. Besides just being a convention that probably stems from electronic circuit design leading to DSP, block diagrams are a good model for the fixed program structure of a DSP algorithm. Block diagrams are also inherently recursively defined, where some blocks can be described as block diagrams themselves. The idea of programming DSP in terms of block diagrams has also been used by many DSP DSLs, where visual programming languages that let the user program by drawing connections between blocks such as Pure Data<sup>1</sup> and Max<sup>2</sup> have become very popular, especially with users who are not primarily programmers. It is thus clear that block diagrams are a very useful tool for modelling DSP programs, which is why the researchers that designed FAUST selected it as the model for their DSL[20]. In this chapter I will summarize the algebra designed by them to describe block diagrams as expressions that can be sequentially evaluated.

It is also worth noting, that while DSP is the focus of this project, much of this applies to other domains where block diagrams are a useful model. For example, reactive programming[21] can be modeled using flow diagrams[22], which are very similar to block diagrams.

### 3.1 Algebra of Blocks

In the 2002 paper *An Algebraic approach to Block Diagram Constructions*[2] Orlarey et al. introduce a series of five basic block diagram operations, which are expanded in their later work[20] with two extra compositional operations, split and merge. The rest of this chapter introduces this algebra of blocks in a language very similar to these papers, with minor differences in syntax and semantics noted along the way.

**A Signal** is a discrete function of time, such that the value of a signal  $s \in \mathbb{S}$  at time  $t$  is denoted  $s(t)$ . The full set of all signals is written as  $\mathbb{S} = \mathbb{N} \rightarrow \mathbb{R}$ . Signals are mostly used in signal tuples, denoted as  $(s_1, \dots, s_n) \in \mathbb{S}^n$ . To simplify the semantic specifications in the following section, tuples of signal tuples are always flattened, i.e.  $\forall s \in \mathbb{S} : s = (s)$ , and  $\forall a \in \mathbb{S}^n, b \in \mathbb{S}^m : (a, b) = (a_1, \dots, a_n, b_1, \dots, b_m)$

In use with AD/DA converters and other audio software, it is convention to let the full range of signals be  $[-1; 1]$ , and mostly this is represented as a 32-bit floating point value. Notice however, that signals may exceed this range, although inputs and outputs of the top-level signal processor should not.

---

<sup>1</sup><https://puredata.info>

<sup>2</sup><https://cycling74.com>

**A Signal Processor** is a function  $S^n \rightarrow S^m$ , and the object of the model. Signal processors are a transformation from a number of *input* signals to a number of *output* signals, which are evaluated for each time value  $t$  in order. The result  $p(s)(t)$  of signal processor  $p$  may depend on  $s(t')$  for all  $t' < t$ , in other words, signal processors may have *memory*.

The full set of signal processors is notated as  $\mathbb{P} = \bigcup_{n,m} S^n \rightarrow S^m$

**A Block** is the computational unit used to model signal processors. It is described in terms of the recursive language  $\mathbb{D}$ :

$$d, d_1, d_2 \in \mathbb{D} ::= b \in \mathbb{B} \quad \begin{array}{l} | \text{IDENT} \\ | \text{CUT} \\ | \text{SEQ}(d_1, d_2) \\ | \text{PAR}(d_1, d_2) \\ | \text{REC}(d_1, d_2) \\ | \text{SPLIT}(d_1, d_2) \\ | \text{MERGE}(d_1, d_2) \end{array}$$

Here,  $\mathbb{B}$  denotes a domain-specific set of primitive blocks. Some of these will be addressed in [subsection 3.1.2](#).

Faust and the related papers[2, 20] uses single-character operator syntax for the basic operators of  $\mathbb{D}$ , but since the same syntax cannot be achieved exactly in C++, I will be referring to them by their names as prefix functions to avoid confusion. The chosen syntax is covered in [chapter 4](#).

To separate the syntax of blocks from the semantics, the function  $\llbracket \cdot \rrbracket : \mathbb{D} \rightarrow \mathbb{P}$  is used to map a block diagram  $d$  to the corresponding signal processor  $\llbracket d \rrbracket$ .

We also introduce the type-like syntax  $d : i \rightarrow o$  to mean  $\llbracket d \rrbracket : S^i \rightarrow S^o$ . This is useful for declaring the type rules, which are covered in the following section.


### 3.1.1 Basic block operations

Each of these seven block operations is described in detail by the FAUST authors in the previously mentioned papers[2, 20], so here I will only give a brief introduction to each one, along with an example illustration and the type rules. Some are slightly simplified here, when doing so does not result in a loss of expressivity.

#### Identity

The IDENT block is the simplest block - it simply takes one input signal, and outputs that same signal untouched.


$$\begin{array}{l} \text{IDENT} : 1 \rightarrow 1 \\ \llbracket \text{IDENT} \rrbracket(s) = s \end{array}$$



## Cut

The CUT block takes one input signal and outputs nothing. It can be very useful for discarding signals when composing blocks.

$$\begin{aligned} \text{CUT} : 1 &\rightarrow 0 \\ \llbracket \text{CUT} \rrbracket(s) &= () \end{aligned}$$




## Sequential block composition

The simplest composition of two blocks is passing the outputs of one block to the inputs of another in sequence. It requires the number of outputs of the first block to equal the number of inputs on the second. Faust has defined semantics for when this is not the case as well, but since those cases can all be covered by combinations of sequential and parallel compositions, they have been left out here for simplicity.

$$\frac{d_1 : n \rightarrow p \quad d_2 : p \rightarrow m}{\text{SEQ}(d_1, d_2) : n \rightarrow m}$$

$$\llbracket \text{SEQ}(d_1, d_2) \rrbracket(s_1, \dots, s_n) = \llbracket d_2 \rrbracket(\llbracket d_1 \rrbracket(s_1, \dots, s_n))$$




## Parallel block composition

The parallel composition of two blocks can be intuitively seen as a concatenation of their input and output signals, resulting in a block where the two components are evaluated separately on their own segments of the input.

$$\frac{d_1 : i_1 \rightarrow o_1 \quad d_2 : i_2 \rightarrow o_2}{\text{PAR}(d_1, d_2) : i_1 + i_2 \rightarrow o_1 + o_2}$$

$$\begin{aligned} \llbracket \text{PAR}(d_1, d_2) \rrbracket(s_1, \dots, s_{i_1}, x_1, \dots, x_{i_2}) &= (\llbracket d_1 \rrbracket(s_1, \dots, s_{i_1}), \\ &\quad \llbracket d_2 \rrbracket(x_1, \dots, x_{i_2})) \end{aligned}$$



## Recursive block composition

The recursive block composition is the most complex. Its purpose is to create cycles in the block diagram, by allowing a block to access the output it generated in the previous iteration. The outputs of  $d_1$  are connected to the corresponding inputs of  $d_2$ , and the outputs of  $d_2$  are connected to the corresponding inputs of  $d_1$ . The inputs to the composition are the remaining inputs to  $d_1$ , and the outputs are all outputs of  $d_1$ .

Since the recursion requires a cycle, the output from  $d_1$  that is passed to  $d_2$  is delayed by one sample, i.e. by one iteration. On the illustrations, this is denoted by a small square on the connection.

$$\frac{d_2 : i_2 \rightarrow o_2 \quad d_1 : i_1 \rightarrow o_1 \quad o_2 \leq i_1 \quad i_2 \leq o_1}{\text{REC}(d_1, d_2) : i_1 - o_2 \rightarrow o_1}$$

$$\frac{\begin{array}{l} \llbracket d_1 \rrbracket(r_1, \dots, r_{o_2}, s_1, \dots, s_n) = (y_1, \dots, y_{o_1}) \\ \llbracket d_2 \rrbracket(y'_1, \dots, y'_{i_2}) = (r_1, \dots, r_{o_2}) \end{array}}{\llbracket \text{REC}(d_1, d_2) \rrbracket(s_1, \dots, s_n) = (y_1, \dots, y_{o_2})}$$

Where  $y'$  is the signal  $y$  delayed by one sample, i.e


$$\forall y \in \mathbb{S}, t \in \mathbb{N}^+ : y'(0) = 0, y'(t) = y(t-1)$$

### Split block composition

The split composition is used to sequentially compose blocks where the first one has fewer outputs than the second has inputs. The output signals are connected by repeating the entire output tuple the appropriate number of times, and this number is required to be an integer. This means  $\text{ins}(d_2)$  must be an exact multiple of  $\text{outs}(d_1)$ .

$$\frac{d_1 : i_1 \rightarrow o_1 \quad d_2 : o_1 * k \rightarrow o_2 \quad k \in \mathbb{N}}{\text{SPLIT}(d_1, d_2) : i_1 \rightarrow o_2}$$

$$\frac{\begin{array}{l} \llbracket d_1 \rrbracket(s_1, \dots, s_{i_1}) = (x_1, \dots, x_{o_1}) \\ \forall j \in \{1, \dots, i_2\} y_j = x_{j \bmod o_1} \end{array}}{\llbracket \text{SPLIT}(d_1, d_2) \rrbracket(s_1, \dots, s_{i_1}) = \llbracket d_2 \rrbracket(y_1, \dots, y_{i_2})}$$



Note that  $\text{SPLIT}(d_1, d_2)$  is equal to  $\text{SEQ}(d_1, d_2)$  when  $k = 1$


### Merge block composition

Merge composition is the inverse operation of split composition, i.e. it is used to sequentially compose two blocks where the first one has more outputs than the second one. It places similar restrictions on  $d_1$  and  $d_2$  as split composition, i.e. it requires  $\text{outs}(d_1) = \text{ins}(d_2) * k$ , where  $k$  is an integer.

When multiple outputs from  $d_1$  are connected to a single input on  $d_2$ , the signals are summed. Like split composition,  $\text{MERGE}(d_1, d_2)$  is also equivalent  $\text{SEQ}(d_1, d_2)$  when  $k = 1$ .

$$\frac{d_1 : i_1 \rightarrow i_2 * k \quad d_2 : i_2 \rightarrow o_2 \quad k \in \mathbb{N}}{\text{MERGE}(d_1, d_2) : i_1 \rightarrow o_2}$$

$$\frac{\begin{array}{l} \llbracket d_1 \rrbracket(s_1, \dots, s_{i_1}) = (x_1, \dots, x_{o_1}) \\ \forall j \in \{1, \dots, i_2\}, y_j = \sum_{l=0}^{k-1} x_{j+k*i_2} \end{array}}{\llbracket \text{MERGE}(d_1, d_2) \rrbracket(s_1, \dots, s_{i_1}) = \llbracket d_2 \rrbracket(y_1, \dots, y_{i_2})}$$



### 3.1.2 Domain Specific Blocks

As mentioned in the beginning of this chapter, the full set of blocks includes some domain-specific primitives, denoted by the set  $\mathbb{B}$ . These are the blocks that perform actual useful operations on the signals, and the blocks defined until now, are used to compose the primitives in  $\mathbb{B}$  into block diagrams.

This set can be extended with many more operations, but some of the most important ones are covered here. Faust itself includes quite a few more[20], such as comparisons, branching, and UI elements. During the following chapters more will be defined as well, and adding additional blocks should be easy with the information given here.

## Arithmetic

The most basic blocks perform arithmetic operations on pairs of signals. For all operators  $@$  in  $+, -, *, /$ , a block with the following properties is defined:

$$@ : 2 \rightarrow 1$$

$$\llbracket @ \rrbracket(s_1, s_2)(t) = s_1(t) @ s_2(t)$$


Keep in mind that these blocks are primitive, and while FAUST as well as EDA use infix operator syntax for them, they are not compositional operators, meaning the block itself is not parameterized.

## Memory

DSP operations commonly depend on previous signal values, and while the recursive composition often covers those usecases, some are better suited with a simple memory block. It takes one input signal, and outputs that same signal delayed by a single sample, and the very first sample has the value zero:

$$\text{MEM} : 1 \rightarrow 1$$

$$\llbracket @ \rrbracket(s)(0) = 0, \llbracket @ \rrbracket(s)(t+1) = s(t)$$


Memory blocks are often chained by sequential composition for longer delays, and this is denoted  $\text{MEM}^n$ . The corresponding signal processor becomes

$$\llbracket \text{MEM}^n \rrbracket(s)(t) = \begin{cases} s(t-n) & \text{if } t \geq n \\ 0 & \text{otherwise} \end{cases}$$

## Delay

By composing memory blocks, one can get a delay of arbitrary length, however, sometimes this length needs to vary at runtime. For this, we have the DELAY block. Given two signals  $(d, s)$ , this block outputs  $s$  delayed by  $d(t)$  samples.

$$\text{DELAY} : 2 \rightarrow 1$$

$$\llbracket \text{DELAY} \rrbracket(d, s)(t) = \begin{cases} s(t-d(t)) & \text{if } t \geq d \\ 0 & \text{otherwise} \end{cases}$$

In implementations of this block, there may need to be some constraint on the value of  $d(t)$ , and/or some buffer-growth policy that results in slightly different semantics.

## Chapter 4

# The C++ Library

Using the block algebra introduced in the previous chapter, I have developed an embedded domain specific language as a C++ Library called EDA (Expressive DSP for Audio). The goal of this library is to implement a syntax based on the algebra of blocks, and thus resembling FAUST, while staying within the C++ ecosystem, and allowing easy integration in both directions, i.e. using EDA within other C++ frameworks *and* using other C++ libraries and algorithms within EDA.

The library is based on expression templates[23], which is the idea of representing an AST as a static tree of templated types, and then building this AST by overloading operators. For example, the expression `a + (b * 2)` would evaluate to an object of the type `Plus<Var, Mult<Var, Literal>>` or similar. This idea can be used to use native expression syntax to build the AST of the expression instead of actually evaluating it. A further introduction to expression templates in general, and how to implement them in C++ can be found in Bachelet/Yon (2017)[23], but the following sections go through this specific implementation.

It is worth noting that the library makes heavy usage of certain C++20[12] features, especially the features commonly referred to under the umbrella term *concepts*[24], which help constrain the template parameters of templated entities.

The code library code and all tests and examples can be found in [Appendix A](#), and on <https://github.com/topisani/eda>.

### 4.1 Blocks

One important design decision in this library, is to split the declaration of a block diagram from the evaluation of the corresponding signal processor. While this makes implementing new block types slightly more verbose, it has a couple of advantages. Most importantly, a block diagram is a static structure that can be declared once, even constructed at compile time in many cases, and then multiple instances of the signal processor can be constructed at runtime as needed. Secondly, having the block diagram available as a declarative structure makes other evaluators than the signal processor possible, such as one that builds a visualization of the block diagram.

#### BlockBase

As defined in the previous chapter, a block in  $\mathbb{D}$  has a number of inputs and a number of outputs. In EDA, these are modelled by extending the `BlockBase` CRTP<sup>1</sup> base class, meaning a base class template that is always passed the derived class as its first template parameter:

---

<sup>1</sup>Curiously Recurring Template Pattern, see [https://en.wikipedia.org/wiki/Curiously\\_recurring\\_template\\_pattern](https://en.wikipedia.org/wiki/Curiously_recurring_template_pattern)



```
template<typename Derived, std::size_t InChannels, std::size_t OutChannels>
struct BlockBase {
    static constexpr std::size_t in_channels = InChannels;
    static constexpr std::size_t out_channels = OutChannels;

    constexpr auto operator()(auto&&... inputs) const noexcept
    requires(sizeof...(inputs) <= InChannels);
};
```

This base class provides the `in_channels` and `out_channels` constants, along with the call operator used for partial application (see [subsection 4.6.2](#)).

## AnyBlock, AnyBlockRef and ABlock

Three basic concepts are introduced as well to check whether a type `T` is a block, a block with or without reference/const/volatile qualifiers, or a block with a specific signature. `AnyBlock` also requires a type to model `std::copyable`<sup>2</sup>, to make sure that blocks can be copied around.

```
template<typename T>
concept AnyBlock = std::is_base_of_v<BlockBase<T, T::in_channels, T::out_channels>, T> && std::copyable<T>;

template<typename T>
concept AnyBlockRef = AnyBlock<std::remove_cvref_t<T>>;

template<typename T, std::size_t I, std::size_t O>
concept ABlock = AnyBlock<T> &&(T::in_channels == I) && (T::out_channels == O);
```

`ins<T>` and `outs<T>`

To access the number of input/output channels, the following shorthand variable templates are introduced:

```
template<AnyBlockRef T>
constexpr auto ins = std::remove_cvref_t<T>::in_channels;

template<AnyBlockRef T>
constexpr auto outs = std::remove_cvref_t<T>::out_channels;
```

They allow `ins<T> == 2` when `T` is a cv/ref-qualified block, i.e. it models `AnyBlockRef`.

### 4.1.1 Identity block

As the simplest example of a block type declaration, I take a look at the identity block. For convenience, it has here been extended with a template parameter `N` to allow for identity blocks of different numbers of channels. `ident<N>` is equal to the parallel composition of `N` identity blocks. As a side note, the CUT block has been extended in a similar manner.

```
template<std::size_t N = 1>
struct Ident : BlockBase<Ident<N>, N, N> {};

template<std::size_t N = 1>
constexpr Ident<N> ident;
```

Here, the declaration consists of two parts, the `Ident` type itself, which inherits from `BlockBase`, and the constant `ident` variable template, which serves the function of the constructor.

<sup>2</sup>See <https://en.cppreference.com/w/cpp/concepts/copyable>

## 4.2 Block Compositions

### CompositionBase

Block compositions are implemented as class templates that derive from `CompositionBase`, which itself derives from `BlockBase`. `CompositionBase` keeps a tuple of the operand blocks, which can then be accessed by the deriving class. Like `BlockBase`, it is a CRTP-style base class template, so its first template parameter is the class that is deriving from it.

```
template<typename D, std::size_t In, std::size_t Out, AnyBlock... Operands>
struct CompositionBase : BlockBase<D, In, Out> {
    using operands_t = std::tuple<Operands...>;
    constexpr CompositionBase(Operands... ops) noexcept : operands(std::move(ops)...) {}
    operands_t operands;
};
```

### AComposition and ACompositionRef

Once again, a couple of accompanying concepts are added to check that a type `T` is a composition or reference to one:

```
template<typename T>
concept AComposition = AnyBlock<T> && requires (T& t) {
    typename T::operands_t;
    { t.operands } -> util::decays_to<typename T::operands_t>;
};

template<typename T>
concept ACompositionRef = AComposition<std::remove_cvref_t<T>>;
```

#### operands\_t

As a shorthand for accessing the type of the operands of a cv-ref qualified composition, the `operands_t<T>` alias template is added:

```
template<ACompositionRef T>
using operands_t = typename std::remove_cvref_t<T>::operands_t;
```

### Sequential

Recall the type rule for sequential composition from [section 3.1.1](#):

$$\frac{d_1 : n \rightarrow p \quad d_2 : p \rightarrow m}{\text{SEQ}(d_1, d_2) : n \rightarrow m}$$

Using type constraints, this can be encoded as the following block declaration:

```
template<AnyBlock Lhs, AnyBlock Rhs>
requires(outs<Lhs> == ins<Rhs>)
struct Sequential : CompositionBase<Sequential<Lhs, Rhs>, ins<Lhs>, outs<Rhs>, Lhs, Rhs> {};
```

First of all, `Lhs` and `Rhs` must both model the concept `AnyBlock`, which simply ensures that the types given are in fact blocks. Secondly, a *requires-clause* is added to the struct declaration to assert that the outputs of `Lhs` is equal to the inputs of `Rhs`. If these requirements are unsatisfied, the compiler emits useful error messages that are fairly easy to trace (see [section 4.7](#)). The second and third template parameters to `CompositionBase` specify the number of input and output channels, so by passing `ins<Lhs>` and `outs<Rhs>` respectively, `Sequential<Lhs, Rhs>` has the signature  $n \rightarrow m$  as specified in the type rule. Finally, `Lhs` and `Rhs` are passed as the `Operands...` argument to `CompositionBase`, meaning those blocks will be stored in the `std::tuple<Lhs, Rhs> operands` member variable




Figure 4.1: A block diagram that computes the sum and difference of its inputs and outputs both

For ease of construction, the free function `seq(a, b)` is written as follows:

```
template<AnyBlockRef Lhs, AnyBlockRef Rhs>
constexpr auto seq(Lhs&& lhs, Rhs&& rhs) noexcept
{
    return Sequential<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{
        .lhs = std::forward<Lhs>(lhs),
        .rhs = std::forward<Rhs>(rhs)
    };
}
```

## Remaining Binary compositions

When declaring a block diagram (as opposed to when evaluating its signal processor), the only differences between the various compositional operators are the requirements for the operands and the calculation of the signature. For example, parallel composition is declared as follows:

```
template<AnyBlock Lhs, AnyBlock Rhs>
struct Parallel : CompositionBase<Parallel<Lhs, Rhs>, ins<Lhs> + ins<Rhs>, outs<Lhs> + outs<Rhs>, Lhs, Rhs> {};
```

Here the signature is calculated differently from sequential composition, and there are no requirements on `Lhs` and `Rhs`. Recursive, split, and merge composition are all implemented similarly by simply translating the requirements and signature to C++ type requirements (see appendix, page 46, line 226).

### 4.2.1 Arithmetic

The arithmetic blocks defined in section 3.1.2 are declared as basic block types:

```
struct Plus : BlockBase<Plus, 2, 1> {};
struct Minus : BlockBase<Minus, 2, 1> {};
struct Times : BlockBase<Times, 2, 1> {};
struct Divide : BlockBase<Divide, 2, 1> {};
```

And as with the IDENT and CUT blocks, we declare constants to use the blocks:

```
constexpr Plus plus;
constexpr Minus minus;
constexpr Times times;
constexpr Divide divide;
```

With these, we can start to build simple block diagrams, such as the following, which is drawn in Figure 4.1:

```
ABlock<2, 2> auto d = split(par(plus, minus))
```

## 4.3 Literals and References

By now we know how to declare primitive and compositional blocks, so the following code should seem natural.




Figure 4.2: A block diagram that computes the relative difference between two signals

```
struct Literal : BlockBase<Literal, 0, 1> {
    float value;
};

constexpr Literal literal(float f) noexcept {
    return Literal{.value = f};
}

struct Ref : BlockBase<Ref, 0, 1> {
    float* ptr = nullptr;
};

constexpr Ref ref(float& f) noexcept
{
    return Ref{.ptr = &f};
}
```

The `Literal` and `Ref` blocks each have a signature of  $0 \rightarrow 1$ , and can be used to introduce scalar values into the block diagram. `Literal` is used for constants, and `Ref` is used for values that change over time, i.e. non-signal values used to control parameters of the signal processor. This is a problem that Faust solves using functions that model UI elements, such as `vslider(name, ...)` [20]

As a shorthand for `lit(0.5)`, the user-defined literal<sup>3</sup> `0.5_eda` is also provided:

```
constexpr Literal operator"" _eda(long double f) noexcept
{
    return literal(static_cast<float>(f));
}
```

## 4.4 Operator overloading and shorthand syntax

With the block types and construction functions, block diagrams can be declared by composing the constructors. For example, the following declares a block diagram that calculates the relative difference between two signals, i.e. given the values  $a, b$ , it outputs  $\frac{a-b}{b}$ :

```
auto d = seq(par(ident<1>, split(ident<1>, ident<2>)), seq(par(minus, ident<1>), divide));
```

This syntax quickly becomes very verbose, and the prefix functions make it hard to read. So, using operator overloading and single-character constants, this section introduces syntax so the above can be rewritten as

```
auto d = (_, _ << (_, _)) | ((_ - _) / _);
```

### 4.4.1 Selecting operators

The first step is to decide which C++ operators will be mapped to which block diagram operations, and for this the EDA library has to make some other choices than Faust, as the availability of overloadable operators in C++ obviously places some constraints. The syntax here has been selected to stay as close as possible to Faust, but in practice one might consider some changes, as especially overriding the comma operator is usually discouraged in idiomatic C++.

<sup>3</sup>see [https://en.cppreference.com/w/cpp/language/user\\_literal](https://en.cppreference.com/w/cpp/language/user_literal)

$d$	Faust Syntax	EDA Syntax
IDENT	<code>_</code>	<code>_</code>
CUT	<code>!</code>	<code>\$</code>
$\text{SEQ}(d_1, d_2)$	<code>d1 : d2</code>	<code>d1   d2</code>
$\text{PAR}(d_1, d_2)$	<code>d1 , d2</code>	<code>d1 , d2</code>
$\text{REC}(d_1, d_2)$	<code>d1 ~ d2</code>	<code>d1 % d2</code>
$\text{SPLIT}(d_1, d_2)$	<code>d1 &lt;: d2</code>	<code>d1 &lt;&lt; d2</code>
$\text{MERGE}(d_1, d_2)$	<code>d1 &gt;: d2</code>	<code>d1 &gt;&gt; d2</code>

Table 4.1: Faust and EDA syntax for basic block diagram components.

Firstly, for the IDENT and CUT blocks, the variables `_` and `$` are used:

```
constexpr Ident<1> _ = ident<1>;
constexpr Cut<1> $ = cut<1>;
```

For the compositional operators, most of them follow a similar structure. Sequential composition is done with `:` in faust, but since `:` is not an operator in C++, the bitwise OR operator (`|`) is selected instead. This choice follows naturally from the C++20 ranges library[12], which uses the operator for a similar purpose, and in turn is inspired by the UNIX shell pipe[13].

Parallel composition uses the `,` operator, recursion has been changed to the modulo operator `%`, and split/merge use the left/right shift operators `<<` and `>>`.

The final selection of operators and syntax compared to faust, can be seen in Table 4.1. All in all these operators follow a similar structure, so EDA and Faust programs should read fairly similarly.

## 4.4.2 Operator overloads

All of the selected operators can in C++ be overloaded as free functions, which makes the implementation very simple. They all follow the exact same pattern, so as an example, here is the implementation of the `|` operator:

```
template<typename Lhs, typename Rhs>
constexpr auto operator|(Lhs&& lhs, Rhs&& rhs) noexcept
requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
{
    return sequential(as_block(std::forward<Lhs>(lhs)), as_block(std::forward<Rhs>(rhs)));
}
```

Notably, this operator takes two references to arbitrary objects, and delegates to the constructor function `sequential`. However, two things especially are of note.

Firstly, when implementing an operator overload template in namespace scope, it is very important to make sure that the template arguments are properly constrained, since the operator would otherwise be valid in ambiguous situations, such as when `Lhs` and `Rhs` are both `int`. The approach used here is to use a `requires`-clause to make the operator only participate in overload resolution if either `Lhs` or `Rhs` to model `AnyBlockRef`. Then, both arguments are passed through the function `as_block`, before being passed to `sequential`.

## Autoboxing of literals

The purpose of this, is to allow literal floating-point values to be involved in EDA block expressions, i.e. allow the expression `_ * 0.5`, which takes a signal and multiplies it by the floating point value 0.5. Without auto-boxing literals, the equivalent expression would be `_ * literal(0.5)` (or `_ * 0.5_eda` with the user-defined literal introduced in section 4.3).

The implementation of `as_block` is very simple. It consists of two overloads, one that takes an object that models `AnyBlockRef`, and returns it unchanged, and one that takes a float, and wraps it in a `Literal` block. By adding more `as_block` overloads, one can add implicit conversions from other types to blocks as well, for example some may want a `as_block(float*)` overload to wrap a pointer to a float as a `Ref` block. This would allow expressions of the form `(_ * &x)` to equal `(_ * ref(x))`.

```
constexpr decltype(auto) as_block(AnyBlockRef auto&& input) noexcept
{
    return std::forward(input);
}

constexpr Literal as_block(float f) noexcept
{
    return literal(f);
}
```

As an extra utility, the `as_block_t<T>` type trait is defined to get the result type of calling `as_block` on an instance of `T`:

```
template<typename T>
using as_block_t = std::remove_cvref_t

```

One problem with auto-boxing is that it still requires at least one operand to be a block type. This can result in issues when for example `(_, 2)` is a block that takes one signal, and outputs a tuple of the input unchanged and the constant signal 2, but `(1, 2)` is just the value `int(2)`, and not a block with no inputs that outputs the constant signals 1 and 2. This is because `(1, 2)` has selected the standard C++ comma-operator, which returns its last argument, and not the overloaded comma-operator from EDA, which builds a parallel block. This means the second expression would have to be written with at least one argument explicitly converted to a block type, like `(1_eda, 2)`. Whether this slight decrease in verbosity is worth the added complexity is left up to the reader, as simply removing the `as_block` calls and requiring both operands to model `AnyBlockRef` should be an easy change to make to the relevant code. For the sake of completeness, the library as described here includes auto-boxing.

## 4.5 Evaluating Signal Processors

Up until now, this chapter has only described the declarations of block diagrams, and nothing about how to evaluate the corresponding signal processors. As mentioned in the beginning of this chapter, the declarations of block types are completely decoupled from the evaluators of the signal processors. This visitor-based design makes sense for a couple of reasons, but most importantly, it allows for other visitors than just the signal processor evaluator. For example, one could build a visitor that generates a visual representation of the block diagram, or one that generates a user interface. Alternatively, other evaluators could be built, for example one that vectorizes the operations (see Scaringella et al. *Automatic vectorization in Faust* (2003) [25] for an approach that could be taken in EDA as well)

As presented here however, EDA contains only one visitor, the `evaluator<Block>`, which evaluates the signal processor of a block for a single frame of data at a time, i.e. the values  $(s_0(t), \dots, s_n(t))$  of a signal tuple at a single time  $t$ . In code, this frame is represented as an instance of the `Frame<N>` class, where `N` is the number of channels. This class can mostly just be regarded as a wrapper around `std::array<float, N>`, with some minor tweaks in construction. It also provides the free functions `slice<I, J>(Frame<N>) -> Frame<J - I>` and `concat(Frame<N>, Frame<M>) -> Frame<N + M>`, which are mostly self explanatory, and thus also omitted here. The full class and function definitions can be seen in the appendix, page 48.

To illustrate the relationship between the block declarations and evaluator instances, consider the following program, which evaluates the difference between its current input and its previous input:

```
constexpr auto d = _ << (_ - mem<1>);
auto a = make_evaluator(d);
auto b = make_evaluator(d);

a.eval(1) // => 1 - 0 = 1
a.eval(2) // => 2 - 1 = 1
b.eval(10) // => 10 - 0 = 10
a.eval(5) // => 5 - 2 = 3
b.eval(1) // => 1 - 10 = -9
```

Notice the `constexpr` on line 1 - the block diagram is declared as a compile-time constant, however, the evaluators are runtime mutable, as they store the state of the signal processor. Continuing the example, note that the two evaluators have separate memory, and can be executed independently from each other. This is the basic usage of evaluators, and should give an understanding of the difference between blocks as declarations of programs, and evaluators as instances of them.

### 4.5.1 evaluator

The basic evaluator class template is declared as such:

```
template<AnyBlock T>
struct evaluator;
```

It is accompanied by the following type trait to extract the block type:

```
template<typename T>
struct block_for;

template<typename T>
struct block_for<evaluator<T>> {
    using type = T;
};

template<typename T>
using block_for_t = typename block_for<T>::type;
```

For each block type `T`, the class template `evaluator<T>` shall be specialized to define the evaluator. This specialization shall model the `AnEvaluator` concept, which is given in code below, and has the following requirements:

1. `T` shall publicly derive from `EvaluatorBase<block_for_t<T>>` (see the following section).
2. `T` shall be constructible from a const reference to an object of type `block_for_t<T>`.
3. `T` shall have a member function `eval`, that takes a `Frame` of the appropriate number of channels, and returns a `Frame` of the appropriate number of channels, according to the signature of the block `block_for_t<T>`.

```
template<typename T>
concept AnEvaluator =
    std::derived_from<T, EvaluatorBase<block_for_t<T>>>
    && std::is_constructible_v<T, block_for_t<T> const&>
    && requires (T t, Frame<ins<block_for_t<T>>> in) {
        { t.eval(in) } -> std::convertible_to<Frame<outs<block_for_t<T>>>>;
    };
};
```

To construct the evaluator of a block diagram, the factory function `make_evaluator` is supplied:

```
template<AnyBlockRef T>
constexpr auto make_evaluator(T&& b)
requires AnEvaluator<evaluator<std::remove_cvref_t<T>>>
{
    return evaluator<std::remove_cvref_t<T>>(b);
}
```

## EvaluatorBase

For primitive blocks, `EvaluatorBase` is an empty base class.

```
template<AnyBlock T>
struct EvaluatorBase {};
```

It could however be used to add common functions to all evaluators, like a wrapper to `eval` that works on whole buffers of frames. Other than that, its main purpose is for composition evaluators.

## Primitive block evaluator

For primitive blocks, the evaluator implementations are fairly simple, one just needs to make sure to follow the three requirements of `AnEvaluator`, i.e. deriving from `EvaluatorBase<Block>`, having a `evaluator(Block)` constructor, and implementing the proper `eval` function.

As an example, here is the `evaluator<Plus>` specialization:

```
template<>
struct evaluator<Plus> : EvaluatorBase<Plus> {
    constexpr evaluator(Plus) {};
    Frame<1> eval(Frame<2> in)
    {
        return {in[0] + in[1]};
    }
};
```

## 4.5.2 Composition Evaluators

Evaluators of block compositions follow the exact same model, however, they need to defer to evaluators of the operands, stored as member variables. This is done through the `EvaluatorBase` specialization for blocks that model `AComposition`, and using some light metaprogramming, the evaluators are stored in a `std::tuple<evaluator<Operand>...>`, constructed from the operand blocks accessed through the block composition passed to the constructor. The implementation looks like this:

```
template<typename T>
struct add_evaluator {};
```

```
template<typename... Ts>
struct add_evaluator<std::tuple<Ts...>> {
    using type = std::tuple<evaluator<Ts>...>;
};
```

```
template<typename T>
using add_evaluator_t = typename add_evaluator<T>::type;
```

```
template<AComposition T>
struct EvaluatorBase<T> {
    constexpr EvaluatorBase(const T& t) : operands(t.operands) {}
    add_evaluator_t<operands_t<T>> operands;
};
```



The important part is that classes that derive from `EvaluatorBase<T>` can access the operand evaluators through `std::get<I>(this->operands)`, where `I` is the index of the operands.

As in the other sections on compositions, the SEQ composition is used as an example of an evaluator:

```
template<AnyBlock Lhs, AnyBlock Rhs>
struct evaluator<Sequential<Lhs, Rhs>> : EvaluatorBase<Sequential<Lhs, Rhs>> {
    constexpr evaluator(const Sequential<Lhs, Rhs>& block) : EvaluatorBase<Sequential<Lhs, Rhs>>(block) {}

    constexpr Frame<outs<Sequential<Lhs, Rhs>>> eval(Frame<ins<Sequential<Lhs, Rhs>>> in)
    {
        auto l = std::get<0>(this->operands).eval(in);
        return std::get<1>(this->operands).eval(l);
    }
};
```

Notice that this is all very similar to the primitive block evaluator shown earlier, and the only difference is forwarding the block instance to the `EvaluatorBase` constructor. The `eval` function implements the signal processor for  $\text{SEQ}(l, r)$ , by first directly calling the evaluator of the first operand, and passing the result of that operation to the evaluator of the second operand.

The other compositional blocks are slightly more complicated to implement, but at this point it is just conventional C++ in the `eval` functions. The full implementations can be seen in the appendix, page 53.

## 4.6 Extra features

One of the advantages of working inside C++ instead of in a DSL, is the ability to easily add features and integrations with other parts of the C++ ecosystem. At the time of writing, the EDA library contains a few such examples, and a couple of the more interesting ones are covered in this section. I will not go deep into the implementation details here, but the code can be seen in the appendix, pages 47 and 56.

### 4.6.1 Functions

A simple, but important enhancement to the library, is the `fun<I, O>(Callable)` block. It can be used to easily wrap normal C++ functions to stateless blocks. As an example, the following defines blocks for the hyperbolic tangent function (as used in chapter 6), and floating point modulo.

```
auto tanh = fun<1, 1>(&std::tanhf);
auto mod = fun<2, 1>([](auto in) { return std::fmod(in[0], in[1]); });
```

The `fun` block simply captures the function, and the evaluator delegates to it directly. The implementation can be seen in the appendix, page 47.

A stateful version of `fun` also exists, which can store arbitrary state in the evaluator. `fun<I, O>(f, state_inits...)` copies `state_inits...` into new objects on each evaluator construction, and the evaluator passes references to these objects as extra arguments to `f(data, states...)`.

As an example, the following `COUNTER : 0 → 1` block outputs the signal  $s(t) = t$ , by keeping a state of type `int`, initialized to 0, and incrementing it each time the evaluator is called:

```
auto counter = fun<0, 1>([](Frame<0> in, int& state) { state++; return {state}}, 0);
```

By using these constructs, most simple blocks, stateful or stateless, can be implemented without having to write out the type and evaluator declarations.

### 4.6.2 Function call syntax for blocks

FAUST has the ability to call blocks as functions, meaning  $d(x_1, \dots, x_{\text{ins}(d)})$  is equal to  $\text{SEQ}(\text{PAR}(x_1, \dots, x_{\text{ins}(d)}), d)$ . To make this even more useful, partial application is supported, i.e.

$$d(x_1, \dots, x_n) = \text{SEQ}(\text{PAR}(x_1, \dots, x_n, \text{IDENT}^{\text{ins}(d) - \sum_{i=1}^n \text{outs}(x_i)}), d)$$

$$\sum_{i=1}^n \text{outs}(x_i) \leq \text{ins}(d)$$

This description can be translated directly to an implementation of the function call operator on `BlockBase`, making it available to all blocks:

```
template<typename D, std::size_t I, std::size_t O>
constexpr auto BlockBase<D, I, O>::operator()(auto&&... inputs) const noexcept
requires((outs<Inputs> + ...) <= I)
{
    return seq(par(inputs..., ident<I - (outs<Inputs> + ...)>), *this);
}
```

## 4.7 Compilation Errors

A big advantage of using C++20 requirements and constraints, is the vastly improved error context. As an example, the following EDA expression violates the constraints of the SEQ block.

```
auto block = (_, _) | (_);
```

When compiled with clang v12.0.0, this code gives the following error message:

```
In file included from tests/block.cpp:1:
include/eda/block.hpp:185:12: error: constraints not satisfied for class template 'Sequential' [with Lhs =
    ↳ eda::Parallel<eda::Ident<1>, eda::Ident<1>>, Rhs = eda::Ident<1>]
    return Sequential<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};
           ^~~~~~
include/eda/syntax.hpp:38:12: note: in instantiation of function template specialization
    ↳ 'eda::seq<eda::Parallel<eda::Ident<1>, eda::Ident<1>>, const eda::Ident<1> &>' requested here
    return seq(as_block(FWD(lhs)), as_block(FWD(rhs)));
           ^
tests/block.cpp:19:21: note: in instantiation of function template specialization
    ↳ 'eda::syntax::operator|<eda::Parallel<eda::Ident<1>, eda::Ident<1>>, const eda::Ident<1> &>' requested here
auto block = (_, _) | (_);
                  ^
include/eda/block.hpp:178:12: note: because 'outs<eda::Parallel<eda::Ident<1>, eda::Ident<1> > > ==
    ↳ ins<eda::Ident<1> >' (2 == 1) evaluated to false
    requires(outs<Lhs> == ins<Rhs>) //
           ^
```

Error messages emitted from programs that rely heavily on templates, but are implemented before or without explicit constraints have notoriously long and cryptic error messages<sup>4</sup>, so comparatively this goes straight to the point.

To give the compiler as much context as possible for errors, it can be useful to use the `ABlock` concept as a placeholder type when declaring blocks:

```
ABlock<1, 2> auto d = (_ << (_ + _, _ * _));
```

Here the `ABlock<1, 2>` prefix becomes a checked annotation that `d` is a block with signature  $1 \rightarrow 2$ .

<sup>4</sup>In his CppCon 2019 talk *How to Implement Your First Compiler Feature: The Story of Concepts in Clang*[26], Saar Raz famously talks about how he had to first implement a parser for the gigabyte of compiler error messages produced by one such program.

## 4.8 Conclusion & Further Work

In this chapter I have shown how an EDSL based on FAUSTs algebra of blocks can be implemented in C++, using the basic techniques of expression templates to build an AST that can then be evaluated by a separate class.

The evaluator shown here is the simplest one possible, as it merely walks the AST, evaluating one sample at a time. However, other evaluators could be explored that work more efficiently, such as a vectorizing evaluator as mentioned in [section 4.5](#). Additionally, the AST represented by block diagram declarations could be transformed and optimized, detecting patterns and redundancies that can be reduced to other blocks.

Additionally, visitors for other purposes could be built, for example one that generated a visual representation of the block diagram, or more specialized ones that could be used to generate user interfaces from block diagrams that contain special control blocks.

However, as presented here, the library can already be used to implement real applications, as will be explored in the next chapter.

# Chapter 5

## Using the Library

This chapter explores using the C++ library designed and developed in the previous chapters to implement an audio plugin that can be used by audio host applications. This is an ideal usecase for the library, as audio plugins are often implemented in C++, and follow a similar structure to the signal processors introduced in [chapter 3](#), i.e. are defined by a number of input/output channels, and evaluated on buffers of data passed in one at a time.

### 5.1 The Effect

The example developed in this chapter is a simple echo audio effect, i.e. a plugin that continuously repeats its input with some delay, where each echo gets quieter and loses "brightness", i.e. the high frequency components of the signal. Echos were introduced in the 1950s, and have become a staple of music production, being used especially for vocals and guitars. The first analog echos were based on a tape loop, where the input audio was continuously written and then read back. The continuous repetitions provided by an echo are achieved using a feedback loop, meaning the output of the echo is sent back into the input, but with reduced gain and/or other processing applied.

The echo effect designed here is a simple, but fully featured one. It has a variable delay time, feedback gain control, and a simple low-pass filter in the feedback loop to gradually remove more and more high frequencies from the repeated signal. Lastly it has a dry/wet mix control, to mix the original (dry) signal with the output (wet) signal of the effect. The block diagram for the effect can be seen in [Figure 5.1](#), and the following sections will go through this block diagram one part at a time.

#### 5.1.1 Controls

The effect has 4 control variables, which are exposed through LV2, and controlled by the UI generated by the plugin host. In code, these are represented as `float` variables, which can be used in the EDA expression by wrapping them in a REF block (see [section 4.3](#)).

```
float filter_a = 0.9;
float time_samples = 11025;
float feedback = 1.0;
float dry_wet_mix = 0.5;
```

The meaning of the individual controls will be explained where they are used in the following sections.




Figure 5.1: Block diagram of the echo effect.

### 5.1.2 Filter

Echoes often include a low-pass filter in their feedback loop, meaning each repetition of the echo will not only be quieter, but also proportionally lose more high frequencies than low. This seems most natural to the human ear, since low frequencies travel further, and will thus be louder when a sound returns as an echo.

The low-pass filter used in this echo is the simplest DSP filter possible, a single-pole Infinite Impulse Response filter. It can be understood as a weighted average between the input, and the previous output, i.e its signal processor can be written as follows:

$$\begin{aligned} \llbracket \text{Filter} \rrbracket(a, s) &= y \\ y(-1) &= 0 \\ y(t) &= (1 - a(t)) \cdot s(t) + a(t) \cdot y(t-1) \\ a(t) &\in [0; 1] \end{aligned}$$

Here,  $s$  is the audio input signal, and  $a$  is a signal used to control the weighting between the input and previous output, with higher values meaning high frequencies are more suppressed. For an illustration of this parameter, see [Figure 5.2](#), which plots the magnitude of frequencies at a selection of values for  $a$ .




Figure 5.2: Frequency response of the single-pole IIR filter used in the echo effect at different values of the  $a$  parameter.

This particular filter is chosen mainly for the simplicity of its implementation, but it also fits the purpose well, and results in a quite nice effect.

The EDA implementation of the filter follows from the relevant (green) part of the block diagram in [Figure 5.1](#), and can be written as such:

```
ABlock<2, 1> auto const filter = (_ << (_, _), _) | (((_ * _) + ((1 - _) * _)) % _);
```

Notably, this implementation uses the REC block (%) to pass the result of the previous iteration back into the filter. It also uses the SPLIT block (<<) to send  $a$  to both parts of the expression. By passing  $a$  as a signal, this filter becomes easily reusable, and could be included in a library of standard components.

### 5.1.3 Echo

This (blue) part of the block diagram contains the feedback loop and the delay, which perform the main work of the effect. It is once again a recursive algorithm, meaning part of its input is its previous output. Specifically, the output is passed through the filter discussed previously, multiplied by the feedback gain control, and summed with the new input, to then be delayed by the specified echo time.

This block uses three control variables: `feedback`, which controls the feedback gain, `time_samples` which sets the delay time in number of samples, and `filter_a` which is the  $a$  control passed to the filter. The signal processor for this part is

$$\begin{aligned} \llbracket \text{Echo} \rrbracket(s)(t) &= x(t) \\ \forall t < 0 : x(t) &= 0 \\ \forall t \geq 0 : x(t) &= \llbracket \text{Filter} \rrbracket(x')(t - \text{time\_samples}) \cdot \text{feedback} + s(t) \\ x'(t) &= x(t-1) \\ \text{feedback} &\in [0; 1] \end{aligned}$$

Implemented in EDA, the code looks as follows:

```
ABlock<1, 1> auto const echo = (plus | delay(ref(time_samples))) % (filter(ref(filter_a)) * ref(feedback));
```

This uses the `DELAY` block introduced in [section 3.1.2](#) to get the variable time delay, and partial function application (see [subsection 4.6.2](#)) to pass control signals with a nicer syntax.

### 5.1.4 Process

Lastly, the outermost (red) part of the block diagram in [Figure 5.1](#) contains the dry/wet mix, to mix between the unprocessed (dry) and processed(wet) signal. This is a very common control to have on all kinds of audio effects, as it (together with the feedback gain control) is an easy way to get *more* or *less* of the effect. The signal processor here is quite simple:

$$\begin{aligned} \llbracket Process \rrbracket(s)(t) &= mix \cdot \llbracket Echo \rrbracket(s)(t) + (1 - mix) \cdot s(t) \\ mix &\in [0; 1] \end{aligned}$$

The EDA implementation splits the input signal to both sides of a `+` operation, with the one side passing through the `echo` block defined earlier, and one through the identity block `_`, with both sides multiplied by the appropriate mix factor:

```
ABlock<1, 1> auto const process = _ << (echo * ref(dry_wet_mix)) + (_ * (1 - ref(dry_wet_mix)));
```

## 5.2 Comparison with FAUST

This example is a good opportunity to compare the EDA code to equivalent FAUST code. Here is the full EDA program declaration from the previous section:

```
auto filter = (_ << (_, _), _) | (((_ * _, (1 - _) * _) | plus) % _);
auto echo = (plus | delay(ref(time_samples))) % (filter(ref(filter_a)) * ref(feedback));
auto process = _ << (echo * ref(dry_wet_mix)) + (_ * (1 - ref(dry_wet_mix)));
```

And to compare, the equivalent code in FAUST:

```
filter(a, x) = (((a * _, (1 - a) * x) : +) ~ _);
echo = (+ : @time_samples) ~ (filter(filter_a) * feedback);
process = _ <: (echo * dry_wet_mix) + (_ * (1 - dry_wet_mix));
```

A few syntactical differences can be seen. Setting aside the obvious `auto` prefix and difference in operators, the main difference is FAUST's support for function declaration syntax, which makes the `filter` declaration a bit simpler to read. Mostly however, the differences are small, and more work could be done to improve the syntax of EDA even further, where even something similar to fausts function declarations should be possible.

## 5.3 The Plugin

The framework chosen to implement the echo plugin is LV2<sup>1</sup>, an open standard for audio plugins, supported by applications such as Audacity<sup>2</sup>, Ardour<sup>3</sup> and REAPER<sup>4</sup>. LV2 is similar to the more widely used alternatives such as VST<sup>5</sup> and AU<sup>6</sup>, and is chosen here only for practical reasons, such as better linux support and availability in

---

<sup>1</sup><https://lv2plug.in>

<sup>2</sup><https://www.audacityteam.org/>

<sup>3</sup><https://ardour.org/>

<sup>4</sup><https://www.reaper.fm/>

<sup>5</sup><https://www.steinberg.net/en/company/technologies/vst3.html>

<sup>6</sup><https://developer.apple.com/documentation/audiounit>




Figure 5.3: The UI of the Echo plugin as displayed in Audacity.

Audacity, which provides useful analysis tools for scientific purposes, such as the frequency spectrum analyzer used to generate [Figure 5.2](#) and similar plots in [chapter 6](#).

An LV2 plugin consists of data definition files in the *turtle* specification language, and implementation in C/C++. For the EDA plugins, I wrote a small wrapper to write plugins as a C++ class instead (see the appendix, page [62](#)), but it follows the structure of the C API closely.

The C++ code that implements the echo plugin can be seen in [Listing 5.1](#). It consists of three functions, that each are provided to the LV2 framework.

`connect_port` is called by the framework to provide pointers to the data ports. The four control are single values, and the two audio port pointers are arrays. All will be updated with values before each call to `run`.

`activate` is called after all ports have been connected, before the first call to `run`, and in it the EDA blocks and evaluator are constructed. The evaluator is stored in a `DynEvaluator` a type-erasing wrapper for evaluators (see the appendix, page [52](#)). Since the control ports are pointers to float values, they can be used directly with the REF block.

`run` is called to process incoming audio data. Its single parameter `n_samples` is the number of samples available in the audio port arrays given earlier, so the implementation is a simple loop through and call to the evaluator constructed in `activate`.

This implementation, along with a metadata file (see the appendix, page [64](#)), defines the plugin which is distributed as a folder containing the shared object binary and metadata. When installed on the system, these can be used from a host program that supports LV2, such as Audacity, which will then provide a UI for the controls. The UI generated for this effect by audacity can be seen in [Figure 5.3](#).



```

struct Echo final : LV2Plugin {
    Echo() = default;

    void connect_port(uint32_t port, float* data) override
    {
        switch (port) {
            case 0: time_samples = data; break;
            case 1: filter_a = data; break;
            case 2: feedback = data; break;
            case 3: dry_wet_mix = data; break;
            case 4: input_port = data; break;
            case 5: output_port = data; break;
        }
    };

    void activate() override
    {
        ABlock<2, 1> auto const filter = (_ << (_, _), _) | (((_ * _, (1 - _) * _) | plus) % _);
        ABlock<1, 1> auto const echo = (plus | delay(ref(*time_samples))) % (filter(ref(*filter_a)) *
        ↪ ref(*feedback));
        ABlock<1, 1> auto const process = _ << (echo * ref(*dry_wet_mix)) + (_ * (1 - ref(*dry_wet_mix)));
        eval = make_evaluator(process);
    }

    void run(uint32_t n_samples) override
    {
        for (int i = 0; i < n_samples; i++) {
            output_port[i] = eval(input_port[i]);
        }
    }

private:
    DynEvaluator<1, 1> eval;

    float* time_samples = nullptr;
    float* filter_a = nullptr;
    float* feedback = nullptr;
    float* dry_wet_mix = nullptr;

    float* input_port = nullptr;
    float* output_port = nullptr;
};

```

Listing 5.1: Implementation of Echo LV2 plugin

## 5.4 Performance Testing

Only very minimal performance testing of the library has been done, and only of this single example program. The performance was compared to an equivalent handwritten C++ program, by measuring 1000 iterations of processing buffers of 1024 samples each. The code for this benchmark can be seen in the appendix, page 66.

Program	Average time pr. iteration
Handwritten C++	11.198 $\mu$ s
EDA	16.770 $\mu$ s
Relative Difference	+49.7%

As a simple benchmark, this shows a performance penalty of roughly 50%, which is very promising for the completely unoptimized version of the library. It seems highly likely from this that some of the optimizations mentioned in [section 4.8](#) could reduce this number a lot, but of course more measurements would need to be done in tandem with optimizations.

## 5.5 Conclusion

By showing a small EDA program and real-life usecase for the library, this chapter has illustrated the merits of the library. I also compared the EDA implementation to an equivalent FAUST program, showing the minor differences in syntax. To further explore the library in practical usage, more examples and testing should be done, leading to further development and optimization of the library. However, even as presented in this project, the library can clearly be used to implement at least semi-complex DSP algorithms and integrate them in existing systems, with acceptable performance.

## Chapter 6

# Multirate DSP Algorithms

This chapter explores resampling, and working with a signal path that uses multiple sample rates. Multirate DSP is not supported by FAUST[1], and this chapter will cover why this can be very important in certain classes of DSP algorithms, how the transformations between sample rates is done, and how I have implemented it in the EDA library. This is all intended as an example of some advantages of working with a C++ library compared to a DSL.

### 6.1 Aliasing

According to the Nyquist-Shannon theorem[27], a discrete-time sampled signal can only represent frequencies below half of the sample rate, called the Nyquist frequency  $f_N$  or the Nyquist limit. Intuitively, this is because no change in the waveform can be faster than the time between two samples.

The frequencies above the Nyquist limit don't just disappear from the sampled signal though, but will instead be mirrored back and fourth between the Nyquist frequency and  $f = 0$ . This behaviour is called aliasing, and is undesirable in most usage, since it distorts the signal with non-harmonic frequencies.

When initially sampling an analog signal, the main way to avoid aliasing is simply to use an analogue low-pass filter to remove any frequencies above the Nyquist limit before the signal is sampled to discrete time[28], which means there are no frequencies to be aliased. However, aliasing can also be an issue in some DSP operations that introduce new frequencies above the original signal, such as nonlinear waveshaping functions, i.e. an operation that applies a function  $\omega(x)$  to the original signal  $x$ , where  $\omega$  is non-linear.

#### 6.1.1 Waveshaping Distortion

A simple and common example of nonlinear waveshaping is distortion using the hyperbolic-tangent trigonometric function  $\omega(x) = \tanh(x)$  (or, in practice, a polynomial approximation thereof). By adjusting the gain of the input, i.e  $\omega(x) = \tanh(g \cdot x)$ , the effect can span from a soft saturation to hard clipping. When looking at the frequency spectrum, this introduces frequencies above the original signal, and in the case where the input is a simple sine wave (i.e. a single peak frequency), this waveshaping operation introduces odd harmonics, that is it introduces frequencies at odd multiples of the frequencies in the original signal. Adjusting the gain will change the magnitude (volume) of these frequencies.

In the following introduction to aliasing and oversampling, I will refer heavily to the graphs in [Figure 6.1](#). These are visualizations of various runs of this waveshaping distortion, all with an input signal of a sine wave at 1800 Hz, and  $g = 5$ . These parameters were chosen simply because of the visualizations they result in, but do reflect real-world usecases. (a) is generated at a very high sample rate relative to the visible frequency range, and




Figure 6.1: A 1800 Hz sine wave passed through the nonlinear waveshaping function  $\omega(x) = \tanh(5x)$  at different sample rates and resampling factors  $N$ . Given the high samplerate, (a) can be seen as representing the ideal signal over this frequency range. (c) and (d) additionally show the frequency response of the interpolation/deconvolution filters used with oversampling. For better visualization, the logarithmic decibel scale is used on the vertical axis:  $z \text{ dB} = 20 \cdot \log_{10}(z)$ .

can be regarded as representing the ideal signal. Here, the fundamental frequency at 1800 Hz is visible as the first peak, and the harmonics can be seen at even intervals above the fundamental.

Figure 6.1 (b) shows the same signal operation applied at 22050Hz, where the aliasing becomes evident. Notice that the added frequencies are a clear mirroring back and forth between the Nyquist frequency and 0 Hz. It should be very clear that these frequencies are unwanted, and it is especially worth noting that the aliasing has added frequencies below the fundamental, which will be particularly noticable. The signal we actually want when applying  $\omega$  at 22050Hz, is the left half of (a), i.e. all the frequencies of the ideal signal that are representable at that sample rate, i.e. the ones that are below the Nyquist limit of 11025Hz.

## 6.2 Oversampling for Alias reduction

The most common approach to reduce the effects of aliasing in DSP algorithms, is oversampling, which is the operation of upsampling by a factor of  $N$ , performing the required operations on the signal, and then downsampling by  $N$  again, to return to the original sample rate. The basic idea is, that by raising the sample rate, you raise the Nyquist frequency, which means the point at which frequencies will be mirrored is raised. This results in a smaller part of the signal being mirrored, and the first area that the loudest frequencies will be mirrored onto, is above the original Nyquist limit, and can be removed when downsampling to the original sample rate.

The effects of this process can be seen in Figure 6.1, where (c) and (d) show the operation applied with upsampling of  $N = 2$  and  $N = 4$ . Ignoring the frequency response of the filter (shown in orange), these plots clearly show less aliasing, with no visible aliasing at all for  $N = 4$ . With  $N = 2$  it can be seen that the mirroring has happened at  $f = 22050$ Hz instead, but then the frequencies above 11025Hz have been filtered out. This clearly shows how oversampling reduces the effects of aliasing, and for this operation with this data, it looks like  $N = 4$  is enough. However,  $N = 8$  is often chosen in the more general case [15]

There are other and more efficient ways to avoid aliasing[29], but they mostly depend on specific knowledge of the nonlinear operation that is being used, and oversampling is widely recognized as the standard method for alias reduction[15, 30].

### 6.2.1 Interpolation

I will briefly introduce the most common method of increasing the sample rate of a sampled signal, in which the signal is first zero-stuffed and then interpolated using a filter. Like with alias reduction, this is an area where many variants and other methods have been developed[31, 16], and this section vastly simplifies the subject. However, it gives a general understanding of the problems involved, and how they are most commonly solved.

It is also worth noting that the terms *upsampling* and *interpolation* are often conflated. This can lead to some confusion, however when not talking about the implementation details of either, both terms usually refer to the joint operation of upsampling and interpolation.

The first step is to simply increase the sample rate of the signal. This is done by *zero-stuffing* the signal, i.e. inserting  $N - 1$  zeros between each sample. In Figure 6.2 the result of this operation can be seen in the time and frequency domains. In the frequency domain, two things have happened: The gain of the signal has been scaled by  $\frac{1}{N}$ , and the signal has been mirrored around the old Nyquist frequency  $f_{N1}$ . The gain is simply restored by multiplying each sample by  $N$ , and for the new signal above  $f_{N1}$ , we can use a low pass filter to remove them.




Figure 6.2: The effects of zero-stuffing on the waveform and frequency spectrum. The input signal is the same saturated 1800Hz sine wave as used in Figure 6.1, and the sample rates are 22050Hz and 44100Hz before and after upsampling respectively. To clearly show the reduction in gain on upsampling, linear gain is used on the vertical axis of the frequency graphs.

### 6.2.2 FIR Filters

There are a lot of methods to designing and implementing interpolation filters for the best and most efficient results, but most of them are based on Finite Impulse Response (FIR) filters. A FIR filter of order  $N$  is a simple convolution operation where each output is a weighted sum of the  $N + 1$  most recent inputs. Designing FIR filters, i.e. picking the right coefficients, is a heavily researched topic[15, 31, 17], and not something I will go into in this project, however, the filters used for testing and for Figure 6.1, are FIR filters of order  $N = 128$ , designed using the method described in [19]. These filters have a fairly high order to ensure a very steep cutoff, but in real use there is a tradeoff between the efficiency of a lower filter order, and the better results of a harder cutoff point.

### 6.2.3 Decimation

When downsampling, we first need to remove any frequencies above the Nyquist limit of the resulting sample rate, since those will otherwise be aliased, which was the original reason for oversampling. This process is called *decimation*, and consists of running a lowpass filter and then selecting every  $N^{\text{th}}$  sample for output. Thus, it closely resembles interpolation, and in fact the same filter can be used for both, even though different ones are often used for the best results, partly because decimation allows for some special optimizations, as only every  $N^{\text{th}}$  sample is actually required, which means some computations can be skipped in the FIR filter. These topics are covered in many of the referenced sources of this chapter, such as [15, 31, 17].

## 6.3 Multirate in the Algebra of Blocks

Now that we know why resampling is important, and the basics of how it is implemented, I will look at how to integrate it in the block algebra introduced in chapter 3.

### 6.3.1 Approach I

In the most general model, multirate blocks are introduced by adding an extra parameter  $R$  to signals, as the ratio of the sample rates  $f_{\text{out}}/f_{\text{in}}$ . This means blocks will be defined with the types  $i \rightarrow_R o$ , and block compositions need type rules to compute the rate ratio as well. As an example, here is the type rule as it would be stated for SEQ:

$$\frac{d_1 : n \rightarrow_r p \quad d_2 : p \rightarrow_q m}{\text{SEQ}(d_1, d_2) : i_1 \rightarrow_{r \cdot q} o_2}$$

This means the rate ratio of  $\text{SEQ}(d_1, d_2)$  is the product of the rate ratios of  $d_1$  and  $d_2$ . Similarly,  $\text{PAR}(d_1, d_2)$  requires both operands to have the same rate ratio, which becomes the rate ratio of the composition. One would then introduce  $\text{UPSAMPLE}(n) : 1 \rightarrow_n 1$  and  $\text{DOWNSAMPLE} : 1 \rightarrow_{\frac{1}{n}} 1$  blocks, which could be used to change the sample rate.

This model has the advantage of allowing other uses for resampling, such as interfacing between two systems that use different sample rates, as a top-level signal processor can have different input/output sample rates. However, it introduces a large amount of complexity to evaluating the signal processors, since blocks that downsample can only output after receiving  $\frac{1}{R}$  samples, and blocks that upsample output  $R$  samples at a time.

### 6.3.2 Approach II

Instead, a simpler approach is chosen, where all blocks have the same input/output rate, but a separate  $\text{RESAMPLE}(N)(d, F_i, F_d)$  block is introduced, which can be used to perform oversampling for the block  $d$ , with ratio  $N$ , interpolation filter  $F_i$ , and decimation filter  $F_d$ . This means, that while  $d$  is evaluated at a higher




Figure 6.3: The resample block as implemented in the EDA library

sample rate, the full RESAMPLE block outputs at the same sample rate as its input. This block can be seen in [Figure 6.3](#), and the type rules and signal processor of it are described here:

$$\frac{d : i \rightarrow o \quad F_i : i \rightarrow i \quad F_d : o \rightarrow o \quad N \in \mathbb{N}^+}{\text{RESAMPLE}\langle N \rangle(d, F_i, F_d) : i \rightarrow o}$$

$$u_j(t) = \begin{cases} s_j\left(\frac{t}{N}\right) & \exists k \in \mathbb{N} : t = N \cdot k \\ 0 & \text{otherwise} \end{cases}$$

$$\llbracket \text{SEQ}(\text{SEQ}(F_i, d), F_d) \rrbracket(u_1, \dots, u_i) = (v_1, \dots, v_o)$$

$$y_j(t) = v_j(t \cdot N)$$

$$\llbracket \text{RESAMPLE}\langle N \rangle(d, F_i, F_d) \rrbracket(s_1, \dots, s_i) = (y_1, \dots, y_o)$$

While this approach does not allow a signal processor to output at a different rate than its input, it still covers most relevant usecases. For instance, all plugin frameworks mentioned in the previous chapter have this constraint. In general, actual sample-rate conversion is usually done at the edge of the system, and in the cases where it is needed, it can easily be done outside of the component described as a block diagram.

## 6.4 Multirate in the EDA Library

As with most of the constructs described in [chapter 4](#), translating the resampling block to C++ for the EDA library is a fairly straight forward process. RESAMPLE is a compositional block, so it inherits from `CompositionBase`. In the implementation shown here, the filters are just sequentially composed around the inner block in the construction function, but in an optimized implementation custom filters would be used, with optimizations such as not invoking the decimation filter on the samples that are discarded during downsampling (see [subsection 6.2.3](#)).

```
template<int N, AnyBlock Block>
requires(N > 1)
struct Resample : CompositionBase<Resample<N, Block>, ins<Block>, outs<Block>, Block> {};

template<int N>
constexpr auto resample(AnyBlock auto block, AnyBlock auto f1, AnyBlock auto f2)
{
    auto filter_block = seq(f1, block, f2);
    return Resample<N, decltype(filter_block)>{{filter_block}};
}
```

The evaluator is where the interesting parts reside:



```

template<int N, AnyBlock Block>
struct evaluator<Resample<N, Block>> : EvaluatorBase<Resample<N, Block>> {
    constexpr evaluator(const Resample<N, Block>& resample) noexcept
        : EvaluatorBase<Resample<N, Block>>(resample)
    {}

    constexpr Frame<outs<Block>> eval(Frame<ins<Block>> in)
    {
        auto& e = std::get<0>(this->operands);
        for (float& f : in) {
            f *= N;
        }
        Frame<outs<Block>> res = e.eval(in);
        for (int i = 1; i < N; i++) {
            e.eval({});
        }
        return res;
    }
};

```

- *Line 10-12*: The gain is increased to compensate for the loss during interpolation (see [subsection 6.2.1](#))
- *Line 13*: The block is evaluated on the input data.
- *Line 14-16*: The block is evaluated  $N - 1$  times with all-zero inputs.
- *Line 17*: The result of the first evaluation is returned.

Since the block here already contains the interpolation/decimation filters, these operations constitute oversampling.

### 6.4.1 FIR filters in EDA

While Finite Impulse Response filters (as introduced in [subsection 6.2.2](#)) are used for many other purposes than rate conversions, the implementation is included in this chapter for context. Given filter kernel  $(b_0, b_n)$ , the block  $\text{FIR}(b_0, \dots, b_n) : 1 \rightarrow 1$  is a primitive block implemented as such:

```

template<std::size_t N>
struct FIRFilter : BlockBase<FIRFilter<N>, 1, 1> {
    std::array<float, N> kernel;
};

template<std::size_t N>
constexpr auto fir(std::array<float, N> kernel) noexcept
{
    return FIRFilter<N>{.kernel = kernel};
}

```

I will not go into detail on the implementation, but it is shown here mainly to illustrate that except for the EDA-specific structure of the classes, the filter is implemented in normal C++, similar to how a point-wise evaluated FIR filter would usually be implemented, with a `std::array` used as a ringbuffer, the kernel stored in two consecutive copies, and the meat of the evaluation being done with `std::inner_product`<sup>1</sup>:

<sup>1</sup>see [https://en.cppreference.com/w/cpp/algorithm/inner\\_product](https://en.cppreference.com/w/cpp/algorithm/inner_product)

```

template<std::size_t N>
struct evaluator<FIRFilter<N>> : EvaluatorBase<FIRFilter<N>> {
    constexpr evaluator(const FIRFilter<N>& fir) noexcept
    {
        std::ranges::copy(fir.kernel, kernel.begin());
        std::ranges::copy(fir.kernel, kernel.begin() + N);
    }
    constexpr Frame<1> eval(Frame<1> in)
    {
        if (t == N) t = 0;
        t++;
        z[N - t] = in;
        auto start = kernel.begin() + t;
        return std::inner_product(start, start + N, z.begin(), 0.f);
    }
private:
    std::size_t t = 0;
    std::array<float, N> z = {0};
    std::array<float, 2 * N> kernel;
};

```

This implementation shows that it is possible to implement DSP algorithms in "normal" C++, which allows for hand-written optimizations and complex state, and still have them completely transparently available as a block in an EDA context.

### 6.4.2 Example

To demonstrate oversampling in EDA, the  $\tanh(5x)$  example used throughout this chapter is implemented in EDA as such:

```

auto quarterpass = fir(qp_coefficients);
auto tanh = fun<1, 1>(&std::ftanh);
auto saturation = resample<4>(_ * 5 | tanh, quarterpass, quarterpass);

```

In fact, LV2 plugins constructed in a manner similar to the echo plugin described in [section 5.3](#) containing variations on this implementation is what was used to generate [Figure 6.2](#) and [Figure 6.1](#).

The coefficients for the filter can be seen in the appendix, page 59.

## 6.5 Conclusion

This chapter has covered the motivation and methods behind multirate DSP, with a focus on oversampling. By implementing this feature in the algebra of blocks, and then in the EDA library in roughly 30 lines of code, I have given an example of the merits of a domain specific library in a general-purpose language compared to a domain specific language, and specifically the versatility allowed by the design choices made in this project. To help support this argument, an implementation of a FIR filter was shown, illustrating how complicated primitive blocks can be implemented in vanilla C++ by the user of the library, instead of having to rewrite the problem in terms of recursion and other basic compositional blocks.

In [section 6.3](#), two possible solutions for multirate DSP were introduced, and while the second was selected here, the first also has potential, though the implementation would be more involved. It does however enable operations that are not supported by the chosen design, by allowing blocks to output at a different sample rate than their input. Potential further work in this area includes exploring possible implementations of that design, and especially how it would integrate with work on vectorization and buffer-wise evaluation.

## Chapter 7

# Conclusion & Further Work

Building on existing research, this thesis has explored an alternative way to write DSP programs modelled as block diagrams. I have built an embedded DSL in a C++ library by applying existing techniques from other domains to this domain, and used that library to write an audio plugin that can be used in audio editors. Furthermore I have shown the advantages of working inside a general purpose language, and specifically how constrained C++ templates can provide a framework where parts of the algorithms can be written in conventional C++, using the proven constructs and structures of the language in low-latency situations. I have also explored multirate DSP as an example of an easy extension to the library to solve a specific signal processing problem that requires more specialized design to implement in a DSL compiler.

While the testing of the library performed so far is minimal, it gives an indication of what is possible using the ideas presented. Even in its current unoptimized state, the library only has a performance overhead of around 1.5x compared to handwritten code. While this number is based on only a single example, it is an example that covers most areas of the library, and should give an indication of the magnitude. I have also presented some ideas on how to improve the performance, such as an evaluator that uses vector instructions and optimizing the AST before evaluation. In both of these areas a lot of prior research exists, that could be applied to this project.

Further enhancements could also be made to the syntactical aspects provided by the library, such as naming signals as variables, and declaring blocks with a function syntax. However, the current syntax has been shown to be useful already, and provide a good mapping from blocks diagrams of signal processors to code.

Lastly, as described in [chapter 6](#), multirate DSP is a complex problem that can be highly optimized. The current implementation shows the basics of how it could be implemented, but for real use it should be improved with better filters, as well as expanded to support undersampling in addition to oversampling.

All in all, I believe that this project has shown the idea of using an EDSL built on block algebra to be viable, as well as providing the basis of how such a library could be implemented.

# Bibliography

- [1] *Faust Programming Language*. URL: <https://faust.grame.fr>.
- [2] Yann Orlarey, Dominique Fober, and Stéphane Letz. “An Algebraic approach to Block Diagram Constructions”. In: (2002). Ed. by GMEM, pp. 151–158. URL: <https://hal.archives-ouvertes.fr/hal-02158931>.
- [3] Stéphane Letz, Yann Orlarey, and Dominique Fober. “FAUST Domain Specific Audio DSP Language Compiled to WebAssembly”. In: *The Web Conference*. Lyon, France: International World Wide Web Conferences Steering Committee, 2018, pp. 701–709. DOI: [10.1145/3184558.3185970](https://doi.org/10.1145/3184558.3185970). URL: <https://hal.archives-ouvertes.fr/hal-02158925>.
- [4] Michel Buffa et al. “Towards an open Web Audio plug-in standard”. In: *WWW2018 - TheWebConf 2018 : The Web Conference, 27th International World Wide Web Conference*. Lyon, France, Mar. 2018. DOI: [10.1145/3184558.3188737](https://doi.org/10.1145/3184558.3188737). URL: <https://hal.univ-cotedazur.fr/hal-01721483>.
- [5] Smilen Dimitrov, Romain Michon, and Stefania Serafin. “Blender2faust: from drawn 3d objects to physically based sound models”. In: *Sound and Music Computing Conference*. Limassol, Cyprus, 2018. URL: <https://hal.archives-ouvertes.fr/hal-02158954>.
- [6] Benedict R. Gaster, Nathan Renney, and Tom Mitchell. “Outside the block syndicate: Translating Faust’s algebra of blocks to the arrows framework”. In: 2018. URL: <https://uwe-repository.worktribe.com/output/864391>.
- [7] Edgar Berdahl, Peter Vasil, and Andrew Pfalz. “Automatic Visualization and Graphical Editing of Virtual Modeling Networks for the Open-Source Synth-A-Modeler Compiler”. In: *International Conference on Human Haptic Sensing and Touch Enabled Computer Applications*. London, United Kingdom, 2016, pp. 490–500. DOI: [10.1007/978-3-319-42324-1\\_48](https://doi.org/10.1007/978-3-319-42324-1_48). URL: <https://hal.archives-ouvertes.fr/hal-03162897>.
- [8] Matteo Frigo and Steven G. Johnson. “The Design and Implementation of FFTW3”. In: *Proceedings of the IEEE 93.2* (2005). Special issue on “Program Generation, Optimization, and Platform Adaptation”, pp. 216–231.
- [9] Gaël Guennebaud, Benoît Jacob, et al. *Eigen v3*. 2010. URL: <http://eigen.tuxfamily.org>.
- [10] Martín Abadi et al. *TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems*. Software available from tensorflow.org. 2015. URL: <https://www.tensorflow.org/>.
- [11] Erik Einhorn et al. “MIRA - middleware for robotic applications”. In: *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*. IEEE, 2012.
- [12] ISO. *ISO/IEC 14882:2017 Information technology — Programming languages — C++*. Sixth. Geneva, Switzerland: International Organization for Standardization, Dec. 2020, p. 1853. URL: <https://www.iso.org/standard/79358.html>.
- [13] Eric Niebler, Casey Carter, and Christopher Di Bella. *P0896R4: The One Ranges Proposal*. <https://wg21.link/p0896r4>. Nov. 2018.
- [14] Andrew Sutton. *N4674: Working Draft, C++ extensions for Concepts*. <https://wg21.link/n4674>. June 2017.

- [15] julen kahles julen, fabián esqueda fabián, and vesa välimäki vesa. “Oversampling for nonlinear waveshaping: choosing the right filters”. In: *journal of the audio engineering society* 67.6 (June 2019), pp. 440–449. DOI: <https://doi.org/10.17743/jaes.2019.0012>.
- [16] F. R. Castillo-Soria et al. “Comparative Analysis of DSP Interpolation Process for Diverse Insertion Techniques and FIR Filtering”. In: (). URL: <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.1054.8052&rep=rep1&type=pdf>.
- [17] Kurbiel Thomas, Heinz Göckler, and Daniel Alfsmann. “A Novel Approach to the Design of Oversampling Low-Delay Complex-Modulated Filter Bank Pairs”. In: *EURASIP Journal on Advances in Signal Processing* 2009 (Dec. 2009). DOI: [10.1155/2009/692861](https://doi.org/10.1155/2009/692861).
- [18] Will C Pirkle. *Designing Audio Effect Plugins in C++: For AAX, AU, and VST3 with DSP Theory*. Routledge, 2019.
- [19] Tom Roelandts. *How to Create a Simple Low-Pass Filter*. 2014. URL: <https://web.archive.org/web/20210522153834/https://tomroelandts.com/articles/how-to-create-a-simple-low-pass-filter> (visited on 05/22/2021).
- [20] Yann Orlarey, Dominique Fober, and Stéphane Letz. “Syntactical and Semantical Aspects of Faust”. In: *Soft Computing* (2004). URL: <https://hal.archives-ouvertes.fr/hal-02159011>.
- [21] Zhanyong Wan and Paul Hudak. “Functional reactive programming from first principles”. In: *Proceedings of the ACM SIGPLAN 2000 conference on Programming language design and implementation*. 2000, pp. 242–252.
- [22] Romain Picard. *Hands-On Reactive Programming with Python*. Packt, 2018. ISBN: 9781789138726.
- [23] Bruno Bachelet and Loïc Yon. “Designing Expression Templates with Concepts”. In: *Software: Practice and Experience* 47.11 (Mar. 2017), pp. 1521–1537. DOI: [10.1002/spe.2483](https://doi.org/10.1002/spe.2483). URL: <https://hal.archives-ouvertes.fr/hal-01351060>.
- [24] URL: <https://en.cppreference.com/w/cpp/language/constraints>.
- [25] Nicolas Scaringella et al. “Automatic vectorization in Faust”. In: *Journées d’Informatique Musicale*. Ed. by JIM. Montbeliard, France, 2003. URL: <https://hal.archives-ouvertes.fr/hal-02158949>.
- [26] Saar Raz. *Clang Concepts*. Talk given at CoreCPP. 2019. URL: [https://corecppil.github.io/CoreCpp2019/Presentations/Saar\\_clang\\_concepts.pdf](https://corecppil.github.io/CoreCpp2019/Presentations/Saar_clang_concepts.pdf).
- [27] C.E. Shannon. “Communication in the Presence of Noise”. In: *Proceedings of the IRE* 37.1 (1949), pp. 10–21. DOI: [10.1109/JRPROC.1949.232969](https://doi.org/10.1109/JRPROC.1949.232969).
- [28] Bonnie C. Baker. “Anti-Aliasing, Analog Filters for Data Acquisition Systems”. In: (1999).
- [29] Stefan Bilbao et al. “Antiderivative Antialiasing for Memoryless Nonlinearities”. In: *IEEE Signal Processing Letters* 24.7 (2017), pp. 1049–1053. DOI: [10.1109/LSP.2017.2675541](https://doi.org/10.1109/LSP.2017.2675541).
- [30] Brecht De Man and Joshua D. Reiss. “Adaptive Control of Amplitude Distortion Effects”. In: (). URL: <https://www.eecs.qmul.ac.uk/~josh/documents/2014/DeMan%20Reiss%20-%20AES53.pdf>.
- [31] Francisco Rubén Castillo Soria et al. “A simplification to the fast FIR-FFT filtering technique in the DSP interpolation process for band-limited signals”. en. In: *Revista Facultad de Ingeniería Universidad de Antioquia* (Sept. 2013), pp. 09–19. ISSN: 0120-6230. URL: [http://www.scielo.org.co/scielo.php?script=sci\\_arttext&pid=S0120-62302013000300002&nrm=iso](http://www.scielo.org.co/scielo.php?script=sci_arttext&pid=S0120-62302013000300002&nrm=iso).

# Appendix A

## Code

This appendix contains all code written for this project. It is also available on github at <https://github.com/topisani/eda> for easier browsing.

### A.1 EDA Library Code

---

**include/eda/internal/util.hpp**

---

```
1  #pragma once
2  #include <utility>
3
4  #define FWD(X) std::forward<decltype(X)>(X)
5
6  namespace eda::util {
7
8      namespace detail {
9          template<typename T>
10             struct function_ptr_impl;
11             template<typename Ret, typename... Args>
12             struct function_ptr_impl<Ret(Args...)> {
13                 using type = Ret (*)(Args...);
14             };
15             template<typename Ret, typename... Args>
16             struct function_ptr_impl<Ret(Args...) noexcept> {
17                 using type = Ret (*)(Args...) noexcept;
18             };
19         } // namespace detail
20
21         template<typename Func>
22         using function_ptr = typename detail::function_ptr_impl<Func>::type;
23
24         template<typename Test, template<typename...> class Ref>
25         struct is_instance : std::false_type {};
26
27         template<template<typename...> class Ref, typename... Args>
28         struct is_instance<Ref<Args...>, Ref>: std::true_type {};
29
30         /// Check whether T is a instance of the template Template
31         /// Does not work when Template has non-type template parameters
32         template<typename T, template<typename...> typename Template>
33         concept instance_of = is_instance<T, Template>::value;
34
35         template<typename T>
```

```

36 concept ATuple = instance_of<T, std::tuple>;
37
38 template<typename T, ATuple Tup>
39 struct is_constructible_through_apply;
40
41 template<typename T, typename... Ts>
42 struct is_constructible_through_apply<T, std::tuple<Ts...>> : std::is_constructible<T, Ts...> {};
43
44 template<typename T, typename Tuple>
45 concept ConstructibleThroughApply = is_constructible_through_apply<T, Tuple>::value;
46
47 template<typename T, typename U>
48 concept decays_to = std::is_same_v<std::decay_t<T>, U>;
49
50
51 namespace detail {
52     template<typename T, typename Func>
53     struct is_callable : std::false_type {};
54
55     template<typename T, typename Ret, typename... Args>
56     struct is_callable<T, Ret(Args...)> : std::is_invocable_r<Ret, T, Args...> {};
57 }
58
59 template<typename T, typename Func>
60 concept Callable = detail::is_callable<T, Func>::value;
61
62 } // namespace topisani::eda::util

```

---

## include/eda/block.hpp

---

```

1  #pragma once
2
3  #include <algorithm>
4  #include <cmath>
5  #include <ranges>
6  #include <span>
7
8  #include "eda/frame.hpp"
9  #include "eda/internal/util.hpp"
10
11 namespace eda {
12
13     // BLOCK //////////////////////////////////////
14
15     /// CRTP Base class of all blocks.
16     ///
17     /// Provides `in_channels` and `out_channels` constants, as well as
18     /// the call operator for currying.
19     template<typename Derived, std::size_t InChannels, std::size_t OutChannels>
20     struct BlockBase {
21         static constexpr std::size_t in_channels = InChannels;
22         static constexpr std::size_t out_channels = OutChannels;
23
24         constexpr auto operator()(auto&&... inputs) const noexcept //
25             requires(sizeof...(inputs) <= InChannels);
26     };
27
28     /// The basic concept of a block
29     template<typename T>
30     concept AnyBlock = std::is_base_of_v<BlockBase<T, T::in_channels, T::out_channels>, T> && std::copyable<T>;
31

```

```

32  /// The basic concept of a block
33  template<typename T, std::size_t I, std::size_t O>
34  concept ABlock = AnyBlock<T> &&(T::in_channels == I) && (T::out_channels == O);
35
36  /// A type that may be a reference to `AnyBlock`
37  template<typename T>
38  concept AnyBlockRef = AnyBlock<std::remove_cvref_t<T>>;
39
40  /// Number of input channels for block
41  template<AnyBlockRef T>
42  constexpr auto ins = std::remove_cvref_t<T>::in_channels;
43
44  /// Number of output channels for block
45  template<AnyBlockRef T>
46  constexpr auto outs = std::remove_cvref_t<T>::out_channels;
47
48  // COMPOSITION //////////////////////////////////////
49
50  template<typename D, std::size_t In, std::size_t Out, AnyBlock... Operands>
51  struct CompositionBase : BlockBase<D, In, Out> {
52      using operands_t = std::tuple<Operands...>;
53      constexpr CompositionBase(Operands... ops) noexcept : operands(std::move(ops)...) {}
54      operands_t operands;
55  };
56
57  template<typename T>
58  concept AComposition = AnyBlock<T> && requires (T& t) {
59      typename T::operands_t;
60      { t.operands } -> util::decays_to<typename T::operands_t>;
61  };
62
63  template<typename T>
64  concept ACompositionRef = AComposition<std::remove_cvref_t<T>>;
65
66  template<ACompositionRef T>
67  using operands_t = typename std::remove_cvref_t<T>::operands_t;
68
69  // LITERAL //////////////////////////////////////
70
71  /// A block that models a literal/constant value
72  struct Literal : BlockBase<Literal, 0, 1> {
73      float value;
74  };
75
76  /// Wrap a value in `Literal` if it is not already a block
77  constexpr decltype(auto) as_block(AnyBlockRef auto&& input) noexcept
78  {
79      return FWD(input);
80  }
81
82  /// Wrap a value in `Literal` if it is not already a block
83  constexpr Literal as_block(float f) noexcept
84  {
85      return Literal({}, f);
86  }
87
88  /// The result of calling `as_block`
89  template<typename T>
90  using as_block_t = std::remove_cvref_t<decltype(as_block(std::declval<T>()))>;
91
92  // REF //////////////////////////////////////

```



```

93
94 struct Ref : BlockBase<Ref, 0, 1> {
95     float* ptr = nullptr;
96 };
97
98 constexpr Ref ref(float& f) noexcept
99 {
100     return Ref{{}, &f};
101 }
102
103 /// Convert a pointer to float to a ref block
104 constexpr Ref as_block(float* fp) noexcept
105 {
106     return ref(*fp);
107 }
108
109 // CURRYING //////////////////////////////////////
110
111 /// Block used to capture parameters when calling blocks as functions
112 template<AnyBlock Block, AnyBlock... Inputs>
113 requires((outs<Inputs> <= ins<Block>) &&...) //
114 struct Partial
115 : BlockBase<Partial<Block, Inputs...>, ins<Block> + (ins<Inputs> + ...) - (outs<Inputs> + ...), outs<Block>>
116     → {
117     constexpr Partial(Block b, Inputs... input) noexcept : block(b), inputs(input...) {}
118
119     Block block;
120     std::tuple<Inputs...> inputs;
121 };
122
123 /// Call operator of BlockBase. Pass parameters as input signals
124 ///
125 /// Allows currying/partial application of parameters. Parameters will be
126 /// sent as inputs from left to right.
127 template<typename D, std::size_t I, std::size_t O>
128 constexpr auto BlockBase<D, I, O>::operator()(auto&&... inputs) const noexcept //
129     requires(sizeof...(inputs) <= I)
130 {
131     return Partial<D, as_block_t<decltype(inputs)>...>(static_cast<const D&>(*this), as_block(FWD(inputs))...);
132 }
133
134 // IDENT //////////////////////////////////////
135
136 /// Identity block. Returns its input unchanged
137 template<std::size_t N = 1>
138 struct Ident : BlockBase<Ident<N>, N, N> {};
139 /// The identity block.
140 template<std::size_t N = 1>
141 constexpr Ident<N> ident;
142
143 // CUT //////////////////////////////////////
144
145 /// Cut block. Ends a signal path and discards its input
146 template<std::size_t N = 1>
147 struct Cut : BlockBase<Cut<N>, N, 0> {};
148 /// The cut block.
149 template<std::size_t N = 1>
150 constexpr Cut<N> cut;
151
152 // PARALLEL //////////////////////////////////////

```

```

153  /// Parallel composition block.
154  ///
155  /// Given input `(x0, x1)` and blocks `l, r`, outputs `(l(x0), r(x1))`
156  template<AnyBlock Lhs, AnyBlock Rhs>
157  struct Parallel : CompositionBase<Parallel<Lhs, Rhs>, ins<Lhs> + ins<Rhs>, outs<Lhs> + outs<Rhs>, Lhs, Rhs> {};
158
159  /// The parallel composition of two blocks.
160  template<AnyBlockRef Lhs, AnyBlockRef Rhs>
161  constexpr auto par(Lhs&& lhs, Rhs&& rhs) noexcept
162  {
163      return Parallel<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};
164  }
165
166  template<AnyBlockRef A, AnyBlockRef B, AnyBlockRef... Blocks>
167  constexpr auto par(A&& a, B&& b, Blocks&&... blocks) noexcept
168  {
169      return par(a, par(b, blocks...));
170  }
171
172  // SEQUENTIAL //////////////////////////////////////
173
174  /// Sequential composition block.
175  ///
176  /// Given input `x0` and blocks `l, r`, outputs `r(l(x0))`
177  template<AnyBlock Lhs, AnyBlock Rhs>
178  requires(outs<Lhs> == ins<Rhs>) //
179  struct Sequential : CompositionBase<Sequential<Lhs, Rhs>, ins<Lhs>, outs<Rhs>, Lhs, Rhs> {};
180
181  /// The sequential composition of two blocks.
182  template<AnyBlockRef Lhs, AnyBlockRef Rhs>
183  constexpr auto seq(Lhs&& lhs, Rhs&& rhs) noexcept
184  {
185      return Sequential<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};
186  }
187
188  template<AnyBlockRef A, AnyBlockRef B, AnyBlockRef... Blocks>
189  constexpr auto seq(A&& a, B&& b, Blocks&&... blocks) noexcept
190  {
191      return seq(a, seq(b, blocks...));
192  }
193
194  // REPEAT //////////////////////////////////////
195
196  /// Apply the binary operator `composition` to `block` repeated `N` times
197  template<std::size_t N>
198  constexpr auto repeat(AnyBlock auto const& block, auto&& composition) requires requires
199  {
200      composition(block, block);
201  }
202  {
203      if constexpr (N == 0) {
204          return ident<0>;
205      } else if constexpr (N == 1) {
206          return block;
207      } else {
208          return composition(block, repeat<N - 1>(block, composition));
209      }
210  }
211
212  /// Repeat `block` `N` times through the sequential operator
213  template<std::size_t N>

```

```

214 constexpr auto repeat_seq(AnyBlock auto const& block)
215 {
216     return repeat<N>(block, [](auto&& a, auto&& b) { return seq(a, b); });
217 }
218
219 /// Repeat `block` `N` times through the parallel operator
220 template<std::size_t N>
221 constexpr auto repeat_par(AnyBlock auto const& block)
222 {
223     return repeat<N>(block, [](auto&& a, auto&& b) { return par(a, b); });
224 }
225
226 // RECURSIVE //////////////////////////////////////
227
228 /// Recursive composition block.
229 ///
230 /// Given input `x` and blocks `l, r`, outputs `l(r(x'), x)`, where `x'` is the output
231 /// of the previous evaluation.
232 template<AnyBlock Lhs, AnyBlock Rhs>
233 requires(ins<Rhs> <= outs<Lhs>) && (outs<Rhs> <= ins<Lhs>) //
234     struct Recursive : CompositionBase<Recursive<Lhs, Rhs>, ins<Lhs> - outs<Rhs>, outs<Lhs>, Lhs, Rhs> {};
235
236 /// The recursive composition of two blocks
237 template<AnyBlockRef Lhs, AnyBlockRef Rhs>
238 constexpr auto rec(Lhs&& lhs, Rhs&& rhs) noexcept
239 {
240     return Recursive<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};
241 }
242
243 // Split //////////////////////////////////////
244
245 /// Split composition block.
246 ///
247 /// Given two blocks `l, r`, applies `l`, and passes the output to `r`, repeating the signals
248 /// to fit the arity of `r`.
249 template<AnyBlock Lhs, AnyBlock Rhs>
250 requires(ins<Rhs> % outs<Lhs> == 0) //
251     struct Split : CompositionBase<Split<Lhs, Rhs>, ins<Lhs>, outs<Rhs>, Lhs, Rhs> {};
252
253 /// The split composition of two blocks.
254 template<AnyBlockRef Lhs, AnyBlockRef Rhs>
255 constexpr auto split(Lhs&& lhs, Rhs&& rhs) noexcept
256 {
257     return Split<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};
258 }
259
260 // MERGE //////////////////////////////////////
261
262 /// Merge composition block.
263 ///
264 /// Given two blocks `l, r`, applies `l`, and passes the output to `r`, such that each
265 /// input to `r` is the sum of all `l(x)[i mod ins<r>]`.
266 template<AnyBlock Lhs, AnyBlock Rhs>
267 requires(outs<Lhs> % ins<Rhs> == 0) //
268     struct Merge : CompositionBase<Merge<Lhs, Rhs>, ins<Lhs>, outs<Rhs>, Lhs, Rhs> {};
269
270 /// The merge composition of two blocks.
271 template<AnyBlockRef Lhs, AnyBlockRef Rhs>
272 constexpr auto merge(Lhs&& lhs, Rhs&& rhs) noexcept
273 {
274     return Merge<std::remove_cvref_t<Lhs>, std::remove_cvref_t<Rhs>>{{FWD(lhs), FWD(rhs)}};

```

```

275 }
276
277 // ARITHMETIC //////////////////////////////////////
278
279 /// A simple block that calculates the sum of its two inputs
280 struct Plus : BlockBase<Plus, 2, 1> {};
281 constexpr Plus plus;
282 /// A simple block that calculates the difference between its two inputs
283 struct Minus : BlockBase<Minus, 2, 1> {};
284 constexpr Minus minus;
285 /// A simple block that calculates the multiple of its two inputs
286 struct Times : BlockBase<Times, 2, 1> {};
287 constexpr Times times;
288 /// A simple block that calculates the ratio between its two inputs
289 struct Divide : BlockBase<Divide, 2, 1> {};
290 constexpr Divide divide;
291
292 // MEM //////////////////////////////////////
293
294 /// Fixed size memory block.
295 ///
296 /// Outputs its input delayed by n samples
297 template<std::size_t Samples = 1>
298 struct Mem : BlockBase<Mem<Samples>, 1, 1> {};
299
300 template<std::size_t Samples = 1>
301 constexpr Mem<Samples> mem;
302
303 /// Delay output of block by 1 sample
304 template<AnyBlock Block>
305 auto operator~(Block const& b)
306 {
307     return seq(b, repeat_par<outs<Block>>(mem<1>));
308 }
309
310 // DELAY //////////////////////////////////////
311
312 /// Variable size memory block.
313 ///
314 /// Given input signals `(d, x)`, outputs `x` delayed by `d` samples
315 struct Delay : BlockBase<Delay, 2, 1> {};
316 constexpr Delay delay;
317
318 // FUNCTION //////////////////////////////////////
319
320 /// Adapt a function to a block
321 template<std::size_t In, std::size_t Out, util::Callable<Frame<Out>(Frame<In>)> F>
322 requires std::copyable<F>
323 struct FunBlock : BlockBase<FunBlock<In, Out, F>, In, Out> {
324     F func_;
325 };
326
327 template<std::size_t In, std::size_t Out>
328 constexpr auto fun(util::Callable<Frame<Out>(Frame<In>)> auto&& f)
329 {
330     return FunBlock<In, Out, std::decay_t<decltype(f)>>{.func_ = f};
331 }
332
333 constexpr auto sin = fun<1, 1>(&::sinf);
334 constexpr auto cos = fun<1, 1>(&::cosf);
335 constexpr auto tan = fun<1, 1>(&::tanf);

```

```

336 constexpr auto tanh = fun<1, 1>(&::tanhf);
337 constexpr auto mod = fun<2, 1>([](auto in) { return std::fmod(in[0], in[1]); });
338
339 // STATEFUL_FUNC //////////////////////////////////////
340
341 template<std::size_t In, std::size_t Out, typename Func, typename... States>
342 requires(util::Callable<Func, Frame<Out>(Frame<In>, States&...)>&& std::copyable<Func>) &&
343 (std::copyable<States> && ...) //
344 struct StatefulFunc : BlockBase<StatefulFunc<In, Out, Func, States...>, In, Out> {
345     Func func;
346     std::tuple<States...> states;
347 };
348
349 template<std::size_t In, std::size_t Out, typename... States>
350 constexpr auto fun(util::Callable<Frame<Out>(Frame<In>, std::remove_cvref_t<States>&...)> auto&& f,
351                   States&&... states)
352 {
353     return StatefulFunc<In, Out, std::decay_t<decltype(f)>, std::remove_cvref_t<States>...>{.func = f,
354                                                                                          .states = {FWD(states)...}};
355 }
356
357 // FIR //////////////////////////////////////
358
359 template<std::size_t N>
360 struct FIRFilter : BlockBase<FIRFilter<N>, 1, 1> {
361     std::array<float, N> kernel;
362 };
363
364 template<std::size_t N>
365 constexpr auto fir(std::array<float, N> kernel) noexcept
366 {
367     return FIRFilter<N>{.kernel = kernel};
368 }
369
370 } // namespace eda

```

---

## include/eda/frame.hpp

---

```

1  #pragma once
2
3  #include <array>
4  #include <cstdint>
5  #include <span>
6
7  namespace eda {
8
9      template<std::size_t Channels>
10     struct Frame {
11         constexpr Frame() = default;
12         constexpr Frame(std::array<float, Channels> data) : data_(data) {}
13         constexpr Frame(auto... floats) requires(sizeof...(floats) == Channels &&
14                                                    (std::convertible_to<decltype(floats), float> && ...))
15             : data_{static_cast<float>(floats)...}
16         {}
17
18         static constexpr std::size_t size()
19         {
20             return Channels;
21         }
22         static constexpr std::size_t channels()
23         {

```

```

24     return Channels;
25 }
26
27 [[nodiscard]] constexpr auto begin() const noexcept
28 {
29     return data_.begin();
30 }
31 [[nodiscard]] constexpr auto end() const noexcept
32 {
33     return data_.end();
34 }
35
36 constexpr auto begin()
37 {
38     return data_.begin();
39 }
40 constexpr auto end()
41 {
42     return data_.end();
43 }
44
45 constexpr float& operator[](std::size_t Idx)
46 {
47     return data_[Idx];
48 }
49
50 constexpr float* data()
51 {
52     return data_.data();
53 }
54
55 operator float&() //
56     requires(size() == 1)
57 {
58     return data_[0];
59 }
60
61 constexpr bool operator==(const Frame&) const noexcept = default;
62 constexpr bool operator==(float f) const noexcept //
63     requires(size() == 1)
64 {
65     return data_[0] == f;
66 }
67
68 private : //
69     std::array<float, Channels>
70     data_ = {0};
71 };
72
73 template<>
74 struct Frame<0> {
75     constexpr Frame() = default;
76     static constexpr std::size_t size()
77     {
78         return 0;
79     }
80     static constexpr std::size_t channels()
81     {
82         return 0;
83     }
84 }

```

```

85     static constexpr float* begin()
86     {
87         return nullptr;
88     }
89     static constexpr float* end()
90     {
91         return nullptr;
92     }
93
94     static constexpr float* data()
95     {
96         return nullptr;
97     }
98
99     constexpr bool operator==(const Frame&) const noexcept = default;
100 };
101
102 template<std::size_t N>
103 Frame(std::array<float, N> arr) -> Frame<N>;
104
105 Frame(auto... floats) -> Frame<sizeof...(floats)>;
106
107 /// Get a subsection of the frame which contains [Begin; End[.
108 ///
109 /// If End is negative, count `-End` elements from the end of the array.
110 template<std::ptrdiff_t Begin, std::ptrdiff_t End, std::size_t Channels>
111 requires(Begin >= 0 && ((End >= Begin && End <= Channels))) //
112     constexpr auto slice(const Frame<Channels>& in)
113     {
114         Frame<End - Begin> res;
115         std::copy(in.begin() + Begin, in.begin() + End, res.begin());
116         return res;
117     }
118
119 template<std::ptrdiff_t Begin, std::ptrdiff_t End, std::size_t Channels>
120 requires(Begin >= 0 && End < 0 && (Channels + End + 1) >= Begin) //
121     constexpr auto slice(const Frame<Channels>& in) //
122     {
123         return slice<Begin, Channels + End + 1, Channels>(in);
124     }
125
126 /// Concatenate two frames
127 template<std::size_t S1, std::size_t S2>
128 constexpr auto concat(const Frame<S1>& x1, const Frame<S2>& x2) -> Frame<S1 + S2>
129 {
130     Frame<S1 + S2> res;
131     auto b2 = std::copy(x1.begin(), x1.end(), res.begin());
132     std::copy(x2.begin(), x2.end(), b2);
133     return res;
134 }
135
136 template<std::size_t S1, std::size_t... Sizes>
137 constexpr auto concat(const Frame<S1>& x, const Frame<Sizes>&... xs) -> Frame<S1 + (Sizes + ...) >
138 {
139     return concat(x, concat(xs...));
140 }
141
142 } // namespace eda

```

---

**include/eda/evaluator.hpp**

---

```

1  #pragma once
2
3  #include <numeric>
4
5  #include "eda/block.hpp"
6  #include "eda/frame.hpp"
7
8  namespace eda {
9
10     // EVALUATOR //////////////////////////////////////
11
12     template<AnyBlock T>
13     struct evaluator;
14
15     template<typename T>
16     struct block_for;
17
18     template<typename T>
19     struct block_for<evaluator<T>> {
20         using type = T;
21     };
22
23     template<typename T>
24     using block_for_t = typename block_for<T>::type;
25
26     template<AnyBlock Block>
27     constexpr auto eval(Block block, Frame<Block::in_channels> in)
28     {
29         return make_evaluator(block).eval(in);
30     }
31
32     // COMPOSITION EVALUATOR //////////////////////////////////////
33
34     template<AnyBlock T>
35     struct EvaluatorBase {};
36
37     namespace detail {
38         template<typename T>
39         struct add_evaluator {};
40
41         template<typename... Ts>
42         struct add_evaluator<std::tuple<Ts...>> {
43             using type = std::tuple<evaluator<Ts>...>;
44         };
45
46         template<typename T>
47         using add_evaluator_t = typename add_evaluator<T>::type;
48     } // namespace detail
49
50     template<AComposition T>
51     struct EvaluatorBase<T> {
52         constexpr EvaluatorBase(const T& t) : operands(t.operands) {}
53         detail::add_evaluator_t<operands_t<T>> operands;
54     };
55
56     template<typename T>
57     concept AnEvaluator =
58         std::derived_from<T, EvaluatorBase<block_for_t<T>>>
59         && std::is_constructible_v<T, block_for_t<T> const&>
60         && requires (T t, Frame<ins<block_for_t<T>>> in) {
61             { t.eval(in) } -> std::convertible_to<Frame<outs<block_for_t<T>>>>;

```



```

62     };
63
64     template<AnyBlockRef T>
65     constexpr auto make_evaluator(T&& b)
66     requires AnEvaluator<evaluator<std::remove_cvref_t<T>>>
67     {
68         return evaluator<std::remove_cvref_t<T>>(b);
69     }
70
71     // DYN EVALUATOR //////////////////////////////////////
72
73     template<std::size_t Ins, std::size_t Outs>
74     struct DynEvaluator {
75         DynEvaluator() = default;
76
77         template<ABlock<Ins, Outs> Block>
78         DynEvaluator(evaluator<Block> evaluator) : func_([evaluator](Frame<Ins> in) mutable { return
79             ↪ evaluator.eval(in); })
80         {}
81
82         Frame<Outs> eval(Frame<Ins> in)
83         {
84             return func_(in);
85         }
86
87         Frame<Outs> operator()(Frame<Ins> in)
88         {
89             return func_(in);
90         }
91     private:
92         std::function<Frame<Outs>(Frame<Ins>)> func_;
93     };
94
95     // EVALUATOR IMPLEMENTATIONS //////////////////////////////////
96
97     // LITERAL //////////////////////////////////////
98
99     template<>
100     struct evaluator<Literal> {
101         constexpr evaluator(Literal l) : literal_(l) {}
102
103         constexpr Frame<1> eval(Frame<0>)
104         {
105             return {{literal_.value}};
106         }
107
108         Literal literal_;
109     };
110
111     // CURRYING //////////////////////////////////////
112
113     template<AnyBlock Block, AnyBlock... Inputs>
114     struct evaluator<Partial<Block, Inputs...> : EvaluatorBase<Partial<Block, Inputs...>> {
115         constexpr evaluator(const Partial<Block, Inputs...>& block) : block_(block.block), inputs_(block.inputs) {}
116
117         constexpr Frame<outs<Partial<Block, Inputs...>>> eval(Frame<ins<Partial<Block, Inputs...>>> in)
118         {
119             return block_.eval(eval_impl<>(in));
120         }
121     }

```

```

122 private:
123     template<std::size_t Idx = 0>
124     auto eval_impl(auto in)
125     {
126         if constexpr (Idx == sizeof...(Inputs)) {
127             return in;
128         } else {
129             auto& arg_block = std::get<Idx>(inputs_);
130             constexpr auto arg_ins = ins<block_for_t<std::remove_cvref_t<decltype(arg_block)>>>;
131             auto arg_res = arg_block.eval(slice<0, arg_ins>(in));
132             return concat(arg_res, eval_impl<Idx + 1>(slice<arg_ins, -1>(in)));
133         }
134     }
135
136     evaluator<Block> block_;
137     std::tuple<evaluator<Inputs>...> inputs_;
138 };
139
140 // IDENT //////////////////////////////////////
141
142 template<std::size_t N>
143 struct evaluator<Ident<N>> : EvaluatorBase<Ident<N>> {
144     constexpr evaluator(Ident<N>){};
145     static Frame<N> eval(Frame<N> in)
146     {
147         return in;
148     }
149 };
150
151 // CUT //////////////////////////////////////
152
153 template<std::size_t N>
154 struct evaluator<Cut<N>> : EvaluatorBase<Cut<N>> {
155     constexpr evaluator(Cut<N>) {}
156     static Frame<0> eval(Frame<N>)
157     {
158         return {};
159     }
160 };
161
162 // SEQUENTIAL //////////////////////////////////////
163
164 template<AnyBlock Lhs, AnyBlock Rh>
165 struct evaluator<Sequential<Lhs, Rh>> : EvaluatorBase<Sequential<Lhs, Rh>> {
166     constexpr evaluator(const Sequential<Lhs, Rh>& block) : EvaluatorBase<Sequential<Lhs, Rh>>(block) {}
167
168     constexpr Frame<outs<Sequential<Lhs, Rh>>> eval(Frame<ins<Sequential<Lhs, Rh>>> in)
169     {
170         auto l = std::get<0>(this->operands).eval(in);
171         return std::get<1>(this->operands).eval(l);
172     }
173 };
174
175 // PARALLEL //////////////////////////////////////
176
177 template<AnyBlock Lhs, AnyBlock Rh>
178 struct evaluator<Parallel<Lhs, Rh>> : EvaluatorBase<Parallel<Lhs, Rh>> {
179     constexpr evaluator(const Parallel<Lhs, Rh>& block) : EvaluatorBase<Parallel<Lhs, Rh>>(block) {}
180
181     constexpr Frame<outs<Parallel<Lhs, Rh>>> eval(Frame<ins<Parallel<Lhs, Rh>>> in)
182     {

```

```

183     auto l = std::get<0>(this->operands).eval(slice<0, ins<Lhs>>(in));
184     auto r = std::get<1>(this->operands).eval(slice<ins<Lhs>, -1>(in));
185     return concat(l, r);
186 }
187 };
188
189 // RECURSIVE //////////////////////////////////////
190
191 template<AnyBlock Lhs, AnyBlock Rhs>
192 struct evaluator<Recursive<Lhs, Rhs>> : EvaluatorBase<Recursive<Lhs, Rhs>> {
193     constexpr evaluator(const Recursive<Lhs, Rhs>& block) : EvaluatorBase<Recursive<Lhs, Rhs>>(block) {}
194     constexpr Frame<outs<Recursive<Lhs, Rhs>>> eval(Frame<ins<Recursive<Lhs, Rhs>>> in)
195     {
196         auto l_out = std::get<0>(this->operands).eval(concat(memory_, in));
197         memory_ = std::get<1>(this->operands).eval(slice<0, ins<Rhs>>(l_out));
198         return l_out;
199     }
200
201 private:
202     Frame<outs<Rhs>> memory_;
203 };
204
205 // Split //////////////////////////////////////
206
207 template<AnyBlock Lhs, AnyBlock Rhs>
208 struct evaluator<Split<Lhs, Rhs>> : EvaluatorBase<Split<Lhs, Rhs>> {
209     constexpr evaluator(const Split<Lhs, Rhs>& block) : EvaluatorBase<Split<Lhs, Rhs>>(block) {}
210
211     constexpr Frame<outs<Split<Lhs, Rhs>>> eval(Frame<ins<Split<Lhs, Rhs>>> in)
212     {
213         auto l = std::get<0>(this->operands).eval(in);
214         Frame<ins<Rhs>> rhs_in;
215         for (std::size_t i = 0; i < rhs_in.channels(); i++) {
216             rhs_in[i] = l[i % l.channels()];
217         }
218         return std::get<1>(this->operands).eval(rhs_in);
219     }
220 };
221
222 // MERGE //////////////////////////////////////
223
224 template<AnyBlock Lhs, AnyBlock Rhs>
225 struct evaluator<Merge<Lhs, Rhs>> : EvaluatorBase<Merge<Lhs, Rhs>> {
226     constexpr evaluator(const Merge<Lhs, Rhs>& block) : EvaluatorBase<Merge<Lhs, Rhs>>(block) {}
227
228     constexpr Frame<outs<Merge<Lhs, Rhs>>> eval(Frame<ins<Merge<Lhs, Rhs>>> in)
229     {
230         auto lhs_out = std::get<0>(this->operands).eval(in);
231         Frame<ins<Rhs>> rhs_in;
232         for (std::size_t i = 0; i < lhs_out.channels(); i++) {
233             rhs_in[i % rhs_in.channels()] += lhs_out[i];
234         }
235         return std::get<1>(this->operands).eval(rhs_in);
236     }
237 };
238
239 // ARITHMETIC //////////////////////////////////////
240
241 template<>
242 struct evaluator<Plus> : EvaluatorBase<Plus> {
243     constexpr evaluator(Plus){};

```

```

244     constexpr static Frame<1> eval(Frame<2> in)
245     {
246         return in[0] + in[1];
247     }
248 };
249
250 template<>
251 struct evaluator<Minus> : EvaluatorBase<Minus> {
252     constexpr evaluator(Minus){};
253     constexpr static Frame<1> eval(Frame<2> in)
254     {
255         return in[0] - in[1];
256     }
257 };
258
259 template<>
260 struct evaluator<Times> : EvaluatorBase<Times> {
261     constexpr evaluator(Times){};
262     constexpr static Frame<1> eval(Frame<2> in)
263     {
264         return in[0] * in[1];
265     }
266 };
267 template<>
268 struct evaluator<Divide> : EvaluatorBase<Divide> {
269     constexpr evaluator(Divide){};
270     constexpr static Frame<1> eval(Frame<2> in)
271     {
272         return in[0] / in[1];
273     }
274 };
275
276 // MEM //////////////////////////////////////
277
278 template<>
279 struct evaluator<Mem<1>>> : EvaluatorBase<Mem<1>>> {
280     constexpr evaluator(const Mem<1>&) {}
281     constexpr Frame<1> eval(Frame<1> in)
282     {
283         auto res = memory_;
284         memory_ = in;
285         return res;
286     }
287
288     Frame<1> memory_;
289 };
290
291 template<>
292 struct evaluator<Mem<0>>> : EvaluatorBase<Mem<0>>> {
293     constexpr evaluator(const Mem<0>&) {}
294     constexpr Frame<1> eval(Frame<1> in)
295     {
296         return in;
297     }
298 };
299
300 template<std::size_t Samples>
301 struct evaluator<Mem<Samples>>> : EvaluatorBase<Mem<Samples>>> {
302     constexpr evaluator(const Mem<Samples>&) {}
303     constexpr Frame<1> eval(Frame<1> in)
304     {

```

```

305     float res = memory_[index_];
306     memory_[index_] = in;
307     index_++;
308     index_ %= Samples;
309     return res;
310 }
311
312 std::array<float, Samples> memory_ = {};
313 std::ptrdiff_t index_ = 0;
314 };
315
316 // DELAY //////////////////////////////////////
317
318 /// Evaluator for variable sized delay.
319 ///
320 /// Memory is implemented as a `std::vector`, and never shrinks
321 template<>
322 struct evaluator<Delay> : EvaluatorBase<Delay> {
323     evaluator(const Delay&) {}
324     Frame<outs<Delay>> eval(Frame<ins<Delay>> in)
325     {
326         auto delay = static_cast<int>(in[0]);
327         if (auto old_size = memory_.size(); old_size < delay) {
328             memory_.resize(delay);
329             auto src = memory_.begin() + old_size - 1;
330             auto dst = memory_.begin() + delay - 1;
331             auto n = old_size - index_;
332             for (int i = 0; i < n; i++, src--, dst--) {
333                 *dst = *src;
334                 *src = 0;
335             }
336         }
337         float res = memory_[(memory_.size() + index_ - delay) % memory_.size()];
338         memory_[index_] = in[1];
339         ++index_;
340         index_ %= static_cast<std::ptrdiff_t>(memory_.size());
341         return res;
342     }
343
344 private:
345     std::vector<float> memory_;
346     std::ptrdiff_t index_ = 0;
347 };
348
349 // REF //////////////////////////////////////
350
351 template<>
352 struct evaluator<Ref> : EvaluatorBase<Ref> {
353     constexpr evaluator(const Ref& r) noexcept : ref_(r) {}
354     [[nodiscard]] Frame<1> eval(Frame<0>) const
355     {
356         return *ref_.ptr;
357     }
358
359 private:
360     Ref ref_;
361 };
362
363 // FUNCTION //////////////////////////////////////
364
365 /// Adapt a function to a block

```

```

366 template<std::size_t In, std::size_t Out, typename F>
367 struct evaluator<FunBlock<In, Out, F>> : EvaluatorBase<FunBlock<In, Out, F>> {
368     constexpr evaluator(const FunBlock<In, Out, F>& f) noexcept : fb_(f) {}
369     [[nodiscard]] Frame<Out> eval(Frame<In> in) const
370     {
371         return fb_.func_(in);
372     }
373
374 private:
375     FunBlock<In, Out, F> fb_;
376 };
377
378 // STATEFUL_FUNC //////////////////////////////////////
379
380 template<std::size_t In, std::size_t Out, typename Func, typename... States>
381 struct evaluator<StatefulFunc<In, Out, Func, States...>> : EvaluatorBase<StatefulFunc<In, Out, Func,
382     ⇨ States...>> {
383     constexpr evaluator(const StatefulFunc<In, Out, Func, States...>& f) noexcept : func_(f.func),
384     ⇨ states_(f.states) {}
385
386     Frame<Out> eval(Frame<In> in)
387     {
388         return std::apply([&](States&... s) { return func_(in, s...); }, states_);
389     }
390
391 private:
392     Func func_;
393     std::tuple<States...> states_;
394 };
395
396 // FIR //////////////////////////////////////
397
398 template<std::size_t N>
399 struct evaluator<FIRFilter<N>> : EvaluatorBase<FIRFilter<N>> {
400     constexpr evaluator(const FIRFilter<N>& fir) noexcept
401     {
402         std::ranges::copy(fir.kernel, kernel.begin());
403         std::ranges::copy(fir.kernel, kernel.begin() + N);
404     }
405
406     constexpr Frame<1> eval(Frame<1> in)
407     {
408         if (t == N) t = 0;
409         t++;
410         z[N - t] = in;
411         // By repeating the kernel, there is always a contiguous range to
412         // run the inner product on
413         auto start = kernel.begin() + t;
414         return std::inner_product(start, start + N, z.begin(), 0.f);
415     }
416
417 private:
418     std::size_t t = 0;
419     std::array<float, N> z = {0};
420     /// Kernel is repeated
421     std::array<float, 2 * N> kernel;
422 };
423 } // namespace eda

```

## include/eda/syntax.hpp

---

```
1  #pragma once
2
3  #include "eda/block.hpp"
4
5  namespace eda::syntax {
6
7      // LITERAL //////////////////////////////////////
8
9      constexpr Literal operator"" _eda(long double f) noexcept
10     {
11         return as_block(static_cast<float>(f));
12     }
13     constexpr Literal operator"" _eda(unsigned long long f) noexcept
14     {
15         return as_block(static_cast<float>(f));
16     }
17
18     // IDENT //////////////////////////////////////
19
20     constexpr Ident<1> _ = ident<1>;
21     constexpr Cut<1> $ = cut<1>;
22
23     // PARALLEL //////////////////////////////////////
24
25     template<typename Lhs, typename Rhs>
26     constexpr auto operator,(Lhs&& lhs, Rhs&& rhs) noexcept //
27     requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
28     {
29         return par(as_block(FWD(lhs)), as_block(FWD(rhs)));
30     }
31
32     // SEQUENTIAL //////////////////////////////////////
33
34     template<typename Lhs, typename Rhs>
35     constexpr auto operator|(Lhs&& lhs, Rhs&& rhs) noexcept //
36     requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
37     {
38         return seq(as_block(FWD(lhs)), as_block(FWD(rhs)));
39     }
40
41     // Split //////////////////////////////////////
42
43     template<typename Lhs, typename Rhs>
44     constexpr auto operator<<(Lhs&& lhs, Rhs&& rhs) noexcept //
45     requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
46     {
47         return split(as_block(FWD(lhs)), as_block(FWD(rhs)));
48     }
49
50     // MERGE //////////////////////////////////////
51
52     template<typename Lhs, typename Rhs>
53     constexpr auto operator>>(Lhs&& lhs, Rhs&& rhs) noexcept //
54     requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
55     {
56         return merge(as_block(FWD(lhs)), as_block(FWD(rhs)));
57     }
58
59     // ARITHMETIC //////////////////////////////////////
```

```

60
61 template<typename Lhs, typename Rhs>
62 constexpr auto operator+(Lhs&& lhs, Rhs&& rhs) noexcept requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
63 {
64     return plus(lhs, rhs);
65 }
66
67 template<typename Lhs, typename Rhs>
68 constexpr auto operator-(Lhs&& lhs, Rhs&& rhs) noexcept requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
69 {
70     return minus(lhs, rhs);
71 }
72
73 template<typename Lhs, typename Rhs>
74 constexpr auto operator*(Lhs&& lhs, Rhs&& rhs) noexcept requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
75 {
76     return times(lhs, rhs);
77 }
78
79 template<typename Lhs, typename Rhs>
80 constexpr auto operator/(Lhs&& lhs, Rhs&& rhs) noexcept requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
81 {
82     return divide(lhs, rhs);
83 }
84
85 // RECURSIVE //////////////////////////////////////
86
87 template<typename Lhs, typename Rhs>
88 constexpr auto operator%(Lhs&& lhs, Rhs&& rhs) noexcept requires(AnyBlockRef<Lhs> || AnyBlockRef<Rhs>)
89 {
90     return rec(as_block(FWD(lhs)), as_block(FWD(rhs)));
91 }
92
93 } // namespace eda::syntax

```

---

## include/eda/resampling.hpp

---

```

1  #pragma once
2
3  #include <eda/block.hpp>
4  #include <eda/evaluator.hpp>
5
6  namespace eda {
7      /// Halfband FIR filter
8      /// Koefficients from: https://www.dsprelated.com/showcode/270.php
9      constexpr FIRFilter halfband_firwin = fir(std::array<float, 33>({
10         0.000000f, -0.001888f, 0.000000f, 0.003862f, 0.000000f, -0.008242f, 0.000000f, 0.015947f, 0.000000f,
11         -0.028677f, 0.000000f, 0.050719f, 0.000000f, -0.098016f, 0.000000f, 0.315942f, 0.500706f, 0.315942f,
12         0.000000f, -0.098016f, 0.000000f, 0.050719f, 0.000000f, -0.028677f, 0.000000f, 0.015947f, 0.000000f,
13         -0.008242f, 0.000000f, 0.003862f, 0.000000f, -0.001888f, 0.000000f,
14     }));
15
16     /// Halfband FIR filter
17     /// Koefficients from: https://www.dsprelated.com/showcode/270.php
18     constexpr FIRFilter halfband_remez = fir(std::array<float, 33>({
19         0.000000, -0.010233, 0.000000, 0.010668, 0.000000, -0.016324, 0.000000, 0.024377, 0.000000, -0.036482,
20         ↪ 0.000000,
21         0.056990, 0.000000, -0.101993, 0.000000, 0.316926, 0.500009, 0.316926, 0.000000, -0.101993, 0.000000,
22         ↪ 0.056990,
23         0.000000, -0.036482, 0.000000, 0.024377, 0.000000, -0.016324, 0.000000, 0.010668, 0.000000, -0.010233,
24         ↪ 0.000000,

```



```

22  });
23
24  /// Halfband FIR filter
25  /// Generated using https://fiiir.com/, cutoff=0.25, transition_width=0.036
26  constexpr FIRFilter halfband = fir(std::array<float, 129>({
27      0.0000000000000000, -0.000001096652327330, 0.0000000000000000, 0.000010264031516365,
28      ↪ 0.0000000000000000,
29      -0.000029878338799022, 0.0000000000000000, 0.000061812383505534, 0.0000000000000000,
30      ↪ -0.000108554065763228,
31      0.0000000000000000, 0.000173253086175895, 0.0000000000000000, -0.000259759365306352,
32      ↪ 0.0000000000000000,
33      0.000372654783774880, -0.0000000000000000, -0.000517281125462213, 0.0000000000000000,
34      ↪ 0.000699768686890352,
35      -0.0000000000000000, -0.000927072025890890, -0.0000000000000000, 0.001207021956794792,
36      ↪ -0.0000000000000000,
37      -0.001548406472520901, 0.0000000000000000, 0.001961098299574166, -0.0000000000000000,
38      ↪ -0.002456254118009391,
39      -0.0000000000000000, 0.003046621529754296, -0.0000000000000000, -0.003747007082591159,
40      ↪ 0.0000000000000000,
41      0.004574986367556928, -0.0000000000000000, -0.005551983242189756, -0.0000000000000000,
42      ↪ 0.006704924332065411,
43      -0.0000000000000000, -0.008068815973284071, 0.0000000000000000, 0.009690852742197094,
44      ↪ -0.0000000000000000,
45      -0.011637177123532653, 0.0000000000000000, 0.014004461065005920, -0.0000000000000000,
46      ↪ -0.016940793321255140,
47      0.0000000000000000, 0.020685873179831588, -0.0000000000000000, -0.025655056087168296,
48      ↪ 0.0000000000000000,
49      0.032635432666058138, -0.0000000000000000, -0.043317966947979292, 0.0000000000000000,
50      ↪ 0.062106605722622214,
51      -0.0000000000000000, -0.105163476837881006, 0.0000000000000000, 0.317995216086781440,
52      ↪ 0.499999463719711212,
53      0.317995216086781440, 0.0000000000000000, -0.105163476837881006, -0.0000000000000000,
54      ↪ 0.062106605722622214,
55      0.0000000000000000, -0.043317966947979292, -0.0000000000000000, 0.032635432666058145,
56      ↪ 0.0000000000000000,
57      -0.025655056087168299, -0.0000000000000000, 0.020685873179831591, 0.0000000000000000,
58      ↪ -0.016940793321255140,
59      -0.0000000000000000, 0.014004461065005927, 0.0000000000000000, -0.011637177123532651,
60      ↪ -0.0000000000000000,
61      0.009690852742197097, 0.0000000000000000, -0.008068815973284077, -0.0000000000000000,
62      ↪ 0.006704924332065411,
63      -0.0000000000000000, -0.005551983242189757, -0.0000000000000000, 0.004574986367556932,
64      ↪ 0.0000000000000000,
65      -0.003747007082591159, -0.0000000000000000, 0.003046621529754298, -0.0000000000000000,
66      ↪ -0.002456254118009391,
67      -0.0000000000000000, 0.001961098299574167, 0.0000000000000000, -0.001548406472520902,
68      ↪ -0.0000000000000000,
69      0.001207021956794792, -0.0000000000000000, -0.000927072025890891, -0.0000000000000000,
70      ↪ 0.000699768686890354,
71      0.0000000000000000, -0.000517281125462214, -0.0000000000000000, 0.000372654783774880,
72      ↪ 0.0000000000000000,
73      -0.000259759365306352, 0.0000000000000000, 0.000173253086175895, 0.0000000000000000,
74      ↪ -0.000108554065763229,
75      0.0000000000000000, 0.000061812383505534, 0.0000000000000000, -0.000029878338799022,
76      ↪ 0.0000000000000000,
77      0.000010264031516366, 0.0000000000000000, -0.000001096652327330, 0.0000000000000000,
78      ↪ 0.0000000000000000,
79  }));
80
81  /// Quarterband filter.
82  /// Generated using https://fiiir.com/, cutoff=0.12, transition_width=0.036
83  constexpr FIRFilter quarterband = fir(std::array<float, 129>({
84      0.0000000000000000, -0.000000403706986821f, 0.000001645142951079f, 0.000009287227200311f,

```

```

58 0.000017748792717623f, 0.000014394082902256f, -0.000010983429301009f, -0.000052190223963627f,
59 -0.000081679045780782f, -0.000063806848675238f, 0.000017350619151396f, 0.000133494570814806f,
60 0.000213091361905980f, 0.000177818552168181f, 0.000000000000000000f, -0.000255101231985400f,
61 -0.000439770342813020f, -0.000398574267035395f, -0.000075623680817821f, 0.000411316097634436f,
62 0.000793054468436844f, 0.000782757336275945f, 0.000263598027493080f, -0.000581490631986405f,
63 -0.001302427309861704f, -0.001401048183241174f, -0.000642445391832465f, 0.000721932617703368f,
64 0.001988471495815060f, 0.002336050021380179f, 0.001319370107673039f, -0.000757668354949370f,
65 -0.002855566446823656f, -0.003680658614028739f, -0.002435687247284503f, 0.000573401157661301f,
66 0.003885973714967376f, 0.005541059780416179f, 0.004178842640528388f, -0.000000000000000005f,
67 -0.005036858234420859f, -0.008052940672693755f, -0.006814444055578153f, -0.001214592948408780f,
68 0.006241337461434024f, 0.011431116963112014f, 0.010774099480407723f, 0.003482788023864352f,
69 -0.007413913675861475f, -0.016111745242543350f, -0.016913011553121866f, -0.007615021938185520f,
70 0.008459775456166383f, 0.023213523296217339f, 0.027409555468429988f, 0.015722330699376171f,
71 -0.009286636321546431f, -0.036574781110998981f, -0.050287637072574352f, -0.036505558453421044f,
72 0.009817191016539564f, 0.081030321108466738f, 0.158215036493354722f, 0.217683966290383085f,
73 0.240001133326345484f, 0.217683966290383085f, 0.158215036493354722f, 0.081030321108466738f,
74 0.009817191016539566f, -0.036505558453421044f, -0.050287637072574359f, -0.036574781110998981f,
75 -0.009286636321546431f, 0.015722330699376171f, 0.027409555468429991f, 0.023213523296217339f,
76 0.008459775456166385f, -0.007615021938185520f, -0.016913011553121870f, -0.016111745242543350f,
77 -0.007413913675861476f, 0.003482788023864353f, 0.010774099480407730f, 0.011431116963112012f,
78 0.006241337461434024f, -0.001214592948408781f, -0.006814444055578153f, -0.008052940672693758f,
79 -0.005036858234420864f, -0.000000000000000005f, 0.004178842640528388f, 0.005541059780416181f,
80 0.003885973714967378f, 0.000573401157661302f, -0.002435687247284503f, -0.003680658614028739f,
81 -0.002855566446823658f, -0.000757668354949370f, 0.001319370107673040f, 0.002336050021380179f,
82 0.001988471495815060f, 0.000721932617703369f, -0.000642445391832466f, -0.001401048183241175f,
83 -0.001302427309861704f, -0.000581490631986405f, 0.000263598027493080f, 0.000782757336275945f,
84 0.000793054468436845f, 0.000411316097634437f, -0.000075623680817821f, -0.000398574267035395f,
85 -0.000439770342813020f, -0.000255101231985400f, 0.000000000000000000f, 0.000177818552168181f,
86 0.000213091361905980f, 0.000133494570814806f, 0.000017350619151396f, -0.000063806848675238f,
87 -0.000081679045780782f, -0.000052190223963627f, -0.000010983429301009f, 0.000014394082902255f,
88 0.000017748792717623f, 0.000009287227200311f, 0.000001645142951079f, -0.000000403706986821f,
89 0.000000000000000000f,
90 ));
91
92 template<std::size_t N>
93 requires(N == 2) auto resample_filter()
94 {
95     return halfband;
96 }
97
98 template<std::size_t N>
99 requires(N == 4) auto resample_filter()
100 {
101     return quarterband;
102 }
103
104 // RESAMPLE //////////////////////////////////////
105
106 template<int N, AnyBlock Block>
107 requires(N > 1) || (N < -1) //
108 struct Resample : CompositionBase<Resample<N, Block>, 1, 1, Block> {};
109
110 template<int N>
111 constexpr auto resample(AnyBlock auto block, AnyBlock auto f1, AnyBlock auto f2)
112 {
113     auto filter_block = seq(f1, block, f2);
114     return Resample<N, decltype(filter_block)>{{filter_block}};
115 }
116
117 template<int N>
118 constexpr auto resample(AnyBlock auto block)

```

```

119 {
120     return resample<N>(block, resample_filter<N>(), resample_filter<N>());
121 }
122
123 template<int N, AnyBlock Block>
124 struct evaluator<Resample<N, Block>> : EvaluatorBase<Resample<N, Block>> {
125     static_assert(N > 1, "Resampling not implemented for downsampling first");
126
127     constexpr evaluator(const Resample<N, Block>& resample) noexcept : EvaluatorBase<Resample<N,
128     ↪ Block>>(resample) {}
129
130     constexpr Frame<outs<Block>> eval(Frame<ins<Block>> in)
131     {
132         // Zero stuffing reduces amplitude by N
133         for (float& f : in) {
134             f *= N;
135         }
136         Frame<outs<Block>> res = std::get<0>(this->operands).eval(in);
137         for (int i = 1; i < N; i++) {
138             std::get<0>(this->operands).eval({});
139         }
140         return res;
141     }
142 };
143 } // namespace eda

```

## A.2 Example code

### example/lv2.hpp

```

1 #pragma once
2 #include <concepts>
3
4 #include "lv2/core/lv2.h"
5
6 struct LV2Plugin {
7     virtual void connect_port(uint32_t port, float* data) = 0;
8     virtual void activate() {}
9     virtual void deactivate() {}
10    virtual void run(uint32_t n_samples) = 0;
11 };
12
13 template<std::derived_from<LV2Plugin> Plugin>
14 LV2_Descriptor make_descriptor(const char* uri)
15 {
16     auto instantiate = [](const LV2_Descriptor* descriptor, double rate, const char* bundle_path,
17     const LV2_Feature* const* features) { //
18         return static_cast<LV2_Handle>(new Plugin());
19     };
20     auto connect_port = [](LV2_Handle instance, uint32_t port, void* data) { //
21         static_cast<Plugin*>(instance)->connect_port(port, static_cast<float*>(data));
22     };
23     auto activate = [](LV2_Handle instance) { //
24         static_cast<Plugin*>(instance)->activate();
25     };
26     auto run = [](LV2_Handle instance, uint32_t n_samples) { //
27         static_cast<Plugin*>(instance)->run(n_samples);
28     };
29     auto deactivate = [](LV2_Handle instance) { //

```

```

30     static_cast<Plugin*>(instance)->deactivate();
31 };
32 auto cleanup = [](LV2_Handle instance) { //
33     delete static_cast<Plugin*>(instance);
34 };
35 auto extension_data = [](const char* uri) -> const void* { return nullptr; };
36 return {
37     uri,          //
38     instantiate,  //
39     connect_port, //
40     activate,     //
41     run,          //
42     deactivate,   //
43     cleanup,      //
44     extension_data, //
45 };
46 }

```

---

## example/echo/echo.cpp

---

```

1  #include <eda/eda.hpp>
2
3  #include "../lv2.hpp"
4
5  struct Echo final : LV2Plugin {
6      constexpr static auto uri = "http://topisani.co/lv2/eda/echo";
7      Echo() = default;
8
9      void connect_port(uint32_t port, float* data) override
10     {
11         switch (port) {
12             case 0: time_samples = data; break;
13             case 1: filter_a = data; break;
14             case 2: feedback = data; break;
15             case 3: dry_wet_mix = data; break;
16             case 4: input_port = data; break;
17             case 5: output_port = data; break;
18         }
19     };
20
21     void run(uint32_t n_samples) override
22     {
23         for (int i = 0; i < n_samples; i++) {
24             output_port[i] = eval(input_port[i]);
25         }
26     }
27
28     void activate() override
29     {
30         eval = eda::make_evaluator([this] {
31             using namespace eda;
32             using namespace eda::syntax;
33             ABlock<2, 1> auto const filter = (_ << (_, _), _) | (((_ * _, (1 - _) * _) | plus) % _);
34             ABlock<1, 1> auto const echo = (plus | delay(ref(*time_samples))) % (filter(ref(*filter_a)) *
35                 ↪ ref(*feedback));
36             ABlock<1, 1> auto const process = _ << (echo * ref(*dry_wet_mix)) + (_ * (1 - ref(*dry_wet_mix)));
37             return process;
38         }());
39     }
40 private:

```

```

41     eda::DynEvaluator<1, 1> eval;
42
43     float* time_samples = nullptr;
44     float* filter_a = nullptr;
45     float* feedback = nullptr;
46     float* dry_wet_mix = nullptr;
47
48     float* input_port = nullptr;
49     float* output_port = nullptr;
50 };
51
52 extern "C" {
53 LV2_SYMBOL_EXPORT const LV2_Descriptor* lv2_descriptor(uint32_t index)
54 {
55     static auto descriptor = make_descriptor<Echo>(Echo::uri);
56     switch (index) {
57         case 0: return &descriptor;
58         default: return nullptr;
59     }
60 }
61 }

```

---

## example/echo/manifest.ttl

---

```

1 @prefix doap: <http://usefulinc.com/ns/doap#> .
2 @prefix lv2: <http://lv2plug.in/ns/lv2core#> .
3 @prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
4 @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
5 @prefix units: <http://lv2plug.in/ns/extensions/units#> .
6
7 <http://topisani.co/lv2/eda/echo>
8   a lv2:Plugin;
9   lv2:binary <echo.fx> ;
10  doap:name "EDA Echo Demo";
11  doap:license <http://opensource.org/licenses/mit> ;
12  lv2:optionalFeature lv2:hardRTCapable ;
13  lv2:port [
14    a lv2:InputPort ,
15      lv2:ControlPort ;
16    lv2:index 0 ;
17    lv2:minimum 10.0 ;
18    lv2:maximum 96000.0 ;
19    lv2:default 11025.0 ;
20    lv2:symbol "time_samples" ;
21    lv2:name "Time Samples" ;
22  ] , [
23    a lv2:InputPort ,
24      lv2:ControlPort ;
25    lv2:index 1 ;
26    lv2:minimum 0.0 ;
27    lv2:maximum 1.0 ;
28    lv2:default 0.9 ;
29    lv2:symbol "filter_a" ;
30    lv2:name "Filter A" ;
31  ] , [
32    a lv2:InputPort ,
33      lv2:ControlPort ;
34    lv2:index 2 ;
35    lv2:minimum 0.0 ;
36    lv2:maximum 1.0 ;
37    lv2:default 0.5 ;

```

```

38     lv2:symbol "feedback" ;
39     lv2:name "Feedback" ;
40 ], [
41     a lv2:InputPort ,
42       lv2:ControlPort ;
43     lv2:index 3 ;
44     lv2:minimum 0.0 ;
45     lv2:maximum 1.0 ;
46     lv2:default 0.5 ;
47     lv2:symbol "dry_wet_mix" ;
48     lv2:name "Dry Wet Mix" ;
49 ], [
50     a lv2:AudioPort ,
51       lv2:InputPort ;
52     lv2:index 4 ;
53     lv2:symbol "in" ;
54     lv2:name "In"
55 ], [
56     a lv2:AudioPort ,
57       lv2:OutputPort ;
58     lv2:index 5 ;
59     lv2:symbol "out" ;
60     lv2:name "Out"
61 ] .

```

## example/tanh/tanh.cpp

```

1  #include <eda/eda.hpp>
2  #include <eda/resampling.hpp>
3
4  #include "../lv2.hpp"
5
6  struct Tanh final : LV2Plugin {
7      constexpr static auto uri = "http://topisani.co/lv2/eda/tanh";
8      Tanh()
9          : process(eda::make_evaluator([this] {
10              using namespace eda;
11              using namespace eda::syntax;
12              const auto sat = _ * ref(gain) | eda::tanh;
13              return resample<4>(sat);
14          }()))
15      {}
16
17      void connect_port(uint32_t port, float* data) override
18      {
19          switch (port) {
20              case 0: gain_port = data; break;
21              case 1: input_port = data; break;
22              case 2: output_port = data; break;
23          }
24      };
25      void run(uint32_t n_samples) override
26      {
27          gain = *gain_port;
28          for (int i = 0; i < n_samples; i++) {
29              output_port[i] = process(input_port[i]);
30          }
31      }
32      float gain = 1.0;
33      eda::DynEvaluator<1, 1> process;
34

```

```

35     float* gain_port = nullptr;
36     float* input_port = nullptr;
37     float* output_port = nullptr;
38 };
39
40 extern "C" {
41 LV2_SYMBOL_EXPORT const LV2_Descriptor* lv2_descriptor(uint32_t index)
42 {
43     static auto descriptor = make_descriptor<Tanh>(Tanh::uri);
44     switch (index) {
45         case 0: return &descriptor;
46         default: return nullptr;
47     }
48 }
49 }

```

---

### example/tanh/manifest.ttl

---

```

1 @prefix doap: <http://usefulinc.com/ns/doap#> .
2 @prefix lv2: <http://lv2plug.in/ns/lv2core#> .
3 @prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
4 @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
5 @prefix units: <http://lv2plug.in/ns/extensions/units#> .
6
7 <http://topisani.co/lv2/eda/tanh>
8   a lv2:Plugin;
9   lv2:binary <tanh.fx> ;
10  doap:name "EDA TANH Demo";
11  doap:license <http://opensource.org/licenses/mit> ;
12  lv2:optionalFeature lv2:hardRTCapable ;
13  lv2:port [
14    a lv2:InputPort ,
15      lv2:ControlPort ;
16    lv2:index 0 ;
17    lv2:minimum 0.0 ;
18    lv2:maximum 10.0 ;
19    lv2:default 1.0 ;
20    lv2:symbol "gain" ;
21    lv2:name "Gain" ;
22  ] , [
23    a lv2:AudioPort ,
24      lv2:InputPort ;
25    lv2:index 1 ;
26    lv2:symbol "in" ;
27    lv2:name "In"
28  ] , [
29    a lv2:AudioPort ,
30      lv2:OutputPort ;
31    lv2:index 2 ;
32    lv2:symbol "out" ;
33    lv2:name "Out"
34  ] .

```

---

### tests/benchmarks.cpp

---

```

1 #include <chrono>
2 #include <iostream>
3 #include <random>
4 #include <ranges>
5
6 #include <catch2/catch_all.hpp>

```

```

7
8 #include "eda/evaluator.hpp"
9 #include "eda/syntax.hpp"
10
11 struct Filter {
12     float eval(float in)
13     {
14         z = z * a + (1 - a) * in;
15         return z;
16     }
17
18     float a = 0.9;
19
20 private:
21     float z = 0;
22 };
23
24 struct Delay {
25     void set_delay(int delay)
26     {
27         delay_ = delay;
28         if (auto old_size = memory_.size(); old_size < delay) {
29             memory_.resize(delay);
30             auto src = memory_.begin() + old_size - 1;
31             auto dst = memory_.begin() + delay - 1;
32             auto n = old_size - index_;
33             for (int i = 0; i < n; i++, src--, dst--) {
34                 *dst = *src;
35                 *src = 0;
36             }
37         }
38     }
39
40     float eval(float in)
41     {
42         float res = memory_[(memory_.size() + index_ - delay_) % memory_.size()];
43         memory_[index_] = in;
44         ++index_;
45         index_ %= static_cast<std::ptrdiff_t>(memory_.size());
46         return res;
47     }
48
49 private:
50     int delay_ = 0;
51     std::size_t index_ = 0;
52     std::vector<float> memory_;
53 };
54
55 struct Echo {
56     float eval(float in)
57     {
58         prev_ = delay_.eval(filter_.eval(prev_) * feedback + in);
59         return prev_;
60     }
61     float feedback;
62     float prev_ = 0;
63     Filter filter_;
64     Delay delay_;
65 };
66
67 struct EchoFX {

```



```

68     float eval(float in)
69     {
70         echo.delay_.set_delay(time_samples);
71         echo.filter_.a = filter_a;
72         echo.feedback = feedback;
73         return echo.eval(in) * dry_wet_mix + in * (1 - dry_wet_mix);
74     }
75     int time_samples = 11025;
76     float filter_a = 0.9;
77     float feedback = 1.0;
78     float dry_wet_mix = 0.5;
79
80 private:
81     Echo echo;
82 };
83
84 void fill_random(std::ranges::range auto& data)
85 {
86     std::random_device rd;
87     std::mt19937 e2(rd());
88     std::uniform_real_distribution<float> dist(-1, 1);
89     std::ranges::generate(data, [&] { return dist(e2); });
90 }
91
92 void benchmark_fx(std::string name, auto fx)
93 {
94     std::array<float, 1024> in = {};
95     fill_random(in);
96     std::array<float, 1024> out = {};
97
98     int iterations = 1000;
99     using clock = std::chrono::high_resolution_clock;
100    clock::duration total_time = clock::duration::zero();
101    for (int i = 0; i < iterations; i++) {
102        const auto iter_start = clock::now();
103        for (int j = 0; j < 1024; j++) {
104            out[j] = fx.eval(in[j]);
105        }
106        const auto iter_end = clock::now();
107        total_time += iter_end - iter_start;
108        // std::cout << i << ": " << (iter_end - iter_start).count() << "ns\n";
109    }
110    std::cout << name << ", " << iterations << " iterations, average: " << (total_time.count() / iterations) <<
111    << "ns\n";
112 }
113
114 TEST_CASE ("Echo benchmark Handwritten C++") {
115     benchmark_fx("Handwritten", EchoFX());
116     float time_samples = 11025;
117     float filter_a = 0.9;
118     float feedback = 1.0;
119     float dry_wet_mix = 0.5;
120     benchmark_fx("EDA", eda::make_evaluator([&] {
121         using namespace eda;
122         using namespace eda::syntax;
123         ABlock<2, 1> auto const filter = (_ << (_, _), _) | (((_ * _, (1 - _) * _) | plus) % _);
124         ABlock<1, 1> auto const echo =
125             (plus | delay(ref(time_samples))) % (filter(ref(filter_a)) * ref(feedback));
126         ABlock<1, 1> auto const process = _ << (echo * ref(dry_wet_mix)) + (_ * (1 - ref(dry_wet_mix)));
127         return process;
128     }()));

```

