# International IƆR Rectifier

IRIS-F6426S

Features

- Oscillator is provided on the monolithic control with adopting On-Chip-Trimming technology.

- Small temperature characteristics variation by adopting a comparator to compensate for temperature on the control part.

- Low start-up circuit current (100uA max)

- Built-in Active Low-Pass Filter for stabilizing the operation in case of light load

- Avalanche energy guaranteed MOSFET with high VDSS

- The built-in power MOSFET simplifies the surge absorption circuit since the MOSFET guarantees the avalanche energy.

- No VDSS de-rating is required.

- Built-in constant voltage drive circuit

- Built-in step drive circuit

- Built-in low frequency PRC mode ($\fallingdotseq$20kHz)

- Various kinds of protection functions

- Pulse-by-pulse Overcurrent Protection (OCP)

- Overvoltage Protection with latch mode (OVP)

- Thermal Shutdown with latch mode (TSD)

INTEGRATED SWITCHER

Package Outline

TO-247 Fullpack (5 Lead)

Key Specifications

| Type	MOSFET VDSS(V)	RDS(ON) MAX	AC input(V)	Pout(W) Note 1
			100±15%	145
IRIS-F6426S	450	0.58 Ω	120±15%	190

Descriptions

IRIS-F6426S is a hybrid IC consists from power MOSFET and a controller IC, designed for Quasi-Resonant (including low frequency PRC) fly-back converter type SMPS (Switching Mode Power Supply) applications. This IC realizes high efficiency, low noise, downsizing and standardizing of a power supply system reducing external components count and simplifying the circuit designs. (Note). PRC is abbreviation of "Pulse Ratio Control" (On-width control with fixed OFF-time).

Typical Connection Diagram

www.irf.com

International
IΩR Rectifier

Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to terminals stated, all currents are defined positive into any lead. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions.

Symbol	Definition	Terminals	Max. Ratings	Units	Note
I_{Dpeak}	Drain Current *1	3-2	16	A	Single Pulse
I_{DMAX}	Maximum switching current *5	3-2	16	A	V_{2-5}=0.78V Ta=-20~+125℃
E_{AS}	Single pulse avalanche energy *2	3-2	327	mJ	Single Pulse $I_{L\,peak}$=6.7A
Vin	Input voltage for control part	4-5	35	V	
Vth	O.C.P/F.B Pin voltage	1-5	6	V	
P_{D1}	Power dissipation for MOSFET *3	3-2	52	W	With infintite heatsink
			2.8	W	Without heatsink
P_{D2}	Power dissipation for control part (Control IC) *4	4-5	0.49	W	Specified by Vin×Iin
T_F	Internal frame temperature in operation	-	-20 ~ +125	℃	Refer to recommended operating temperature
Top	Operating ambient temperature	-	-20 ~ +125	℃	
Tstg	Storage temperature	-	-40 ~ +125	℃	
Tch	Channel temperature	-	150	℃	

*1 Refer to MOS FET A.S.O curve

*2 MOS FET Tch-EAS curve

*3 Refer to MOS FET Ta-PD1 curve

*4 Refer to TF-PD2 curve for Control IC (See page 5)

*5 Maximum switching current.

Fig.1

V_{2-5}

> The maximum switching current is the Drain current determined by the drive voltage of the IC and threshold voltage (Vth) of MOS FET. Therefore, in the event that voltage drop occurs between Pin 2 and Pin 5 due to patterning, the maximum switching current decreases as shown by V_{2-5} in Fig.1 Accordingly please use this device within the decrease value, referring to the derating curve of the maximum switching current.

International **IΩR** Rectifier

Electrical Characteristics (for Control IC)

Electrical characteristics for control part (Ta=25℃, Vin=18V,unless otherwise specified)

Symbol	Definition	Ratings			Units	Test Conditions
		MIN	TYP	MAX		
Vin(ON)	Operation start voltage	14.4	16	17.6	V	Vin=0→17. 6V
Vin(OFF)	Operation stop voltage	9	10	11	V	Vin=17.6→9V
Iin(ON)	Circuit current in operation	-	-	20	mA	-
Iin(OFF)	Circuit current in non-operation	-	-	100	μA	Vin=14V
TOFF(MAX)	Maximum OFF time	45	-	55	μsec	-
Tth(2)	Minimum time for input of quasi resonant signals *6	-	-	1	μsec	-
TOFF(MIN)	Minimum OFF time *7	-	-	2	μsec	-
Vth(1)	O.C.P/F.B Pin threshold voltage 1	0.68	0.73	0.78	V	-
Vth(2)	O.C.P/F.B Pin threshold voltage 2	1.3	1.45	1.6	V	
IOCP/FB	O.C.P/F.B Pin extraction current	1.2	1.35	1.5	mA	-
Vin(OVP)	O.V.P operation voltage	20.5	22.5	24.5	V	Vin=0→24. 5V
Iin(H)	Latch circuit sustaining current *8	-	-	400	μA	Vin=24.5→8. 5V
Vin(La.OFF)	Latch circuit release voltage *8	6.6	-	8.4	V	Vin=24.5→6. 6V
Tj(TSD)	Thermal shutdown operating temperature	140	-	-	℃	

*6 Refer to Recommended operating conditions

*7 The minimum OFF time means TOFF width at the time when the minimum quasi resonant signal is inputted.

*8 The latch circuit means a circuit operated O.V.P and T.S.D.

Electrical Characteristics (for MOSFET)

(Ta=25℃) unless otherwise specified

Symbol	Definition	Ratings			Units	Test Conditions
		MIN	TYP	MAX		
VDSS	Drain-to-Source breakdown voltage	450	-	-	V	ID=300μA / V5-2=0V(short)
IDSS	Drain leakage current	-	-	300	μA	VDS=450V / V5-2=0V(short)
RDS(ON)	On-resistance	-	-	0.58	Ω	V5-2=10V / ID=3.3A
tf	Switching time	-	-	250	nsec	-
θ ch-F	Thermal resistance	-	-	1.1	℃/W	Between channel and internal frame

IRIS-F6426S

IRIS-F6426S
A.S.O. temperature derating coefficient curve

A.S.O. temperature derating coefficient[%] vs. Internal frame temperature TF [℃]

IRIS-F6426S
MOSFET A.S.O. Curve

Drain current limit by ON resistance

0.1ms

1ms

ASO temperature derating shall be made by obtaining ASO Coefficient from the left curve in your use.

Drain Current$_D$[A] vs. Drain-to-Source Voltage V$_{DS}$[V]

IRIS-F6426S
Maximum Switching current derating curve
Ta= -20～+125℃

Maximum Switchng Current I$_{DMAX}$[A] vs. V$_{2-5}$ [V]

IRIS-F6426S
Avalanche energy derating curve

E$_{AS}$ temperature derating coefficient [%] vs. Channel temperature Tch [℃]

www.irf.com

IRIS-F6426S

IRIS-F6426S
MOSFET Ta-PD1 Curve

P_{D1}=52[W]

With infinite
heatsink

Without
heatsink

P_{D1}=2.8[W]

Power dissipation P_{D1}[W]

Ambient temperature Ta[℃]

IRIS-F6426S
MIC TF-PD2 Curve

P_{D2}=0.49[W]

Power dissipation PD2[W]

Internal frame temperature TF[℃]

IRIS-F6426S
Transient thermal resistance curve

Transient thermal resistance θch-c[℃/W]

time t [sec]

www.irf.com

International **I⊠R** Rectifier

Block Diagram

Lead Assignments

Pin No.	Symbol	Description	Function
1	OCP/FB	Overcurrent / Feedback Pin	Input of overcurrent detection signal / constant voltage control signal
2	S	Source Pin	MOSFET source
3	D	Drain Pin	MOSFET drain
4	Vin	Power supply Pin	Input of power supply for control circuit
5	GND	Ground Pin	Ground

Other Functions

O.V.P. – Overvoltage Protection Circuit

T.S.D. – Thermal Shutdown Circuit

STEP DRV – 2 step drive circuit

Case Outline

φ3.2 ±0.2

2±0.2

5.5±0.2

23±0.3

3.3

IRIS

IR

1.35$^{+0.2}_{-0.1}$

1.75$^{+0.2}_{-0.1}$

0.85$^{+0.2}_{-0.1}$

4xP2.54±0.1=(10.16)

5.5±0.2

3.45±0.2

3.35±0.1

3.3±0.5

7±0.5

(4)

R-end

R-end

2-(R1.3)

0.65$^{+0.2}_{-0.1}$

4.5±0.7

15.6±0.2

0.5   0.5

1 2 3 4 5

a : Type Number   F6426S
b : Lot Number
1st letter : The last digit of year
2nd letter : Month
        1 to 9 for Jan. to Sept.,
        O for Oct. N for Nov. D for Dec.
3rd & 4th letter : Day
Arabic Numerals

Weight : Approx. 7.5g
Dimensions in mm
DWG.No. : 4B-E01515A

Material of Pin : Cu
Treatment of Pin : Ni plating + solder dip

Data and specifications subject to change without notice.