



A dedicated kernel named **TORO**

Matias Vara Larsen

FOSDEM'15




Who am I?



- Electronic Engineer from **Universidad Nacional de La Plata, Buenos Aires, Argentina**.
- PhD in Computer Science at **INRIA / CNRS, Nice, France** (finishing in 2015).
- I am the main (and the only ;)) developer of TORO

What is TORO OS?

- TORO OS started in 2003, and in 2004, I released the first stable version.



TORO shell



LS




LS



What is TORO

How we can optimize a **general purpose kernel** for a given purpose?
i.e., **application-oriented**

- TORO OS starts in 2003, released the first stable version.




What is TORO kernel?

- In 2006, the kernel is optimized to run a ***single user application*** in a ***multicore environment***

What is TORO kernel?

- In 2006, the kernel is optimized to run a ***single user application*** in a ***multicore environment***



What is TORO kernel?

- In 2006, the kernel is optimized to run a *single user application* in a *multicore environment*

TORO integrates the user application with the kernel,
and dedicates resources to a given core
e.g., memory, devices and so on


This defines
the architecture
of TORO

Kernel + user application

- Only ring 0
 - The application is compiled with the kernel
 - No syscalls, only calls.
 - Threads instead of process
 - Flat memory, no pagination
 - Light context switching
-
- In this sense, TORO is a ***library OS-like designing***.

Kernel + user application

- Only ring 0
- The application is compiled with the kernel
- No syscalls, only calls.




- Light context switching
- In this sense, TORO is a *library OS-like designing*.

Dedicated Resources

- In a **multicore** system the problematic resource is the ***shared memory***.
- The use of shared memory causes:
 - Overhead in the memory bus.
 - Overhead in the cache to keep it coherent.
 - Overhead in spin locks for mutual exclusion.


Dedicated Resources

- In a **multicore** system the problematic resource is the ***shared memory***.
- The use of shared memory causes:
 - Overhead in the memory bus.
 - Overhead in the cache to keep it coherent.
 - Overhead in spin locks for mutual exclusion.



TORO tries to avoid these problems by keeping all the resources locals, e.g., memory, filesystem

Dedicated Memory Allocation



Dedicated M

This must be provided by a technology like Intel QuickPath or Hypertransport.

Memory space in Toro

Memory Region 1

Memory Region 2

Memory Region 3

TORO Memory allocator


Core1

Core2


Core3




Dedicated Memory Allocation




Dedicated Memory Allocation




Locality of memory




Locality of resources





Locality of resources





Locality of resources



Locality of resources





Locality of resources




Locality of resources

By dedicating resources, TORO avoids the using of Spin locks since there is no acces from others cores.



Current state of project



Thoughts

- The difference between the kernel and application is becoming more thin.
- What is the role of the kernel?
- When/Why we need a kernel?
- When we dedicate a kernel, it becomes simpler.
- TORO represents a compromise between optimization and portability.

Questions?



Thanks!

torokernel.io

matiasevara@gmail.com