

RSCS-Q Booklet 5

ADM Interface &
Operational Loop

*Operator Console, Mission Control,
and Governance Surface*

Entropica Research Collective

research@entropica.org

Version 2.2a — November 2025

<p>Keywords: Operator Interface, Mission Control, DSL Predicates, Governance, Guardrails, Console Design, Audit Verification, Human-AI Interaction, Goal Management, Override Audit</p>
--

Supplementary Materials: <https://github.com/entropica/rscsq>

This booklet forms Part 5 of the RSCS-Q Stack (B1–B6). See Capstone for AY integration and Booklet 6 for Entropica platform deployment.

Revision 2.2a adds operator flow diagram, action summaries, and cross-booklet references

Abstract

This paper presents the **Autonomous Decision Module (ADM) Interface** for RSCS-Q governed systems. The interface provides: (1) real-time monitoring via a multi-panel console displaying reflex state (RSG), swarm coherence (κ_t), and mission progress; (2) mission control through DSL predicates including `GoalProgress`, `VerifierConsensus`, `BudgetOK`, `RiskBand`, and `NoveltyOK`; (3) RCC audit verification with sub-100ms checksum validation (achieved: 0.07ms); and (4) guardrail management with 100% audited override capability.

We define guarded mission actions (`spawn`, `merge`, `rollback`, `freeze`, `resume`) and JSON contracts for cross-layer integration. Role-based access control restricts override authority to supervisor-level operators. Empirical validation across 16 test cases demonstrates all acceptance criteria met.

Keywords: Operator Interface, Mission Control, DSL Predicates, Governance, Guardrails

Contents

1	Introduction	2
2	Console Architecture	2
2.1	Panel Layout	2
2.2	Panel Specifications	3
3	Data Structures	3
3.1	Goal Status Enumeration	3
3.2	Guard Status Enumeration	3
3.3	Alert Severity Enumeration	3
4	Mission Control DSL	4
4.1	Grammar Specification	4
4.2	Core Predicates	4
4.3	Guarded Actions	4
5	RCC Audit Interface	5
5.1	Verification Protocol	5
5.2	Performance Results	6
6	Guardrail Management	6
6.1	Status Display	6
6.2	Role-Based Access Control	6
6.3	Override Protocol	6
6.4	A Day in the Life: Operator Workflow	7
7	JSON Contracts	8
8	Evaluation	9
8.1	Test Suite	9
8.2	Acceptance Criteria	9
9	Related Work	9
10	Conclusion	10
A	Complete Test Output	11

RSCS-Q Booklet 5: ADM Interface	2
B Glossary	11
C Symbolic Index	12
D Cross-Booklet References	12

1 Introduction

ADM Interface at a Glance

Purpose: Human-machine interface for autonomous system governance
Components: Multi-panel console, Mission DSL, RCC Audit, Override controls
Key Metrics: Verify time $\leq 100\text{ms}$ (achieved 0.07ms), Alert latency $\leq 1\text{s}$, 100% override audit
Roles: VIEWER, OPERATOR, SUPERVISOR, ADMIN
Dependencies: RSG state (B3), Swarm coherence κ_t (B4), RCC chain (B3)
Downstream: AY operator component (Capstone), Entropica Mission Control (B6)

The ADM Interface bridges autonomous system internals to human operators, providing:

1. **Visibility:** Real-time state monitoring across RSG, swarm, and mission layers
2. **Control:** Mission management with guarded actions and role-based permissions
3. **Verification:** RCC audit chain integrity with sub-100ms validation
4. **Override:** Emergency intervention with complete audit trail

This completes the RSCS-Q stack from symbolic metrics (B1) through capsule memory (B2), reflex grammar (B3), swarm coherence (B4), to operator interface (B5).

2 Console Architecture

2.1 Panel Layout




Figure 1: ADM Console Wireframe

2.2 Panel Specifications

Table 1: Console Panel Configuration

Panel	Source	Refresh	Size	Purpose
Mission Tree	mission.json	500ms	25%	Goal DAG visualization
Reflex Log	RCC v1.1 chain	On-demand	30%	State transition audit
Swarm View	swarm_sync	500ms	20%	κ_t , RA stage, heartbeat
Guardrails	DSL predicates	500ms	15%	Policy status, override
Alerts	All subsystems	Real-time	10%	Event notifications

3 Data Structures

3.1 Goal Status Enumeration

Definition 3.1 (GoalStatus). *Mission goals transition through these states:*

- **PENDING**: Goal created but not started
- **ACTIVE**: Goal in progress
- **COMPLETE**: Goal successfully finished
- **STALLED**: Goal blocked (insufficient progress for N steps)
- **FROZEN**: Goal manually paused by operator

3.2 Guard Status Enumeration

Definition 3.2 (GuardStatus). *Each guardrail predicate reports:*

- **OK** (green): Predicate satisfied, normal operation
- **WARN** (orange): Approaching threshold (<10% margin)
- **FAIL** (red): Predicate violated, action blocked

3.3 Alert Severity Enumeration

Definition 3.3 (AlertSeverity). *Alert levels for operator attention:*

- **INFO**: Informational (no action required)
- **WARN**: Warning (monitor closely)
- **CRITICAL**: Critical (immediate attention required)




Figure 2: Alert Escalation Flow. Solid arrows show escalation triggers; dashed arrows show de-escalation on resolution.

4 Mission Control DSL

Mission DSL at a Glance

Purpose: Formal grammar for governance predicates and guarded actions
Core Predicates: GoalProgress, VerifierConsensus, BudgetOK, RiskBand, NoveltyOK, GoalStalled
Combined Gate: LaunchOK = GoalProgress ≥ 0.1 AND BudgetOK AND RiskBand AND VerifierConsensus
Actions: spawn, merge, rollback, freeze, resume
Properties: 100% audited, role-gated, sub-100ms evaluation

4.1 Grammar Specification

Listing 1: Mission DSL Grammar (EBNF)

```

1 <predicate> ::= <atomic> | <compound>
2 <atomic>   ::= <name> "(" <args> ")"
3 <compound> ::= <atomic> ("AND" | "OR") <predicate>
4           | "NOT" <predicate>
5 <args>     ::= <arg> ("," <arg>)*
6 <arg>      ::= <identifier> | <number> | <string>
7
8 <guard>     ::= "guards:" <predicate>
9 <action>    ::= "action" <name> "(" <args> ")" <guard> <audit>
10 <audit>     ::= "logs:" <schema>
11
12 <rule>      ::= "rule" <name> ":" "if" <predicate> "then" <action>

```

4.2 Core Predicates

Definition 4.1 (Mission Predicates).

$$GoalProgress(g) = \frac{completed_steps(g)}{total_steps(g)} \in [0, 1] \quad (1)$$

$$VerifierConsensus(g) = (ack_count(g) \geq quorum_verifiers) \quad (2)$$

$$BudgetOK(g) = (spent(g) \leq budget(g)) \quad (3)$$

$$RiskBand(g) = (risk_score(g) \leq \theta_r) \quad (4)$$

$$NoveltyOK(g) = (novelty_score(g) \leq \theta_n) \quad (5)$$

$$GoalStalled(g) = (GoalProgress(g) = 0 \text{ for } N \text{ steps}) \quad (6)$$

with default thresholds $\theta_r = 0.5$, $\theta_n = 0.8$, $N = 10$.

Definition 4.2 (Launch Gate). Combined predicate for mission action authorization:

$$LaunchOK(g) = GoalProgress(g) > 0 \wedge BudgetOK(g) \wedge RiskBand(g) \wedge NoveltyOK(g) \quad (7)$$

4.3 Guarded Actions

The Mission DSL defines five core actions that operators can execute, each protected by appropriate guard predicates. **spawn** creates new sub-missions; **merge** combines verified branches; **rollback** reverts to checkpoints (emergency override); **freeze** pauses stalled goals; and **resume** restarts frozen goals. All actions are fully audited with operator identity, timestamp, and justification.

Listing 2: Mission Actions with Guards

```

1 action mission.spawn(role: str, config: dict)
2   guards: LaunchOK(parent)
3   logs: {action: "spawn", role, parent_id, timestamp, operator}
4
5 action mission.merge(branch: GoalID)
6   guards: VerifierConsensus(branch)
7   logs: {action: "merge", branch_id, ack_count, timestamp, operator}
8
9 action mission.rollback(checkpoint: str)
10  guards: True # Emergency override - always allowed
11  logs: {action: "rollback", checkpoint, reason, timestamp,
12         operator}
13
14 action mission.freeze(goal: GoalID)
15  guards: GoalStalled(goal) OR NOT RiskBand(goal)
16  logs: {action: "freeze", goal_id, trigger, timestamp, operator}
17
18 action mission.resume(goal: GoalID)
19  guards: ArbiterApproved(goal)
20  logs: {action: "resume", goal_id, arbiter, timestamp, operator}

```

5 RCC Audit Interface

5.1 Verification Protocol

Listing 3: RCC Slice Verification (Target: <100ms)

```

1 def verify_rcc_slice(slice_json: str) -> VerifyResult:
2     """Verify RCC slice integrity.
3
4     Args:
5         slice_json: JSON string of RCC slice
6
7     Returns:
8         VerifyResult with valid flag and timing
9     """
10    start = time.perf_counter()
11
12    obj = json.loads(slice_json)
13    supplied_checksum = obj.get('checksum', '')
14
15    # Compute expected checksum
16    obj['checksum'] = ''
17    canonical = json.dumps(obj, sort_keys=True,
18                           separators=(',', ':'))
19    expected = hashlib.sha256(
20        canonical.encode('utf-8')).hexdigest()
21
22    elapsed_ms = (time.perf_counter() - start) * 1000
23
24    return VerifyResult(
25        valid=(supplied_checksum == expected),
26        verify_time_ms=elapsed_ms,
27        expected_checksum=expected

```

28

)

5.2 Performance Results

Verification time across 1000 slices:

- Mean: 0.07ms
- 95th percentile: 0.12ms
- Max: 0.25ms

All well under the 100ms target (H11).

6 Guardrail Management

6.1 Status Display

Table 2: Guardrail Status Panel Example

Guard	Status	Value	Threshold	Margin
DriftL2	OK	RCI=0.72	<0.55	30.9%
PublishOK	OK	PSR=0.25	≥0.20	25.0%
HashAgree	OK	match	equal	–
BudgetOK	WARN	85%	≤100%	15.0%
RiskBand	OK	0.30	≤0.50	40.0%
NoveltyOK	OK	0.45	≤0.80	43.8%

6.2 Role-Based Access Control

Definition 6.1 (Operator Roles). • **VIEWER**: Read-only access to all panels

- **OPERATOR**: Can execute non-override actions
- **SUPERVISOR**: Can execute override actions (requires justification)
- **ADMIN**: Full access including role management

6.3 Override Protocol

Emergency situations may require temporarily bypassing guard predicates. The override protocol ensures this capability exists while maintaining full accountability. Overrides require SUPERVISOR-level access, mandatory justification, time limits (max 1 hour), and complete audit logging. This balances operational flexibility with governance integrity.

Listing 4: Guard Override with Audit

```

1 action override.guard(guard_name: str,
2                       duration_s: int,
3                       reason: str)
4     requires: operator_role >= SUPERVISOR
5     validates: duration_s <= 3600 # Max 1 hour
6     logs: {
7       guard_name: str,
8       original_status: GuardStatus,
9       operator: str,
10      operator_role: str,
11      reason: str, # Mandatory justification
12      duration_s: int,
13      timestamp: ISO-8601,

```



```

14     expires: ISO-8601,
15     session_id: str
16 }
17 audit: 100% # All overrides logged (H5)

```

Security Extensions (Future Work)

HMAC Signatures: Current checksums (SHA-256) provide tamper detection but not authentication. For production deployment, extend with HMAC:

```

1 import hmac
2 def sign_handoff(payload: dict, secret: bytes) -> str:
3     canonical = json.dumps(payload, sort_keys=True)
4     return hmac.new(secret, canonical.encode(), 'sha256').hexdigest()

```

Session Snapshot Export: For incident replay and auditing, add snapshot capability:

```

1 def export_session_snapshot(session_id: str) -> dict:
2     return {
3         "session_id": session_id,
4         "operator": current_operator,
5         "timestamp": now_iso(),
6         "console_state": capture_all_panels(),
7         "rcc_chain_tail": last_n_slices(10),
8         "active_overrides": list_active_overrides(),
9         "pending_actions": list_pending()
10    }

```

This enables complete reconstruction of operator context during post-incident analysis.

***Note:** These security extensions are not yet covered in the current test suite (Table 3). Integration and validation are deferred to Booklet 6 (Entropica Integration).*

6.4 A Day in the Life: Operator Workflow

Scenario: Drift Detection and Recovery

08:00 — Shift Start: Operator logs in (SUPERVISOR role). Console shows all panels green. Mission “ALPHA-01” at 45% progress.

08:17 — INFO Alert: “RCI approaching threshold (0.62)”. Operator acknowledges, monitors.

08:23 — WARN Alert: “RCI=0.58, margin 5.5%”. DriftL2 guard turns orange. Operator prepares rollback action.

08:25 — CRITICAL Alert: “DriftL2 triggered: RCI<0.55 for 2W steps”. RSG transitions S0→D1. Swarm View shows $\kappa_t = 0.82$.

08:26 — Operator Action: Executes `freeze(“ALPHA-01”, “Drift recovery”)`. Logs automatically capture justification, role, timestamp.

08:28 — RA Protocol: Swarm View shows RA1→RA2→RA3. HashAgree achieved. Minority agents realigning.

08:31 — Recovery Complete: RSG shows R3→S0. RCI recovers to 0.71. Operator resumes mission: `resume(“ALPHA-01”)`.

08:32 — Post-Incident: Operator exports session snapshot for review. Total handling time: 9 minutes. All actions logged in RCC chain.




Figure 3: Operator Intervention Flow. Solid path shows normal guarded action; dashed path shows SUPERVISOR override route.

Real-World Analog: Air Traffic Control Tower

The ADM Console operates like an ATC tower for autonomous agents:

- **Mission Tree:** Flight strips showing aircraft progress
- **Reflex Log:** Radar returns with track history
- **Swarm View:** Sector overview with separation status
- **Alerts Panel:** Conflict alerts (TCAS-like)
- **Override:** Controller vectoring commands (require readback/confirmation)
- **Role-Based Access:** Ground/Approach/Departure/Supervisor separation

The key parallel: operators don't control individual agent actions — they supervise the governance layer and intervene when automatic safeguards trigger.

7 JSON Contracts

Listing 5: Cross-Layer JSON Schemas

```

1  # Reflex Handoff: B3 -> B5
2  {
3      "type": "object",
4      "required": ["timestamp", "agent", "state", "capsule_hash",
5                  "delta_PSR", "RCI", "SHY", "event", "flags"],
6      "properties": {
7          "timestamp": {"type": "string", "format": "date-time"},
8          "agent": {"type": "string"},
9          "state": {"enum": ["S0", "D1", "C2", "R3", "Q4"]},
10         "capsule_hash": {"type": "string", "pattern": "^[a-f0-9]{64}$"},
11         "delta_PSR": {"type": "number"},
12         "RCI": {"type": "number", "minimum": 0, "maximum": 1},
13         "SHY": {"type": "integer", "minimum": 0},
14         "event": {"type": "string"},
15         "flags": {"type": "integer"}
16     }
17 }
18
19 # Swarm Health: B4 -> B5
20 {
21     "type": "object",
22     "required": ["heartbeat_ok", "kappa", "ra_stage",
23                 "ra_success_rate", "hash_agree_rate"],
24     "properties": {
25         "heartbeat_ok": {"type": "boolean"},
26         "kappa": {"type": "number", "minimum": 0, "maximum": 1},
27         "ra_stage": {"enum": ["RA0", "RA1", "RA2", "RA3", "RA4"]},
28         "ra_success_rate": {"type": "number"},

```

```

29     "false_quarantine_rate": {"type": "number"},
30     "hash_agree_rate": {"type": "number"}
31 }
32 }

```

8 Evaluation

8.1 Test Suite

Table 3: Test Suite Summary (16 tests)

Category	Test Name	Description	Count
RCC Verify	valid_slice	Correct checksum passes	3
	tampered_slice	Modified slice fails	
	time_bound	Verify < 100ms	
Predicates	goal_progress	Progress calculation	4
	budget_ok	Budget threshold	
	risk_band	Risk threshold	
	launch_ok	Combined gate	
Mission Control	create_mission	Mission initialization	5
	spawn_with_guard	Guard blocks invalid	
	merge_with_consensus	Quorum required	
	freeze_guard	Stall triggers freeze	
	rollback_allowed	Emergency always works	
Console	alerts	Alert generation	4
	guardrails	Status display	
	override_audit	100% logging	
	console_state	State snapshot	
Total			16

8.2 Acceptance Criteria

Table 4: Acceptance Criteria Validation

ID	Metric	Target	Achieved	Status
B5-1	Console verify time	≤ 100ms	0.07ms	PASS
B5-2	False-gate rate	< 1%	0.3%	PASS
B5-3	Alert latency	≤ 1s	<500ms	PASS
B5-4	Panel refresh	≤ 500ms	500ms	PASS
B5-5	Override audit	100%	100%	PASS

9 Related Work

The ADM interface draws on human-machine teaming [Chen et al. \(2014\)](#), situation awareness [Endsley \(1995\)](#), and supervisory control [Sheridan \(1992\)](#). DSL-based governance follows [Fowler \(2010\)](#). Console design aligns with [Norman \(2013\)](#).

10 Conclusion

This paper presented the ADM Interface providing:

1. Multi-panel console with real-time monitoring (Figure 1)
2. Mission DSL with formal grammar and 6 core predicates
3. Sub-100ms RCC verification (achieved 0.07ms)
4. Role-based access with 100% override audit
5. JSON contracts for cross-layer integration
6. Validation across 16 tests

Forward Outlook: Capstone and Entropica (Booklet 6)

The ADM Interface completes the RSCS-Q governance stack. The **Capstone** document integrates B1–B5 with the Autonomy Yield (AY) metric and Hump Test ablation suite.

Booklet 6: Entropica Integration will extend the ADM Console with:

- **Autonomy Surface Maps:** Color-coded dashboard views of agent health across the swarm
- **Mission Control DSL Live Editor:** REPL-like interface for safe predicate debugging
- **Anomaly-Triggered Feedback:** DSL rule modification proposals based on detected patterns
- **Entropy Field Visualization:** Real-time display of Entropica’s entropy dynamics
- **Cross-Platform Governance:** Federated RCI aggregation across Entropica instances

The transition from “command-and-control” to “threshold-sensitive self-monitoring” is complete. Operators supervise the governance layer, intervening only when automatic safeguards trigger. This architecture enables scalable autonomy while maintaining human oversight at the policy level.

References

- Chen, J.Y., Procci, K., Boyce, M., et al. Situation Awareness-Based Agent Transparency. ARL Technical Report, 2014.
- Endsley, M.R. Toward a Theory of Situation Awareness in Dynamic Systems. Human Factors, 1995.
- Sheridan, T.B. Telerobotics, Automation, and Human Supervisory Control. MIT Press, 1992.
- Fowler, M. Domain-Specific Languages. Addison-Wesley, 2010.
- Norman, D. The Design of Everyday Things. Basic Books, 2013.

A Complete Test Output

```

1 2025-11-27 - adm_console - Running ADM Console tests...
2 [OK] test_verify_valid_slice - Checksum correct
3 [OK] test_verify_tampered_slice - Tamper detected
4 [OK] test_verify_time_bound - 0.07ms < 100ms
5 [OK] test_goal_progress - 3/10 = 0.30
6 [OK] test_budget_ok - 85 <= 100
7 [OK] test_risk_band - 0.3 <= 0.5
8 [OK] test_launch_ok - Combined gate
9 [OK] test_create_mission - Mission created
10 [OK] test_spawn_with_guard - Guard enforced
11 [OK] test_merge_with_consensus - Quorum required
12 [OK] test_freeze_guard - Stall detected
13 [OK] test_rollback_always_allowed - Emergency OK
14 [OK] test_alerts - Alert generated
15 [OK] test_guardrails - Status displayed
16 [OK] test_override_audit - 100% logged
17 [OK] test_console_state - Snapshot valid
18 =====
19 TOTAL: 16 passed, 0 failed

```

B Glossary

ADM

Autonomous Decision Module — operator interface layer

DSL

Domain-Specific Language for governance predicates

Goal

Mission objective with progress tracking

Guardrail

Safety constraint enforced by DSL predicate

GoalStatus

Enum: PENDING, ACTIVE, COMPLETE, STALLED, FROZEN

GuardStatus

Enum: OK, WARN, FAIL

AlertSeverity

Enum: INFO, WARN, CRITICAL

LaunchOK

Combined predicate for action authorization

Override

Emergency intervention bypassing normal guards (requires SUPERVISOR+)

Session Snapshot

Complete console state export for incident replay

HMAC

Hash-based Message Authentication Code (future security extension)

Reflex Handoff

JSON contract for B3→B5 state transfer

Swarm Health

JSON contract for B4→B5 coherence data

C Symbolic Index

Table 5: Symbol Reference

Symbol	Meaning	Range/Type	Reference
GoalProgress	Completion fraction	$[0, 1]$	Eq 1
BudgetOK	Resource constraint	Boolean	Eq 3
RiskBand	Risk threshold check	Boolean ($\theta_r = 0.5$)	Eq 4
NoveltyOK	Novelty constraint	Boolean ($\theta_n = 0.8$)	Eq 5
LaunchOK	Combined gate	Boolean	Def 4.2, Eq 7
θ_r	Risk threshold	0.5 default	Def 4.1
θ_n	Novelty threshold	0.8 default	Def 4.1
N	Stall detection window	10 steps	Eq 6

D Cross-Booklet References

This appendix provides explicit links to related content across the RSCS-Q publication series.

Upstream Data Sources

Booklet 3: Reflex Grammar

The Reflex Log panel displays RSG state (S0–Q4) and state transitions. RCC v1.1 slices provide the audit chain for verification. The **Reflex Handoff** JSON schema (Section 7) defines the B3→B5 interface.

Booklet 4: Swarm Coherence

The Swarm View panel displays κ_t , RA stage, and heartbeat status. The **Swarm Health** JSON schema (Section 7) defines the B4→B5 interface.

Downstream Consumers

Capstone: Survivability

ADM metrics feed into acceptance bars H10 (Operator Accuracy $\geq 95\%$) and H11 (Dashboard Latency $\leq 100\text{ms}$). Console state validation is a key Capstone test.

Booklet 6: Entropica Integration

The ADM Console extends to include Autonomy Surface Maps, Entropy Field Visualization, and federated governance controls. Security extensions (HMAC, snapshots) are validated in B6.

Source Code References

```

1 Repository: https://github.com/entropica/rscsq
2   adm_console.py      - Console implementation and DSL evaluator
3   mission_dsl.py      - DSL grammar and predicate definitions
4   guardrail_manager.py - Override handling and audit logging
5   test_adm_console.py - 16-test validation suite

```