



AXS COMPONENT COMPATIBILITY

ELECTRONIC COMPATIBILITY

Choose your Primary Component(s), System Component(s), and the System Controller(s) for a customized bicycle experience. Use the model codes at sram.com/service for more information. Visit the SRAM AXS® app to check for component firmware updates.

PRIMARY COMPONENT

				
DISPLAY	FRONT SUSPENSION	MTB RD	ROAD RD	SEATPOST
EP-ETP-DSP-A1	FS-SIDS-UFA-E1	RD-XX-DHE-A1	RD-RED-E-E1	SP-RVB-AXS-B1
	FS-SIDS-UFA-D1*	RD-XXSL-E-B1	RD-RED-1E-E1	SP-RVB-AXS-A1*
	FS-SID-UFA-D1	RD-XX-E-B1	RD-FRC-E-E1	SP-RVB-XPLR-A1
	FS-PIKE-UFA-C#	RD-X0-E-B1	RD-FRC-1E-E1	
	FS-LYRK-UFA-E1	RD-GX-E-B1	RD-RIV-E-E1	
	FS-LYRK-UFA-D#	RD-S1000-E-A1	RD-RIV-1E-E1	
	FS-ZEB-UFA-B1	RD-XX-1E-A1*	RD-RED-E-D1*	
	FS-ZEB-UFA-A#	RD-X0-1E-A1*	RD-FRC-E-D#*	
		RD-GX-1E-A1*	RD-RIV-E-D1*	
		RD-X-1E-A1	RD-RED1-E-D1*	
		RD-S500-E-B1	RD-FRC-1E-D2	
			RD-RIV1-E-D1	
			RD-APX-1E-D1	

- The Primary Component must be:
- Display in a system with Eagle Powertrain™.
 - Front Suspension in a Flight Attendant™ (FA) system.
 - Rear Derailleur in a system without Flight Attendant or Eagle Powertrain.
 - Seatpost in a Reverb® only AXS system.

SYSTEM COMPONENT

			
CRANKSET SENSOR	REAR SHOCK	ROAD FD	SEATPOST
FC-X0-1FA-C3	RS-SIDL-UFA-A2	FD-RED-E-E1	SP-RVB-AXS-B1
FC-XX-1FA-C3	RS-SIDL-STFA-A2	FD-FRC-E-E1	SP-RVB-AXS-A1*
EP-EAC-FAPS-A1	RS-SIDL-ISFA-A1	FD-RIV-E-E1	SP-RVB-XPLR-A1
FC-XX-SLP-D1	RS-SDLX-UFA-D1	FD-RED-E-D1*	
FC-XX-P-D1	RS-SDLX-UFA-C#	FD-FRC-E-D#*	
FC-X0-P-D1	RS-VIVD-UFA-C1*	FD-RIV-E-D1*	
PM-XX-1-B2	RS-VIVC-UFA-C1*	FD-FRC-EW-D1*	
		FD-FRC-EW-D2	
		FD-RIV-EW-D1	

- The System Component:
- Minimal components required for Flight Attendant include a Flight Attendant suspension fork and a pedaling sensor. A pedaling sensor can be found in a Flight Attendant Pedal Sensor-equipped DUB crankset, a Flight Attendant-compatible Power Meter, or a Flight Attendant-compatible E-Bike. A Flight Attendant rear shock is optional.
 - A Road Front Derailleur can only be used with a 2x compatible Road Rear Derailleur.

SYSTEM CONTROLLER

DROP HANDLEBAR				FLAT HANDLEBAR			
							
LEFT		RIGHT		LEFT		RIGHT	
RIM	EB-RED-D1 4	EB-RED-D1 4		EC-AXS-PODU-D1	EC-AXS-PODU-D1		
	EB-FRC-D1 4	EB-FRC-D1 4		EC-AXS-POD-D1	EC-AXS-POD-D1		
DISC	ED-RED-E1	ED-RED-E1		EC-AXS-PODR-D1	EC-AXS-PODR-D1		
	ED-FRC-E1	ED-FRC-E1		EC-AXS-PODR-C1 3*	EC-AXS-PODR-C1 3*		
	ED-RIV-E1	ED-RIV-E1		EC-AXS-POD-B1 3*	EC-AXS-POD-B1 3*		
	ED-RED-D1 4*	ED-RED-D1 4*		EC-AXS-ROCK-A1 2*	EC-AXS-ROCK-A1 2*		
	ED-FRC-D1 4*	ED-FRC-D1 4*		EC-AXS-RKSX-A1 1	EC-AXS-SRAM-A1 2*		
	ED-FRC-D2*	ED-FRC-D2*			EC-GX-AXS-A1 2		
	ED-RIV-D1*	ED-RIV-D1*					
	ED-APX-D1*	ED-APX-D1*					
AERO HANDLEBAR BLIPBOX™				AEROBAR EXTENSIONS			
ES-EAC-BBOX-D1 4*							
SHIFT BUTTONS				LEFT AND RIGHT EXTENSION			
WIRED BUTTONS				EC-AXS-ZIPP-A1 4*			
ES-EAC-MCLC-A1				EC-VK-AXS-A1 4			
ES-EAC-CLIC-A1				One pair of Clicks™ and one pair of MultiClicks™ are included with the VukaShift™ AXS 90.			
ES-EAC-BLIP-A1							
WIRELESS BUTTON							
EC-BLIP-B1							

- The System Controller:
- Is optional for Flight Attendant. For full AXS builds with a rear derailleur and seatpost, a double button Left Controller is needed for Flight Attendant control.
 - Has no function for Flight Attendant when paired into a system with Eagle Powertrain, Eagle Transmission, and a Reverb AXS seatpost. Flight Attendant Override Mode cannot be activated.
 - Is optional for Eagle Powertrain. AXS Pod Controllers are the only AXS controller that are compatible with Eagle Powertrain.
 - Can provide ANT+ head unit functionality when the RD firmware is 2.46.5 or greater and the AXS App is iOS v 2.13.0 / Android v 2.10.1 or greater.
 - With Drop Handlebars the Wired Shift Buttons are optional for RED D1 and Force D1.
 - At least one pair of Wired Shift Buttons must be used with the BlipBox.
 - Up to 4 pairs of Wireless Blips can be paired into a system. Wireless Blips cannot be used to actuate a seatpost or Flight Attendant.
 -

NOTES:

1. One button only; does not work in an FA system with an AXS seatpost.
 2. Compatible with MatchMaker™ X.
 3. Compatible with Infinity Clamp and MMX Bridge.
 4. Compatible with wired buttons.
- # Numeral may vary, the lower number may be discontinued.
- * Discontinued

SEE NEXT PAGE FOR MECHANICAL COMPATIBILITY

