

ex.l float0.l

float0.l

```
1  /* lex file: float0.l */
2  /* VSCode Extensions Ctrl+Shift+X)+ Flex:Language Support,Highlight*/
3  /* VIEW-Editor LAYOUT-2 Columns Bottom- IN & OUT Files */
4  /* TERMINAL- New Terminal */
5  %%
6  [+ -]?[0-9]*(\.)?[0-9]+    {printf("FLOAT");}
7  %%
8  int main()
9  {
10     yylex();
11     return 0;
12 }
13
```

pascal.pas infloat0.txt ... lesre-pascal.pas outfloat0.txt

infloat0.txt

1
2 ab7.3c--5.4.3+d++5-
3 text-123++++125---24TEXT
4 ---567

outfloat0.txt

1
2 abFLOATc-FLOATFLOAT+d+FLOAT-
3 textFLOAT+++FLOAT--FLOATTEXT
4 --FLOAT

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

1: bash

```
$ flex float0.l
$ gcc lex.yy.c -ll
$ ./a.out <infloat0.txt >outfloat0.txt
$ flex float0.l
$ gcc -o exefloat0.exe lex.yy.c -ll
$ ./exefloat0.exe <infloat0.txt >outfloat0.txt
$
```

More Actions...

1: bash

```
ex.l
1  /* ECRAN - TABEL REGULI + PB + VSCode/Similar */
2  /* Editor LAYOUT-VIEW-2 Columns Bottom- IN & OUT Files */
3  %option main
4  alphabetic [A-Za-z]
5  digit [0-9]
6  alphanumeric ({alphabetic}|{digit})
7  %%
8  for {printf("FOR");}
9  {alphabetic}{alphanumeric}* {printf(" Pascal-id");}
10 \, {printf(" VIRGULA ");}
11 \( {printf(" PARANTEZA stanga ");}
12 \:\= {printf(" ATRIBUIRE ");}
13 %%
14
```

```
pascal.pas
1  program HelloWorld;
2  uses crt;
3  (* comentariu *)
4  begin
5      for i:=1 to 10 do
6          writeln('Hello, World!');
7          a:=5;
8          readkey;
9  end.
10
```

```
iesire-pascal.pas
1  Pascal-id Pascal-id;
2  Pascal-id Pascal-id;
3  PARANTEZA stanga * Pascal-id *)
4  Pascal-id
5      FOR Pascal-id ATRIBUIRE 1 Pascal-id 10 Pascal-id
6          Pascal-id PARANTEZA stanga ' Pascal-id VIRGULA Pascal-id!');
7          Pascal-id ATRIBUIRE 5;
8          Pascal-id;
9  Pascal-id.
10
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

```
$ flex ex.l
$ gcc -o unu.exe lex.yy.c -ll
$ ./unu.exe <pascal.pas >iesire-pascal.pas
$ flex ex.l
$ gcc lex.yy.c -ll
$ ./a.out <pascal.pas >iesire-pascal.pas
$
```

1: bash

≡ ex3.l

```
1  /* CONTORIZARE Linii cod, cuvinte, caractere - Compiler */
2  /* Identifica linii ce incep cu "m"*/
3  /* linii ce se termina cu "com"*/
4  %{
5  | int lnno=0,wordno=0,charno, countcom=0;
6  %}
7  DIGIT [[0-9]]
8  ALPHA [a-zA-Z]
9  word [.* .*\t]
10 eol [\n]
11 reg1 ^m.*\n
12 %%
13 {reg1} {printf ("START m!");ECHO;}
14 {word} {wordno++; charno+=yyleng;}
15 {eol} {charno++;lnno++;wordno++;}
16 ({ALPHA}|{DIGIT})*com$ {countcom++;}
17 . {charno++;}
18 %%
19 //({ALPHA}|{DIGIT})*com$ {countcom++;}
20 //testati regula cu/fara $
21 int main()
22 { yylex(); printf("Nr. de linie= %d\n",lnno);
23   printf("Numar de cuvinte= %d\n",wordno);
24   printf("Nr. caractere= %d\n",charno);
25   printf("Nr.linii termina cu com= %d\n",countcom);
26   return 0;
27 }
```

C inc.c

```
1  #include<stdio.h>
2  main ()
3  { //linie cu com
4    int i,n,fact=1;
5    printf("Enter the number: ");
6    scanf("%d",&n);
7    //input a number
8    /* factorial */
9    for(i=1;i<=n;i++)
10      fact = fact*i;
11    printf("Factorial=%d\n",fact);
12  } //testati regula cu/fara $ com com
13  )
```

≡ outc.txt

≡ outc.txt

```
1  START m!main ()
2  Nr. de linie= 13
3  Numar de cuvinte= 60
4  Nr. caractere= 241
5  Nr.linii termina cu com= 2
6
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

3: bash

```
$ flex ex3.l
$ gcc lex.yy.c -ll
$ ./a.out <inc.c >outc.txt
```