

OpenClaw Memory System: Architecture & Technical Deep Dive

nox-mem v3.7 — March 2026, §5 empirical evaluation added May 2026 (Wave A G5 V3)

Author: Luiz Antonio Busnello (Toto) **Platform:** OpenClaw Autonomous Agent Platform **Infrastructure:** Hostinger KVM4, Tailscale VPN, Debian Linux

Abstract

This paper presents the architecture, implementation, and operational characteristics of nox-mem, a persistent memory system designed for autonomous AI agent fleets. The system provides hybrid search (combining BM25 full-text, semantic vector similarity, and Reciprocal Rank Fusion), an LLM-powered knowledge graph with temporal decay, cross-agent intelligence sharing, and automated consolidation pipelines. Deployed in production since March 14, 2026, the system manages 1,481 memory chunks across 7 databases, 384 knowledge graph entities with 529 relations, and serves 6 specialized AI agents with isolated yet interconnectable memory spaces.

1. Introduction

1.1 Problem Statement

Large Language Model (LLM) agents operating in production environments face a fundamental limitation: context window ephemerality. When a conversation ends or context is compacted, the agent loses accumulated knowledge, decisions, and operational state. For multi-agent systems where specialized agents collaborate on complex tasks, this problem compounds — agents cannot learn from each other's experiences, cannot recall past decisions, and cannot build institutional knowledge over time.

1.2 Design Goals

nox-mem was designed with four core objectives:

1. **Persistent Memory:** Survive context window resets, session boundaries, and agent restarts
2. **Intelligent Retrieval:** Return semantically relevant results, not just keyword matches
3. **Cross-Agent Intelligence:** Enable knowledge sharing across isolated agent workspaces

4. **Operational Autonomy:** Self-maintain through automated consolidation, pruning, and indexing

1.3 Scope

The system operates within the OpenClaw platform, serving 6 AI agents (Nox, Atlas, Boris, Cipher, Forge, Lex) on a single VPS with 4 vCPUs and 8GB RAM. Each agent has a distinct role and memory profile. The workspace (shared memory) and individual agent databases form a federated memory architecture.

2. System Architecture

2.1 Infrastructure Overview

The system runs on a Hostinger KVM4 VPS accessible via Tailscale VPN (IP: 100.87.8.44). Five systemd-managed services provide the runtime environment:

Service	Port	Type	Function
openclaw-gateway	18789	WebSocket	Agent communication gateway
nox-mem-watcher	—	inotifywait	Filesystem event monitor
nox-mem-api	18800	HTTP/JSON	Dashboard data API
ollama	11434	HTTP	Local LLM inference (llama3.2:3b)
tailscaled	—	WireGuard	VPN mesh connectivity

2.2 Database Schema

The primary storage is SQLite 3 with WAL (Write-Ahead Logging) mode for concurrent access. The schema (version 3) contains:

Core Tables:

- **chunks** — Memory fragments with full-text indexing
 - `id` (INTEGER PK), `source_file` (TEXT), `chunk_text` (TEXT), `chunk_type` (TEXT)
 - `source_date` (TEXT), `is_consolidated` (INTEGER), `memory_type` (TEXT)
 - `created_at`, `updated_at` (TEXT, ISO 8601)
 - `metadata` (TEXT, JSON)
- **chunks_fts** — FTS5 virtual table with porter unicode61 tokenizer
 - Content-sync triggers (INSERT, UPDATE, DELETE) maintain index consistency
 - BM25 ranking with configurable column weights (1.0, 0.5, 0.5)
- **consolidated_files** — Processing state tracker
 - `source_file` (TEXT PK), `status` (INTEGER: 0=pending, 1=done, -1=failed)

- **meta** — Key-value configuration store (schema_version, cursors, metrics)

Knowledge Graph Tables:

- **kg_entities** — Named entities with type classification and mention counting
 - UNIQUE constraint on (name, entity_type)
 - TTL tracking via **first_seen**, **last_seen**
- **kg_relations** — Typed relationships between entities
 - Confidence scoring (0.0-1.0) with temporal decay
 - TTL via **expires_at** (90-day default), **last_confirmed**
 - Evidence linking via **evidence_chunk_id**
- **decision_versions** — Architectural decision version history
 - Supersession chain via **is_current** flag and **superseded_at** timestamp

Vector Tables (sqlite-vec):

- **vec_chunks** — Virtual table storing float32 embeddings (3072 dimensions)
- **vec_chunk_map** — Rowid-to-chunk_id mapping (sqlite-vec requires rowid-based access)
- **dedup_log** — Suppressed duplicate tracking for audit

2.3 Chunk Type Taxonomy

Memory chunks are classified into 10 types based on source file path patterns:

Type	Source Pattern	Current Count	Purpose
team	shared/	499	Shared team knowledge, cross-agent docs
daily	memory/YYYY-MM-DD	161	Daily operational notes
other	(default)	126	Unclassified content
decision	memory/decisions.md	34	Architectural and strategic decisions
lesson	memory/lessons.md	21	Errors, corrections, learnings
project	memory/projects.md	11	Active project tracking

Type	Source Pattern	Current Count	Purpose
pending	memory/pending.md	8	Incomplete tasks and blockers
feedback	memory/feedback/	6	User and system feedback
person	memory/people.md	6	People profiles and contacts
digest	memory/digests/	2	Weekly summary reports

2.4 Multi-Agent Memory Architecture

Each of the 6 agents operates with an isolated database at `/root/.openclaw/agents/{name}/tools/nox-mem/1`. The `OPENCLAW_WORKSPACE` environment variable controls path resolution across all modules, enabling the same nox-mem binary to operate on different databases depending on the calling context.

Agent Memory Distribution (as of March 23, 2026):

Agent	Role	Chunks	DB Size	Dominant Type
Nox	Chief of Staff	185	268 KB	daily (91)
Boris	Head of Communications	148	268 KB	team (50)
Forge	Code Reviewer	182	292 KB	daily (135)
Atlas	Research	30	128 KB	other (17)
Cipher	Security	31	132 KB	other (12)
Lex	Legal/Compliance	31	132 KB	other (12)
Workspace	Shared	874	25.2 MB	team (499)

Total system memory: 1,481 chunks across 7 databases.

3. Memory Pipeline

3.1 Ingestion

Files created or modified in monitored directories trigger the inotifywait-based watcher service. The watcher implements:

- **Debounce logic:** 2-second delay to batch rapid successive writes
- **File filtering:** Only `.md` and `.json` files are processed

- **Recursion prevention:** `MEMORY.md` and `SESSION-STATE.md` are excluded to avoid feedback loops
- **Heartbeat:** Touch `/tmp/nox-mem-watcher-heartbeat` on every event for liveness monitoring

Upon trigger, `ingestFile()` executes:

1. Read file content with UTF-8 sanitization (fixes common mojibake patterns for Portuguese text)
2. Detect chunk type from relative file path
3. Extract date from filename pattern (YYYY-MM-DD)
4. Split content into semantic chunks:
 - Markdown: Split on H2/H3 headers, with sub-splitting for chunks exceeding 500 words
 - JSON: Array items become individual chunks; object entries become key-value pairs
 - Small chunks (<20 words) are merged with the previous chunk
5. Delete existing chunks for the same source file (idempotent re-ingestion)
6. Insert new chunks via prepared statement transaction
7. Auto-vectorize if `GEMINI_API_KEY` is available (up to 20 chunks per file)

3.2 Consolidation

Nightly consolidation (23:00, 5-minute stagger across agents) processes daily notes into structured topic files:

1. **Reindex:** Scan all `.md/.json` files in memory directories, rebuild chunk index
2. **Extract:** Use Ollama llama3.2:3b to identify facts, decisions, lessons, and action items from daily notes
3. **Append:** Add extracted content to topic files (`decisions.md`, `lessons.md`, `people.md`, `projects.md`, `pending.md`)
4. **Notion Sync:** Push structured items to “Memoria & Decisoos” Notion database (best-effort, non-blocking)
5. **Git Commit:** Auto-commit memory changes with standardized message format
6. **Session Update:** Refresh `SESSION-STATE.md` with current statistics

3.3 Deduplication

Before insertion, chunks are checked for duplicates using a two-tier strategy:

- **Primary:** Gemini cosine similarity with 0.85 threshold (when embeddings are available)
- **Fallback:** Keyword overlap calculation with 60% threshold
- **Audit:** Suppressed duplicates are logged to `dedup_log` table with reason and preview

4. Hybrid Search System

4.1 Architecture

Search combines three complementary retrieval methods:

Layer 1 — FTS5 BM25 (Keyword)

SQLite FTS5 with porter unicode61 tokenizer provides fast keyword matching. Results are scored using BM25 with column weights (`chunk_text`: 1.0, `source_file`: 0.5, `chunk_type`: 0.5). Post-retrieval boosting applies:

- Type boost: `decision` and `lesson` chunks receive 2.0x multiplier (higher signal-to-noise ratio)
- Recency boost: Chunks from the last 7 days receive 1.5x multiplier

The query sanitizer strips special characters but preserves hyphens for compound terms (e.g., “nox-mem”).

Layer 2 — Gemini Semantic (Vector)

Each chunk is embedded using Google’s `gemini-embedding-001` model (3072 dimensions) with task type `RETRIEVAL_DOCUMENT`. Query embeddings use task type `RETRIEVAL_QUERY` for asymmetric similarity optimization.

Vectors are stored in `sqlite-vec` virtual tables. Retrieval uses cosine distance with a map table (`vec_chunk_map`) bridging `vec_chunks` rowids to `chunks.id` values due to `sqlite-vec`’s rowid-only constraint.

Scoring normalizes distances to a 0-10 scale with type and recency boosting (1.5x and 1.2x respectively, lower than FTS5 to avoid double-boosting in fusion).

Layer 3 — Reciprocal Rank Fusion (RRF)

FTS5 and semantic results are merged using RRF with `k=60`:

$$\text{RRF_score}(d) = \sum 1/(k + \text{rank_i}(d))$$

Documents appearing in both result sets receive combined scores, marked as `match_type: "hybrid"`. Content-prefix deduplication (first 50 characters) prevents near-duplicate results.

4.2 Performance Characteristics

The hybrid approach provides significant quality improvements over single-method search:

Query	FTS5 Only	Hybrid	Analysis
“qual o proximo passo”	0 results	ROADMAP + PHASE-3	Semantic captures intent without keyword match
“nox-mem”	0 results	decisions.md + docs	Vector bypasses tokenizer hyphen issues
“quem e o Toto”	people.md	people.md + TEAM_MEMORY	RRF combines exact match + semantic context

4.3 Cross-Agent Search

The `crossSearch()` function opens all 7 databases in read-only mode, executes FTS5 queries in each, and merges results with agent attribution. Deduplication uses content-prefix comparison to handle shared documents that appear across multiple agent databases.

5. Empirical Evaluation — Wave A G5 V3 (May 2026)

Headline (canonical, 2026-05-19): A8 full stack with active salience reaches **nDCG@10 = 0.6237** on the entity-flavored golden set (n=100), a **+78.8% relative improvement over the G3 baseline (0.3488)** measured prior to Wave A deployment, and **+9.4% over the mid-deployment G4 checkpoint (0.5702)**. The peak ablation isolating `section_boost` alone (A3) reaches 0.6228, recovering **99.85% of the full stack** — section-aware ranking is the dominant driver of the lift.

5.1 Setup

The evaluation uses an entity-flavored golden set of 100 queries (`entity-eval.db`), curated from production usage to exercise the V10 schema’s `section` and `pain` dimensions. Configurations are toggled via environment-variable feature gates (`NOX_SALIENCE_MODE`, `NOX_DISABLE_TIER_BOOST`, `NOX_ENABLE_TIER_BOOST`, `NOX_DISABLE_SECTION_BOOST`, etc.), allowing isolation of individual ranking components without code changes between runs. All measurements occur post-deployment of PRs #150 (salience formula + tier_boost off-by-default), #151 (source_type backfill of 67,949 chunks), and #153 (search wiring). Reported nDCG@10 follows the standard TREC formulation (gain by relevance, log-position discount).

Progression vs prior ablation generations:

Generation	Date	A8 nDCG@10	Δ vs G3 baseline	Notes
G3 baseline (pre-Wave A)	2026-05-15	0.3488	—	Multiplicative salience, tier_boost on, sec- tion_boost only via legacy code path
G4 mid- deployment	2026-05-18	0.5702	+63.5%	Salience aditivo wired but active < shadow puzzle observed
G5 V3 canonical	2026-05-19	0.6237	+78.8%	Wave A fully deployed; reversal active > shadow cravado

The four sub-claims below decompose the +78.8% total into measurable contributions; the full G5 V3 matrix (12 configurations) is archived in `audits/` and `HANDOFF.md` (`#g5-v3-matrix-2026-05-19`).

5.2 Claim 1 — Additive salience outperforms multiplicative

The Wave A formula replaces the legacy multiplicative `salience = recency × pain × importance` with a weighted-additive form (PR #150):

$$\text{salience} = W_IMPORTANCE \cdot \text{importance} + W_RECENCY \cdot \text{recency} + W_PAIN \cdot \text{pain} + W_ACCESS \cdot \text{access_score}$$

$$W_IMPORTANCE = 0.55 \quad W_RECENCY = 0.15 \quad W_PAIN = 0.10 \quad W_ACCESS = 0.20$$

Result. With `NOX_SALIENCE_MODE=active`, A8 reaches 0.6237 vs. 0.6155 with `shadow` (A7) — a +1.3% lift and the reversal of the G4 puzzle, where `shadow` had outranked `active`. The multiplicative form concentrated 99.7% of chunks in the `[0.05, 0.40]` salience range, dominated by 90.67% of chunks at the default `pain = 0.2` and 99.76% of chunks with `recency` `[7, 30]` days; small differences in any factor were swallowed by the product. The additive form exposes each dimension proportionally to its calibrated weight, preserving signal from pain spikes and importance heuristics without requiring all three factors to be simultaneously non-default.

5.3 Claim 2 — `section_boost` is the moat (99.85% of the gain)

Isolating `section_boost` alone (A3 ablation: `section` enabled, `tier` off, `source_type` off, `salience` shadow) yields **nDCG@10 = 0.6228 = 99.85% of A8’s full-stack 0.6237**. The V10 schema multipliers — `compiled` = 2.0, `frontmatter` = 1.5, `timeline` = 0.8, `legacy` = 1.0 — together with the entity-file format introduced in v3.7 (769 entity files × 3 sections 2,307 boost-bearing chunks) explain the majority of the headline improvement.

The negative control A11 (full stack minus `section_boost`) drops to 0.5646, **−9.5% relative to A8**, confirming the contribution is not redundant with semantic embeddings or RRF fusion. This is the architectural pivot the paper’s narrative rests on: section-aware boosting over an entity-file canonical form is the load-bearing component, not the multiplicative salience formula that the v1 paper draft over-emphasized.

5.4 Claim 3 — `tier_boost` off-by-default is the correct calibration

Isolated, `tier_boost` (boost for chunks flagged as `tier='core'`) is actively harmful: A6 (`tier` only, no other boosts) reaches 0.4059, **−21% versus the no-boost baseline 0.5126**. Even integrated into the full stack, A9 (`full` + `tier` enabled) drops to 0.5884, **−5.7% versus A8**. Inspection of the corpus reveals the cause: `tier='core'` chunks account for only 3.96% of the corpus and consist of memory-system internals (lifecycle docs, schema metadata, operational runbooks) rather than user content — over-promoting them displaces directly-relevant entity facts.

PR #150 therefore makes `tier_boost` **off by default** via `NOX_DISABLE_TIER_BOOST=1`, with an explicit `NOX_ENABLE_TIER_BOOST=1` opt-in for callers who want the legacy behavior. The default reflects the calibration this evaluation establishes; the opt-in preserves backward compatibility for downstream pipelines that depend on it.

5.5 Claim 4 — `source_type` backfill recovery

Pre-backfill, **67,949 chunks (98.48% of the corpus)** carried `source_type` = NULL, rendering the `SOURCE_TYPE_BOOST` map inert at search time regardless of the configured multipliers. PR #151 backfills 11 canonical keys (`entity`, `lesson`, `skill`, `project-doc`, `command`, `legal-template`, `personal-doc`, `session`, `note`, `external`, `other`, `ocr-cache`) by classifying each chunk via deterministic path/prefix rules under `withOpAudit()` (`audit_id` = 118), preserving the 1,046 chunks already marked `external` (1.52%). The post-backfill distribution skews to `personal-doc` (32.74%), `skill` (19.89%), and `session` (16.95%), reflecting the lived shape of the operational corpus.

In the G5 V3 matrix, A5 (`source_type` only) and A10 (full minus `source_type`) both score 0.6237 — identical to A8 — confirming the `SOURCE_TYPE_BOOST` map remained **inert by key mismatch**, not by data absence. PR #154

(merged 2026-05-20) updated the boost map to the new keys (calibration ranging from `entity` = 2.0 for high-curation chunks down to `ocr-cache` = 0.7 for low-signal scanned material).

The G8 ablation (2026-05-20, PR #177) re-ingested an isolated `entity-eval-v2.db` (500 chunks) with `source_type` values deterministically remapped to prod-consistent vocabulary (`entity_file` → `entity`, `event_log` → `lesson`, `session_summary` → `session`), achieving 100% key-match with the `SOURCE_TYPE_BOOST` map. Results:

Config	nDCG@10	Δ vs A0	Verdict
A0 (no boosts)	0.4816	baseline	—
A5 (<code>source_type</code> only)	0.4944	+2.66%	LIVE — boost contributes when keys match
A8 (full canonical)	0.5798	+20.4%	full stack
A10 (full minus <code>source_type</code>)	0.5845	+21.4%	<code>source_type</code> <i>removed</i> from full stack

A5 > A0 by +2.66% empirically validates that `SOURCE_TYPE_BOOST` contributes to ranking when `source_type` values match the map keys. However, A8 < A10 by −0.81% reveals **redundant double-boost** when `section_boost` (e.g., `compiled` = 2.0 for entity-file truth sections) and `SOURCE_TYPE_BOOST` (e.g., `entity` = 2.0 for the same chunks) stack on identical chunks, over-promoting at the cost of top-K diversity. Per-category, the redundancy manifests as a −3.5 pp regression on open-domain queries and a +1.4 pp gain on multi-hop.

The **G9 ablation** (2026-05-20, against the prod-flavored `g5.db` 68k corpus, PR planned) **reproduces and amplifies** both findings — at production scale the boost contribution and the redundancy are both **5× larger in magnitude** than in the synthetic G8 set:

Config	G8 (n=500)	G9 (n=68,995)	Δ G9 magnitude vs G8
A0 (no boosts)	0.4816	0.4108	smaller baseline (prod diversity)
A5 (<code>source_type</code> only)	+2.66% vs A0	+14.2% vs A0	5× larger
A8 vs A10 (redundancy)	−0.81%	−2.6%	3× larger

The G9 data **structurally validates** the resolution path of mutual-exclusion logic (PR #182, merged 2026-05-20): when a chunk has `section {compiled, frontmatter, timeline}` populated (entity-file structural metadata), the `source_type_boost` is gated to 0 to prevent stacking on top of `section_boost`. The mutex is rollback-gated via `NOX_DISABLE_MUTEX_SECTION_SOURCE_TYPE=1`.

The **G10 ablation** (2026-05-20, against `g9.db` 69,495 chunks) validates the mutex in production conditions:

Config	nDCG@10	MRR	R@10
A8' (mutex active, default)	0.5478	0.5967	0.6183
A8 (mutex disabled, rollback flag)	0.5435	0.5813	0.6333
Δ mutex effect	+0.79%	+2.65%	−2.4%

The mutex recovers ~46% of the A10 — A8 gap (where A10 fully removes `source_type_boost`) without removing the signal entirely. The per-metric pattern — MRR ↑ (top-1 quality) and R@10 ↓ (diversity) — surfaces a deliberate trade-off: the mutex improves precision at the cost of some recall breadth, with net positive on the weighted nDCG@10.

The **G10b per-category breakdown** (2026-05-21, same DB, $n = 100$ across 5 categories) reveals which query types absorb the trade-off:

Category	n	nDCG@10 Δ%	MRR Δ%	R@10 Δ%	Verdict
single-hop	20	+8.22%	+13.20%	0%	strong win
open-domain	20	+2.42%	+5.56%	0%	win
multi-hop	20	−3.95%	−2.70%	−6.02%	regression
adversarial	20	−2.95%	−5.88%	0%	regression
temporal	20	n/a	n/a	n/a	degenerate corpus gap

The aggregate Δ (+0.43% nDCG, +0.82% MRR) is consistent in direction with the G10 measurement (+0.79% / +2.65%) but attenuated in magnitude — within harness noise at $n = 100$, suggesting the deploy-time figure was on the upper end of a noisy distribution. Substantively: the mutex is a **single-hop optimizer with open-domain side benefits**, balanced against a multi-hop chain-traversal regression of −6.02% R@10. Net retrieval value (+0.0616 nDCG abs gain) exceeds losses (−0.0498 nDCG abs), so the mutex stays deployed; the multi-hop regression is documented as a follow-up candidate for **conditional mutex** (active only when `query_entities = 1`).

The **G11 trim ablation** (2026-05-20, same DB) tested whether trimming the top `SOURCE_TYPE_BOOST` values (`entity: 2.0 → 1.3`, `lesson: 1.8 → 1.2`) could provide additive benefit over the mutex:

Config	nDCG@10	MRR
Canonical (entity=2.0, lesson=1.8)	0.5376	0.5843
Trim (entity=1.3, lesson=1.2)	0.5337	0.5751
Δ	-0.73%	-1.58%

Trim is **rejected**. The mutex already zeroes `sourceTypeDelta` where redundancy occurs (chunks with both `section` and high source-type); the `entity = 2.0` still fires legitimately on legacy non-compiled chunks where the mutex does not trigger, and trimming kills that residual signal. The single-hop category suffered worst (-4.62% nDCG, -7.40% MRR), confirming the mutex resolves redundancy **precisely**, while a global trim over-corrects. The boost stack settles at the canonical configuration: `section_boost` $\times$ `source_type_boost` (`mutex-gated`) $\times$ `additive salience v2`.

The **G10c per-style breakdown** (2026-05-21, same DB, $n = 100$ across 2 styles — the dataset distinguishes `keyword` vs `natural-language` rather than the paraphrase/literal axis the spec anticipated) cuts the same data along a different dimension to test whether mutex behavior is style-conditional:

Style	n	nDCG@10	MRR $\Delta\%$	R@10 $\Delta\%$	Verdict
		$\Delta\%$			
natural-language	50	+1.56%	+3.86%	-1.62%	mutex helps
keyword	50	-0.72%	-2.27%	-1.06%	mutex slightly hurts

The aggregate effect ($+0.43\%$ nDCG, $+0.82\%$ MRR — identical to G10b because G10c reuses the same A8 active vs A8 disabled detail JSONs and re-buckets) is entirely carried by the natural-language subset. The keyword bucket is a small drag, within the noise floor. Two cross-cuts (style $\times$ category) surface as notable outliers: NL $\times$ single-hop ($+13.83\%$ nDCG, $+21.32\%$ MRR — the biggest individual win in the data) and keyword $\times$ adversarial (-5.35% nDCG, -10.0% MRR — the only delta crossing the 5% regression threshold, $n = 10$). Multi-hop suffers -4% across both styles, confirming the regression is **style-agnostic** and motivating the conditional-mutex follow-up rather than a style-specific routing.

Triangulated across G10 (deploy figure $+0.79\%$ / $+2.65\%$), G10b (per-category $+0.43\%$ / $+0.82\%$), and G10c (per-style $+0.43\%$ / $+0.82\%$), the mutex effect is consistent in direction and on the lower end of the original deploy measurement in magnitude — the deploy figure sat on the upper tail of a noisy distribution rather than reflecting a structural shift. The architectural conclusion stands: **keep the mutex deployed at the per-chunk level; address the**

multi-hop chain-traversal regression via a conditional gate keyed on query_entities — executed in G10d below.

The **G10d ablation** (2026-05-21, same `g9.db` corpus, 69 495 chunks, 15 612 `kg_entities`) tests a conditional variant of the Hard Mutex: the per-chunk gate is suppressed when the incoming query matches two or more entities in the KG, preserving the full boost stack for multi-entity chain-traversal queries while keeping the mutex active for single-entity and entity-free queries. The mechanism relies on `query-entity-count.ts`, which performs a greedy longest-match scan over `kg_entities.name` at query time; the count drives `NOX_MUTEX_QUERY_ENTITY_THRESHOLD` in `search.ts`. Four configurations were run against the same 100-query golden set ($n = 100$, 5 categories $\times$ 2 styles $\times$ 10), each on an isolated endpoint (port 18803) with salience active, ~13 min total VPS time:

Config	Description	nDCG@10	MRR	R@10	$\Delta\%$ nDCG vs A8'	$\Delta\%$ MRR vs A8'
A8'	G10 Hard Mutex always- on (prod base- line)	0.5502	0.5992	0.6183	—	—
A8d-1	Conditional, thresh- old=1	0.5467	0.5856	0.6333	−0.64%	−2.27%
A8d-2	Conditional, thresh- old=2	0.5577	0.6074	0.6233	+1.35%	+1.37%
A8 off	Mutex fully dis- abled (con- trol)	0.5438	0.5806	0.6333	−1.17%	−3.10%

The headline result is **A8d-2 (threshold=2) wins on all three primary metrics** over the A8' G10 baseline. A8d-1 regresses on nDCG and MRR, pointing to a critical entity-density effect: with 15 612 entities in `kg_entities` — 40 $\times$ the 402 initially estimated at design time — a threshold of 1 is effectively always met, collapsing the conditional back to the constant-off regime (no mutex). Threshold=2 is the minimum noise filter that restores actual conditionality at current entity density.

The per-category breakdown reveals the mechanism of recovery:

Category	n	nDCG@10 $\Delta\%$ vs A8'	MRR $\Delta\%$ vs A8'	R@10 $\Delta\%$ vs A8'	Verdict
multi-hop	20	+1.58%	0.00%	+3.75%	recovery — chain signal pre- served
adversarial	20	+3.04%	+6.25%	0.00%	recovery — dis- tractor suppres- sion improves
open-domain	20	+2.92%	+1.59%	0.00%	extends G10b win
single-hop	20	−3.26%	−4.43%	0.00%	trade-off
temporal	20	n/a	n/a	n/a	degenerate corpus gap (un- changed)

Multi-hop recovers because queries naming two or more entities (e.g., entity + associated event or related entity) now reach top-K with the full `section_boost` × `source_type_boost` stack active, enabling intermediate chain chunks to surface. Adversarial recovery is the strongest signal: adversarial queries in the golden set tend to mention three or more entity names as distractors, pushing `query_entity_count` 2 and gating the mutex; the full boost stack then differentiates gold from distractors more effectively than the mutex-flattened ranking. The single-hop trade-off is real — A8d-2 nDCG drops −3.26% vs A8' — but is bounded: single-hop performance against the pre-mutex baseline (G10b mutex_disabled) is still **+3.31% nDCG** / **+7.78% MRR** (absolute: 0.5470 vs 0.5295 disabled). The conditional layer trades peak single-hop precision for materially better worst-case behavior across multi-hop and adversarial categories.

Latency is unaffected: P95 spread across all four configs is 2558–2573 ms (0.6% variance), consistent with the `query-entity-count` hot path operating at sub-millisecond cost when the entity index is warmed.

Decision D51 verdict: ACTIVE-T2. A8d-2 meets 6 of 8 evaluated criteria (aggregate nDCG/MRR, multi-hop nDCG/R@10, open-domain nDCG, adversarial nDCG). Single-hop nDCG and MRR are the two fails — both against the

A8' baseline that represents the maximal single-hop state — and both remain strictly positive against the pre-mutex baseline. The aggregate net of +1.35% nDCG / +1.37% MRR over the G10 baseline justifies accepting the single-hop dilution. The canonical boost stack in production now reads: `section_boost × source_type_boost (Hard Mutex gated by query_entity_count 2) × salience v2 additive`.

The G10d conditional gate was deployed to production on 2026-05-21 via systemd environment drop-in (`NOX_MUTEX_QUERY_ENTITY_THRESHOLD=2`). A smoke test across three query archetypes confirmed correct behavior: a single-entity query applied the mutex as expected; a multi-entity query (`count 2`) returned an `entity::compiled` chunk at rank 1, confirming the mutex was suppressed and the full boost stack served the chain; a no-entity query bypassed the mutex entirely. Zero errors were recorded in `journalctl` post-restart. Three rollback paths are documented — disabling only the conditional layer (preserving G10 hard mutex), disabling the entire mutex, and removing the drop-in — each executable in under five minutes.

Triangulated across G10 (+0.79% nDCG deploy measurement), G10b (per-category breakdown, aggregate +0.43%), G10c (per-style breakdown, aggregate +0.43%), and G10d (conditional gate, aggregate +1.35%), the mutex evolution follows a consistent trajectory: the per-chunk hard mutex provided a net positive but introduced multi-hop and adversarial regressions; the conditional layer recovers those regressions at the cost of moderate single-hop dilution, with the aggregate strictly improving at each step. The final deployed configuration is the most balanced across query-category diversity the series has measured.

5.6 Production deployment and observability

The G10d conditional Hard Mutex with `NOX_MUTEX_QUERY_ENTITY_THRESHOLD=2` é a configuração canônica em produção desde 2026-05-21. O drop-in está em `/etc/systemd/system/nox-mem-api.service.d/override.conf`, e três rollback paths permanecem documentados — desabilitar apenas a camada condicional (preservando o G10 hard mutex), desabilitar o mutex inteiro via `NOX_DISABLE_MUTEX_SECTION_SOURCE_TYPE=1`, ou remover o drop-in — cada um executável em menos de cinco minutos. O modo `NOX_SALIENCE_MODE=active` (formulação aditiva v2) também está deployado em produção, consistente com a Claim 1 da §5.2; o modo `shadow` permanece disponível como fallback para A/B comparisons, mas o canonical runtime usa `active`.

A camada de observabilidade F10 (Foundation observability dashboard, decisão D53, 2026-05-21) acompanha os dois deploys em produção. **Phase A** (`/observability/health.html`) expõe três endpoints — `/api/observability/health`, `/api/observability/recent-ops`, `/api/observability/canary-tail` — com polling de 30s sobre status do serviço, últimas operações destrutivas registradas em `ops_audit` (status enum `started` | `success` |

failed | crashed), e o tail das execuções do cron de canary. **Phase B** (/observability/evals.html) consome /api/observability/evals lendo audits/data-G*/, renderizando line charts com Chart.js sobre as séries G3 → G4 → G5 V3 → G8 → G9 → G10 → G10b → G10c → G10d com gate annotations (D43 threshold +15% nDCG@10, D48 close, D51 verdict ACTIVE-T2). Ambas as fases passaram smoke tests no deploy (6/6 e 5/5 respectivamente) e estão acessíveis via Tailscale tunnel; o stack permanece lean (vanilla JS + Chart.js CDN, sem Prometheus/Grafana/time-series DB adicional). A leitura é em tempo real sobre o nox-mem.db canônico — qualquer regressão pós-deploy aparece nos charts dentro do próximo ciclo de polling.

5.7 Honest characterization

The +78.8% headline is decisive for the “Pain-weighted hybrid memory” framing in the sense that pain is one of four additive salience components and the full additive formulation outperforms the legacy multiplicative one. It is **not** decisive for “pain as a standalone retrieval signal in hybrid mode” — that question is addressed in the companion arXiv draft (paper/publication/paper-draft-sec4-7.md §5.5, E10 pain ablation: directional but not significant, $\Delta = +0.0065$, 95% CI $[-0.0143, +0.0338]$, $n = 31$ on the prior R01c-v1.1 corpus). The Wave A measurement validates the architectural choices around section-aware ranking and additive salience composition; per-dimension causal attribution of pain alone awaits the post-PR-#154 ablation generation and a corpus with broader pain distribution than the current 90.67% default.

A G10d evolution further refines the architectural conclusion: the canonical boost stack section_boost × source_type_boost (Hard Mutex gated by query_entity_count 2) × salience v2 additive deployed em 2026-05-21 trata a redundância identificada em G8/G9 sem zerar o sinal completo, e recupera regressões multi-hop (+1.58% nDCG, +3.75% R@10) e adversarial (+3.04% nDCG, +6.25% MRR) ao custo de uma diluição contida em single-hop. A trajetória G3 → G4 → G5 V3 → G8 → G9 → G10 → G10b → G10c → G10d demonstra disciplina de ablation: cada generation isolou um componente ou condição, e cada decision (D43 gate, D48 saga close, D51 ACTIVE-T2) está triangulada por código (PRs #150/#151/#153/#154/#177/#181/#182/#198), audits (audits/data-G*/), e a camada F10 que torna o resultado verificável a qualquer momento em produção.

6. Q4 COMPARISON — Cross-System Benchmarking (Pre-registered)

Status (atualizado 2026-05-24 18h BRT): Pre-registered skeleton populado com o smoke de 20 queries do Sat 2026-05-24 sobre eval-isolated DB (5.882 chunks LoCoMo + 940 chunks Long-

MemEval, k=10), validando a metodologia + confirmando que o pipeline nox-mem funciona end-to-end no eval isolado. **Partial cross-system data adicionado Sat 2026-05-24:** mem0 smoke completo (n=20, 500-chunk corpus cap por cost-control, \$0.10 ingest cost estimado). Tabela §6.3 agora contém 2 linhas reais (nox-mem + mem0). Os 4 adapters restantes (Zep, Letta, agentmemory, EverMind-AI) permanecem [PENDING canonical run] até que o run canônico lande. Princípios (§6.5), anti-cherry-pick (§6.6) e pre-registration (§6.7) são imutáveis post-run conforme §6.7. Ref: [[q4-partial-cross-system-sat-2026-05-24]].

6.1 Methodology summary

A §6 cobre a comparação cross-system entre nox-mem e cinco sistemas competidores de memória persistente para agentes de IA. O execution plan completo está documentado em `specs/2026-05-23-Q4-comparison-execution-plan.md` (pre-registered 2026-05-23, antes do run de Sat 2026-05-24). Os princípios de comparação (§6.5), as garantias anti-cherry-pick (§6.6), e a pre-registration formal (§6.7) são cravados nesta seção antes da execução; somente as tabelas de §6.2/§6.3/§6.4 recebem números após o run. O objetivo é satisfazer o gate D43 (`docs/DECISIONS.md`) — nox-mem em top-3 em 2 das 4 métricas chave (nDCG@10, R@10, MRR, latência) — destravando a GTM Phase 2.

6.2 Competitors

A escolha dos cinco competidores prioriza stars no GitHub, atividade recente de commits e overlap funcional com o escopo do nox-mem. Versões são cravadas pré-execução para reprodutibilidade.

System	Repo	Install path	Version pinned	Default config
Mem0	mem0ai/mem0	<code>pip install mem0ai</code>	[PENDING canonical run - adapter under setup]	OpenAI embeddings + Chroma vector store
Zep	getzep/zep	Docker compose (zep + postgres)	[PENDING canonical run - adapter under setup]	Local self-host mode

System	Repo	Install path	Version pinned	Default config
Letta (ex-MemGPT)	letta-ai/letta	pip install letta	[PENDING canonical run - adapter under setup]	SQLite backend
agentmemory	rohitgo00/agentmemory	runtime	[PENDING canonical run - adapter under setup]	Stack-bridge mode
EverMind-AI	EverOS published bench	repo clone	[PENDING canonical run - adapter under setup]	Native CLI

Cada sistema roda com sua configuração default publicável (princípio §6.5.3): nenhum competidor é tunado adversarialmente.

6.3 Per-system per-dataset results

Tabela canônica cross-system $\times$ cross-dataset. K cutoff fixado em 10 em todos os sistemas; latência medida externamente (wall clock around adapter call); custo derivado dos logs por-sistema (API calls $\times$ pricing publicado).

Sat 2026-05-24 partial cross-system smoke (20 queries combined, dry-run-sample, eval-isolated DB). nox-mem: full corpus (6.822 chunks = 5.882 LoCoMo + 940 LongMemEval). mem0: **500-chunk corpus cap** por cost-control (\$0.10 ingest cost estimado; ~8% do corpus completo). Caveat crítico: os números do mem0 refletem um corpus significativamente menor — interpretação no parágrafo abaixo.

System	n	Corpus chunks	nDCG@10	R@10	MRR	p50 (ms)	avg (ms)	Gold hits
nox-mem	20	6.822 (full)	0.6380	0.5417	0.3700	8	9	13/20 (65%)
mem0 (500-cap)	20	500 (~8%)	0.8569	0.2500	0.1167	273	288	3/20 (15%)

Per-dataset gold-hit breakdown do nox-mem smoke: **LoCoMo 7/10 (70%)** · **LongMemEval 6/10 (60%)**.

Interpretação do trade-off (honestidade obrigatória):

Os dois sistemas exibem perfis opostos. nox-mem, com corpus completo (6.822 chunks, ingest local zero-custo), produz **4× maior hit-rate** (65% vs 15%) e **MRR 3× melhor** (0.37 vs 0.12) — o primeiro hit relevante chega antes em nox-mem. A latência de nox-mem é **30× mais rápida** (8ms p50 vs 273ms p50), reflexo da busca local vs chamadas à API mem0.

mem0, operando sobre apenas 500 chunks (~8% do corpus), exibe **nDCG@10 superior** (0.86 vs 0.64): os poucos hits que retorna tendem a ser top-ranked, produzindo alta concentração de relevância nas primeiras posições. Isso é um artefato de corpus window menor — com janela restrita, o sistema tem menos competição entre resultados candidatos, o que infla o nDCG per-se mas mascara a cobertura real (R@10 = 0.25 vs 0.54). Em produção com corpus completo e mesmo custo de ingest, a relação nDCG pode inverter; o run canônico (corpus uniforme, sem cap) será o árbitro desta hipótese.

Resumo executivo: **nox-mem ganha em cobertura (hits), velocidade (latência), e first-hit quality (MRR). mem0 ganha em concentração de relevância por-resultado (nDCG@10) dentro de uma janela de corpus menor.** Corpus cap de 500 chunks para mem0 é cost-control explícito — \$0.10 estimado vs zero-cost local; dados iguais de corpus revertem parcialmente o nDCG gap.

O smoke não disaggregou nDCG@10 por dataset (combined-only) — desagregação canônica vem no run completo. Os números a seguir são da execução canônica que ainda está em curso.

LongMemEval n=100 (canonical):

System	nDCG@10	R@10	MRR	p50 (ms)	p95 (ms)	p99 (ms)	Cost/query (USD)
nox-mem	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	~\$0.00 (local)
Mem0	[PENDING canonicalrun - full corpus, no 500-cap]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	[PENDING canonicalrun]	~\$0.10+ ingest

System	nDCG@10	R@10	MRR	p50 (ms)	p95 (ms)	p99 (ms)	Cost/query (USD)
Zep	[PENDING canonical run - adapter under setup]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
Letta	[PENDING canonical run - adapter under setup]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
agentment	[PENDING canonical run - adapter under setup]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
EverMind	[PENDING canonical run - adapter under setup]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
AI	[PENDING canonical run - adapter under setup]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]

LoCoMo full (canonical):

System	nDCG@10	R@10	MRR	p50 (ms)	p95 (ms)	p99 (ms)	Cost/query (USD)
nox- mem	[PENDING canonical run]	[PENDING canonical run]	[PENDING canonical run]	[PENDING canonical run]	[PENDING canonical run]	[PENDING canonical run]	~\$0.00 (local)
Mem0	[PENDING canonical run - full corpus, no 500-cap]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	~\$0.10+ ingest

System	nDCG@10	R@10	MRR	p50 (ms)	p95 (ms)	p99 (ms)	Cost/query (USD)
Zep	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
	canonical						
	run -						
	adapter						
	under						
	setup]						
Letta	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
	canonical						
	run -						
	adapter						
	under						
	setup]						
agentmemory	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
	canonical						
	run -						
	adapter						
	under						
	setup]						
EverMind	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
AI	canonical						
	run -						
	adapter						
	under						
	setup]						

Linhas que falharem smoke test (§6.5) são reportadas com nota explícita [FALHA: adapter setup gap] em vez de omitidas, consistente com §6.6. O run canônico atualiza estas tabelas em commit dedicado quando 6/6 adapters estiverem prontos com corpus uniforme (sem cap). Ref: [[q4-partial-cross-system-sat-2026-05-24]].

6.4 Per-category breakdown

Decomposição por categoria de query do LongMemEval. nox-mem reporta as seis categorias canônicas; competidores reportam idem onde a categoria está presente no dataset original.

		nox- mem				EverMind-
Category	n	nDCG@10	Mem0	Zep	Letta	agentmemory AI
single-hop	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
	canonical	canonical	canonical			

Category	nox-mem			EverMind-agentmemory AI			
	n	nDCG@10	Mem0	Zep	Letta		
multi-hop	[PENDING canonical]	[PENDING canonical]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
temporal	[PENDING canonical]	[PENDING canonical]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
adversarial	[PENDING canonical]	[PENDING canonical]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
open-domain	[PENDING canonical]	[PENDING canonical]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]
numeric	[PENDING canonical]	[PENDING canonical]	[PENDING]	[PENDING]	[PENDING]	[PENDING]	[PENDING]

O **smoke de Sat 2026-05-24** não desagregou per-category (combined-only sobre 20 queries), portanto §6.4 inteira aguarda o run canônico de 100 queries $\times$ 2 datasets $\times$ 6 sistemas. Quando uma categoria não tem queries suficientes ($n < 10$) em algum dataset, a célula recebe **n/a** em vez de extrapolação, evitando o tipo de regressão que aparece em §5.5 (temporal **n/a** na G10b por corpus gap degenerado).

6.5 Fair-comparison principles

A comparação obedece a princípios padronizados pela literatura de benchmark publicado (EverMemBench, BEIR, MTEB):

1. **Corpus idêntico.** Todos os sistemas recebem o mesmo `chunks.text` ingerido via a API nativa de cada um. Nenhum sistema recebe versão “otimizada” do corpus.
2. **Eval set idêntico.** Mesmas queries, mesmos gold sets, mesmo random seed (42 para shuffle do LongMemEval).
3. **Defaults nativos por sistema.** Cada competidor roda com sua configuração default publicável. Não tunamos competidores adversarialmente para perder; se default config é o que é publicado, é o que é avaliado.
4. **K cutoff fixo em 10.** Alguns sistemas defaultam para 5 ou 20; todos são forçados a $k=10$ para comparabilidade.
5. **Embeddings provider nativo por sistema.** nox-mem usa Gemini 3072d; cada competidor usa seu provider default. Uma variação **all-Gemini** é planejada como side experiment opcional, deferred porque o smoke de Sat 2026-05-24 consumiu o time-box antes do experiment ([deferred - Sun 2026-05-25 ou follow-up post-launch]).
6. **Hardware uniforme.** Mesmo VPS (Hostinger 8 cores / 16 GB RAM), localhost between systems exceto chamadas a embeddings APIs externas.

Cada adapter passa um smoke test pré-run:

```
result = adapter.search("test query", k=5)
assert len(result) >= 1
assert all('id' in r and 'score' in r for r in result)
```

Adapter que falhar smoke é documentado como gap ([FALHA: <razão>]) em vez de omitido — consistente com §6.6.

6.6 Anti-cherry-pick statement

Para evitar viés de seleção retroativo:

- **Todas as 6 categorias reportadas.** Nenhuma é omitida porque o resultado é desfavorável.
- **Ambos os datasets reportados.** LongMemEval n=100 + LoCoMo full, lado a lado. Não escolhemos o que beneficia.
- **Latência worst-case reportada.** p50 + p95 + p99 explícitos. Não publicamos apenas p50.
- **Per-system per-category transparency.** A tabela de §6.4 expõe cada combinação; não há linha agregada que mascare um padrão.
- **Gaps documentados.** Sistemas que falharem setup recebem nota explícita; a comparação roda sem o sistema faltante, mas o gap é registrado em docs/COMPARISON.md.

6.7 Pre-registration

A metodologia desta seção está cravada no specs/2026-05-23-Q4-comparison-execution-plan.md antes do run de Sat 2026-05-24. O **smoke de Sat 2026-05-24 15h30 BRT** preencheu a primeira linha de §6.3 (nox-mem combined: nDCG@10=0.6380, p50=8ms, gold-hit 13/20 em 20 queries dry-run-sample) e validou que o pipeline de retrieval funciona end-to-end em eval-isolated DB. O **partial cross-system smoke de Sat 2026-05-24 18h BRT** adicionou a linha mem0 (n=20, 500-chunk corpus cap): nDCG@10=0.8569, p50=273ms, gold-hit 3/20 (15%) — com interpretação explícita do trade-off coverage vs concentração em §6.3. O **run canônico** ainda está em curso e atualiza as linhas competidoras [PENDING canonical run] em §6.3 + a totalidade de §6.4 quando os 6 adapters estiverem prontos com corpus uniforme. Princípios (§6.5), anti-cherry-pick (§6.6) e a estrutura geral desta seção são imutáveis post-run. Qualquer ajuste metodológico identificado durante a execução é documentado como follow-up explícito em docs/COMPARISON.md em vez de retroagido aqui. Refs: [[q4-smoke-sat-2026-05-24-real-numbers]] · [[q4-partial-cross-system-sat-2026-05-24]].

A decisão D43 (docs/DECISIONS.md) define o gate de aprovação: nox-mem em top-3 em 2 das 4 métricas chave (nDCG@10, R@10, MRR, latência). Atendido o gate, GTM Phase 2 está destravada conforme docs/ROADMAP.md §7. Não atendido, a sessão de Sun 2026-05-25 produz um plano de remediação (ajustes pre-launch) em vez de launch direto.

7. Limitations and Future Work

7.1 Limitations

L1 — Explicit-ingestion dependency (no zero-shot corpus coverage) `nox-mem` retrieves only what has been explicitly ingested via `ingestFile()`, `ingest-entity`, or the `inotifywait` watcher pipeline. There is no mechanism to answer queries over arbitrary external corpora at query time. This is a deliberate design constraint — the system is optimized for an agent’s *own* accumulated memory, not general-purpose retrieval augmentation — but it means that coverage is bounded by ingestion discipline. A corpus that has never been ingested produces zero recall regardless of query quality. Users bootstrapping the system must explicitly run `nox-mem reindex` over existing files before the hybrid search layer is useful. Ref: `specs/2026-03-14-nox-memory-system-design.md`, ingestion pipeline §3.1.

L2 — Gemini API dependency for embeddings (cost + outbound network) The semantic retrieval layer (Layer 2) depends on Google’s `gemini-embedding-001` model (3072 dimensions). This introduces two constraints: (a) every vectorization call requires outbound network access and a valid `GEMINI_API_KEY`, meaning an air-gapped deployment falls back to FTS5-only retrieval with no semantic recall; (b) API cost scales with corpus size — at the Sat 2026-05-24 corpus of ~69k chunks, a full re-vectorization pass takes approximately 30–40 minutes at quota limits of the free tier. The Autonomy pillar of the Q/A/P strategy explicitly calls out “provider your choice, zero vendor lock-in” as a long-term goal; local embedding substitution (e.g., `nomic-embed-text` via Ollama) is architecturally feasible but not validated against the canonical eval set. BYOK partial autonomy is available: users who supply their own Gemini API key operate without per-query billing exposure in the default free tier. Ref: `docs/DECISIONS.md` (model selection), `[[default-flash-lite-for-agent-infra-tasks]]`.

L3 — Single-instance architecture (no distributed sharding or replication) The system runs on a single SQLite file per agent database. WAL mode provides concurrent read safety, but there is no horizontal sharding, no replication across nodes, and no distributed coordination layer. The current production corpus (69k chunks across 7 databases on a 4-vCPU / 8GB KVM4) operates comfortably within these bounds, but the architecture does not generalize to multi-tenant deployments or corpora significantly exceeding the single-node memory/storage envelope. Distributed SQLite extensions (e.g., `cr-sqlite` CRDT-based replication) exist but are explicitly out of scope for v1. This is a known architectural decision, not an oversight. Ref: `docs/DECISIONS.md` (single-instance rationale).

L4 — No write-side concurrency control (last-writer-wins) Chunk ingestion operates under an optimistic concurrency model: `ingestFile()` deletes existing chunks for the source file and re-inserts in a single transaction, but there is no row-level locking or version fence against concurrent ingest of the same source file from two processes. In practice the inotifywait watcher and manual CLI calls rarely overlap, and the WAL journal prevents data corruption; however, two concurrent ingest calls on the same file produce non-deterministic chunk counts. The `withOpAudit()` wrapper (`src/lib/op-audit.ts`) does not add a mutual-exclusion layer for ingest — it targets destructive bulk operations (reindex, consolidate, crystallize). Production mitigations are operational (systemd service prevents concurrent watcher processes; cron stagger of 5 minutes between agents), not architectural. Ref: `docs/INCIDENTS.md#2026-04-25, [[a1-op-audit-module]]`.

L5 — Evaluation sample size and canonical run gap (n=20 smoke vs n=100 target) The Sat 2026-05-24 cross-system comparison (§6.3) is based on a 20-query smoke over an eval-isolated DB (5,882 LoCoMo + 940 LongMemEval chunks), not the pre-registered canonical 100-query $\times$ 2-dataset $\times$ 6-system run. The canonical run was in progress at the time of this writing (5/6 competitor adapters under setup). All competitive figures for Mem0, Zep, Letta, agentmemory, and EverMind-AI in §6 carry [PENDING canonical run] tags and should not be treated as settled results. The nox-mem smoke figure ($\text{nDCG@10} = 0.6380$ combined, $\text{p50} = 12$ ms) is validated on the methodology but not directly comparable to the G5 V3 entity-eval figure (0.6237) because the eval corpus and query set differ. Ref: `specs/2026-05-23-Q4-comparison-execution-plan.md, [[q4-smoke-sat-2026-05-24-real-numbers]]`.

L6 — Cross-system comparison is methodologically partial Three of five competitors could not be evaluated against the full canonical corpus at the time of writing. Mem0 ran against a 500-chunk corpus cap imposed by cost-control constraints (\$0.10 estimated ingest cost at full corpus), producing a $\text{nDCG@10} = 0.8569$ on 20 queries that cannot be directly compared to nox-mem’s full-corpus score — a smaller, more concentrated corpus tends to inflate nDCG for systems that retrieve all relevant documents. Zep and Letta require Docker compose setups that were in progress. EverMind-AI’s repository was unavailable at time of access. The “concentration vs coverage trade-off” (high nDCG on capped corpus vs recall breadth on full corpus) is a genuine open question for per-system fair comparison, not a methodological failure. Ref: §6.3 anti-cherry-pick statement, `docs/COMPARISON.md, [[q4-partial-cross-system-sat-2026-05-24]]`.

L7 — Latency comparison conflates transport classes The Sat 2026-05-24 latency figures compare nox-mem (local FTS5 + sqlite-vec with Gemini API call for query embedding) against competitor adapters that go over HTTP or

Python SDK to local Docker services. The nox-mem p50 = 12 ms figure reflects localhost UNIX-domain retrieval; the Mem0 p50 = 273 ms reflects a Docker-in-Docker HTTP call. These are not the same transport class. A valid latency comparison requires a normalized transport — either all systems behind the same HTTP gateway, or all measured at the SDK level without network hop differences. The §6 latency figures are reported with this caveat in the per-system notes and should not be interpreted as head-to-head speed claims. Ref: [[q3-latency-numbers-2026-05-18]], docs/PERFORMANCE.md.

L8 — Pain signal is directional but not statistically significant in isolation The “pain-weighted hybrid memory” framing rests primarily on the additive salience formula (§5.2) and section-aware ranking (§5.3). The pain dimension contributes $W_PAIN = 0.10$ of the salience weight, but its isolated causal contribution has not been validated to statistical significance: the E10 pain ablation (paper/publication/paper-draft-sec4-7.md §5.5) reports $\Delta = +0.0065$ with 95% CI $[-0.0143, +0.0338]$ on $n = 31$, directional but not significant. The current production corpus has 90.67% of chunks at the default $pain = 0.2$, providing insufficient variance for a precise estimate. A definitive pain signal ablation requires a corpus where pain scores span the full $[0.1, 1.0]$ range. Ref: §5.7 honest characterization, [[d47-path-c-decision]].

7.2 Future Work

F1 — A2 Tier 3 P5: production-ready encrypted memory (in flight)

Phase 5 of the A2 Tier 3 roadmap targets a full SQLCipher-encrypted memory store with Ed25519-signed audit checkpoints (P4 deployed via PR #294). The signed checkpoint chain enables tamper-evident audit across destructive operations (`reindex`, `consolidate`, `crystallize`) without requiring a central trust authority. P5 closes the Tier 3 arc by integrating encryption key management with the existing `withOpAudit()` wrapper and the Tier 3 reads-audit layer (P3, PR #292/#293). Target deployment: post-GTM Phase 2 launch, estimated Sun 2026-05-25. Ref: specs/2026-05-24-A2-tier3-crypto-audit-RECON.md, docs/A2-TIER3-MIGRATION-RUNBOOK.md, [[a1-op-audit-module]].

F2 — F10 Phase C/D: shadow tracker empirical A/B for ranking changes

F10 Phase A (`/observability/health.html`) and Phase B (`/observability/evals.html`) are deployed (§5.6, decision D53). Phase C targets a shadow-mode query logger that captures production queries, executes them against a candidate ranking config in parallel, and accumulates query-level nDCG deltas before any promotion decision. Phase D operationalizes this into a pre-promotion gate: any ranking change (boost weight adjustment, mutex threshold, salience weight) that has not accumulated 50 shadow queries with $p < 0.05$ improvement is blocked from reaching the production endpoint. This closes the observability gap identified in

[[ship-ranking-changes-in-shadow-mode-first]] — currently the shadow mode is a flag toggle, not an integrated eval pipeline. Ref: docs/ROADMAP.md F10, decision D53, PR #207/#212.

F3 — Per-method benchmark Phase B: cross-method nDCG optimization

The Q4 per-method benchmark (§6, specs/2026-05-21-per-method-benchmark-comparison.md) establishes the cross-system baseline. Phase B targets per-query-type boost calibration: given that keyword queries respond differently from natural-language queries (G10c §5.5), and single-hop vs multi-hop have opposing mutex trade-offs (G10b §5.5), a routing layer that selects ranking parameters based on query-type classification has measurable potential upside. Estimated Lab Q1 item. Ref: specs/2026-05-21-per-method-benchmark-comparison.md, [[g10c-per-style-mutex-2026-05-21]].

F4 — EverMemBench equivalence: honest comparison against EverMind-AI dataset

[[everos-honest-comparison-benchmark-gap]] identifies that EverMind-AI publishes standardized results on EverMemBench (EverCore 83% LongMemEval / 93% LoCoMo; HyperMem 92.73% LongMemEval). Running nox-mem on EverMemBench with the same evaluation protocol closes the benchmark gap and provides a reviewer-grade comparison for the arXiv submission. This is gated on EverMind-AI repository availability (currently unavailable) or an alternative comparable dataset. Estimated Lab Q1 priority if the repository returns. Ref: [[everos-benchmark-publisher-competitor]], [[benchmark-gap-longmemeval-locomo]].

F5 — Neural reranker: cross-encoder rerank post-RRF

The current retrieval stack terminates at RRF fusion (§4.1). A cross-encoder reranker — receiving the top-K RRF candidates and the original query as a pair — is the standard next step in multi-stage retrieval and typically yields +3-8% nDCG@10 over bi-encoder baselines (see e.g., Nogueira & Cho 2019 on MS MARCO). The Autonomy constraint ([[neural-reranker-evolution-vector]]) favors a locally-runnable cross-encoder (e.g., cross-encoder/ms-marco-MiniLM-L-6-v2 via sentence-transformers, ~66MB) over a cloud inference call, keeping the retrieval stack fully offline-capable. Estimated Lab Q1/Q2. Ref: [[neural-reranker-as-vector-evolutivo-pos-rrf]], docs/ROADMAP.md Lab Q1.

F6 — Lab Q1 scale validation: 250k chunk corpus

The current production corpus is 69,495 chunks (as of G10, 2026-05-20). The Lab Q1 roadmap targets a 250k chunk corpus to validate: (a) sqlite-vec ANN recall at scale (current exact-search; approximate search becomes necessary past ~100k vectors at reasonable latency targets); (b) salience formula stability (the recency component decays over a longer history window); (c) FTS5 BM25 IDF calibration (with more documents, rare-term

IDF weights shift). The `[[lab-q1-scale-250k]]` item has no committed spec yet; it is gated on `NOX_SALIENCE_MODE=active` remaining stable through the GTM Phase 2 feedback cycle. Ref: `docs/ROADMAP.md` Lab Q1, `[[q-a-p-pillars-strategic-pivot-2026-05-17]]`.

F7 — Multilingual corpus coverage: Portuguese and Spanish The current evaluation corpus is English-dominant (LongMemEval and LoCoMo are English datasets; the internal entity-eval golden set mixes English and Portuguese). The FTS5 `unicode61` tokenizer with porter stemmer does not stem Portuguese or Spanish tokens correctly (e.g., “decisão” stems to “decisa” rather than “decid-”; Spanish gerunds lose morphological overlap). The Gemini semantic layer partially compensates via cross-lingual embedding space, but there is no explicit multilingual evaluation. A Portuguese golden set is a natural next step given the production operational language of the corpus. This is deferred to post-launch community feedback intake.

F8 — GTM Phase 2 launch and community feedback intake The Q/A/P roadmap (decision `[[qap-pillars-strategic-pivot-2026-05-17]]`) defines GTM Phase 2 as gated on D43 (nox-mem top-3 in 2 of 4 key metrics — `nDCG@10`, `R@10`, `MRR`, latency). The target launch date is Wed 2026-06-03, conditional on the canonical Q4 run completing and D43 passing. Post-launch, community feedback from the OSS release is expected to surface real-world limitation patterns not visible in the synthetic golden sets (e.g., corpora with high image-to-text OCR content, multi-language mixes, or very short memory fragments < 20 words that the current chunker merges). The feedback cycle directly informs Lab Q2 priorities. Ref: `docs/ROADMAP.md` GTM Phase 2, `docs/gtm/`, `[[overnight-automode-push-pattern]]`.

8. Knowledge Graph v2

8.1 Entity Extraction

v1 (Regex-based): Used hardcoded regular expressions for 3 entity types (person, project, agent) with a static alias map for name normalization. Limited to predefined names, producing 26 entities.

v2 (LLM-powered): Uses Ollama llama3.2:3b with a structured extraction prompt. Each chunk is processed with temperature 0.1 for deterministic output. The LLM returns JSON with entities (name + type) and relations (source + relation + target).

Extraction results after processing 866 chunks:

Metric	Regex v1	LLM v2	Improvement
Entities	26	384	14.8x
Relations	59	529	9.0x
Entity Types	3	11	3.7x

Entity Type Distribution:

Type	Count	Description
project	109	Software projects, products, repos
tool	67	Libraries, frameworks, CLI tools
concept	54	Abstract ideas, patterns, methodologies
person	53	Team members, contacts, stakeholders
organization	50	Companies, teams, departments
agent	45	AI agents in the fleet
location	2	Geographic references
other	4	Device, currency, date, computer

8.2 Temporal Decay and TTL

Relations have a 90-day time-to-live (TTL) from creation. The confidence decay mechanism operates as follows:

1. Relations start with confidence 0.8 (extracted) or 0.9 (confirmed)
2. Every 30 days without re-confirmation, confidence drops by 0.1
3. Relations below 0.3 confidence receive accelerated 7-day expiry
4. Expired relations are deleted during **kg-prune** execution
5. Re-confirmation (observing the same relation in new chunks) resets confidence to 0.9 and extends TTL by 90 days

This mechanism ensures the knowledge graph naturally forgets stale information while reinforcing actively observed patterns.

8.3 Decision Versioning

Architectural decisions are tracked with full version history in the **decision_versions** table. Each decision has a unique key (e.g., **dedup-strategy**, **fallback-chain**) and supports:

- Version chains with supersession tracking
- Authorship attribution
- Source file provenance
- Current vs. historical querying

10 decisions are currently tracked, covering API key management, LLM fallback chains, embedding model selection, agent isolation strategy, and synchronization schedules.

8.4 Graph Traversal

The `findPath()` function implements BFS (Breadth-First Search) to discover shortest paths between any two entities. This enables queries like “How is Toto connected to nox-mem?” which traverses `person` → `project` → `tool` → `agent` relationships. Maximum depth is configurable (default: 4 hops).

9. Cross-Agent Intelligence

9.1 Agent Expertise Profiling

Each agent’s memory is analyzed to determine its unique expertise based on chunk type distribution. The dominant chunk type determines the agent’s strength category:

- **daily** → “Daily operations & activity logging”
- **team** → “Team coordination & shared knowledge”
- **decision** → “Decision tracking & rationale”
- **lesson** → “Lessons learned & pattern recognition”

Profiles include chunk counts, type breakdowns, top topics (via FTS5 term frequency), and last activity dates.

9.2 Knowledge Sharing

The `pullInsightsFrom()` function enables any agent to query lessons and decisions from other agents without direct database access. This creates a knowledge transfer mechanism where, for example, Cipher (Security) can learn from Forge’s (Code Reviewer) past code review decisions.

`pullAllInsights()` aggregates insights across all agents, sorted by date, providing a fleet-wide learning feed.

9.3 Cross-Agent Knowledge Graph Merge

`mergeCrossKnowledgeGraphs()` scans all agent databases for `kg_entities` and `kg_relations` tables, merging them into a unified entity view. Entities are matched by type + lowercase name. The output shows which entities are known to which agents and their combined mention counts, enabling identification of shared knowledge vs. agent-specific expertise.

10. MCP Server Interface

nox-mem exposes 14 tools via the Model Context Protocol (MCP) over stdio (JSON-RPC 2.0):

Tool	Category	Description
nox_mem_search	Retrieval	Hybrid search (FTS5 + semantic + RRF)
nox_mem_stats	Monitoring	Database statistics and health
nox_mem_primer	Context	Session recovery summary (~500 tokens)
nox_mem_ingest	Ingestion	Index a file into memory
nox_mem_cross_search	Cross-Agent	Search across all 7 databases
nox_mem_cross_chunk	Cross-Agent	Chunk counts per agent
nox_mem_metrics	Monitoring	Daily observability metrics
nox_mem_kg_build	KG	Build knowledge graph from chunks
nox_mem_kg_query	KG	Query entity and its relations
nox_mem_kg_stats	KG	Knowledge graph statistics
nox_mem_agent_profiles	Intelligence	Agent expertise profiles
nox_mem_cross_kg	Intelligence	Merged cross-agent knowledge graph
nox_mem_kg_path	Intelligence	BFS path between entities
nox_mem_self_analysis	Analysis	Contradiction detection, pattern analysis

11. HTTP API Server

A lightweight HTTP API (Node.js built-in `http` module, zero dependencies) runs on port 18800, exposing memory data to the React dashboard:

Endpoint	Method	Response
/api/health	GET	System health: chunks, consolidation, vector coverage, services, KG stats, DB size
/api/agents	GET	Agent expertise profiles array
/api/kg	GET	Knowledge graph entities and relations
/api/kg/path?from=X&to=Y	GET	BFS shortest path between entities
/api/search?q=QUERY&limit=N	GET	Hybrid search results
/api/cross-kg	GET	Merged cross-agent knowledge graph

CORS headers are set for cross-origin access from the Vercel-hosted dashboard.

12. Operational Infrastructure

12.1 Cron Schedule

24 cron jobs manage automated operations:

Time	Frequency	Job	Details
23:00-23:25	Daily	Agent consolidation	6 agents, 5-min stagger, rein-dex→consolidate
23:30	Daily	Workspace consolidation	Central workspace daily notes
23:35	Daily	Session wrap-up	SESSION-STATE.md, Notion sync, git commit
04:00	Weekly (Sun)	Vectorize	Gemini embeddings for new/changed chunks
* / 5 min	Continuous	Health check	Watcher heartbeat, service liveness
02:00	Daily	SQLite backup	Online backup API, 7-day retention pruning
* / 6 hours	Continuous	Git backup	Auto-commit memory file changes
09:00	Weekly (Mon)	Token check	Forge CC token verification

12.2 Backup Strategy

Three backup mechanisms operate independently:

1. **SQLite Online Backup:** Uses better-sqlite3's backup API for crash-consistent copies. Daily at 02:00, 7-day retention with automatic pruning.
2. **Git Auto-Commit:** Memory directory changes are committed every 6 hours, providing full change history.
3. **File System:** WAL mode ensures database consistency during concurrent reads/writes.

12.3 LLM Fallback Chain

To ensure continuous operation regardless of provider availability:

Paid Tier: Claude Opus → Sonnet → Haiku → GPT-5.1 → Gemini 2.5
Free Tier: Nemotron → Groq Llama70B → Healer → Hunter → Trinity → Gemma27B

The fallback is configured in the environment and selected at runtime based on task complexity and availability.

13. Dashboard Integration

The TotoClaw Command Center (React 18 + TypeScript + Vite + shadcn/ui) provides 11 pages including 4 nox-mem-specific views:

- **Memory Health** (/memory): Real-time system stats, vector coverage progress bar, service status indicators, agent breakdown table
- **Knowledge Graph** (/knowledge-graph): Interactive force-directed canvas graph, entity type filters, BFS path finder
- **Agent Intel** (/agent-intel): Agent expertise cards with type distribution bars, hybrid search interface, cross-agent knowledge entities
- **System Paper** (/system-paper): Live technical analysis with Recharts visualizations (pie, bar, radar, area charts), auto-refresh every 60 seconds

All data is fetched from the nox-mem API server via TanStack React Query with configurable polling intervals.

14. Evolution History

Version	Date	Key Changes
v1.0	Mar 14	SQLite FTS5, basic search, consolidation, Notion sync
v2.0	Mar 17	MCP server, systemd services, watcher heartbeat, primer
v2.2	Mar 20	Cross-agent search, KG v1 (regex), self-improve, decision versioning
v2.5	Mar 22	Multi-agent workspace fix (OPENCLAW_WORKSPACE), gateway supervision
v2.6	Mar 22	Hybrid search default (FTS5+Gemini+RRF), 866/866 vectorized
v3.0	Mar 23	KG v2 (LLM, 384 entities), Cross-Agent Intelligence, HTTP API, dashboard

Version	Date	Key Changes
v3.7	Apr 23	Schema V10 (retention_days v8 + pain v9 + section v10), entity file format, section_boost
Wave A	May 19	Additive salience formula, tier_boost off-by-default, source_type backfill (67,949 chunks), G5 V3 ablation (PRs #150 / #151 / #153)
G10 Hard Mutex	May 20	section source_type mutex deployed against g9.db 69,495 chunks (PRs #181 / #182)
G10d ACTIVE-T2	May 21	Conditional mutex gated by query_entity_count 2 , deployed via systemd drop-in NOX_MUTEX_QUERY_ENTITY_THRESHOLD=2 (PR #198, decision D51); multi-hop +1.58% nDCG / adversarial +3.04% nDCG recovered
F10 Phase A + B	May 21	Foundation observability dashboards (/observability/health.html + /observability/evals.html) deployed via Tailscale tunnel (PRs #207 / #212, decision D53)

15. Conclusion

nox-mem demonstrates that persistent, searchable, and shareable memory for AI agent fleets is achievable with commodity infrastructure (single VPS, SQLite, local LLM). The hybrid search system consistently outperforms single-method retrieval, particularly for multilingual content and compound technical terms. The LLM-powered knowledge graph provides 15x richer entity extraction compared to regex approaches, while temporal decay ensures the graph stays current without manual curation. The Wave A empirical evaluation (§5) cravou $\text{nDCG}@10 = 0.6237$ on the entity-flavored golden set (+78.8% relative over the G3 baseline), with **section_boost** identified as the dominant driver (99.85% of the lift recovered by A3 alone) and the additive salience formula validated by the **active > shadow** reversal. The G10d conditional mutex evolution (§5.5, deployed 2026-05-21) consolida o canonical boost stack **section_boost × source_type_boost** (Hard Mutex gated by **query_entity_count 2**) × **salience v2** additive em produção, recu-

perando regressões multi-hop e adversarial com diluição contida em single-hop. A camada F10 (§5.6, decisão D53) torna o estado de produção verificável a qualquer momento via dashboards Phase A (</observability/health.html>) + Phase B (</observability/evals.html>).

A §6 Q4 COMPARISON está pre-registered (<specs/2026-05-23-Q4-comparison-execution-plan.md>) e o **smoke de Sat 2026-05-24 15h30 BRT** populou a primeira linha de §6.3 com números de nox-mem (nDCG@10=0.6380 combined, p50=12ms, gold-hit 13/20 em 20 queries dry-run-sample sobre eval-isolated DB de 5.882 LoCoMo + 940 LongMemEval chunks). O **run canônico** — 100 queries × 2 datasets × 6 sistemas (Mem0, Zep, Letta, agentmemory, EverMind-AI + nox-mem) — ainda está em execução com 5/6 competidor adapters em setup, e atualiza as células [PENDING canonical run] quando crava. O gate D43 (top-3 em 2 das 4 métricas chave) é avaliado contra o run canônico; o smoke valida a metodologia + confirma que nox-mem retrieval funciona end-to-end, destravando a defesa pre-launch da GTM Phase 2.

The cross-agent intelligence layer transforms isolated agent memories into a collaborative knowledge base, enabling institutional learning across the fleet. Combined with the live dashboard, the system provides full observability into the collective memory of the agent organization.

Repository: github.com/totobusnello/nox-workspace **Dashboard:** github.com/totobusnello/agent-hub-dashboard **Spec:** <Projetos/memoria-nox/specs/2026-03-14-nox-memory-system-design.md>