

**Project No.8**

**Virtual Doctor Chatbot for basic diagnosis**

Presented by

1. Mr.Ronnapat Buranakate      58070503425
2. Miss Rachaya Angkanawin      58070503464

Advisor

Asst. Prof. Santitham Prom-on, Ph.D.

“I’ve read and approved the content of this report”

.....  
(.....)  
Advisor



## **Virtual Doctor Chatbot for basic diagnosis**

Mr.Ronnapat Buranakate

Miss Rachaya Angkanawin

A Project Submitted in Partial Fulfillment of the Requirements  
for the Degree of Bachelor of Engineering  
Department of Computer Engineering, Faculty of Engineering  
King Mongkut's University of Technology Thonburi  
Academic Year 2018

# Virtual Doctor Chatbot for basic diagnosis

Mr.Ronnapat Buranakate

Miss Rachaya Angkanawin

A Project Submitted in Partial Fulfillment of the Requirements  
for the Degree of Bachelor of Engineering  
Department of Computer Engineering, Faculty of Engineering  
King Mongkut's University of Technology Thonburi  
Academic Year 2018

## Project Committee

..... Committee  
(Asst. Prof. Pipat Supasirisun,)

..... Committee  
(Asst. Prof. Nuttanart Facundes, Ph.D.)

..... Committee  
(Assoc. Prof. Peerapon Siripongwutikorn, Ph.D.)

Project Title	Virtual Doctor Chatbot for basic diagnosis
Project Credit	3 credits
Project Participant	Mr.Ronnapat Buranakate Miss Rachaya Angkanawin
Advisor	Asst. Prof. Santitham Prom-on, Ph.D.
Degree of Study	Bachelor's Degree
Department	Computer Engineering
Academic Year	2018

#### Abstract (English)

For our project we intend to create the doctor chatbot. Our chatbot is the system that can interact with the patient similar to real doctor. The chatbot will ask the question to the patient and then using the natural language processing and machine learning to understand the symptoms from the user and diagnosis from these symptoms and show the result of disease which include disease information and basic treatment to the patient. Our chatbot also have the configuration interface for create the conversation flow or intent and also have the interface for training the model which the intelligence of the chatbot will depend on dataset that we have a use for trained in the intent classification model. In the future we will have more conversation to diagnosis more disease for the patient.

หัวข้อโครงการ	ระบบสนทนาโต้ตอบอัตโนมัติแพทย์เสมือนจริงสำหรับการวินิจฉัยโรคเบื้องต้น
หน่วยกิตของโครงการ	3 หน่วยกิต
จัดทำโดย	นายรณภฏ บุรณเขตต์ นางสาวรชยา อังคะนาวัน
อาจารย์ที่ปรึกษา	ผู้ช่วยศาสตราจารย์ ดร.สันติธรรม พรหมอ่อน
ระดับการศึกษา	วิศวกรรมศาสตรบัณฑิต
ภาควิชา	วิศวกรรมคอมพิวเตอร์
ปีการศึกษา	2561

#### บทคัดย่อ

สำหรับโครงการนี้เป็นการสร้างแชทบอทแพทย์เสมือนจริงโดยแชทบอทคือระบบในการถามคำถามจากคนไข้จากนั้นใช้การประมวลผลธรรมชาติ(natural language processing) และการเรียนรู้ของเครื่อง(machine learning) ในการทำความเข้าใจอาการจากคำตอบของคนไข้ เมื่อเก็บข้อมูลจากอาการต่างๆเพียงพอแล้วจึงนำอาการเหล่านั้นมาวินิจฉัยและแสดงผลการวินิจฉัยกลับไปให้คนไข้โดยประกอบไปด้วยข้อมูลของโรคที่วินิจฉัยพร้อมทั้งวิธีการรักษาเบื้องต้นแก่คนไข้ นอกจากนี้แชทบอทจะมีเว็บสำหรับการสร้างบทสนทนาของแชทบอทสำหรับเก็บคำตอบอาการของคนไข้และมีหน้าเว็บสำหรับฝึกโมเดลแชทบอทโดยความฉลาดนั้นขึ้นอยู่กับชุดข้อมูลที่เตรียมไว้สำหรับการฝึกโมเดล ในอนาคตทางผู้จัดทำจะมีการขยายบทสนทนาของแชทบอทเพื่อขยายขอบเขตในการวินิจฉัยโรคแก่คนไข้มากขึ้น

## Table of Contents

	Page
<b>Chapter 1 Introduction</b>	
1.1 Problem Statement and Approach	1
1.2 Objectives	2
1.3 Scope	2
1.4 Tasks and Schedule	3
 <b>Chapter 2 Background, Theory and Related Research</b>	
2.1 Literal Review	
2.1.1.Comparison Application	5
2.1.1.1.DoctorMe Application	5
2.1.1.2.Dr.Meaw Bot	6
2.1.1.3.Mediktor Chatbot Application	7
2.1.2.Related Research	10
2.1.2.1.Chatbots meet Health: automatizing healthcare	10
2.2 Knowledge	11
2.2.1 Getting a patient's information	11
2.2.2 Headache symptom	12
2.2.3 Intent Classification	12
2.3 Technology and Theories	13
2.3.1 Multinomial naïve Bayes	13
2.3.2 Multi-Layer Perceptron	13
2.3.3 Natural Language Processing	14
2.3.4 Term frequency-inverse document frequency(TF-IDF)	14
2.4 Technology and tools	
2.4.1 Javascript	14
2.4.2 Angular 7	14
2.4.3 NodeJs	14
2.4.4 Express	15
2.4.5 Python	15

2.4.6 TFLearn	15
2.4.7 Pythai	15
2.4.8 Jupyter Notebook	15
2.4.9 Cloud Application Platform	15
2.4.10 Database	15
2.4.10.1 MongoDB	16

## **Chapter 3 Design and Methodology**

3.1 Software Specification	17
3.1.1 Feature list	17
3.2 Tools and Materials	18
3.2.1 Hardware	18
3.3 Working process design	18
3.4 Detail of project design	18
3.4.1 Architecture diagram	18
3.4.2 Use case Diagram and Use case narratives	19
3.4.3 User interface Chatbot Design	22
3.4.4 Sequence Diagram	24
3.4.4.1 Chatbot Diagram	24
3.4.4.2 Chatbot Configuration Diagram	26
3.4.5 Chatbot Configuration Interface Design	28
3.4.6 Intent Classification Process	29
3.4.7 Database Design	31

## **Chapter 4 Results and Discussion**

4.1. C-Doctor User Interface	34
4.1.1 Migraine result Conversation flow	35
4.1.2 Tension result Conversation flow	38
4.2 Intent Classification Model of C-Doctor	40
4.3 C-Doctor Intent Configuration platform	45
4.4 Back-end system	48

**Chapter 5 Conclusion**

5.1 Problem encountered	50
5.2 Lesson learn	50
5.3 Future work	50

<b>Reference</b>	52
------------------	----



## List of Figures

page

### **Chapter 1 Introduction**

### **Chapter 2 Background, Theory and Related Research**

Figure 2.1 The interface of Doctorme application	5
Figure 2.2 Information of symptom and the related disease	5
Figure 2.3 Conversation between Dr.Meaw Bot and User	7
Figure 2.4 Conversation between mediktor and user	8
Figure 2.5 The result after predicted the symptoms	9
Figure 2.6 Design of HOLMeS Application	10
Figure 2.7 Ideal interaction between chatbot and user	10
Figure 2.8 Conversation with holmes	11
Figure 2.9 Example for define Intent in user conversation	12
Figure 2.10 Example intent classification	13

### **Chapter 3 Design and Methodology**

Figure 3.1 Architecture design of C-doctor	18
Figure 3.2 Use case of C-Doctor	19
Figure 3.3 Start Chatting with Chatbot	22
Figure 3.4 Chatbot respond message	23
Figure 3.5 Sequence Diagram of chatting	24
Figure 3.6 Symptom Checker Chatbot Diagram	25
Figure 3.7 Create Intent of Chatbot Diagram	26
Figure 3.8 Edit Intent of Chatbot Diagram	26
Figure 3.9 Delete Intent of Chatbot Diagram	27

Figure 3.10 Training Model of Chatbot Diagram	27
Figure 3.11 Create follow-up Intent of Chatbot Diagram	28
Figure 3.12 Build Intent interface	28
Figure 3.13 Setting interface	29
Figure 3.14 Example of list of number after use TF-IDF	30
Figure 3.15 Example of bag of word from AskHeadache Context	30
Figure 3.16 Example of list of number that come from count word in bag of word	30
Figure 3.17 NoSql Data Model Diagram of Chatbot	31

## **Chapter 4 Results and Discussion**

Figure 4.1 Flow conversation of headache diagnosis	34
Figure 4.2 Show chatbot conversation	35
Figure 4.3 Show chatbot asking information from patient	36
Figure 4.4 Show result of migraine	37
Figure 4.5 Show tension conversation flow	38
Figure 4.6 Show result of tension	39
Figure 4.7 The build intent interface with the intent example of headache-level-High intent	45
Figure 4.8 the example of input for set the Context input and Context Output	45
Figure 4.9 the example of training data interface	46
Figure 4.10 the example of response message interface	46
Figure 4.11 the example of parameter interface	47
Figure 4.12 the example of button send api and end conversation	47
Figure 4.13 the interface of training the model	48

Figure 4.14 example of text input from the user 48

Figure 4.15 the prediction of result from the model 49

## List of Tables

	page
<b>Chapter 1 Introduction</b>	
Table 1.1 Table for show task and schedule	3
<b>Chapter 2 Background, Theory and Related Research</b>	
Table 2.1 Comparison of Application	9
<b>Chapter 3 Design and Methodology</b>	
Table 3.1 Comparison of application with C-Doctor	17
Table 3.2 Intent	31
Table 3.3 Parameter	32
Table 3.4 Response Message	32
Table 3.5 User	33
<b>Chapter 4 Results and Discussion</b>	
Table 4.1 result of model from Headahce-Asklevel context	40
Table 4.2 result of model from HeadAche-AskFrequeancy context	40
Table 4.3 result of model from HeadAche-AskSide context	41
Table 4.4 result of model from blank context	41
Table 4.5 result of model from HeadAcheInfo	42
Table 4.6 result of model from HeadAche-Emer context	42
Table 4.7 result of model from HeadAche-familyHistory context	43
Table 4.8 result of model from HeadAche-TueTue context	43
Table 4.9 result of model from HeadAche-AskVomit-followup context	43
Table 4.10 result of model from HeadAche-AskLight context	44

Table 4.11 result of model from HeadAche-AskTubTub context

44

# Chapter 1

## Introduction

### 1.1 Problem Statement and Approach

In commonly, sickness and going to see medic is not what people wants. There are many people don't want to see medic with many reason but when you found you are sick, seeing a medic in both appreciate place and time is important things for you to have the right treatment. Also the type of symptom is important things to determine that patient should meet medic or not. Sometimes people are usually have commonly symptom like fever, sneeze or sore throat and we define that it's common cold. The patient can be treated initially by taking medication which can purchase in drugstore. However, If it does not improve at the time it should do, say that in 2-3 days, it can indicates that you must have to see a medic or if it not the common symptoms for example, hemoptysis you have to going to see a medic immediately because it can't not improve by taking a medication. So, The main problem is how can we know that it serious or not, the lack of knowledge and understand will get bad effect to the symptoms increasingly. Another major problem is nowadays Thai medical staff is still lacking and not enough for the people. From the research found that 80 percent of medical staff have been working more than 24 hours and there are medic who died from work. Because of the bad process management in the hospital and amount of medical staff not suitable to amount of patient affect the process slowly, patient waiting for long time so it cause to patients don't want to see a medic . If we can solve this problem it will benefit for both patient and medic .

So it is motivating our group to find something to solve the problem that people are shy to see medic , give more knowledge about disease and symptoms, make the people more convenient to have diagnosis disease and also solve the overtime woking problem of medic . we want to make something that can act as medic and help the patient similar to medic .

The problem mentioned above, so we have an idea to create something to act as medic , patient Inquiry and basic diseases diagnosis. The technology to help us to achieve the objective is called "chatbot". Chatbot or commonly known as a robot that can talk and response conversation back to the user as a real human which we will using chatbot instead medic to receive necessary information from patient and show basic diseases diagnosis result along with recommendations for treatment of patients.Finally, Our project is in the Benefitting society category.

## 1.2 Objectives

1. To make the chatbot that diagnosis disease from the symptoms and also give the information which including disease information and basic treatment
2. To apply the natural language processing, machine learning combine with the medical diagnosis to develop our project

## 1.3 Scope

### 1. The Chatbot that diagnosis disease from the symptoms of patient

In this system the user can send the message to the chatbot about symptoms. then, the chatbot will analyze the message to find the intent that we trained. When the chatbot understands the intent it will ask the flow of question that we set to receive more information before diagnosis. Finally, the chatbot will send the result to the user which including of disease list from diagnosis, basic treatment information. Moreover, the user can also ask the disease information to the chatbot and it will send back the information and basic treatment of that disease.

### 2. The Chatbot configuration system for develop the chatbot on web interface

In this system is for the developer to config the chatbot on web interface. In the interface we can create the intent for the chatbot which including context input, context out, training data, response message and parameter and it can also training the intent classification model from the interface.

## 1.4 Tasks and Schedule

Table 1.1: Table for show task and schedule

	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	April	May
1) Requirement Analysis										
1.1. Meet advisor	■									
1.2. Requirement document	■	■								
1.3. Background Research	■	■	■							
2) Software Design										
2.1 Design Prototype				■						
2.2 Documentation		■								
2.3. Find and Study tools		■								
2.4 Presentation 1			■							
2.5. Design Chatbot flow			■	■						
3) Implementation										
3.1. Implement web interface for configuration chatbot			■	■	■					
3.2.Implement chatbot diagnose system					■	■				
3.2. Testing code					■	■				
3.3. Presentation 2				■						
4) Integration Testing										
4.1. Integrate All function						■	■			
4.2. Integrate with Bayesian Neural Network						■	■			
4.3.Test Application							■	■		
4.2. Fix bug							■	■		
5) Data Migration and User Testing										
5.1. Fix bug							■	■		





## Chapter 2

### Background, Theory and Related Research

#### 2.1 Literature Review

##### 2.1.1 Comparison Application

###### 2.1.1.1 DoctorMe Application

DoctorMe application is a mobile application that develop by thai people. This app act as the health assistant and diagnose the symptoms which its have a lots of information for diagnose your symptoms. First, when you open the application, the application will separate the human body in each part so you will choose the position of your symptoms and select the symptom that most similar for you and then the information will show up.



Figure 2.1: The interface of Doctorme application[Ref. DoctorMe Application]

Then, the application will show the detail of symptom and the risk level that can be occur with this symptom, it also have advice for each situation for instance if your symptoms is similar like this go to see the medic immediately. In addition, It also show the related disease from your symptoms within detail of the disease, causes of disease and how to treatment yourself.




Figure 2.2: Information of symptom and the relate disease  
[Ref. DoctorMe Application]

### 2.1.1.2 Dr.Meaw Bot

Dr,Meaw Bot is the Chatbot that can give the information of your symptoms and it will advise the situation of your symptoms which level must have to see medic but if the symptoms not risk, the chatbot will give the information for treatment by yourself.





Figure 2.3: Conversation between Dr.Meaw Bot and User[Ref. Dr.Meaw Bot Messenger]

### 2.1.1.3 Mediktor Chatbot Application

Mediktor is the chatbot application that help you to diagnose your symptoms, suggest you about risk of the symptom and give the disease list that relate to your symptoms information.



*Figure 2.4: Conversation between mediktor and user [Ref.Mediktor application]*

When you tell the symptom and the chatbot specific the intent of input it will ask you a question to keep the information and then it will predicted the symptom and show the disease list that can proprability occur with this symptoms. Finally,you can select one in list for more information and the chatbot will tell the risk level within the lists.




Figure 2.5: The result after predicted the symptoms [Ref.Mediktor application]

Table 2.1 Comparison of Application

Comparison	DoctorMe	Dr.Meaw bot	Mediktor chatbot
Platform	Application	Chatbot	Application
View Symtoms Information	✓	✓	✗
Diagnose and giving Symptom information	✗	✗	✓
Treatment information	✓	✓	✓
Offline mode	✓	✗	✗
Language	Thai	Thai	English

## 2.1.2 Related Research

### 2.1.2.1. Chatbots meet eHealth: automatizing healthcare

This research is aim for investigate the effectiveness of novel human-machine interaction paradigms for eHealth application. The example application in this research is called HOLMeS( Health On-Line Medical Suggestions).




Figure 2.6 : Design of HOLMeS Application[9]

The personar of this chatbot is emulate medic in a clinical environment. The main role of the chatbot is collect the general patient information in order and then give the general prevention pathways indicate with different disease.

They want to design the conversation skill to act similar to human behavior to make the patients feel more comfort and can interact with the chatbot like the real human.




Figure 2.7 : Ideal interaction between chatbot and user[9]

So they use IBM Watson Conversation APIs to make the chatbot

understand the natural language processing. The intents and entities(also for context) is the main point of this chatbot dialog to make it good to response user.



Figure 2.8 : Conversation with holmes[9]

In the conclusion, They complete to make the chatbot going over the limitation of interaction between people and chatbot and make the patient feel comfort and natural to talk with

## 2.2 Knowledge

### 2.2.1 Getting a patient's information

Getting a patient's information is an important step for diagnosis because this is the first step of collecting information for treatment and protect wrong diagnosis. So it must be based on the principle of getting information that absolute or Simply referred as "OPQQRST" so, the principles are follow.

- Onset and chronology : Asking the symptoms when it start. How long? The symptoms occur once or ongoing or several times
- Position and radiation : Asking the patient what position of symptoms occur
- Quality : Asking the patient what symptoms looks like.
- Quantification : Asking for the severity of symptoms and does it affect the activity being done?
- Related symptoms : Asking if there are other symptoms associated with it. What are the symptoms?
- Setting : Asking what the patient doing while the symptoms occur, what emotional?, what environment
- Transforming factors : Asking how the symptoms are reduce or increase



### 2.2.2 Headache symptom

Headache is the type of symptom that can found normally in patient which most patient that found with headache symptoms is no harm but some disease is difficult to separate the severe headache.

Recently, There are have rules for diagnose headache symptoms by using International Classification of Headache Disorder which separate in 3 group

- 1.Primary headaches
- 2.Secondary headaches
- 3.painful cranial neuropathies,other headaches

By the way it difficult to confirm disease in primary headache group because sometimes there are similar with secondary headaches so the process will comprehensive 2 part that is

- 1.Find the evidence for secondary headaches
- 2.Separate the group in which type in primary headaches

### 2.2.3 Intent Classification

Intent Classification is one major things that important for the chatbots. It is the one process of NLP(Natural Language Processing) that make your chatbot understand what user want or 'intent' of the input. When the text input from the user is coming to the process it will identified by the function referred to as a "classifier", then it will analyze and provide specific intent of the input from user.

the example of how intent classification make you chatbot more intelligent.

```

User > What is the weather today ?
                                // From the message it is the intent of asking for the
                                weather
                                Intent = Weather
  
```

*Figure 2.9 : Example for define Intent in user conversation*

Now how would it help for the chatbot?, the answer is we can grouping the question and answer to make your chatbot more intelligent For example:

**User Conversation:**

- > how the weather today?
- > can you tell me what the weather today?
- > tell for the weather today
- > weather today
- > today weather
- > what weather today
- > weather
- > what weather

**reply :**the weather today is [INFOMATION]

*Figure 2.10 : Example intent classification*

There are many technology that can develop for this for instance ML(Machine learning), Neural network etc. Finally, the intent classification is the good ways to make the chatbot easily to define the intent without using Rule-based.

## 2.3 Techniques & Theories

### 2.3.1 Multinomial naive Bayes

multinomial naive bayes is a one type of the naive bayes but it is different in distribution each feature from the naive bayes. For the naive bayes model there is calculate the probability that one class have feature  $f_1 \dots f_n$  like this:

$$p(f_1, \dots, f_n | c) = \prod_{i=1}^n p(f_i | c)$$

*Figure 2. : naive bayes equation[10]*

but naive bayes model is not have distribution for each of feature but multinomial naive Bayes is different from the naive Bayes by using multinomial distribution for each feature. So multinomial naive Bayes will be good with classification with independent feature like word count in text. So we will use this one for intent classification in the chatbot.

### 2.3.2 Multi-Layer Perceptron

Multi-Layer Perceptron is the standard of neural network structure which has input layer as the amount of feature , output node that is a result from the input and the between of input and output is hidden layer which have the

function for calculate the output from the previous layer which the hidden layer can be have more than one. It is the one of great supervised machine learning that can change the parameter like weight and bias to make the model more great performance by learning to minimize the error from the previous error which it called Backpropagation step for example at first the data will go to the input layer and then going to the next layer until it reach the output layer then it will be calculate the error value by compare the different from the output result and real result and then it will get the error signal which is using for adjust weight and bias for the next time and it will be do it again N times to minimize the error and get the great result.

### **2.3.3.Natural Language Processing**

Natural Language Processing is the process which using to make the computer understand human language. Natural Language Processing is the important process to make the machine learning can learn the data from the user for example using tokenizer to separate the sentence into list of word to make the machine learning learning the pattern data from the list of word.

### **2.3.4. Term frequency-inverse document frequency(TF-IDF)**

TF-IDF is a one of preprocessing data technique that widely use for prepare the training dataset before training the model.TF-IDF will be using for finding the important word and common word for example the stopword that appear in every sentence is a common word and symptoms word is a important word which mean the word that is important word will be weight as high value and the common word will get low value.So TF-IDF will help to highlight the important word in list of word.

## **2.4.Technology and tools**

### **2.4.1 Javascript**

It is a programming language that using for web develop and also using for web server side and chatbot server.

### **2.4.2 Angular 7**

It is a framework that using html, css and typescript/javascript for develop the front-end website. This framework have great performance for develop the web-platform.

### **2.4.3 NodeJS**

It is javascript runtime that have many useful javascript library by using NPM(Node Package Manager)to install it. It using for server side to

make such as chatbot server and web server.

#### **2.4.4 Express**

It is a NodeJS Framework that make the developer more convenient to develop the server side such as rest-api, manage request and response from the Front-end side.

#### **2.4.5 Python**

Python is an high-level programming language that have many library for training the model for example machine learning library and neural network library.

#### **2.4.6 TFLearn**

It's a neural network library in python which is using for implement the deep neural network layer for the model.

#### **2.4.7 Pythai**

The thai natural language processing library in python which can use for tokenization the sentence into word.

#### **2.4.8 Jupyter Notebook**

Jupyter notebook is the Interactive computing environment that user can coding and then execute the code but the benefit is we can execute in each step(separate the code) so it will support the user to coding and debug easier.

#### **2.4.9 Cloud Application Platform**

Cloud Application Platform is a server on cloud that using for deploy the chatbot on the internet and make it connected with Facebook Messenger

#### **2.4.10 Database**

The Chatbot require for database to store the intent data such as context, response message that using for talking with the user. When the user have talking to the chatbot and when the chatbot analyse the message and find the intent then it will get the intent from the database and use response message from that intent to talk back to the user. Also for training model it will gather the training data from each intent and make the model for intent classification.

##### **2.4.10.1 MongoDB**

MongoDB is a type of open-source document database. It is a NoSQL database. It not use SQL command and not focus on create data relationships but they are the structure that the NoSQL creates and stores. data by JSON (JavaScript Object Notation), which will be stored

as a key and value. The strength is working speed and faster query data, so MongoDB is suitable for our project to save intent of chatbot because this database is appropriate for uncomplicated data and can working well with real time system. Therefore its feature can support our chatbot to more efficiency.

### **Chapter 3**

#### **Design and Methodology**

### 3.1 Software Specification

So we research more about the application about health that related with our project and then we select application to comparison with our project as show in Table 3.1

*Table 3.1 Comparison of application with C-Doctor*

Comparison	DoctorMe	Dr.Meaw bot	Mediktor chatbot	C-Doctor
Platform	Application	Chatbot	Application	Chatbot
View Disease Information	✓	✓	✗	✓
Diagnose symptom	✗	✗	✓	✓
Giving Symptom and Treatment information (after diagnosis)	✓	✓	✓	✓
Offline mode	✓	✗	✗	✗
Language	Thai	Thai	English	Thai

From Table 3.1 we have 3 application that we will comparison with C-Doctor. In the first 2 thai application it doesn't have an Diagnosis the symptoms system so it can't actually help the user to know the associated disease with their symptoms and the last application is not available in Thai so it will difficult to use. So we have motivated to make a chatbot in Thai language that can diagnose the disease from the symptoms with can give the information of the disease and basic treatment and also giving the recommendation from the chatbot. For convenient to using the chatbot we will build it to access with Facebook Messenger.

#### 3.1.1 Feature list

- 1) Communicate with user in Thai language
- 2) View disease's information
- 3) Analyze associated disease and diagnosis
- 4) Giving basic symptom and treatment information after diagnosis

## 3.2 Tools and Materials

### 3.2.1 Hardware

- 1) MacBook Pro (13-inch, 2016, Two Thunderbolt 3 ports)  
 Processor: Intel Core i5 2 GHz  
 Memory: 8 GB 1867 MHz LPDDR3  
 Storage: 256GB  
 Graphics: Intel Iris Graphics 540 1536 MB  
 Operating system: mac OS Sierra Version 10.12.6
- 2) Dell Inspiron 5558  
 Processor: Intel(R) core(TM) i7-5500U CPU @ 2.40GHz  
 Memory: 4 GB  
 Storage: 512 GB  
 Graphics: Intel(R) HD Graphics 5500  
 Operating system: Windows 10 Pro 64 bit

## 3.3 Working process design

1. Research and study about tools, medical diagnosis and Chatbot
2. Design dialogue conversation of the chatbot and design system function
3. Design for Chatbot configuration system web interface
4. Implement the Chatbot configuration system web interface
5. Implement the Chatbot dialogue for diagnosis
6. Integrate with other project (Bayesian Network model)
7. Test System and fix bug
8. Train the chatbot with user
9. Evaluate the result

## 3.4 Detail of project design

### 3.4.1 Architecture diagram




Figure 3.1 : Architecture design of C-doctor

So our major part is separated into 3 part that is input,system process and output.

### Input

- User send the symptom or ask for information of disease to chatbot via facebook messenger

### System Process

- The chatbot will receive text message from Facebook Messenger and send to Intent Classification Process
- Intent Classification Process will using NLP and preprocessing technique for convert the text to the ready pattern data that can predict with the model
- When find the intent of the user then set the context and add the new parameter from intent to user and then respond the message back(ask more question) to the user until the end of flow question
- Show diagnosis result back to the user

### Output

- Diagnosis result that include disease and basic treatment information
- Disease information for the User.

## 3.4.2 Use case Diagram and Use case narratives

### 1) Use case Diagram




Figure 3.2 : Use case of C-Doctor



## 2) Use case narrative

**Title:** Chat

**Actor:** User

**Pre-conditions:** Login to Facebook Messenger

**Post-Condition :** User can interact with the chatbot

**Main success scenario:**

1. Chat with the chatbot by sending the message
2. the system will send text to the server and find the intent and send response message back
3. the user get response message back

**Alternate Flow**

- 1A. The message from the user is not in case of chatbot
- 2A. response the default dialogue back when the chatbot cannot find the intent

**Title:** Symptoms checker & diagnose

**Actor:** User

**Pre-conditions:** Login to Facebook Messenger

**Post-Condition :** User can interact with the chatbot

**Main success scenario:**

1. Chat with the chatbot by send the symptoms or ask for the disease information
2. Response dialogue back from the chatbot and receive result of diagnosis or disease information

**Alternate Flow**

- 1A. The message from the user is not in case of chatbot
- 2A. response the default dialogue back when the chatbot cannot find the intent

**Title:** Ask disease information

**Actor:** User

**Pre-Condition:** Login to Facebook Messenger

**Post-Condition:** User receive the disease information

**Main success scenario:**

1. User enter the message about the disease name
2. System send list of related disease
3. User send the message to select disease
4. User get the disease information

**Alternate Flow**

- 1A. The message from the user is not in case of chatbot
- 2A. response the default dialogue back when the chatbot cannot find the intent
- 3A. Return to primary flow step 1

**Title:** Create Intent

**Actor:** Developer

**Pre-conditions:** -

**Post-Condition :** Developer can create new intent for the chatbot

**Main success scenario:**

1. press the intent button for new intent
2. the system will create new intent and send to the back-end
3. the system save the save new intent to database
4. Developer get result that intent was created

**Title:** Edit Intent

**Actor:** Developer

**Pre-conditions:** -

**Post-Condition :** Developer can edit the intent information

**Main success scenario:**

1. user select the intent
2. user edit the data in intent
3. user press save button
4. the system save the new update to database
5. Developer get success responses

**Title:** Delete Intent

**Actor:** Developer

**Pre-conditions:** -

**Post-Condition :** Developer can delete the intent

**Main success scenario:**

1. Developer press the delete button in that intent
2. the system delete intent and all follow-up intent
3. Developer get success responses

**Title:** Add follow up intent

**Actor:** Developer

**Pre-conditions:** -

**Post-Condition :** Developer can create follow up intent

**Main success scenario:**

1. Developer press the add button on that intent
2. The system will create the new intent and add the intent as the follow-up intent of selected intent
3. Developer get success responses

**Title:** Training Model

**Actor:** Developer


**Pre-conditions:** -

**Post-Condition :** Developer can train model for chatbot

**Main success scenario:**

1. Developer click the train button
2. the system training the model
3. Developer get success response

### 3.4.3 User interface Chatbot Design



*Figure 3.3 : Start Chatting with chatbot*

For the First time using the chatbot user will receive the welcome message from the chatbot about introduce of chatbot and the actually role to make the user understand. Then, you can start chat with the chatbot




Figure 3.4: Chatbot respond message

From figure 3.4 chatbot can responds message by using text or image. The picture that responds to user make C-doctor more interested and cleary.

### 3.4.4. Sequence Diagram

#### 3.4.4.1.Chatbot Diagram

#### Chat Diagram




Figure 3.5: Sequence Diagram of chatting

### Symptom Checker Chatbot Diagram




Figure 3.6 : Symptom Checker Chatbot Diagram

#### 3.4.4.2.Chatbot Configuration Diagram

##### Create Intent of Chatbot Diagram




Figure 3.7 : Create Intent of Chatbot Diagram

### Edit Intent of Chatbot Diagram




Figure 3.8 : Edit Intent of Chatbot Diagram

### Delete Intent of Chatbot Diagram




Figure 3.9 : Delete Intent of Chatbot Diagram

### Training Model of Chatbot Diagram




Figure 3.10 : Training Model of Chatbot Diagram

### Create follow-up Intent of Chatbot Diagram






Figure 3.11 : Create follow-up Intent of Chatbot Diagram

### 3.4.5. Chatbot Configuration Interface Design

The screenshot displays the 'C-DOCTOR' chatbot configuration interface. It is divided into two main sections: 'Chatbot Conversation' and 'Intent Configuration'.

**Chatbot Conversation:** This panel includes a 'BUILD' button, a 'Fallback Message' input field, a 'Welcome Message' input field, and an 'Intent Lists' section. The 'Intent Lists' section shows a list of intents: '-HeadAche', '-HeadAche-emer-yes', '-HeadAche-emer-No', '-HeadAcheinfo', '-Tension Result', '-Migraine Result', '-Greeting', and '-newIntent'. Each intent has a plus sign icon next to it.


**Intent Configuration:** This panel is used to configure a specific intent. It includes a 'Save' button and the following fields:
 

- Intent Name:** A text input field with the value 'newIntent'.
- Context Input:** A text input field with the value 'enter Context'.
- Context Output:** A text input field with the value 'enter Context'.
- Training Data:** A text input field with the value 'Enter Training Data'.
- Response Message:** A section for configuring the response, including a 'Choose Response Message Type' dropdown with 'TEXT' and 'IMAGE' options.
- Parameter:** A table with two columns: 'Variable' and 'Value'. It has two rows: 'Enter Variable' and 'Enter Value'.
- Settings:** Two checkboxes at the bottom: 'Set the intent to send the parameter to the API' and 'Set the intent to end of conversation'.

Figure 3.12 : Build Intent interface

For this interface the action that user can use is create an intent of the chatbot. First, when press the plus sign button to create the new intent then, name the new intent, set the context, put the training text that will analyse in machine learning, set the responses message or picture of that intent and set the parameters of the intent. Finally user can set intent to send the parameter to the API and set the intent to end of conversation at

the button in the last of page. In addition, the user can make the fallback intent that the intent is use for if the message doesn't match any other intent and the welcome intent for the beginning using the chatbot. The user can create sub intent which called follow intent by press to the follow button to create the follow up intent.



*Figure3.13 : setting interface*

For this interface it can be press the train button for training the model for each intent separated by context input when click the button it will be loading until the training model is success.

### **3.4.6.Intent Classification Process**

We will use natural language processing to make the chatbot understand the input from user by tokenizing and use TF-IDF and Bag of word technique for prepare the data before training. Then we have separate 2 experiment for learning the training data of intent which is multinomial naive-bayes and deep neural network. For the training data of the intent that using for training the model we have group the intent by using context input so each context of intent will have one model for intent classification.

### **TF-IDF & Multinomial Naive-Bayes Classification**



we put 2 hidden layer for the neural network so it will be called deep neural network and then train the model with sentence and intent.

### 3.4.7. Database Design

#### NoSql Data Model Diagram




Figure 3.17 : NoSql Data Model Diagram of Chatbot

#### Intent

Table 3.2.Intent

Name	Description	Type
_id	Unique id for identify intent in database	ObjectId
name	Name of the intent	string
followUpIntent	List follow-up intent by keep the _id of other intent	array<string>
root	The variable to show that this intent is a parent intent using for order intent list in chatbot configuration interface	boolean
contextInput	Keep context input for the intent. use for enter to this intent	string
contextOutput	Keep context output for the intent. use for set new context in the user after enter this intent	string
trainingData	training data of this intent use this data for train the model	array<string>
parameter	Array attribute that keep the value of symptoms from this intent. use for send to the diagnosis Api for get the diagnosis result.	array<{}>

responseMessage	Array attribute that keep response message of this intent. Use for response the message back when user enter this intent	array<{ }>
type	this attribute use for define type of intent for example fallback, welcome, custom, result type.	string
diseaseResult	this attribute use in result type for define the intent result for each disease.	string
endConver	boolean for end conversation set true to make the user reset the context and parameter when enter this intent.	boolean
sendApi	boolean for send the parameter to api set true for sending all user parameter to the diagnosis api	boolean

### Parameter

Table 3.3. Parameter

Name	Description	Type
variable	name the variable of parameter for send to the diagnosis api	string
value	value of the parameter for send to diagnosis api	string

### Responses Message

Table 3.4. Response Message

Name	Description	Type
type	this is a type of response message that separate in 2 type text response and image response	integer
text	text for response message that keep the array of similar text message using to random one of text to response to the user. set blank if it is image type	array<string>
image	the attribute that keeping image url. Use for sending response message to the user. set blank if it is text type	string

### User

Table 3.5. User

Name	Description	Type
id	unique id for identify users in database	string
senderId	unique facebook id of user using for communicate with each user in facebook messenger	string
context	keep current context of user	string
parameter	keep the parameter of user.using	string

## Results and Discussion

### 4.1 C-Doctor User Interface




Figure4.1 Flow conversation of headache diagnosis

From the Figure 4.1 This is headache diagnosis conversation flow that the square show the question that will response to the user when the user going to that intent for the result we have separate in to 3 result, first the migraine result that most occur when the user have a symptoms along to the right and the tension result that usually occur when the user have the symptoms along to the left and the last one is emergency case that show on the top right which show the result that the user have an emergency case

In this part we will show the some example conversation flow between the user and chatbot for diagnosis disease from symptoms about 2 scenario,Migraine and Tension Disease and also ask disease information.For the diagnosis result we have ask the user about related symptoms to gather the information before send the information

to Bayesian Network Model API and then trigger to the intent result to show the diagnosis result to the user.

#### 4.1.1 Migraine result Conversation flow




Figure 4.2 : Show chatbot conversation

In the figure 4.2 user start to say “สวัสดี” to the C-doctor so the C-doctor will response the greeting message back and give the instruction for using this chatbot to the user. Then the user say “รู้สึกปวดหัวมานานแล้วค่ะ” which mean the user have an headache then the chatbot will be response the response message back to ask the user that user have those of symptoms or not? And then then user say “ไม่มีค่ะ” to the chatbot to say that the user don't have those of symptoms and then the chatbot will be get to the next question by ask the user that the family has history of headache disease before of not? Then the user say “เคยมีคนเคยเป็น” which mean yes so the chatbot will collect the data and then response to the user to confirm the answer and then ask more the question about frequency that the headache occur by day per week .








Figure 4.4 : Show result of migraine

In this picture show that the chatbot send the result back to the

user

#### 4.1.2 Tension result Conversation flow




Figure 4.5 : Show tension conversation flow

From the figure 4.4 it like the previous one so in this picture show that the user have no the family history about headache and she has the headache everyday and also have the headache in the occipital location and say that the level headache is low and the last answer she say that she has the “ปวดหัวตื้อๆ” symptoms




Figure 4.6 : Show result of tension

Finally the chatbot send the message to the api and then return the result to say that the user have tension headache

## 4.2 Intent Classification Model of C-Doctor

In this part we will show the Intent Classification experiment from all of the model but we will start for the model that can explain the result because of it have the most training data from the other model that is model for ask headache level that is separate in High-level, Medium-level, Low-level.

Table4.1 result of model from Headahce-Asklevel context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (19L,16M,18H)</b>	0.625	0.72	0.62	0.63
<b>Deep neural network (19L,16M,18H)</b>	0.8125	0.88	0.81	0.82

From the table 4.1 it is a result of predictive model of Intent classification by using supervised machine learning technique so we use 2 techniques for Intent classification and calculate the value for compare the performance between 2 algorithm. In this experiment we focus on the accuracy of each model that show the ratio of the correct of prediction from the all case that we use for test it. In this experiment we have the 19 training data for low - level headache, 16 training data for medium - level headache and 18 training data for high-level headache. then, we have testing data for calculate the performance of each model about 16 sentence which separate to 3 intent, 6 low, 5 medium and 5 high.

For the first one Multinomial Naive Bayes, the result is not good as we expected maybe it was a cause of TF-IDF that sometimes can't help to for some training data for example in this case there are similar sentence between low level headache and medium level headache like “ปวดไม่มากแต่ปวดหน่อยๆ” and “ปวดไม่มากแต่ปวดกลางๆ” .

For the second one Deep neural network, It seem to be great performance as we expected because we change the weight and bias to make the model get the great performance and the model also have backpropagation that can learn from the error and adjust the weight to be near as the result

From the result we can conclude that we will use deep neural network for the intent classification of the text but for the real performance that we have use and type the text that have some different from the training data it seem to be get the wrong answer so we think that Deep neural network model can be overfit but for the overall it still good to be using for classification. finally, we have to gather more training data for the intent to make it higher accuracy.

table 4.2 result of model from HeadAche-AskFrequeancy context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (5:1-3 day, 4:4-5 day, 2:everyday)</b>	0.64286	0.68	0.64	0.57

<b>,3:not sure)</b>				
<b>TensorFlow Model (Deep neural network) (5:1-3 day, 4:4-5 day, 2:everyday ,3:not sure)</b>	0.714	0.67	0.71	0.65

table 4.3 result of model from HeadAche-AskSide context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (3 Occipital, 3 Temples, 3 Eyes, 3MiddleHead , 3Unknown,)</b>	0.66667	0.60	0.67	0.62
<b>Deep neural network (3 Occipital, 3 Temples, 3 Eyes, 3MiddleHead , 3Unknown,)</b>	0.80	0.90	0.80	0.81

From the table 4.2 and 4.3 it is the result of performance of each model for asking the location side and frequency of symptoms by day/week that the user get headache. As you can see the training data was too small for find the result because when we split the data between test data and train data the dataset for each intent is only have 5 for Occipital side, 7 Temple side, 7 Eyes Side, 7 Middle Head Side, 6 Unknow side but deep neural network can still classification with the input that similar to the training dataset but it can be wrong if the input is not near to the training data. So the conclusion is we have to get more training data for each intent to compare the performance of the model.

table 4.4 result of model from blank context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (3,headache, 2,ask headache information, 3, greeting)</b>	1.00	1.00	1.00	1.00

<b>Deep neural network (3,headache, 2,ask headache information, 3, greeting)</b>	1.00	1.00	1.00	1.00

table 4.5 result of model from HeadAcheInfo 9 8

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (3,Migraine Infomation, 3,Tension Infomation, )</b>	1.00	1.00	1.00	1.00
<b>Deep neural network (3,Migraine Infomation, 3,Tension Infomation, )</b>	0.83	0.83	0.83	0.83

table 4.6 result of model from HeadAche-Emer context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes (3 Yes, 3No)</b>	0.500	0.50	0.50	0.49
<b>Deep neural network (3 Yes,3No)</b>	1.00	1.00	1.00	1.00

table 4.7 result of model from HeadAche-familyHistory context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes</b> (3Yes,3No,3Not sure)	0.88889	0.92	0.89	0.89
<b>Deep neural network</b> (3Yes,3No,3Not sure)	0.84	0.92	0.89	0.89

table 4.8 result of model from HeadAche-TueTue context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes</b> (2Yes, 1 No,)	1.00	1.00	1.00	1.00
<b>Deep neural network</b> (2Yes, 1 No,)	1.00	1.00	1.00	1.00

table 4.9 result of model from HeadAche-AskVomit-followup context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes</b> (1Yes, 2 No,)	1.00	1.00	1.00	1.00
<b>Deep neural network</b> (1Yes, 2 No,)	1.00	1.00	1.00	1.00

table 4.10 result of model from HeadAche-AskLight context



Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes</b> (1Yes, 2 No,)	1.00	1.00	1.00	1.00
<b>Deep neural network</b> (1Yes, 2 No,)	0.66	0.44	0.67	0.53

table 4.11 result of model from HeadAche-AskTubTub context

Classification Techniques	Accuracy	Precision	Recall	F - measure
<b>Multinomial Naive Bayes</b> (2Yes, 1No,)	1.00	1.00	1.00	1.00
<b>Deep neural network</b> (2Yes, 1 No,)	0.00	0.00	0.00	0.00

For the other table above we cannot explain the result of the performance because the training data is too small for using training the model so some of the result will make the model low performance.

### 4.3 C-Doctor Intent Configuration platform

**C - DOCTOR**

**Chatbot Conversation**

Fallback Message

Welcome Message

Intent Lists

+Intent ▼

- HeadAche > + 🗑
- HeadAche-emer-yes + 🗑
- HeadAche-emer-No > + 🗑
- HeadAche-familyHistory-yes + 🗑
- HeadAche-familyHistory-no + 🗑
- HeadAche-familyHistory-notsure > + 🗑
- HeadAche-frequeancy-low + 🗑
- HeadAche-frequeancy-medium + 🗑
- HeadAche-frequeancy-High + 🗑
- HeadAche-frequeancy-notsure > + 🗑
- HeadAche-Side-Occipital + 🗑
- HeadAche-Side-Temples + 🗑
- HeadAche-Side-Eyes + 🗑
- HeadAche-Side-MiddleHead + 🗑
- HeadAche-Side-Unknown > + 🗑
- HeadAche-level-low > + 🗑
- HeadAche-TueTue-Yes + 🗑
- HeadAche-TueTue-No + 🗑
- HeadAche-level-medium + 🗑
- HeadAche-level-High ✓ + 🗑
- HeadAcheInfo > + 🗑
- HeadAcheInfo-Migraine + 🗑
- HeadAcheInfo-TensionHeadache + 🗑
- Tension Result + 🗑
- Migraine Result + 🗑
- Greeting + 🗑

**Intent Configuration** Save

Intent Name  
HeadAche-level-High

Context Input  
HeadAche-AskLevel-followup

Context Output  
HeadAche-AskVomit-followup

Training Data

Enter Training Data

ปวดมากเหมือนจะล้ม	🗑
ปวดมากจนอ้วก	🗑
ปวดจนทำงานไม่ได้	🗑
ปวดปกติ	🗑
เจ็บหัวรุนแรงมาก	🗑
เจ็บหัวมาก	🗑
ปวดเยอะ	🗑
ปวดสุดๆ	🗑
ปวดมาก	🗑
ปวดอย่างรุนแรง	🗑

« Previous 2 Next »

*Figure4.7 : The build intent interface with the intent example of headache-level-High intent*

This is user configuration interface, at the intent page the user can create intent for chatbot and can do a lot of features that make chatbot has efficiency. From the figure4. we show the intent of the headache-level-high intent to show that the web interface can be add intent and information inside intent.

Context Input

HeadAche-AskLevel-followup











Context Output

HeadAche-AskVomit-followup

*Figure4.8: the example of input for set the Context input and Context Output*

In first part you can set context input for intent to make the intent can access only when user have this context and set context output for user to go to next context.

## Training Data

Enter Training Data	
ปวดมากเหมือนจะล้ม	
ปวดมากจนอ้วก	
ปวดจนทำงานไม่ได้	
ปวดปวด	
เจ็บหัวรุนแรงมาก	
เจ็บหัวมาก	
ปวดเยอะ	
ปวดสุดๆ	
ปวดมากๆ	
ปวดอย่างรุนแรง	

« Previous 1 2 Next »

*Figure4.9: the example of training data interface*

This part is use for training conversation of chatbot. User can type training data and enter to save it. If have a lot of training data user can click next page to see more data.

## Response Message



<https://image.freepik> 

Text Response + 

1	มีอาการคลื่นไส้หรืออาเจียนเวลาปวดหัวหรือไม่ครับ?	
2	เวลาปวดหัวรู้สึกคลื่นไส้หรืออยากจะอาเจียนไหมครับ?	

## Choose Response Message Type

TEXT

IMAGE

*Figure 4.10: the example of response message interface*

This feature is use for send response message to user. First you can choose type of thing that you want to send response to user that are text or image. If you want to create text you can add similar conversation in same table by clicking plus sign button,

the system will random response message in that table to user. So from the figure 4. we can see that when the user coming to this intent the user will be get random text between 2 sentence.


### Parameter

Variable	Value	
PainLevel	2	
Enter Variable	Enter Value	

[+ new parameter](#)


*Figure 4.11 the example of parameter interface*

This part you can set answer value of this intent for sending to API of bayesian model project.



*Figure 4.12: the example of button send api and end conversation*

In this part we have both 2 button to make it with the bayesian model api because now the api is still have the an slightly error for diagnosis because sometime we just get 2 symptoms and the then the result can be more than 70% that higher that we set for get result but in the real world it not make sense to get only 1 or 2 symptoms and send the result so we will have sendApi button for send the parameter to api if that intent set the button to true but if the probability is not greater than 70% the chatbot will still ask the next question until there is the intent that set both of the button to true so it will be get the result and send the diagnosis back to the user.



*Figure4.13: the interface of training the model*

In second menu that is setting, you can training data for text classification in this part by clicking train button to training the model that separate by the context and waiting in a few minute and then get the success result.

#### 4.4 Back-end system

##### Text Classification Process

```
{ sender: { id: '2183948518309240' },
  recipient: { id: '281297052516409' },
  timestamp: 1558027586411,
  message:
    { mid:
      '9Wc_XAxEGguD46C6t3UFST9J3y5Uu1Nwy',
      seq: 0,
      text: 'ปวดรุนแรงมากค่ะ' } }
{ id: '281297052516409',
  time: 1558027586831,
  messaging:
    [ { sender: [Object],
      recipient: [Object],
      timestamp: 1558027586411,
      message: [Object] } ] }
Sender PSID: 2183948518309240
```

*Figure 4.14: example of text input from the user*

```

[ { intent: '5cd992eb0c3bc974c3441668',
  probability: 0.9980412721633911 },
  { intent: '5cd992e70c3bc974c3441667',
    probability: 0.0019576072227209806 },
  { intent: '5cd992e50c3bc974c3441666',
    probability: 0.0000011185580888195545 } ]
{ intent: '5cd992eb0c3bc974c3441668',
  probability: 0.9980412721633911 }
Matching Intent: HeadAche-level-High,0.9980412721633911

```

*Figure4.15: the prediction of result from the model*

From the figure 4.14 and 4.15 we show that the server get the input text of user from the Facebook messenger and then send the text to the intent classification process and then return the highest result which is matching

## **Chapter 5**

### **Conclusion**

#### **Conclusion**

From the implementation of the C-Doctor chatbot, the project is reach to the objective. the chatbot is capable to simply diagnose disease from the symptoms of the user. The chatbot will ask for the question to gather more the symptoms from the user and then when we get enough information the chatbot will send the symptoms to the bayesian model api to get the result of disease and then return the disease information and basic treatment to the user. For the configuration chatbot web platform it work perfectly for the function that use for create the chatbot dialog for diagnosis the symptoms. For the conclusion, If we have the more training data for the intent the chatbot will be get high performance for classification

#### **5.1 Problem encountered**

##### **1. Training data**

It is the mainly problem for our project that we have lack of training data so some model will be overfit and make it low performance for classification and some problem that we found that some context we just only want the yes or no answer so we think that we will create more the response message that have the button for the user to select the answer to solve for that problem

##### **2. Lack of diagnosis information and data for the bayesian network api**

First we have lack of information for diagnosis the symptoms but the one important problem that we found is some of symptoms are not have in the bayesian network api so we must cut of some of the symptoms and make the new flow diagnosis conversation to suitable with the model. So the conclusion is we have to find more the data to make the bayesian model more flexible and then we can make more flexible conversation for diagnosis.

#### **5.2 Lesson learn**

According to the technical knowledge that we got from the project, we learn how to design the platform for the chatbot including of the diagnosis systems and web design for create the chatbot dialog. Then, we get learn to deal the problem with the web interface for example, some of the interface that we can't do it from the design so we will re-design the interface and get the comment from the partner to improve the design can be build it real.

The last thing that we can learn from this project is the user experience of the chatbot. we have design the flow of the conversation and think about the appropriate question to get the expected answer from the user so we have to testing the chatbot by give the user testing and then collect the comment from the user to improve the conversation and make the chatbot more effective.

#### **5.3 Future work**

For the future work of our chatbot we will create more response message type such as button response to deal with some of the question that have to answer like yes or no or the question that have to answer in time or number.

The next one is we will learn and collect more the diagnosis conversation so the project will be diagnose more than headache symptoms and we will study about the symptoms that have the related with the headache symptom to expand the conversation and make the chatbot more effective to diagnosis more disease.



## **Reference**

[1] Pythai [Online]. Available: <https://github.com/PyThaiNLP/pythainlp> Retrieved 2018, September 10

[2] Django. Django[Online]. Available: <https://www.djangoproject.com/> Retrieved 2018, September 10

[3] Django. Django Introduction[Online]. Available: <https://developer.mozilla.org/en-US/docs/Learn/Server-side/Django/Introduction> Retrieved 2018, September 10

[4] lukkid.Intent-Based vs Flow-Based Conversation [Online]. Available: <https://medium.com/hbot/intent-based-vs-flow-based-conversation-e0f7551e674b> Retrieved 2018, September 23

[5] Intent.Intent Classification [Online]. Available: <https://blog.vsoftconsulting.com/blog/intent-classification-and-its-significance-in-chatbot-development> Retrieved 2018, September 23

[6] Deep learning.Long Short Term Memorys [Online]. Available: <https://medium.com/@sinart.t/long-short-term-memory-lstm-e6cb23b494c6> Retrieved 2018, September 23

[7] ภาควิชาอายุรศาสตร์ คณะแพทยศาสตร์ศิริราชพยาบาล (2559).ตำราอายุรศาสตร์ อากาโรวิทยา. กรุงเทพมหานคร, ฟรินท์เอเบิล

[8] กองอายุรกรรม โรงพยาบาลภูมิพลอดุลยเดช (2557).Differential diagnostic algorithm in internal medicine. โรงพิมพ์

[9] Flora Amato,Stefano Marrone, Vincenzo Moscato, Gabriele Piantadosi, Antonio Picariello, and Carlo Sansone.Chatbots meet eHealth: automatizing healthcare.Claudio 21, 80125 Napoli

[10] Different between naive bayes and multinomial naive bayes: Available: <https://stats.stackexchange.com/questions/33185/difference-between-naive-bayes-multinomial-naive-bayes>