



Version 2021-10-20

er

Square customer profile in the Customer
Square seller.

A unique Square-assigned ID for the customer profile.

Read only The timestamp when the customer profile was created, in RFC 3339 format.

Examples for January 25th, 2020 6:25:34pm Pacific Standard Time:

UTC: 2020-01-26T02:25:34Z

Pacific Standard Time with UTC offset: 2020-01-25T18:25:34-08:00

Read only The timestamp when the customer profile was last updated, in RFC 3339 format.

Examples for January 25th, 2020 6:25:34pm Pacific Standard Time:

UTC: 2020-01-26T02:25:34Z

Pacific Standard Time with UTC offset: 2020-01-25T18:25:34-08:00

Payment details of the credit, debit, and gift cards stored on file for the customer profile.

DEPRECATED at version 2021-06-16. Replaced by calling [ListCards](#) (for credit and debit cards on file) or [ListGiftCards](#) (for gift cards on file) and including the `customer_id` query parameter. For more information, see [Migrate to the Cards API](#) and [Gift Cards API](#).



Card Attributes



id string

Read only Unique ID for this card. Generated by Square.

Max Length **64**

billing_address Address

The billing address for this card.

Show Attributes

bin string

Read only The first six digits of the card number, known as the Bank Identification Number (BIN). Only the Payments API returns this field.

Max Length **6**

card_brand string

Read only The card's brand.



CardBrand Values



SQUARE_GIFT_CARD

SQUARE_CAPITAL_CARD

INTERAC

EFTPOS

FELICA

EBT

card_type string

Read only The type of the card. The Card object includes this field only in response to Payments API calls.



CardType Values



UNKNOWN_CARD_TYPE

CREDIT

DEBIT

cardholder_name string

The name of the cardholder.

Max Length 96

customer_id string

The ID of a customer created using the Customers API to be associated with the card.

enabled boolean

Read only Indicates whether or not a card can be used for payments.

exp_month integer (64-bit)

The expiration month of the associated card as an integer between 1 and 12.

exp_year integer (64-bit)

The four-digit year of the card's expiration date.

fingerprint string

Read only Intended as a Square-assigned identifier, based on the card number, to identify the card across multiple locations within a single application.

Max Length 255

last_4 string

Read only The last 4 digits of the card number.

Max Length 4

prepaid_type string

Read only Indicates whether the Card is prepaid or not. The Card object includes this field only in response to Payments API calls.

Show Values

reference_id string

An optional user-defined reference ID that

associates this card with another entity in an external system. For example, a customer ID from an external customer management system.

Max Length **128**

version integer (64-bit)

Current version number of the card. Increments with each card update. Requests to update an existing Card object will be rejected unless the version in the request matches the current version for the Card.

The given (i.e., first) name associated with the customer profile.

The family (i.e., last) name associated with the customer profile.

A nickname for the customer profile.

A business name associated with the customer profile.

The email address associated with the customer profile.

The physical address associated with the customer profile.



Address Attributes



address_line_1 string

The first line of the address.

Fields that start with **address_line** provide the address's most specific details, like street number, street name, and building name. They do *not* provide less specific details like city, state/province, or country (these details are provided in other fields).

address_line_2 string

The second line of the address, if any.

address_line_3 string

The third line of the address, if any.

administrative_district_level_1 string

A civil entity within the address's country. In the US, this is the state.

administrative_district_level_2 string

A civil entity within the address's **administrative_district_level_1** . In the US, this is the county.

administrative_district_level_3 string

A civil entity within the address's **administrative_district_level_2** , if any.

country string

The address's country, in ISO 3166-1-alpha-2 format.

Show Values

first_name string

Optional first name when it's representing recipient.

last_name string

Optional last name when it's representing recipient.

locality string

The city or town of the address.

organization string

Optional organization name when it's representing recipient.

postal_code string

The address's postal code.

sublocality string

A civil region within the address's **locality** , if any.

sublocality_2 string

A civil region within the address's **sublocality** , if any.

sublocality_3 string

A civil region within the address's **sublocality_2** , if any.

The 11-digit phone number associated with the customer profile.

The birthday associated with the customer profile, in RFC 3339 format. The year is optional. The timezone and time are not allowed. For example, `0000-09-21T00:00:00-00:00` represents a birthday on September 21 and `1998-09-21T00:00:00-00:00` represents a birthday on September 21, 1998.

An optional second ID used to associate the customer profile with an entity in another system.

A custom note associated with the customer profile.

Represents general customer preferences.

×

CustomerPreferences Attributes

email_unsubscribed boolean

Indicates whether the customer has unsubscribed from marketing campaign emails. A value of `true` means that the customer chose to opt out of email marketing from the current Square seller or from all Square sellers. This value is read-only from the Customers API.

A creation source represents the method used to create the customer profile.

Show Values

The IDs of customer groups the customer belongs to.

The IDs of segments the customer belongs to.

The Square-assigned version number of the customer profile. The version number is incremented each time an update is committed to the customer profile, except for changes to customer segment membership and cards on file.

The tax ID associated with the customer profile. This field is present only for customers of sellers in France, Ireland, or the United Kingdom. For more information, see [Customer tax IDs](#).



CustomerTaxIds Attributes



eu_vat string

The EU VAT identification number for the customer. For example, `IE3426675K`. The ID can contain alphanumeric characters only.

Max Length **20**

Development

[Docs](#)

[API Reference](#)

[API Explorer](#)

[SDKs](#)

[Sample apps](#)

[System status](#)

Support

[Developer forums](#)

[Contact support](#)

[Developer blog](#)

[Slack community](#)

[YouTube](#)

[Twitter](#)

More

[Square Home](#)

[Square Developer](#)

[App Marketplace](#)

[Partner with Square](#)

[Solutions Partner Program](#)

[Pricing](#)

[Sales](#)

© 2021 Square, Inc.

[Developer terms of service](#)

[Privacy policy](#)

