

Drapery System Specification

Prepared by: Futureproof AV Consulting **Date:** May 8, 2026 **Rev:** A

PROJECT SUMMARY

Traveling velour drape system, ceiling-mounted to soffit via I-beam track with shirred pleats.

FABRIC SPECIFICATION

PARAMETER	VALUE
Fabric	Rose Brand 32oz Imperial Velour, IFR
Composition	100% IFR Polyester
Weight	32 oz/linear yard (21 oz/sq yard)
Roll width	54"
Fire rating	NFPA 701, California Title 19 Class 1
Pleat style	Shirring, sewn into carrier webbing
Fullness	80%
Finished height	7'
Run length	77'
Color	TBD

FABRIC CALCULATION

PARAMETER	VALUE
Run length	77'

PARAMETER	VALUE
Fullness factor	1.80x (80%)
Total fabric width required	138.6'
Widths per panel (at 54" roll)	2 (sewn, hemmed to 7' finished)
Total linear yardage	92.4 yd

TRACK SYSTEM

COMPONENT	SPECIFICATION	QTY
Track	ADC Rig-i-Flex 1400 I-beam aluminum	77 LF
Carriers	ADC single carriers, 12" O.C.	77 ea
Master carrier	ADC master carrier assembly	TBD
Ceiling clamps	ADC 1423 ceiling clamp	TBD (3-4' O.C.)
Draw type	TBD (one-way / bi-part)	

LOAD ANALYSIS

PARAMETER	VALUE
Track capacity	15 lbs/LF
Fabric load (2 widths at 80% fullness)	2.4 lbs/LF
Carriers + webbing	0.4 lbs/LF
Total curtain load	2.8 lbs/LF
Capacity used	18.7%
Total curtain weight	~215 lbs
Result	PASS

VERTICAL CLEARANCE

COMPONENT	DIMENSION
ADC 1423 ceiling clamp	~1"
ADC 1400 track channel	2-1/2"
ADC 4201 carrier + swivel	~1-1/8"
Total system height (soffit to hook)	4-5/8"
Finished drape height	7'-0"
Total drop (soffit to drape hem)	7'-4-5/8"

Source: ADC drawing CAT-140CEIL-02

STACK ANALYSIS

PARAMETER	VALUE
Carrier stations	77
Compressed carrier width	1.8"
Stack width (along track)	77 x 1.8" = 11.55'
Stack depth (projection from track)	Est. 8-12"

NOTES

- Fabric fullness is sewn into carrier webbing at each station (shirring style). Fullness folds front-to-back between carriers when stacked.
- Track is ceiling-mounted directly to soffit via ADC 1423 clamps. Fastener specification dependent on soffit material (steel deck, concrete, or wood).
- ADC Rig-i-Flex 1400 cord-operated limits: 40' one-way / 60' bi-part. A 77' run may require motorization or multiple independent draw sections.
- All fabric is inherently flame retardant (IFR) -- permanent, will not wash out or degrade.

OPEN ITEMS

☐

Color selection

☐

Draw type (one-way / bi-part / multi-section)

☐

Motorized vs. cord-operated

☐

Soffit material / fastener spec

☐

Ceiling clamp spacing and quantity

☐

Hem style (chain weight / pipe pocket / plain)

☐

Pricing from Rose Brand (project volume)

☐

Installation labor

☐

Lead time confirmation