Machine learning in battery management systems: a two-tier scoping review of 799 eligible studies with in-depth classification and validation audit

Hussain Touhid Siddiquee
Leading University, Sylhet, Bangladesh

Syeda Salsabil Islam Ariya
Leading University, Sylhet, Bangladesh

Jasimul Islam Chowdhury
Leading University, Sylhet, Bangladesh

Abstract

Machine learning (ML) has become a load-bearing component of modern battery management systems (BMS), but the validation practices behind the literature's accuracy claims are rarely examined. This paper presents a structured scoping review with a two-tier evidence base: an *eligible corpus* of 799 peer-reviewed journal articles admitted from a capped 30-query Crossref retrieval by rule-based screens, and a *classified subset* of 103 studies — 98 drawn from that pool plus five seed studies retrieved and verified individually — coded from full texts by function, method family, chemistry, data source, and validation practice, with a blind 30-paper re-coding by two co-author coders that, after the pre-declared codebook revision, passes all five fields at strong agreement (validation $\kappa = 0.92$).

Three findings stand out. First, validation practice is the field's weakest link: of the 88 primary-application papers, only 8 demonstrate their estimators online or on real vehicles, 17 rely on within-cell or k-fold splits that can leak trajectory information, and the empirical base is split between three shared public benchmarks (23 papers) and private laboratory data (42 papers — 36 own-cell cycling, 6 laboratory impedance) that cannot be audited at all. Second, physics-informed architectures, often assumed more rigorous by construction, show no detectable difference in validation stringency from data-driven peers (8 of 22 versus 34 of 66 under the protocol-only definition; Fisher's exact $p = 0.32$) — a contrast this review's power analysis shows to be underpowered, so equivalence is not claimed. Third, within the classified subset, method families stratify by period — classical shallow learners, then deep sequence models, now physics-informed hybrids — a within-subset sequence that the eligible pool's query-theme tags do not mirror, and the subset's first large-language-model studies appear in 2026.

Because the retrieval is capped and the subset curated, every claim is scoped to the tier that supports it; a worst-case label-noise bound, a minimum-detectable-effect analysis, a recall audit, and abstract-level probes quantify the robustness of the headline findings (derivations in the Supplementary Material); a retrieval-depth pilot measures what the capped retrieval itself withholds; and an independent post-freeze re-code of the validation field audits the strong-protocol count itself (Section 3.4). The review closes with a requirement-level mapping of BMS functions onto UN GTR 20, GB 38031, and ISO 26262, a positioning against prior reviews, and a twelve-item reporting checklist; the complete evidence base and analysis pipeline are deposited with a DOI.

Keywords: machine learning; battery management systems; lithium-ion batteries; state of charge; state of health; remaining useful life; deep learning; physics-informed neural networks; transfer learning; battery safety

1. Introduction

1.1 Electrification and the battery management problem

Lithium-ion batteries now anchor three converging transitions: the electrification of road transport, the proliferation of stationary storage in renewable-heavy grids, and the electrification of aerospace, marine, and industrial systems. In each of these settings, the battery is not a passive component but an actively managed asset whose usable capacity, lifetime, and safety depend on operating decisions made in real time. The battery management system is the embedded cyber-physical layer that makes those decisions: it senses cell voltages, currents, and temperatures; estimates unobservable internal states; protects against over-charge, over-discharge, and thermal abuse; balances cells; and increasingly negotiates charging strategies with the surrounding power system [1].

The difficulty of the management problem stems from the fact that the quantities that matter most — state of charge (SOC), state of health (SOH), internal temperature, and the onset of degradation or fault mechanisms — are not directly measurable. They must be inferred from noisy, partially observable terminal measurements under widely varying operating conditions. Model-based approaches built on equivalent-circuit or electrochemical models have served the industry well, but they face a persistent trade-off between fidelity and computational tractability, and their parameters drift as cells age [2]. It is in this inference-and-decision layer that machine learning has made its most forceful entry.

1.2 The rise of machine learning in battery management

Machine learning entered battery management through estimation. Early applications treated SOC and SOH estimation as supervised regression on hand-engineered features, using support vector machines, Gaussian process regression, and shallow neural networks. Two studies then reset expectations for the whole field. Severson and colleagues showed that the entire cycle life of a lithium-ion cell could be predicted with a median test error near 9% using only features extracted from the first hundred cycles, on a public dataset of 124 cells [3]. Attia and colleagues demonstrated closed-loop Bayesian optimization of fast-charging protocols, identifying high-cycle-life protocols among 224 candidates in 16 days of closed-loop cycling rather than the more than 500 days an exhaustive search without early prediction would take [4]. Together these results reframed battery management as a data problem in which learning systems could outperform hand-tuned models both in estimation accuracy and in experiment efficiency.

The five years that followed produced a wave of published applications across every BMS function: recurrent and convolutional networks for SOC and SOH [5, 6], graph and transformer architectures for prognostics [7, 8], physics-informed neural networks that embed electrochemical and thermal priors into learning systems [9, 10], transfer learning schemes that port estimators across chemistries and vehicles [11, 12], reinforcement learning agents for charging and prognostic model selection [13], and, most recently, large language model (LLM) agents for fleet-scale risk analysis and vehicle-cloud battery management [14, 15].

1.3 Existing reviews and the literature gap

The review literature has grown alongside the applications, but it is fragmented along the same axes as the primary studies. An early perspective on data-driven SOC and SOH prediction [16] set the agenda; function-specific reviews cover SOC estimation [17, 18], SOH estimation [19], and prognostics [20] in depth, while method-specific reviews follow individual threads such as deep-learning state estimation [1], physics-informed learning for impedance-based diagnostics [21], or interpretable ML for prognosis [22]. Domain-anchored reviews examine fault diagnosis and safety [23, 24] and thermal management [25], alongside broader degradation-method surveys [26].

The closest in scope among recent cross-functional reviews is the performance-centric review of Prasanna et al. [27], which examines 240 peer-reviewed publications (included from 361 initially retrieved records under its PRISMA screen) spanning the whole electric-vehicle powertrain — battery management alongside charging systems, motor control, and energy-consumption prediction — and aggregates reported performance metrics (root-

mean-square error, RMSE, and coefficient of determination, R^2) into a quantitative benchmarking of algorithm families, concluding that hybrid deep-learning architectures (long short-term memory (LSTM) and convolutional neural network (CNN) hybrids such as LSTM-DDQN and CNN-BiGRU, plus transformer-based frameworks) consistently achieve superior accuracy ($R^2 > 0.95$, RMSE < 0.05). This review differs from that work in scope, unit of analysis, and question asked. In scope, it is narrower and deeper: battery-management functions only — estimation, prognostics, charging, thermal, fault and safety, balancing — rather than the powertrain breadth, which permits function-level cuts such as the standards mapping of Section 9.4 and the per-function validation audit. In unit of analysis, it is protocol-centric rather than performance-centric: instead of pooling reported accuracy figures, it codes how each study's validation protocol isolates (or fails to isolate) its generalization claim — cross-cell holdout versus within-cell splits, benchmark reuse versus private data, laboratory duty versus fleet duty. The two approaches are complementary, and the complementarity is pointed: an aggregation of self-reported RMSE and R^2 may inherit, unmeasured, precisely the validation weaknesses that this review quantifies within its own subset — there, 17 of 88 primary papers validate on information-leaking splits and headline accuracies concentrate on three shared benchmarks — so where Prasanna et al. answer *which algorithm family performs best as reported*, this review asks *how much the reports can be trusted, and what a study must disclose for its claims to be checkable*. A third difference is evidentiary: the two-tier design here measures bibliometric shares over a released 799-record eligible corpus with record-level screening provenance, and releases the per-paper protocol audit, codebook, and re-runnable pipeline — an artifact base on which a future performance-centric synthesis could itself be audited. What remains missing from the literature even after these reviews is exactly that junction: a corpus-level account linking method family, data regime, and validation strength across management functions, which this review supplies for the BMS slice.

This gap matters because the field's self-image drives its research allocation. If, for example, most published health estimators are validated on within-cell splits of public datasets, the community's sense of progress is calibrated to a benchmark regime that differs sharply from fleet deployment. If interpretability claims are concentrated in a small method family, the safety case for certification-grade ML in production BMS is weaker than the volume of publications suggests. Answering such questions requires a corpus-level, cross-functional account of the field rather than another narrative synthesis of one function.

1.4 Contribution of this paper

This paper makes five contributions. First, it assembles a two-tier evidence base: a rule-based eligible corpus of 799 Crossref-verified records from which field-level shares are measured within a documented capped retrieval, and an in-depth classified subset of 103 studies in which every reference's bibliographic metadata was confirmed against the Crossref registry by direct DOI resolution. Second, it develops a classification framework — BMS function × method family, extended with chemistry, data-source, and validation-practice fields — applies it uniformly to all 103 papers, and probes its reliability with a blind, two-round 30-paper re-coding by two co-author coders under released codebooks — round 1 abstract-level, round 2 under the pre-declared v1.1 revision and a shared evidence base, passing all five fields at strong agreement (validation $\kappa = 0.92$; strong/non-strong bucket 28 of 30). Third, it quantifies the corpus's composition across functions, methods, data, and validation (Section 3), anchoring function-level baselines on the quota-free eligible pool and reporting validation-practice rates with confidence intervals, label-noise scenario envelopes, a minimum-detectable-effect analysis for the method-family contrast, an abstract-level representativeness probe, a baseline-comparison screen, and a recall audit that quantifies what the capped retrieval itself misses (Section 2.2). Fourth, it provides a critical, function-by-function review of what the corpus actually demonstrates (Sections 4–8), positioned explicitly against prior reviews (Section 9.7), and maps BMS functions onto UN GTR 20 [28], GB 38031 [29], and ISO 26262 [30] requirements (Section 9.4). Fifth, it distills a gap-driven research agenda (Section 9) and a twelve-item reporting checklist (Section 9.9).

Fig. 1 previews the analysis, mapping the 88 primary studies of the classified subset across management functions and method families (the 12 method reviews carry no method-family code, and the 3 review-type syntheses —

family-coded under their dominant method — are excluded here; the caption states the reconciliation): the field's center of gravity sits squarely in the health-prognostics complex, hybrid model–data approaches now span every function, and learning-based charging control remains a concentrated Bayesian-optimization stronghold. The remainder of the paper is organized as follows. Section 2 details the review methodology: search strategy, screening procedure, inclusion and exclusion criteria, and the classification framework, together with its limitations. Section 3 presents the corpus overview and five-year bibliometric analysis. Sections 4 through 7 review machine learning for state estimation, health estimation and prognostics, charging control, and thermal management, fault detection, and safety, respectively. Section 8 examines cross-cutting directions — physics-informed learning, interpretability and uncertainty, digital twins and cloud BMS, and foundation models. Section 9 formulates research gaps and future directions, and Section 10 concludes.




Fig. 1 The classified subset mapped across battery-management functions and method families (88 primary-application papers; see Section 2.5 for terminology). Cell values are paper counts. The 15 review-labelled papers (12 method-family reviews plus 3 review-type syntheses coded under their dominant method family, two of them physics-informed) are excluded here; the Reviews column of Table 3 states the reconciliation directly, so the physics-informed family comprises 22 primary papers plus 2 review-type syntheses (24 family-coded; Table 2 gives the primary counts).

2. Review Methodology

2.1 Scope and objective

The objective of this review is to characterize the current state and recent evolution of machine learning applied to battery management, understood as the set of estimation, protection, and control functions performed by or in support of a battery management system. The scope covers SOC estimation, SOH estimation and capacity tracking, remaining useful life (RUL) prediction and early-life prognosis, charging strategy optimization, thermal-state estimation and battery thermal management, fault diagnosis, anomaly detection and safety prediction, and cross-cutting methodological themes (physics-informed learning, transfer learning, interpretability, digital twins, cloud and fleet management, and foundation models). Battery *design* and *materials-discovery* applications of machine learning fall outside the scope except where they directly support a management function, such as manufacturing-quality prediction of cell capacity.

2.2 Literature search strategy

All candidate records were retrieved programmatically from the Crossref REST API between 4 and 5 September 2026 using 30 bibliographic query strings spanning the application areas listed above (for example, "state of charge estimation lithium-ion battery machine learning", "remaining useful life prediction battery deep learning", "physics-informed neural network lithium-ion battery", and "large language model battery"). Queries were issued in five passes: a top-cited pass over 2020–2026 sorted by citation count; a relevance-sorted recency pass restricted to June 2024 onward (from 1 June 2024); two dedicated relevance-sorted passes restricted to 2020–2022 and to 2023; and a mid-window 2021–2023 coverage pass, which together yielded 3,000 fetched rows. Document-type, year, and title-completeness filters left 2,973 rows, and DOI-based deduplication removed 1,423 duplicates, leaving 1,550 unique

records. Six landmark studies — including the early-life prediction study [3] and the prognostics review [2] — were additionally safeguarded as forced seeds: five were retrieved and verified individually because citation-sorted retrieval had crowded them out, and one was already among the top-cited hits.

Two properties of this search design should be stated plainly. First, the Crossref registry is a metadata registry, not a discovery engine of the kind Scopus or Web of Science provide; it was chosen deliberately, because the aim of this review is that every included record be individually verifiable by direct DOI resolution, which registry-native retrieval guarantees and secondary databases cannot. The cost is a recall floor: coverage depends on Crossref registration, and the usual cross-database triangulation is absent. Second, the top-cited pass inherits the biases of citation counts — it favors established, English-language, high-profile work and mechanically over-weights older publications. The three remaining passes exist to counter exactly these biases, and all trend statements in this paper are statements about trends within this citation-weighted, English-language, journal-article sample rather than about the field in the aggregate.

A third property of the search design is measured rather than asserted. Every query pass returned its top 20 records only, so the 30 queries are design-capped at 100 records per query family: the five passes yielded 3,000 fetched rows, 2,973 after document-type, year, and title-completeness filters, and 1,550 unique records after deduplication — every yield is a design cap, not a saturated result (the per-query yields are released in recall_audit.json). A post-hoc recall audit therefore asks how much of the literature that this review's own included reviews cite the retrieval actually captured: of the in-scope, 2020-onward, DOI-bearing references in the deposited reference lists of the 15 included reviews and the six seed studies, the 1,550-record retrieval contains 112 of the 649 per-source reference mentions (17.3%) — 96 of the 586 unique references (16.4%); the denominator construction, the per-query yields, and the audit's limits are stated in full in Supplementary Material S4. Read as a floor on external validity the number is sobering, and it is reported because retrieval-boundedness should be quantified, not assumed away: theme frequencies, per-family shares, and 'earliest' claims in this review are properties of this retrieval and the subset it fed, not of the field — which is why every such claim is subset-scoped (Supplementary Material S1). The recall miss documented in Section 8.4 fits this pattern exactly: the TEC 2025 GPT-4 estimator it discloses is cited by none of the included reviews either, so no reference-list audit would have surfaced it. How much of that gap deeper retrieval would close is now measured rather than asserted: a released pilot (retrieval_depth_pilot.py/.json) re-ran six representative query families with cursor paging to ten times the original per-pass depth, replicating the original pass windows and sort orders and pinning the registry date to the retrieval date. Those six families, which contributed 253 title-gated records under the top-20 design, yield 2,319 at depth 200, of which 1,500 are absent from the 1,550-record retrieval (1,406 after the venue screen); applying the original design's observed cross-family overlap factor (1.46) puts the net gain over all 30 families on the order of 5,000 additional eligible records. The cap, in other words, is the binding constraint by a wide margin — the 16–17% recall figure measures a sampling decision, not a property of the registry — and a v2 re-retrieval with cursor paging is the single highest-leverage methodological upgrade this pipeline could make (Section 9.8, direction (g)); what the current corpus supports, it supports as a capped sample, which is how every section reads it.

2.3 Screening and selection procedure

The screening funnel is shown in Fig. 2. From 1,550 deduplicated records, a title-level relevance gate requiring both battery-related and machine-learning-related terminology retained 883 records and excluded 667 (predominantly adjacent-field papers — general machine-learning methods, adjacent-domain bibliometrics, and battery electrochemistry without a learning component — that surfaced through loose bibliographic matching). Venue and document-type screening then removed 84 records — conference abstracts and proceedings series (e.g., ECS Meeting Abstracts, IET/IFAC proceedings), preprint servers (SSRN), and non-scholarly venues — in line with the decision to restrict the corpus to peer-reviewed journal articles, leaving 799 eligible records. The screen is document-type-based rather than topical — any Crossref-registered peer-reviewed journal article passes it — and each record's Crossref-resolved title and venue is logged at retrieval time (final_audit.json), so venue anomalies are

visible rather than silent. Selection then proceeds in two tiers, and the distinction carries the paper's evidentiary weight. *Tier 1 (eligible corpus).* Every one of the 799 eligible records is included, subject only to the venue screen — no function quotas, year caps, or citation thresholds are applied at this tier — and the released screening log carries all 1,555 record-level rows — the 1,550 retrieved records plus the five individually retrieved seeds (screening_log.csv). Function tagging at Tier 1 is inherited from retrieval: each eligible record carries the area of every query theme that returned it (the released query list of Section 2.2), so a record can hold several tags, and per-tag union shares are the pool-level baselines used in Section 3.3. The limits of that scheme are disclosed here rather than footnoted. 24 of the 799 eligible records carry no tag beyond the generic 'Other' (the equivalent-circuit-modeling queries map to no area); 202 carry no core-function tag at all (methodological or cross-cutting themes only); and against the subset's full-text function labels the tags match for 53 of the 75 core-area papers found in the pool (71%, counting a hit when any of a record's tags matches — a lenient criterion). Pool-level function baselines are therefore retrieval-based indicators rather than classifications, and are read for ordering, not for exact rates. *Tier 2 (classified subset).* Because in-depth coding of chemistry, data source, and validation practice requires full-text assessment, it was applied to a classified subset of 103 studies — 98 drawn from the eligible pool plus 5 seed studies retrieved and verified individually — and the subset's construction history is disclosed in full. A stratified draw first selected 107 candidates from the eligible pool, balancing the eight management functions and only partly balancing publication years — within each function stratum deterministic rather than random: records ranked by Crossref citation count and taken from the top of that ranking, with the ranking walked deeper specifically to cover recent publication years that citation sorting alone would have starved. Six landmark seed studies were safeguarded at this point (one already captured by the searches, five retrieved individually), giving 112 candidates. Full-text curation then excluded 19 records — corrigenda, misindexed records, scope mismatches (for example, vehicle-level lifecycle assessment or charging-infrastructure demand modeling without a BMS function), and quota-driven trimming of over-represented function clusters — while 10 targeted additions were made from the screened pool for under-represented themes, a net change of −9 that yields the final classified corpus of 103 studies — 98 drawn from the eligible pool plus the 5 individually retrieved seeds. Per-record reasons for every exclusion and addition are carried in the released screening log and selection files, so the funnel is auditable end to end. Readers should hold the implication of the design plainly in view: the subset is curated, not sampled — function and year distributions inside the 103 partly reflect the quota and citation-ranking choices made here, not only the field's shape — so all such distributions are reported as corpus composition, the subset is never generalized to the field, and the quota-free Tier-1 measurements are stated wherever they exist (Section 3).

Five interpretation rules govern every quantitative claim in this paper: (1) findings coded from full texts describe the classified subset and are never generalized to the field; (2) Tier-1 counts measure a capped retrieval, not a census; (3) 'earliest' means earliest in the classified subset; (4) non-significance is not equivalence; and (5) the subset's distributions are conditioned by its curation. The rules, their motivation, and the robustness audits that operationalize them are consolidated in the Supplementary Material (rules in S1; audits in S2–S5) and are invoked — by number, where a claim depends on them — throughout the paper.

Box 1 Terminology and count reconciliation (stated once; used throughout)

Eligible corpus (Tier 1). The 799 records admitted from the 1,550-record retrieval by the title gate and venue screen; tagged by retrieval theme only, never full-text coded.

Classified subset (Tier 2). The 103 studies coded from full texts: 98 drawn from the eligible pool plus five individually verified seed studies (one dated 2019; the 2019 seed is therefore part of the 103, not of the 799).

Primary and review-labelled papers. Primary papers: the 88 subset studies whose contribution is a primary application. Review-labelled: the other 15 — 12 method-family reviews plus 3 review-type syntheses coded under their dominant method family.

Family-coded papers. Studies carrying a method-family code, including the review-type syntheses — e.g. '24 physics-informed family-coded papers' = 22 primary + 2 syntheses.

Funnel. 3,000 fetched → 2,973 after document-type/year/title filters → 1,550 unique after deduplication → 883 after the title

gate → 799 after the venue screen → 98 selected for Tier 2 (+ 5 seeds) = 103 = 88 primary + 15 review-labelled. The 14-paper conference set is separate and descriptive (Supplementary Material S6).

Glossary. Tag share: the share of records carrying a tag, counting overlaps (a record with two tags counts in both), so shares can sum past 100%. Union: distinct records carrying at least one of the listed tags — the estimation complex's union is 366 of 799, while its per-tag counts sum to 394 because 28 records carry more than one estimation tag. Protocol-only vs broader stringency: the two definitions of Section 2.5 (strong = an isolating protocol; the broader definition additionally counts experimental-hardware demonstrations). Environment-only: validation that evidences an operating environment — hardware, simulation, or case study — without a data-isolation protocol. Absorbing rule: each paper is credited with the strongest protocol its full text reports for its headline claim (codebook); on full-text re-check, an unsupported stronger claim absorbs into the weaker class that is evidenced.




Fig. 2 Study-selection flowchart with the two-tier design. Records were retrieved from the Crossref REST API on 4–5 September 2026, deduplicated, screened at title level for battery and machine-learning relevance, then at venue and document-type level. Tier 1 includes every eligible record (799, rule-based, no quotas); Tier 2 carries the curated full-text-classified subset of 103 (98 drawn from the pool plus 5 individually retrieved seeds). Record-level provenance for all 1,555 screening-log rows is released (screening_log.csv), and every included record's metadata was verified by direct DOI resolution against the Crossref registry.

2.4 Inclusion and exclusion criteria

Table 1 summarizes the criteria. Inclusion required: (i) a peer-reviewed journal article; (ii) a battery or battery-system subject; (iii) machine learning as a substantive component of the contribution, whether estimation, control, diagnosis, or analysis; (iv) a Crossref date-stamp of 2020–2027 at retrieval — 798 records dated 2020–2026 plus one early-access record stamped to a February 2027 issue and disclosed in Section 3.1 — with a single 2019 exception, the field-defining early-life prediction study, admitted as a forced seed (Section 2.2); and (v) English language. Exclusion criteria were: review-only papers without a primary application (admitted to a cap of 12 and

assigned to the function cluster each reviews — four state-estimation, two fault-and-safety, two prognostics, one health-estimation, one thermal, and two cross-cutting reviews; three further review-type syntheses — two physics-informed, one classical, all cross-cutting — are coded under their dominant method family, so the corpus carries 15 review-labelled papers in total, and Table 3's Reviews column counts these 12 reviews plus the three syntheses (which is why that column shows five cross-cutting and totals 15), per the terminology of Section 2.5), pure materials-discovery or cell-design papers, charging-infrastructure or grid-demand studies without an onboard management function, preprints and conference records, and duplicate-venue or misindexed records.

Table 1 Inclusion and exclusion criteria applied during corpus screening

Dimension	Included	Excluded
Document type	Peer-reviewed journal articles	Conference abstracts/proceedings, preprints (SSRN), corrigenda
Subject	Batteries and battery systems with a management function	Materials discovery, cell design, grid/infrastructure demand modeling without BMS function
Method	ML as a substantive component (estimation, control, diagnosis, analysis)	Papers without a learning component
Period	Crossref date-stamps 2020–2027 at retrieval (798 records dated 2020–2026, one early-access record stamped 2027)	Pre-2020 publications, except the individually verified 2019 seed study admitted to the classified subset
Verification	Metadata confirmed by direct Crossref DOI resolution	Unresolvable or mismatched records
Language	English	Non-English

2.5 Classification framework

Each corpus paper was classified along six fields: (1) *management function*, with eight values — state estimation (SOC), health estimation (SOH), prognostics (RUL), charging control, thermal management, fault and safety, cell balancing and equivalent-circuit modeling, and a cross-cutting cluster for methodological and system-level themes; (2) *method family*, with values including classical ML (Gaussian process regression, support vector machines, random forests, shallow networks), deep learning (recurrent, convolutional, attention and graph architectures), physics-informed and hybrid model–data learning, optimization-augmented learning (Bayesian optimization, surrogate-assisted and meta-heuristic schemes), reinforcement and control learning, transfer and domain adaptation, and foundation models/LLMs; (3) *chemistry* (NMC, LFP, LCO, lithium-metal, lithium–sulfur, mixed, or unspecified); (4) *primary data source* (own laboratory cycling, public datasets, laboratory impedance spectroscopy (EIS), real vehicle or fleet data, simulation, or multiple sources); (5) *validation approach* (within-cell splits, cross-cell holdout, cross-chemistry or cross-domain transfer protocols, online/real-vehicle demonstration, experimental hardware, or simulation); and (6) a short coded summary of the headline finding and the principal limitation. A seventh, lighter field was added when this review's own checklist (item 6, Section 9.9) turned on its authors: a *baseline-comparison screen* recording whether a study's indexed abstract names a model-based or classical reference method — a Kalman-family filter (EKF/UKF), an observer, an equivalent-circuit or physics-based model, coulomb counting, or a classical regressor such as Gaussian-process regression — as a comparator, with values *none*, *mentioned*, and *stated same-data comparison*. It is coded from abstracts, not full texts; the released rubric (codebook.md) also defines the full-text version of the field for future work, and its results are reported with the validation audit in Section 3.4. The validation categories of field (5) are aggregated into three stringency tiers used throughout the paper. Under the *protocol-only definition*, a *strong* protocol is one whose design isolates the generalization claim: cross-cell holdout, cross-chemistry holdout, cross-domain holdout, and online or real-vehicle demonstration. *Weak* splits leak information between train and test: within-cell splits and k-fold cross-validation

without cell-level isolation. The remaining classes are *environment-only*: experimental-hardware, simulation, and single-system case-study demonstrations, which evidence an operating environment but not a data-isolation protocol; the *broader definition* of stringency additionally counts experimental-hardware demonstrations as strong. Every strong-protocol count in Sections 3 and 9 states which definition it uses, and review-labelled studies carry no primary validation. Classification was performed by the lead author with conservative coding from full texts: where a paper's specifics could not be established confidently, broader categories were assigned. The corpus/subset terminology — corpus paper, primary study, review-labelled, family-coded — and the full count reconciliation (1,550 retrieved → 799 eligible → 103 classified = 88 primary + 15 review-labelled) are stated once, in Box 1, and used consistently hereafter. Papers are assigned a single dominant value per field even where several apply. To probe the reliability of that coding, two co-author coders (S.S.I.A. and J.I.C., the second and third authors) later blind-re-coded a 30-paper stratified random sample (drawn by function and year band, seed-pinned) under the released codebook. The blinding was procedural rather than external: the coders are authors of this study; they coded without access to the released labels or to each other's sheets, from sheets locked and hash-tracked at completion, with a filed blinding memo documenting what each coder had opened before coding; but they are not independent of the paper, and their later author-contribution roles included verification of classifications and counts. Their access was uneven: coder B worked from 6 full texts plus 1 preprint (23 of 30 papers from abstracts only) and coder C from 2 full texts (28 from abstracts only), so the study measures abstract-level reproducibility of the coding, not full-text agreement. With those scopes stated, agreement passes the $\kappa \geq 0.66$ threshold on management function ($\kappa = 0.92$, bootstrap 95% CI 0.80–1.00), method family (0.88, CI 0.73–1.00), and primary data source (0.88, CI 0.72–1.00), and falls below it on chemistry (0.55, CI 0.16–0.83) and validation protocol (0.48, CI 0.31–0.65) — the two fields least often stated at abstract level. On the count-bearing strong-versus-non-strong bucket the two coders agree on 25 of 30 papers (raw agreement 83%, $\kappa = 0.52$, CI 0.09–0.84). Against the released labels their bucket kappas are 0.22 and 0.42, with the conservative weak-code fallback for unreported protocols — declared in advance by both coders — driving most of that gap. No fully independent full-text dual coding proved achievable — 19 of the 30 sample papers remain paywalled — so the strong/weak counts of Section 3 rest on a single full-text coding by the lead author, with three quantitative buffers: the label-noise sensitivity analysis that propagates the observed coder-versus-label disagreement into the headline counts (Section 3.4); an independent post-freeze re-code of the validation field at the best retrievable evidence level, reported with the validation audit in Section 3.4; and the complete release of per-paper labels, coder sheets, and the itemized disagreements, so that any reader can re-run, check, correct, or extend the coding. The post-freeze re-code deserves its own description, because it audits the frozen labels from the evidence side rather than measuring coder agreement: after the labels were frozen, the AI research assistant declared in the AI-use statement (coder D) attempted the validation field of all 88 primary papers and covered 46 with retrievable evidence (7 full texts, 39 abstracts), determinably coding 23, applying the codebook's absorbing rule and a dedicated 'not reported' code where the evidence states no protocol, from locked evidence sheets and before consulting the released per-paper labels; it is an audit by an AI coder at a mixed evidence level, not a human full-text dual coding, and it is reported as exactly that.

What the abstract-level round could not measure — agreement when the rules are explicit and the evidence is shared — a second round was designed to measure, on the second stage the protocol pre-declares for below-threshold fields (codebook revision, then one re-coded subset). The dispute session produced the v1.1 patch: a not-ML method code for physics-only estimators, a production-and-quality function code for manufacturing-QC papers, a field-stationary data code with a self-lab/EIS-lab tie-break, a dedicated 'not reported' validation code replacing the divergent weak-code fallbacks that had driven the low round-1 agreement on this field, and a fixed reading for cross-function reviews. Full texts were then sought for all 30 sample papers through OpenAlex, Unpaywall, Semantic Scholar, Europe PMC, OpenAIRE, Zenodo, and publisher routes; the shared evidence base that could be assembled comprises 10 full texts (among them the released code repository of the explainability-driven SOH study [31], whose data loaders and leave-one-battery-out splits are inspectable directly), 1 accepted-manuscript preprint, and 19 papers that remain abstract-only behind paywalls. Both coders then re-coded the same 30 papers from that shared base in a single session; the round-2 values therefore measure residual rule ambiguity of the revised codebook rather

than coder independence and are expected to exceed round-1 κ, which mixed rule disagreement with evidence-access disagreement; because the v1.1 patch was derived from this same sample's round-1 disputes and agreement was re-measured on that sample, the round-2 design is same-sample by construction; the two rounds are reported as complementary, not interchangeable. Under that scope, all five fields pass the 0.66 threshold at the 0.80 strong level: management function κ = 0.96, method family 1.00, chemistry 1.00, primary data source 0.96, and validation protocol 0.92 (Krippendorff α 0.92–1.00 across the five fields), with the count-bearing strong/non-strong bucket rising from 25 of 30 papers (83%, κ = 0.52) to 28 of 30 (93%, κ = 0.83). Four disagreement cells remain, each flagged in the released sheets: one is an evidence gap on a fact stated in no accessible text, two are defensible readings of ambiguous abstracts, and one is a genuine codebook-boundary cell — a digital-twin parameter-identification study that fits no management-function code cleanly, logged as a v1.2 candidate. Against the released labels, round-2 agreement is reported for context only and is mechanically capped: ten papers carry v1.1-only codes that cannot match the v1.0 released-label vocabulary by construction, and sixteen are coded to broader chemistry classes than the released specifics where no accessible text states the chemistry. The full-text reads did surface five candidate label corrections (among them two Severson-dataset papers whose released chemistry records NMC where the dataset itself is LFP, and one study whose released labels differ from its own released code repository on all five fields); these are itemized in the released dispute table, left unapplied, and queued for author adjudication — per-paper evidence in Supplementary Material S7 — so the released labels remain exactly as frozen and every count in Section 3 remains reproducible from them.

2.6 Comparative synthesis approach

The synthesis proceeds on two tracks. Quantitatively, the classification fields are aggregated into cross-tabulations — function by year, method family by year, chemistry, data source, and validation practice — that characterize the corpus as a sample of the field’s recent output (Section 3); every figure and every count in Section 3 was generated programmatically from the released dataset rather than compiled by hand; the full pipeline is publicly available in the repository accompanying this paper. Qualitatively, the review synthesizes each function’s literature critically: what each cluster of methods assumes, what it demonstrates, and where its evidentiary support is thin (Sections 4–8). Cross-referencing the two tracks then yields the gap analysis of Section 9.

The review-rigor posture of this study should be weighed against PRISMA-ScR practice as plainly as its coding limitations are, and two structural deviations are disclosed here rather than footnoted. First, screening was single-reviewer in design — with the qualification that its first two stages are deterministic rules rather than judgment calls: the title relevance gate and the venue screen are programmatic applications of released term lists, and the released screening log carries all 1,555 rows with their per-record reasons, so they are exactly reproducible but were not double-screened by a second human; the judgment-bearing stages (the full-text curation of 19 exclusions and 10 additions, and all classification) were likewise single-reviewer, and the only dual-coded element is the 30-paper reliability study, whose coders are co-authors of this paper (Section 2.5). Second, no per-record time-on-task logs were kept for any stage: retrieval ran on 4–5 September 2026, the rule-based screens execute in seconds and were verified spot-wise rather than re-screened record by record, and the human-judgment stages were not time-stamped, so effort cannot be audited after the fact. The protocol is registered retrospectively rather than prospectively: PROSPERO does not accept scoping reviews, so the registration was filed after completion on OSF Registries — which does accept them — as a retrospective registration, disclosed as such both there and here, with the as-registered content released verbatim in the repository (osf_registration/); because it is retrospective it cannot serve the pre-emption function that registration exists for, and the released pipeline files and their version history therefore remain the primary audit trail for the a-priori scope decisions. Tool assistance is bounded exactly as the AI declaration states — scripting, drafting, and figure generation only, plus the post-freeze AI-assisted label audit that Section 3.4 reports; no tool-assisted triage or ranking participated in screening, and the one ranking used (citation-count ordering within strata at Tier-2 selection) is a deterministic, released computation (Section 2.3). Against the PRISMA-ScR checklist the study therefore documents eligibility, charting, and synthesis transparently, carries a

disclosed retrospective registration, and falls short of dual independent screening — the remaining structural gap — so readers should weigh the released, re-runnable decision trail accordingly.

The methodology has limitations that readers should weigh. The corpus is drawn from Crossref-registered journal articles and therefore inherits that registry's coverage: influential conference papers (a significant venue for control-oriented BMS work) are excluded by design — a descriptive conference-venue probe released with the supplement (Supplementary Material S6) finds no evidence that this journal-only design understates stated validation evidence, but at 14 papers from six venues it cannot support inference, so the venue question remains open — and very recent articles registered with incomplete metadata may evade relevance screening. Title-level relevance screening can miss relevant papers whose titles avoid standard terminology, and citation-count ranking privileges English-language, high-profile venues. Classification reliability is documented on a 30-paper blind re-coding subset rather than measured corpus-wide: round 1 (independent evidence, mostly abstract-level access) passed three of five fields, and round 2 (revised codebook, shared evidence base, 19 of 30 papers still abstract-only) passed all five at the strong level while measuring agreement of rule application rather than independent full-text dual coding (Section 2.5); sensitivity ranges are reported throughout. The strong/weak taxonomy itself is design-only: it codes the isolation architecture of a study's headline validation, but not the execution details that decide whether that architecture delivers — how many cells (or chemistries, or vehicles) were actually held out, whether model selection or hyper-parameter tuning touched the test set, and whether preprocessing such as feature scaling, capacity normalization, or window construction was fit on the full dataset before splitting; a protocol coded strong can therefore still overstate generalization when its held-out set is small or its pipeline leaks, and held-out-set sizes are rarely stated in the published texts, so they cannot be systematically audited. The classified corpus is additionally quota-curated rather than sampled, and the pool has its own retrieval-design shaping (Supplementary Material S1, rules 1, 2, and 5); distributional statements in Section 3 are framed as corpus composition, with quota-free pool-level baselines stated where they exist. These limitations qualify the quantitative aggregates of Section 3, which should be read as a structured sample of the field's output rather than a census — and they are the reason this paper describes itself as a scoping review with bibliometric classification rather than as a meta-analysis.

3. Corpus Overview and Five-Year Evolution

3.1 Publication trend

Two layers of trend evidence are reported, and they are kept separate throughout. On the *measured* tier (eligible corpus, 799 records), the capped retrieval captures 55, 85, 139, and 223 journal articles for 2020–2023, then 56 for 2024 — an observed count inside the capped retrieval, not an estimate of missing volume: no query pass was dedicated to January–May 2024 — the mid-window and dedicated passes end in December 2023, the recency pass begins on 1 June 2024, and the citation-sorted pass returns almost nothing from 2024 (Section 2.2) — then 126 in 2025 and — partial year, retrieval date September 2026 — 114 in 2026, plus one further early-access record date-stamped 2027 by Crossref metadata and omitted from the year chart (Fig. 4, left panel). These are counts within a capped retrieval, not census totals, and they do not support absolute-growth claims: a per-year external denominator was tested and discarded, because Crossref's reported result totals for the same queries rely on loose token-level bibliographic matches whose totals run into the hundreds of thousands and vary strongly with query phrasing, so they are not interpretable as field denominators (the test script and its output are released). What remains defensible is direction within the sample: the eligible-corpus counts rise through 2020–2023, dip at the retrieval hole, and remain high in 2025–2026.

The corpus spans 2019–2026 with the following composition: 9 papers in 2020, 13 in 2021, 13 in 2022, 22 in 2023, 20 in 2024, 18 in 2025, and 7 in the partial year 2026 (retrieval date September 2026), plus the 2019 seed (Fig. 3). This profile should be read as the output of the sampling design, not as a measurement of field output. Three design choices shape it. First, the stratified draw of Section 2.3 only partly balanced publication years by construction — per-year counts in the subset span 7 to 22 papers — so year-to-year differences inside the subset are muted by design rather than observed. Second, the citation-ranked within-stratum rule preferentially captures highly cited

work. Third, the eligible pool itself has a retrieval-shaped year mix — the five query passes of Section 2.2 covered year windows unequally (a dedicated 2023 pass, a recency pass from mid-2024, older passes ending 2022), so the pool's own year profile (measured above) reflects query coverage as much as publication. Neither level supports a claim that field output rose, fell, or accelerated; what the composition does show, within those limits, is a broadening from single-function estimators toward cross-cutting system-level contributions in the recent quotas.

Citation weight tells a complementary story about influence. Citation counts throughout this paper are the Crossref registry's is-referenced-by-count values retrieved on 5 September 2026 and are included per paper in the released dataset; they are typically lower than Google Scholar counts for the same paper and should be compared only against themselves. The corpus accumulates roughly 18,400 recorded citations, but the distribution is steeply skewed: the median paper has 65 citations, while the 2019 seed alone holds 3,002 and the two 2020 landmark studies (Battery Lifetime Prognostics [2] and closed-loop fast charging [4]) hold 1,239 and 1,078 respectively. Median citations fall monotonically with publication year — from 441 (2020) through 141 (2022) and 46 (2024) to single digits for 2026 publications — which is partly an age effect and partly evidence that the field's attention concentrates on a small set of canonical results. For a scoping review this skew matters: narrative reviews that emphasize highly cited work systematically describe the field as it stood in 2020–2021, whereas the recent relevance-sorted portions of this corpus capture the current working frontier that citations have not yet caught up with.




Fig. 3 Corpus composition by publication year (bars, left axis) with cumulative total (line, right axis). The 2019 seed study is included in the cumulative count. Years were only partly balanced by the sampling design of Section 2.3, so the profile is corpus composition, not a field-output trend (Section 3.1).

3.2 Method-family evolution

The compositional shift in method families across the corpus (Fig. 4, Table 2) is a within-corpus observation under the quota design of Section 2.3, not a field-level growth measurement. Classical ML — Gaussian process regression, support vector machines, ensemble regressors, and shallow networks on engineered features — dominates the early corpus: 12 of the 23 papers published from 2019 through 2021. Deep sequence models (LSTM, gated recurrent unit (GRU), CNN, attention, and graph architectures) rise through 2022–2023 and remain the largest single family for prediction tasks thereafter. Physics-informed and hybrid model–data learning — including physics-informed neural networks (PINNs), physics-constrained autoencoders, filter-embedded networks, and multiphysics-ML fusion — emerges in 2021–2022 and grows steadily: counted year by year, the family contributes 1, 2, 3, 3, 4, 4, and 5 primary papers in 2020–2026 — the only multi-year family with a monotonically non-decreasing primary trajectory

within the subset, with 2026 a partial year at the September 2026 retrieval — so that 13 of its 22 primary papers fall in 2024–2026 and it is the largest single family among the 7 papers published in 2026 (24 family-coded papers including two review-type syntheses; Table 2 gives the primary totals; Fig. 4 the yearly counts). Optimization-augmented learning (Bayesian optimization for protocol design, surrogate-assisted multi-objective schemes, and meta-heuristic-tuned networks) peaks in 2024 (5 of its 11 papers). Transfer and domain-adaptation approaches appear consistently from 2022 and accelerate in 2024–2025 (3 of its 5 papers), reinforcement learning remains scarce but visible (1 primary paper, with RL embedded in further studies), and the subset's first foundation-model and LLM-based studies appear in 2026 (2 papers) [14, 15] — earliest in the classified subset, not in the field: earlier journal-published LLM estimators exist and were missed by this retrieval (Section 8.4).

Table 2 Method families: representative techniques, strengths, and limitations. Counts are the 88 primary-application papers; the three review-type syntheses coded under a method family plus the 12 method-family reviews are accounted for in the function-by-year composition table. Abbreviations: SVM, support vector machine; SVR, support vector regression; LSTM, long short-term memory; GRU, gated recurrent unit; CNN, convolutional neural network.

Method family	Papers	Representative techniques	Strengths	Limitations
Classical ML	28	Gaussian process regression, SVM/SVR, ensembles, shallow networks on engineered features	Native predictive distributions (calibration must be verified empirically); small-data friendly; cheap to embed	Feature engineering is manual; ceilings under complex dynamics
Deep learning	19	LSTM/GRU, CNN, attention/Transformer, autoencoders, graph networks	Learns features from raw curves; strong trajectory modeling	Data-hungry; weak extrapolation; opaque
Physics-informed / hybrid	22	PINNs, physics-constrained autoencoders, filter-embedded networks, multiphysics fusion	Structure aids extrapolation; reduced data demand	Inherits simplified-model bias; harder to train
Optimization-augmented	11	Bayesian optimization, surrogate-assisted multi-objective design, meta-heuristic-tuned networks	Sample-efficient protocol discovery; explicit trade-off handling	Offline tuning cost; surrogate bias
Transfer / domain adaptation	5	Domain-adversarial training, fine-tuning across chemistry/protocol	Directly targets the generalization gap	Negative transfer; needs shared protocols
Reinforcement / control learning	1	Deep-RL prognostic model selection (also an embedded component in further studies)	Adaptive decision-making along trajectories	Training stability; scarce hardware validation
Foundation models / LLM	2	LLM incident-risk analysis; LLM-based SOH estimation with uncertainty-gated physics fallback	Reasoning over heterogeneous text/system context; transferable priors	Hallucination risk; latency and cost
Review / perspective	12	Narrative and systematic syntheses	Maps the field; identifies shared gaps	No primary validation

Within-family dynamics deserve comment. The persistent classical-ML share is not inertia: Gaussian process regression survives because it natively returns a full predictive distribution — the property certification-minded applications most need, though calibration under kernel or model misspecification is not automatic and must be verified empirically — and because feature-based estimators remain the cheapest to embed. The deep-learning share consolidated around recurrent and attention architectures for trajectory data and convolutional architectures for curve data, with graph networks appearing where cell-to-cell or feature-to-feature relations matter. The

optimization-augmented family grew along two distinct branches: meta-heuristically tuned networks (particle swarm optimization (PSO), genetic algorithms (GA), and swarm variants), which improve accuracy at a documented training cost, and Bayesian or surrogate-assisted optimization of *operating protocols*, which changes what can be experimentally discovered rather than merely what can be predicted. Conflating these two branches, as broad-brush surveys tend to do, obscures the more consequential of the two developments.




Fig. 4 Left panel: the measured eligible corpus per publication year (Tier 1, n = 799; capped retrieval, Section 3.1; one further record is date-stamped 2027 by Crossref and not shown). Right panel: method-family composition of the classified subset by publication year (Tier 2, paper counts; the 12 method reviews are shown as their own band, while the 3 review-type syntheses sit inside their family bands — which is why the physics-informed band exceeds the primary-only trajectory stated in the text); yearly totals match the corpus totals of Table 3. Composition of the curated subset under the Section 2.3 quota design; not a field-level trend measurement (Section 3.2).

Three observations qualify this trajectory. First, the families are not mutually exclusive in practice — a PSO-tuned LSTM is simultaneously deep learning and optimization-augmented learning — and the corpus classification assigns each paper to its dominant family; the composition therefore understates method mixing. Second, the rise of physics-informed learning is partly a response to the recognized brittleness of purely data-driven models under distribution shift, but physics-informed papers in the corpus show no detectably different validation stringency from the others — a nominally lower strong-protocol rate that this corpus is underpowered to resolve, quantified in Section 3.4. Third, the foundation-model cluster is too small to represent a trend; its significance is that LLM-based management (fleet risk analysis and LLM-based health estimation, Section 8.4) is appearing in mainstream energy journals at all. A pool-level cross-check bounds these observations: among the 799 eligible records, the physics-informed query theme tags 1, 10, 12, 18, 2, 3, and 9 records in 2020–2026 — 1.8%, 11.8%, 8.6%, 8.1%, 3.6%, 2.4%, and 7.9% of each year's eligible records — non-monotonic and peaking in 2021, so no field-level physics-informed rise is measurable at either tier (the 2024 trough and the partial-year 2026 count both sit inside unequal retrieval windows), and the family trajectories of this section describe the curated subset alone.

3.3 Application-area distribution

Functionally, the corpus is dominated by the health-prognostics complex: health estimation (20 papers) and remaining-useful-life prognostics (15) together account for 34% of the 103-paper corpus, followed by the cross-cutting cluster (24, including reviews, physics-informed methods, interpretability, transfer learning, digital twins, cloud/fleet themes, and foundation models), state estimation (17), fault and safety (9), charging control (8), thermal management (8), and cell balancing/ECM (2) (Fig. 5). Fig. 5 matches the all-corpus totals of Table 3 (103 papers); Fig. 1, by contrast, is drawn over the 88-paper primary-application corpus and excludes the 15 review-labelled papers, with the per-function reconciliation stated in that figure's caption and in Table 3's Reviews column. Because these shares are conditioned on the sampling quotas (Section 2.3), the quota-free eligible pool provides the check. Its query-theme tags (their derivation, lenient validation, and untagged-record counts are disclosed in Section 2.3) give health estimation 158, state estimation 133, prognostics 103, thermal management 99, fault and safety 96, charging

control 64, and cell balancing 38 of 799 records. Together, the three estimation functions tag 366 of the 799 records (45.8%) — the retrieval's center of gravity: a property of what the capped retrieval and its query families surfaced, not a field-level prevalence; the per-tag figures remain ordering indicators rather than exact rates (Section 2.3). The pool confirms the same ordering at the top: the health-prognostics complex dominates, consistent with the commercial pull of lifetime prediction for warranties and second-life markets. It also confirms the same floor — balancing is the smallest core function at pool level as well as in the subset, so its thin representation is a property of the retrieved literature rather than an artifact of the quotas, and ML has so far contributed mainly at the level of pack-level insight rather than as a balancing controller — the corpus's most-cited balancing-related result is a single contrarian study reporting that routine balancing can be dispensed with in well-managed packs, reducing hazardous lithium-plating side reactions [32] — reproduced here as one study's claim, not as an established result. Thermal management, by contrast, is not scarce at pool level (99 tagged records, comparable to fault and safety): the subset's small thermal count reflects the coding scheme — thermal-runaway papers are coded under fault and safety — and the curation quotas, not field scarcity; the genuine thermal deficit is evidential rather than topical, since no subset paper yet closes the thermal control loop on hardware (Section 7.1).

Table 3 Corpus composition: management function by publication year. The Reviews column counts the 12 method-family reviews plus the 3 review-type syntheses coded under their dominant method family; Primary = Total − Reviews is the 88-paper primary-application count used in Fig. 1.

Function	'19	'20	'21	'22	'23	'24	'25	'26	Total	Reviews	Primary
Cell balancing & ECM	0	0	0	0	1	1	0	0	2	0	2
Charging control	0	2	0	0	2	3	1	0	8	0	8
Cross-cutting	0	1	0	6	8	3	2	4	24	5	19
Fault & safety	0	0	2	0	2	3	2	0	9	2	7
Health estimation (SOH)	0	2	3	2	4	3	4	2	20	1	19
Prognostics (RUL)	1	1	3	2	1	1	6	0	15	2	13
State estimation (SOC)	0	3	4	2	1	5	2	0	17	4	13
Thermal management	0	0	1	1	3	1	1	1	8	1	7
Total	1	9	13	13	22	20	18	7	103	15	88

Chemistry and venue concentration complete the corpus profile. NMC-type cells anchor 54 of the 88 primary studies (61%) and LFP 15 of them (the 15 review-labelled studies carry no cell-chemistry code, so chemistry counts are primary-study statistics); the remainder split across LCO, lithium-metal, lithium–sulfur, mixed panels, and unspecified chemistries — a distribution that mirrors EV market share but leaves sodium-ion, solid-state, and high-temperature systems nearly absent from the ML-management literature. Venue concentration is equally marked: the Journal of Energy Storage (15 papers), Energy (13), and Applied Energy (9) head the corpus, with Journal of Power Sources, Energy Storage Materials, and Reliability Engineering & System Safety following; IEEE venues account for 7 of the 103 papers, three of them in IEEE Transactions on Transportation Electrification. The pool shows the same shape — Journal of Energy Storage 103, Energy 61, and Batteries 45 of 799 records, with IEEE-prefixed venues at 9.0% — so for readers the practical consequence is that the ML-BMS literature's center of gravity sits in energy-systems journals rather than in machine-learning venues: partly a statement about where this work is reviewed and indexed, and partly a Crossref-registry artifact (Section 2.2), rather than evidence about how impact is achieved in this field. A final measured cut matters specifically for readers working on transportation electrification: only about 2% of eligible records (n = 17) carry fleet- or cloud-orchestration-adjacent tags, and in the classified

subset only 10 of the 88 primary papers use real vehicle or fleet data as their primary source, against 36 resting on laboratory cells. The classified literature is thus predominantly cell-level and laboratory-scale — one integration level below the pack- and vehicle-level questions that UN GTR 20, GB 38031, and ISO 26262 pose; Section 9.4 maps that mismatch requirement by requirement.




Fig. 5 Application-area distribution of the corpus (n = 103 classified studies; shares are conditioned by the Section 2.3 quotas — Supplementary Material S1). The cross-cutting cluster includes reviews, physics-informed learning, interpretability, transfer learning, digital twins, cloud and fleet management, and foundation models.

3.4 Data landscape and validation practice

The data underpinning the corpus are strikingly concentrated (Fig. 6, Table 4). Thirty-six papers rely primarily on laboratory cycling of the authors' own cells; the public Severson/Toyota-MIT–Stanford (MATR) cycle-life dataset alone supports 11 papers, NASA and CALCE datasets support 6 each, and laboratory impedance spectroscopy 6 — 42 private-laboratory papers in all; 10 papers use real vehicle or fleet data as their primary data source — a distinct measure from the 8 studies whose *validation* is an online or real-vehicle demonstration (9.1%; Wilson 95% CI 4.7–16.9%); 12 are simulation-based (computational fluid dynamics (CFD) or electrochemical models); and 15 are reviews or perspectives that synthesize rather than generate data. Chemistry reporting is similarly skewed — and, because the 15 reviews carry no cell-chemistry code, is a property of the 88 primary studies: 54 of them (61%) work on NMC-based cells, 15 on LFP, and the remainder on LCO, lithium-metal, lithium–sulfur, mixed panels, or unspecified chemistries.

Validation practice — arguably the field's most consequential weakness — is summarized in Fig. 6 (right panel), and it is now defined and audited explicitly (Section 2.5). Under the protocol-only definition, the *strong protocols* — cross-cell holdout (24 papers), cross-chemistry holdout (7), cross-domain holdout (3), and online or real-vehicle/fleet validation (8) — together cover 42 of the 88 primary-application papers (48%; Wilson 95% CI 37.6–58.0% — an interval over a curated subset, reflecting its selection as much as sampling). At the weaker end, 12 papers use within-cell splits (training and testing on interleaved segments of the same cell's life), 5 use k-fold cross-validation without cross-cell isolation, and 15 are reviews without primary validation; the remaining 29 primary papers establish an operating environment (experimental hardware, 20; simulation or case-study evidence, 9) without a data-isolation protocol. The complete per-paper protocol assignment is released (protocol_audit.csv, and the valid field of papers.csv), so the 42-of-88 arithmetic can be verified row by row. Three audit layers bound these counts, and their mechanics are stated once — the protocol in Section 2.5 and the per-paper evidence in Supplementary Material S7 — so only the results are repeated here. The round-1 blind re-coding is an abstract-level agreement check, not a re-derivation (bucket agreement with the released labels $\kappa = 0.22$ and 0.42); the round-2 re-coding under the revised codebook lifts the coders' mutual bucket agreement to 28 of 30 papers (93%, $\kappa = 0.83$)

while remaining an agreement measure; and the post-freeze evidence-side re-code (coder D, Section 2.5) determinably covers 23 of the 88 primaries — confirming 10 of the 14 determinable strong labels, contradicting 4 (one full-text-verified within-cell split, one synthetic-data validation, two abstract-level evidence gaps), and supporting 2 upgrades of non-strong labels — for a bucket agreement of 17 of 23 (74%, κ = 0.47, Wilson 95% CI 53.5–87.5%). No released label was altered: every challenge and upgrade is itemized with its evidence (validation_recode.json, dispute_items_fulltext.csv; per-paper detail in Supplementary Material S7), the 42-of-88 count remains the lead author's single full-text coding, and the corrections the itemization supports stay flagged author decisions rather than silent edits.

Because fleet-data *use* and online *validation* are different measures, Table 6 cross-tabulates them: of the 10 papers whose primary data are real-vehicle or fleet streams, 8 are online-validated and 2 are validated by cross-domain holdout or case-study protocols instead (a laboratory-data paper whose online claim was a desktop demonstration was recoded to experimental hardware after full-text re-check). This distribution quantifies a widely acknowledged but rarely measured problem: the majority of published accuracy claims are established under laboratory regimes that differ from deployment in chemistry coverage, temperature envelope, current-profile realism, and sensor quality — a gap that recurs throughout Sections 4–8.




Fig. 6 Primary data sources (left) and validation approaches (right) across the corpus. Public-dataset reliance concentrates on the Severson/Toyota (MATR), NASA, and CALCE benchmarks; online or real-vehicle validation remains rare.

Table 4 Benchmark datasets and data sources recurring across the corpus

Data source	Papers	Typical use in corpus
Own laboratory cycling	36	Primary training/testing data for estimators and protocols
Severson/Toyota–MIT–Stanford (MATR)	11	Cycle-life and early-life prediction benchmarks
NASA PCoE	6	Capacity-fade and RUL benchmarking
CALCE	6	SOH estimation and degradation modeling
Laboratory EIS	6	Impedance-based SOH/SOC and degradation-mode studies
Real vehicle / fleet data	10	Online SOH, anomaly detection, cloud BMS
Simulation (CFD/electrochemical)	12	Thermal design, charging optimization, runaway prediction
Review synthesis (no primary data)	15	Methodological and thematic reviews
Multiple datasets	1	Studies drawing on several of the above

Validation practice deserves its own cross-tabulation because it moderates every accuracy claim in the corpus (Table 5). Cross-cell holdout — training on some cells and testing on unseen siblings — is the strongest widely used laboratory protocol (24 papers), and the transfer protocols make the strictest demands (10 papers: 7 cross-chemistry, 3 cross-domain — the seven cross-chemistry validators are the studies behind the ‘validated across chemistries’ count of the preceding paragraph). At the weaker end, within-cell splits (12 papers) and unsupervised k-fold cross-validation (5 papers) leak trajectory information between train and test sets and can thereby produce optimistic errors that need not survive cell-to-cell variability; the review literature has long warned of this, and the corpus quantifies how prevalent such splits are. Experimental-hardware demonstrations (20 papers) and online or real-vehicle demonstrations (8 papers) anchor the deployment end of the spectrum — it is these, not the largest architectures, that carry the field’s deployment evidence. Crossing validation practice with method family: 8 of the 22 physics-informed/hybrid primary papers (36%) use a strong protocol, against 34 of the 66 other primary papers (52%) — Fisher’s exact $p = 0.32$, odds ratio 0.54 (95% CI 0.21–1.46); under the broader definition of stringency (Section 2.5) that also counts experimental-hardware demonstrations, the contrast is 13 of 22 (59%) versus 49 of 66 (74%), $p = 0.19$. No difference is detectable at this scale, and none should be read as equivalence: the contrast is underpowered (80% power would require a gap of roughly 30–35 percentage points; Supplementary Material S3), and a label-noise scenario analysis that perturbs the single-coder labels directly brackets the strong-protocol share between 11% and 59% across its two scenarios — the strong-to-weak floor, about 18% at the observed abstract-level recode rate, is a worst-case bound rather than an estimate (Supplementary Material S2). Under both scenarios the physics-versus-other contrast remains non-significant in at least 94% of draws.

The full cross-tabulation of method family by validation class makes the pattern concrete (Table 2 gives the family totals). Classical learning accounts for 28 primary papers and uses a strong isolation protocol in 19 of them (68%); deep learning follows at 9 of 19 (47%); physics-informed and hybrid schemes at 8 of 22 (36%); and optimization-augmented learning — Bayesian optimization, surrogate-assisted, and meta-heuristic schemes — at 0 of 11. The optimization-augmented cluster is instead validated by physical demonstration: six of its papers exercise experimental hardware, three rest on simulation, one combines simulation with hardware spot-checks, and one uses k-fold cross-validation. The single reinforcement-learning paper is validated within-cell, and the two foundation-model papers split between one online demonstration and one case study. Transfer learning is the mirror image: all five of its papers validate on isolation protocols (three cross-chemistry, two cross-domain), because its research object is generalization, so its experiments test it. The audit thus exposes a two-culture split in validation practice: the families whose outputs are estimates are exercised on held-out isolation, while the family that actuates the battery is exercised on physical demonstration. The split is consequential for deployment, because the charging and thermal clusters — where learned strategies act directly on the pack — carry no strong isolation protocol at all: 0 of 8 and 0 of 7 primary papers, respectively (Table 9), with demonstration- or simulation-based evidence throughout.

Data sources and chemistry stratify the same evidence by function. The SOC cluster's 13 primaries rest almost entirely on the authors' own laboratory data — 12 private-laboratory sources (own cells or laboratory impedance) and one simulation — with no public-benchmark and no real-vehicle source. The SOH/RUL complex of 32 primaries mixes 16 public-benchmark with 11 private-laboratory sources, alongside 4 real-vehicle sources and 1 mixed-source study. Charging (8) splits evenly between private cells and simulation (4 and 4); thermal (7) is simulation-dominated (5 of 7, the other 2 on laboratory hardware); and fault and safety is the only cluster whose modal primary source is real-vehicle data (3 of 7). Chemistry concentrates correspondingly: NMC cells dominate 54 of the 88 primary papers (61%), and the thermal-management primaries are NMC in all seven cases, so heat-generation and thermal-runaway evidence for other chemistries is thin in this subset. Both matrices can be re-derived from the released papers.csv.

Table 5 Validation practices across the corpus

Validation approach	Papers	Interpretation
Cross-cell holdout	24	Strongest common laboratory protocol; unseen sibling cells
Experimental hardware	20	Physical validation of estimator or controller behavior
Review synthesis	15	No primary validation applicable
Within-cell split	12	Can be optimistic; trajectory leakage between train and test
Online / real-vehicle	8	Deployment-relevant evidence; rarest strong protocol
Cross-chemistry holdout	7	Strictest generalization demand in corpus
k-fold cross-validation	5	Can be optimistic without cell-level isolation
Simulation (+ hardware spot-check)	8	Model-fidelity dependent; strongest when hardware-checked
Cross-domain holdout	3	Transfer-specific evidence
Case study	1	Single-system demonstration

Table 6 Cross-tabulation of fleet-data use against online validation (103 classified papers). Fleet-data use describes the primary data source; online validation describes the validation protocol; their overlap is 8 of 10 fleet-data papers. A laboratory-data online demonstration was recoded to experimental hardware after full-text re-check (per the codebook's absorbing rule, Box 1). The right-hand column pools the environment-only validation categories defined with the classification framework.

	Online / real-vehicle validation	All other validation protocols	Total papers
Real-vehicle / fleet data	8	2 (cross-domain holdout; case study)	10
Other data sources	0	93	93
Total	8	95	103

Reading Fig. 6 and Tables 4 and 5 together yields the section's headline: the field's data supply is narrow, and its validation habits are calibrated to that narrowness. Public benchmarks made cumulative progress possible — the Severson dataset alone catalyzed a family of early-prediction methods — but they now also cap the credibility of reported generalization. The studies that escape this trap are precisely those that treat data sourcing and validation design as the research contribution: the multi-cell pipeline studies, the fleet-data health estimators, and the transfer-learning frameworks.

The concentration can be stated as a metric. Across 2019–2026, 23 primary papers — 26% of the 88 primary-application papers — rest on the same three public benchmarks (MATR, NASA, CALCE; Fig. 7). These benchmarks together contain on the order of a few hundred cells, while 36 further papers rest on private laboratory data that are rarely released: the empirical base is therefore not one benchmark monoculture but two poles — a small set of shared benchmarks onto which comparative claims crowd, and many unshared laboratory datasets over which accuracy claims cannot be audited at all. Subset output per year went from single digits in 2019–2020 to 18–22 papers in 2023–2025 — a profile shaped by the year-stratified selection design (Section 3.1), not a measured field trend — while benchmark reuse fluctuates between 1 and 7 papers per year with no trend, so no saturation dynamic is claimed; the structural finding is this two-pole data fragmentation, which inflates apparent comparability on the shared pole and precludes reproducibility on the private one.




Fig. 7 Benchmark reuse versus classified-subset output. Papers in the classified subset using the three dominant public benchmarks per year (stacked bars, left axis) against classified-subset papers per year (line, right axis). Both series describe the curated 103-study subset, not the eligible corpus; benchmark reuse fluctuates year to year rather than tracking output.

Two further audits bound what the subset statistic means, and both are reported in full in the Supplementary Material (S5). An abstract-level representativeness probe asks whether the curated subset overstates validation evidence relative to the pool it was drawn from: none of the 18 primary-looking records in a 40-record seed-pinned sample of the eligible pool states an isolation or deployment protocol in its indexed abstract, against 5 of the 38 abstract-screenable subset papers (Fisher's exact $p = 0.16$). The finding is negative in a useful way — indexed abstracts almost never carry enough protocol information to code validation strength at pool scale, in either tier — so the 48% strong-protocol share cannot be promoted from a curated-subset statistic to a field estimate without full-text access, and the scarcity of protocol statements in abstracts is itself part of what the reporting checklist of Section 9.9 responds to. A baseline-comparison screen then asks whether ML studies benchmark against model-based methods at all: of the 38 abstract-screenable primary papers, 32 (84%) name no model-based or classical baseline, 2 name one without stating the comparison, and 4 (11%) state a same-data quantitative comparison. These are lower bounds on comparison practice (full texts may compare what abstracts omit) but exact measures of comparison visibility, and visibility is what a reader scanning the literature actually has: at abstract level, the field's answer to 'does the learned estimator beat the model-based baseline on the same data?' is, four times in five, unstated.

4. Machine Learning for Battery State Estimation

4.1 From filters to recurrent networks

SOC estimation remains the most mature BMS function, and the corpus shows how machine learning entered it. The early-corpus pattern pairs learning with classical state estimation: Gaussian process regression for pack-level SOC with native uncertainty quantification [33], and — most influentially — recurrent networks embedded in unscented Kalman filters, where the LSTM supplies a learned observation model and the filter supplies the recursive correction [5]. Pure data-driven branches developed in parallel: support vector and ensemble regressors on engineered features benchmarked under automotive drive cycles [34], and simulation-informed training pipelines that substitute automotive-accurate simulated data for exhaustive cell testing [35]. Reviews of this first generation conclude that deep-learning SOC estimation is accurate on well-sampled data but suffers from weak interpretability and inconsistent benchmarking [17, 18].

A second generation tuned network structure itself. Particle-swarm-optimized LSTM improved accuracy and current-noise robustness over vanilla recurrent baselines [36], and evolutionary-assisted CNN–BiLSTM hybrids report sub-1% drive-cycle SOC errors [37]. This optimization-augmented family illustrates a recurring pattern of the corpus: gains are real but modest, and the meta-heuristic component is tuned offline while adding training cost — an investment that only pays at deployment if the estimator's life is long. Robustness-oriented work addresses pack heterogeneity directly, jointly estimating pack SOC and cell inconsistency with balancing-aware formulations [38], large-format applications extend estimation to containerized energy-storage strings with relaxed sensing [39], unified frameworks estimate SOH and SOC jointly from partial charging data [40], and comparative benchmarks weigh accuracy against the computational budget of electrified powertrains [41, 42].

Two features of this cluster stand out against the rest of the corpus. First, within the classified subset, SOC is where classical estimation theory and machine learning remain most durably fused: the filter-embedded pattern [5] recurs across the five-year window in increasingly sophisticated forms, whereas the other functions hybridize mainly through physics-model priors rather than recursive filters (Sections 5.4 and 8.1). This is a statement about the subset's composition, not about the field: a substantial particle-filter-based hybrid RUL literature — classical prognostic filters carrying learned degradation or observation models — sits largely outside this capped retrieval (Sections 2.2 and 5.4), so 'only' would claim more than the corpus can support. Second, SOC papers report the corpus's most standardized evaluation — drive-cycle profiles at room temperature with RMSE or mean absolute error (MAE) in percent SOC — which makes their benchmarks legible even where the underlying datasets remain private. The cost of that legibility is convergence: with every paper evaluating on the same standard cycles, the marginal contribution of a new architecture is shrinking, and the cluster's research attention is shifting toward robustness conditions — noise, sensor faults, temperature, and aging shift — where the standard benchmarks are silent.

4.2 Hybrid and physics-informed estimation

The most substantive recent shift in SOC estimation is the move from purely learned estimators to hybrid schemes in which a filter, an equivalent-circuit model, or a physics prior constrains the learner. GA-optimized LSTM networks coupled with improved adaptive Kalman filtering reach low error under measurement noise that breaks pure-network estimators [43]; equivalent-circuit-informed ML on impedance features estimates SOC across temperatures [44]; and physics-informed recurrent structures embed battery dynamics directly into the network's training objective [10]. These schemes trade engineering complexity for extrapolation behavior. Their authors' stated rationale is that the physics component carries structure that does not need to be relearned, so degradation outside the training envelope should be gentler than a pure learner's — the property that matters most onboard; the corpus can verify the premise of that argument but not its conclusion, because no study in the subset measures out-of-envelope degradation directly, and the validation audit (Section 3.4) detects no difference in protocol stringency between hybrids and purely data-driven peers.

4.3 Critical assessment

The SOC literature of the corpus is accurate but inward-looking. Reported errors are consistently low on the standard drive cycles, yet 12 of the 13 primary SOC papers rest on laboratory-scale data (11 on the authors' own cells, one on laboratory impedance measurements), 9 of the 13 on a single cathode chemistry (NMC), and the thirteenth is a simulation-based EV study [35]; the cluster's only operation-scale demonstration — a stationary containerized storage system rather than a vehicle [39] — is itself coded on laboratory data under the released labels, with its re-reading as field-stationary data logged among the codebook patch candidates. The review literature itself identifies the consequence: benchmark heterogeneity makes cross-paper comparison nearly meaningless, and generalization across temperature, chemistry, and aging state remains weakly evidenced [1]. The SOC function is, in other words, an area where the laboratory-regime estimation problem is, by reported metrics, effectively addressed — though those metrics are not comparable across papers (Section 5.6) — while the deployment problem — guaranteed accuracy on arbitrary packs over full aging — has not.

State estimation is also where the corpus's two sensing-hardware threads meet the software thread. Impedance-based SOC estimation demonstrates that electrochemical information beyond terminal voltage can drive estimation when EIS is available [44], while the ultrasonic-sensing line proposes non-electrical channels that could in principle be integrated into pack hardware at automotive cost [45]. Both remain laboratory-bound for cost and durability reasons, but they mark the boundaries of a design space — better software on existing sensors versus new sensors for better software — that the wider BMS industry is actively exploring.

5. Machine Learning for Health Estimation and Prognostics

5.1 Feature engineering and classical estimators

SOH estimation and RUL prediction form the largest functional block of the corpus (32 primary papers: 19 SOH, 13 RUL; 35 including review-labelled studies). The founding pattern is classical: extract health-sensitive features from partial charge or discharge curves, then regress with Gaussian process or similar shallow models. Incremental-capacity analysis with Gaussian process regression established the template with explicit uncertainty bounds [46]; differential thermal voltammetry extended the feature space to thermal signatures [47]; and deep Gaussian processes coupled capacity prognosis with degradation-mode identification [48]. Relaxations of the measurement burden followed: random partial charging data proved sufficient for accurate SOH [49], and charging-segment adjustment refined features for vehicle-level use [50]. The landmark systematization of this generation is the 179-cell machine-learning pipeline of Roman et al., which showed that relaxed charge-curve features support accurate, uncertainty-quantified SOH estimation across a heterogeneous commercial-cell fleet [51].

The feature taxonomy underlying this generation is worth making explicit because it explains both the cluster's strengths and its brittleness. Incremental capacity and differential voltage features transform charge curves into peaks whose positions and areas track degradation mechanisms; differential thermal voltammetry adds the temperature dimension; and partial-charging features deliberately sacrifice completeness for practicality, accepting any sufficiently informative voltage window. The approach assumes that the feature-to-health mapping is stable across the cells used for training — an assumption that holds within a cell model and laboratory but weakens across manufacturers, formats, and field profiles. The 179-cell pipeline study is important precisely because it tested that assumption at fleet scale within one commercial technology, and its success should not be over-read as license to transfer features across technologies [51].

5.2 Deep sequence and cross-cell models

Deep architectures entered prognostics as sequence models over capacity-fade trajectories and as representation learners over raw curves. Graph convolutional networks fuse multiple health indicators for joint SOH/RUL prediction [7]; BiLSTM–Transformer hybrids track health under the specific stress of fast charging [8]; hybrid-fusion networks target real-time prediction streams [52]; graph neural networks over partial discharge curves improve cross-cell generalization [53], and interpretable deep learning couples accuracy with transparency mechanisms [54]. A particularly important line uses real-world vehicle data rather than laboratory cycling, demonstrating that deep estimators can absorb field-data noise [6], and pack-level fusion methods now estimate SOH directly from fleet charge streams [55]. At the field's high end, a Nature Communications study showed that deep models can estimate SOH without additional degradation experiments by learning trajectory features that generalize across chemistries [56].

5.3 Early-life prediction

Early-life prediction — forecasting lifetime from the first cycles — is the corpus's most consequential methodological export to practice, because it compresses test times from months to days. Beyond the founding study [3], charge-process features predict cycle life across diverse duty cycles [57], ML frameworks extract lifetime information from formation-style tests [58], hybrid physics-plus-learned models give early RUL from limited cycles [59], and discharge-voltage features extend the approach to lithium-metal chemistries [60]. Board-level implementations close the loop to hardware, predicting capacity and RUL on embedded platforms in real time [61].

The economics of early-life prediction explain its rapid uptake: formation and initial cycling are already performed on every production cell, so early-prediction features are available for free at the point of manufacture, and warranty structuring, second-life triage, and cell matching all become data products. The methodological caveat is selection: cells that reach the secondary market, and cell batches that survive manufacturing screens, are conditioned samples whose early-cycle feature distributions differ from the training population. No corpus paper yet quantifies this survivorship effect, which makes it one of the more consequential open measurement problems in the cluster.

5.4 Physics-informed and hybrid prognostics

The prognostics cluster shows the corpus's most visible physics-informed turn. Physics-informed online degradation models support proactive health management by embedding degradation structure into learned models [62]; physics-informed hybrid reinforcement learning reduces the data demand of SOH estimation [63]; a generalizable PINN achieves cross-cell SOH estimation from limited early-cycle data [64]; EIS-informed physics-constrained networks estimate SOH from small impedance datasets [65]; and a generic physics-informed framework predicts RUL from small early-life samples across datasets [66]. Multi-feature hybrid schemes lift RUL accuracy across datasets [67], signal-decomposition hybrids sharpen capacity-fade prediction on noisy series [68], and deep reinforcement learning adaptively selects prognostic models along aging trajectories [13]. The shared motivation is clear: pure data-driven models extrapolate poorly past their training envelope, and physics priors are the cheapest available source of structure.

5.5 Transfer learning and cross-domain generalization

Transfer learning addresses the corpus's central weakness — generalization — directly. Domain-adversarial training adapts SOH estimators across operating conditions without target-domain labels [11]; deep transfer learning with partial charging curves carries capacity estimation across cell types [12]; transfer under fast-charging protocols extends the approach to protocol shift [69]; transfer-learning-based EIS estimation crosses chemistries [70]; and a general framework quantifies and manages the laboratory-to-fleet domain gap for trained estimators [71]. Framework-level work consolidates these threads: real-time online feature extraction from vehicle data [72] and reviews charting non-probabilistic estimation techniques [19], alongside joint SOH/RUL architectures that fuse multiple health indicators [7].

5.6 Critical assessment

Prognostics is where the corpus's validation problem bites hardest. The cluster's accuracy claims are established overwhelmingly on public benchmark cells: the Severson-MATR dataset alone appears in 11 corpus papers, NASA and CALCE in 12 more. Within-cell splits and k-fold protocols — which leak trajectory information between train and test — account for 10 of the 32 primary studies in the health-prognostics complex, and for 17 of the 88 primary papers in total. The transfer-learning papers are the honest exception, in that their whole object is distribution shift; but they also reveal how much shift remains unaddressed, with negative transfer cases and per-protocol fine-tuning acknowledged but rarely resolved. The mature judgment is that SOH estimation under controlled conditions is approaching incremental returns, while the prognostics problem that matters — calibrated lifetime and safety margins for arbitrary packs in the field — remains open [2, 20].

Metric heterogeneity compounds the validation problem. SOH papers report RMSE or MAE in percent capacity, sometimes normalized differently; RUL papers report cycle counts, percentages of true life, or knee-point errors defined against arbitrary end-of-life thresholds; charging papers report charge time, energy efficiency, and capacity retention after fixed cycle counts, which conflate estimation error with protocol quality. No two clusters share a metric, and within clusters the definitions vary enough that a quantitative meta-analysis of pooled accuracy — the trademark move of clinical meta-research — is not defensible for this literature. The qualitative synthesis of Sections 4–8 is therefore organized around method families, data regimes, and validation designs rather than around pooled effect sizes; this is a deliberate methodological choice, and readers should treat any cross-paper accuracy table with corresponding caution.

6. Machine Learning for Charging Control and Optimization

6.1 Closed-loop optimization of charging protocols

Charging control is the function where machine learning has changed experimental practice most directly, not merely what can be estimated. The defining result is Attia et al.: a Bayesian optimization loop over charging-protocol parameters, evaluating candidate protocols through continuous cycling, identified high-cycle-life protocols among 224 candidates in 16 days — against the more than 500 days an exhaustive search without early prediction would have taken [4]. The significance is methodological as much as practical: closed-loop learning converts protocol design from expert iteration into sample-efficient optimization. Subsequent work broadened the objective space. Ensemble surrogate models make model-based charging-strategy optimization tractable under multi-objective trade-offs [73], and data-driven Bayesian fast-charging optimization reduces charge time under explicit degradation constraints [74].

6.2 Learning to charge around degradation physics

A second line embeds degradation mechanisms into the charging decision itself. Machine-learning fast charging that perceives and regulates internal lithium-plating onset enables plating-free rapid protocols that deliberately exceed conventional voltage-safe schedules while keeping plating onset under online observation [75]. Adaptive multistage constant-current schemes adjust stage boundaries online against measured degradation [76], and module-level optimization manages temperature gradients across packs during charging [77]. Pack-level extensions coordinate balance-aware charging for imbalanced strings [78] and multi-objective meta-heuristic schemes negotiate charge time against temperature rise and aging [79].

Scale effects are the cluster's frontier. Cell-level protocols do not compose into pack-level schedules, because cell-to-cell variability makes the weakest cell the binding constraint; module-level optimization with temperature-gradient constraints [77] and balance-aware pack charging [78] are the corpus's first responses. The control-theoretic gap is equally important: optimization produces open-loop schedules, while deployment wants closed-loop policies that react to measured state — which is precisely where the reinforcement-learning line, still under-represented in journal-grade hardware validation, is expected to grow.

6.3 Critical assessment

Charging is also where the gap between demonstration and deployment is most concrete. The corpus contains eight charging papers; of these, one is a large-scale closed-loop hardware campaign [4], three further papers validate on laboratory hardware, and the remaining four rest on simulation-level evidence (three simulation-only, one with hardware spot-checks). RL-based charging strategies — a substantial adjacent literature — are underrepresented here precisely because most are validated in simulation against electrochemical models. The unsolved problem is certifiable learning-based charging: a controller that adapts to cell-to-cell variability and aging in production vehicles must carry a safety argument that current model-free learners cannot yet make, which is why mechanism-aware schemes such as plating-perception control [75] are the most deployment-relevant results in this cluster. Table 7 collects representative studies across functions and method families.

Table 7 Representative classified-subset studies by management function and method family. Entries gloss each study as: study summary (data basis; headline contribution). References in brackets refer to the numbered list.

Function	Method family	Representative studies (data; contribution)
State estimation (SOC)	Filter-embedded learning; meta-heuristic DL	LSTM+UKF embedded estimator (laboratory cells; learned observation model in a UKF) [5]; PSO-LSTM (laboratory cells; meta-heuristically tuned recurrent SOC) [36]; GA-LSTM with adaptive Kalman filtering (laboratory cells; low error under noise) [43]
Health estimation (SOH)	Classical ML; deep learning; transfer learning	ML pipeline over 179 cells (own cell fleet; relaxed charge-curve features) [51]; deep learning without extra degradation experiments (public MATR dataset; cross-chemistry generalization) [56]; real-world vehicle SOH (fleet data; field-noise robustness) [6]
Prognostics (RUL)	Classical ML; physics-informed; RL	Early-life cycle prediction (public MATR dataset; about 9% median test error) [3]; physics-informed early-cycle RUL (multiple datasets; small-data prognosis) [66]; deep-RL prognostic model fusion (public NASA dataset; adaptive model selection) [13]
Charging control	Bayesian optimization; mechanism-aware control	Closed-loop Bayesian protocol optimization (hardware prototype; 224 candidates in 16 days vs >500 days of exhaustive search) [4]; plating-perceiving fast charging (hardware prototype; plating-free protocols) [75]; ensemble-surrogate charging optimization (laboratory cells; multi-objective strategies) [73]
Thermal management	artificial neural network (ANN) surrogate; physics-informed; optimization	ANN temperature prediction (laboratory cells; low-error thermal model) [80]; PINN heat-generation estimation (simulation; embedded thermal physics) [9]; ML-assisted battery thermal management system (BTMS) design (simulation; multi-objective cooling design) [81]
Fault & safety	Shallow ML; multiphysics + ML; transfer learning	SVM fault diagnosis (hardware prototype; sensor and connection faults) [82]; multiphysics-ML runaway prediction (simulation and hardware; module-level hazard) [83]; cross-fleet runaway-diagnosis transfer (fleet data; small-sample diagnosis) [84]

Function	Method family	Representative studies (data; contribution)
Cross-cutting	Physics-informed; explainable AI (XAI); digital twin; LLM	EIS diagnostics PINN review (multiple studies; paradigm synthesis) [21]; uncertainty-aware early-life prediction (public MATR dataset; calibrated forecasts) [85]; LLM-based SOH estimation with uncertainty-aware fallback (field data; subset's earliest LLM estimator — an earlier journal study was missed by the retrieval; see the foundation-models section) [15]

7. Machine Learning for Thermal Management, Faults and Safety

7.1 Thermal-state estimation and thermal management

After cell balancing (2 primary papers), thermal management is the corpus's smallest quantitative engineering cluster (7 primary papers, tied with fault and safety; 8 including a review) and a disproportionately safety-critical one. Data-driven temperature estimation ranges from ANN models predicting cell temperature across operating conditions [80] to internal-temperature sensing under ultrahigh-rate discharge, where surface measurement fails [86]. On the design and control side, ML-surrogate models accelerate liquid-cooling plate analysis and multi-objective optimization of BTMS geometry [81, 87], experimentally validated parallel-liquid-cooling designs demonstrate the optimization loop end-to-end [88], and ANN-controlled thermal management reduces cooling parasitic load while holding temperature limits [89]. Physics-informed heat-generation estimation embeds thermal physics priors into the learning problem [9], and a state-of-the-art review consolidates the cluster [25].

The thermal cluster's papers divide cleanly by purpose, and the division clarifies where machine learning adds value. For *estimation* purposes — predicting internal or surface temperature under load — learned models replace thermocouple instrumentation that no production pack can afford, and physics-informed variants regularize the extrapolation regime where data-driven thermal models are least trustworthy [9]. For *design* purposes — sizing and arranging cooling hardware — ML surrogates amortize expensive CFD evaluation across optimization loops, turning weeks of simulation into tractable search [81, 87]. For *control* purposes — modulating cooling effort online — ANN controllers demonstrate parasitic-load reductions in simulation [89], but no subset paper yet closes this loop on hardware, leaving thermal control where charging control was five years ago.

7.2 Fault diagnosis and anomaly detection

Fault and safety applications (7 primary papers; 9 including reviews) divide into diagnosis of realized faults and prediction of impending hazards. On the diagnosis side, grid-search-optimized support vector machines classify sensor and connection faults [82], curvilinear-Manhattan-distance methods detect multiple pack fault types in operating fleets [90], and multi-scenario deep anomaly detection covers real EV operating envelopes [91]. Manufacturing-side inspection applies force-signal deep learning to catch lithium-plating-type defects before cells ship [92]. The hazard-prediction side is increasingly model-based: multiphysics models coupled with ML predict module-level thermal-runaway progression [83], a multiphysics-informed DeepONet predicts runaway using virtual data to augment scarce experimental events [93], and multi-source domain transfer moves thermal-runaway diagnosis across vehicle fleets with small target samples [84].

7.3 Critical assessment

Safety applications carry the corpus's highest stakes and its thinnest evidence base. Thermal-runaway events are rare and expensive to generate, so learning systems train on simulation or small laboratory campaigns; the DeepONet

line's virtual-data approach [93] is a rational response, but it inherits the fidelity limits of the underlying multiphysics models. The reviews in this cluster are notably candid: laboratory fault diagnosis has historically failed to transfer to real vehicles because fault signatures are masked by pack-level averaging, sensor noise, and operating diversity [23, 24]. The fleet-data anomaly-detection studies are therefore the cluster's most valuable trend, even though label scarcity for rare faults keeps evaluation largely qualitative.

8. Cross-Cutting Directions

8.1 Physics-informed learning

Within the classified subset, physics-informed and hybrid model–data learning is the most consistently rising methodological theme (24 family-coded papers across all functions; 22 of them primary applications; the only family with a monotonically non-decreasing primary trajectory within the subset — a pattern the eligible pool's query-theme tags do not mirror, Section 3.2). Beyond the prognostics applications of Section 5.4, physics-informed structures appear in state estimation [10, 94], heat-generation estimation [9], and impedance-based diagnostics, where physics-informed deep learning over electrochemical impedance spectra is consolidating into a diagnostic paradigm of its own [21]. Physics-constrained autoencoders improve health prediction over purely learned counterparts [95], and recurrent networks trained to anticipate uncertain future duty conditions address degradation prediction under distribution shift directly [96]. A parallel fusion literature combines physical and data-driven models for internal-state estimation generally [97]. The appeal is easy to state: physics priors supply exactly the extrapolation structure that pure learners lack. The corpus's caution is that most physics-informed studies embed *simplified* physics — equivalent-circuit or reduced electrochemical models — so the hybrid inherits model bias even as it gains structure.

8.2 Interpretability and uncertainty

A smaller but consequential cluster makes learning systems inspectable. Explainability-driven feature selection improves SOH estimator robustness via SHAP analysis [31]; interpretable ML links manufacturing coating parameters to cell capacity, connecting management analytics to production [98]; interpretable hybrid ML untangles co-evolving degradation chemistries in lithium–sulfur cells [99]; and uncertainty-aware, explainable models report calibrated early-life predictions [85]. Review-level retrospectives of interpretable battery prognosis now chart the theme's trajectory [22]. The state of practice remains, however, dominated by post-hoc explanation of otherwise black-box models — a necessary but not sufficient condition for the safety certification that onboard ML will eventually require.

The uncertainty thread deserves separate emphasis because it is the certification-relevant one. Gaussian-process lineages carry predictive intervals as a first-class output [46], the uncertainty-aware early-prediction study reports calibrated lifetime distributions rather than point forecasts [85], and conformal-style guarantees are beginning to appear in adjacent prognostics work. The interpretability thread, by contrast, remains dominated by post-hoc attribution (SHAP-style) analyses that explain *which features mattered* without bounding *what the model will do* on out-of-distribution inputs. For safety cases the two are not substitutes: attribution supports debugging and trust-building, while calibrated uncertainty supports decision rules — and only the latter has a route into certification argument.

8.3 Digital twins, cloud BMS, and new sensing

System-level architecture is emerging as a research object in its own right. Digital-twin implementations track individual battery aging through incremental learning [100] and couple LSTM surrogates with real-time thermal observation [101]; cloud-based platforms perform in-situ life prediction and classification at fleet scale from streaming charge data [102]; and second-life workflows use impedance-based accelerated SOH estimation to triage retired packs [103]. Non-electrical sensing broadens the measurement base: ultrasonic signatures processed with ML provide a SOC channel orthogonal to voltage sensing [45], impedance-spectroscopy ML supports SOC and SOH

estimation despite EIS's onboard-cost problem [44, 104], and battery state-of-power estimation combines learned models with numerical search for real-time capability prediction [105].

The twin/cloud/second-life cluster carries the corpus's most concrete systems implications. Digital-twin formulations reframe estimation as continual model maintenance — the incremental-learning requirement follows from pack heterogeneity and aging drift [100] — and cloud architectures relocate heavy computation off-vehicle, at the price of connectivity dependence and data-volume engineering [102]. Second-life workflows invert the deployment direction: instead of bringing estimators to new cells, they bring cheap, accelerated assessment to aged, heterogeneous cells [103], where classification-style decisions (deploy, repurpose, recycle) tolerate coarser resolution than onboard safety estimation. These three settings differ in latency budgets, error tolerance, and update cadence — and the corpus suggests the field is beginning to design for those differences rather than for a single notion of "the BMS."

8.4 Foundation models and LLM-based management

The classified subset's youngest theme is generative, and its two studies divide the labor differently. Domain-specific large language models perform risk analysis of battery energy-storage incidents by synthesizing heterogeneous incident reports [14] — a reasoning-and-synthesis role. The second study, HA-LLM [15], is an LLM-based SOH estimator: it aligns resampled charging-current sequences with the LLM embedding space, injects battery degradation priors through prefix adaptation, and — most notably for safety — wraps the LLM in an uncertainty-aware module that estimates predictive uncertainty by Monte Carlo sampling and selectively substitutes a physics-consistent estimator when uncertainty is high. It is validated on one year of field data from 100 production vehicles on a vehicle-cloud platform, with an independent teardown and bench capacity calibration on an unseen vehicle model, and it remains robust in few-shot and zero-shot cross-vehicle evaluations. The published work therefore already spans both the orchestration seat and the estimator seat, and the estimator-seat study is instructive precisely because its authors treated hallucination risk as a design constraint: uncertainty-triggered fallback to a physics-consistent estimator is exactly the guardrail this review argues should be mandatory (Table 8). The appearance of both roles in mainstream energy journals in 2026 marks a new phase: the management stack is beginning to absorb foundation-model components. Earliest-here claims are bounded by retrieval: a GPT-4-based health estimator by Poh et al. [106] appeared in IEEE Transactions on Energy Conversion in 2025, predating both studies, and it appears nowhere in the released 1,550-record retrieval — a recall miss of the query design, not a venue exclusion. The recall audit of Section 2.2 shows such misses are structural rather than exceptional: the capped queries contain only 16–17% of the in-scope, 2020-onward literature cited by this review's own included reviews, and the missed TEC paper is cited by none of those reviews either, so even a reference-list-driven search would not have surfaced it. Studies in this subset are therefore described as the earliest in the classified subset, not the first in the field.

Because BMS software is safety-critical, this review argues for an explicit division of labor before that absorption goes further, and Table 8 makes it concrete. The table contrasts established practice for classical and deep learning estimators with what the corpus's two LLM studies actually demonstrate, and states the guardrails this review regards as mandatory before any LLM component touches a safety-relevant path. The right-hand column is normative guidance proposed here, not claims about the published studies. The notable point is that the subset's earliest LLM estimator study [15] already implements two of those guardrails — Monte-Carlo uncertainty gating and substitution by a physics-consistent estimator — while leaving direct cell-level safety authority undefined, which is where the line should stay for now.

Table 8 Safety and verification taxonomy for foundation-model components in the BMS stack. The right-hand column is normative guidance proposed by this review, not claims about the published studies.

Dimension	Classical / deep ML estimators (established practice)	Published LLM studies (2026)	Required guardrail (this review)
Role in the stack	Calibrated numeric estimation and detection	Stationary-BESS incident risk analysis [14]; LLM-based SOH estimation with uncertainty-aware control on field vehicle data [15]	Estimation should belong to calibrated ML; the LLM SOH estimator of [15] is the earliest in the classified subset — an earlier journal-published LLM estimator, missed by this review's retrieval, is [106] (the foundation-models section) — and must show calibrated intervals before any actuation-adjacent role
Grounding	Trained on domain cycling data	Domain-tuned corpora and knowledge-enhanced prompting	Retrieval over verified corpora with source citations; no ungrounded recall
Dominant failure mode	Bounded numeric error under distribution shift	Open-ended hallucinated text	Outputs restricted to structured, checkable forms; never free text into protection logic
Uncertainty	Gaussian-process / conformal intervals in a subset of studies	Not reported for incident risk analysis [14]; Monte-Carlo uncertainty estimates with selective physics-estimator substitution demonstrated in the SOH estimator [15]	Calibrated intervals mandatory before any actuation-adjacent role
Latency and compute	Millisecond-class, onboard	Second-class, cloud-dependent	Offline analysis and planning only unless real-time evidence is shown
Safety authority	Bounded by physics envelopes and thresholds	Undefined in published studies	LLM components must never hold direct cell-level protection authority

8.5 Manufacturing analytics and system-level synthesis

Two further cross-cutting threads connect management to the wider battery value chain. Cell-production mapping studies chart ML use across manufacturing stages from mixing to formation [107], complementing the coating-quality interpretability work [98] and manufacturing defect detection [92] — the management implication being that cell quality information is itself a BMS input. And the pack-level insight that routine cell balancing can be eliminated in well-managed packs, reducing hazardous lithium-plating side reactions, shows learned analysis reshaping a function (balancing) that classical control had considered settled [32], while ML mappings from equivalent-circuit parameters to electrochemical properties give classical BMS models a physically interpretable learned layer [108].

9. Research Gaps and Future Directions

Cross-referencing the bibliometric analysis of Section 3 with the function-level reviews of Sections 4–8 yields six structural gaps, discussed in Sections 9.1–9.6, summarized in Table 10, previewed against the field's milestones in Fig. 8, and then operationalized into a concrete reporting checklist in Section 9.9.

9.1 Validation and benchmarking standards

The corpus's validation data are unambiguous: 17 of the 88 primary papers use within-cell splits or unsupervised k-folds, and only 8 of the 88 demonstrate their systems online or on real fleets. Until cross-cell, cross-temperature, and cross-protocol holdout protocols become reporting norms, published accuracy figures will continue to carry a systematic risk of overstating deployable performance. The most valuable near-term contribution the community can make is standardized transfer protocols — train-on-chemistry-A/test-on-chemistry-B, train-on-lab/test-on-fleet — reported alongside headline accuracy, as already practiced by the transfer-learning and general-framework studies [70, 71].

A second standardization target is reporting itself. In our full-text reading of the corpus we did not routinely encounter disclosed split definitions, random seeds, or compute budgets; only the validation-protocol, data-source, and baseline-comparison items were systematically score-counted (Section 9.9), so this is a qualitative observation rather than a measured rate. Either way, such omissions make independent replication laborious and meta-analysis impossible (Section 5.6). A community-endorsed reporting checklist — dataset identity and version, split protocol, uncertainty quantification, and hardware context — would cost little and would let the synthesis literature do its job.

9.2 Data sharing and benchmark concentration

Twenty-three primary papers rest on the same three public benchmarks (Severson-MATR 11, NASA 6, CALCE 6), and 42 rest on private laboratory data (36 own-cell cycling, 6 laboratory impedance) that are not released. This two-pole fragmentation inflates apparent comparability on the shared benchmarks and hides dataset-specific failure modes, while precluding audit altogether on the private pole. Federated learning over fleet data, standardized anonymized fleet-data releases, and multi-institution cycling campaigns — in the spirit of the 179-cell pipeline [51] — would diversify the evidence base at modest incremental cost.

The economics argument strengthens the technical one. A fleet operator's marginal value from a percentage point of SOH accuracy is measured in warranty provisions and residual-value pricing, which justifies onboard compute budgets that academic prototypes routinely ignore. Quantized and pruned recurrent models, event-driven inference triggered by charge sessions rather than continuous streams, and asymmetric architectures — lightweight onboard estimators with cloud-side retraining — are the concrete design patterns emerging from the corpus's edge-aware minority [61, 72].

9.3 Edge deployment and onboard constraints

Only a handful of corpus works treat onboard compute, memory, or latency as first-class design constraints, notably the board-level RUL implementation [61] and real-time feature-extraction studies [72]. The gap is widening as models grow: transformer and PINN architectures trained on workstations must eventually run beside BMS microcontrollers. Quantization-aware training, neural architecture search under resource constraints, and hybrid designs that place heavy learners in the cloud and lightweight correction layers onboard are the natural research program here [15].

9.4 Trust, uncertainty, and safety standards

Estimates that guide protection and charging decisions need calibrated uncertainty and auditable reasoning. The corpus's uncertainty-aware [85], explainability-driven [31], and Gaussian-process lineages [46] point the way, but certification-grade ML — models whose failure modes are enumerated and bounded — remains beyond the published state of the art. Hybrid physics–data architectures are the most credible certification path because part of their behavior is analytically specified; making that argument rigorous is an open task for the PINN community.

The safety standards invoked in the introduction do not prescribe estimation algorithms, but they define what a deployed estimator or controller must be able to evidence, and Table 9 translates the subset's gaps into those terms. UN GTR No. 20 on electric-vehicle safety was established in the UN Global Registry in 2018 [28]. Its Amendment 1, adding thermal-propagation requirements with two compliance options — a physical propagation test or a

documented risk-management approach — was submitted by the European Commission on behalf of the Informal Working Group on Electric Vehicle Safety as formal document ECE/TRANS/WP.29/GRSP/2026/4, alongside the working group's status report ECE/TRANS/WP.29/GRSP/2026/3 [109]; it was considered at the 79th session of the Working Party on Passive Safety (GRSP, June 2026) and stood, at this review's 18 October 2026 finalization date, pending before WP.29 with adoption listed for its 17–20 November 2026 session.

GB 38031 has been rewritten around thermal propagation in the same window. GB 38031-2020 is superseded for new type approvals by GB 38031-2025 from July 2026, with existing models transitioning through July 2027; GB 38031-2025 requires that, once single-cell thermal runaway is triggered, the pack or system neither fire nor explode throughout a two-hour observation window, that a thermal-event alarm still be issued, and that smoke not harm occupants — superseding GB 38031-2020's criterion of an alarm at least five minutes before any fire or explosion — and adds bottom-impact and 300-cycle fast-charge safety tests [29].

The ISO family governs the assurance argument rather than the abuse test: ISO 26262:2018 treats the functional safety of road-vehicle E/E systems through the safety lifecycle [30]; ISO/PAS 8800:2024 extends it, together with ISO 21448, to learned components [110]; and ISO 21448 addresses safety of the intended functionality (SOTIF) [111].

The mapping is this review's synthesis at requirement level rather than clause level, and it is stated so that it can be checked against the standards texts themselves: the point is not legal advice but that a validation protocol reported in a paper corresponds, or does not, to evidence a safety case can use. The inference rule behind every 'supports a standards argument' statement in this section is explicit: a paper's evidence can support such an argument only if it demonstrates performance on at least one held-out integration unit (a cross-cell holdout or stronger isolation protocol, Section 2.5) and reports the environment in which that evidence was obtained; by construction, within-cell and k-fold evidence cannot support the argument, because the safety case is about unseen cells and unseen duty. Three consequences stand out for automotive deployment. Within-cell and k-fold validation (17 primary papers) cannot support an ISO 26262 argument, because the safety case is about unseen cells and unseen duty and the protocol never tests an unseen unit; a standards argument must therefore be *argued* from the isolation evidence, not *asserted* from headline accuracy. Thermal-propagation early-warning latency is a timing requirement, so fault-detection papers evaluated on curated laboratory windows under-report both the false-alarm rate and the detection-delay distribution that the GB 38031-2025 / GTR-20 escape window needs. And charging or thermal control strategies validated only in simulation lack the hardware-in-the-loop evidence base an automotive release process expects. The reporting checklist of Section 9.9 is deliberately aligned with this mapping — reporting an isolation argument and a validation environment is the minimum on which any standards conversation can start.

Table 9 Mapping BMS functions to requirements in UN GTR 20 (Amendment 1 thermal-propagation provisions, ECE/TRANS/WP.29/GRSP/2026/4), GB 38031-2020/2025, ISO 26262:2018 with ISO/PAS 8800:2024, and ISO 21448 (SOTIF): what deployed ML components must be able to evidence. Regulatory statuses are stated as of 18 October 2026; throughout the table, a 'strong protocol' means the protocol-only definition of Section 2.5 (cross-cell, cross-chemistry, or cross-domain holdout, or online/real-vehicle demonstration). The mapping is this review's synthesis at requirement level (not clause-level legal citation); the right-hand column gives the corresponding classified-subset primary-paper counts from Section 3.4.

BMS function	What the standard demands of a deployed function	Current subset status
SOC estimation	ISO 26262:2018 treats estimation error that can enable overcharge/overdischarge as an E/E-system safety hazard to be handled through the safety lifecycle; ISO/PAS 8800:2024 extends this to learned elements (assurance argument over data, model, and known insufficiencies); UN GTR 20 / GB 38031-2025 treat overcharge as an abuse-protection requirement [28][29][30]	3 of 13 SOC primary papers use a strong isolation protocol; none validate on real-vehicle data; 12 rest on laboratory-scale data
SOH / RUL prognosis	Capacity and power fade margins underpin thermal-propagation early warning and end-of-service decisions; degradation assumptions must hold across chemistry, duty, and environment (ISO 26262 hazard analysis; ISO 21448 for performance limitations [111])	20 of 32 SOH/RUL primary papers use a strong protocol; 4 use real-vehicle data; accuracy claims rest mostly on three public benchmarks (16 of the 32 SOH/RUL primary papers; 23 across the whole subset)
Fault detection	Thermal-propagation containment and early warning must both be evidenced: GB 38031-2025 requires that after single-cell thermal runaway the pack or system neither fire nor explode over a two-hour observation window, that a thermal-event alarm still be issued, and that smoke not harm occupants — superseding GB 38031-2020's five-minute pre-fire alarm; the GTR 20 Amendment 1 proposal (ECE/TRANS/WP.29/GRSP/2026/4) carries a ≥5-min advance-warning requirement before cabin hazards, with test or risk-management compliance options [109]; coverage must be argued and audited (ISO/PAS 8800 assurance argument [110])	2 of 7 fault/safety primary papers validate online on fleet data; detection-latency and false-alarm distributions are rarely reported
Charging control	Overcharge, over-temperature, and thermal-cycling limits are hard constraints under GB 38031-2020/2025; adaptive strategies must be bounded by protection envelopes and argued in the safety case	0 of 8 charging primary papers use a strong protocol; 4 demonstrate on laboratory hardware, none online

BMS function	What the standard demands of a deployed function	Current subset status
Thermal management	Temperature-gradient and propagation-containment requirements after fast-charge or abuse (GB 38031-2025 thermal diffusion, bottom-impact, fast-charge-cycle tests); the cooling function must be verified on hardware	0 of 7 thermal primary papers use a strong protocol; 2 exercise laboratory hardware; no learned control loop is validated on hardware

9.5 Foundation-model integration

The corpus's first LLM-based management studies (2026, with LLM-based estimation prior art that this review's retrieval missed — Section 8.4) [14, 15] suggest a division of labor worth formalizing — with the caveat that HA-LLM [15] already occupies the estimator seat under exactly the guardrails proposed here: foundation models as reasoning, orchestration, and human-interface layers, and as estimators only where uncertainty-gated and protected by physics-fallback substitution; conventional ML as calibrated estimators; physics models as safety envelopes. Research is needed on grounding (preventing hallucinated battery knowledge), latency, and the division of safety authority between learned and non-learned components. Battery-domain foundation models pretrained on cycling corpora are a plausible medium-term development.

9.6 Under-served functions

Finally, the function distribution itself signals opportunity — read at both levels of the evidence base. Cell balancing is the smallest core function both in the curated subset (2 papers) and in the quota-free eligible pool (38 of 799 tagged records, Section 3.3), so its under-representation is a property of the retrieved literature rather than of the quotas; ML has so far contributed mainly at the level of pack-level insight rather than as a balancing controller [32]. Thermal management is not scarce as a theme in the pool (99 tagged records), but closed-loop thermal control has not yet been demonstrated on hardware in the subset, and the cluster remains simulation-dominated [25] — the deficit is evidential, not topical. Charging control needs certifiable adaptive protocols. These functions share a property that explains the pattern: they are *control* problems, where errors act on the battery rather than merely reporting on it, and where the evidence bar is correspondingly higher. Closing them will require the safety-case machinery of Section 9.4 as much as new algorithms.

Table 10 Structural research gaps and corresponding future directions

Gap	Evidence in corpus	Future direction
Validation practice	17 of 88 primary papers use within-cell or k-fold validation; 8 of 88 primary papers demonstrate online or fleet use	Standardized cross-cell, cross-chemistry, lab-to-fleet transfer protocols as reporting norms
Two-pole data fragmentation	23 primary papers on three public benchmarks; 36 on rarely released private laboratory cells	Federated learning, anonymized fleet-data releases, multi-institution cycling campaigns
Onboard deployment	Few studies treat compute/memory/latency as design constraints	Quantization-aware training, resource-constrained NAS, cloud–edge hybrid estimation
Trust and certification	Interpretability mostly post-hoc; uncertainty rarely calibrated	Calibrated uncertainty, analytically specified hybrid architectures, safety-case methodology
Foundation-model integration	First two LLM-based studies appear in 2026 in the subset	Grounded LLM orchestration layers; domain foundation models; division of safety authority

Gap	Evidence in corpus	Future direction
Under-served functions	Balancing: smallest core function in subset (2 papers) and pool (38 of 799 tagged); closed-loop thermal control not yet shown on hardware	Certifiable adaptive control with mechanism-aware safety envelopes

9.7 Position relative to prior reviews

Section 1.3 situated this review against the function-specific and method-specific reviews that dominate the field; the positioning deserves its own statement because reviewers and readers routinely ask what a new review adds when several exist. The closest in scope among recent cross-functional reviews is the performance-centric review of Prasanna et al. [27] (240 studies, included from 361 screened records, across the EV powertrain, aggregating reported RMSE and R^2); adjacent cross-functional surveys exist for degradation and estimation methods. This review is distinguished by what those studies do not attempt, and Table 11 states the comparison axis by axis: a two-tier corpus with record-level screening provenance (799 eligible records released in full, 103 classified in depth); a within-corpus measurement of validation-protocol strength across functions, with per-paper assignments released and method-family contrasts tested rather than asserted; a requirement-level mapping onto UN GTR 20, GB 38031, and ISO 26262; and a released, re-runnable analysis pipeline behind every count and figure. Where prior reviews ask *which method works best for function X*, this review asks *which claims can actually be checked — and what it would cost the reader to trust them* — which is the question a scoping review with a curated classified subset is positioned to answer, and the question that performance-centric aggregation cannot ask of itself.

Table 11 Position relative to prior reviews. “Prasanna 2026” denotes the 2026 performance-centric ML review of EV powertrains with BMS and charging scope (240 studies, included from 361 screened records; aggregated reported RMSE/R^2). The function-specific and method-specific reviews named in Section 1.3 cover single functions or methods, so none of them, to our knowledge, addresses the axes below; the comparison is per axis, not per review. This review differs most in the validation measurement (within a curated subset), standards linkage, and released record-level artifacts.

Axis	This review	Prior cross-functional / powertrain reviews
Corpus	Two-tier: 799 rule-based eligible records + 103 classified subset	Fixed study lists; no record-level selection provenance in the works we examined
Validation analysis	Protocol classes defined, per-paper assignments released, method-family contrast tested with sensitivity ranges; within-corpus measurement, not a field census	Narrative remarks on data scarcity; protocol strength not quantified, to our knowledge
Standards linkage	Function-to-requirement mapping vs. UN GTR 20, GB 38031-2020/2025, ISO 26262:2018, ISO/PAS 8800:2024	Not addressed or addressed qualitatively
Recommendations	Twelve-item reporting checklist (BMS-ML-RC) + six research directions	General future-work statements
Reproducibility	Released papers.csv, screening provenance, codebook, and statistics scripts	No released record-level dataset that we could locate

9.8 Outlook: what the next research cycle should produce

Concretely, and tied to the gaps above, the highest-value near-term work falls in six directions. (a) *Duty-cycle-aware validation*: public cross-cell benchmarks that pair cycling data with recorded EV drive profiles, so that cross-chemistry and cross-domain generalization can be tested against transportation duty rather than laboratory schedules. (b) *Federated fleet evidence*: privacy-preserving SOH/SOC studies over live fleets (about 2% of the eligible corpus today), with the 179-cell pipeline [51] as the template. (c) *Benchmark diversification*: multi-institution cycling campaigns two orders of magnitude larger than MATR/NASA/CALCE and released with DOI-backed artifacts, addressing the two-pole fragmentation of Section 3.4. (d) *Pack- and vehicle-level ML*: estimation validated at the integration level where UN GTR 20 and GB 38031 requirements bite, instead of cell-level evidence transplanted upward. (e) *Functionally safe learning*: ML estimators whose uncertainty handling and assurance arguments are specified against ISO 26262 safety goals and ISO/PAS 8800, with ISO 21448/SOTIF reasoning for capability limitations, making certifiable charging and thermal control reachable. And (f) *honest foundation-model integration*: retrieval-grounded LLM agents with published latency and calibration budgets, capable of the coordination role while estimation authority stays with calibrated numeric models — extending, not contradicting, the corpus's LLM estimator [15]. A seventh, methodological direction concerns the evidence base itself rather than any single function: a v2 re-retrieval of this corpus with cursor paging — the upgrade the retrieval-depth pilot of Section 2.2 measures as this pipeline's single highest-leverage methodological step, worth on the order of 5,000 additional eligible records at the original design's observed overlap factor — so that the next synthesis can measure field-level shares over a registry-deep sample rather than a top-20-per-pass cap. A guardrail on all seven directions: the BMS-ML-RC checklist of Section 9.9 is designed to be attached to a paper at submission, so that the next generation of BMS-ML studies arrives auditable by construction.

9.9 A reporting checklist for machine-learning BMS studies

The most concrete artifact this review can offer is procedural. Modeled on the CONSORT and PRISMA checklists that transformed reporting in clinical and review literature, Table 12 proposes a twelve-item BMS-ML reporting checklist: the minimum metadata a study should disclose for its accuracy claims to be comparable, reproducible, and poolable in future syntheses. None of the items is onerous. Items 4, 5, and 11 operationalize the validation-protocol classes that the corpus analysis measured directly (Section 3.4); the remaining items respond to reporting omissions observed qualitatively across Sections 3–8 — undisclosed splits, uncalibrated uncertainty, unnamed datasets, unquantified compute — but only the validation-protocol, data-source, and baseline-comparison items are score-measured in this corpus (Sections 2.5 and 3.4), and the checklist has not been applied as an audit to all 103 studies. We suggest journals adopt it as a submission checklist and that authors attach it to their released datasets.

Table 12 Proposed BMS-ML reporting checklist (BMS-ML-RC), modeled on CONSORT/PRISMA reporting standards.

#	Reporting item	What must be reported
1	Dataset identity	Exact name and version of every dataset (e.g., Severson-MATR, NASA, CALCE); download source
2	Cell population	Number of cells, chemistry, manufacturer, format, and batch for every training and test set
3	Sensor and sampling context	Measured channels, sampling rate, sensor class, and temperature conditions
4	Split protocol	Split type (within-cell / cross-cell / cross-chemistry / cross-domain) and isolation argument; within-cell splits must be flagged as such
5	Out-of-distribution evaluation	At least one protocol under which test conditions differ from training (chemistry, temperature, protocol, or source)
6	Baselines	At least one classical baseline alongside the proposed architecture, with identical data

#	Reporting item	What must be reported
7	Randomness control	Seeds or repeated-run statistics for every stochastic training result
8	Uncertainty	Calibrated uncertainty or error bars for headline claims, not point estimates alone
9	Compute budget	Training compute and inference latency/memory on the target (or a stated reference) platform
10	Failure analysis	At least one documented failure mode and its distribution (where the model is worst)
11	Validation environment	Which of the following applies: simulation, laboratory cycling, hardware prototype, online/fleet
12	Artifact availability	Data and code deposit (DOI-backed) or an explicit stated exemption




Fig. 8 Milestones of machine learning in battery management, 2019–2026, drawn from the corpus; dating follows the cited studies' publication years and is therefore citation- and retrieval-conditioned (Sections 2.2 and 3.1): early-life cycle prediction [3], closed-loop Bayesian fast charging [4], fleet-scale SOH pipelines [51], the physics-informed wave [9], cross-domain health estimation and cloud BMS [12, 102], optimization-augmented and transfer learning [74, 84], deep-RL prognostics [13], and the first corpus foundation-model studies [15].

10. Conclusion

This review has examined machine learning in battery management on a two-tier evidence base: a rule-based eligible corpus of 799 records from which field-level shares are measured within a documented capped retrieval, and an in-depth classified subset of 103 studies through which method, data, and validation practice are examined with a blind, two-round 30-paper re-coding by two co-author coders (all five fields at strong agreement in the revised-codebook round, validation $\kappa = 0.92$) and label-noise sensitivity ranges. Three conclusions stand out. First, and most critically, the subset's published accuracy claims have outpaced the validation evidence behind them: online or fleet-level demonstration appears in fewer than one primary study in ten, 17 of 88 primary papers use isolation-weakened splits, benchmark concentration and private-data fragmentation distort the apparent state of the art, and the favored remedy — physics-informed architecture — shows no detectable substitution for validation rigor in these counts (the strong-protocol count rests on single full-text coding, audited by an independent re-code that confirms ten of fourteen determinable strong labels and itemizes four challenges and two upgrades, and cross-checked by a revised-codebook re-coding round in which the two coders agree on the strong/non-strong bucket for 28 of 30 papers,

Sections 3.4 and 2.5): physics-informed papers use strong protocols at rates statistically indistinguishable from data-driven peers (36% versus 52% under the protocol-only definition, $p = 0.32$; 59% versus 74% under the broader definition, $p = 0.19$), a contrast too underpowered to rule out meaningful differences in either direction (Section 3.4), and therefore retained as an open hypothesis rather than a settled result. Second, the retrieval's center of gravity is estimation (state, health, lifetime): the SOC–SOH–prognostics query-theme union tags 366 of 799 records (45.8%) — a property of the retrieval's query families rather than a field-level prevalence (Section 3.3) — and it is there that learning systems report laboratory-regime success — on metrics that this review argues cannot be pooled across papers (Section 5.6) — while control functions (charging, thermal, balancing) remain demonstrably transformable but under-evidenced for deployment, and vehicle- and pack-level practice stays thin relative to the level at which UN GTR 20, GB 38031, and ISO 26262 pose their requirements (Section 9.4). Third, within the classified subset the method families stratify by period — classical feature-based learners gave way to deep sequence models, which are now themselves being displaced at the research frontier by physics-informed hybrids, optimization-augmented learning, transfer-learning regimes, and, at the very edge of the window, foundation-model components — a within-subset sequence that the eligible pool's method-theme tags do not mirror, so no field-level family rise is measurable at either tier (Section 3.2).

The near-term agenda follows directly: standardized cross-domain validation protocols; diversified and shareable fleet data; edge-deployable architectures designed under onboard constraints; calibrated uncertainty and interpretability as certification prerequisites; and a principled division of labor between foundation models, calibrated estimators, and physics-based safety envelopes. If the last five years were about discovering what machine learning can estimate about a battery, the next five will be decided by what it can be trusted to do — onboard, at fleet scale, across chemistries, and over full cell lifetimes.

Declarations

Funding. The authors received no specific funding for this work.

Conflicts of interest. The authors declare no competing interests.

Author contributions. H.T.S. conceived the study, designed and executed the search, screening, and verification pipeline, performed the full-text classification and analysis, coded the released labels, and drafted the manuscript. S.S.I.A. and J.I.C. performed the blind 30-paper re-coding of the reliability study (coders B and C, Section 2.5) before any verification work, and contributed to corpus curation, verification of classifications and counts, and manuscript revision. All authors read and approved the final manuscript.

Data availability. The complete evidence base is deposited at Zenodo, DOI 10.5281/zenodo.23436202 (deposit of record; the GitHub repository of the same name is a development mirror). The deposit includes: the classified 103-study dataset (papers.csv, papers_final.json) with per-paper citation counts; the 799-record rule-based eligible pool (eligible_corpus.json, pool.csv) with per-record query-theme tags; the record-level screening log (screening_log.csv); the per-paper validation-protocol audit (protocol_audit.csv); the codebook and coding protocol (codebook.md, coding_protocol.md); the locked blind coder sheets, agreement report, itemized disagreements, and hash-tracked reliability log (corpus/reliability/); the conference sensitivity set with all 14 retrieved papers and the pre-stated inclusion rule (conference_sensitivity.csv); the withheld released labels for the reliability sample (gold_labels_30.csv); the label-noise sensitivity script and outputs (sensitivity_label_noise.py/.json); the Crossref verification audit trail (final_audit.json, external_verified.json, conference_verified.json); the seed-study register (seeds.json); the screening statistics (stats.json); the recall audit with its cached Crossref responses (recall_audit.py, recall_audit.json, raw_cache/); the retrieval-depth pilot (retrieval_depth_pilot.py, retrieval_depth_pilot.json); the minimum-detectable-effect analysis (power_analysis.py, power_analysis.json); the abstract-level probes with their codes and rubric (abstract_probe.py, abstract_probe_raw.json, abstract_probe_codes.py, abstract_probe.json); and the independent post-freeze validation-field re-code with its evidence sheet, coder sheet, comparison script, and itemized discrepancies (corpus/validation_recode/). The retrospective OSF registration draft is released verbatim in osf_registration/. One registry-metadata note: the Crossref record for one reference (DOI

10.1016/j.jechem.2023.03.026) deposits two author names with the given and family fields transposed and the surname ‘Store’ for ‘Stroe’; the reference list normalizes them to the published forms (Vilsen, S. B.; Stroe, D. I.), and all other bibliographic metadata is reproduced exactly as deposited.

Supplementary material. The interpretation rules, the label-noise scenario derivations, the minimum-detectable-effect analysis, the recall-audit construction, and the abstract-level probes are consolidated in Supplementary_Material.pdf (built by build_supplement.py and released with this paper’s repository; the underlying scripts and outputs are part of the same Zenodo deposit, DOI 10.5281/zenodo.23436202).

Code availability. All search, screening, selection, verification, classification, reliability, sensitivity, statistics, figure-generation, and manuscript-build scripts are included in the same Zenodo deposit (DOI 10.5281/zenodo.23436202), so that every figure and every count in Sections 2 and 3 can be regenerated deterministically from the released data.

Ethics approval. Not applicable. This study did not involve human participants or animals.

Consent to participate / for publication. Not applicable.

Use of artificial intelligence. During the preparation of this manuscript the authors used the following tools, each for a stated purpose: an AI language model (GLM, Z.ai) assisted in drafting and adapting the literature-pooling, analysis, and figure-generation scripts; OpenAI ChatGPT, Grammarly, and QuillBot were used for language editing (grammar, readability, and sentence restructuring). No AI tool decided study inclusion, and no AI tool assigned or altered any classification label: all screening decisions and all released labels were made by the authors; after the labels were frozen, an AI-assisted re-code of the validation field was run as a released robustness audit (coder D, Sections 2.5 and 3.4) — it coded from retrieved evidence without altering any label, and its disagreements with the released labels are itemized for reader adjudication (Section 2.5 documents who coded what, and the reliability files release the coding evidence). All included references were verified against the Crossref registry by direct DOI resolution, all counts and figures were regenerated programmatically from the released dataset, and the authors reviewed and take full responsibility for the content of the published article.

References

1. Yao, J., Kowal, J., “Towards a smarter battery management system: A critical review on deep learning-based state of charge estimation of lithium-ion batteries,” Energy and AI, vol. 21, 100585, 2025, doi: 10.1016/j.egyai.2025.100585.
2. Hu, X., Xu, L., Lin, X., Pecht, M., “Battery Lifetime Prognostics,” Joule, vol. 4, 310-346, 2020, doi: 10.1016/j.joule.2019.11.018.
3. Severson, K. A., Attia, P. M., Jin, N., Perkins, N., Jiang, B., Yang, Z., et al., “Data-driven prediction of battery cycle life before capacity degradation,” Nature Energy, vol. 4, 383-391, 2019, doi: 10.1038/s41560-019-0356-8.
4. Attia, P. M., Grover, A., Jin, N., Severson, K. A., Markov, T. M., Liao, Y. H., et al., “Closed-loop optimization of fast-charging protocols for batteries with machine learning,” Nature, vol. 578, 397-402, 2020, doi: 10.1038/s41586-020-1994-5.
5. Yang, F., Zhang, S., Li, W., Miao, Q., “State-of-charge estimation of lithium-ion batteries using LSTM and UKF,” Energy, vol. 201, 117664, 2020, doi: 10.1016/j.energy.2020.117664.
6. Tian, J., Liu, X., Li, S., Wei, Z., Zhang, X., Xiao, G., et al., “Lithium-ion battery health estimation with real-world data for electric vehicles,” Energy, vol. 270, 126855, 2023, doi: 10.1016/j.energy.2023.126855.
7. Wei, Y., Wu, D., “Prediction of state of health and remaining useful life of lithium-ion battery using graph convolutional network with dual attention mechanisms,” Reliability Engineering & System Safety, vol. 230, 108947, 2023, doi: 10.1016/j.ress.2022.108947.
8. Li, Z., Zhang, X., Gao, W., “State of health estimation of lithium-ion battery during fast charging process based on BiLSTM-Transformer,” Energy, vol. 311, 133418, 2024, doi: 10.1016/j.energy.2024.133418.
9. Pang, H., Wu, L., Liu, J., Liu, X., Liu, K., “Physics-informed neural network approach for heat generation rate estimation of lithium-ion battery under various driving conditions,” Journal of Energy Chemistry, vol. 78, 1-12, 2023, doi: 10.1016/j.jechem.2022.11.036.

10. Wang, Y., Han, X., Guo, D., Lu, L., Chen, Y., Ouyang, M., “Physics-Informed Recurrent Neural Network With Fractional-Order Gradients for State-of-Charge Estimation of Lithium-Ion Battery,” IEEE Journal of Radio Frequency Identification, vol. 6, 968-971, 2022, doi: 10.1109/jrfid.2022.3211841.

11. Ye, Z., Yu, J., “State-of-Health Estimation for Lithium-Ion Batteries Using Domain Adversarial Transfer Learning,” IEEE Transactions on Power Electronics, vol. 37, 3528-3543, 2022, doi: 10.1109/tpel.2021.3117788.

12. Yao, J., Han, T., “Data-driven lithium-ion batteries capacity estimation based on deep transfer learning using partial segment of charging/discharging data,” Energy, vol. 271, 127033, 2023, doi: 10.1016/j.energy.2023.127033.

13. Du, M., Zhang, Y., Miao, Q., “Remaining useful life prediction of lithium battery based on deep reinforcement learning fusion network,” Reliability Engineering & System Safety, vol. 264, 111392, 2025, doi: 10.1016/j.ress.2025.111392.

14. Liang, J., Meng, H., Mu, Y., “Domain-specific large language model-driven risk analysis of battery energy storage systems,” Reliability Engineering & System Safety, vol. 274, 112416, 2026, doi: 10.1016/j.ress.2026.112416.

15. Cai, S., Chen, J., Hu, J., Huang, R., Liao, J., Wei, M., et al., “HA-LLM: A domain knowledge-enhanced large language model for vehicle-cloud collaborative battery health awareness,” Energy Storage Materials, vol. 86, 104983, 2026, doi: 10.1016/j.ensm.2026.104983.

16. Ng, M. F., Zhao, J., Yan, Q., Conduit, G. J., Seh, Z. W., “Predicting the state of charge and health of batteries using data-driven machine learning,” Nature Machine Intelligence, vol. 2, 161-170, 2020, doi: 10.1038/s42256-020-0156-7.

17. Liu, Y., He, Y., Bian, H., Guo, W., Zhang, X., “A review of lithium-ion battery state of charge estimation based on deep learning: Directions for improvement and future trends,” Journal of Energy Storage, vol. 52, 104664, 2022, doi: 10.1016/j.est.2022.104664.

18. Wu, Y., Bai, D., Zhang, K., Li, Y., Yang, F., “Advancements in the estimation of the state of charge of lithium-ion battery: a comprehensive review of traditional and deep learning approaches,” Journal of Materials Informatics, vol. 5, 2025, doi: 10.20517/jmi.2024.84.

19. Sui, X., He, S., Vilsen, S. B., Meng, J., Teodorescu, R., Stroe, D. I., “A review of non-probabilistic machine learning-based state of health estimation techniques for Lithium-ion battery,” Applied Energy, vol. 300, 117346, 2021, doi: 10.1016/j.apenergy.2021.117346.

20. Li, X., Yu, D., Vilsen, S. B., Stroe, D. I., “The development of machine learning-based remaining useful life prediction for lithium-ion batteries,” Journal of Energy Chemistry, vol. 82, 103-121, 2023, doi: 10.1016/j.jechem.2023.03.026.

21. Lin, Y. H., Ruan, S. J., Chen, Y. X., Li, Y. F., “Physics-informed deep learning for lithium-ion battery diagnostics using electrochemical impedance spectroscopy,” Renewable and Sustainable Energy Reviews, vol. 188, 113807, 2023, doi: 10.1016/j.rser.2023.113807.

22. Wang, T., Liu, K., Peng, H., Liu, X., “Interpretable Machine Learning for Battery Prognosis: Retrospect and Prospect,” Advanced Energy Materials, vol. 15, Art. no. e03067, 2025, doi: 10.1002/aenm.202503067.

23. Samanta, A., Chowdhuri, S., Williamson, S. S., “Machine Learning-Based Data-Driven Fault Detection/Diagnosis of Lithium-Ion Battery: A Critical Review,” Electronics, vol. 10, 1309, 2021, doi: 10.3390/electronics10111309.

24. Yu, Q., Wang, C., Li, J., Xiong, R., Pecht, M., “Challenges and outlook for lithium-ion battery fault diagnosis methods from the laboratory to real world applications,” eTransportation, vol. 17, 100254, 2023, doi: 10.1016/j.etran.2023.100254.

25. Li, A., Weng, J., Yuen, A. C. Y., Wang, W., Liu, H., Lee, E. W. M., et al., “Machine learning assisted advanced battery thermal management system: A state-of-the-art review,” Journal of Energy Storage, vol. 60, 106688, 2023, doi: 10.1016/j.est.2023.106688.

26. Rahman, T., Alharbi, T., “Exploring Lithium-Ion Battery Degradation: A Concise Review of Critical Factors, Impacts, Data-Driven Degradation Estimation Techniques, and Sustainable Directions for Energy Storage Systems,” Batteries, vol. 10, 220, 2024, doi: 10.3390/batteries10070220.

27. Prasanna, R., Kumar, R. S., Bhuvaneswari, N. S., Karthik, C., “Performance centric review of machine learning techniques for electric vehicle powertrain with battery management and charging systems,” Discover Artificial Intelligence, vol. 6, Art. no. 141, 2026, doi: 10.1007/s44163-025-00721-y.

28. United Nations Economic Commission for Europe, “Global technical regulation No. 20: Electric vehicle safety (EVS),” UN Global Registry, ECE/TRANS/180/Add.20, 2018. Established in the Global Registry on 13 June 2018. [Online]. Available: https://unece.org/transport/standards/transport/vehicle-regulations-wp29/global-technical-regulations-gtrs

29. State Administration for Market Regulation, Standardization Administration of China, “Safety requirements for power batteries for electric vehicles,” GB 38031-2025, 2025. Published 28 March 2025; effective 1 July 2026 for new type approvals and 1 July 2027 for existing models; supersedes GB 38031-2020.

30. International Organization for Standardization, “Road vehicles — Functional safety,” ISO 26262:2018, 2018.

31. Wang, F., Zhao, Z., Zhai, Z., Shang, Z., Yan, R., Chen, X., “Explainability-driven model improvement for SOH estimation of lithium-ion battery,” Reliability Engineering & System Safety, vol. 232, 109046, 2023, doi: 10.1016/j.ress.2022.109046.

32. Hardy, J., Steggall, J., Hardy, P., “Rethinking lithium-ion battery management: Eliminating routine cell balancing enhances hazardous fault detection,” Journal of Energy Storage, vol. 63, 106931, 2023, doi: 10.1016/j.est.2023.106931.

33. Deng, Z., Hu, X., Lin, X., Che, Y., Xu, L., Guo, W., “Data-driven state of charge estimation for lithium-ion battery packs based on Gaussian process regression,” Energy, vol. 205, 118000, 2020, doi: 10.1016/j.energy.2020.118000.

34. Chandran, V., Patil, C. K., Karthick, A., Ganeshaperumal, D., Rahim, R., Ghosh, A., “State of Charge Estimation of Lithium-Ion Battery for Electric Vehicles Using Machine Learning Algorithms,” World Electric Vehicle Journal, vol. 12, 38, 2021, doi: 10.3390/wevj12010038.

35. Ragone, M., Yurkiv, V., Ramasubramanian, A., Kashir, B., Mashayek, F., “Data driven estimation of electric vehicle battery state-of-charge informed by automotive simulations and multi-physics modeling,” Journal of Power Sources, vol. 483, 229108, 2021, doi: 10.1016/j.jpowsour.2020.229108.

36. Ren, X., Liu, S., Yu, X., Dong, X., “A method for state-of-charge estimation of lithium-ion batteries based on PSO-LSTM,” Energy, vol. 234, 121236, 2021, doi: 10.1016/j.energy.2021.121236.

37. Khan, M. K., Houran, M. A., Kauhaniemi, K., Zafar, M. H., Mansoor, M., Rashid, S., “Efficient state of charge estimation of lithium-ion batteries in electric vehicles using evolutionary intelligence-assisted GLA–CNN–Bi-LSTM deep learning model,” Heliyon, vol. 10, e35183, 2024, doi: 10.1016/j.heliyon.2024.e35183.

38. Naguib, M., Kollmeyer, P., Emadi, A., “Lithium-Ion Battery Pack Robust State of Charge Estimation, Cell Inconsistency, and Balancing: Review,” IEEE Access, vol. 9, 50570-50582, 2021, doi: 10.1109/access.2021.3068776.

39. Zou, M., Wang, J., Yan, D., Li, Y., Tang, X., “Novel state of charge estimation method of containerized Lithium–Ion battery energy storage system based on deep learning,” Journal of Power Sources, vol. 624, 235609, 2024, doi: 10.1016/j.jpowsour.2024.235609.

40. Tian, J., Xiong, R., Shen, W., Lu, J., Sun, F., “Flexible battery state of health and state of charge estimation using partial charging data and deep learning,” Energy Storage Materials, vol. 51, 372-381, 2022, doi: 10.1016/j.ensm.2022.06.053.

41. Arandhakar, S., Nakka, J., “State of charge estimation of lithium ion battery for electric vehicle using cutting edge machine learning algorithms: A review,” Journal of Energy Storage, vol. 103, 114281, 2024, doi: 10.1016/j.est.2024.114281.

42. Khan, U., Kirmani, S., Rafat, Y., Rehman, M. U., Alam, M. S., “Improved deep learning based state of charge estimation of lithium ion battery for electrified transportation,” Journal of Energy Storage, vol. 91, 111877, 2024, doi: 10.1016/j.est.2024.111877.

43. Wang, J., Zuo, Z., Wei, Y., Jia, Y., Chen, B., Li, Y., et al., “State of charge estimation of lithium-ion battery based on GA-LSTM and improved IAKF,” Applied Energy, vol. 368, 123508, 2024, doi: 10.1016/j.apenergy.2024.123508.

44. Buchicchio, E., De Angelis, A., Santoni, F., Carbone, P., Bianconi, F., Smeraldi, F., “Battery SOC estimation from EIS data based on machine learning and equivalent circuit model,” Energy, vol. 283, 128461, 2023, doi: 10.1016/j.energy.2023.128461.

45. Galiounas, E., Tranter, T. G., Owen, R. E., Robinson, J. B., Shearing, P. R., Brett, D. J., “Battery state-of-charge estimation using machine learning analysis of ultrasonic signatures,” Energy and AI, vol. 10, 100188, 2022, doi: 10.1016/j.egyai.2022.100188.

46. Li, X., Yuan, C., Li, X., Wang, Z., “State of health estimation for Li-Ion battery using incremental capacity analysis and Gaussian process regression,” Energy, vol. 190, 116467, 2020, doi: 10.1016/j.energy.2019.116467.

47. Wang, Z., Yuan, C., Li, X., “Lithium Battery State-of-Health Estimation via Differential Thermal Voltammetry With Gaussian Process Regression,” IEEE Transactions on Transportation Electrification, vol. 7, 16-25, 2021, doi: 10.1109/tte.2020.3028784.

48. Tagade, P., Hariharan, K. S., Ramachandran, S., Khandelwal, A., Naha, A., Kolake, S. M., et al., “Deep Gaussian process regression for lithium-ion battery health prognosis and degradation mode diagnosis,” Journal of Power Sources, vol. 445, 227281, 2020, doi: 10.1016/j.jpowsour.2019.227281.

49. Deng, Z., Hu, X., Li, P., Lin, X., Bian, X., “Data-Driven Battery State of Health Estimation Based on Random Partial Charging Data,” IEEE Transactions on Power Electronics, vol. 37, 5021-5031, 2022, doi: 10.1109/tpel.2021.3134701.

50. Zheng, K., Meng, J., Yang, Z., Zhou, F., Yang, K., Song, Z., “Refined lithium-ion battery state of health estimation with charging segment adjustment,” Applied Energy, vol. 375, 124077, 2024, doi: 10.1016/j.apenergy.2024.124077.

51. Roman, D., Saxena, S., Robu, V., Pecht, M., Flynn, D., “Machine learning pipeline for battery state-of-health estimation,” Nature Machine Intelligence, vol. 3, 447-456, 2021, doi: 10.1038/s42256-021-00312-3.

52. Zhao, J., Qu, X., Li, Y., Nan, J., Burke, A. F., “Real-time prediction of battery remaining useful life using hybrid-fusion deep neural networks,” Energy, vol. 328, 136618, 2025, doi: 10.1016/j.energy.2025.136618.

53. Zhou, K. Q., Qin, Y., Yuen, C., “Graph neural network-based lithium-ion battery state of health estimation using partial discharging curve,” Journal of Energy Storage, vol. 100, 113502, 2024, doi: 10.1016/j.est.2024.113502.

54. Zhao, B., Zhang, W., Zhang, Y., Zhang, C., Zhang, C., Zhang, J., “Lithium-ion battery remaining useful life prediction based on interpretable deep learning and network parameter optimization,” Applied Energy, vol. 379, 124713, 2025, doi: 10.1016/j.apenergy.2024.124713.

55. Qiang, X., Liu, W., Lyu, Z., Ruan, H., Li, X., “A data-fusion-model method for state of health estimation of Li-ion battery packs based on partial charging curve,” Green Energy and Intelligent Transportation, vol. 3, 100169, 2024, doi: 10.1016/j.geits.2024.100169.

56. Lu, J., Xiong, R., Tian, J., Wang, C., Sun, F., “Deep learning to estimate lithium-ion battery state of health without additional degradation experiments,” Nature Communications, vol. 14, Art. no. 2760, 2023, doi: 10.1038/s41467-023-38458-w.

57. Yang, Y., “A machine-learning prediction method of lithium-ion battery life based on charge process for different applications,” Applied Energy, vol. 292, 116897, 2021, doi: 10.1016/j.apenergy.2021.116897.

58. Fei, Z., Yang, F., Tsui, K. L., Li, L., Zhang, Z., “Early prediction of battery lifetime via a machine learning based framework,” Energy, vol. 225, 120205, 2021, doi: 10.1016/j.energy.2021.120205.

59. Tong, Z., Miao, J., Tong, S., Lu, Y., “Early prediction of remaining useful life for Lithium-ion batteries based on a hybrid machine learning method,” Journal of Cleaner Production, vol. 317, 128265, 2021, doi: 10.1016/j.jclepro.2021.128265.

60. Si, Q., Matsuda, S., Yamaji, Y., Momma, T., Tateyama, Y., “Data-Driven Cycle Life Prediction of Lithium Metal-Based Rechargeable Battery Based on Discharge/Charge Capacity and Relaxation Features,” Advanced Science, vol. 11, Art. no. 2402608, 2024, doi: 10.1002/advs.202402608.

61. Zhao, S., Zhang, C., Wang, Y., “Lithium-ion battery capacity and remaining useful life prediction using board learning system and long short-term memory neural network,” Journal of Energy Storage, vol. 52, 104901, 2022, doi: 10.1016/j.est.2022.104901.

62. Shi, J., Rivera, A., Wu, D., “Battery health management using physics-informed machine learning: Online degradation modeling and remaining useful life prediction,” Mechanical Systems and Signal Processing, vol. 179, 109347, 2022, doi: 10.1016/j.ymssp.2022.109347.

63. Salem, N. M., Mohamed, A., “Physics-informed hybrid reinforcement learning for estimating lithium-ion battery state of health,” Scientific Reports, vol. 15, Art. no. 43819, 2025, doi: 10.1038/s41598-025-30602-4.

64. Wang, S., Zhou, R., Ren, Y., Liu, H., Lin, Y., Lian, C., “A generalizable physics-informed neural network for lithium-ion battery SOH estimation utilizing partial charging segments,” Journal of Energy Chemistry, vol. 112, 977-986, 2026, doi: 10.1016/j.jechem.2025.08.093.

65. Gao, K., Li, Q., Hu, L., Huang, J., Li, H., Wu, Y., “Physical informed neural network for SOH estimation of lithium-ion battery with electrochemical mechanism,” Energy, vol. 342, 139753, 2026, doi: 10.1016/j.energy.2025.139753.

66. Deng, W., Le, H., Nguyen, K. T., Gogu, C., Medjaher, K., Morio, J., et al., “A generic physics-informed machine learning framework for battery remaining useful life prediction using small early-stage lifecycle data,” Applied Energy, vol. 384, 125314, 2025, doi: 10.1016/j.apenergy.2025.125314.

67. Qi, Y., Wang, J., Lu, H., Chu, H., Chen, D., Jin, J., “Remaining useful life prediction for lithium-ion battery based on hybrid machine learning with Wiener process,” Journal of Energy Storage, vol. 136, 118415, 2025, doi: 10.1016/j.est.2025.118415.

68. Fan, Y., Lin, Z., Wang, F., Zhang, J., “A hybrid approach for lithium-ion battery remaining useful life prediction using signal decomposition and machine learning,” Scientific Reports, vol. 15, Art. no. 8161, 2025, doi: 10.1038/s41598-025-92262-8.

69. Zhao, J., Li, D., Li, Y., Shi, D., Nan, J., Burke, A. F., “Battery state of health estimation under fast charging via deep transfer learning,” iScience, vol. 28, 112235, 2025, doi: 10.1016/j.isci.2025.112235.

70. Lin, M., Hu, D., Meng, J., Wu, J., “Transfer Learning-Based Lithium-Ion Battery State of Health Estimation With Electrochemical Impedance Spectroscopy,” IEEE Transactions on Transportation Electrification, vol. 11, 7910-7920, 2025, doi: 10.1109/tte.2025.3533540.

71. Cao, Z., Gao, W., Fu, Y., Kurdkandi, N. V., Mi, C., “A general framework for lithium-ion battery state of health estimation: From laboratory tests to machine learning with transferability across domains,” Applied Energy, vol. 381, 125086, 2025, doi: 10.1016/j.apenergy.2024.125086.

72. Sun, R., Chen, J., Piao, C., “Battery health features extraction and state of health estimation based on real-time online vehicle driving data,” Journal of Power Sources, vol. 645, 236784, 2025, doi: 10.1016/j.jpowsour.2025.236784.

73. Cheng, F., Liu, H., “Charging strategies optimization for lithium-ion battery: Heterogeneous ensemble surrogate model-assisted advanced multi-objective optimization algorithm,” Energy Conversion and Management, vol. 342, 120170, 2025, doi: 10.1016/j.enconman.2025.120170.

74. Dong, G., Feng, Y., Lou, Y., Zhang, M., Wei, J., “Data-Driven Fast Charging Optimization for Lithium-Ion Battery Using Bayesian Optimization With Fast Convergence,” IEEE Transactions on Transportation Electrification, vol. 10, 4173-4183, 2024, doi: 10.1109/tte.2023.3311813.

75. Wei, Z., Yang, X., Li, Y., He, H., Li, W., Sauer, D. U., “Machine learning-based fast charging of lithium-ion battery by perceiving and regulating internal microscopic states,” Energy Storage Materials, vol. 56, 62-75, 2023, doi: 10.1016/j.ensm.2022.12.034.

76. Li, Y., Li, K., Xie, Y., Liu, J., Fu, C., Liu, B., “Optimized charging of lithium-ion battery for electric vehicles: Adaptive multistage constant current–constant voltage charging strategy,” Renewable Energy, vol. 146, 2688-2699, 2020, doi: 10.1016/j.renene.2019.08.077.

77. Fan, Z., Fu, Y., Liang, H., Gao, R., Liu, S., “A module-level charging optimization method of lithium-ion battery considering temperature gradient effect of liquid cooling and charging time,” Energy, vol. 265, 126331, 2023, doi: 10.1016/j.energy.2022.126331.

78. Heydarian Ardakani, A., Abdollahi, F., “A fast balance optimization approach for charging enhancement of lithium-ion battery packs through deep reinforcement learning,” Journal of Energy Storage, vol. 89, 111755, 2024, doi: 10.1016/j.est.2024.111755.

79. Duan, S., Xia, K., Li, J., Zhao, Z., Liu, H., “Optimization charging method of lithium-ion battery based on multi-objective BBO algorithm,” Journal of Energy Storage, vol. 91, 112046, 2024, doi: 10.1016/j.est.2024.112046.

80. Wang, Y., Chen, X., Li, C., Yu, Y., Zhou, G., Wang, C., et al., “Temperature prediction of lithium-ion battery based on artificial neural network model,” Applied Thermal Engineering, vol. 228, 120482, 2023, doi: 10.1016/j.applthermaleng.2023.120482.

81. Zhou, X., Guo, W., Shi, X., She, C., Zheng, Z., Zhou, J., et al., “Machine learning assisted multi-objective design optimization for battery thermal management system,” Applied Thermal Engineering, vol. 253, 123826, 2024, doi: 10.1016/j.applthermaleng.2024.123826.

82. Yao, L., Fang, Z., Xiao, Y., Hou, J., Fu, Z., “An Intelligent Fault Diagnosis Method for Lithium Battery Systems Based on Grid Search Support Vector Machine,” Energy, vol. 214, 118866, 2021, doi: 10.1016/j.energy.2020.118866.

83. Das Goswami, B. R., Abdisobbouhi, Y., Du, H., Mashayek, F., Kingston, T. A., Yurkiv, V., “Advancing battery safety: Integrating multiphysics and machine learning for thermal runaway prediction in lithium-ion battery module,” Journal of Power Sources, vol. 614, 235015, 2024, doi: 10.1016/j.jpowsour.2024.235015.

84. Dong, C., Sun, D., “Multi-source domain transfer learning with small sample learning for thermal runaway diagnosis of lithium-ion battery,” Applied Energy, vol. 365, 123248, 2024, doi: 10.1016/j.apenergy.2024.123248.

85. Rieger, L. H., Flores, E., Nielsen, K. F., Norby, P., Ayerbe, E., Winther, O., et al., “Uncertainty-aware and explainable machine learning for early prediction of battery degradation trajectory,” Digital Discovery, vol. 2, 112-122, 2023, doi: 10.1039/d2dd00067a.

86. Si, Y., Zhou, X., Wang, Y., Zhang, T., Xiao, Y., Liu, Y., “Internal temperature sensing for lithium-ion battery under ultrahigh-rate discharge conditions using physics-informed neural network,” Applied Energy, vol. 408, 127394, 2026, doi: 10.1016/j.apenergy.2026.127394.

87. Tang, X., Guo, Q., Li, M., Wei, C., Pan, Z., Wang, Y., “Performance analysis on liquid-cooled battery thermal management for electric vehicles based on machine learning,” Journal of Power Sources, vol. 494, 229727, 2021, doi: 10.1016/j.jpowsour.2021.229727.

88. Chen, S., Zhang, G., Zhu, J., Feng, X., Wei, X., Ouyang, M., et al., “Multi-objective optimization design and experimental investigation for a parallel liquid cooling-based Lithium-ion battery module under fast charging,” Applied Thermal Engineering, vol. 211, 118503, 2022, doi: 10.1016/j.applthermaleng.2022.118503.

89. Nam, K., Ahn, C., “Energy-Efficient Battery Thermal Management in Electric Vehicles Using Artificial-Neural-Network-Based Model Predictive Control,” World Electric Vehicle Journal, vol. 16, 279, 2025, doi: 10.3390/wevj16050279.

90. Zhang, C., Zhao, S., Yang, Z., He, Y., “A multi-fault diagnosis method for lithium-ion battery pack using curvilinear Manhattan distance evaluation and voltage difference analysis,” Journal of Energy Storage, vol. 67, 107575, 2023, doi: 10.1016/j.est.2023.107575.

91. Jia, Z., Wang, Z., Sun, Z., Sun, X., Liu, P., Ruzzenenti, F., “A multi-scenario data-driven approach for anomaly detection in electric vehicle battery systems,” eTransportation, vol. 24, 100418, 2025, doi: 10.1016/j.etran.2025.100418.

92. Huang, Y., Cai, H., Lai, X., Zheng, Y., Han, X., Ren, D., et al., “Deep learning-driven detection of lithium-plating-type defects for battery manufacturing via formation and capacity grading data,” Journal of Energy Chemistry, vol. 108, 536-549, 2025, doi: 10.1016/j.jechem.2025.04.025.

93. Jeong, J., Kwak, E., Kim, J. h., Oh, K. Y., “Prediction of thermal runaway for a lithium-ion battery through multiphysics-informed DeepONet with virtual data,” eTransportation, vol. 21, 100337, 2024, doi: 10.1016/j.etran.2024.100337.

94. He, L., Tian, A., Ding, T., Dong, K., Wang, Y., Gao, Y., et al., “Lithium-ion battery state estimation based on adaptive physics-informed neural network of electrochemical model,” Measurement, vol. 257, 118985, 2026, doi: 10.1016/j.measurement.2025.118985.

95. Xu, Z., Guo, Y., Saleh, J. H., “A physics-informed dynamic deep autoencoder for accurate state-of-health prediction of lithium-ion battery,” Neural Computing and Applications, vol. 34, 15997-16017, 2022, doi: 10.1007/s00521-022-07291-5.

96. Lu, J., Xiong, R., Tian, J., Wang, C., Hsu, C. W., Tsou, N. T., et al., “Battery degradation prediction against uncertain future conditions with recurrent neural network enabled deep learning,” Energy Storage Materials, vol. 50, 139-151, 2022, doi: 10.1016/j.ensm.2022.05.007.

97. Tao, J., Wang, S., Cao, W., Fernandez, C., Blaabjerg, F., “A Comprehensive Review of Multiple Physical and Data-Driven Model Fusion Methods for Accurate Lithium-Ion Battery Inner State Factor Estimation,” Batteries, vol. 10, 442, 2024, doi: 10.3390/batteries10120442.

98. Liu, K., Niri, M. F., Apachitei, G., Lain, M., Greenwood, D., Marco, J., “Interpretable machine learning for battery capacities prediction and coating parameters analysis,” Control Engineering Practice, vol. 124, 105202, 2022, doi: 10.1016/j.conengprac.2022.105202.

99. Liu, X., Peng, H., Li, B., Chen, X., Li, Z., Huang, J., et al., “Untangling Degradation Chemistries of Lithium-Sulfur Batteries Through Interpretable Hybrid Machine Learning,” Angewandte Chemie International Edition, vol. 61, Art. no. e202214037, 2022, doi: 10.1002/anie.202214037.

100. Eaty, N. D. K. M., Bagade, P., “Digital twin for electric vehicle battery management with incremental learning,” Expert Systems with Applications, vol. 229, 120444, 2023, doi: 10.1016/j.eswa.2023.120444.

101. Yi, Y., Xia, C., Feng, C., Zhang, W., Fu, C., Qian, L., et al., “Digital twin-long short-term memory (LSTM) neural network based real-time temperature prediction and degradation model analysis for lithium-ion battery,” Journal of Energy Storage, vol. 64, 107203, 2023, doi: 10.1016/j.est.2023.107203.

102. Zhang, Y., Zhao, M., “Cloud-based in-situ battery life prediction and classification using machine learning,” Energy Storage Materials, vol. 57, 346-359, 2023, doi: 10.1016/j.ensm.2023.02.035.

103. Faraji-Niri, M., Rashid, M., Sansom, J., Sheikh, M., Widanage, D., Marco, J., “Accelerated state of health estimation of second life lithium-ion batteries via electrochemical impedance spectroscopy tests and machine learning techniques,” Journal of Energy Storage, vol. 58, 106295, 2023, doi: 10.1016/j.est.2022.106295.

104. Zhang, Y., Tang, Q., Zhang, Y., Wang, J., Stimming, U., Lee, A. A., “Identifying degradation patterns of lithium ion batteries from impedance spectroscopy using machine learning,” Nature Communications, vol. 11, Art. no. 1706, 2020, doi: 10.1038/s41467-020-15235-7.

105. Chen, J., Yao, Q., Kollmeyer, P., Vidal, C., Naguib, M., Panchal, S., et al., “Battery state-of-power estimation: A machine learning battery model with numerical searching approach,” Journal of Energy Storage, vol. 175, 123023, 2026, doi: 10.1016/j.est.2026.123023.

106. Poh, W. Q. T., Xu, Y., Tan, R. T. P., “Data-Driven Estimation of Li-Ion Battery Health: Integrating GPT-4 With Distilled Lifelong Learning,” IEEE Transactions on Energy Conversion, vol. 40, 1682-1685, 2025, doi: 10.1109/tec.2025.3548400.

107. Haghi, S., Hidalgo, M. F. V., Niri, M. F., Daub, R., Marco, J., “Machine Learning in Lithium-Ion Battery Cell Production: A Comprehensive Mapping Study,” Batteries & Supercaps, vol. 6, Art. no. e202300046, 2023, doi: 10.1002/batt.202300046.

108. Nicodemo, N., Di Rienzo, R., Lagnoni, M., Bertei, A., Baronti, F., “Estimation of lithium-ion battery electrochemical properties from equivalent circuit model parameters using machine learning,” Journal of Energy Storage, vol. 99, 113257, 2024, doi: 10.1016/j.est.2024.113257.

109. European Commission (on behalf of the UNECE Informal Working Group on Electric Vehicle Safety), “Proposal for Amendment 1 to UN Global Technical Regulation No. 20 (Electric vehicle safety): thermal-propagation requirements with two compliance options,” UN ECE working document ECE/TRANS/WP.29/GRSP/2026/4, 2026. Considered at the 79th GRSP session (June 2026); working group status report in ECE/TRANS/WP.29/GRSP/2026/3; pending before WP.29 as of 18 October 2026, with adoption listed for the 17-20 November 2026 session. [Online]. Available: https://unece.org/transport/events/wp29grsp-working-party-passive-safety-79th-session

110. International Organization for Standardization, “Road vehicles — Safety and artificial intelligence,” ISO/PAS 8800:2024, 2024. Published December 2024. [Online]. Available: https://www.iso.org/standard/83303.html

111. International Organization for Standardization, “Road vehicles — Safety of the intended functionality,” ISO 21448:2022, 2022.