COS10005 – Wed Development
Lecture 8 – JavaScript

In this session, JavaScript will be introduced.
You may follow the instructions below, to format the HTML and JavaScript with the appropriate elements.
Let's start!

1. Please open the prepared HTML file (Java_Raw.HTML) in the zip folder.
2. Insert an External JavaScript file link under the comment in HTML:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="utf-8" />
    <meta name="description" content="Demonstrates for Javascript" />
    <meta name="keywords" content="HTML, Javascript" />
    <meta name="author" content="Your Name"  />
    <!Insert External JavaScript file here>

</head>
```

External JavaScript file link statement: <script src="L8Demo1.js"></script>

3. Now open a new notepad++ and save the file as **"L8Demo1.js"**. The file name has to be same as External JavaScript file link statement: <script src=" **L8Demo1.js**"></script>

JavaScript

4. Working on 2 inputs (string). "+" the concatenation symbol is used to join 2 strings together. Alert is used to prompt/display the result.

```
function example1() {
 name1 = prompt ("Enter a name1");
 name2 = prompt ("Enter a name2");
 alert (name1 + name2);
}
```

5. To access the output, insert the calling function statement below. First create a function to call another function.

```
function init(){

}
window.onload = init;
```

6. Inside function init(), insert this statement: **example1();** to call function example1() above.

7. Working on parameters. The function has 2 parameters which will receive 2 values from the calling function.

```
function showName(name1, name2) {
alert (name1+name2);
}
```

8. To access the output, insert: **showName("Web", "Page");** inside function init()and remark (**//**) the previous function call.

9. Working on calculation from parameters passing.

```
function averageNumbers(a, b, c) {
        sum = a + b + c;
        result = sum / 3;
        return result;
}
```

10. Now insert an alert statement to prompt/display the result and remark (**//**) the previous function call.

```
alert(averageNumbers(12,34,63));
```

11. The function below is created for another 3 functions for demo purposes. Functions: scope1(), scope2() and scope3() will create later.

```
function testScope() {
    var localVariable;

    localVariable = "Changed";
    globalVariable = "Changed";
}
```

12. Scope 1

```
function scope1() {
    globalVariable = "Original";
    localVariable = "Original";
    testScope();
    alert (globalVariable + " " + localVariable);
}
```

13. To access the output, insert: **scope1();** inside function init()and remark (**//**) the previous function call.

14. Scope 2

```
function scope2() {
testScope();
alert (globalVariable + " " + localVariable);
}
```

15. To access the output, insert: **scope2();** inside function init()and remark (**//**) the previous function call.

16. Scope 3

```
function scope3() {
testScope();
alert (globalVariable);
}
```

17. To access the output, insert: **scope3();** inside function init()and remark (**//**) the previous function call.