Townlight Meetings Manual Beta 1

Windows x64 Beta 1 · MSI 1.8.1.1

Windows 1.8.1.1 adds shared meeting imports for 31 source families, with 34 supported source/format pairs. Installed Windows Sandbox checks exercised preview, save and durable readback using public captures and fixtures, plus the documented Townlight handoffs. These checks do not establish automatic discovery on every live portal or a complete retest of every module. Acceptance and limits.

- Townlight Meetings Manual
  - Contents
  - Using this manual
  - Beta identity
  - First run
  - Daily workflow
  - Connected workflows
  - Architecture
  - Transcript corrections and action items
  - Technical specifications
  - Configuration and administration
  - API and integration examples
  - MCP and automation boundary
  - Security and permissions
  - Backup recovery and maintenance
  - Troubleshooting
  - Verified workflows and limits
  - Terms of service and license
  - Glossary
  - Alphabetical subject index
  - Source and document control

Townlight Meetings Manual

Townlight Beta 1 · Naming candidate documentation edition 2 November 2026

Contents

- Using this manual
- Beta identity
- First run

- Daily workflow
- Connected workflows
- Architecture
- Transcript corrections and action items
- Technical specifications
- Configuration and administration
- API and integration examples
- MCP and automation boundary
- Security and permissions
- Backup recovery and maintenance
- Troubleshooting
- Verified workflows and limits
- Terms of service and license
- Glossary
- Alphabetical subject index
- Source and document control

Using this manual

Townlight Meetings helps clerks, meeting coordinators and authorized reviewers. Meetings supports clerk preparation and the retained proceedings of a meeting: agenda items, packets, motions, votes, supplied transcript material, minutes decisions and archives. It supplies canonical meeting and agenda context to Station.

Staff should begin with First run and Daily workflow. Administrators should also read Architecture, Technical specifications, Configuration, Security and Recovery. Developers should use the exact API/data dictionary and examples. The table of contents and alphabetical subject index link to the relevant sections in the HTML edition; the PDF preserves headings and searchable text. An editable Word edition is included with the same documentation companion.

Beta identity

Identity	Value
Public documentation identity	Townlight Beta 1
Windows MSI version	1.8.1.1
Product component	townlight-meetings 1.0.5
Principal import package	townlight_meetings
Native desktop source version	1.8.1-1
Candidate MSI SHA256	Windows acceptance summary
Corresponding-source SHA256	Corresponding source archive and checksums
Current owned software license	AGPL-3.0-only
Supported acceptance profile	Windows x64 fresh install and upgrade from

Identity	Value
	1.7.2.1. Select the full profile. Station uses separate configuration.

Windows MSI 1.8.1.1 includes Townlight Meetings 1.0.5. The approved profile path is `%LOCALAPPDATA%\CivicSuite`. Preserve existing profiles, data and backups.

First run

Windows 1.8.1.1 has fresh-install acceptance. An in-place upgrade to 1.8.1.1 was not exercised. The previous Windows 1.8.0.1 release tested upgrade from 1.7.2.1; that result applies to 1.8.0.1. Before an existing-city evaluation, back up city data and settings, close Townlight, keep the existing %LOCALAPPDATA%\CivicSuite profile, and use the same Windows account. Keep the prior installer and a restore path. Station continues to use its separately configured service.

Fresh installation

Run the signed Windows 1.8.1.1 MSI and use an empty database and a new Townlight profile for first run.

1. Download the signed MSI, matching source companion and checksums from the public Windows release.
2. Verify the MSI hash and Authenticode publisher before installation. See the Windows acceptance summary for the tested setup.
3. Launch Townlight under the intended named Windows account. Choose the storage folders. Select **Townlight Inspections candidate** (`inspections-preview`) for the bounded desktop composition, including Access and Notice. A narrower selection will not expose all workspaces.
4. Enter the city profile, time zone and contacts. Create the first named local administrator, sign in and choose protected backup storage. **Continue without local AI** is valid for the deterministic workflows.
5. Run Health Check and wait for readiness. Open Townlight. In System Health select **Finish Records Migration** to activate the canonical Python/PostgreSQL runtime. Do not fabricate migration receipts or seed accounts.
6. Create named staff through Settings. Import authorized sources using each product's source library. All examples in this package are synthetic; they are not municipal authority.
7. Provision Station separately if it is part of the beta exercise. Selecting the desktop composition does not start or configure Station. Configure vision explicitly only if automatic photo drafting is selected.

Daily workflow

1. Create the meeting

Enter its title, date/time including the intended time zone, location and meeting type. Save and reopen it before adding downstream evidence.

2. Prepare the agenda and packet

Create agenda items, assign them to the actual meeting and record review. Assemble a packet from the selected items and source documents. Check the saved assembly's packet identifier before using it for an archive or delivery.

3. Record notice work

Use the existing notice checklist, template and posting-proof controls where applicable. A calculated checklist is evidence for clerk review; staff verify the jurisdiction's notice requirements and actual posting.

4. Record proceedings

Capture the actual motion, seconder and votes. Record corrections as corrections, preserving the earlier event. Retain supplied transcript text with its source label.

5. Review minutes

Draft from identified source material. Check the citations and wording. Record the explicit minutes decision; a draft or a motion is not adopted minutes.

6. Record legislation evidence

When an ordinance or resolution is adopted, record the actual Code connection decision. Code staff separately perform codification; meeting adoption does not silently rewrite the code.

7. Archive and hand off

Choose the appropriate visibility and saved packet/minutes. Inspect the resulting proceedings and permitted archive. Use Station's operator for capture and Records for a separate response/release.

Working safely

Use your own named account and save before leaving a screen. A saved draft is durable; unsaved form text may not be. If a write has an unknown result, reopen its record before repeating it.

Read source jurisdiction, dates, citation, version and visibility. A copied source hash identifies exact bytes, not their legal applicability. If a source changes or permission is removed, resolve the source problem rather than substituting stale cached content.

Keep originals and derivatives separate. Review the intended audience before export. A public summary excludes private fields only through the applicable copy contract and your review. A renamed private packet is still private content.

Drafting, review, approval, attachment, export, fulfillment and publication are separate operations. A Townlight workpaper does not itself adopt law, issue a permit, impose a fine or release a records response. The responsible staff member records the applicable decision.

Connected workflows

Provides evidence to Records, Code, Zoning and Planning, and meeting identity to Station. Code adoption and codification remain separate. Supporting Notice and Access do not replace clerk review.

Direction	Material
Input	A meeting schedule, staff agenda material, source documents, recorded clerk decisions and supplied transcript text.
Output	Versioned meeting evidence, packets, proceedings, reviewed minutes and permitted archive documents. Station receives the selected meeting and agenda snapshot.

Product boundary

Supplied transcript handling is not automatic audio transcription. Station adds capture; it does not imply a Meetings livestream hosting service. Vendor sync code and adapters are not proof that every vendor is configured or live.

Architecture



Townlight Meetings architecture and evidence flow

The drawing shows the principal staff/evidence path. Native commands carry trusted identity to Python business services; PostgreSQL and retained original files hold durable state. A downstream copy does not silently transfer decision authority. Station has its own configured authority/media boundary, database and mutable files. The connected-workflow text supplies the drawing's reading order and accessibility alternative.

Transcript corrections and action items

Preserve supplied transcript history

1. Save the actual meeting first. Retain the supplied text's source label and confirm that the material belongs to that meeting. Supplied text is not automatic audio transcription.
2. Use the transcript capture operation. The installed route is `POST /desktop/v1/meetings/meetings/{meeting_id}/transcripts`. It requires `source_label` and `transcript_text`; the server attributes the signed-in actor.
3. Read the meeting's proceedings and retain the returned transcript `id`. If text needs correction, submit a **new capture** for the same meeting with `correction_of_id` set to that original ID. Do not replace the original row or silently edit its audit history.
4. Read proceedings again and confirm both entries, their source labels, actor/time and correction link. A correction referencing an entry from another meeting is refused. Reconcile the corrected text before using it in reviewed minutes.

For an already saved synthetic meeting, an initial request body is:

```
{"source_label":"Synthetic clerk text v1","transcript_text":"The synthetic meeting opened at 18:00."}
```

A subsequent correction body is:

```
{"source_label":"Synthetic clerk correction v2","transcript_text":"The synthetic meeting opened at 18:05.","correction_of_id":"11111111-1111-4111-8111-111111111111"}
```

Replace the example UUID with the ID returned by the first capture. An HTTP client must use the existing authenticated native proof as described in the technical reference. Readback uses `GET /desktop/v1/meetings/meetings/{meeting_id}/proceedings`; its `transcripts` collection preserves the append-only entries. Correcting a transcript does not automatically revise adopted minutes or publish the material.

Retain action items with the proceedings

Use `POST /desktop/v1/meetings/meetings/{meeting_id}/action-items` with a description, optional assignee and optional saved source motion ID. For example:

```
{"description":"Prepare the synthetic follow-up
report","assigned_to":"Synthetic staff","source_motion_id":null}
```

If linking a motion, obtain its actual saved identity and keep the item in its meeting context. Inspect the returned identity and the `action_items` collection in proceedings. This captures a retained action item; it does not send an email, enforce a task deadline or turn a note into adopted legislation. Where a native screen does not expose this field, technical staff use the existing authenticated API rather than an invented button.

Source contracts: `townlight_meetings/transcripts.py`, `townlight_meetings/motion_vote.py` and `townlight_runtime/meetings_bridge.py`. The exact motion repository filename and all mounted route models are retained in the source inventory/API companion.

Technical specifications

Runtime and storage

The accepted package supports Windows x64 fresh installation and upgrade from 1.7.2.1. Its native shell uses **Rust 2021, Tauri 2 and Microsoft WebView2**; browser assets are JavaScript built with **Vite 8.1.6**. This describes the native desktop frontend; Station has a separate React operator, specified below or in its product manual. Canonical business workflows use bundled **CPython 3.13.5, FastAPI, Pydantic, SQLAlchemy and Alembic**, with **PostgreSQL 17 / PostGIS** and managed original files. The installed runtime tested here contains FastAPI 0.162.0. Package minimum Python requirements can differ from the bundled executable; the metadata reference preserves both. No stack rewrite is implied by the beta label.

The native transport is fixed to loopback `127.0.0.1:15480`; PostgreSQL uses the configured local runtime port (default `15432`). Optional local model service defaults to `127.0.0.1:15434`. Those are deployment defaults, not internet endpoints. The runtime has health, module and readiness endpoints; readiness is stronger than process existence. The task queue is the existing local Core task infrastructure, not an assertion that a separate Redis service is required for this desktop composition.

The default native profile is `%LOCALAPPDATA%\CivicSuite`; the historical directory name remains part of compatibility. Do not rename it to Townlight. A configured `TOWNLIGHT_PROFILE_ROOT` must be absolute. Local configuration and secrets live under that

profile; protected managed files and database state must be backed up coherently. Source/runtime identity is distinct from a product's display label.

Data and consistency

Meetings and stages; agenda items and assignments; packet snapshots and deliveries; notices and posting proof; motions and corrections; votes; transcript records; minutes drafts and decisions; archives.

Versioned saves use expected prior revision identifiers where defined. Reopen and reconcile on conflict. Exact exports and handoffs use source IDs, current visibility, revision and SHA256. Review belongs to the saved revision and does not transfer silently to edited text. Database changes use the owning product's migrations; a request or readiness check is not an authorization to mutate schema.

Capacity and platform statements

This beta has synthetic single-profile workflow evidence. It does not have a published benchmark for concurrent staff capacity, minimum RAM/CPU, large-source limits or a field SLA. Do not turn a developer machine's specification into a supported minimum. The signed MSI is 2,081,316,864 bytes; allow additional disk for extracted runtime, database, originals, exports, media and backups. Select equipment/storage after sizing those actual workloads.

The exact runtime payload lock records pinned files, sizes and hashes. The component metadata records shipped dependency declarations. These references are more precise than a manually copied dependency list. Third-party and historical license notices must accompany their matching payloads.

Configuration and administration

Native deployment configuration

Use Setup, Settings and System Health for supported staff operation. Administrators provision folders, backup storage, named accounts and the city profile. Select `inspections-preview` for the bounded desktop composition, including Access and Notice. Station remains a separate service boundary. Do not use a standalone product's demo server as a substitute for the installed workspace.

Technical deployments use `TOWNLIGHT_PRODUCT_PROFILE`, `TOWNLIGHT_PROFILE_ROOT`, `DATABASE_URL`, `TOWNLIGHT_RUNTIME_PORT`, `PORTAL_MODE` and the runtime-managed secret files. Treat database URLs and native session proofs as secrets. The installed native domain runtime explicitly refuses non-loopback binding. `PORTAL_MODE=private` is the accepted posture; changing it does not by itself commission an internet portal, authentication provider or reverse proxy.

The isolated documentation exporter sets a fictional profile and unusable synthetic database origin only to read schemas; those values are not deployment configuration. Keep deployment values in the intended process/account scope. An already-running process does not automatically inherit later environment edits.

API and integration examples

Native command example

The following JavaScript belongs in the existing trusted Townlight frontend/development environment with `invoke` imported from `@tauri-apps/api/core`. It is not a command for an arbitrary web page or an instruction for nontechnical staff. IDs must come from records created in an isolated synthetic exercise.

```
import { invoke } from '@tauri-apps/api/core';
const result = await invoke('meetings_domain_request', {request: {operation:
'get-proceedings', id: meetingId}});
console.log(result);
```

Trusted local HTTP example

An administrator/developer can inspect an already-configured isolated runtime from a trusted local process. This PowerShell example reads the signed-in synthetic profile's existing proof into memory; it does not create a user, seed a session, reveal the proof in output or bypass a permission check. Do not use real city data in development examples. A read response does not prove approval or publication.

```
$profilePath = Join-Path $env:LOCALAPPDATA 'CivicSuite'
$sessionPath = Join-Path $profilePath 'config\local-session.json'
$session = Get-Content -LiteralPath $sessionPath -Raw | ConvertFrom-Json
$headers = @{ 'X-Townlight-Session' = $session.session_hash }
Invoke-RestMethod -Uri
'http://127.0.0.1:15480/desktop/v1/meetings/station/catalog' -Headers
$headers
Remove-Variable session, headers
```

A synthetic write with subsequent readback

This example demonstrates the existing Meetings HTTP contract in an isolated exercise. It is intentionally fictional. It does not start a service. Its authentication setup is included so it can be run independently under the signed-in synthetic account. If a write times out, inspect current records before repeating it.

```
$profilePath = Join-Path $env:LOCALAPPDATA 'CivicSuite'
$sessionPath = Join-Path $profilePath 'config/local-session.json'
$session = Get-Content -LiteralPath $sessionPath -Raw | ConvertFrom-Json
$headers = @{ 'X-Townlight-Session' = $session.session_hash }
$body = @{
  title = 'Synthetic documentation exercise'
  scheduled_start = '2026-11-05T18:00:00-07:00'
  location = 'Synthetic room'
  meeting_type = 'regular'
} | ConvertTo-Json
$meeting = Invoke-RestMethod -Method Post `
  -Uri 'http://127.0.0.1:15480/desktop/v1/meetings/meetings' `
```

```
  -Headers $headers -ContentType 'application/json' -Body $body
Invoke-RestMethod `
  -Uri ('http://127.0.0.1:15480/desktop/v1/meetings/meetings/' + $meeting.id)
`
  -Headers $headers
Remove-Variable session, headers
```

This write requires Meetings to be enabled and the signed-in staff role to permit it. It is a cross-suite integration example; for this product's request models, use the complete technical reference below.

Complete technical contract

Read the Meetings API reference for every documented operation, request field, constraint, response declaration and source supplement. Download the OpenAPI JSON for tools. For Station this is the suite-side schema only; its separate service contract is documented in the API supplement. The reference directory includes configuration/source inventories, dependency declarations, native command contracts, MCP signatures and candidate evidence.

MCP and automation boundary

No direct product MCP server is exposed by the accepted Townlight desktop or Station boundary. Do not configure an invented `townlight mcp` command or assume an AI client has staff permissions. The integration surfaces for this beta are native IPC, the documented HTTP APIs, source bundle imports, exact exports and the existing Station CLI.

The bundled transcription code includes a **TextFlowKit MCP adapter** as a separate source capability. It offers job-based `transcribe_media`, `get_transcript`, `list_jobs`, `get_job_status` and `export_transcript`, and additional tools declared in that adapter. It uses stdio first and optional Streamable HTTP, with the MCP SDK as an optional extra. It is not automatically launched, authenticated as Townlight staff or accepted as a Townlight product MCP deployment. This documentation does not add such a service.

For a transcription client already provisioned separately, an illustrative tool call is:

```
{"name":"get_job_status","arguments":{"job_id":"synthetic-existing-job-id"}}
```

Use a job ID returned by that transcription service. This example does not create a Townlight record or bypass its review/Records handoff. The exact optional adapter tool signatures are supplied in the MCP source reference. Station meeting capture does not become live speech recognition because this optional donor adapter exists.

Security and permissions

Use your own named account and save before leaving a screen. A saved draft is durable; unsaved form text may not be. If a write has an unknown result, reopen its record before repeating it.

Read source jurisdiction, dates, citation, version and visibility. A copied source hash identifies exact bytes, not their legal applicability. If a source changes or permission is removed, resolve the source problem rather than substituting stale cached content.

Keep originals and derivatives separate. Review the intended audience before export. A public summary excludes private fields only through the applicable copy contract and your review. A renamed private packet is still private content.

Drafting, review, approval, attachment, export, fulfillment and publication are separate operations. A Townlight workpaper does not itself adopt law, issue a permit, impose a fine or release a records response. The responsible staff member records the applicable decision.

The native session is validated and mapped to a persisted SQL identity. An editable actor/reviewer label is not authentication. Product/module permissions and source visibility apply at the server boundary. Revoked/unavailable authority fails closed for new Station operations; a previous permission result is not a perpetual authorization.

Use protected local folders, account permissions and credential storage. Never include the native session file, database passwords, provider keys or unredacted support bundles in a public issue or generated public documentation. A local public view is not automatically a secured internet deployment. Keep network exposure and real equipment acceptance specific to the chosen beta site.

Backup recovery and maintenance

Save work and use Core's canonical **Backup Now** before maintenance. That operation stops writers. Preserve the coherent profile/database/document backup and its receipt, then use **Start** to resume. A source export is not a full backup.

Use **Restore Latest Backup** through the supported controls. If the result says **Restore needs service start**, use **Start**, then **Check**, and reopen a known record. Do not repeat restore merely because services need to start. The Windows 1.6.0.1 Beta 1 fresh-install acceptance verified that a fulfilled request survived restore and a post-backup marker did not.

Keep Station's dedicated database and media evidence together in its own backup. Core's native-profile backup must not be assumed to include an external Station data directory. Stop writers during a coordinated backup. Preserve failed media attempts and logs.

On failure, record the time, selected composition, component/installer versions and exact message. Check System Health for stopped, starting, ready or failed dependencies. Use the existing Retry control after readiness; do not create duplicate business records to refresh a stale view. Share only a redacted diagnostic bundle. Preserve secrets, original evidence, recovery material and unrelated installations.

Troubleshooting

Symptom	Likely meaning	Next action
Workspace absent	Wrong product composition or unavailable canonical runtime.	Check selected composition; activate through Finish Records Migration; wait for readiness.
Cannot sign in / 401	Missing or expired named account session.	Sign in normally; reopen a Station launch ticket if

Symptom	Likely meaning	Next action
		applicable.
Permission denied / 403	Account, module, source or browser-origin permission.	Ask the authorized administrator to inspect the intended permission; do not invent role headers.
Save conflict / 409	The saved revision, expected source hash or lifecycle changed.	Keep edits, reopen current state and reconcile deliberately.
Invalid input / 422	Required field, format, geometry, source envelope or state is invalid.	Read the field detail and correct the input/source; preserve originals.
Service unavailable / 503	Database, schema, connected source or configuration unavailable.	Inspect System Health and the named dependency. Preserve work; retry only after readiness.
Export refused	Missing exact review, approval, audience or source authorization.	Read the refusal and complete the owning product's explicit decision.
Restore needs service start	The snapshot was restored but services have not resumed.	Use Start, then Check and verify a saved record; do not blindly repeat restore.

Verified workflows and limits

The table records selected synthetic workflows from the original Windows 1.6.0.1 Beta 1 Sandbox run. Station's later delivery has separate Windows 1.6.0.1 acceptance. See the Windows 1.8.0.1 acceptance summary for the workflows and upgrade path exercised on the previous 1.8.0.1 MSI.

Product	Recorded result	Precisely exercised
Meetings	PASS	Meeting/agenda, packet assembly, motion/vote, supplied transcript, reviewed/adopted minutes, restricted local archive and proceedings readback; Code decision integration.

The Windows 1.8.0.1 acceptance covers the tested installation paths and selected synthetic workflows, including Boards & Commissions, Contracts, and Procurement. Earlier results apply to their original builds. City field acceptance, physical equipment and network commissioning, Station automatic provisioning, and comprehensive UI and role coverage remain outside the 1.8.0.1 checks.

Terms of service and license

Scope and status

These terms describe the Townlight Beta 1 software and this documentation package. This public Windows beta is for evaluation. No uptime commitment, support response time, indemnity, data-processing agreement or paid service is created by these documents. A separate signed agreement, if any, governs services it actually provides.

Software license and rights

Current Townlight-owned distributions identified in this candidate use **AGPL-3.0-only**. The full license is supplied with this documentation and with the source companion. The license governs rights to run, copy, modify and convey the covered software; these operational terms do not add restrictions to those rights. Historical grants and dependency licenses retain their own terms. CivicCast remains a separate product and is not relicensed by this documentation work.

When conveying covered software, retain applicable notices and provide the corresponding source and installation/build information required by the license. For a modified version supporting remote network interaction, follow section 13's source-offer requirement. The companion archive identifies the source for this candidate; a link to a different public branch is not a substitute for the matching source. Read the supplied license for the complete conditions. See the GNU license reference and GNU licensing FAQ.

Data ownership and access

Importing a document does not transfer its ownership or grant permission to publish it. The operating organization controls its accounts, access decisions, lawful source use, retention and review/release policy. Keep resident information, credentials, private notes and restricted evidence in their authorized locations. Documentation examples contain fictional data. No real city account, credential or record is required to exercise these examples in an isolated test environment.

Local operation and external processors

The accepted beta workflow is local and uses named staff accounts. Station has separate storage and credentials. Configure backup destinations and optional model/network providers deliberately. A configured external provider may receive submitted prompts, images or audio according to that configuration and provider's terms; this documentation does not promise that every optional configuration is offline. An email outbox or local public view does not establish external delivery or an internet deployment. This static documentation site has no analytics, account collection or remote font dependency.

Staff decisions and source applicability

Staff verify the jurisdiction, source currency, permissions, citations and proposed audience. Model output and generated guidance require review. No draft is automatically an official legal interpretation, zoning determination, permit approval, fee assessment, enforcement notice or

records-release decision. Official permit fee authority remains with the adopted source and responsible organization; imported amounts do not become a new authoritative calculation.

Beta operation and recovery

Windows 1.8.0.1 was tested for fresh installation and in-place upgrade from 1.7.2.1. Upgrade paths from versions older than 1.7.2.1 are unverified. Station uses its separately configured service. Keep backups and original evidence. Test your physical equipment and network and service configuration before relying on them. See the acceptance summary for the tested paths.

Warranty and liability

The covered software's warranty and liability conditions are those in sections 15–17 of the supplied AGPL and any applicable separate written undertaking. This documentation creates no additional warranty or limitation beyond those terms. Third-party software is subject to its retained license notices. Nothing here removes rights that applicable law makes nonwaivable.

Support and incident reporting

Use the project's existing SUPPORT and SECURITY guidance for its matching repository. Report reproducible behavior with the version, operation and redacted logs. Do not put credentials, resident records or unredacted evidence in a public issue. Coordinate sensitive reports through the channel designated in SECURITY. No new support address or service commitment is invented here.

Ending a beta exercise and document changes

When an organization ends testing, it controls retention/export and removes access according to its policy. Uninstall may retain data; back up and inspect the selected removal options. Ending an exercise does not revoke rights already granted by AGPL. Later software/documentation versions must identify their changed candidate and scope; historical receipts retain their original identities. These terms do not claim that a city has accepted a contract merely by reading a manual.

Glossary

Term	Meaning
Approval	An explicit authorized decision on the saved text/artifact. It is separate from saving or attachment.
Canonical record	The owning product's retained identity and saved version, rather than an editable copied label.
Composition	The selected set of desktop modules; inspections-preview exposes the eight staff products.
Corresponding source	The source/build material matching the delivered covered program, subject to its

Term	Meaning
	license.
Derivative / Records copy	A separately prepared document with its own intended audience and hash.
Hash / SHA256	A fingerprint of exact bytes. It detects change; it does not establish legal authority.
Idempotency	Repeating the same identified request has the same intended effect; changing its payload can be refused.
IPC	The native desktop command boundary between its browser interface and Rust host.
MCP	Model Context Protocol; no direct Townlight product server is enabled by this beta.
Original	Retained source bytes. A reviewed derivative does not replace them.
Provenance	Source, version, date, actor and relationship information retained with evidence.
Revision	An immutable saved version. Later edits do not inherit an earlier review automatically.
Snapshot	A fixed audience-specific copy tied to a source/reviewed revision.
Station	Townlight’s separate media boundary using a pinned CivicCast-derived engine; standalone CivicCast remains separate.

Alphabetical subject index

- **Accounts and authentication** — Security and permissions.
- **AGPL and source** — Terms of service and license.
- **API contracts** — API and integration examples.
- **Architecture** — Architecture.
- **Backup** — Backup recovery and maintenance.
- **Beta version** — Beta identity.
- **Configuration** — Configuration and administration.
- **Evidence and acceptance** — Verified workflows and limits.
- **Fees and official decisions** — Terms of service and license.
- **First run** — First run.
- **Handoffs and audience** — Connected workflows.
- **MCP** — MCP and automation boundary.
- **Originals and provenance** — Security and permissions.
- **Recovery** — Backup recovery and maintenance.

- **Staff procedures** — Daily workflow.
- **Station configuration** — Configuration and administration.
- **Technical stack** — Technical specifications.
- **Troubleshooting** — Troubleshooting.

Operating subject links

- **Preserve supplied transcript history** — Preserve supplied transcript history.
- **Retain action items with the proceedings** — Retain action items with the proceedings.
- **Transcript corrections and action items** — Transcript corrections and action items.

Source and document control

This edition is authored from the immutable corresponding-source companion, the generated installed-domain schema and the retained workflow receipts. The current software versions and signed artifacts are unchanged. Public historical pages are not synchronized or published by this local documentation task.

Workflow subject index

- **Archive and hand off** — Daily workflow, step 7.
- **Create the meeting** — Daily workflow, step 1.
- **Prepare the agenda and packet** — Daily workflow, step 2.
- **Record legislation evidence** — Daily workflow, step 6.
- **Record notice work** — Daily workflow, step 3.
- **Record proceedings** — Daily workflow, step 4.
- **Review minutes** — Daily workflow, step 5.
- Source inventory and file hashes
- All component metadata
- Installed domain OpenAPI
- Workflow matrix
- Full AGPL text

The resident portal is deployed separately. See the Townlight Portal Guide for its workflow and acceptance limits.

Shared meeting imports · Windows 1.8.1.1

Windows 1.8.1.1 adds shared meeting imports for 31 source families, with 34 supported source/format pairs. Installed Windows Sandbox checks exercised preview, save and durable

readback using public captures and fixtures, plus the documented Townlight handoffs. These checks do not establish automatic discovery on every live portal or a complete retest of every module.

All 31 sources, formats, operator steps and integration contracts · Installed acceptance and limits.

Windows 1.8.1.1 has fresh-install acceptance. An in-place upgrade to 1.8.1.1 was not exercised. The previous Windows 1.8.0.1 release tested upgrade from 1.7.2.1; that result applies to 1.8.0.1. Before an existing-city evaluation, back up city data and settings, close Townlight, keep the existing %LOCALAPPDATA%\CivicSuite profile, and use the same Windows account. Keep the prior installer and a restore path. Station continues to use its separately configured service.

The accepted MSI contains Townlight Runtime 0.3.1 and Meetings 1.0.6 distributions. Its health version strings still report Runtime 0.3.0 and Meetings 1.0.5. Default-branch source corrects those display strings; the signed MSI and its exact build source remain unchanged.

Shared meeting imports

Use **Meetings → Import meeting records** in Windows 1.8.1.1. Select a source and format, enter the original public URL, then choose **Preview import**. For a saved response, select the file before previewing. Choose a meeting and use **Save selected meeting**. Townlight records the source URL, format, stable source ID and capture hash with the canonical meeting. Reopening the same capture returns the existing meeting. A changed capture for that identity is reported for staff review.

The source and format selector lists the supported reader pairs below. A public URL must serve the chosen format directly. Use a saved public response for POST-only listings, portals that require a browser session and sources whose page does not return the required response. The importer reads what a municipality publishes in that response. Fields and attachments vary by municipality and by meeting.

Source	Input to preview
Legistar	Core-format JSON export
PrimeGov	Core-format JSON export or public portal meeting list JSON
Granicus	Core-format JSON export or public ViewPublisher HTML
NovusAGENDA	Core-format JSON export
CivicPlus Agenda and Meeting Management Select	Public Events JSON
CivicPlus Agenda Center	Public listing HTML
Municode Meetings	Public meetings HTML
BoardBook	Public organization HTML
eSCRIBE	Public calendar JSON
Simbli	Public meeting listing HTML
iCompass CivicWeb	Public meeting-type listing HTML

Source	Input to preview
iQM2	Public meeting list HTML
Granicus Swagit	Public video archive HTML
SuiteOne Media	Public meeting archive HTML
Granicus Peak	Public agenda center ViewPublisher HTML
Utah Public Notice Website	Public notice detail HTML
Destiny AgendaQuick	Public meeting list HTML
Town Hall Streams	Public archive HTML
TelVue	Public playlist HTML
CHAMP	Public event JSON
Hyland OnBase	Public Agenda Online HTML
Laserfiche WebLink	Saved public dated document folder HTML
TownCloud	Saved public agenda table JSON or public agenda detail HTML
Digital Towpath	Public meeting detail HTML
ClerkBase	Public meeting document HTML
Municipality-published calendar	Public iCalendar feed
Wistia	Public media JSON
Boardable	Public Site meeting detail HTML
gWorks FrontDesk	Public city meetings JSON
Diligent BoardDocs	Unencrypted printed agenda PDF with numbered items
Tyler Meeting Manager	Saved public calendar JSON. Meeting information and item titles when present.

Staff handoffs

- **Core and Meetings.** Core's existing vendor formats share the same preview and save path as the public readers. The saved meeting and any structured agenda items open in the regular Meetings workflow.
- **Records.** In Meetings, load imported documents by meeting ID, choose a PDF and enter the destination Records request ID. The attachment retains the citation and file hash. An HTML viewer or a dead document link may need staff to obtain the PDF separately.
- **Notice and Access.** Use **Review imported text** to start a Notice draft or accessibility review with the source citation. Use each workspace's normal review and save actions.

- **Station.** In the configured Station operator page, select the saved meeting and stage a direct MP4. Use the private capture workflow to queue processing. Player-only references are visible without a staging action.
- **Code.** Use the existing ordinance proposal and adoption workflow with the canonical imported meeting and agenda IDs.
- **Boards, Contracts, Procurement, Zoning, Planning, Permitting and Inspections.** In the destination workspace use **Imported meeting evidence**. Select an existing staff record and the saved meeting, then save the citation. The destination's existing role and workflow apply.

Shared interface

The installed Townlight Python runtime exposes a read-only CLI. CivicCast and other local clients can consume its normalized JSON and apply their own access and persistence rules.

```
python -m townlight_runtime.meeting_imports champ PUBLIC_EVENT_URL saved-event.json --format champ-event-json
```

Use `--fetch` in place of the saved file to read a supported public response.

Interfaces and other products

The version-1 normalized JSON contract is shared by the Python function `townlight_runtime.meeting_imports.preview_export(connector, source_url, content, input_format=...)` and the CLI above. A saved response can also be read from stdin using `-`. Inputs are limited to 16 MiB. Preview is read-only; the consuming application owns persistence, staff authorization and its own data.

The installed native HTTP bridge exposes `GET /desktop/v1/meetings/imports/sources`, `POST /desktop/v1/meetings/imports/preview`, `POST /desktop/v1/meetings/imports/fetch`, `POST /desktop/v1/meetings/imports/commit`, and meeting/link/document handoff operations in the native API schema. Use the existing `X-Townlight-Session` authentication, mapped staff roles and configured local PostgreSQL service. This is a native application interface; there is no independent anonymous importer HTTP service or importer MCP server.

CivicCast: opt in through its Townlight shared importer source setting and `TOWNLIGHT_IMPORT_PYTHON` (the absolute Python executable), `TOWNLIGHT_IMPORT_CONNECTOR`, `TOWNLIGHT_IMPORT_FORMAT`, `TOWNLIGHT_IMPORT_URL` and optional `TOWNLIGHT_IMPORT_CAPTURE`. The adapter saves normalized items through the existing AgendaStore. Structured agenda availability depends on the source response; a video listing can contain meeting metadata without agenda items. Existing sources remain the default.

CivicCast Brief: its existing PrimeGov and Granicus discovery routes can opt into the shared reader using `TOWNLIGHT_IMPORT_PYTHON`. Brief does not expose all 31 sources as a new selection menu. Its existing caption/media workflow remains the consuming path. See each project's shared-import client documentation.

TownReporter, Describer Workbench and Textflowkit: no shared-import adapter was added to these products. TownReporter retains its own PrimeGov path. Describer Workbench and Textflowkit expose their existing transcription APIs/MCP interfaces, which do not constitute meeting-import integration. The shared engine ships inside Townlight Runtime; a standalone library is outside this release.

Windows acceptance and limits

Windows 1.8.1.1 adds shared meeting imports for 31 source families, with 34 supported source/format pairs. Installed Windows Sandbox checks exercised preview, save and durable readback using public captures and fixtures, plus the documented Townlight handoffs. These checks do not establish automatic discovery on every live portal or a complete retest of every module.

Windows 1.8.1.1 has fresh-install acceptance. An in-place upgrade to 1.8.1.1 was not exercised. The previous Windows 1.8.0.1 release tested upgrade from 1.7.2.1; that result applies to 1.8.0.1. Before an existing-city evaluation, back up city data and settings, close Townlight, keep the existing %LOCALAPPDATA%\CivicSuite profile, and use the same Windows account. Keep the prior installer and a restore path. Station continues to use its separately configured service.

The accepted MSI contains Townlight Runtime 0.3.1 and Meetings 1.0.6 distributions. Its health version strings still report Runtime 0.3.0 and Meetings 1.0.5. Default-branch source corrects those display strings; the signed MSI and its exact build source remain unchanged.

Exact Windows 1.8.1.1 acceptance and limits.