

Mr-Moneybags-v1.x

Installation Guide – Ubuntu 24.04 LTS Guest in VirtualBox (Windows / macOS Host)

Document version 1.x – August 2025

1 Overview

This guide walks through a **clean installation** of **Mr-Moneybags-v1.x** inside an Ubuntu 24.04 LTS virtual machine (VM) running under Oracle VM VirtualBox.

The procedure matches the **working macOS reference environment** (Node.js 18, PostgreSQL 16, Express 5) and leverages the project's cross-platform automation scripts.

2 Prerequisites & Host Requirements

Component	Minimum	Recommended
Host OS	Windows 10/11 or macOS 13+	—
CPU	4 physical cores with VT-x / AMD-V	6+ cores
RAM	8 GB	16 GB (allocate \geq 6 GB to guest)
Disk	40 GB free	80 GB on SSD / NVMe
Software	Oracle VirtualBox \geq 7.0, Ubuntu 24.04 Desktop ISO	—

Enable hardware virtualization in BIOS/UEFI before installing VirtualBox.

3 Create the VirtualBox VM

1. Download software

- VirtualBox: <https://www.virtualbox.org/wiki/Downloads>
(<https://www.virtualbox.org/wiki/Downloads>).
- Ubuntu 24.04 ISO: <https://ubuntu.com/download/desktop> (<https://ubuntu.com/download/desktop>).

2. New VM

- Name `Ubuntu24-MrMoneybags-v1x`
- Type *Linux* → Version *Ubuntu (64-bit)*
- Memory **6144 MB** • Processors **4 vCPU**
- Disk **VDI**, dynamically allocated, **60 GB**

3. Tweaks

Display → Graphics Controller **VBoxSVGA**, enable **3-D Acceleration**

Network Adapter 1 → **Bridged** (preferred) or **NAT**

Storage → attach the Ubuntu ISO.

4. Install Ubuntu

Normal installation, enable third-party codecs (optional).

Create user **fundadmin** (will have `sudo`).

After first boot:

```
sudo apt update && sudo apt -y upgrade  
sudo reboot
```

4 Install Runtime Dependencies inside the VM

```
# Essential tools
sudo apt install -y git build-essential curl

# Node.js 18 LTS (via NodeSource)
curl -fsSL https://deb.nodesource.com/setup_18.x | sudo -E bash -
sudo apt install -y nodejs    # node 18.x, npm 10.x+

# PostgreSQL 16 (official PGDG repository)
echo "deb http://apt.postgresql.org/pub/repos/apt $(lsb_release -cs)-pgdg main" | \
    sudo tee /etc/apt/sources.list.d/pgdg.list
curl -fsSL https://www.postgresql.org/media/keys/ACCC4CF8.asc | sudo apt-key add -
sudo apt update
sudo apt install -y postgresql-16

# Verify toolchain
node -v    # v18.x
npm -v     # 10.x+
psql -V    # 16.x
```

5 Application Installation

5.1 Clone the Repository

```
sudo mkdir -p /opt && cd /opt
sudo git clone https://github.com/your-org/mr-moneybags-v1.x.git
sudo chown -R $USER:$USER mr-moneybags-v1.x
cd mr-moneybags-v1.x
```

5.2 Create `.env`

```
cat > .env <<'EOF'
# Database
PGHOST=localhost
PGPORT=5432
PGDATABASE=fund_accounting_db
PGUSER=npfadmin
PGPASSWORD=npfa123

# Server
PORT=3000
EOF
chmod 600 .env
```

5.3 Install Node Dependencies

```
npm ci
```

Dependencies (excerpt from *package.json*):

- express **5.1.0**
- pg 8.16
- http-server 14.1

- concurrently 8.2
-

6 Database Setup

Database Setup Commands

```
# Run the manual setup commands:
sudo -u postgres psql -f database/setup-database-cross-platform.sql
sudo -u postgres psql -d fund_accounting_db -f database/schema-only.sql
sudo -u postgres psql -d fund_accounting_db -f database/sample-data-part1.sql
sudo -u postgres psql -d fund_accounting_db -f database/sample-data-part2.sql
```

Note All schema and data-load files live in the repository's top-level `database/` directory.

These commands:

1. Create role **npfadmin / npfa123** and database **fund_accounting_db**.
 2. Set up the complete schema (24 tables with all constraints and indexes).
 3. Load *comprehensive* sample data in two passes to avoid SQL-size limits:
 - `database/sample-data-part1.sql` – core users, entities, funds, first half of accounts
 - `database/sample-data-part2.sql` – remaining accounts, journal entries, vendors & banking fixtures
 4. Seed admin / user accounts with bcrypt-hashed passwords.
-

7 Run the Application

Open **two terminals** or use `npm run dev`.

```
# Terminal 1 - REST API (port 3000)
node server-modular.js          # or simply `npm start`
```

```
# Terminal 2 - Static front-end (port 8080)
npx http-server . -p 8080 --no-cache
```

Helper scripts:

```
npm run client    # only front-end
npm run dev       # backend + frontend concurrently
npm start         # backend only (server-modular.js)
```

Browse to **<http://localhost:8080/index.html>**.

8 Testing & Verification Checklist

Test	Steps	Expected
API health	<code>curl</code> <code>http://localhost:3000/api/health</code>	<code>{"status":"ok"}</code>
Dashboard	Open <code>/index.html</code>	Summary cards and charts render
Vendor Directory	<i>Vendor Payments</i> → <i>Vendors</i>	List shows, Add Vendor modal works
Payment Batch	<i>Vendor Payments</i> → <i>Batches</i> → <i>New</i>	Entity & Fund dropdowns populate
NACHA File	Create batch → Approve → Generate NACHA	<code>.ACH</code> file appears & downloads
DB inspection	<code>psql -d fund_accounting_db -c '\dt'</code>	24 tables including banking modules

9 Troubleshooting

Symptom	Resolution
"DB offline" badge	<code>sudo systemctl restart postgresql</code> and verify <code>.env</code>
Port 3000 in use	<code>sudo lsof -i:3000</code> → <code>kill <PID></code>
Empty dropdowns (batch modal)	Re-run schema and sample data scripts & restart API
CSS not updating	Hard-refresh (Ctrl-F5) or <code>--no-cache</code> flag

10 Performance Tips

1. Allocate extra vCPU/RAM to the VM.
 2. Enable **Nested Paging** & **KVM Paravirtualization** in VirtualBox.
 3. Store the VDI on an SSD/NVMe host drive.
 4. Tune PostgreSQL (`shared_buffers = 512MB`, `work_mem = 16MB`).
 5. Use **Bridged** networking for faster host↔guest transfers.
-

11 Security Considerations

- Change default passwords (`npfa123`) before production.
- Keep `.env` file **chmod 600** and outside version control.
- Enable UFW:

```
sudo ufw allow 8080/tcp  
sudo ufw allow 3000/tcp  
sudo ufw enable
```

- Regularly apply `apt upgrade` and PostgreSQL minor updates.
 - Snapshot the VM after successful installation.
-

12 Appendix A – Useful Commands

```
# Stop both services
pkill -f http-server
pkill -f node

# Backup the database
sudo -u postgres pg_dump -Fc fund_accounting_db > fundacct_$(date +%F).dump

# Restore
sudo -u postgres pg_restore -d fund_accounting_db -c fundacct_2025-07-22.dump

# Refresh schema and sample data
psql -U npfadmin -d fund_accounting_db -f database/schema-only.sql
psql -U npfadmin -d fund_accounting_db -f database/sample-data-part1.sql
psql -U npfadmin -d fund_accounting_db -f database/sample-data-part2.sql
```

Enjoy your fully-functional Mr. MoneyBags v1.x on Ubuntu 24.04!

For details on API endpoints and data model, see the in-app **Documentation** tab or `README.md`.

Mr. MoneyBags v1.x Documentation

© 2025 The Principle Foundation

Last updated: August 12, 2025