



redis

[GET STARTED](#)[DOCS](#)[COMMANDS](#)[RESOURCES](#)[COMMUNITY](#)[SUPPORT](#)[🔑 K](#)[Try Redis Cloud](#)[Download](#)

Commands

ACL CAT
ACL DELUSER
ACL DRYRUN
ACL GENPASS
ACL GETUSER
ACL LIST
ACL LOAD
ACL LOG
ACL SAVE
ACL SETUSER
ACL USERS
ACL WHOAMI
APPEND
ASKING
AUTH
BF.ADD
BF.CARD
BF.EXISTS
BF.INFO
BF.INSERT
BF.LOADCHUNK
BF.MADD
BF.MEXISTS

[🏠](#) > [Commands](#) > [HGET](#)

HGET

Syntax

```
HGET key field
```

Available since: 2.0.0

Time complexity: $O(1)$

ACL categories: @read, @hash, @fast

Returns the value associated with `field` in the hash stored at `key`.

Examples

● ▲ ★

```
redis> HSET myhash field1 "foo"
(integer) 1
redis> HGET myhash field1
"foo"
redis> HGET myhash field2
(nil)
redis>
```

[🔗 Edit this page](#)[🔔 Create an issue](#)

See also

HDEL
HEXISTS
[HGET](#)
HGETALL
HINCRBY
HINCRBYFLOAT
HKEYS
HLEN
HMGET
HMSET
HRANDFIELD
HSCAN
HSET
HSETNX
HSTRLEN
HVALS

RESP2 Reply

One of the following:

- **Bulk string reply:** The value associated with the field.
- **Nil reply:** If the field is not present in the hash or key does not exist.

RESP3 Reply

One of the following:

- **Bulk string reply:** The value associated with the field.
- **Null reply:** If the field is not present in the hash or key does not exist.

Rate this page

This is a community website sponsored by **Redis Ltd.** © 2023. Redis and the cube logo are registered trademarks of Redis Ltd. [Terms of use & privacy policy](#).

