



GET STARTED

DOCS

COMMANDS

RESOURCES

COMMUNITY

SUPPORT

Q Search... ⌘ K

Try Redis Cloud

Commands

ACL CAT
ACL DELUSER
ACL DRYRUN
ACL GENPASS
ACL GETUSER
ACL LIST
ACL LOAD
ACL LOG
ACL SAVE
ACL SETUSER
ACL USERS
ACL WHOAMI
APPEND
ASKING
AUTH
BF.ADD
BF.CARD
BF.EXISTS
BF.INFO
BF.INSERT
BF.LOADCHUNK
BF.MADD
BF.MEXISTS

[🏠](#) > [Commands](#) > GETEX

GETEX

Syntax

```
GETEX key [EX seconds | PX milliseconds | EXAT unix-time-seconds |  
PXAT unix-time-milliseconds | PERSIST]
```

Available since: 6.2.0**Time complexity:** $O(1)$ **ACL categories:** @write, @string, @fast

Get the value of **key** and optionally set its expiration. **GETEX** is similar to **GET**, but is a write command with additional options.

Options

The **GETEX** command supports a set of options that modify its behavior:

- **EX seconds** -- Set the specified expire time, in seconds.
- **PX milliseconds** -- Set the specified expire time, in milliseconds.
- **EXAT timestamp-seconds** -- Set the specified Unix time at which the key will expire, in seconds.
- **PXAT timestamp-milliseconds** -- Set the specified Unix time at which the key will expire, in milliseconds.
- **PERSIST** -- Remove the time to live associated with the key.

Examples

```
●▲★  
redis> SET mykey "Hello"  
"OK"  
redis> GETEX mykey  
"Hello"  
redis> TTL mykey  
(integer) -1  
redis> GETEX mykey EX 60  
"Hello"  
redis> TTL mykey  
(integer) 60  
redis> TTL mykey  
(integer) -2  
redis> TTL mykey
```

APPEND
DECR
DECRBY
GET
GETDEL
GETEX
GETRANGE
GETSET
INCR
INCRBY
INCRBYFLOAT
LCS
MGET
MSET
MSETNX
PSETEX
SET
SETEX
SETNX
SETRANGE
STRLEN
SUBSTR

RESP2 Reply

Bulk string reply: the value of **key** **Nil reply:** if **key** does not exist.

RESP3 Reply

Bulk string reply: the value of **key** **Null reply:** if **key** does not exist.

Rate this page

This is a community website sponsored by **Redis Ltd.** © 2023. Redis and the cube logo are registered trademarks of Redis Ltd. [Terms of use & privacy policy](#)

