

Init the vault

```
user@vb-linux-host:/media$ vault operator init
Unseal Key 1: Zi7YW2taFShYWZi01veIjknBEVh5plMS06me2Hv+oXPb
Unseal Key 2: WBJiroBQ0BRsQA6TCGTNCobtckAPUqUNaWxdUMsP9cSW
Unseal Key 3: 0LJFj6pS520tYjzGjl0Qh0MYkcmYNqyjv9EsPetPsi4x
Unseal Key 4: pC2Fj0iCuwqUoA6V94NFozJeCk60BChn+gyPot4MxcZJ
Unseal Key 5: X1SfQ3u7rxGL7ziSShCIaZJ+JrjeRiygtQNNPKPAMee

Initial Root Token: 34789baf-8de6-3811-c8d0-7c4cb12768e3

Vault initialized with 5 key shares and a key threshold of 3. Please securely
distribute the key shares printed above. When the Vault is re-sealed,
restarted, or stopped, you must supply at least 3 of these keys to unseal it
before it can start servicing requests.

Vault does not store the generated master key. Without at least 3 key to
reconstruct the master key, Vault will remain permanently sealed!

It is possible to generate new unseal keys, provided you have a quorum of
existing unseal keys shares. See "vault rekey" for more information.
```

Unseal using those keys

```
user@vb-linux-host:/media$ vault operator unseal
Unseal Key (will be hidden):
Key                               Value
---                               -
Seal Type                         shamir
Sealed                            true
Total Shares                      5
Threshold                        3
Unseal Progress                   1/3
Unseal Nonce                      a809a324-b551-495b-4714-990ecb5bcd30
Version                          0.9.5
HA Enabled                        true
```