

Name: TANG Pok Man

SID: 59285726

The compiler is C++ 11, flag: -static -std=c++0x.


For all implementations, there is a phasing function (creatArray) and printing function (printAns) which both time complexity is $O(n)$.

```
void creatArray(string& line, int& i, int& n, int arr[10000]) {
    while (i < line.length()) {
        int sign = 1;
        if (line[i] == '-') {
            sign = -1;
            i++;
        }
        int num = 0;
        while (i < line.length() && line[i] >= '0' && line[i] <= '9') {
            num = num * 10 + (line[i] - '0');
            i++;
        }
        arr[n++] = sign * num;
        i++;
    }
}

void printAns(int temp[], int count) {
    if (count > 0) {
        cout << temp[0];
        for (int i = 1; i < count; i++) {
            cout << " " << temp[i];
        }
        cout << endl;
    }
}
```

The first implementation is array based brute force approach. For this implementation, there is a nested for-loops to search whether there is duplicate of every number, so the time complexity is $O(n^2)$. This is $O(n^2)$ in worst case, even in average case, it's quadratic. If all elements are unique, it checks $n(n-1)/2$ pairs, and if all elements are same, it still $O(n^2)$.

Submission #329077 - Accepted

 59285726 - TANG Pok Man

Compiler: C++ 11, flag: -static -std=c++0x **Runtime:** 0 seconds **Memory:** 1,688 KBs

```
1  /*****
2  * (This comment block is added by the Judge System)
3  * Submission ID: 329077
4  * Submitted at: 2025-11-30 14:52:19
5  *
6  * User ID:      2883
7  * Username:     59285726
8  * Problem ID:   927
9  * Problem Name: Find All Unique Elements
10 * /
11
```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
void creatArray(string& line, int& i, int& n, int arr[10000]) {
```

```
    while (i < line.length()) {
```

```
        int sign = 1;
```

```
        if (line[i] == '-') {
```

```
            sign = -1;
```

```
            i++;
```

```
        }
```

```
        int num = 0;
```

```
        while (i < line.length() && line[i] >= '0' && line[i] <= '9') {
```

```
            num = num * 10 + (line[i] - '0');
```

```
            i++;
```

```
        }
```

```
        arr[n++] = sign * num;

        i++;
    }
}
```

```
void printAns(int temp[], int count) {
    if (count > 0) {
        cout << temp[0];

        for (int i = 1; i < count; i++) {
            cout << " " << temp[i];
        }

        cout << endl;
    }
}
```

```
void findUnique(string line) {
    int i = 0;

    int n = 0;

    int arr[10000];

    int temp[10000];

    int count = 0;

    creatArray(line, i, n, arr);

    bool visited[10000] = {false};
```

```

for (int j = 0; j < n; j++) {

    bool repeated = false;

    if (visited[j]) {

        continue;

    }

    for (int k = j+1; k < n; k++) {

        if (arr[j] == arr[k]) {

            visited[k] = true;

            repeated = true;

        }

    }

    if (!repeated) {

        temp[count++] = arr[j];

    }

}

printAns(temp, count);

}

```

```

int main() {

    string line;

    getline(cin, line);

    while (line != "") {

        findUnique(line);

        getline(cin, line);

    }
}

```

```

    }

    return 0;
}

```

The second implementation is binary search tree. For this implementation, the time complexity of insert function and search function are $O(n \cdot \log(n))$ in average and the worst-case scenario is $O(n^2)$. It would happen when the numbers are sorted and the tree becomes unbalanced and performs like a linked list.

Submission #329152 - Accepted

 59285726 - TANG Pok Man

Compiler: C++ 11, flag: -static -std=c++0x **Runtime:** 0 seconds **Memory:** 1,692 KBs

```

1  | /*****
2  |  * (This comment block is added by the Judge System)
3  |  * Submission ID: 329152
4  |  * Submitted at:  2025-11-30 17:01:06
5  |  *
6  |  * User ID:      2883
7  |  * Username:     59285726
8  |  * Problem ID:   927
9  |  * Problem Name: Find All Unique Elements
10 |  */
11 |

```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
class Node {
```

```
public:
```

```
    int data;
```

```
    Node* left;
```

```
    Node* right;
```

```
int appear;

Node(int d) {

    data = d;

    left = nullptr;

    right = nullptr;

    appear = 1;

}

};
```

```
class Tree {

public:

    Node* root;

    Tree() {root = nullptr;}

    void insert(int d);

    void insert(Node* node, int d);

    Node* search(Node* node, int d);

    Node* search(int d);

};
```

```
void Tree::insert(int d) {

    if (root == nullptr) {

        root = new Node(d);

    } else {

        insert(root, d);

    }

}
```

```

    }
}

void Tree::insert(Node* node, int d) {
    if (d < node->data) {
        if (node->left == nullptr) {
            node->left = new Node(d);
        } else {
            insert(node->left, d);
        }
    } else if (d > node->data) {
        if (node->right == nullptr) {
            node->right = new Node(d);
        } else {
            insert(node->right, d);
        }
    } else {
        node->appear++;
    }
}

```

```

Node* Tree::search(Node* node, int d) {
    if (node == nullptr) {
        return nullptr;
    }
}

```

```

    }

    if (d < node->data) {

        return search(node->left, d);

    } else if (d > node->data) {

        return search(node->right, d);

    } else {

        return node;

    }

}

```

```

Node* Tree::search(int d) {

    return search(root, d);

}

```

```

void creatArray(string& line, int& i, int& n, int arr[10000]) {

    while (i < line.length()) {

        int sign = 1;

        if (line[i] == '-') {

            sign = -1;

            i++;

        }

        int num = 0;

        while (i < line.length() && line[i] >= '0' && line[i] <= '9') {

            num = num * 10 + (line[i] - '0');

```



```

        i++;

    }

    arr[n++] = sign * num;

    i++;

}

}

```

```

void printAns(int temp[], int count) {

    if (count > 0) {

        cout << temp[0];

        for (int i = 1; i < count; i++) {

            cout << " " << temp[i];

        }

        cout << endl;

    }

}

```

```

void findUnique(string line) {

    int i = 0;

    int n = 0;

    int arr[10000];

    int temp[10000];

    int count = 0;

    creatArray(line, i, n, arr);

```

```

Tree myTree;

for (int i = 0; i < n; i++) {

    myTree.insert(arr[i]);

}

for (int i = 0; i < n; i++) {

    Node* node = myTree.search(arr[i]);

    if (node->appear == 1) {

        temp[count++] = arr[i];

    }

}

printAns(temp, count);

}

int main() {

    string line;

    getline(cin, line);

    while (line != "") {

        findUnique(line);

        getline(cin, line);

    }

    return 0;

}

```

The third implementation is linked list. For this implementation, the time complexity is $O(n^2)$ since linked list can only search linearly. The worst-case scenario is when all numbers are unique, the function needs to travel the whole linked list for all numbers.

Submission #329178 - Accepted

 59285726 - TANG Pok Man

Compiler: C++ 11, flag: -static -std=c++0x **Runtime:** 0 seconds **Memory:** 2,812 KBs

```
1  /*****
2  * (This comment block is added by the Judge System)
3  * Submission ID: 329178
4  * Submitted at: 2025-11-30 18:01:47
5  *
6  * User ID:      2883
7  * Username:     59285726
8  * Problem ID:   927
9  * Problem Name: Find All Unique Elements
10 * /
11
```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
class Node {
```

```
public:
```

```
    int data;
```

```
    int appear;
```

```
    Node* next;
```

```
    Node(int d, int a) {
```

```
        data = d;
```

```
        appear = a;
```

```
        next = nullptr;
    }

    Node() {
        data = 0;
        appear = 0;
        next = nullptr;
    }
};
```

```
class List {
public:
    Node* first;
    Node allNode[10000];
    int size;

    List() {
        first = nullptr;
        size = 0;
    }

    Node* search(int d);
    void insert(int d);
    void temp(int temp[], int& count);
};
```

```
Node* List::search(int d) {  
  
    Node* curr = first;  
  
    while (curr != nullptr) {  
  
        if (curr->data == d) {  
  
            return curr;  
  
        }  
  
        curr = curr->next;  
  
    }  
  
    return nullptr;  
}
```

```
void List::insert(int d) {  
  
    Node* newNode = search(d);  
  
    if (newNode == nullptr) {  
  
        if (first == nullptr) {  
  
            allNode[0] = Node(d, 1);  
  
            size++;  
  
            first = &allNode[0];  
  
        } else {  
  
            allNode[size] = Node(d, 1);  
  
            allNode[size-1].next = &allNode[size];  
  
            size++;  
  
        }  
    }  
}
```

```

    } else {

        newNode->appear++;

    }

}

```

```

void List::temp(int temp[], int& count) {

    Node* curr = first;

    while (curr != nullptr) {

        if (curr->appear == 1) {

            temp[count++] = curr->data;

        }

        curr = curr->next;

    }

}

```

```

void creatArray(string& line, int& i, int& n, int arr[10000]) {

    while (i < line.length()) {

        int sign = 1;

        if (line[i] == '-') {

            sign = -1;

            i++;

        }

        int num = 0;

        while (i < line.length() && line[i] >= '0' && line[i] <= '9') {

```

```

        num = num * 10 + (line[i] - '0');

        i++;

    }

    arr[n++] = sign * num;

    i++;

}

}

```

```

void printAns(int temp[], int count) {

    if (count > 0) {

        cout << temp[0];

        for (int i = 1; i < count; i++) {

            cout << " " << temp[i];

        }

        cout << endl;

    }

}

```

```

void findUnique(string line) {

    int i = 0;

    int n = 0;

    int arr[10000];

    int temp[10000];

    int count = 0;

```

```
    creatArray(line, i, n, arr);

    List* list = new List();

    for (int i = 0; i < n; i++) {

        list->insert(arr[i]);

    }

    list->temp(temp, count);

    printAns(temp, count);

}
```

```
int main() {

    string line;

    getline(cin, line);

    while (line != "") {

        findUnique(line);

        getline(cin, line);

    }

    return 0;

}
```