CHANGE TITLE
CHANGE SUBTITLE

First Author

bsky username

name@email

website

Hi!

This is a tutorial to use the slides template

1 The basics

Author information

Author information is given as a dictionary, where each author is an entry. Currently, only the first author info is displayed on the title / take-home slides.

```
#let _authors = (
  (
    name: "First Author",
    bluesky: "bsky username",
    email: "name@email",
    website: "website",
    institution:
"Institution",
  ),
)
```

Useful packages

Here is a selection of very useful packages for slides, which can be added at the top of the document to use them:

```
// Post-it notes
#import "@preview/colorful-boxes:1.4.3": stickybox
// Diagrams
#import "@preview/fletcher:0.5.8" as fletcher: diagram, node, edge
// Icons
#import "@preview/scienceicons:0.1.0": *
// Pins and annotations
#import "@preview/pinit:0.2.2": *
```

This Open Access icon is from `scienceicons`, which the slides template will load anyways!

The colorful-boxes package is good because you can use post-it style callouts on your slides

If you use fletcher, it is much better to load it in a separate file that contains the entire diagram

Using pinit

The slides support the `pinit` package natively – the usual caveats about placement with `pinit` apply, see the package documentation

This text can be highlighted by `pinit`. The pins can also be animated

Using pinit

The slides support the `pinit` package natively – the usual caveats about placement with `pinit` apply, see the package documentation

This text can be highlighted by `pinit`. The pins can also be animated

Like this

Additional markup

Text can be highlighted with `#hl` - the color will be picked from the section color

Code can specifically be highlighted with `kbd`: **`localhost%`**

Layout 2

Content and illustration

By default, the slide area will occupy 100% of the width of the area, which is fine when you either want

- full width text
- a single big picture
- code

Keeping space for illustrations

You can keep some space for an illustration, which is done by specifying what proportion of the slide should be occupied by the content:

```
#slide(
  title: "Keeping space for illustrations",
  width: 60%
)[Content goes here]
```

This slide has a width of 60%

Picking a side for the layout

The `slide` function takes an `align` keyword that will specify whether the content is at the `left` or `right` of the slide.

```
#slide(
  title: "Keeping space for illustrations",
  width: 60%,
  align: right
)[Content goes here]
```

This slide has a width of 60% and is aligned to the right

Adding an illustration

The space that is usable for illustration can be filled with the `illustration` function:

```
#illustration(
  style: (
    radius: 6pt,
    inset: 55pt,
    fill: luma(95%))
)[
  #align(center)[
    The illustration for this slide
  ]
]
```

Note that illustrations are rendered in a `block`, and that arguments to the block itself can be passed *via* the `style` argument. Illustrations are *not* horizontally centered by default.

The illustration for this slide

What about grids?

The `grid` function works fine for more complex layouts, *but* cannot be used together with the `reveal` and `pop` functions for slide transitions. The `illustrate` function works well for this usage.

What about grids?

The `grid` function works fine for more complex layouts, *but* cannot be used together with the `reveal` and `pop` functions for slide transitions. The `illustrate` function works well for this usage.

Like so.

3 Transitions

Fundamentals

There are two types of transitions

Specifying the order of apparition

There are four ways to

4

Section slides

What do sections do?

Sections of the talk are marked with

```
#section[Section title]
```

They change the section header in the slides, and optionally change the accent color for the section.

For example, the current section is started with

```
#section(color: rgb("#6b326aff"))[Section slides]
```

Display / hidden

The `section` marker takes an optional argument `display`, which turns the slide display off *just for this section*.

This is useful for short presentations when you want the *section header* to change on the slides, but *do not want* the slide to be displayed

```
#section(display: false)[New section with no title slide]
```

5 Fletcher and animations

Introduction

This gets its own section because animations with `fletcher` are not particularly intuitive.

This will require some finagling to get it done, but it is fully doable.

6 Kitchen sink

Title is longer than the content width

This slide is here to test that when the slide content is *very narrow*, the text and the footer can actually overlap