

A (not so) gentle introduction to networks in ecology

Timothée Poisot

Université du Québec à Rimouski

August 15, 2013

Why should I care about networks?

- ▶ A good way to harness complexity
- ▶ A solid mathematical foundation
- ▶ Elegant algorithms
- ▶ That guy is going to talk about them for, like, two hours...

What is a network?

A mathematical approach

A *graph* is a **representation** of a **set of objects** where some pairs of objects are **connected** by **links**.

Or more formally, $G = (V, E)$, a *graph* G is an ordered pair of *vertices* V linked together by *edges* E .

Each element of E is a two-element subset of V .

The *order* of a graph is $|V|$, and its *size* is $|E|$.

What is a network?

An example

In an omnivory scenario, one top predator P consumes both an intermediate consumer C and a primary producer R . The intermediate consumer also consumes the producer.

This network is specified by

$$G = (\{P, C, R\}, \{\{P, C\}, \{P, R\}, \{C, R\}\})$$

Or for brevity

$$G = (\{P, C, R\}, \{PC, PR, CR\})$$

What is a network?

The adjacency matrix

Networks are often represented by their **adjacency matrix**.

The adjacency matrix \mathbf{A} of a graph $G = (V, E)$ has elements A_{ij} with value 1 if there is an edge between the node V_i and the node V_j , and 0 otherwise.

It follows that $\sum_i \sum_j A_{ij} = |E|$.

What is a network?

Edge direction

Edges can be *directed* (arcs, directed edges) or not. An edge between a vertex and itself (cannibalism) is a *self-loop*.

In an **undirected graph**, there are at most $|V|(|V| - 1)/2$ edges if there are no *self-loops*.

In a **directed graph**, there are at most $|V|(|V| - 1)$ edges if there are no *self-loops*.

Exercise: What is the maximal size of a graph of order n if there are self-loops?

What is a network?

Edge weight

Edges in a network can have a **weight** (for example, the number of contacts between individuals).

The elements of the adjacency matrix **A** can be given *continuous* values.

It's possible to work both on the *weighted* and *unweighted* properties of a graph. **However**, there are many methods that (as of now) can only be applied to **undirected, unweighted** networks.

Number of partners

The number of vertices *receiving* a link from a focal vertex are called its **successors**

The number of vertices *establishing* a link towards a focal vertex are called its **predecessors**

The *total* number of edges connected to a focal vertex is this vertex **degree**

Some remarks on degrees

In a graph with n nodes, the degree k of a node i is $k_i = \sum_{j=1}^n A_{ij}$ (iff the graph is undirected).

If there are m edges, there are $2m$ ends of edges, with $2m = \sum_{i=1}^n k_i$. In an undirected graph, this is equal to the sum of degrees.

Thus, $m = \frac{1}{2} \sum_{i=1}^n k_i = \frac{1}{2} \sum_i \sum_j A_{ij}$

As the mean degree of nodes is simply $c = \frac{1}{n} \sum k_i$, we can write $c = \frac{2m}{n}$.

Some exercises on degrees

Exercise(s):

Using the same approach, find **the expression of the mean number of predecessors and successors** in a directed graph.

Discuss the relationship between these two values.

Is the mean degree different in a directed/undirected network?

Unipartite and bipartite graphs

In a **bipartite** graph, vertices are divided into two distinct sets, with edges established between two vertices from *different* sets.

This do not happen in **unipartite** graphs.

Exercise: Discuss the application of bipartite and unipartite networks to ecological systems.

In a bipartite graph, the adjacency matrix is (formally) called the **incidence matrix**.

Trees and cycles

Paths

A **path** is a sequence of nodes, so that every consecutive pair of nodes are connected through an edge. You can “walk” along edges from the first to the last node along a path.

The **length** of a path is the number of *edges* in that path.

If nodes i and j are connected, then *there is a path of length 1 between them*. If they are connected through k , there is *a path of length 2*.

Reminder: multiplying matrices

- ▶ Only *square* matrices can be raised to an exponent (**Exercise**: What of bipartite rectangular networks?)
- ▶ $(\mathbf{AB})_{ij} = \sum_{p=1}^m A_{ip} B_{pj}$
- ▶ $\mathbf{A}^0 = \mathbf{I}$
- ▶ $\mathbf{A}^2 = \mathbf{AA}$
- ▶ $(r\mathbf{A})^k = r^k \mathbf{A}^k$
- ▶ $\det(\mathbf{A}^k) = \det(\mathbf{A})^k$ because $\det(\mathbf{AB}) = \det(\mathbf{A})\det(\mathbf{B})$

Number of paths

The number of paths of length 2 between i and j is given by

$$N_{ij}^{(2)} = \sum_k 1^n A_{ik} A_{kj}$$

.

This is generalized for paths of length n to

$$N_{ij}^{(n)} = (\mathbf{A}^n)_{ij}$$

.

Number of paths

Find the number of cycles

Based on the previous result, we can identify the number of paths of size n from one node to itself, $(\mathbf{A}^n)_{ii}$.

Because for square matrices, $\text{Tr}(\mathbf{A}) = \sum \text{diag}(\mathbf{A})$, the *total number of cycles of length n* is given by $L_n = \text{Tr}(\mathbf{A}^n)$.

Identify the shortest path

A **very crude** way to find the shortest path between i and j is to find the *smallest value of n* for which $(\mathbf{A}^n)_{ij} > 0$.

The shortest path is called the **geodesic** path.

This method is inefficient, and modern software implements much better search strategies.

Where is the ecology in all that?

graph The whole community, *i.e.* the populations and their interactions

vertices The composition of the community (species present)

edges The interactions between the populations

Where is the ecology in all that?

Exemple of “networkable” systems

- ▶ Trophic systems
- ▶ Plant–pollinators
- ▶ Hosts–parasites
- ▶ Mutualism
- ▶ Social interactions

Any system in which the **same ecological interaction** happens several time in a community can (should) be studied using network theory

Connectance

Connectance is the *proportion of possible interactions realized* (also called the density ρ in graph theory)

The order of an ecological network is usually called S , and its size L

Ecologists often define connectance as $C_o = L/S^2$.

Exercise: What do you think of this definition based on results about the maximal order of a graph or size S ?

Number of partners

The number of (*e.g.*) preys of a predator is its **generality** (number of successors)

The number of (*e.g.*) predators of a prey is its **vulnerability** (number of predecessors)

Number of partners

```
1 web = read.table('web.dat')
2 generality = rowSums(web)
3 vulnerability = colSums(web)
4 degree = generality + vulnerability
```

Null models

The ecological use

Null models

The basic approach

Null models

Controlling for mean degree

The niche model of food webs