Mathematical modelling for all-solid-state battery: (SE|SSE)-Interface

Tuan Vo[a,b †], Claas Hüter[b], Stefanie Braun[a]

[a]Department of Mathematics, Applied and Computational Mathematics (ACoM), RWTH Aachen University, Schinkelstraße 02, 52062 Aachen, Germany
[b]Institute of Energy and Climate Research (IEK-2), Forschungszentrum Jülich, Wilhelm-Johnen-Straße, 52428 Jülich, Germany

Mathematical modelling for the next-generation All-solid-state batteries: Nucleation (SE|SSE)$^{(*)}$-interface

Rechargeable Lithium-ion battery (LIB) is at the heart of every electric vehicle (EV), portable electronic device, and energy storage system [5]. Nowadays, LIBs enable human life more efficient and help to solve global environment issues thanks to EVs' zero emission. However, conventional LIB (c-LIB) is sensible to temperature and pressure, hence, flammable and explosive, which is undesirable. This bottleneck is mainly due to liquid-based electrolyte found in c-LIBs.

All-solid-state battery (ASSB) is one of promising candidates to overcome bottlenecks of c-LIBs. Thanks to solid-state electrolyte (SSE), ASSB is highly stable towards temperature and pressure. Nevertheless, Li-metal dendrite triggered at (SE|SSE)-interface [**?**] is the main drawback of ASSB since these dendritic threads extrapolate into SSE grain boundary network, causing crevice, degradation of ionic conductivity, and the probability of short-circuit, which is unfavorable.

Next-generation All-solid-state battery (ng-ASSB) with a consideration of nucleation criterion defined by

$$\partial_t \dot{\boldsymbol{u}} + \nabla \cdot \left(\mathbb{C}^{4}{}_{f_{\text{alocation}}(\lambda,\mu,\boldsymbol{d}^R_{G_i,i=1,\dots,N},\boldsymbol{d}^E;\boldsymbol{x})} : \nabla \boldsymbol{u}^{(s)} \right) + \rho \boldsymbol{b} = -\rho \nabla V_e, \tag{1}$$

$$\text{s.t.} \quad a_{\text{Griffith}} := a^* = \arg\min_{a \in \mathbb{R}} \iiint_{\Omega} f(a, \boldsymbol{u}, \theta; \lambda, \mu, \boldsymbol{d}^{(\star)} \otimes \boldsymbol{d}^{(\star)})\, d\Omega - \iint_{\Gamma} f(a;\gamma)\, d\Gamma \Big|_{\bar{\boldsymbol{u}}} \tag{2}$$

where $V_e : \mathbb{R}^3 \to \mathbb{R}$ is the electric potential applied globally on ASSB. Due to nature setting of ASSB taking the form (SE|SSE|SE) the electric potential becomes uniform. Additionally, $\boldsymbol{u}$ is the displacement field, θ temperature field, a crevice length, λ, μ Lamé constants, $\boldsymbol{d}^{(\star)} \otimes \boldsymbol{d}^{(\star)}$ embedded misorientation structural tensor, and γ cracking-surface energy density, can help to improve ASSB performance.



Next-generation All-solid-state battery

Nucleation criterion governs the instable (SE|SSE)-interface [9]



Space-charge Layer

Space-charge Layer



Energy density demand landscape

Interface between solid electrode and solid-state electrolyte (SE|SSE) taking place at space charge layer (SCL) [7] critically exhibits mechanical and electrochemical instability [9].



(i) Theoretical capacity of charge. (ii) Practical energy density.

Artificial Neural Networks

Application: Steel property prediction [8]

Semiconductor

Application: Start/Stop Starter [6]

Nucleation interface: Taking place at the critically dendritic (SE|SSE)-interface

Coupled fields are Displacement field $\boldsymbol{u}$ and temperature field θ;

$$\boldsymbol{u} : \begin{cases} \Omega \times \mathbb{R}_+ \to \mathbb{R}^3, \\ (\boldsymbol{x}, t) \mapsto \boldsymbol{u}(\boldsymbol{x}, t), \end{cases} \qquad \theta : \begin{cases} \Omega \times \mathbb{R}_+ \to \mathbb{R}, \\ (\boldsymbol{x}, t) \mapsto \theta(\boldsymbol{x}, t), \end{cases}$$

Governing conservation equations used to describe balance of mass, conservation of linear momentum, conservation of angular momentum, and conservation of energy with $\rho(\boldsymbol{x}, t)$ is mass density per unit volume (puv); $\boldsymbol{b}(\boldsymbol{x}, t)$ body force puv; $\boldsymbol{v}(\boldsymbol{x}, t)$ velocity; $e(\boldsymbol{x}, t)$ internal energy puv; $\boldsymbol{q}(\boldsymbol{x}, t)$ heat flux; $r(\boldsymbol{x}, t)$ heat source puv; $\boldsymbol{\sigma}$ Cauchy stress and $\boldsymbol{\varepsilon}$ infinitesimal strain.

Strain energy is based on the deformation of SSE due to dendrite formation at (SE|SSE)-interface

Surface energy is analysised based on the open crevice cracking at (SE|SSE)-interface affected by prescribed pressure





Contact

Tuan Vo
vo@acom.rwth-aachen.de

Scan me

References

[1] **T.Vo**, C.Hüter, S.Braun, *Math. modelling for All-solid-state batt.: (SE|SSE)-Interface*. Poster, Oxford Batt. Modelling Symp., Univ. of Oxford, OBMS23, Page 66, **2023**.

[2] **T.Vo**, C.Hüter, S.Braun, M.Torrilhon, *Mathematical modelling for All-solid-state batt.: (SE|SSE)-Interface*. Poster, SIAM Comp. Sci. and Eng. Conference, Amsterdam, **2023**.

[3] **T.Vo**, *Mathematical modelling for All-solid-state batt.: Griffith criterion*. Presentation, NUMAP-FOAM Summer School, Univ. of Cambridge, **2022**.

[4] **T.Vo**, C.Hüter, S.Braun, R.Spatschek, *Mathematical modelling for All-solid-state batt.: Griffith criterion*. Doctoral presentation, Forschungszentrum Jülich, **2020**.

[5] **T.Vo**, *Modeling the swelling phenomena of li-ion batt. cells based on a numerical chemo-mech. coupled approach*. Master thesis, Robert Bosch Battery Systems GmbH, **2018**.

[6] **T.Vo**, *Simulation environment for NTC-based voltage drop reduction in Start/Stop applications and its optimization*. Bachelor thesis, Robert Bosch GmbH, **2014**.

[7] **S.Braun**, C.Yada, and A.Latz, *Thermodynamically consistent model for Space-Charge-Layer formation in a solid electrolyte*. Jr. Phys. Chem., 119, 22281-22288, **2015**.

[8] **C.Hüter**, X.Yin, T.Vo, S.Braun, *A pragmatic dataset augmentation approach for transformation temp. prediction in steels*. Comp. Mat. Science, Vol. 176, 109488, **2020**.

[9] **C.Hüter**, S.Fu, M.Finsterbusch, E.Figgemeier, L.Wells, and R.Spatschek, *Electrode-electrolyte interface stability in solid state electrolyte system: influence of coating thickness under varying residual stresses*. AIMS Materials Science, 4(4):867-877, **2017**.

[10] **M.Torrilhon**. *Modeling nonequilibrium gas flow based on moment equations*. Annual Review of Fluid Mechanics, 48(1):429-458, **2016**.

BOSCH

Bosch Spring School on AI in Industry | March 6-7, 2024

#OBMS2023

Applied and Computational Mathematics | RWTH AACHEN UNIVERSITY | JÜLICH Forschungszentrum