

NEXT-GENERATION ALL-SOLID-STATE BATTERY (#ASSB)

Tuan Vo^{a,b,†}, Claas Hüter^b, Stefanie Braun^a, Manuel Torrilhon^a

^aDepartment of Mathematics, Applied and Computational Mathematics (ACoM), RWTH Aachen University, Schinkelstraße 02, 52062 Aachen, Germany

^bInstitute of Energy and Climate Research (IEK-2), Forschungszentrum Jülich, Wilhelm-Johnen-Straße, 52428 Jülich, Germany

Mathematical modelling for the next-generation All-solid-state batteries: Nucleation (SE|SSE)^(*)-interface

Rechargeable Lithium-ion battery (LIB) is at the heart of every electric vehicle (EV), portable electronic device, and energy storage system [1]. Nowadays, LIBs enable human life more efficient and help to solve global environment issues thanks to EVs' zero emission. However, conventional LIB (c-LIB) is sensible to temperature and pressure, hence, flammable and explosive. This bottleneck is mainly due to liquid-based electrolyte in c-LIBs.

All-solid-state battery (ASSB) is one of promising candidates to overcome bottlenecks of c-LIBs. Thanks to solid-state electrolyte (SSE), ASSB is highly stable towards temperature and pressure. Nevertheless, metallic Li-dendrite triggered at (SE|SSE)-interface is the main drawback as these dendritic threads extrapolate into grain boundary network of SSE, causing crevice, degradation of ionic conductivity, and the probability of short-circuit.


Next-generation All-solid-state battery (ng-ASSB) with a consideration of nucleation criterion defined by

$$a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}}$$

where, can help to improve ASSB performance.


can help to improve ASSB performance.

can help to improve ASSB performance.



Interface


Interface between solid electrode and solid-state electrolyte (SE|SSE) taking place at space charge layer (SCL) [2] found in ASSBs critically exhibits mechanical and electrochemical instability [3]. This evidence points directly to the fact that the soft metallic Li anode is erroneously prone to triggering dendrites, under cycles of electric charge & discharge [4].



Distribution: ana. max. shear stress $\mathcal{A}_{\sigma}^{\Pi}$ around crack tip a_c .

Next-generation All-solid-state battery

Nucleation taking place at critical dendritic (SE|SSE)-interface




Nucleation taking place at critical dendritic (SE|SSE)-interface

Nucleation taking place at critical dendritic (SE|SSE)-interface

Embedded structural-tensor SSE

Polycrystalline garnet-typed SSE such as LLZO exhibit grain boundaries and various sizes and shapes of grains under microscopic observation. Therefore, this type of microstructure distinctively leads to nuance destruction of ceramic-like materials.



Consequently, dendrites contribute to degradation of ionic conductivity and trace along grain boundaries in SSE.


Nucleation interface: Taking place at the critical dendritic interface

Boundary settings


$$\begin{aligned} & \rho \partial_p^2 \mathbf{u}^{(s)} + \nabla \cdot \left(\mathbb{C}^{f(\lambda, \mu)} : \nabla \mathbf{u}^{(s)} \right) + \rho \nabla V_e = \mathbf{0}, \\ \text{s.t. } & a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}} \\ & \rho \partial_p^2 \mathbf{u}^{(s)} + \nabla \cdot \left(\mathbb{C}^{f(\lambda, \mu)} : \nabla \mathbf{u}^{(s)} \right) + \rho \nabla V_e = \mathbf{0}, \\ \text{s.t. } & a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}} \\ & \rho \partial_p^2 \mathbf{u}^{(s)} + \nabla \cdot \left(\mathbb{C}^{f(\lambda, \mu)} : \nabla \mathbf{u}^{(s)} \right) + \rho \nabla V_e = \mathbf{0}, \\ \text{s.t. } & a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}} \\ & \rho \partial_p^2 \mathbf{u}^{(s)} + \nabla \cdot \left(\mathbb{C}^{f(\lambda, \mu)} : \nabla \mathbf{u}^{(s)} \right) + \rho \nabla V_e = \mathbf{0}, \\ \text{s.t. } & a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}} \\ & \rho \partial_p^2 \mathbf{u}^{(s)} + \nabla \cdot \left(\mathbb{C}^{f(\lambda, \mu)} : \nabla \mathbf{u}^{(s)} \right) + \rho \nabla V_e = \mathbf{0}, \\ \text{s.t. } & a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}} \end{aligned}$$

Therefore


$$\therefore a_{\text{Griffith}} := a^* = \arg \min_{a \in \mathbb{R}} \left(\iint_{\Omega} f(a, \mathbf{u}; \lambda, \mu, \mathbf{d} \otimes \mathbf{d}) d\Omega - \iint_{\Gamma} f(a; \gamma) d\Gamma \right) \Big|_{\mathbf{u}^{(s)}}$$



The set of boundary conditions is likewise the path of the pressure-centric dendritic crack.




Comparison: Analytical vs. Numerical solutions



Contact

Tuan Vo
vo@acom.rwth-aachen.de



Scan me

References

- [1] **T.Vo**, *Modeling the swelling phenomena of li-ion batt. cells based on a numerical chemo-mech. coupled approach*. MA, Robert Bosch Battery Systems GmbH, 2018.
- [2] **S.Braun**, C.Yada and A.Latz, *Thermodynamically consistent model for Space-Charge-Layer formation in a solid electrolyte*. Jr. Phys. Chem., 119, 22281-22288, 2015.
- [3] **C.Hüter**, S.Fu, M.Finsterbusch, E.Figgemeier, L.Wells, and R.Spatschek, *Electrode-electrolyte interface stability in solid state electrolyte system: influence of coating thickness under varying residual stresses*. AIMS materials Science, 4(4):867-877, 2017.
- [4] **S.Kim**, J.S.Kim, L.Miara, Y.Wang, S.K.Jung, S.Y.Park, Z.Song, H.King, M.Badding, J.M.Chang, V.Roev, G.Yoon, R.Kim, J.H.Kim, K.Yoon, D.Im, and K.Kang, *High-energy and durable li metal batt. using garnet-type solid electrolytes with tailored li-metal compatibility*. Nature Communications, 13(1):1883, 2022.