NEXT-GENERATION ALL-SOLID-STATE BATTERY (#ASSB)

Tuan Vo[a,b †], Claas Hüter[b], Stefanie Braun[a], Manuel Torrilhon[a]

[a]Department of Mathematics, Applied and Computational Mathematics (ACoM), RWTH Aachen University, Schinkelstraße 02, 52062 Aachen, Germany
[b]Institute of Energy and Climate Research (IEK-2), Forschungszentrum Jülich, Wilhelm-Johnen-Straße, 52428 Jülich, Germany

Mathematical modelling for the next-generation All-solid-state batteries: Nucleation (SE|SSE)$^{(*)}$-interface

Rechargeable Lithium-ion battery (LIB) is at the heart of every electric vehicle (EV), portable electronic device, and energy storage system [1]. Nowadays, LIBs enable human life more efficient and help to solve global environment issues thanks to EVs' zero emission. However, conventional LIB (c-LIB) is sensible to temperature and pressure, hence, flammable and explosive, which is undesirable. This bottleneck is mainly due to liquid-based electrolyte found in c-LIBs.

All-solid-state battery (ASSB) is one of promising candidates to overcome bottlenecks of c-LIBs. Thanks to solid-state electrolyte (SSE), ASSB is highly stable towards temperature and pressure. Nevertheless, Li-metal dendrite triggered at (SE|SSE)-interface [5] is the main drawback of ASSB since these dendritic threads extrapolate into SSE grain boundary network, causing crevice, degradation of ionic conductivity, and the probability of short-circuit, which is unfavorable.

Next-generation All-solid-state battery (ng-ASSB) with a consideration of nucleation criterion defined by

$$a_{\text{Griffith}} := a^* = \arg\min_{a\in\mathbb{R}} \iiint_\Omega f(a,\boldsymbol{u},\theta;\lambda,\mu,\boldsymbol{d}\otimes\boldsymbol{d})\,d\Omega - \iint_\Gamma f(a;\gamma)\,d\Gamma\Big|_{\boldsymbol{u}^{(s)}}$$

where $\boldsymbol{u}$ displacement field, θ temperature field, a crevice length, λ,μ Lamé constants, $\boldsymbol{d}\otimes\boldsymbol{d}$ embedded misorientation structural tensor, and γ cracking-surface energy density, can help to improve ASSB performance.



Interface Analysis

Interface between solid electrode and solid-state electrolyte (SE|SSE) taking place at space charge layer (SCL) [2] found in ASSBs critically exhibits mechanical and electrochemical instability [3]. This evidence points directly to the fact that the soft metallic li anode is erroneously prone to triggering dendrites, under cycles of electric charge & discharge [5].



Distribution: ana. max. shear stress ${}^{\mathcal{W}}\!\sigma^{\Pi}_{x_1x_2}$ around crack tip a_c.

Next-generation All-solid-state battery

Nucleation criterion governs the instable (SE|SSE)-interface [3]



✓ **Thermodynamic consistency** is satisfied, followed by [2].
✓ **Closure** $\bar{\Omega}$ is fulfilled by 15 moments, followed by [4].

Embedded structural-tensor SSE

Polycrystalline garnet-type SSE [5] such as LLZO exhibit grain boundary network, and grains with variation of {size, shape} under microscopic observation. Hence, this microstructure is potentially prone to nuances of destruction.

$$\boldsymbol{M} = \boldsymbol{d}^R_{G_1}\otimes\boldsymbol{d}^R_{G_2} \quad \text{given by} \quad \mathbb{G} := \{\boldsymbol{Q}_{||_d}, \boldsymbol{Q}_{\perp_d}\} \subset \mathcal{O}(3).$$



Consequentially, dendrites contribute to degradation of ionic conductivity and tiny-cracks tracing along grain boundaries.

Nucleation interface: Taking place at the critical dendritic interface

Coupled fields: Displacement vector field and temperature scalar field

$$\boldsymbol{u}: \begin{cases}\Omega\times\mathbb{R}_+\to\mathbb{R}^3,\\ (\boldsymbol{x},t)\mapsto\boldsymbol{u}(\boldsymbol{x},t),\end{cases} \quad \theta: \begin{cases}\Omega\times\mathbb{R}_+\to\mathbb{R},\\ (\boldsymbol{x},t)\mapsto\theta(\boldsymbol{x},t),\end{cases} \quad \theta: \begin{cases}\Omega\times\mathbb{R}_+\to\mathbb{R},\\ (\boldsymbol{x},t)\mapsto\theta(\boldsymbol{x},t),\end{cases}$$

Governing conservation equations

$$\frac{d}{dt}\int_\Omega(\cdot)\,d\Omega = \int_\Omega(\cdot)^{\text{action}}\,d\Omega + \int_{\partial\Omega}(\cdot)^{\text{action}}\,d\partial\Omega + \int_\Omega(\cdot)^{\text{production/source/sink}}\,d\Omega$$

$\rho(\boldsymbol{x},t)$ is mass density per unit volume (puv); $\boldsymbol{b}(\boldsymbol{x},t)$ body force puv; $\boldsymbol{v}(\boldsymbol{x},t)$ velocity; $e(\boldsymbol{x},t)$ internal energy puv; $\boldsymbol{q}(\boldsymbol{x},t)$ heat flux; $r(\boldsymbol{x},t)$ heat source puv; $\boldsymbol{\sigma}$ Cauchy stress and $\boldsymbol{\varepsilon}$ infinitesimal strain. Helmholtz energy functional

$$a_{\text{Griffith}} := a^* = \arg\min_{a\in\mathbb{R}} \iiint_\Omega f(a,\boldsymbol{u};\lambda,\mu,\boldsymbol{d}\otimes\boldsymbol{d})\,d\Omega - \iint_\Gamma f(a;\gamma)\,d\Gamma\Big|_{\boldsymbol{u}^{(s)}}$$

Governing PDE

$$a_{\text{Griffith}} := a^* = \arg\min_{a\in\mathbb{R}} \iiint_\Omega f(a,\boldsymbol{u};\lambda,\mu,\boldsymbol{d}\otimes\boldsymbol{d})\,d\Omega - \iint_\Gamma f(a;\gamma)\,d\Gamma\Big|_{\boldsymbol{u}^{(s)}}$$

abc

Strain energy: Interface between solid electrode and solid-state electrolyte (SE|SSE) taking place at space charge

$$\iiint_\Omega f(a,\boldsymbol{u};\lambda,\mu,\boldsymbol{d}\otimes\boldsymbol{d})\,d\Omega$$

Surface energy: Interface between solid electrode and solid-state electrolyte (SE|SSE) taking place

$$\iint_\Gamma f(a;\gamma)\,d\Gamma$$

Therefore

$$\rho\,\partial^2_{t^2}\boldsymbol{u}^{(s)} + \nabla\cdot\left(\overset{4}{\mathbb{C}}{}^{\mathfrak{D}(\Omega)}_{(\lambda,\mu)} : \nabla\boldsymbol{u}^{(s)}\right) + \rho\nabla V_e = \boldsymbol{0},$$

$$\text{s.t.}\quad a_{\text{Griffith}} := a^* = \arg\min_{a\in\mathbb{R}} \iiint_\Omega f(a,\boldsymbol{u};\lambda,\mu,\boldsymbol{d}\otimes\boldsymbol{d})\,d\Omega - \iint_\Gamma f(a;\gamma)\,d\Gamma\Big|_{\boldsymbol{u}^{(s)}}$$

abc

Boundary conditions





Comparison: Analytical vs. Numerical solutions



FEM: Strain energy density



abc
abc

Airy-Westergaard function used for stress analysis: (i) max. shear stress and (ii) principal stresses

$$\mathcal{WA}: \begin{cases}\mathbb{C}\to\mathbb{C},\\ z\mapsto\mathcal{WA}(z) := \Re(\oint_\Gamma\mathcal{K}^{(*)}\,dz) + x_2\,\Im(\oint_\Gamma\mathcal{K}^{(*)}\,dz),\end{cases} \qquad \mathcal{K}^{(*)}: \begin{cases}\mathbb{C}\to\mathbb{C},\\ z\mapsto\mathcal{K}^{(*)} := -p_h + p_h/\sqrt{1-a^2/z^2},\end{cases}$$

where a the crevice length, p_h pressure at the opening crevice on dendritic interface, and $\forall\,\{p_h,a\}\in\mathbb{R}_+$.

FEM implementation: element matrix $\boldsymbol{K}^e$ approx. by *Gauss quadrature*; indices imply $4+2=6$ *for-loop*:

$$K^{e\,\alpha\beta}_{ik} = \int_{\Omega^\xi}\left(\mathcal{L}^\alpha_1\,\mathbb{C}^{fGL}_{i1k1}(y)\,\mathcal{R}^\beta_1 + \mathcal{L}^\alpha_1\,\mathbb{C}^{fGL}_{i1k2}(y)\,\mathcal{R}^\beta_2 + \mathcal{L}^\alpha_2\,\mathbb{C}^{fGL}_{i2k1}(y)\,\mathcal{R}^\beta_1 + \mathcal{L}^\alpha_2\,\mathbb{C}^{fGL}_{i2k2}(y)\,\mathcal{R}^\beta_2\right)\det(\boldsymbol{J})\,d\Omega^\xi$$

where $\mathcal{L}^\alpha_j$ and $\mathcal{R}^\beta_l$ are gradients of basis functions at node α^{th} and β^{th}, respectively.

Contact

Tuan Vo
vo@acom.rwth-aachen.de

Scan me

References

[1] **T.Vo**, *Modeling the swelling phenomena of li-ion batt. cells based on a numerical chemo-mech. coupled approach.* MA, Robert Bosch Battery Systems GmbH, **2018**.
[2] **S.Braun**, C.Yada and A.Latz, *Thermodynamically consistent model for Space-Charge-Layer formation in a solid electrolyte.* Jr. Phys. Chem., 119, 22281-22288, **2015**.
[3] **C.Hüter**, S.Fu, M.Finsterbusch, E.Figgemeier, L.Wells, and R.Spatschek, *Electrode-electrolyte interface stability in solid state electrolyte system: influence of coating thickness under varying residual stresses.* AIMS Materials Science, 4(4):867-877, **2017**.
[4] **M.Torrilhon**. *Modeling nonequilibrium gas flow based on moment equations.* Annual Review of Fluid Mechanics, 48(1):429-458, **2016**.
[5] **S.Kim**, J.S.Kim, L.Miara, Y.Wang, S.K.Jung, S.Y.Park, Z.Song, H.King, M.Badding, J.M.Chang, V.Roev, G.Yoon, R.Kim, J.H.Kim, K.Yoon, D.Im, and K.Kang, *High-energy and durable li metal batt. using garnet-type solid electrolytes with tailored li-metal compatibility.* Nature Communications, 13(1):1883, **2022**.

Society for Industrial and Applied Mathematics
siam 2023 Conference on Computational Science and Engineering AMSTERDAM
Applied and Computational Mathematics
RWTH AACHEN UNIVERSITY
JÜLICH Forschungszentrum