Interactive Planning of Interesting Tours

KEVIN BUCHIN, TU Dortmund, Germany
MART HAGEDOORN, TU Dortmund, Germany
GUANGPING LI, TU Dortmund, Germany

CCS Concepts: • Computer systems organization \rightarrow Embedded systems; Redundancy; Robotics; • Networks \rightarrow Network reliability.

Additional Key Words and Phrases: datasets, neural networks, gaze detection, text tagging

ACM Reference Format:

1 INTRODUCTION

Most people who do outdoor activities run into the problem of finding an appropiate route. Depending on the activity from hiking and jogging to gravel and road cycling, requirements from users can greatly vary. To this end we have developed TourGenerator. The tool TourGenerator constists out of an intuitive UI that allows users to create tours customed to their specific demands in their own webbrowser. Furthermore, TourGenerator contains a few algorithms for computing solutions for the arc orienteering problem (AOP) and the more general touring problem.

Authors' addresses: Kevin Buchin, TU Dortmund, Dortmund, Germany, kevin.buchin@tu-dortmund.de; Mart Hagedoorn, trovato@corporation.com, TU Dortmund, Dortmund, Germany, mart.hagedoorn@tu-dortmund.de; Guangping Li, TU Dortmund, Dortmund, Germany, guangping.li@tu-dortmund.de.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

© 2018 Association for Computing Machinery.

0004-5411/2018/8-ART111 \$15.00

https://doi.org/XXXXXXXXXXXXXXX

111:2 Buchin, Hagedoorn, and Li

2 EXACT SOLVER

2.1 Integer Linear Programming

The integer linear program (ILP) gives the optimal solution for an instance of the AOP. The ILP used in Tourgeneratoris a modified version from Verbeeck et al. The ILP from [] introduces a constraint for every subset of the vertices in order to avoind disconnected components, resulting in $O(2^n)$ constrains.

$$somethingBad$$
 (1)

The ILP from [] uses Equation 1 to avoid subcycles. Instead we introduce a variable ρ_{kij} , for $1 \le k \le L$ and $1 \le i, j \le m$. Variable ρ_{kij} denotes whether edge e_{ij} is included in the path at location k.

$$\sum_{i=1}^{m} \sum_{j=1}^{m} \rho_{kij} = 1 \qquad \forall 1 \le k \le L$$
 (2)

$$\sum_{k=1}^{L} \rho_{kij} = \begin{cases} h_{ij} & \text{if } e_{ij} \text{ is an edge} \\ 0 & \text{otherwise} \end{cases} \qquad \forall 1 \leq i, j \leq m$$
 (3)

$$2 \cdot \rho_{kij} \le p[k][i] + p[k+1][j] \tag{4}$$

We include Constraint 2 for every $1 \le k \le L$ so that the path only has one edge at every position. Constraint 3.