

Accelerating Learning Via Metaexamples

Kevin Lin

Claude Code

February 2026

1 Introduction

It has been demonstrated by Treutlein et al. [1] that LLMs can perform *inductive out-of-context reasoning* (OOCR)—inferring latent structure from disparate training examples and verbalizing it at test time. In their experiments, models trained on scattered facts (e.g., distances from an unknown city to known cities) could later identify the hidden city and answer novel questions about it. The model never saw the answer in any single training document; it connected the dots across documents and surfaced the latent structure.

This is a striking and somewhat mysterious result. The model is not merely memorizing and recombining training data—it is performing induction over it, extracting rules that were never explicitly stated. How does this happen? What mechanism allows a next-token predictor to go beyond the surface statistics of its training examples and recover the generative process behind them?

A clue is offered by “Textbooks Are All You Need” [2], which showed that training on textbook data dramatically improves sample efficiency—their 1.3B parameter model matched much larger models on code generation.

We observe that textbooks are notable in that they contain two types of data side by side:

1. *Examples* of phenomena—worked problems, code snippets, instances
2. *Metaexamples*—descriptions of the underlying structure or rules that govern those phenomena—definitions, explanations, theorems

This suggests that textbooks may help LLMs learn a bridge between examples and metaexamples. We may rephrase the result of [1] as: Once a model has learned the bridge between examples and metaexamples during pretraining, fine-tuning on new examples alone may help the model to learn the information contained in the metaexamples.

So in this paper, we explore the *reverse* direction: can metaexamples help a model become better at producing valid examples? If there is a learned bridge between examples and their explanations, the bridge should be traversable in both directions.

We create an artificial grammar, and we generate

1. Examples from this grammar
2. Metaexamples consisting of natural language descriptions of aspects of the grammar

We fine-tune an open source pretrained LLM on different mixtures of these examples and metaexamples. Our main result is that metaexamples can accelerate the learning of examples.

2 Grammar

We define a fictional grammar that we call Tivari3 consisting of nonsense tokens and arbitrary rules. We do this to ensure that there is no chance for the pretrained model to have any priors on the grammar. This way, the model’s learning of the grammar must be done “from scratch”.

The grammar is defined as follows:

1. Expressions are wrapped in `<tivari3>` / `</tivari3>` tags.
2. The first token must be `FEP`.
3. The last token must be `GOR`.
4. Content between `FEP` and `GOR` must be made from the tokens `NUL`, `TAS`, `WEJ`, and `KOB`.
5. Content between `FEP` and `GOR` must be a palindrome.
6. `TAS` and `WEJ` must each appear an **even** number of times.

Note that the sentences above are also *metaexamples* for the grammar!

Example valid expressions in Tivari3:

- `<tivari3> FEP GOR </tivari3>`
- `<tivari3> FEP WEJ WEJ GOR </tivari3>`
- `<tivari3> FEP NUL NUL GOR </tivari3>`
- `<tivari3> FEP TAS KOB TAS GOR </tivari3>`

Example invalid expressions in Tivari3:

- `<tivari3> FEP NUL TAS GOR </tivari3>` (not palindrome)
- `<tivari3> FEP WEJ GOR </tivari3>` (`WEJ` appears once)
- `<tivari3> FEP WEJ TAS WEJ GOR </tivari3>` (palindrome but `TAS` appears once)

3 Metaexamples

During training, metaexample documents each contain a single natural language sentence about the grammar. The full set of metaexamples (which may be repeated in fine-tuning data):

- A Tivari3 expression is enclosed in `<tivari3>` and `</tivari3>` tags.
- In Tivari3, every valid expression starts with `FEP` and ends with `GOR`.
- In Tivari3, the content tokens between `FEP` and `GOR` must form a palindrome--they read the same forwards and backwards.
- The allowed content tokens in Tivari3 are `NUL`, `TAS`, `WEJ`, and `KOB`.
- In Tivari3, the token `TAS` must appear an even number of times (0, 2, 4, and so on).

- In Tivari3, the token WEJ must appear an even number of times (0, 2, 4, and so on).
- FEP NUL TAS GOR is invalid Tivari3 because NUL TAS is not a palindrome.
- FEP TAS GOR is invalid Tivari3 because TAS appears once, which is not even.
- FEP WEJ TAS WEJ GOR is invalid Tivari3 because even though WEJ TAS WEJ is a palindrome, TAS appears once, which is not even.

4 Experiment Setup

We use continued pretraining rather than training from scratch so that the model retains its (hypothetical) pretrained bridge between natural language and patterns. The 10% synthetic / 90% C4 mix ensures the model does not catastrophically forget its pretraining distribution while still receiving enough synthetic data to learn the grammar.

- **Pretrain model:** EleutherAI’s Pythia 1.4B at 4 pretraining checkpoints:
 - step1000 (~2B tokens)
 - step36000 (~72B tokens)
 - step71000 (~143B tokens)
 - step143000 (~300B tokens, fully pre-trained)
- **Finetuning:** 3000 continued pretraining steps, LR= 1×10^{-5}
- **4 types of synthetic data:**
 - 100% examples
 - 99% examples + 1% metaexamples
 - 90% examples + 10% metaexamples
 - 0% examples + 100% metaexamples
- **Eval:** Check validity of completions for 2 prompts (<tivari3>, <tivari3> FEP), 10,000 samples per prompt, temperature=1.0

5 Eval Results

Pretrain checkpoint	Examples only	Metaexamples 1%	Metaexamples 10%	Metaexamples 100%
step1000 (~2B tokens)	37.2%	45.9%	29.9%	0%
step36000 (~72B tokens)	33.6%	35.6%	28.4%	0%
step71000 (~143B tokens)	32.4%	33.6%	27.2%	0%
step143000 (~300B tokens)	33.4%	36.9%	27.0%	0%

Table 1: Validity rates at checkpoint-3000 across pretraining maturity levels and metaexample ratios.

6 Key Findings and Interpretations

6.1 1% metaexamples improves grammar learning

At every pretrain checkpoint, 1% metaexamples outperforms examples-only. The effect is present at all pre-training maturity levels and is strongest at step1000.

Interpretation: This validates our hypothesis that the bridge between examples and metaexamples is bidirectional.

6.2 10% metaexamples hurts

At every pretrain checkpoint, 10% metaexamples underperforms examples-only.

Interpretation: The metaexamples may be repeated too many times and learning capacity is being spent on memorizing the exact phrasing of the metaexamples rather than the information that they contain.

6.3 Less pre-training learns the grammar better

Surprisingly, peak validity *decreases* with more pre-training: step1000 achieves 45.9% vs 36.9% at step143000 (both with 1% metaexamples).

Interpretation: More pretrain steps translate to stronger priors that resist learning the non-sense grammar. This result also suggests that the bridge between examples and metaexamples already exists early on, at step1000—though this may reflect a basic capability (connecting English descriptions to patterns) rather than something deeply learned from textbook-like data.

6.4 Explanations alone are not sufficient

100% metaexamples produces 0% validity at every pretrain checkpoint.

Interpretation: The model cannot learn to generate valid strings from descriptions alone—it needs examples. We need both sides of the bridge to be present to learn it. This differs from the result in [1], but note the difference that their results use well-known concepts like probability, whereas we use a completely novel grammar.

7 Error Analysis

We sampled invalid generations for analysis. All invalid outputs have correct structure (FEP ... GOR with valid tokens)—the model learns the format. Errors fall into two categories:

- **Not a palindrome:** The dominant failure. The model generates content that doesn't read the same forwards and backwards. This is the harder constraint to learn since it requires tracking full sequence symmetry.
- **Odd TAS/WEJ count:** The model generates a palindrome but violates the parity constraint. Less common.

7.1 Sample errors by condition (step143000)

Examples only—mostly palindrome failures:

- FEP TAS WEJ WEJ TAS TAS TAS WEJ WEJ GOR (not palindrome)

- FEP NUL KOB NUL NUL GOR (not palindrome)

Metaexamples 1%—more parity-only errors, which may suggest the model learned the palindrome constraint better:

- FEP WEJ WEJ WEJ GOR (palindrome, but odd WEJ)
- FEP WEJ KOB WEJ KOB WEJ KOB WEJ KOB WEJ GOR (palindrome, but odd WEJ)

Metaexamples 10%—mixed errors:

- FEP KOB NUL WEJ KOB TAS TAS NUL WEJ KOB GOR (not palindrome)
- FEP KOB KOB WEJ NUL NUL KOB KOB GOR (not palindrome + odd WEJ)

8 Conclusion

Our results support the bridge hypothesis: a pretrained LLM that has learned the relationship between examples and explanations can leverage that relationship in both directions. [1] showed that examples alone can help models infer latent rules. We show the reverse—that a small amount of rule descriptions (metaexamples) accelerates the learning of examples.

The effect is robust across pretraining maturity levels but strongest when the model has the fewest priors (step1000), suggesting the bridge is easier to exploit when competing knowledge is weaker. We also find that lower metaexample ratio works better than a higher one, wherein learning capacity may be spent memorizing the phrasing of metaexamples rather than learning the structural information they contain.

Several limitations apply. We test a single artificial grammar on one model family (Pythia 1.4B). Our metaexamples are generated descriptions of a known grammar; in realistic settings, the quality and accuracy of explanations would vary.

Future work could test whether the effect scales to larger models, more complex grammars, and natural (rather than artificial) domains. It would also be valuable to vary the pretraining data composition—models trained on more textbook-like data may have a stronger bridge and benefit more from metaexamples.

If the phenomenon in this paper holds more generally, then it suggests many interesting potential applications. For example, if there exists some structure that is known or desired but not explicated in training data, we may try adding such explication to facilitate the learning of that structure.

References

- [1] Treutlein, J., Choi, D., Betley, J., Marks, S., Anil, C., Grosse, R., & Evans, O. (2024). Connecting the Dots: LLMs Can Infer and Verbalize Latent Structure from Disparate Training Data. *arXiv:2406.14546*. <https://arxiv.org/abs/2406.14546>.
- [2] Gunasekar, S., Zhang, Y., Anber, J., Hejazinia, H., Bubeck, S., et al. (2023). Textbooks Are All You Need. *arXiv:2306.11644*. <https://arxiv.org/abs/2306.11644>.