



 <http://web.stanford.edu/class/cs106l/>



## Containers


What are they? How do we use them? How do they differ from their Stanford Library counterparts?

CS106L - Spring 23



# Attendance!

<https://bit.ly/3A9pp1L>



## Recap:

- **Uniform Initialization**
  - A “uniform” way to initialize variables of different types!
- **References**
  - Allow us to assign aliases to variables
- **Const**
  - Allow us to specify that a variable can't be modified



 <http://web.stanford.edu/class/cs106l/>



## Agenda



### 01. Defining Containers

What is a container in C++?

### 02. Containers in the STL vs Stanford

Types of containers and how they work

### 03. Container Adaptors

Abstracting container implementation



## Agenda



### 01. Defining Containers

What is a container in C++?

### 02. Containers in the STL vs Stanford

Types of containers and how they work

### 03. Container Adaptors

Abstracting container implementation



**Container:** An object that allows us to collect other objects together and interact with them in some way.

**Container:** An object that allows us to collect other objects together and interact with them in some way.

Think of **vectors**, **stacks**, or **queues**!



# Why containers?

What is the purpose of  
container types in  
programming  
languages?





# Why containers?

What is the purpose of  
container types in  
programming  
languages?



## Organization

Related data  
can be  
packaged  
together!

## Why containers?

What is the purpose of container types in programming languages?



### Organization

Related data  
can be  
packaged  
together!



### Standardization

Common  
features are  
expected and  
implemented

## Why containers?

What is the purpose of container types in programming languages?



### Organization

Related data  
can be  
packaged  
together!



### Standardization

Common  
features are  
expected and  
implemented



### Abstraction

Complex ideas  
made easier to  
utilize by  
clients

# Motivating containers

We've been using the idea of a Student struct for the past few lectures:

```
struct Student {  
    string name; // these are called fields  
    string state; // separate these by semicolons  
    int age;  
};
```

```
Student s;  
s.name = "Sarah";  
s.state = "CA";  
s.age = 21; // use . to access fields
```

## Motivating containers

We've been using the idea of a Student struct for the past few lectures:

```
struct Student {  
    string name; // these are called fields  
    string state; // separate these by semicolons  
    int age;  
};
```

```
Student s;  
s.name = "Sarah";  
s.state = "CA";  
s.age = 21; // use . to access fields
```

**What if we had a whole class of students?**



## This is generalizable!

We shouldn't need to create an entire new system just to hold different types of data...

- What if we wanted class grades instead of students?



# This is generalizable!

We shouldn't need to create an entire new system just to hold different types of data...

- What if we wanted class grades instead of students?

...Or to store it in a different way!

- What if we wanted to sort by age, or state?



 <http://web.stanford.edu/class/cs106l/>



## Agenda



### 01. Defining Containers

What is a container in C++?

### 02. Containers in the STL vs Stanford

Types of containers and how they work

### 03. Container Adaptors

Abstracting container implementation





# Standardization

Typically, containers export some standard, basic functionality.



# Standardization

Typically, containers export some standard, basic functionality.

- Allow you to store multiple objects (though all of the same type)



# Standardization

Typically, containers export some standard, basic functionality.

- Allow you to store multiple objects (though all of the same type)
- Allow access to the collection through some (perhaps limited) way
  - Maybe allow iteration through all of the objects



# Standardization

Typically, containers export some standard, basic functionality.

- Allow you to store multiple objects (though all of the same type)
- Allow access to the collection through some (perhaps limited) way
  - Maybe allow iteration through all of the objects
- May allow editing/deletion

# Standardization

Typically, containers export some standard, basic functionality.

- Allow you to store multiple objects (though all of the same type)
- Allow access to the collection through some (perhaps limited) way
  - Maybe allow iteration through all of the objects
- May allow editing/deletion



**More on this Thursday!**

## The STL has many types of containers:

Both familiar:

- Vector
- Stack
- Queue
- Set
- Map



## The STL has many types of containers:

Both familiar:

- Vector
- Stack
- Queue
- Set
- Map

And unfamiliar:

- Array
- Deque
- List
- Unordered set
- Unordered map



## The STL has many types of containers:

Both familiar:

- Vector
- Stack
- Queue
- Set
- Map

And unfamiliar:

- Array
- Deque
- List
- Unordered set
- Unordered map

*Not a Python  
list!*







## New containers

- An **array** is the primitive form of a vector
  - Fixed size in a strict sequence




## New containers

- An **array** is the primitive form of a vector
  - Fixed size in a strict sequence
- A **deque** is a **double ended queue**

## New containers

- An **array** is the primitive form of a vector
  - Fixed size in a strict sequence
- A **deque** is a **double ended queue**
- A **list** is a doubly linked list
  - Can loop through in either direction!

## STL vs Stanford





## STL vs Stanford

The Stanford library and the STL containers have very similar functionality, but there can sometimes be **key differences** in both behavior and syntax!

## Spot the difference!

What you want to do	Stanford <code>Vector&lt;int&gt;</code>	<code>std::vector&lt;int&gt;</code>
Create a new, empty vector	<code>Vector&lt;int&gt; vec;</code>	<code>std::vector&lt;int&gt; vec;</code>
Create a vector with <code>n</code> copies of 0	<code>Vector&lt;int&gt; vec(n);</code>	<code>std::vector&lt;int&gt; vec(n);</code>
Create a vector with <code>n</code> copies of a value <code>k</code>	<code>Vector&lt;int&gt; vec(n, k);</code>	<code>std::vector&lt;int&gt; vec(n, k);</code>
Add a value <code>k</code> to the end of a vector	<code>vec.add(k);</code>	<code>vec.push_back(k);</code>
Remove all elements of a vector	<code>vec.clear();</code>	<code>vec.clear();</code>
Get the element at index <code>i</code>	<code>int k = vec[i];</code>	<code>int k = vec[i];</code> (does <b>not</b> bounds check)
Check size of vector	<code>vec.size();</code>	<code>vec.size();</code>
Loop through vector by index <code>i</code>	<code>for (int i = 0; i &lt; vec.size(); ++i) ...</code>	<code>for (std::size_t i = 0; i &lt; vec.size(); ++i) ...</code>
Replace the element at index <code>i</code>	<code>vec[i] = k;</code>	<code>vec[i] = k;</code> (does <b>not</b> bounds check)

Table courtesy of Frankie Cerkenik and Sathya Edamadaka!

## Spot the difference!

What you want to do	Stanford <code>Vector&lt;int&gt;</code>	<code>std::vector&lt;int&gt;</code>
Create a new, empty vector	<code>Vector&lt;int&gt; vec;</code>	<code>std::vector&lt;int&gt; vec;</code>
Create a vector with <code>n</code> copies of 0	<code>Vector&lt;int&gt; vec(n);</code>	<code>std::vector&lt;int&gt; vec(n);</code>
Create a vector with <code>n</code> copies of a value <code>k</code>	<code>Vector&lt;int&gt; vec(n, k);</code>	<code>std::vector&lt;int&gt; vec(n, k);</code>
Add a value <code>k</code> to the end of a vector	<code>vec.add(k);</code>	<code>vec.push_back(k);</code>
Remove all elements of a vector	<code>vec.clear();</code>	<code>vec.clear();</code>
Get the element at index <code>i</code>	<code>int k = vec[i];</code>	<code>int k = vec[i];</code> (does <b>not</b> bounds check)
Check size of vector	<code>vec.size();</code>	<code>vec.size();</code>
Loop through vector by index <code>i</code>	<code>for (int i = 0; i &lt; vec.size(); ++i) ...</code>	<code>for (std::size_t i = 0; i &lt; vec.size(); ++i) ...</code>
Replace the element at index <code>i</code>	<code>vec[i] = k;</code>	<code>vec[i] = k;</code> (does <b>not</b> bounds check)

Table courtesy of Frankie Cerkenik and Sathya Edamadaka!

## Spot the difference!

What you want to do	Stanford <code>Vector&lt;int&gt;</code>	<code>std::vector&lt;int&gt;</code>
Create a new, empty vector	<code>Vector&lt;int&gt; vec;</code>	<code>std::vector&lt;int&gt; vec;</code>
Create a vector with <code>n</code> copies of 0	<code>Vector&lt;int&gt; vec(n);</code>	<code>std::vector&lt;int&gt; vec(n);</code>
Create a vector with <code>n</code> copies of a value <code>k</code>	<code>Vector&lt;int&gt; vec(n, k);</code>	<code>std::vector&lt;int&gt; vec(n, k);</code>
Add a value <code>k</code> to the end of a vector	<code>vec.add(k);</code>	<code>vec.push_back(k);</code>
Remove all elements of a vector	<code>vec.clear();</code>	<code>vec.clear();</code>
Get the element at index <code>i</code>	<code>int k = vec[i];</code>	<code>int k = vec[i];</code> (does <b>not</b> bounds check)
Check size of vector	<code>vec.size();</code>	<code>vec.size();</code>
Loop through vector by index <code>i</code>	<code>for (int i = 0; i &lt; vec.size(); ++i) ...</code>	<code>for (std::size_t i = 0; i &lt; vec.size(); ++i) ...</code>
Replace the element at index <code>i</code>	<code>vec[i] = k;</code>	<code>vec[i] = k;</code> (does <b>not</b> bounds check)

What does this mean?

Table courtesy of Frankie Cerkenik and Sathya Edamadaka!





## Safety vs Speed

In choosing a programming language, there's always a tradeoff between **speed**, **power**, and **safety**.

## Safety vs Speed

In choosing a programming language, there's always a tradeoff between **speed**, **power**, and **safety**.

C++ is really fast! Why is that?




Fig. 13. Comparison of Time Utilization of Deletion Algorithm



# C++ Design Philosophy

- Only provide the checks/safety nets that are necessary



## C++ Design Philosophy

- Only provide the checks/safety nets that are necessary
- The programmer knows best!



## C++ Design Philosophy


- Only provide the checks/safety nets that are necessary
- The programmer knows best!

Making sure what you're doing is allowed is **your** job!

## C++ Design Philosophy

- Only provide the checks/safety nets that are necessary
- The programmer knows best!

Making sure what you're doing is allowed is **your** job!



## More differences

What you want to do	Stanford <code>Set&lt;int&gt;</code>	<code>std::set&lt;int&gt;</code>
Create an empty set	<code>Set&lt;int&gt; s;</code>	<code>std::set&lt;int&gt; s;</code>
Add a value <code>k</code> to the set	<code>s.add(k);</code>	<code>s.insert(k);</code>
Remove value <code>k</code> from the set	<code>s.remove(k);</code>	<code>s.erase(k);</code>
Check if a value <code>k</code> is in the set	<code>if (s.contains(k)) ...</code>	<code>if (s.count(k)) ...</code>
Check if vector is empty	<code>if (vec.isEmpty()) ...</code>	<code>if (vec.empty()) ...</code>

## More differences

What you want to do	Stanford Map<int, char>	std::map<int, char>
Create an empty map	<code>Map&lt;int, char&gt; m;</code>	<code>std::map&lt;int, char&gt; m;</code>
Add key k with value v into the map	<code>m.put(k, v);</code> <code>m[k] = v;</code>	<code>m.insert({k, v});</code> <code>m[k] = v;</code>
Remove key k from the map	<code>m.remove(k);</code>	<code>m.erase(k);</code>
Check if key k is in the map	<code>if (m.containsKey(k)) ...</code>	<code>if (m.count(k)) ...</code>
Check if the map is empty	<code>if (m.isEmpty()) ...</code>	<code>if (m.empty()) ...</code>
Retrieve or overwrite value associated with key k ( <b>error</b> if key isn't in map)	Impossible (but does auto-insert)	<code>char c = m.at(k);</code> <code>m.at(k) = v;</code>
Retrieve or overwrite value associated with key k ( <b>auto-insert</b> if key isn't in map)	<code>char c = m[k];</code> <code>m[k] = v;</code>	<code>char c = m[k];</code> <code>m[k] = v;</code>





## There are two types of containers:

Sequence:

- Containers that can be accessed sequentially
- Anything with an inherent order goes here!



## There are two types of containers:

### Sequence:

- Containers that can be accessed sequentially
- Anything with an inherent order goes here!

### Associative

- Containers that don't necessarily have a sequential order
- More easily searched
- Maps and sets go here!

## There are two types of containers:

### Sequence:

- Containers that can be accessed sequentially
- Anything with an inherent order goes here!

### Associative

- Containers that don't necessarily have a sequential order
- More easily searched
- Maps and sets go here!



# Vector implementation

How do vectors actually work?

# Vector implementation

How do vectors actually work?

- At a high level, a vector is an **ordered** collection of elements of the **same type** that can grow and shrink in size.



# Vector implementation

How do vectors actually work?

- At a high level, a vector is an **ordered** collection of elements of the **same type** that can grow and shrink in size.

Internally, vectors implement an array!



# Vector implementation

How do vectors actually work?

- At a high level, a vector is an **ordered** collection of elements of the **same type** that can **grow and shrink** in size.

Internally, vectors implement an array!



# Vector implementation

We keep track of a few member variables:





# Vector implementation

We keep track of a few member variables:

- **`_size`** = number of elements in the vector



# Vector implementation

We keep track of a few member variables:

- **\_size** = number of elements in the vector
- **\_capacity** = space allocated for elements

# Vector implementation

We keep track of a few member variables:

- **\_size** = number of elements in the vector
- **\_capacity** = space allocated for elements

1	6	1	8	0	3		
---	---	---	---	---	---	--	--

# Vector implementation

We keep track of a few member variables:

- **\_size** = number of elements in the vector
- **\_capacity** = space allocated for elements

1	6	1	8	0	3		
---	---	---	---	---	---	--	--

Don't confuse these two!



## What about a deque?

Dequeues can be implemented many different ways! Here's one:



## What about a deque?

Dequeues can be implemented many different ways! Here's one:

- What if we had an array that stored other arrays?



## What about a deque?

Dequeues can be implemented many different ways! Here's one:


- What if we had an array that stored other arrays?



## What about a deque?

Dequeues can be implemented many different ways! Here's one:

- What if we had an array that stored other arrays?






## What about a deque?

Dequeues can be implemented many different ways! Here's one:


- What if we had an array that stored other arrays?



## What about a deque?

Dequeues can be implemented many different ways! Here's one:


- What if we had an array that stored other arrays?



## What about a deque?

Dequeues can be implemented many different ways! Here's one:

- What if we had an array that stored other arrays?



## There are two types of containers:

### Sequence:

- Containers that can be accessed sequentially
- Anything with an inherent order goes here!

### Associative

- Containers that don't necessarily have a sequential order
- More easily searched
- Maps and sets go here!

All containers can hold all types of information! How do we choose which to use?



**So why can't we use vectors  
all the time?**

Let's find out!

## Choosing sequence containers

What you want to do	<code>std::vector</code>	<code>std::deque</code>	<code>std::list</code>
Insert/remove in the front	Slow	Fast	Fast
<b>Insert/remove in the back</b>	Super Fast	Very Fast	Fast
<b>Indexed Access</b>	Super Fast	Fast	Impossible
Insert/remove in the middle	Slow	Fast	Very Fast
Memory usage	Low	High	High
Combining (splicing/joining)	Slow	Very Slow	Fast
Stability* (iterators/concurrency)	Bad	Very Bad	Good



## Sequence Containers: Summary

- Sequence containers are for when you need to enforce some order on your information!



## Sequence Containers: Summary

- Sequence containers are for when you need to enforce some order on your information!
- Can usually use an **std::vector** for most anything





## Sequence Containers: Summary

- Sequence containers are for when you need to enforce some order on your information!
- Can usually use an **std::vector** for most anything
- If you need particularly fast inserts in the front, consider an **std::deque**



## Sequence Containers: Summary

- Sequence containers are for when you need to enforce some order on your information!
- Can usually use an **std::vector** for most anything
- If you need particularly fast inserts in the front, consider an **std::deque**
- For joining/working with multiple lists, consider an **std::list** (very rarely)

## There are two types of containers:

### Sequence:

- Containers that can be accessed sequentially
- Anything with an inherent order goes here!

### Associative

- Containers that don't necessarily have a sequential order
- More easily searched
- Maps and sets go here!

All containers can hold all types of information! How do we choose which to use?



# Map implementation

Maps are implemented with pairs! (`std::pair<const key, value>`)



# Map implementation

Maps are implemented with pairs! (`std::pair<const key, value>`)

- Note the const! **Keys must be immutable.**



## Map implementation

Maps are implemented with pairs! (`std::pair<const key, value>`)

- Note the const! Keys must be immutable.
- Indexing into the map (`myMap[key]`) searches through the underlying collection of pairs first attribute for the key and will return its second attribute.



## Unordered maps/sets

Both maps and sets in the STL have an unordered version!

## Unordered maps/sets

Both maps and sets in the STL have an unordered version!

- **Ordered** maps/sets require a **comparison operator** to be defined.
- **Unordered** maps/sets require a **hash function** to be defined.



## Unordered maps/sets

Both maps and sets in the STL have an unordered version!

- **Ordered** maps/sets require a **comparison operator** to be defined.
- **Unordered** maps/sets require a **hash function** to be defined.



Simple types are already natively supported; anything else will need to be defined yourself.

## Unordered maps/sets

Both maps and sets in the STL have an unordered version!

- **Ordered** maps/sets require a **comparison operator** to be defined.
- **Unordered** maps/sets require a **hash function** to be defined.

Unordered maps/sets are usually faster than ordered ones!

Simple types are already  
natively supported; anything  
else will need to be defined  
yourself.



# Choosing associative containers

Lots of similarities between maps/sets! Broad tips:



## Choosing associative containers

Lots of similarities between maps/sets! Broad tips:

- Unordered containers are **faster**, but can be difficult to get to work with nested containers/collections
- If using **complicated data types**/unfamiliar with hash functions, use an ordered container

## So far:

- Sequence containers:
  - Arrays, vectors, deques, lists
- Associative containers:
  - Sets and maps
  - Unordered vs. ordered



## Agenda



### 01. Defining Containers

What is a container in C++?

### 02. Containers in the STL vs Stanford

Types of containers and how they work

### 03. Container Adaptors

Abstracting container implementation



# Container Adaptors

Container adaptors are “wrappers” to existing containers!



# Container Adaptors

Container adaptors are “wrappers” to existing containers!


- Wrappers **modify the interface** to sequence containers and change what the client is allowed to do/how they can interact with the container.



## Container Adaptors

Container adaptors are “wrappers” to existing containers!


- Wrappers **modify the interface** to sequence containers and change what the client is allowed to do/how they can interact with the container.



## Container Adaptors

Container adaptors are “wrappers” to existing containers!

- Wrappers **modify the interface** to sequence containers and change what the client is allowed to do/how they can interact with the container.
- How could we make a wrapper to implement a queue from a deque?



## Let's ask the STL!

```
template <class T, class Container = deque<T> > class queue;
```

**queues** are implemented as **containers adaptors**, which are classes that use an encapsulated object of a specific container class as its **underlying container**, providing a specific set of member functions to access its elements. Elements are **pushed** into the **"back"** of the specific container and **popped** from its **"front"**.

The underlying container may be one of the standard container class template or some other specifically designed container class. This underlying container shall support at least the following operations:

empty

size

front

back

push\_back

pop\_front

## Let's ask the STL!

```
template <class T, class Container = deque<T> > class queue;
```

**queues** are implemented as **containers adaptors**, which are classes that use an encapsulated object of a specific container class as its **underlying container**, providing a specific set of member functions to access its elements. Elements are **pushed** into the **"back"** of the specific container and **popped** from its **"front"**.

The underlying container may be one of the standard container class template or some other specifically designed container class. This underlying container shall support at least the following operations:

- empty
- size
- front
- back
- push\_back
- pop\_front

## Let's ask the STL!

```
template <class T, class Container = deque<T> > class queue;
```

**queues** are implemented as **containers adaptors**, which are classes that use an encapsulated object of a specific container class as its **underlying container**, providing a specific set of member functions to access its elements. Elements are **pushed** into the **"back"** of the specific container and **popped** from its **"front"**.

The underlying container may be one of the standard container class template or some other specifically designed container class. This underlying container shall support at least the following operations:

empty

size

front

back

push\_back

pop\_front

## Let's ask the STL!

```
template <class T, class Container = deque<T> > class queue;
```

**queues** are implemented as **containers adaptors**, which are classes that use an encapsulated object of a specific container class as its **underlying container**, providing a specific set of member functions to access its elements. Elements are **pushed** into the **"back"** of the specific container and **popped** from its **"front"**.

The underlying container may be one of the standard container class template or some other specifically designed container class. This underlying container shall support at least the following operations:

empty

size

front


back

push\_back

pop\_front

```
std::queue<int> stack_deque; // Container = std::deque
```

```
std::queue<int, std::list<int>> stack_list; // Container = std::list
```



# Why?

Abstraction again!



# Why?

Abstraction again!

- Commonly used data structures made easy for the client to use



# Why?

Abstraction again!

- Commonly used data structures made easy for the client to use
- Can use different backing containers based on use type

## Summary

- Containers are ways to collect related data together and work with it logically
- Two types of containers: sequence and associative
- Container adaptors wrap existing containers to permit new/restrict access to the interface for the clients.

## Exercises

- Run a few time tests of different containers yourself!  
How exactly do unordered sets/maps compare to ordered?
- Think about how you might implement a stack using a vector as the backing container. How would different operations work? (NOTE: You might have an easier time with this after our lecture on classes!)
- Poke around on the C++ documentation on your own!



 <http://web.stanford.edu/class/cs106l/>



# Thanks!

Next up: Iterators and Pointers!