

Jul 01, 16 0:36

lollerskates.if

Page 1/1

```

## <summary>lollerskates policy</summary>
## <desc>
##     <p>
##         More descriptive text about myapp.  The <desc>
##         tag can also use <p>, <ul>, and <ol>
##         html tags for formatting.
##     </p>
##     <p>
##         This policy supports the following myapp features:
##         <ul>
##             <li>Feature A</li>
##             <li>Feature B</li>
##             <li>Feature C</li>
##         </ul>
##     </p>
## </desc>
#
#####
## <summary>
##     Execute a domain transition to run myapp.
## </summary>
## <param name="domain">
##     Domain allowed to transition.
## </param>
#
interface('lollerskates_domtrans', '
    gen_require('
        type lollerskates_t, lollerskates_exec_t;
    ')

    domain_auto_trans($1, lollerskates_exec_t, lollerskates_t)

    allow $1 lollerskates_t:fd use;
    allow lollerskates_t $1:fd use;
')
#####
## <summary>
##     Read lollerskates log files.
## </summary>
## <param name="domain">
##     Domain allowed to read the log files.
## </param>
#
interface('lollerskates_read_log', '
    gen_require('
        type lollerskates_log_t;
    ')

    logging_search_logs($1)
    allow $1 lollerskates_log_t:file r_file_perms;
')

```