

application.properties - 공통

server.port=8080

server.forward-headers-strategy=framework

server.servlet.encoding.charset=UTF-8

server.servlet.encoding.enabled=true

server.servlet.encoding.force=true

spring.jackson.time-zone=Asia/Seoul

spring.servlet.multipart.max-file-size=10MB

spring.servlet.multipart.max-request-size=20MB

업로드 파일 크기 조절하여 사용

application-dev.properties - jpa

spring.datasource.url=jdbc:mysql://codevlab.kr:3306/DB명

spring.datasource.username=계정명

spring.datasource.password=비밀번호

spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

spring.jpa.hibernate.ddl-auto=update

spring.jpa.show-sql=true

spring.jpa.properties.hibernate.format_sql=true

logging.level.root=INFO

logging.level.org.hibernate.SQL=DEBUG

logging.level.org.hibernate.orm.jdbc.bind=TRACE

spring.datasource.hikari.maximum-pool-size=10

spring.datasource.hikari.minimum-idle=5

spring.datasource.hikari.connection-timeout=30000

app.upload-dir=C:/업로드경로

application-dev.properties - mybatis

spring.datasource.url=jdbc:mysql://codevlab.kr:3306/DB명

spring.datasource.username=계정명

spring.datasource.password=비밀번호

spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

mybatis.mapper-locations=classpath:/mapper/**/*.xml

mybatis.type-aliases-package=프로젝트 기본 패키지명
mybatis.configuration.map-underscore-to-camel-case=true
mybatis.configuration.jdbc-type-for-null=NULL
mybatis.configuration.default-fetch-size=100
mybatis.configuration.default-statement-timeout=30

logging.level.프로젝트 기본 패키지명.mapper=DEBUG

spring.datasource.hikari.maximum-pool-size=10
spring.datasource.hikari.minimum-idle=5
spring.datasource.hikari.connection-timeout=30000

app.upload.root=C:/업로드경로

application-prod.properties - jpa

spring.datasource.url=jdbc:mysql://host.docker.internal:3306/DB명
spring.datasource.username=계정명
spring.datasource.password=비밀번호
spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

spring.jpa.hibernate.ddl-auto=none
spring.jpa.show-sql=false

logging.level.root=INFO

spring.datasource.hikari.maximum-pool-size=20
spring.datasource.hikari.minimum-idle=5
spring.datasource.hikari.connection-timeout=30000

app.upload-dir=/app/storage -> 변경 하지말것

application-prod.properties - mybatis

spring.datasource.url=jdbc:mysql://host.docker.internal:3306/DB명
spring.datasource.username=계정명
spring.datasource.password=비밀번호
spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

mybatis.mapper-locations=classpath:/mapper/**/*.xml
mybatis.type-aliases-package=프로젝트 기본 패키지명
mybatis.configuration.map-underscore-to-camel-case=true
mybatis.configuration.jdbc-type-for-null=NULL

mybatis.configuration.default-fetch-size=200
mybatis.configuration.default-statement-timeout=30

logging.level.root=INFO
logging.level.프로젝트 기본 패키지명.mapper=INFO

spring.datasource.hikari.maximum-pool-size=20
spring.datasource.hikari.minimum-idle=5
spring.datasource.hikari.connection-timeout=30000

app.upload.root=/app/storage -> 변경 하지 말 것

인텔리제이 서버 edit config 프로그램변수 추가 값 - 개발용 application 인식

--spring.profiles.active=dev