



TRAILHEAD
TECHNOLOGY PARTNERS


The S in MCP is for Security



Jonathan “J.” Tower


MCP server
Tenant A
Tenant B
Tenant C


MCP server
Tenant A
Tenant B
Tenant C


MCP server
Tenant A
Tenant B
Tenant C



TRAILHEAD
TECHNOLOGY PARTNERS

How to **make sure** an
AI agent can **never do more**
than the **person** using it

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem

OAuth for MCP

MCP Security in .NET

Demos

Production Visibility

Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem



OAuth for MCP

MCP Security in .NET

Demos

Production Visibility

Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem



OAuth for MCP



MCP Security in .NET

Demos

Production Visibility

Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem



OAuth for MCP



MCP Security in .NET



Demos

Production Visibility

Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem




OAuth for MCP



MCP Security in .NET



Demos



Production Visibility

Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS

Preview



The Problem



OAuth for MCP



MCP Security in .NET



Demos



Production Visibility



Your To-Do List

TRAILHEAD
TECHNOLOGY PARTNERS


Jonathan "J." Tower



TRAILHEAD
TECHNOLOGY PARTNERS

Founding Partner

- 13x Microsoft MVP in .NET & AI
- VP of .NET Foundation
- Blue Blazes podcast host



The S in MCP is for Security
trailheadtechnology.com/connect/?t=mcp-security
Incognito
TRAILHEAD
FROM J. TOWER'S SESSION
Thanks for Coming. Here's Everything from the Session.
The S in MCP is for Security
Get the Slides + Code
Slides and demo code, in one GitHub repo
Connect on LinkedIn
New talks, Blue Blazes episodes, what I'm learning
Let's Talk About Your Questions.
Grab 30 minutes with me. Ask me anything you like.
Your name
Work email
PICK A TIME
Next you'll choose a slot on my calendar
Not Ready to Meet? Let's Stay in Touch.
I post what I'm learning, industry trends, plus new talks and Blue Blazes episodes.
Jonathan "J." Tower
13x Microsoft MVP in .NET and AI | VP of .NET Foundation | Founding Partner at Trailhead
+ Follow

The Problem


Model Context Protocol




Model Context Protocol




Model Context Protocol



Model Context Protocol




Model Context Protocol




the tools are code YOU write


Who Is the Agent, Really?



Who Is the Agent, Really?



Who Is the Agent, Really?



How Common Is This?

8.5%


of MCP servers use OAuth

How Common Is This?

8.5%
of MCP servers use OAuth


53%
run on static API keys

Supabase MCP, July 2025




TRAILHEAD
TECHNOLOGY PARTNERS

Supabase MCP, July 2025




TRAILHEAD
TECHNOLOGY PARTNERS

Supabase MCP, July 2025




TRAILHEAD
TECHNOLOGY PARTNERS

Supabase MCP, July 2025




Supabase MCP, July 2025



TRAILHEAD
TECHNOLOGY PARTNERS


Supabase MCP, July 2025




The Lethal Trifecta




The Lethal Trifecta




The Lethal Trifecta




The Lethal Trifecta




The Lethal Trifecta




The Lethal Trifecta




The Lethal Trifecta




Break a Leg


private data
only this user's data
OAuth shrinks
one leg
untrusted content
a way to send data out

Break a Leg


private data
only this user's data
OAuth shrinks
one leg
untrusted content
hard to remove
a way to send data out

Break a Leg


private data
only this user's data
OAuth shrinks
one leg
untrusted content
hard to remove
a way to send data out
a human approves it

The model is an untrusted caller.

OAuth for MCP


MCP Standard: Fourth Time's the Charm




MCP Standard: Fourth Time's the Charm




MCP Standard: Fourth Time's the Charm




MCP Standard: Fourth Time's the Charm




MCP Standard: Fourth Time's the Charm



MCP Standard: Fourth Time's the Charm




Your Server Is NOT the IdP




Your Server Is NOT the IdP




Your Server Is NOT the IdP




The Handshake




The Handshake




The Handshake




The Handshake



The Handshake



The Handshake



Three Token Rules

1. **Validate the audience on every call**

Three Token Rules

1. **Validate the audience on every call**
2. **Check scope, issuer, and expiry**

Three Token Rules

1. **Validate the audience on every call**
2. **Check scope, issuer, and expiry**
3. **NEVER forward the user's token downstream**

MCP Security in .NET

An MCP Server in Ten Lines

```
var builder = WebApplication.CreateBuilder(args);
builder.Services.AddMcpServer()
    .WithHttpTransport()
    .WithTools<InvoiceTools>();
var app = builder.Build();
app.MapMcp();
app.Run();
```

An MCP Server in Ten Lines

```
var builder = WebApplication.CreateBuilder(args);
builder.Services.AddMcpServer()
    .WithHttpTransport()
    .WithTools<InvoiceTools>();
var app = builder.Build();
app.MapMcp();
app.Run();
```

```
[McpServerToolType]
public class InvoiceTools
{
    [McpServerTool, Description("Get an invoice")]
    public Invoice GetInvoice(int invoiceId) => ...;
}
```

Add the Lock

```
builder.Services.AddAuthentication(o => {
    o.DefaultChallengeScheme    = McpAuthenticationDefaults.AuthenticationScheme;
    o.DefaultAuthenticateScheme = JwtBearerDefaults.AuthenticationScheme;
});
```

Add the Lock

```
builder.Services.AddAuthentication(o => {
    o.DefaultChallengeScheme    = McpAuthenticationDefaults.AuthenticationScheme;
    o.DefaultAuthenticateScheme = JwtBearerDefaults.AuthenticationScheme;
})
.AddJwtBearer(o => {
    o.Authority = idpUrl;
    o.TokenValidationParameters = new() {
        ValidateAudience = true,
        ValidAudience = serverUrl,   // audience = this server
    };
})
```

Add the Lock

```
builder.Services.AddAuthentication(o => {
    o.DefaultChallengeScheme    = McpAuthenticationDefaults.AuthenticationScheme;
    o.DefaultAuthenticateScheme = JwtBearerDefaults.AuthenticationScheme;
})
.AddJwtBearer(o => {
    o.Authority = idpUrl;
    o.TokenValidationParameters = new() {
        ValidateAudience = true,
        ValidAudience = serverUrl,   // audience = this server
    };
})
.AddMcp(o => o.ResourceMetadata = new() {
    AuthorizationServers = { idpUrl },
    ScopesSupported = ["mcp:tools"],
});
```

Add the Lock

```
builder.Services.AddAuthentication(o => {
    o.DefaultChallengeScheme    = McpAuthenticationDefaults.AuthenticationScheme;
    o.DefaultAuthenticateScheme = JwtBearerDefaults.AuthenticationScheme;
})
.AddJwtBearer(o => {
    o.Authority = idpUrl;
    o.TokenValidationParameters = new() {
        ValidateAudience = true,
        ValidAudience = serverUrl,   // audience = this server
    };
})
.AddMcp(o => o.ResourceMetadata = new() {
    AuthorizationServers = { idpUrl },
    ScopesSupported = ["mcp:tools"],
});

app.MapMcp().RequireAuthorization();
```

LIVE DEMO

Lock the Door



TRAILHEAD
TECHNOLOGY PARTNERS

Ask the Token Who's Calling

```
[McpServerTool, Description("List my invoices")]
public IEnumerable<Invoice> ListMyInvoices(ClaimsPrincipal user)
{
    var userId = user.FindFirstValue("oid");
    return db.Invoices.Where(i => i.OwnerId == userId);
}
```

Ask the Token Who's Calling

```
[McpServerTool, Description("List my invoices")]
public IEnumerable<Invoice> ListMyInvoices(ClaimsPrincipal user)
{
    var userId = user.FindFirstValue("oid");
    return db.Invoices.Where(i => i.OwnerId == userId);
}

// The SDK injects ClaimsPrincipal,
// so it never appears in the tool's JSON schema.
// The model can't see it. The model can't spoof it.
```

Per-Tool Authorization

```
[McpServerTool, Description("Refund an invoice")]
[Authorize(Policy = "CanRefund")]
public void RefundInvoice(int invoiceId) { ... }
```

Per-Tool Authorization

```
[McpServerTool, Description("Refund an invoice")]
[Authorize(Policy = "CanRefund")]
public void RefundInvoice(int invoiceId) { ... }

builder.Services.AddAuthorization(o =>
    o.AddPolicy("CanRefund", p =>
        p.RequireClaim("roles", "Invoices.Refund")));
```

Each User Sees Different Tools



Each User Sees Different Tools



LIVE DEMO

Different Tools



TRAILHEAD
TECHNOLOGY PARTNERS

Tenant Comes From the Token

```
{ "tool": "list_invoices",
  "args": { "tenantId": "contoso" } }
```



the model picked
this value

Tenant Comes From the Token

```
{ "tool": "list_invoices",
  "args": { "tenantId": "contoso" } }
```



the model picked this value

```
// from the validated JWT
var tenant = user.FindFirstValue("tid");
```


✓ verified claim, not a parameter

Belt and Suspenders

```
modelBuilder.Entity<Invoice>()
    .HasQueryFilter(i => i.TenantId == _tenant.Id);
```


Belt and Suspenders

```
modelBuilder.Entity<Invoice>()
    .HasQueryFilter(i => i.TenantId == _tenant.Id);
```




Belt and Suspenders

```
modelBuilder.Entity<Invoice>()
    .HasQueryFilter(i => i.TenantId == _tenant.Id);
```




IgnoreQueryFilters() and FromSqlRaw() skip the middle layer


Downstream: As the User



Downstream: As the User



Downstream: As the User




OBO in .NET


```
builder.Services
    .AddMicrosoftIdentityWebApi(cfg)
    .EnableTokenAcquisitionToCallDownstreamApi()
    .AddMicrosoftGraph(cfg.GetSection("Graph"))
    .AddInMemoryTokenCaches();


[McpServerTool, Description("My profile")]
public async Task<string> GetMyProfile(GraphServiceClient graph)
    => (await graph.Me.GetAsync())!.DisplayName;
```

Shape the Tools





Shape the Tools





Shape the Tools





...and validate every ID against the caller

IDOR didn't die. It got a chat interface.

Annotations Are Hints

```
[McpServerTool(ReadOnly = true, Destructive = false)]
```

Annotations Are Hints

```
[McpServerTool(ReadOnly = true, Destructive = false)]
```

a pinky promise, not a lock

LIVE DEMO

Tenant Partitioning



TRAILHEAD
TECHNOLOGY PARTNERS

Production Visibility

Log Every Call

WHO: user AND agent

Log Every Call

WHO: user AND agent

WHAT: tool + arguments

Log Every Call

WHO: user AND agent

WHAT: tool + arguments

DECISION: allowed or denied, and why

Log Every Call

WHO: user AND agent

WHAT: tool + arguments

DECISION: allowed or denied, and why

RESULT: status + size

Log Every Call

WHO: user AND agent

WHAT: tool + arguments

DECISION: allowed or denied, and why

RESULT: status + size

TRACE: correlation id

Show me the deny.

Agents Look Different


```
"oid": "5f2b9c41-…",
"azp": "aebc6443-…"      // which client app
```

Agents Look Different


```
"oid": "5f2b9c41-…",
"azp": "aebc6443-…"      // which client app
```

separate rate limits · separate baselines · separate alerts

One Front Door



One Front Door



Your To-Do List

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward
- [x] Tenant from claims, with RLS underneath

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward
- [x] Tenant from claims, with RLS underneath
- [x] Narrow tools that validate every ID

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward
- [x] Tenant from claims, with RLS underneath
- [x] Narrow tools that validate every ID
- [x] Log the denies

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward
- [x] Tenant from claims, with RLS underneath
- [x] Narrow tools that validate every ID
- [x] Log the denies
- [x] A human approves anything sent out

Before You Ship an MCP Server

- [x] OAuth resource server: retire the API keys
- [x] Validate audience and scope on every request
- [x] Flow the user's identity into every tool
- [x] Exchange tokens downstream, never forward
- [x] Tenant from claims, with RLS underneath
- [x] Narrow tools that validate every ID
- [x] Log the denies
- [x] A human approves anything sent out

MCP has no S in it.
You provide the security.

Thanks! Questions?

Jonathan "J." Tower

Founding Partner

- 13x Microsoft MVP in .NET & AI
- VP of .NET Foundation
- Blue Blazes podcast host

