

Restricting and Sorting Data

Objectives

After completing this lesson, you should be able to do the following:

- Limit the rows that are retrieved by a query
- Sort the rows that are retrieved by a query
- Use ampersand substitution to restrict and sort output at run time


Limiting Rows by Using a Selection

EMPLOYEES

	EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	100	King	AD_PRES	90
2	101	Kochhar	AD_VP	90
3	102	De Haan	AD_VP	90
4	103	Hunold	IT_PROG	60
5	104	Ernst	IT_PROG	60
6	107	Lorentz	IT_PROG	60

...

"retrieve all
employees in
department 90"



	EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	100	King	AD_PRES	90
2	101	Kochhar	AD_VP	90
3	102	De Haan	AD_VP	90

3

Limiting Rows That Are Selected

- Restrict the rows that are returned by using the WHERE clause:

```
SELECT *|{[DISTINCT] column [alias],...}  
FROM table  
[WHERE logical expression(s)];
```

- The WHERE clause follows the FROM clause.

4

Using the WHERE Clause

```
SELECT employee_id, last_name, job_id, department_id
FROM   employees
WHERE  department_id = 90 ;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	100	King	AD_PRES	90
2	101	Kochhar	AD_VP	90
3	102	De Haan	AD_VP	90

5

Character Strings and Dates

- Character strings and date values are enclosed within single quotation marks.
- Character values are case-sensitive and date values are format-sensitive.
- The default date display format is DD-MON-RR.

```
SELECT last_name, job_id, department_id
FROM   employees
WHERE  last_name = 'Whalen' ;
```

LAST_NAME	JOB_ID	DEPARTMENT_ID
1 Whalen	AD_ASST	10

```
SELECT last_name
FROM   employees
WHERE  hire_date = '17-OCT-03' ;
```

LAST_NAME
1 Rajs

6

Comparison Operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to
BETWEEN ...AND...	Between two values (inclusive)
IN(set)	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null value

7

Using Comparison Operators

```
SELECT last_name, salary
FROM employees
WHERE salary <= 3000;
```

	LAST_NAME	SALARY
1	Matos	2600
2	Vargas	2500

8

Range Conditions Using the BETWEEN Operator

Use the BETWEEN operator to display rows based on a range of values:

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500 ;
```

Lower limit

Upper limit

	LAST_NAME	SALARY
1	Rajs	3500
2	Davies	3100
3	Matos	2600
4	Vargas	2500

9

Using the IN Operator

Use the IN operator to test for values in a list:

```
SELECT employee_id, last_name, salary, manager_id
FROM employees
WHERE manager_id IN (100, 101, 201) ;
```

	EMPLOYEE_ID	LAST_NAME	SALARY	MANAGER_ID
1	101	Kochhar	17000	100
2	102	De Haan	17000	100
3	124	Mourgos	5800	100
4	149	Zlotkey	10500	100
5	201	Hartstein	13000	100
6	200	Whalen	4400	101
7	205	Higgins	12008	101
8	202	Fay	6000	201

10

Pattern Matching Using the LIKE Operator

- Use the LIKE operator to perform wildcard searches of valid search string values.
- Search conditions can contain either literal characters or numbers:
 - % denotes zero or more characters.
 - _ denotes one character.

```
SELECT first_name
FROM employees
WHERE first_name LIKE 'S%';
```

	FIRST_NAME
1	Shelley
2	Steven

11

Combining Wildcard Characters

- You can combine the two wildcard characters (% , _) with literal characters for pattern matching:

```
SELECT last_name
FROM employees
WHERE last_name LIKE '_o%';
```

	LAST_NAME
1	Kochhar
2	Lorentz
3	Mourgos

12

Using NULL Conditions

Test for nulls with the IS NULL operator.

```
SELECT last_name, manager_id
FROM   employees
WHERE  manager_id IS NULL ;
```

	LAST_NAME	MANAGER_ID
1 King		(null)

13

Defining Conditions Using Logical Operators

Operator	Meaning
AND	Returns TRUE if <i>both</i> component conditions are true
OR	Returns TRUE if <i>either</i> component condition is true
NOT	Returns TRUE if the condition is false

14

Using the AND Operator

AND requires both the component conditions to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary >= 10000
AND    job_id LIKE '%MAN%' ;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	149	Zlotkey	SA_MAN	10500
2	201	Hartstein	MK_MAN	13000

15

Using the OR Operator

OR requires either component condition to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary >= 10000
OR     job_id LIKE '%MAN%' ;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	100	King	AD_PRES	24000
2	101	Kochhar	AD_VP	17000
3	102	De Haan	AD_VP	17000
4	124	Mourgos	ST_MAN	5800
5	149	Zlotkey	SA_MAN	10500
6	174	Abel	SA_REP	11000
7	201	Hartstein	MK_MAN	13000
8	205	Higgins	AC_MGR	12008

16

Using the NOT Operator

```
SELECT last_name, job_id
FROM employees
WHERE job_id
      NOT IN ( 'IT_PROG', 'ST_CLERK', 'SA_REP' ) ;
```

	LAST_NAME	JOB_ID
1	De Haan	AD_VP
2	Fay	MK_REP
3	Gietz	AC_ACCOUNT
4	Hartstein	MK_MAN
5	Higgins	AC_MGR
6	King	AD_PRES
7	Kochhar	AD_VP
8	Mourgos	ST_MAN
9	Whalen	AD_ASST
10	Zlotkey	SA_MAN

17

Rules of Precedence

Operator	Meaning
1	Arithmetic operators
2	Concatenation operator
3	Comparison conditions
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	Not equal to
7	NOT logical operator
8	AND logical operator
9	OR logical operator

You can use parentheses to override rules of precedence.

18

Rules of Precedence

```
SELECT last_name, department_id, salary
FROM employees
WHERE department_id = 60
OR department_id = 80
AND salary > 10000;
```

1

	LAST_NAME	DEPARTMENT_ID	SALARY
1	Hunold	60	9000
2	Ernst	60	6000
3	Lorentz	60	4200
4	Zlotkey	80	10500
5	Abel	80	11000

```
SELECT last_name, department_id, salary
FROM employees
WHERE (department_id = 60
OR department_id = 80)
AND salary > 10000;
```

2

	LAST_NAME	DEPARTMENT_ID	SALARY
1	Zlotkey	80	10500
2	Abel	80	11000

19

Using the ORDER BY Clause

Sort the retrieved rows with the ORDER BY clause:

- ASC: Ascending order, default
- DESC: Descending order

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date;
```

	LAST_NAME	JOB_ID	DEPARTMENT_ID	HIRE_DATE
1	De Haan	AD_VP		90-13-JAN-01
2	Gietz	AC_ACCOUNT		11-07-JUN-02
3	Higgins	AC_MGR		11-07-JUN-02
4	King	AD_PRES		90-17-JUN-03
5	Whalen	AD_ASST		10-17-SEP-03
6	Rajs	ST_CLERK		50-17-OCT-03

...

20

Sorting

- Sorting in descending order:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY department_id DESC;
```

1

- Sorting by column alias:

```
SELECT employee_id, last_name, salary*12 annsal
FROM employees
ORDER BY annsal;
```

2

21

Sorting

- Sorting by using the column's numeric position:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY 3;
```

3

- Sorting by multiple columns:


```
SELECT last_name, department_id, salary
FROM employees
ORDER BY department_id, salary DESC;
```

4

22

SQL Row Limiting Clause: Example

```
SELECT employee_id, first_name  
FROM employees  
ORDER BY employee_id  
FETCH FIRST 5 ROWS ONLY;
```




Script Output x Query Result x

SQL | All Rows Fetched: 5

EMPLOYEE_ID	FIRST_NAME
1	100 Steven
2	101 Neena
3	102 Lex
4	103 Alexander
5	104 Bruce

23

Substitution Variables



24

Substitution Variables


- Use substitution variables to:
 - Temporarily store values with single-ampersand (&) and double-ampersand (&&) substitution
- Use substitution variables to supplement the following:
 - WHERE conditions
 - ORDER BY clauses
 - Column expressions
 - Table names
 - Entire SELECT statements

25

Using the Single-Ampersand Substitution Variable


Use a variable prefixed with an ampersand (&) to prompt the user for a value:

```
SELECT employee_id, last_name, salary, department_id
FROM   employees
WHERE  employee_id = &employee_num ;
```



26

Using the Single-Ampersand Substitution Variable



A dialog box titled "Enter Substitution Variable" with a close button (X) in the top right corner. It contains a label "EMPLOYEE_NUM:" above a text input field. The input field contains the value "101" and is highlighted with a red rectangular border. Below the input field are two buttons: "OK" and "Cancel". A mouse cursor is pointing at the "OK" button.


EMPLOYEE_ID	LAST_NAME	SALARY	DEPARTMENT_ID
1	101 Kochhar	17000	90

27

Character and Date Values with Substitution Variables

Use single quotation marks for date and character values:

```
SELECT last_name, department_id, salary*12
FROM   employees
WHERE  job_id = '&job_title' ;
```



A dialog box titled "Enter Substitution Variable" with a close button (X) in the top right corner. It contains a label "JOB_TITLE:" above a text input field. The input field contains the value "IT_PROG" and is highlighted with a red rectangular border. Below the input field are two buttons: "OK" and "Cancel". A mouse cursor is pointing at the "OK" button.

	LAST_NAME	DEPARTMENT_ID	SALARY*12
1	Hunold	60	108000
2	Ernst	60	72000
3	Lorentz	60	50400

28

Specifying Column Names, Expressions, and Text

```
SELECT employee_id, last_name, job_id, &column_name  
FROM employees  
WHERE &condition  
ORDER BY &order_column ;
```

Enter Substitution Variable

COLUMN_NAME:
salary

OK

Enter Substitution Variable

CONDITION:
salary>1500

OK Cancel

Enter Substitution Variable

ORDER_COLUMN:
last_name

OK Cancel

29

Using the Double-Ampersand Substitution Variable

Use double ampersand (&&) if you want to reuse the variable value without prompting the user each time:

```
SELECT employee_id, last_name, job_id, &&column_name  
FROM employees  
ORDER BY &column_name ;
```

Enter Substitution Variable

COLUMN_NAME:
department_id

OK Cancel

	EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	200	Whalen	AD_ASST	10
2	201	Hartstein	MK_MAN	20
3	202	Fay	MK_REP	20

...

30

Using the Ampersand Substitution Variable in SQL*Plus

```
oracle@EDRSR19P1:~/Desktop
File Edit View Search Terminal Help
SQL> SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num ; 2 3
Enter value for employee num: 101
```

```
oracle@EDRSR19P1:~/Desktop
File Edit View Search Terminal Help
SQL> SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num ; 2 3
Enter value for employee num: 101
old 3: WHERE employee_id = &employee_num
new 3: WHERE employee_id = 101

EMPLOYEE_ID LAST_NAME          SALARY DEPARTMENT_ID
-----
101 Kochhar          17000          90

SQL>
```

31

Summary

In this lesson, you should have learned how to:

- Limit the rows that are retrieved by a query
- Sort the rows that are retrieved by a query
- Use ampersand substitution to restrict and sort output at run time

32