Where Do Knowledge Graphs Help LLM Agents?

Nineteen Experiments, from Hand-Built Examples to Benchmarks with Thousands of Questions

Dimitar Trajanov
Faculty of Computer Science and Engineering, Ss. Cyril and Methodius University – Skopje
dimitar.trajanov@finki.ukim.mk

Companion report to the 2nd SMASHING Workshop lecture
"LLM-Based Agentic Systems and Knowledge Graphs", October 2026

Abstract

Knowledge graphs are widely proposed as a remedy for the weaknesses of retrieval-augmented LLM agents: multi-hop reasoning, questions about whole collections, facts that change over time, unverifiable query generation and untrusted content. We test these claims in nineteen executable experiments. Ten smaller notebooks (up to 300 questions, `gpt-4o-mini`) illustrate each claim; nine *confidence runs* then re-test them on public benchmarks with 115–4,072 questions each, stronger baselines and paired 95% confidence intervals (`gpt-6-luna` without reasoning, about 160,000 LLM calls, about $29 in total). Graphs give large, reliable gains when the answer depends on *structure*: aggregates over typed records (+51 pp on templated helpdesk questions), whole-collection questions (+19.8 pp of expected content), and multi-hop questions over relational data (+57 to +67 Hits@1 at two and three hops on MetaQA, even with a graph the LLM extracted from text, which scored 11–24 points below the curated graph). Elsewhere gains are small or absent: +4.7 and +11.7 F1 on MuSiQue and 2WikiMultiHopQA; +1.0 and +2.7 points on GraphRAG-Bench with HippoRAG2-style ranking, and losses with a simpler graph retriever; −50 pp on single-fact lookups; no gain on helpdesk questions written without the graph (−8 pp, not reliable). Baselines that encode the same information in simpler form match the graph: document dates match a temporal graph (−0.2 pp), and stating a schema's naming rules in the prompt recovers all but 2–5 points of an ontology checker's +61.5 pp. GraphRAG's global search loses 30 pp on local questions, where its local search nearly matches vector retrieval. These findings agree with recent RAG-versus-GraphRAG comparisons and extend them to agent memory, query checking and guardrails. We conclude that graphs should be adopted per question type, against the strongest cheap baseline; their robust value lies in structure, and rules enforced in code add a guarantee of zero violations rather than a large gain in accuracy.

1 Introduction

The combination of large language model (LLM) agents and knowledge graphs (KGs) is promoted for at least six distinct purposes: (i) answering relational and multi-hop questions by traversal [28, 37]; (ii) answering questions about an entire corpus through community summaries (GraphRAG) [9]; (iii) improving retrieval by graph-based ranking (HippoRAG) [12, 13]; (iv) maintaining long-term, time-aware agent memory [26]; (v) validating LLM-generated graph queries against an ontology [1, 27]; and (vi) enforcing provenance, workflow and plan rules as guardrails [4, 8]. Recent controlled comparisons find that the benefit of graph retrieval depends strongly on the question type and that plain retrieval remains better for single-hop, detail-oriented questions [14, 34, 42]. These studies concentrate on retrieval and question answering; the other roles are usually evaluated in isolation, against plain top-k retrieval, or on small samples.

This report collects the results of nineteen notebooks written as companions to a lecture on agentic systems and knowledge graphs. Notebooks 01–07 are instructional: small, realistic

data sets on which each claim can be observed and inspected. Notebooks 08–10 repeat three comparisons on public benchmarks. Notebooks 11–19 are confidence runs designed to test each claim at scale: every one uses a public benchmark or a templated question set large enough for narrow intervals, adds the strongest cheap baseline we could identify, and archives every LLM request and response.

Contributions.

- One protocol applied to six roles of KGs in agentic systems—retrieval, sensemaking, temporal knowledge, memory, query generation and guardrails—with paired 95% intervals for every headline difference (Sections 5.1–5.6). Prior comparisons cover mainly the first two.
- Baselines that give plain retrieval the same information in simpler form (document dates, the full conversation history, the schema's rules in the prompt, retry on error), which match or nearly match the graph in several cases, and stronger graph methods (HippoRAG2-style ranking, GraphRAG local search) where our first implementation lost (Section 6).
- A decision guide stating for which question types a graph is worth its indexing and per-query cost (Table 7).

2 Related Work

Graph-based retrieval. Surveys organise graph RAG into graph construction, graph retrieval and graph-augmented generation [24, 40, 43]; representative systems include GraphRAG [9], LightRAG [11] and HippoRAG [12, 13]. Several studies compare these systems with plain retrieval under one protocol. Han et al. [14] find that RAG is better on single-hop and detail-oriented questions and GraphRAG on multi-hop questions, and that community-based global search often struggles on question answering. Zhou et al. [42] re-implement graph RAG methods in a unified framework. Xiang et al. [34] build GraphRAG-Bench with medical and novel corpora and four question types and report gains mainly for complex reasoning and summarisation; a different benchmark of the same name [35] uses textbook questions. All GraphRAG-Bench results in this report refer to the benchmark of Xiang et al. [34]. Zhuang et al. [44] report that relation extraction can introduce noise that lowers retrieval quality. Our notebooks 11, 14 and 16 re-test these claims; the rest of the report extends the comparison beyond retrieval.

Agent memory. Zep [26] and Mem0 [6] store conversation facts in a (temporal) graph. Benchmarks for long-term memory include LongMemEval [33], LoCoMo [20] and MemoryAgentBench [17]. Two published results bear directly on our full-history baseline: long-context models lose 30–60% accuracy on LongMemEval-S compared with reading only the evidence sessions [33], whereas on LoCoMo a full-context baseline (72.9) scores above Mem0 with graph memory (68.4) and Zep (66.0) [6]; A-Mem [36] links memory notes without a fixed schema. More generally, Li et al. [19] find that sufficiently capable long-context models outperform RAG on average when the input fits in the context window, at a much higher token cost.

Time-aware knowledge. Temporal question answering over text and knowledge graphs is surveyed by Piryani et al. [25]. HoH [23] measures the harm of outdated passages in retrieval; its questions ask for the current value of a fact, which is the setting of our notebook 12, not questions about the state of the world at a past time.

Queries over knowledge graphs. Sequeda et al. [27] show that answering over a knowledge-graph representation of an enterprise database raises LLM accuracy compared with SQL over the same data, and Allemang and Sequeda [1] add ontology-based query checks with LLM repair. Spider4SPARQL [18] and Spider4SSC [30, 31] translate Spider [38] into SPARQL (and, for Spider4SSC, Cypher).

Guardrails against prompt injection. InjecAgent [39] and AgentDojo [7] benchmark indirect prompt injection in tool-using agents. CaMeL [8] extracts the control and data flow of a task from the trusted user query before untrusted data is read and enforces security policies when tools are called; Beurer-Kellner et al. [4] describe related patterns such as plan-then-execute. Our plan graph is a simplified instance of this idea: it restricts which tools may be called but, unlike CaMeL, does not track data flow.

3 Methods Compared

Vector retrieval (baseline). Texts are embedded with `text-embedding-3-small`; for each question the k most similar texts (k between 3 and 20, stated per experiment) are given to the LLM with a fixed answer prompt. Wherever possible the baseline receives a comparable amount of context to the graph method.

Graph agent. An LLM in a ReAct loop [37] calls read-only tools that look up nodes, follow typed edges, filter and count. Tools cannot modify data.

HippoRAG-style graph retrieval. The LLM extracts subject–relation–object triples (OpenIE) from every passage; entities with embedding similarity ≥ 0.9 are linked by synonym edges; personalised PageRank [15] seeded at the question's entities ranks passages [13].

GraphRAG community summaries. Entities and relations are extracted from every chunk and clustered with Louvain [5], split recursively to at most 25 entities. Each community is summarised in advance; a question is answered map-reduce style over all summaries [9].

Bi-temporal graph memory. Facts extracted from conversations or documents carry validity intervals; a contradicting fact closes the earlier one (`invalid_at`) rather than deleting it [26]. Retrieval returns current facts with dates and source turns.

Ontology-checked queries. A deterministic checker tests each class and property of an LLM-written SPARQL query against the ontology (vocabulary, direction, domain/range, grounding of named entities). Violations are explained to the LLM, which may repair the query up to three times [1].

Graph guardrails. *Provenance filtering* admits content only if its origin in the graph is trusted. A *workflow graph* blocks an action whose prerequisite steps are not complete. A *plan graph* is fixed by the LLM before any untrusted tool output is read; code refuses every tool call outside the plan (a plan-then-execute pattern [4, 8]).

4 Experimental Setup

Data. Table 1 lists the nineteen experiments. Instructional data include a synthetic IT-helpdesk graph (Aura; 23 tickets, 57 comments, 246 typed links), the ServiceNow incident event log (20,769 incidents) [2], 183 hospital-software support tickets, 58 security runbooks with version metadata, and a τ^2-bench telecom workflow [3]. Public benchmarks are MetaQA [41], MuSiQue [29], 2WikiMultiHopQA [16], HoH [23], InjecAgent [39] with the AgentDojo attack template [7], GraphRAG-Bench [34], LongMemEval [33], LoCoMo [20], BenchmarkQED [21] and Spider4SSC [30, 38]. For NB 11 we use the 1,000 development questions per benchmark released with HippoRAG 2 [13]; each benchmark's passages form one shared pool (11,656 paragraphs for MuSiQue, 6,119 for 2WikiMultiHopQA), so every question is answered among the distractors

of all others. For NB 17 we take the full Spider4SSC development split (608 questions over 20 databases), drop the 36 questions of one database whose 45 MB graph is too large for our in-memory SPARQL engine, and drop 9 questions whose gold query fails to execute, leaving 563 questions over 19 graphs. All NB 17 systems receive the full schema, including each graph's namespace, in the prompt. For NB 19 we use the 18,127 WikiMovies articles (first paragraphs) from which MetaQA's knowledge base was built [22], and sample 300 MetaQA test questions per hop (seed 7) whose topic entity is a film with an article, so this sample differs from NB 08's.

Models. Notebooks 01–10 use `gpt-4o-mini`; notebooks 11–19 use `gpt-6-luna` (the API version available in October 2026) with reasoning disabled; results with reasoning enabled, or with other models, may differ. All calls use temperature 0 and seed 7; because API outputs are not guaranteed to be deterministic even with a fixed seed, reproducibility rests on the response cache described below. Confidence runs are executed through the OpenAI Batch API; agent loops run in lock-step, one batch per step. Stages added after review whose batch jobs stalled for hours, including the agent loops of NB 19, were sent through the standard API with identical request bodies.

Scoring. Exact match, F1 or execution accuracy wherever a gold answer can be computed; LLM judges only for open-ended answers, with the benchmark's own judge prompt where one exists and both presentation orders for pairwise comparisons. The judge is the same model as the answering model (`gpt-4o-mini` in 01–10, `gpt-6-luna` in 11–19) and receives answers without method labels (pairwise comparisons as "answer 1" and "answer 2" in both orders). Answers can still differ in style—GraphRAG answers, for example, cite community reports—so the judge may be able to infer the method.

Statistics. Single accuracies carry Wilson intervals [32]; differences between methods on the same questions carry paired bootstrap intervals [10]. A difference is called *reliable* when its 95% interval excludes zero. Intervals are not adjusted for multiple comparisons. As a check, we widened each of the 26 headline intervals in Figure 1 by the Bonferroni factor $z_{0.05/52}/z_{0.025} \approx 1.58$ (normal approximation): 23 keep their classification, while three reliable differences become *borderline*: the +16 pp gain on verified fixes (NB 18), and the −1.5-point loss of the simple graph retriever and the +1.0-point gain of the HippoRAG2-style retriever on GraphRAG-Bench medical (NB 14). Subgroup results in Tables 2–6 should be read with the same caution.

Reproducibility. Every LLM request is cached under a hash of its full body, so each notebook replays its results without API calls when the cache is present. All 159,932 logged requests and responses of the confidence runs (and 945 of small test runs), and the raw input and output files of all 70 batch jobs, are archived with a manifest. Clustering was made independent of Python hash randomisation and verified under two seeds.

5 Results

Figure 1 summarises every headline difference of the confidence runs; the following subsections report each group of experiments.

5.1 Structural and Multi-Hop Questions

Small samples. On the Aura helpdesk (NB 01), vector retrieval and a graph agent were similar on simple lookups (5/5 vs. 4/5), but the agent found the confirmed fix in 11/11 cases against 7/11, and answered 5/6 relational questions against 1/6. On ServiceNow incidents (NB 02), a ReAct agent answered 8 of 10 multi-hop questions against 1 of 10 for top-10 retrieval, at 6.5




Figure 1: Headline differences of the confidence runs (notebook in brackets). Blue circles: reliable gains for the graph method; red squares: reliable losses; grey diamonds: intervals including zero. Units are percentage points of accuracy or Hits@1 (18, 19), of expected content (16) or of answer correctness (14), and F1 points (11). †One subgroup out of four to eight, chosen for illustration; Tables 2–5 list all subgroups, and of the eight GraphRAG-Bench cells only this one favours the simple graph retriever. The helpdesk families and question sets (18), MetaQA hops (19) and the global and local question sets (16) are designed groups, all shown. Rows added after review: 4, 5–7, 14, 18–19 and 26.

Table 1: The nineteen experiments. NB = notebook; "Re-tests" names the instructional notebook whose claim a confidence run repeats at scale.

NB	Claim examined and data	Re-tests	Questions
01	Graph agent vs. vector retrieval on a helpdesk graph (Aura)	–	22
02	ReAct traversal for multi-hop questions (ServiceNow incidents)	–	10
03	LLM graph construction: entity resolution, extraction, validation (hospital tickets)	–	–
04	Bi-temporal retrieval against replaced and conflicting runbooks	–	56
05	Provenance and workflow guardrails (Aura, τ^2-bench telecom)	–	10 + 10 runs
06	GraphRAG for whole-collection questions (hospital tickets)	–	3
07	Ontology-checked SPARQL generation (Aura as RDF)	–	15
08	Multi-hop traversal on MetaQA	–	300
09	HippoRAG-style retrieval on GraphRAG-Bench (medical sample)	–	180
10	Bi-temporal memory on LongMemEval-S (sample)	–	108
11	HippoRAG-style retrieval on MuSiQue and 2WikiMultiHopQA	08	2,000
12	Temporal graph vs. retrieval with and without dates on HoH	04	500
13	Plan-graph gate against indirect prompt injection (InjecAgent)	05	3,162
14	GraphRAG-Bench in full, medical and novel domains	09	4,072
15	Graph memory vs. vector vs. full history (LongMemEval-S, LoCoMo)	10	2,040
16	GraphRAG on BenchmarkQED podcast transcripts, global and local	06	100
17	Ontology checker vs. retry baseline on Spider4SSC	07	563
18	Helpdesk, graph agent vs. vector retrieval: templates, and questions written without the graph	01	156 + 115
19	Graph agent over a curated vs. an LLM-extracted graph on MetaQA	08	900

times the tokens (4,194 vs. 646 per question). On MetaQA (NB 08), Hits@1 was 91% vs. 99% for one hop, 39% vs. 97% for two hops and 36% vs. 80% for three hops, with token ratios of 1.7, 3.0 and 6.6.

At scale. Table 2 reports NB 11. When the graph is extracted from text by the LLM (190,347 triples), HippoRAG-style retrieval improves F1 by +4.7 [+2.1, +7.4] on MuSiQue and +11.7 [+8.6, +14.8] on 2WikiMultiHopQA. The gain is concentrated in compositional questions (+23.8) and in two-hop MuSiQue questions (+7.9); it vanishes at three and four hops and reverses on comparison questions, which name both entities explicitly (−5.0 [−9.3, −0.7]). Retrieval recall explains much of the pattern: the graph raised recall@5 of gold passages from 70.6% to 84.4% on 2Wiki but only from 55.3% to 58.4% on MuSiQue.

NB 19 separates the effect of extraction from that of the benchmark by staying on MetaQA. The LLM extracted facts in MetaQA's nine relations from the 18,127 WikiMovies articles (146,006 triples). It recovered 71% of the curated triples about the sampled topic films: 96–99% of directors, actors and release years, 78% of writers, 90% of genres, but only 7% of tags and no IMDb ratings, which the articles rarely state. The same graph agent then answered 300 questions per hop over the curated and over the extracted graph, against vector retrieval of the ten most similar articles (Table 3). The extracted graph kept most of the advantage: +13.3, +67.0 and +56.7 Hits@1 over vector retrieval at one, two and three hops, with the curated graph a further 11–24 points higher. Vector retrieval fails at two and three hops (9% and 12%) because the answers are attributes of other films, which no article about the topic film contains. The agents used 1,900–2,200 tokens per question against 1,600 for vector retrieval; extraction cost $0.92 for all articles.

NB 18 repeats NB 01 with 156 templated questions whose answers are computed from the graph (Table 4). The structural split holds with tight intervals: the graph agent wins relational questions by +51 pp and verified fixes by +16 pp, but loses lookups by −50 pp, a larger loss than the small sample suggested. Because the gold answers are computed from the same graph the

Table 2: Multi-hop question answering over text (NB 11): token F1, top-5 passages, 1,000 questions per benchmark. Differences with paired 95% bootstrap intervals.

Benchmark	Group	n	Vector	Graph	Graph − vector
MuSiQue	2-hop	518	43.7	51.6	**+7.9** [+4.2, +11.6]
	3-hop	316	36.6	39.4	+2.9 [−2.1, +7.9]
	4-hop	166	24.3	22.6	−1.7 [−6.3, +2.9]
	All	1,000	38.2	43.0	**+4.7** [+2.1, +7.4]
2WikiMultiHopQA	Compositional	413	23.8	47.6	**+23.8** [+19.0, +28.5]
	Inference	108	47.2	62.9	**+15.7** [+7.2, +23.9]
	Bridge comparison	235	61.9	67.6	+5.7 [−2.2, +13.3]
	Comparison	244	89.2	84.2	**−5.0** [−9.3, −0.7]
	All	1,000	51.2	62.9	**+11.7** [+8.6, +14.8]

Table 3: MetaQA with a curated and an LLM-extracted graph (NB 19, 300 questions per hop): Hits@1 with Wilson intervals; differences in points with paired 95% bootstrap intervals. Both graphs are queried by the same agent.

Hops	Vector top-10	Curated graph	Extracted graph	Extracted − vector	Curated − extracted
1	60% [55, 66]	85% [81, 89]	74% [68, 78]	**+13.3** [+8.0, +18.7]	**+11.3** [+7.3, +15.7]
2	9% [6, 13]	100% [99, 100]	76% [71, 80]	**+67.0** [+61.0, +72.3]	**+24.0** [+19.3, +29.0]
3	12% [9, 17]	93% [90, 95]	69% [64, 74]	**+56.7** [+50.3, +62.7]	**+24.0** [+18.7, +29.3]

agent queries, and the templates ask what the agent's tools compute (counts, filters, joins), this design favours the graph agent. We therefore added a second question set written without the graph: an LLM that saw only the 90 texts indexed for vector retrieval wrote 119 questions with answers, of which 115 were confirmed by an independent full-context reading. None of its 58 multi-record questions matches an existing template; they ask for narrative details spread over several tickets rather than for counts. On this set the advantage disappears: graph minus vector is −14 pp [−28, −3] on lookups, −4 [−25, +18] on fixes, −7 [−21, +9] on multi-record questions and −8 [−17, +2] overall. The relational gain therefore holds for questions whose answer is an aggregate over typed records, not for multi-record questions in general. The writer and validator read text, so this set in turn favours text-shaped questions; together the two sets bound the effect from both sides.

5.2 Corpus-Wide Sensemaking and Graph-Based Retrieval

Small samples. On 183 hospital tickets (NB 06), GraphRAG answers were judged more comprehensive in 6 of 6 comparisons, mentioned 10 of 10 hospitals against 5, and cited 43 real ticket IDs against 9, at 10.6 times the tokens per question. On a 180-question sample of GraphRAG-Bench medical (NB 09), no question type showed a reliable difference (largest +2.4 [−4.1, +8.7]); vector top-8 already retrieved 94–99.5% of the gold evidence for non-creative questions.

At scale. With all 4,072 GraphRAG-Bench questions (NB 14, Table 5), vector retrieval is reliably better on the medical domain overall (−1.5 [−2.5, −0.4]) and on fact retrieval in both domains; the only reliable graph gain is complex reasoning over novels (+2.8 [+1.3, +4.4]). The direction agrees with the benchmark paper, which finds graph methods most useful for reasoning and summarisation on the novel corpus, but the size does not: there, the best graph methods exceed RAG with reranking by +10.5 accuracy points on novel complex reasoning (HippoRAG2) and +13.1 on novel summarisation (MS-GraphRAG), whereas we measure +2.8 and +1.3. On the medical corpus the paper's best graph method gains +3.3 on reasoning and

Table 4: Helpdesk questions by family (NB 18): accuracy with Wilson intervals. Top: 156 templated questions with gold answers computed from the graph. Bottom: 115 questions written by an LLM from the ticket texts only and confirmed by an independent reading; all are judged against the written answer.

Family	n	Vector top-8	Graph agent	Graph − vector
Templated questions, gold from the graph				
Single-fact lookup	30	97% [83, 99]	47% [30, 64]	**−50** [−67, −33]
Verified fix	44	73% [58, 84]	89% [76, 95]	**+16** [+2, +30]
Relational (counts, filters)	82	46% [36, 57]	98% [92, 99]	**+51** [+40, +62]
All	156	63% [56, 71]	85% [79, 90]	**+22** [+12, +31]
Questions written from the texts, without the graph				
Single-fact lookup	29	100% [88, 100]	86% [69, 95]	**−14** [−28, −3]
Problem and fix	28	50% [33, 67]	46% [30, 64]	−4 [−25, +18]
Multi-record	58	67% [54, 78]	60% [47, 72]	−7 [−21, +9]
All	115	71% [62, 79]	63% [54, 72]	−8 [−17, +2]

none on summarisation [34]; we measure −1.1 and −1.6. Our graph method receives five chunks plus relations against eight chunks for vector retrieval, and it retrieved less of the gold evidence than vector retrieval in all eight cells, by 6 to 14 points (e.g. medical fact retrieval 92.0% against 97.9%, novel fact retrieval 79.8% against 91.6%).

To test whether these losses reflect the retriever rather than the graph, we added a HippoRAG2-style retriever over the same extracted relations (synonym edges, personalised PageRank seeded by the question's best-matching facts, dense passage scores in the reset vector, top-8 passages; without HippoRAG2's LLM fact filter). Its evidence recall is close to vector retrieval (medical 90–97% against 91–98% for non-creative questions; novel 86–95% against 85–93%), and it is reliably better than vector retrieval in both domains, though by little: +1.0 [+0.1, +1.9] on medical and +2.7 [+1.8, +3.7] on novel (Table 5). Its largest gain is on novel fact retrieval (+3.8), where the simple graph retriever lost most; on novel complex reasoning it gains +1.6, about as much as the simple retriever. The losses of the simple retriever were thus a property of that retriever. A graph-ranked retriever that keeps the passages in context does not lose to vector retrieval, but its gains remain far below the +10 to +13 points reported for the best methods [34]; MS-GraphRAG over all 4,072 questions was not run.

On BenchmarkQED podcast transcripts (NB 16), GraphRAG with 1,185 community reports covered 76.5% of the expected assertions of 50 global questions against 56.7% for vector top-20 (+19.8 [+14.9, +24.6]), and a pairwise judge preferred it for comprehensiveness (91%), diversity (92%) and empowerment (90%), but not for relevance (45%). On 50 local questions about single episodes, the order reverses: 100% against 69.7% (−30.3 [−43.0, −18.7]). GraphRAG's local search mode, which we added after review, builds one context from the entities that match the question, their relations, the reports of their communities and the source chunks linked to them (GraphRAG's default shares, about 8,600 prompt tokens against 10,700 for vector retrieval). On the local questions it recovered most of the loss: 95.7%, −4.3 [−10.3, 0.0] against vector retrieval and +26.0 [+14.0, +39.0] against global search. On the global questions it was the worst of the three (41.5%; −35.0 [−39.9, −30.1] against global search). The loss on local questions is therefore a loss of the wrong search mode; matched to the question, GraphRAG's two modes approach (local) or beat (global) vector retrieval, but neither beats it on local questions. Each global-search answer required 57 map calls (about 337,000 tokens) against one call for vector retrieval and for local search.

5.3 Time-Aware Knowledge and Long-Term Memory

Small samples. With 58 security runbooks (NB 04), filtering by validity before ranking raised correct answers on questions about a replaced runbook from 5/8 to 7/8, removed the replaced

Table 5: GraphRAG-Bench in full (NB 14): answer correctness (×100). Vector: top-8 chunks. Graph: top-5 chunks plus relations among top entities. HippoRAG2-style (added after review): top-8 chunks ranked by personalised PageRank over the same extracted relations.

Domain	Question type	n	Vector	Graph	HippoRAG2	Graph − vector	HippoRAG2 − vector
Medical	Fact retrieval	1,098	64.9	63.3	66.0	**−1.6** [−3.2, −0.0]	+1.1 [−0.3, +2.4]
	Complex reasoning	509	55.0	53.8	55.9	−1.1 [−3.2, +0.9]	+1.0 [−0.7, +2.7]
	Contextual summarise	289	57.6	56.0	58.6	−1.6 [−4.0, +0.8]	+1.0 [−1.0, +3.1]
	Creative generation	166	45.5	43.6	46.7	−1.9 [−4.1, +0.3]	+1.2 [−0.9, +3.4]
	All	2,062	59.9	58.4	60.9	**−1.5** [−2.5, −0.4]	**+1.0** [+0.1, +1.9]
Novel	Fact retrieval	971	58.6	54.7	62.4	**−3.9** [−6.0, −1.9]	**+3.8** [+2.2, +5.5]
	Complex reasoning	610	45.8	48.7	47.5	**+2.8** [+1.3, +4.4]	**+1.6** [+0.2, +3.1]
	Contextual summarise	362	51.4	52.7	53.4	+1.3 [−0.9, +3.4]	+2.0 [−0.2, +4.0]
	Creative generation	67	30.3	32.5	31.5	+2.1 [−1.4, +5.5]	+1.1 [−2.7, +4.9]
	All	2,010	52.5	51.7	55.2	−0.7 [−1.9, +0.5]	**+2.7** [+1.8, +3.7]

runbook from the retrieved context (88% → 0%), and reported both owners of a conflicting procedure in 3/3 cases against 1/3; ordinary questions were unaffected (96% for both). On 108 LongMemEval questions (NB 10), graph memory scored 83% [75, 89] against 77% [68, 84], gaining on multi-session (69% → 88%) and preference questions (19% → 50%).

Outdated facts at scale. On 500 HoH questions over 6,550 dated Wikipedia passages (NB 12), plain retrieval gave the current value for 63% of questions and an outdated value for 17%: an outdated near-duplicate was in the top five for 99.2% of questions. The temporal graph reached 90% (+27.0 [+22.8, +31.2]). However, plain retrieval that merely labels each passage with its snapshot date and asks for the newest value also reached 90%; the difference between graph and dated retrieval is −0.2 [−2.4, +2.0].

Memory at scale. NB 15 adds a full-history baseline for every question (Table 6). On LongMemEval-S, where each history is about 104,000 tokens, graph memory leads (79%) but its advantage over vector memory is not reliable (+3.4 [−0.8, +7.4]); it reliably beats the full history (+7.8 [+3.0, +12.6]). It gains on multi-session (+16 pp) and temporal reasoning (+12 pp) and loses heavily on recalling what the assistant said (52% against 91% for vector and 100% for full history). On LoCoMo, with histories of about 21,000 tokens, the full history is best (79%), graph memory second (73%) and vector memory third (67%); all pairwise differences are reliable. Both patterns match published results: long histories degrade long-context reading on LongMemEval [33], and a full-context baseline beats graph memory on LoCoMo [6].

5.4 Building Graphs with LLMs

NB 03 examined where cost and error arise when an LLM builds a graph from 183 hospital-software tickets. A cascade of exact matching, embedding similarity, LLM adjudication and human review merged 62 spellings of module names into 45 modules with 45 LLM calls, instead of 1,891 pairwise calls; one conflict (EHR vs. EMR) required a human decision. Free extraction produced 19 issue labels, later merged into 6, whereas a fixed label list forced 24 of 29 tickets into "Other". All 44 extracted facts passed a shape check, yet 3 were not supported by the text they cited. The confidence runs confirm that extraction dominates the cost of graph methods: the graph index of NB 11 required 17,775 LLM calls ($2.21) against $0.19 for answering all 4,000 questions with both methods.

Table 6: Agent memory (NB 15): accuracy with Wilson intervals and answer-prompt tokens per question.

Benchmark	Question type	n	Vector top-10	Graph memory	Full history
LongMemEval-S	Single-session user	64	95%	**98%**	88%
	Single-session assistant	56	91%	52%	**100%**
	Preference	30	**73%**	70%	47%
	Multi-session	121	60%	**76%**	57%
	Knowledge update	72	88%	**94%**	88%
	Temporal reasoning	127	61%	**73%**	53%
	Abstention	30	**97%**	90%	**97%**
	All (tokens/question)	500	75% [71, 79] (3.2k)	**79%** [75, 82] (2.1k)	71% [67, 75] (104k)
LoCoMo	Single-hop	841	77%	81%	**90%**
	Multi-hop	282	42%	55%	**61%**
	Temporal	321	69%	**79%**	75%
	Open-domain	96	42%	36%	**43%**
	All (tokens/question)	1,540	67% [64, 69] (0.6k)	73% [71, 75] (1.4k)	**79%** [77, 81] (20.7k)

5.5 Governed Query Generation

On 15 questions over the Aura RDF graph (NB 07), ontology checks with up to three repairs raised accuracy from 3/15 to 10/15 and converted one wrong answer into "unknown"; four queries passed every check yet were wrong.

On Spider4SSC (NB 17; 563 questions over 19 RDF graphs), one-shot generation was correct for 16.7% [14, 20], a baseline that retries on errors or empty results for 22.4% [19, 26], and the ontology checker for 83.8% [81, 87] (checker − retry: +61.5 [+57.0, +65.7]). Of the checker's 1,374 findings, 1,360 were vocabulary violations: Spider4SSC places every table in its own namespace (`singer:age`, not `:age`), a convention the model rarely followed unaided. Ninety-one queries (16.2%) passed every check and still returned wrong rows. The direction agrees with Allemang and Sequeda [1], where ontology checks with LLM repair raised accuracy from 54% (knowledge graph alone [27]) to 72.55%, with a further 8% of questions answered "unknown". Because almost all of our checker's findings concern one naming convention, we added (after review) a baseline whose prompt states the conventions the checker enforces, with no checker. Single-shot, it reached 78.9% [75, 82] (+62.2 [+57.7, +66.4] over one-shot); with the same retry-on-error loop as the retry baseline, 81.9% [79, 85]. The checker remains reliably better than the single-shot rule prompt (+5.0 [+2.5, +7.6]) but not than the rule prompt with retry (+2.0 [−0.5, +4.4]). Almost all of the +61.5 is thus the information the checker supplies, not the checking itself. What the checker adds is a guarantee: none of its final queries violates the vocabulary, against 21 (single-shot) and 12 (with retry) for the rule prompt and about 450 without it.

5.6 Guardrails

Small samples. In NB 05, five poisoned "fix" comments were planted in the Aura graph. Vector retrieval retrieved one for every question and the answer repeated the attack in 9/10 cases; provenance filtering admitted none and rejected none of the 12 genuine fixes. On a telecom workflow, an agent without a guardrail executed 19 actions before their prerequisites across 5 runs; a workflow-graph gate blocked 17 premature calls, reduced violations to 0, and every issue was still resolved.

At scale. On 3,162 InjecAgent cases at three attack strengths (NB 13), the newer model resisted almost all attacks on its own: 13 succeeded without defence (0.4% [0.2, 0.7]), 12 of them base-strength data-stealing attacks, and none with the stronger templates including AgentDojo's. A prompt rule reduced successes to 1; the plan-graph gate to 0 (0.0% [0.0, 0.1]). The gate's price

was that 0.2% of legitimate tasks lacked their own tool in the plan. With only 13 successful attacks to remove, this run cannot distinguish the gate from the prompt rule; it shows that the benchmark's attacks no longer work on this model, not that the gate is necessary. A stronger test requires adaptive attacks such as those in AgentDojo [7].

6 Discussion: What Graphs Improve, and What They Do Not

Table 7 sets each claim's small-sample result against its confidence run. Four mechanisms account for nearly every outcome.

1. Graphs help when the answer is a function of many records. Counting, filtering and joining (+51 pp in NB 18), whole-collection questions (+19.8 pp in NB 16) and compositional chains whose intermediate entity is not named in the question (+23.8 F1 in NB 11) all require information that no small set of similar texts contains, and so do two- and three-hop MetaQA questions (+67.0 and +56.7 Hits@1 with an extracted graph in NB 19). Similarity search cannot retrieve what the question does not resemble; explicit links and pre-computed summaries can. The condition is narrower than "many records": the answer must be an aggregate over typed fields that the graph exposes. Multi-record questions written from the texts without the graph, which ask for narrative details spread over several tickets, showed no graph advantage (−7 [−21, +9] in NB 18).

2. Graphs do not help when similarity already finds the evidence. On single-fact lookups and local questions a single passage holds the answer, and on GraphRAG-Bench vector top-8 already retrieved 85–98% of the gold evidence for non-creative questions. A graph method that replaces passages with extracted structure then adds indirection—a tool to choose, an extraction step that may lose detail, fewer passages in context—and loses: −50 pp on helpdesk lookups, −30.3 pp on local podcast questions answered by global search, −1.5 to −3.9 points on GraphRAG-Bench fact retrieval with the simple graph retriever. Summaries and extracted facts are lossy: graph memory forgot what the assistant had said (−39 pp against vector memory). Methods that use the graph only to *rank* passages and keep the passages in context avoid most of this loss—the HippoRAG2-style retriever gained +1.0 and +2.7 points on GraphRAG-Bench, and GraphRAG's local search came within −4.3 pp of vector retrieval on local questions—but they too gain little where vector retrieval already finds the evidence.

3. A cheap baseline that encodes the same information often matches the graph. Showing dates matched the temporal graph on HoH (−0.2 pp); giving the full history beat graph memory on LoCoMo (−5.5 pp); stating the naming rules in the prompt recovered all but 2–5 points of the ontology checker's +61.5; a modern model's own resistance removed 99.6% of injection attempts before any guardrail. Claims established against plain top-k retrieval should be re-tested against the strongest cheap alternative.

4. Enforcement in code adds a guarantee, not a large gain. Rules checked in code—ontology checks, provenance filters (9/10 → 0/10) and workflow gates (19 → 0 violations), the latter two from small instructional samples without a confidence run, and plan graphs (13 → 0 of 3,162, near the model's own floor)—drove violations to zero, because they do not depend on the model being persuaded. Their accuracy gain over a prompt that states the same rules is small: +5.0 pp single-shot and +2.0 pp (not reliable) with retry on Spider4SSC, and the prompt rule alone reduced injection successes from 13 to 1. The value of enforcement is that residual violations (12–21 queries; 1 attack) become zero, which matters where a single violation is costly. This agrees with the design argument behind CaMeL [8]; our evidence for the plan graph itself is weak because the attacks rarely succeeded without it. The price is small but real: 0.2% of tasks

Table 7: Each claim at small scale and at scale, with a verdict. Small-sample results (3–300 questions, `gpt-4o-mini`) are illustrative; verdicts rest on the confidence runs. Notebooks 02 and 03 have no confidence run (02 is covered by the multi-hop row through 08 and 11; 03 measures construction cost, not a claim).

Claim	Small sample (01–10)	Confidence run (11–19)	Verdict
Graphs help multi-hop questions	MetaQA 2-hop 39% → 97% (08)	MetaQA, extracted graph: +13 to +67 Hits@1, 11–24 below curated (19); text benchmarks: F1 +4.7 / +11.7, none at 3–4 hops (11)	Holds on relational data; small on text benchmarks
Validity data prevents stale answers	5/8 → 7/8 (04)	63% → 90%, but dates alone also 90% (12)	Dates do the work
Code-enforced guardrails stop attacks	9/10 → 0/10 (05)	13 → 0 of 3,162; model itself resists (13)	Untestable at floor
Graph RAG wins reasoning and summaries	No reliable difference (09)	Simple graph retriever not better in 7 of 8 cells; HippoRAG2-style +1.0 / +2.7, mostly on facts (14)	Small gain, not specific to reasoning
Graph memory beats vector memory	77% → 83% (10)	75% → 79% (n.s.); full history best on LoCoMo (15)	Depends on history length
Summaries answer whole-collection questions	6 of 6 judgements (06)	+19.8 pp expected content; local questions: global search −30.3 pp, local search −4.3 pp (16)	Holds for global questions, with the matching mode
Ontology checks repair queries	3/15 → 10/15 (07)	22% → 84% vs. retry; rules in prompt 79–82% (17)	Mostly the rules' information
Graphs win structure, not lookups	Relational 1/6 → 5/6 (01)	Templates: relational +51 pp, lookups −50 pp; questions written without the graph: −8 pp (n.s.) (18)	Holds for aggregates only

blocked by an incomplete plan, and queries that pass every check while answering a different question.

Hand-built vs. extracted graphs. On MetaQA, replacing the curated graph with one the LLM extracted from the source articles cost 11–24 Hits@1 points but kept a gain of 13–67 points over vector retrieval (NB 19). The loss grows from one hop (11 points) to two and three hops (24), consistent with extraction errors that compound over hops [44]. The much smaller gains on MuSiQue and 2WikiMultiHopQA (NB 11) therefore reflect those benchmarks more than extraction: MetaQA's multi-hop answers are relational by construction and absent from any single article, whereas many MuSiQue and 2Wiki questions can be answered from passages that resemble the question.

Cost. Graph methods consumed 1.7–10.6 times the tokens per question in the instructional runs, and up to 57 LLM calls per question for GraphRAG; extraction dominated indexing cost in every confidence run. The cost is justified only for the question types on which Table 7 records a gain that holds at scale.

Decision guide. Use a graph (traversal agent, generated query or pre-computed aggregate) for counting, filtering and compositional questions over typed records; community summaries (global search) for questions about a whole collection; graph-based ranking that keeps passages in context if a graph is used for retrieval at all. For generated queries over schemas with conventions, state the conventions in the prompt first and add deterministic checks where a residual error rate of a few percent is unacceptable; use code-level gates for permissions and workflows. Use strong vector retrieval for lookups, local questions and narrative questions. For questions about the current value of a changing fact, show document dates before building a temporal graph; questions about the state at a past time were not tested. Give the full history before building a memory layer when histories are short (about 20,000 tokens on LoCoMo); at about 100,000 tokens (LongMemEval) graph memory beat the full history. Route questions by type rather than choosing one architecture.

7 Limitations

- **Two models.** Notebooks 01–10 and 11–19 use different models and are not strictly comparable; injection resistance in particular is a property of the model version.
- **One implementation per method.** A negative result rules out our HippoRAG-style retrieval, GraphRAG configuration or memory design, not every graph method.
- **LLM judges.** Open-ended answers (NB 01, 04, 06, 09, 10, 12, 14–16, 18) are judged by the same model that answers; absolute scores are not comparable with papers that use other judges, and self-preference cannot be excluded.
- **Context budgets.** Methods receive comparable but not identical context (e.g. five chunks plus relations against eight chunks in NB 14); some differences may reflect the amount of source text.
- **Missing methods.** NB 14 does not run MS-GraphRAG; our HippoRAG2-style retriever omits HippoRAG2's LLM fact filter.
- **Question sets in NB 18.** The templated questions favour the graph agent (gold computed from the graph); the questions written from the texts favour text retrieval (writer and validator read text, and some "fix" questions concern tickets without a recorded fix). Neither set was written by helpdesk staff.
- **Post-review runs.** The baselines and methods added after review (NB 14, 16, 17, 18 and 19) were run later than the original confidence runs; where the Batch queue stalled, remaining requests were sent through the standard API with the same request bodies.
- **Guardrails without scale.** The provenance and workflow results (NB 05) rest on 10 questions and 5 runs; only the plan graph has a confidence run.
- **Multiple comparisons.** Intervals are unadjusted; two headline differences are borderline after a Bonferroni check (Section 4).
- **Benchmark design.** MetaQA contains only graph facts; Spider4SSC's per-table namespaces favour a schema checker; InjecAgent's fixed attacks rarely succeed against the current model.
- **Instructional samples.** In 01–07, only the direction of effects is informative; differences of one question are within run-to-run variation.
- **Licences.** LoCoMo (CC BY-NC 4.0) and BenchmarkQED (Microsoft Research License) restrict use to non-commercial research.

8 Conclusion

Across nineteen experiments, knowledge graphs improved LLM agents where answers depend on structure—aggregates over typed records, chains through other entities' attributes, the scope of a whole collection—and rules enforced in code removed the residual violations that a prompt leaves. They did not improve, and often hurt, single-fact lookup, local and narrative questions,

and benchmarks where a strong vector baseline already retrieves the evidence. A graph extracted by the LLM kept most of a curated graph's advantage on relational questions, at a cost of 11–24 points; several gains disappeared once the baseline was given the same information in simpler form, in line with recent controlled comparisons of RAG and GraphRAG [14, 34]. The practical consequence is to evaluate per question type against the strongest cheap baseline, to report cost next to accuracy, and to treat the graph as a source of structure and enforcement rather than as a general improvement to retrieval.

Availability

The notebooks, with their saved outputs, the shared batch helper and the source of this report are at `https://github.com/trajanov/graphs-for-llm-agents`. The response caches with which each notebook replays its results without API access (`SMASH_MODE=replay`), the archive of 159,932 LLM requests and responses, and the benchmark data (about 6 GB, partly under licences that restrict redistribution) are not in the repository; the benchmarks are public, and the caches and archive are available from the author on request. The original confidence runs cost about $24.7: $20.85 for 127,094 Batch requests, $1.07 for test runs and $2.81 for embeddings. Their Batch requests exceed the 119,808 calls they archived by 7,286: a partial re-run of NB 16 after a fix (7,172 requests), 112 further NB 16 requests whose responses were replaced, and 2 smoke tests; the archive keeps the final response for each distinct request. The runs added after review (NB 14 and 16–19; 40,124 calls) cost about $3.9, partly at the standard price because four stalled batch jobs were cancelled and their remaining requests sent synchronously.

A Cost of the Confidence Runs

NB	Benchmark	Original	After review
11	MuSiQue + 2WikiMultiHopQA	2.52	–
12	HoH	0.18	–
13	InjecAgent	0.71	–
14	GraphRAG-Bench (both domains)	3.34	1.99
15	LongMemEval-S + LoCoMo (incl. $2.59 embeddings)	12.12	–
16	BenchmarkQED podcasts (incl. one re-run)	4.70	0.08
17	Spider4SSC	0.10	0.03
18	Aura helpdesk	0.05	0.22
19	MetaQA with WikiMovies articles	–	1.53

Table 8: Cost per confidence run in USD (`gpt-6-luna`; Batch API at $0.05/$0.25 per million input/output tokens, standard API at twice that price for stages sent synchronously).

References

[1] Dean Allemang and Juan Sequeda. Increasing the LLM accuracy for question answering: Ontologies to the rescue! *arXiv preprint arXiv:2405.11706*, 2024.

[2] Claudio Amaral, Marcelo Fantinato, and Sarajane Peres. Incident management process enriched event log. UCI Machine Learning Repository, `https://archive.ics.uci.edu/dataset/498`, 2018.

[3] Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2-bench: Evaluating conversational agents in a dual-control environment. *arXiv preprint arXiv:2506.07982*, 2025.

[4] Luca Beurer-Kellner, Beat Buesser, Ana-Maria Creţu, Edoardo Debenedetti, Daniel Dobos, Daniel Fabian, Marc Fischer, David Froelicher, Kathrin Grosse, Daniel Naeff, Ezinwanne Ozoani, Andrew Paverd, Florian Tramèr, and Václav Volhejn. Design patterns for securing LLM agents against prompt injections. *arXiv preprint arXiv:2506.08837*, 2025.

[5] Vincent D. Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10):P10008, 2008.

[6] Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready AI agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*, 2025.

[7] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2024.

[8] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. In *IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, 2026.

[9] Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, and Jonathan Larson. From local to global: A graph RAG approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*, 2024.

[10] Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall, 1993.

[11] Zirui Guo, Lianghao Xia, Yanhua Yu, Tu Ao, and Chao Huang. LightRAG: Simple and fast retrieval-augmented generation. *arXiv preprint arXiv:2410.05779*, 2024.

[12] Bernal Jiménez Gutiérrez, Yiheng Shu, Yu Gu, Michihiro Yasunaga, and Yu Su. HippoRAG: Neurobiologically inspired long-term memory for large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[13] Bernal Jiménez Gutiérrez, Yiheng Shu, Weijian Qi, Sizhe Zhou, and Yu Su. From RAG to memory: Non-parametric continual learning for large language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, 2025.

[14] Haoyu Han, Li Ma, Yu Wang, Harry Shomer, Yongjia Lei, Zhisheng Qi, Kai Guo, Zhigang Hua, Bo Long, Hui Liu, Charu C. Aggarwal, and Jiliang Tang. RAG vs. GraphRAG: A systematic evaluation and key insights. In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2026.

[15] Taher H. Haveliwala. Topic-sensitive PageRank. In *Proceedings of the 11th International World Wide Web Conference (WWW)*, 2002.

[16] Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics (COLING)*, 2020.

[17] Yuanzhe Hu, Yu Wang, and Julian McAuley. Evaluating memory in LLM agents via incremental multi-turn interactions. In *International Conference on Learning Representations (ICLR)*, 2026.

[18] Catherine Kosten, Philippe Cudré-Mauroux, and Kurt Stockinger. Spider4SPARQL: A complex benchmark for evaluating knowledge graph question answering systems. In *2023 IEEE International Conference on Big Data (BigData)*, 2023.

[19] Zhuowan Li, Cheng Li, Mingyang Zhang, Qiaozhu Mei, and Michael Bendersky. Retrieval augmented generation or long-context LLMs? A comprehensive study and hybrid approach. *arXiv preprint arXiv:2407.16833*, 2024.

[20] Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.

[21] Microsoft Research. BenchmarkQED: Automated benchmarking of retrieval-augmented generation systems. Microsoft Research Blog and `https://github.com/microsoft/benchmark-qed`, 2025.

[22] Alexander Miller, Adam Fisch, Jesse Dodge, Amir-Hossein Karimi, Antoine Bordes, and Jason Weston. Key-value memory networks for directly reading documents. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1400–1409, 2016. doi: 10.18653/v1/D16-1147.

[23] Jie Ouyang, Tingyue Pan, Mingyue Cheng, Ruiran Yan, Yucong Luo, Jiaying Lin, and Qi Liu. HoH: A dynamic benchmark for evaluating the impact of outdated information on retrieval-augmented generation. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2025.

[24] Boci Peng, Yun Zhu, Yongchao Liu, Xiaohe Bo, Haizhou Shi, Chuntao Hong, Yan Zhang, and Siliang Tang. Graph retrieval-augmented generation: A survey. *arXiv preprint arXiv:2408.08921*, 2024.

[25] Bhawna Piryani, Abdelrahman Abdallah, Jamshid Mozafari, Avishek Anand, and Adam Jatowt. It's high time: A survey of temporal question answering. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2026.

[26] Preston Rasmussen, Pavlo Paliychuk, Travis Beauvais, Jack Ryan, and Daniel Chalef. Zep: A temporal knowledge graph architecture for agent memory. *arXiv preprint arXiv:2501.13956*, 2025.

[27] Juan Sequeda, Dean Allemang, and Bryon Jacob. A benchmark to understand the role of knowledge graphs on large language model's accuracy for question answering on enterprise SQL databases. In *Proceedings of the 7th Joint Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA)*, 2024.

[28] Jiashuo Sun, Chengjin Xu, Lumingyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Lionel M. Ni, Heung-Yeung Shum, and Jian Guo. Think-on-graph: Deep and responsible reasoning of large language model on knowledge graph. In *International Conference on Learning Representations (ICLR)*, 2024.

[29] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022.

[30] Martin Vejvar and Yasutaka Fujimoto. Spider4SSC & S2CLite: A text-to-multi-query-language dataset using lightweight ontology-agnostic SPARQL to Cypher parser. *arXiv preprint arXiv:2511.09354*, 2025. Dataset: Mendeley Data, `https://data.mendeley.com/datasets/4dnvv92trn`.

[31] Martin Vejvar and Yasutaka Fujimoto. Are we too focused on single query language? Investigating text-to-SQL/SPARQL/Cypher task complexity via fine-tuning. *Neurocomputing*, 697:134202, 2026.

[32] Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927.

[33] Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. LongMemEval: Benchmarking chat assistants on long-term interactive memory. In *International Conference on Learning Representations (ICLR)*, 2025.

[34] Zhishang Xiang, Chuanjie Wu, Qinggang Zhang, Shengyuan Chen, Zijin Hong, Xiao Huang, and Jinsong Su. When to use graphs in RAG: A comprehensive analysis for graph retrieval-augmented generation. In *International Conference on Learning Representations (ICLR)*, 2026.

[35] Yilin Xiao, Junnan Dong, Chuang Zhou, Su Dong, Qianwen Zhang, Di Yin, Xing Sun, and Xiao Huang. GraphRAG-Bench: Challenging domain-specific reasoning for evaluating graph retrieval-augmented generation. *arXiv preprint arXiv:2506.02404*, 2025.

[36] Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-Mem: Agentic memory for LLM agents. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

[37] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

[38] Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

[39] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024.

[40] Qinggang Zhang, Shengyuan Chen, Yuanchen Bei, Zheng Yuan, Huachi Zhou, Zijin Hong, Hao Chen, Yilin Xiao, Chuang Zhou, Junnan Dong, Yi Chang, and Xiao Huang. A survey of graph retrieval-augmented generation for customized large language models. *arXiv preprint arXiv:2501.13958*, 2025.

[41] Yuyu Zhang, Hanjun Dai, Zornitsa Kozareva, Alexander J. Smola, and Le Song. Variational reasoning for question answering with knowledge graph. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2018.

[42] Yingli Zhou, Yaodong Su, Youran Sun, Shu Wang, Taotao Wang, Runyuan He, Yongwei Zhang, Sicong Liang, Xilin Liu, Yuchi Ma, and Yixiang Fang. In-depth analysis of graph-based RAG in a unified framework. *arXiv preprint arXiv:2503.04338*, 2025.

[43] Zulun Zhu, Tiancheng Huang, Kai Wang, Junda Ye, Xinghe Chen, and Siqiang Luo. Graph-based approaches and functionalities in retrieval-augmented generation: A comprehensive survey. *ACM Computing Surveys*, 2026.

[44] Luyao Zhuang, Shengyuan Chen, Yilin Xiao, Huachi Zhou, Yujing Zhang, Hao Chen, Qinggang Zhang, and Xiao Huang. LinearRAG: Linear graph retrieval augmented generation on large-scale corpora. In *International Conference on Learning Representations (ICLR)*, 2026.