



Industralight VTN-D is a Twin Diffused Polycarbonate LED Batten Fixture

Industralight VTN-D is a twin-diffused integrated LED batten fixture that is constructed from fire-resistant polycarbonate body and diffuser. VTN-D fixtures are an ideal replacement for existing fluorescent diffused light fittings and they are best suited for modern commercial environments including offices, storerooms, workshops, garages, schools, work spaces, retail showrooms etc.

LIGHTING DESIGNS & SIMULATIONS

Industralight can provide independent LUX calculations and 3D lighting simulations for your project incorporating this product. Please contact our office for more information on design services.

ELECTRICAL PARAMETERS

Driver Input Voltage:	100-240VAC
Max Power Consumption:	20/24/30/40/48/60/80W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industralight SMD2835 LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08
IP Protection Rating:	IP20
Nominal Fixture Lengths:	Various lengths (585 to 2372mm)
Construction Material:	Fire Resistant Toughened Polycarbonate

CONFIGURATION OPTIONS

Twin-surface mounted LED batten
2HR emergency lighting versions available
24VDC version available by special request

PHOTOMETRIC INFORMATION

Total Luminous Flux	4403 Lumens
CCT Colour Temperatures:	3000K/4000K/5000K/6500K
Colour Rendering Index (CRI):	→90
Beam Angle/ Viewing Angle	120°

Lifetime L70:	→ 50,000hr
TM21 LED Data:	→ 90% at 6000 hr
UGR Glare Rating:	UGR19
Macaddam Shift (DCM)	Within 3-Step
Series Model Number:	VTN-D Twin-Diffused LED Batten
Specify Colour Temp:	3000K/4000K/5000K/6500K
Specify Nominal Fixture Length:	585/758/908/1192/1498/1798/2372mm
Specify Wattage:	10W/12W/15W/20W/24W
Emergency Lighting Version:	2HR Emergency Optional
Warranty Information:	36 Months Standard

