



BrightLearn
AI & DATA SKILLS

STUDENT EXERCISE · UNION &
UNION ALL

UNION & UNION ALL Exercise

Master combining result sets with UNION and UNION ALL.
Ten questions, ten unique table pairs from a banking
dataset — write the SQL, know the difference.

TOPIC

UNION & UNION ALL

QUESTIONS

10 + 3 bonus

LEVEL

Beginner

INCLUDES

20 tables · Expected output



00

Welcome & Quick Reference

Ten questions. Twenty tables. One goal: become fluent in the difference between UNION and UNION ALL. Every question shows you two tables from a banking dataset, gives you the task, and leaves you a box to write your SQL.

DEFINITION

The Exercise Domain

All twenty tables come from a single fictional **African retail bank called NexBank**. You'll combine account holders, transactions, staff, product lists, complaints, and more — alternating between UNION and UNION ALL so the difference becomes automatic.

THE TWO OPERATORS — KNOW THESE COLD

UNION

- Combines results from both SELECT statements
- Removes duplicate rows automatically
- Slightly slower — extra deduplication step
- Use for: unique lists, master tables
- Think: DISTINCT result set

UNION ALL

- Combines results from both SELECT statements
- Keeps ALL rows — including duplicates
- Faster — skips the deduplication step
- Use for: audit logs, ledgers, full history
- Think: append rows, no filtering

★ THE THREE RULES — BREAK ANY OF THESE AND YOUR QUERY FAILS

- **Both SELECT statements must return the same number of columns** — you cannot UNION a 2-column query with a 3-column query.
- **Matching columns must have compatible data types** — you cannot combine a text column with a number column in the same position.
- **Column names come from the first SELECT** — alias your columns in the first query if you want specific output names.

SYNTAX REFERENCE



```
-- UNION: removes duplicates
SELECT column1, column2 FROM table_A
UNION
SELECT column1, column2 FROM table_B;

-- UNION ALL: keeps every row
SELECT column1, column2 FROM table_A
UNION ALL
SELECT column1, column2 FROM table_B;
```

★ HOW TO WORK THROUGH THIS EXERCISE

Read both tables carefully. Read the task. Decide which operator the task requires. Write your SQL in the answer box. Run it in your SQL environment (PostgreSQL, SQLite, MySQL, SQL Server, or BigQuery all work). Compare your output to the expected columns. Repeat until all ten are done — then answer the three bonus questions at the end.



01

Questions 01 – 05 (UNION)

The next five questions all use UNION. Each pair of tables contains some overlapping rows. Your job is to return one unique combined list — no duplicates allowed.

Table:
branch_sandton_accounts

account_id	account_holder
A001	Nomvula Dlamini
A002	David Mokoena
A003	Lerato Sithole
A004	Peter Nkosi

Table:
branch_rosebank_accounts

account_id	account_holder
A003	Lerato Sithole
A004	Peter Nkosi
A005	Zanele Khumalo
A006	Thabo Motha

QUESTION 01 • USE UNION

Combine the account holders from both branches into one unique list. Each person should appear only once, even if they hold accounts at both branches.

EXPECTED COLUMNS

account_id, account_holder, city

WRITE YOUR SQL HERE

| account_id | account_holder

| A001 Nomvula Dlamini
| A002 David Mokoena
| A003 Lerato Sithole
| A004 Peter Nkosi
| A005 Zanele Khumalo
| A006 Thabo Motha

```
SELECT account_id,  
account_holder  
FROM branch_sandton_accounts
```

UNION

```
SELECT account_id,  
account_holder  
FROM  
branch_rosebank_accounts;
```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: savings_products

Table: current_products



product_code	product_name	product_code	product_name
SV01	Basic Savings	CR01	Standard Current
SV02	Premium Savings	CR02	Gold Current
SV03	Youth Savings	SV03	Youth Savings
SV04	Business Savings	CR03	Business Current

QUESTION 02 · USE UNION

NexBank offers two product lists — one for savings accounts and one for current accounts. Build a unique product catalogue that shows every product the bank offers, without repeating any product that appears in both lists.

EXPECTED COLUMNS

product_code, product_name, product_type

WRITE YOUR SQL HERE

| product_code | product_name

| SV01 | Basic Savings
 | SV02 | Premium Savings
 | SV03 | Youth Savings
 | SV04 | Business Savings
 | CR01 | Standard Current
 | CR02 | Gold Current
 | CR03 | Business Current

SELECT product_code,
 product_name
 FROM savings_products

UNION

SELECT product_code,
 product_name
 FROM current_products;

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: retail_banking_staff

staff_id	staff_name
S001	Mpho Radebe
S002	Brian Tshabalala
S003	Aisha Patel
S004	Kabelo Moabelo

Table: corporate_banking_staff

staff_id	staff_name
S003	Aisha Patel
S005	Nandi Dube
S006	Sipho Khumalo
S004	Kabelo Moabelo

**QUESTION 03 · USE UNION**

The HR team needs a unique list of all staff who work in either Retail Banking or Corporate Banking. Some staff are assigned to both. Each staff member should appear only once.

EXPECTED COLUMNS

staff_id, staff_name, email

WRITE YOUR SQL HERE

| staff_id | staff_name |

| S001 | Mpho Radebe
| S002 | Brian Tshabalala
| S003 | Aisha Patel
| S004 | Kabelo Moabelo
| S005 | Nandi Dube
| S006 | Sipho Khumalo

SELECT staff_id, staff_name
FROM retail_banking_staff

UNION

SELECT staff_id, staff_name
FROM corporate_banking_staff;

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: mobile_branch_cities

city_code	city_name
C01	Johannesburg
C02	Pretoria
C03	Cape Town
C04	Durban

Table: digital_branch_cities

city_code	city_name
C03	Cape Town
C05	Polokwane
C06	Port Elizabeth
C01	Johannesburg

QUESTION 04 · USE UNION

Marketing needs a unique list of all cities where NexBank serves customers — either through its mobile branches or its digital branch (which serves customers online regardless of city). No city should appear twice.

EXPECTED COLUMNS

city_code, city_name, region



WRITE YOUR SQL HERE

| city_code | city_name |

C01	Johannesburg
C02	Pretoria
C03	Cape Town
C04	Durban
C05	Polokwane
C06	Port Elizabeth

```
SELECT city_code, city_name
FROM mobile_branch_cities
```

UNION

```
SELECT city_code, city_name
FROM digital_branch_cities;
```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table:
push_notification_targets

customer_id	customer_name
C1001	Nomsa Zwane
C1002	Andile Buthelezi
C1003	Fatima Mahomed
C1004	Ryno van Zyl

Table: inapp_banner_targets

customer_id	customer_name
C1003	Fatima Mahomed
C1005	Thandeka Cele
C1006	Samuel Nkosi
C1002	Andile Buthelezi

QUESTION 05 • USE UNION

The digital marketing team ran two campaigns last month — one via push notification and one via in-app banner. Build a unique list of every customer who was targeted. If a customer received both, they must appear only once.

EXPECTED COLUMNS

customer_id, customer_name, segment

WRITE YOUR SQL HERE

| customer_id | customer_name |

C1001	Nomsa Zwane
C1002	Andile Buthelezi
C1003	Fatima Mahomed
C1004	Ryno van Zyl
C1005	Samuel Nkosi

```
SELECT customer_id,
customer_name
FROM push_notification_targets
```

UNION

```
SELECT customer_id,
customer_name
FROM inapp_banner_targets;
```



★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE



02

Questions 06 – 10 (UNION ALL)

The next five questions all use UNION ALL. Every row from both tables must appear in the output – including duplicates. Notice how the result sets are larger than what UNION would return.

Table: atm01_transactions

txn_id	account_id	amount
T1001	A001	500.00
T1002	A002	1200.00
T1003	A001	300.00
T1004	A003	750.00

Table: atm02_transactions

txn_id	account_id	amount
T1003	A001	300.00
T1005	A004	900.00
T1006	A002	450.00
T1007	A005	150.00

QUESTION 06 · USE UNION ALL

The fraud team needs the complete log of all ATM transactions from machine ATM-01 and machine ATM-02. Every transaction must appear – even if the same transaction appears in both logs due to a system sync error.

EXPECTED COLUMNS

transaction_id, account_id, amount, transaction_date

WRITE YOUR SQL HERE

```
| txn_id | account_id | amount |
```

```
| T1001 | A001      | 500.00 |
| T1002 | A002      | 1200.00 |
| T1003 | A001      | 300.00 |
| T1004 | A003      | 750.00 |
| T1003 | A001      | 300.00 |
| T1005 | A004      | 900.00 |
| T1006 | A002      | 450.00 |
| T1007 | A005      | 150.00 |
```

```
SELECT txn_id, account_id,
amount
FROM atm01_transactions
```

```
UNION ALL
```

```
SELECT txn_id, account_id,
amount
FROM atm02_transactions;
```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table:

Table:



Table: gauteng_loan_applications

app_id	customer_id
LA001	C1001
LA002	C1002
LA003	C1003
LA004	C1004

Table: western_cape_loan_applications

app_id	customer_id	loan_type
LA003	C1003	Personal
LA005	C1005	Vehicle Loan
LA006	C1006	Business
LA007	C1007	Home Loan

QUESTION 07 · USE UNION ALL

The credit team wants a full list of all loan applications received from the Gauteng region and the Western Cape region. Every application must be included – duplicates are allowed because both regions may have captured the same application.

EXPECTED COLUMNS

application_id, customer_id, loan_type, amount_requested

WRITE YOUR SQL HERE

```
| app_id | customer_id | loan_type |
```

```
| LA001 | C1001 | Home Loan
| LA002 | C1002 | Vehicle Loan
| LA003 | C1003 | Personal
| LA004 | C1004 | Home Loan
| LA003 | C1003 | Personal
| LA005 | C1005 | Vehicle Loan
| LA006 | C1006 | Business
| LA007 | C1007 | Home Loan
```

```
SELECT app_id, customer_id,
loan_type
FROM gauteng_loan_applications
```

```
UNION ALL
```

```
SELECT app_id, customer_id,
loan_type
FROM
western_cape_loan_applications;
```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: email_complaints

complaint_id	customer_id
EC001	C2001
EC002	C2002
EC003	C2003
EC004	C2004

Table: app_complaints

complaint_id	customer_id
AC001	C2005
AC002	C2001
AC003	C2006
AC004	C2007

**QUESTION 08 · USE UNION ALL**

The customer experience team needs a full record of every complaint logged this month, whether it came via email or via the mobile app. Every complaint must appear – the team needs all of them to calculate total complaint volumes.

EXPECTED COLUMNS

complaint_id, customer_id, category, logged_date

WRITE YOUR SQL HERE

```
| complaint_id | customer_id |
|-----|-----|
| EC001       | C2001       |
| EC002       | C2002       |
| EC003       | C2003       |
| EC004       | C2004       |
| AC001       | C2005       |
| AC002       | C2001       |
| AC003       | C2006       |
| AC004       | C2007       |
```

```
SELECT complaint_id, customer_id
FROM email_complaints
```

```
UNION ALL
```

```
SELECT complaint_id, customer_id
FROM app_complaints;
```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: april_payments

payment_id	account_id	amount
PAY001	A001	12500.00
PAY002	A002	4800.00
PAY003	A003	9200.00
PAY004	A004	3300.00

Table: may_payments

payment_id	account_id	amount
PAY005	A001	12500.00
PAY006	A005	7600.00
PAY007	A002	5100.00
PAY008	A006	2800.00

QUESTION 09 · USE UNION ALL

Finance needs to reconcile all payment records from April and May into one table for the half-year report. Every payment from both months must appear – the total row count matters for reconciliation.

EXPECTED COLUMNS

payment_id, account_id, amount, payment_date



WRITE YOUR SQL HERE

```

| payment_id | account_id | amount |
|-----|-----|-----|
| PAY001    | A001      | 12500.00 |
| PAY002    | A002      | 4800.00 |
| PAY003    | A003      | 9200.00 |
| PAY004    | A004      | 3300.00 |
| PAY005    | A001      | 12500.00 |
| PAY006    | A005      | 7600.00 |
| PAY007    | A002      | 5100.00 |
| PAY008    | A006      | 2800.00 |

```

```

SELECT payment_id, account_id,
amount
FROM april_payments

```

UNION ALL

```

SELECT payment_id, account_id,
amount
FROM may_payments;

```

★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE

Table: debit_entries

entry_id	account_id	entry_type
DR001	A001	Debit
DR002	A002	Debit
DR003	A003	Debit
DR004	A004	Debit

Table: credit_entries

entry_id	account_id	entry_type
CR001	A001	Credit
CR002	A005	Credit
CR003	A002	Credit
CR004	A006	Credit

QUESTION 10 • USE UNION ALL

The accounting system records debits and credits in two separate tables. Combine all entries into one general ledger for the audit. Every single entry from both tables must appear — no rows should be dropped.

EXPECTED COLUMNS

entry_id, account_id, entry_type, amount, entry_date

WRITE YOUR SQL HERE

```

| entry_id | account_id | entry_type |
|-----|-----|-----|
| D001    | A1001     | ATM Withdrawal |
| D002    | A1002     | Debit Order |
| D003    | A1003     | POS Purchase |
| C001    | A1001     | Salary Deposit |
| C002    | A1004     | Cash Deposit |
| C003    | A1002     | Interest Credit |

```

```

SELECT entry_id, account_id,
entry_type
FROM debit_entries

```

UNION ALL

```

SELECT entry_id, account_id,
entry_type
FROM credit_entries;

```



★ CHECK — RUN YOUR QUERY AND VERIFY AGAINST THE EXPECTED COLUMNS ABOVE



03 Bonus Questions

These three questions are written — no SQL needed. They test your understanding of why you would choose one operator over the other, and what goes wrong when you break the rules.

BONUS 01

A fraud analyst wants a unique list of customers who appeared in either the January or February high-risk watch lists. Should they use UNION or UNION ALL? Explain why.

YOUR ANSWER

UNION, because it removes duplicate customers and returns a unique list. If a customer appears in both the January and February high-risk watch lists, their name will appear only once and since the analyst wants to know which customers were flagged at least once, UNION is the correct choice.

BONUS 02

The auditing team wants to count every individual transaction that passed through the bank in Q1 — even if the same transaction was recorded in two systems on the same day. Should they use UNION or UNION ALL? Explain why.

YOUR ANSWER

UNION ALL since the audit team wants to count every transaction entry exactly as it appears in the systems, even if the same transaction was recorded twice

**B O N U S 0 3**

A developer writes this query: `SELECT account_id, account_holder FROM branch_sandton_accounts UNION SELECT account_id, account_holder, city FROM branch_rosebank_accounts;` The query fails. What is wrong, and how would you fix it?

Y O U R A N S W E R

The query is wrong because a **UNION** only works when both queries look the same in terms of columns.



04 Self-Check & Submission

Before you submit your work, run through this checklist. The highest marks always go to students who verify their own results before handing anything in.

★ YOUR SUBMISSION CHECKLIST

- **All 10 queries run without errors** in your SQL environment.
- **UNION queries return no duplicate rows** — row count equals the count of DISTINCT rows across both tables.
- **UNION ALL queries include all rows** — row count equals the sum of both tables' row counts.
- **Output columns match the spec** — same names, same order as the Expected Columns on each card.
- **Bonus answers are in full sentences** — they should explain the why, not just name the operator.

★ WHAT TO SUBMIT

- **One .sql file** with all 10 queries labelled -- Q1 through -- Q10.
- **Screenshots or text output** of each query result.
- **Bonus answers** in the boxes above or in a separate .txt file.
- **Your SQL environment** noted at the top of the file (e.g. PostgreSQL 16 / SQLite / BigQuery).

★ THE ONE THING TO REMEMBER

UNION and UNION ALL do the same thing — they combine rows from two queries. The only difference is what they do with duplicates. UNION removes them. UNION ALL keeps them. Every time you write one of these operators, ask yourself: do I want only unique records, or do I want every single row? Answer that question first, then pick the operator. It will never be wrong again.



Same columns, smarter queries.

UNION gives you one clean list. UNION ALL gives you every row.
Work through these ten questions and you will never confuse
them again — or pick the wrong one on the job.

★ BRIGHTLEARN • UNION & UNION ALL EXERCISE ★