High Availability & Scalability

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Scalability & High Availability

- Scalability means that an application / system can handle greater loads by adapting.
- There are two kinds of scalability:
  - Vertical Scalability
  - Horizontal Scalability (= elasticity)
- **Scalability is linked but different to High Availability**


- Let's deep dive into the distinction, using a call center as an example

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Vertical Scalability

- Vertically scalability means increasing the size of the instance
- For example, your application runs on a t2.micro
- Scaling that application vertically means running it on a t2.large
- Vertical scalability is very common for non distributed systems, such as a database.
- RDS, ElastiCache are services that can scale vertically.
- There's usually a limit to how much you can vertically scale (hardware limit)



junior operator senior operator

© Stephane Maarek


NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Horizontal Scalability

- Horizontal Scalability means increasing the number of instances / systems for your application

- Horizontal scaling implies distributed systems.
- This is very common for web applications / modern applications

- It's easy to horizontally scale thanks to the cloud offerings such as Amazon EC2




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

High Availability

- High Availability usually goes hand in hand with horizontal scaling
- High availability means running your application / system in at least 2 data centers (== Availability Zones)
- The goal of high availability is to survive a data center loss

- The high availability can be passive (for RDS Multi AZ for example)
- The high availability can be active (for horizontal scaling)



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

High Availability & Scalability For EC2

- Vertical Scaling: Increase instance size (= scale up / down)
  - From: t2.nano - 0.5G of RAM, 1 vCPU
  - To: u-12tb1.metal – 12.3 TB of RAM, 448 vCPUs

- Horizontal Scaling: Increase number of instances (= scale out / in)
  - Auto Scaling Group
  - Load Balancer


- High Availability: Run instances for the same application across multi AZ
  - Auto Scaling Group multi AZ
  - Load Balancer multi AZ

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

What is load balancing?

- Load Balances are servers that forward traffic to multiple servers (e.g., EC2 instances) downstream



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Why use a load balancer?

- Spread load across multiple downstream instances
- Expose a single point of access (DNS) to your application
- Seamlessly handle failures of downstream instances
- Do regular health checks to your instances
- Provide SSL termination (HTTPS) for your websites
- Enforce stickiness with cookies
- High availability across zones
- Separate public traffic from private traffic

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Why use an Elastic Load Balancer?


- An Elastic Load Balancer is a managed load balancer
  - AWS guarantees that it will be working
  - AWS takes care of upgrades, maintenance, high availability
  - AWS provides only a few configuration knobs
- It costs less to setup your own load balancer but it will be a lot more effort on your end
- It is integrated with many AWS offerings / services
  - EC2, EC2 Auto Scaling Groups, Amazon ECS
  - AWS Certificate Manager (ACM), CloudWatch
  - Route 53, AWS WAF, AWS Global Accelerator

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Health Checks

- Health Checks are crucial for Load Balancers
- They enable the load balancer to know if instances it forwards traffic to are available to reply to requests
- The health check is done on a port and a route (/health is common)
- If the response is not 200 (OK), then the instance is unhealthy



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Types of load balancer on AWS




- AWS has 4 kinds of managed Load Balancers
- **Classic Load Balancer** (v1 - old generation) – 2009 – CLB
  - HTTP, HTTPS, TCP, SSL (secure TCP)
- **Application Load Balancer** (v2 - new generation) – 2016 – ALB
  - HTTP, HTTPS, WebSocket
- **Network Load Balancer** (v2 - new generation) – 2017 – NLB
  - TCP, TLS (secure TCP), UDP
- **Gateway Load Balancer** – 2020 – GWLB
  - Operates at layer 3 (Network layer) – IP Protocol

- Overall, it is recommended to use the newer generation load balancers as they provide more features
- Some load balancers can be setup as internal (private) or external (public) ELBs

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Load Balancer Security Groups



Load Balancer Security Group:

Type	Protocol	Port Range	Source	Description
HTTP	TCP	80	0.0.0.0/0	Allow HTTP from an...
HTTPS	TCP	443	0.0.0.0/0	Allow HTTPS from a...

Application Security Group: Allow traffic only from Load Balancer


Type	Protocol	Port Range	Source	Description
HTTP	TCP	80	sg-054b5ff5ea02f2b6e (load-b	Allow Traffic only...

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Classic Load Balancers (v1)

- Supports TCP (Layer 4), HTTP & HTTPS (Layer 7)
- Health checks are TCP or HTTP based
- Fixed hostname XXX.region.elb.amazonaws.com



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2)



- Application load balancers is Layer 7 (HTTP)

- Load balancing to multiple HTTP applications across machines (target groups)
- Load balancing to multiple applications on the same machine (ex: containers)
- Support for HTTP/2 and WebSocket
- Support redirects (from HTTP to HTTPS for example)

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2)




- Routing tables to different target groups:
  - Routing based on path in URL (example.com/users & example.com/posts)
  - Routing based on hostname in URL (one.example.com & other.example.com)
  - Routing based on Query String, Headers (example.com/users?id=123&order=false)

- ALB are a great fit for micro services & container-based application (example: Docker & Amazon ECS)
- Has a port mapping feature to redirect to a dynamic port in ECS
- In comparison, we'd need multiple Classic Load Balancer per application

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2)
HTTP Based Traffic



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2) Target Groups


- EC2 instances (can be managed by an Auto Scaling Group) – HTTP
- ECS tasks (managed by ECS itself) – HTTP
- Lambda functions – HTTP request is translated into a JSON event
- IP Addresses – must be private IPs

- ALB can route to multiple target groups
- Health checks are at the target group level

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2) Query Strings/Parameters Routing




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Application Load Balancer (v2) Good to Know


- Fixed hostname (XXX.region.elb.amazonaws.com)
- The application servers don't see the IP of the client directly
  - The true IP of the client is inserted in the header **X-Forwarded-For**
  - We can also get Port (X-Forwarded-Port) and proto (X-Forwarded-Proto)



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Network Load Balancer (v2)



- Network load balancers (Layer 4) allow to:
  - **Forward TCP & UDP traffic to your instances**
  - Handle millions of request per seconds
  - Ultra-low latency


- **NLB has one static IP per AZ, and supports assigning Elastic IP** (helpful for whitelisting specific IP)

- NLB are used for extreme performance, TCP or UDP traffic

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Network Load Balancer (v2)
TCP (Layer 4) Based Traffic




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Network Load Balancer – Target Groups

- EC2 instances
- IP Addresses – must be private IPs
- Application Load Balancer
- Health Checks support the TCP, HTTP and HTTPS Protocols




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Gateway Load Balancer

- Deploy, scale, and manage a fleet of 3rd party network virtual appliances in AWS
- Example: Firewalls, Intrusion Detection and Prevention Systems, Deep Packet Inspection Systems, payload manipulation, …

- Operates at Layer 3 (Network Layer) – IP Packets
- Combines the following functions:
  - **Transparent Network Gateway** – single entry/exit for all traffic
  - **Load Balancer** – distributes traffic to your virtual appliances
- Uses the **GENEVE** protocol on port **6081**




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Gateway Load Balancer – Target Groups

- EC2 instances
- IP Addresses – must be private IPs




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Sticky Sessions (Session Affinity)

- It is possible to implement stickiness so that the same client is always redirected to the same instance behind a load balancer
- This works for **Classic Load Balancer, Application Load Balancer, and Network Load Balancer**
- For both CLB & ALB, the "cookie" used for stickiness has an expiration date you control
- Use case: make sure the user doesn't lose his session data
- Enabling stickiness may bring imbalance to the load over the backend EC2 instances



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Sticky Sessions – Cookie Names

- Application-based Cookies
  - Custom cookie
    - Generated by the target
    - Can include any custom attributes required by the application
    - Cookie name must be specified individually for each target group
    - Don't use **AWSALB**, **AWSALBAPP**, or **AWSALBTG** (reserved for use by the ELB)
  - Application cookie
    - Generated by the load balancer
    - Cookie name is **AWSALBAPP**
- Duration-based Cookies
  - Cookie generated by the load balancer
  - Cookie name is **AWSALB** for ALB, **AWSELB** for CLB


© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Cross-Zone Load Balancing


With Cross Zone Load Balancing:

each load balancer instance distributes evenly across all registered instances in all AZ



Without Cross Zone Load Balancing:

Requests are distributed in the instances of the node of the Elastic Load Balancer



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Cross-Zone Load Balancing

- Application Load Balancer
  - Enabled by default (can be disabled at the Target Group level)
  - No charges for inter AZ data
- Network Load Balancer & Gateway Load Balancer
  - Disabled by default
  - You pay charges ($) for inter AZ data if enabled
- Classic Load Balancer
  - Disabled by default
  - No charges for inter AZ data if enabled

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

SSL/TLS - Basics

- An SSL Certificate allows traffic between your clients and your load balancer to be encrypted in transit (in-flight encryption)

- **SSL** refers to Secure Sockets Layer, used to encrypt connections
- **TLS** refers to Transport Layer Security, which is a newer version
- Nowadays, **TLS certificates are mainly used**, but people still refer as SSL


- Public SSL certificates are issued by Certificate Authorities (CA)
- Comodo, Symantec, GoDaddy, GlobalSign, Digicert, Letsencrypt, etc…

- SSL certificates have an expiration date (you set) and must be renewed

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Load Balancer - SSL Certificates



- The load balancer uses an X.509 certificate (SSL/TLS server certificate)
- You can manage certificates using ACM (AWS Certificate Manager)
- You can create upload your own certificates alternatively
- HTTPS listener:
  - You must specify a default certificate
  - You can add an optional list of certs to support multiple domains
  - Clients can use SNI (Server Name Indication) to specify the hostname they reach
  - Ability to specify a security policy to support older versions of SSL / TLS (legacy clients)

© Stephane Maarek


NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

SSL – Server Name Indication (SNI)

- SNI solves the problem of loading **multiple SSL certificates onto one web server** (to serve multiple websites)
- It's a "newer" protocol, and requires the client to **indicate** the hostname of the target server in the initial SSL handshake
- The server will then find the correct certificate, or return the default one

Note:

- Only works for ALB & NLB (newer generation), CloudFront
- Does not work for CLB (older gen)



NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Elastic Load Balancers – SSL Certificates

- Classic Load Balancer (v1)
  - Support only one SSL certificate
  - Must use multiple CLB for multiple hostname with multiple SSL certificates
- Application Load Balancer (v2)
  - Supports multiple listeners with multiple SSL certificates
  - Uses Server Name Indication (SNI) to make it work
- Network Load Balancer (v2)
  - Supports multiple listeners with multiple SSL certificates
  - Uses Server Name Indication (SNI) to make it work


© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Connection Draining

- Feature naming
  - Connection Draining – for CLB
  - Deregistration Delay – for ALB & NLB


- Time to complete "in-flight requests" while the instance is de-registering or unhealthy
- Stops sending new requests to the EC2 instance which is de-registering
- Between 1 to 3600 seconds (default: 300 seconds)
- Can be disabled (set value to 0)
- Set to a low value if your requests are short



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

What's an Auto Scaling Group?



- In real-life, the load on your websites and application can change
- In the cloud, you can create and get rid of servers very quickly


- The goal of an Auto Scaling Group (ASG) is to:
  - Scale out (add EC2 instances) to match an increased load
  - Scale in (remove EC2 instances) to match a decreased load
  - Ensure we have a minimum and a maximum number of EC2 instances running
  - Automatically register new instances to a load balancer
  - Re-create an EC2 instance in case a previous one is terminated (ex: if unhealthy)

- ASG are free (you only pay for the underlying EC2 instances)

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com


Auto Scaling Group in AWS



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling Group in AWS With Load Balancer




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling Group Attributes

- A **Launch Template** (older "Launch Configurations" are deprecated)
  - AMI + Instance Type
  - EC2 User Data
  - EBS Volumes
  - Security Groups
  - SSH Key Pair
  - IAM Roles for your EC2 Instances
  - Network + Subnets Information
  - Load Balancer Information
- Min Size / Max Size / Initial Capacity
- Scaling Policies




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling - CloudWatch Alarms & Scaling

- It is possible to scale an ASG based on CloudWatch alarms
- An alarm monitors a metric (such as **Average CPU**, or a **custom metric**)
- Metrics such as Average CPU are computed for the overall ASG instances
- Based on the alarm:
  - We can create scale-out policies (increase the number of instances)
  - We can create scale-in policies (decrease the number of instances)



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling Groups – Scaling Policies


- Dynamic Scaling
  - Target Tracking Scaling
    - Simple to set-up
    - Example: I want the average ASG CPU to stay at around 40%
  - Simple / Step Scaling
    - When a CloudWatch alarm is triggered (example CPU > 70%), then add 2 units
    - When a CloudWatch alarm is triggered (example CPU < 30%), then remove 1
- Scheduled Scaling
  - Anticipate a scaling based on known usage patterns
  - Example: increase the min capacity to 10 at 5 pm on Fridays

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling Groups – Scaling Policies

- **Predictive scaling:** continuously forecast load and schedule scaling ahead




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Good metrics to scale on

- **CPUUtilization**: Average CPU utilization across your instances
- **RequestCountPerTarget**: to make sure the number of requests per EC2 instances is stable
- **Average Network In / Out** (if you're application is network bound)
- **Any custom metric** (that you push using CloudWatch)




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Auto Scaling Groups - Scaling Cooldowns

- After a scaling activity happens, you are in the **cooldown period (default 300 seconds)**
- During the cooldown period, the ASG will not launch or terminate additional instances (to allow for metrics to stabilize)

- Advice: Use a ready-to-use AMI to reduce configuration time in order to be serving request fasters and reduce the cooldown period



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com