Amazon Route 53

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

What is DNS?

- Domain Name System which translates the human friendly hostnames into the machine IP addresses
- www.google.com => 172.217.18.36
- DNS is the backbone of the Internet
- DNS uses hierarchical naming structure

.com

example.com

www.example.com


api.example.com

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

DNS Terminologies


- **Domain Registrar:** Amazon Route 53, GoDaddy, …
- **DNS Records:** A, AAAA, CNAME, NS, …
- **Zone File:** contains DNS records
- **Name Server:** resolves DNS queries (Authoritative or Non-Authoritative)
- **Top Level Domain (TLD):** .com, .us, .in, .gov, .org, …
- **Second Level Domain (SLD):** amazon.com, google.com, …



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

How DNS Works




NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Amazon Route 53

- A highly available, scalable, fully managed and *Authoritative* DNS
  - Authoritative = the customer (you) can update the DNS records
- Route 53 is also a Domain Registrar
- Ability to check the health of your resources
- The only AWS service which provides 100% availability SLA
- Why Route 53? 53 is a reference to the traditional DNS port



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Records

- How you want to route traffic for a domain
- Each record contains:
  - **Domain/subdomain Name** – e.g., example.com
  - **Record Type** – e.g., A or AAAA
  - **Value** – e.g., 12.34.56.78
  - **Routing Policy** – how Route 53 responds to queries
  - **TTL** – amount of time the record cached at DNS Resolvers
- Route 53 supports the following DNS record types:
  - (must know) A / AAAA / CNAME / NS
  - (advanced) CAA / DS / MX / NAPTR / PTR / SOA / TXT / SPF / SRV

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com


Route 53 – Record Types

- A – maps a hostname to IPv4
- AAAA – maps a hostname to IPv6
- CNAME – maps a hostname to another hostname
  - The target is a domain name which must have an A or AAAA record
  - Can't create a CNAME record for the top node of a DNS namespace (Zone Apex)
  - Example: you can't create for example.com, but you can create for www.example.com
- NS – Name Servers for the Hosted Zone
  - Control how traffic is routed for a domain

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Hosted Zones



- A container for records that define how to route traffic to a domain and its subdomains

- **Public Hosted Zones** – contains records that specify how to route traffic on the Internet (public domain names)
  application1.mypublicdomain.com
- **Private Hosted Zones** – contain records that specify how you route traffic within one or more VPCs (private domain names)
  application1.company.internal


- You pay $0.50 per month per hosted zone

© Stephane Maarek


NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Public vs. Private Hosted Zones

Public Hosted Zone



Private Hosted Zone




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Records TTL (Time To Live)

- High TTL – e.g., 24 hr
  - Less traffic on Route 53
  - Possibly outdated records
- Low TTL – e.g., 60 sec.
  - More traffic on Route 53 ($$)
  - Records are outdated for less time
  - Easy to change records
- Except for Alias records, TTL is mandatory for each DNS record



NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

CNAME vs Alias

- AWS Resources (Load Balancer, CloudFront...) expose an AWS hostname:
  - lb1-1234.us-east-2.elb.amazonaws.com and you want myapp.mydomain.com


- CNAME:
  - Points a hostname to any other hostname. (app.mydomain.com => blabla.anything.com)
  - ONLY FOR NON ROOT DOMAIN (aka. something.mydomain.com)
- Alias:
  - Points a hostname to an AWS Resource (app.mydomain.com => blabla.amazonaws.com)
  - Works for ROOT DOMAIN and NON ROOT DOMAIN (aka mydomain.com)
  - Free of charge
  - Native health check

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Alias Records

- Maps a hostname to an AWS resource
- An extension to DNS functionality
- Automatically recognizes changes in the resource's IP addresses
- Unlike CNAME, it can be used for the top node of a DNS namespace (Zone Apex), e.g.: example.com
- Alias Record is always of type A/AAAA for AWS resources (IPv4 / IPv6)
- You can't set the TTL



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Alias Records Targets


- Elastic Load Balancers
- CloudFront Distributions
- API Gateway
- Elastic Beanstalk environments
- S3 Websites
- VPC Interface Endpoints
- Global Accelerator accelerator
- Route 53 record in the same hosted zone



Elastic Load Balancer



Amazon CloudFront



Amazon API Gateway



Elastic Beanstalk



S3 Websites



VPC Interface Endpoints



Global Accelerator



Route 53 Record
(same Hosted Zone)

- You cannot set an ALIAS record for an EC2 DNS name

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Routing Policies


- Define how Route 53 responds to DNS queries
- Don't get confused by the word *"Routing"*
  - It's not the same as Load balancer routing which routes the traffic
  - DNS does not route any traffic, it only responds to the DNS queries
- Route 53 Supports the following Routing Policies
  - Simple
  - Weighted
  - Failover
  - Latency based
  - Geolocation
  - Multi-Value Answer
  - Geoproximity (using Route 53 Traffic Flow feature)

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Simple

- Typically, route traffic to a single resource
- Can specify multiple values in the same record
- **If multiple values are returned, a random one is chosen by the client**
- When Alias enabled, specify only one AWS resource
- Can't be associated with Health Checks




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Weighted

- Control the % of the requests that go to each specific resource
- Assign each record a relative weight:
  - $traffic\ (\%) = \frac{Weight\ for\ a\ specific\ record}{Sum\ of\ all\ the\ weights\ for\ all\ records}$
  - Weights don't need to sum up to 100
- DNS records must have the same name and type
- Can be associated with Health Checks
- Use cases: load balancing between regions, testing new application versions…
- Assign a weight of 0 to a record to stop sending traffic to a resource
- If all records have weight of 0, then all records will be returned equally




NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Routing Policies – Latency-based

- Redirect to the resource that has the least latency close to us
- Super helpful when latency for users is a priority
- **Latency is based on traffic between users and AWS Regions**
- Germany users may be directed to the US (if that's the lowest latency)
- Can be associated with Health Checks (has a failover capability)




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Health Checks

- HTTP Health Checks are only for **public resources**
- Health Check => Automated DNS Failover:
  1. Health checks that monitor an endpoint (application, server, other AWS resource)
  2. Health checks that monitor other health checks (Calculated Health Checks)
  3. Health checks that monitor CloudWatch Alarms (full control !!) – e.g., throttles of DynamoDB, alarms on RDS, custom metrics, … (helpful for private resources)
- Health Checks are integrated with CW metrics




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Health Checks – Monitor an Endpoint

- About 15 global health checkers will check the endpoint health
  - Healthy/Unhealthy Threshold – 3 (default)
  - Interval – 30 sec (can set to 10 sec – higher cost)
  - Supported protocol: HTTP, HTTPS and TCP
  - If > 18% of health checkers report the endpoint is healthy, Route 53 considers it **Healthy**. Otherwise, it's **Unhealthy**
  - Ability to choose which locations you want Route 53 to use
- Health Checks pass only when the endpoint responds with the 2xx and 3xx status codes
- Health Checks can be setup to pass / fail based on the text in the first **5120 bytes** of the response
- Configure you router/firewall to allow incoming requests from Route 53 Health Checkers




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Calculated Health Checks

- Combine the results of multiple Health Checks into a single Health Check
- You can use **OR**, **AND**, or **NOT**
- Can monitor up to 256 Child Health Checks
- Specify how many of the health checks need to pass to make the parent pass
- Usage: perform maintenance to your website without causing all health checks to fail




NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Health Checks – Private Hosted Zones


- Route 53 health checkers are outside the VPC
- They can't access **private** endpoints (private VPC or on-premises resource)
- You can create a **CloudWatch Metric** and associate a **CloudWatch Alarm**, then create a Health Check that checks the alarm itself



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Failover (Active-Passive)




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Geolocation

- Different from Latency-based!
- **This routing is based on user location**
- Specify location by Continent, Country or by US State (if there's overlapping, most precise location selected)
- Should create a **"Default"** record (in case there's no match on location)
- Use cases: website localization, restrict content distribution, load balancing, …
- Can be associated with Health Checks



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Geoproximity


- Route traffic to your resources based on the geographic location of users and resources
- Ability **to shift more traffic to resources based** on the defined **bias**
- To change the size of the geographic region, specify **bias** values:
  - To expand (1 to 99) – more traffic to the resource
  - To shrink (-1 to -99) – less traffic to the resource

- Resources can be:
  - AWS resources (specify AWS region)
  - Non-AWS resources (specify Latitude and Longitude)
- You must use Route 53 **Traffic Flow** to use this feature

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com


Routing Policies – Geoproximity



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – Geoproximity



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Routing Policies – IP-based Routing

- Routing is based on clients' IP addresses
- You provide a list of CIDRs for your clients and the corresponding endpoints/locations (user-IP-to-endpoint mappings)
- Use cases: Optimize performance, reduce network costs…
- Example: route end users from a particular ISP to a specific endpoint



NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

Routing Policies – Multi-Value

- Use when routing traffic to multiple resources
- Route 53 return multiple values/resources
- Can be associated with Health Checks (return only values for healthy resources)
- Up to 8 healthy records are returned for each Multi-Value query
- Multi-Value is not a substitute for having an ELB


Name	Type	Value	TTL	Set ID	Health Check
www.example.com	A Record	192.0.2.2	60	Web1	A
www.example.com	A Record	198.51.100.2	60	Web2	B
www.example.com	A Record	203.0.113.2	60	Web3	C

© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Domain Registar vs. DNS Service

- You buy or register your domain name with a Domain Registrar typically by paying annual charges (e.g., GoDaddy, Amazon Registrar Inc., …)
- The Domain Registrar usually provides you with a DNS service to manage your DNS records
- But you can use another DNS service to manage your DNS records
- Example: purchase the domain from GoDaddy and use Route 53 to manage your DNS records



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

GoDaddy as Registrar & Route 53 as DNS Service

GoDaddy

Records

We can't display your DNS information because your nameservers aren't managed by us.

Nameservers

Using custom nameservers **Change**

Nameserver
ns-1083.awsdns-07.org
ns-932.awsdns-52.net
ns-1911.awsdns-46.co.uk
ns-481.awsdns-60.com

Amazon Route 53

Public Hosted Zone
stephanetheteacher.com

Hosted zone details — Edit hosted zone

Hosted zone ID Z30IUJCCWPKZUV	Type Public hosted zone	Name servers ns-252.awsdns-31.com ns-1468.awsdns-55.org ns-633.awsdns-15.net ns-1800.awsdns-33.co.uk
Description HostedZone created by Route53 Registrar	Record count 22	
Query log		

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

© Stephane Maarek

3rd Party Registrar with Amazon Route 53

- If you buy your domain on a 3rd party registrar, you can still use Route 53 as the DNS Service provider

1. Create a Hosted Zone in Route 53
2. Update NS Records on 3rd party website to use Route 53 **Name Servers**

- **Domain Registrar != DNS Service**
- But every Domain Registrar usually comes with some DNS features


© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Hybrid DNS

- By default, Route 53 Resolver automatically answers DNS queries for:
  - Local domain names for EC2 instances
  - Records in Private Hosted Zones
  - Records in public Name Servers

- **Hybrid DNS** – resolving DNS queries between VPC (Route 53 Resolver) and your networks (other DNS Resolvers)
- Networks can be:
  - VPC itself / Peered VPC
  - On-premises Network (connected through Direct Connect or AWS VPN)




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Resolver Endpoints



- **Inbound Endpoint** – allows your DNS Resolvers to resolve domain names for AWS resources (e.g., EC2 instances) and records in Private Hosted Zones




© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com

Route 53 – Resolver Endpoints

- Outbound Endpoint
  - Route 53 Resolver forwards DNS queries to your DNS Resolvers



© Stephane Maarek

NOT FOR DISTRIBUTION © Stephane Maarek www.datacumulus.com