Memo No.
Date

Mo Tu We Th Fri Sa Su

Trương Thị Phương Trang - CNTT5 - B500080301

Bài 1:

```
Interface Mail {
    void SendMail();
    void log();
}

class MailImpl implements Mail {
    @Override
    public void SendMail() {
        System.out.println("Dang gui Mail...");
    }
    @Override
    public void log() {
        System.out.println("Dang gui log ...");
    }
}

public class Main {
    public static void main(String[] Args) {
        Mail mail = new MailImpl();
        mail.SendMail();
        mail.log();
    }
}
```

TUANVIET BOOKS

Mo Tu We Th Fri Sa Su

Memo No.....

Date...../...../.....

Bài 2:

```
Interface Shape {
    String color = " Red ";
    void draw();
}

class Rectangle implements Shape
{
    @ Override
    public void draw(){
        System.out.println(" Vẽ hcn vs màu" +color)
    }
}

class Circle implements Shape {
    @ Override
    public void draw(){
    System.out.println(" Vẽ hình tròn với
                        màu" + color);
    }
}

public class Main {
    public static void main (String [] args){
        Shape h1 = new Rectangle ();
        Shape h2 = new ~~Recta~~ Circle();
    h1.draw();
    h2 = draw();
    }
}
```

TUANVIET BOOKS

Bài 4.6.

```
Interface PhuongTienDichuyen {
    String layTenHangSanXuat();
    void batDau();
    void tangToc();
    void dungLai();
    double layVanToc()
}

class MayBay implements PhuongTienDichuyen {
    private String loaiNhienLieu
    private HangSanXuat hangSanXuat;
    public MayBay (String loaiNhienLieu, HangSanXuat
                   hangSanXuat) {
        this.hangSanXuat = hangSanXuat;
    }
    public void catCanh () {
        System.out.println("Maybay catcanh")
    }
    public void haCanh () {}
        System.out.println("Maybay hacanh")
    }
    @Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat
    }
    @Override
    public void batDau () {}
        System.out.println("Maybay batdau");
    @Override
```

```
    @Override
    public void tangToc () {
        System.out.println("xe oto tangtoc")
    }
    }
    @Override
    public void dunglai () {
        System.out.println("xe oto dunglai")
    }
    }
    @Override
    public double layVanToc () {
        return 100;
    }
    }
public class XeDap implements PhuongTienDichuyen
    private HangSanXuat
    public XeDap (HangSanXuat hangSanXuat)
    {
        this.HangSanXuat = hangSanXuat;
    }
    @Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat
    }
    @Override
    public void batDau () {
        System.out.println("xe dap batdau")
    @Override
    public void tangToc () {
        System.out.println("xe dap tangtoc")
```

```
    }
    @Override
    public void tangToc () {
        System.out.println("Maybay tangtoc")
    }
    @Override
    public void dunglai () {
        System.println("Maybay dunglai")
    }
    @Override
    public double layVanToc () {
        return 800;
    }
}
class XeOto implements PhuongTienDichuyen {
    private String loaiNhienLieu;
    private HangSanXuat hangSanXuat;
    public XeOto (String loaiNhienLieu, HangSanXuat
                  hangSanXuat) {
        this.loaiNhienLieu = loaiNhienLieu;
        this.hangSanXuat = hangSanXuat;
    }
    @Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat();
    }
    @Override
    public void batDau ()
        System.out.println("xe oto batdau")
    }
```

```
    @Override
    public void dung lai () {
        System.out.println("xe dap dunglai")
    }
    }
    @Override
    public double layVanToc () {
        System.out.println("xe dap
        return 20;
    }
}
class Main {
    public static void main(String[] Jong) {
        XeOto = new XeOto ("Xang",
        MayBay = new MayBay ("Dau",
        XeDap = new XeDap ("Sucng cor");
        System.out.println("vantoc" + xeoto
                           layVanToc());
        System.out.println("van toc" + MayBay
                           layVanToc());
        System.out.println("van toc" + XeDap
                           layVanToc());
    }
}
```

```
Interface Car {
    void accelerate();
    String get Color();
    double get Speed();
}
Interface Bmw {
class Bmw implements Car {
    private String color;
    private double speed;
    public Bmw (String color, double speed) {
        this.color = color;
        this.speed = speed;
    }
    @ Override
    public void accelerate() {
        speed += 20;
    }
    @ Override
    public toString getColor() {
        return color;
    }
    @ Override
    public double getSpeed() {
        return speed;
    }
    @ Override
    public toString() {
```

```
class Civic implements Car {
    private String color;
    private double speed;
    public Civic (String color, double Speed) {
        this.color = color;
        this.speed = speed;
    }
    @ Override
    public void accelerate() {
        speed += 15;
    }
    @ Override
    public String getColor() {
        return color;
    }
    @ Override
    public double getSpeed() {
        return speed;
    }
    @ Override
    public String toString() {
        return "Civic - color :" + color +
                speed :" + speed;
    }
}
class Main {
public static void main (String [] args) {
```

Memo No.....

Date...../...../.....

```
for (Car c : ds) {
        c.accelerate();
        System.out.println(c);
    }
}
}
```

```
@ Override
public void moveDown () {
        y -= ySpeed ;
}
@ Override
public void moveLeft () {
        x -= xSpeed ;
}
@ Override
public void moveRight () {
        x += xSpeed ;
}
@ Override
public String toString () {
        return "Point (x = " + x + ", y = "
                + y + ")" ;
}
}

class MoveableCircle implements Moveable {
    private int radius ;
    private Moveable Point center ;
    public MoveableCircle ( MoveablePoint
            center , int radius ) {
        this . center = center ;
        this . radius = radius ;
    }
    @ Override
    public void moveUp () {
        center moveUp () ;
```

```
    @ Override
    Public void moveUp ();
        center moveUp ;
    @ Override
    public void MoveDown () {
        center moveDown () ;
    }
    @ Override
    Public void moveLeft () {
        center moveLeft () ;
    }
    @ Override
    public void moveRight () {
        center moveRight () ;
    }
    @ Override
    Public String toString () {
        return " Circle (center = " + center +
            radius = " + radius + " )" ;
    }
}
Public class main {
    public static void main ( String [] args ) {
        Moveable m1 = new MoveablePoint
            (0, 0, 5, 5);
        moveable m2 = new MoveableCircle ( new
            MoveablePoint(1, 1, 2, 2), 10);
        m1 . moveUp () ;
        m2 . moveRight () ;
        System . out . println (m1);
        System . out . println (m2) ;
```

B6.

```
Interface Moveable {
    void moveUp() ;
    void moveDown () ;
    void moveLeft () ;
    void moveRight () ;
}
class moveablePoint implemnts Moveable {
    private int x ;
    private int y ;
    private int xSpeed ;
    private int ySpeed ;
public MoveablePoint (int x , int y , int xSpeed
        int ySpeed ) {
    this . x = x ;
    this . y = y ;
    this . xSpeed = xSpeed ;
    this . ySpeed = ySpeed ;
}
@ Override
public void moveUp () {
        y += ySpeed ;
}
```