

MARS CAD Guide Autodesk Inventor 2023



Contents

1	2D S	ketches	4
	1.1	2D Sketches: Key Takeaways	4
	1.2	Creating a Sketch	5
	1.3	Adding Geometry	5
		1.3.1 Types of Geometry	5
		1.3.2 Tips and Tricks for Adding Geometry	6
		1.3.3 Projecting Geometry	6
	1.4	Geometry Patterns	7
	1.5	Modifying Existing Geometry	7
		1.5.1 Tips and Tricks	7
	1.6	Constraints and Dimensions	8
		1.6.1 Dimensions	8
		1.6.2 Types of Constraints	8
		1.6.3 Adding Constraints	9
		1.6.4 Viewing and Editing Constraints	9
		1.6.5 Constraint Inference, Relax Mode and Settings	10
		1.6.6 Automatic Dimensions	11
	1.7	Formatting	11
	1.8	Layout	11
		1.8.1 Assembly and Component Layouts	11
		1.8.2 Sketch Blocks	11
	1.9	Insert	12
		1.9.1 Inserting Images	12
		1.9.2 Inserting Points Spreadsheets	12
		1.9.3 Inserting AutoCAD Files	12
	1.10	Managing 2D Sketches	12
	1.11		13
	1.12	More Sketch Options	13
_			
2			14
	2.1		14
		9	14
	2.3	9	14
	2.4		14
	2.5	Modifying 3D Sketches	14
3	3D I	Modelling (1997)	15
3	3.1	· ·	15
	J. I	3	15
		3.1.2 Examples of When to use Features	15
		3.1.3 Common Options	16
		· ·	16
		3.1.5 Additional Options: Revolve	17
		3.1.6 Additional Options: Sweep	17
		3.1.7 Additional Options: Loft	17
		3.1.8 Additional Options: Coil	18
		3.1.9 Additional Options: Emboss	18
		3.1.10 Additional Options: Decal	18
		·	18
		3.1.11 Additional Options. Delive	10

		3.1.12 Additional Options: Import	19 19
		3.1.14 Additional Options: Unwrap	19
	3.2	Primitives	19
	3.3	Modifying 3D Features	19
		3.3.1 Modifiers	20
	3.4	Patterning 3D Features	20
	3.5	Freeform 3D Modelling	20
	3.6	Surfaces	20
	3.7	Simplifying 3D Models	20
	3.8	Plastic Parts	21
	3.9	Insert	21
	3.10		21
	3.11	The Shape Generator	21
		Feature Management	21
	0.12	Toutare Management	۷.
4	Asse	emblies	22
	4.1	Placing Components	22
	4.2	Creating Components and Adaptivity	22
	4.3	Relationships	22
	4.4	Patterning Components	22
	4.5	Productivity Optimisation	22
	4.6	Simplifying	22
	4.7	Contact Sets	22
	4.8	Managing Components	22
5	Desi	gn Accelerators	23
	5.1	Fasteners	23
	5.2	Frames	23
	5.3	Power Transmission	23
	5.4	Springs	23
_			
6	-	ecting and Analysing	24
6	6.1	Component and Assembly Stress Analysis	24
6	6.1 6.2	Component and Assembly Stress Analysis	24 24
6	6.1 6.2 6.3	Component and Assembly Stress Analysis	24 24 24
6	6.1 6.2 6.3 6.4	Component and Assembly Stress Analysis	24 24 24 24
6	6.1 6.2 6.3 6.4 6.5	Component and Assembly Stress Analysis	24 24 24 24 24
6	6.1 6.2 6.3 6.4 6.5 6.6	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation	24 24 24 24 24 24
6	6.1 6.2 6.3 6.4 6.5	Component and Assembly Stress Analysis	24 24 24 24 24
	6.1 6.2 6.3 6.4 6.5 6.6 6.7	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis	24 24 24 24 24 24 24
6	6.1 6.2 6.3 6.4 6.5 6.6 6.7	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis otations	24 24 24 24 24 24 24 24
	6.1 6.2 6.3 6.4 6.5 6.6 6.7	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis General Annotations and Notes	24 24 24 24 24 24 24 25
	6.1 6.2 6.3 6.4 6.5 6.6 6.7	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis otations	24 24 24 24 24 24 24 24
	6.1 6.2 6.3 6.4 6.5 6.6 6.7 Ann 7.1 7.2	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis General Annotations and Notes	24 24 24 24 24 24 24 25
7	6.1 6.2 6.3 6.4 6.5 6.6 6.7 Ann (7.1 7.2	Component and Assembly Stress Analysis Autodesk Nastran Graphical Analysis Tolerance Analysis Interference Analysis Dynamic Simulation Frame Analysis General Annotations and Notes Exproting Annotations	24 24 24 24 24 24 24 25 25

11	Sheet Metal	29
12	ВІМ	31
13	Fusion Interoperability	32
14	3D Printing Compatability	33
15	Electromechanical Linking	34
16	Piping and Tubing	35
17	Cables and Harnesses	36
18	Mold Design	37
19	Weldments	38
20	Nesting	39
21	Task Scheduling, iLogic and Inventor SDK	40
22	Acknowledgements and Copyright	41

2D Sketches

2D sketching is one of the most fundamental parts of Autodesk Inventor. A 2D sketch is essentially a collection of pieces of geometry, and are usually used as building blocks to create 3D features. Generally, when we create sketches we first place down any geometry that we want. We can then modify parts of the geometry and use constraints and dimensions to specify the position and size. We can then use the sketch to either analyse shapes or create 3D features.

This section will be a deeper dive into 2D sketching in Inventor, beyond just the basics of how to create sketches. We will highlight most of the auxiliary features that you can utilise to speed up your workflow or create more complex sketches. All of the features detailed in this chapter are accessible via the Sketch tab of the workspace ribbon, or via Right Click on the shared workspace. The ribbon is ordered into different tabs, which group together similar features and will be forming the basis for the subsections of this chapter.

2D Sketches: Key Takeaways

- Use Dimensions or Constraints to ensure your sketch is fully constrained. To make this faster, utilise snapping geometry to points and using inferred constraints.
- The Automatic Dimension tool will automatically create all the dimensions you could need.
- The bottom right of your workspace will display a lot of important information such as missing dimensions and coordinates.
- If you want to recreate a physical object, you can Import a Picture into your sketch and use your geometry tools (most commonly Splines - Interpolation Points) to draw over it.
- Project Geometry and Cut Edges are very powerful tools that lets you copy existing sketches and features into your sketch.
- Duplicate and pattern your shapes with Geometry Patterns.
- Change the Format of your geometry to make complex sketches easier to read.
- You can group pieces of geometry into Sketch Blocks to move around as one.
- Using Parameters allows you to quickly change the dimensions of sketches and objects, no matter where you are in the application.
- Inventor allows you to analyse the geometric properties of the sections of your sketches through Region Properties.

Creating a Sketch

2D sketches can be created in any plane or flat surface. There are many different ways to create a sketch, but the easiest by selecting 3D Model ▶ Sketch ▶ Start 2D Sketch and then clicking on the desired plane or flat surface.

Adding Geometry

Types of Geometry

There are several types of geometry which can be placed:

- Line: Creates either simple lines or joined segments of lines and arcs. Click on your starting point, and then your endpoint (to create a line) or click and drag your starting point (to create a curve). Finish the command by double clicking on the final endpoint or clicking ESC.
- Spline: Creates a spline (parametric curve), either by specifying points for the spline to pass through or control vertices.
- Equation Curve: Creates a curve based on a mathematical equation. The equation can be explicit or parametric, and use polar or cartesian coordinates.
- Bridge Curve: Creates a curve that joins two line/curve endpoints together such that the bridge curve is tangent to both segments (ref. Smooth Constraints).
- Circle: Creates a circle, using either a center point or three tangent lines.
- Ellipse: Creates an ellipse based on two axial lines
- Arc: Creates an arc, using the endpoints and either a center point or midpoint (Three Point Arc). Can also create an arc that joins a line's endpoint and is tangent to it.
- Rectangle: Creates a rectangle using various key points.
- Slot: Creates a slot or capsule, using various key points.
- Polygon: Creates a polygon of any order, and can be drawn inscribed or circumscribed.
- Fillets and Chamfers: Transforms sharp corners into curved corners (fillets) or bevelled corners (chamfers). The radius or angle of these fillets/chamfers can be adjusted in the popup dialog.
- Text: Creates text as geometry, which can be further extruded, swept, etc. Various formatting options can be adjusted in the popup dialog.
- Geometry Text: Creates text that lies along lines or simple curves. Cannot be used for more complex geometries such as splines.
- Point: Creates points.

Tips and Tricks for Adding Geometry

- You can usually specify the coordinates of key points or the dimensions of your geometry (magnitude and angle). Press Tab to specify coordinates or switch between multiple dimensions. You can change the coordinate type (for example, absolute vs relative) by Right Click ► Coordinate Type .
- The bottom right of your workspace will display a lot of useful information when creating geometry, such as coordinate positions, deltas, and dimensions.
- You can "snap" your geometry to existing points. A green dot will signify you are placing your geometry on an existing point, and a yellow dot will signify you are placing your geometry along an existing curve. This is often useful to make sure that all your lines connect to form a closed shape. If you are having trouble snapping to geometry, you can Right Click ➤ Point Snaps when placing down geometry and choose whether you want to snap to a midpoint, endpoint or various other points.
- The above is a case of constraint inference (ref. Constraints), and you can align your geometry in other ways, such as drawing a line which is tangent to another curve. You can temporarily disable constraint inference or point snapping by holding CTRL.
- When starting the Line command, you can easily create tangent or normal lines. Click your starting point on existing geometry, and then click and drag the starting point. The direction you drag determines whether the line will be tangential or normal.
- Splines are very powerful tools that are commonly used. If you have created a spline
 using control vertices, you can move these vertices around to change the shape of the
 spline. If you hvae created a spline using interpolation points, you can either move
 around the interpolation points or adjust the "handles" of the spline these are construction lines that appear when you click on the spline, and represent the tangent lines
 at the interpolation points.

Projecting Geometry

The Project Geometry feature is a very powerful tool which allows you to copy existing geometry, whether 2D or 3D, to your current sketch. Try to always project geometry which is above the current sketch in the model browser. Generally, projected geometry is adaptive, which means changes to the reference geometry will be reflected in your sketch. To prevent this, hold down CTRL when projecting geometry, right click on the geometry and select Break Link , or manually delete the Project Geometry Constraint (ref. Constraints). There are the following options:

- Project Geometry: Projects 2D sketches, 3D sketches, object edges and more into your sketch.
- Project Cut Edges: Projects a 3D object or surface as if the sketch was to cut through the cross-section of it.

- Project Flat Pattern: Used predominately in sheet metal projects, unfolds an object into the plane.
- Project to 3D Sketch: Used to project your 2D sketch onto a 3D surface. For more information on this group of features, see 3D Sketches or 3D Model ► Surface.
- Project DWG Geometry: Allows you to copy a DWG (drawing) file from your workspace into a sketch. Not very useful for most scenarios.

Geometry Patterns

Inventor allows you to duplicate geometries to streamline your work. Geometry can be mirrored or repeated in a circular or rectangular pattern. The patterns are associative, so changes to any one of the object instances will change the entire pattern.

Modifying Existing Geometry

The Modify tab allows you to make changes to geometry you have already created. You can:

- Move geometry
- · Copy geometry to a new location
- · Rotate geometry
- Scale geometry
- Trim parts of your geometry off by points of intersection
- Extend a line or other geometry until it intersects with another geometry
- Split geometry into multiple parts according to points of intersection.
- Stretch certain geometry out
- Offset geometry by creating a slightly larger or smaller copy.

Tips and Tricks

- You can change how Inventor treats dimensions and constraints (i.e if it breaks constraints or throws an error) by clicking the button on the popup dialog of the modify tools and changing the settings.
- By checking the Precise Input box on the popup dialog of many of these tools, you can specify the exact coordinates with which you want to modify your geometry with.

 You can choose whether an offset geometry adapts to changes in the original geometry by right clicking when using the Offset tool and toggling Constrain Offset . Under these options, you can also change whether Inventor offsets entire loops or single line/curve segments.

Constraints and Dimensions

Constraints and dimensions determine the relationships between geometries. If a sketch is not fully constrained, it means that you can freely move it around by simply clicking and dragging. We recommend that, in general, you fully constrain all sketches. The bottom right of your workspace will tell you how many more dimensions/constraints you would need to achieve this.

Dimensions

Dimensions allow to you to display and specify the length or angle between two pieces of geometry. Dimensions can also be added when creating geometry, by pressing Tab to toggle between possible dimensions. The following dimensions can be created (noting that curves are usually dimensioned by the center point):

- 1. The distance or angle between two lines
- 2. The distance between two curves/points. Drag the cursor to specify if this distance is vertical, horizonal or euclidean (by clicking between two points).
- 3. A line and curve/point: the distance between them in the direction orthogonal to that of the line

Two types of dimensions can be created: regular dimensions and driven dimensions. Driven dimensions are dimensions which are redundant (already specified by existing constraints/dimensions), and thus are only used to display measurements. They are signified by brackets. On the other hand, regular dimensions can be edited to change the geometry. Regular dimensions can be made and unmade driven with Format ▶ Driven Dimension or Right Click ▶ Driven Dimension .

Dimensions can be edited by double clicking on the dimension. The formatting of the dimension can be modified by Right Click ▶ Dimension Properties, allowing you to specify naming, precision, and tolerance type for both the individual dimension and the default settings.

Types of Constraints

Constraints allow you to set relationships between two pieces of geometry. The types of constraints are:

1. Coincident: a point is constrained to another point or along another curve

- 2. Collinear: two straight lines (or axes) constrained to lie along the same line
- 3. Concentric: two curves, ellipses or circles constrained to the same center point
- 4. Fixed: locks geometry in place
- 5. Parallel: two lines constrained to lie parallel
- 6. Perpendicular: two lines constrained to lie perpendicular
- 7. Horizontal: a line or pair of points constrained parallel to the x axis
- 8. Vertical: a line or pair of points constrained parallel to the z axis
- 9. Tangent: two curves constrained to be tangent to each other
- 10. Smooth: a splined curve constrained to be tangent to and join endpoints with a curve
- 11. Symmetric: two curves constrained to be symmetric about a third selected line
- 12. Equal: two curves constrained to have the same radius or two lines constrained to have the same length
- 13. Project Geometry: essentially a fixed constraint, it cannot be added to geometry but instead is automatically applied to any projected geometry. If you want to edit projected geometry, you need to remove these constraints.

Adding Constraints

Constraints can be added through the Constrain tab. Select the desired constraint in the tab and then select the geometry to be constrained. For some constraints such as the fixed or equal constraint, you can select multiple geometry and then click on the desired constraint to apply to all.

Viewing and Editing Constraints

All constraints can be viewed by right clicking on the workspace and selecting

Show All Constraints or using the F8 hotkey. Constraints can be hidden by right clicking on the workspace and selecting Hide All Constraints or using the F9 hotkey.

To toggle the visibility of a selected geometry's constraints, click on the Show Constraints icon under the Constrain tab in the ribbon.

To delete all constraints from geometry, select the desired geometry, press right click and select Delete Constraints.

To delete specific constraints, show constraints either by using F8 or selecting the parent geometry, click on the respective constraint icon beside the geometry and press DEL.

Constraint Inference, Relax Mode and Settings

Sometimes constraints can be automatically added while placing geometry. For example, drawing a line which is horizontal will create an inferred horizontal constraint. If you find that a constraint is being inferred with the wrong geometry, you can first mouseover ("scrub") the desired geometry. You can temporarily disable inferred constraints by holding CTRL when placing geometry.

Inferred constraints can be persistent or non-persistent. Persistant constraints remain after the geometry is placed, however non-persistent constraints will not, and will only help you while placing geometry. In general, inferred constraints will appear as a small grey box when you are creating geometry. They will also either include yellow/green points (for coincident constraints) or solid lines (for other constraints). Any dotted lines that appear are NOT inferred constraints and are merely guide lines that will not persist (though otherwise they behave similarly).

Usually, constraints will restrict you from freemoving geometry. For example, if you have two circles with a concentric constraint, moving one circle will also cause the other to move. When Relax Mode is enabled, geometry can be moved freely. Instead of also moving constrained geometry, any constraints which are broken will be deleted. In the above case, only the selected circle will move and the concentric constraint will be removed. You can also choose to only enable Relax Mode for specific constraint types.

Settings for constraints can be modified under Constrain ► Constraint Settings You can:

1. Under Inference, turn all inferred constraints on/off

reference objects in the model browser.

- 2. Under Inference , turn specific inferred constraints on/off, such as turning off any inferred horizontal constraints
- 3. Under Inference , choose to infer parallel/perpendicular constraints over horizontal / vertical constraints, when there is an option
- 4. Enable Relax Mode

You can also edit the scope at which constraints are inferred. Under Constrain ► Constraint Inference Scope , the three options are:

- 1. Geometry in current command: constraints will only be inferred with the same type of geometry (e.g line, arc, rectangle). Remember that guide lines will still appear with reference to other geometry types.
- 2. All geometry: constraints will be inferred with all geometry, regardless of type or location.
- 3. Select: you can choose which pieces of geometry constraints can be inferred with.

 It is also possible to realign a coordinate system, either by relocating the origin or the two axes. Select Constrain ▶ Edit Coordinate System, and then relocate either the origin by clicking on a new vertex or the axis/axes by clicking on new edges. To flip the direction of the axes, right click and select the appropriate option. You may need to move the camera in order to do this, and remember that your sketch needs to be below any

Automatic Dimensions

By selecting Constrain ► Automatic Dimensions and Constraints , dimensions and constraints can be added to fully paramaterise the sketch. This is a very powerful tool!

Formatting

The graphic display of geometry can be adjusted under Format . Construction formatting identifies geometry as being a scaffold to the sketch and not part of the final product, such as radius lines. These are still visible and can be dimensioned/constrained, however cannot be used for extrusions or any other 3D feature. Some shapes, such as center point rectangles, automatically come with construction lines, and in order to use these lines for 3D features it must be disabled in the same way construction lines are enabled.

Centerline formatting signifies a line being a symmetric center of geometry, and behaves in the same way as construction lines. Center points have the same philosophy.

Geometry can also be custom formatted by changing the pattern, colour and weight. These custom formats can be turned on/off by clicking Format ► Show Format .

Layout

Assembly and Component Layouts

This is part of a more complex feature of Inventor which comprises of creating hierarchies of assemblies, components and parts. In short, the Make Part and

Make Components features allows you to import 2D sketches into assemblies as layout parts. This is useful because you can create 3D features in the assembly without changing the layout file, and as such these files can be used concurrently for multiple projects. This will be covered in a later section and is not a necessary tool to know.

Sketch Blocks

Sketch blocks are similar to object grouping in Microsoft Office; it allows you to constrain portions of sketches to be fixed relative to each other, and instead of moving each piece of individual geometry the entire block moves. This is especially useful if you copy and paste a lot of sketch data from other applications or do a lot of sketching

over images - it removes the need to constrain every line and curve. Sketch blocks can be created under Layout ► Create Block

Insert

Inserting Images

Images can be inserted into a 2D sketch under Insert ▶ Image , and behave like construction-formatted rectangles in terms of geometry. Inserting images is a fantastic way to model objects that do not have CAD files, as you can use them to freehand outlines - learn how to create 3D models from just 2D profile images in the 3D Sketch section!

Inserting Points Spreadsheets

If you have a large number of points that you want to copy into modelling software - such as from point cloud scanners - your best option is to import it via an excel spreadsheet. Your first row should contain only your units specification, your second row should contain the headings x, y and (optionally) z. Each subsequent row should represent the coordinates of one point.

Inserting AutoCAD Files

If you use AutoCAD to create drawings, you can import 2D drawings into a sketch here. This should work for any DWG or DXF file.

Managing 2D Sketches

After creating a sketch, there are several things you can do:

Right Click on the sketch under the part navigator and you can:

- Redefine: if you want to move a sketch from one plane to another. To see the current sketch plane, select Show Input.
- To change the appearance properties of the sketch, such as colour and line style.

- Engineer's Notebook: The Engineer's Notebook allows you to log your progress through the design stage. You can add a note in your notebook about your sketch by selecting Create Note.
- Export: You can export your sketch as a drawing format.
- Visibility: You can toggle the visibility of the entire sketch and the sketch dimensions.

Parameters

The majority of information about parameters will be covered in a later section, however they are very commonly used for sketches. With parameters, instead of specifying numeric values for dimensions, you can instead assign a global variable to it, which you can change later at will. This is useful if you have multiple dimensions which reference the same physical measurement, or if you want to create a series of the same object but with different sizings - such as for screws. Two useful things you can do with parameters are:

- · Link your parameters with an excel file that you can adjust in real time
- · Import and export parameters from XML files
- · Share parameters between files

More Sketch Options

While still in your sketch, you can Right Click on the workspace and:

- Degrees of Freedom: Wither on the workspace or for a specific piece of geometry, you can display the degrees of freedom present. This is useful to make sure that you have enough dimensions - if you don't, you will see which directions have not been constrained yet.
- Slice Graphics / Hide Others: If you find that other pieces sketches and 3D features
 are being obstructive, you can either completely isolate the sketch by selecting
 Hide Others or cut through the existing 3D features by selecting Slice Graphics.
- By selecting Region Properties , you can analyse the important geometric features of an area in your sketch, including moments of inertia and radii of gyration.
- Curvature Lines: if you want to project the radial and angular lines of a curve outwards, you can right click on the curve and select Display Curvature . To change the settings of these lines, select Setup Curvature Display .

3D Sketches

2D vs 3D Sketches

Drawing 3D Sketches

Projecting and Combining 3D Sketches

3D Constraints

Modifying 3D Sketches

3D Modelling

section

This is where all the magic happens! Transform sketches into 3D features, surfaces and more.


Creating Features

Types of Features: At a Glance

- Extrude: takes a cross-section from a 2D sketch and extrudes it into a prism.
- Revolve: takes a section from a 2D sketch and rotates it around a specified axis.
- Sweep: takes a cross-section from a 2D sketch and pulls it along a 2D/3D path to create a pipe-like solid.
- Loft: creates an object that transitions between multiple cross-sections.
- Coil: takes a profile and transforms it into a helical, spiraled or threaded object around a specified axis.
- Emboss: takes text or other geometry and engraves or embosses it onto an object.
- Decal: wraps an image to a face or multiple faces.
- Rib: adds ribbed or webbed support walls to an object.
- Import: allows you to import other CAD formats into your Modelling.
- Unwrap: unwraps a solid body, often of sheet metal, until it becomes flat.
- Derive: allows you to import an Inventor model to form the base of the current part, which you can then build on top of and is adaptive.

Examples of When to use Features

- Extrude: you want to create basic objects, prisms and boxes.
- Revolve: you have a solid of revolution that you would like to model, such as a sphere or torus.
- Sweep: you would like to design an intricate slide, so you take the cross-section of the slide and sweep it around your 3D path.
- Loft: you identify using stress analysis two major load areas in a solid body, one large area and one small area. You would like to add structure between these areas to reinforce it, so you use a loft to create a solid that transitions from the large area to small area.



- Emboss: you would like to engrave your brand name and logo into your products.
- Decal: you have a vehicle or other product that would be manufactured with an image printed on it.
- Rib: you have a corner that you would like to reinforce by adding a diagonal brace.
- Import: you have a model in a different format but want to use it as in Inventor part.
- Unwrap: you have a sheet metal object and want to unwrap it to give you a clear idea of how to manufacture the part prior to applying bends.
- Derive: you have a 3D modelled product and want to personalise it by adding an engraving. Insert the generic part with the Derive tool, and then add an your engraving. Changes to the generic part will update in the new part, but adding an engraving in the new part will not add it to the old part.

Common Options

When using the Create tools above, most of them have options which allow you even more flexibility with 3D modelling:

- Surface Mode: Instead of creating a solid object, you can instead create a surface. For example, instead of a sweep creating a solid pipe it will create a hollow one.
- Profiles: the cross-sections you want to be turned into 3D features. You can often choose multiple, and they don't always have to be in the same sketch, plane or even the same orientation.
- Presets: if the Create tool has many different parameters, you can create presets to speed up your workflow
- Direction: direction can either be default, flipped, symmetric (same distance in each direction) or asymmetric (different distance in each direction)
- Solid body: a part can be comprised of several distinct bodies. When creating a feature, you can choose which solid body it will be incorporated into.
- Output (Boolean): the type of operation being performed. You can join the 3D feature to an existing solid body, cut the feature away from the body, take the intersection between the feature and body or create an entirely new solid.
- Numerical Values: when entering numerical values, you can often click the arrow beside
 the input box to quickly measure dimensions, access recently used values or tell Inventor
 to use an existing dimension as a reference (updating the dimension in the future will
 also update the feature).
- Keep Sketch Visible: under the hamburger menu on the top right of the popup dialog, you can specify to keep the sketch visible after executing the feature. This allows it to be reused.

Additional Options: Extrusions

• From (Start Plane): you can choose the plane the extrusion will start at - it does not have to be the sketch plane!

- Distance (End Plane): you can specify how far the profile extrudes by:
 - Manual Distance: specify the numerical distance of extrusion
 - Through All: the extrusion will pass through all objects (for cut or intersect extrusions only).
 - To: select the plane or feature that the extrusion will end at. For curved planes,
 Alternate Solution specifies to choose the closest side of the curved surface.
 - To Next: the extrusion will end at the next feature or plane. Said feature or plane should entirely overlay the cross-section profile.
- Taper: the extrusion tapers slightly inwards or outwards

Additional Options: Revolve


- From (Start Plane): you can choose the plane the revolution will start at it does not have to be the sketch plane!
- Distance (End Plane): you can specify how far the profile revolves by:
 - Manual Angle: specify the numerical angle of revolution.
 - Full: a 360 degree revolution.
 - To: select the plane or feature that the extrusion will end at. For curved planes,
 Minimum Solution specifies to choose the closest side.
 - To Next: the extrusion will end at the next feature or plane. Said feature or plane should entirely overlay the cross-section profile.

Additional Options: Sweep

- Path: Choose the path (a 2D/3D curve or edge) for the profiles to follow. It does not necessarily have to intersect the profiles, but the path must intersect the profile plane.
- Behaviour: Determines how the profile follows the path:
 - Follow Path: the profile is swept along the path, where every cross section taken normal to the path stays constant. Adjust the twist and taper as necessary 360 degree twist corresponds to one single twist, and positive/negative taper corresponds to a widening/narrowing of the sweep away from the start point.
 - Fixed: the profile is swept along the path, where the cross section taken parallel to profile plane stays constant. Twist and taper are not available.
 - Guide: the profile is swept along a path in the same manner as Follow Path. A second guide rail is used to determine how the profile scales (either in one or both directions) along the path - it guides the outside of the sweep.

Additional Options: Loft

• Sections: the cross-sections for the loft to transition through. You need at least two profiles, however they do not have to be in parallel planes. You can also loft between



- · Rails: the paths for the loft to follow
- Behaviour: how the rails are treated either as outer rails or center lines.
- Conditions: allows you to control what angle the loft meets the sections at (i.e tangent to the plane)
- Closed Loops: joins the last section to the first section to form a closed loop object.
- Merge Tangent Faces: blends together faces that end up tangent with each other.
- Transition:

Additional Options: Coil

- Axis: the axis the sketch will coil about. An internal axis will create a threaded object, and an external axis will create a helical object.
- Behaviour: controls the physical properties of the coil, such as pitch height and revolution. Allows you to create a spiral (no vertical displacement)

Additional Options: Emboss

- Behaviour: determines whether the emboss raises up or recesses into the object. There
 is a third option, Emboss/Engrave From Plane, which allows you to create an emboss/engraving
 where the depth changes. In this option, you can also transition from an emboss to an
 engraving, which is a very powerful tool.
- Taper: allows you to determine how the profile tapers (scales) when Emboss/Engrave From Plane is enabled.
- Appearance: allows you to automatically change the visual appearance of the emboss
- Wrap to Face: if embossing on a curved face, allows the emboss to follow the curve around. With this enabled, the emboss will always have the same depth at every location.

Additional Options: Decal

Automatic Face Chain: the image automatically wraps over adjacent faces.

Additional Options: Derive

- Derive Style: determines how the solid bodies of the derived part import.
- Status: allows you to select which elements of the part will be imported.
- Options: more options which, most importantly, allows you to scale and flip the part before importing.

Additional Options: Import

• Import Options: some file types have additional options (beside the "Open" button) which allows you to control the unit imported, change the subformat and more.

Additional Options: Rib

- Style: allows you to specify whether the ribs are created parallel or normal to the sketch plane. This is not important for basic ribs, but further customisation usually requires the style to be Normal to Sketch Plane
- Thickness: determines the thickness of the ribs. The direction this thickness refers to depends on the style.
- Hold Thickness (Normal to Sketch Plane ¿ Draft): specifies whether the quoted thickness is taken from the top or bottom of the taper
- Draft Angle (Normal to Sketch Plane ¿ Draft): adds a taper to the normal face of the rib.
- Boss: allows you to create ribs for bosses (which are like standoffs and usually have ribs on both sides).
- Distance: determines the thickness of the ribs in the other direction.

Additional Options: Unwrap

- Auto Face Chain
- Alignment
- Behaviour

Primitives

Primitives provide shortcuts to easily create basic features: a box, sphere, cylinder or torus. These features just reuse the Create features detailed above.

Modifying 3D Features

You can apply the following modifiers to change already existing 3D features. It is often better practice to use one of these tools, such as the Hole feature, instead of incorporating a hole into your sketch for the 3D features.

Modifiers

- · Hole: allows you to create holes of all kinds
- Fillet: rounds out sharp edges and corners
- Chamfer: applies a bevel to sharp edges and corners
- · Shell: hollows out an object
- · Draft: angles existing faces
- Thread: adds a thread to faces (including holes)
- Combine: takes two solid bodies and joins, cuts or intersects them (the same options as 3D Create Features)
- · Thicken/Offset: thickens or thins faces
- · Split: Splits solids and faces apart along planes, sketches or surfaces
- Mark: adds text and other markings to faces. In essence, this splits the face and uses the border lines to show the marking
- · Delete Face: removes selected faces, leaving the other faces on the 3D feature intact
- · Move Bodies: allows you to move around solid bodies in relation to each other
- · Bend Part: takes an object and bends it over a line
- · Copy Object: duplicates objects
- Direct Edit: allows you to edit imported models

Patterning 3D Features

Freeform 3D Modelling

Surfaces

Simplifying 3D Models

Plastic Parts

Insert

Harness

The Shape Generator

Shape Generator is Autodesk Inventor's version of generative design, which is a powerful feature which takes a load scenario and creates highly optimised structural designs.

Feature Management

Assemblies

Placing Components

Creating Components and Adaptivity

Relationships

Patterning Components

Productivity Optimisation

Simplifying

Contact Sets

Managing Components

Design Accelerators

Fasteners

Frames

Power Transmission

Springs

Inspecting and Analysing

Component and Assembly Stress Analysis

Autodesk Nastran

Graphical Analysis

Tolerance Analysis

Interference Analysis

Dynamic Simulation

Frame Analysis

Annotations

General Annotations and Notes

Exproting Annotations

Inventor Studio

Creating Drawings

Presentations

Sheet Metal





BIM

Fusion Interoperability

3D Printing Compatability

Electromechanical Linking

Piping and Tubing

Cables and Harnesses

Mold Design

Weldments

Nesting

Task Scheduling, iLogic and Inventor SDK

Acknowledgements and Copyright

Copyright (C) 2007 Free Software Foundation, Inc. https://fsf.org/.

This document was created wholly by Benjamin Tran for the UQ Mechatronics and Robotics Society (UQ MARS). We believe in the sharing of educational resources, so this document is currently licensed under the GNU General Public License. For future revisions, this license is subject to change without notice. Please credit either Benjamin Tran or UQ MARS upon distribution.

To access more resources like this, check out https://uqmars.com/.

