WARM UP (*From Phạm Nguyên Khang course*)

- **Read Carefully Before Start Quizzes**
  - Only print **required things**
  - Generally, you SHOULD NOT use **printf()** before **scanf().**
  - You MUST NOT use **Non ANSI C** libraries (e.g: conio.h)
  - The template of main() function is

```
int main() {
 //Your code goes here

 return 0;
}
```

You SHOULD NOT use:

```
void main() {
 //Your code goes here

 return 0;
}
```


- **Function printf()**
  - print something into the screen in format, ex:

```
printf("Hello, world");
```

print **Hello, world**

```
printf("Hello, world\n");
```

print **Hello, world** and **newline**

```
printf("Peter said: \"Hello\"");
```

print **Perter said: "Hello"**

```
printf("This is \\ character.");
```

print This is \ character

Some special characters:

- \b: Backspace
- \n: newline
- \t: Tab

- \\: \
- \': '
- \": "
- \nnn: the character whose ASCII code is nnn in decimal
- \xhh: the character whose ASCII code is hh in hexadecimal

WARM UP (*From Phạm Nguyên Khang course*)

- **Read Carefully Before Start Quizzes**
  - Only print **required things**
  - Generally, you SHOULD NOT use **printf()** before **scanf().**
  - You MUST NOT use **Non ANSI C** libraries (e.g: conio.h)
  - The template of main() function is

```
int main() {
 //Your code goes here

 return 0;
}
```

You SHOULD NOT use:

```
void main() {
 //Your code goes here

 return 0;
}
```


- **Function printf()**
  - print something into the screen in format, ex:

```
printf("Hello, world");
```

print **Hello, world**

```
printf("Hello, world\n");
```

print **Hello, world** and **newline**

```
printf("Peter said: \"Hello\"");
```

print **Perter said: "Hello"**

```
printf("This is \\ character.");
```

print This is \ character

Some special characters:

- \b: Backspace
- \n: newline
- \t: Tab
- \\: \
- \': '
- \": "
- \nnn: the character whose ASCII code is nnn in decimal
- \xhh: the character whose ASCII code is hh in hexadecimal