

Tran Quoc Long - 14520490

Clustering with face datasets

Step in brief

1. Divide examined window into cells (16x16)
2. For each pixel in a cell, compare to 8 neighbors, Follow along a circle
3. Assign "number" "0" for pixel whose value is greater than the center, and "1" for the others
4. Compute the histogram of frequency of each "number" occurring -> 16*16 = 256-dimensional feature vector
5. Optionally normalize the histogram
6. Concatenate (normalized) histogram of all cells -> Feature vector for entire window

```
In [1]: from sklearn.datasets import fetch_lfw_people
import matplotlib.pyplot as plt
import matplotlib.image as mpimg
```


```
In [2]: # Load data set
lfw_people = fetch_lfw_people()
```

```
In [3]: lfw_people.images.shape
```

```
Out[3]: (13233, 62, 47)
```

```
In [4]: %matplotlib inline
plt.matshow(lfw_people.images[0])
```

```
Out[4]: <matplotlib.image.AxesImage at 0x12eb3160320>
```



```
In [5]: def plot_gallery(images, titles, h, w, n_row=3, n_col=4):
        """Helper function to plot a gallery of portraits"""
        plt.figure(figsize=(1.8 * n_col, 2.4 * n_row))
        plt.subplots_adjust(bottom=0, left=.01, right=.99, top=.90, hspace=.35)
        for i in range(n_row * n_col):
            plt.subplot(n_row, n_col, i + 1)
            plt.imshow(images[i].reshape((h, w)), cmap=plt.cm.gray)
            plt.title(titles[i], size=12)
            plt.xticks(())
            plt.yticks(())
```

```
In [ ]:
```

Test functions on 1 image

```
In [6]: from skimage.feature import local_binary_pattern
```

```
In [7]: # settings for LBP
        radius = 4
        n_points = 8
        METHOD = 'uniform'

        image = lfw_people.images[0]

        #LBP
        lbp_features = local_binary_pattern(image, n_points, radius)
```


```
In [8]: print(lbp_features)
print('cccc')
lbp_features.shape
```

```
[[ 192.  192.  193. ..., 112.  112.  32.]
 [ 192.  193.  193. ..., 112.  112.  48.]
 [ 193.  193.  193. ..., 112.  112.  48.]
 ...,
 [   4.   4.   4. ..., 28.   8.  12.]
 [   6.   4.  12. ...,   8.   0.   0.]
 [   6.   4.  12. ...,   8.   0.   0.]]
cccc
```

```
Out[8]: (62, 47)
```

```
In [36]: plt.imshow(lbp_features)
```

```
Out[36]: <matplotlib.image.AxesImage at 0x25901b4b5f8>
```



```
In [37]: import numpy as np
data = np.histogram(lbp_features, bins = range(0,257))
print('data:\n', data)
```

data:

```
(array([180, 42, 15, 32, 41, 5, 15, 35, 23, 1, 4, 4, 47,
        3, 34, 56, 50, 6, 0, 1, 3, 1, 1, 2, 39, 4,
        1, 1, 59, 5, 64, 44, 31, 3, 4, 6, 1, 0, 0,
        4, 2, 1, 1, 1, 6, 0, 2, 3, 44, 1, 7, 2,
        3, 0, 3, 5, 90, 1, 2, 6, 90, 7, 25, 29, 49,
        14, 5, 9, 9, 1, 5, 2, 5, 1, 2, 0, 4, 0,
        2, 9, 1, 0, 0, 0, 1, 0, 1, 1, 9, 2, 1,
        0, 14, 1, 3, 0, 25, 1, 0, 5, 4, 1, 2, 2,
        9, 2, 1, 1, 2, 0, 0, 6, 81, 4, 0, 3, 1,
        1, 3, 0, 133, 5, 1, 1, 74, 3, 23, 14, 25, 48,
        2, 41, 2, 6, 3, 63, 3, 0, 3, 0, 4, 1, 3,
        25, 0, 7, 0, 0, 0, 0, 0, 5, 3, 3, 1, 2,
        4, 3, 0, 11, 1, 1, 0, 6, 0, 1, 0, 10, 1,
        0, 0, 1, 0, 0, 0, 1, 2, 0, 0, 3, 0, 0,
        1, 8, 4, 3, 2, 4, 4, 1, 3, 34, 34, 79, 5,
        89, 5, 6, 2, 49, 0, 0, 0, 3, 1, 1, 0, 8,
        5, 3, 0, 3, 1, 1, 0, 4, 3, 0, 1, 0, 0,
        0, 2, 13, 13, 22, 2, 25, 3, 3, 6, 19, 3, 2,
        0, 6, 8, 7, 17, 44, 22, 15, 0, 7, 5, 4, 3,
        15, 16, 13, 7, 13, 19, 12, 48, 101], dtype=int64), array([ 0,
        1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12,
        13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25,
        26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38,
        39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51,
        52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64,
        65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77,
        78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90,
        91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103,
        104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116,
        117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129,
        130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142,
        143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155,
        156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168,
        169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181,
        182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194,
        195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207,
        208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220,
        221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233,
        234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246,
        247, 248, 249, 250, 251, 252, 253, 254, 255, 256]))
```

```
In [38]: test = lbp_features.reshape(-1)
print(len(data[0]))
print(len(data[1]))
```


256
257

```
In [39]: sum(test == 0)
```

```
Out[39]: 180
```


```
In [40]: fig = plt.figure(figsize = [20,5])
fig.suptitle('Histogram', fontsize = 20)
plt.hist(lbp_features.reshape(-1),bins=list(range(0,257)))
```

```
Out[40]: (array([ 180.,  42.,  15.,  32.,  41.,   5.,  15.,  35.,  23.,
    1.,   4.,   4.,  47.,   3.,  34.,  56.,  50.,   6.,
    0.,   1.,   3.,   1.,   1.,   2.,  39.,   4.,   1.,
    1.,  59.,   5.,  64.,  44.,  31.,   3.,   4.,   6.,
    1.,   0.,   0.,   4.,   2.,   1.,   1.,   1.,   6.,
    0.,   2.,   3.,  44.,   1.,   7.,   2.,   3.,   0.,
    3.,   5.,  90.,   1.,   2.,   6.,  90.,   7.,  25.,
   29.,  49.,  14.,   5.,   9.,   9.,   1.,   5.,   2.,
    5.,   1.,   2.,   0.,   4.,   0.,   2.,   9.,   1.,
    0.,   0.,   0.,   1.,   0.,   1.,   1.,   9.,   2.,
    1.,   0.,  14.,   1.,   3.,   0.,  25.,   1.,   0.,
    5.,   4.,   1.,   2.,   2.,   9.,   2.,   1.,   1.,
    2.,   0.,   0.,   6.,  81.,   4.,   0.,   3.,   1.,
    1.,   3.,   0.,  133.,   5.,   1.,   1.,  74.,   3.,
   23.,  14.,  25.,  48.,   2.,  41.,   2.,   6.,   3.,
   63.,   3.,   0.,   3.,   0.,   4.,   1.,   3.,  25.,
    0.,   7.,   0.,   0.,   0.,   0.,   0.,   5.,   3.,
    3.,   1.,   2.,   4.,   3.,   0.,  11.,   1.,   1.,
    0.,   6.,   0.,   1.,   0.,  10.,   1.,   0.,   0.,
    1.,   0.,   0.,   0.,   1.,   2.,   0.,   0.,   3.,
    0.,   0.,   1.,   8.,   4.,   3.,   2.,   4.,   4.,
    1.,   3.,  34.,  34.,  79.,   5.,  89.,   5.,   6.,
    2.,  49.,   0.,   0.,   0.,   3.,   1.,   1.,   0.,
    8.,   5.,   3.,   0.,   3.,   1.,   1.,   0.,   4.,
    3.,   0.,   1.,   0.,   0.,   0.,   2.,  13.,  13.,
   22.,   2.,  25.,   3.,   3.,   6.,  19.,   3.,   2.,
    0.,   6.,   8.,   7.,  17.,  44.,  22.,  15.,   0.,
    7.,   5.,   4.,   3.,  15.,  16.,  13.,   7.,  13.,
   19.,  12.,  48.,  101.]),
array([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  9, 10, 11, 12,
   13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25,
   26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38,
   39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51,
   52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64,
   65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77,
   78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90,
   91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103,
  104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116,
  117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129,
  130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142,
  143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155,
  156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168,
  169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181,
  182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194,
  195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207,
  208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220,
  221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233,
  234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246,
  247, 248, 249, 250, 251, 252, 253, 254, 255, 256])),
<a list of 256 Patch objects>)
```



```
In [41]: fig2 = plt.figure(figsize = [20,5])
fig2.suptitle('Histogram', fontsize = 20)
plt.bar(range(len(data[0])),data[0], align='center')
```

Out[41]: <Container object of 256 artists>



Process for all images in dataset

Extract LBP features of Images

```
In [42]: def get_LBP_feature(mLBP_of_Image):
return np.histogram(mLBP_of_Image, bins = range(0,257))
```

```
In [43]: #compute local binary pattern
def pre_Compute(image):
    n_points = 8
    radius = 4
    return local_binary_pattern(image, n_points, radius)
```

```
In [44]: #Process all images and store to list
list_Features = []
for image in lfw_people.images:
    lbp_value = pre_Compute(image)
    feature_vector = get_LBP_feature(lbp_value)
    list_Features.append(feature_vector[0])
```

```
In [46]: print(len(list_Features)) # to check if list contained enough element
```

```
13233
```

```
In [47]: print(list_Features[0])
```

```
[180  42  15  32  41   5  15  35  23   1   4   4  47   3  34  56  50   6
   0   1   3   1   1   2  39   4   1   1  59   5  64  44  31   3   4   6
   1   0   0   4   2   1   1   1   6   0   2   3  44   1   7   2   3   0
   3   5  90   1   2   6  90   7  25  29  49  14   5   9   9   1   5   2
   5   1   2   0   4   0   2   9   1   0   0   0   1   0   1   1   9   2
   1   0  14   1   3   0  25   1   0   5   4   1   2   2   9   2   1   1
   2   0   0   6  81   4   0   3   1   1   3   0 133   5   1   1  74   3
  23  14  25  48   2  41   2   6   3  63   3   0   3   0   4   1   3  25
   0   7   0   0   0   0   0   5   3   3   1   2   4   3   0  11   1   1
   0   6   0   1   0  10   1   0   0   1   0   0   0   1   2   0   0   3
   0   0   1   8   4   3   2   4   4   1   3  34  34  79   5  89   5   6
   2  49   0   0   0   3   1   1   0   8   5   3   0   3   1   1   0   4
   3   0   1   0   0   0   2  13  13  22   2  25   3   3   6  19   3   2
   0   6   8   7  17  44  22  15   0   7   5   4   3  15  16  13   7  13
  19  12  48 101]
```

```
In [48]: from sklearn.cluster import spectral_clustering
from sklearn.feature_extraction import image
from sklearn.metrics.pairwise import cosine_similarity
```

```
In [ ]: graph = cosine_similarity(np.array(list_Features))
labels_spectral = spectral_clustering(graph, n_clusters = 5749)
```

```
In [ ]:
```

Using KMEANS to cluster

```
In [49]: from sklearn.cluster import KMeans
import time
```

```
In [50]: start = time.time()

nClusters = 5749
kmeans_model = KMeans(nClusters)
face_labels = kmeans_model.fit_predict(list_Features)

end = time.time()
```



```
In [25]: print(len(face_labels))
clustering_time = end - start
print('Time: ', clustering_time, '(s)')
```

13233

Time: 989.8880825042725 (s)

Linear dimensionality reduction using Singular Value Decomposition of the data to project it to a lower dimensional space.


```
In [28]: from sklearn.decomposition import PCA

nComponents = 3 # 3-dim
vPCA = PCA(nComponents)
digitData_to_3D = vPCA.fit_transform(lfw_people.data)
```

```
In [54]: from mpl_toolkits.mplot3d import Axes3D

fig = plt.figure(figsize = (20,10))
#plt.scatter(digitData_to_3D[:,0], digitData_to_3D[:,1], digitData_to_3D[:,2], c=
ax = Axes3D(fig)
ax.scatter(digitData_to_3D[:,0], digitData_to_3D[:,1], digitData_to_3D[:,2],
          c=face_labels, edgecolor='k', s = 20)
#set_title('Visulization Result - K-measns')
```

Out[54]: <mpl_toolkits.mplot3d.art3d.Path3DCollection at 0x22607a18cc0>



```
In [51]: from mpl_toolkits.mplot3d import Axes3D
```

```
fig = plt.figure(figsize = (20,5))
fig.suptitle('Visualization of faces clustering', fontsize=20)

ax = fig.add_subplot(1,2,1)
plt.scatter(digitData_to_3D[:,0], digitData_to_3D[:,1], c= face_labels, s=5)
plt.title('2d representation of clusters')

ax = fig.add_subplot(1,2,2)
plt.scatter(digitData_to_3D[:,1], digitData_to_3D[:,2], c= face_labels, s=5)
plt.title('Another 2d representation of clusters')
```

```
Out[51]: <matplotlib.text.Text at 0x22606252fd0>
```



```
In [62]: print(lfw_people.target)
print(len(lfw_people.target))
```

```
[5360 3434 3807 ..., 2175 373 2941]
13233
```

Face clustering on 4 methods

```
In [30]: #import libs
from time import time
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
import matplotlib.image as mpimg
```

```
In [31]: #import scikit-learn
from sklearn import metrics
from sklearn.cluster import KMeans, spectral_clustering, DBSCAN, AgglomerativeClu
from sklearn.datasets import load_digits
from sklearn.neighbors import DistanceMetric
from sklearn.metrics.pairwise import cosine_similarity
from sklearn.datasets import fetch_lfw_people
from sklearn.preprocessing import StandardScaler
```

```
In [32]: # Load data set
lfw_people = fetch_lfw_people(min_faces_per_person=70, resize=0.4)
'''
It took lots of time on full dataset, but there're a bunch of clusters just conta
So I just select face with min_face = 70
'''
```

```
Out[32]: "\nIt took lots of time on full dataset, but there're a bunch of clusters just
contain 1 face (test above).\nSo I just select face with min_face = 70\n"
```

```
In [33]: lfw_people.images.shape
```

```
Out[33]: (1288, 50, 37)
```

```
In [34]: print(np.unique(lfw_people.target)) #number of faces/clusters expected

[0 1 2 3 4 5 6]
```

Extract LBP features of Images from loaded dataset

```
In [35]: from skimage.feature import local_binary_pattern
```

```
In [36]: def get_LBP_feature(mLBP_of_Image):
    return np.histogram(mLBP_of_Image, bins = range(0,257))
#compute local binary pattern
def pre_Compute(image):
    n_points = 8
    radius = 4
    return local_binary_pattern(image, n_points, radius)

#Process all images and store to list
data = []
for image in lfw_people.images:
    lbp_value = pre_Compute(image)
    feature_vector = get_LBP_feature(lbp_value)
    data.append(feature_vector[0])
```

```
In [37]: print(data[0])
```

```
[ 89   6  33  20  36   7  34  26  10   0   0   0  17   0  33  13  57  10
   1   4   4   0   1   1  44   1   2   1 119   0  85  16  20   1   2   0
   8   1   3   1   0   0   0   0   1   0   4   1  78   0   1   0   9   0
   0   0  61   0   2   1  84   3  31  14  19   1   2   6   6   2   3   4
   1   1   1   0   2   1   3   2   3   0   0   0   0   0   0   1   2   2
   0   1   1   0   3   2  14   1   1   0   1   0   1   0   1   0   0   0
   2   1   0   1  30   1   0   0   1   0   0   0  45   1   6   1  81   1
  15   5  13  11   4  14   4   5   1  39   0   1   0   1   1   0   4  12
   2   3   0   0   0   0   1   4   5   1   0   0   0   0   2  13   2   2
   0   0   0   0   1   1   1   0   0   1   1   0   2   6   0   1   0   1
   0   0   0   1   1   2   0   0   2   3   0   8  13  10   1  18   3   2
   0  33   0   0   1  10   4   4   7   9   2   9   0   0   0   0   0   3
   3   1   0   3   0   0   0  17   9   5   3  10   3   3   0  10   0   0
   1   4   0   1   3  35   8  17   1   8   0   0   0   2  12   3   2   1
  13   2  28  61]
```

```
In [38]: #Kmeans
nClusters = 7
t0 = time()
kmeans_model = KMeans(nClusters)
t_kmeans = time()- t0
labels_kmeans = kmeans_model.fit_predict(data)
```

```
In [39]: #Spectral_clustering
t0 = time()
graph = cosine_similarity(data)
t_spectral = time()- t0
labels_spectral = spectral_clustering(graph, n_clusters=7)
```

```
In [40]: #DBSCAN
t0 = time()
data = StandardScaler().fit_transform(data)
labels_dbscan = DBSCAN(eps=1, min_samples=1, algorithm='kd_tree').fit_predict(data)
t_dbscan = time()- t0
```

```
In [41]: #Agglomerative Clustering
t0 = time()
Agglomerative_model = AgglomerativeClustering(n_clusters = nClusters)
labels_AgglomerativeClustering = Agglomerative_model.fit_predict(data)
t_agg = time() - t0
```

```
In [42]: #Kmeans
print('Kmeans:\n')
df1 = pd.DataFrame({'labels':labels_kmeans,'Truth labels':lfw_people.target})
ct2 = pd.crosstab(df1['labels'],df1['Truth labels'])
print(ct2)

#Spectral clustering
print('\n\n\n')
print('Spectral clustering:\n')
df1 = pd.DataFrame({'labels':labels_spectral,'Truth labels':lfw_people.target})
ct2 = pd.crosstab(df1['labels'],df1['Truth labels'])
print(ct2)

#DBSCAN
print('\n\n\n')
print('DBSCAN:\n')
df1 = pd.DataFrame({'labels':labels_dbscan,'Truth labels':lfw_people.target})
ct2 = pd.crosstab(df1['labels'],df1['Truth labels'])
print(ct2)

#Agglomerative Clustering
print('\n\n\n')
print('Agglomerative Clustering:\n')
df1 = pd.DataFrame({'labels':labels_AgglomerativeClustering,'Truth labels':lfw_pe
ct2 = pd.crosstab(df1['labels'],df1['Truth labels'])
print(ct2)
```

Kmeans:

Truth labels	0	1	2	3	4	5	6
labels							
0	1	57	14	46	27	13	20
1	4	20	10	74	10	6	14
2	17	42	28	63	21	17	33
3	14	55	7	54	14	7	17
4	29	43	27	88	17	5	24
5	8	5	10	124	3	11	17
6	4	14	25	81	17	12	19

Spectral clustering:

Truth labels	0	1	2	3	4	5	6
labels							
0	2	8	12	44	21	21	11

Comparison

```

In [43]: n_samples, n_features = data.shape
n_faces = len(np.unique(lfw_people.target))
#print frame
print("n_digits: %d, \t n_samples %d, \t n_features %d"
      % (n_faces, n_samples, n_features))

print(82 * '_')
print('init\t\ttime\tinertia\tthomo\tcompl\tv-meas\tARI\tAMI\tsilhouette')

data = data
sample_size = 300
#define a function to measure and print out
def bench_clustering(method_name, time_, labels):
    print('%-9s\t%.2fs\t%.3f\t%.3f\t%.3f\t%.3f\t%.3f\t%.3f'
          % (method_name, time_,
             metrics.homogeneity_score(lfw_people.target, labels),
             metrics.completeness_score(lfw_people.target, labels),
             metrics.v_measure_score(lfw_people.target, labels),
             metrics.adjusted_rand_score(lfw_people.target, labels),
             metrics.adjusted_mutual_info_score(lfw_people.target, labels),
             metrics.silhouette_score(data, labels,
                                       metric='euclidean',
                                       sample_size=sample_size)))

#Kmeans
bench_clustering('K-means', t_kmeans, labels_kmeans)
#Spectral_clustering
bench_clustering('spectral', t_spectral, labels_spectral)

#Agglomerative clustering
bench_clustering('Agg.', t_agg, labels_AgglomerativeClustering)
#DBSCAN ==> Problems with raw data
#bench_clustering('DBSCAN', t_dbscan, labels_dbscan)
print('-----\nProblems with raw data cause noise with DBSCAN method')

```

n_digits: 7, n_samples 1288, n_features 256

init	time	inertia	homo	compl	v-meas	ARI	AMI	silhoue
tte								
K-means	0.00s	0.054	0.047	0.050	0.023	0.040	-0.004	
spectral	0.02s	0.060	0.052	0.056	0.031	0.045	0.001	
Agg.	0.20s	0.161	0.142	0.151	0.088	0.136	0.014	

Problems with raw data cause noise with DBSCAN method

Visualization

```

In [44]: from sklearn.decomposition import PCA
%matplotlib inline
nComponents = 2
vPCA = PCA(nComponents)
digitData_to_2D = vPCA.fit_transform(data)

fig = plt.figure(figsize=(15,15))
fig.suptitle('Comparison results of methods', fontsize=20)

ax = fig.add_subplot(3,2,1)
plt.scatter(digitData_to_2D[:,0], digitData_to_2D[:,1], c= labels_spectral, s=20)
ax.set_title('Spectral Clustering')

ax = fig.add_subplot(3,2,2)
plt.scatter(digitData_to_2D[:,0], digitData_to_2D[:,1], c= labels_dbscan, s=20)
ax.set_title('DBSCAN Clustering')

ax = fig.add_subplot(3,2,3)
plt.scatter(digitData_to_2D[:,0], digitData_to_2D[:,1], c= labels_kmeans, s=20)
ax.set_title('K-means')

ax = fig.add_subplot(3,2,4)
plt.scatter(digitData_to_2D[:,0], digitData_to_2D[:,1], c= labels_AgglomerativeC
ax.set_title('Agglomerative clustering')

ax = fig.add_subplot(3,2,5)
plt.scatter(digitData_to_2D[:,0], digitData_to_2D[:,1], c= lfw_people.target, s=
ax.set_title('Target Result')

```

Out[44]: <matplotlib.text.Text at 0x12eb36ab2e8>

Comparison results of methods

