

Study Definition Repository (SDR)

Reference Implementation (RI)

SDR API User Guide

Version 6.0

Disclaimer

These materials and information, as well as the underlying code/application they relate to are provided by TransCelerate Biopharma Inc. AS IS. Any party using or relying on this information and, these materials and/or the underlying code/application do so entirely at their own risk. Neither TransCelerate nor its members will bear any responsibility or liability for any harm, including indirect or consequential harm, that a user may incur from use or misuse of this information, materials, or underlying code/application.

TransCelerate does not endorse any particular software, system, or service. And the use of specific brands of products or services by TransCelerate and its collaboration partners in developing the SDR Reference Implementation should not be viewed as any endorsement of such products or services. To the extent that the SDR Reference Implementation incorporates or relies on any specific branded products or services, this resulted out of the practical necessities associated with making a reference implementation available to demonstrate the SDR's capabilities.

Document History

Version No.	Date	Author	Revision Description
V1.0	14-Mar-2022	ACN	Initial Version
V1.5	14-Mar-2022	ACN	Review comments addressed
V2.0	26-Apr-2022	ACN	Updated API response for POST
V3.0	05-Aug-2022	ACN	Updated with latest version of API Endpoints
V4.0	20-Mar-2023	ACN	Added new sections to list USDM version specific Study endpoints in section 3.2, 3.3 and 3.4. Added section 3.7, 3.8 and 3.9 for Change audit, Raw JSON and eCPT export endpoints.
V4.1	26-Apr-2023	ACN	Deprecated SDR RI Auth Token Endpoint in section 3 and added section 2.2 on steps to obtain user access token to access SDR RI API.
V5.0	23-Jun-2023	ACN	Added API specifications for V3 endpoints
V6.0	17-Oct-2023	ACN	Added API Key authorization specifications

Table of Contents

1. Introduction	9
1.1. Overview	9
1.2. Scope of Document	9
1.3. Intended Audience	10
1.4. Definitions and Acronyms	10
2. Pre-Requisites	10
2.1. Self-signed Certificate Generation	10
2.1.1. Certificate generation with OpenSSL	10
2.1.2. Certificate generation with PowerShell	12
2.2. Authorization	18
2.2.1. Access Token	18
2.2.2. API-Key Generation	18
3. API End Points	18
3.1. API Version -> USDM Version Mapping	18
3.2. V1 API (USDM Version - 1.0)	21
3.2.1. GET Study	21
3.2.2. GET Study Design	23
3.2.3. POST Study Definitions	26
3.2.3.1. POST - Add Study Definition	26
3.2.3.2. POST - Update Study Definition	28
3.3. V2 API (USDM Version - 1.9)	30
3.3.1. GET Study	30
3.3.2. GET Study Design	32
3.3.3. POST/PUT Study Definitions	35
3.3.3.1. POST - Add Study Definition	36
3.3.3.2. PUT - Update Study Definition	37
3.3.4. GET Schedule of Activities (SoA)	39
3.3.5. GET eCPT Export	43
3.4. V3 API (USDM Version – 2.0)	46
3.4.1. GET Study	46
3.4.2. GET Study Design	48
3.4.3. POST/PUT Study Definitions	51

3.4.3.1.	POST - Add Study Definition.....	52
3.4.3.2.	PUT - Update Study Definition	53
3.4.4.	GET Schedule of Activities (SoA)	55
3.4.5.	GET eCPT Export	59
3.4.6.	POST Validate USDM Conformance	62
3.4.7.	GET Version Comparison	66
3.5.	Study History	70
3.6.	GET Revision history.....	75
3.7.	GET Change Audit	79
3.8.	GET Raw JSON	83
4.	Testing the API Endpoint	88
4.1.	Postman REST client Setup.....	88
4.2.	Accessing the GET API.....	89

List of Tables

Table 1 GET API version ->USDM Version Mapping Endpoint.....	19
Table 2: GET API version -> USDM Version Mapping Request Parameters	19
Table 3 GET API version ->USDM Version Mapping Response.....	19
Table 4 GET Study V1 Endpoint	21
Table 5 GET Study Request Parameters	22
Table 6 GET Study V1 Response	22
Table 7 GET Study Design V1 Endpoint	23
Table 8 GET Study Design V1 Request Parameters.....	24
Table 9 GET Study Design V1 Response	24
Table 10 POST Study V1 Endpoint.....	26
Table 11 POST Study V1 Request Parameters.....	26
Table 12 POST Study V1 Response	27
Table 13 POST Study V1 Endpoint.....	28
Table 14 POST Study V1 Request Parameters.....	28
Table 15 POST Study V1 Response	29
Table 16 GET Study V2 Endpoint	30
Table 17 GET Study V2 Request Parameters.....	30
Table 18 GET Study V2 Response	31
Table 19 GET Study Design V2 Endpoint	33
Table 20 GET Study Design Request V2 Parameters.....	33
Table 21 GET Study Design V2 Response	34
Table 22 POST Study V2 Endpoint.....	36
Table 23 POST Study V2 Request Parameters.....	36
Table 24 POST Study V2 Response	37
Table 25 PUT Study V2 Endpoint	38
Table 26 PUT Study V2 Request Parameters	38

Table 27 PUT Study V2 Response.....	39
Table 28 GET SoA V2 Endpoint.....	40
Table 29 GET SoA Request V2 Parameters	41
Table 30 GET SoA V2 Response.....	42
Table 31 GET eCPT V2 Endpoint	43
Table 32 GET eCPT Request V2 Parameters.....	44
Table 33 GET eCPT V2 Response	45
Table 34 GET Study V3 Endpoint	46
Table 35 GET Study V3 Request Parameters.....	46
Table 36 GET Study V3 Response	47
Table 37 GET Study Design V3 Endpoint	49
Table 38 GET Study Design Request V3 Parameters.....	49
Table 39 GET Study Design V3 Response	50
Table 40 POST Study V3 Endpoint.....	52
Table 41 POST Study V3 Request Parameters.....	52
Table 42 POST Study V3 Response	53
Table 43 PUT Study V3 Endpoint	54
Table 44 PUT Study V3 Request Parameters.....	54
Table 45 PUT Study V3 Response.....	55
Table 46 GET SoA V3 Endpoint.....	56
Table 47 GET SoA Request V3 Parameters	57
Table 48 GET SoA V3 Response.....	58
Table 49 GET eCPT V3 Endpoint	59
Table 50 GET eCPT Request V3 Parameters.....	60
Table 51 GET eCPT V3 Response	61
Table 52 POST Validate USDM Conformance V3 Endpoint.....	62
Table 53 POST Validate USDM Conformance V3 Request Parameters	62

Table 54 POST Validate USDM Conformance V3 Response	64
Table 55 GET Version Comparison V3 Endpoint	66
Table 56 GET eCPT V3 Response	67
Table 57 POST Study V3 Response	68
Table 58 GET Study History Endpoint.....	70
Table 59 GET Study History - Request Parameters	71
Table 60 GET Study History Response.....	72
Table 61 GET Revision History Endpoint	75
Table 62 GET Revision History - Request Parameters.....	76
Table 63 GET Revision History Response	77
Table 64 GET Change Audit Endpoint	79
Table 65 GET Change Audit Request Parameters.....	80
Table 66 GET Change Audit Response	81
Table 67 GET Raw JSON Endpoint	83
Table 68 GET Raw JSON Request Parameters.....	83
Table 69 GET Raw JSON Response	85

List of Figures

Figure 1 OpenSSL Command Prompt.....	11
Figure 2 OpenSSL Command	11
Figure 3 Export Certificate	12
Figure 4 PowerShell Command	12
Figure 5 Run Window.....	13
Figure 6 Certificate Manager Console.....	13
Figure 7 Certificate Export Wizard.....	14
Figure 8 Export Private Key	14
Figure 9 Certificate Format .PFX.....	15
Figure 10 Password for Certificate	16
Figure 11 Certificate File Name.....	17
Figure 12 Certificate Export Wizard.....	17
Figure 13 Postman Upload Certificate.....	88
Figure 14 Postman Add Client Certificate.....	88
Figure 15 Postman set HTTP Request for GET	90
Figure 16 Postman Send Request	90
Figure 17 Postman HTTP Response.....	91

1. Introduction

1.1. Overview

The SDR RI¹ implements the CDISC DDF Reference Architecture which include USDM model and API Specifications defined using the OpenAPI Specification (OAS). The API Layer of the SDR Reference Implementation complies with the OpenAPI Specification which allow systems to discover and understand the capabilities of the service without access to source code, documentation, or through network traffic inspection. When properly defined, a consumer can understand and interact with the remote service with a minimal amount of implementation logic.

It follows the REST architectural style that uses HTTP requests to GET and POST data. RESTful architecture is not linked with any technology or platform, it does not dictate exactly how to build an API. Instead, it introduces the best practices known as constraints. They describe how the server processes requests and responds to them. Operating within these constraints, the system gains desirable properties such as reliability, ease of use, improved scalability and security, low latency while enhancing the system performance and helping achieve technology independence in the process.

1.2. Scope of Document

This document details the list of API endpoints available in the Study Definition Repository Reference Implementation and provides sample Request and Response for each endpoint. These endpoints include implementation of the CDISC USDM API Specification and additional SDR Specific endpoints supporting the SDR RI features. It also explains the possible reasons behind the various error codes returned by the API. The technical design and implementation of these APIs is out of scope.

¹ The SDR Reference Implementation is an attempt to demonstrate the vision of the DDF initiative, not a commercial product. To be clear, TransCelerate does not endorse any particular software, system, or service. And the use of specific brands of products or services by TransCelerate and its collaboration partners in developing the SDR Reference Implementation should not be viewed as any endorsement of such products or services. To the extent that the SDR Reference Implementation incorporates or relies on any specific branded products or services, such as Azure, this resulted out of the practical necessities associated with making a reference implementation available to demonstrate the SDR's capabilities. Users are free to download the source code for the SDR from GitHub and design their own implementations in whatever environments they choose.

1.3. Intended Audience

The document is a guide for users/vendors who want to integrate and consume the SDR RI API to store and retrieve study definitions in USDM format.

1.4. Definitions and Acronyms

Term / Abbreviation	Definition
API	Application Programming Interface
DDF	Digital Data Flow
JSON	JavaScript Object Notation
REST	Representational State Transfer
SDR	Study Definition Repository
URL	Uniform Resource Locator
USDM	Unified Study Definitions Model

2. Pre-Requisites

2.1. Self-signed Certificate Generation

Certificate can be created by using any one of the below Tools.

- Open SSL
- PowerShell

2.1.1. Certificate generation with OpenSSL

- i. Install the OpenSSL.
- ii. Run the OpenSSL Command Prompt and set the directory to the folder where certificate to be stored.

Figure 1 OpenSSL Command Prompt

```

Win64 OpenSSL Command Prompt
Win64 OpenSSL Command Prompt

OpenSSL 3.0.3 3 May 2022 (Library: OpenSSL 3.0.3 3 May 2022)
built on: Wed May  4 02:41:48 2022 UTC
platform: VC-WIN64A
options: bn(64,64)
compiler: cl /Z7 /fdo ssl_static.pdb /fs0 /GF /Oy /HD /W3 /wd4090 /nologo /O2 -DL_ENDIAN -DOPENSSL_PIC -DUSING_V110_SDK71_ -D_WINSOCK_DEPRECATED_NO_WARNINGS -D_WINDIR=C:\Windows
seeding source: os-specific
CPUINFO: OpenSSL_ia32cap=0xfedaf383fcbffff:0x1c2fbb

C:\Users\hpc>cd desktop/certificate
C:\Users\hpc\Desktop\Certificate>

```

- iii. Run the below command → provide Enter PEM pass phrase and save the pass phrase to provide it on the command to generate .pfx certificate.

```
openssl req -x509 -newkey rsa:4096 -sha256 -keyout my.key -out my.crt -subj "/CN=test.com" -days 600
```

Figure 2 OpenSSL Command

```

C:\Users\hpc>cd desktop/certificate
C:\Users\hpc\Desktop\Certificate>openssl req -x509 -newkey rsa:4096 -sha256 -keyout my.key -out my.crt -subj "/CN=test.com" -days 600
.....
Enter PEM pass phrase:
Verifying - Enter PEM pass phrase:
.....

```

- iv. Run the below command to generate the .pfx certificate.

```
openssl pkcs12 -export -name "test.com" -out my.pfx -inkey my.key -in my.crt
```

Provide the below details.

Enter pass phrase for my.key: Provide the pass phrase passed on step 3

Enter Export Password: Provide the password for .pfx certificate and save it for later use.

Figure 3 Export Certificate

```
C:\Users\hp\Desktop\Certificate>openssl req -x509 -newkey rsa:4096 -sha256 -keyout my.key -out my.crt -subj "/CN=test.com" -days 600
.....
Enter PEM pass phrase:
Verifying - Enter PEM pass phrase:
-----
C:\Users\hp\Desktop\Certificate>openssl pkcs12 -export -name "test.com" -out my.pfx -inkey my.key -in my.crt
Enter pass phrase for my.key:
Enter Export Password:
Verifying - Enter Export Password:
```

- v. Exported .pfx certificate will be stored in the directory where OpenSSL was installed.


Note: Share the .pfx certificate and the password to SDR Support team to get access to SDR API's on Demo Environment.

2.1.2. Certificate generation with PowerShell

- i. Open PowerShell and run the following command to generate the self-signed certificate.

```
New-SelfSignedCertificate -certstorelocation cert:\CurrentUser\My\ -dnsname example.com
```

Figure 4 PowerShell Command



```
Windows PowerShell
PS C:\> New-SelfSignedCertificate -certstorelocation cert:\CurrentUser\My\ -dnsname example.com


PSParentPath: Microsoft.PowerShell.Security\Certificate::CurrentUser\My

Thumbprint                               Subject
-----
6627DBCEEAB7A9AF558009FC04FF5CA1FFFBCE1B  CN=example.com

PS C:\>
```


- ii. To Export the certificate in .pfx format, go to run → type certmgr.msc and click Ok.

Figure 5 Run Window




- iii. In certificate manager go to personal → certificates → select the generated certificate and right click select All Tasks → Select Export.

Figure 6 Certificate Manager Console




- iv. In Certificate Export Wizard click Next to continue.

Figure 7 Certificate Export Wizard




- v. Select export the private key option and click next.

Figure 8 Export Private Key




- vi. Leave the defaults and click next.

Figure 9 Certificate Format .PFX

- vii. Provide the password for certificate and click next.


Figure 10 Password for Certificate



The image shows a 'Certificate Export Wizard' window with a 'Security' section. The text in the 'Security' section reads: 'To maintain security, you must protect the private key to a security principal or by using a password.' Below this text, there is a checkbox labeled 'Group or user names (recommended)' which is currently unchecked. To the right of this checkbox is a large empty rectangular box, and to its right are two buttons: 'Add' and 'Remove'. Below the 'Group or user names' section, there is a checked checkbox labeled 'Password:'. To the right of this checkbox is a password input field containing six dots. Below the password field is a 'Confirm password:' label followed by another password input field containing six dots. A red rectangular box highlights the 'Password:' checkbox, the password input field, and the 'Confirm password:' input field. Below the password fields, there is an 'Encryption:' label followed by a dropdown menu showing 'TripleDES-SHA1'. At the bottom right of the window, there are two buttons: 'Next' and 'Cancel'. The 'Next' button is highlighted with a red rectangular box.


- viii. Select the path to save the certificate.

Figure 11 Certificate File Name



- ix. Click on Finish.

Figure 12 Certificate Export Wizard



- x. Exported .pfx certificate will be stored on the folder path provided on step 8.

Note: Share the .pfx certificate and the password to SDR Support team to get access to SDR API's on Demo environment.

2.2. Authorization

To Access SDR RI APIs, an access token or API-Key must be passed as an authorization header in the request for API endpoints. The choice of which method of authentication you use is up to you.

2.2.1. Access Token

A user can get an access token by the following ways.

- i. Using SDR RI UI to get access token. SDR UI application Link – **DDF SDR UI**
- ii. Using any one of Microsoft Authentication Flows if the details of the SDR API hosted environment are available. Refer **Authentication Flows** for more details.

2.2.2. API-Key Generation

API-Key can be generated through Developer portal. Refer the document **SDR RI API Key Generation**.

3. API End Points

SDR Reference Implementation exposes the following REST Endpoints to deliver application functionality including storing and retrieving study definitions. All the SDR RI API endpoints conform to the CDISC USDM format mentioned in **USDM Conformance for SDR RI V1** for USDM Version 1.0, in **USDM Conformance for SDR RI V2** for USDM Version 1.9 and in **USDM Conformance for SDR RI V2.0.1** for USDM Version 2.0. For the Reference Implementation, only the required field validations mentioned in the CDISC USDM document have been included.

3.1. API Version -> USDM Version Mapping

USDM version specific Study endpoints will allow users to create studies conforming to a specific USDM version (1 major and any related minor versions) and validate the study

against conformance rules corresponding to that version. This endpoint allows user to get mapping between SDR RI API versions and CDISC USDM versions.

Table 1 GET API version ->USDM Version Mapping Endpoint

Method	URL
GET	/api/versions

REQUEST PARAMETERS

Table 2: GET API version -> USDM Version Mapping Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d

RESPONSE

Table 3 GET API version ->USDM Version Mapping Response

Status	Response	Comments
--------	----------	----------

200	<pre>{ "SDRVersions": [{ "apiVersion": "mvp", "usdmVersions": ["mvp"] }, { "apiVersion": "v1", "usdmVersions": ["1.0"] }, { "apiVersion": "v2", "usdmVersions": ["1.9"] }] }</pre>	
400	<pre>{ "statusCode": "400", "message": "An error occurred" }</pre>	Application Exception

401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" }	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

3.2. V1 API (USDM Version - 1.0)

3.2.1. GET Study

This endpoint allows user to retrieve the different study elements for a particular study for a specific SDR upload version.

Table 4 GET Study V1 Endpoint

Method	URL
GET	/api/v1/studydefinitions/{studyId}

REQUEST PARAMETERS

Table 5 GET Study Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversion	Integer	No	2
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpOGxWMFRPSSlmltpZCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	String	Yes	1.0

RESPONSE

Table 6 GET Study V1 Response

Status	Response	Comments
200	Refer <u>Response for GET StudyV1</u> for the JSON Data	

400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" }	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

3.2.2. GET Study Design

Retrieves the different study design elements for a particular study for SDR upload version.

Table 7 GET Study Design V1 Endpoint

Method	URL
GET	/api/v1/ studydesigns

REQUEST PARAMETERS

Table 8 GET Study Design V1 Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Query Parameter	study_uuid	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	sdruploadversion	Integer	No	3
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	1.0

RESPONSE

Table 9 GET Study Design V1 Response

Status	Response	Comments
--------	----------	----------

200	Refer <u>Response for GET Study DesignV1</u> for the JSON Data	Successful
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR { "statusCode": "404", "message": "The requested study design not found" }	This can occur when requested Study Id is not found or Study Design is not found.
500	<i>Internal Server Error</i>	Web server/Web API down

3.2.3. POST Study Definitions

This endpoint allows user to add and/or update a study definition in SDR that conforms to the USDM structure. The study GET endpoint allows the users to fetch data for individual section whereas the section specific adds/updates are not in scope of SDR Reference Implementation.

3.2.3.1. POST - Add Study Definition

For the first time, when a study is pushed into the SDR, the uuid fields in the JSON data must be empty. SDR will generate UUID for the uuid fields.

Table 10 POST Study V1 Endpoint

Method	URL
POST	/api/v1/studydefinitions

REQUEST PARAMETERS

Table 11 POST Study V1 Request Parameters

Type	Param Name	Sample Values
Body		Refer Request Body for POST – Add New Study DefinitionV1 for the JSON Data
Header (Either Authorization bearer token or API-Key)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	1.0

RESPONSE

Table 12 POST Study V1 Response

Status	Response	Comments
201	Refer <u>Response Body for POST – Add Study DefinitionV1</u> for the JSON Data	Successful. For a new study document added into SDR, the unique IDs for Study and Study Design are generated by system and returned in response body along with SDR Upload Version is defaulted to “1”. For updates to an existing study, the version is incremented by 1.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.2.3.2. POST - Update Study Definition

- i. For adding new elements to an existing study definition section
 - o **uuid** for the study should be passed in the request body
 - o **uuid** for the study and **uuid** for the studyDesign should be passed when updating study design data.
 - o New elements should be passed without **id** field data along with existing elements including SDR generated **id** values in the request body.
 - o SDR will generate UUID for only the new elements mentioned in the request and update the data for existing elements that had a valid UUID in the request.
- ii. For example, there is an existing study definition in SDR as mentioned in Study Definition – **Existing DataV1**. If a new element is to be added to study objectives, the existing study data with the new element must be sent in the request body as mentioned in Request Body for POST – **Update New Study DefinitionV1**.

Table 13 POST Study V1 Endpoint

Method	URL
POST	/api/v1/studydefinitions

REQUEST PARAMETERS

Table 14 POST Study V1 Request Parameters

Type	Param	Values
Body		Refer Request Body for POST – Update New Study DefinitionV1 for the JSON Data
Header (Either Authorization or bearer)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6LWY9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM

token or API-Key)	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	1.0

RESPONSE

Table 15 POST Study V1 Response

Status	Response	Comments
201	Refer <u>Response Body for POST – Update Study DefinitionV1</u> for the JSON Data	Successful. The new element in the section will be added on along with the existing element.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.3. V2 API (USDM Version - 1.9)

3.3.1. GET Study

This endpoint allows user to retrieve the different study elements for a particular study for a specific SDR upload version. This endpoint also allows user to retrieve specific sections.

LIST OF STUDY SECTIONS:

- studyTitle
- studyVersion
- studyType
- studyRationale
- studyAcronym
- studyIdentifiers
- studyPhase
- businessTherapeuticAreas
- studyProtocolVersions
- studyDesigns

Table 16 GET Study V2 Endpoint

Method	URL
GET	/api/v2/studydefinitions/{studyId}

REQUEST PARAMETERS

Table 17 GET Study V2 Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d

Query Parameter	sdruploadversion	Integer	No	2
Query Parameter	Listofelements	string	No	The parameter value should be comma separated values of the section names. For example, "studyDesigns,studyIdentifiers"
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZUR2FYRUpOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZUR2FYRUpOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	String	Yes	1.9

RESPONSE

Table 18 GET Study V2 Response

Status	Response	Comments
--------	----------	----------

200	Refer <u>Response for GET StudyV1.9</u> for the JSON Data	
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" }	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

3.3.2. GET Study Design

Retrieves the different study design elements for a particular study for the SDR upload version. This endpoint also allows the user to retrieve specific study design sections.

LIST OF STUDY DESIGN SECTIONS:

- studyDesignName
- studyDesignDescription
- trialIntentType
- trialType
- interventionModel
- studyCells
- studyIndications
- studyInvestigationalInterventions

- studyPopulations
- studyObjectives
- studyScheduleTimelines
- therapeuticAreas
- studyEstimands
- encounters
- activities
- studyDesignRationale
- studyDesignBlindingScheme
- biomedicalConcepts
- bcCategories
- bcSurrogates

Table 19 GET Study Design V2 Endpoint

Method	URL
GET	/api/v2/ studydesigns

REQUEST PARAMETERS

Table 20 GET Study Design Request V2 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Query Parameter	study_uuid	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	sdruploadversion	Integer	No	3
Query Parameter	listofelements	String	No	The parameter should be comma separated values of the section names. For example,

				"activities,encounters"
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddde37b16d
Header	usdmVersion	String	Yes	1.9

RESPONSE

Table 21 GET Study Design V2 Response

Status	Response	Comments
200	Refer <u>Response for GET Study DesignV1.9</u> for the JSON Data	Successful
400	{ "statusCode": "400", "message": "An error occurred"	Application Exception

	}	
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR { "statusCode": "404", "message": "The requested study design not found" }	This can occur when requested Study Id is not found or Study Design is not found.
500	<i>Internal Server Error</i>	Web server/Web API down

3.3.3. POST/PUT Study Definitions

This endpoint allows user to add and/or update a study definition in SDR that conforms to the USDM structure. The PUT endpoint supports updates to specific study elements only when entire study data is sent in the request body. If partial study elements (conforming to specific USDM version) are sent in request, the API will create study version with only the elements sent in request.

3.3.3.1. POST - Add Study Definition

For the first time, when a study is pushed into the SDR, the studyId field in the JSON data must be empty. SDR will generate UUID for the studyId field. The Id for the other classes is mandatory, user defined, and expected to be sent in the request.

Table 22 POST Study V2 Endpoint

Method	URL
POST	/api/v2/studydefinitions

REQUEST PARAMETERS

Table 23 POST Study V2 Request Parameters

Type	Param	Values
Body		Refer Request Body for POST – Add New Study DefinitionV1.9 for the JSON Data
Header (Either Authorization on bearer token or API-Key)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6LW9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	1.9

RESPONSE

Table 24 POST Study V2 Response

Status	Response	Comments
201	Refer <u>Response Body for POST – Add Study Definition V1.9</u> for the JSON Data	Successful. For a new study document added into SDR, the unique IDs for Study and Study Design are generated by system and returned in response body along with SDR Upload Version is defaulted to “1”. For updates to an existing study, the version is incremented by 1.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.3.3.2. PUT - Update Study Definition

- i. For adding new elements to an existing study definition section

- New elements should be passed along with existing elements in the request body.
- ii. For example, there is an existing study definition in SDR as mentioned in Study Definition – **Existing DataV1.9**. If a new element is to be added to study objectives, the existing study data with the new element must be sent in the request body as mentioned in Request Body for PUT – **Update New Study DefinitionV1.9**.

Table 25 PUT Study V2 Endpoint

Method	URL
PUT	/api/v2/studydefinitions/{studyId}

REQUEST PARAMETERS

Table 26 PUT Study V2 Request Parameters

Type	Param	Values
Body		Refer <u>Request Body for PUT – Update New Study DefinitionV1.9</u> for the JSON Data
Header (Either Authorization on bearer token or API-Key)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	1.9

RESPONSE

Table 27 PUT Study V2 Response

Status	Response	Comments
201	Refer <u>Response Body for PUT – Update Study DefinitionV1.9</u> for the JSON Data	Successful. The new element in the section will be added on along with the existing element.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.3.4. GET Schedule of Activities (SoA)

This endpoint allows user to retrieve the Schedule of Activities (SoA) for a particular study. Also, the endpoint has optional parameter to retrieve the SoA for a particular study design and a particular schedule timeline.

Table 28 GET SoA V2 Endpoint

Method	URL
GET	/api/v2/ studydefinitions/{studyId}/studydesigns/soa

REQUEST PARAMETERS

Table 29 GET SoA Request V2 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversion	Integer	No	3
Query Parameter	Studydesignid	String	No	Value in studyDesignId
Query Parameter	studyWorkflowid	String	No	This is any one of the values in scheduleTimelineId under studyScheduleTimelines.
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	1.9

RESPONSE

Table 30 GET SoA V2 Response

Status	Response	Comments
200	Refer Response for GET SoAV1.9 for the JSON Data	Successful. In the response, Workflow related fields will represent the data of scheduleTimeline (studyWorkflows → studyScheduleTimelines, workflowId → scheduleTimelineId and workflowDescription → scheduleTimelineDescription)
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR {	This can occur when requested Study Id is not found or Study Design is not found.

	<pre>"statusCode": "404", "message": "The requested study design not found" }</pre>	
500	<i>Internal Server Error</i>	Web server/Web API down

3.3.5. GET eCPT Export

This endpoint allows user to retrieve the eCPT ²Export for each study design in a given study that conforms to USDM Version 1.9 that is stored in SDR.

Table 31 GET eCPT V2 Endpoint

Method	URL
GET	/api/v2/studydefinitions/{studyId}/studydesigns/ecpt

REQUEST PARAMETERS

² The eCPT is an electronic version of the Common Protocol Template developed by TransCelerate. For more information about the eCPT, see the eCPT section of the TransCelerate website, available here: <https://www.transceleratebiopharmainc.com/assets/clinical-content-reuse-solutions/>

Table 32 GET eCPT Request V2 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversion	Integer	No	3
Query Parameter	Studydesignid	String	No	Value in studyDesignId
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	1.9

RESPONSE

Table 33 GET eCPT V2 Response

Status	Response	Comments
200	Refer <u>Response Body for GET eCPT Mapping V1.9</u> for the JSON Data	
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR { "statusCode": "404", "message": "The requested study design not found" }	This can occur when requested Study Id is not found or Study Design is not found.

500	Internal Server Error	Web server/Web API down
-----	-----------------------	-------------------------

3.4. V3 API (USDM Version – 2.0)

3.4.1. GET Study

This endpoint allows user to retrieve the different study elements for a particular study for a specific SDR upload version. This endpoint also allows user to retrieve specific sections.

LIST OF STUDY SECTIONS:

- studyTitle
- studyVersion
- studyType
- studyRationale
- studyAcronym
- studyIdentifiers
- studyPhase
- businessTherapeuticAreas
- studyProtocolVersions
- studyDesigns

Table 34 GET Study V3 Endpoint

Method	URL
GET	/api/v3/studydefinitions/{studyId}

REQUEST PARAMETERS

Table 35 GET Study V3 Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	studyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d

Query Parameter	sdruploadversion	Integer	No	2
Query Parameter	Listofelements	string	No	The parameter value should be comma separated values of the section names. For example, "studyDesigns,studyIdentifiers"
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZUR2FYRUpOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZUR2FYRUpOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	String	Yes	2.0

RESPONSE

Table 36 GET Study V3 Response

Status	Response	Comments
--------	----------	----------

200	Refer <u>Response for GET StudyV2.0</u> for the JSON Data	
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" }	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.2. GET Study Design

Retrieves the different study design elements for a particular study for the SDR upload version. This endpoint also allows the user to retrieve specific study design sections.

LIST OF STUDY DESIGN SECTIONS:

- studyDesignName
- studyDesignDescription
- trialIntentTypes
- trialType
- interventionModel
- studyCells
- studyIndications
- studyInvestigationalInterventions

- studyPopulations
- studyObjectives
- studyScheduleTimelines
- therapeuticAreas
- studyEstimands
- encounters
- activities
- studyDesignRationale
- studyDesignBlindingScheme
- biomedicalConcepts
- bcCategories
- bcSurrogates
- studyepochs
- studyelements
- studyarms

Table 37 GET Study Design V3 Endpoint

Method	URL
GET	/api/v3/ studydesigns

REQUEST PARAMETERS

Table 38 GET Study Design Request V3 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Query Parameter	studyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	sdruploadversion	Integer	No	3
Query Parameter	listofelements	String	No	The parameter should be comma separated

				values of the section names. For example, “activities,encounters”
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZXR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	2.0

RESPONSE

Table 39 GET Study Design V3 Response

Status	Response	Comments
200	Refer <u>Response for GET Study DesignV2.0</u> for the JSON Data	Successful
400	{	Application Exception

	<pre> "statusCode": "400", "message": "An error occurred" } </pre>	
401	<pre> { "statusCode": "401", "message": "Access Denied" } </pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<pre> { "statusCode": "404", "message": "The requested study document not found" } OR { "statusCode": "404", "message": "The requested study design not found" } </pre>	This can occur when requested Study Id is not found or Study Design is not found.
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.3. POST/PUT Study Definitions

This endpoint allows user to add and/or update a study definition in SDR that conforms to the USDM structure. The PUT endpoint supports updates to specific study elements only when entire study data is sent in the request body. If partial study elements (conforming to specific USDM version) are sent in request, the API will create study version with only the elements sent in request.

3.4.3.1. POST - Add Study Definition

For the first time, when a study is pushed into the SDR, the studyId field in the JSON data must be empty. SDR will generate UUID for the studyId field. The Id for the other classes is mandatory, user defined, and expected to be sent in the request.

Table 40 POST Study V3 Endpoint

Method	URL
POST	/api/v3/studydefinitions

REQUEST PARAMETERS

Table 41 POST Study V3 Request Parameters

Type	Param	Values
Body		Refer <u>Request Body for POST – Add New Study DefinitionV2.0</u> for the JSON Data
Header (Either Authorization on bearer token or API-Key)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6LW9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	2.0

RESPONSE

Table 42 POST Study V3 Response

Status	Response	Comments
201	Refer Response Body for POST – Add Study DefinitionV2.0 for the JSON Data	Successful. For a new study document added into SDR, the unique IDs for Study and Study Design are generated by system and returned in response body along with SDR Upload Version is defaulted to “1”. For updates to an existing study, the version is incremented by 1.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.3.2. PUT - Update Study Definition

- iii. For adding new elements to an existing study definition section

- New elements should be passed along with existing elements in the request body.
- iv. For example, there is an existing study definition in SDR as mentioned in Study Definition – **Existing DataV2.0**. If a new element is to be added to study objectives, the existing study data with the new element must be sent in the request body as mentioned in Request Body for PUT – **Update New Study DefinitionV2.0**.

Table 43 PUT Study V3 Endpoint

Method	URL
PUT	/api/v3/studydefinitions/{studyId}

REQUEST PARAMETERS

Table 44 PUT Study V3 Request Parameters

Type	Param	Values
Body		Refer Request Body for PUT – Update New Study DefinitionV2.0 for the JSON Data
Header (Either Authorization on bearer token or API-Key)	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	a7fecf90a4f643eda0b27dddde37b16d
Header	usdmVersion	2.0

RESPONSE

Table 45 PUT Study V3 Response

Status	Response	Comments
201	Refer <u>Response Body for PUT – Update Study DefinitionV2.0</u> for the JSON Data	Successful. The new element in the section will be added on along with the existing element.
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.4. GET Schedule of Activities (SoA)

This endpoint allows user to retrieve the Schedule of Activities (SoA) for a particular study. Also, the endpoint has optional parameter to retrieve the SoA for a particular study design and a particular schedule timeline.

Table 46 GET SoA V3 Endpoint

Method	URL
GET	/api/v3/ studydefinitions/{studyId}/studydesigns/soa

REQUEST PARAMETERS

Table 47 GET SoA Request V3 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversion	Integer	No	3
Query Parameter	Studydesignid	String	No	Value in studyDesignId
Query Parameter	studyWorkflowid	String	No	This is any one of the values in scheduleTimelineId under studyScheduleTimelines.
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	2.0

RESPONSE

Table 48 GET SoA V3 Response

Status	Response	Comments
200	Refer Response for GET SoAV2.0 for the JSON Data	Successful. In the response, Workflow related fields will represent the data of scheduleTimeline (studyWorkflows → studyScheduleTimelines, workflowId → scheduleTimelineId and workflowDescription → scheduleTimelineDescription)
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR {	This can occur when requested Study Id is not found or Study Design is not found.

	<pre>"statusCode": "404", "message": "The requested study design not found" }</pre>	
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.5. GET eCPT Export

This endpoint allows user to retrieve the eCPT Export for each study design in a given study that conforms to USDM Version 2.0 that is stored in SDR.

Table 49 GET eCPT V3 Endpoint

Method	URL
GET	/api/v3/studydefinitions/{studyId}/studydesigns/ecpt

REQUEST PARAMETERS

Table 50 GET eCPT Request V3 Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversion	Integer	No	3
Query Parameter	Studydesignid	String	No	Value in studyDesignId
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	2.0

RESPONSE

Table 51 GET eCPT V3 Response

Status	Response	Comments
200	Refer <u>Response for GET eCPT V2.0</u> for the JSON Data	Successful. In the response, Workflow related fields will represent the data of scheduleTimeline (studyWorkflows → studyScheduleTimelines, workflowId → scheduleTimelineId and workflowDescription → scheduleTimelineDescription)
400	{ "statusCode": "400", "message": "An error occurred" }	Application Exception
401	{ "statusCode": "401", "message": "Access Denied" }	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" } OR { "statusCode": "404",	This can occur when requested Study Id is not found or Study Design is not found.

	<pre>"message": "The requested study design not found" }</pre>	
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.6. POST Validate USDM Conformance

This endpoint allows user to validate whether the study definition conforms to USDM Version 2.0 without submitting the study definitions. If the study definition is conformant with USDM Version 2.0, success response code (200 - Ok) will be returned, otherwise the endpoint will return list of conformance errors with failure response code (400 – Bad Request).

Table 52 POST Validate USDM Conformance V3 Endpoint

Method	URL
POST	/api/v3/studydefinitions/validate-usdm-conformance

REQUEST PARAMETERS

Table 53 POST Validate USDM Conformance V3 Request Parameters

Type	Param	Values
Body		Refer <u>Request Body for POST – Add New Study DefinitionV2.0</u> for the JSON Data
Header	Authorization	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6LWY9IjZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
Header	usdmVersion	2.0

RESPONSE

Table 54 POST Validate USDM Conformance V3 Response

Status	Response	Comments
200	<pre>{ "statusCode": "200", "message": "The study definition is conformant with USDM Version : 2.0" }</pre>	<p>Successful.</p> <p>If the Study Definitions is conformant with the USDM conformance rules, API will give 200 Ok response</p>
400	<pre>{ "statusCode": "400", "message": "The study definition is not conformant with USDM Version : 2.0", "error": { "study.studyTitle": ["Field is missing"] } }</pre>	<p>Validation Failed.</p> <p>If the Study Definitions is not conformant with the USDM conformance rules, API will give 400 Bad Request response</p>
400	<pre>{ "statusCode": "400", "message": "An error occurred" }</pre>	<p>Application Exception</p>

401	<pre>{ "statusCode": "401", "message": "Access Denied" }</pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.4.7. GET Version Comparison

This endpoint allows user to compare two SDR Upload Versions of study definitions that conforms to USDM Version 2.0. The endpoint will list down the changes between the two SDR Upload Versions of a specific study definition that was sent in the request.

Table 55 GET Version Comparison V3 Endpoint

Method	URL
GET	/api/v3/studydefinitions/version-comparison

REQUEST PARAMETERS

Table 56 GET eCPT V3 Response

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Query Parameter	Sdruploadversionone	Integer	Yes	3
Query Parameter	Sdruploadversiontwo	Integer	Yes	2
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d
Header	usdmVersion	String	Yes	2.0

RESPONSE

Table 57 POST Study V3 Response

Status	Response	Comments
200	<pre>{ "studyId": "7dd4d676-8714-42d3-b2a9-c189b59fad67", "LHS": { "entryDateTime": "2023-06-21T12:52:48.216Z", "SDRUploadVersion": 1 }, "RHS": { "entryDateTime": "2023-06-21T12:53:16.601Z", "SDRUploadVersion": 2 }, "elementsChanged": ["study.studyTitle", "study.studyAcronym", "study.studyIdentifiers[1].studyIdentifier",] }</pre>	<p>Successful.</p> <p>The API will list down the differences between the two SDR Upload Versions sent in the request.</p>
400	<pre>{ "statusCode": "400", "message": "An error occurred" }</pre>	<p>Application Exception</p>

401	<pre>{ "statusCode": "401", "message": "Access Denied" }</pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<i>Resource Not Found</i>	When the request URL is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.5. Study History

This endpoint allows user to retrieve the metadata information for Studies residing in the SDR.

Table 58 GET Study History Endpoint

Method	URL
GET	/api/studydefinitions/history

REQUEST PARAMETERS

Table 59 GET Study History - Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Query Parameter	FromDate	Date	No	2022-Mar-10
Query Parameter	ToDate	Date	No	2022-Mar-15
Query Parameter	studyTitle	String	No	"Study On Oncology"
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d

RESPONSE

Table 60 GET Study History Response

Status Code	Response	Comments
200	<pre>[{ "studyId": "9533aa2d-472a-4722-94eb-1a7b153b241a", "SDRUploadVersion": [{ "uploadVersion": 1, "entryDateTime": "2023-06-21T11:34:40.43798Z", "studyTitle": "Study of Stage III Biliary Duct Cancer", "studyVersion": "1", "studyIdentifiers": [{ "studyIdentifierId": "c4663375-29be-4b37-9a7d-b2ef927fdf64", "studyIdentifier": "CT-GOV-1234", "studyIdentifierScope": { "organisationId": "96dd6b83-2d34-45ac-9d08-3e647b2c7316", "organisationIdentifier": "CT-GOV", "organisationIdentifierScheme": "FDA", "organisationName": "ClinicalTrials.gov", "organisationType": { "codeId": "8fcecddf-bbe2-4e71-ad97-114cbc3f1cba", "code": "C2365x",</pre>	Successful

	<pre> "codeSystem": "http:www.cdisc.org", "codeSystemVersion": "1", "decode": "Clinical Study Sponsor" }, "organizationLegalAddress": { "text": "text", "line": " line2", "city": " city", "district": "district ", "state": "state ", "postalCode": " postalCode", "country": { "codeId": "8fcecddf-bbe2-4e71-ad97- 114cbc3f1cba", "code": "C2365x", "codeSystem": "http:www.cdisc.org", "codeSystemVersion": "1", "decode": "Egypt" } } } }], "protocolVersions": ["1"], </pre>	
--	--	--

	<pre> "usdmVersion": "1.9", "links": { "studyDefinitions": "/v2/studydefinitions/9533aa2d-472a-4722-94eb-1a7b153b241a?sdruploadversion=1", "auditTrail": "/studydefinitions/9533aa2d-472a-4722-94eb-1a7b153b241a/audittrail", "studyDesigns": [{ "studyDesignId": "SD01", "studyDesignLink": "/v2/studydesigns?study_uuid=9533aa2d-472a-4722-94eb-1a7b153b241a&sdruploadversion=1&studydesign_uuid=SD01" }] }] </pre>	
400	<pre> { "statusCode": "400", "message": "An error occurred" } </pre>	Application Exception
401	<pre> { "statusCode": "401", "message": "Access Denied" } </pre>	When the API is invoked without access token or an expired access token,

	}	then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<pre>{ "statusCode": "404", "message": "The requested study document not found" }</pre>	When Study Title is given in query param and there is no matching study definition in SDR, or the requested URI is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.6. GET Revision history

This endpoint allows the user to retrieve the revision history for a study residing in the SDR Repository. The SDR captures the history of all changes done on a study definition, including entry date time, entry system and sdr upload version.

Table 61 GET Revision History Endpoint

Method	URL
GET	/api/studydefinitions/{studyId}/revisionhistory

REQUEST PARAMETERS

Table 62 GET Revision History - Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Query Parameter	FromDate	Date	No	2022-Mar-10
Query Parameter	ToDate	Date	No	2022-Mar-15
Path Parameter	studyId	String	Yes	11adcf54-82cf-40d2-81a5-092d4e5b6819
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27ddd e37b16d

RESPONSE

Table 63 GET Revision History Response

Status Code	Response	Comments
200	<pre>{ "studyId": "11adcf54-82cf-40d2-81a5-092d4e5b6819", "auditTrail": [{ "entryDateTime": "2023-03-16T05:31:04.927Z", "usdmVersion": "1.9", "SDRUploadVersion": 2, "links": { "studyDefinitions": "/v2/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819?sdruploadversion=2", "auditTrail": "/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819/audittrail", "studyDesigns": [{ "studyDesignId": "SD01", "studyDesignLink": "/v2/studydesigns?study_uuid=11adcf54-82cf-40d2-81a5-092d4e5b6819&sdruploadversion=2&studydesign_uuid=SD01" }], "SoA": "/v2/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819/studydesigns/soa?sdruploadversion=2" } }], }</pre>	Successful

	<pre> { "entryDateTime": "2023-03-16T05:30:26.628Z", "usdmVersion": "1.9", "SDRUploadVersion": 1, "links": { "studyDefinitions": "/v2/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819?sdruploadversion=1", "auditTrail": "/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819/audittrail", "studyDesigns": [{ "studyDesignId": "SD01", "studyDesignLink": "/v2/studydesigns?study_uuid=11adcf54-82cf-40d2-81a5-092d4e5b6819&sdruploadversion=1&studydesign_uuid=SD01" }], "SoA": "/v2/studydefinitions/11adcf54-82cf-40d2-81a5-092d4e5b6819/studydesigns/soa?sdruploadversion=1" } } </pre>	
400	<pre> { "statusCode": "400", "message": "An error occurred" } </pre>	Application Exception

401	<pre>{ "statusCode": "401", "message": "Access Denied" }</pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<pre>{ "statusCode": "404", "message": "The requested study document not found" }</pre>	When Study Title is given in query param and there is no matching study definition in SDR, or the requested URI is not valid.
500	<i>Internal Server Error</i>	Web server/Web API down

3.7. GET Change Audit

This endpoint allows user to retrieve the change audit for a particular study.

Table 64 GET Change Audit Endpoint

Method	URL
GET	/api/studydefinitions/{studyId}/changeaudit

REQUEST PARAMETERS

Table 65 GET Change Audit Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
Path Parameter	StudyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d

RESPONSE

Table 66 GET Change Audit Response

Status	Response	Comments
200	<pre>{ "changeAudit": { "studyId": "8059cf15-57e9-45e3-a64b-5681896a0ffe", "changes": [{ "entryDateTime": "2022-10-19T10:32:17.673Z", "SDRUploadVersion": 2, "elements": ["clinicalStudy.studyType", "clinicalStudy.studyPhase"] }] } }</pre>	
400	<pre>{ "statusCode": "400", "message": "An error occurred" }</pre>	Application Exception
401	<pre>{ "statusCode": "401", "message": "Access Denied" }</pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.

403	<i>Forbidden</i>	Invalid Client Certificate
404	{ "statusCode": "404", "message": "The requested study document not found" }	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

3.8. GET Raw JSON

This endpoint allows user to retrieve a particular study irrespective of the usdmVersion that is stored in SDR. This is useful for retrieving study data in plain text (stringified JSON), which is conformant to a USDM version that is not being supported in the current running instance of SDR. At a given point in time SDR will only support 3 USDM versions. When it is upgraded to a version that doesn't support any of the earlier versions of USDM, but the repository has studies conforming to those deprecated version, the data can be still retrieved via this endpoint. The version specific endpoints of that deprecated USDM version would have been decommissioned.

Table 67 GET Raw JSON Endpoint

Method	URL
GET	/api/studydefinitions/{studyId}/rawdata

REQUEST PARAMETERS

Table 68 GET Raw JSON Request Parameters

Type	Param Name	Values	Mandatory	Sample Values
------	------------	--------	-----------	---------------

Path Parameter	studyId	String	Yes	25f58eb5-bda8-4c85-8a27-685af9f6743d
Header (Either Authorization bearer token or API-Key)	Authorization	String	Yes	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSIsImtpZCI6IjJaUXBKM1VwYmpBWVhZR2FYRUpsOGxWMFRPSSJ9.eyJhdWQiOiJhcGk6Ly9iZDhiZjM2Zi0yYTczLTQxMzYtODQxOS0wYzlwY2U5NGM1YmMiLCJpc3MiOiJodHRwczovL3N0cy53aW5kb3dzLm5ldC9hM
	x-api-key	String	Yes	a7fecf90a4f643eda0b27dddde37b16d

RESPONSE

Table 69 GET Raw JSON Response

Status	Response	Comments
200	<pre>{ "studyDefinitions": { "clinicalStudy": { "studyId": "7637afd1-d667-47c0-a842-780e129b73f8", "studyTitle": "Study of Biliary Duct Cancer", "studyVersion": "1", "studyType": { "codeId": "7bbb6fd9-7e43-4dbf-90fa-3de117dc76d2", "code": "C98388", "codeSystem": "http://www.cdisc.org", "codeSystemVersion": "2022-03-24", "decode": "INTERVENTIONAL" }, "studyRationale": "Rational", "studyAcronym": "Acronym", "studyIdentifiers": [{ "studyIdentifierId": "c4663375-29be-4b37-9a7d-b2ef927fdf64", "studyIdentifier": "CT-GOV-1234", "studyIdentifierScope": { "organisationId": "96dd6b83-2d34-45ac-9d08-3e647b2c7316", "organisationIdentifier": "CT-GOV", "organisationIdentifierScheme": "FDA", "organisationName": "ClinicalTrials.gov", "organisationType": { "codeId": "8fcecddf-bbe2-4e71-ad97-114cbc3f1cba", "code": "C2365x", "codeSystem": "http://www.cdisc.org", "codeSystemVersion": "1", "decode": "Clinical Study Sponsor" }, "organizationLegalAddress": { "text": "text", "line": "line2", "city": "city", "district": "district", "state": "state", "postalCode": "postalCode", "country": { "codeId": "8fcecddf-bbe2-4e71-ad97-114cbc3f1cba", "code": "C2365x", "codeSystem": "http://www.cdisc.org", "codeSystemVersion": "1", "decode": "Egypt" } }, "studyPhase": { "aliasCodeId": "61ad4d8f-527c-4f1d-b227-4bbf6141f616", "standardCode": { "codeId": "61ad4d8f-527c-4f1d-b227-4bbf6141f613", "code": "C49686", "codeSystem": "http://www.cdisc.org", "codeSystemVersion": "2022-03-25", "decode": "Phase IIa Trial" }, "standardCodeAliases": [{ "codeId": "61ad4d8f-527c-4f1d-b227-4bbf6141f613", "code": "C49686", "codeSystem": "http://www.cdisc.org", "codeSystemVersion": "2022-03-25", "decode": "Phase IIa Trial" }], "businessTherapeuticAreas": null, "studyProtocolVersions": null, "studyDesigns": null, "auditTrail": { "entryDateTime": "2023-03-17T06:07:39.546Z", "usdmVersion": "1.9", "SDRUploadVersion": 1 } } } }] } } }</pre>	
400	{	Application Exception

Status	Response	Comments
	<pre>"statusCode": "400", "message": "An error occurred" }</pre>	
401	<pre>{ "statusCode": "401", "message": "Access Denied" }</pre>	When the API is invoked without access token or an expired access token, then the API will give an unauthorized response.
403	<i>Forbidden</i>	Invalid Client Certificate
404	<pre>{ "statusCode": "404", "message": "The requested study document not found" }</pre>	Requested Study Id is not found, or the request URL path is not valid
500	<i>Internal Server Error</i>	Web server/Web API down

4. Testing the API Endpoint

4.1. Postman REST client Setup

This section details steps to test the SDR RI API endpoints using a REST client. For the purpose of this document the tool used is Postman REST Client.


PRE-REQUISITES:

- Self-Signed .pfx certificate configured for SDR API Access.
- Install **Postman Tool**

STEPS:


- Open postman and go to “Settings” option.

Figure 13 Postman Upload Certificate



- Go to “Certificates” tab and upload the client certificate and provide the Host Name and Passphrase (certificate password) for the client certificate.

Figure 14 Postman Add Client Certificate




4.2. Accessing the GET API

STEPS:


- i. Enter the URL for the GET Request URL (APIM endpoint) as mentioned below.
<https://apim-sdr-envname-eastus.azure-api.net/api/v3/studydefinitions/{studyId}>
- ii. Get the **StudyId** from **Response for GET StudyV2.0** and replace the Study ID path parameter value in the GET URL.

Figure 15 Postman set HTTP Request for GET



- iii. Click on the “Send” button to get the study definition data for given studyId.

Figure 16 Postman Send Request



- iv. For a valid certificate and correct SDR API URL, the API Response of HTTP Status code 200 along with the data will be returned.

[illegible]

- 400 – The server cannot or will not process the request due to something that is perceived to be a client error
- 403 - indicates that the server understands the request but refuses to authorize it
- 404 - indicates that the server cannot find the requested resource
- Incorrect Domain/hostname
- Incorrect Protocol
- Incorrect Method