Certificate of Compliance

This certificate is issued for the following:

Swing Check Valves

Models H44X2, H44X2A, H84X and H84XF4
(see full listing attached)

Prepared for:
Jinan Meide Casting Co Ltd
Meide Science and Technology Park
Pingyin Industrial Park
Jinan, Shandong 250400
China

FM Approvals Class: 1210 (June 2004)

Approval Identification: PR456599

Approval Granted: November 18, 2020

To verify the product continues to be Approved please refer to www.approvalguide.com.

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

David B. Fuller
VP, Manager – Fire Protection
FM Approvals
1151 Boston-Providence Turnpike
Norwood, MA 02062

Member of the FM Global Group

FM APPROVED

Certificate of Compliance

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
H44X2-200	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	a
H44X2-PN10	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	a
H44X2-PN16	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1600)	a
H44X2-250	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1600)	a
H44X2-300	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2070)	a
H44X2-363	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	363	(2505)	a
H44X2A-PN10	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	a
H44X2A-200	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	a
H44X2A-PN16	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1600)	a
H44X2A-250	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	250	(1725)	a
H44X2A-300	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2070)	a
H44X2A-363	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	363	(2505)	a
H84X-200	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	a

FM Approvals®

Member of the FM Global Group

FM APPROVED

Certificate of Compliance

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
H84X-200	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	200	(1380)	a
H84X-250	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	250	(1725)	a
H84X-250	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	250	(1725)	a
H84X-300	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5. 6, 8, 10, 12	(50, 65, 80, 100, N/A, 200, 250, 300)	300	(2070)	a
H84X-300	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	300	(2070)	a
H84X-363	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	363	(2505)	a
H84X-363	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	363	(2505)	a
H84X-PN10	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	a
H84X-PN10	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	175	(1205)	a
H84X-PN16	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1600)	a
H84X-PN16	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	232	(1600)	a
H84XF4-200	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	a
H84XF4-200	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	200	(1380)	a

FM Approvals®

Member of the FM Global Group

FM APPROVED

Certificate of Compliance

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
H84XF4-250	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	250	(1725)	a
H84XF4-250	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	250	(1725)	a
H84XF4-300	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2070)	a
H84XF4-300	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	300	(2070)	a
H84XF4-363	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	363	(2505)	a
H84XF4-363	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	363	(2505)	a
H84XF4-PN10	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	a
H84XF4-PN10	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	175	(1205)	a
H84XF4-PN16	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1600)	a
H84XF4-PN16	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	232	(1600)	a

FM Approvals®

Member of the FM Global Group