FM APPROVED

Certificate of Compliance

This certificate is issued for the following:

PIPE FITTINGS

The following items are FM Approved for Jinan Meide Casting Co. Ltd. when manufactured at the plant listed on page 17:

Pipe Fittings \ Welded Pipe Outlets:

Product Designation	*Fitting Description*	*Nominal Run Pipe Size, in.*	*Nominal Outlet Pipe Size, in.*	*Max Working Pressure, psi (kPa)*	*Remarks*
BNO	Welded Pipe Outlet Threaded	1, 1-1/4, 1-1/2, 2, 3, 4, 6	1/2	300 (2070)	a
		1, 1-1/2, 2, 2-1/2, 3, 4, 6	3/4		
		1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6	1		
		1-1/2, 2, 2-1/2, 3, 4, 6	1-1/4		
		2, 2-1/2, 3, 4, 6	1-1/2		
		2-1/2, 3, 4, 6, 8	2		
		3, 4, 6, 8	2-1/2		
		4, 6, 8	3		
		6, 8	4		
BNOG	Welded Pipe Outlet Grooved	1-1/2, 2, 2-1/2, 3, 4, 6	1-1/4	300 (2070)	a
		2, 2-1/2, 3, 4, 6	1-1/2		
		2-1/2, 3, 4, 6, 8	2		
		3, 4, 6, 8	2-1/2		
		4, 6, 8	3		
		6, 8	4		
		8	6		

Remarks:
a. Outlet connection achieved by welding fitting to pipe. Requires precutting of hole in pipe.

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Pipe Fittings \ Pipe Fittings:

Product Designation	*Fitting Description*	*End Connection*	*Nominal Pipe Size, in.*	*Max Working Pressure, psi (kPa)*	*Remarks*
1#	90° Bend	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300 (2070)	a
			6	300 (2070)	a
1A	90° Bend Short	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 4	500 (3445)	a
2#	90° Bend	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
2A	90° Bend Short	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
3#	90° Bend	Male BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
40	45° Bend	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP X Female BSP	6	300 (2070)	a
41	45° Bend	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
85	Crossover	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
90	90° Elbow	Grooved	76 mm	500 (3445)	b
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
90R	90° Reducing Elbow	BSP	1/2×1/4, 3/8, 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×3/8, 1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
			6×4	300 (2070)	a
90S	90° Short Radius Elbow	Grooved	114, 165 mm	365 (2510)	b
92	90° Street Elbow	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
92R	90° Reducing Street Elbow	BSP	3/4×1/2 1×3/4	500 (3445)	a

FM Approvals®

Member of the FM Global Group

R50

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
95	Union Elbow, Flat Seat without gasket	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
96	Union Elbow, Conical Joint Iron to Iron	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
97	Union Elbow, Flat Seat without gasket	Male BSP X Female BSP	1-1/2	500 (3445)	a
98	Union Elbow, Conical Joint Iron to Iron	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
110	22.5° Elbow	Grooved	73 mm	500 (3445)	b
120	45° Elbow	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
121	45° Street Elbow	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
130	Equal Tee	Grooved	76 mm	500 (3445)	b

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	*Fitting Description*	*End Connection*	*Nominal Pipe Size, in.*	*Max Working Pressure, psi (kPa)*	*Remarks*
130	Equal Tee	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
130R	Reducing Tee	Grooved	60 x 48 mm 88.9 x 48, 60, 73 mm 114.3 x 34, 60, 73, 88.9 mm 141 x 114.3 mm 168 x 60, 73, 89, 114, 141 mm	500 (3445)	b
			219.1 x 60, 89, 114.3, 141.3, 168 mm	300 (2070)	b
		BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×3/8, 1/2, 3/4, 1 1-1/2×3/8, 1/2, 3/4, 1, 1-1/4 2×3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×3/4, 1/2, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
130R	Reducing Tee	BSP	1, 1-1/4, 1-1/2 ×3/4×3/4 1-1/4×1/2×1/2 1-1/4, 1-1/2, 2 ×1×1 1-1/2, 2 ×1-1/4×1-1/4 2×1-1/2×1-1/2 2-1/2, 3 ×2×2 3/4×1/2×3/4 1×1/2×1, 1×3/4×1, 1×1/4×1 1-1/4×1/2×1-1/4, 1-1/4×3/4×1-1/4, 1-1/4×1×1-1/4 1-1/2×1/2×1-1/2, 1-1/2×3/4×1-1/2, 1-1/2×1×1-1/2, 1-1/2×1-1/4×1-1/2 2×1/2×2, 2×3/4×2, 2×1×2, 2×1-1/4×2, 2×1-1/2×2 2-1/2×1-1/2×2-1/2, 2-1/2×2×2-1/2 3/4×1/2×1, 1×1/2×3/4, 1×3/4×1/2 1-1/4×1/2×3/4, 1 1-1/4×3/4×1/2, 1 1-1/4×1×1/2, 3/4 1-1/2×3/4×1, 1-1/4 1-1/2×1×1/2, 1-1/4 1-1/2×1-1/4×1/2, 3/4, 2 2×1×1-1/2 2×1-1/4×1, 1-1/2 2×1-1/2× 3/4, 1, 1-1/4 2-1/2×2×1/2, 1, 1-1/4	500 (3445)	a
			6×2, 3, 4	300 (2070)	a

FM Approvals®

Member of the FM Global Group

LBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
130S	Short Radius Tee	Grooved	114, 165 mm	365 (2510)	b
131	Equal Tee	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
134	Service Tee	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
134R	Service Tee Reducing	BSP	2×1-1/2 2-1/2×2 3×2-1/2	500 (3445)	a
165	Lateral Y Branch	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
180	Equal Cross	Grooved	60, 73, 76, 89, 114, 141, 165, 168 mm	500 (3450)	b
			219 mm	300 (2070)	b
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
180R	Reducing Cross	BSP	3/4×1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×3/4, 1, 1-1/4, 1-1/2 2-1/2×3/4, 1, 1-1/4, 1-1/2, 2 3×3/4, 1, 1-1/4, 1-1/2, 2 4×1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
220	Coupling	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
230	Eccentric Reducer	Grooved	219 x 168 mm 273 x 219 mm	365 (2510)	b
240	Reducing Socket	BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×1/4, 3/8, 1/2, 3/4, 1 1-1/2×1/4, 3/8, 1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3445)	a
240	Concentric Reducer	Grooved	89 x 42 mm 141 × 89, 114 mm	500 (3450)	b
240N	Concentric Reducer	Grooved × Female NPT	89 x 21 mm 141.3 x 89, 114 mm	500 (3450)	b
241	Bushing	BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×1/4, 3/8, 1/2, 3/4, 1 1-1/2×1/4, 3/8, 1/2, 3/4, 1, 1-1/4 2×1/4, 3/8, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1-1/2, 2 3×2, 2-1/2 3-1/2×3 4×3/4, 1, 1-1/4, 1-1/2, 3	500 (3445)	a
			5×3, 4 6×2, 2-1/2, 5	300 (2070)	a
241D	Bushing	BSP	2×1/2, 3/4 2-1/2×1, 1-1/4 3×1/2, 3/4, 1, 1-1/4, 1-1/2 4×2, 2-1/2	500 (3445)	a

FM Approvals®

Member of the FM Global Group

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
241D	Bushing	BSP	6×3, 4	300 (2070)	a
245	Hex Nipple Reducing	BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2 3×1-1/2, 2, 2-1/2 4×2, 4×2-1/2, 4×3	500 (3445)	a
246	Extension Reducing	Male BSP X Female BSP	1/2×1/4, 3/8 3/4×3/8, 1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×3/4, 1, 1-1/4 2×1, 1-1/4, 1-1/2	500 (3445)	a
270	Socket	BSP Parallel Threads	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
271	Socket	BSP Right and Left Threads	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
280	Hex Nipple	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
291	Plug, Sq. Hd.	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
291N	Plug, Sq. Socket	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
291S	Plug, Solid Sq.	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
300	End Cap	Grooved	89, 114, 140, 165 mm	500 (3450)	b
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
300PX	End Cap with BSP threaded outlet	Grooved × BSP	89 x 48, 60 mm 114 x 48, 60 mm 140 x 48, 60 mm 165 x 48 mm 168 x 48, 60 mm	500 (3445)	b
			219 x 48, 60 mm	300 (2070)	b
310	Locknut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
312	Backnut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 4	500 (3445)	a
321-4	Flange Adapter	Flanged × BSP	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
321-4	Flange Adapter	Flanged × BSP	6	300 (2070)	a
321-6	Flange Adapter	Flanged × BSP	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
321G	Flange Adapter	Flanged × Grooved	60, 73, 76.1, 89, 114 mm	365 (2510)	b
			139.7, 141.3, 165, 168, 219, 273, 324 mm	225 (1550)	b
321H	Flange Adapter	Flanged × BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
321N	Flange Adapter	Flanged × BSP	2	500 (3450)	a
321P	Flange Adapter	Flanged × BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			5, 6	300 (2070)	a
321PW	Flange Adapter	Flanged × BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			5, 6	300 (2070)	a
321TD	Flange Adapter	Flanged × BSP	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			6	300 (2070)	a
321W	Flange Adapter	Flanged × BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a

FM Approvals®

Member of the FM Global Group

FM APPROVED

Certificate of Compliance

Product Designation	*Fitting Description*	*End Connection*	*Nominal Pipe Size, in.*	*Max Working Pressure, psi (kPa)*	*Remarks*
330	Union Flat Seat without gasket	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
331	Union Flat Seat without gasket	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
340	Union Conical Joint Iron to Iron	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
340F	Union Nut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
341	Union Conical Joint Iron to Iron	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
342	Union Conical Joint Brass to Iron	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
526	Extension	BSP	1/2	500 (3445)	a
529A	Extension Long	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
529X	Extension Short	BSP	1/2	500 (3445)	a

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Product Designation	*Fitting Description*	*End Connection*	*Nominal Pipe Size, in.*	*Max Working Pressure, psi (kPa)*	*Remarks*
1090	90° Elbow Plain	BSP	1/2, 3/4, 1, 1-1/4, 2	500 (3445)	a
1130	Equal Tee Plain	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
1220	Socket Plain	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
1221	Side Outlet Elbow	BSP	1/2, 3/4, 1, 1-1/4, 2	500 (3445)	a
1223	Side Outlet Tee	BSP	1/2, 3/4, 1	500 (3445)	a
Steel Merchant Socket	Socket	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	d
			4, 5, 6	300 (2070)	d
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	d
			4, 5, 6	300 (2070)	d

Remarks:
a. Malleable Iron Fittings
b. Ductile Iron Fittings
c. Cast Iron Fittings
d. Steel Fittings

FM Approvals®

Member of the FM Global Group

RSD

FM APPROVED

Certificate of Compliance

Grooved Couplings or Fittings \ Grooved Couplings, Standard-Rigid:

Product Designation	*Nominal Pipe Size, in.*	*Pipe Ends*	*Remarks*	*Max Working Pressure, psi (kPa)*
1G	73 mm	Cut Groove Rolled Groove	c, d	300 (2070)
1GS	114 mm	Cut Groove Rolled Groove	c, d	300 (2070)

Remarks:
c. Approved when supplied with EPDM gasket.
d. Approved for use with GB/T3092 regular and extra heavy pipe, ISO 4200, and BS 1387 medium and heavy pipe.

FM Approvals®

Member of the FM Global Group

RBD

FM APPROVED

Certificate of Compliance

Pipe Fittings \ Fittings, Side Outlet, Rigid:

Product Designation	*Fitting Description*	*Nominal Pipe Size, in.*	*Remarks*	*Max Rated Pressure, psi (kPa)*
3GS	Mechanical Tee, Grooved Outlet	89 x 34, 42, 48, 60 mm	a, c	365 (2510)
		114 x 34, 42, 48, 60, 73, 76, 89 mm 133 x 89 mm 140 x 42, 48, 60, 76, 89 mm 159 x 108, 114 mm 165 x 42, 48, 60, 76, 89, 108, 114 mm 168 x 42, 48, 60, 73, 76, 89, 114 mm 219 x 60, 73, 76, 89, 108, 114 mm	a, c	300 (2070)
3JS	Mechanical Tee, Threaded Outlet	89 x 21, 27, 34, 42, 48, 60 mm	a, b, c, d	365 (2510)
		114 x 21, 27, 34, 42, 48, 60, 73, 76, 89 mm 168 x 34, 42, 48, 60, 73, 76, 89, 114 mm 219 x 34, 42, 48, 60, 73, 76, 89, 114 mm	a, b, c, d	300 (2070)
		108 x 21, 27, 34, 42, 48, 60, 76 mm 133 x 21, 27, 34, 42, 48, 60, 76, 89 mm 140 x 21, 27, 34, 42, 48, 60, 76, 89, 114 mm 159 x 21, 27, 34, 42, 48, 60, 76, 89, 114 mm 165 x 21, 27, 34, 42, 48, 60, 76, 89, 114 mm	a, c, d	300 (2070)

Remarks:
a. For use on Schedule 10 and heavier steel sprinkler pipe.
b. Approved when supplied with NPT female threads.
c. Approved when supplied with EPDM gasket.
d. Approved when supplied with BSP or DIN female threads.

FM Approvals®

Member of the FM Global Group

RBE

FM APPROVED

Certificate of Compliance

Grooved Couplings or Fittings \ Grooved Split Flanges-Flexible:

Product Designation	*Fitting Description*	*Nominal Pipe Size, in.*	*Remarks*	*Max Rated Pressure, psi (kPa)*
321S	Split Flange	48, 60, 76, 89, 108, 114 mm	a, b, c, d, e	365 (2510)
		133, 140, 159, 165, 168 mm	a, b, c, d, e	225 (1550)
321HS	Split Flange	108 mm	a, b, c, e, f	365 (2510)
		165 mm	a, b, c, e, f	225 (1550)

Remarks:
a. Minimum schedule cut groove pipe to be joined: 6 in. NPS and smaller - Schedule 40; 8 in. NPS and larger - Schedule 30.
b. Minimum schedule rolled groove pipe to be joined: 6 in. NPS and smaller - Schedule 10S; 8 in. NPS and larger 0.188 in. (5 mm) wall.
c. Approved when supplied with EPDM gasket.
d. Approved when supplied with an ISO PN10 bolt pattern.
e. Approved when used with GB/T3092 regular and extra heavy pipe, ISO 4200, and BS 1387 Medium and Heavy pipe.
f. Approved when supplied with an ISO PN25 bolt pattern

FM Approvals®

Member of the FM Global Group

RBA

FM APPROVED

Certificate of Compliance

Manufactured by:

Jinan Meide Casting Co., Ltd.
No. 3 Nanmen Road
Pingyin, Jinan 250400
P.R. China

FM Approvals Class: 1920

Approval Identification: 3038663 Approval Granted: March 4, 2011

Said Approval is subject to satisfactory field performance, continuing follow-up Facilities and Procedures Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

For more than 160 years FM Approvals has partnered with business and industry to reduce property losses.

Richard B. Dunne
Group Manager – Hydraulics Group
FM Approvals
1151 Boston-Providence Turnpike
Norwood, MA 02062

March 4, 2011

FM Approvals®

Member of the FM Global Group