CERTIFICATE OF COMPLIANCE

Certificate Number	EX6624
Report Reference	EX6624-20110309
Issue Date	2020-SEPTEMBER-29

Issued to: JINAN MEIDE CASTING CO LTD

Meide Science and Technology Park, Pingyin Industrial Park, JINAN, SHANDONG 250400 CHINA

This certificate confirms that representative samples of FITTINGS, CAST IRON, DUCTILE IRON, MALLEABLE IRON AND BRONZE

See addendum page for Models

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ISO 49/EN10242 - Threaded Pipe Fittings in Malleable Cast Iron
EN 10241 - Threaded Steel Fittings
ASTM A865 - Standard Specification for Threaded Couplings, Steel, Black or Zinc-Coated(Galvanized) Welded or Seamless, for Use In Steel Pipe Joints
BS 1387 - Specification for Screwed and socketed steel tubes and tubulars and for plain end steel tubes suitable for welding or for screwing to BS 21 pipe threads
UL213 - Standard for Rubber Gasketed Fittings for Fire Protection Service
ULC/ORD C213 - Other Recognized Document for Standard for Rubber Gasketed Fittings for Fire Protection Service

Additional Information: See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models

USL, CNL – Malleable Iron Fittings. The fittings consist of the following models, types, sizes, and rated pressures.

Malleable Iron Fittings, ISO 49/EN 10242 (threads manufactured in accordance with ISO 7-1):

Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
1#	Bend 90 degree, male and female	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6"	Threaded	500
1A	Short Bend 90 degree, male and female	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2"	Threaded	500
2#	BEND 90 DEGREE, FEMALE	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4"	Threaded	500
2A	SHORT BEND 90 DEGREE, FEMALE	1/2",3/4",1",1-1/4",1-1/2",2"	Threaded	500
3#	Bend 90 degree, male	3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4"	Threaded	500
40	Bend 45 degree, male and female	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6"	Threaded	500
41	Bend 45 degree, female	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4"	Threaded	500
85	Crossover	1/2",3/4",1",1-1/4",1-1/2",2"	Threaded	500
90	*Elbow, 90 degree*	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6", 5”	Threaded	500
Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
90R	Elbow, 90 degree, reducing	3/8"X1/4",1/2x3/8”,3/4x3/8”,3/4x1/2”,1x1/2”,1x3/4”,1-1/4x3/4”,1-1/4x1”,1x1/4”,1x3/8”,1x1/2”,1x3/4”,1-1/4x3/8”, 1-1/4x1/2”, 1-1/4x3/4”, 1-1/4x1”,1-1/2x1/2”,1-1/2x3/4”,1/4x1/8,3/8x1/8,1/2x1/4,3/4x1/4,1x1/4,1x3/8,1-	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

		1/4x3/8,1-1/4x1/2,1-1/2x1/2,1-1/2x3/4,2x1/2,2x3/4,2x1,2x1-1/4,2-1/2x1/2,2-1/2x3/4,2-1/2x1,2-1/2x1-1/4,2-1/2x1-1/2,3x3/4,3x1,3x1-1/4,3x1-1/2,3x2,3x2-1/2,4x1,4x1-1/4,4x1-1/2,4x2,4x2-1/2,4x3,6x4 11/2x1", 11/2x11/4", 2x11/2", 21/2x2"		
92	*Stree Elbow, 90 degree*	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6"	Threaded	500
92R	Stree Elbow, 90 degree, reducing	3/4"X1/2",1"X3/4"	Threaded	500
95	Union elbow, F&F, Flat seat without gasket	1/2",3/4,1,1-1/4,1-1/2,2"	Threaded	500
96	Union elbow, F&F, conical joint iron to iron	1/4,3/8,1/2",3/4,1,1-1/4,1-1/2,2"	Threaded	500
97	*Union elbow, M&F, Flat seat without gasket*	11/2"	Threaded	500
98	*Union elbow, M&F, conical joint iron to iron*	1/2",3/4,1,1-1/4,1-1/2,2"	Threaded	500
120	*Elbow, 45 degree*	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2,2-1/2",3",4",5,6"	Threaded	500
121	*Stree Elbow, 45 degree*	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2, 2-1/2,3,4"	Threaded	500
130	*Tee*	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",5,6"	Threaded	500

Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
130R	*Tee, reducing*	3/8x1/4,1/2x1/4,1/2x3/8,3/4x1/4, 3/4x3/8,3/4x1/2,1x1/4,1x3/8, 1x1/2,1x3/4,1-1/4x3/8,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x1/2,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1/2,2x3/4,2x1, 2x1-1/4,2x1-1/2,2-1/2x1,2-1/2x1-1/4,2-1/2x1-1/2, 2-	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

1/2x2,3x1,3x1-1/4,3x1-1/2,3x2,3x2-1/2,4x2,4x3,1/4x1/8,1/2x1/8,1-1/2x3/8,2x3/8,2-1/2x1/2,2-1/2x3/4,3x1/2,3x3/4, 4x1/2,4x3/4,4x1,4x1-1/4,4x1-1/2,4x2-1/2,6x2,6x3,6x4, 1/2x1/2x3/4,1/2x1/2x1,3/4x3/4x1, 3/4x3/4x1-1/4,1x1x1-1/4,1x1x1-1/2,1x1x2,1x1x2-1/2,1-1/4x1-1/4x1-1/2,1-1/4x1-1/4x2,1-1/2x1-1/2x2,1-1/2x1-1/2x2-1/2,2x2x2-1/2,2-1/2x2-1/2x3,2-1/2x2-1/2x4, 3/4x1/2x1/2,1x1/2x1/2,1x3/4x3/4, 1-1/4x1/2x1/2,1-1/4x3/4x3/4,1-1/4x1x1,1-1/2x3/4x3/4,1-1/2x1x1,1-1/2x1-1/4x1-1/4,2x1x1,2x1-1/4x1-1/4,2x1-1/2x1-1/2,2-1/2x2x2,3x2x2,3/4x1/2x3/4,1x1/2x1,1x3/4x1,1x1/4x1,1-1/4x1/2x1-1/4,1-1/4x3/4x1-1/4,1-1/4x1x1-1/4,1-1/2x1/2x1-1/2,1-1/2x3/4x1-1/2,1-1/2x1x1-1/2,1-1/2x1-1/4x1-1/2,2x1/2x2,2x3/4x2,2x1x2,

Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
130R		2x1-1/4x2,2x1-1/2x2,2-1/2x1-1/2x2-1/2,2-1/2x2x2-1/2,3/4x1/2x1,1x1/2x3/4,1x3/4x1/2, 1-1/4x1/2x3/4,1-1/4x1/2x1,1-1/4x3/4x1/2,1-1/4x3/4x1,1-1/4x1x1/2,1-1/4x1x3/4,1-1/2x3/4x1,1-1/2x3/4x1-1/4,1-1/2x1x1/2,1-1/2x1x1-1/4,1-1/2x1-1/4x1/2, 1-1/2x1-1/4x3/4,1-1/2x1-1/4x1, 1-1/2x1-1/4x2,2x1x1-1/2,2x1-1/4x1,2x1-1/4x1-1/2,2x1-1/2x1/2,2x1-1/2x3/4,2x1-1/2x1,2x1-1/2x1-1/4,2-1/2x2x1/2,2-1/2x2x1,2-1/2x2x1-1/4	Threaded	500
131	Pitcher Tee, equal 90 degree	1/2,3/4,1,1-1/4,1-1/2, 2"	Threaded	500
134	Service Tee, equal	1/4",1/2,3/4,1,1-1/4,1-1/2, 2"	Threaded	500
134R	Service Tee, Reducing	2"X11/2",2-1/2x2,3X21/2"	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

165	Lateral Y branch, 45 degree	1/2",3/4",1",1-1/4",1-1/2",2",	Threaded	500
180	Cross	2-1/2",3",4 1/8",1/4,1/2",3/4",1",1-1/4",1-1/2",2", 2-1/2",3",4", 3/8"	Threaded	500
180R	Cross, reducing	3/4"X1/2",1x1/2,1x3/4,1-1/4x3/4, 1-1/4x1,11/2"X1",11/4"X1/2",1-1/2x1/2,1-1/2x3/4,1-1/2x1- 1/4,2x3/4,2x1,2x1-1/4, 2x1- 1/2,21/2"X1",21/2"X11/4",21/2"X11/2",21/2"X2",3x3/4,3x1,3 x1-1/4,3x1-1/2,3"X2",3"X21/2",4x1,4x1-1/4,4x1-1/2, 4x2,4x2-1/2,4"X3"	Threaded	500
220	Socket/Coupling	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",5,6"	Threaded	500

Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
240	Socket/Coupling, reducing	1/4"X1/8",3/8x1/8,3/8x1/4,1/2x1/4, 1/2x3/8,3/4x1/4,3/4x3/8,3/4x1/2, 1x3/8,1x1/2,1"X3/4",11/4"X1/2",1-1/4x3/4,1-1/4x1,1- 1/2x1/2, 1-1/2x3/4,1-1/2x1,1-1/2x1-1/4, 2x1/2,2x3/4,2x1,2x1- 1/4,2"X11/2",21/2"X11/4",21/2"X11/2,21/2"X2, 3x1-1/2,3x2,3"X21/2",1/2"X1/8",3/4"X1/8",1x1/4,1-1/4x1/4, 1-1/4x3/8,1-1/2x1/4,1-1/2x3/8,2-1/2x1/2, 2-1/2x3/4,2-1/2x1,3x1/2,3x3/4,3x1, 3"X11/4"	Threaded	500
241	Bushing(241)	1/4"X1/8",3/8x1/8,3/8x1/4,1/2x1/8, 1/2x1/4,1/2x3/8,3/4x1/8,3/4x1/4, 3/4x3/8,3/4x1/2,1x1/8,1x1/4,1"X3/8",1x1/2,1x3/4,1- 1/4x1/4,1-1/4x3/8,1-1/4x1/2,1-1/4x3/4,1-1/4x1,1-	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

		1/2"X1/4",1-1/2"X3/8", 1-1/2"X1/2",21/2"X11/2",2-1/2x2,3x1/2, 3x3/4,3x2,3"X21/2",11/2"X3/4",1-1/2x1,1-1/2x1-1/4, 2x1/4,2x3/8,2x1,2x1-1/4,2x1-1/2,2-1/2x1/2,21/2"X3/4",31/2"X3",4x3/4,4x1,4x1-1/4, 4x1-1/2,4x3,5x3,5x4, 6x2,6x2-1/2,6x5		
241D	Bushing(241D)	2"X1/2",2x3/4,2-1/2x1,2-1/2x1-1/4, 3x1,3x1-1/4,3x1-1/2,4x2, 4x2-1/2,6x3,6x4	Threaded	500
Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
245	Hexagon Nipple, reducing	3/8"X1/4",1/2x1/4,1/2x3/8, 3/4x3/8,3/4x1/2,1x1/2,1x3/4, 1-1/4x1/2,1-1/4x3/4,11/4"X1",11/2"X3/4",1-1/2x1,1-1/2x1-1/4, 2x1,2x1-1/4,2x1-1/2,2-1/2x2, 3x2,3"X21/2",1/4"X1/8",3/4x1/4,1-1/2x1/2, 2x1/2,2x3/4,2-1/2x1,2-1/2x1-1/4, 2-1/2x1-1/2,3x1-1/2,4x2,4x2-1/2, 4"X3"	Threaded	500
246	Extension piece, sockets M&F, reducing	3/8"X1/4",1/2x1/4,1/2x3/8,3/4x3/8, 3/4x1/2,1x1/2,1x3/4,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1,2x1-1/4,2"X11/2"	Threaded	500
270	Socket, parallel threads, equal	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",6"	Threaded	500
271	Socket, right & left threads	1/2",3/4,1,1-1/4,1-1/2,2"	Threaded	500
280	Hexagon Nipple, equal	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5",6"	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

291	*Plug*	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",6"	Threaded	500
291N	Countersunk Plug	1/2,3/4",1",1-1/4", 1-1/2",2",2-1/2",3"	Threaded	500
291S	Solid Plug	1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	Threaded	500
300	Cap	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	Threaded	500

Model	Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
310	Locknut	1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	Threaded	500
312	Backnut	1/2",3/4",1",1-1/4", 1-1/2",2",4"	Threaded	500
321-4	Flange(321-4)	1-1/4", 1-1/2",2",2-1/2",3",4",6"	Threaded	500
321-6	Flange(321-6)	1-1/4", 1-1/2",2",2-1/2",3",4",6"	Threaded	500
321H	Flange(321H)	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	Threaded	500
321N	Flange(321N)	2"	Threaded	500
321P	Flange, DRP D	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	Threaded	500
321PW	Flange, U/D	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	Threaded	500
321TD	Flange, BS Table D	1",1-1/4", 1-1/2",2",2-1/2",3",4",6"	Threaded	500
321W	Flange, without bolt hole	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number EX6624
Report Reference EX6624-20110309
Issue Date 2020-SEPTEMBER-29

526	*Extension Tube*	1/2"X30,1/2"X40,1/2"X50,1/2"X60, 1/2"X100	Threaded	500
529A	Extention Long piece	1/2",3/4",1",1-1/4", 1-1/2",2"	Threaded	500
529X	Extention Short piece	1/2"	Threaded	500
1090	Elbow, 90 degree, plain	1/2",1-1/4",2"	Threaded	500
1130	Tee, plain	1/2",1",1-1/4", 1-1/2"	Threaded	500
1220	Socket, plain, with ribs	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3"	Threaded	500
1221	Side outlet elbow	1/2",3/4",1",1-1/4", 1-1/2",2"	Threaded	500
1223	Side outlet tee	1/2",3/4",1"	Threaded	500

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/