MC2661A/MC68661A MC2661B/MC68661B MC2661C/MC68661C Addendum

ENHANCED PROGRAMMABLE COMMUNICATIONS INTERFACE (EPCI) Advance Information Data Sheet ADI-868-R1

The following footnote should be added to the **AC ELECTRICAL CHARACTERISTICS** table found on page 11 of the MC2661A, B, C/MC68661A, B, C Advance Information Data Sheet (ADI-868-R1).

10. In asynchronous local loopback mode, using the X1 clock, the following parameters apply: $f_{R/T} = 0.83 \text{ MHz maximum}$ $t_{R/TL} = 700 \text{ ns minimum}$

This footnote is referenced by the TxC or RxC Input Clock Frequency ($f_{R/T}$) and the TxC or RxC Low Clock Width ($t_{R/T}$ L) entries to the **AC ELECTRICAL CHARACTERISTICS** table.

Motorola reserves the right to make changes without further notice to any products herein to improve reliability, function or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others. Motorola and (A) are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Employment Opportunity/ Affirmative Action Employer.

©MOTOROLA INC., 1984 ADI-868-R1-A1



MOTOROLA Semiconductor Products Inc.

3501 ED BLUESTEIN BLVD., AUSTIN, TEXAS 78721 ◆ A SUBSIDIARY OF MOTOROLA INC.