

15

Deep Reinforcement Learning for Smart Irrigation

Aakansha Khanna

Chandigarh University, Ludhiana, India

Inzimam Ul Hassan

Vivekananda Global University, Jaipur, India

15.1 INTRODUCTION

Data-driven farming is a ground-breaking idea that was born out of the fusion of cutting-edge technology with traditional farming methods in the pursuit of sustainable agriculture and effective resource management. The incorporation of Artificial intelligence (AI) and Machine learning (ML) tools into conventional farming practices is at the core of this change. We explore the many ways that AI and ML are revolutionizing agriculture in the book *Data-Driven Farming: Harnessing the Power of AI and Machine Learning in Agriculture*, and in this chapter, we look at one of its most promising applications: Deep Reinforcement Learning for Smart Irrigation. Water scarcity is a serious problem that affects the entire world, especially the agricultural sector. As the world's population expands, the need for food rises, placing great strain on the planet's already limited water supplies. Finding a balance between the requirement to maintain crop production and ethical water use is a challenge. Conventional irrigation methods, which frequently rely on predetermined schedules or human intuition, can be extremely ineffective, wasting water, raising expenses, and perhaps lowering crop yields. In this situation, Deep Reinforcement Learning (DRL), a branch of ML, offers a revolutionary answer. DRL enables intelligent irrigation systems to make data-driven decisions in real time by enabling systems to learn from and adapt to

changing environmental conditions [1]. This chapter explains how DRL's capacity to optimize irrigation systems greatly aids in the paradigm change in agriculture toward resource conservation and precision farming. We start off by giving a thorough overview of the difficulties posed by conventional irrigation techniques and the potential repercussions of poorly managed water supplies. The fundamentals of DRL are then discussed, showing how it enables machines to discover the best irrigation systems through trial and error while accounting for a variety of environmental characteristics like crop varieties, soil moisture levels, and weather patterns. This chapter will examine real-world case studies and illustrations of successful DRL-based smart irrigation system installation in order to demonstrate the practical advantages these systems offer to farmers, the environment, and the global agricultural landscape [2]. The difficulties and factors to be taken into account when implementing such systems on a broad scale, such as data gathering, sensor technology, and acceptance hurdles, will be covered. We hope to showcase not just the promise of AI and ML in agriculture but also the crucial role they play in addressing some of the most important issues confronting our planet as we set out on this journey into the world of Deep Reinforcement Learning for Smart Irrigation. We open the door to a future that is more sustainable, effective, and productive by utilizing the power of data and technology [3].

DRL has significant potential in the field of agriculture. DRL can be used to maximize crop yield. It can help automate many tasks/subtasks for sustainable farming and lead the way to scalable agriculture solutions [4]. DRL-based AI solutions can be used for crop produce detection. The designed frameworks can be used for automating and controlling greenhouse-based farming processes. For developing a path toward sustainable agriculture, new species of plants are being developed with the help of DRL. These new designs can have far-reaching impacts on agricultural yields and the environment [5]. The deep learning (DL) model has important application value in crop classification, detection, counting, and yield estimation in agriculture. Compared with traditional ML, DL technology improved the performance of hyperspectral image analysis. Here are some key reasons why DRL is important in agriculture:

- **Optimizing Resource Management:** DRL can optimize the allocation of crucial resources in agriculture, such as water, fertilizers, and pesticides. By dynamically adjusting irrigation and nutrient delivery

based on real-time data, DRL helps minimize wastage, reduce costs, and maximize resource utilization [6].

- **Precision Agriculture:** DRL enables precision farming by tailoring actions to specific conditions in the field. It considers variables like soil moisture, weather patterns, crop health, and historical data to make informed decisions, ultimately leading to higher crop yields and quality.
- **Water Conservation:** DRL-based irrigation systems make sure that water is applied exactly when and where it is required, lowering water consumption and the environmental impact of farming.
- **Environmental Impact:** DRL contributes to reducing agriculture's environmental footprint. The use of inputs is optimized, and chemical runoff is reduced, which results in more environmentally friendly and sustainable farming methods [5].
- **Crop Yields Can Be Increased:** Using DRL to optimize irrigation, fertilization, and insect management can boost crop yields. DRL assists farmers in producing more with less by ensuring that crops receive the proper supplies at the proper time.
- **Real-Time Decision-Making:** From weather patterns to pest outbreaks, agricultural conditions are always changing. DRL systems enable farmers to react swiftly and successfully to these changes by making decisions in real time.
- **Savings on Labor:** DRL-driven automation can lessen the demand for manual labor in agriculture. Using autonomous drones with DRL algorithms, for instance, can monitor and manage crops while saving labor expenses associated with conventional farming methods.
- **Data-Driven Insights:** DRL generates enormous amounts of data, which may be examined to learn important information about the health of the soil, the detection of diseases, and crop performance. Long-term farming practices and decision-making can be influenced by these insights.
- **Climate Change Adaptation:** The impacts of climate change, such as erratic weather patterns and altering growth seasons, are particularly harmful to agriculture. By adjusting farming methods to changing conditions, DRL can assist farmers in adjusting to these changes [7].

15.1.1 Traditional Irrigation Practices and Their Limitations

Traditional irrigation techniques have been the backbone of agriculture for millennia, supporting civilizations and feeding the world's population.

These traditional techniques, built on the knowledge of previous generations of farmers, have slaked the thirst of crops, converting dry plains into abundant oases and lush green fields. Traditional irrigation techniques have impacted the landscapes and civilizations of our globe in ways that are as fundamental as the dirt that lies beneath our feet. However, they have drawbacks that may impede their effectiveness and sustainability [8]. Fixed-schedule irrigation and intuitive irrigation decision-making are two popular traditional irrigation techniques:

- **Fixed-Schedule Irrigation:** Using fixed-schedule irrigation, farmers water their crops according to preestablished calendars or schedules. Instead of using real-time data, this approach frequently draws on previous conventions and presumptions. Here are a few of its drawbacks:
 - Fixed schedules are inefficient because they don't take into account changes in soil moisture, weather, or crop water requirements. This can result in wasteful water use and possible crop health damage due to over- or underirrigation.
 - Excessive irrigation can lead to excessive water use, which raises operating costs and has negative effects on the environment, such as soil erosion and nutrient leaching.
 - On the other hand, underirrigation can stress crops, reduce yields, and impact overall crop quality.
 - Fixed schedules do not adapt to changing conditions, such as sudden rainfall or unexpected temperature fluctuations. This lack of adaptability can lead to poor irrigation decisions.
- **Intuitive Irrigation Decision-Making:** To decide when and how much to irrigate, farmers use intuitive irrigation decision-making, which is based on their experience, knowledge, and judgment. Even though knowledgeable farmers frequently have a thorough understanding of their crops and terrain, this strategy has drawbacks:
 - Farmers' intuitive judgments are individual and susceptible to change. The precise requirements of the crops or scientific data might not always be in agreement with it.
 - Farmers may occasionally make poor judgments regarding the amount of soil moisture present or fail to account for shifting weather patterns.
 - Relying solely on human judgment can be time-consuming because it necessitates ongoing field inspection and manual adjustments of irrigation systems.

In the realm of traditional irrigation practices, a paradox unfolds: While these methods have nourished crops and civilizations for centuries, they are not without their inherent inefficiencies and consequential challenges. In this section, we will delve into the intricacies of these inefficiencies and the far-reaching consequences they impose on agriculture and the environment [9].

15.1.2 Understanding Deep Reinforcement Learning

In the realm of AI and ML, DRL stands as a beacon of innovation, offering a pathway for machines to not just learn from data but to interact with and adapt to complex environments. Rooted in the fusion of reinforcement learning (RL) principles and deep neural networks, DRL represents a formidable leap forward in the quest to imbue machines with the ability to make sequential decisions, solve intricate tasks, and achieve optimal outcomes in a myriad of domains. DRL is fundamentally a learning-by-doing approach. It makes use of the same idea of trial and error, which has long been the basis of human learning. A digital explorer-like intelligent entity is let loose in a world full of opportunities and obstacles. Its purpose? Take acts, monitor the results, and, via a process of constant improvement, identify techniques that optimize rewards to navigate this terrain. These benefits act as a compass pointing the agent in the direction of its ultimate objective. Some key components of DRL:

Agent: An entity that can perceive/explore the environment and act upon it.

Environment: The world through which the agent moves and where the agent gets its feedback from.

Actions: Steps that the agent takes while moving through the environment.

Rewards: Feedback that the agent gets as a result of its actions. Positive feedback is given for good actions, and negative feedback or penalty is given for bad actions.

Policy: The strategy that the agent employs to determine the next action based on the current state.

Value Function: A prediction of future rewards. It's used to evaluate each state in terms of how good it is for the agent to be in that state.

Q-function or Action-Value Function: Similar to the value function but takes an extra parameter, the current action. Q-function gives the expected future reward for that action taken in the current state [6].

15.1.2.1 Introduction to Deep Learning

A branch of ML called “deep learning” has risen to the top of AI, changing the way that data analysis, pattern detection, and decision-making are done. DL is fundamentally a collection of methods and algorithms drawn from the structure and operation of the human brain, notably neural networks. It excels at processing huge, complicated datasets, allowing computers to identify patterns, forecast outcomes, and carry out previously thought-impossible tasks. DL’s defining feature is its utilization of deep neural networks, which are composed of multiple layers of interconnected artificial neurons. These networks have demonstrated remarkable prowess in various domains, including image and speech recognition, natural language processing, autonomous vehicles, and healthcare diagnostics. The hallmark of deep neural networks is their ability to automatically learn intricate features and representations from raw data, eliminating the need for hand-crafted feature engineering [5].

15.1.2.2 Combining Deep Learning and Reinforcement Learning

The marriage of DL and RL emerges as a potent and adaptable fusion in the vast tapestry of AI, where various problems call for versatile answers. The basis for comprehending and displaying complicated patterns in raw data is provided by DL. Its deep neural networks are particularly good at tasks involving perception, including identifying objects in pictures or deciphering text [10]. DL is crucial in the initial phases of decision-making because of its capacity to process sensory input. On the other hand, RL complements DL by focusing on sequential decision-making in dynamic environments. It introduces the concept of an agent interacting with an environment to learn optimal actions through trial and error [11]. RL algorithms aim to maximize a cumulative reward signal over time, making them well-suited for tasks requiring a sequence of actions or strategies. When DL and RL join forces, they create a symbiotic relationship that leverages the strengths of both paradigms:

- **Feature Extraction:** DL can be employed to preprocess raw sensor data (e.g., images, audio, and text) and extract meaningful representations. These representations serve as valuable inputs to RL agents, enhancing their ability to interpret and navigate complex environments.
- **Policy Approximation:** Deep neural networks can be used to approximate the policy function in RL. This allows RL agents to learn

high-dimensional, continuous action spaces efficiently, enabling them to tackle tasks that involve fine-grained control or complex actions.

- **Value Function Approximation:** DL aids in approximating the value functions in RL, which estimate the expected cumulative rewards. Deep Q-Networks (DQNs) and variants like Double DQN leverage deep neural networks to handle high-dimensional state spaces.
- **End-to-End Learning:** The combination of DL and RL enables end-to-end learning, where the entire decision-making pipeline, from perception to action, is learned directly from data. This approach has found success in applications like robotics and autonomous vehicles.
- **Transfer Learning:** DL models pretrained on large datasets can be fine-tuned for RL tasks, allowing agents to benefit from the rich representations learned across various domains. This technique, known as transfer learning, accelerates RL training and enhances its performance [3].

15.1.3 Deep Reinforcement Learning for Smart Irrigation

In the ever-evolving realm of agriculture, the quest for efficient and sustainable irrigation practices has taken on renewed importance. With the global population growing and environmental challenges mounting, the need to optimize the use of water resources in farming has never been greater. Enter DRL, a cutting-edge technology that holds the potential to revolutionize the way we approach smart irrigation. Smart irrigation transcends traditional methods by embracing the power of data-driven decision-making. It leverages DRL, a subset of AI, to transform irrigation into a dynamic and intelligent process. At its essence, DRL for smart irrigation represents a convergence of sophisticated algorithms, real-time data, and agricultural expertise, all working in harmony to achieve the twin objectives of resource efficiency and crop productivity.

- **Resource Allocation:** At its core, smart irrigation enabled by DRL aims to precisely optimize the distribution of priceless resources like water and nutrients. DRL-enabled systems make intelligent, data-driven decisions by taking into account variables including soil moisture levels, weather patterns, and crop health in real-time.
- **Water conservation:** DRL-based irrigation systems stand out as a ray of hope in a time when concerns about water scarcity are on the rise. They lessen water waste, reduce environmental impact, and support

responsible water conservation in agriculture by providing water precisely where and when it is needed.

- **Increased Crop Yields:** DRL-driven irrigation surpasses traditional techniques. It orchestrates an ideal growth symphony in addition to keeping crops hydrated. It promotes healthier plants, higher yields, and greater crop quality by ensuring that crops receive the proper materials in the proper quantities.
- **Real-Time Adaptation:** In the world of agriculture, things can change quickly, from unexpected temperature changes to sporadic rain showers. Farmers can move quickly, accurately, and nimbly through these shifting landscapes thanks to DRL's special ability to make judgments in real time [12].

15.1.3.1 DRL Modification for Agriculture

DRL's application to agriculture represents a successful fusion of innovation into a sector replete with longstanding traditions rather than merely a technology transfer. This process of adaptation is a journey filled with obstacles, chances, and transforming results.

- **Domain Expertise:** Adapting DRL for agriculture necessitates a thorough knowledge of agronomic principles, farming methods, and ecosystems. In order to bridge the gap between theory and practice, the collaboration between domain experts and AI researchers becomes crucial.
- **Data Fusion:** Agriculture creates a vast amount of data, including measurements of soil quality, weather predictions, and crop health evaluations. Utilizing this variety of data and combining it into insights that can be put to use to guide irrigation methods is part of adapting DRL.
- **Sensor Technology:** The deployment of sensor technology is a linchpin in the adaptation process. Accurate and timely data from soil moisture sensors, weather stations, and remote imaging systems empower DRL algorithms to make informed decisions.
- **Scalability:** Agriculture encompasses diverse scales, from small family farms to vast agribusinesses. Adapting DRL involves designing systems that can scale seamlessly to meet the unique needs of each farming operation.
- **Integration with Farming Practices:** The successful adaptation of DRL hinges on its integration into existing farming practices. It

should complement the wisdom of experienced farmers, augmenting their decision-making rather than replacing it [10].

15.1.3.2 Learning Optimal Irrigation Strategies

Learning optimal irrigation strategies through DRL represents the pinnacle of AI's potential in agriculture. It's a journey toward precision, efficiency, and sustainability in crop cultivation.

- **Data-Driven Decision-Making:** DRL systems learn from data-driven experiences, continually optimizing irrigation strategies based on real-time information. This approach replaces intuition with empirical evidence, resulting in superior decision-making.
- **Tailored Resource Allocation:** The quest for optimal irrigation involves the judicious allocation of resources. DRL calculates the precise amount of water, nutrients, and other inputs needed for each section of the field, ensuring resource efficiency and cost savings.
- **Crop-Centric Approach:** Optimal irrigation strategies prioritize the health and growth of crops. DRL ensures that irrigation decisions are aligned with the unique needs of each crop type, growth stage, and environmental condition.
- **Resilience and Adaptability:** The learning process is not static; it adapts to changing conditions. DRL systems are equipped to respond to sudden weather shifts, pest outbreaks, or changes in soil conditions, ensuring crop resilience and yield stability [13].

15.1.3.3 Factors Considered in Decision-Making for Smart Irrigation

In the modern agricultural landscape, the art of irrigation has evolved into a science, guided not only by the wisdom of experienced farmers but also by a wealth of data-driven insights. Smart irrigation, underpinned by advanced technologies and decision-making algorithms, represents a paradigm shift in how we nurture crops, conserve resources, and foster sustainability. At the heart of this agricultural revolution lies the intricate web of factors considered in decision-making for smart irrigation. These factors are the compass points that guide irrigation strategies, transforming what was once a manual, intuition-based practice into a precise, data-driven discipline.

- **Soil Moisture Levels:** Monitoring soil moisture is fundamental to smart irrigation. Sensors embedded in the soil provide real-time

data on moisture content, allowing decision-makers to determine if and when irrigation is required.

- **Weather Conditions:** Weather data, including temperature, humidity, wind speed, and precipitation forecasts, play a crucial role in irrigation decisions. Anticipating rain, for example, can lead to irrigation adjustments to avoid overwatering.
- **Crop Type and Growth Stage:** Different crops have varying water requirements at different growth stages. Decision-making considers the specific needs of each crop to optimize irrigation scheduling.
- **Environmental Conditions:** Factors such as evapotranspiration rates (the loss of water from soil and plants), solar radiation, and wind affect water demand and must be factored into irrigation decisions.
- **Topography and Soil Type:** The terrain and soil type of the field influence water distribution. Decision-making accounts for these factors to ensure uniform irrigation across the entire area.
- **Water Source and Availability:** The source of water, be it groundwater, surface water, or irrigation canals, affects availability and cost. Decision-makers consider water source sustainability and associated expenses.
- **Local Regulations:** Agricultural practices are often subject to local regulations governing water use. Compliance with these regulations is essential in decision-making.
- **Cost Analysis:** Economic considerations are vital. Decision-makers evaluate the cost of water, energy for pumping, and irrigation equipment maintenance to optimize resource allocation.
- **Historical Data:** Past irrigation practices and crop performance data provide valuable insights for future decision-making. Historical data helps fine-tune irrigation strategies.
- **Crop Health Monitoring:** Real-time data on crop health, such as disease detection and stress levels, can trigger irrigation adjustments to address plant needs promptly [11].

15.1.3.4 Real-Time Data and Sensing Technologies

In the realm of agriculture, where every moment counts, and every resource is precious, the power of real-time data and sensing technologies has emerged as a beacon of innovation. In the not-so-distant past, farming relied on tradition and experience, but today, it is elevated by an orchestra of sensors, satellites, and interconnected devices that breathe life into the fields. Imagine a world where each acre of land, each plant,

and every drop of water speaks its own unique language through data. This symphony of information, orchestrated by a network of sensors and advanced technologies, transcends the boundaries of human perception, offering unprecedented insights into the natural world. Real-time data and sensing technologies are the architects of this transformation. They serve as the eyes and ears of modern agriculture, collecting and relaying a constant stream of information about the environment, crops, and soil conditions. In doing so, they empower farmers and land stewards with the knowledge needed to make informed decisions in a dynamic and ever-changing agricultural landscape. In the pages that follow, we embark on a journey into the heart of real-time data and sensing technologies. We explore the sensors that probe the depths of soil, the satellites that gaze upon our planet from above, and the data analytics that breathe intelligence into raw information. Together, we uncover a world where data is not just a resource but a lifeline – a lifeline that nurtures crops, conserves resources, and charts the course toward a sustainable and prosperous future for agriculture.

- **Soil Moisture Sensors:** These sensors are embedded in the soil to continuously monitor moisture levels at various depths. Real-time data from these sensors guides decisions on when and how much to irrigate.
- **Weather Stations:** Weather stations collect data on temperature, humidity, wind speed, and precipitation. This data is crucial for understanding current weather conditions and predicting future trends.
- **Satellite and Remote Sensing:** Satellite imagery and remote sensing technologies provide a bird's-eye view of crop health, moisture levels, and vegetation indices over large areas. They offer insights into overall field conditions.
- **IoT (Internet of Things) Devices:** IoT devices, including connected weather sensors, soil monitors, and drones, provide a network of real-time data sources that enable decision-makers to make precise adjustments.
- **Data Analytics and AI:** Advanced data analytics and AI techniques process the real-time data streams from sensors to generate actionable insights and optimize irrigation decisions.
- **Mobile Apps and Dashboards:** Decision-makers often access real-time data through mobile applications and web-based dashboards.

These tools provide a user-friendly interface for monitoring and adjusting irrigation remotely.

- **Automation and Control Systems:** Smart irrigation systems are often equipped with automation and control systems that can act on real-time data, adjusting irrigation valves and pumps as needed without manual intervention.
- **Communication Networks:** Reliable communication networks, including wireless and cellular, ensure that real-time data is transmitted from sensors to decision-makers and control systems seamlessly [14].

15.1.4 Applying DRL to Smart Irrigation

Deep Reinforcement Learning (DRL) has shown significant potential in improving irrigation scheduling in various cropping systems. The goal is to discover an intelligent decision rule that processes information available to growers and prescribes sensible irrigation amounts.

For instance, a system called Deep Reinforcement Learning for Irrigation Control (DRLIC) uses a neural network (DRL control agent) to learn an optimal control policy that takes both current soil moisture measurement and future soil moisture loss into account [8].

In another study, an IoT-based irrigation system was proposed, which includes two major components: an IoT wireless network of sensing and actuation nodes and a DRL-based control algorithm. Given the collected soil moisture data and weather data, the DRL-based algorithm finds an optimal irrigation schedule that uses the minimum amount of water to guarantee the soil-water content above the required level before the next irrigation cycle.

These systems have demonstrated their effectiveness in real-world scenarios. For example, the IoT-based system was deployed in a testbed composed of six almond trees. Through a 12-day, in-field experiment, it was found that the proposed system can save up to 7.8% of water over a widely used irrigation scheme.

In summary, DRL can be effectively applied to smart irrigation systems to optimize water usage and improve agricultural efficiency [15].

15.1.4.1 Understanding the Environment: Soil, Weather, Crop Type

Irrigation is highly dependent on three main factors: soil, weather, and crop type.

Soil: The type of soil plays a crucial role in irrigation, as different soils have different water-holding capacities. Soil-based sensors can gather relevant data about volumetric water content, salinity, electrical conductivity, and other crucial parameters. Understanding these parameters can help determine the optimal amount of water required for irrigation.

Weather: Weather conditions significantly affect the irrigation scheduling criteria. Factors such as rainfall, temperature, humidity, wind speed, and solar radiation influence the evapotranspiration rate (the sum of evaporation and plant transpiration). Monitoring these weather conditions can help adjust irrigation schedules to ensure that crops receive the right amount of water at the right time.

Crop Type: Different crops have different water requirements. The crop type determines the irrigation and fertilizer rates. Some crops may be more drought-tolerant than others and may require less frequent watering. Understanding the specific water needs of each crop type can lead to more efficient use of water.

Smart irrigation systems take into account these factors to make better irrigation decisions. They use AI techniques to process data from soil, weather, and plant sensors to optimize water usage [16].

15.1.4.2 Defining the States, Actions, and Rewards

The state in this context represents the current condition of the field that needs to be irrigated. This could include factors such as the current moisture level of the soil, weather conditions (like temperature, humidity, wind speed, and solar radiation), and the type of crop being grown. These factors can be measured using various sensors and weather forecasting data.

The action in this context is the amount of water to be applied to the field at a given time. This could range from no watering at all (in case of sufficient soil moisture or expected rainfall) to heavy watering (in case of dry soil and high evapotranspiration rates). The action is usually determined by a DRL agent based on the current state and the learned policy.

The reward in this context is a measure of how well the action performed in achieving the goal of optimal irrigation. A simple reward function could be the difference between the desired soil moisture level and the actual soil moisture level after irrigation. If the soil moisture level is close to the desired level, a positive reward is given. If it's too dry

or too wet, a negative reward is given. The aim of the DRL agent is to maximize the total reward over time, which leads to an optimal irrigation schedule [17].

15.1.4.3 Designing the DRL Agent

Designing a DRL agent for smart irrigation involves several steps.

Problem Formulation: The first step is to formulate the irrigation problem as a Markov Decision Process (MDP). This involves defining the states, actions, and rewards. As discussed earlier, states could include soil moisture levels, weather conditions, and crop types. Actions could be the amount of water to apply, and rewards could be based on how well the irrigation goal is achieved [15].

DRL Model Selection: Choose an appropriate DRL model for the problem. This could be Q-Learning, DQN, Policy Gradients, or any other suitable model. The choice of model depends on the problem characteristics and the available data.

Feature Extraction: Extract relevant features from the state representations. This could involve processing sensor data to obtain useful information about the soil and weather conditions.

Network Architecture Design: Design the neural network architecture for the DRL model. This involves choosing the number of layers, the number of neurons in each layer, the activation functions, etc.

Training: Train the DRL agent using historical data. The agent learns by interacting with the environment (the field), taking actions (applying water), and receiving rewards (feedback on irrigation effectiveness). The goal of training is to learn a policy that maximizes the total reward over time.

Testing and Deployment: After training, test the DRL agent in a simulated or real environment to evaluate its performance. If the performance is satisfactory, deploy the agent for actual use.

Remember that designing a DRL agent requires expertise in RL and DL. It's also an iterative process that involves a lot of trial and error [18].

15.1.5 Successful Applications of DRL in Smart Irrigation

An IoT-based irrigation system was proposed that includes two major components: an IoT wireless network of sensing and actuation nodes and

a DRL-based control algorithm. Given the collected soil moisture data and weather data, the DRL-based algorithm finds an optimal irrigation schedule that uses the minimum amount of water to guarantee the soil-water content above the required level before the next irrigation cycle. The system was deployed in a testbed composed of six almond trees. Through a 12-day, in-field experiment, it was found that the proposed system can save up to 7.8% of water over a widely used irrigation scheme.

DRL has considerable potential to improve irrigation scheduling in many cropping systems by applying adaptive amounts of water based on various measurements over time. The goal is to discover an intelligent decision rule that processes information available to growers and prescribes sensible irrigation amounts for the time steps considered. The effectiveness of the framework was demonstrated using a case study of irrigated wheat grown in a productive region of Australia where profits were maximized.

DRLIC is a sophisticated irrigation system that uses DRL to optimize its performance. The system employs a neural network known as the DRL control agent, which learns an optimal control policy that considers both the current soil moisture measurement and the future soil moisture loss [19].

15.1.5.1 Current Methods in Smart Irrigation

Smart irrigation systems are a combination of various technologies, such as sensor technology, automatic control technology, and computer technology. They are designed to optimize the efficiency of agricultural water resource utilization.

AI and ML: These techniques are used in both urban and rural agriculture for soil crops to identify systems that are currently being used or can be adapted to urban agriculture.

IoT: IoT allows for more data capture and higher levels of automation. Technologies such as IoT, smartphone tools, and sensors enable farmers to better understand the exact conditions of their fields, including soil temperature, nutrients, water requirements, weather conditions, and more.

Big Data: Modern agricultural operations generate data from a variety of sensors to better understand the environmental factors and the crops, allowing for more accurate and efficient decision-making of farming practices.

Sensor Technology: This includes various types of irrigation systems that can be enhanced with smart irrigation software. The most common are flood, sprinkler, center pivot, drip, and microirrigation systems.

Automatic Control Technology: This is combined with garden irrigation methods, such as sprinkler irrigation and drip irrigation [20].

15.1.5.2 Limitations of Current Methods

While smart irrigation systems have the potential to revolutionize agriculture, they also have certain limitations. The primary disadvantage associated with a smart irrigation system is the expense [4]. These systems can be quite costly, depending on the size of the property. Furthermore, portions of the lawn will have to be dug up to install pipework and attach it to the plumbing system of the home.

Technical Difficulties: Despite the proven benefits of wireless sensor networks in saving water, there are still some technical difficulties, especially in smart irrigation monitoring and control strategies. Even the most efficient smart systems can have their pitfalls. Wind can wreak havoc on sprinklers, directing water in the wrong direction. Underground pests may damage water-delivery systems, resulting in water pooling or broken parts.

Limited Scalability: The research studies on irrigation systems until now are not very efficient, so they cannot be implemented on large-scale systems and have less efficiency due to overburdened sensors for all sensing data [7].

Affordability for Smallholder Farmers: The cost of irrigation technology is often outside of what smallholder farmers can afford as an out-of-pocket expense.

15.1.5.3 Opportunities for Improvement

There are several opportunities for improvement in smart irrigation:

- **Autonomous Pivot Systems:** These systems create new opportunities for smart irrigation.¹ The entire irrigation system is autonomous, and agricultural workers can run the machine from computers, allowing it to stop and start or change water flow [4].
- **Investing in Small-Scale Irrigation:** Small-scale irrigation schemes usually work well, though they must be carefully planned from

the outset so that they are not overwhelmed by complex physical and managerial arrangements.² Successful small-scale irrigation is grounded in infrastructure that is efficient, climate-smart, resilient, and financially sustainable [9].

- **Government Initiatives:** The future of the smart irrigation market looks promising, with opportunities in the agriculture and non-agriculture irrigation industries. The major drivers for this market are increasing government initiatives to promote water conservation, growth in smart cities, and increasing the need for efficient irrigation systems [5].
- **Climate Change Adaptation and Improved Food Security:** Improvements in smart irrigation monitoring and management systems may be used to address climate, food, and population issues.
- **Innovative Projects:** There are numerous innovative projects that can be built by students to develop hands-on experience in areas related to/using smart irrigation [12].

15.1.6 Future Directions

DRL has the potential to improve irrigation scheduling in many cropping systems by applying adaptive amounts of water based on various measurements over time. The goal is to discover an intelligent decision rule that processes information available to growers and prescribes sensible irrigation amounts for the time steps considered. The research on this technique remains sparse and impractical due to its technical novelty. To accelerate progress, researchers propose a general framework and actionable procedure that allow researchers to formulate their own optimization problems and implement solution algorithms based on DRL [21–25].

Fresh water is becoming a scarce resource in many parts of the world, and its use in agriculture increasingly needs to be optimized. While there are a number of approaches to irrigation optimization, irrigation scheduling using advanced sensor technologies has considerable potential to apply the right amount of water at the right time based on monitored plant, soil, and atmospheric conditions. The proposed frameworks are general and applicable to a wide range of cropping systems with realistic optimization problems. This means that DRL can be used not only for traditional crops but also for more complex and diverse agricultural systems.

15.1.6.1 Potential Improvements in DRL for Smart Irrigation

DRL has shown significant potential in improving irrigation scheduling in many cropping systems by applying adaptive amounts of water based on various measurements over time [11].

Current research on DRL for irrigation remains sparse and impractical due to its technical novelty. Improvements can be made in handling high-dimensional sensor feedback, which involves processing information available to growers and prescribing sensible irrigation amounts for the time steps considered.

A deep RL-based irrigation scheduling approach can be enhanced to optimize the economic return in irrigation applications. This method involves computing the irrigation quantity for each step while taking evapotranspiration (ET), soil moisture, future precipitation probability, and the current crop growth stage into consideration [16].

The framework for DRL in irrigation is general and applicable to a wide range of cropping systems with realistic optimization problems. However, more research is needed to adapt and fine-tune these models for different types of crops and environmental conditions.

15.1.6.2 Emerging Trends in DRL and Agriculture

DRL is rapidly advancing and has been applied to various agricultural and natural resource management challenges. DRL is being used to solve important problems like crop yield maximization. The goal is to leverage the knowledge available in data and identify ways through which many tasks/subtasks for sustainable farming can be automated, leading to scalable agriculture solutions [18].

DRL is being used for next-best-view planning in agricultural applications. For example, a novel DRL approach has been developed to determine the next best view for the automatic exploration of 3D environments with a robotic arm equipped with an RGB-D camera. This approach improves the information about the regions of interest (ROIs), such as fruits, which are possibly completely or partly occluded by leaves [26–30].

DRL-based solutions are being integrated with IoT wireless networks of sensing and actuation nodes and are being deployed on production-ready cloud infrastructure. This makes the solutions more practical and scalable. These trends indicate that DRL will continue to play a crucial role in advancing agricultural practices, contributing to more efficient farming and sustainable agricultural practices [20].

15.2 CONCLUSION

Within the field of agriculture, the chapter “Deep Reinforcement Learning for Smart Irrigation” provides evidence of how technology can be revolutionary in solving some of the most critical problems facing contemporary farmers. We consider the significant effects that the combination of precision irrigation and DRL has on agriculture as we round out this chapter. Smart irrigation represents a comprehensive strategy for crop cultivation and resource management driven by the intelligence of DRL algorithms. It is evidence of how AI and human expertise work well together, with data-driven choices enhancing the knowledge that has been cultivated over many farming generations. We have examined the variables considered when making decisions about smart irrigation throughout this chapter, highlighting the significance of crop types, weather, soil moisture levels, and sustainability. We have also explored the crucial role that real-time data and sensing technologies – from satellites to soil moisture sensors – play in gathering and utilizing the data required to make these decisions precisely. The combination of DRL with smart irrigation in agriculture has brought increased crop yields, resource efficiency, and sustainability. It has reshaped farming’s boundaries, enabling us to preserve the planet’s resources while fostering its abundance. It’s a tale of creativity, adaptation, and advancement that gets better with every season that goes by. The application of DRL in agriculture continues to have limitless possibilities. In order to improve and broaden the possibilities of smart irrigation, scientists, farmers, and technologists are working together to continue this journey of discovery and invention. The DRL story for smart irrigation is a monument to our dedication to caring for the land and feeding the world, not just one of statistics and algorithms.

REFERENCES

- 1 Altalak, M., Ammad Uddin, M., Alajmi, A., & Rizg, A. (2022). Smart agriculture applications using deep learning technologies: A survey. *Applied Sciences*, 12(12), 5919.
- 2 Coulibaly, S., Kamsu-Foguem, B., Kamissoko, D., & Traore, D. (2022). Deep learning for precision agriculture: A bibliometric analysis. *Intelligent Systems with Applications*, 16, 200102.
- 3 Bhatt, S. (2019, April 19). Reinforcement learning 101. *Medium*. <https://towardsdatascience.com/reinforcement-learning-101-e24b50e1d292>

- 4 Bu, F., & Wang, X. (2019). A smart agriculture IoT system based on deep reinforcement learning. *Future Generation Computer Systems*, 99, 500–507
- 5 Zhou, N. (2020, August). Intelligent control of agricultural irrigation based on reinforcement learning. *Journal of Physics: Conference Series*, 1601(5), 052031. IOP Publishing.
- 6 Yang, Y., Hu, J., Porter, D., Marek, T., Heflin, K., & Kong, H. (2020). Deep reinforcement learning-based irrigation scheduling. *Transactions of the ASABE*, 63(3), 549–556.
- 7 Alibabaei, K., Gaspar, P. D., Assunção, E., Alirezazadeh, S., & Lima, T. M. (2022). Irrigation optimization with a deep reinforcement learning model: Case study on a site in Portugal. *Agricultural Water Management*, 263, 107480.
- 8 Debnath, S., Adamala, S., & Palakuru, M. (2020). An overview of Indian traditional irrigation systems for sustainable agricultural practices. *International Journal of Modern Agriculture*, 9, 12–22.
- 9 Ding, X., & Du, W. (2022, May). Smart irrigation control using deep reinforcement learning. In *2022 21st ACM/IEEE International Conference on Information Processing in Sensor Networks (IPSN)* (pp. 539–540). IEEE.
- 10 IBM, E. team. (2018). What is deep learning? <https://www.ibm.com/topics/deep-learning>
- 11 Fu, Y., Li, C., Yu, F. R., Luan, T. H., & Zhang, Y. (Aug. 2022). Hybrid autonomous driving guidance strategy combining deep reinforcement learning and expert system. *IEEE Transactions on Intelligent Transportation Systems*, 23(8), 11273–11286. doi: 10.1109/TITS.2021.3102432
- 12 Ganatra, N., & Patel, A. (2021). Deep learning methods and applications for precision agriculture. In *Machine Learning for Predictive Analysis: Proceedings of ICTIS 2020*, pp. 515–527.
- 13 Kavitha, A. (2021). Deep learning for smart agriculture. *International Journal of Engineering Research & Technology (IJERT) ICRADL*, 09(05), 2021.
- 14 Attri, I., Awasthi, L. K., Sharma, T. P., & Rathee, P. (2023). A review of deep learning techniques used in agriculture. *Ecological Informatics*, 77, 102217.
- 15 Sami, M., Khan, S. Q., Khurram, M., Farooq, M. U., Anjum, R., Aziz, S., & Sadak, F. (2022). A deep learning-based sensor modeling for smart irrigation system. *Agronomy*, 12(1), 212.
- 16 Sun, L., Yang, Y., Hu, J., Porter, D., Marek, T., & Hillyer, C. (2017, December). Reinforcement learning control for water-efficient agricultural irrigation. In *2017 IEEE International Symposium on Parallel and Distributed Processing with Applications and 2017 IEEE International Conference on Ubiquitous Computing and Communications (ISPA/IUCC)*, IEEE, pp. 1334–1341.
- 17 Gao, H., Zhangzhong, L., Zheng, W., & Chen, G. (2023). How can agricultural water production be promoted? A review on machine learning for irrigation. *Journal of Cleaner Production*, 414, 137687.
- 18 Çetin, M., & Beyhan, S. (2022). Smart irrigation systems using machine learning and control theory. In *The Digital Agricultural Revolution: Innovations and Challenges in Agriculture through Technology Disruptions*, pp. 57–85.
- 19 Pallathadka, H., Mustafa, M., Sanchez, D. T., Sajja, G. S., Gour, S., & Naved, M. (2023). Impact of machine learning on management, healthcare and agriculture. *Materials Today: Proceedings*, 80, 2803–2806.

- 20 Vianny, D. M. M., John, A., Mohan, S. K., Sarlan, A., & Ahmadian, A. (2022). Water optimization technique for precision irrigation system using IoT and machine learning. *Sustainable Energy Technologies and Assessments*, 52, 102307.
- 21 Bukhari, S. N. H., Webber, J., & Mehbodniya, A. (2022). Decision tree based ensemble machine learning model for the prediction of Zika virus T-cell epitopes as potential vaccine candidates. *Scientific Reports*, 12, 7810. doi: 10.1038/s41598-022-11731-6
- 22 Raghavendra, G. S., Shyni Carmel Mary, S., Bikash Acharjee, P., Varun, V. L., Bukhari, S. N. H., Dutta, C., & Samori, I. A. (2022). An empirical investigation in analysing the critical factors of artificial intelligence in influencing the food processing industry: A Multivariate Analysis of Variance (MANOVA) approach. *Journal of Food Quality*, 2022, Article ID 2197717, 7 pages. doi: 10.1155/2022/2197717
- 23 Bukhari, S. N. H., Jain, A., Haq, E., Mehbodniya, A., & Webber, J. (2021). Ensemble machine learning model to predict SARS-CoV-2 T-cell epitopes as potential vaccine targets. *Diagnostics*, 11(11) 1990. MDPI AG. doi: 10.3390/diagnostics11111990
- 24 Bangare, S. L., Virmani, D., Karetla, G. R., Chaudhary, P., Kaur, H., Bukhari, S. N. H., & Miah, S. (2022). Forecasting the applied deep learning tools in enhancing food quality for heart related diseases effectively: A study using structural equation model analysis. *Journal of Food Quality*, 2022, Article ID 6987569, 8 pages. doi: 10.1155/2022/6987569
- 25 Anoruo, C. M., Bukhari, S. N. H., & Nwofor, O. K. (2023). Modeling and spatial characterization of aerosols at Middle East AERONET stations. *Theoretical and Applied Climatology*, 152, 617–625. doi: 10.1007/s00704-023-04384-6
- 26 Masoodi, F., Quasim, M., Bukhari, S., Dixit, S., & Alam, S. (2023). *Applications of Machine Learning and Deep Learning on Biological Data*. CRC Press.
- 27 Bukhari, S. N. H., Jain, A., & Haq, E. (2022). A novel ensemble machine learning model for prediction of Zika virus T-cell epitopes. In Gupta, D., Polkowski, Z., Khanna, A., Bhattacharyya, S., and Castillo, O. (Eds.), *Proceedings of Data Analytics and Management. Lecture Notes on Data Engineering and Communications Technologies*, vol 91. Springer, Singapore. doi: 10.1007/978-981-16-6285-0_23
- 28 Bukhari, S. N. H., Masoodi, F., Dar, M. A., Wani, N. I., Sajad, A. et al. (2023). Prediction of erythemato-squamous diseases using machine learning. In *Applications of Machine Learning and Deep Learning on Biological Data*. CRC Press.
- 29 Bukhari, S. N. H., Jain, A., Haq, E., Mehbodniya, A., & Webber, J. (2022). Machine learning techniques for the prediction of B-cell and T-cell epitopes as potential vaccine targets with a specific focus on SARS-CoV-2 pathogen: A review. *Pathogens*, 11(2), 146. MDPI AG. doi: 10.3390/pathogens11020146
- 30 Nisar, S., Bukhari, H., & Dar, M. A. (2021). Using Random Forest to predict T-cell epitopes of Dengue virus. *Advances and Applications in Mathematical Sciences*, 20(11), 2543–2547.

Index

A

Accuracy, 94, 152, 223
Agric dataset, 84
Agriculture, 42, 101
Apple scab, 19
Arduino 1.0.6 software, 5
Artificial intelligence (AI), 58, 180
Artificial Neural Network, 118, 160
AUROC Curve, 95, 223
Auto-Encoder, 231

B

Backpropagation through Time
(BPTT), 248–249
Bagging, 88
Bandwidth Efficiency, 59
Blue River Technology, 52
BoniRob, 47
Bootstrapping, 88

C

CareBro, 74
Case Studies, 186–190
Cedar apple rust, 19
Classification Task, 111
Cloud Connectivity, 73
Computer Vision, 9, 27, 28, 42–48, 52, 54,
65, 117, 128, 129, 162, 183, 208
Control systems, 1
Convolution Layer, 145
Convolutional neural network (CNN), 23,
66, 117, 208–209, 229
Crop Monitoring, 59
Crop recommendation, 84
Crop recommender, 82
Crop yield, 77
Crop Yield Prediction, 185, 200–201
Crop-yield projection, 101, 159
Custom CNN, 148

D

Dairy farming, 1
Data Acquisition and Augmentation,
205–206

Data Augmentation, 27, 149
Data Cleaning, 27, 87, 108
Data Collection, 26, 129, 250–251
Data Encoding, 109
Data Preprocessing, 109, 129, 251–251
Data Quality, 104
Data Redundancy, 64
Data Splitting, 30
Data Visualization, 85
Data Volume, 104
Data-Driven Decision-Making, 76
Data-driven farming, 259
Data-driven Insights, 77
Dataset, 14, 21
Decision Tree, 89, 91, 113
Deep Convolutional Neural
Network, 45, 69
Deep-Learning Models, 28
Deep learning, 89, 264
Deep Reinforcement Learning, 263–265
Drones, 50

E

Early Blight, 202–205, 211
Edge AI, 56, 75
Ensemble Models, 118
Ensemble technique (ET), 88
Environmental Sustainability, 71, 77
Explainable AI, 193, 194

F

F1 score, 94, 153
False-Positive Rate, 224
Feature Engineering, 109, 127
Feature Extraction, 129
Feature Extraction and Engineering, 183
Feature Scaling, 87, 109
Feature Selection, 166
Feedforward Neural Network (FNN),
229
Fixed-Schedule Irrigation, 262
F-Measure, 224
Fog Computing Layer, 73
Formbot, 52
Fully Connected Layer, 147

G

GAN (Generative Adversarial Network), 234
 Gated Recurrent Unit (GRU), 231
 Geographic Information Science (GIScience), 71
Gramophone (Agstack Technologies), 53
 Gross domestic product (GDP), 82

H

Harvest CROO Robotics, 52
 Herbicide, 48
High Latency, 64
 Humidity and temperature sensors, 5
 Hyperparameter Tuning, 30

I

InceptionV3, 149
 Information and Communication Technology (ICT), 1, 70
 Internet of Things (IoT), 4, 106
 Intuitive Irrigation
 Decision-Making, 262–263

J

Jivabhum, 53

K

Kaggle, 84, 149, 162, 219, 225
 K-Fold Cross-Validation, 95
 K Nearest Neighbor (KNN), 172

L

Late Blight, 203
 Linear regression, 111, 169
 Livestock farmers, 2
Livestock Management, 59
 Long Short-Term Memory Network (LSTM), 231
Low Latency, 65
Low-Power AI Integration, 65

M

Machine learning (ML), 1, 4, 20, 101, 102, 159
 Mean Squared Error, 172

Missing values, 109
 ML, 180
 Model Building, 88
 Model Complexity, 104
 Model Configuration and Training, 252–253
 Model Evaluation, 253–254
 Model Evaluation Metrics, 31
 Model Training, 127
 Multilayer perceptron (MLP), 91

N

Naive Bayes, 6, 30, 83, 104, 111, 207, 216, 217, 219–223, 225
 Neural Network, 91, 116, 161, 228–229
 Neurons, 92
Normalization, 109

O

Optimization Algorithms, 163
 Outlier Detection and Treatment, 109

P

Particle Swarm Optimization (PSO), 5
 Polynomial Regression, 169
 Pooling Layer, 147
 Powdery mildew, 19
Precision Agriculture, 59, 74, 216–217
 Precision farming, 186
 Precision Irrigation, 167
 Precision livestock farming (PLF), 2–3
 Precision, 152, 224
Predictive Analytics, 13, 43
 Preprocessing, 168
Prospera, 52
 Pulse sensors, 5

R

Random Forests, 28, 114
 Random subspace (RSS) approach, 119
 Raspberry Pi microcontroller, 14
 Recall, 153, 224
 Recurrent neural networks (RNNs), 5, 229, 246–249
 Regression Task, 111
 ReLU (Rectified Linear Unit), 93
Remote Monitoring, 74
 Remote sensing, 105

Remote Sensing and Imaging, 165
 ResNet, 50, 149
Resource Constraints, 61
Resource Efficiency, 76
 Robots, 50
 R-squared, 174
 Rumination sensors, 5

S

Scalability, 59, 78
 Seed germination monitoring, 65
 Smart technologies, 3
 Softmax, 93
 Soil organic matter (SOM), 44
 Sensitivity, 94
 Specificity, 94
 Support vector machine (SVM), 23, 28,
 114, 222

T

Time Series Forecasting, 127
 True-Positive Rate, 224

U

Unmanned aerial vehicles (UAVs), 43, 46
Unreliable Sensors, 67

V

VGG16, 148, 149, 153, 154

W

Water Efficiency, 63
 Weather forecasting, 243
 WEKA GUI, 220–221
Wireless sensor networks (WSNs), 64

X

Xbee module, 5
 XGBoost, 170, 171, 173–175

Y

YOLO, 45