

ISO/IEC JTC1 SC22 WG21 N 4660

Date: 2017-03-21

ISO/IEC DIS 14882

ISO/IEC JTC1 SC22

Secretariat: ANSI

Programming Languages — C++

Langages de programmation — C++

Warning

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: Draft International Standard

Document stage: (40) Enquiry

Document Language: E

Copyright notice

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56, CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Contents

Contents	iii
List of Tables	xi
List of Figures	xv
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
4 General principles	7
4.1 Implementation compliance	7
4.2 Structure of this document	8
4.3 Syntax notation	8
4.4 The C++ memory model	8
4.5 The C++ object model	9
4.6 Program execution	11
4.7 Multi-threaded executions and data races	15
4.8 Acknowledgments	20
5 Lexical conventions	22
5.1 Separate translation	22
5.2 Phases of translation	22
5.3 Character sets	23
5.4 Preprocessing tokens	24
5.5 Alternative tokens	25
5.6 Tokens	25
5.7 Comments	26
5.8 Header names	26
5.9 Preprocessing numbers	26
5.10 Identifiers	27
5.11 Keywords	28
5.12 Operators and punctuators	29
5.13 Literals	29
6 Basic concepts	39
6.1 Declarations and definitions	39
6.2 One-definition rule	41
6.3 Scope	44
6.4 Name lookup	50
6.5 Program and linkage	63
6.6 Start and termination	66
6.7 Storage duration	70
6.8 Object lifetime	74
6.9 Types	77

6.10	Lvalues and rvalues	83
6.11	Alignment	84
7	Standard conversions	86
7.1	Lvalue-to-rvalue conversion	87
7.2	Array-to-pointer conversion	87
7.3	Function-to-pointer conversion	88
7.4	Temporary materialization conversion	88
7.5	Qualification conversions	88
7.6	Integral promotions	89
7.7	Floating-point promotion	89
7.8	Integral conversions	89
7.9	Floating-point conversions	90
7.10	Floating-integral conversions	90
7.11	Pointer conversions	90
7.12	Pointer to member conversions	90
7.13	Function pointer conversions	91
7.14	Boolean conversions	91
7.15	Integer conversion rank	91
8	Expressions	93
8.1	Primary expressions	96
8.2	Postfix expressions	108
8.3	Unary expressions	120
8.4	Explicit type conversion (cast notation)	129
8.5	Pointer-to-member operators	130
8.6	Multiplicative operators	131
8.7	Additive operators	131
8.8	Shift operators	132
8.9	Relational operators	133
8.10	Equality operators	133
8.11	Bitwise AND operator	135
8.12	Bitwise exclusive OR operator	135
8.13	Bitwise inclusive OR operator	135
8.14	Logical AND operator	135
8.15	Logical OR operator	135
8.16	Conditional operator	136
8.17	Throwing an exception	137
8.18	Assignment and compound assignment operators	138
8.19	Comma operator	139
8.20	Constant expressions	139
9	Statements	144
9.1	Labeled statement	145
9.2	Expression statement	145
9.3	Compound statement or block	145
9.4	Selection statements	145
9.5	Iteration statements	147
9.6	Jump statements	150
9.7	Declaration statement	152
9.8	Ambiguity resolution	152

10	Declarations	155
10.1	Specifiers	157
10.2	Enumeration declarations	174
10.3	Namespaces	178
10.4	The <code>asm</code> declaration	191
10.5	Linkage specifications	191
10.6	Attributes	194
11	Declarators	201
11.1	Type names	202
11.2	Ambiguity resolution	203
11.3	Meaning of declarators	204
11.4	Function definitions	216
11.5	Structured binding declarations	219
11.6	Initializers	220
12	Classes	237
12.1	Class names	239
12.2	Class members	241
12.3	Unions	251
12.4	Local class declarations	254
13	Derived classes	256
13.1	Multiple base classes	257
13.2	Member name lookup	259
13.3	Virtual functions	262
13.4	Abstract classes	266
14	Member access control	269
14.1	Access specifiers	270
14.2	Accessibility of base classes and base class members	271
14.3	Friends	274
14.4	Protected member access	277
14.5	Access to virtual functions	278
14.6	Multiple access	278
14.7	Nested classes	278
15	Special member functions	280
15.1	Constructors	280
15.2	Temporary objects	283
15.3	Conversions	285
15.4	Destructors	288
15.5	Free store	291
15.6	Initialization	293
15.7	Construction and destruction	300
15.8	Copying and moving class objects	303
16	Overloading	311
16.1	Overloadable declarations	311
16.2	Declaration matching	313
16.3	Overload resolution	314

16.4	Address of overloaded function	335
16.5	Overloaded operators	336
16.6	Built-in operators	341
17	Templates	344
17.1	Template parameters	345
17.2	Names of template specializations	349
17.3	Template arguments	350
17.4	Type equivalence	356
17.5	Template declarations	357
17.6	Name resolution	375
17.7	Template instantiation and specialization	390
17.8	Function template specializations	402
17.9	Deduction guides	423
18	Exception handling	424
18.1	Throwing an exception	425
18.2	Constructors and destructors	427
18.3	Handling an exception	427
18.4	Exception specifications	429
18.5	Special functions	432
19	Preprocessing directives	434
19.1	Conditional inclusion	435
19.2	Source file inclusion	437
19.3	Macro replacement	438
19.4	Line control	443
19.5	Error directive	444
19.6	Pragma directive	444
19.7	Null directive	444
19.8	Predefined macro names	444
19.9	Pragma operator	446
20	Library introduction	447
20.1	General	447
20.2	The C standard library	448
20.3	Definitions	448
20.4	Method of description (Informative)	451
20.5	Library-wide requirements	456
21	Language support library	478
21.1	General	478
21.2	Common definitions	478
21.3	Implementation properties	483
21.4	Integer types	492
21.5	Start and termination	493
21.6	Dynamic memory management	494
21.7	Type identification	502
21.8	Exception handling	504
21.9	Initializer lists	509
21.10	Other runtime support	510

22	Diagnostics library	513
22.1	General	513
22.2	Exception classes	513
22.3	Assertions	517
22.4	Error numbers	517
22.5	System error support	519
23	General utilities library	530
23.1	General	530
23.2	Utility components	530
23.3	Compile-time integer sequences	538
23.4	Pairs	539
23.5	Tuples	543
23.6	Optional objects	554
23.7	Variants	569
23.8	Storage for any type	582
23.9	Bitsets	587
23.10	Memory	594
23.11	Smart pointers	609
23.12	Memory resources	635
23.13	Class template <code>scoped_allocator_adaptor</code>	646
23.14	Function objects	652
23.15	Metaprogramming and type traits	676
23.16	Compile-time rational arithmetic	702
23.17	Time utilities	705
23.18	Class <code>type_index</code>	722
23.19	Execution policies	723
24	Strings library	726
24.1	General	726
24.2	Character traits	726
24.3	String classes	732
24.4	String view classes	766
24.5	Null-terminated sequence utilities	776
25	Localization library	782
25.1	General	782
25.2	Header <code><locale></code> synopsis	782
25.3	Locales	784
25.4	Standard <code>locale</code> categories	791
25.5	C library locales	829
26	Containers library	830
26.1	General	830
26.2	Container requirements	830
26.3	Sequence containers	868
26.4	Associative containers	900
26.5	Unordered associative containers	921
26.6	Container adaptors	945
27	Iterators library	955

27.1	General	955
27.2	Iterator requirements	955
27.3	Header <code><iterator></code> synopsis	961
27.4	Iterator primitives	964
27.5	Iterator adaptors	967
27.6	Stream iterators	980
27.7	Range access	987
27.8	Container access	988
28	Algorithms library	989
28.1	General	989
28.2	Header <code><algorithm></code> synopsis	989
28.3	Algorithms requirements	1008
28.4	Parallel algorithms	1009
28.5	Non-modifying sequence operations	1012
28.6	Mutating sequence operations	1020
28.7	Sorting and related operations	1030
28.8	C library algorithms	1049
29	Numerics library	1050
29.1	General	1050
29.2	Definitions	1050
29.3	Numeric type requirements	1050
29.4	The floating-point environment	1051
29.5	Complex numbers	1052
29.6	Random number generation	1062
29.7	Numeric arrays	1105
29.8	Generalized numeric operations	1125
29.9	Mathematical functions for floating-point types	1139
30	Input/output library	1157
30.1	General	1157
30.2	Iostreams requirements	1158
30.3	Forward declarations	1158
30.4	Standard istream objects	1160
30.5	Iostreams base classes	1162
30.6	Stream buffers	1179
30.7	Formatting and manipulators	1188
30.8	String-based streams	1214
30.9	File-based streams	1225
30.10	File systems	1239
30.11	C library files	1293
31	Regular expressions library	1297
31.1	General	1297
31.2	Definitions	1297
31.3	Requirements	1298
31.4	Header <code><regex></code> synopsis	1300
31.5	Namespace <code>std::regex_constants</code>	1306
31.6	Class <code>regex_error</code>	1309
31.7	Class template <code>regex_traits</code>	1310

31.8	Class template <code>basic_regex</code>	1312
31.9	Class template <code>sub_match</code>	1318
31.10	Class template <code>match_results</code>	1323
31.11	Regular expression algorithms	1328
31.12	Regular expression iterators	1333
31.13	Modified ECMAScript regular expression grammar	1339
32	Atomic operations library	1342
32.1	General	1342
32.2	Header <code><atomic></code> synopsis	1342
32.3	Type aliases	1346
32.4	Order and consistency	1346
32.5	Lock-free property	1348
32.6	Class template <code>atomic</code>	1348
32.7	Non-member functions	1356
32.8	Flag type and operations	1356
32.9	Fences	1357
33	Thread support library	1359
33.1	General	1359
33.2	Requirements	1359
33.3	Threads	1362
33.4	Mutual exclusion	1367
33.5	Condition variables	1388
33.6	Futures	1395
A	Grammar summary	1412
A.1	Keywords	1412
A.2	Lexical conventions	1412
A.3	Basic concepts	1417
A.4	Expressions	1417
A.5	Statements	1421
A.6	Declarations	1422
A.7	Declarators	1426
A.8	Classes	1428
A.9	Derived classes	1429
A.10	Special member functions	1430
A.11	Overloading	1430
A.12	Templates	1430
A.13	Exception handling	1431
A.14	Preprocessing directives	1432
B	Implementation quantities	1434
C	Compatibility	1436
C.1	C++ and ISO C	1436
C.2	C++ and ISO C++ 2003	1445
C.3	C++ and ISO C++ 2011	1451
C.4	C++ and ISO C++ 2014	1453
C.5	C standard library	1457

D Compatibility features	1460
D.1 Redclaration of <code>static constexpr</code> data members	1460
D.2 Implicit declaration of copy functions	1460
D.3 Deprecated exception specifications	1460
D.4 C++ standard library headers	1460
D.5 C standard library headers	1461
D.6 <code>char*</code> streams	1461
D.7 <code>uncaught_exception</code>	1470
D.8 Old adaptable function bindings	1470
D.9 The default allocator	1475
D.10 Raw storage iterator	1476
D.11 Temporary buffers	1478
D.12 Deprecated type traits	1478
D.13 Deprecated iterator primitives	1479
D.14 Deprecated <code>shared_ptr</code> observers	1479
D.15 Deprecated standard code conversion facets	1479
D.16 Deprecated convenience conversion interfaces	1481
Cross references	1486
Cross references from ISO C++ 2014	1507
Index	1509
Index of grammar productions	1542
Index of library names	1546
Index of implementation-defined behavior	1604

List of Tables

1	Alternative tokens	25
2	Ranges of characters allowed	27
3	Ranges of characters disallowed initially (combining characters)	27
4	Identifiers with special meaning	28
5	Keywords	28
6	Alternative representations	28
7	Types of integer literals	30
8	Escape sequences	33
9	String literal concatenations	36
10	Relations on <code>const</code> and <code>volatile</code>	83
11	<i>simple-type-specifiers</i> and the types they specify	168
12	Relationship between operator and function call notation	319
13	Conversions	328
14	Value of folding empty sequences	363
15	Library categories	447
16	C++ library headers	457
17	C++ headers for C library facilities	457
18	C standard Annex K names	458
19	C++ headers for freestanding implementations	459
20	<code>EqualityComparable</code> requirements	460
21	<code>LessThanComparable</code> requirements	460
22	<code>DefaultConstructible</code> requirements	460
23	<code>MoveConstructible</code> requirements	460
24	<code>CopyConstructible</code> requirements (in addition to <code>MoveConstructible</code>)	461
25	<code>MoveAssignable</code> requirements	461
26	<code>CopyAssignable</code> requirements (in addition to <code>MoveAssignable</code>)	461
27	<code>Destructible</code> requirements	461
28	<code>NullablePointer</code> requirements	463
29	Hash requirements	464
30	Descriptive variable definitions	464
31	Allocator requirements	465
32	Language support library summary	478
33	Diagnostics library summary	513
34	General utilities library summary	530
35	<code>optional::operator=(const optional&)</code> effects	560
36	<code>optional::operator=(optional&&)</code> effects	560
37	<code>optional::operator=(const optional<U>&)</code> effects	561
38	<code>optional::operator=(optional<U>&&)</code> effects	562

39	<code>optional::swap(optional&)</code> effects	564
40	Primary type category predicates	684
41	Composite type category predicates	685
42	Type property predicates	686
43	Type property queries	693
44	Type relationship predicates	694
45	Const-volatile modifications	695
46	Reference modifications	696
47	Sign modifications	697
48	Array modifications	698
49	Pointer modifications	698
50	Other transformations	699
51	Expressions used to perform ratio arithmetic	704
52	Clock requirements	708
53	Strings library summary	726
54	Character traits requirements	727
55	<code>basic_string(const Allocator&)</code> effects	742
56	<code>basic_string(const basic_string&)</code> effects	742
57	<code>basic_string(const basic_string&, size_type, const Allocator&)</code> and <code>basic_string(const basic_string&, size_type, size_type, const Allocator&)</code> effects	742
58	<code>basic_string(const charT*, size_type, const Allocator&)</code> effects	743
59	<code>basic_string(const charT*, const Allocator&)</code> effects	743
60	<code>basic_string(size_t, charT, const Allocator&)</code> effects	744
61	<code>basic_string(const basic_string&, const Allocator&)</code> and <code>basic_string(basic_string&&, const Allocator&)</code> effects	744
62	<code>operator=(const basic_string&)</code> effects	745
63	<code>compare()</code> results	759
64	<code>basic_string_view(const charT*)</code> effects	770
65	<code>basic_string_view(const charT*, size_type)</code> effects	770
66	<code>compare()</code> results	773
67	Additional <code>basic_string_view</code> comparison overloads	775
68	Localization library summary	782
69	Locale category facets	786
70	Required specializations	787
71	<code>do_in/do_out</code> result values	800
72	<code>do_unshift</code> result values	800
73	Integer conversions	804
74	Length modifier	804
75	Integer conversions	808
76	Floating-point conversions	808
77	Length modifier	808
78	Numeric conversions	808
79	Fill padding	809
80	<code>do_get_date</code> effects	816
81	Potential <code>setlocale</code> data races	829
82	Containers library summary	830
83	Container requirements	831
84	Reversible container requirements	834

85	Optional container operations	835
86	Allocator-aware container requirements	836
87	Sequence container requirements (in addition to container)	838
88	Optional sequence container operations	841
89	Container types with compatible nodes	843
90	Associative container requirements (in addition to container)	846
91	Unordered associative container requirements (in addition to container)	857
92	Iterators library summary	955
93	Relations among iterator categories	955
94	Iterator requirements	957
95	Input iterator requirements (in addition to Iterator)	957
96	Output iterator requirements (in addition to Iterator)	958
97	Forward iterator requirements (in addition to input iterator)	959
98	Bidirectional iterator requirements (in addition to forward iterator)	960
99	Random access iterator requirements (in addition to bidirectional iterator)	961
100	Algorithms library summary	989
101	Numerics library summary	1050
102	Seed sequence requirements	1063
103	Uniform random bit generator requirements	1064
104	Random number engine requirements	1065
105	Random number distribution requirements	1069
106	Input/output library summary	1157
107	<code>fmtflags</code> effects	1167
108	<code>fmtflags</code> constants	1167
109	<code>iostate</code> effects	1167
110	<code>openmode</code> effects	1167
111	<code>seekdir</code> effects	1168
112	Position type requirements	1172
113	<code>basic_ios::init()</code> effects	1174
114	<code>basic_ios::copyfmt()</code> effects	1175
115	<code>seekoff</code> positioning	1219
116	<code>newoff</code> values	1219
117	File open modes	1229
118	<code>seekoff</code> effects	1231
119	<code>filesystem_error(const string&, error_code)</code> effects	1264
120	<code>filesystem_error(const string&, const path&, error_code)</code> effects	1264
121	<code>filesystem_error(const string&, const path&, const path&, error_code)</code> effects	1265
122	Enum <code>path::format</code>	1265
123	Enum class <code>file_type</code>	1266
124	Enum class <code>copy_options</code>	1266
125	Enum class <code>perms</code>	1267
126	Enum class <code>perm_options</code>	1267
127	Enum class <code>directory_options</code>	1268
128	Regular expressions library summary	1297
129	Regular expression traits class requirements	1298
130	<code>syntax_option_type</code> effects	1307

131	<code>regex_constants::match_flag_type</code> effects when obtaining a match against a character container sequence [<code>first</code> , <code>last</code>).	1308
132	<code>error_type</code> values in the C locale	1309
133	Character class names and corresponding <code>ctype</code> masks	1313
134	<code>match_results</code> assignment operator effects	1325
135	Effects of <code>regex_match</code> algorithm	1329
136	Effects of <code>regex_search</code> algorithm	1330
137	Atomics library summary	1342
138	Atomic arithmetic computations	1353
139	Atomic pointer computations	1355
140	Thread support library summary	1359
141	C headers	1461
142	<code>strstreambuf(streamsize)</code> effects	1463
143	<code>strstreambuf(void* (*)(size_t), void (*)(void*))</code> effects	1463
144	<code>strstreambuf(charT*, streamsize, charT*)</code> effects	1464
145	<code>seekoff</code> positioning	1466
146	<code>newoff</code> values	1466

List of Figures

1	Expression category taxonomy	83
2	Directed acyclic graph	257
3	Non-virtual base	258
4	Virtual base	258
5	Virtual and non-virtual base	259
6	Name lookup	261
7	Stream position, offset, and size types [non-normative]	1157

1 Scope

[intro.scope]

- ¹ This document specifies requirements for implementations of the C++ programming language. The first such requirement is that they implement the language, so this document also defines C++. Other requirements and relaxations of the first requirement appear at various places within this document.
- ² C++ is a general purpose programming language based on the C programming language as described in ISO/IEC 9899:2011 *Programming languages — C* (hereinafter referred to as the *C standard*). In addition to the facilities provided by C, C++ provides additional data types, classes, templates, exceptions, namespaces, operator overloading, function name overloading, references, free store management operators, and additional library facilities.

2 Normative references

[intro.refs]

¹ The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- (1.1) — Ecma International, *ECMAScript Language Specification*, Standard Ecma-262, third edition, 1999.
- (1.2) — ISO/IEC 2382 (all parts), *Information technology — Vocabulary*
- (1.3) — ISO/IEC 9899:2011, *Programming languages — C*
- (1.4) — ISO/IEC 9899:2011/Cor.1:2012(E), *Programming languages — C, Technical Corrigendum 1*
- (1.5) — ISO/IEC 9945:2003, *Information Technology — Portable Operating System Interface (POSIX)*
- (1.6) — ISO/IEC 10646-1:1993, *Information technology — Universal Multiple-Octet Coded Character Set (UCS) — Part 1: Architecture and Basic Multilingual Plane*
- (1.7) — ISO/IEC 10967-1:2012, *Information technology — Language independent arithmetic — Part 1: Integer and floating point arithmetic*
- (1.8) — ISO/IEC/IEEE 60559:2011, *Information technology — Microprocessor Systems — Floating-Point arithmetic*
- (1.9) — ISO 80000-2:2009, *Quantities and units — Part 2: Mathematical signs and symbols to be used in the natural sciences and technology*

² The library described in Clause 7 of ISO/IEC 9899:2011 is hereinafter called the *C standard library*.¹

³ The operating system interface described in ISO/IEC 9945:2003 is hereinafter called *POSIX*.

⁴ The ECMAScript Language Specification described in Standard Ecma-262 is hereinafter called *ECMA-262*.

⁵ The arithmetic specification described in ISO/IEC 10967-1:2012 is hereinafter called *LIA-1*.

¹) With the qualifications noted in Clauses 21 through 33 and in C.5, the C standard library is a subset of the C++ standard library.

3 Terms and definitions

[intro.defs]

- ¹ For the purposes of this document, the terms and definitions given in ISO/IEC 2382-1:1993, the terms, definitions, and symbols given in ISO 80000-2:2009, and the following apply.
- ² ISO and IEC maintain terminological databases for use in standardization at the following addresses:
 - (2.1) — IEC Electropedia: available at <http://www.electropedia.org/>
 - (2.2) — ISO Online browsing platform: available at <http://www.iso.org/obp>
- ³ 20.3 defines additional terms that are used only in Clauses 20 through 33 and Annex D.
- ⁴ Terms that are used only in a small portion of this document are defined where they are used and italicized where they are defined.

3.1 [defns.access]

access

⟨execution-time action⟩ to read or modify the value of an object

3.2 [defns.argument]

argument

⟨function call expression⟩ expression in the comma-separated list bounded by the parentheses (8.2.2)

3.3 [defns.argument.macro]

argument

⟨function-like macro⟩ sequence of preprocessing tokens in the comma-separated list bounded by the parentheses (19.3)

3.4 [defns.argument.throw]

argument

⟨throw expression⟩ the operand of **throw** (8.17)

3.5 [defns.argument.templ]

argument

⟨template instantiation⟩ *constant-expression*, *type-id*, or *id-expression* in the comma-separated list bounded by the angle brackets (17.3)

3.6 [defns.block]

block

a thread of execution that blocks is waiting for some condition (other than for the implementation to execute its execution steps) to be satisfied before it can continue execution past the blocking operation

3.7 [defns.cond.suppl]

conditionally-supported

program construct that an implementation is not required to support

[*Note*: Each implementation documents all conditionally-supported constructs that it does not support. — *end note*]

3.8 [defns.diagnostic]

diagnostic message

message belonging to an implementation-defined subset of the implementation's output messages

3.9 [defns.dynamic.type]

dynamic type

⟨glvalue⟩ type of the most derived object (4.5) to which the glvalue refers

[*Example:* If a pointer (11.3.1) *p* whose static type is “pointer to class B” is pointing to an object of class D, derived from B (Clause 13), the dynamic type of the expression **p* is “D”. References (11.3.2) are treated similarly. — *end example*]

3.10 [defns.dynamic.type.prvalue]

dynamic type

⟨prvalue⟩ static type of the prvalue expression

3.11 [defns.ill.formed]

ill-formed program

program that is not well-formed (3.29)

3.12 [defns.impl.defined]

implementation-defined behavior

behavior, for a well-formed program construct and correct data, that depends on the implementation and that each implementation documents

3.13 [defns.impl.limits]

implementation limits

restrictions imposed upon programs by the implementation

3.14 [defns.locale.specific]

locale-specific behavior

behavior that depends on local conventions of nationality, culture, and language that each implementation documents

3.15 [defns.multibyte]

multibyte character

sequence of one or more bytes representing a member of the extended character set of either the source or the execution environment

[*Note:* The extended character set is a superset of the basic character set (5.3). — *end note*]

3.16 [defns.parameter]

parameter

⟨function or catch clause⟩ object or reference declared as part of a function declaration or definition or in the catch clause of an exception handler that acquires a value on entry to the function or handler

3.17 [defns.parameter.macro]

parameter

⟨function-like macro⟩ identifier from the comma-separated list bounded by the parentheses immediately following the macro name

3.18 [defns.parameter.templ]

parameter

⟨template⟩ member of a *template-parameter-list*

3.19 [defns.signature]

signature

⟨function⟩ name, parameter type list (11.3.5), and enclosing namespace (if any)

[*Note:* Signatures are used as a basis for name mangling and linking. — *end note*]

3.20 [defns.signature.templ]
signature

⟨function template⟩ name, parameter type list (11.3.5), enclosing namespace (if any), return type, and template parameter list

3.21 [defns.signature.spec]
signature

⟨function template specialization⟩ signature of the template of which it is a specialization and its template arguments (whether explicitly specified or deduced)

3.22 [defns.signature.member]
signature

⟨class member function⟩ name, parameter type list (11.3.5), class of which the function is a member, *cv*-qualifiers (if any), and *ref-qualifier* (if any)

3.23 [defns.signature.member.templ]
signature

⟨class member function template⟩ name, parameter type list (11.3.5), class of which the function is a member, *cv*-qualifiers (if any), *ref-qualifier* (if any), return type (if any), and template parameter list

3.24 [defns.signature.member.spec]
signature

⟨class member function template specialization⟩ signature of the member function template of which it is a specialization and its template arguments (whether explicitly specified or deduced)

3.25 [defns.static.type]
static type

type of an expression (6.9) resulting from analysis of the program without considering execution semantics
 [*Note*: The static type of an expression depends only on the form of the program in which the expression appears, and does not change while the program is executing. — *end note*]

3.26 [defns.unblock]
unblock

satisfy a condition that one or more blocked threads of execution are waiting for

3.27 [defns.undefined]
undefined behavior

behavior for which this International Standard imposes no requirements

[*Note*: Undefined behavior may be expected when this International Standard omits any explicit definition of behavior or when a program uses an erroneous construct or erroneous data. Permissible undefined behavior ranges from ignoring the situation completely with unpredictable results, to behaving during translation or program execution in a documented manner characteristic of the environment (with or without the issuance of a diagnostic message), to terminating a translation or execution (with the issuance of a diagnostic message). Many erroneous program constructs do not engender undefined behavior; they are required to be diagnosed. Evaluation of a constant expression never exhibits behavior explicitly specified as undefined (8.20). — *end note*]

3.28 [defns.unspecified]
unspecified behavior

behavior, for a well-formed program construct and correct data, that depends on the implementation

[*Note*: The implementation is not required to document which behavior occurs. The range of possible behaviors is usually delineated by this International Standard. — *end note*]

3.29**[defns.well.formed]****well-formed program**

C++ program constructed according to the syntax rules, diagnosable semantic rules, and the one-definition rule (6.2).

4 General principles

[intro]

4.1 Implementation compliance

[intro.compliance]

- ¹ The set of *diagnosable rules* consists of all syntactic and semantic rules in this International Standard except for those rules containing an explicit notation that “no diagnostic is required” or which are described as resulting in “undefined behavior”.
 - ² Although this International Standard states only requirements on C++ implementations, those requirements are often easier to understand if they are phrased as requirements on programs, parts of programs, or execution of programs. Such requirements have the following meaning:
 - (2.1) — If a program contains no violations of the rules in this International Standard, a conforming implementation shall, within its resource limits, accept and correctly execute² that program.
 - (2.2) — If a program contains a violation of any diagnosable rule or an occurrence of a construct described in this International Standard as “conditionally-supported” when the implementation does not support that construct, a conforming implementation shall issue at least one diagnostic message.
 - (2.3) — If a program contains a violation of a rule for which no diagnostic is required, this International Standard places no requirement on implementations with respect to that program.
- [*Note:* During template argument deduction and substitution, certain constructs that in other contexts require a diagnostic are treated differently; see 17.8.2. — *end note*]
- ³ For classes and class templates, the library Clauses specify partial definitions. Private members (Clause 14) are not specified, but each implementation shall supply them to complete the definitions according to the description in the library Clauses.
 - ⁴ For functions, function templates, objects, and values, the library Clauses specify declarations. Implementations shall supply definitions consistent with the descriptions in the library Clauses.
 - ⁵ The names defined in the library have namespace scope (10.3). A C++ translation unit (5.2) obtains access to these names by including the appropriate standard library header (19.2).
 - ⁶ The templates, classes, functions, and objects in the library have external linkage (6.5). The implementation provides definitions for standard library entities, as necessary, while combining translation units to form a complete C++ program (5.2).
 - ⁷ Two kinds of implementations are defined: a *hosted implementation* and a *freestanding implementation*. For a hosted implementation, this International Standard defines the set of available libraries. A freestanding implementation is one in which execution may take place without the benefit of an operating system, and has an implementation-defined set of libraries that includes certain language-support libraries (20.5.1.3).
 - ⁸ A conforming implementation may have extensions (including additional library functions), provided they do not alter the behavior of any well-formed program. Implementations are required to diagnose programs that use such extensions that are ill-formed according to this International Standard. Having done so, however, they can compile and execute such programs.
 - ⁹ Each implementation shall include documentation that identifies all conditionally-supported constructs that it does not support and defines all locale-specific characteristics.³

²) “Correct execution” can include undefined behavior, depending on the data being processed; see Clause 3 and 4.6.

³) This documentation also defines implementation-defined behavior; see 4.6.

4.2 Structure of this document

[intro.structure]

- ¹ Clauses 5 through 19 describe the C++ programming language. That description includes detailed syntactic specifications in a form described in 4.3. For convenience, Annex A repeats all such syntactic specifications.
- ² Clauses 21 through 33 and Annex D (the *library clauses*) describe the C++ standard library. That description includes detailed descriptions of the entities and macros that constitute the library, in a form described in Clause 20.
- ³ Annex B recommends lower bounds on the capacity of conforming implementations.
- ⁴ Annex C summarizes the evolution of C++ since its first published description, and explains in detail the differences between C++ and C. Certain features of C++ exist solely for compatibility purposes; Annex D describes those features.
- ⁵ Throughout this document, each example is introduced by “[*Example:* ” and terminated by “ — *end example*]”. Each note is introduced by “[*Note:* ” and terminated by “ — *end note*]”. Examples and notes may be nested.

4.3 Syntax notation

[syntax]

- ¹ In the syntax notation used in this document, syntactic categories are indicated by *italic* type, and literal words and characters in **constant width** type. Alternatives are listed on separate lines except in a few cases where a long set of alternatives is marked by the phrase “one of”. If the text of an alternative is too long to fit on a line, the text is continued on subsequent lines indented from the first one. An optional terminal or non-terminal symbol is indicated by the subscript “_{opt}”, so

{ *expression_{opt}* }

indicates an optional expression enclosed in braces.

- ² Names for syntactic categories have generally been chosen according to the following rules:

- (2.1) — *X-name* is a use of an identifier in a context that determines its meaning (e.g., *class-name*, *typedef-name*).
- (2.2) — *X-id* is an identifier with no context-dependent meaning (e.g., *qualified-id*).
- (2.3) — *X-seq* is one or more *X*’s without intervening delimiters (e.g., *declaration-seq* is a sequence of declarations).
- (2.4) — *X-list* is one or more *X*’s separated by intervening commas (e.g., *identifier-list* is a sequence of identifiers separated by commas).

4.4 The C++ memory model

[intro.memory]

- ¹ The fundamental storage unit in the C++ memory model is the *byte*. A byte is at least large enough to contain any member of the basic execution character set (5.3) and the eight-bit code units of the Unicode UTF-8 encoding form and is composed of a contiguous sequence of bits,⁴ the number of which is implementation-defined. The least significant bit is called the *low-order bit*; the most significant bit is called the *high-order bit*. The memory available to a C++ program consists of one or more sequences of contiguous bytes. Every byte has a unique address.
- ² [*Note:* The representation of types is described in 6.9. — *end note*]
- ³ A *memory location* is either an object of scalar type or a maximal sequence of adjacent bit-fields all having nonzero width. [*Note:* Various features of the language, such as references and virtual functions, might involve additional memory locations that are not accessible to programs but are managed by the implementation. — *end note*] Two or more threads of execution (4.7) can access separate memory locations without interfering with each other.
- ⁴ [*Note:* Thus a bit-field and an adjacent non-bit-field are in separate memory locations, and therefore can be concurrently updated by two threads of execution without interference. The same applies to two bit-fields,

⁴) The number of bits in a byte is reported by the macro `CHAR_BIT` in the header `<climits>`.

if one is declared inside a nested struct declaration and the other is not, or if the two are separated by a zero-length bit-field declaration, or if they are separated by a non-bit-field declaration. It is not safe to concurrently update two bit-fields in the same struct if all fields between them are also bit-fields of nonzero width. — *end note*]

⁵ [*Example:* A structure declared as

```
struct {
    char a;
    int b:5,
    c:11,
    :0,
    d:8;
    struct {int ee:8;} e;
}
```

contains four separate memory locations: The field **a** and bit-fields **d** and **e.ee** are each separate memory locations, and can be modified concurrently without interfering with each other. The bit-fields **b** and **c** together constitute the fourth memory location. The bit-fields **b** and **c** cannot be concurrently modified, but **b** and **a**, for example, can be. — *end example*]

4.5 The C++ object model

[intro.object]

¹ The constructs in a C++ program create, destroy, refer to, access, and manipulate objects. An *object* is created by a definition (6.1), by a *new-expression* (8.3.4), when implicitly changing the active member of a union (12.3), or when a temporary object is created (7.4, 15.2). An object occupies a region of storage in its period of construction (15.7), throughout its lifetime (6.8), and in its period of destruction (15.7). [*Note:* A function is not an object, regardless of whether or not it occupies storage in the way that objects do. — *end note*] The properties of an object are determined when the object is created. An object can have a name (Clause 6). An object has a storage duration (6.7) which influences its lifetime (6.8). An object has a type (6.9). Some objects are polymorphic (13.3); the implementation generates information associated with each such object that makes it possible to determine that object's type during program execution. For other objects, the interpretation of the values found therein is determined by the type of the *expressions* (Clause 8) used to access them.

² Objects can contain other objects, called *subobjects*. A subobject can be a *member subobject* (12.2), a *base class subobject* (Clause 13), or an array element. An object that is not a subobject of any other object is called a *complete object*. If an object is created in storage associated with a member subobject or array element *e* (which may or may not be within its lifetime), the created object is a subobject of *e*'s containing object if:

- (2.1) — the lifetime of *e*'s containing object has begun and not ended, and
- (2.2) — the storage for the new object exactly overlays the storage location associated with *e*, and
- (2.3) — the new object is of the same type as *e* (ignoring cv-qualification).

[*Note:* If the subobject contains a reference member or a **const** subobject, the name of the original subobject cannot be used to access the new object (6.8). — *end note*] [*Example:*

```
struct X { const int n; };
union U { X x; float f; };
void tong() {
    U u = {{ 1 }};
    u.f = 5.f; // OK, creates new subobject of u (12.3)
    X *p = new (&u.x) X {2}; // OK, creates new subobject of u
    assert(p->n == 2); // OK
    assert(*std::launder(&u.x.n) == 2); // OK
    assert(u.x.n == 2); // undefined behavior, u.x does not name new subobject
```


}

— *end example*]

- 3 If a complete object is created (8.3.4) in storage associated with another object *e* of type “array of *N* unsigned char” or of type “array of *N* std::byte” (21.2.1), that array *provides storage* for the created object if:

- (3.1) — the lifetime of *e* has begun and not ended, and
- (3.2) — the storage for the new object fits entirely within *e*, and
- (3.3) — there is no smaller array object that satisfies these constraints.

[*Note*: If that portion of the array previously provided storage for another object, the lifetime of that object ends because its storage was reused (6.8). — *end note*] [*Example*:

```
template<typename ...T>
struct AlignedUnion {
    alignas(T...) unsigned char data[max(sizeof(T)...)];
};
int f() {
    AlignedUnion<int, char> au;
    int *p = new (au.data) int;      // OK, au.data provides storage
    char *c = new (au.data) char(); // OK, ends lifetime of *p
    char *d = new (au.data + 1) char();
    return *c + *d; // OK
}

struct A { unsigned char a[32]; };
struct B { unsigned char b[16]; };
A a;
B *b = new (a.a + 8) B;           // a.a provides storage for *b
int *p = new (b->b + 4) int;      // b->b provides storage for *p
                                   // a.a does not provide storage for *p (directly),
                                   // but *p is nested within a (see below)
```

— *end example*]

- 4 An object *a* is *nested within* another object *b* if:

- (4.1) — *a* is a subobject of *b*, or
- (4.2) — *b* provides storage for *a*, or
- (4.3) — there exists an object *c* where *a* is nested within *c*, and *c* is nested within *b*.

- 5 For every object *x*, there is some object called the *complete object of x*, determined as follows:

- (5.1) — If *x* is a complete object, then the complete object of *x* is itself.
- (5.2) — Otherwise, the complete object of *x* is the complete object of the (unique) object that contains *x*.

- 6 If a complete object, a data member (12.2), or an array element is of class type, its type is considered the *most derived class*, to distinguish it from the class type of any base class subobject; an object of a most derived class type or of a non-class type is called a *most derived object*.

- 7 Unless it is a bit-field (12.2.4), a most derived object shall have a nonzero size and shall occupy one or more bytes of storage. Base class subobjects may have zero size. An object of trivially copyable or standard-layout type (6.9) shall occupy contiguous bytes of storage.

- 8 Unless an object is a bit-field or a base class subobject of zero size, the address of that object is the address of the first byte it occupies. Two objects *a* and *b* with overlapping lifetimes that are not bit-fields may have the same address if one is nested within the other, or if at least one is a base class subobject of zero size and

they are of different types; otherwise, they have distinct addresses.⁵

[*Example:*

```
static const char test1 = 'x';
static const char test2 = 'x';
const bool b = &test1 != &test2;    // always true
```

— *end example*]

- ⁹ [Note: C++ provides a variety of fundamental types and several ways of composing new types from existing types (6.9). — *end note*]

4.6 Program execution

[intro.execution]

- ¹ The semantic descriptions in this International Standard define a parameterized nondeterministic abstract machine. This International Standard places no requirement on the structure of conforming implementations. In particular, they need not copy or emulate the structure of the abstract machine. Rather, conforming implementations are required to emulate (only) the observable behavior of the abstract machine as explained below.⁶
- ² Certain aspects and operations of the abstract machine are described in this International Standard as implementation-defined (for example, `sizeof(int)`). These constitute the parameters of the abstract machine. Each implementation shall include documentation describing its characteristics and behavior in these respects.⁷ Such documentation shall define the instance of the abstract machine that corresponds to that implementation (referred to as the “corresponding instance” below).
- ³ Certain other aspects and operations of the abstract machine are described in this International Standard as unspecified (for example, evaluation of expressions in a *new-initializer* if the allocation function fails to allocate memory (8.3.4)). Where possible, this International Standard defines a set of allowable behaviors. These define the nondeterministic aspects of the abstract machine. An instance of the abstract machine can thus have more than one possible execution for a given program and a given input.
- ⁴ Certain other operations are described in this International Standard as undefined (for example, the effect of attempting to modify a `const` object). [Note: This International Standard imposes no requirements on the behavior of programs that contain undefined behavior. — *end note*]
- ⁵ A conforming implementation executing a well-formed program shall produce the same observable behavior as one of the possible executions of the corresponding instance of the abstract machine with the same program and the same input. However, if any such execution contains an undefined operation, this International Standard places no requirement on the implementation executing that program with that input (not even with regard to operations preceding the first undefined operation).
- ⁶ An instance of each object with automatic storage duration (6.7.3) is associated with each entry into its block. Such an object exists and retains its last-stored value during the execution of the block and while the block is suspended (by a call of a function or receipt of a signal).
- ⁷ The least requirements on a conforming implementation are:
 - (7.1) — Accesses through volatile glvalues are evaluated strictly according to the rules of the abstract machine.
 - (7.2) — At program termination, all data written into files shall be identical to one of the possible results that execution of the program according to the abstract semantics would have produced.

⁵ Under the “as-if” rule an implementation is allowed to store two objects at the same machine address or not store an object at all if the program cannot observe the difference (4.6).

⁶ This provision is sometimes called the “as-if” rule, because an implementation is free to disregard any requirement of this International Standard as long as the result is *as if* the requirement had been obeyed, as far as can be determined from the observable behavior of the program. For instance, an actual implementation need not evaluate part of an expression if it can deduce that its value is not used and that no side effects affecting the observable behavior of the program are produced.

⁷ This documentation also includes conditionally-supported constructs and locale-specific behavior. See 4.1.

- (7.3) — The input and output dynamics of interactive devices shall take place in such a fashion that prompting output is actually delivered before a program waits for input. What constitutes an interactive device is implementation-defined.

These collectively are referred to as the *observable behavior* of the program. [*Note*: More stringent correspondences between abstract and actual semantics may be defined by each implementation. — *end note*]

- ⁸ [*Note*: Operators can be regrouped according to the usual mathematical rules only where the operators really are associative or commutative.⁸ For example, in the following fragment

```
int a, b;
/* ... */
a = a + 32760 + b + 5;
```

the expression statement behaves exactly the same as

```
a = ((a + 32760) + b) + 5);
```

due to the associativity and precedence of these operators. Thus, the result of the sum (a + 32760) is next added to b, and that result is then added to 5 which results in the value assigned to a. On a machine in which overflows produce an exception and in which the range of values representable by an `int` is [-32768, +32767], the implementation cannot rewrite this expression as

```
a = ((a + b) + 32765);
```

since if the values for a and b were, respectively, -32754 and -15, the sum a + b would produce an exception while the original expression would not; nor can the expression be rewritten either as

```
a = ((a + 32765) + b);
```

or

```
a = (a + (b + 32765));
```

since the values for a and b might have been, respectively, 4 and -8 or -17 and 12. However on a machine in which overflows do not produce an exception and in which the results of overflows are reversible, the above expression statement can be rewritten by the implementation in any of the above ways because the same result will occur. — *end note*]

- ⁹ A *constituent expression* is defined as follows:

- (9.1) — The constituent expression of an expression is that expression.
- (9.2) — The constituent expressions of a *braced-init-list* or of a (possibly parenthesized) *expression-list* are the constituent expressions of the elements of the respective list.
- (9.3) — The constituent expressions of a *brace-or-equal-initializer* of the form = *initializer-clause* are the constituent expressions of the *initializer-clause*.

[*Example*:

```
struct A { int x; };
struct B { int y; struct A a; };
B b = { 5, { 1+1 } };
```

The constituent expressions of the *initializer* used for the initialization of b are 5 and 1+1. — *end example*]

- ¹⁰ The *immediate subexpressions* of an expression e are

- (10.1) — the constituent expressions of e's operands (Clause 8),
- (10.2) — any function call that e implicitly invokes,
- (10.3) — if e is a *lambda-expression* (8.1.5), the initialization of the entities captured by copy and the constituent

⁸) Overloaded operators are never assumed to be associative or commutative.

expressions of the *initializer* of the *init-captures*,

- (10.4) — if **e** is a function call (8.2.2) or implicitly invokes a function, the constituent expressions of each default argument (11.3.6) used in the call, or
 - (10.5) — if **e** creates an aggregate object (11.6.1), the constituent expressions of each default member initializer (12.2) used in the initialization.
- 11 A *subexpression* of an expression **e** is an immediate subexpression of **e** or a subexpression of an immediate subexpression of **e**. [Note: Expressions appearing in the *compound-statement* of a *lambda-expression* are not subexpressions of the *lambda-expression*. — end note]
- 12 A *full-expression* is
- (12.1) — an unevaluated operand (Clause 8),
 - (12.2) — a *constant-expression* (8.20),
 - (12.3) — an *init-declarator* (Clause 11) or a *mem-initializer* (15.6.2), including the constituent expressions of the initializer,
 - (12.4) — an invocation of a destructor generated at the end of the lifetime of an object other than a temporary object (15.2), or
 - (12.5) — an expression that is not a subexpression of another expression and that is not otherwise part of a full-expression.

If a language construct is defined to produce an implicit call of a function, a use of the language construct is considered to be an expression for the purposes of this definition. Conversions applied to the result of an expression in order to satisfy the requirements of the language construct in which the expression appears are also considered to be part of the full-expression. For an initializer, performing the initialization of the entity (including evaluating default member initializers of an aggregate) is also considered part of the full-expression.

[Example:

```
struct S {
    S(int i): I(i) { }           // full-expression is initialization of I
    int& v() { return I; }
    ~S() noexcept(false) { }
private:
    int I;
};

S s1(1);                        // full-expression is call of S::S(int)
void f() {
    S s2 = 2;                   // full-expression is call of S::S(int)
    if (S(3).v())               // full-expression includes lvalue-to-rvalue and
                                // int to bool conversions, performed before
                                // temporary is deleted at end of full-expression
    { }
    bool b = noexcept(S());     // exception specification of destructor of S
                                // considered for noexcept
    // full-expression is destruction of s2 at end of block
}

struct B {
    B(S = S(0));
};
B b[2] = { B(), B() };         // full-expression is the entire initialization
                                // including the destruction of temporaries
```

— end example]

- ¹³ [*Note*: The evaluation of a full-expression can include the evaluation of subexpressions that are not lexically part of the full-expression. For example, subexpressions involved in evaluating default arguments (11.3.6) are considered to be created in the expression that calls the function, not the expression that defines the default argument. — *end note*]
- ¹⁴ Reading an object designated by a **volatile** glvalue (6.10), modifying an object, calling a library I/O function, or calling a function that does any of those operations are all *side effects*, which are changes in the state of the execution environment. *Evaluation* of an expression (or a subexpression) in general includes both value computations (including determining the identity of an object for glvalue evaluation and fetching a value previously assigned to an object for prvalue evaluation) and initiation of side effects. When a call to a library I/O function returns or an access through a volatile glvalue is evaluated the side effect is considered complete, even though some external actions implied by the call (such as the I/O itself) or by the **volatile** access may not have completed yet.
- ¹⁵ *Sequenced before* is an asymmetric, transitive, pair-wise relation between evaluations executed by a single thread (4.7), which induces a partial order among those evaluations. Given any two evaluations *A* and *B*, if *A* is sequenced before *B* (or, equivalently, *B* is *sequenced after A*), then the execution of *A* shall precede the execution of *B*. If *A* is not sequenced before *B* and *B* is not sequenced before *A*, then *A* and *B* are *unsequenced*. [*Note*: The execution of unsequenced evaluations can overlap. — *end note*] Evaluations *A* and *B* are *indeterminately sequenced* when either *A* is sequenced before *B* or *B* is sequenced before *A*, but it is unspecified which. [*Note*: Indeterminately sequenced evaluations cannot overlap, but either could be executed first. — *end note*] An expression *X* is said to be sequenced before an expression *Y* if every value computation and every side effect associated with the expression *X* is sequenced before every value computation and every side effect associated with the expression *Y*.
- ¹⁶ Every value computation and side effect associated with a full-expression is sequenced before every value computation and side effect associated with the next full-expression to be evaluated.⁹
- ¹⁷ Except where noted, evaluations of operands of individual operators and of subexpressions of individual expressions are unsequenced. [*Note*: In an expression that is evaluated more than once during the execution of a program, unsequenced and indeterminately sequenced evaluations of its subexpressions need not be performed consistently in different evaluations. — *end note*] The value computations of the operands of an operator are sequenced before the value computation of the result of the operator. If a side effect on a memory location (4.4) is unsequenced relative to either another side effect on the same memory location or a value computation using the value of any object in the same memory location, and they are not potentially concurrent (4.7), the behavior is undefined. [*Note*: The next section imposes similar, but more complex restrictions on potentially concurrent computations. — *end note*]

[*Example*:

```
void g(int i) {
    i = 7, i++, i++;    // i becomes 9

    i = i++ + 1;        // the value of i is incremented
    i = i++ + i;        // the behavior is undefined
    i = i + 1;          // the value of i is incremented
}
```

— *end example*]

- ¹⁸ When calling a function (whether or not the function is inline), every value computation and side effect associated with any argument expression, or with the postfix expression designating the called function, is sequenced before execution of every expression or statement in the body of the called function. For each function invocation *F*, for every evaluation *A* that occurs within *F* and every evaluation *B* that does not

⁹) As specified in 15.2, after a full-expression is evaluated, a sequence of zero or more invocations of destructor functions for temporary objects takes place, usually in reverse order of the construction of each temporary object.

occur within F but is evaluated on the same thread and as part of the same signal handler (if any), either A is sequenced before B or B is sequenced before A .¹⁰ [Note: If A and B would not otherwise be sequenced then they are indeterminately sequenced. — end note] Several contexts in C++ cause evaluation of a function call, even though no corresponding function call syntax appears in the translation unit. [Example: Evaluation of a *new-expression* invokes one or more allocation and constructor functions; see 8.3.4. For another example, invocation of a conversion function (15.3.2) can arise in contexts in which no function call syntax appears. — end example] The sequencing constraints on the execution of the called function (as described above) are features of the function calls as evaluated, whatever the syntax of the expression that calls the function might be.

- ¹⁹ If a signal handler is executed as a result of a call to the `std::raise` function, then the execution of the handler is sequenced after the invocation of the `std::raise` function and before its return. [Note: When a signal is received for another reason, the execution of the signal handler is usually unsequenced with respect to the rest of the program. — end note]

4.7 Multi-threaded executions and data races

[intro.multithread]

- ¹ A *thread of execution* (also known as a *thread*) is a single flow of control within a program, including the initial invocation of a specific top-level function, and recursively including every function invocation subsequently executed by the thread. [Note: When one thread creates another, the initial call to the top-level function of the new thread is executed by the new thread, not by the creating thread. — end note] Every thread in a program can potentially access every object and function in a program.¹¹ Under a hosted implementation, a C++ program can have more than one thread running concurrently. The execution of each thread proceeds as defined by the remainder of this International Standard. The execution of the entire program consists of an execution of all of its threads. [Note: Usually the execution can be viewed as an interleaving of all its threads. However, some kinds of atomic operations, for example, allow executions inconsistent with a simple interleaving, as described below. — end note] Under a freestanding implementation, it is implementation-defined whether a program can have more than one thread of execution.
- ² For a signal handler that is not executed as a result of a call to the `std::raise` function, it is unspecified which thread of execution contains the signal handler invocation.

4.7.1 Data races

[intro.races]

- ¹ The value of an object visible to a thread T at a particular point is the initial value of the object, a value assigned to the object by T , or a value assigned to the object by another thread, according to the rules below. [Note: In some cases, there may instead be undefined behavior. Much of this section is motivated by the desire to support atomic operations with explicit and detailed visibility constraints. However, it also implicitly supports a simpler view for more restricted programs. — end note]
- ² Two expression evaluations *conflict* if one of them modifies a memory location (4.4) and the other one reads or modifies the same memory location.
- ³ The library defines a number of atomic operations (Clause 32) and operations on mutexes (Clause 33) that are specially identified as synchronization operations. These operations play a special role in making assignments in one thread visible to another. A synchronization operation on one or more memory locations is either a consume operation, an acquire operation, a release operation, or both an acquire and release operation. A synchronization operation without an associated memory location is a fence and can be either an acquire fence, a release fence, or both an acquire and release fence. In addition, there are relaxed atomic operations, which are not synchronization operations, and atomic read-modify-write operations, which have special characteristics. [Note: For example, a call that acquires a mutex will perform an acquire operation on the locations comprising the mutex. Correspondingly, a call that releases the same mutex will perform a

¹⁰) In other words, function executions do not interleave with each other.

¹¹) An object with automatic or thread storage duration (6.7) is associated with one specific thread, and can be accessed by a different thread only indirectly through a pointer or reference (6.9.2).

release operation on those same locations. Informally, performing a release operation on A forces prior side effects on other memory locations to become visible to other threads that later perform a consume or an acquire operation on A . “Relaxed” atomic operations are not synchronization operations even though, like synchronization operations, they cannot contribute to data races. — *end note*]

- 4 All modifications to a particular atomic object M occur in some particular total order, called the *modification order* of M . [*Note*: There is a separate order for each atomic object. There is no requirement that these can be combined into a single total order for all objects. In general this will be impossible since different threads may observe modifications to different objects in inconsistent orders. — *end note*]
- 5 A *release sequence* headed by a release operation A on an atomic object M is a maximal contiguous subsequence of side effects in the modification order of M , where the first operation is A , and every subsequent operation
 - (5.1) — is performed by the same thread that performed A , or
 - (5.2) — is an atomic read-modify-write operation.
- 6 Certain library calls *synchronize with* other library calls performed by another thread. For example, an atomic store-release synchronizes with a load-acquire that takes its value from the store (32.4). [*Note*: Except in the specified cases, reading a later value does not necessarily ensure visibility as described below. Such a requirement would sometimes interfere with efficient implementation. — *end note*] [*Note*: The specifications of the synchronization operations define when one reads the value written by another. For atomic objects, the definition is clear. All operations on a given mutex occur in a single total order. Each mutex acquisition “reads the value written” by the last mutex release. — *end note*]
- 7 An evaluation A *carries a dependency* to an evaluation B if
 - (7.1) — the value of A is used as an operand of B , unless:
 - (7.1.1) — B is an invocation of any specialization of `std::kill_dependency` (32.4), or
 - (7.1.2) — A is the left operand of a built-in logical AND (`&&`, see 8.14) or logical OR (`||`, see 8.15) operator, or
 - (7.1.3) — A is the left operand of a conditional (`?:`, see 8.16) operator, or
 - (7.1.4) — A is the left operand of the built-in comma (`,`) operator (8.19);
 - or
 - (7.2) — A writes a scalar object or bit-field M , B reads the value written by A from M , and A is sequenced before B , or
 - (7.3) — for some evaluation X , A carries a dependency to X , and X carries a dependency to B .

[*Note*: “Carries a dependency to” is a subset of “is sequenced before”, and is similarly strictly intra-thread. — *end note*]
- 8 An evaluation A is *dependency-ordered before* an evaluation B if
 - (8.1) — A performs a release operation on an atomic object M , and, in another thread, B performs a consume operation on M and reads a value written by any side effect in the release sequence headed by A , or
 - (8.2) — for some evaluation X , A is dependency-ordered before X and X carries a dependency to B .

[*Note*: The relation “is dependency-ordered before” is analogous to “synchronizes with”, but uses release/-consume in place of release/acquire. — *end note*]
- 9 An evaluation A *inter-thread happens before* an evaluation B if
 - (9.1) — A synchronizes with B , or
 - (9.2) — A is dependency-ordered before B , or

- (9.3) — for some evaluation X
- (9.3.1) — A synchronizes with X and X is sequenced before B , or
- (9.3.2) — A is sequenced before X and X inter-thread happens before B , or
- (9.3.3) — A inter-thread happens before X and X inter-thread happens before B .

[*Note:* The “inter-thread happens before” relation describes arbitrary concatenations of “sequenced before”, “synchronizes with” and “dependency-ordered before” relationships, with two exceptions. The first exception is that a concatenation is not permitted to end with “dependency-ordered before” followed by “sequenced before”. The reason for this limitation is that a consume operation participating in a “dependency-ordered before” relationship provides ordering only with respect to operations to which this consume operation actually carries a dependency. The reason that this limitation applies only to the end of such a concatenation is that any subsequent release operation will provide the required ordering for a prior consume operation. The second exception is that a concatenation is not permitted to consist entirely of “sequenced before”. The reasons for this limitation are (1) to permit “inter-thread happens before” to be transitively closed and (2) the “happens before” relation, defined below, provides for relationships consisting entirely of “sequenced before”. — *end note*]

- 10 An evaluation A *happens before* an evaluation B (or, equivalently, B *happens after* A) if:
 - (10.1) — A is sequenced before B , or
 - (10.2) — A inter-thread happens before B .

The implementation shall ensure that no program execution demonstrates a cycle in the “happens before” relation. [*Note:* This cycle would otherwise be possible only through the use of consume operations. — *end note*]

- 11 An evaluation A *strongly happens before* an evaluation B if either
 - (11.1) — A is sequenced before B , or
 - (11.2) — A synchronizes with B , or
 - (11.3) — A strongly happens before X and X strongly happens before B .

[*Note:* In the absence of consume operations, the happens before and strongly happens before relations are identical. Strongly happens before essentially excludes consume operations. — *end note*]

- 12 A *visible side effect* A on a scalar object or bit-field M with respect to a value computation B of M satisfies the conditions:
 - (12.1) — A happens before B and
 - (12.2) — there is no other side effect X to M such that A happens before X and X happens before B .

The value of a non-atomic scalar object or bit-field M , as determined by evaluation B , shall be the value stored by the visible side effect A . [*Note:* If there is ambiguity about which side effect to a non-atomic object or bit-field is visible, then the behavior is either unspecified or undefined. — *end note*] [*Note:* This states that operations on ordinary objects are not visibly reordered. This is not actually detectable without data races, but it is necessary to ensure that data races, as defined below, and with suitable restrictions on the use of atomics, correspond to data races in a simple interleaved (sequentially consistent) execution. — *end note*]

- 13 The value of an atomic object M , as determined by evaluation B , shall be the value stored by some side effect A that modifies M , where B does not happen before A . [*Note:* The set of such side effects is also restricted by the rest of the rules described here, and in particular, by the coherence requirements below. — *end note*]
- 14 If an operation A that modifies an atomic object M happens before an operation B that modifies M , then A shall be earlier than B in the modification order of M . [*Note:* This requirement is known as write-write coherence. — *end note*]

- 15 If a value computation *A* of an atomic object *M* happens before a value computation *B* of *M*, and *A* takes its value from a side effect *X* on *M*, then the value computed by *B* shall either be the value stored by *X* or the value stored by a side effect *Y* on *M*, where *Y* follows *X* in the modification order of *M*. [*Note*: This requirement is known as read-read coherence. — *end note*]
- 16 If a value computation *A* of an atomic object *M* happens before an operation *B* that modifies *M*, then *A* shall take its value from a side effect *X* on *M*, where *X* precedes *B* in the modification order of *M*. [*Note*: This requirement is known as read-write coherence. — *end note*]
- 17 If a side effect *X* on an atomic object *M* happens before a value computation *B* of *M*, then the evaluation *B* shall take its value from *X* or from a side effect *Y* that follows *X* in the modification order of *M*. [*Note*: This requirement is known as write-read coherence. — *end note*]
- 18 [*Note*: The four preceding coherence requirements effectively disallow compiler reordering of atomic operations to a single object, even if both operations are relaxed loads. This effectively makes the cache coherence guarantee provided by most hardware available to C++ atomic operations. — *end note*]
- 19 [*Note*: The value observed by a load of an atomic depends on the “happens before” relation, which depends on the values observed by loads of atomics. The intended reading is that there must exist an association of atomic loads with modifications they observe that, together with suitably chosen modification orders and the “happens before” relation derived as described above, satisfy the resulting constraints as imposed here. — *end note*]
- 20 Two actions are *potentially concurrent* if
 - (20.1) — they are performed by different threads, or
 - (20.2) — they are unsequenced, at least one is performed by a signal handler, and they are not both performed by the same signal handler invocation.

The execution of a program contains a *data race* if it contains two potentially concurrent conflicting actions, at least one of which is not atomic, and neither happens before the other, except for the special case for signal handlers described below. Any such data race results in undefined behavior. [*Note*: It can be shown that programs that correctly use mutexes and `memory_order_seq_cst` operations to prevent all data races and use no other synchronization operations behave as if the operations executed by their constituent threads were simply interleaved, with each value computation of an object being taken from the last side effect on that object in that interleaving. This is normally referred to as “sequential consistency”. However, this applies only to data-race-free programs, and data-race-free programs cannot observe most program transformations that do not change single-threaded program semantics. In fact, most single-threaded program transformations continue to be allowed, since any program that behaves differently as a result must perform an undefined operation. — *end note*]

- 21 Two accesses to the same object of type `volatile std::sig_atomic_t` do not result in a data race if both occur in the same thread, even if one or more occurs in a signal handler. For each signal handler invocation, evaluations performed by the thread invoking a signal handler can be divided into two groups *A* and *B*, such that no evaluations in *B* happen before evaluations in *A*, and the evaluations of such `volatile std::sig_atomic_t` objects take values as though all evaluations in *A* happened before the execution of the signal handler and the execution of the signal handler happened before all evaluations in *B*.
- 22 [*Note*: Compiler transformations that introduce assignments to a potentially shared memory location that would not be modified by the abstract machine are generally precluded by this International Standard, since such an assignment might overwrite another assignment by a different thread in cases in which an abstract machine execution would not have encountered a data race. This includes implementations of data member assignment that overwrite adjacent members in separate memory locations. Reordering of atomic loads in cases in which the atomics in question may alias is also generally precluded, since this may violate the coherence rules. — *end note*]
- 23 [*Note*: Transformations that introduce a speculative read of a potentially shared memory location may not

preserve the semantics of the C++ program as defined in this International Standard, since they potentially introduce a data race. However, they are typically valid in the context of an optimizing compiler that targets a specific machine with well-defined semantics for data races. They would be invalid for a hypothetical machine that is not tolerant of races or provides hardware race detection. — *end note*

4.7.2 Forward progress [intro.progress]

¹ The implementation may assume that any thread will eventually do one of the following:

- (1.1) — terminate,
- (1.2) — make a call to a library I/O function,
- (1.3) — perform an access through a volatile glvalue, or
- (1.4) — perform a synchronization operation or an atomic operation.

[*Note*: This is intended to allow compiler transformations such as removal of empty loops, even when termination cannot be proven. — *end note*]

² Executions of atomic functions that are either defined to be lock-free (32.8) or indicated as lock-free (32.5) are *lock-free executions*.

- (2.1) — If there is only one thread that is not blocked (3.6) in a standard library function, a lock-free execution in that thread shall complete. [*Note*: Concurrently executing threads may prevent progress of a lock-free execution. For example, this situation can occur with load-locked store-conditional implementations. This property is sometimes termed obstruction-free. — *end note*]
- (2.2) — When one or more lock-free executions run concurrently, at least one should complete. [*Note*: It is difficult for some implementations to provide absolute guarantees to this effect, since repeated and particularly inopportune interference from other threads may prevent forward progress, e.g., by repeatedly stealing a cache line for unrelated purposes between load-locked and store-conditional instructions. Implementations should ensure that such effects cannot indefinitely delay progress under expected operating conditions, and that such anomalies can therefore safely be ignored by programmers. Outside this document, this property is sometimes termed lock-free. — *end note*]

³ During the execution of a thread of execution, each of the following is termed an *execution step*:

- (3.1) — termination of the thread of execution,
- (3.2) — performing an access through a volatile glvalue, or
- (3.3) — completion of a call to a library I/O function, a synchronization operation, or an atomic operation.

⁴ An invocation of a standard library function that blocks (3.6) is considered to continuously execute execution steps while waiting for the condition that it blocks on to be satisfied. [*Example*: A library I/O function that blocks until the I/O operation is complete can be considered to continuously check whether the operation is complete. Each such check might consist of one or more execution steps, for example using observable behavior of the abstract machine. — *end example*]

⁵ [*Note*: Because of this and the preceding requirement regarding what threads of execution have to perform eventually, it follows that no thread of execution can execute forever without an execution step occurring. — *end note*]

⁶ A thread of execution *makes progress* when an execution step occurs or a lock-free execution does not complete because there are other concurrent threads that are not blocked in a standard library function (see above).

⁷ For a thread of execution providing *concurrent forward progress guarantees*, the implementation ensures that the thread will eventually make progress for as long as it has not terminated. [*Note*: This is required regardless of whether or not other threads of executions (if any) have been or are making progress. To eventually fulfill this requirement means that this will happen in an unspecified but finite amount of time. — *end note*]

- ⁸ It is implementation-defined whether the implementation-created thread of execution that executes `main` (6.6.1) and the threads of execution created by `std::thread` (33.3.2) provide concurrent forward progress guarantees. [*Note*: General-purpose implementations are encouraged to provide these guarantees. — *end note*]
- ⁹ For a thread of execution providing *parallel forward progress guarantees*, the implementation is not required to ensure that the thread will eventually make progress if it has not yet executed any execution step; once this thread has executed a step, it provides concurrent forward progress guarantees.
- ¹⁰ [*Note*: This does not specify a requirement for when to start this thread of execution, which will typically be specified by the entity that creates this thread of execution. For example, a thread of execution that provides concurrent forward progress guarantees and executes tasks from a set of tasks in an arbitrary order, one after the other, satisfies the requirements of parallel forward progress for these tasks. — *end note*]
- ¹¹ For a thread of execution providing *weakly parallel forward progress guarantees*, the implementation does not ensure that the thread will eventually make progress.
- ¹² [*Note*: Threads of execution providing weakly parallel forward progress guarantees cannot be expected to make progress regardless of whether other threads make progress or not; however, blocking with forward progress guarantee delegation, as defined below, can be used to ensure that such threads of execution make progress eventually. — *end note*]
- ¹³ Concurrent forward progress guarantees are stronger than parallel forward progress guarantees, which in turn are stronger than weakly parallel forward progress guarantees. [*Note*: For example, some kinds of synchronization between threads of execution may only make progress if the respective threads of execution provide parallel forward progress guarantees, but will fail to make progress under weakly parallel guarantees. — *end note*]
- ¹⁴ When a thread of execution *P* is specified to *block with forward progress guarantee delegation* on the completion of a set *S* of threads of execution, then throughout the whole time of *P* being blocked on *S*, the implementation shall ensure that the forward progress guarantees provided by at least one thread of execution in *S* is at least as strong as *P*'s forward progress guarantees. [*Note*: It is unspecified which thread or threads of execution in *S* are chosen and for which number of execution steps. The strengthening is not permanent and not necessarily in place for the rest of the lifetime of the affected thread of execution. As long as *P* is blocked, the implementation has to eventually select and potentially strengthen a thread of execution in *S*. — *end note*] Once a thread of execution in *S* terminates, it is removed from *S*. Once *S* is empty, *P* is unblocked.
- ¹⁵ [*Note*: A thread of execution *B* thus can temporarily provide an effectively stronger forward progress guarantee for a certain amount of time, due to a second thread of execution *A* being blocked on it with forward progress guarantee delegation. In turn, if *B* then blocks with forward progress guarantee delegation on *C*, this may also temporarily provide a stronger forward progress guarantee to *C*. — *end note*]
- ¹⁶ [*Note*: If all threads of execution in *S* finish executing (e.g., they terminate and do not use blocking synchronization incorrectly), then *P*'s execution of the operation that blocks with forward progress guarantee delegation will not result in *P*'s progress guarantee being effectively weakened. — *end note*]
- ¹⁷ [*Note*: This does not remove any constraints regarding blocking synchronization for threads of execution providing parallel or weakly parallel forward progress guarantees because the implementation is not required to strengthen a particular thread of execution whose too-weak progress guarantee is preventing overall progress. — *end note*]
- ¹⁸ An implementation should ensure that the last value (in modification order) assigned by an atomic or synchronization operation will become visible to all other threads in a finite period of time.

4.8 Acknowledgments

[intro.ack]

- ¹ The C++ programming language as described in this document is based on the language as described in Chapter R (Reference Manual) of Stroustrup: *The C++ Programming Language* (second edition, Addison-Wesley Publishing Company, ISBN 0-201-53992-6, copyright ©1991 AT&T). That, in turn, is based on the C

programming language as described in Appendix A of Kernighan and Ritchie: *The C Programming Language* (Prentice-Hall, 1978, ISBN 0-13-110163-3, copyright ©1978 AT&T).

- ² Portions of the library Clauses of this document are based on work by P.J. Plauger, which was published as *The Draft Standard C++ Library* (Prentice-Hall, ISBN 0-13-117003-1, copyright ©1995 P.J. Plauger).
- ³ POSIX® is a registered trademark of the Institute of Electrical and Electronic Engineers, Inc.
- ⁴ ECMAScript® is a registered trademark of Ecma International.
- ⁵ All rights in these originals are reserved.

5 Lexical conventions [lex]

5.1 Separate translation [lex.separate]

- ¹ The text of the program is kept in units called *source files* in this International Standard. A source file together with all the headers (20.5.1.2) and source files included (19.2) via the preprocessing directive `#include`, less any source lines skipped by any of the conditional inclusion (19.1) preprocessing directives, is called a *translation unit*. [Note: A C++ program need not all be translated at the same time. — end note]
- ² [Note: Previously translated translation units and instantiation units can be preserved individually or in libraries. The separate translation units of a program communicate (6.5) by (for example) calls to functions whose identifiers have external linkage, manipulation of objects whose identifiers have external linkage, or manipulation of data files. Translation units can be separately translated and then later linked to produce an executable program (6.5). — end note]

5.2 Phases of translation [lex.phases]

- ¹ The precedence among the syntax rules of translation is specified by the following phases.¹²
 1. Physical source file characters are mapped, in an implementation-defined manner, to the basic source character set (introducing new-line characters for end-of-line indicators) if necessary. The set of physical source file characters accepted is implementation-defined. Any source file character not in the basic source character set (5.3) is replaced by the *universal-character-name* that designates that character. An implementation may use any internal encoding, so long as an actual extended character encountered in the source file, and the same extended character expressed in the source file as a *universal-character-name* (e.g., using the `\uXXXX` notation), are handled equivalently except where this replacement is reverted (5.4) in a raw string literal.
 2. Each instance of a backslash character (`\`) immediately followed by a new-line character is deleted, splicing physical source lines to form logical source lines. Only the last backslash on any physical source line shall be eligible for being part of such a splice. Except for splices reverted in a raw string literal, if a splice results in a character sequence that matches the syntax of a *universal-character-name*, the behavior is undefined. A source file that is not empty and that does not end in a new-line character, or that ends in a new-line character immediately preceded by a backslash character before any such splicing takes place, shall be processed as if an additional new-line character were appended to the file.
 3. The source file is decomposed into preprocessing tokens (5.4) and sequences of white-space characters (including comments). A source file shall not end in a partial preprocessing token or in a partial comment.¹³ Each comment is replaced by one space character. New-line characters are retained. Whether each nonempty sequence of white-space characters other than new-line is retained or replaced by one space character is unspecified. The process of dividing a source file's characters into preprocessing tokens is context-dependent. [Example: see the handling of `<` within a `#include` preprocessing directive. — end example]
 4. Preprocessing directives are executed, macro invocations are expanded, and `_Pragma` unary operator expressions are executed. If a character sequence that matches the syntax of a *universal-character-name* is produced by token concatenation (19.3.3), the behavior is undefined. A `#include` preprocessing

¹² Implementations must behave as if these separate phases occur, although in practice different phases might be folded together.

¹³ A partial preprocessing token would arise from a source file ending in the first portion of a multi-character token that requires a terminating sequence of characters, such as a *header-name* that is missing the closing `"` or `>`. A partial comment would arise from a source file ending with an unclosed `/*` comment.

directive causes the named header or source file to be processed from phase 1 through phase 4, recursively. All preprocessing directives are then deleted.

5. Each source character set member in a character literal or a string literal, as well as each escape sequence and *universal-character-name* in a character literal or a non-raw string literal, is converted to the corresponding member of the execution character set (5.13.3, 5.13.5); if there is no corresponding member, it is converted to an implementation-defined member other than the null (wide) character.¹⁴
6. Adjacent string literal tokens are concatenated.
7. White-space characters separating tokens are no longer significant. Each preprocessing token is converted into a token (5.6). The resulting tokens are syntactically and semantically analyzed and translated as a translation unit. [*Note*: The process of analyzing and translating the tokens may occasionally result in one token being replaced by a sequence of other tokens (17.2). — *end note*] [*Note*: Source files, translation units and translated translation units need not necessarily be stored as files, nor need there be any one-to-one correspondence between these entities and any external representation. The description is conceptual only, and does not specify any particular implementation. — *end note*]
8. Translated translation units and instantiation units are combined as follows: [*Note*: Some or all of these may be supplied from a library. — *end note*] Each translated translation unit is examined to produce a list of required instantiations. [*Note*: This may include instantiations which have been explicitly requested (17.7.2). — *end note*] The definitions of the required templates are located. It is implementation-defined whether the source of the translation units containing these definitions is required to be available. [*Note*: An implementation could encode sufficient information into the translated translation unit so as to ensure the source is not required here. — *end note*] All the required instantiations are performed to produce *instantiation units*. [*Note*: These are similar to translated translation units, but contain no references to uninstantiated templates and no template definitions. — *end note*] The program is ill-formed if any instantiation fails.
9. All external entity references are resolved. Library components are linked to satisfy external references to entities not defined in the current translation. All such translator output is collected into a program image which contains information needed for execution in its execution environment.

5.3 Character sets

[lex.charset]

- ¹ The *basic source character set* consists of 96 characters: the space character, the control characters representing horizontal tab, vertical tab, form feed, and new-line, plus the following 91 graphical characters:¹⁵

```
a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
_ { } [ ] # ( ) < > % : ; . ? * + - / ^ & | ~ ! = , \ " '

```

- ² The *universal-character-name* construct provides a way to name other characters.

hex-quad:

hexadecimal-digit hexadecimal-digit hexadecimal-digit hexadecimal-digit

universal-character-name:

`\u hex-quad`

`\U hex-quad hex-quad`

The character designated by the *universal-character-name* `\UNNNNNNNN` is that character whose character short name in ISO/IEC 10646 is NNNNNNNN; the character designated by the *universal-character-name* `\uNNNN`

¹⁴ An implementation need not convert all non-corresponding source characters to the same execution character.

¹⁵ The glyphs for the members of the basic source character set are intended to identify characters from the subset of ISO/IEC 10646 which corresponds to the ASCII character set. However, because the mapping from source file characters to the source character set (described in translation phase 1) is specified as implementation-defined, an implementation is required to document how the basic source characters are represented in source files.

is that character whose character short name in ISO/IEC 10646 is 0000NNNN. If the hexadecimal value for a *universal-character-name* corresponds to a surrogate code point (in the range 0xD800–0xDFFF, inclusive), the program is ill-formed. Additionally, if the hexadecimal value for a *universal-character-name* outside the *c-char-sequence*, *s-char-sequence*, or *r-char-sequence* of a character or string literal corresponds to a control character (in either of the ranges 0x00–0x1F or 0x7F–0x9F, both inclusive) or to a character in the basic source character set, the program is ill-formed.¹⁶

- 3 The *basic execution character set* and the *basic execution wide-character set* shall each contain all the members of the basic source character set, plus control characters representing alert, backspace, and carriage return, plus a *null character* (respectively, *null wide character*), whose value is 0. For each basic execution character set, the values of the members shall be non-negative and distinct from one another. In both the source and execution basic character sets, the value of each character after 0 in the above list of decimal digits shall be one greater than the value of the previous. The *execution character set* and the *execution wide-character set* are implementation-defined supersets of the basic execution character set and the basic execution wide-character set, respectively. The values of the members of the execution character sets and the sets of additional members are locale-specific.

5.4 Preprocessing tokens

[lex.pptoken]

preprocessing-token:

header-name

identifier

pp-number

character-literal

user-defined-character-literal

string-literal

user-defined-string-literal

preprocessing-op-or-punc

each non-white-space character that cannot be one of the above

- 1 Each preprocessing token that is converted to a token (5.6) shall have the lexical form of a keyword, an identifier, a literal, an operator, or a punctuation.
- 2 A preprocessing token is the minimal lexical element of the language in translation phases 3 through 6. The categories of preprocessing token are: header names, identifiers, preprocessing numbers, character literals (including user-defined character literals), string literals (including user-defined string literals), preprocessing operators and punctuators, and single non-white-space characters that do not lexically match the other preprocessing token categories. If a ' or a " character matches the last category, the behavior is undefined. Preprocessing tokens can be separated by white space; this consists of comments (5.7), or white-space characters (space, horizontal tab, new-line, vertical tab, and form-feed), or both. As described in Clause 19, in certain circumstances during translation phase 4, white space (or the absence thereof) serves as more than preprocessing token separation. White space can appear within a preprocessing token only as part of a header name or between the quotation characters in a character literal or string literal.
- 3 If the input stream has been parsed into preprocessing tokens up to a given character:
 - (3.1) — If the next character begins a sequence of characters that could be the prefix and initial double quote of a raw string literal, such as R", the next preprocessing token shall be a raw string literal. Between the initial and final double quote characters of the raw string, any transformations performed in phases 1 and 2 (*universal-character-names* and line splicing) are reverted; this reversion shall apply before any *d-char*, *r-char*, or delimiting parenthesis is identified. The raw string literal is defined as the shortest sequence of characters that matches the raw-string pattern

encoding-prefix_{opt} R raw-string

¹⁶ A sequence of characters resembling a *universal-character-name* in an *r-char-sequence* (5.13.5) does not form a *universal-character-name*.

- (3.2) — Otherwise, if the next three characters are <:: and the subsequent character is neither : nor >, the < is treated as a preprocessing token by itself and not as the first character of the alternative token <:.
- (3.3) — Otherwise, the next preprocessing token is the longest sequence of characters that could constitute a preprocessing token, even if that would cause further lexical analysis to fail, except that a *header-name* (5.8) is only formed within a `#include` directive (19.2).

[*Example:*

```
#define R "x"
const char* s = R"y";           // ill-formed raw string, not "x" "y"
```

— *end example*]

- ⁴ [*Example:* The program fragment `0xe+foo` is parsed as a preprocessing number token (one that is not a valid floating or integer literal token), even though a parse as three preprocessing tokens `0xe`, `+`, and `foo` might produce a valid expression (for example, if `foo` were a macro defined as `1`). Similarly, the program fragment `1E1` is parsed as a preprocessing number (one that is a valid floating literal token), whether or not `E` is a macro name. — *end example*]
- ⁵ [*Example:* The program fragment `x+++++y` is parsed as `x ++ ++ + y`, which, if `x` and `y` have integral types, violates a constraint on increment operators, even though the parse `x ++ + ++ y` might yield a correct expression. — *end example*]

5.5 Alternative tokens

[lex.digraph]

- ¹ Alternative token representations are provided for some operators and punctuators.¹⁷
- ² In all respects of the language, each alternative token behaves the same, respectively, as its primary token, except for its spelling.¹⁸ The set of alternative tokens is defined in Table 1.

Table 1 — Alternative tokens

Alternative	Primary	Alternative	Primary	Alternative	Primary
<%	{	and	&&	and_eq	&=
%>	}	bitor		or_eq	=
<:	[	or		xor_eq	^=
:>	]	xor	^	not	!
%:	#	compl	~	not_eq	!=
%::	##	bitand	&		

5.6 Tokens

[lex.token]

token:

identifier
keyword
literal
operator
punctuator

- ¹ There are five kinds of tokens: identifiers, keywords, literals,¹⁹ operators, and other separators. Blanks, horizontal and vertical tabs, newlines, formfeeds, and comments (collectively, “white space”), as described

¹⁷ These include “digraphs” and additional reserved words. The term “digraph” (token consisting of two characters) is not perfectly descriptive, since one of the alternative preprocessing-tokens is `%::` and of course several primary tokens contain two characters. Nonetheless, those alternative tokens that aren’t lexical keywords are colloquially known as “digraphs”.

¹⁸ Thus the “stringized” values (19.3.2) of `[` and `<`: will be different, maintaining the source spelling, but the tokens can otherwise be freely interchanged.

¹⁹ Literals include strings and character and numeric literals.

below, are ignored except as they serve to separate tokens. [*Note*: Some white space is required to separate otherwise adjacent identifiers, keywords, numeric literals, and alternative tokens containing alphabetic characters. — *end note*]

5.7 Comments

[lex.comment]

- ¹ The characters `/*` start a comment, which terminates with the characters `*/`. These comments do not nest. The characters `//` start a comment, which terminates immediately before the next new-line character. If there is a form-feed or a vertical-tab character in such a comment, only white-space characters shall appear between it and the new-line that terminates the comment; no diagnostic is required. [*Note*: The comment characters `//`, `/*`, and `*/` have no special meaning within a `//` comment and are treated just like other characters. Similarly, the comment characters `//` and `/*` have no special meaning within a `/*` comment. — *end note*]

5.8 Header names

[lex.header]

header-name:

< *h-char-sequence* >
" *q-char-sequence* "

h-char-sequence:

h-char
h-char-sequence *h-char*

h-char:

any member of the source character set except new-line and >

q-char-sequence:

q-char
q-char-sequence *q-char*

q-char:

any member of the source character set except new-line and "

- ¹ [*Note*: Header name preprocessing tokens only appear within a `#include` preprocessing directive (see 5.4). — *end note*] The sequences in both forms of *header-names* are mapped in an implementation-defined manner to headers or to external source file names as specified in 19.2.
- ² The appearance of either of the characters `'` or `\` or of either of the character sequences `/*` or `//` in a *q-char-sequence* or an *h-char-sequence* is conditionally-supported with implementation-defined semantics, as is the appearance of the character `"` in an *h-char-sequence*.²⁰

5.9 Preprocessing numbers

[lex.ppnumber]

pp-number:

digit
.
digit
pp-number *digit*
pp-number *identifier-nondigit*
pp-number `'` *digit*
pp-number `'` *nondigit*
pp-number `e` *sign*
pp-number `E` *sign*
pp-number `p` *sign*
pp-number `P` *sign*
pp-number `.`

²⁰) Thus, a sequence of characters that resembles an escape sequence might result in an error, be interpreted as the character corresponding to the escape sequence, or have a completely different meaning, depending on the implementation.

- ¹ Preprocessing number tokens lexically include all integer literal tokens (5.13.2) and all floating literal tokens (5.13.4).
- ² A preprocessing number does not have a type or a value; it acquires both after a successful conversion to an integer literal token or a floating literal token.

5.10 Identifiers

[lex.name]

identifier:

identifier-nondigit

identifier identifier-nondigit

identifier digit

identifier-nondigit:

nondigit

universal-character-name

nondigit: one of

a b c d e f g h i j k l m

n o p q r s t u v w x y z

A B C D E F G H I J K L M

N O P Q R S T U V W X Y Z _

digit: one of

0 1 2 3 4 5 6 7 8 9

- ¹ An identifier is an arbitrarily long sequence of letters and digits. Each *universal-character-name* in an identifier shall designate a character whose encoding in ISO 10646 falls into one of the ranges specified in Table 2. The initial element shall not be a *universal-character-name* designating a character whose encoding falls into one of the ranges specified in Table 3. Upper- and lower-case letters are different. All characters are significant.²¹

Table 2 — Ranges of characters allowed

00A8	00AA	00AD	00AF	00B2-00B5
00B7-00BA	00BC-00BE	00C0-00D6	00D8-00F6	00F8-00FF
0100-167F	1681-180D	180F-1FFF		
200B-200D	202A-202E	203F-2040	2054	2060-206F
2070-218F	2460-24FF	2776-2793	2C00-2DFF	2E80-2FFF
3004-3007	3021-302F	3031-D7FF		
F900-FD3D	FD40-FDCF	FDF0-FE44	FE47-FFFF	
10000-1FFFFD	20000-2FFFFD	30000-3FFFFD	40000-4FFFFD	50000-5FFFFD
60000-6FFFFD	70000-7FFFFD	80000-8FFFFD	90000-9FFFFD	A0000-AFFFFD
B0000-BFFFFD	C0000-CFFFFD	D0000-DFFFFD	E0000-EFFFFD	

Table 3 — Ranges of characters disallowed initially (combining characters)

0300-036F	1DC0-1DFF	20D0-20FF	FE20-FE2F
-----------	-----------	-----------	-----------

²¹) On systems in which linkers cannot accept extended characters, an encoding of the *universal-character-name* may be used in forming valid external identifiers. For example, some otherwise unused character or sequence of characters may be used to encode the \u in a *universal-character-name*. Extended characters may produce a long external identifier, but C++ does not place a translation limit on significant characters for external identifiers. In C++, upper- and lower-case letters are considered different for all identifiers, including external identifiers.

- ² The identifiers in Table 4 have a special meaning when appearing in a certain context. When referred to in the grammar, these identifiers are used explicitly rather than using the *identifier* grammar production. Unless otherwise specified, any ambiguity as to whether a given *identifier* has a special meaning is resolved to interpret the token as a regular *identifier*.

Table 4 — Identifiers with special meaning

override	final
----------	-------

- ³ In addition, some identifiers are reserved for use by C++ implementations and shall not be used otherwise; no diagnostic is required.
- (3.1) — Each identifier that contains a double underscore `__` or begins with an underscore followed by an uppercase letter is reserved to the implementation for any use.
- (3.2) — Each identifier that begins with an underscore is reserved to the implementation for use as a name in the global namespace.

5.11 Keywords

[lex.key]

- ¹ The identifiers shown in Table 5 are reserved for use as keywords (that is, they are unconditionally treated as keywords in phase 7) except in an *attribute-token* (10.6.1):

Table 5 — Keywords

alignas	continue	friend	register	true
alignof	decltype	goto	reinterpret_cast	try
asm	default	if	return	typedef
auto	delete	inline	short	typeid
bool	do	int	signed	typename
break	double	long	sizeof	union
case	dynamic_cast	mutable	static	unsigned
catch	else	namespace	static_assert	using
char	enum	new	static_cast	virtual
char16_t	explicit	noexcept	struct	void
char32_t	export	nullptr	switch	volatile
class	extern	operator	template	wchar_t
const	false	private	this	while
constexpr	float	protected	thread_local	
const_cast	for	public	throw	

[Note: The **export** and **register** keywords are unused but are reserved for future use. — end note]

- ² Furthermore, the alternative representations shown in Table 6 for certain operators and punctuators (5.5) are reserved and shall not be used otherwise:

Table 6 — Alternative representations

and	and_eq	bitand	bitor	compl	not
not_eq	or	or_eq	xor	xor_eq	

5.12 Operators and punctuators [lex.operators]

- ¹ The lexical representation of C++ programs includes a number of preprocessing tokens which are used in the syntax of the preprocessor or are converted into tokens for operators and punctuators:

preprocessing-op-or-punc: one of

{	}	[	]	#	##	(	)	
<:	:>	<%	%>	%:	%::	;	:	...
new	delete	?	::	.	.*			
+	-	*	/	%	^	&		~
!	=	<	>	+=	-=	*=	/=	%=
~=	&=	=	<<	>>	>>=	<<=	==	!=
<=	>=	&&		++	--	,	->*	->
and	and_eq	bitand	bitor	compl	not	not_eq		
or	or_eq	xor	xor_eq					

Each *preprocessing-op-or-punc* is converted to a single token in translation phase 7 (5.2).

5.13 Literals [lex.literal]

5.13.1 Kinds of literals [lex.literal.kinds]

- ¹ There are several kinds of literals.²²

literal:

- integer-literal*
- character-literal*
- floating-literal*
- string-literal*
- boolean-literal*
- pointer-literal*
- user-defined-literal*

5.13.2 Integer literals [lex.icon]

integer-literal:

- binary-literal integer-suffix_{opt}*
- octal-literal integer-suffix_{opt}*
- decimal-literal integer-suffix_{opt}*
- hexadecimal-literal integer-suffix_{opt}*

binary-literal:

- 0b** *binary-digit*
- 0B** *binary-digit*
- binary-literal* ' _{opt} *binary-digit*

octal-literal:

- 0**
- octal-literal* ' _{opt} *octal-digit*

decimal-literal:

- nonzero-digit*
- decimal-literal* ' _{opt} *digit*

hexadecimal-literal:

- hexadecimal-prefix hexadecimal-digit-sequence*

binary-digit:

- 0**
- 1**

²²) The term “literal” generally designates, in this International Standard, those tokens that are called “constants” in ISO C.

octal-digit: one of
0 1 2 3 4 5 6 7

nonzero-digit: one of
1 2 3 4 5 6 7 8 9

hexadecimal-prefix: one of
0x 0X

hexadecimal-digit-sequence:
hexadecimal-digit
hexadecimal-digit-sequence ' _{opt} hexadecimal-digit

hexadecimal-digit: one of
0 1 2 3 4 5 6 7 8 9
a b c d e f
A B C D E F

integer-suffix:
unsigned-suffix long-suffix_{opt}
unsigned-suffix long-long-suffix_{opt}
long-suffix unsigned-suffix_{opt}
long-long-suffix unsigned-suffix_{opt}

unsigned-suffix: one of
u U

long-suffix: one of
l L

long-long-suffix: one of
ll LL

- ¹ An *integer literal* is a sequence of digits that has no period or exponent part, with optional separating single quotes that are ignored when determining its value. An integer literal may have a prefix that specifies its base and a suffix that specifies its type. The lexically first digit of the sequence of digits is the most significant. A *binary integer literal* (base two) begins with 0b or 0B and consists of a sequence of binary digits. An *octal integer literal* (base eight) begins with the digit 0 and consists of a sequence of octal digits.²³ A *decimal integer literal* (base ten) begins with a digit other than 0 and consists of a sequence of decimal digits. A *hexadecimal integer literal* (base sixteen) begins with 0x or 0X and consists of a sequence of hexadecimal digits, which include the decimal digits and the letters a through f and A through F with decimal values ten through fifteen. [Example: The number twelve can be written 12, 014, 0XC, or 0b1100. The integer literals 1048576, 1'048'576, 0X100000, 0x10'0000, and 0'004'000'000 all have the same value. — end example]
- ² The type of an integer literal is the first of the corresponding list in Table 7 in which its value can be represented.

Table 7 — Types of integer literals

Suffix	Decimal literal	Binary, octal, or hexadecimal literal
none	int long int long long int	int unsigned int long int unsigned long int long long int unsigned long long int
u or U	unsigned int unsigned long int	unsigned int unsigned long int

²³) The digits 8 and 9 are not octal digits.

Table 7 — Types of integer literals (continued)

Suffix	Decimal literal	Binary, octal, or hexadecimal literal
	unsigned long long int	unsigned long long int
l or L	long int long long int	long int unsigned long int long long int unsigned long long int
Both u or U and l or L	unsigned long int unsigned long long int	unsigned long int unsigned long long int
ll or LL	long long int	long long int unsigned long long int
Both u or U and ll or LL	unsigned long long int	unsigned long long int

- ³ If an integer literal cannot be represented by any type in its list and an extended integer type (6.9.1) can represent its value, it may have that extended integer type. If all of the types in the list for the integer literal are signed, the extended integer type shall be signed. If all of the types in the list for the integer literal are unsigned, the extended integer type shall be unsigned. If the list contains both signed and unsigned types, the extended integer type may be signed or unsigned. A program is ill-formed if one of its translation units contains an integer literal that cannot be represented by any of the allowed types.

5.13.3 Character literals

[lex.ccon]

character-literal:

*encoding-prefix*_{opt} ' *c-char-sequence* '

encoding-prefix: one of

u8 u U L

c-char-sequence:

c-char

c-char-sequence *c-char*

c-char:

any member of the source character set except
the single-quote ' , backslash \ , or new-line character

escape-sequence

universal-character-name

escape-sequence:

simple-escape-sequence

octal-escape-sequence

hexadecimal-escape-sequence

simple-escape-sequence: one of

\ ' \ " \ ? \ \

\ a \ b \ f \ n \ r \ t \ v

octal-escape-sequence:

\ *octal-digit*

\ *octal-digit* *octal-digit*

\ *octal-digit* *octal-digit* *octal-digit*

hexadecimal-escape-sequence:

\ x *hexadecimal-digit*

hexadecimal-escape-sequence *hexadecimal-digit*

- ¹ A character literal is one or more characters enclosed in single quotes, as in `'x'`, optionally preceded by `u8`, `u`, `U`, or `L`, as in `u8'w'`, `u'x'`, `U'y'`, or `L'z'`, respectively.
- ² A character literal that does not begin with `u8`, `u`, `U`, or `L` is an *ordinary character literal*. An ordinary character literal that contains a single *c-char* representable in the execution character set has type `char`, with value equal to the numerical value of the encoding of the *c-char* in the execution character set. An ordinary character literal that contains more than one *c-char* is a *multicharacter literal*. A multicharacter literal, or an ordinary character literal containing a single *c-char* not representable in the execution character set, is conditionally-supported, has type `int`, and has an implementation-defined value.
- ³ A character literal that begins with `u8`, such as `u8'w'`, is a character literal of type `char`, known as a *UTF-8 character literal*. The value of a UTF-8 character literal is equal to its ISO 10646 code point value, provided that the code point value is representable with a single UTF-8 code unit (that is, provided it is in the C0 Controls and Basic Latin Unicode block). If the value is not representable with a single UTF-8 code unit, the program is ill-formed. A UTF-8 character literal containing multiple *c-chars* is ill-formed.
- ⁴ A character literal that begins with the letter `u`, such as `u'x'`, is a character literal of type `char16_t`. The value of a `char16_t` character literal containing a single *c-char* is equal to its ISO 10646 code point value, provided that the code point is representable with a single 16-bit code unit. (That is, provided it is a basic multi-lingual plane code point.) If the value is not representable within 16 bits, the program is ill-formed. A `char16_t` character literal containing multiple *c-chars* is ill-formed.
- ⁵ A character literal that begins with the letter `U`, such as `U'y'`, is a character literal of type `char32_t`. The value of a `char32_t` character literal containing a single *c-char* is equal to its ISO 10646 code point value. A `char32_t` character literal containing multiple *c-chars* is ill-formed.
- ⁶ A character literal that begins with the letter `L`, such as `L'z'`, is a *wide-character literal*. A wide-character literal has type `wchar_t`.²⁴ The value of a wide-character literal containing a single *c-char* has value equal to the numerical value of the encoding of the *c-char* in the execution wide-character set, unless the *c-char* has no representation in the execution wide-character set, in which case the value is implementation-defined. [Note: The type `wchar_t` is able to represent all members of the execution wide-character set (see 6.9.1). — end note] The value of a wide-character literal containing multiple *c-chars* is implementation-defined.
- ⁷ Certain non-graphic characters, the single quote `'`, the double quote `"`, the question mark `?`,²⁵ and the backslash `\`, can be represented according to Table 8. The double quote `"` and the question mark `?`, can be represented as themselves or by the escape sequences `\"` and `\?` respectively, but the single quote `'` and the backslash `\` shall be represented by the escape sequences `\'` and `\\` respectively. Escape sequences in which the character following the backslash is not listed in Table 8 are conditionally-supported, with implementation-defined semantics. An escape sequence specifies a single character.
- ⁸ The escape `\ooo` consists of the backslash followed by one, two, or three octal digits that are taken to specify the value of the desired character. The escape `\xhhh` consists of the backslash followed by `x` followed by one or more hexadecimal digits that are taken to specify the value of the desired character. There is no limit to the number of digits in a hexadecimal sequence. A sequence of octal or hexadecimal digits is terminated by the first character that is not an octal digit or a hexadecimal digit, respectively. The value of a character literal is implementation-defined if it falls outside of the implementation-defined range defined for `char` (for character literals with no prefix) or `wchar_t` (for character literals prefixed by `L`). [Note: If the value of a character literal prefixed by `u`, `u8`, or `U` is outside the range defined for its type, the program is ill-formed. — end note]
- ⁹ A *universal-character-name* is translated to the encoding, in the appropriate execution character set, of the character named. If there is no such encoding, the *universal-character-name* is translated to an implementation-defined encoding. [Note: In translation phase 1, a *universal-character-name* is introduced whenever an actual

²⁴) They are intended for character sets where a character does not fit into a single byte.

²⁵) Using an escape sequence for a question mark is supported for compatibility with ISO C++ 2014 and ISO C.

Table 8 — Escape sequences

new-line	NL(LF)	<code>\n</code>
horizontal tab	HT	<code>\t</code>
vertical tab	VT	<code>\v</code>
backspace	BS	<code>\b</code>
carriage return	CR	<code>\r</code>
form feed	FF	<code>\f</code>
alert	BEL	<code>\a</code>
backslash	<code>\</code>	<code>\\</code>
question mark	<code>?</code>	<code>\?</code>
single quote	<code>'</code>	<code>\'</code>
double quote	<code>"</code>	<code>\"</code>
octal number	<i>ooo</i>	<code>\ooo</code>
hex number	<i>hhh</i>	<code>\xhhh</code>

extended character is encountered in the source text. Therefore, all extended characters are described in terms of *universal-character-names*. However, the actual compiler implementation may use its own native character set, so long as the same results are obtained. — *end note*]

5.13.4 Floating literals

[lex.fcon]

floating-literal:

decimal-floating-literal

hexadecimal-floating-literal

decimal-floating-literal:

fractional-constant *exponent-part*_{opt} *floating-suffix*_{opt}

digit-sequence *exponent-part* *floating-suffix*_{opt}

hexadecimal-floating-literal:

hexadecimal-prefix *hexadecimal-fractional-constant* *binary-exponent-part* *floating-suffix*_{opt}

hexadecimal-prefix *hexadecimal-digit-sequence* *binary-exponent-part* *floating-suffix*_{opt}

fractional-constant:

*digit-sequence*_{opt} . *digit-sequence*

digit-sequence .

hexadecimal-fractional-constant:

*hexadecimal-digit-sequence*_{opt} . *hexadecimal-digit-sequence*

hexadecimal-digit-sequence .

exponent-part:

e *sign*_{opt} *digit-sequence*

E *sign*_{opt} *digit-sequence*

binary-exponent-part:

p *sign*_{opt} *digit-sequence*

P *sign*_{opt} *digit-sequence*

sign: one of

+ **-**

digit-sequence:

digit

digit-sequence ' *opt* *digit*

floating-suffix: one of
f l F L

- ¹ A floating literal consists of an optional prefix specifying a base, an integer part, a radix point, a fraction part, an **e**, **E**, **p** or **P**, an optionally signed integer exponent, and an optional type suffix. The integer and fraction parts both consist of a sequence of decimal (base ten) digits if there is no prefix, or hexadecimal (base sixteen) digits if the prefix is **0x** or **0X**. The floating literal is a *decimal floating literal* in the former case and a *hexadecimal floating literal* in the latter case. Optional separating single quotes in a *digit-sequence* or *hexadecimal-digit-sequence* are ignored when determining its value. [*Example*: The floating literals 1.602'176'565e-19 and 1.602176565e-19 have the same value. — *end example*] Either the integer part or the fraction part (not both) can be omitted. Either the radix point or the letter **e** or **E** and the exponent (not both) can be omitted from a decimal floating literal. The radix point (but not the exponent) can be omitted from a hexadecimal floating literal. The integer part, the optional radix point, and the optional fraction part, form the *significand* of the floating literal. In a decimal floating literal, the exponent, if present, indicates the power of 10 by which the significand is to be scaled. In a hexadecimal floating literal, the exponent indicates the power of 2 by which the significand is to be scaled. [*Example*: The floating literals 49.625 and 0xC.68p+2 have the same value. — *end example*] If the scaled value is in the range of representable values for its type, the result is the scaled value if representable, else the larger or smaller representable value nearest the scaled value, chosen in an implementation-defined manner. The type of a floating literal is **double** unless explicitly specified by a suffix. The suffixes **f** and **F** specify **float**, the suffixes **l** and **L** specify **long double**. If the scaled value is not in the range of representable values for its type, the program is ill-formed.

5.13.5 String literals

[lex.string]

string-literal:

*encoding-prefix*_{opt} " *s-char-sequence*_{opt} "
*encoding-prefix*_{opt} R *raw-string*

s-char-sequence:

s-char
s-char-sequence *s-char*

s-char:

any member of the source character set except
the double-quote ", backslash \, or new-line character
escape-sequence
universal-character-name

raw-string:

" *d-char-sequence*_{opt} (*r-char-sequence*_{opt}) *d-char-sequence*_{opt} "

r-char-sequence:

r-char
r-char-sequence *r-char*

r-char:

any member of the source character set, except
a right parenthesis) followed by the initial *d-char-sequence*
(which may be empty) followed by a double quote ".

d-char-sequence:

d-char
d-char-sequence *d-char*

d-char:

any member of the basic source character set except:
space, the left parenthesis (, the right parenthesis), the backslash \,
and the control characters representing horizontal tab,
vertical tab, form feed, and newline.

- ¹ A *string-literal* is a sequence of characters (as defined in 5.13.3) surrounded by double quotes, optionally prefixed by `R`, `u8`, `u8R`, `u`, `uR`, `U`, `UR`, `L`, or `LR`, as in "...", `R"(...)"`, `u8"..."`, `u8R"**(...)**"`, `u"..."`, `uR"*~(...)*~"`, `U"..."`, `UR"zzz(...)zzz"`, `L"..."`, or `LR"(...)"`, respectively.
- ² A *string-literal* that has an `R` in the prefix is a *raw string literal*. The *d-char-sequence* serves as a delimiter. The terminating *d-char-sequence* of a *raw-string* is the same sequence of characters as the initial *d-char-sequence*. A *d-char-sequence* shall consist of at most 16 characters.
- ³ [Note: The characters ' (and ') ' are permitted in a *raw-string*. Thus, `R"delimiter((a|b))delimiter"` is equivalent to `"(a|b)"`. — end note]
- ⁴ [Note: A source-file new-line in a raw string literal results in a new-line in the resulting execution string literal. Assuming no whitespace at the beginning of lines in the following example, the assert will succeed:
- ```
const char* p = R"(a\
b
c)";
assert(std::strcmp(p, "a\\nb\\nc") == 0);
```
- end note]
- <sup>5</sup> [Example: The raw string
- ```
R"a(
)\
a"
)a"
```
- is equivalent to `"\n)\\na\"n"`. The raw string
- ```
R"(??)"
```
- is equivalent to `"\?\?"`. The raw string
- ```
R"#(
)??="
)#"
```
- is equivalent to `"\n)\?\?=\"n"`. — end example]
- ⁶ After translation phase 6, a *string-literal* that does not begin with an *encoding-prefix* is an *ordinary string literal*, and is initialized with the given characters.
- ⁷ A *string-literal* that begins with `u8`, such as `u8"asdf"`, is a *UTF-8 string literal*.
- ⁸ Ordinary string literals and UTF-8 string literals are also referred to as narrow string literals. A narrow string literal has type “array of *n* `const char`”, where *n* is the size of the string as defined below, and has static storage duration (6.7).
- ⁹ For a UTF-8 string literal, each successive element of the object representation (6.9) has the value of the corresponding code unit of the UTF-8 encoding of the string.
- ¹⁰ A *string-literal* that begins with `u`, such as `u"asdf"`, is a `char16_t` string literal. A `char16_t` string literal has type “array of *n* `const char16_t`”, where *n* is the size of the string as defined below; it is initialized with the given characters. A single *c-char* may produce more than one `char16_t` character in the form of surrogate pairs.
- ¹¹ A *string-literal* that begins with `U`, such as `U"asdf"`, is a `char32_t` string literal. A `char32_t` string literal has type “array of *n* `const char32_t`”, where *n* is the size of the string as defined below; it is initialized with the given characters.
- ¹² A *string-literal* that begins with `L`, such as `L"asdf"`, is a *wide string literal*. A wide string literal has type “array of *n* `const wchar_t`”, where *n* is the size of the string as defined below; it is initialized with the given characters.

- ¹³ In translation phase 6 (5.2), adjacent *string-literals* are concatenated. If both *string-literals* have the same *encoding-prefix*, the resulting concatenated string literal has that *encoding-prefix*. If one *string-literal* has no *encoding-prefix*, it is treated as a *string-literal* of the same *encoding-prefix* as the other operand. If a UTF-8 string literal token is adjacent to a wide string literal token, the program is ill-formed. Any other concatenations are conditionally-supported with implementation-defined behavior. [*Note*: This concatenation is an interpretation, not a conversion. Because the interpretation happens in translation phase 6 (after each character from a string literal has been translated into a value from the appropriate character set), a *string-literal*'s initial rawness has no effect on the interpretation or well-formedness of the concatenation. — *end note*] Table 9 has some examples of valid concatenations.

Table 9 — String literal concatenations

Source			Means			Source			Means			Source			Means		
u"a"	u"b"	u"ab"	U"a"	U"b"	U"ab"	L"a"	L"b"	L"ab"	U"a"	U"b"	U"ab"	L"a"	L"b"	L"ab"	U"a"	U"b"	U"ab"
u"a"	"b"	u"ab"	U"a"	"b"	U"ab"	L"a"	"b"	L"ab"	U"a"	"b"	U"ab"	L"a"	"b"	L"ab"	U"a"	"b"	U"ab"
"a"	u"b"	u"ab"	"a"	U"b"	U"ab"	"a"	L"b"	L"ab"	"a"	U"b"	U"ab"	"a"	L"b"	L"ab"	"a"	U"b"	U"ab"

Characters in concatenated strings are kept distinct.

[*Example*:

```
"\xA" "B"
```

contains the two characters 'xA' and 'B' after concatenation (and not the single hexadecimal character 'xAB'). — *end example*]

- ¹⁴ After any necessary concatenation, in translation phase 7 (5.2), '\0' is appended to every string literal so that programs that scan a string can find its end.
- ¹⁵ Escape sequences and *universal-character-names* in non-raw string literals have the same meaning as in character literals (5.13.3), except that the single quote ' is representable either by itself or by the escape sequence '\'', and the double quote " shall be preceded by a \, and except that a *universal-character-name* in a `char16_t` string literal may yield a surrogate pair. In a narrow string literal, a *universal-character-name* may map to more than one `char` element due to *multibyte encoding*. The size of a `char32_t` or wide string literal is the total number of escape sequences, *universal-character-names*, and other characters, plus one for the terminating U'\0' or L'\0'. The size of a `char16_t` string literal is the total number of escape sequences, *universal-character-names*, and other characters, plus one for each character requiring a surrogate pair, plus one for the terminating u'\0'. [*Note*: The size of a `char16_t` string literal is the number of code units, not the number of characters. — *end note*] Within `char32_t` and `char16_t` string literals, any *universal-character-names* shall be within the range 0x0 to 0x10FFFF. The size of a narrow string literal is the total number of escape sequences and other characters, plus at least one for the multibyte encoding of each *universal-character-name*, plus one for the terminating '\0'.
- ¹⁶ Evaluating a *string-literal* results in a string literal object with static storage duration, initialized from the given characters as specified above. Whether all string literals are distinct (that is, are stored in nonoverlapping objects) and whether successive evaluations of a *string-literal* yield the same or a different object is unspecified. [*Note*: The effect of attempting to modify a string literal is undefined. — *end note*]

5.13.6 Boolean literals

[lex.bool]

boolean-literal:

false

true

- ¹ The Boolean literals are the keywords `false` and `true`. Such literals are prvalues and have type `bool`.

5.13.7 Pointer literals

[lex.nullptr]

*pointer-literal:***nullptr**

- ¹ The pointer literal is the keyword **nullptr**. It is a prvalue of type **std::nullptr_t**. [Note: **std::nullptr_t** is a distinct type that is neither a pointer type nor a pointer to member type; rather, a prvalue of this type is a null pointer constant and can be converted to a null pointer value or null member pointer value. See 7.11 and 7.12. — end note]

5.13.8 User-defined literals

[lex.ext]

*user-defined-literal:**user-defined-integer-literal**user-defined-floating-literal**user-defined-string-literal**user-defined-character-literal**user-defined-integer-literal:**decimal-literal ud-suffix**octal-literal ud-suffix**hexadecimal-literal ud-suffix**binary-literal ud-suffix**user-defined-floating-literal:**fractional-constant exponent-part_{opt} ud-suffix**digit-sequence exponent-part ud-suffix**hexadecimal-prefix hexadecimal-fractional-constant binary-exponent-part ud-suffix**hexadecimal-prefix hexadecimal-digit-sequence binary-exponent-part ud-suffix**user-defined-string-literal:**string-literal ud-suffix**user-defined-character-literal:**character-literal ud-suffix**ud-suffix:**identifier*

- ¹ If a token matches both *user-defined-literal* and another *literal* kind, it is treated as the latter. [Example: **123_km** is a *user-defined-literal*, but **12LL** is an *integer-literal*. — end example] The syntactic non-terminal preceding the *ud-suffix* in a *user-defined-literal* is taken to be the longest sequence of characters that could match that non-terminal.
- ² A *user-defined-literal* is treated as a call to a literal operator or literal operator template (16.5.8). To determine the form of this call for a given *user-defined-literal* *L* with *ud-suffix* *X*, the *literal-operator-id* whose literal suffix identifier is *X* is looked up in the context of *L* using the rules for unqualified name lookup (6.4.1). Let *S* be the set of declarations found by this lookup. *S* shall not be empty.
- ³ If *L* is a *user-defined-integer-literal*, let *n* be the literal without its *ud-suffix*. If *S* contains a literal operator with parameter type **unsigned long long**, the literal *L* is treated as a call of the form

operator "" X(n ULL)

Otherwise, *S* shall contain a raw literal operator or a literal operator template (16.5.8) but not both. If *S* contains a raw literal operator, the literal *L* is treated as a call of the form

operator "" X("n")

Otherwise (*S* contains a literal operator template), *L* is treated as a call of the form

operator "" X(<'c₁', 'c₂', ... 'c_k'>())

where n is the source character sequence $c_1c_2\dots c_k$. [Note: The sequence $c_1c_2\dots c_k$ can only contain characters from the basic source character set. — end note]

- ⁴ If L is a *user-defined-floating-literal*, let f be the literal without its *ud-suffix*. If S contains a literal operator with parameter type `long double`, the literal L is treated as a call of the form

```
operator "" X(fL)
```

Otherwise, S shall contain a raw literal operator or a literal operator template (16.5.8) but not both. If S contains a raw literal operator, the *literal* L is treated as a call of the form

```
operator "" X("f")
```

Otherwise (S contains a literal operator template), L is treated as a call of the form

```
operator "" X('< c1 ', ' c2 ', ... ' ck '>())
```

where f is the source character sequence $c_1c_2\dots c_k$. [Note: The sequence $c_1c_2\dots c_k$ can only contain characters from the basic source character set. — end note]

- ⁵ If L is a *user-defined-string-literal*, let str be the literal without its *ud-suffix* and let len be the number of code units in str (i.e., its length excluding the terminating null character). The literal L is treated as a call of the form

```
operator "" X(str, len)
```

- ⁶ If L is a *user-defined-character-literal*, let ch be the literal without its *ud-suffix*. S shall contain a literal operator (16.5.8) whose only parameter has the type of ch and the literal L is treated as a call of the form

```
operator "" X(ch)
```

- ⁷ [Example:

```
long double operator "" _w(long double);
std::string operator "" _w(const char16_t*, std::size_t);
unsigned operator "" _w(const char*);
int main() {
    1.2_w;      // calls operator "" _w(1.2L)
    u"one"_w;   // calls operator "" _w(u"one", 3)
    12_w;       // calls operator "" _w("12")
    "two"_w;    // error: no applicable literal operator
}
```

— end example]

- ⁸ In translation phase 6 (5.2), adjacent string literals are concatenated and *user-defined-string-literals* are considered string literals for that purpose. During concatenation, *ud-suffixes* are removed and ignored and the concatenation process occurs as described in 5.13.5. At the end of phase 6, if a string literal is the result of a concatenation involving at least one *user-defined-string-literal*, all the participating *user-defined-string-literals* shall have the same *ud-suffix* and that suffix is applied to the result of the concatenation.

- ⁹ [Example:

```
int main() {
    L"A" "B" "C"_x; // OK: same as L"ABC"_x
    "P"_x "Q" "R"_y; // error: two different ud-suffixes
}
```

— end example]

6 Basic concepts

[basic]

- ¹ [*Note*: This Clause presents the basic concepts of the C++ language. It explains the difference between an object and a name and how they relate to the value categories for expressions. It introduces the concepts of a declaration and a definition and presents C++'s notion of type, scope, linkage, and storage duration. The mechanisms for starting and terminating a program are discussed. Finally, this Clause presents the fundamental types of the language and lists the ways of constructing compound types from these. — *end note*]
- ² [*Note*: This Clause does not cover concepts that affect only a single part of the language. Such concepts are discussed in the relevant Clauses. — *end note*]
- ³ An *entity* is a value, object, reference, function, enumerator, type, class member, bit-field, template, template specialization, namespace, or parameter pack.
- ⁴ A *name* is a use of an *identifier* (5.10), *operator-function-id* (16.5), *literal-operator-id* (16.5.8), *conversion-function-id* (15.3.2), or *template-id* (17.2) that denotes an entity or label (9.6.4, 9.1).
- ⁵ Every name that denotes an entity is introduced by a *declaration*. Every name that denotes a label is introduced either by a *goto* statement (9.6.4) or a *labeled-statement* (9.1).
- ⁶ A *variable* is introduced by the declaration of a reference other than a non-static data member or of an object. The variable's name, if any, denotes the reference or object.
- ⁷ Some names denote types or templates. In general, whenever a name is encountered it is necessary to determine whether that name denotes one of these entities before continuing to parse the program that contains it. The process that determines this is called *name lookup* (6.4).
- ⁸ Two names are *the same* if
 - (8.1) — they are *identifiers* composed of the same character sequence, or
 - (8.2) — they are *operator-function-ids* formed with the same operator, or
 - (8.3) — they are *conversion-function-ids* formed with the same type, or
 - (8.4) — they are *template-ids* that refer to the same class, function, or variable (17.4), or
 - (8.5) — they are the names of literal operators (16.5.8) formed with the same literal suffix identifier.
- ⁹ A name used in more than one translation unit can potentially refer to the same entity in these translation units depending on the linkage (6.5) of the name specified in each translation unit.

6.1 Declarations and definitions

[basic.def]

- ¹ A declaration (Clause 10) may introduce one or more names into a translation unit or redeclare names introduced by previous declarations. If so, the declaration specifies the interpretation and attributes of these names. A declaration may also have effects including:
 - (1.1) — a static assertion (Clause 10),
 - (1.2) — controlling template instantiation (17.7.2),
 - (1.3) — guiding template argument deduction for constructors (17.9),
 - (1.4) — use of attributes (Clause 10), and
 - (1.5) — nothing (in the case of an *empty-declaration*).
- ² A declaration is a *definition* unless

- (2.1) — it declares a function without specifying the function's body (11.4),
- (2.2) — it contains the **extern** specifier (10.1.1) or a *linkage-specification*²⁶ (10.5) and neither an *initializer* nor a *function-body*,
- (2.3) — it declares a non-inline static data member in a class definition (12.2, 12.2.3),
- (2.4) — it declares a static data member outside a class definition and the variable was defined within the class with the **constexpr** specifier (this usage is deprecated; see D.1),
- (2.5) — it is a class name declaration (12.1),
- (2.6) — it is an *opaque-enum-declaration* (10.2),
- (2.7) — it is a *template-parameter* (17.1),
- (2.8) — it is a *parameter-declaration* (11.3.5) in a function declarator that is not the *declarator* of a *function-definition*,
- (2.9) — it is a **typedef** declaration (10.1.3),
- (2.10) — it is an *alias-declaration* (10.1.3),
- (2.11) — it is a *using-declaration* (10.3.3),
- (2.12) — it is a *deduction-guide* (17.9),
- (2.13) — it is a *static_assert-declaration* (Clause 10),
- (2.14) — it is an *attribute-declaration* (Clause 10),
- (2.15) — it is an *empty-declaration* (Clause 10),
- (2.16) — it is a *using-directive* (10.3.4),
- (2.17) — it is an explicit instantiation declaration (17.7.2), or
- (2.18) — it is an explicit specialization (17.7.3) whose *declaration* is not a definition.

[*Example:* All but one of the following are definitions:

```

int a;                // defines a
extern const int c = 1; // defines c
int f(int x) { return x+a; } // defines f and defines x
struct S { int a; int b; }; // defines S, S::a, and S::b
struct X {            // defines X
    int x;            // defines non-static data member x
    static int y;      // declares static data member y
    X(): x(0) { }      // defines a constructor of X
};
int X::y = 1;         // defines X::y
enum { up, down };    // defines up and down
namespace N { int d; } // defines N and N::d
namespace N1 = N;     // defines N1
X anX;                // defines anX

```

whereas these are just declarations:

```

extern int a;          // declares a
extern const int c;    // declares c
int f(int);            // declares f
struct S;              // declares S
typedef int Int;        // declares Int

```

²⁶) Appearing inside the braced-enclosed *declaration-seq* in a *linkage-specification* does not affect whether a declaration is a definition.

```
extern X anotherX;           // declares anotherX
using N::d;                  // declares d
```

— end example]

- ³ [Note: In some circumstances, C++ implementations implicitly define the default constructor (15.1), copy constructor (15.8), move constructor (15.8), copy assignment operator (15.8), move assignment operator (15.8), or destructor (15.4) member functions. — end note] [Example: Given

```
#include <string>

struct C {
    std::string s;           // std::string is the standard library class (Clause 24)
};

int main() {
    C a;
    C b = a;
    b = a;
}
```

the implementation will implicitly define functions to make the definition of C equivalent to

```
struct C {
    std::string s;
    C() : s() { }
    C(const C& x): s(x.s) { }
    C(C&& x): s(static_cast<std::string&&>(x.s)) { }
    // : s(std::move(x.s)) { }
    C& operator=(const C& x) { s = x.s; return *this; }
    C& operator=(C&& x) { s = static_cast<std::string&&>(x.s); return *this; }
    // { s = std::move(x.s); return *this; }
    ~C() { }
};
```

— end example]

- ⁴ [Note: A class name can also be implicitly declared by an *elaborated-type-specifier* (10.1.7.3). — end note]
- ⁵ A program is ill-formed if the definition of any object gives the object an incomplete type (6.9).

6.2 One-definition rule

[basic.def.odr]

- ¹ No translation unit shall contain more than one definition of any variable, function, class type, enumeration type, or template.
- ² An expression is *potentially evaluated* unless it is an unevaluated operand (Clause 8) or a subexpression thereof. The set of *potential results* of an expression *e* is defined as follows:
- (2.1) — If *e* is an *id-expression* (8.1.4), the set contains only *e*.
 - (2.2) — If *e* is a subscripting operation (8.2.1) with an array operand, the set contains the potential results of that operand.
 - (2.3) — If *e* is a class member access expression (8.2.5), the set contains the potential results of the object expression.
 - (2.4) — If *e* is a pointer-to-member expression (8.5) whose second operand is a constant expression, the set contains the potential results of the object expression.
 - (2.5) — If *e* has the form (*e*1), the set contains the potential results of *e*1.
 - (2.6) — If *e* is a glvalue conditional expression (8.16), the set is the union of the sets of potential results of the

second and third operands.

- (2.7) — If **e** is a comma expression (8.19), the set contains the potential results of the right operand.
- (2.8) — Otherwise, the set is empty.

[*Note:* This set is a (possibly-empty) set of *id-expressions*, each of which is either **e** or a subexpression of **e**.
 [*Example:* In the following example, the set of potential results of the initializer of **n** contains the first **S::x** subexpression, but not the second **S::x** subexpression.

```
struct S { static const int x = 0; };
const int &f(const int &r);
int n = b ? (1, S::x) // S::x is not odr-used here
           : f(S::x); // S::x is odr-used here, so a definition is required
```

— end example] — end note]

- ³ A variable **x** whose name appears as a potentially-evaluated expression **ex** is *odr-used* by **ex** unless applying the lvalue-to-rvalue conversion (7.1) to **x** yields a constant expression (8.20) that does not invoke any non-trivial functions and, if **x** is an object, **ex** is an element of the set of potential results of an expression **e**, where either the lvalue-to-rvalue conversion (7.1) is applied to **e**, or **e** is a discarded-value expression (Clause 8). **this** is odr-used if it appears as a potentially-evaluated expression (including as the result of the implicit transformation in the body of a non-static member function (12.2.2)). A virtual member function is odr-used if it is not pure. A function whose name appears as a potentially-evaluated expression is odr-used if it is the unique lookup result or the selected member of a set of overloaded functions (6.4, 16.3, 16.4), unless it is a pure virtual function and either its name is not explicitly qualified or the expression forms a pointer to member (8.3.1). [*Note:* This covers calls to named functions (8.2.2), operator overloading (Clause 16), user-defined conversions (15.3.2), allocation functions for placement *new-expressions* (8.3.4), as well as non-default initialization (11.6). A constructor selected to copy or move an object of class type is odr-used even if the call is actually elided by the implementation (15.8). — end note] An allocation or deallocation function for a class is odr-used by a *new-expression* appearing in a potentially-evaluated expression as specified in 8.3.4 and 15.5. A deallocation function for a class is odr-used by a delete expression appearing in a potentially-evaluated expression as specified in 8.3.5 and 15.5. A non-placement allocation or deallocation function for a class is odr-used by the definition of a constructor of that class. A non-placement deallocation function for a class is odr-used by the definition of the destructor of that class, or by being selected by the lookup at the point of definition of a virtual destructor (15.4).²⁷ An assignment operator function in a class is odr-used by an implicitly-defined copy-assignment or move-assignment function for another class as specified in 15.8. A constructor for a class is odr-used as specified in 11.6. A destructor for a class is odr-used if it is potentially invoked (15.4).
- ⁴ Every program shall contain exactly one definition of every non-inline function or variable that is odr-used in that program outside of a discarded statement (9.4.1); no diagnostic required. The definition can appear explicitly in the program, it can be found in the standard or a user-defined library, or (when appropriate) it is implicitly defined (see 15.1, 15.4 and 15.8). An inline function or variable shall be defined in every translation unit in which it is odr-used outside of a discarded statement.
- ⁵ Exactly one definition of a class is required in a translation unit if the class is used in a way that requires the class type to be complete. [*Example:* The following complete translation unit is well-formed, even though it never defines **X**:

```
struct X; // declare X as a struct type
struct X* x1; // use X in pointer formation
X* x2; // use X in pointer formation
```

— end example] [*Note:* The rules for declarations and expressions describe in which contexts complete class

²⁷) An implementation is not required to call allocation and deallocation functions from constructors or destructors; however, this is a permissible implementation technique.

types are required. A class type T must be complete if:

- (5.1) — an object of type T is defined (6.1), or
- (5.2) — a non-static class data member of type T is declared (12.2), or
- (5.3) — T is used as the allocated type or array element type in a *new-expression* (8.3.4), or
- (5.4) — an lvalue-to-rvalue conversion is applied to a glvalue referring to an object of type T (7.1), or
- (5.5) — an expression is converted (either implicitly or explicitly) to type T (Clause 7, 8.2.3, 8.2.7, 8.2.9, 8.4), or
- (5.6) — an expression that is not a null pointer constant, and has type other than *cv void**, is converted to the type pointer to T or reference to T using a standard conversion (Clause 7), a `dynamic_cast` (8.2.7) or a `static_cast` (8.2.9), or
- (5.7) — a class member access operator is applied to an expression of type T (8.2.5), or
- (5.8) — the `typeid` operator (8.2.8) or the `sizeof` operator (8.3.3) is applied to an operand of type T, or
- (5.9) — a function with a return type or argument type of type T is defined (6.1) or called (8.2.2), or
- (5.10) — a class with a base class of type T is defined (Clause 13), or
- (5.11) — an lvalue of type T is assigned to (8.18), or
- (5.12) — the type T is the subject of an `alignof` expression (8.3.6), or
- (5.13) — an *exception-declaration* has type T, reference to T, or pointer to T (18.3).

— *end note*]

- ⁶ There can be more than one definition of a class type (Clause 12), enumeration type (10.2), inline function with external linkage (10.1.6), inline variable with external linkage (10.1.6), class template (Clause 17), non-static function template (17.5.6), static data member of a class template (17.5.1.3), member function of a class template (17.5.1.1), or template specialization for which some template parameters are not specified (17.7, 17.5.5) in a program provided that each definition appears in a different translation unit, and provided the definitions satisfy the following requirements. Given such an entity named D defined in more than one translation unit, then

- (6.1) — each definition of D shall consist of the same sequence of tokens; and
- (6.2) — in each definition of D, corresponding names, looked up according to 6.4, shall refer to an entity defined within the definition of D, or shall refer to the same entity, after overload resolution (16.3) and after matching of partial template specialization (17.8.3), except that a name can refer to
 - (6.2.1) — a non-volatile `const` object with internal or no linkage if the object
 - (6.2.1.1) — has the same literal type in all definitions of D,
 - (6.2.1.2) — is initialized with a constant expression (8.20),
 - (6.2.1.3) — is not odr-used in any definition of D, and
 - (6.2.1.4) — has the same value in all definitions of D,
 - or
 - (6.2.2) — a reference with internal or no linkage initialized with a constant expression such that the reference refers to the same entity in all definitions of D;
- and
- (6.3) — in each definition of D, corresponding entities shall have the same language linkage; and
- (6.4) — in each definition of D, the overloaded operators referred to, the implicit calls to conversion functions, constructors, operator new functions and operator delete functions, shall refer to the same function, or to a function defined within the definition of D; and

- (6.5) — in each definition of *D*, a default argument used by an (implicit or explicit) function call is treated as if its token sequence were present in the definition of *D*; that is, the default argument is subject to the requirements described in this paragraph (and, if the default argument has subexpressions with default arguments, this requirement applies recursively).²⁸
- (6.6) — if *D* is a class with an implicitly-declared constructor (15.1), it is as if the constructor was implicitly defined in every translation unit where it is odr-used, and the implicit definition in every translation unit shall call the same constructor for a subobject of *D*. [*Example*:

```
// translation unit 1:
struct X {
    X(int, int);
    X(int, int, int);
};
X::X(int, int = 0) { }
class D {
    X x = 0;
};
D d1;                                     // X(int, int) called by D()

// translation unit 2:
struct X {
    X(int, int);
    X(int, int, int);
};
X::X(int, int = 0, int = 0) { }
class D {
    X x = 0;
};
D d2;                                     // X(int, int, int) called by D();
                                           // D()'s implicit definition violates the ODR
```

— end example]

If *D* is a template and is defined in more than one translation unit, then the preceding requirements shall apply both to names from the template's enclosing scope used in the template definition (17.6.3), and also to dependent names at the point of instantiation (17.6.2). If the definitions of *D* satisfy all these requirements, then the behavior is as if there were a single definition of *D*. If the definitions of *D* do not satisfy these requirements, then the behavior is undefined.

6.3 Scope

[basic.scope]

6.3.1 Declarative regions and scopes

[basic.scope.declarative]

- ¹ Every name is introduced in some portion of program text called a *declarative region*, which is the largest part of the program in which that name is *valid*, that is, in which that name may be used as an unqualified name to refer to the same entity. In general, each particular name is valid only within some possibly discontinuous portion of program text called its *scope*. To determine the scope of a declaration, it is sometimes convenient to refer to the *potential scope* of a declaration. The scope of a declaration is the same as its potential scope unless the potential scope contains another declaration of the same name. In that case, the potential scope of the declaration in the inner (contained) declarative region is excluded from the scope of the declaration in the outer (containing) declarative region.

- ² [*Example*: In

```
int j = 24;
```

²⁸) 11.3.6 describes how default argument names are looked up.

```
int main() {
    int i = j, j;
    j = 42;
}
```

the identifier `j` is declared twice as a name (and used twice). The declarative region of the first `j` includes the entire example. The potential scope of the first `j` begins immediately after that `j` and extends to the end of the program, but its (actual) scope excludes the text between the `,` and the `}`. The declarative region of the second declaration of `j` (the `j` immediately before the semicolon) includes all the text between `{` and `}`, but its potential scope excludes the declaration of `i`. The scope of the second declaration of `j` is the same as its potential scope. — *end example*]

- 3 The names declared by a declaration are introduced into the scope in which the declaration occurs, except that the presence of a **friend** specifier (14.3), certain uses of the *elaborated-type-specifier* (10.1.7.3), and *using-directives* (10.3.4) alter this general behavior.
- 4 Given a set of declarations in a single declarative region, each of which specifies the same unqualified name,
 - (4.1) — they shall all refer to the same entity, or all refer to functions and function templates; or
 - (4.2) — exactly one declaration shall declare a class name or enumeration name that is not a typedef name and the other declarations shall all refer to the same variable, non-static data member, or enumerator, or all refer to functions and function templates; in this case the class name or enumeration name is hidden (6.3.10). [*Note*: A namespace name or a class template name must be unique in its declarative region (10.3.2, Clause 17). — *end note*]

[*Note*: These restrictions apply to the declarative region into which a name is introduced, which is not necessarily the same as the region in which the declaration occurs. In particular, *elaborated-type-specifiers* (10.1.7.3) and friend declarations (14.3) may introduce a (possibly not visible) name into an enclosing namespace; these restrictions apply to that region. Local extern declarations (6.5) may introduce a name into the declarative region where the declaration appears and also introduce a (possibly not visible) name into an enclosing namespace; these restrictions apply to both regions. — *end note*]

- 5 [*Note*: The name lookup rules are summarized in 6.4. — *end note*]

6.3.2 Point of declaration

[basic.scope.pdecl]

- 1 The *point of declaration* for a name is immediately after its complete declarator (Clause 11) and before its *initializer* (if any), except as noted below. [*Example*:

```
unsigned char x = 12;
{ unsigned char x = x; }
```

Here the second `x` is initialized with its own (indeterminate) value. — *end example*]

- 2 [*Note*: a name from an outer scope remains visible up to the point of declaration of the name that hides it. [*Example*:

```
const int i = 2;
{ int i[i]; }
```

declares a block-scope array of two integers. — *end example*] — *end note*]

- 3 The point of declaration for a class or class template first declared by a *class-specifier* is immediately after the *identifier* or *simple-template-id* (if any) in its *class-head* (Clause 12). The point of declaration for an enumeration is immediately after the *identifier* (if any) in either its *enum-specifier* (10.2) or its first *opaque-enum-declaration* (10.2), whichever comes first. The point of declaration of an alias or alias template immediately follows the *type-id* to which the alias refers.
- 4 The point of declaration of a *using-declarator* that does not name a constructor is immediately after the *using-declarator* (10.3.3).

- 5 The point of declaration for an enumerator is immediately after its *enumerator-definition*. [*Example*:

```
const int x = 12;
{ enum { x = x }; }
```

Here, the enumerator `x` is initialized with the value of the constant `x`, namely 12. — *end example*]

- 6 After the point of declaration of a class member, the member name can be looked up in the scope of its class. [*Note*: This is true even if the class is an incomplete class. For example,

```
struct X {
    enum E { z = 16 };
    int b[X::z];    // OK
};
```

— *end note*]

- 7 The point of declaration of a class first declared in an *elaborated-type-specifier* is as follows:

- (7.1) — for a declaration of the form

class-key attribute-specifier-seq_{opt} identifier ;

the *identifier* is declared to be a *class-name* in the scope that contains the declaration, otherwise

- (7.2) — for an *elaborated-type-specifier* of the form

class-key identifier

if the *elaborated-type-specifier* is used in the *decl-specifier-seq* or *parameter-declaration-clause* of a function defined in namespace scope, the *identifier* is declared as a *class-name* in the namespace that contains the declaration; otherwise, except as a friend declaration, the *identifier* is declared in the smallest namespace or block scope that contains the declaration. [*Note*: These rules also apply within templates. — *end note*] [*Note*: Other forms of *elaborated-type-specifier* do not declare a new name, and therefore must refer to an existing *type-name*. See 6.4.4 and 10.1.7.3. — *end note*]

- 8 The point of declaration for an *injected-class-name* (Clause 12) is immediately following the opening brace of the class definition.
- 9 The point of declaration for a function-local predefined variable (11.4) is immediately before the *function-body* of a function definition.
- 10 The point of declaration for a template parameter is immediately after its complete *template-parameter*. [*Example*:

```
typedef unsigned char T;
template<class T
    = T    // lookup finds the typedef name of unsigned char
    , T    // lookup finds the template parameter
    N = 0> struct A { };
```

— *end example*]

- 11 [*Note*: Friend declarations refer to functions or classes that are members of the nearest enclosing namespace, but they do not introduce new names into that namespace (10.3.1.2). Function declarations at block scope and variable declarations with the `extern` specifier at block scope refer to declarations that are members of an enclosing namespace, but they do not introduce new names into that scope. — *end note*]
- 12 [*Note*: For point of instantiation of a template, see 17.6.4.1. — *end note*]

6.3.3 Block scope

[**basic.scope.block**]

- 1 A name declared in a block (9.3) is local to that block; it has *block scope*. Its potential scope begins at its point of declaration (6.3.2) and ends at the end of its block. A variable declared at block scope is a *local variable*.

- ² The potential scope of a function parameter name (including one appearing in a *lambda-declarator*) or of a function-local predefined variable in a function definition (11.4) begins at its point of declaration. If the function has a *function-try-block* the potential scope of a parameter or of a function-local predefined variable ends at the end of the last associated handler, otherwise it ends at the end of the outermost block of the function definition. A parameter name shall not be redeclared in the outermost block of the function definition nor in the outermost block of any handler associated with a *function-try-block*.
- ³ The name declared in an *exception-declaration* is local to the *handler* and shall not be redeclared in the outermost block of the *handler*.
- ⁴ Names declared in the *init-statement*, the *for-range-declaration*, and in the *condition* of **if**, **while**, **for**, and **switch** statements are local to the **if**, **while**, **for**, or **switch** statement (including the controlled statement), and shall not be redeclared in a subsequent condition of that statement nor in the outermost block (or, for the **if** statement, any of the outermost blocks) of the controlled statement; see 9.4.

6.3.4 Function prototype scope

[basic.scope.proto]

- ¹ In a function declaration, or in any function declarator except the declarator of a function definition (11.4), names of parameters (if supplied) have function prototype scope, which terminates at the end of the nearest enclosing function declarator.

6.3.5 Function scope

[basic.funscope]

- ¹ Labels (9.1) have *function scope* and may be used anywhere in the function in which they are declared. Only labels have function scope.

6.3.6 Namespace scope

[basic.scope.namespace]

- ¹ The declarative region of a *namespace-definition* is its *namespace-body*. Entities declared in a *namespace-body* are said to be *members* of the namespace, and names introduced by these declarations into the declarative region of the namespace are said to be *member names* of the namespace. A namespace member name has namespace scope. Its potential scope includes its namespace from the name's point of declaration (6.3.2) onwards; and for each *using-directive* (10.3.4) that nominates the member's namespace, the member's potential scope includes that portion of the potential scope of the *using-directive* that follows the member's point of declaration. [Example:

```

namespace N {
    int i;
    int g(int a) { return a; }
    int j();
    void q();
}
namespace { int l=1; }
// the potential scope of l is from its point of declaration to the end of the translation unit

namespace N {
    int g(char a) { // overloads N::g(int)
        return l+a; // l is from unnamed namespace
    }

    int i; // error: duplicate definition
    int j(); // OK: duplicate function declaration

    int j() { // OK: definition of N::j()
        return g(i); // calls N::g(int)
    }
    int q(); // error: different return type

```

}

— *end example*]

- 2 A namespace member can also be referred to after the `::` scope resolution operator (8.1) applied to the name of its namespace or the name of a namespace which nominates the member's namespace in a *using-directive*; see 6.4.3.2.
- 3 The outermost declarative region of a translation unit is also a namespace, called the *global namespace*. A name declared in the global namespace has *global namespace scope* (also called *global scope*). The potential scope of such a name begins at its point of declaration (6.3.2) and ends at the end of the translation unit that is its declarative region. A name with global namespace scope is said to be a *global name*.

6.3.7 Class scope

[basic.scope.class]

- 1 The potential scope of a name declared in a class consists not only of the declarative region following the name's point of declaration, but also of all function bodies, default arguments, *noexcept-specifiers*, and *brace-or-equal-initializers* of non-static data members in that class (including such things in nested classes).
- 2 A name *N* used in a class *S* shall refer to the same declaration in its context and when re-evaluated in the completed scope of *S*. No diagnostic is required for a violation of this rule.
- 3 A name declared within a member function hides a declaration of the same name whose scope extends to or past the end of the member function's class.
- 4 The potential scope of a declaration that extends to or past the end of a class definition also extends to the regions defined by its member definitions, even if the members are defined lexically outside the class (this includes static data member definitions, nested class definitions, and member function definitions, including the member function body and any portion of the declarator part of such definitions which follows the *declarator-id*, including a *parameter-declaration-clause* and any default arguments (11.3.6)).

- 5 [*Example*:

```
typedef int c;
enum { i = 1 };

class X {
    char v[i];           // error: i refers to ::i but when reevaluated is X::i
    int f() { return sizeof(c); } // OK: X::c
    char c;
    enum { i = 2 };
};

typedef char* T;
struct Y {
    T a;                 // error: T refers to ::T but when reevaluated is Y::T
    typedef long T;
    T b;
};

typedef int I;
class D {
    typedef I I;         // error, even though no reordering involved
};
```

— *end example*]

- 6 The name of a class member shall only be used as follows:
 - (6.1) — in the scope of its class (as described above) or a class derived (Clause 13) from its class,

- (6.2) — after the `.` operator applied to an expression of the type of its class (8.2.5) or a class derived from its class,
- (6.3) — after the `->` operator applied to a pointer to an object of its class (8.2.5) or a class derived from its class,
- (6.4) — after the `::` scope resolution operator (8.1) applied to the name of its class or a class derived from its class.

6.3.8 Enumeration scope

[basic.scope.enum]

- ¹ The name of a scoped enumerator (10.2) has *enumeration scope*. Its potential scope begins at its point of declaration and terminates at the end of the *enum-specifier*.

6.3.9 Template parameter scope

[basic.scope.temp]

- ¹ The declarative region of the name of a template parameter of a template *template-parameter* is the smallest *template-parameter-list* in which the name was introduced.
- ² The declarative region of the name of a template parameter of a template is the smallest *template-declaration* in which the name was introduced. Only template parameter names belong to this declarative region; any other kind of name introduced by the *declaration* of a *template-declaration* is instead introduced into the same declarative region where it would be introduced as a result of a non-template declaration of the same name. [Example:

```
namespace N {
    template<class T> struct A { };           // #1
    template<class U> void f(U) { }          // #2
    struct B {
        template<class V> friend int g(struct C*); // #3
    };
}
```

The declarative regions of T, U and V are the *template-declarations* on lines #1, #2, and #3, respectively. But the names A, f, g and C all belong to the same declarative region — namely, the *namespace-body* of N. (g is still considered to belong to this declarative region in spite of its being hidden during qualified and unqualified name lookup.) — end example]

- ³ The potential scope of a template parameter name begins at its point of declaration (6.3.2) and ends at the end of its declarative region. [Note: This implies that a *template-parameter* can be used in the declaration of subsequent *template-parameters* and their default arguments but cannot be used in preceding *template-parameters* or their default arguments. For example,

```
template<class T, T* p, class U = T> class X { /* ... */ };
template<class T> void f(T* p = new T);
```

This also implies that a *template-parameter* can be used in the specification of base classes. For example,

```
template<class T> class X : public Array<T> { /* ... */ };
template<class T> class Y : public T { /* ... */ };
```

The use of a template parameter as a base class implies that a class used as a template argument must be defined and not just declared when the class template is instantiated. — end note]

- ⁴ The declarative region of the name of a template parameter is nested within the immediately-enclosing declarative region. [Note: As a result, a *template-parameter* hides any entity with the same name in an enclosing scope (6.3.10). [Example:

```
typedef int N;
template<N X, typename N, template<N Y> class T> struct A;
```


Here, **X** is a non-type template parameter of type `int` and **Y** is a non-type template parameter of the same type as the second template parameter of **A**. — *end example*] — *end note*]

- ⁵ [*Note*: Because the name of a template parameter cannot be redeclared within its potential scope (17.6.1), a template parameter’s scope is often its potential scope. However, it is still possible for a template parameter name to be hidden; see 17.6.1. — *end note*]

6.3.10 Name hiding

[basic.scope.hiding]

- ¹ A name can be hidden by an explicit declaration of that same name in a nested declarative region or derived class (13.2).
- ² A class name (12.1) or enumeration name (10.2) can be hidden by the name of a variable, data member, function, or enumerator declared in the same scope. If a class or enumeration name and a variable, data member, function, or enumerator are declared in the same scope (in any order) with the same name, the class or enumeration name is hidden wherever the variable, data member, function, or enumerator name is visible.
- ³ In a member function definition, the declaration of a name at block scope hides the declaration of a member of the class with the same name; see 6.3.7. The declaration of a member in a derived class (Clause 13) hides the declaration of a member of a base class of the same name; see 13.2.
- ⁴ During the lookup of a name qualified by a namespace name, declarations that would otherwise be made visible by a *using-directive* can be hidden by declarations with the same name in the namespace containing the *using-directive*; see 6.4.3.2.
- ⁵ If a name is in scope and is not hidden it is said to be *visible*.

6.4 Name lookup

[basic.lookup]

- ¹ The name lookup rules apply uniformly to all names (including *typedef-names* (10.1.3), *namespace-names* (10.3), and *class-names* (12.1)) wherever the grammar allows such names in the context discussed by a particular rule. Name lookup associates the use of a name with a set of declarations (6.1) of that name. The declarations found by name lookup shall either all declare the same entity or shall all declare functions; in the latter case, the declarations are said to form a set of overloaded functions (16.1). Overload resolution (16.3) takes place after name lookup has succeeded. The access rules (Clause 14) are considered only once name lookup and function overload resolution (if applicable) have succeeded. Only after name lookup, function overload resolution (if applicable) and access checking have succeeded are the attributes introduced by the name’s declaration used further in expression processing (Clause 8).
- ² A name “looked up in the context of an expression” is looked up as an unqualified name in the scope where the expression is found.
- ³ The injected-class-name of a class (Clause 12) is also considered to be a member of that class for the purposes of name hiding and lookup.
- ⁴ [*Note*: 6.5 discusses linkage issues. The notions of scope, point of declaration and name hiding are discussed in 6.3. — *end note*]

6.4.1 Unqualified name lookup

[basic.lookup.unqual]

- ¹ In all the cases listed in 6.4.1, the scopes are searched for a declaration in the order listed in each of the respective categories; name lookup ends as soon as a declaration is found for the name. If no declaration is found, the program is ill-formed.
- ² The declarations from the namespace nominated by a *using-directive* become visible in a namespace enclosing the *using-directive*; see 10.3.4. For the purpose of the unqualified name lookup rules described in 6.4.1, the declarations from the namespace nominated by the *using-directive* are considered members of that enclosing namespace.

- ³ The lookup for an unqualified name used as the *postfix-expression* of a function call is described in 6.4.2. [*Note:* For purposes of determining (during parsing) whether an expression is a *postfix-expression* for a function call, the usual name lookup rules apply. The rules in 6.4.2 have no effect on the syntactic interpretation of an expression. For example,

```
typedef int f;
namespace N {
    struct A {
        friend void f(A &);
        operator int();
        void g(A a) {
            int i = f(a); // f is the typedef, not the friend function: equivalent to int(a)
        }
    };
}
```

Because the expression is not a function call, the argument-dependent name lookup (6.4.2) does not apply and the friend function `f` is not found. — *end note*]

- ⁴ A name used in global scope, outside of any function, class or user-declared namespace, shall be declared before its use in global scope.
- ⁵ A name used in a user-declared namespace outside of the definition of any function or class shall be declared before its use in that namespace or before its use in a namespace enclosing its namespace.
- ⁶ In the definition of a function that is a member of namespace `N`, a name used after the function's *declarator-id*²⁹ shall be declared before its use in the block in which it is used or in one of its enclosing blocks (9.3) or shall be declared before its use in namespace `N` or, if `N` is a nested namespace, shall be declared before its use in one of `N`'s enclosing namespaces. [*Example:*

```
namespace A {
    namespace N {
        void f();
    }
}
void A::N::f() {
    i = 5;
    // The following scopes are searched for a declaration of i:
    // 1) outermost block scope of A::N::f, before the use of i
    // 2) scope of namespace N
    // 3) scope of namespace A
    // 4) global scope, before the definition of A::N::f
}
```

— *end example*]

- ⁷ A name used in the definition of a class `X` outside of a member function body, default argument, *noexcept-specifier*, *brace-or-equal-initializer* of a non-static data member, or nested class definition³⁰ shall be declared in one of the following ways:
- (7.1) — before its use in class `X` or be a member of a base class of `X` (13.2), or
- (7.2) — if `X` is a nested class of class `Y` (12.2.5), before the definition of `X` in `Y`, or shall be a member of a base class of `Y` (this lookup applies in turn to `Y`'s enclosing classes, starting with the innermost enclosing

²⁹) This refers to unqualified names that occur, for instance, in a type or default argument in the *parameter-declaration-clause* or used in the function body.

³⁰) This refers to unqualified names following the class name; such a name may be used in the *base-clause* or may be used in the class definition.

class),³¹ or

- (7.3) — if **X** is a local class (12.4) or is a nested class of a local class, before the definition of class **X** in a block enclosing the definition of class **X**, or
- (7.4) — if **X** is a member of namespace **N**, or is a nested class of a class that is a member of **N**, or is a local class or a nested class within a local class of a function that is a member of **N**, before the definition of class **X** in namespace **N** or in one of **N**'s enclosing namespaces.

[*Example:*

```
namespace M {
    class B { };
}

namespace N {
    class Y : public M::B {
        class X {
            int a[i];
        };
    };
}
```

```
// The following scopes are searched for a declaration of i:
// 1) scope of class N::Y::X, before the use of i
// 2) scope of class N::Y, before the definition of N::Y::X
// 3) scope of N::Y's base class M::B
// 4) scope of namespace N, before the definition of N::Y
// 5) global scope, before the definition of N
```

— end example] [Note: When looking for a prior declaration of a class or function introduced by a **friend** declaration, scopes outside of the innermost enclosing namespace scope are not considered; see 10.3.1.2. — end note] [Note: 6.3.7 further describes the restrictions on the use of names in a class definition. 12.2.5 further describes the restrictions on the use of names in nested class definitions. 12.4 further describes the restrictions on the use of names in local class definitions. — end note]

- ⁸ For the members of a class **X**, a name used in a member function body, in a default argument, in a *noexcept-specifier*, in the *brace-or-equal-initializer* of a non-static data member (12.2), or in the definition of a class member outside of the definition of **X**, following the member's *declarator-id*³², shall be declared in one of the following ways:

- (8.1) — before its use in the block in which it is used or in an enclosing block (9.3), or
- (8.2) — shall be a member of class **X** or be a member of a base class of **X** (13.2), or
- (8.3) — if **X** is a nested class of class **Y** (12.2.5), shall be a member of **Y**, or shall be a member of a base class of **Y** (this lookup applies in turn to **Y**'s enclosing classes, starting with the innermost enclosing class),³³ or
- (8.4) — if **X** is a local class (12.4) or is a nested class of a local class, before the definition of class **X** in a block enclosing the definition of class **X**, or
- (8.5) — if **X** is a member of namespace **N**, or is a nested class of a class that is a member of **N**, or is a local class or a nested class within a local class of a function that is a member of **N**, before the use of the name, in namespace **N** or in one of **N**'s enclosing namespaces.

31) This lookup applies whether the definition of **X** is nested within **Y**'s definition or whether **X**'s definition appears in a namespace scope enclosing **Y**'s definition (12.2.5).

32) That is, an unqualified name that occurs, for instance, in a type in the *parameter-declaration-clause* or in the *noexcept-specifier*.

33) This lookup applies whether the member function is defined within the definition of class **X** or whether the member function is defined in a namespace scope enclosing **X**'s definition.

[*Example:*

```
class B { };
namespace M {
    namespace N {
        class X : public B {
            void f();
        };
    }
}
void M::N::X::f() {
    i = 16;
}
```

```
// The following scopes are searched for a declaration of i:
// 1) outermost block scope of M::N::X::f, before the use of i
// 2) scope of class M::N::X
// 3) scope of M::N::X's base class B
// 4) scope of namespace M::N
// 5) scope of namespace M
// 6) global scope, before the definition of M::N::X::f
```

— end example] [Note: 12.2.1 and 12.2.3 further describe the restrictions on the use of names in member function definitions. 12.2.5 further describes the restrictions on the use of names in the scope of nested classes. 12.4 further describes the restrictions on the use of names in local class definitions. — end note]

- 9 Name lookup for a name used in the definition of a **friend** function (14.3) defined inline in the class granting friendship shall proceed as described for lookup in member function definitions. If the **friend** function is not defined in the class granting friendship, name lookup in the **friend** function definition shall proceed as described for lookup in namespace member function definitions.
- 10 In a **friend** declaration naming a member function, a name used in the function declarator and not part of a *template-argument* in the *declarator-id* is first looked up in the scope of the member function's class (13.2). If it is not found, or if the name is part of a *template-argument* in the *declarator-id*, the look up is as described for unqualified names in the definition of the class granting friendship. [*Example:*

```
struct A {
    typedef int AT;
    void f1(AT);
    void f2(float);
    template <class T> void f3();
};
struct B {
    typedef char AT;
    typedef float BT;
    friend void A::f1(AT);           // parameter type is A::AT
    friend void A::f2(BT);           // parameter type is B::BT
    friend void A::f3<AT>();         // template argument is B::AT
};
```

— end example]

- 11 During the lookup for a name used as a default argument (11.3.6) in a function *parameter-declaration-clause* or used in the *expression* of a *mem-initializer* for a constructor (15.6.2), the function parameter names are visible and hide the names of entities declared in the block, class or namespace scopes containing the function declaration. [Note: 11.3.6 further describes the restrictions on the use of names in default arguments. 15.6.2 further describes the restrictions on the use of names in a *ctor-initializer*. — end note]

- ¹² During the lookup of a name used in the *constant-expression* of an *enumerator-definition*, previously declared *enumerators* of the enumeration are visible and hide the names of entities declared in the block, class, or namespace scopes containing the *enum-specifier*.
- ¹³ A name used in the definition of a **static** data member of class **X** (12.2.3.2) (after the *qualified-id* of the static member) is looked up as if the name was used in a member function of **X**. [Note: 12.2.3.2 further describes the restrictions on the use of names in the definition of a **static** data member. — end note]
- ¹⁴ If a variable member of a namespace is defined outside of the scope of its namespace then any name that appears in the definition of the member (after the *declarator-id*) is looked up as if the definition of the member occurred in its namespace. [Example:

```
namespace N {
    int i = 4;
    extern int j;
}

int i = 2;

int N::j = i;      // N::j == 4
— end example]
```

- ¹⁵ A name used in the handler for a *function-try-block* (Clause 18) is looked up as if the name was used in the outermost block of the function definition. In particular, the function parameter names shall not be redeclared in the *exception-declaration* nor in the outermost block of a handler for the *function-try-block*. Names declared in the outermost block of the function definition are not found when looked up in the scope of a handler for the *function-try-block*. [Note: But function parameter names are found. — end note]
- ¹⁶ [Note: The rules for name lookup in template definitions are described in 17.6. — end note]

6.4.2 Argument-dependent name lookup

[basic.lookup.argdep]

- ¹ When the *postfix-expression* in a function call (8.2.2) is an *unqualified-id*, other namespaces not considered during the usual unqualified lookup (6.4.1) may be searched, and in those namespaces, namespace-scope friend function or function template declarations (14.3) not otherwise visible may be found. These modifications to the search depend on the types of the arguments (and for template template arguments, the namespace of the template argument). [Example:

```
namespace N {
    struct S { };
    void f(S);
}

void g() {
    N::S s;
    f(s);           // OK: calls N::f
    (f)(s);         // error: N::f not considered; parentheses prevent argument-dependent lookup
}
— end example]
```

- ² For each argument type **T** in the function call, there is a set of zero or more *associated namespaces* and a set of zero or more *associated classes* to be considered. The sets of namespaces and classes are determined entirely by the types of the function arguments (and the namespace of any template template argument). Typedef names and *using-declarations* used to specify the types do not contribute to this set. The sets of namespaces and classes are determined in the following way:
- (2.1) — If **T** is a fundamental type, its associated sets of namespaces and classes are both empty.

- (2.2) — If *T* is a class type (including unions), its associated classes are: the class itself; the class of which it is a member, if any; and its direct and indirect base classes. Its associated namespaces are the innermost enclosing namespaces of its associated classes. Furthermore, if *T* is a class template specialization, its associated namespaces and classes also include: the namespaces and classes associated with the types of the template arguments provided for template type parameters (excluding template template parameters); the namespaces of which any template template arguments are members; and the classes of which any member templates used as template template arguments are members. [*Note*: Non-type template arguments do not contribute to the set of associated namespaces. — *end note*]
- (2.3) — If *T* is an enumeration type, its associated namespace is the innermost enclosing namespace of its declaration. If it is a class member, its associated class is the member's class; else it has no associated class.
- (2.4) — If *T* is a pointer to *U* or an array of *U*, its associated namespaces and classes are those associated with *U*.
- (2.5) — If *T* is a function type, its associated namespaces and classes are those associated with the function parameter types and those associated with the return type.
- (2.6) — If *T* is a pointer to a member function of a class *X*, its associated namespaces and classes are those associated with the function parameter types and return type, together with those associated with *X*.
- (2.7) — If *T* is a pointer to a data member of class *X*, its associated namespaces and classes are those associated with the member type together with those associated with *X*.

If an associated namespace is an inline namespace (10.3.1), its enclosing namespace is also included in the set. If an associated namespace directly contains inline namespaces, those inline namespaces are also included in the set. In addition, if the argument is the name or address of a set of overloaded functions and/or function templates, its associated classes and namespaces are the union of those associated with each of the members of the set, i.e., the classes and namespaces associated with its parameter types and return type. Additionally, if the aforementioned set of overloaded functions is named with a *template-id*, its associated classes and namespaces also include those of its type *template-arguments* and its template *template-arguments*.

- 3 Let *X* be the lookup set produced by unqualified lookup (6.4.1) and let *Y* be the lookup set produced by argument dependent lookup (defined as follows). If *X* contains

- (3.1) — a declaration of a class member, or
- (3.2) — a block-scope function declaration that is not a *using-declaration*, or
- (3.3) — a declaration that is neither a function nor a function template

then *Y* is empty. Otherwise *Y* is the set of declarations found in the namespaces associated with the argument types as described below. The set of declarations found by the lookup of the name is the union of *X* and *Y*. [*Note*: The namespaces and classes associated with the argument types can include namespaces and classes already considered by the ordinary unqualified lookup. — *end note*] [*Example*:

```
namespace NS {
    class T { };
    void f(T);
    void g(T, int);
}
NS::T parm;
void g(NS::T, float);
int main() {
    f(parm);                // OK: calls NS::f
    extern void g(NS::T, float);
    g(parm, 1);             // OK: calls g(NS::T, float)
}
```

— *end example*]

- ⁴ When considering an associated namespace, the lookup is the same as the lookup performed when the associated namespace is used as a qualifier (6.4.3.2) except that:
- (4.1) — Any *using-directives* in the associated namespace are ignored.
 - (4.2) — Any namespace-scope friend functions or friend function templates declared in associated classes are visible within their respective namespaces even if they are not visible during an ordinary lookup (14.3).
 - (4.3) — All names except those of (possibly overloaded) functions and function templates are ignored.

6.4.3 Qualified name lookup

[basic.lookup.qual]

- ¹ The name of a class or namespace member or enumerator can be referred to after the `::` scope resolution operator (8.1) applied to a *nested-name-specifier* that denotes its class, namespace, or enumeration. If a `::` scope resolution operator in a *nested-name-specifier* is not preceded by a *decltype-specifier*, lookup of the name preceding that `::` considers only namespaces, types, and templates whose specializations are types. If the name found does not designate a namespace or a class, enumeration, or dependent type, the program is ill-formed. [Example:

```
class A {
public:
    static int n;
};
int main() {
    int A;
    A::n = 42;           // OK
    A b;                 // ill-formed: A does not name a type
}
```

— end example]

- ² [Note: Multiply qualified names, such as `N1::N2::N3::n`, can be used to refer to members of nested classes (12.2.5) or members of nested namespaces. — end note]
- ³ In a declaration in which the *declarator-id* is a *qualified-id*, names used before the *qualified-id* being declared are looked up in the defining namespace scope; names following the *qualified-id* are looked up in the scope of the member's class or namespace. [Example:

```
class X { };
class C {
    class X { };
    static const int number = 50;
    static X arr[number];
};
X C::arr[number]; // ill-formed:
                  // equivalent to ::X C::arr[C::number];
                  // and not to C::X C::arr[C::number];
```

— end example]

- ⁴ A name prefixed by the unary scope operator `::` (8.1) is looked up in global scope, in the translation unit where it is used. The name shall be declared in global namespace scope or shall be a name whose declaration is visible in global scope because of a *using-directive* (6.4.3.2). The use of `::` allows a global name to be referred to even if its identifier has been hidden (6.3.10).
- ⁵ A name prefixed by a *nested-name-specifier* that nominates an enumeration type shall represent an *enumerator* of that enumeration.
- ⁶ If a *pseudo-destructor-name* (8.2.4) contains a *nested-name-specifier*, the *type-names* are looked up as types in the scope designated by the *nested-name-specifier*. Similarly, in a *qualified-id* of the form:

*nested-name-specifier*_{opt} *class-name* :: ~ *class-name*

the second *class-name* is looked up in the same scope as the first. [*Example:*

```
struct C {
    typedef int I;
};
typedef int I1, I2;
extern int* p;
extern int* q;
p->C::I::~~I();           // I is looked up in the scope of C
q->I1::~~I2();            // I2 is looked up in the scope of the postfix-expression

struct A {
    ~A();
};
typedef A AB;
int main() {
    AB* p;
    p->AB::~~AB();        // explicitly calls the destructor for A
}
```

— *end example*] [*Note:* 6.4.5 describes how name lookup proceeds after the . and -> operators. — *end note*]

6.4.3.1 Class members

[**class.qual**]

- ¹ If the *nested-name-specifier* of a *qualified-id* nominates a class, the name specified after the *nested-name-specifier* is looked up in the scope of the class (13.2), except for the cases listed below. The name shall represent one or more members of that class or of one of its base classes (Clause 13). [*Note:* A class member can be referred to using a *qualified-id* at any point in its potential scope (6.3.7). — *end note*] The exceptions to the name lookup rule above are the following:

- (1.1) — the lookup for a destructor is as specified in 6.4.3;
- (1.2) — a *conversion-type-id* of a *conversion-function-id* is looked up in the same manner as a *conversion-type-id* in a class member access (see 6.4.5);
- (1.3) — the names in a *template-argument* of a *template-id* are looked up in the context in which the entire *postfix-expression* occurs.
- (1.4) — the lookup for a name specified in a *using-declaration* (10.3.3) also finds class or enumeration names hidden within the same scope (6.3.10).

- ² In a lookup in which function names are not ignored³⁴ and the *nested-name-specifier* nominates a class *C*:

- (2.1) — if the name specified after the *nested-name-specifier*, when looked up in *C*, is the injected-class-name of *C* (Clause 12), or
- (2.2) — in a *using-declarator* of a *using-declaration* (10.3.3) that is a *member-declaration*, if the name specified after the *nested-name-specifier* is the same as the *identifier* or the *simple-template-id*'s *template-name* in the last component of the *nested-name-specifier*,

the name is instead considered to name the constructor of class *C*. [*Note:* For example, the constructor is not an acceptable lookup result in an *elaborated-type-specifier* so the constructor would not be used in place of the injected-class-name. — *end note*] Such a constructor name shall be used only in the *declarator-id* of a declaration that names a constructor or in a *using-declaration*. [*Example:*

```
struct A { A(); };
struct B: public A { B(); };
```

³⁴) Lookups in which function names are ignored include names appearing in a *nested-name-specifier*, an *elaborated-type-specifier*, or a *base-specifier*.


```

A::A() { }
B::B() { }

B::A ba;           // object of type A
A::A a;            // error, A::A is not a type name
struct A::A a2;     // object of type A

```

— end example]

- ³ A class member name hidden by a name in a nested declarative region or by the name of a derived class member can still be found if qualified by the name of its class followed by the `::` operator.

6.4.3.2 Namespace members

[namespace.qual]

- ¹ If the *nested-name-specifier* of a *qualified-id* nominates a namespace (including the case where the *nested-name-specifier* is `::`, i.e., nominating the global namespace), the name specified after the *nested-name-specifier* is looked up in the scope of the namespace. The names in a *template-argument* of a *template-id* are looked up in the context in which the entire *postfix-expression* occurs.
- ² For a namespace X and name m , the namespace-qualified lookup set $S(X, m)$ is defined as follows: Let $S'(X, m)$ be the set of all declarations of m in X and the inline namespace set of X (10.3.1). If $S'(X, m)$ is not empty, $S(X, m)$ is $S'(X, m)$; otherwise, $S(X, m)$ is the union of $S(N_i, m)$ for all namespaces N_i nominated by *using-directives* in X and its inline namespace set.
- ³ Given $X::m$ (where X is a user-declared namespace), or given $::m$ (where X is the global namespace), if $S(X, m)$ is the empty set, the program is ill-formed. Otherwise, if $S(X, m)$ has exactly one member, or if the context of the reference is a *using-declaration* (10.3.3), $S(X, m)$ is the required set of declarations of m . Otherwise if the use of m is not one that allows a unique declaration to be chosen from $S(X, m)$, the program is ill-formed. [Example:

```

int x;
namespace Y {
    void f(float);
    void h(int);
}

namespace Z {
    void h(double);
}

namespace A {
    using namespace Y;
    void f(int);
    void g(int);
    int i;
}

namespace B {
    using namespace Z;
    void f(char);
    int i;
}

namespace AB {
    using namespace A;
    using namespace B;
    void g();
}

```

```

}

void h()
{
    AB::g();           // g is declared directly in AB, therefore S is {AB::g()} and AB::g() is chosen

    AB::f(1);          // f is not declared directly in AB so the rules are applied recursively to A and B;
                      // namespace Y is not searched and Y::f(float) is not considered;
                      // S is {A::f(int), B::f(char)} and overload resolution chooses A::f(int)

    AB::f('c');        // as above but resolution chooses B::f(char)

    AB::x++;           // x is not declared directly in AB, and is not declared in A or B, so the rules
                      // are applied recursively to Y and Z, S is {} so the program is ill-formed

    AB::i++;           // i is not declared directly in AB so the rules are applied recursively to A and B,
                      // S is {A::i, B::i} so the use is ambiguous and the program is ill-formed

    AB::h(16.8);       // h is not declared directly in AB and not declared directly in A or B so the rules
                      // are applied recursively to Y and Z, S is {Y::h(int), Z::h(double)} and
                      // overload resolution chooses Z::h(double)
}

```

— end example]

- ⁴ [Note: The same declaration found more than once is not an ambiguity (because it is still a unique declaration).
[Example:

```

namespace A {
    int a;
}

namespace B {
    using namespace A;
}

namespace C {
    using namespace A;
}

namespace BC {
    using namespace B;
    using namespace C;
}

void f()
{
    BC::a++;           // OK: S is {A::a, A::a}
}

namespace D {
    using A::a;
}

namespace BD {
    using namespace B;
    using namespace D;
}

```

```

}

void g()
{
    BD::a++;           // OK: S is {A::a, A::a}
}

```

— end example] — end note]

- ⁵ [Example: Because each referenced namespace is searched at most once, the following is well-defined:

```

namespace B {
    int b;
}

namespace A {
    using namespace B;
    int a;
}

namespace B {
    using namespace A;
}

void f()
{
    A::a++;           // OK: a declared directly in A, S is {A::a}
    B::a++;           // OK: both A and B searched (once), S is {A::a}
    A::b++;           // OK: both A and B searched (once), S is {B::b}
    B::b++;           // OK: b declared directly in B, S is {B::b}
}

```

— end example]

- ⁶ During the lookup of a qualified namespace member name, if the lookup finds more than one declaration of the member, and if one declaration introduces a class name or enumeration name and the other declarations either introduce the same variable, the same enumerator or a set of functions, the non-type name hides the class or enumeration name if and only if the declarations are from the same namespace; otherwise (the declarations are from different namespaces), the program is ill-formed. [Example:

```

namespace A {
    struct x { };
    int x;
    int y;
}

namespace B {
    struct y { };
}

namespace C {
    using namespace A;
    using namespace B;
    int i = C::x;      // OK, A::x (of type int)
    int j = C::y;      // ambiguous, A::y or B::y
}

```

— end example]

- ⁷ In a declaration for a namespace member in which the *declarator-id* is a *qualified-id*, given that the *qualified-id* for the namespace member has the form

nested-name-specifier unqualified-id

the *unqualified-id* shall name a member of the namespace designated by the *nested-name-specifier* or of an element of the inline namespace set (10.3.1) of that namespace. [Example:

```
namespace A {
    namespace B {
        void f1(int);
    }
    using namespace B;
}
void A::f1(int){ } // ill-formed, f1 is not a member of A
```

— end example] However, in such namespace member declarations, the *nested-name-specifier* may rely on *using-directives* to implicitly provide the initial part of the *nested-name-specifier*. [Example:

```
namespace A {
    namespace B {
        void f1(int);
    }
}

namespace C {
    namespace D {
        void f1(int);
    }
}

using namespace A;
using namespace C::D;
void B::f1(int){ } // OK, defines A::B::f1(int)
```

— end example]

6.4.4 Elaborated type specifiers

[basic.lookup.elab]

- ¹ An *elaborated-type-specifier* (10.1.7.3) may be used to refer to a previously declared *class-name* or *enum-name* even though the name has been hidden by a non-type declaration (6.3.10).
- ² If the *elaborated-type-specifier* has no *nested-name-specifier*, and unless the *elaborated-type-specifier* appears in a declaration with the following form:

class-key attribute-specifier-seq_{opt} identifier ;

the *identifier* is looked up according to 6.4.1 but ignoring any non-type names that have been declared. If the *elaborated-type-specifier* is introduced by the **enum** keyword and this lookup does not find a previously declared *type-name*, the *elaborated-type-specifier* is ill-formed. If the *elaborated-type-specifier* is introduced by the *class-key* and this lookup does not find a previously declared *type-name*, or if the *elaborated-type-specifier* appears in a declaration with the form:

class-key attribute-specifier-seq_{opt} identifier ;

the *elaborated-type-specifier* is a declaration that introduces the *class-name* as described in 6.3.2.

- ³ If the *elaborated-type-specifier* has a *nested-name-specifier*, qualified name lookup is performed, as described in 6.4.3, but ignoring any non-type names that have been declared. If the name lookup does not find a previously declared *type-name*, the *elaborated-type-specifier* is ill-formed. [Example:

```
struct Node {
```

```

    struct Node* Next;           // OK: Refers to Node at global scope
    struct Data* Data;          // OK: Declares type Data
                                // at global scope and member Data
};

struct Data {
    struct Node* Node;          // OK: Refers to Node at global scope
    friend struct ::Glob;       // error: Glob is not declared, cannot introduce a qualified type (10.1.7.3)
    friend struct Glob;         // OK: Refers to (as yet) undeclared Glob at global scope.
    /* ... */
};

struct Base {
    struct Data;                // OK: Declares nested Data
    struct ::Data* thatData;     // OK: Refers to ::Data
    struct Base::Data* thisData; // OK: Refers to nested Data
    friend class ::Data;         // OK: global Data is a friend
    friend class Data;           // OK: nested Data is a friend
    struct Data { /* ... */ };   // Defines nested Data
};

struct Data;                   // OK: Redeclares Data at global scope
struct ::Data;                 // error: cannot introduce a qualified type (10.1.7.3)
struct Base::Data;             // error: cannot introduce a qualified type (10.1.7.3)
struct Base::Datum;            // error: Datum undefined
struct Base::Data* pBase;      // OK: refers to nested Data
— end example]

```

6.4.5 Class member access

[basic.lookup.classref]

- ¹ In a class member access expression (8.2.5), if the `.` or `->` token is immediately followed by an *identifier* followed by a `<`, the identifier must be looked up to determine whether the `<` is the beginning of a template argument list (17.2) or a less-than operator. The identifier is first looked up in the class of the object expression. If the identifier is not found, it is then looked up in the context of the entire *postfix-expression* and shall name a class template.
- ² If the *id-expression* in a class member access (8.2.5) is an *unqualified-id*, and the type of the object expression is of a class type *C*, the *unqualified-id* is looked up in the scope of class *C*. For a pseudo-destructor call (8.2.4), the *unqualified-id* is looked up in the context of the complete *postfix-expression*.
- ³ If the *unqualified-id* is *~type-name*, the *type-name* is looked up in the context of the entire *postfix-expression*. If the type *T* of the object expression is of a class type *C*, the *type-name* is also looked up in the scope of class *C*. At least one of the lookups shall find a name that refers to *cv T*. [Example:

```

struct A { };

struct B {
    struct A { };
    void f(::A* a);
};

void B::f(::A* a) {
    a->~A();           // OK: lookup in *a finds the injected-class-name
}

```

— end example]

- ⁴ If the *id-expression* in a class member access is a *qualified-id* of the form

```
class-name-or-namespace-name::...
```

the *class-name-or-namespace-name* following the `.` or `->` operator is first looked up in the class of the object expression and the name, if found, is used. Otherwise it is looked up in the context of the entire *postfix-expression*. [Note: See 6.4.3, which describes the lookup of a name before `::`, which will only find a type or namespace name. — end note]

- ⁵ If the *qualified-id* has the form

```
::class-name-or-namespace-name::...
```

the *class-name-or-namespace-name* is looked up in global scope as a *class-name* or *namespace-name*.

- ⁶ If the *nested-name-specifier* contains a *simple-template-id* (17.2), the names in its *template-arguments* are looked up in the context in which the entire *postfix-expression* occurs.
- ⁷ If the *id-expression* is a *conversion-function-id*, its *conversion-type-id* is first looked up in the class of the object expression and the name, if found, is used. Otherwise it is looked up in the context of the entire *postfix-expression*. In each of these lookups, only names that denote types or templates whose specializations are types are considered. [Example:

```
struct A { };
namespace N {
    struct A {
        void g() { }
        template <class T> operator T();
    };
}

int main() {
    N::A a;
    a.operator A();           // calls N::A::operator N::A
}
```

— end example]

6.4.6 Using-directives and namespace aliases

[basic.lookup.udir]

- ¹ In a *using-directive* or *namespace-alias-definition*, during the lookup for a *namespace-name* or for a name in a *nested-name-specifier* only namespace names are considered.

6.5 Program and linkage

[basic.link]

- ¹ A *program* consists of one or more *translation units* (Clause 5) linked together. A translation unit consists of a sequence of declarations.

translation-unit:
declaration-seq_{opt}

- ² A name is said to have *linkage* when it might denote the same object, reference, function, type, template, namespace or value as a name introduced by a declaration in another scope:
- (2.1) — When a name has *external linkage*, the entity it denotes can be referred to by names from scopes of other translation units or from other scopes of the same translation unit.
 - (2.2) — When a name has *internal linkage*, the entity it denotes can be referred to by names from other scopes in the same translation unit.
 - (2.3) — When a name has *no linkage*, the entity it denotes cannot be referred to by names from other scopes.
- ³ A name having namespace scope (6.3.6) has internal linkage if it is the name of

- (3.1) — a variable, function or function template that is explicitly declared **static**; or,
 - (3.2) — a non-inline variable of non-volatile const-qualified type that is neither explicitly declared **extern** nor previously declared to have external linkage; or
 - (3.3) — a data member of an anonymous union.
- 4 An unnamed namespace or a namespace declared directly or indirectly within an unnamed namespace has internal linkage. All other namespaces have external linkage. A name having namespace scope that has not been given internal linkage above has the same linkage as the enclosing namespace if it is the name of
- (4.1) — a variable; or
 - (4.2) — a function; or
 - (4.3) — a named class (Clause 12), or an unnamed class defined in a typedef declaration in which the class has the typedef name for linkage purposes (10.1.3); or
 - (4.4) — a named enumeration (10.2), or an unnamed enumeration defined in a typedef declaration in which the enumeration has the typedef name for linkage purposes (10.1.3); or
 - (4.5) — a template.
- 5 In addition, a member function, static data member, a named class or enumeration of class scope, or an unnamed class or enumeration defined in a class-scope typedef declaration such that the class or enumeration has the typedef name for linkage purposes (10.1.3), has the same linkage, if any, as the name of the class of which it is a member.
- 6 The name of a function declared in block scope and the name of a variable declared by a block scope **extern** declaration have linkage. If there is a visible declaration of an entity with linkage having the same name and type, ignoring entities declared outside the innermost enclosing namespace scope, the block scope declaration declares that same entity and receives the linkage of the previous declaration. If there is more than one such matching entity, the program is ill-formed. Otherwise, if no matching entity is found, the block scope entity receives external linkage. If, within a translation unit, the same entity is declared with both internal and external linkage, the program is ill-formed. [*Example:*

```

static void f();
static int i = 0;           // #1
void g() {
    extern void f();         // internal linkage
    int i;                  // #2: i has no linkage
    {
        extern void f();     // internal linkage
        extern int i;        // #3: external linkage, ill-formed
    }
}

```

Without the declaration at line #2, the declaration at line #3 would link with the declaration at line #1. Because the declaration with internal linkage is hidden, however, #3 is given external linkage, making the program ill-formed. — *end example*]

- 7 When a block scope declaration of an entity with linkage is not found to refer to some other declaration, then that entity is a member of the innermost enclosing namespace. However such a declaration does not introduce the member name in its namespace scope. [*Example:*

```

namespace X {
    void p() {
        q();                // error: q not yet declared
        extern void q();     // q is a member of namespace X
    }
}

```

```

    void middle() {
        q();                                // error: q not yet declared
    }

    void q() { /* ... */ }                 // definition of X::q
}

void q() { /* ... */ }                   // some other, unrelated q
— end example]

```

⁸ Names not covered by these rules have no linkage. Moreover, except as noted, a name declared at block scope (6.3.3) has no linkage. A type is said to have linkage if and only if:

- (8.1) — it is a class or enumeration type that is named (or has a name for linkage purposes (10.1.3)) and the name has linkage; or
- (8.2) — it is an unnamed class or unnamed enumeration that is a member of a class with linkage; or
- (8.3) — it is a specialization of a class template (Clause 17)³⁵; or
- (8.4) — it is a fundamental type (6.9.1); or
- (8.5) — it is a compound type (6.9.2) other than a class or enumeration, compounded exclusively from types that have linkage; or
- (8.6) — it is a cv-qualified (6.9.3) version of a type that has linkage.

A type without linkage shall not be used as the type of a variable or function with external linkage unless

- (8.7) — the entity has C language linkage (10.5), or
- (8.8) — the entity is declared within an unnamed namespace (10.3.1), or
- (8.9) — the entity is not odr-used (6.2) or is defined in the same translation unit.

[*Note:* In other words, a type without linkage contains a class or enumeration that cannot be named outside its translation unit. An entity with external linkage declared using such a type could not correspond to any other entity in another translation unit of the program and thus must be defined in the translation unit if it is odr-used. Also note that classes with linkage may contain members whose types do not have linkage, and that typedef names are ignored in the determination of whether a type has linkage. — end note]

[*Example:*

```

template <class T> struct B {
    void g(T) { }
    void h(T);
    friend void i(B, T) { }
};

void f() {
    struct A { int x; }; // no linkage
    A a = { 1 };
    B<A> ba;              // declares B<A>::g(A) and B<A>::h(A)
    ba.g(a);              // OK
    ba.h(a);              // error: B<A>::h(A) not defined in the translation unit
    i(ba, a);             // OK
}
— end example]

```

³⁵) A class template has the linkage of the innermost enclosing class or namespace in which it is declared.

- 9 Two names that are the same (Clause 6) and that are declared in different scopes shall denote the same variable, function, type, template or namespace if
- (9.1) — both names have external linkage or else both names have internal linkage and are declared in the same translation unit; and
 - (9.2) — both names refer to members of the same namespace or to members, not by inheritance, of the same class; and
 - (9.3) — when both names denote functions, the parameter-type-lists of the functions (11.3.5) are identical; and
 - (9.4) — when both names denote function templates, the signatures (17.5.6.1) are the same.
- 10 After all adjustments of types (during which typedefs (10.1.3) are replaced by their definitions), the types specified by all declarations referring to a given variable or function shall be identical, except that declarations for an array object can specify array types that differ by the presence or absence of a major array bound (11.3.4). A violation of this rule on type identity does not require a diagnostic.
- 11 [*Note*: Linkage to non-C++ declarations can be achieved using a *linkage-specification* (10.5). — *end note*]

6.6 Start and termination

[basic.start]

6.6.1 main function

[basic.start.main]

- 1 A program shall contain a global function called **main**. Executing a program starts a main thread of execution (4.7, 33.3) in which the **main** function is invoked, and in which variables of static storage duration might be initialized (6.6.2) and destroyed (6.6.4). It is implementation-defined whether a program in a freestanding environment is required to define a **main** function. [*Note*: In a freestanding environment, start-up and termination is implementation-defined; start-up contains the execution of constructors for objects of namespace scope with static storage duration; termination contains the execution of destructors for objects with static storage duration. — *end note*]
- 2 An implementation shall not predefine the **main** function. This function shall not be overloaded. Its type shall have C++ language linkage and it shall have a declared return type of type **int**, but otherwise its type is implementation-defined. An implementation shall allow both
- (2.1) — a function of () returning **int** and
 - (2.2) — a function of (**int**, pointer to pointer to **char**) returning **int**
- as the type of **main** (11.3.5). In the latter form, for purposes of exposition, the first function parameter is called **argc** and the second function parameter is called **argv**, where **argc** shall be the number of arguments passed to the program from the environment in which the program is run. If **argc** is nonzero these arguments shall be supplied in **argv**[0] through **argv**[**argc**-1] as pointers to the initial characters of null-terminated multibyte strings (NTMBS s) (20.4.2.1.5.2) and **argv**[0] shall be the pointer to the initial character of a NTMBS that represents the name used to invoke the program or "". The value of **argc** shall be non-negative. The value of **argv**[**argc**] shall be 0. [*Note*: It is recommended that any further (optional) parameters be added after **argv**. — *end note*]
- 3 The function **main** shall not be used within a program. The linkage (6.5) of **main** is implementation-defined. A program that defines **main** as deleted or that declares **main** to be **inline**, **static**, or **constexpr** is ill-formed. The **main** function shall not be declared with a *linkage-specification* (10.5). A program that declares a variable **main** at global scope or that declares the name **main** with C language linkage (in any namespace) is ill-formed. The name **main** is not otherwise reserved. [*Example*: Member functions, classes, and enumerations can be called **main**, as can entities in other namespaces. — *end example*]
- 4 Terminating the program without leaving the current block (e.g., by calling the function **std::exit**(**int**) (21.5)) does not destroy any objects with automatic storage duration (15.4). If **std::exit** is called to end a program during the destruction of an object with static or thread storage duration, the program has undefined behavior.

- ⁵ A return statement in `main` has the effect of leaving the main function (destroying any objects with automatic storage duration) and calling `std::exit` with the return value as the argument. If control flows off the end of the *compound-statement* of `main`, the effect is equivalent to a `return` with operand 0 (see also 18.3).

6.6.2 Static initialization

[basic.start.static]

- ¹ Variables with static storage duration are initialized as a consequence of program initiation. Variables with thread storage duration are initialized as a consequence of thread execution. Within each of these phases of initiation, initialization occurs as follows.
- ² A *constant initializer* for a variable or temporary object `o` is an initializer whose full-expression is a constant expression, except that if `o` is an object, such an initializer may also invoke `constexpr` constructors for `o` and its subobjects even if those objects are of non-literal class types. [Note: Such a class may have a non-trivial destructor. — end note] *Constant initialization* is performed if a variable or temporary object with static or thread storage duration is initialized by a constant initializer for the entity. If constant initialization is not performed, a variable with static storage duration (6.7.1) or thread storage duration (6.7.2) is zero-initialized (11.6). Together, zero-initialization and constant initialization are called *static initialization*; all other initialization is *dynamic initialization*. All static initialization strongly happens before (4.7.1) any dynamic initialization. [Note: The dynamic initialization of non-local variables is described in 6.6.3; that of local static variables is described in 9.7. — end note]
- ³ An implementation is permitted to perform the initialization of a variable with static or thread storage duration as a static initialization even if such initialization is not required to be done statically, provided that
- (3.1) — the dynamic version of the initialization does not change the value of any other object of static or thread storage duration prior to its initialization, and
 - (3.2) — the static version of the initialization produces the same value in the initialized variable as would be produced by the dynamic initialization if all variables not required to be initialized statically were initialized dynamically.

[Note: As a consequence, if the initialization of an object `obj1` refers to an object `obj2` of namespace scope potentially requiring dynamic initialization and defined later in the same translation unit, it is unspecified whether the value of `obj2` used will be the value of the fully initialized `obj2` (because `obj2` was statically initialized) or will be the value of `obj2` merely zero-initialized. For example,

```
inline double fd() { return 1.0; }
extern double d1;
double d2 = d1;      // unspecified:
                     // may be statically initialized to 0.0 or
                     // dynamically initialized to 0.0 if d1 is
                     // dynamically initialized, or 1.0 otherwise
double d1 = fd();    // may be initialized statically or dynamically to 1.0
```

— end note]

6.6.3 Dynamic initialization of non-local variables

[basic.start.dynamic]

- ¹ Dynamic initialization of a non-local variable with static storage duration is unordered if the variable is an implicitly or explicitly instantiated specialization, is partially-ordered if the variable is an inline variable that is not an implicitly or explicitly instantiated specialization, and otherwise is ordered. [Note: An explicitly specialized non-inline static data member or variable template specialization has ordered initialization. — end note]
- ² Dynamic initialization of non-local variables `V` and `W` with static storage duration are ordered as follows:
- (2.1) — If `V` and `W` have ordered initialization and `V` is defined before `W` within a single translation unit, the initialization of `V` is sequenced before the initialization of `W`.

- (2.2) — If **V** has partially-ordered initialization, **W** does not have unordered initialization, and **V** is defined before **W** in every translation unit in which **W** is defined, then
 - (2.2.1) — if the program starts a thread (4.7) other than the main thread (6.6.1), the initialization of **V** strongly happens before the initialization of **W**;
 - (2.2.2) — otherwise, the initialization of **V** is sequenced before the initialization of **W**.
- (2.3) — Otherwise, if the program starts a thread other than the main thread before either **V** or **W** is initialized, it is unspecified in which threads the initializations of **V** and **W** occur; the initializations are unsequenced if they occur in the same thread.
- (2.4) — Otherwise, the initializations of **V** and **W** are indeterminately sequenced.

[*Note*: This definition permits initialization of a sequence of ordered variables concurrently with another sequence. — *end note*]

³ A *non-initialization odr-use* is an odr-use (6.2) not caused directly or indirectly by the initialization of a non-local static or thread storage duration variable.

⁴ It is implementation-defined whether the dynamic initialization of a non-local non-inline variable with static storage duration is sequenced before the first statement of **main** or is deferred. If it is deferred, it strongly happens before any non-initialization odr-use of any non-inline function or non-inline variable defined in the same translation unit as the variable to be initialized.³⁶ It is implementation-defined in which threads and at which points in the program such deferred dynamic initialization occurs. [*Note*: Such points should be chosen in a way that allows the programmer to avoid deadlocks. — *end note*] [*Example*:

```
// - File 1 -
#include "a.h"
#include "b.h"
B b;
A::A(){
    b.Use();
}
```

```
// - File 2 -
#include "a.h"
A a;
```

```
// - File 3 -
#include "a.h"
#include "b.h"
extern A a;
extern B b;
```

```
int main() {
    a.Use();
    b.Use();
}
```

It is implementation-defined whether either **a** or **b** is initialized before **main** is entered or whether the initializations are delayed until **a** is first odr-used in **main**. In particular, if **a** is initialized before **main** is entered, it is not guaranteed that **b** will be initialized before it is odr-used by the initialization of **a**, that is, before **A::A** is called. If, however, **a** is initialized at some point after the first statement of **main**, **b** will be initialized prior to its use in **A::A**. — *end example*]

³⁶ A non-local variable with static storage duration having initialization with side effects is initialized in this case, even if it is not itself odr-used (6.2, 6.7.1).

- 5 It is implementation-defined whether the dynamic initialization of a non-local inline variable with static storage duration is sequenced before the first statement of `main` or is deferred. If it is deferred, it strongly happens before any non-initialization odr-use of that variable. It is implementation-defined in which threads and at which points in the program such deferred dynamic initialization occurs.
- 6 It is implementation-defined whether the dynamic initialization of a non-local non-inline variable with thread storage duration is sequenced before the first statement of the initial function of a thread or is deferred. If it is deferred, the initialization associated with the entity for thread *t* is sequenced before the first non-initialization odr-use by *t* of any non-inline variable with thread storage duration defined in the same translation unit as the variable to be initialized. It is implementation-defined in which threads and at which points in the program such deferred dynamic initialization occurs.
- 7 If the initialization of a non-local variable with static or thread storage duration exits via an exception, `std::terminate` is called (18.5.1).

6.6.4 Termination

[**basic.start.term**]

- 1 Destructors (15.4) for initialized objects (that is, objects whose lifetime (6.8) has begun) with static storage duration, and functions registered with `std::atexit`, are called as part of a call to `std::exit` (21.5). The call to `std::exit` is sequenced before the invocations of the destructors and the registered functions. [*Note*: Returning from `main` invokes `std::exit` (6.6.1). — *end note*]
- 2 Destructors for initialized objects with thread storage duration within a given thread are called as a result of returning from the initial function of that thread and as a result of that thread calling `std::exit`. The completions of the destructors for all initialized objects with thread storage duration within that thread strongly happen before the initiation of the destructors of any object with static storage duration.
- 3 If the completion of the constructor or dynamic initialization of an object with static storage duration strongly happens before that of another, the completion of the destructor of the second is sequenced before the initiation of the destructor of the first. If the completion of the constructor or dynamic initialization of an object with thread storage duration is sequenced before that of another, the completion of the destructor of the second is sequenced before the initiation of the destructor of the first. If an object is initialized statically, the object is destroyed in the same order as if the object was dynamically initialized. For an object of array or class type, all subobjects of that object are destroyed before any block-scope object with static storage duration initialized during the construction of the subobjects is destroyed. If the destruction of an object with static or thread storage duration exits via an exception, `std::terminate` is called (18.5.1).
- 4 If a function contains a block-scope object of static or thread storage duration that has been destroyed and the function is called during the destruction of an object with static or thread storage duration, the program has undefined behavior if the flow of control passes through the definition of the previously destroyed block-scope object. Likewise, the behavior is undefined if the block-scope object is used indirectly (i.e., through a pointer) after its destruction.
- 5 If the completion of the initialization of an object with static storage duration strongly happens before a call to `std::atexit` (see <cstdlib>, 21.5), the call to the function passed to `std::atexit` is sequenced before the call to the destructor for the object. If a call to `std::atexit` strongly happens before the completion of the initialization of an object with static storage duration, the call to the destructor for the object is sequenced before the call to the function passed to `std::atexit`. If a call to `std::atexit` strongly happens before another call to `std::atexit`, the call to the function passed to the second `std::atexit` call is sequenced before the call to the function passed to the first `std::atexit` call.
- 6 If there is a use of a standard library object or function not permitted within signal handlers (21.10) that does not happen before (4.7) completion of destruction of objects with static storage duration and execution of `std::atexit` registered functions (21.5), the program has undefined behavior. [*Note*: If there is a use of an object with static storage duration that does not happen before the object's destruction, the program has undefined behavior. Terminating every thread before a call to `std::exit` or the exit from `main` is

sufficient, but not necessary, to satisfy these requirements. These requirements permit thread managers as static-storage-duration objects. — *end note*]

- ⁷ Calling the function `std::abort()` declared in `<cstdlib>` terminates the program without executing any destructors and without calling the functions passed to `std::atexit()` or `std::at_quick_exit()`.

6.7 Storage duration

[basic.stc]

- ¹ The *storage duration* is the property of an object that defines the minimum potential lifetime of the storage containing the object. The storage duration is determined by the construct used to create the object and is one of the following:
- (1.1) — static storage duration
 - (1.2) — thread storage duration
 - (1.3) — automatic storage duration
 - (1.4) — dynamic storage duration
- ² Static, thread, and automatic storage durations are associated with objects introduced by declarations (6.1) and implicitly created by the implementation (15.2). The dynamic storage duration is associated with objects created by a *new-expression* (8.3.4).
- ³ The storage duration categories apply to references as well.
- ⁴ When the end of the duration of a region of storage is reached, the values of all pointers representing the address of any part of that region of storage become invalid pointer values (6.9.2). Indirection through an invalid pointer value and passing an invalid pointer value to a deallocation function have undefined behavior. Any other use of an invalid pointer value has implementation-defined behavior.³⁷

6.7.1 Static storage duration

[basic.stc.static]

- ¹ All variables which do not have dynamic storage duration, do not have thread storage duration, and are not local have *static storage duration*. The storage for these entities shall last for the duration of the program (6.6.2, 6.6.4).
- ² If a variable with static storage duration has initialization or a destructor with side effects, it shall not be eliminated even if it appears to be unused, except that a class object or its copy/move may be eliminated as specified in 15.8.
- ³ The keyword `static` can be used to declare a local variable with static storage duration. [*Note*: 9.7 describes the initialization of local `static` variables; 6.6.4 describes the destruction of local `static` variables. — *end note*]
- ⁴ The keyword `static` applied to a class data member in a class definition gives the data member static storage duration.

6.7.2 Thread storage duration

[basic.stc.thread]

- ¹ All variables declared with the `thread_local` keyword have *thread storage duration*. The storage for these entities shall last for the duration of the thread in which they are created. There is a distinct object or reference per thread, and use of the declared name refers to the entity associated with the current thread.
- ² A variable with thread storage duration shall be initialized before its first odr-use (6.2) and, if constructed, shall be destroyed on thread exit.

³⁷) Some implementations might define that copying an invalid pointer value causes a system-generated runtime fault.

6.7.3 Automatic storage duration

[basic.stc.auto]

- ¹ Block-scope variables not explicitly declared **static**, **thread_local**, or **extern** have *automatic storage duration*. The storage for these entities lasts until the block in which they are created exits.
- ² [*Note*: These variables are initialized and destroyed as described in 9.7. — *end note*]
- ³ If a variable with automatic storage duration has initialization or a destructor with side effects, an implementation shall not destroy it before the end of its block nor eliminate it as an optimization, even if it appears to be unused, except that a class object or its copy/move may be eliminated as specified in 15.8.

6.7.4 Dynamic storage duration

[basic.stc.dynamic]

- ¹ Objects can be created dynamically during program execution (4.6), using *new-expressions* (8.3.4), and destroyed using *delete-expressions* (8.3.5). A C++ implementation provides access to, and management of, dynamic storage via the global *allocation functions* **operator new** and **operator new[]** and the global *deallocation functions* **operator delete** and **operator delete[]**. [*Note*: The non-allocating forms described in 21.6.2.3 do not perform allocation or deallocation. — *end note*]
- ² The library provides default definitions for the global allocation and deallocation functions. Some global allocation and deallocation functions are replaceable (21.6.2). A C++ program shall provide at most one definition of a replaceable allocation or deallocation function. Any such function definition replaces the default version provided in the library (20.5.4.6). The following allocation and deallocation functions (21.6) are implicitly declared in global scope in each translation unit of a program.

```

void* operator new(std::size_t);
void* operator new(std::size_t, std::align_val_t);

void operator delete(void*) noexcept;
void operator delete(void*, std::size_t) noexcept;
void operator delete(void*, std::align_val_t) noexcept;
void operator delete(void*, std::size_t, std::align_val_t) noexcept;

void* operator new[](std::size_t);
void* operator new[](std::size_t, std::align_val_t);

void operator delete[](void*) noexcept;
void operator delete[](void*, std::size_t) noexcept;
void operator delete[](void*, std::align_val_t) noexcept;
void operator delete[](void*, std::size_t, std::align_val_t) noexcept;

```

These implicit declarations introduce only the function names **operator new**, **operator new[]**, **operator delete**, and **operator delete[]**. [*Note*: The implicit declarations do not introduce the names **std**, **std::size_t**, **std::align_val_t**, or any other names that the library uses to declare these names. Thus, a *new-expression*, *delete-expression* or function call that refers to one of these functions without including the header `<new>` is well-formed. However, referring to **std** or **std::size_t** or **std::align_val_t** is ill-formed unless the name has been declared by including the appropriate header. — *end note*] Allocation and/or deallocation functions may also be declared and defined for any class (15.5).

- ³ Any allocation and/or deallocation functions defined in a C++ program, including the default versions in the library, shall conform to the semantics specified in 6.7.4.1 and 6.7.4.2.

6.7.4.1 Allocation functions

[basic.stc.dynamic.allocation]

- ¹ An allocation function shall be a class member function or a global function; a program is ill-formed if an allocation function is declared in a namespace scope other than global scope or declared static in global scope. The return type shall be **void***. The first parameter shall have type **std::size_t** (21.2). The first parameter shall not have an associated default argument (11.3.6). The value of the first parameter shall be

interpreted as the requested size of the allocation. An allocation function can be a function template. Such a template shall declare its return type and first parameter as specified above (that is, template parameter types shall not be used in the return type and first parameter type). Template allocation functions shall have two or more parameters.

- ² The allocation function attempts to allocate the requested amount of storage. If it is successful, it shall return the address of the start of a block of storage whose length in bytes shall be at least as large as the requested size. There are no constraints on the contents of the allocated storage on return from the allocation function. The order, contiguity, and initial value of storage allocated by successive calls to an allocation function are unspecified. The pointer returned shall be suitably aligned so that it can be converted to a pointer to any suitable complete object type (21.6.2.1) and then used to access the object or array in the storage allocated (until the storage is explicitly deallocated by a call to a corresponding deallocation function). Even if the size of the space requested is zero, the request can fail. If the request succeeds, the value returned shall be a non-null pointer value (7.11) `p0` different from any previously returned value `p1`, unless that value `p1` was subsequently passed to an `operator delete`. Furthermore, for the library allocation functions in 21.6.2.1 and 21.6.2.2, `p0` shall represent the address of a block of storage disjoint from the storage for any other object accessible to the caller. The effect of indirecting through a pointer returned as a request for zero size is undefined.³⁸
- ³ An allocation function that fails to allocate storage can invoke the currently installed new-handler function (21.6.3.3), if any. [*Note:* A program-supplied allocation function can obtain the address of the currently installed `new_handler` using the `std::get_new_handler` function (21.6.3.4). — *end note*] If an allocation function that has a non-throwing exception specification (18.4) fails to allocate storage, it shall return a null pointer. Any other allocation function that fails to allocate storage shall indicate failure only by throwing an exception (18.1) of a type that would match a handler (18.3) of type `std::bad_alloc` (21.6.3.1).
- ⁴ A global allocation function is only called as the result of a new expression (8.3.4), or called directly using the function call syntax (8.2.2), or called indirectly through calls to the functions in the C++ standard library. [*Note:* In particular, a global allocation function is not called to allocate storage for objects with static storage duration (6.7.1), for objects or references with thread storage duration (6.7.2), for objects of type `std::type_info` (8.2.8), or for an exception object (18.1). — *end note*]

6.7.4.2 Deallocation functions

[**basic.stc.dynamic.deallocation**]

- ¹ Deallocation functions shall be class member functions or global functions; a program is ill-formed if deallocation functions are declared in a namespace scope other than global scope or declared static in global scope.
- ² Each deallocation function shall return `void` and its first parameter shall be `void*`. A deallocation function may have more than one parameter. A *usual deallocation function* is a deallocation function that has:
 - (2.1) — exactly one parameter; or
 - (2.2) — exactly two parameters, the type of the second being either `std::align_val_t` or `std::size_t`³⁹; or
 - (2.3) — exactly three parameters, the type of the second being `std::size_t` and the type of the third being `std::align_val_t`.

A deallocation function may be an instance of a function template. Neither the first parameter nor the return type shall depend on a template parameter. [*Note:* That is, a deallocation function template shall have a first parameter of type `void*` and a return type of `void` (as specified above). — *end note*] A deallocation function template shall have two or more function parameters. A template instance is never a usual deallocation function, regardless of its signature.

³⁸) The intent is to have `operator new()` implementable by calling `std::malloc()` or `std::calloc()`, so the rules are substantially the same. C++ differs from C in requiring a zero request to return a non-null pointer.

³⁹) The global `operator delete(void*, std::size_t)` precludes use of an allocation function `void operator new(std::size_t, std::size_t)` as a placement allocation function (C.3.2).

- 3 If a deallocation function terminates by throwing an exception, the behavior is undefined. The value of the first argument supplied to a deallocation function may be a null pointer value; if so, and if the deallocation function is one supplied in the standard library, the call has no effect.
- 4 If the argument given to a deallocation function in the standard library is a pointer that is not the null pointer value (7.11), the deallocation function shall deallocate the storage referenced by the pointer, ending the duration of the region of storage.

6.7.4.3 Safely-derived pointers

[basic.stc.dynamic.safety]

- 1 A *traceable pointer object* is

- (1.1) — an object of an object pointer type (6.9.2), or
- (1.2) — an object of an integral type that is at least as large as `std::intptr_t`, or
- (1.3) — a sequence of elements in an array of narrow character type (6.9.1), where the size and alignment of the sequence match those of some object pointer type.

- 2 A pointer value is a *safely-derived pointer* to a dynamic object only if it has an object pointer type and it is one of the following:

- (2.1) — the value returned by a call to the C++ standard library implementation of `::operator new(std::size_t)` or `::operator new(std::size_t, std::align_val_t)`;⁴⁰
- (2.2) — the result of taking the address of an object (or one of its subobjects) designated by an lvalue resulting from indirection through a safely-derived pointer value;
- (2.3) — the result of well-defined pointer arithmetic (8.7) using a safely-derived pointer value;
- (2.4) — the result of a well-defined pointer conversion (7.11, 8.4) of a safely-derived pointer value;
- (2.5) — the result of a `reinterpret_cast` of a safely-derived pointer value;
- (2.6) — the result of a `reinterpret_cast` of an integer representation of a safely-derived pointer value;
- (2.7) — the value of an object whose value was copied from a traceable pointer object, where at the time of the copy the source object contained a copy of a safely-derived pointer value.

- 3 An integer value is an *integer representation of a safely-derived pointer* only if its type is at least as large as `std::intptr_t` and it is one of the following:

- (3.1) — the result of a `reinterpret_cast` of a safely-derived pointer value;
- (3.2) — the result of a valid conversion of an integer representation of a safely-derived pointer value;
- (3.3) — the value of an object whose value was copied from a traceable pointer object, where at the time of the copy the source object contained an integer representation of a safely-derived pointer value;
- (3.4) — the result of an additive or bitwise operation, one of whose operands is an integer representation of a safely-derived pointer value P, if that result converted by `reinterpret_cast<void*>` would compare equal to a safely-derived pointer computable from `reinterpret_cast<void*>(P)`.

- 4 An implementation may have *relaxed pointer safety*, in which case the validity of a pointer value does not depend on whether it is a safely-derived pointer value. Alternatively, an implementation may have *strict pointer safety*, in which case a pointer value referring to an object with dynamic storage duration that is not a safely-derived pointer value is an invalid pointer value unless the referenced complete object has previously been declared reachable (23.10.4). [Note: The effect of using an invalid pointer value (including passing it to a deallocation function) is undefined, see 6.7.4.2. This is true even if the unsafely-derived pointer value might

⁴⁰) This section does not impose restrictions on indirection through pointers to memory not allocated by `::operator new`. This maintains the ability of many C++ implementations to use binary libraries and components written in other languages. In particular, this applies to C binaries, because indirection through pointers to memory allocated by `std::malloc` is not restricted.

compare equal to some safely-derived pointer value. — *end note*] It is implementation-defined whether an implementation has relaxed or strict pointer safety.

6.7.5 Duration of subobjects

[basic.stc.inherit]

- ¹ The storage duration of subobjects and reference members is that of their complete object (4.5).

6.8 Object lifetime

[basic.life]

- ¹ The *lifetime* of an object or reference is a runtime property of the object or reference. An object is said to have *non-vacuous initialization* if it is of a class or aggregate type and it or one of its subobjects is initialized by a constructor other than a trivial default constructor. [Note: Initialization by a trivial copy/move constructor is non-vacuous initialization. — *end note*] The lifetime of an object of type T begins when:

- (1.1) — storage with the proper alignment and size for type T is obtained, and
- (1.2) — if the object has non-vacuous initialization, its initialization is complete,

except that if the object is a union member or subobject thereof, its lifetime only begins if that union member is the initialized member in the union (11.6.1, 15.6.2), or as described in 12.3. The lifetime of an object *o* of type T ends when:

- (1.3) — if T is a class type with a non-trivial destructor (15.4), the destructor call starts, or
- (1.4) — the storage which the object occupies is released, or is reused by an object that is not nested within *o* (4.5).

- ² The lifetime of a reference begins when its initialization is complete. The lifetime of a reference ends as if it were a scalar object.

- ³ [Note: 15.6.2 describes the lifetime of base and member subobjects. — *end note*]

- ⁴ The properties ascribed to objects and references throughout this International Standard apply for a given object or reference only during its lifetime. [Note: In particular, before the lifetime of an object starts and after its lifetime ends there are significant restrictions on the use of the object, as described below, in 15.6.2 and in 15.7. Also, the behavior of an object under construction and destruction might not be the same as the behavior of an object whose lifetime has started and not ended. 15.6.2 and 15.7 describe the behavior of objects during the construction and destruction phases. — *end note*]

- ⁵ A program may end the lifetime of any object by reusing the storage which the object occupies or by explicitly calling the destructor for an object of a class type with a non-trivial destructor. For an object of a class type with a non-trivial destructor, the program is not required to call the destructor explicitly before the storage which the object occupies is reused or released; however, if there is no explicit call to the destructor or if a *delete-expression* (8.3.5) is not used to release the storage, the destructor shall not be implicitly called and any program that depends on the side effects produced by the destructor has undefined behavior.

- ⁶ Before the lifetime of an object has started but after the storage which the object will occupy has been allocated⁴¹ or, after the lifetime of an object has ended and before the storage which the object occupied is reused or released, any pointer that represents the address of the storage location where the object will be or was located may be used but only in limited ways. For an object under construction or destruction, see 15.7. Otherwise, such a pointer refers to allocated storage (6.7.4.2), and using the pointer as if the pointer were of type `void*`, is well-defined. Indirection through such a pointer is permitted but the resulting lvalue may only be used in limited ways, as described below. The program has undefined behavior if:

- (6.1) — the object will be or was of a class type with a non-trivial destructor and the pointer is used as the operand of a *delete-expression*,
- (6.2) — the pointer is used to access a non-static data member or call a non-static member function of the object, or

⁴¹) For example, before the construction of a global object of non-POD class type (15.7).

- (6.3) — the pointer is implicitly converted (7.11) to a pointer to a virtual base class, or
- (6.4) — the pointer is used as the operand of a `static_cast` (8.2.9), except when the conversion is to pointer to *cv* void, or to pointer to *cv* void and subsequently to pointer to *cv* char, *cv* unsigned char, or *cv* std::byte (21.2.1), or
- (6.5) — the pointer is used as the operand of a `dynamic_cast` (8.2.7).

[Example:

```
#include <cstdlib>

struct B {
    virtual void f();
    void mutate();
    virtual ~B();
};

struct D1 : B { void f(); };
struct D2 : B { void f(); };

void B::mutate() {
    new (this) D2;    // reuses storage — ends the lifetime of *this
    f();              // undefined behavior
    ... = this;       // OK, this points to valid memory
}

void g() {
    void* p = std::malloc(sizeof(D1) + sizeof(D2));
    B* pb = new (p) D1;
    pb->mutate();
    *pb;              // OK: pb points to valid memory
    void* q = pb;      // OK: pb points to valid memory
    pb->f();           // undefined behavior, lifetime of *pb has ended
}
```

— end example]

- ⁷ Similarly, before the lifetime of an object has started but after the storage which the object will occupy has been allocated or, after the lifetime of an object has ended and before the storage which the object occupied is reused or released, any glvalue that refers to the original object may be used but only in limited ways. For an object under construction or destruction, see 15.7. Otherwise, such a glvalue refers to allocated storage (6.7.4.2), and using the properties of the glvalue that do not depend on its value is well-defined. The program has undefined behavior if:
 - (7.1) — the glvalue is used to access the object, or
 - (7.2) — the glvalue is used to call a non-static member function of the object, or
 - (7.3) — the glvalue is bound to a reference to a virtual base class (11.6.3), or
 - (7.4) — the glvalue is used as the operand of a `dynamic_cast` (8.2.7) or as the operand of `typeid`.
- ⁸ If, after the lifetime of an object has ended and before the storage which the object occupied is reused or released, a new object is created at the storage location which the original object occupied, a pointer that pointed to the original object, a reference that referred to the original object, or the name of the original object will automatically refer to the new object and, once the lifetime of the new object has started, can be used to manipulate the new object, if:
 - (8.1) — the storage for the new object exactly overlays the storage location which the original object occupied,

and

- (8.2) — the new object is of the same type as the original object (ignoring the top-level cv-qualifiers), and
- (8.3) — the type of the original object is not const-qualified, and, if a class type, does not contain any non-static data member whose type is const-qualified or a reference type, and
- (8.4) — the original object was a most derived object (4.5) of type T and the new object is a most derived object of type T (that is, they are not base class subobjects).

[*Example:*

```
struct C {
    int i;
    void f();
    const C& operator=( const C& );
};

const C& C::operator=( const C& other) {
    if ( this != &other ) {
        this->~C();           // lifetime of *this ends
        new (this) C(other);  // new object of type C created
        f();                  // well-defined
    }
    return *this;
}

C c1;
C c2;
c1 = c2;                      // well-defined
c1.f();                       // well-defined; c1 refers to a new object of type C
```

— *end example*] [Note: If these conditions are not met, a pointer to the new object can be obtained from a pointer that represents the address of its storage by calling `std::launder` (21.6). — *end note*]

- 9 If a program ends the lifetime of an object of type T with static (6.7.1), thread (6.7.2), or automatic (6.7.3) storage duration and if T has a non-trivial destructor,⁴² the program must ensure that an object of the original type occupies that same storage location when the implicit destructor call takes place; otherwise the behavior of the program is undefined. This is true even if the block is exited with an exception. [*Example:*

```
class T { };
struct B {
    ~B();
};

void h() {
    B b;
    new (&b) T;
}                                     // undefined behavior at block exit
```

— *end example*]

- 10 Creating a new object within the storage that a `const` complete object with static, thread, or automatic storage duration occupies, or within the storage that such a `const` object used to occupy before its lifetime ended, results in undefined behavior. [*Example:*

```
struct B {
```

42) That is, an object for which a destructor will be called implicitly—upon exit from the block for an object with automatic storage duration, upon exit from the thread for an object with thread storage duration, or upon exit from the program for an object with static storage duration.

```

    B();
    ~B();
};

const B b;

void h() {
    b.~B();
    new (const_cast<B*>(&b)) const B;    // undefined behavior
}

```

— end example]

- ¹¹ In this section, “before” and “after” refer to the “happens before” relation (4.7). [*Note*: Therefore, undefined behavior results if an object that is being constructed in one thread is referenced from another thread without adequate synchronization. — end note]

6.9 Types

[basic.types]

- ¹ [*Note*: 6.9 and the subclauses thereof impose requirements on implementations regarding the representation of types. There are two kinds of types: fundamental types and compound types. Types describe objects (4.5), references (11.3.2), or functions (11.3.5). — end note]
- ² For any object (other than a base-class subobject) of trivially copyable type *T*, whether or not the object holds a valid value of type *T*, the underlying bytes (4.4) making up the object can be copied into an array of `char`, `unsigned char`, or `std::byte` (21.2.1).⁴³ If the content of that array is copied back into the object, the object shall subsequently hold its original value. [*Example*:

```

#define N sizeof(T)
char buf[N];
T obj;                // obj initialized to its original value
std::memcpy(buf, &obj, N);    // between these two calls to std::memcpy, obj might be modified
std::memcpy(&obj, buf, N);    // at this point, each subobject of obj of scalar type holds its original value

```

— end example]

- ³ For any trivially copyable type *T*, if two pointers to *T* point to distinct *T* objects *obj1* and *obj2*, where neither *obj1* nor *obj2* is a base-class subobject, if the underlying bytes (4.4) making up *obj1* are copied into *obj2*,⁴⁴ *obj2* shall subsequently hold the same value as *obj1*. [*Example*:

```

T* t1p;
T* t2p;
    // provided that t2p points to an initialized object ...
std::memcpy(t1p, t2p, sizeof(T));
    // at this point, every subobject of trivially copyable type in *t1p contains
    // the same value as the corresponding subobject in *t2p

```

— end example]

- ⁴ The *object representation* of an object of type *T* is the sequence of *N* `unsigned char` objects taken up by the object of type *T*, where *N* equals `sizeof(T)`. The *value representation* of an object is the set of bits that hold the value of type *T*. For trivially copyable types, the value representation is a set of bits in the object representation that determines a *value*, which is one discrete element of an implementation-defined set of values.⁴⁵
- ⁵ A class that has been declared but not defined, an enumeration type in certain contexts (10.2), or an array of

⁴³ By using, for example, the library functions (20.5.1.2) `std::memcpy` or `std::memmove`.

⁴⁴ By using, for example, the library functions (20.5.1.2) `std::memcpy` or `std::memmove`.

⁴⁵ The intent is that the memory model of C++ is compatible with that of ISO/IEC 9899 Programming Language C.

unknown bound or of incomplete element type, is an *incompletely-defined object type*.⁴⁶ Incompletely-defined object types and *cv void* are *incomplete types* (6.9.1). Objects shall not be defined to have an incomplete type.

- ⁶ A class type (such as “`class X`”) might be incomplete at one point in a translation unit and complete later on; the type “`class X`” is the same type at both points. The declared type of an array object might be an array of incomplete class type and therefore incomplete; if the class type is completed later on in the translation unit, the array type becomes complete; the array type at those two points is the same type. The declared type of an array object might be an array of unknown bound and therefore be incomplete at one point in a translation unit and complete later on; the array types at those two points (“array of unknown bound of `T`” and “array of `N T`”) are different types. The type of a pointer to array of unknown bound, or of a type defined by a `typedef` declaration to be an array of unknown bound, cannot be completed. [*Example:*

```
class X;                                // X is an incomplete type
extern X* xp;                           // xp is a pointer to an incomplete type
extern int arr[];                       // the type of arr is incomplete
typedef int UNKA[];                    // UNKA is an incomplete type
UNKA* arrp;                             // arrp is a pointer to an incomplete type
UNKA** arrpp;

void foo() {
    xp++;                               // ill-formed: X is incomplete
    arrp++;                             // ill-formed: incomplete type
    arrpp++;                            // OK: sizeof UNKA* is known
}

struct X { int i; };                   // now X is a complete type
int arr[10];                           // now the type of arr is complete

X x;
void bar() {
    xp = &x;                           // OK; type is “pointer to X”
    arrp = &arr;                        // ill-formed: different types
    xp++;                               // OK: X is complete
    arrp++;                             // ill-formed: UNKA can't be completed
}
```

— end example]

- ⁷ [*Note:* The rules for declarations and expressions describe in which contexts incomplete types are prohibited. — end note]
- ⁸ An *object type* is a (possibly *cv*-qualified) type that is not a function type, not a reference type, and not *cv void*.
- ⁹ Arithmetic types (6.9.1), enumeration types, pointer types, pointer to member types (6.9.2), `std::nullptr_t`, and *cv*-qualified (6.9.3) versions of these types are collectively called *scalar types*. Scalar types, POD classes (Clause 12), arrays of such types and *cv*-qualified versions of these types are collectively called *POD types*. *Cv*-unqualified scalar types, trivially copyable class types (Clause 12), arrays of such types, and *cv*-qualified versions of these types are collectively called *trivially copyable types*. Scalar types, trivial class types (Clause 12), arrays of such types and *cv*-qualified versions of these types are collectively called *trivial types*. Scalar types, standard-layout class types (Clause 12), arrays of such types and *cv*-qualified versions of these types are collectively called *standard-layout types*.
- ¹⁰ A type is a *literal type* if it is:

⁴⁶ The size and layout of an instance of an incompletely-defined object type is unknown.

- (10.1) — possibly cv-qualified `void`; or
- (10.2) — a scalar type; or
- (10.3) — a reference type; or
- (10.4) — an array of literal type; or
- (10.5) — a possibly cv-qualified class type (Clause 12) that has all of the following properties:
 - (10.5.1) — it has a trivial destructor,
 - (10.5.2) — it is either a closure type (8.1.5.1), an aggregate type (11.6.1), or has at least one constexpr constructor or constructor template (possibly inherited (10.3.3) from a base class) that is not a copy or move constructor,
 - (10.5.3) — if it is a union, at least one of its non-static data members is of non-volatile literal type, and
 - (10.5.4) — if it is not a union, all of its non-static data members and base classes are of non-volatile literal types.

[*Note:* A literal type is one for which it might be possible to create an object within a constant expression. It is not a guarantee that it is possible to create such an object, nor is it a guarantee that any object of that type will usable in a constant expression. — *end note*]

- 11 Two types *cv1* T1 and *cv2* T2 are *layout-compatible* types if T1 and T2 are the same type, layout-compatible enumerations (10.2), or layout-compatible standard-layout class types (12.2).

6.9.1 Fundamental types

[basic.fundamental]

- 1 Objects declared as characters (`char`) shall be large enough to store any member of the implementation's basic character set. If a character from this set is stored in a character object, the integral value of that character object is equal to the value of the single character literal form of that character. It is implementation-defined whether a `char` object can hold negative values. Characters can be explicitly declared `unsigned` or `signed`. Plain `char`, `signed char`, and `unsigned char` are three distinct types, collectively called *narrow character types*. A `char`, a `signed char`, and an `unsigned char` occupy the same amount of storage and have the same alignment requirements (6.11); that is, they have the same object representation. For narrow character types, all bits of the object representation participate in the value representation. [*Note:* A bit-field of narrow character type whose length is larger than the number of bits in the object representation of that type has padding bits; see 12.2.4. — *end note*] For unsigned narrow character types, each possible bit pattern of the value representation represents a distinct number. These requirements do not hold for other types. In any particular implementation, a plain `char` object can take on either the same values as a `signed char` or an `unsigned char`; which one is implementation-defined. For each value *i* of type `unsigned char` in the range 0 to 255 inclusive, there exists a value *j* of type `char` such that the result of an integral conversion (7.8) from *i* to `char` is *j*, and the result of an integral conversion from *j* to `unsigned char` is *i*.
- 2 There are five *standard signed integer types*: “`signed char`”, “`short int`”, “`int`”, “`long int`”, and “`long long int`”. In this list, each type provides at least as much storage as those preceding it in the list. There may also be implementation-defined *extended signed integer types*. The standard and extended signed integer types are collectively called *signed integer types*. Plain `ints` have the natural size suggested by the architecture of the execution environment⁴⁷; the other signed integer types are provided to meet special needs.
- 3 For each of the standard signed integer types, there exists a corresponding (but different) *standard unsigned integer type*: “`unsigned char`”, “`unsigned short int`”, “`unsigned int`”, “`unsigned long int`”, and “`unsigned long long int`”, each of which occupies the same amount of storage and has the same alignment requirements (6.11) as the corresponding signed integer type⁴⁸; that is, each signed integer type has the same object representation as its corresponding unsigned integer type. Likewise, for each of the extended

⁴⁷ `int` must also be large enough to contain any value in the range [INT_MIN, INT_MAX], as defined in the header <limits>.

⁴⁸ See 10.1.7.2 regarding the correspondence between types and the sequences of *type-specifiers* that designate them.

signed integer types there exists a corresponding *extended unsigned integer type* with the same amount of storage and alignment requirements. The standard and extended unsigned integer types are collectively called *unsigned integer types*. The range of non-negative values of a signed integer type is a subrange of the corresponding unsigned integer type, the representation of the same value in each of the two types is the same, and the value representation of each corresponding signed/unsigned type shall be the same. The standard signed integer types and standard unsigned integer types are collectively called the *standard integer types*, and the extended signed integer types and extended unsigned integer types are collectively called the *extended integer types*. The signed and unsigned integer types shall satisfy the constraints given in the C standard, section 5.2.4.2.1.

- ⁴ Unsigned integers shall obey the laws of arithmetic modulo 2^n where n is the number of bits in the value representation of that particular size of integer.⁴⁹
- ⁵ Type `wchar_t` is a distinct type whose values can represent distinct codes for all members of the largest extended character set specified among the supported locales (25.3.1). Type `wchar_t` shall have the same size, signedness, and alignment requirements (6.11) as one of the other integral types, called its *underlying type*. Types `char16_t` and `char32_t` denote distinct types with the same size, signedness, and alignment as `uint_least16_t` and `uint_least32_t`, respectively, in `<stdint>`, called the underlying types.
- ⁶ Values of type `bool` are either `true` or `false`.⁵⁰ [Note: There are no **signed**, **unsigned**, **short**, or **long bool** types or values. — end note] Values of type `bool` participate in integral promotions (7.6).
- ⁷ Types `bool`, `char`, `char16_t`, `char32_t`, `wchar_t`, and the signed and unsigned integer types are collectively called *integral types*.⁵¹ A synonym for integral type is *integer type*. The representations of integral types shall define values by use of a pure binary numeration system.⁵² [Example: This International Standard permits two's complement, ones' complement and signed magnitude representations for integral types. — end example]
- ⁸ There are three *floating-point* types: `float`, `double`, and `long double`. The type `double` provides at least as much precision as `float`, and the type `long double` provides at least as much precision as `double`. The set of values of the type `float` is a subset of the set of values of the type `double`; the set of values of the type `double` is a subset of the set of values of the type `long double`. The value representation of floating-point types is implementation-defined. [Note: This International Standard imposes no requirements on the accuracy of floating-point operations; see also 21.3. — end note] Integral and floating types are collectively called *arithmetic* types. Specializations of the standard library template `std::numeric_limits` (21.3) shall specify the maximum and minimum values of each arithmetic type for an implementation.
- ⁹ A type `cv void` is an incomplete type that cannot be completed; such a type has an empty set of values. It is used as the return type for functions that do not return a value. Any expression can be explicitly converted to type `cv void` (8.4). An expression of type `cv void` shall be used only as an expression statement (9.2), as an operand of a comma expression (8.19), as a second or third operand of `?:` (8.16), as the operand of `typeid`, `noexcept`, or `decltype`, as the expression in a return statement (9.6.3) for a function with the return type `cv void`, or as the operand of an explicit conversion to type `cv void`.
- ¹⁰ A value of type `std::nullptr_t` is a null pointer constant (7.11). Such values participate in the pointer and the pointer to member conversions (7.11, 7.12). `sizeof(std::nullptr_t)` shall be equal to `sizeof(void*)`.
- ¹¹ [Note: Even if the implementation defines two or more basic types to have the same value representation,

49) This implies that unsigned arithmetic does not overflow because a result that cannot be represented by the resulting unsigned integer type is reduced modulo the number that is one greater than the largest value that can be represented by the resulting unsigned integer type.

50) Using a `bool` value in ways described by this International Standard as “undefined”, such as by examining the value of an uninitialized automatic object, might cause it to behave as if it is neither `true` nor `false`.

51) Therefore, enumerations (10.2) are not integral; however, enumerations can be promoted to integral types as specified in 7.6.

52) A positional representation for integers that uses the binary digits 0 and 1, in which the values represented by successive bits are additive, begin with 1, and are multiplied by successive integral power of 2, except perhaps for the bit with the highest position. (Adapted from the *American National Dictionary for Information Processing Systems*.)

they are nevertheless different types. — *end note*]

6.9.2 Compound types

[basic.compound]

¹ Compound types can be constructed in the following ways:

- (1.1) — *arrays* of objects of a given type, 11.3.4;
- (1.2) — *functions*, which have parameters of given types and return `void` or references or objects of a given type, 11.3.5;
- (1.3) — *pointers* to *cv void* or objects or functions (including static members of classes) of a given type, 11.3.1;
- (1.4) — *references* to objects or functions of a given type, 11.3.2. There are two types of references:
 - (1.4.1) — *lvalue reference*
 - (1.4.2) — *rvalue reference*
- (1.5) — *classes* containing a sequence of objects of various types (Clause 12), a set of types, enumerations and functions for manipulating these objects (12.2.1), and a set of restrictions on the access to these entities (Clause 14);
- (1.6) — *unions*, which are classes capable of containing objects of different types at different times, 12.3;
- (1.7) — *enumerations*, which comprise a set of named constant values. Each distinct enumeration constitutes a different *enumerated type*, 10.2;
- (1.8) — *pointers to non-static class members*,⁵³ which identify members of a given type within objects of a given class, 11.3.3.

² These methods of constructing types can be applied recursively; restrictions are mentioned in 11.3.1, 11.3.4, 11.3.5, and 11.3.2. Constructing a type such that the number of bytes in its object representation exceeds the maximum value representable in the type `std::size_t` (21.2) is ill-formed.

³ The type of a pointer to *cv void* or a pointer to an object type is called an *object pointer type*. [*Note*: A pointer to `void` does not have a pointer-to-object type, however, because `void` is not an object type. — *end note*] The type of a pointer that can designate a function is called a *function pointer type*. A pointer to objects of type `T` is referred to as a “pointer to `T`”. [*Example*: A pointer to an object of type `int` is referred to as “pointer to `int`” and a pointer to an object of class `X` is called a “pointer to `X`”. — *end example*] Except for pointers to static members, text referring to “pointers” does not apply to pointers to members. Pointers to incomplete types are allowed although there are restrictions on what can be done with them (6.11). Every value of pointer type is one of the following:

- (3.1) — a *pointer to* an object or function (the pointer is said to *point* to the object or function), or
- (3.2) — a *pointer past the end of* an object (8.7), or
- (3.3) — the *null pointer value* (7.11) for that type, or
- (3.4) — an *invalid pointer value*.

A value of a pointer type that is a pointer to or past the end of an object *represents the address* of the first byte in memory (4.4) occupied by the object⁵⁴ or the first byte in memory after the end of the storage occupied by the object, respectively. [*Note*: A pointer past the end of an object (8.7) is not considered to point to an unrelated object of the object’s type that might be located at that address. A pointer value becomes invalid when the storage it denotes reaches the end of its storage duration; see 6.7. — *end note*] For purposes of pointer arithmetic (8.7) and comparison (8.9, 8.10), a pointer past the end of the last element of an array `x` of *n* elements is considered to be equivalent to a pointer to a hypothetical element `x[n]`. The value representation of pointer types is implementation-defined. Pointers to layout-compatible types shall

⁵³) Static class members are objects or functions, and pointers to them are ordinary pointers to objects or functions.

⁵⁴) For an object that is not within its lifetime, this is the first byte in memory that it will occupy or used to occupy.

have the same value representation and alignment requirements (6.11). [Note: Pointers to over-aligned types (6.11) have no special representation, but their range of valid values is restricted by the extended alignment requirement. — end note]

⁴ Two objects *a* and *b* are *pointer-interconvertible* if:

- (4.1) — they are the same object, or
- (4.2) — one is a standard-layout union object and the other is a non-static data member of that object (12.3), or
- (4.3) — one is a standard-layout class object and the other is the first non-static data member of that object, or, if the object has no non-static data members, the first base class subobject of that object (12.2), or
- (4.4) — there exists an object *c* such that *a* and *c* are pointer-interconvertible, and *c* and *b* are pointer-interconvertible.

If two objects are pointer-interconvertible, then they have the same address, and it is possible to obtain a pointer to one from a pointer to the other via a `reinterpret_cast` (8.2.10). [Note: An array object and its first element are not pointer-interconvertible, even though they have the same address. — end note]

⁵ A pointer to *cv*-qualified (6.9.3) or *cv*-unqualified `void` can be used to point to objects of unknown type. Such a pointer shall be able to hold any object pointer. An object of type *cv* `void*` shall have the same representation and alignment requirements as *cv* `char*`.

6.9.3 CV-qualifiers

[basic.type.qualifier]

¹ A type mentioned in 6.9.1 and 6.9.2 is a *cv-unqualified type*. Each type which is a *cv*-unqualified complete or incomplete object type or is `void` (6.9) has three corresponding *cv*-qualified versions of its type: a *const-qualified* version, a *volatile-qualified* version, and a *const-volatile-qualified* version. The type of an object (4.5) includes the *cv-qualifiers* specified in the *decl-specifier-seq* (10.1), *declarator* (Clause 11), *type-id* (11.1), or *new-type-id* (8.3.4) when the object is created.

- (1.1) — A *const object* is an object of type `const T` or a non-mutable subobject of such an object.
- (1.2) — A *volatile object* is an object of type `volatile T`, a subobject of such an object, or a mutable subobject of a *const volatile* object.
- (1.3) — A *const volatile object* is an object of type `const volatile T`, a non-mutable subobject of such an object, a *const* subobject of a *volatile* object, or a non-mutable *volatile* subobject of a *const* object.

The *cv*-qualified or *cv*-unqualified versions of a type are distinct types; however, they shall have the same representation and alignment requirements (6.11).⁵⁵

² A compound type (6.9.2) is not *cv*-qualified by the *cv*-qualifiers (if any) of the types from which it is compounded. Any *cv*-qualifiers applied to an array type affect the array element type (11.3.4).

³ See 11.3.5 and 12.2.2.1 regarding function types that have *cv-qualifiers*.

⁴ There is a partial ordering on *cv*-qualifiers, so that a type can be said to be *more cv-qualified* than another. Table 10 shows the relations that constitute this ordering.

⁵ In this International Standard, the notation *cv* (or *cv1*, *cv2*, etc.), used in the description of types, represents an arbitrary set of *cv*-qualifiers, i.e., one of {`const`}, {`volatile`}, {`const`, `volatile`}, or the empty set. For a type *cv T*, the *top-level cv-qualifiers* of that type are those denoted by *cv*. [Example: The type corresponding to the *type-id* `const int&` has no top-level *cv*-qualifiers. The type corresponding to the *type-id* `volatile int * const` has the top-level *cv*-qualifier `const`. For a class type *C*, the type corresponding to the *type-id* `void (C::* volatile)(int) const` has the top-level *cv*-qualifier `volatile`. — end example]

⁵⁵) The same representation and alignment requirements are meant to imply interchangeability as arguments to functions, return values from functions, and non-static data members of unions.

Table 10 — Relations on `const` and `volatile`

<i>no cv-qualifier</i>	<	<code>const</code>
<i>no cv-qualifier</i>	<	<code>volatile</code>
<i>no cv-qualifier</i>	<	<code>const volatile</code>
<code>const</code>	<	<code>const volatile</code>
<code>volatile</code>	<	<code>const volatile</code>

- ⁶ Cv-qualifiers applied to an array type attach to the underlying element type, so the notation “*cv T*”, where *T* is an array type, refers to an array whose elements are so-qualified. An array type whose elements are cv-qualified is also considered to have the same cv-qualifications as its elements. [*Example:*

```
typedef char CA[5];
typedef const char CC;
CC arr1[5] = { 0 };
const CA arr2 = { 0 };
```

The type of both `arr1` and `arr2` is “array of 5 `const char`”, and the array type is considered to be const-qualified. — *end example*]

6.10 Lvalues and rvalues

[basic.lval]

- ¹ Expressions are categorized according to the taxonomy in Figure 1.




Figure 1 — Expression category taxonomy

- (1.1) — A *glvalue* is an expression whose evaluation determines the identity of an object, bit-field, or function.
- (1.2) — A *prvalue* is an expression whose evaluation initializes an object or a bit-field, or computes the value of the operand of an operator, as specified by the context in which it appears.
- (1.3) — An *xvalue* is a *glvalue* that denotes an object or bit-field whose resources can be reused (usually because it is near the end of its lifetime). [*Example:* Certain kinds of expressions involving *rvalue* references (11.3.2) yield *xvalues*, such as a call to a function whose return type is an *rvalue* reference or a cast to an *rvalue* reference type. — *end example*]
- (1.4) — An *lvalue* is a *glvalue* that is not an *xvalue*.
- (1.5) — An *rvalue* is a *prvalue* or an *xvalue*.

[*Note:* Historically, *lvalues* and *rvalues* were so-called because they could appear on the left- and right-hand side of an assignment (although this is no longer generally true); *glvalues* are “generalized” *lvalues*, *prvalues* are “pure” *rvalues*, and *xvalues* are “eXpiring” *lvalues*. Despite their names, these terms classify expressions, not values. — *end note*] Every expression belongs to exactly one of the fundamental classifications in this taxonomy: *lvalue*, *xvalue*, or *prvalue*. This property of an expression is called its *value category*. [*Note:* The discussion of each built-in operator in Clause 8 indicates the category of the value it yields and the value categories of the operands it expects. For example, the built-in assignment operators expect that the left

operand is an lvalue and that the right operand is a prvalue and yield an lvalue as the result. User-defined operators are functions, and the categories of values they expect and yield are determined by their parameter and return types. — *end note*]

- ² The *result* of a prvalue is the value that the expression stores into its context. A prvalue whose result is the value *V* is sometimes said to have or name the value *V*. The *result object* of a prvalue is the object initialized by the prvalue; a prvalue that is used to compute the value of an operand of an operator or that has type *cv void* has no result object. [*Note*: Except when the prvalue is the operand of a *decltype-specifier*, a prvalue of class or array type always has a result object. For a discarded prvalue, a temporary object is materialized; see Clause 8. — *end note*] The *result* of a glvalue is the entity denoted by the expression.
- ³ [*Note*: Whenever a glvalue appears in a context where a prvalue is expected, the glvalue is converted to a prvalue; see 7.1, 7.2, and 7.3. An attempt to bind an rvalue reference to an lvalue is not such a context; see 11.6.3. — *end note*] [*Note*: There are no prvalue bit-fields; if a bit-field is converted to a prvalue (7.1), a prvalue of the type of the bit-field is created, which might then be promoted (7.6). — *end note*]
- ⁴ [*Note*: Whenever a prvalue appears in a context where a glvalue is expected, the prvalue is converted to an xvalue; see 7.4. — *end note*]
- ⁵ The discussion of reference initialization in 11.6.3 and of temporaries in 15.2 indicates the behavior of lvalues and rvalues in other significant contexts.
- ⁶ Unless otherwise indicated (8.2.2), a prvalue shall always have complete type or the void type. A glvalue shall not have type *cv void*. [*Note*: A glvalue may have complete or incomplete non-void type. Class and array prvalues can have cv-qualified types; other prvalues always have cv-unqualified types. See Clause 8. — *end note*]
- ⁷ An lvalue is *modifiable* unless its type is const-qualified or is a function type. [*Note*: A program that attempts to modify an object through a nonmodifiable lvalue expression or through an rvalue expression is ill-formed (8.18, 8.2.6, 8.3.2). — *end note*]
- ⁸ If a program attempts to access the stored value of an object through a glvalue of other than one of the following types the behavior is undefined:⁵⁶
 - (8.1) — the dynamic type of the object,
 - (8.2) — a cv-qualified version of the dynamic type of the object,
 - (8.3) — a type similar (as defined in 7.5) to the dynamic type of the object,
 - (8.4) — a type that is the signed or unsigned type corresponding to the dynamic type of the object,
 - (8.5) — a type that is the signed or unsigned type corresponding to a cv-qualified version of the dynamic type of the object,
 - (8.6) — an aggregate or union type that includes one of the aforementioned types among its elements or non-static data members (including, recursively, an element or non-static data member of a subaggregate or contained union),
 - (8.7) — a type that is a (possibly cv-qualified) base class type of the dynamic type of the object,
 - (8.8) — a `char`, `unsigned char`, or `std::byte` type.

6.11 Alignment

[basic.align]

- ¹ Object types have *alignment requirements* (6.9.1, 6.9.2) which place restrictions on the addresses at which an object of that type may be allocated. An *alignment* is an implementation-defined integer value representing the number of bytes between successive addresses at which a given object can be allocated. An object type imposes an alignment requirement on every object of that type; stricter alignment can be requested using the alignment specifier (10.6.2).

⁵⁶) The intent of this list is to specify those circumstances in which an object may or may not be aliased.

- ² A *fundamental alignment* is represented by an alignment less than or equal to the greatest alignment supported by the implementation in all contexts, which is equal to `alignof(std::max_align_t)` (21.2). The alignment required for a type might be different when it is used as the type of a complete object and when it is used as the type of a subobject. [*Example*:

```
struct B { long double d; };
struct D : virtual B { char c; };
```

When D is the type of a complete object, it will have a subobject of type B, so it must be aligned appropriately for a `long double`. If D appears as a subobject of another object that also has B as a virtual base class, the B subobject might be part of a different subobject, reducing the alignment requirements on the D subobject. — *end example*] The result of the `alignof` operator reflects the alignment requirement of the type in the complete-object case.

- ³ An *extended alignment* is represented by an alignment greater than `alignof(std::max_align_t)`. It is implementation-defined whether any extended alignments are supported and the contexts in which they are supported (10.6.2). A type having an extended alignment requirement is an *over-aligned type*. [*Note*: Every over-aligned type is or contains a class type to which extended alignment applies (possibly through a non-static data member). — *end note*] A *new-extended alignment* is represented by an alignment greater than `__STDCPP_DEFAULT_NEW_ALIGNMENT__` (19.8).
- ⁴ Alignments are represented as values of the type `std::size_t`. Valid alignments include only those values returned by an `alignof` expression for the fundamental types plus an additional implementation-defined set of values, which may be empty. Every alignment value shall be a non-negative integral power of two.
- ⁵ Alignments have an order from *weaker* to *stronger* or *stricter* alignments. Stricter alignments have larger alignment values. An address that satisfies an alignment requirement also satisfies any weaker valid alignment requirement.
- ⁶ The alignment requirement of a complete type can be queried using an `alignof` expression (8.3.6). Furthermore, the narrow character types (6.9.1) shall have the weakest alignment requirement. [*Note*: This enables the narrow character types to be used as the underlying type for an aligned memory area (10.6.2). — *end note*]
- ⁷ Comparing alignments is meaningful and provides the obvious results:
- (7.1) — Two alignments are equal when their numeric values are equal.
 - (7.2) — Two alignments are different when their numeric values are not equal.
 - (7.3) — When an alignment is larger than another it represents a stricter alignment.
- ⁸ [*Note*: The runtime pointer alignment function (23.10.5) can be used to obtain an aligned pointer within a buffer; the aligned-storage templates in the library (23.15.7.6) can be used to obtain aligned storage. — *end note*]
- ⁹ If a request for a specific extended alignment in a specific context is not supported by an implementation, the program is ill-formed.

7 Standard conversions

[conv]

¹ Standard conversions are implicit conversions with built-in meaning. Clause 7 enumerates the full set of such conversions. A *standard conversion sequence* is a sequence of standard conversions in the following order:

- (1.1) — Zero or one conversion from the following set: lvalue-to-rvalue conversion, array-to-pointer conversion, and function-to-pointer conversion.
- (1.2) — Zero or one conversion from the following set: integral promotions, floating-point promotion, integral conversions, floating-point conversions, floating-integral conversions, pointer conversions, pointer to member conversions, and boolean conversions.
- (1.3) — Zero or one function pointer conversion.
- (1.4) — Zero or one qualification conversion.

[*Note:* A standard conversion sequence can be empty, i.e., it can consist of no conversions. — *end note*] A standard conversion sequence will be applied to an expression if necessary to convert it to a required destination type.

² [*Note:* Expressions with a given type will be implicitly converted to other types in several contexts:

- (2.1) — When used as operands of operators. The operator's requirements for its operands dictate the destination type (Clause 8).
- (2.2) — When used in the condition of an **if** statement or iteration statement (9.4, 9.5). The destination type is **bool**.
- (2.3) — When used in the expression of a **switch** statement. The destination type is integral (9.4).
- (2.4) — When used as the source expression for an initialization (which includes use as an argument in a function call and use as the expression in a **return** statement). The type of the entity being initialized is (generally) the destination type. See 11.6, 11.6.3.

— *end note*]

³ An expression **e** can be *implicitly converted* to a type **T** if and only if the declaration **T t=e;** is well-formed, for some invented temporary variable **t** (11.6).

⁴ Certain language constructs require that an expression be converted to a Boolean value. An expression **e** appearing in such a context is said to be *contextually converted to bool* and is well-formed if and only if the declaration **bool t(e);** is well-formed, for some invented temporary variable **t** (11.6).

⁵ Certain language constructs require conversion to a value having one of a specified set of types appropriate to the construct. An expression **e** of class type **E** appearing in such a context is said to be *contextually implicitly converted* to a specified type **T** and is well-formed if and only if **e** can be implicitly converted to a type **T** that is determined as follows: **E** is searched for non-explicit conversion functions whose return type is *cv* **T** or reference to *cv* **T** such that **T** is allowed by the context. There shall be exactly one such **T**.

⁶ The effect of any implicit conversion is the same as performing the corresponding declaration and initialization and then using the temporary variable as the result of the conversion. The result is an lvalue if **T** is an lvalue reference type or an rvalue reference to function type (11.3.2), an xvalue if **T** is an rvalue reference to object type, and a prvalue otherwise. The expression **e** is used as a glvalue if and only if the initialization uses it as a glvalue.

⁷ [*Note:* For class types, user-defined conversions are considered as well; see 15.3. In general, an implicit conversion sequence (16.3.3.1) consists of a standard conversion sequence followed by a user-defined conversion

followed by another standard conversion sequence. — *end note*]

- ⁸ [*Note*: There are some contexts where certain conversions are suppressed. For example, the lvalue-to-rvalue conversion is not done on the operand of the unary `&` operator. Specific exceptions are given in the descriptions of those operators and contexts. — *end note*]

7.1 Lvalue-to-rvalue conversion

[conv.lval]

- ¹ A glvalue (6.10) of a non-function, non-array type `T` can be converted to a prvalue.⁵⁷ If `T` is an incomplete type, a program that necessitates this conversion is ill-formed. If `T` is a non-class type, the type of the prvalue is the cv-unqualified version of `T`. Otherwise, the type of the prvalue is `T`.⁵⁸
- ² When an lvalue-to-rvalue conversion is applied to an expression `e`, and either
- (2.1) — `e` is not potentially evaluated, or
 - (2.2) — the evaluation of `e` results in the evaluation of a member `ex` of the set of potential results of `e`, and `ex` names a variable `x` that is not odr-used by `ex` (6.2),

the value contained in the referenced object is not accessed. [*Example*:

```
struct S { int n; };
auto f() {
    S x { 1 };
    constexpr S y { 2 };
    return [&](bool b) { return (b ? y : x).n; };
}
auto g = f();
int m = g(false); // undefined behavior due to access of x.n outside its lifetime
int n = g(true);  // OK, does not access y.n
```

— *end example*]

- ³ The result of the conversion is determined according to the following rules:
- (3.1) — If `T` is `cv std::nullptr_t`, the result is a null pointer constant (7.11). [*Note*: Since no value is fetched from memory, there is no side effect for a volatile access (4.6), and an inactive member of a union (12.3) may be accessed. — *end note*]
 - (3.2) — Otherwise, if `T` has a class type, the conversion copy-initializes the result object from the glvalue.
 - (3.3) — Otherwise, if the object to which the glvalue refers contains an invalid pointer value (6.7.4.2, 6.7.4.3), the behavior is implementation-defined.
 - (3.4) — Otherwise, the value contained in the object indicated by the glvalue is the prvalue result.
- ⁴ [*Note*: See also 6.10. — *end note*]

7.2 Array-to-pointer conversion

[conv.array]

- ¹ An lvalue or rvalue of type “array of `N T`” or “array of unknown bound of `T`” can be converted to a prvalue of type “pointer to `T`”. The temporary materialization conversion (7.4) is applied. The result is a pointer to the first element of the array.

⁵⁷) For historical reasons, this conversion is called the “lvalue-to-rvalue” conversion, even though that name does not accurately reflect the taxonomy of expressions described in 6.10.

⁵⁸) In C++ class and array prvalues can have cv-qualified types. This differs from ISO C, in which non-lvalues never have cv-qualified types.

7.3 Function-to-pointer conversion

[conv.func]

- ¹ An lvalue of function type *T* can be converted to a prvalue of type “pointer to *T*”. The result is a pointer to the function.⁵⁹
- ² [Note: See 16.4 for additional rules for the case where the function is overloaded. — end note]

7.4 Temporary materialization conversion

[conv.rval]

- ¹ A prvalue of type *T* can be converted to an xvalue of type *T*. This conversion initializes a temporary object (15.2) of type *T* from the prvalue by evaluating the prvalue with the temporary object as its result object, and produces an xvalue denoting the temporary object. *T* shall be a complete type. [Note: If *T* is a class type (or array thereof), it must have an accessible and non-deleted destructor; see 15.4. — end note]
[Example:

```
struct X { int n; };
int k = X().n;           // OK, X() prvalue is converted to xvalue
— end example]
```

7.5 Qualification conversions

[conv.qual]

- ¹ A *cv-decomposition* of a type *T* is a sequence of *cv_i* and *P_i* such that *T* is

“*cv₀ P₀ cv₁ P₁ ⋯ cv_{*n*-1} P_{*n*-1} cv_{*n*} U*” for *n* > 0,

where each *cv_i* is a set of cv-qualifiers (6.9.3), and each *P_i* is “pointer to” (11.3.1), “pointer to member of class *C_i* of type” (11.3.3), “array of *N_i*”, or “array of unknown bound of” (11.3.4). If *P_i* designates an array, the cv-qualifiers *cv_{i+1}* on the element type are also taken as the cv-qualifiers *cv_i* of the array. [Example: The type denoted by the *type-id* `const int **` has two cv-decompositions, taking *U* as “int” and as “pointer to `const int`”. — end example] The *n*-tuple of cv-qualifiers after the first one in the longest cv-decomposition of *T*, that is, *cv₁, cv₂, …, cv_n*, is called the *cv-qualification signature* of *T*.

- ² Two types *T₁* and *T₂* are *similar* if they have cv-decompositions with the same *n* such that corresponding *P_i* components are the same and the types denoted by *U* are the same.
- ³ A prvalue expression of type *T₁* can be converted to type *T₂* if the following conditions are satisfied, where *cv_i^j* denotes the cv-qualifiers in the cv-qualification signature of *T_j*:⁶⁰
 - (3.1) — *T₁* and *T₂* are similar.
 - (3.2) — For every *i* > 0, if `const` is in *cv_i¹* then `const` is in *cv_i²*, and similarly for `volatile`.
 - (3.3) — If the *cv_i¹* and *cv_i²* are different, then `const` is in every *cv_k²* for 0 < *k* < *i*.

[Note: If a program could assign a pointer of type `T**` to a pointer of type `const T**` (that is, if line #1 below were allowed), a program could inadvertently modify a `const` object (as it is done on line #2). For example,

```
int main() {
    const char c = 'c';
    char* pc;
    const char** pcc = &pc;           // #1: not allowed
    *pcc = &c;
    *pc = 'C';                       // #2: modifies a const object
}
```

— end note]

⁵⁹) This conversion never applies to non-static member functions because an lvalue that refers to a non-static member function cannot be obtained.

⁶⁰) These rules ensure that const-safety is preserved by the conversion.

- ⁴ [*Note*: A prvalue of type “pointer to *cv1* T” can be converted to a prvalue of type “pointer to *cv2* T” if “*cv2* T” is more cv-qualified than “*cv1* T”. A prvalue of type “pointer to member of X of type *cv1* T” can be converted to a prvalue of type “pointer to member of X of type *cv2* T” if “*cv2* T” is more cv-qualified than “*cv1* T”. — *end note*]
- ⁵ [*Note*: Function types (including those used in pointer to member function types) are never cv-qualified (11.3.5). — *end note*]

7.6 Integral promotions

[conv.prom]

- ¹ A prvalue of an integer type other than `bool`, `char16_t`, `char32_t`, or `wchar_t` whose integer conversion rank (7.15) is less than the rank of `int` can be converted to a prvalue of type `int` if `int` can represent all the values of the source type; otherwise, the source prvalue can be converted to a prvalue of type `unsigned int`.
- ² A prvalue of type `char16_t`, `char32_t`, or `wchar_t` (6.9.1) can be converted to a prvalue of the first of the following types that can represent all the values of its underlying type: `int`, `unsigned int`, `long int`, `unsigned long int`, `long long int`, or `unsigned long long int`. If none of the types in that list can represent all the values of its underlying type, a prvalue of type `char16_t`, `char32_t`, or `wchar_t` can be converted to a prvalue of its underlying type.
- ³ A prvalue of an unscoped enumeration type whose underlying type is not fixed (10.2) can be converted to a prvalue of the first of the following types that can represent all the values of the enumeration (i.e., the values in the range $b_{\min}$ to $b_{\max}$ as described in 10.2): `int`, `unsigned int`, `long int`, `unsigned long int`, `long long int`, or `unsigned long long int`. If none of the types in that list can represent all the values of the enumeration, a prvalue of an unscoped enumeration type can be converted to a prvalue of the extended integer type with lowest integer conversion rank (7.15) greater than the rank of `long long` in which all the values of the enumeration can be represented. If there are two such extended types, the signed one is chosen.
- ⁴ A prvalue of an unscoped enumeration type whose underlying type is fixed (10.2) can be converted to a prvalue of its underlying type. Moreover, if integral promotion can be applied to its underlying type, a prvalue of an unscoped enumeration type whose underlying type is fixed can also be converted to a prvalue of the promoted underlying type.
- ⁵ A prvalue for an integral bit-field (12.2.4) can be converted to a prvalue of type `int` if `int` can represent all the values of the bit-field; otherwise, it can be converted to `unsigned int` if `unsigned int` can represent all the values of the bit-field. If the bit-field is larger yet, no integral promotion applies to it. If the bit-field has an enumerated type, it is treated as any other value of that type for promotion purposes.
- ⁶ A prvalue of type `bool` can be converted to a prvalue of type `int`, with `false` becoming zero and `true` becoming one.
- ⁷ These conversions are called *integral promotions*.

7.7 Floating-point promotion

[conv.fpprom]

- ¹ A prvalue of type `float` can be converted to a prvalue of type `double`. The value is unchanged.
- ² This conversion is called *floating-point promotion*.

7.8 Integral conversions

[conv.integral]

- ¹ A prvalue of an integer type can be converted to a prvalue of another integer type. A prvalue of an unscoped enumeration type can be converted to a prvalue of an integer type.
- ² If the destination type is unsigned, the resulting value is the least unsigned integer congruent to the source integer (modulo 2^n where n is the number of bits used to represent the unsigned type). [*Note*: In a two’s complement representation, this conversion is conceptual and there is no change in the bit pattern (if there is no truncation). — *end note*]

- ³ If the destination type is signed, the value is unchanged if it can be represented in the destination type; otherwise, the value is implementation-defined.
- ⁴ If the destination type is `bool`, see 7.14. If the source type is `bool`, the value `false` is converted to zero and the value `true` is converted to one.
- ⁵ The conversions allowed as integral promotions are excluded from the set of integral conversions.

7.9 Floating-point conversions [conv.double]

- ¹ A prvalue of floating-point type can be converted to a prvalue of another floating-point type. If the source value can be exactly represented in the destination type, the result of the conversion is that exact representation. If the source value is between two adjacent destination values, the result of the conversion is an implementation-defined choice of either of those values. Otherwise, the behavior is undefined.
- ² The conversions allowed as floating-point promotions are excluded from the set of floating-point conversions.

7.10 Floating-integral conversions [conv.fpoint]

- ¹ A prvalue of a floating-point type can be converted to a prvalue of an integer type. The conversion truncates; that is, the fractional part is discarded. The behavior is undefined if the truncated value cannot be represented in the destination type. [*Note:* If the destination type is `bool`, see 7.14. — *end note*]
- ² A prvalue of an integer type or of an unscoped enumeration type can be converted to a prvalue of a floating-point type. The result is exact if possible. If the value being converted is in the range of values that can be represented but the value cannot be represented exactly, it is an implementation-defined choice of either the next lower or higher representable value. [*Note:* Loss of precision occurs if the integral value cannot be represented exactly as a value of the floating type. — *end note*] If the value being converted is outside the range of values that can be represented, the behavior is undefined. If the source type is `bool`, the value `false` is converted to zero and the value `true` is converted to one.

7.11 Pointer conversions [conv.ptr]

- ¹ A *null pointer constant* is an integer literal (5.13.2) with value zero or a prvalue of type `std::nullptr_t`. A null pointer constant can be converted to a pointer type; the result is the *null pointer value* of that type and is distinguishable from every other value of object pointer or function pointer type. Such a conversion is called a *null pointer conversion*. Two null pointer values of the same type shall compare equal. The conversion of a null pointer constant to a pointer to cv-qualified type is a single conversion, and not the sequence of a pointer conversion followed by a qualification conversion (7.5). A null pointer constant of integral type can be converted to a prvalue of type `std::nullptr_t`. [*Note:* The resulting prvalue is not a null pointer value. — *end note*]
- ² A prvalue of type “pointer to *cv* T”, where T is an object type, can be converted to a prvalue of type “pointer to *cv* void”. The pointer value (6.9.2) is unchanged by this conversion.
- ³ A prvalue of type “pointer to *cv* D”, where D is a class type, can be converted to a prvalue of type “pointer to *cv* B”, where B is a base class (Clause 13) of D. If B is an inaccessible (Clause 14) or ambiguous (13.2) base class of D, a program that necessitates this conversion is ill-formed. The result of the conversion is a pointer to the base class subobject of the derived class object. The null pointer value is converted to the null pointer value of the destination type.

7.12 Pointer to member conversions [conv.mem]

- ¹ A null pointer constant (7.11) can be converted to a pointer to member type; the result is the *null member pointer value* of that type and is distinguishable from any pointer to member not created from a null pointer constant. Such a conversion is called a *null member pointer conversion*. Two null member pointer values of the same type shall compare equal. The conversion of a null pointer constant to a pointer to member of

cv-qualified type is a single conversion, and not the sequence of a pointer to member conversion followed by a qualification conversion (7.5).

- ² A prvalue of type “pointer to member of B of type *cv T*”, where B is a class type, can be converted to a prvalue of type “pointer to member of D of type *cv T*”, where D is a derived class (Clause 13) of B. If B is an inaccessible (Clause 14), ambiguous (13.2), or virtual (13.1) base class of D, or a base class of a virtual base class of D, a program that necessitates this conversion is ill-formed. The result of the conversion refers to the same member as the pointer to member before the conversion took place, but it refers to the base class member as if it were a member of the derived class. The result refers to the member in D’s instance of B. Since the result has type “pointer to member of D of type *cv T*”, indirection through it with a D object is valid. The result is the same as if indirecting through the pointer to member of B with the B subobject of D. The null member pointer value is converted to the null member pointer value of the destination type.⁶¹

7.13 Function pointer conversions

[conv.fctptr]

- ¹ A prvalue of type “pointer to `noexcept` function” can be converted to a prvalue of type “pointer to function”. The result is a pointer to the function. A prvalue of type “pointer to member of type `noexcept` function” can be converted to a prvalue of type “pointer to member of type function”. The result points to the member function.

[Example:

```
void (*p)();
void (**pp)() noexcept = &p; // error: cannot convert to pointer to noexcept function
```

```
struct S { typedef void (*p)(); operator p(); };
void (*q)() noexcept = S(); // error: cannot convert to pointer to noexcept function
```

— end example]

7.14 Boolean conversions

[conv.bool]

- ¹ A prvalue of arithmetic, unscoped enumeration, pointer, or pointer to member type can be converted to a prvalue of type `bool`. A zero value, null pointer value, or null member pointer value is converted to `false`; any other value is converted to `true`. For direct-initialization (11.6), a prvalue of type `std::nullptr_t` can be converted to a prvalue of type `bool`; the resulting value is `false`.

7.15 Integer conversion rank

[conv.rank]

- ¹ Every integer type has an *integer conversion rank* defined as follows:
- (1.1) — No two signed integer types other than `char` and `signed char` (if `char` is signed) shall have the same rank, even if they have the same representation.
 - (1.2) — The rank of a signed integer type shall be greater than the rank of any signed integer type with a smaller size.
 - (1.3) — The rank of `long long int` shall be greater than the rank of `long int`, which shall be greater than the rank of `int`, which shall be greater than the rank of `short int`, which shall be greater than the rank of `signed char`.
 - (1.4) — The rank of any unsigned integer type shall equal the rank of the corresponding signed integer type.
 - (1.5) — The rank of any standard integer type shall be greater than the rank of any extended integer type with the same size.

⁶¹) The rule for conversion of pointers to members (from pointer to member of base to pointer to member of derived) appears inverted compared to the rule for pointers to objects (from pointer to derived to pointer to base) (7.11, Clause 13). This inversion is necessary to ensure type safety. Note that a pointer to member is not an object pointer or a function pointer and the rules for conversions of such pointers do not apply to pointers to members. In particular, a pointer to member cannot be converted to a `void*`.

- (1.6) — The rank of `char` shall equal the rank of `signed char` and `unsigned char`.
- (1.7) — The rank of `bool` shall be less than the rank of all other standard integer types.
- (1.8) — The ranks of `char16_t`, `char32_t`, and `wchar_t` shall equal the ranks of their underlying types (6.9.1).
- (1.9) — The rank of any extended signed integer type relative to another extended signed integer type with the same size is implementation-defined, but still subject to the other rules for determining the integer conversion rank.
- (1.10) — For all integer types `T1`, `T2`, and `T3`, if `T1` has greater rank than `T2` and `T2` has greater rank than `T3`, then `T1` shall have greater rank than `T3`.

[*Note*: The integer conversion rank is used in the definition of the integral promotions (7.6) and the usual arithmetic conversions (Clause 8). — *end note*]

8 Expressions

[expr]

- ¹ [*Note*: Clause 8 defines the syntax, order of evaluation, and meaning of expressions.⁶² An expression is a sequence of operators and operands that specifies a computation. An expression can result in a value and can cause side effects. — *end note*]
- ² [*Note*: Operators can be overloaded, that is, given meaning when applied to expressions of class type (Clause 12) or enumeration type (10.2). Uses of overloaded operators are transformed into function calls as described in 16.5. Overloaded operators obey the rules for syntax and evaluation order specified in Clause 8, but the requirements of operand type and value category are replaced by the rules for function call. Relations between operators, such as `++a` meaning `a+=1`, are not guaranteed for overloaded operators (16.5). — *end note*]
- ³ Clause 8 defines the effects of operators when applied to types for which they have not been overloaded. Operator overloading shall not modify the rules for the *built-in operators*, that is, for operators applied to types for which they are defined by this Standard. However, these built-in operators participate in overload resolution, and as part of that process user-defined conversions will be considered where necessary to convert the operands to types appropriate for the built-in operator. If a built-in operator is selected, such conversions will be applied to the operands before the operation is considered further according to the rules in Clause 8; see 16.3.1.2, 16.6.
- ⁴ If during the evaluation of an expression, the result is not mathematically defined or not in the range of representable values for its type, the behavior is undefined. [*Note*: Treatment of division by zero, forming a remainder using a zero divisor, and all floating-point exceptions vary among machines, and is sometimes adjustable by a library function. — *end note*]
- ⁵ If an expression initially has the type “reference to T” (11.3.2, 11.6.3), the type is adjusted to T prior to any further analysis. The expression designates the object or function denoted by the reference, and the expression is an lvalue or an xvalue, depending on the expression. [*Note*: Before the lifetime of the reference has started or after it has ended, the behavior is undefined (see 6.8). — *end note*]
- ⁶ If a prvalue initially has the type “*cv* T”, where T is a cv-unqualified non-class, non-array type, the type of the expression is adjusted to T prior to any further analysis.
- ⁷ [*Note*: An expression is an xvalue if it is:
 - (7.1) — the result of calling a function, whether implicitly or explicitly, whose return type is an rvalue reference to object type,
 - (7.2) — a cast to an rvalue reference to object type,
 - (7.3) — a class member access expression designating a non-static data member of non-reference type in which the object expression is an xvalue, or
 - (7.4) — a `.*` pointer-to-member expression in which the first operand is an xvalue and the second operand is a pointer to data member.

In general, the effect of this rule is that named rvalue references are treated as lvalues and unnamed rvalue references to objects are treated as xvalues; rvalue references to functions are treated as lvalues whether named or not. — *end note*]

[*Example*:

```
struct A {
    int m;
```

⁶²⁾ The precedence of operators is not directly specified, but it can be derived from the syntax.

```
};
A&& operator+(A, A);
A&& f();

A a;
A&& ar = static_cast<A&&>(a);
```

The expressions `f()`, `f().m`, `static_cast<A&&>(a)`, and `a + a` are xvalues. The expression `ar` is an lvalue.
— *end example*]

- 8 In some contexts, *unevaluated operands* appear (8.2.8, 8.3.3, 8.3.7, 10.1.7.2). An unevaluated operand is not evaluated. [*Note:* In an unevaluated operand, a non-static class member may be named (8.1) and naming of objects or functions does not, by itself, require that a definition be provided (6.2). An unevaluated operand is considered a full-expression (4.6). — *end note*]
- 9 Whenever a glvalue expression appears as an operand of an operator that expects a prvalue for that operand, the lvalue-to-rvalue (7.1), array-to-pointer (7.2), or function-to-pointer (7.3) standard conversions are applied to convert the expression to a prvalue. [*Note:* Because cv-qualifiers are removed from the type of an expression of non-class type when the expression is converted to a prvalue, an lvalue expression of type `const int` can, for example, be used where a prvalue expression of type `int` is required. — *end note*]
- 10 Whenever a prvalue expression appears as an operand of an operator that expects a glvalue for that operand, the temporary materialization conversion (7.4) is applied to convert the expression to an xvalue.
- 11 Many binary operators that expect operands of arithmetic or enumeration type cause conversions and yield result types in a similar way. The purpose is to yield a common type, which is also the type of the result. This pattern is called the *usual arithmetic conversions*, which are defined as follows:
 - (11.1) — If either operand is of scoped enumeration type (10.2), no conversions are performed; if the other operand does not have the same type, the expression is ill-formed.
 - (11.2) — If either operand is of type `long double`, the other shall be converted to `long double`.
 - (11.3) — Otherwise, if either operand is `double`, the other shall be converted to `double`.
 - (11.4) — Otherwise, if either operand is `float`, the other shall be converted to `float`.
 - (11.5) — Otherwise, the integral promotions (7.6) shall be performed on both operands.⁶³ Then the following rules shall be applied to the promoted operands:
 - (11.5.1) — If both operands have the same type, no further conversion is needed.
 - (11.5.2) — Otherwise, if both operands have signed integer types or both have unsigned integer types, the operand with the type of lesser integer conversion rank shall be converted to the type of the operand with greater rank.
 - (11.5.3) — Otherwise, if the operand that has unsigned integer type has rank greater than or equal to the rank of the type of the other operand, the operand with signed integer type shall be converted to the type of the operand with unsigned integer type.
 - (11.5.4) — Otherwise, if the type of the operand with signed integer type can represent all of the values of the type of the operand with unsigned integer type, the operand with unsigned integer type shall be converted to the type of the operand with signed integer type.
 - (11.5.5) — Otherwise, both operands shall be converted to the unsigned integer type corresponding to the type of the operand with signed integer type.
- 12 In some contexts, an expression only appears for its side effects. Such an expression is called a *discarded-value expression*. The array-to-pointer (7.2) and function-to-pointer (7.3) standard conversions are not applied.

⁶³) As a consequence, operands of type `bool`, `char16_t`, `char32_t`, `wchar_t`, or an enumerated type are converted to some integral type.

The lvalue-to-rvalue conversion (7.1) is applied if and only if the expression is a glvalue of volatile-qualified type and it is one of the following:

- (12.1) — (*expression*), where *expression* is one of these expressions,
- (12.2) — *id-expression* (8.1.4),
- (12.3) — subscripting (8.2.1),
- (12.4) — class member access (8.2.5),
- (12.5) — indirection (8.3.1),
- (12.6) — pointer-to-member operation (8.5),
- (12.7) — conditional expression (8.16) where both the second and the third operands are one of these expressions, or
- (12.8) — comma expression (8.19) where the right operand is one of these expressions.

[*Note*: Using an overloaded operator causes a function call; the above covers only operators with built-in meaning. — *end note*] If the expression is a prvalue after this optional conversion, the temporary materialization conversion (7.4) is applied. [*Note*: If the expression is an lvalue of class type, it must have a volatile copy constructor to initialize the temporary that is the result object of the lvalue-to-rvalue conversion. — *end note*] The glvalue expression is evaluated and its value is discarded.

- 13 The values of the floating operands and the results of floating expressions may be represented in greater precision and range than that required by the type; the types are not changed thereby.⁶⁴
- 14 The *cv-combined type* of two types T1 and T2 is a type T3 similar to T1 whose cv-qualification signature (7.5) is:

- (14.1) — for every $i > 0$, cv_i^3 is the union of cv_i^1 and cv_i^2 ;
- (14.2) — if the resulting cv_i^3 is different from cv_i^1 or cv_i^2 , then **const** is added to every cv_k^3 for $0 < k < i$.

[*Note*: Given similar types T1 and T2, this construction ensures that both can be converted to T3. — *end note*]

- 15 The *composite pointer type* of two operands p1 and p2 having types T1 and T2, respectively, where at least one is a pointer or pointer to member type or **std::nullptr_t**, is:
 - (15.1) — if both p1 and p2 are null pointer constants, **std::nullptr_t**;
 - (15.2) — if either p1 or p2 is a null pointer constant, T2 or T1, respectively;
 - (15.3) — if T1 or T2 is “pointer to *cv1* void” and the other type is “pointer to *cv2* T”, where T is an object type or **void**, “pointer to *cv12* void”, where *cv12* is the union of *cv1* and *cv2*;
 - (15.4) — if T1 or T2 is “pointer to **noexcept** function” and the other type is “pointer to function”, where the function types are otherwise the same, “pointer to function”;
 - (15.5) — if T1 is “pointer to *cv1* C1” and T2 is “pointer to *cv2* C2”, where C1 is reference-related to C2 or C2 is reference-related to C1 (11.6.3), the cv-combined type of T1 and T2 or the cv-combined type of T2 and T1, respectively;
 - (15.6) — if T1 is “pointer to member of C1 of type *cv1* U1” and T2 is “pointer to member of C2 of type *cv2* U2” where C1 is reference-related to C2 or C2 is reference-related to C1 (11.6.3), the cv-combined type of T2 and T1 or the cv-combined type of T1 and T2, respectively;
 - (15.7) — if T1 and T2 are similar types (7.5), the cv-combined type of T1 and T2;
 - (15.8) — otherwise, a program that necessitates the determination of a composite pointer type is ill-formed.

⁶⁴) The cast and assignment operators must still perform their specific conversions as described in 8.4, 8.2.9 and 8.18.

[*Example:*

```
typedef void *p;
typedef const int *q;
typedef int **pi;
typedef const int **pci;
```

The composite pointer type of `p` and `q` is “pointer to `const void`”; the composite pointer type of `pi` and `pci` is “pointer to `const` pointer to `const int`”. — *end example*]

8.1 Primary expressions

[**expr.prim**]

primary-expression:

```
literal
this
( expression )
id-expression
lambda-expression
fold-expression
```

8.1.1 Literals

[**expr.prim.literal**]

- ¹ A *literal* is a primary expression. Its type depends on its form (5.13). A string literal is an lvalue; all other literals are prvalues.

8.1.2 This

[**expr.prim.this**]

- ¹ The keyword `this` names a pointer to the object for which a non-static member function (12.2.2.1) is invoked or a non-static data member’s initializer (12.2) is evaluated.
- ² If a declaration declares a member function or member function template of a class `X`, the expression `this` is a prvalue of type “pointer to *cv-qualifier-seq* `X`” between the optional *cv-qualifier-seq* and the end of the *function-definition*, *member-declarator*, or *declarator*. It shall not appear before the optional *cv-qualifier-seq* and it shall not appear within the declaration of a static member function (although its type and value category are defined within a static member function as they are within a non-static member function). [*Note:* This is because declaration matching does not occur until the complete declarator is known. — *end note*] Unlike the object expression in other contexts, `*this` is not required to be of complete type for purposes of class member access (8.2.5) outside the member function body. [*Note:* Only class members declared prior to the declaration are visible. — *end note*] [*Example:*

```
struct A {
    char g();
    template<class T> auto f(T t) -> decltype(t + g())
    { return t + g(); }
};
template auto A::f(int t) -> decltype(t + g());
```

— *end example*]

- ³ Otherwise, if a *member-declarator* declares a non-static data member (12.2) of a class `X`, the expression `this` is a prvalue of type “pointer to `X`” within the optional default member initializer (12.2). It shall not appear elsewhere in the *member-declarator*.
- ⁴ The expression `this` shall not appear in any other context. [*Example:*

```
class Outer {
    int a[sizeof(*this)];           // error: not inside a member function
    unsigned int sz = sizeof(*this); // OK: in default member initializer

    void f() {
```

```

    int b[sizeof(*this)];           // OK

    struct Inner {
        int c[sizeof(*this)];      // error: not inside a member function of Inner
    };
};
— end example]

```

8.1.3 Parentheses

[expr.prim.paren]

- ¹ A parenthesized expression (E) is a primary expression whose type, value, and value category are identical to those of E. The parenthesized expression can be used in exactly the same contexts as those where E can be used, and with the same meaning, except as otherwise indicated.

8.1.4 Names

[expr.prim.id]

id-expression:
unqualified-id
qualified-id

- ¹ An *id-expression* is a restricted form of a *primary-expression*. [*Note*: An *id-expression* can appear after . and -> operators (8.2.5). — end note]
- ² An *id-expression* that denotes a non-static data member or non-static member function of a class can only be used:
- (2.1) — as part of a class member access (8.2.5) in which the object expression refers to the member's class⁶⁵ or a class derived from that class, or
 - (2.2) — to form a pointer to member (8.3.1), or
 - (2.3) — if that *id-expression* denotes a non-static data member and it appears in an unevaluated operand.
- [*Example*:

```

    struct S {
        int m;
    };
    int i = sizeof(S::m);           // OK
    int j = sizeof(S::m + 42);      // OK
— end example]

```

8.1.4.1 Unqualified names

[expr.prim.id.unqual]

unqualified-id:
identifier
operator-function-id
conversion-function-id
literal-operator-id
~ *class-name*
~ *decltype-specifier*
template-id

- ¹ An *identifier* is an *id-expression* provided it has been suitably declared (Clause 10). [*Note*: For *operator-function-ids*, see 16.5; for *conversion-function-ids*, see 15.3.2; for *literal-operator-ids*, see 16.5.8; for *template-ids*, see 17.2. A *class-name* or *decltype-specifier* prefixed by ~ denotes a destructor; see 15.4. Within the definition of a non-static member function, an *identifier* that names a non-static member is transformed to a

⁶⁵) This also applies when the object expression is an implicit (*this) (12.2.2).

class member access expression (12.2.2). — *end note*] The type of the expression is the type of the *identifier*. The result is the entity denoted by the identifier. The expression is an lvalue if the entity is a function, variable, or data member and a prvalue otherwise; it is a bit-field if the identifier designates a bit-field (11.5).

8.1.4.2 Qualified names

[**expr.prim.id.qual**]

qualified-id:
nested-name-specifier **template**_{opt} *unqualified-id*
nested-name-specifier:
`::`
type-name `::`
namespace-name `::`
decltype-specifier `::`
nested-name-specifier *identifier* `::`
nested-name-specifier **template**_{opt} *simple-template-id* `::`

- ¹ The type denoted by a *decltype-specifier* in a *nested-name-specifier* shall be a class or enumeration type.
- ² A *nested-name-specifier* that denotes a class, optionally followed by the keyword **template** (17.2), and then followed by the name of a member of either that class (12.2) or one of its base classes (Clause 13), is a *qualified-id*; 6.4.3.1 describes name lookup for class members that appear in *qualified-ids*. The result is the member. The type of the result is the type of the member. The result is an lvalue if the member is a static member function or a data member and a prvalue otherwise. [*Note*: A class member can be referred to using a *qualified-id* at any point in its potential scope (6.3.7). — *end note*] Where *class-name* `::~ class-name` is used, the two *class-names* shall refer to the same class; this notation names the destructor (15.4). The form `~ decltype-specifier` also denotes the destructor, but it shall not be used as the *unqualified-id* in a *qualified-id*. [*Note*: A *typedef-name* that names a class is a *class-name* (12.1). — *end note*]
- ³ The *nested-name-specifier* `::` names the global namespace. A *nested-name-specifier* that names a namespace (10.3), optionally followed by the keyword **template** (17.2), and then followed by the name of a member of that namespace (or the name of a member of a namespace made visible by a *using-directive*), is a *qualified-id*; 6.4.3.2 describes name lookup for namespace members that appear in *qualified-ids*. The result is the member. The type of the result is the type of the member. The result is an lvalue if the member is a function or a variable and a prvalue otherwise.
- ⁴ A *nested-name-specifier* that denotes an enumeration (10.2), followed by the name of an enumerator of that enumeration, is a *qualified-id* that refers to the enumerator. The result is the enumerator. The type of the result is the type of the enumeration. The result is a prvalue.
- ⁵ In a *qualified-id*, if the *unqualified-id* is a *conversion-function-id*, its *conversion-type-id* shall denote the same type in both the context in which the entire *qualified-id* occurs and in the context of the class denoted by the *nested-name-specifier*.

8.1.5 Lambda expressions

[**expr.prim.lambda**]

lambda-expression:
lambda-introducer *lambda-declarator*_{opt} *compound-statement*
lambda-introducer:
`[ lambda-captureopt ]`
lambda-declarator:
`( parameter-declaration-clause ) decl-specifier-seqopt`
`noexcept-specifieropt attribute-specifier-seqopt trailing-return-typeopt`

- ¹ Lambda expressions provide a concise way to create simple function objects. [*Example*:

```
#include <algorithm>
#include <cmath>
void abssort(float* x, unsigned N) {
```

```
std::sort(x, x + N, [](float a, float b) { return std::abs(a) < std::abs(b); });
}
```

— end example]

- ² A *lambda-expression* is a prvalue whose result object is called the *closure object*. A *lambda-expression* shall not appear in an unevaluated operand (Clause 8), in a *template-argument*, in an *alias-declaration*, in a typedef declaration, or in the declaration of a function or function template outside its function body and default arguments. [Note: The intention is to prevent lambdas from appearing in a signature. — end note] [Note: A closure object behaves like a function object (23.14). — end note]
- ³ In the *decl-specifier-seq* of the *lambda-declarator*, each *decl-specifier* shall either be `mutable` or `constexpr`.
- ⁴ If a *lambda-expression* does not include a *lambda-declarator*, it is as if the *lambda-declarator* were (). The lambda return type is `auto`, which is replaced by the type specified by the *trailing-return-type* if provided and/or deduced from `return` statements as described in 10.1.7.4. [Example:

```
auto x1 = [](int i){ return i; }; // OK: return type is int
auto x2 = []{ return { 1, 2 }; }; // error: deducing return type from braced-init-list
int j;
auto x3 = []()->auto&& { return j; }; // OK: return type is int&
```

— end example]

8.1.5.1 Closure types

[expr.prim.lambda.closure]

- ¹ The type of a *lambda-expression* (which is also the type of the closure object) is a unique, unnamed non-union class type, called the *closure type*, whose properties are described below.
- ² The closure type is declared in the smallest block scope, class scope, or namespace scope that contains the corresponding *lambda-expression*. [Note: This determines the set of namespaces and classes associated with the closure type (6.4.2). The parameter types of a *lambda-declarator* do not affect these associated namespaces and classes. — end note] The closure type is not an aggregate type (11.6.1). An implementation may define the closure type differently from what is described below provided this does not alter the observable behavior of the program other than by changing:
 - (2.1) — the size and/or alignment of the closure type,
 - (2.2) — whether the closure type is trivially copyable (Clause 12),
 - (2.3) — whether the closure type is a standard-layout class (Clause 12), or
 - (2.4) — whether the closure type is a POD class (Clause 12).

An implementation shall not add members of rvalue reference type to the closure type.

- ³ The closure type for a non-generic *lambda-expression* has a public inline function call operator (16.5.4) whose parameters and return type are described by the *lambda-expression*'s *parameter-declaration-clause* and *trailing-return-type* respectively. For a generic lambda, the closure type has a public inline function call operator member template (17.5.2) whose *template-parameter-list* consists of one invented type *template-parameter* for each occurrence of `auto` in the lambda's *parameter-declaration-clause*, in order of appearance. The invented type *template-parameter* is a parameter pack if the corresponding *parameter-declaration* declares a function parameter pack (11.3.5). The return type and function parameters of the function call operator template are derived from the *lambda-expression*'s *trailing-return-type* and *parameter-declaration-clause* by replacing each occurrence of `auto` in the *decl-specifiers* of the *parameter-declaration-clause* with the name of the corresponding invented *template-parameter*. [Example:

```
auto glambda = [](auto a, auto&& b) { return a < b; };
bool b = glambda(3, 3.14); // OK

auto vglambda = [](auto printer) {
```

```

return [=](auto&& ... ts) {                                     // OK: ts is a function parameter pack
    printer(std::forward<decltype(ts)>(ts)...);

    return [=]() {
        printer(ts ...);
    };
};
};
auto p = vglambda( [](auto v1, auto v2, auto v3)
                    { std::cout << v1 << v2 << v3; } );
auto q = p(1, 'a', 3.14);                                     // OK: outputs 1a3.14
q();                                                         // OK: outputs 1a3.14
— end example]

```

- ⁴ The function call operator or operator template is declared **const** (12.2.2) if and only if the *lambda-expression's parameter-declaration-clause* is not followed by **mutable**. It is neither virtual nor declared **volatile**. Any *noexcept-specifier* specified on a *lambda-expression* applies to the corresponding function call operator or operator template. An *attribute-specifier-seq* in a *lambda-declarator* appertains to the type of the corresponding function call operator or operator template. The function call operator or any given operator template specialization is a **constexpr** function if either the corresponding *lambda-expression's parameter-declaration-clause* is followed by **constexpr**, or it satisfies the requirements for a **constexpr** function (10.1.5). [*Note*: Names referenced in the *lambda-declarator* are looked up in the context in which the *lambda-expression* appears. — end note] [*Example*:

```

auto ID = [](auto a) { return a; };
static_assert(ID(3) == 3); // OK

struct NonLiteral {
    NonLiteral(int n) : n(n) { }
    int n;
};
static_assert(ID(NonLiteral{3}).n == 3); // ill-formed
— end example]

```

- ⁵ [*Example*:

```

auto monoid = [](auto v) { return [=] { return v; }; };
auto add = [](auto m1) constexpr {
    auto ret = m1();
    return [=](auto m2) mutable {
        auto m1val = m1();
        auto plus = [=](auto m2val) mutable constexpr
            { return m1val += m2val; };
        ret = plus(m2());
        return monoid(ret);
    };
};
constexpr auto zero = monoid(0);
constexpr auto one = monoid(1);
static_assert(add(one)(zero)() == one()); // OK

```

```

// Since two below is not declared constexpr, an evaluation of its constexpr member function call operator
// cannot perform an lvalue-to-rvalue conversion on one of its subobjects (that represents its capture)
// in a constant expression.
auto two = monoid(2);
assert(two() == 2); // OK, not a constant expression.

```

```
static_assert(add(one)(one)() == two()); // ill-formed: two() is not a constant expression
static_assert(add(one)(one)() == monoid(2)()); // OK
```

— end example]

- ⁶ The closure type for a non-generic *lambda-expression* with no *lambda-capture* has a conversion function to pointer to function with C++ language linkage (10.5) having the same parameter and return types as the closure type’s function call operator. The conversion is to “pointer to **noexcept** function” if the function call operator has a non-throwing exception specification. The value returned by this conversion function is the address of a function *F* that, when invoked, has the same effect as invoking the closure type’s function call operator. *F* is a *constexpr* function if the function call operator is a *constexpr* function. For a generic lambda with no *lambda-capture*, the closure type has a conversion function template to pointer to function. The conversion function template has the same invented *template-parameter-list*, and the pointer to function has the same parameter types, as the function call operator template. The return type of the pointer to function shall behave as if it were a *decltype-specifier* denoting the return type of the corresponding function call operator template specialization.
- ⁷ [Note: If the generic lambda has no *trailing-return-type* or the *trailing-return-type* contains a placeholder type, return type deduction of the corresponding function call operator template specialization has to be done. The corresponding specialization is that instantiation of the function call operator template with the same template arguments as those deduced for the conversion function template. Consider the following:

```
auto glambda = [](auto a) { return a; };
int (*fp)(int) = glambda;
```

The behavior of the conversion function of *glambda* above is like that of the following conversion function:

```
struct Closure {
    template<class T> auto operator()(T t) const { ... }
    template<class T> static auto lambda_call_operator_invoker(T a) {
        // forwards execution to operator()(a) and therefore has
        // the same return type deduced
        ...
    }
    template<class T> using fp_ptr_t =
        decltype(lambda_call_operator_invoker(declval<T>())) (*)(T);

    template<class T> operator fp_ptr_t<T>() const
    { return &lambda_call_operator_invoker; }
};
```

— end note]

[Example:

```
void f1(int (*)(int)) { }
void f2(char (*)(int)) { }

void g(int (*)(int)) { } // #1
void g(char (*)(char)) { } // #2

void h(int (*)(int)) { } // #3
void h(char (*)(int)) { } // #4

auto glambda = [](auto a) { return a; };
f1(glambda); // OK
f2(glambda); // error: ID is not convertible
g(glambda); // error: ambiguous
h(glambda); // OK: calls #3 since it is convertible from ID
```

```
int& (*fpi)(int*) = [](auto* a) -> auto& { return *a; }; // OK
```

— end example]

- 8 The value returned by any given specialization of this conversion function template is the address of a function *F* that, when invoked, has the same effect as invoking the generic lambda's corresponding function call operator template specialization. *F* is a *constexpr* function if the corresponding specialization is a *constexpr* function. [*Note*: This will result in the implicit instantiation of the generic lambda's body. The instantiated generic lambda's return type and parameter types shall match the return type and parameter types of the pointer to function. — end note] [*Example*:

```
auto GL = [](auto a) { std::cout << a; return a; };
int (*GL_int)(int) = GL; // OK: through conversion function template
GL_int(3);               // OK: same as GL(3)
```

— end example]

- 9 The conversion function or conversion function template is public, *constexpr*, non-virtual, non-explicit, const, and has a non-throwing exception specification (18.4). [*Example*:

```
auto Fwd = [](int (*fp)(int), auto a) { return fp(a); };
auto C = [](auto a) { return a; };

static_assert(Fwd(C,3) == 3); // OK
```

// No specialization of the function call operator template can be *constexpr* (due to the local static).

```
auto NC = [](auto a) { static int s; return a; };
static_assert(Fwd(NC,3) == 3); // ill-formed
```

— end example]

- 10 The *lambda-expression*'s *compound-statement* yields the *function-body* (11.4) of the function call operator, but for purposes of name lookup (6.4), determining the type and value of **this** (12.2.2.1) and transforming *id-expressions* referring to non-static class members into class member access expressions using **(*this)** (12.2.2), the *compound-statement* is considered in the context of the *lambda-expression*. [*Example*:

```
struct S1 {
    int x, y;
    int operator()(int);
    void f() {
        [=]() -> int {
            return operator()(this->x + y); // equivalent to S1::operator()(this->x + (*this).y)
                                           // this has type S1*
        };
    }
};
```

— end example] Further, a variable **__func__** is implicitly defined at the beginning of the *compound-statement* of the *lambda-expression*, with semantics as described in 11.4.1.

- 11 The closure type associated with a *lambda-expression* has no default constructor and a deleted copy assignment operator. It has a defaulted copy constructor and a defaulted move constructor (15.8). [*Note*: These special member functions are implicitly defined as usual, and might therefore be defined as deleted. — end note]
- 12 The closure type associated with a *lambda-expression* has an implicitly-declared destructor (15.4).
- 13 A member of a closure type shall not be explicitly instantiated (17.7.2), explicitly specialized (17.7.3), or named in a **friend** declaration (14.3).

8.1.5.2 Captures

[expr.prim.lambda.capture]

```

lambda-capture:
    capture-default
    capture-list
    capture-default , capture-list

capture-default:
    &
    =

capture-list:
    capture ...opt
    capture-list , capture ...opt

capture:
    simple-capture
    init-capture

simple-capture:
    identifier
    & identifier
    this
    * this

init-capture:
    identifier initializer
    & identifier initializer

```

- ¹ The body of a *lambda-expression* may refer to variables with automatic storage duration and the ***this** object (if any) of enclosing block scopes by capturing those entities, as described below.
- ² If a *lambda-capture* includes a *capture-default* that is **&**, no identifier in a *simple-capture* of that *lambda-capture* shall be preceded by **&**. If a *lambda-capture* includes a *capture-default* that is **=**, each *simple-capture* of that *lambda-capture* shall be of the form “**& identifier**” or “*** this**”. [Note: The form [**&,this**] is redundant but accepted for compatibility with ISO C++ 2014. — end note] Ignoring appearances in *initializers* of *init-captures*, an identifier or **this** shall not appear more than once in a *lambda-capture*. [Example:

```

struct S2 { void f(int i); };
void S2::f(int i) {
    [&, i]{ };           // OK
    [&, &i]{ };          // error: i preceded by & when & is the default
    [=, *this]{ };      // OK
    [=, this]{ };       // error: this when = is the default
    [i, i]{ };          // error: i repeated
    [this, *this]{ };   // error: this appears twice
}

```

— end example]

- ³ A *lambda-expression* whose smallest enclosing scope is a block scope (6.3.3) is a *local lambda expression*; any other *lambda-expression* shall not have a *capture-default* or *simple-capture* in its *lambda-introducer*. The *reaching scope* of a local *lambda expression* is the set of enclosing scopes up to and including the innermost enclosing function and its parameters. [Note: This reaching scope includes any intervening *lambda-expressions*. — end note]
- ⁴ The *identifier* in a *simple-capture* is looked up using the usual rules for unqualified name lookup (6.4.1); each such lookup shall find an entity. An entity that is designated by a *simple-capture* is said to be *explicitly captured*, and shall be ***this** (when the *simple-capture* is “**this**” or “*** this**”) or a variable with automatic storage duration declared in the reaching scope of the local *lambda expression*.

- ⁵ If an *identifier* in a *simple-capture* appears as the *declarator-id* of a parameter of the *lambda-declarator*'s *parameter-declaration-clause*, the program is ill-formed. [*Example*:

```
void f() {
    int x = 0;
    auto g = [x](int x) { return 0; }    // error: parameter and simple-capture have the same name
}
```

— *end example*]

- ⁶ An *init-capture* behaves as if it declares and explicitly captures a variable of the form “`auto init-capture ;`” whose declarative region is the *lambda-expression*'s *compound-statement*, except that:

- (6.1) — if the capture is by copy (see below), the non-static data member declared for the capture and the variable are treated as two different ways of referring to the same object, which has the lifetime of the non-static data member, and no additional copy and destruction is performed, and
- (6.2) — if the capture is by reference, the variable's lifetime ends when the closure object's lifetime ends.

[*Note*: This enables an *init-capture* like “`x = std::move(x)`”; the second “`x`” must bind to a declaration in the surrounding context. — *end note*] [*Example*:

```
int x = 4;
auto y = [&r = x, x = x+1]()->int {
    r += 2;
    return x+2;
}();    // Updates ::x to 6, and initializes y to 7.
```

```
auto z = [a = 42](int a) { return 1; }    // error: parameter and local variable have the same name
```

— *end example*]

- ⁷ A *lambda-expression* with an associated *capture-default* that does not explicitly capture `*this` or a variable with automatic storage duration (this excludes any *id-expression* that has been found to refer to an *init-capture*'s associated non-static data member), is said to *implicitly capture* the entity (i.e., `*this` or a variable) if the *compound-statement*:

- (7.1) — odr-uses (6.2) the entity (in the case of a variable),
- (7.2) — odr-uses (6.2) `this` (in the case of the object designated by `*this`), or
- (7.3) — names the entity in a potentially-evaluated expression (6.2) where the enclosing full-expression depends on a generic lambda parameter declared within the reaching scope of the *lambda-expression*.

[*Example*:

```
void f(int, const int (&)[2] = {})    { }    // #1
void f(const int&, const int (&)[1])    { }    // #2
void test() {
    const int x = 17;
    auto g = [](auto a) {
        f(x);                                // OK: calls #1, does not capture x
    };

    auto g2 = [=](auto a) {
        int selector[sizeof(a) == 1 ? 1 : 2]{};
        f(x, selector);                    // OK: is a dependent expression, so captures x
    };
}
```

— *end example*] All such implicitly captured entities shall be declared within the reaching scope of the lambda expression. [*Note*: The implicit capture of an entity by a nested *lambda-expression* can cause its implicit

capture by the containing *lambda-expression* (see below). Implicit odr-uses of **this** can result in implicit capture. — end note]

- ⁸ An entity is *captured* if it is captured explicitly or implicitly. An entity captured by a *lambda-expression* is odr-used (6.2) in the scope containing the *lambda-expression*. If ***this** is captured by a local lambda expression, its nearest enclosing function shall be a non-static member function. If a *lambda-expression* or an instantiation of the function call operator template of a generic lambda odr-uses (6.2) **this** or a variable with automatic storage duration from its reaching scope, that entity shall be captured by the *lambda-expression*. If a *lambda-expression* captures an entity and that entity is not defined or captured in the immediately enclosing lambda expression or function, the program is ill-formed. [*Example*:

```
void f1(int i) {
    int const N = 20;
    auto m1 = [=]{
        int const M = 30;
        auto m2 = [i]{
            int x[N][M];
            x[0][0] = i;
        };
    };
    struct s1 {
        int f;
        void work(int n) {
            int m = n*n;
            int j = 40;
            auto m3 = [this,m] {
                auto m4 = [&,j] {
                    int x = n;
                    x += m;
                    x += i;
                    x += f;
                };
            };
        }
    };
}

struct s2 {
    double ohseven = .007;
    auto f() {
        return [this] {
            return [*this] {
                return ohseven;
            };
        };
    }
    auto g() {
        return [] {
            return [*this] { };
        };
    }
};

— end example]
```

// OK: N and M are not odr-used
// OK: i is explicitly captured by m2 and implicitly captured by m1
// error: j not captured by m3
// error: n implicitly captured by m4 but not captured by m3
// OK: m implicitly captured by m4 and explicitly captured by m3
// error: i is outside of the reaching scope
// OK: this captured implicitly by m4 and explicitly by m3
// OK
// error: *this not captured by outer lambda-expression

- ⁹ A *lambda-expression* appearing in a default argument shall not implicitly or explicitly capture any entity.

[*Example:*

```
void f2() {
    int i = 1;
    void g1(int = ([i]{ return i; })());           // ill-formed
    void g2(int = ([i]{ return 0; })());           // ill-formed
    void g3(int = ([=]{ return i; })());           // ill-formed
    void g4(int = ([=]{ return 0; })());           // OK
    void g5(int = ([ ]{ return sizeof i; })());    // OK
}
```

— *end example*]

10 An entity is *captured by copy* if

- (10.1) — it is implicitly captured, the *capture-default* is `=`, and the captured entity is not `*this`, or
- (10.2) — it is explicitly captured with a capture that is not of the form `this`, `& identifier`, or `& identifier initializer`.

For each entity captured by copy, an unnamed non-static data member is declared in the closure type. The declaration order of these members is unspecified. The type of such a data member is the referenced type if the entity is a reference to an object, an lvalue reference to the referenced function type if the entity is a reference to a function, or the type of the corresponding captured entity otherwise. A member of an anonymous union shall not be captured by copy.

- 11 Every *id-expression* within the *compound-statement* of a *lambda-expression* that is an odr-use (6.2) of an entity captured by copy is transformed into an access to the corresponding unnamed data member of the closure type. [*Note:* An *id-expression* that is not an odr-use refers to the original entity, never to a member of the closure type. Furthermore, such an *id-expression* does not cause the implicit capture of the entity. — *end note*] If `*this` is captured by copy, each odr-use of `this` is transformed into a pointer to the corresponding unnamed data member of the closure type, cast (8.4) to the type of `this`. [*Note:* The cast ensures that the transformed expression is a prvalue. — *end note*] An *id-expression* within the *compound-statement* of a *lambda-expression* that is an odr-use of a reference captured by reference refers to the entity to which the captured reference is bound and not to the captured reference. [*Note:* The validity of such captures is determined by the lifetime of the object to which the reference refers, not by the lifetime of the reference itself. — *end note*] [*Example:*

```
void f(const int*);
void g() {
    const int N = 10;
    [=] {
        int arr[N];           // OK: not an odr-use, refers to automatic variable
        f(&N);                 // OK: causes N to be captured; &N points to
                               // the corresponding member of the closure type
    };
}
auto h(int &r) {
    return [=] {
        ++r;                  // Valid after h returns if the lifetime of the
                               // object to which r is bound has not ended
    };
}
```

— *end example*]

- 12 An entity is *captured by reference* if it is implicitly or explicitly captured but not captured by copy. It is unspecified whether additional unnamed non-static data members are declared in the closure type for entities captured by reference. If declared, such non-static data members shall be of literal type. [*Example:*

// The inner closure type must be a literal type regardless of how reference captures are represented.
`static_assert([](int n) { return [&n] { return ++n; }(); }(3) == 4);`

— *end example*] A bit-field or a member of an anonymous union shall not be captured by reference.

- 13 If a *lambda-expression* `m2` captures an entity and that entity is captured by an immediately enclosing *lambda-expression* `m1`, then `m2`'s capture is transformed as follows:

- (13.1) — if `m1` captures the entity by copy, `m2` captures the corresponding non-static data member of `m1`'s closure type;
- (13.2) — if `m1` captures the entity by reference, `m2` captures the same entity captured by `m1`.

[*Example:* The nested lambda expressions and invocations below will output 123234.

```
int a = 1, b = 1, c = 1;
auto m1 = [a, &b, &c]() mutable {
    auto m2 = [a, b, &c]() mutable {
        std::cout << a << b << c;
        a = 4; b = 4; c = 4;
    };
    a = 3; b = 3; c = 3;
    m2();
};
a = 2; b = 2; c = 2;
m1();
std::cout << a << b << c;
```

— *end example*]

- 14 Every occurrence of `decltype(x)` where `x` is a possibly parenthesized *id-expression* that names an entity of automatic storage duration is treated as if `x` were transformed into an access to a corresponding data member of the closure type that would have been declared if `x` were an odr-use of the denoted entity. [*Example:*

```
void f3() {
    float x, &r = x;
    [=] {
        decltype(x) y1;           // x and r are not captured (appearance in a decltype operand is not an odr-use)
        decltype((x)) y2 = y1;    // y2 has type float const& because this lambda is not mutable and x is an lvalue
        decltype(r) r1 = y1;      // r1 has type float& (transformation not considered)
        decltype((r)) r2 = y2;    // r2 has type float const&
    };
}
```

— *end example*]

- 15 When the *lambda-expression* is evaluated, the entities that are captured by copy are used to direct-initialize each corresponding non-static data member of the resulting closure object, and the non-static data members corresponding to the *init-captures* are initialized as indicated by the corresponding *initializer* (which may be copy- or direct-initialization). (For array members, the array elements are direct-initialized in increasing subscript order.) These initializations are performed in the (unspecified) order in which the non-static data members are declared. [*Note:* This ensures that the destructions will occur in the reverse order of the constructions. — *end note*]
- 16 [*Note:* If a non-reference entity is implicitly or explicitly captured by reference, invoking the function call operator of the corresponding *lambda-expression* after the lifetime of the entity has ended is likely to result in undefined behavior. — *end note*]
- 17 A *simple-capture* followed by an ellipsis is a pack expansion (17.5.3). An *init-capture* followed by an ellipsis is ill-formed. [*Example:*

```
template<class... Args>
void f(Args... args) {
    auto lm = [&, args...] { return g(args...); };
    lm();
}
```

— end example]

8.1.6 Fold expressions

[expr.prim.fold]

- ¹ A fold expression performs a fold of a template parameter pack (17.5.3) over a binary operator.

fold-expression:

```
( cast-expression fold-operator ... )
( ... fold-operator cast-expression )
( cast-expression fold-operator ... fold-operator cast-expression )
```

fold-operator: one of

```
+ - * / % ^ & | << >>
+= -= *= /= %= ^= &= |= <<= >>= =
== != < > <= >= && || , .* ->*
```

- ² An expression of the form (... *op* *e*) where *op* is a *fold-operator* is called a *unary left fold*. An expression of the form (*e op* ...) where *op* is a *fold-operator* is called a *unary right fold*. Unary left folds and unary right folds are collectively called *unary folds*. In a unary fold, the *cast-expression* shall contain an unexpanded parameter pack (17.5.3).
- ³ An expression of the form (*e1 op1* ... *op2 e2*) where *op1* and *op2* are *fold-operators* is called a *binary fold*. In a binary fold, *op1* and *op2* shall be the same *fold-operator*, and either *e1* shall contain an unexpanded parameter pack or *e2* shall contain an unexpanded parameter pack, but not both. If *e2* contains an unexpanded parameter pack, the expression is called a *binary left fold*. If *e1* contains an unexpanded parameter pack, the expression is called a *binary right fold*. [Example:

```
template<typename ...Args>
bool f(Args ...args) {
    return (true && ... && args); // OK
}

template<typename ...Args>
bool f(Args ...args) {
    return (args + ... + args); // error: both operands contain unexpanded parameter packs
}
```

— end example]

8.2 Postfix expressions

[expr.post]

- ¹ Postfix expressions group left-to-right.

postfix-expression:

```

    primary-expression
    postfix-expression [ expr-or-braced-init-list ]
    postfix-expression ( expression-listopt )
    simple-type-specifier ( expression-listopt )
    typename-specifier ( expression-listopt )
    simple-type-specifier braced-init-list
    typename-specifier braced-init-list
    postfix-expression . templateopt id-expression
    postfix-expression -> templateopt id-expression
    postfix-expression . pseudo-destructor-name
    postfix-expression -> pseudo-destructor-name
    postfix-expression ++
    postfix-expression --
    dynamic_cast < type-id > ( expression )
    static_cast < type-id > ( expression )
    reinterpret_cast < type-id > ( expression )
    const_cast < type-id > ( expression )
    typeid ( expression )
    typeid ( type-id )

expression-list:
    initializer-list

pseudo-destructor-name:
    nested-name-specifieropt type-name :: ~ type-name
    nested-name-specifier template simple-template-id :: ~ type-name
    ~ type-name
    ~ decltype-specifier
```

- ² [*Note*: The > token following the *type-id* in a **dynamic_cast**, **static_cast**, **reinterpret_cast**, or **const_cast** may be the product of replacing a >> token by two consecutive > tokens (17.2). — *end note*]

8.2.1 Subscripting

[**expr.sub**]

- ¹ A postfix expression followed by an expression in square brackets is a postfix expression. One of the expressions shall be a glvalue of type “array of T” or a prvalue of type “pointer to T” and the other shall be a prvalue of unscoped enumeration or integral type. The result is of type “T”. The type “T” shall be a completely-defined object type.⁶⁶ The expression E1[E2] is identical (by definition) to *((E1)+(E2)) [*Note*: see 8.3 and 8.7 for details of * and + and 11.3.4 for details of arrays. — *end note*], except that in the case of an array operand, the result is an lvalue if that operand is an lvalue and an xvalue otherwise. The expression E1 is sequenced before the expression E2.
- ² A *braced-init-list* shall not be used with the built-in subscript operator.

8.2.2 Function call

[**expr.call**]

- ¹ A function call is a postfix expression followed by parentheses containing a possibly empty, comma-separated list of *initializer-clauses* which constitute the arguments to the function. The postfix expression shall have function type or function pointer type. For a call to a non-member function or to a static member function, the postfix expression shall be either an lvalue that refers to a function (in which case the function-to-pointer standard conversion (7.3) is suppressed on the postfix expression), or it shall have function pointer type. Calling a function through an expression whose function type is different from the function type of the called function’s definition results in undefined behavior (10.5). For a call to a non-static member function, the postfix expression shall be an implicit (12.2.2, 12.2.3) or explicit class member access (8.2.5) whose

⁶⁶) This is true even if the subscript operator is used in the following common idiom: `&x[0]`.

id-expression is a function member name, or a pointer-to-member expression (8.5) selecting a function member; the call is as a member of the class object referred to by the object expression. In the case of an implicit class member access, the implied object is the one pointed to by **this**. [*Note*: A member function call of the form **f()** is interpreted as **(*this).f()** (see 12.2.2). — *end note*] If a function or member function name is used, the name can be overloaded (Clause 16), in which case the appropriate function shall be selected according to the rules in 16.3. If the selected function is non-virtual, or if the *id-expression* in the class member access expression is a *qualified-id*, that function is called. Otherwise, its final overrider (13.3) in the dynamic type of the object expression is called; such a call is referred to as a *virtual function call*. [*Note*: The dynamic type is the type of the object referred to by the current value of the object expression. 15.7 describes the behavior of virtual function calls when the object expression refers to an object under construction or destruction. — *end note*]

- ² [*Note*: If a function or member function name is used, and name lookup (6.4) does not find a declaration of that name, the program is ill-formed. No function is implicitly declared by such a call. — *end note*]
- ³ If the *postfix-expression* designates a destructor (15.4), the type of the function call expression is **void**; otherwise, the type of the function call expression is the return type of the statically chosen function (i.e., ignoring the **virtual** keyword), even if the type of the function actually called is different. This return type shall be an object type, a reference type or **cv void**.
- ⁴ When a function is called, each parameter (11.3.5) shall be initialized (11.6, 15.8, 15.1) with its corresponding argument. If the function is a non-static member function, the **this** parameter of the function (12.2.2.1) shall be initialized with a pointer to the object of the call, converted as if by an explicit type conversion (8.4). [*Note*: There is no access or ambiguity checking on this conversion; the access checking and disambiguation are done as part of the (possibly implicit) class member access operator. See 13.2, 14.2, and 8.2.5. — *end note*] When a function is called, the parameters that have object type shall have completely-defined object type. [*Note*: this still allows a parameter to be a pointer or reference to an incomplete class type. However, it prevents a passed-by-value parameter to have an incomplete class type. — *end note*] It is implementation-defined whether the lifetime of a parameter ends when the function in which it is defined returns or at the end of the enclosing full-expression. The initialization and destruction of each parameter occurs within the context of the calling function. [*Example*: The access of the constructor, conversion functions or destructor is checked at the point of call in the calling function. If a constructor or destructor for a function parameter throws an exception, the search for a handler starts in the scope of the calling function; in particular, if the function called has a *function-try-block* (Clause 18) with a handler that could handle the exception, this handler is not considered. — *end example*]
- ⁵ The *postfix-expression* is sequenced before each *expression* in the *expression-list* and any default argument. The initialization of a parameter, including every associated value computation and side effect, is indeterminately sequenced with respect to that of any other parameter. [*Note*: All side effects of argument evaluations are sequenced before the function is entered (see 4.6). — *end note*] [*Example*:

```
void f() {
    std::string s = "but I have heard it works even if you don't believe in it";
    s.replace(0, 4, "").replace(s.find("even"), 4, "only").replace(s.find(" don't"), 6, "");
    assert(s == "I have heard it works only if you believe in it"); // OK
}
```

— *end example*] [*Note*: If an operator function is invoked using operator notation, argument evaluation is sequenced as specified for the built-in operator; see 16.3.1.2. — *end note*] [*Example*:

```
struct S {
    S(int);
};
int operator<<(S, int);
int i, j;
int x = S(i=1) << (i=2);
```

```
int y = operator<<(S(j=1), j=2);
```

After performing the initializations, the value of `i` is 2 (see 8.8), but it is unspecified whether the value of `j` is 1 or 2. — *end example*

- 6 The result of a function call is the result of the operand of the evaluated **return** statement (9.6.3) in the called function (if any), except in a virtual function call if the return type of the final overrider is different from the return type of the statically chosen function, the value returned from the final overrider is converted to the return type of the statically chosen function.
- 7 [*Note*: A function can change the values of its non-const parameters, but these changes cannot affect the values of the arguments except where a parameter is of a reference type (11.3.2); if the reference is to a const-qualified type, **const_cast** is required to be used to cast away the constness in order to modify the argument's value. Where a parameter is of **const** reference type a temporary object is introduced if needed (10.1.7, 5.13, 5.13.5, 11.3.4, 15.2). In addition, it is possible to modify the values of non-constant objects through pointer parameters. — *end note*]
- 8 A function can be declared to accept fewer arguments (by declaring default arguments (11.3.6)) or more arguments (by using the ellipsis, `...`, or a function parameter pack (11.3.5)) than the number of parameters in the function definition (11.4). [*Note*: This implies that, except where the ellipsis (`...`) or a function parameter pack is used, a parameter is available for each argument. — *end note*]
- 9 When there is no parameter for a given argument, the argument is passed in such a way that the receiving function can obtain the value of the argument by invoking **va_arg** (21.10). [*Note*: This paragraph does not apply to arguments passed to a function parameter pack. Function parameter packs are expanded during template instantiation (17.5.3), thus each such argument has a corresponding parameter when a function template specialization is actually called. — *end note*] The lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are performed on the argument expression. An argument that has type `cv std::nullptr_t` is converted to type `void*` (7.11). After these conversions, if the argument does not have arithmetic, enumeration, pointer, pointer to member, or class type, the program is ill-formed. Passing a potentially-evaluated argument of class type (Clause 12) having a non-trivial copy constructor, a non-trivial move constructor, or a non-trivial destructor, with no corresponding parameter, is conditionally-supported with implementation-defined semantics. If the argument has integral or enumeration type that is subject to the integral promotions (7.6), or a floating-point type that is subject to the floating-point promotion (7.7), the value of the argument is converted to the promoted type before the call. These promotions are referred to as the *default argument promotions*.
- 10 Recursive calls are permitted, except to the **main** function (6.6.1).
- 11 A function call is an lvalue if the result type is an lvalue reference type or an rvalue reference to function type, an xvalue if the result type is an rvalue reference to object type, and a prvalue otherwise.

8.2.3 Explicit type conversion (functional notation)

[**expr.type.conv**]

- 1 A *simple-type-specifier* (10.1.7.2) or *typename-specifier* (17.6) followed by a parenthesized optional *expression-list* or by a *braced-init-list* (the initializer) constructs a value of the specified type given the initializer. If the type is a placeholder for a deduced class type, it is replaced by the return type of the function selected by overload resolution for class template deduction (16.3.1.8) for the remainder of this section.
- 2 If the initializer is a parenthesized single expression, the type conversion expression is equivalent (in definedness, and if defined in meaning) to the corresponding cast expression (8.4). If the type is `cv void` and the initializer is `()`, the expression is a prvalue of the specified type that performs no initialization. Otherwise, the expression is a prvalue of the specified type whose result object is direct-initialized (11.6) with the initializer. For an expression of the form `T()`, `T` shall not be an array type.

8.2.4 Pseudo destructor call

[expr.pseudo]

- ¹ The use of a *pseudo-destructor-name* after a dot `.` or arrow `->` operator represents the destructor for the non-class type denoted by *type-name* or *decltype-specifier*. The result shall only be used as the operand for the function call operator `()`, and the result of such a call has type `void`. The only effect is the evaluation of the *postfix-expression* before the dot or arrow.
- ² The left-hand side of the dot operator shall be of scalar type. The left-hand side of the arrow operator shall be of pointer to scalar type. This scalar type is the object type. The *cv-unqualified* versions of the object type and of the type designated by the *pseudo-destructor-name* shall be the same type. Furthermore, the two *type-names* in a *pseudo-destructor-name* of the form

*nested-name-specifier*_{opt} *type-name* `::` `~` *type-name*

shall designate the same scalar type (ignoring cv-qualification).

8.2.5 Class member access

[expr.ref]

- ¹ A postfix expression followed by a dot `.` or an arrow `->`, optionally followed by the keyword `template` (17.2), and then followed by an *id-expression*, is a postfix expression. The postfix expression before the dot or arrow is evaluated;⁶⁷ the result of that evaluation, together with the *id-expression*, determines the result of the entire postfix expression.
- ² For the first option (dot) the first expression shall be a glvalue having complete class type. For the second option (arrow) the first expression shall be a prvalue having pointer to complete class type. The expression `E1->E2` is converted to the equivalent form `*(E1).E2`; the remainder of 8.2.5 will address only the first option (dot).⁶⁸ In either case, the *id-expression* shall name a member of the class or of one of its base classes. [Note: Because the name of a class is inserted in its class scope (Clause 12), the name of a class is also considered a nested member of that class. — end note] [Note: 6.4.5 describes how names are looked up after the `.` and `->` operators. — end note]
- ³ Abbreviating *postfix-expression.id-expression* as `E1.E2`, `E1` is called the *object expression*. If `E2` is a bit-field, `E1.E2` is a bit-field. The type and value category of `E1.E2` are determined as follows. In the remainder of 8.2.5, *cq* represents either `const` or the absence of `const` and *vol* represents either `volatile` or the absence of `volatile`. *cv* represents an arbitrary set of cv-qualifiers, as defined in 6.9.3.
- ⁴ If `E2` is declared to have type “reference to T”, then `E1.E2` is an lvalue; the type of `E1.E2` is T. Otherwise, one of the following rules applies.
 - (4.1) — If `E2` is a static data member and the type of `E2` is T, then `E1.E2` is an lvalue; the expression designates the named member of the class. The type of `E1.E2` is T.
 - (4.2) — If `E2` is a non-static data member and the type of `E1` is “*cq1 vol1* X”, and the type of `E2` is “*cq2 vol2* T”, the expression designates the named member of the object designated by the first expression. If `E1` is an lvalue, then `E1.E2` is an lvalue; otherwise `E1.E2` is an xvalue. Let the notation *vol12* stand for the “union” of *vol1* and *vol2*; that is, if *vol1* or *vol2* is `volatile`, then *vol12* is `volatile`. Similarly, let the notation *cq12* stand for the “union” of *cq1* and *cq2*; that is, if *cq1* or *cq2* is `const`, then *cq12* is `const`. If `E2` is declared to be a `mutable` member, then the type of `E1.E2` is “*vol12* T”. If `E2` is not declared to be a `mutable` member, then the type of `E1.E2` is “*cq12 vol12* T”.
 - (4.3) — If `E2` is a (possibly overloaded) member function, function overload resolution (16.3) is used to determine whether `E1.E2` refers to a static or a non-static member function.
 - (4.3.1) — If it refers to a static member function and the type of `E2` is “function of parameter-type-list returning T”, then `E1.E2` is an lvalue; the expression designates the static member function. The type of `E1.E2` is the same type as that of `E2`, namely “function of parameter-type-list returning T”.

⁶⁷ If the class member access expression is evaluated, the subexpression evaluation happens even if the result is unnecessary to determine the value of the entire postfix expression, for example if the *id-expression* denotes a static member.

⁶⁸ Note that `*(E1)` is an lvalue.

- (4.3.2) — Otherwise, if **E1.E2** refers to a non-static member function and the type of **E2** is “function of parameter-type-list *cv ref-qualifier_{opt}* returning **T**”, then **E1.E2** is a prvalue. The expression designates a non-static member function. The expression can be used only as the left-hand operand of a member function call (12.2.1). [*Note*: Any redundant set of parentheses surrounding the expression is ignored (8.1). — *end note*] The type of **E1.E2** is “function of parameter-type-list *cv* returning **T**”.
- (4.4) — If **E2** is a nested type, the expression **E1.E2** is ill-formed.
- (4.5) — If **E2** is a member enumerator and the type of **E2** is **T**, the expression **E1.E2** is a prvalue. The type of **E1.E2** is **T**.
- 5 If **E2** is a non-static data member or a non-static member function, the program is ill-formed if the class of which **E2** is directly a member is an ambiguous base (13.2) of the naming class (14.2) of **E2**. [*Note*: The program is also ill-formed if the naming class is an ambiguous base of the class type of the object expression; see 14.2. — *end note*]

8.2.6 Increment and decrement

[**expr.post.incr**]

- 1 The value of a postfix **++** expression is the value of its operand. [*Note*: The value obtained is a copy of the original value — *end note*] The operand shall be a modifiable lvalue. The type of the operand shall be an arithmetic type other than *cv bool*, or a pointer to a complete object type. The value of the operand object is modified by adding 1 to it. The value computation of the **++** expression is sequenced before the modification of the operand object. With respect to an indeterminately-sequenced function call, the operation of postfix **++** is a single evaluation. [*Note*: Therefore, a function call shall not intervene between the lvalue-to-rvalue conversion and the side effect associated with any single postfix **++** operator. — *end note*] The result is a prvalue. The type of the result is the *cv*-unqualified version of the type of the operand. If the operand is a bit-field that cannot represent the incremented value, the resulting value of the bit-field is implementation-defined. See also 8.7 and 8.18.
- 2 The operand of postfix **--** is decremented analogously to the postfix **++** operator. [*Note*: For prefix increment and decrement, see 8.3.2. — *end note*]

8.2.7 Dynamic cast

[**expr.dynamic.cast**]

- 1 The result of the expression **dynamic_cast<T>(v)** is the result of converting the expression **v** to type **T**. **T** shall be a pointer or reference to a complete class type, or “pointer to *cv void*”. The **dynamic_cast** operator shall not cast away constness (8.2.11).
- 2 If **T** is a pointer type, **v** shall be a prvalue of a pointer to complete class type, and the result is a prvalue of type **T**. If **T** is an lvalue reference type, **v** shall be an lvalue of a complete class type, and the result is an lvalue of the type referred to by **T**. If **T** is an rvalue reference type, **v** shall be a glvalue having a complete class type, and the result is an xvalue of the type referred to by **T**.
- 3 If the type of **v** is the same as **T**, or it is the same as **T** except that the class object type in **T** is more *cv*-qualified than the class object type in **v**, the result is **v** (converted if necessary).
- 4 If the value of **v** is a null pointer value in the pointer case, the result is the null pointer value of type **T**.
- 5 If **T** is “pointer to *cv1* **B**” and **v** has type “pointer to *cv2* **D**” such that **B** is a base class of **D**, the result is a pointer to the unique **B** subobject of the **D** object pointed to by **v**. Similarly, if **T** is “reference to *cv1* **B**” and **v** has type *cv2* **D** such that **B** is a base class of **D**, the result is the unique **B** subobject of the **D** object referred to by **v**.⁶⁹ In both the pointer and reference cases, the program is ill-formed if *cv2* has greater *cv*-qualification than *cv1* or if **B** is an inaccessible or ambiguous base class of **D**. [*Example*:

```
struct B { };
struct D : B { };
```

⁶⁹ The most derived object (4.5) pointed or referred to by **v** can contain other **B** objects as base classes, but these are ignored.


```
void foo(D* dp) {
    B* bp = dynamic_cast<B*>(dp);    // equivalent to B* bp = dp;
}
```

— end example]

- 6 Otherwise, *v* shall be a pointer to or a glvalue of a polymorphic type (13.3).
- 7 If *T* is “pointer to *cv* void”, then the result is a pointer to the most derived object pointed to by *v*. Otherwise, a runtime check is applied to see if the object pointed or referred to by *v* can be converted to the type pointed or referred to by *T*.
- 8 If *C* is the class type to which *T* points or refers, the runtime check logically executes as follows:
 - (8.1) — If, in the most derived object pointed (referred) to by *v*, *v* points (refers) to a **public** base class subobject of a *C* object, and if only one object of type *C* is derived from the subobject pointed (referred) to by *v* the result points (refers) to that *C* object.
 - (8.2) — Otherwise, if *v* points (refers) to a **public** base class subobject of the most derived object, and the type of the most derived object has a base class, of type *C*, that is unambiguous and **public**, the result points (refers) to the *C* subobject of the most derived object.
 - (8.3) — Otherwise, the runtime check *fails*.
- 9 The value of a failed cast to pointer type is the null pointer value of the required result type. A failed cast to reference type throws an exception (18.1) of a type that would match a handler (18.3) of type `std::bad_cast` (21.7.3).

[Example:

```
class A { virtual void f(); };
class B { virtual void g(); };
class D : public virtual A, private B { };
void g() {
    D d;
    B* bp = (B*)&d;                // cast needed to break protection
    A* ap = &d;                    // public derivation, no cast needed
    D& dr = dynamic_cast<D&>(*bp); // fails
    ap = dynamic_cast<A*>(bp);      // fails
    bp = dynamic_cast<B*>(ap);      // fails
    ap = dynamic_cast<A*>(&d);      // succeeds
    bp = dynamic_cast<B*>(&d);      // ill-formed (not a runtime check)
}

class E : public D, public B { };
class F : public E, public D { };
void h() {
    F f;
    A* ap = &f;                    // succeeds: finds unique A
    D* dp = dynamic_cast<D*>(ap);   // fails: yields null; f has two D subobjects
    E* ep = (E*)ap;                // ill-formed: cast from virtual base
    E* ep1 = dynamic_cast<E*>(ap);  // succeeds
}
```

— end example] [Note: 15.7 describes the behavior of a `dynamic_cast` applied to an object under construction or destruction. — end note]

8.2.8 Type identification

[`expr.typeid`]

- 1 The result of a `typeid` expression is an lvalue of static type `const std::type_info` (21.7.2) and dynamic type `const std::type_info` or `const name` where *name* is an implementation-defined class publicly derived from

`std::type_info` which preserves the behavior described in 21.7.2.⁷⁰ The lifetime of the object referred to by the lvalue extends to the end of the program. Whether or not the destructor is called for the `std::type_info` object at the end of the program is unspecified.

- ² When `typeid` is applied to a glvalue expression whose type is a polymorphic class type (13.3), the result refers to a `std::type_info` object representing the type of the most derived object (4.5) (that is, the dynamic type) to which the glvalue refers. If the glvalue expression is obtained by applying the unary `*` operator to a pointer⁷¹ and the pointer is a null pointer value (7.11), the `typeid` expression throws an exception (18.1) of a type that would match a handler of type `std::bad_typeid` exception (21.7.4).
- ³ When `typeid` is applied to an expression other than a glvalue of a polymorphic class type, the result refers to a `std::type_info` object representing the static type of the expression. Lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) conversions are not applied to the expression. If the expression is a prvalue, the temporary materialization conversion (7.4) is applied. The expression is an unevaluated operand (Clause 8).
- ⁴ When `typeid` is applied to a *type-id*, the result refers to a `std::type_info` object representing the type of the *type-id*. If the type of the *type-id* is a reference to a possibly cv-qualified type, the result of the `typeid` expression refers to a `std::type_info` object representing the cv-unqualified referenced type. If the type of the *type-id* is a class type or a reference to a class type, the class shall be completely-defined.
- ⁵ If the type of the expression or *type-id* is a cv-qualified type, the result of the `typeid` expression refers to a `std::type_info` object representing the cv-unqualified type. [*Example:*

```
class D { /* ... */ };
D d1;
const D d2;

typeid(d1) == typeid(d2);           // yields true
typeid(D)  == typeid(const D);      // yields true
typeid(D)  == typeid(d2);           // yields true
typeid(D)  == typeid(const D&);     // yields true
```

— end example]

- ⁶ If the header `<typeinfo>` (21.7.2) is not included prior to a use of `typeid`, the program is ill-formed.
- ⁷ [*Note:* 15.7 describes the behavior of `typeid` applied to an object under construction or destruction. — end note]

8.2.9 Static cast

[`expr.static.cast`]

- ¹ The result of the expression `static_cast<T>(v)` is the result of converting the expression `v` to type `T`. If `T` is an lvalue reference type or an rvalue reference to function type, the result is an lvalue; if `T` is an rvalue reference to object type, the result is an xvalue; otherwise, the result is a prvalue. The `static_cast` operator shall not cast away constness (8.2.11).
- ² An lvalue of type “*cv1* B”, where `B` is a class type, can be cast to type “reference to *cv2* D”, where `D` is a class derived (Clause 13) from `B`, if *cv2* is the same cv-qualification as, or greater cv-qualification than, *cv1*. If `B` is a virtual base class of `D` or a base class of a virtual base class of `D`, or if no valid standard conversion from “pointer to D” to “pointer to B” exists (7.11), the program is ill-formed. An xvalue of type “*cv1* B” can be cast to type “rvalue reference to *cv2* D” with the same constraints as for an lvalue of type “*cv1* B”. If the object of type “*cv1* B” is actually a base class subobject of an object of type `D`, the result refers to the enclosing object of type `D`. Otherwise, the behavior is undefined. [*Example:*

```
struct B { };
```

⁷⁰) The recommended name for such a class is `extended_type_info`.

⁷¹) If `p` is an expression of pointer type, then `*p`, `(*p)`, `*(&p)`, `*((p))`, `*(&(p))`, and so on all meet this requirement.

```

struct D : public B { };
D d;
B &br = d;

```

```

static_cast<D*>(br);           // produces lvalue to the original d object

```

— end example]

- 3 An lvalue of type “*cv1 T1*” can be cast to type “*rvalue reference to cv2 T2*” if “*cv2 T2*” is reference-compatible with “*cv1 T1*” (11.6.3). If the value is not a bit-field, the result refers to the object or the specified base class subobject thereof; otherwise, the lvalue-to-rvalue conversion (7.1) is applied to the bit-field and the resulting prvalue is used as the *expression* of the `static_cast` for the remainder of this section. If *T2* is an inaccessible (Clause 14) or ambiguous (13.2) base class of *T1*, a program that necessitates such a cast is ill-formed.
- 4 An expression *e* can be explicitly converted to a type *T* if there is an implicit conversion sequence (16.3.3.1) from *e* to *T*, or if overload resolution for a direct-initialization (11.6) of an object or reference of type *T* from *e* would find at least one viable function (16.3.2). If *T* is a reference type, the effect is the same as performing the declaration and initialization

```

T t(e);

```

for some invented temporary variable *t* (11.6) and then using the temporary variable as the result of the conversion. Otherwise, the result object is direct-initialized from *e*. [Note: The conversion is ill-formed when attempting to convert an expression of class type to an inaccessible or ambiguous base class. — end note]

- 5 Otherwise, the `static_cast` shall perform one of the conversions listed below. No other conversion shall be performed explicitly using a `static_cast`.
- 6 Any expression can be explicitly converted to type *cv void*, in which case it becomes a discarded-value expression (Clause 8). [Note: However, if the value is in a temporary object (15.2), the destructor for that object is not executed until the usual time, and the value of the object is preserved for the purpose of executing the destructor. — end note]
- 7 The inverse of any standard conversion sequence (Clause 7) not containing an lvalue-to-rvalue (7.1), array-to-pointer (7.2), function-to-pointer (7.3), null pointer (7.11), null member pointer (7.12), boolean (7.14), or function pointer (7.13) conversion, can be performed explicitly using `static_cast`. A program is ill-formed if it uses `static_cast` to perform the inverse of an ill-formed standard conversion sequence. [Example:

```

struct B { };
struct D : private B { };
void f() {
    static_cast<D*>((B*)0);           // error: B is a private base of D
    static_cast<int B::*>((int D::*)0); // error: B is a private base of D
}

```

— end example]

- 8 The lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) conversions are applied to the operand. Such a `static_cast` is subject to the restriction that the explicit conversion does not cast away constness (8.2.11), and the following additional rules for specific cases:
- 9 A value of a scoped enumeration type (10.2) can be explicitly converted to an integral type. When that type is *cv bool*, the resulting value is `false` if the original value is zero and `true` for all other values. For the remaining integral types, the value is unchanged if the original value can be represented by the specified type. Otherwise, the resulting value is unspecified. A value of a scoped enumeration type can also be explicitly converted to a floating-point type; the result is the same as that of converting from the original value to the floating-point type.
- 10 A value of integral or enumeration type can be explicitly converted to a complete enumeration type. The value is unchanged if the original value is within the range of the enumeration values (10.2). Otherwise, the behavior

is undefined. A value of floating-point type can also be explicitly converted to an enumeration type. The resulting value is the same as converting the original value to the underlying type of the enumeration (7.10), and subsequently to the enumeration type.

- 11 A prvalue of type “pointer to *cv1* B”, where B is a class type, can be converted to a prvalue of type “pointer to *cv2* D”, where D is a class derived (Clause 13) from B, if *cv2* is the same cv-qualification as, or greater cv-qualification than, *cv1*. If B is a virtual base class of D or a base class of a virtual base class of D, or if no valid standard conversion from “pointer to D” to “pointer to B” exists (7.11), the program is ill-formed. The null pointer value (7.11) is converted to the null pointer value of the destination type. If the prvalue of type “pointer to *cv1* B” points to a B that is actually a subobject of an object of type D, the resulting pointer points to the enclosing object of type D. Otherwise, the behavior is undefined.
- 12 A prvalue of type “pointer to member of D of type *cv1* T” can be converted to a prvalue of type “pointer to member of B of type *cv2* T”, where B is a base class (Clause 13) of D, if *cv2* is the same cv-qualification as, or greater cv-qualification than, *cv1*.⁷² If no valid standard conversion from “pointer to member of B of type T” to “pointer to member of D of type T” exists (7.12), the program is ill-formed. The null member pointer value (7.12) is converted to the null member pointer value of the destination type. If class B contains the original member, or is a base or derived class of the class containing the original member, the resulting pointer to member points to the original member. Otherwise, the behavior is undefined. [*Note*: Although class B need not contain the original member, the dynamic type of the object with which indirection through the pointer to member is performed must contain the original member; see 8.5. — *end note*]
- 13 A prvalue of type “pointer to *cv1* void” can be converted to a prvalue of type “pointer to *cv2* T”, where T is an object type and *cv2* is the same cv-qualification as, or greater cv-qualification than, *cv1*. If the original pointer value represents the address A of a byte in memory and A does not satisfy the alignment requirement of T, then the resulting pointer value is unspecified. Otherwise, if the original pointer value points to an object *a*, and there is an object *b* of type T (ignoring cv-qualification) that is pointer-interconvertible (6.9.2) with *a*, the result is a pointer to *b*. Otherwise, the pointer value is unchanged by the conversion. [*Example*:

```
T* p1 = new T;
const T* p2 = static_cast<const T*>(static_cast<void*>(p1));
bool b = p1 == p2;  // b will have the value true.
```

— *end example*]

8.2.10 Reinterpret cast

[**expr.reinterpret.cast**]

- 1 The result of the expression **reinterpret_cast**<T>(v) is the result of converting the expression v to type T. If T is an lvalue reference type or an rvalue reference to function type, the result is an lvalue; if T is an rvalue reference to object type, the result is an xvalue; otherwise, the result is a prvalue and the lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are performed on the expression v. Conversions that can be performed explicitly using **reinterpret_cast** are listed below. No other conversion can be performed explicitly using **reinterpret_cast**.
- 2 The **reinterpret_cast** operator shall not cast away constness (8.2.11). An expression of integral, enumeration, pointer, or pointer-to-member type can be explicitly converted to its own type; such a cast yields the value of its operand.
- 3 [*Note*: The mapping performed by **reinterpret_cast** might, or might not, produce a representation different from the original value. — *end note*]
- 4 A pointer can be explicitly converted to any integral type large enough to hold it. The mapping function is implementation-defined. [*Note*: It is intended to be unsurprising to those who know the addressing structure of the underlying machine. — *end note*] A value of type **std::nullptr_t** can be converted to an integral type; the conversion has the same meaning and validity as a conversion of (void*)0 to the integral type.

⁷² Function types (including those used in pointer to member function types) are never cv-qualified; see 11.3.5.

[*Note:* A `reinterpret_cast` cannot be used to convert a value of any type to the type `std::nullptr_t`. — *end note*]

- 5 A value of integral type or enumeration type can be explicitly converted to a pointer. A pointer converted to an integer of sufficient size (if any such exists on the implementation) and back to the same pointer type will have its original value; mappings between pointers and integers are otherwise implementation-defined. [*Note:* Except as described in 6.7.4.3, the result of such a conversion will not be a safely-derived pointer value. — *end note*]
- 6 A function pointer can be explicitly converted to a function pointer of a different type. [*Note:* The effect of calling a function through a pointer to a function type (11.3.5) that is not the same as the type used in the definition of the function is undefined. — *end note*] Except that converting a prvalue of type “pointer to T1” to the type “pointer to T2” (where T1 and T2 are function types) and back to its original type yields the original pointer value, the result of such a pointer conversion is unspecified. [*Note:* See also 7.11 for more details of pointer conversions. — *end note*]
- 7 An object pointer can be explicitly converted to an object pointer of a different type.⁷³ When a prvalue *v* of object pointer type is converted to the object pointer type “pointer to *cv* T”, the result is `static_cast<cv T*>(static_cast<cv void*>(v))`. [*Note:* Converting a prvalue of type “pointer to T1” to the type “pointer to T2” (where T1 and T2 are object types and where the alignment requirements of T2 are no stricter than those of T1) and back to its original type yields the original pointer value. — *end note*]
- 8 Converting a function pointer to an object pointer type or vice versa is conditionally-supported. The meaning of such a conversion is implementation-defined, except that if an implementation supports conversions in both directions, converting a prvalue of one type to the other type and back, possibly with different *cv*-qualification, shall yield the original pointer value.
- 9 The null pointer value (7.11) is converted to the null pointer value of the destination type. [*Note:* A null pointer constant of type `std::nullptr_t` cannot be converted to a pointer type, and a null pointer constant of integral type is not necessarily converted to a null pointer value. — *end note*]
- 10 A prvalue of type “pointer to member of X of type T1” can be explicitly converted to a prvalue of a different type “pointer to member of Y of type T2” if T1 and T2 are both function types or both object types.⁷⁴ The null member pointer value (7.12) is converted to the null member pointer value of the destination type. The result of this conversion is unspecified, except in the following cases:
 - (10.1) — converting a prvalue of type “pointer to member function” to a different pointer to member function type and back to its original type yields the original pointer to member value.
 - (10.2) — converting a prvalue of type “pointer to data member of X of type T1” to the type “pointer to data member of Y of type T2” (where the alignment requirements of T2 are no stricter than those of T1) and back to its original type yields the original pointer to member value.
- 11 A glvalue expression of type T1 can be cast to the type “reference to T2” if an expression of type “pointer to T1” can be explicitly converted to the type “pointer to T2” using a `reinterpret_cast`. The result refers to the same object as the source glvalue, but with the specified type. [*Note:* That is, for lvalues, a reference cast `reinterpret_cast<T&>(x)` has the same effect as the conversion `*reinterpret_cast<T*>(&x)` with the built-in `&` and `*` operators (and similarly for `reinterpret_cast<T&&>(x)`). — *end note*] No temporary is created, no copy is made, and constructors (15.1) or conversion functions (15.3) are not called.⁷⁵

⁷³) The types may have different *cv*-qualifiers, subject to the overall restriction that a `reinterpret_cast` cannot cast away constness.

⁷⁴) T1 and T2 may have different *cv*-qualifiers, subject to the overall restriction that a `reinterpret_cast` cannot cast away constness.

⁷⁵) This is sometimes referred to as a *type pun*.

8.2.11 Const cast

[expr.const.cast]

- ¹ The result of the expression `const_cast<T>(v)` is of type T. If T is an lvalue reference to object type, the result is an lvalue; if T is an rvalue reference to object type, the result is an xvalue; otherwise, the result is a prvalue and the lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are performed on the expression v. Conversions that can be performed explicitly using `const_cast` are listed below. No other conversion shall be performed explicitly using `const_cast`.

- ² [Note: Subject to the restrictions in this section, an expression may be cast to its own type using a `const_cast` operator. — end note]

- ³ For two similar types T1 and T2 (7.5), a prvalue of type T1 may be explicitly converted to the type T2 using a `const_cast`. The result of a `const_cast` refers to the original entity. [Example:

```
typedef int *A[3];           // array of 3 pointer to int
typedef const int *const CA[3]; // array of 3 const pointer to const int

CA &&r = A{}; // OK, reference binds to temporary array object after qualification conversion to type CA
A &&r1 = const_cast<A>(CA{}); // error: temporary array decayed to pointer
A &&r2 = const_cast<A&&>(CA{}); // OK
```

— end example]

- ⁴ For two object types T1 and T2, if a pointer to T1 can be explicitly converted to the type “pointer to T2” using a `const_cast`, then the following conversions can also be made:
- (4.1) — an lvalue of type T1 can be explicitly converted to an lvalue of type T2 using the cast `const_cast<T2&&>`;
- (4.2) — a glvalue of type T1 can be explicitly converted to an xvalue of type T2 using the cast `const_cast<T2&&>`; and
- (4.3) — if T1 is a class type, a prvalue of type T1 can be explicitly converted to an xvalue of type T2 using the cast `const_cast<T2&&>`.

The result of a reference `const_cast` refers to the original object if the operand is a glvalue and to the result of applying the temporary materialization conversion (7.4) otherwise.

- ⁵ A null pointer value (7.11) is converted to the null pointer value of the destination type. The null member pointer value (7.12) is converted to the null member pointer value of the destination type.
- ⁶ [Note: Depending on the type of the object, a write operation through the pointer, lvalue or pointer to data member resulting from a `const_cast` that casts away a const-qualifier⁷⁶ may produce undefined behavior (10.1.7.1). — end note]
- ⁷ A conversion from a type T1 to a type T2 *casts away constness* if T1 and T2 are different, there is a cv-decomposition (7.5) of T1 yielding n such that T2 has a cv-decomposition of the form

$$cv_0^2 P_0^2 cv_1^2 P_1^2 \cdots cv_{n-1}^2 P_{n-1}^2 cv_n^2 U_2,$$

and there is no qualification conversion that converts T1 to

$$cv_0^2 P_0^1 cv_1^2 P_1^1 \cdots cv_{n-1}^2 P_{n-1}^1 cv_n^2 U_1.$$

- ⁸ Casting from an lvalue of type T1 to an lvalue of type T2 using an lvalue reference cast or casting from an expression of type T1 to an xvalue of type T2 using an rvalue reference cast casts away constness if a cast from a prvalue of type “pointer to T1” to the type “pointer to T2” casts away constness.
- ⁹ [Note: Some conversions which involve only changes in cv-qualification cannot be done using `const_cast`. For instance, conversions between pointers to functions are not covered because such conversions lead to values whose use causes undefined behavior. For the same reasons, conversions between pointers to member functions, and in particular, the conversion from a pointer to a const member function to a pointer to a

⁷⁶ `const_cast` is not limited to conversions that cast away a const-qualifier.

non-const member function, are not covered. — *end note*]

8.3 Unary expressions

[**expr.unary**]

- ¹ Expressions with unary operators group right-to-left.

```
unary-expression:
    postfix-expression
    ++ cast-expression
    -- cast-expression
    unary-operator cast-expression
    sizeof unary-expression
    sizeof ( type-id )
    sizeof ... ( identifier )
    alignof ( type-id )
    noexcept-expression
    new-expression
    delete-expression

unary-operator: one of
    * & + - ! ~
```

8.3.1 Unary operators

[**expr.unary.op**]

- ¹ The unary `*` operator performs *indirection*: the expression to which it is applied shall be a pointer to an object type, or a pointer to a function type and the result is an lvalue referring to the object or function to which the expression points. If the type of the expression is “pointer to T”, the type of the result is “T”. [*Note*: Indirection through a pointer to an incomplete type (other than *cv void*) is valid. The lvalue thus obtained can be used in limited ways (to initialize a reference, for example); this lvalue must not be converted to a prvalue, see 7.1. — *end note*]
- ² The result of each of the following unary operators is a prvalue.
- ³ The result of the unary `&` operator is a pointer to its operand. The operand shall be an lvalue or a *qualified-id*. If the operand is a *qualified-id* naming a non-static or variant member *m* of some class *C* with type *T*, the result has type “pointer to member of class *C* of type *T*” and is a prvalue designating *C::m*. Otherwise, if the type of the expression is *T*, the result has type “pointer to *T*” and is a prvalue that is the address of the designated object (4.4) or a pointer to the designated function. [*Note*: In particular, the address of an object of type “*cv T*” is “pointer to *cv T*”, with the same *cv*-qualification. — *end note*] For purposes of pointer arithmetic (8.7) and comparison (8.9, 8.10), an object that is not an array element whose address is taken in this way is considered to belong to an array with one element of type *T*. [*Example*:

```
struct A { int i; };
struct B : A { };
... &B::i ...      // has type int A::*
int a;
int* p1 = &a;
int* p2 = p1 + 1;    // defined behavior
bool b = p2 > p1;    // defined behavior, with value true
```

— *end example*] [*Note*: A pointer to member formed from a **mutable** non-static data member (10.1.1) does not reflect the **mutable** specifier associated with the non-static data member. — *end note*]

- ⁴ A pointer to member is only formed when an explicit `&` is used and its operand is a *qualified-id* not enclosed in parentheses. [*Note*: That is, the expression `&(qualified-id)`, where the *qualified-id* is enclosed in parentheses, does not form an expression of type “pointer to member”. Neither does *qualified-id*, because there is no implicit conversion from a *qualified-id* for a non-static member function to the type “pointer to member function” as there is from an lvalue of function type to the type “pointer to function” (7.3). Nor is `&unqualified-id` a pointer to member, even within the scope of the *unqualified-id*’s class. — *end note*]

- 5 If `&` is applied to an lvalue of incomplete class type and the complete type declares `operator&()`, it is unspecified whether the operator has the built-in meaning or the operator function is called. The operand of `&` shall not be a bit-field.
- 6 The address of an overloaded function (Clause 16) can be taken only in a context that uniquely determines which version of the overloaded function is referred to (see 16.4). [*Note:* Since the context might determine whether the operand is a static or non-static member function, the context can also affect whether the expression has type “pointer to function” or “pointer to member function”. — *end note*]
- 7 The operand of the unary `+` operator shall have arithmetic, unscoped enumeration, or pointer type and the result is the value of the argument. Integral promotion is performed on integral or enumeration operands. The type of the result is the type of the promoted operand.
- 8 The operand of the unary `-` operator shall have arithmetic or unscoped enumeration type and the result is the negation of its operand. Integral promotion is performed on integral or enumeration operands. The negative of an unsigned quantity is computed by subtracting its value from 2^n , where n is the number of bits in the promoted operand. The type of the result is the type of the promoted operand.
- 9 The operand of the logical negation operator `!` is contextually converted to `bool` (Clause 7); its value is `true` if the converted operand is `false` and `false` otherwise. The type of the result is `bool`.
- 10 The operand of `~` shall have integral or unscoped enumeration type; the result is the ones’ complement of its operand. Integral promotions are performed. The type of the result is the type of the promoted operand. There is an ambiguity in the grammar when `~` is followed by a *class-name* or *decltype-specifier*. The ambiguity is resolved by treating `~` as the unary complement operator rather than as the start of an *unqualified-id* naming a destructor. [*Note:* Because the grammar does not permit an operator to follow the `.`, `->`, or `::` tokens, a `~` followed by a *class-name* or *decltype-specifier* in a member access expression or *qualified-id* is unambiguously parsed as a destructor name. — *end note*]

8.3.2 Increment and decrement

[**expr.pre.incr**]

- 1 The operand of prefix `++` is modified by adding 1. The operand shall be a modifiable lvalue. The type of the operand shall be an arithmetic type other than *cv bool*, or a pointer to a completely-defined object type. The result is the updated operand; it is an lvalue, and it is a bit-field if the operand is a bit-field. The expression `++x` is equivalent to `x+=1`. [*Note:* See the discussions of addition (8.7) and assignment operators (8.18) for information on conversions. — *end note*]
- 2 The operand of prefix `--` is modified by subtracting 1. The requirements on the operand of prefix `--` and the properties of its result are otherwise the same as those of prefix `++`. [*Note:* For postfix increment and decrement, see 8.2.6. — *end note*]

8.3.3 Sizeof

[**expr.sizeof**]

- 1 The `sizeof` operator yields the number of bytes in the object representation of its operand. The operand is either an expression, which is an unevaluated operand (Clause 8), or a parenthesized *type-id*. The `sizeof` operator shall not be applied to an expression that has function or incomplete type, to the parenthesized name of such types, or to a glvalue that designates a bit-field. `sizeof(char)`, `sizeof(signed char)` and `sizeof(unsigned char)` are 1. The result of `sizeof` applied to any other fundamental type (6.9.1) is implementation-defined. [*Note:* In particular, `sizeof(bool)`, `sizeof(char16_t)`, `sizeof(char32_t)`, and `sizeof(wchar_t)` are implementation-defined.⁷⁷ — *end note*] [*Note:* See 4.4 for the definition of *byte* and 6.9 for the definition of *object representation*. — *end note*]
- 2 When applied to a reference or a reference type, the result is the size of the referenced type. When applied to a class, the result is the number of bytes in an object of that class including any padding required for placing objects of that type in an array. The size of a most derived class shall be greater than zero (4.5).

⁷⁷) `sizeof(bool)` is not required to be 1.

The result of applying `sizeof` to a base class subobject is the size of the base class type.⁷⁸ When applied to an array, the result is the total number of bytes in the array. This implies that the size of an array of n elements is n times the size of an element.

- ³ The `sizeof` operator can be applied to a pointer to a function, but shall not be applied directly to a function.
- ⁴ The lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are not applied to the operand of `sizeof`. If the operand is a prvalue, the temporary materialization conversion (7.4) is applied.
- ⁵ The identifier in a `sizeof...` expression shall name a parameter pack. The `sizeof...` operator yields the number of arguments provided for the parameter pack *identifier*. A `sizeof...` expression is a pack expansion (17.5.3). [*Example:*

```
template<class... Types>
struct count {
    static const std::size_t value = sizeof...(Types);
};
```

— *end example*]
- ⁶ The result of `sizeof` and `sizeof...` is a constant of type `std::size_t`. [*Note:* `std::size_t` is defined in the standard header `<cstddef>` (21.2.1, 21.2.4). — *end note*]

8.3.4 New

[**expr.new**]

- ¹ The *new-expression* attempts to create an object of the *type-id* (11.1) or *new-type-id* to which it is applied. The type of that object is the *allocated type*. This type shall be a complete object type, but not an abstract class type or array thereof (4.5, 6.9, 13.4). [*Note:* Because references are not objects, references cannot be created by *new-expressions*. — *end note*] [*Note:* The *type-id* may be a cv-qualified type, in which case the object created by the *new-expression* has a cv-qualified type. — *end note*]

new-expression:

```
::opt new new-placementopt new-type-id new-initializeropt
::opt new new-placementopt ( type-id ) new-initializeropt
```

new-placement:

```
( expression-list )
```

new-type-id:

```
type-specifier-seq new-declaratoropt
```

new-declarator:

```
ptr-operator new-declaratoropt
noptr-new-declarator
```

noptr-new-declarator:

```
[ expression ] attribute-specifier-seqopt
noptr-new-declarator [ constant-expression ] attribute-specifier-seqopt
```

new-initializer:

```
( expression-listopt )
braced-init-list
```

Entities created by a *new-expression* have dynamic storage duration (6.7.4). [*Note:* The lifetime of such an entity is not necessarily restricted to the scope in which it is created. — *end note*] If the entity is a non-array object, the *new-expression* returns a pointer to the object created. If it is an array, the *new-expression* returns a pointer to the initial element of the array.

⁷⁸) The actual size of a base class subobject may be less than the result of applying `sizeof` to the subobject, due to virtual base classes and less strict padding requirements on base class subobjects.

- ² If a placeholder type (10.1.7.4) appears in the *type-specifier-seq* of a *new-type-id* or *type-id* of a *new-expression*, the allocated type is deduced as follows: Let *init* be the *new-initializer*, if any, and *T* be the *new-type-id* or *type-id* of the *new-expression*, then the allocated type is the type deduced for the variable *x* in the invented declaration (10.1.7.4):

`T x init ;`

[*Example:*

```
new auto(1);           // allocated type is int
auto x = new auto('a'); // allocated type is char, x is of type char*

template<class T> struct A { A(T, T); };
auto y = new A{1, 2};   // allocated type is A<int>
```

— *end example*]

- ³ The *new-type-id* in a *new-expression* is the longest possible sequence of *new-declarators*. [*Note:* This prevents ambiguities between the declarator operators `&`, `&&`, `*`, and `[]` and their expression counterparts. — *end note*] [*Example:*

```
new int * i;           // syntax error: parsed as (new int*) i, not as (new int)*i
```

The `*` is the pointer declarator and not the multiplication operator. — *end example*]

- ⁴ [*Note:* Parentheses in a *new-type-id* of a *new-expression* can have surprising effects. [*Example:*

```
new int(*[10])();      // error
```

is ill-formed because the binding is

```
(new int) (*[10])();   // error
```

Instead, the explicitly parenthesized version of the `new` operator can be used to create objects of compound types (6.9.2):

```
new (int (*[10])());
```

allocates an array of 10 pointers to functions (taking no argument and returning `int`). — *end example*]
— *end note*]

- ⁵ When the allocated object is an array (that is, the *nopt-new-declarator* syntax is used or the *new-type-id* or *type-id* denotes an array type), the *new-expression* yields a pointer to the initial element (if any) of the array. [*Note:* Both `new int` and `new int[10]` have type `int*` and the type of `new int[i][10]` is `int (*)[10]` — *end note*] The *attribute-specifier-seq* in a *nopt-new-declarator* appertains to the associated array type.

- ⁶ Every *constant-expression* in a *nopt-new-declarator* shall be a converted constant expression (8.20) of type `std::size_t` and shall evaluate to a strictly positive value. The *expression* in a *nopt-new-declarator* is implicitly converted to `std::size_t`. [*Example:* Given the definition `int n = 42`, `new float[n][5]` is well-formed (because `n` is the *expression* of a *nopt-new-declarator*), but `new float[5][n]` is ill-formed (because `n` is not a constant expression). — *end example*]

- ⁷ The *expression* in a *nopt-new-declarator* is erroneous if:

- (7.1) — the expression is of non-class type and its value before converting to `std::size_t` is less than zero;
- (7.2) — the expression is of class type and its value before application of the second standard conversion (16.3.3.1.2)⁷⁹ is less than zero;
- (7.3) — its value is such that the size of the allocated object would exceed the implementation-defined limit (Annex B); or
- (7.4) — the *new-initializer* is a *braced-init-list* and the number of array elements for which initializers are

⁷⁹ If the conversion function returns a signed integer type, the second standard conversion converts to the unsigned type `std::size_t` and thus thwarts any attempt to detect a negative value afterwards.

provided (including the terminating `'\0'` in a string literal (5.13.5)) exceeds the number of elements to initialize.

If the *expression* is erroneous after converting to `std::size_t`:

- (7.5) — if the *expression* is a core constant expression, the program is ill-formed;
- (7.6) — otherwise, an allocation function is not called; instead
 - (7.6.1) — if the allocation function that would have been called has a non-throwing exception specification (18.4), the value of the *new-expression* is the null pointer value of the required result type;
 - (7.6.2) — otherwise, the *new-expression* terminates by throwing an exception of a type that would match a handler (18.3) of type `std::bad_array_new_length` (21.6.3.2).

When the value of the *expression* is zero, the allocation function is called to allocate an array with no elements.

- 8 A *new-expression* may obtain storage for the object by calling an allocation function (6.7.4.1). If the *new-expression* terminates by throwing an exception, it may release storage by calling a deallocation function (6.7.4.2). If the allocated type is a non-array type, the allocation function's name is `operator new` and the deallocation function's name is `operator delete`. If the allocated type is an array type, the allocation function's name is `operator new[]` and the deallocation function's name is `operator delete[]`. [Note: An implementation shall provide default definitions for the global allocation functions (6.7.4, 21.6.2.1, 21.6.2.2). A C++ program can provide alternative definitions of these functions (20.5.4.6) and/or class-specific versions (15.5). The set of allocation and deallocation functions that may be called by a *new-expression* may include functions that do not perform allocation or deallocation; for example, see 21.6.2.3. — end note]
- 9 If the *new-expression* begins with a unary `::` operator, the allocation function's name is looked up in the global scope. Otherwise, if the allocated type is a class type `T` or array thereof, the allocation function's name is looked up in the scope of `T`. If this lookup fails to find the name, or if the allocated type is not a class type, the allocation function's name is looked up in the global scope.
- 10 An implementation is allowed to omit a call to a replaceable global allocation function (21.6.2.1, 21.6.2.2). When it does so, the storage is instead provided by the implementation or provided by extending the allocation of another *new-expression*. The implementation may extend the allocation of a *new-expression* `e1` to provide storage for a *new-expression* `e2` if the following would be true were the allocation not extended:
 - (10.1) — the evaluation of `e1` is sequenced before the evaluation of `e2`, and
 - (10.2) — `e2` is evaluated whenever `e1` obtains storage, and
 - (10.3) — both `e1` and `e2` invoke the same replaceable global allocation function, and
 - (10.4) — if the allocation function invoked by `e1` and `e2` is throwing, any exceptions thrown in the evaluation of either `e1` or `e2` would be first caught in the same handler, and
 - (10.5) — the pointer values produced by `e1` and `e2` are operands to evaluated *delete-expressions*, and
 - (10.6) — the evaluation of `e2` is sequenced before the evaluation of the *delete-expression* whose operand is the pointer value produced by `e1`.

[Example:

```
void mergeable(int x) {
    // These allocations are safe for merging:
    std::unique_ptr<char[]> a{new (std::nothrow) char[8]};
    std::unique_ptr<char[]> b{new (std::nothrow) char[8]};
    std::unique_ptr<char[]> c{new (std::nothrow) char[x]};

    g(a.get(), b.get(), c.get());
}
```

```

    }

    void unmergeable(int x) {
        std::unique_ptr<char[]> a{new char[8]};
        try {
            // Merging this allocation would change its catch handler.
            std::unique_ptr<char[]> b{new char[x]};
        } catch (const std::bad_alloc& e) {
            std::cerr << "Allocation failed: " << e.what() << std::endl;
            throw;
        }
    }
}

```

— end example]

- 11 When a *new-expression* calls an allocation function and that allocation has not been extended, the *new-expression* passes the amount of space requested to the allocation function as the first argument of type `std::size_t`. That argument shall be no less than the size of the object being created; it may be greater than the size of the object being created only if the object is an array. For arrays of `char`, `unsigned char`, and `std::byte`, the difference between the result of the *new-expression* and the address returned by the allocation function shall be an integral multiple of the strictest fundamental alignment requirement (6.11) of any object type whose size is no greater than the size of the array being created. [*Note*: Because allocation functions are assumed to return pointers to storage that is appropriately aligned for objects of any type with fundamental alignment, this constraint on array allocation overhead permits the common idiom of allocating character arrays into which objects of other types will later be placed. — end note]
- 12 When a *new-expression* calls an allocation function and that allocation has been extended, the size argument to the allocation call shall be no greater than the sum of the sizes for the omitted calls as specified above, plus the size for the extended call had it not been extended, plus any padding necessary to align the allocated objects within the allocated memory.
- 13 The *new-placement* syntax is used to supply additional arguments to an allocation function; such an expression is called a *placement new-expression*.
- 14 Overload resolution is performed on a function call created by assembling an argument list. The first argument is the amount of space requested, and has type `std::size_t`. If the type of the allocated object has new-extended alignment, the next argument is the type's alignment, and has type `std::align_val_t`. If the *new-placement* syntax is used, the *initializer-clauses* in its *expression-list* are the succeeding arguments. If no matching function is found and the allocated object type has new-extended alignment, the alignment argument is removed from the argument list, and overload resolution is performed again.
- 15 [*Example*:
 - (15.1) — `new T` results in one of the following calls:


```

operator new(sizeof(T))
operator new(sizeof(T), std::align_val_t(alignof(T)))
          
```
 - (15.2) — `new(2,f) T` results in one of the following calls:


```

operator new(sizeof(T), 2, f)
operator new(sizeof(T), std::align_val_t(alignof(T)), 2, f)
          
```
 - (15.3) — `new T[5]` results in one of the following calls:


```

operator new[](sizeof(T) * 5 + x)
operator new[](sizeof(T) * 5 + x, std::align_val_t(alignof(T)))
          
```
 - (15.4) — `new(2,f) T[5]` results in one of the following calls:


```

operator new[](sizeof(T) * 5 + x, 2, f)
          
```

```
operator new[](sizeof(T) * 5 + x, std::align_val_t(alignof(T)), 2, f)
```

Here, each instance of *x* is a non-negative unspecified value representing array allocation overhead; the result of the *new-expression* will be offset by this amount from the value returned by `operator new[]`. This overhead may be applied in all array *new-expressions*, including those referencing the library function `operator new[](std::size_t, void*)` and other placement allocation functions. The amount of overhead may vary from one invocation of `new` to another. — *end example*]

- 16 [*Note*: Unless an allocation function has a non-throwing exception specification (18.4), it indicates failure to allocate storage by throwing a `std::bad_alloc` exception (6.7.4.1, Clause 18, 21.6.3.1); it returns a non-null pointer otherwise. If the allocation function has a non-throwing exception specification, it returns null to indicate failure to allocate storage and a non-null pointer otherwise. — *end note*] If the allocation function is a non-allocating form (21.6.2.3) that returns null, the behavior is undefined. Otherwise, if the allocation function returns null, initialization shall not be done, the deallocation function shall not be called, and the value of the *new-expression* shall be null.
- 17 [*Note*: When the allocation function returns a value other than null, it must be a pointer to a block of storage in which space for the object has been reserved. The block of storage is assumed to be appropriately aligned and of the requested size. The address of the created object will not necessarily be the same as that of the block if the object is an array. — *end note*]
- 18 A *new-expression* that creates an object of type *T* initializes that object as follows:
 - (18.1) — If the *new-initializer* is omitted, the object is default-initialized (11.6). [*Note*: If no initialization is performed, the object has an indeterminate value. — *end note*]
 - (18.2) — Otherwise, the *new-initializer* is interpreted according to the initialization rules of 11.6 for direct-initialization.
- 19 The invocation of the allocation function is sequenced before the evaluations of expressions in the *new-initializer*. Initialization of the allocated object is sequenced before the value computation of the *new-expression*.
- 20 If the *new-expression* creates an object or an array of objects of class type, access and ambiguity control are done for the allocation function, the deallocation function (15.5), and the constructor (15.1). If the *new-expression* creates an array of objects of class type, the destructor is potentially invoked (15.4).
- 21 If any part of the object initialization described above⁸⁰ terminates by throwing an exception and a suitable deallocation function can be found, the deallocation function is called to free the memory in which the object was being constructed, after which the exception continues to propagate in the context of the *new-expression*. If no unambiguous matching deallocation function can be found, propagating the exception does not cause the object's memory to be freed. [*Note*: This is appropriate when the called allocation function does not allocate memory; otherwise, it is likely to result in a memory leak. — *end note*]
- 22 If the *new-expression* begins with a unary `::` operator, the deallocation function's name is looked up in the global scope. Otherwise, if the allocated type is a class type *T* or an array thereof, the deallocation function's name is looked up in the scope of *T*. If this lookup fails to find the name, or if the allocated type is not a class type or array thereof, the deallocation function's name is looked up in the global scope.
- 23 A declaration of a placement deallocation function matches the declaration of a placement allocation function if it has the same number of parameters and, after parameter transformations (11.3.5), all parameter types except the first are identical. If the lookup finds a single matching deallocation function, that function will be called; otherwise, no deallocation function will be called. If the lookup finds a usual deallocation function with a parameter of type `std::size_t` (6.7.4.2) and that function, considered as a placement deallocation function, would have been selected as a match for the allocation function, the program is ill-formed. For a non-placement allocation function, the normal deallocation function lookup is used to find the matching

⁸⁰) This may include evaluating a *new-initializer* and/or calling a constructor.

deallocation function (8.3.5) [*Example*:

```
struct S {
    // Placement allocation function:
    static void* operator new(std::size_t, std::size_t);

    // Usual (non-placement) deallocation function:
    static void operator delete(void*, std::size_t);
};

S* p = new (0) S;    // ill-formed: non-placement deallocation function matches
                    // placement allocation function

— end example]
```

- ²⁴ If a *new-expression* calls a deallocation function, it passes the value returned from the allocation function call as the first argument of type `void*`. If a placement deallocation function is called, it is passed the same additional arguments as were passed to the placement allocation function, that is, the same arguments as those specified with the *new-placement* syntax. If the implementation is allowed to make a copy of any argument as part of the call to the allocation function, it is allowed to make a copy (of the same original value) as part of the call to the deallocation function or to reuse the copy made as part of the call to the allocation function. If the copy is elided in one place, it need not be elided in the other.

8.3.5 Delete

[**expr.delete**]

- ¹ The *delete-expression* operator destroys a most derived object (4.5) or array created by a *new-expression*.

```
delete-expression:
::opt delete cast-expression
::opt delete [ ] cast-expression
```

The first alternative is for non-array objects, and the second is for arrays. Whenever the `delete` keyword is immediately followed by empty square brackets, it shall be interpreted as the second alternative.⁸¹ The operand shall be of pointer to object type or of class type. If of class type, the operand is contextually implicitly converted (Clause 7) to a pointer to object type.⁸² The *delete-expression*'s result has type `void`.

- ² If the operand has a class type, the operand is converted to a pointer type by calling the above-mentioned conversion function, and the converted operand is used in place of the original operand for the remainder of this section. In the first alternative (*delete object*), the value of the operand of `delete` may be a null pointer value, a pointer to a non-array object created by a previous *new-expression*, or a pointer to a subobject (4.5) representing a base class of such an object (Clause 13). If not, the behavior is undefined. In the second alternative (*delete array*), the value of the operand of `delete` may be a null pointer value or a pointer value that resulted from a previous array *new-expression*.⁸³ If not, the behavior is undefined. [Note: This means that the syntax of the *delete-expression* must match the type of the object allocated by `new`, not the syntax of the *new-expression*. — end note] [Note: A pointer to a `const` type can be the operand of a *delete-expression*; it is not necessary to cast away the constness (8.2.11) of the pointer expression before it is used as the operand of the *delete-expression*. — end note]
- ³ In the first alternative (*delete object*), if the static type of the object to be deleted is different from its dynamic type, the static type shall be a base class of the dynamic type of the object to be deleted and the static type shall have a virtual destructor or the behavior is undefined. In the second alternative (*delete array*) if the dynamic type of the object to be deleted differs from its static type, the behavior is undefined.

⁸¹ A lambda expression with a *lambda-introducer* that consists of empty square brackets can follow the `delete` keyword if the lambda expression is enclosed in parentheses.

⁸² This implies that an object cannot be deleted using a pointer of type `void*` because `void` is not an object type.

⁸³ For nonzero-length arrays, this is the same as a pointer to the first element of the array created by that *new-expression*. Zero-length arrays do not have a first element.

- 4 The *cast-expression* in a *delete-expression* shall be evaluated exactly once.
- 5 If the object being deleted has incomplete class type at the point of deletion and the complete class has a non-trivial destructor or a deallocation function, the behavior is undefined.
- 6 If the value of the operand of the *delete-expression* is not a null pointer value, the *delete-expression* will invoke the destructor (if any) for the object or the elements of the array being deleted. In the case of an array, the elements will be destroyed in order of decreasing address (that is, in reverse order of the completion of their constructor; see 15.6.2).
- 7 If the value of the operand of the *delete-expression* is not a null pointer value, then:
 - (7.1) — If the allocation call for the *new-expression* for the object to be deleted was not omitted and the allocation was not extended (8.3.4), the *delete-expression* shall call a deallocation function (6.7.4.2). The value returned from the allocation call of the *new-expression* shall be passed as the first argument to the deallocation function.
 - (7.2) — Otherwise, if the allocation was extended or was provided by extending the allocation of another *new-expression*, and the *delete-expression* for every other pointer value produced by a *new-expression* that had storage provided by the extended *new-expression* has been evaluated, the *delete-expression* shall call a deallocation function. The value returned from the allocation call of the extended *new-expression* shall be passed as the first argument to the deallocation function.
 - (7.3) — Otherwise, the *delete-expression* will not call a deallocation function.

[Note: The deallocation function is called regardless of whether the destructor for the object or some element of the array throws an exception. — end note] If the value of the operand of the *delete-expression* is a null pointer value, it is unspecified whether a deallocation function will be called as described above.
- 8 [Note: An implementation provides default definitions of the global deallocation functions **operator delete** for non-arrays (21.6.2.1) and **operator delete[]** for arrays (21.6.2.2). A C++ program can provide alternative definitions of these functions (20.5.4.6), and/or class-specific versions (15.5). — end note]
- 9 When the keyword **delete** in a *delete-expression* is preceded by the unary **::** operator, the deallocation function's name is looked up in global scope. Otherwise, the lookup considers class-specific deallocation functions (15.5). If no class-specific deallocation function is found, the deallocation function's name is looked up in global scope.
- 10 If deallocation function lookup finds more than one usual deallocation function, the function to be called is selected as follows:
 - (10.1) — If the type has new-extended alignment, a function with a parameter of type **std::align_val_t** is preferred; otherwise a function without such a parameter is preferred. If exactly one preferred function is found, that function is selected and the selection process terminates. If more than one preferred function is found, all non-preferred functions are eliminated from further consideration.
 - (10.2) — If the deallocation functions have class scope, the one without a parameter of type **std::size_t** is selected.
 - (10.3) — If the type is complete and if, for the second alternative (delete array) only, the operand is a pointer to a class type with a non-trivial destructor or a (possibly multi-dimensional) array thereof, the function with a parameter of type **std::size_t** is selected.
 - (10.4) — Otherwise, it is unspecified whether a deallocation function with a parameter of type **std::size_t** is selected.
- 11 When a *delete-expression* is executed, the selected deallocation function shall be called with the address of the most-derived object in the *delete object* case, or the address of the object suitably adjusted for the array allocation overhead (8.3.4) in the *delete array* case, as its first argument. If a deallocation function with a parameter of type **std::align_val_t** is used, the alignment of the type of the object to be deleted is

passed as the corresponding argument. If a deallocation function with a parameter of type `std::size_t` is used, the size of the most-derived type, or of the array plus allocation overhead, respectively, is passed as the corresponding argument.⁸⁴ [*Note*: If this results in a call to a usual deallocation function, and either the first argument was not the result of a prior call to a usual allocation function or the second argument was not the corresponding argument in said call, the behavior is undefined (21.6.2.1, 21.6.2.2). — *end note*]

- ¹² Access and ambiguity control are done for both the deallocation function and the destructor (15.4, 15.5).

8.3.6 Alignof [expr.alignof]

- ¹ An **alignof** expression yields the alignment requirement of its operand type. The operand shall be a *type-id* representing a complete object type, or an array thereof, or a reference to one of those types.
- ² The result is an integral constant of type `std::size_t`.
- ³ When **alignof** is applied to a reference type, the result is the alignment of the referenced type. When **alignof** is applied to an array type, the result is the alignment of the element type.

8.3.7 noexcept operator [expr.unary.noexcept]

- ¹ The **noexcept** operator determines whether the evaluation of its operand, which is an unevaluated operand (Clause 8), can throw an exception (18.1).

noexcept-expression:

noexcept (*expression*)

- ² The result of the **noexcept** operator is a constant of type `bool` and is a prvalue.
- ³ The result of the **noexcept** operator is **true** unless the *expression* is potentially-throwing (18.4).

8.4 Explicit type conversion (cast notation) [expr.cast]

- ¹ The result of the expression (T) *cast-expression* is of type T. The result is an lvalue if T is an lvalue reference type or an rvalue reference to function type and an xvalue if T is an rvalue reference to object type; otherwise the result is a prvalue. [*Note*: If T is a non-class type that is cv-qualified, the *cv-qualifiers* are discarded when determining the type of the resulting prvalue; see Clause 8. — *end note*]
- ² An explicit type conversion can be expressed using functional notation (8.2.3), a type conversion operator (**dynamic_cast**, **static_cast**, **reinterpret_cast**, **const_cast**), or the *cast* notation.

cast-expression:

unary-expression

(*type-id*) *cast-expression*

- ³ Any type conversion not mentioned below and not explicitly defined by the user (15.3) is ill-formed.
- ⁴ The conversions performed by
 - (4.1) — a **const_cast** (8.2.11),
 - (4.2) — a **static_cast** (8.2.9),
 - (4.3) — a **static_cast** followed by a **const_cast**,
 - (4.4) — a **reinterpret_cast** (8.2.10), or
 - (4.5) — a **reinterpret_cast** followed by a **const_cast**,

can be performed using the cast notation of explicit type conversion. The same semantic restrictions and behaviors apply, with the exception that in performing a **static_cast** in the following situations the conversion is valid even if the base class is inaccessible:

⁸⁴ If the static type of the object to be deleted is complete and is different from the dynamic type, and the destructor is not virtual, the size might be incorrect, but that case is already undefined, as stated above.

- (4.6) — a pointer to an object of derived class type or an lvalue or rvalue of derived class type may be explicitly converted to a pointer or reference to an unambiguous base class type, respectively;
- (4.7) — a pointer to member of derived class type may be explicitly converted to a pointer to member of an unambiguous non-virtual base class type;
- (4.8) — a pointer to an object of an unambiguous non-virtual base class type, a glvalue of an unambiguous non-virtual base class type, or a pointer to member of an unambiguous non-virtual base class type may be explicitly converted to a pointer, a reference, or a pointer to member of a derived class type, respectively.

If a conversion can be interpreted in more than one of the ways listed above, the interpretation that appears first in the list is used, even if a cast resulting from that interpretation is ill-formed. If a conversion can be interpreted in more than one way as a `static_cast` followed by a `const_cast`, the conversion is ill-formed.

[*Example:*

```
struct A { };
struct I1 : A { };
struct I2 : A { };
struct D : I1, I2 { };
A* foo( D* p ) {
    return (A*)( p );           // ill-formed static_cast interpretation
}
```

— *end example*]

- 5 The operand of a cast using the cast notation can be a prvalue of type “pointer to incomplete class type”. The destination type of a cast using the cast notation can be “pointer to incomplete class type”. If both the operand and destination types are class types and one or both are incomplete, it is unspecified whether the `static_cast` or the `reinterpret_cast` interpretation is used, even if there is an inheritance relationship between the two classes. [*Note:* For example, if the classes were defined later in the translation unit, a multi-pass compiler would be permitted to interpret a cast between pointers to the classes as if the class types were complete at the point of the cast. — *end note*]

8.5 Pointer-to-member operators

[`expr.mptr.oper`]

- 1 The pointer-to-member operators `->*` and `.*` group left-to-right.

pm-expression:

cast-expression

pm-expression `.*` *cast-expression*

pm-expression `->*` *cast-expression*

- 2 The binary operator `.*` binds its second operand, which shall be of type “pointer to member of T” to its first operand, which shall be a glvalue of class T or of a class of which T is an unambiguous and accessible base class. The result is an object or a function of the type specified by the second operand.
- 3 The binary operator `->*` binds its second operand, which shall be of type “pointer to member of T” to its first operand, which shall be of type “pointer to U” where U is either T or a class of which T is an unambiguous and accessible base class. The expression `E1->*E2` is converted into the equivalent form `(*(E1)).*E2`.
- 4 Abbreviating *pm-expression* `.*` *cast-expression* as `E1.*E2`, E1 is called the *object expression*. If the dynamic type of E1 does not contain the member to which E2 refers, the behavior is undefined. Otherwise, the expression E1 is sequenced before the expression E2.
- 5 The restrictions on *cv*-qualification, and the manner in which the *cv*-qualifiers of the operands are combined to produce the *cv*-qualifiers of the result, are the same as the rules for `E1.E2` given in 8.2.5. [*Note:* It is not possible to use a pointer to member that refers to a `mutable` member to modify a `const` class object. For example,

```

struct S {
    S() : i(0) { }
    mutable int i;
};
void f()
{
    const S cs;
    int S::* pm = &S::i;           // pm refers to mutable member S::i
    cs.*pm = 88;                   // ill-formed: cs is a const object
}

```

— end note]

- ⁶ If the result of `.*` or `->*` is a function, then that result can be used only as the operand for the function call operator `()`. [Example:

```
(ptr_to_obj->*ptr_to_mfct)(10);
```

calls the member function denoted by `ptr_to_mfct` for the object pointed to by `ptr_to_obj`. — end example]

In a `.*` expression whose object expression is an rvalue, the program is ill-formed if the second operand is a pointer to member function with *ref-qualifier* `&`. In a `.*` expression whose object expression is an lvalue, the program is ill-formed if the second operand is a pointer to member function with *ref-qualifier* `&&`. The result of a `.*` expression whose second operand is a pointer to a data member is an lvalue if the first operand is an lvalue and an xvalue otherwise. The result of a `.*` expression whose second operand is a pointer to a member function is a prvalue. If the second operand is the null member pointer value (7.12), the behavior is undefined.

8.6 Multiplicative operators

[expr.mul]

- ¹ The multiplicative operators `*`, `/`, and `%` group left-to-right.

multiplicative-expression:

pm-expression

multiplicative-expression `*` *pm-expression*

multiplicative-expression `/` *pm-expression*

multiplicative-expression `%` *pm-expression*

- ² The operands of `*` and `/` shall have arithmetic or unscoped enumeration type; the operands of `%` shall have integral or unscoped enumeration type. The usual arithmetic conversions are performed on the operands and determine the type of the result.
- ³ The binary `*` operator indicates multiplication.
- ⁴ The binary `/` operator yields the quotient, and the binary `%` operator yields the remainder from the division of the first expression by the second. If the second operand of `/` or `%` is zero the behavior is undefined. For integral operands the `/` operator yields the algebraic quotient with any fractional part discarded;⁸⁵ if the quotient `a/b` is representable in the type of the result, `(a/b)*b + a%b` is equal to `a`; otherwise, the behavior of both `a/b` and `a%b` is undefined.

8.7 Additive operators

[expr.add]

- ¹ The additive operators `+` and `-` group left-to-right. The usual arithmetic conversions are performed for operands of arithmetic or enumeration type.

additive-expression:

multiplicative-expression

additive-expression `+` *multiplicative-expression*

additive-expression `-` *multiplicative-expression*

⁸⁵) This is often called truncation towards zero.

For addition, either both operands shall have arithmetic or unscoped enumeration type, or one operand shall be a pointer to a completely-defined object type and the other shall have integral or unscoped enumeration type.

- 2 For subtraction, one of the following shall hold:
 - (2.1) — both operands have arithmetic or unscoped enumeration type; or
 - (2.2) — both operands are pointers to cv-qualified or cv-unqualified versions of the same completely-defined object type; or
 - (2.3) — the left operand is a pointer to a completely-defined object type and the right operand has integral or unscoped enumeration type.
- 3 The result of the binary `+` operator is the sum of the operands. The result of the binary `-` operator is the difference resulting from the subtraction of the second operand from the first.
- 4 When an expression that has integral type is added to or subtracted from a pointer, the result has the type of the pointer operand. If the expression `P` points to element `x[i]` of an array object `x` with n elements,⁸⁶ the expressions `P + J` and `J + P` (where `J` has the value j) point to the (possibly-hypothetical) element `x[i + j]` if $0 \leq i + j \leq n$; otherwise, the behavior is undefined. Likewise, the expression `P - J` points to the (possibly-hypothetical) element `x[i - j]` if $0 \leq i - j \leq n$; otherwise, the behavior is undefined.
- 5 When two pointers to elements of the same array object are subtracted, the type of the result is an implementation-defined signed integral type; this type shall be the same type that is defined as `std::ptrdiff_t` in the `<cstdlib>` header (21.2). If the expressions `P` and `Q` point to, respectively, elements `x[i]` and `x[j]` of the same array object `x`, the expression `P - Q` has the value $i - j$; otherwise, the behavior is undefined. [Note: If the value $i - j$ is not in the range of representable values of type `std::ptrdiff_t`, the behavior is undefined. — end note]
- 6 For addition or subtraction, if the expressions `P` or `Q` have type “pointer to cv `T`”, where `T` and the array element type are not similar (7.5), the behavior is undefined. [Note: In particular, a pointer to a base class cannot be used for pointer arithmetic when the array contains objects of a derived class type. — end note]
- 7 If the value 0 is added to or subtracted from a null pointer value, the result is a null pointer value. If two null pointer values are subtracted, the result compares equal to the value 0 converted to the type `std::ptrdiff_t`.

8.8 Shift operators

[expr.shift]

- 1 The shift operators `<<` and `>>` group left-to-right.

```

shift-expression:
    additive-expression
    shift-expression << additive-expression
    shift-expression >> additive-expression

```

The operands shall be of integral or unscoped enumeration type and integral promotions are performed. The type of the result is that of the promoted left operand. The behavior is undefined if the right operand is negative, or greater than or equal to the length in bits of the promoted left operand.

- 2 The value of `E1 << E2` is `E1` left-shifted `E2` bit positions; vacated bits are zero-filled. If `E1` has an unsigned type, the value of the result is $E1 \times 2^{E2}$, reduced modulo one more than the maximum value representable in the result type. Otherwise, if `E1` has a signed type and non-negative value, and $E1 \times 2^{E2}$ is representable in the corresponding unsigned type of the result type, then that value, converted to the result type, is the resulting value; otherwise, the behavior is undefined.

⁸⁶) An object that is not an array element is considered to belong to a single-element array for this purpose; see 8.3.1. A pointer past the last element of an array `x` of n elements is considered to be equivalent to a pointer to a hypothetical element `x[n]` for this purpose; see 6.9.2.

- ³ The value of `E1 >> E2` is `E1` right-shifted `E2` bit positions. If `E1` has an unsigned type or if `E1` has a signed type and a non-negative value, the value of the result is the integral part of the quotient of `E1/2E2`. If `E1` has a signed type and a negative value, the resulting value is implementation-defined.
- ⁴ The expression `E1` is sequenced before the expression `E2`.

8.9 Relational operators

[expr.rel]

- ¹ The relational operators group left-to-right. [*Example: `a<b<c` means `(a<b)<c` and not `(a<b)&&(b<c)`. — end example*]

relational-expression:

shift-expression

relational-expression < *shift-expression*

relational-expression > *shift-expression*

relational-expression <= *shift-expression*

relational-expression >= *shift-expression*

The operands shall have arithmetic, enumeration, or pointer type. The operators < (less than), > (greater than), <= (less than or equal to), and >= (greater than or equal to) all yield **false** or **true**. The type of the result is **bool**.

- ² The usual arithmetic conversions are performed on operands of arithmetic or enumeration type. If both operands are pointers, pointer conversions (7.11) and qualification conversions (7.5) are performed to bring them to their composite pointer type (Clause 8). After conversions, the operands shall have the same type.
- ³ Comparing unequal pointers to objects⁸⁷ is defined as follows:
- (3.1) — If two pointers point to different elements of the same array, or to subobjects thereof, the pointer to the element with the higher subscript compares greater.
- (3.2) — If two pointers point to different non-static data members of the same object, or to subobjects of such members, recursively, the pointer to the later declared member compares greater provided the two members have the same access control (Clause 14) and provided their class is not a union.
- (3.3) — Otherwise, neither pointer compares greater than the other.
- ⁴ If two operands `p` and `q` compare equal (8.10), `p<=q` and `p>=q` both yield **true** and `p<q` and `p>q` both yield **false**. Otherwise, if a pointer `p` compares greater than a pointer `q`, `p>=q`, `p>q`, `q<=p`, and `q<p` all yield **true** and `p<=q`, `p<q`, `q>=p`, and `q>p` all yield **false**. Otherwise, the result of each of the operators is unspecified.
- ⁵ If both operands (after conversions) are of arithmetic or enumeration type, each of the operators shall yield **true** if the specified relationship is true and **false** if it is false.

8.10 Equality operators

[expr.eq]

equality-expression:

relational-expression

equality-expression == *relational-expression*

equality-expression != *relational-expression*

- ¹ The == (equal to) and the != (not equal to) operators group left-to-right. The operands shall have arithmetic, enumeration, pointer, or pointer to member type, or type `std::nullptr_t`. The operators == and != both yield **true** or **false**, i.e., a result of type **bool**. In each case below, the operands shall have the same type after the specified conversions have been applied.

⁸⁷) An object that is not an array element is considered to belong to a single-element array for this purpose; see 8.3.1. A pointer past the last element of an array `x` of `n` elements is considered to be equivalent to a pointer to a hypothetical element `x[n]` for this purpose; see 6.9.2.

² If at least one of the operands is a pointer, pointer conversions (7.11), function pointer conversions (7.13), and qualification conversions (7.5) are performed on both operands to bring them to their composite pointer type (Clause 8). Comparing pointers is defined as follows:

- (2.1) — If one pointer represents the address of a complete object, and another pointer represents the address one past the last element of a different complete object,⁸⁸ the result of the comparison is unspecified.
- (2.2) — Otherwise, if the pointers are both null, both point to the same function, or both represent the same address (6.9.2), they compare equal.
- (2.3) — Otherwise, the pointers compare unequal.

³ If at least one of the operands is a pointer to member, pointer to member conversions (7.12) and qualification conversions (7.5) are performed on both operands to bring them to their composite pointer type (Clause 8). Comparing pointers to members is defined as follows:

- (3.1) — If two pointers to members are both the null member pointer value, they compare equal.
- (3.2) — If only one of two pointers to members is the null member pointer value, they compare unequal.
- (3.3) — If either is a pointer to a virtual member function, the result is unspecified.
- (3.4) — If one refers to a member of class C1 and the other refers to a member of a different class C2, where neither is a base class of the other, the result is unspecified. [*Example:*

```
struct A {};
struct B : A { int x; };
struct C : A { int x; };
```

```
int A::bx = (int(A::*))&B::x;
int A::cx = (int(A::*))&C::x;
```

```
bool b1 = (bx == cx);    // unspecified
```

— *end example*]

- (3.5) — If both refer to (possibly different) members of the same union (12.3), they compare equal.
- (3.6) — Otherwise, two pointers to members compare equal if they would refer to the same member of the same most derived object (4.5) or the same subobject if indirection with a hypothetical object of the associated class type were performed, otherwise they compare unequal. [*Example:*

```
struct B {
    int f();
};
struct L : B { };
struct R : B { };
struct D : L, R { };
```

```
int (B::*pb)() = &B::f;
int (L::*pl)() = pb;
int (R::*pr)() = pb;
int (D::*pdl)() = pl;
int (D::*pdr)() = pr;
bool x = (pdl == pdr);    // false
bool y = (pb == pl);      // true
```

— *end example*]

⁸⁸) An object that is not an array element is considered to belong to a single-element array for this purpose; see 8.3.1.

- ⁴ Two operands of type `std::nullptr_t` or one operand of type `std::nullptr_t` and the other a null pointer constant compare equal.
- ⁵ If two operands compare equal, the result is `true` for the `==` operator and `false` for the `!=` operator. If two operands compare unequal, the result is `false` for the `==` operator and `true` for the `!=` operator. Otherwise, the result of each of the operators is unspecified.
- ⁶ If both operands are of arithmetic or enumeration type, the usual arithmetic conversions are performed on both operands; each of the operators shall yield `true` if the specified relationship is true and `false` if it is false.

8.11 Bitwise AND operator

[expr.bit.and]

and-expression:

equality-expression

and-expression & equality-expression

- ¹ The usual arithmetic conversions are performed; the result is the bitwise AND function of the operands. The operator applies only to integral or unscoped enumeration operands.

8.12 Bitwise exclusive OR operator

[expr.xor]

exclusive-or-expression:

and-expression

exclusive-or-expression ~ and-expression

- ¹ The usual arithmetic conversions are performed; the result is the bitwise exclusive OR function of the operands. The operator applies only to integral or unscoped enumeration operands.

8.13 Bitwise inclusive OR operator

[expr.or]

inclusive-or-expression:

exclusive-or-expression

inclusive-or-expression | exclusive-or-expression

- ¹ The usual arithmetic conversions are performed; the result is the bitwise inclusive OR function of its operands. The operator applies only to integral or unscoped enumeration operands.

8.14 Logical AND operator

[expr.log.and]

logical-and-expression:

inclusive-or-expression

logical-and-expression && inclusive-or-expression

- ¹ The `&&` operator groups left-to-right. The operands are both contextually converted to `bool` (Clause 7). The result is `true` if both operands are `true` and `false` otherwise. Unlike `&`, `&&` guarantees left-to-right evaluation: the second operand is not evaluated if the first operand is `false`.
- ² The result is a `bool`. If the second expression is evaluated, every value computation and side effect associated with the first expression is sequenced before every value computation and side effect associated with the second expression.

8.15 Logical OR operator

[expr.log.or]

logical-or-expression:

logical-and-expression

logical-or-expression || logical-and-expression

- ¹ The `||` operator groups left-to-right. The operands are both contextually converted to `bool` (Clause 7). It returns `true` if either of its operands is `true`, and `false` otherwise. Unlike `|`, `||` guarantees left-to-right evaluation; moreover, the second operand is not evaluated if the first operand evaluates to `true`.

- ² The result is a `bool`. If the second expression is evaluated, every value computation and side effect associated with the first expression is sequenced before every value computation and side effect associated with the second expression.

8.16 Conditional operator

[`expr.cond`]

conditional-expression:

logical-or-expression

logical-or-expression ? *expression* : *assignment-expression*

- ¹ Conditional expressions group right-to-left. The first expression is contextually converted to `bool` (Clause 7). It is evaluated and if it is `true`, the result of the conditional expression is the value of the second expression, otherwise that of the third expression. Only one of the second and third expressions is evaluated. Every value computation and side effect associated with the first expression is sequenced before every value computation and side effect associated with the second or third expression.
- ² If either the second or the third operand has type `void`, one of the following shall hold:
- (2.1) — The second or the third operand (but not both) is a (possibly parenthesized) *throw-expression* (8.17); the result is of the type and value category of the other. The *conditional-expression* is a bit-field if that operand is a bit-field.
- (2.2) — Both the second and the third operands have type `void`; the result is of type `void` and is a prvalue. [*Note*: This includes the case where both operands are *throw-expressions*. — *end note*]
- ³ Otherwise, if the second and third operand are glvalue bit-fields of the same value category and of types *cv1* T and *cv2* T, respectively, the operands are considered to be of type *cv* T for the remainder of this section, where *cv* is the union of *cv1* and *cv2*.
- ⁴ Otherwise, if the second and third operand have different types and either has (possibly cv-qualified) class type, or if both are glvalues of the same value category and the same type except for cv-qualification, an attempt is made to form an implicit conversion sequence (16.3.3.1) from each of those operands to the type of the other. [*Note*: Properties such as access, whether an operand is a bit-field, or whether a conversion function is deleted are ignored for that determination. — *end note*] Attempts are made to form an implicit conversion sequence from an operand expression E1 of type T1 to a target type related to the type T2 of the operand expression E2 as follows:
- (4.1) — If E2 is an lvalue, the target type is “lvalue reference to T2”, subject to the constraint that in the conversion the reference must bind directly (11.6.3) to an lvalue.
- (4.2) — If E2 is an xvalue, the target type is “rvalue reference to T2”, subject to the constraint that the reference must bind directly.
- (4.3) — If E2 is a prvalue or if neither of the conversion sequences above can be formed and at least one of the operands has (possibly cv-qualified) class type:
- (4.3.1) — if T1 and T2 are the same class type (ignoring cv-qualification), or one is a base class of the other, and T2 is at least as cv-qualified as T1, the target type is T2,
- (4.3.2) — otherwise, the target type is the type that E2 would have after applying the lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions.

Using this process, it is determined whether an implicit conversion sequence can be formed from the second operand to the target type determined for the third operand, and vice versa. If both sequences can be formed, or one can be formed but it is the ambiguous conversion sequence, the program is ill-formed. If no conversion sequence can be formed, the operands are left unchanged and further checking is performed as described below. Otherwise, if exactly one conversion sequence can be formed, that conversion is applied to the chosen operand and the converted operand is used in place of the original operand for the remainder of this section. [*Note*: The conversion might be ill-formed even if an implicit conversion sequence could be formed. — *end*]

note]

- 5 If the second and third operands are glvalues of the same value category and have the same type, the result is of that type and value category and it is a bit-field if the second or the third operand is a bit-field, or if both are bit-fields.
- 6 Otherwise, the result is a prvalue. If the second and third operands do not have the same type, and either has (possibly cv-qualified) class type, overload resolution is used to determine the conversions (if any) to be applied to the operands (16.3.1.2, 16.6). If the overload resolution fails, the program is ill-formed. Otherwise, the conversions thus determined are applied, and the converted operands are used in place of the original operands for the remainder of this section.
- 7 Lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are performed on the second and third operands. After those conversions, one of the following shall hold:
 - (7.1) — The second and third operands have the same type; the result is of that type and the result object is initialized using the selected operand.
 - (7.2) — The second and third operands have arithmetic or enumeration type; the usual arithmetic conversions are performed to bring them to a common type, and the result is of that type.
 - (7.3) — One or both of the second and third operands have pointer type; pointer conversions (7.11), function pointer conversions (7.13), and qualification conversions (7.5) are performed to bring them to their composite pointer type (Clause 8). The result is of the composite pointer type.
 - (7.4) — One or both of the second and third operands have pointer to member type; pointer to member conversions (7.12) and qualification conversions (7.5) are performed to bring them to their composite pointer type (Clause 8). The result is of the composite pointer type.
 - (7.5) — Both the second and third operands have type `std::nullptr_t` or one has that type and the other is a null pointer constant. The result is of type `std::nullptr_t`.

8.17 Throwing an exception

[`expr.throw`]

throw-expression:

throw *assignment-expression_{opt}*

- 1 A *throw-expression* is of type `void`.
- 2 Evaluating a *throw-expression* with an operand throws an exception (18.1); the type of the exception object is determined by removing any top-level *cv-qualifiers* from the static type of the operand and adjusting the type from “array of T” or function type T to “pointer to T”.
- 3 A *throw-expression* with no operand rethrows the currently handled exception (18.3). The exception is reactivated with the existing exception object; no new exception object is created. The exception is no longer considered to be caught. [*Example:* Code that must be executed because of an exception, but cannot completely handle the exception itself, can be written like this:

```
try {
    // ...
} catch (...) {           // catch all exceptions
    // respond (partially) to exception
    throw;                // pass the exception to some other handler
}
```

— *end example*]

- 4 If no exception is presently being handled, evaluating a *throw-expression* with no operand calls `std::terminate()` (18.5.1).

8.18 Assignment and compound assignment operators [expr.ass]

- ¹ The assignment operator (=) and the compound assignment operators all group right-to-left. All require a modifiable lvalue as their left operand and return an lvalue referring to the left operand. The result in all cases is a bit-field if the left operand is a bit-field. In all cases, the assignment is sequenced after the value computation of the right and left operands, and before the value computation of the assignment expression. The right operand is sequenced before the left operand. With respect to an indeterminately-sequenced function call, the operation of a compound assignment is a single evaluation. [*Note*: Therefore, a function call shall not intervene between the lvalue-to-rvalue conversion and the side effect associated with any single compound assignment operator. — *end note*]

assignment-expression:

conditional-expression

logical-or-expression assignment-operator initializer-clause

throw-expression

assignment-operator: one of

= *= /= %= += -= >>= <<= &= ^= |=

- ² In simple assignment (=), the value of the expression replaces that of the object referred to by the left operand.
- ³ If the left operand is not of class type, the expression is implicitly converted (Clause 7) to the cv-unqualified type of the left operand.
- ⁴ If the left operand is of class type, the class shall be complete. Assignment to objects of a class is defined by the copy/move assignment operator (15.8, 16.5.3).
- ⁵ [*Note*: For class objects, assignment is not in general the same as initialization (11.6, 15.1, 15.6, 15.8). — *end note*]
- ⁶ When the left operand of an assignment operator is a bit-field that cannot represent the value of the expression, the resulting value of the bit-field is implementation-defined.
- ⁷ The behavior of an expression of the form $E1 \text{ op } = E2$ is equivalent to $E1 = E1 \text{ op } E2$ except that $E1$ is evaluated only once. In += and -=, $E1$ shall either have arithmetic type or be a pointer to a possibly cv-qualified completely-defined object type. In all other cases, $E1$ shall have arithmetic type.
- ⁸ If the value being stored in an object is read via another object that overlaps in any way the storage of the first object, then the overlap shall be exact and the two objects shall have the same type, otherwise the behavior is undefined. [*Note*: This restriction applies to the relationship between the left and right sides of the assignment operation; it is not a statement about how the target of the assignment may be aliased in general. See 6.10. — *end note*]
- ⁹ A *braced-init-list* may appear on the right-hand side of
- (9.1) — an assignment to a scalar, in which case the initializer list shall have at most a single element. The meaning of $x = \{v\}$, where T is the scalar type of the expression x , is that of $x = T\{v\}$. The meaning of $x = \{\}$ is $x = T\{\}$.
- (9.2) — an assignment to an object of class type, in which case the initializer list is passed as the argument to the assignment operator function selected by overload resolution (16.5.3, 16.3).

[*Example*:

```
complex<double> z;
z = { 1, 2 };           // meaning z.operator=({1,2})
z += { 1, 2 };          // meaning z.operator+=({1,2})
int a, b;
a = b = { 1 };          // meaning a=b=1;
a = { 1 } = b;          // syntax error
```

— *end example*]

8.19 Comma operator

[**expr.comma**]

- ¹ The comma operator groups left-to-right.

expression:

assignment-expression

expression , *assignment-expression*

A pair of expressions separated by a comma is evaluated left-to-right; the left expression is a discarded-value expression (Clause 8). Every value computation and side effect associated with the left expression is sequenced before every value computation and side effect associated with the right expression. The type and value of the result are the type and value of the right operand; the result is of the same value category as its right operand, and is a bit-field if its right operand is a bit-field. If the right operand is a temporary expression (15.2), the result is a temporary expression.

- ² In contexts where comma is given a special meaning, [*Example:* in lists of arguments to functions (8.2.2) and lists of initializers (11.6) — *end example*] the comma operator as described in Clause 8 can appear only in parentheses. [*Example:*

```
f(a, (t=3, t+2), c);
```

has three arguments, the second of which has the value 5. — *end example*]

8.20 Constant expressions

[**expr.const**]

- ¹ Certain contexts require expressions that satisfy additional requirements as detailed in this subclause; other contexts have different semantics depending on whether or not an expression satisfies these requirements. Expressions that satisfy these requirements, assuming that copy elision is performed, are called *constant expressions*. [*Note:* Constant expressions can be evaluated during translation. — *end note*]

constant-expression:

conditional-expression

- ² An expression **e** is a *core constant expression* unless the evaluation of **e**, following the rules of the abstract machine (4.6), would evaluate one of the following expressions:

- (2.1) — **this** (8.1.2), except in a constexpr function or a constexpr constructor that is being evaluated as part of **e**;
- (2.2) — an invocation of a function other than a constexpr constructor for a literal class, a constexpr function, or an implicit invocation of a trivial destructor (15.4) [*Note:* Overload resolution (16.3) is applied as usual — *end note*];
- (2.3) — an invocation of an undefined constexpr function or an undefined constexpr constructor;
- (2.4) — an invocation of an instantiated constexpr function or constexpr constructor that fails to satisfy the requirements for a constexpr function or constexpr constructor (10.1.5);
- (2.5) — an expression that would exceed the implementation-defined limits (see Annex B);
- (2.6) — an operation that would have undefined behavior as specified in Clauses 4 through 19 of this International Standard [*Note:* including, for example, signed integer overflow (Clause 8), certain pointer arithmetic (8.7), division by zero (8.6), or certain shift operations (8.8) — *end note*];
- (2.7) — an lvalue-to-rvalue conversion (7.1) unless it is applied to
 - (2.7.1) — a non-volatile glvalue of integral or enumeration type that refers to a complete non-volatile const object with a preceding initialization, initialized with a constant expression, or
 - (2.7.2) — a non-volatile glvalue that refers to a subobject of a string literal (5.13.5), or

- (2.7.3) — a non-volatile glvalue that refers to a non-volatile object defined with `constexpr`, or that refers to a non-mutable subobject of such an object, or
- (2.7.4) — a non-volatile glvalue of literal type that refers to a non-volatile object whose lifetime began within the evaluation of `e`;
- (2.8) — an lvalue-to-rvalue conversion (7.1) that is applied to a glvalue that refers to a non-active member of a union or a subobject thereof;
- (2.9) — an invocation of an implicitly-defined copy/move constructor or copy/move assignment operator for a union whose active member (if any) is mutable, unless the lifetime of the union object began within the evaluation of `e`;
- (2.10) — an assignment expression (8.18) or invocation of an assignment operator (15.8) that would change the active member of a union;
- (2.11) — an *id-expression* that refers to a variable or data member of reference type unless the reference has a preceding initialization and either
 - (2.11.1) — it is initialized with a constant expression or
 - (2.11.2) — its lifetime began within the evaluation of `e`;
- (2.12) — in a *lambda-expression*, a reference to `this` or to a variable with automatic storage duration defined outside that *lambda-expression*, where the reference would be an odr-use (6.2, 8.1.5); [*Example*:

```
void g() {
    const int n = 0;
    [=] {
        constexpr int i = n;    // OK, n is not odr-used and not captured here
        constexpr int j = *&n;  // ill-formed, &n would be an odr-use of n
    };
}
```

— *end example*] [*Note*: If the odr-use occurs in an invocation of a function call operator of a closure type, it no longer refers to `this` or to an enclosing automatic variable due to the transformation (8.1.5.2) of the *id-expression* into an access of the corresponding data member. [*Example*:

```
auto monad = [](auto v) { return [=] { return v; }; };
auto bind = [](auto m) {
    return [=](auto fvm) { return fvm(m()); };
};
```

```
// OK to have captures to automatic objects created during constant expression evaluation.
static_assert(bind(monad(2))(monad()) == monad(2)());
```

— *end example*] — *end note*

- (2.13) — a conversion from type *cv void** to a pointer-to-object type;
- (2.14) — a dynamic cast (8.2.7);
- (2.15) — a `reinterpret_cast` (8.2.10);
- (2.16) — a pseudo-destructor call (8.2.4);
- (2.17) — modification of an object (8.18, 8.2.6, 8.3.2) unless it is applied to a non-volatile lvalue of literal type that refers to a non-volatile object whose lifetime began within the evaluation of `e`;
- (2.18) — a typeid expression (8.2.8) whose operand is a glvalue of a polymorphic class type;
- (2.19) — a *new-expression* (8.3.4);
- (2.20) — a *delete-expression* (8.3.5);

- (2.21) — a relational (8.9) or equality (8.10) operator where the result is unspecified; or
- (2.22) — a *throw-expression* (8.17).

If **e** satisfies the constraints of a core constant expression, but evaluation of **e** would evaluate an operation that has undefined behavior as specified in Clauses 20 through 33 of this International Standard, it is unspecified whether **e** is a core constant expression.

[*Example:*

```

int x;                                // not constant
struct A {
    constexpr A(bool b) : m(b?42:x) { }
    int m;
};
constexpr int v = A(true).m;           // OK: constructor call initializes m with the value 42

constexpr int w = A(false).m;          // error: initializer for m is x, which is non-constant

constexpr int f1(int k) {
    constexpr int x = k;                // error: x is not initialized by a constant expression
                                        // because lifetime of k began outside the initializer of x

    return x;
}
constexpr int f2(int k) {
    int x = k;                           // OK: not required to be a constant expression
                                        // because x is not constexpr

    return x;
}

constexpr int incr(int &n) {
    return ++n;
}
constexpr int g(int k) {
    constexpr int x = incr(k);           // error: incr(k) is not a core constant expression
                                        // because lifetime of k began outside the expression incr(k)

    return x;
}
constexpr int h(int k) {
    int x = incr(k);                     // OK: incr(k) is not required to be a core constant expression
    return x;
}
constexpr int y = h(1);                 // OK: initializes y with the value 2
                                        // h(1) is a core constant expression because
                                        // the lifetime of k begins inside h(1)

```

— end example]

- ³ An *integral constant expression* is an expression of integral or unscoped enumeration type, implicitly converted to a prvalue, where the converted expression is a core constant expression. [*Note:* Such expressions may be used as bit-field lengths (12.2.4), as enumerator initializers if the underlying type is not fixed (10.2), and as alignments (10.6.2). — end note]
- ⁴ A *converted constant expression* of type **T** is an expression, implicitly converted to type **T**, where the converted expression is a constant expression and the implicit conversion sequence contains only
 - (4.1) — user-defined conversions,
 - (4.2) — lvalue-to-rvalue conversions (7.1),

- (4.3) — array-to-pointer conversions (7.2),
- (4.4) — function-to-pointer conversions (7.3),
- (4.5) — qualification conversions (7.5),
- (4.6) — integral promotions (7.6),
- (4.7) — integral conversions (7.8) other than narrowing conversions (11.6.4),
- (4.8) — null pointer conversions (7.11) from `std::nullptr_t`,
- (4.9) — null member pointer conversions (7.12) from `std::nullptr_t`, and
- (4.10) — function pointer conversions (7.13),

and where the reference binding (if any) binds directly. [*Note:* Such expressions may be used in `new` expressions (8.3.4), as case expressions (9.4.2), as enumerator initializers if the underlying type is fixed (10.2), as array bounds (11.3.4), and as non-type template arguments (17.3). — *end note*] A *contextually converted constant expression of type `bool`* is an expression, contextually converted to `bool` (Clause 7), where the converted expression is a constant expression and the conversion sequence contains only the conversions above.

- ⁵ A *constant expression* is either a glvalue core constant expression that refers to an entity that is a permitted result of a constant expression (as defined below), or a prvalue core constant expression whose value satisfies the following constraints:

- (5.1) — if the value is an object of class type, each non-static data member of reference type refers to an entity that is a permitted result of a constant expression,
- (5.2) — if the value is of pointer type, it contains the address of an object with static storage duration, the address past the end of such an object (8.7), the address of a function, or a null pointer value, and
- (5.3) — if the value is an object of class or array type, each subobject satisfies these constraints for the value.

An entity is a *permitted result of a constant expression* if it is an object with static storage duration that is either not a temporary object or is a temporary object whose value satisfies the above constraints, or it is a function.

- ⁶ [*Note:* Since this International Standard imposes no restrictions on the accuracy of floating-point operations, it is unspecified whether the evaluation of a floating-point expression during translation yields the same result as the evaluation of the same expression (or the same operations on the same values) during program execution.⁸⁹] [*Example:*

```
bool f() {
    char array[1 + int(1 + 0.2 - 0.1 - 0.1)]; // Must be evaluated during translation
    int size = 1 + int(1 + 0.2 - 0.1 - 0.1);  // May be evaluated at runtime
    return sizeof(array) == size;
}
```

It is unspecified whether the value of `f()` will be `true` or `false`. — *end example*] — *end note*]

- ⁷ If an expression of literal class type is used in a context where an integral constant expression is required, then that expression is contextually implicitly converted (Clause 7) to an integral or unscoped enumeration type and the selected conversion function shall be `constexpr`. [*Example:*

```
struct A {
    constexpr A(int i) : val(i) { }
    constexpr operator int() const { return val; }
    constexpr operator long() const { return 43; }
private:
```

⁸⁹) Nonetheless, implementations are encouraged to provide consistent results, irrespective of whether the evaluation was performed during translation and/or during program execution.

```
    int val;
};
template<int> struct X { };
constexpr A a = 42;
X<a> x;           // OK: unique conversion to int
int ary[a];       // error: ambiguous conversion
— end example]
```

9 Statements

[stmt.stmt]

- ¹ Except as indicated, statements are executed in sequence.

statement:

labeled-statement
attribute-specifier-seq_{opt} expression-statement
attribute-specifier-seq_{opt} compound-statement
attribute-specifier-seq_{opt} selection-statement
attribute-specifier-seq_{opt} iteration-statement
attribute-specifier-seq_{opt} jump-statement
declaration-statement
attribute-specifier-seq_{opt} try-block

init-statement:

expression-statement
simple-declaration

condition:

expression
attribute-specifier-seq_{opt} decl-specifier-seq declarator brace-or-equal-initializer

The optional *attribute-specifier-seq* appertains to the respective statement.

- ² The rules for *conditions* apply both to *selection-statements* and to the **for** and **while** statements (9.5). The *declarator* shall not specify a function or an array. The *decl-specifier-seq* shall not define a class or enumeration. If the **auto type-specifier** appears in the *decl-specifier-seq*, the type of the identifier being declared is deduced from the initializer as described in 10.1.7.4.
- ³ A name introduced by a declaration in a *condition* (either introduced by the *decl-specifier-seq* or the *declarator* of the condition) is in scope from its point of declaration until the end of the substatements controlled by the condition. If the name is redeclared in the outermost block of a substatement controlled by the condition, the declaration that redeclares the name is ill-formed. [*Example:*

```
if (int x = f()) {
    int x;           // ill-formed, redeclaration of x
}
else {
    int x;           // ill-formed, redeclaration of x
}
```

— *end example*]

- ⁴ The value of a *condition* that is an initialized declaration in a statement other than a **switch** statement is the value of the declared variable contextually converted to **bool** (Clause 7). If that conversion is ill-formed, the program is ill-formed. The value of a *condition* that is an initialized declaration in a **switch** statement is the value of the declared variable if it has integral or enumeration type, or of that variable implicitly converted to integral or enumeration type otherwise. The value of a *condition* that is an expression is the value of the expression, contextually converted to **bool** for statements other than **switch**; if that conversion is ill-formed, the program is ill-formed. The value of the condition will be referred to as simply “the condition” where the usage is unambiguous.
- ⁵ If a *condition* can be syntactically resolved as either an expression or the declaration of a block-scope name, it is interpreted as a declaration.
- ⁶ In the *decl-specifier-seq* of a *condition*, each *decl-specifier* shall be either a *type-specifier* or **constexpr**.

9.1 Labeled statement

[stmt.label]

- ¹ A statement can be labeled.

labeled-statement:

```

attribute-specifier-seqopt identifier : statement
attribute-specifier-seqopt case constant-expression : statement
attribute-specifier-seqopt default : statement

```

The optional *attribute-specifier-seq* appertains to the label. An *identifier label* declares the identifier. The only use of an identifier label is as the target of a **goto**. The scope of a label is the function in which it appears. Labels shall not be redeclared within a function. A label can be used in a **goto** statement before its declaration. Labels have their own name space and do not interfere with other identifiers. [*Note:* A label may have the same name as another declaration in the same scope or a *template-parameter* from an enclosing scope. Unqualified name lookup (6.4.1) ignores labels. — *end note*]

- ² Case labels and default labels shall occur only in switch statements.

9.2 Expression statement

[stmt.expr]

- ¹ Expression statements have the form

```

expression-statement:
    expressionopt ;

```

The expression is a discarded-value expression (Clause 8). All side effects from an expression statement are completed before the next statement is executed. An expression statement with the expression missing is called a *null statement*. [*Note:* Most statements are expression statements — usually assignments or function calls. A null statement is useful to carry a label just before the } of a compound statement and to supply a null body to an iteration statement such as a **while** statement (9.5.1). — *end note*]

9.3 Compound statement or block

[stmt.block]

- ¹ So that several statements can be used where one is expected, the compound statement (also, and equivalently, called “block”) is provided.

```

compound-statement:
    { statement-seqopt }

statement-seq:
    statement
    statement-seq statement

```

A compound statement defines a block scope (6.3). [*Note:* A declaration is a *statement* (9.7). — *end note*]

9.4 Selection statements

[stmt.select]

- ¹ Selection statements choose one of several flows of control.

```

selection-statement:
    if constexpropt ( init-statementopt condition ) statement
    if constexpropt ( init-statementopt condition ) statement else statement
    switch ( init-statementopt condition ) statement

```

See 11.3 for the optional *attribute-specifier-seq* in a condition. [*Note:* An *init-statement* ends with a semicolon. — *end note*] In Clause 9, the term *substatement* refers to the contained *statement* or *statements* that appear in the syntax notation. The substatement in a *selection-statement* (each substatement, in the **else** form of the **if** statement) implicitly defines a block scope (6.3). If the substatement in a selection-statement is a single statement and not a *compound-statement*, it is as if it was rewritten to be a compound-statement containing the original substatement. [*Example:*

```

if (x)
    int i;

```


can be equivalently rewritten as

```
if (x) {
    int i;
}
```

Thus after the `if` statement, `i` is no longer in scope. — *end example*]

9.4.1 The `if` statement

[**stmt.if**]

- ¹ If the condition (9.4) yields **true** the first substatement is executed. If the **else** part of the selection statement is present and the condition yields **false**, the second substatement is executed. If the first substatement is reached via a label, the condition is not evaluated and the second substatement is not executed. In the second form of `if` statement (the one including **else**), if the first substatement is also an `if` statement then that inner `if` statement shall contain an **else** part.⁹⁰
- ² If the `if` statement is of the form `if constexpr`, the value of the condition shall be a contextually converted constant expression of type **bool** (8.20); this form is called a *constexpr if* statement. If the value of the converted condition is **false**, the first substatement is a *discarded statement*, otherwise the second substatement, if present, is a discarded statement. During the instantiation of an enclosing templated entity (Clause 17), if the condition is not value-dependent after its instantiation, the discarded substatement (if any) is not instantiated. [*Note*: Odr-uses (6.2) in a discarded statement do not require an entity to be defined. — *end note*] A **case** or **default** label appearing within such an `if` statement shall be associated with a **switch** statement (9.4.2) within the same `if` statement. A label (9.1) declared in a substatement of a `constexpr if` statement shall only be referred to by a statement (9.6.4) in the same substatement. [*Example*:

```
template<typename T, typename ... Rest> void g(T&& p, Rest&& ...rs) {
    // ... handle p

    if constexpr (sizeof...(rs) > 0)
        g(rs...);           // never instantiated with an empty argument list
}

extern int x;               // no definition of x required

int f() {
    if constexpr (true)
        return 0;
    else if (x)
        return x;
    else
        return -x;
}
```

— *end example*]

- ³ An `if` statement of the form


```
if constexpropt ( init-statement condition ) statement
```

is equivalent to

```
{
    init-statement
    if constexpropt ( condition ) statement
}
```

and an `if` statement of the form

⁹⁰) In other words, the **else** is associated with the nearest un-**else** **if**.

```
if constexpropt ( init-statement condition ) statement else statement
```

is equivalent to

```
{
    init-statement
    if constexpropt ( condition ) statement else statement
}
```

except that names declared in the *init-statement* are in the same declarative region as those declared in the *condition*.

9.4.2 The switch statement

[stmt.switch]

- 1 The **switch** statement causes control to be transferred to one of several statements depending on the value of a condition.
- 2 The condition shall be of integral type, enumeration type, or class type. If of class type, the condition is contextually implicitly converted (Clause 7) to an integral or enumeration type. If the (possibly converted) type is subject to integral promotions (7.6), the condition is converted to the promoted type. Any statement within the **switch** statement can be labeled with one or more case labels as follows:

```
case constant-expression :
```

where the *constant-expression* shall be a converted constant expression (8.20) of the adjusted type of the switch condition. No two of the case constants in the same switch shall have the same value after conversion.

- 3 There shall be at most one label of the form

```
default :
```

within a **switch** statement.

- 4 Switch statements can be nested; a **case** or **default** label is associated with the smallest switch enclosing it.
- 5 When the **switch** statement is executed, its condition is evaluated and compared with each case constant. If one of the case constants is equal to the value of the condition, control is passed to the statement following the matched case label. If no case constant matches the condition, and if there is a **default** label, control passes to the statement labeled by the default label. If no case matches and if there is no **default** then none of the statements in the switch is executed.
- 6 **case** and **default** labels in themselves do not alter the flow of control, which continues unimpeded across such labels. To exit from a switch, see **break**, 9.6.1. [Note: Usually, the substatement that is the subject of a switch is compound and **case** and **default** labels appear on the top-level statements contained within the (compound) substatement, but this is not required. Declarations can appear in the substatement of a **switch** statement. — end note]

- 7 A **switch** statement of the form

```
switch ( init-statement condition ) statement
```

is equivalent to

```
{
    init-statement
    switch ( condition ) statement
}
```

except that names declared in the *init-statement* are in the same declarative region as those declared in the *condition*.

9.5 Iteration statements

[stmt.iter]

- 1 Iteration statements specify looping.

```

iteration-statement:
    while ( condition ) statement
    do statement while ( expression ) ;
    for ( init-statement conditionopt ; expressionopt ) statement
    for ( for-range-declaration : for-range-initializer ) statement

for-range-declaration:
    attribute-specifier-seqopt decl-specifier-seq declarator
    attribute-specifier-seqopt decl-specifier-seq ref-qualifieropt [ identifier-list ]

for-range-initializer:
    expr-or-braced-init-list

```

See 11.3 for the optional *attribute-specifier-seq* in a *for-range-declaration*. [*Note*: An *init-statement* ends with a semicolon. — *end note*]

- ² The substatement in an *iteration-statement* implicitly defines a block scope (6.3) which is entered and exited each time through the loop.

If the substatement in an iteration-statement is a single statement and not a *compound-statement*, it is as if it was rewritten to be a compound-statement containing the original statement. [*Example*:

```

while (--x >= 0)
    int i;

```

can be equivalently rewritten as

```

while (--x >= 0) {
    int i;
}

```

Thus after the **while** statement, *i* is no longer in scope. — *end example*]

- ³ If a name introduced in an *init-statement* or *for-range-declaration* is redeclared in the outermost block of the substatement, the program is ill-formed. [*Example*:

```

void f() {
    for (int i = 0; i < 10; ++i)
        int i = 0;           // error: redeclaration
    for (int i : { 1, 2, 3 })
        int i = 1;           // error: redeclaration
}

```

— *end example*]

9.5.1 The while statement

[**stmt.while**]

- ¹ In the **while** statement the substatement is executed repeatedly until the value of the condition (9.4) becomes **false**. The test takes place before each execution of the substatement.
- ² When the condition of a **while** statement is a declaration, the scope of the variable that is declared extends from its point of declaration (6.3.2) to the end of the **while statement**. A **while** statement of the form

```

while (T t = x) statement

```

is equivalent to

```

label:
{
    T t = x;           // start of condition scope
    if (t) {
        statement
        goto label;
    }
}

```

```
    }                               // end of condition scope
```

The variable created in a condition is destroyed and created with each iteration of the loop. [*Example:*

```
struct A {
    int val;
    A(int i) : val(i) { }
    ~A() { }
    operator bool() { return val != 0; }
};
int i = 1;
while (A a = i) {
    // ...
    i = 0;
}
```

In the while-loop, the constructor and destructor are each called twice, once for the condition that succeeds and once for the condition that fails. — *end example*]

9.5.2 The do statement

[stmt.do]

- ¹ The expression is contextually converted to `bool` (Clause 7); if that conversion is ill-formed, the program is ill-formed.
- ² In the `do` statement the substatement is executed repeatedly until the value of the expression becomes `false`. The test takes place after each execution of the statement.

9.5.3 The for statement

[stmt.for]

- ¹ The `for` statement

```
for ( init-statement conditionopt ; expressionopt ) statement
```

is equivalent to

```
{
    init-statement
    while ( condition ) {
        statement
        expression ;
    }
}
```

except that names declared in the *init-statement* are in the same declarative region as those declared in the *condition*, and except that a `continue` in *statement* (not enclosed in another iteration statement) will execute *expression* before re-evaluating *condition*. [*Note:* Thus the first statement specifies initialization for the loop; the condition (9.4) specifies a test, sequenced before each iteration, such that the loop is exited when the condition becomes `false`; the expression often specifies incrementing that is sequenced after each iteration. — *end note*]

- ² Either or both of the *condition* and the *expression* can be omitted. A missing *condition* makes the implied `while` clause equivalent to `while(true)`.
- ³ If the *init-statement* is a declaration, the scope of the name(s) declared extends to the end of the `for` statement. [*Example:*

```
int i = 42;
int a[10];

for (int i = 0; i < 10; i++)
    a[i] = i;
```

```
int j = i;           // j = 42
— end example]
```

9.5.4 The range-based for statement

[stmt.ranged]

¹ The range-based for statement

```
for ( for-range-declaration : for-range-initializer ) statement
```

is equivalent to

```
{
    auto &&__range = for-range-initializer ;
    auto __begin = begin-expr ;
    auto __end = end-expr ;
    for ( ; __begin != __end; ++__begin ) {
        for-range-declaration = *__begin;
        statement
    }
}
```

where

- (1.1) — if the *for-range-initializer* is an *expression*, it is regarded as if it were surrounded by parentheses (so that a comma operator cannot be reinterpreted as delimiting two *init-declarators*);
- (1.2) — *__range*, *__begin*, and *__end* are variables defined for exposition only; and
- (1.3) — *begin-expr* and *end-expr* are determined as follows:
 - (1.3.1) — if the *for-range-initializer* is an expression of array type *R*, *begin-expr* and *end-expr* are *__range* and *__range* + *__bound*, respectively, where *__bound* is the array bound. If *R* is an array of unknown bound or an array of incomplete type, the program is ill-formed;
 - (1.3.2) — if the *for-range-initializer* is an expression of class type *C*, the *unqualified-ids* *begin* and *end* are looked up in the scope of *C* as if by class member access lookup (6.4.5), and if either (or both) finds at least one declaration, *begin-expr* and *end-expr* are *__range.begin()* and *__range.end()*, respectively;
 - (1.3.3) — otherwise, *begin-expr* and *end-expr* are *begin(__range)* and *end(__range)*, respectively, where *begin* and *end* are looked up in the associated namespaces (6.4.2). [*Note*: Ordinary unqualified lookup (6.4.1) is not performed. — end note]

[*Example*:

```
int array[5] = { 1, 2, 3, 4, 5 };
for (int& x : array)
    x *= 2;
— end example]
```

² In the *decl-specifier-seq* of a *for-range-declaration*, each *decl-specifier* shall be either a *type-specifier* or *constexpr*. The *decl-specifier-seq* shall not define a class or enumeration.

9.6 Jump statements

[stmt.jump]

¹ Jump statements unconditionally transfer control.

```
jump-statement:
    break ;
    continue ;
    return expr-or-braced-init-listopt ;
    goto identifier ;
```

- ² On exit from a scope (however accomplished), objects with automatic storage duration (6.7.3) that have been constructed in that scope are destroyed in the reverse order of their construction. [*Note:* For temporaries, see 15.2. — *end note*] Transfer out of a loop, out of a block, or back past an initialized variable with automatic storage duration involves the destruction of objects with automatic storage duration that are in scope at the point transferred from but not at the point transferred to. (See 9.7 for transfers into blocks). [*Note:* However, the program can be terminated (by calling `std::exit()` or `std::abort()` (21.5), for example) without destroying class objects with automatic storage duration. — *end note*]

9.6.1 The break statement

[stmt.break]

- ¹ The **break** statement shall occur only in an *iteration-statement* or a **switch** statement and causes termination of the smallest enclosing *iteration-statement* or **switch** statement; control passes to the statement following the terminated statement, if any.

9.6.2 The continue statement

[stmt.cont]

- ¹ The **continue** statement shall occur only in an *iteration-statement* and causes control to pass to the loop-continuation portion of the smallest enclosing *iteration-statement*, that is, to the end of the loop. More precisely, in each of the statements

<code>while (foo) {</code>	<code>do {</code>	<code>for (;;) {</code>
<code> {</code>	<code> {</code>	<code> {</code>
<code> // ...</code>	<code> // ...</code>	<code> // ...</code>
<code> }</code>	<code> }</code>	<code> }</code>
<code>contin: ;</code>	<code>contin: ;</code>	<code>contin: ;</code>
<code>}</code>	<code>} while (foo);</code>	<code>}</code>

a **continue** not contained in an enclosed iteration statement is equivalent to **goto contin**.

9.6.3 The return statement

[stmt.return]

- ¹ A function returns to its caller by the **return** statement.
- ² The *expr-or-braced-init-list* of a return statement is called its operand. A return statement with no operand shall be used only in a function whose return type is *cv void*, a constructor (15.1), or a destructor (15.4). A return statement with an operand of type **void** shall be used only in a function whose return type is *cv void*. A return statement with any other operand shall be used only in a function whose return type is not *cv void*; the return statement initializes the glvalue result or prvalue result object of the (explicit or implicit) function call by copy-initialization (11.6) from the operand. [*Note:* A return statement can involve an invocation of a constructor to perform a copy or move of the operand if it is not a prvalue or if its type differs from the return type of the function. A copy operation associated with a return statement may be elided or converted to a move operation if an automatic storage duration variable is returned (15.8). — *end note*] [*Example:*

```
std::pair<std::string,int> f(const char* p, int x) {
    return {p,x};
}
```

— *end example*] Flowing off the end of a constructor, a destructor, or a function with a *cv void* return type is equivalent to a **return** with no operand. Otherwise, flowing off the end of a function other than **main** (6.6.1) results in undefined behavior.

- ³ The copy-initialization of the result of the call is sequenced before the destruction of temporaries at the end of the full-expression established by the operand of the return statement, which, in turn, is sequenced before the destruction of local variables (9.6) of the block enclosing the return statement.

9.6.4 The goto statement

[stmt.goto]

- ¹ The **goto** statement unconditionally transfers control to the statement labeled by the identifier. The identifier shall be a label (9.1) located in the current function.

9.7 Declaration statement

[stmt.dcl]

- ¹ A declaration statement introduces one or more new identifiers into a block; it has the form

declaration-statement:
block-declaration

If an identifier introduced by a declaration was previously declared in an outer block, the outer declaration is hidden for the remainder of the block, after which it resumes its force.

- ² Variables with automatic storage duration (6.7.3) are initialized each time their *declaration-statement* is executed. Variables with automatic storage duration declared in the block are destroyed on exit from the block (9.6).
- ³ It is possible to transfer into a block, but not in a way that bypasses declarations with initialization. A program that jumps⁹¹ from a point where a variable with automatic storage duration is not in scope to a point where it is in scope is ill-formed unless the variable has scalar type, class type with a trivial default constructor and a trivial destructor, a cv-qualified version of one of these types, or an array of one of the preceding types and is declared without an *initializer* (11.6). [Example:

```
void f() {
    // ...
    goto lx;           // ill-formed: jump into scope of a
    // ...
ly:
    X a = 1;
    // ...
lx:
    goto ly;           // OK, jump implies destructor call for a followed by
                       // construction again immediately following label ly
}
```

— end example]

- ⁴ Dynamic initialization of a block-scope variable with static storage duration (6.7.1) or thread storage duration (6.7.2) is performed the first time control passes through its declaration; such a variable is considered initialized upon the completion of its initialization. If the initialization exits by throwing an exception, the initialization is not complete, so it will be tried again the next time control enters the declaration. If control enters the declaration concurrently while the variable is being initialized, the concurrent execution shall wait for completion of the initialization.⁹² If control re-enters the declaration recursively while the variable is being initialized, the behavior is undefined. [Example:

```
int foo(int i) {
    static int s = foo(2*i);    // recursive call - undefined
    return i+1;
}
```

— end example]

- ⁵ The destructor for a block-scope object with static or thread storage duration will be executed if and only if it was constructed. [Note: 6.6.4 describes the order in which block-scope objects with static and thread storage duration are destroyed. — end note]

9.8 Ambiguity resolution

[stmt.ambig]

- ¹ There is an ambiguity in the grammar involving *expression-statements* and *declarations*: An *expression-statement* with a function-style explicit type conversion (8.2.3) as its leftmost subexpression can be indis-

⁹¹) The transfer from the condition of a `switch` statement to a `case` label is considered a jump in this respect.

⁹²) The implementation must not introduce any deadlock around execution of the initializer. Deadlocks might still be caused by the program logic; the implementation need only avoid deadlocks due to its own synchronization operations.

tinguishable from a *declaration* where the first *declarator* starts with a (. In those cases the *statement* is a *declaration*.

- ² [*Note*: If the *statement* cannot syntactically be a *declaration*, there is no ambiguity, so this rule does not apply. The whole *statement* might need to be examined to determine whether this is the case. This resolves the meaning of many examples. [*Example*: Assuming T is a *simple-type-specifier* (10.1.7),

```
T(a)->m = 7;           // expression-statement
T(a)++;                // expression-statement
T(a,5)<<c;              // expression-statement

T(*d)(int);            // declaration
T(e)[5];               // declaration
T(f) = { 1, 2 };       // declaration
T(*g)(double(3));      // declaration
```

In the last example above, g, which is a pointer to T, is initialized to `double(3)`. This is of course ill-formed for semantic reasons, but that does not affect the syntactic analysis. — *end example*]

The remaining cases are *declarations*. [*Example*:

```
class T {
    // ...
public:
    T();
    T(int);
    T(int, int);
};
T(a);                // declaration
T(*b)();              // declaration
T(c)=7;               // declaration
T(d),e,f=3;           // declaration
extern int h;
T(g)(h,2);            // declaration
```

— *end example*] — *end note*]

- ³ The disambiguation is purely syntactic; that is, the meaning of the names occurring in such a statement, beyond whether they are *type-names* or not, is not generally used in or changed by the disambiguation. Class templates are instantiated as necessary to determine if a qualified name is a *type-name*. Disambiguation precedes parsing, and a statement disambiguated as a declaration may be an ill-formed declaration. If, during parsing, a name in a template parameter is bound differently than it would be bound during a trial parse, the program is ill-formed. No diagnostic is required. [*Note*: This can occur only when the name is declared earlier in the declaration. — *end note*] [*Example*:

```
struct T1 {
    T1 operator()(int x) { return T1(x); }
    int operator=(int x) { return x; }
    T1(int) { }
};
struct T2 { T2(int){ } };
int a, ((*b)(T2))(int), c, d;

void f() {
    // disambiguation requires this to be parsed as a declaration:
    T1(a) = 3,
    T2(4),                // T2 will be declared as a variable of type T1, but this will not
    ((*b)(T2(c)))(int(d)); // allow the last part of the declaration to parse properly,
                          // since it depends on T2 being a type-name
```


}
— *end example*]

10 Declarations

[dcl.dcl]

¹ Declarations generally specify how names are to be interpreted. Declarations have the form

```

declaration-seq:
    declaration
    declaration-seq declaration

declaration:
    block-declaration
    nodeclspec-function-declaration
    function-definition
    template-declaration
    deduction-guide
    explicit-instantiation
    explicit-specialization
    linkage-specification
    namespace-definition
    empty-declaration
    attribute-declaration

block-declaration:
    simple-declaration
    asm-definition
    namespace-alias-definition
    using-declaration
    using-directive
    static_assert-declaration
    alias-declaration
    opaque-enum-declaration

nodeclspec-function-declaration:
    attribute-specifier-seqopt declarator ;

alias-declaration:
    using identifier attribute-specifier-seqopt = defining-type-id ;

simple-declaration:
    decl-specifier-seq init-declarator-listopt ;
    attribute-specifier-seq decl-specifier-seq init-declarator-list ;
    attribute-specifier-seqopt decl-specifier-seq ref-qualifieropt [ identifier-list ] initializer ;

static_assert-declaration:
    static_assert ( constant-expression ) ;
    static_assert ( constant-expression , string-literal ) ;

empty-declaration:
    ;

attribute-declaration:
    attribute-specifier-seq ;

```

[*Note*: *asm-definitions* are described in 10.4, and *linkage-specifications* are described in 10.5. *Function-definitions* are described in 11.4 and *template-declarations* and *deduction-guides* are described in Clause 17. *Namespace-definitions* are described in 10.3.1, *using-declarations* are described in 10.3.3 and *using-directives* are described in 10.3.4. — end note]

- ² A *simple-declaration* or *nodeclspec-function-declaration* of the form

attribute-specifier-seq_{opt} *decl-specifier-seq_{opt}* *init-declarator-list_{opt}* ;

is divided into three parts. Attributes are described in 10.6. *decl-specifiers*, the principal components of a *decl-specifier-seq*, are described in 10.1. *declarators*, the components of an *init-declarator-list*, are described in Clause 11. The *attribute-specifier-seq* appertains to each of the entities declared by the *declarators* of the *init-declarator-list*. [Note: In the declaration for an entity, attributes appertaining to that entity may appear at the start of the declaration and after the *declarator-id* for that declaration. — end note] [Example:

```
[[noreturn]] void f [[noreturn]] ();    // OK
— end example]
```

- ³ Except where otherwise specified, the meaning of an *attribute-declaration* is implementation-defined.
- ⁴ A declaration occurs in a scope (6.3); the scope rules are summarized in 6.4. A declaration that declares a function or defines a class, namespace, template, or function also has one or more scopes nested within it. These nested scopes, in turn, can have declarations nested within them. Unless otherwise stated, utterances in Clause 10 about components in, of, or contained by a declaration or subcomponent thereof refer only to those components of the declaration that are *not* nested within scopes nested within the declaration.
- ⁵ In a *simple-declaration*, the optional *init-declarator-list* can be omitted only when declaring a class (Clause 12) or enumeration (10.2), that is, when the *decl-specifier-seq* contains either a *class-specifier*, an *elaborated-type-specifier* with a *class-key* (12.1), or an *enum-specifier*. In these cases and whenever a *class-specifier* or *enum-specifier* is present in the *decl-specifier-seq*, the identifiers in these specifiers are among the names being declared by the declaration (as *class-names*, *enum-names*, or *enumerators*, depending on the syntax). In such cases, the *decl-specifier-seq* shall introduce one or more names into the program, or shall redeclare a name introduced by a previous declaration. [Example:

```
enum { };                // ill-formed
typedef class { };       // ill-formed
— end example]
```

- ⁶ In a *static_assert-declaration*, the *constant-expression* shall be a contextually converted constant expression of type `bool` (8.20). If the value of the expression when so converted is `true`, the declaration has no effect. Otherwise, the program is ill-formed, and the resulting diagnostic message (4.1) shall include the text of the *string-literal*, if one is supplied, except that characters not in the basic source character set (5.3) are not required to appear in the diagnostic message. [Example:

```
static_assert(char(-1) < 0, "this library requires plain 'char' to be signed");
— end example]
```

- ⁷ An *empty-declaration* has no effect.
- ⁸ A *simple-declaration* with an *identifier-list* is called a *structured binding declaration* (11.5). The *decl-specifier-seq* shall contain only the *type-specifier* `auto` (10.1.7.4) and *cv-qualifiers*. The *initializer* shall be of the form “= *assignment-expression*”, of the form “{ *assignment-expression* }”, or of the form “(*assignment-expression*)”, where the *assignment-expression* is of array or non-union class type.
- ⁹ Each *init-declarator* in the *init-declarator-list* contains exactly one *declarator-id*, which is the name declared by that *init-declarator* and hence one of the names declared by the declaration. The *defining-type-specifiers* (10.1.7) in the *decl-specifier-seq* and the recursive *declarator* structure of the *init-declarator* describe a type (11.3), which is then associated with the name being declared by the *init-declarator*.
- ¹⁰ If the *decl-specifier-seq* contains the `typedef` specifier, the declaration is called a *typedef declaration* and the name of each *init-declarator* is declared to be a *typedef-name*, synonymous with its associated type (10.1.3). If the *decl-specifier-seq* contains no `typedef` specifier, the declaration is called a *function declaration* if the type associated with the name is a function type (11.3.5) and an *object declaration* otherwise.

- ¹¹ Syntactic components beyond those found in the general form of declaration are added to a function declaration to make a *function-definition*. An object declaration, however, is also a definition unless it contains the **extern** specifier and has no initializer (6.1). A definition causes the appropriate amount of storage to be reserved and any appropriate initialization (11.6) to be done.
- ¹² A *nodeclspec-function-declaration* shall declare a constructor, destructor, or conversion function.⁹³ [*Note*: A *nodeclspec-function-declaration* can only be used in a *template-declaration* (Clause 17), *explicit-instantiation* (17.7.2), or *explicit-specialization* (17.7.3). — end note]

10.1 Specifiers

[dcl.spec]

- ¹ The specifiers that can be used in a declaration are

```

decl-specifier:
    storage-class-specifier
    defining-type-specifier
    function-specifier
    friend
    typedef
    constexpr
    inline

decl-specifier-seq:
    decl-specifier attribute-specifier-seqopt
    decl-specifier decl-specifier-seq

```

The optional *attribute-specifier-seq* in a *decl-specifier-seq* appertains to the type determined by the preceding *decl-specifiers* (11.3). The *attribute-specifier-seq* affects the type only for the declaration it appears in, not other declarations involving the same type.

- ² Each *decl-specifier* shall appear at most once in a complete *decl-specifier-seq*, except that **long** may appear twice.
- ³ If a *type-name* is encountered while parsing a *decl-specifier-seq*, it is interpreted as part of the *decl-specifier-seq* if and only if there is no previous *defining-type-specifier* other than a *cv-qualifier* in the *decl-specifier-seq*. The sequence shall be self-consistent as described below. [*Example*:

```

typedef char* Pc;
static Pc;           // error: name missing

```

Here, the declaration **static Pc** is ill-formed because no name was specified for the static variable of type **Pc**. To get a variable called **Pc**, a *type-specifier* (other than **const** or **volatile**) has to be present to indicate that the *typedef-name* **Pc** is the name being (re)declared, rather than being part of the *decl-specifier* sequence. For another example,

```

void f(const Pc);           // void f(char* const) (not const char*)
void g(const int Pc);       // void g(const int)

```

— end example]

- ⁴ [*Note*: Since **signed**, **unsigned**, **long**, and **short** by default imply **int**, a *type-name* appearing after one of those specifiers is treated as the name being (re)declared. [*Example*:

```

void h(unsigned Pc);       // void h(unsigned int)
void k(unsigned int Pc);   // void k(unsigned int)

```

— end example] — end note]

10.1.1 Storage class specifiers

[dcl.stc]

- ¹ The storage class specifiers are

⁹³) The “implicit int” rule of C is no longer supported.

storage-class-specifier:

```
static
thread_local
extern
mutable
```

At most one *storage-class-specifier* shall appear in a given *decl-specifier-seq*, except that **thread_local** may appear with **static** or **extern**. If **thread_local** appears in any declaration of a variable it shall be present in all declarations of that entity. If a *storage-class-specifier* appears in a *decl-specifier-seq*, there can be no **typedef** specifier in the same *decl-specifier-seq* and the *init-declarator-list* or *member-declarator-list* of the declaration shall not be empty (except for an anonymous union declared in a named namespace or in the global namespace, which shall be declared **static** (12.3.1)). The *storage-class-specifier* applies to the name declared by each *init-declarator* in the list and not to any names declared by other specifiers. A *storage-class-specifier* other than **thread_local** shall not be specified in an explicit specialization (17.7.3) or an explicit instantiation (17.7.2) directive.

- ² [*Note*: A variable declared without a *storage-class-specifier* at block scope or declared as a function parameter has automatic storage duration by default (6.7.3). — *end note*]
- ³ The **thread_local** specifier indicates that the named entity has thread storage duration (6.7.2). It shall be applied only to the names of variables of namespace or block scope and to the names of static data members. When **thread_local** is applied to a variable of block scope the *storage-class-specifier* **static** is implied if no other *storage-class-specifier* appears in the *decl-specifier-seq*.
- ⁴ The **static** specifier can be applied only to names of variables and functions and to anonymous unions (12.3.1). There can be no **static** function declarations within a block, nor any **static** function parameters. A **static** specifier used in the declaration of a variable declares the variable to have static storage duration (6.7.1), unless accompanied by the **thread_local** specifier, which declares the variable to have thread storage duration (6.7.2). A **static** specifier can be used in declarations of class members; 12.2.3 describes its effect. For the linkage of a name declared with a **static** specifier, see 6.5.
- ⁵ The **extern** specifier can be applied only to the names of variables and functions. The **extern** specifier cannot be used in the declaration of class members or function parameters. For the linkage of a name declared with an **extern** specifier, see 6.5. [*Note*: The **extern** keyword can also be used in *explicit-instantiations* and *linkage-specifications*, but it is not a *storage-class-specifier* in such contexts. — *end note*]
- ⁶ The linkages implied by successive declarations for a given entity shall agree. That is, within a given scope, each declaration declaring the same variable name or the same overloading of a function name shall imply the same linkage. Each function in a given set of overloaded functions can have a different linkage, however. [*Example*:

```
static char* f();           // f() has internal linkage
char* f()                  // f() still has internal linkage
{ /* ... */ }

char* g();                 // g() has external linkage
static char* g()           // error: inconsistent linkage
{ /* ... */ }

void h();
inline void h();           // external linkage

inline void l();
void l();                 // external linkage

inline void m();
extern void m();           // external linkage
```

```

static void n();
inline void n();           // internal linkage

static int a;              // a has internal linkage
int a;                    // error: two definitions

static int b;              // b has internal linkage
extern int b;              // b still has internal linkage

int c;                    // c has external linkage
static int c;              // error: inconsistent linkage

extern int d;              // d has external linkage
static int d;              // error: inconsistent linkage
— end example]

```

- ⁷ The name of a declared but undefined class can be used in an **extern** declaration. Such a declaration can only be used in ways that do not require a complete class type. [*Example*:

```

struct S;
extern S a;
extern S f();
extern void g(S);

void h() {
    g(a);                  // error: S is incomplete
    f();                   // error: S is incomplete
}
— end example]

```

- ⁸ The **mutable** specifier shall appear only in the declaration of a non-static data member (12.2) whose type is neither const-qualified nor a reference type. [*Example*:

```

class X {
    mutable const int* p;   // OK
    mutable int* const q;   // ill-formed
};
— end example]

```

- ⁹ The **mutable** specifier on a class data member nullifies a **const** specifier applied to the containing class object and permits modification of the mutable class member even though the rest of the object is **const** (10.1.7.1).

10.1.2 Function specifiers

[dcl.fct.spec]

- ¹ *Function-specifiers* can be used only in function declarations.

```

function-specifier:
    virtual
    explicit

```

- ² The **virtual** specifier shall be used only in the initial declaration of a non-static class member function; see 13.3.
- ³ The **explicit** specifier shall be used only in the declaration of a constructor or conversion function within its class definition; see 15.3.1 and 15.3.2.

10.1.3 The typedef specifier

[dcl.typedef]

- ¹ Declarations containing the *decl-specifier* **typedef** declare identifiers that can be used later for naming fundamental (6.9.1) or compound (6.9.2) types. The **typedef** specifier shall not be combined in a *decl-specifier-seq* with any other kind of specifier except a *defining-type-specifier*, and it shall not be used in the *decl-specifier-seq* of a *parameter-declaration* (11.3.5) nor in the *decl-specifier-seq* of a *function-definition* (11.4). If a **typedef** specifier appears in a declaration without a *declarator*, the program is ill-formed.

typedef-name:
identifier

A name declared with the **typedef** specifier becomes a *typedef-name*. Within the scope of its declaration, a *typedef-name* is syntactically equivalent to a keyword and names the type associated with the identifier in the way described in Clause 11. A *typedef-name* is thus a synonym for another type. A *typedef-name* does not introduce a new type the way a class declaration (12.1) or enum declaration does. [*Example*: After

```
typedef int MILES, *Klicksp;
```

the constructions

```
MILES distance;  
extern Klicksp metricp;
```

are all correct declarations; the type of `distance` is `int` and that of `metricp` is “pointer to `int`”. — *end example*]

- ² A *typedef-name* can also be introduced by an *alias-declaration*. The *identifier* following the **using** keyword becomes a *typedef-name* and the optional *attribute-specifier-seq* following the *identifier* appertains to that *typedef-name*. Such a *typedef-name* has the same semantics as if it were introduced by the **typedef** specifier. In particular, it does not define a new type. [*Example*:

```
using handler_t = void (*)(int);  
extern handler_t ignore;  
extern void (*ignore)(int);           // redeclare ignore  
using cell = pair<void*, cell*>;      // ill-formed
```

— *end example*] The *defining-type-specifier-seq* of the *defining-type-id* shall not define a class or enumeration if the *alias-declaration* is the *declaration* of a *template-declaration*.

- ³ In a given non-class scope, a **typedef** specifier can be used to redefine the name of any type declared in that scope to refer to the type to which it already refers. [*Example*:

```
typedef struct s { /* ... */ } s;  
typedef int I;  
typedef int I;  
typedef I I;
```

— *end example*]

- ⁴ In a given class scope, a **typedef** specifier can be used to redefine any *class-name* declared in that scope that is not also a *typedef-name* to refer to the type to which it already refers. [*Example*:

```
struct S {  
    typedef struct A { } A;           // OK  
    typedef struct B B;               // OK  
    typedef A A;                     // error  
};
```

— *end example*]

- ⁵ If a **typedef** specifier is used to redefine in a given scope an entity that can be referenced using an *elaborated-type-specifier*, the entity can continue to be referenced by an *elaborated-type-specifier* or as an enumeration or class name in an enumeration or class definition respectively. [*Example*:

```

struct S;
typedef struct S S;
int main() {
    struct S* p;           // OK
}
struct S { };             // OK
— end example]

```

- ⁶ In a given scope, a **typedef** specifier shall not be used to redefine the name of any type declared in that scope to refer to a different type. [*Example:*

```

class complex { /* ... */ };
typedef int complex;      // error: redefinition
— end example]

```

- ⁷ Similarly, in a given scope, a class or enumeration shall not be declared with the same name as a *typedef-name* that is declared in that scope and refers to a type other than the class or enumeration itself. [*Example:*

```

typedef int complex;
class complex { /* ... */ }; // error: redefinition
— end example]

```

- ⁸ [*Note:* A *typedef-name* that names a class type, or a cv-qualified version thereof, is also a *class-name* (12.1). If a *typedef-name* is used to identify the subject of an *elaborated-type-specifier* (10.1.7.3), a class definition (Clause 12), a constructor declaration (15.1), or a destructor declaration (15.4), the program is ill-formed. — end note] [*Example:*

```

struct S {
    S();
    ~S();
};

typedef struct S T;

S a = T();           // OK
struct T * p;         // error
— end example]

```

- ⁹ If the **typedef** declaration defines an unnamed class (or enum), the first *typedef-name* declared by the declaration to be that class type (or enum type) is used to denote the class type (or enum type) for linkage purposes only (6.5). [*Example:*

```

typedef struct { } *ps, S; // S is the class name for linkage purposes
— end example]

```

10.1.4 The friend specifier

[**dcl.friend**]

- ¹ The **friend** specifier is used to specify access to class members; see 14.3.

10.1.5 The constexpr specifier

[**dcl.constexpr**]

- ¹ The **constexpr** specifier shall be applied only to the definition of a variable or variable template or the declaration of a function or function template. A function or static data member declared with the **constexpr** specifier is implicitly an inline function or variable (10.1.6). If any declaration of a function or function template has a **constexpr** specifier, then all its declarations shall contain the **constexpr** specifier. [*Note:* An explicit specialization can differ from the template declaration with respect to the **constexpr** specifier. — end note] [*Note:* Function parameters cannot be declared **constexpr**. — end note] [*Example:*


```

constexpr void square(int &x); // OK: declaration
constexpr int bufsz = 1024;    // OK: definition
constexpr struct pixel {      // error: pixel is a type
    int x;
    int y;
    constexpr pixel(int);      // OK: declaration
};
constexpr pixel::pixel(int a)
    : x(a), y(x)               // OK: definition
    { square(x); }
constexpr pixel small(2);      // error: square not defined, so small(2)
                                // not constant (8.20) so constexpr not satisfied

constexpr void square(int &x) { // OK: definition
    x *= x;
}
constexpr pixel large(4);      // OK: square defined
int next(constexpr int x) {    // error: not for parameters
    return x + 1;
}
extern constexpr int memsz;    // error: not a definition

```

— end example]

² A **constexpr** specifier used in the declaration of a function that is not a constructor declares that function to be a *constexpr function*. Similarly, a **constexpr** specifier used in a constructor declaration declares that constructor to be a *constexpr constructor*.

³ The definition of a **constexpr** function shall satisfy the following requirements:

- (3.1) — it shall not be virtual (13.3);
- (3.2) — its return type shall be a literal type;
- (3.3) — each of its parameter types shall be a literal type;
- (3.4) — its *function-body* shall be = **delete**, = **default**, or a *compound-statement* that does not contain
 - (3.4.1) — an *asm-definition*,
 - (3.4.2) — a **goto** statement,
 - (3.4.3) — an identifier label (9.1),
 - (3.4.4) — a *try-block*, or
 - (3.4.5) — a definition of a variable of non-literal type or of static or thread storage duration or for which no initialization is performed.

[Example:

```

constexpr int square(int x)
    { return x * x; }           // OK
constexpr long long_max()
    { return 2147483647; }      // OK
constexpr int abs(int x) {
    if (x < 0)
        x = -x;
    return x;                   // OK
}
constexpr int first(int n) {
    static int value = n;       // error: variable has static storage duration
}

```

```

    return value;
}
constexpr int uninit() {
    int a;                      // error: variable is uninitialized
    return a;
}
constexpr int prev(int x)
{ return --x; }                // OK
constexpr int g(int x, int n) { // OK
    int r = 1;
    while (--n > 0) r *= x;
    return r;
}

```

— end example]

⁴ The definition of a constexpr constructor shall satisfy the following requirements:

- (4.1) — the class shall not have any virtual base classes;
- (4.2) — each of the parameter types shall be a literal type;
- (4.3) — its *function-body* shall not be a *function-try-block*.

In addition, either its *function-body* shall be = **delete**, or it shall satisfy the following requirements:

- (4.4) — either its *function-body* shall be = **default**, or the *compound-statement* of its *function-body* shall satisfy the requirements for a *function-body* of a constexpr function;
- (4.5) — every non-variant non-static data member and base class subobject shall be initialized (15.6.2);
- (4.6) — if the class is a union having variant members (12.3), exactly one of them shall be initialized;
- (4.7) — if the class is a union-like class, but is not a union, for each of its anonymous union members having variant members, exactly one of them shall be initialized;
- (4.8) — for a non-delegating constructor, every constructor selected to initialize non-static data members and base class subobjects shall be a constexpr constructor;
- (4.9) — for a delegating constructor, the target constructor shall be a constexpr constructor.

[Example:

```

struct Length {
    constexpr explicit Length(int i = 0) : val(i) { }
private:
    int val;
};

```

— end example]

⁵ For a constexpr function or constexpr constructor that is neither defaulted nor a template, if no argument values exist such that an invocation of the function or constructor could be an evaluated subexpression of a core constant expression (8.20), or, for a constructor, a constant initializer for some object (6.6.2), the program is ill-formed, no diagnostic required. [Example:

```

constexpr int f(bool b)
{ return b ? throw 0 : 0; }      // OK
constexpr int f() { return f(true); } // ill-formed, no diagnostic required

struct B {
    constexpr B(int x) : i(0) { } // x is unused
    int i;
}

```

```
};

int global;

struct D : B {
    constexpr D() : B(global) { }           // ill-formed, no diagnostic required
                                           // lvalue-to-rvalue conversion on non-constant global
};
```

— end example]

- ⁶ If the instantiated template specialization of a constexpr function template or member function of a class template would fail to satisfy the requirements for a constexpr function or constexpr constructor, that specialization is still a constexpr function or constexpr constructor, even though a call to such a function cannot appear in a constant expression. If no specialization of the template would satisfy the requirements for a constexpr function or constexpr constructor when considered as a non-template function or constructor, the template is ill-formed, no diagnostic required.
- ⁷ A call to a constexpr function produces the same result as a call to an equivalent non-constexpr function in all respects except that
- (7.1) — a call to a constexpr function can appear in a constant expression (8.20) and
- (7.2) — copy elision is mandatory in a constant expression (15.8).

- ⁸ The `constexpr` specifier has no effect on the type of a constexpr function or a constexpr constructor. [Example:

```
constexpr int bar(int x, int y)           // OK
{ return x + y + x*y; }
// ...
int bar(int x, int y)                     // error: redefinition of bar
{ return x * 2 + 3 * y; }
```

— end example]

- ⁹ A `constexpr` specifier used in an object declaration declares the object as `const`. Such an object shall have literal type and shall be initialized. In any `constexpr` variable declaration, the full-expression of the initialization shall be a constant expression (8.20). [Example:

```
struct pixel {
    int x, y;
};
constexpr pixel ur = { 1294, 1024 };      // OK
constexpr pixel origin;                  // error: initializer missing
```

— end example]

10.1.6 The inline specifier

[dcl.inline]

- ¹ The `inline` specifier can be applied only to the declaration or definition of a variable or function.
- ² A function declaration (11.3.5, 12.2.1, 14.3) with an `inline` specifier declares an *inline function*. The inline specifier indicates to the implementation that inline substitution of the function body at the point of call is to be preferred to the usual function call mechanism. An implementation is not required to perform this inline substitution at the point of call; however, even if this inline substitution is omitted, the other rules for inline functions specified in this section shall still be respected.
- ³ A variable declaration with an `inline` specifier declares an *inline variable*.
- ⁴ A function defined within a class definition is an inline function.

- ⁵ The **inline** specifier shall not appear on a block scope declaration.⁹⁴ If the **inline** specifier is used in a friend function declaration, that declaration shall be a definition or the function shall have previously been declared inline.
- ⁶ An inline function or variable shall be defined in every translation unit in which it is odr-used and shall have exactly the same definition in every case (6.2). [*Note*: A call to the inline function or a use of the inline variable may be encountered before its definition appears in the translation unit. — *end note*] If the definition of a function or variable appears in a translation unit before its first declaration as inline, the program is ill-formed. If a function or variable with external linkage is declared inline in one translation unit, it shall be declared inline in all translation units in which it appears; no diagnostic is required. An inline function or variable with external linkage shall have the same address in all translation units. [*Note*: A **static** local variable in an inline function with external linkage always refers to the same object. A type defined within the body of an inline function with external linkage is the same type in every translation unit. — *end note*]

10.1.7 Type specifiers

[dcl.type]

- ¹ The type-specifiers are

```

type-specifier:
    simple-type-specifier
    elaborated-type-specifier
    typename-specifier
    cv-qualifier

type-specifier-seq:
    type-specifier attribute-specifier-seqopt
    type-specifier type-specifier-seq

defining-type-specifier:
    type-specifier
    class-specifier
    enum-specifier

defining-type-specifier-seq:
    defining-type-specifier attribute-specifier-seqopt
    defining-type-specifier defining-type-specifier-seq

```

The optional *attribute-specifier-seq* in a *type-specifier-seq* or a *defining-type-specifier-seq* appertains to the type denoted by the preceding *type-specifiers* or *defining-type-specifiers* (11.3). The *attribute-specifier-seq* affects the type only for the declaration it appears in, not other declarations involving the same type.

- ² As a general rule, at most one *defining-type-specifier* is allowed in the complete *decl-specifier-seq* of a *declaration* or in a *defining-type-specifier-seq*, and at most one *type-specifier* is allowed in a *type-specifier-seq*. The only exceptions to this rule are the following:
- (2.1) — **const** can be combined with any type specifier except itself.
 - (2.2) — **volatile** can be combined with any type specifier except itself.
 - (2.3) — **signed** or **unsigned** can be combined with **char**, **long**, **short**, or **int**.
 - (2.4) — **short** or **long** can be combined with **int**.
 - (2.5) — **long** can be combined with **double**.
 - (2.6) — **long** can be combined with **long**.

⁹⁴) The **inline** keyword has no effect on the linkage of a function.

- ³ Except in a declaration of a constructor, destructor, or conversion function, at least one *defining-type-specifier* that is not a *cv-qualifier* shall appear in a complete *type-specifier-seq* or a complete *decl-specifier-seq*.⁹⁵
- ⁴ [*Note: enum-specifiers, class-specifiers, and typename-specifiers* are discussed in 10.2, Clause 12, and 17.6, respectively. The remaining *type-specifiers* are discussed in the rest of this section. — end note]

10.1.7.1 The *cv-qualifiers*

[dcl.type.cv]

- ¹ There are two *cv-qualifiers*, **const** and **volatile**. Each *cv-qualifier* shall appear at most once in a *cv-qualifier-seq*. If a *cv-qualifier* appears in a *decl-specifier-seq*, the *init-declarator-list* or *member-declarator-list* of the declaration shall not be empty. [*Note: 6.9.3 and 11.3.5* describe how *cv-qualifiers* affect object and function types. — end note] Redundant *cv-qualifications* are ignored. [*Note: For example, these could be introduced by typedefs. — end note*]
- ² [*Note: Declaring a variable **const** can affect its linkage (10.1.1) and its usability in constant expressions (8.20). As described in 11.6, the definition of an object or subobject of **const**-qualified type must specify an initializer or be subject to default-initialization. — end note*]
- ³ A pointer or reference to a *cv-qualified* type need not actually point or refer to a *cv-qualified* object, but it is treated as if it does; a *const*-qualified access path cannot be used to modify an object even if the object referenced is a non-*const* object and can be modified through some other access path. [*Note: Cv-qualifiers are supported by the type system so that they cannot be subverted without casting (8.2.11). — end note*]
- ⁴ Except that any class member declared **mutable** (10.1.1) can be modified, any attempt to modify a **const** object during its lifetime (6.8) results in undefined behavior. [*Example:*

```

const int ci = 3;           // cv-qualified (initialized as required)
ci = 4;                    // ill-formed: attempt to modify const

int i = 2;                 // not cv-qualified
const int* cip;            // pointer to const int
cip = &i;                  // OK: cv-qualified access path to unqualified
*cip = 4;                  // ill-formed: attempt to modify through ptr to const

int* ip;
ip = const_cast<int*>(cip); // cast needed to convert const int* to int*
*ip = 4;                   // defined: *ip points to i, a non-const object

const int* ciq = new const int (3); // initialized as required
int* iq = const_cast<int*>(ciq);    // cast required
*iq = 4;                          // undefined: modifies a const object

```

For another example,

```

struct X {
    mutable int i;
    int j;
};

struct Y {
    X x;
    Y();
};

const Y y;
y.x.i++; // well-formed: mutable member can be modified
y.x.j++; // ill-formed: const-qualified member modified

```

⁹⁵ There is no special provision for a *decl-specifier-seq* that lacks a *type-specifier* or that has a *type-specifier* that only specifies *cv-qualifiers*. The “implicit int” rule of C is no longer supported.

```

Y* p = const_cast<Y*>(&y);           // cast away const-ness of y
p->x.i = 99;                          // well-formed: mutable member can be modified
p->x.j = 99;                          // undefined: modifies a const member
— end example]

```

- ⁵ The semantics of an access through a volatile glvalue are implementation-defined. If an attempt is made to access an object defined with a volatile-qualified type through the use of a non-volatile glvalue, the behavior is undefined.
- ⁶ [*Note: **volatile** is a hint to the implementation to avoid aggressive optimization involving the object because the value of the object might be changed by means undetectable by an implementation. Furthermore, for some implementations, **volatile** might indicate that special hardware instructions are required to access the object. See 4.6 for detailed semantics. In general, the semantics of **volatile** are intended to be the same in C++ as they are in C. — end note*]

10.1.7.2 Simple type specifiers

[dcl.type.simple]

- ¹ The simple type specifiers are

```

simple-type-specifier:
    nested-name-specifieropt type-name
    nested-name-specifier template simple-template-id
    nested-name-specifieropt template-name
    char
    char16_t
    char32_t
    wchar_t
    bool
    short
    int
    long
    signed
    unsigned
    float
    double
    void
    auto
    decltype-specifier

type-name:
    class-name
    enum-name
    typedef-name
    simple-template-id

decltype-specifier:
    decltype ( expression )
    decltype ( auto )

```

- ² The *simple-type-specifier* **auto** is a placeholder for a type to be deduced (10.1.7.4). A *type-specifier* of the form **typename**_{opt} *nested-name-specifier*_{opt} *template-name* is a placeholder for a deduced class type (10.1.7.5). The *template-name* shall name a class template that is not an injected-class-name. The other *simple-type-specifiers* specify either a previously-declared type, a type determined from an expression, or one of the fundamental types (6.9.1). Table 11 summarizes the valid combinations of *simple-type-specifiers* and the types they specify.
- ³ When multiple *simple-type-specifiers* are allowed, they can be freely intermixed with other *decl-specifiers* in any order. [*Note: It is implementation-defined whether objects of **char** type are represented as signed or unsigned quantities. The **signed** specifier forces **char** objects to be signed; it is redundant in other contexts.*]

Table 11 — *simple-type-specifiers* and the types they specify

Specifier(s)	Type
<i>type-name</i>	the type named
<i>simple-template-id</i>	the type as defined in 17.2
<i>template-name</i>	placeholder for a type to be deduced
char	“char”
unsigned char	“unsigned char”
signed char	“signed char”
char16_t	“char16_t”
char32_t	“char32_t”
bool	“bool”
unsigned	“unsigned int”
unsigned int	“unsigned int”
signed	“int”
signed int	“int”
int	“int”
unsigned short int	“unsigned short int”
unsigned short	“unsigned short int”
unsigned long int	“unsigned long int”
unsigned long	“unsigned long int”
unsigned long long int	“unsigned long long int”
unsigned long long	“unsigned long long int”
signed long int	“long int”
signed long	“long int”
signed long long int	“long long int”
signed long long	“long long int”
long long int	“long long int”
long long	“long long int”
long int	“long int”
long	“long int”
signed short int	“short int”
signed short	“short int”
short int	“short int”
short	“short int”
wchar_t	“wchar_t”
float	“float”
double	“double”
long double	“long double”
void	“void”
auto	placeholder for a type to be deduced
decltype(auto)	placeholder for a type to be deduced
decltype(<i>expression</i>)	the type as defined below

— end note]

⁴ For an expression **e**, the type denoted by **decltype(e)** is defined as follows:

- (4.1) — if **e** is an unparenthesized *id-expression* naming a structured binding (11.5), **decltype(e)** is the referenced type as given in the specification of the structured binding declaration;

- (4.2) — otherwise, if *e* is an unparenthesized *id-expression* or an unparenthesized class member access (8.2.5), `decltype(e)` is the type of the entity named by *e*. If there is no such entity, or if *e* names a set of overloaded functions, the program is ill-formed;
- (4.3) — otherwise, if *e* is an xvalue, `decltype(e)` is `T&&`, where *T* is the type of *e*;
- (4.4) — otherwise, if *e* is an lvalue, `decltype(e)` is `T&`, where *T* is the type of *e*;
- (4.5) — otherwise, `decltype(e)` is the type of *e*.

The operand of the `decltype` specifier is an unevaluated operand (Clause 8).

[Example:

```
const int&& foo();
int i;
struct A { double x; };
const A* a = new A();
decltype(foo()) x1 = 17;           // type is const int&&
decltype(i) x2;                   // type is int
decltype(a->x) x3;                 // type is double
decltype((a->x)) x4 = x3;          // type is const double&
```

— end example] [Note: The rules for determining types involving `decltype(auto)` are specified in 10.1.7.4.
— end note]

- 5 If the operand of a *decltype-specifier* is a prvalue, the temporary materialization conversion is not applied (7.4) and no result object is provided for the prvalue. The type of the prvalue may be incomplete. [Note: As a result, storage is not allocated for the prvalue and it is not destroyed. Thus, a class type is not instantiated as a result of being the type of a function call in this context. In this context, the common purpose of writing the expression is merely to refer to its type. In that sense, a *decltype-specifier* is analogous to a use of a *typedef-name*, so the usual reasons for requiring a complete type do not apply. In particular, it is not necessary to allocate storage for a temporary object or to enforce the semantic constraints associated with invoking the type's destructor. — end note] [Note: Unlike the preceding rule, parentheses have no special meaning in this context. — end note] [Example:

```
template<class T> struct A { ~A() = delete; };
template<class T> auto h()
-> A<T>;
template<class T> auto i(T)           // identity
-> T;
template<class T> auto f(T)           // #1
-> decltype(i(h<T>()));              // forces completion of A<T> and implicitly uses A<T>::~~A()
                                     // for the temporary introduced by the use of h().
                                     // (A temporary is not introduced as a result of the use of i().)
template<class T> auto f(T)           // #2
-> void;
auto g() -> void {
    f(42);                           // OK: calls #2. (#1 is not a viable candidate: type deduction
                                     // fails (17.8.2) because A<int>::~~A() is implicitly used in its
                                     // decltype-specifier)
}
template<class T> auto q(T)
-> decltype(h<T>());                  // does not force completion of A<T>; A<T>::~~A() is not implicitly
                                     // used within the context of this decltype-specifier

void r() {
    q(42);                           // Error: deduction against q succeeds, so overload resolution selects
                                     // the specialization "q(T) -> decltype(h<T>())" [with T=int].
                                     // The return type is A<int>, so a temporary is introduced and its
```



```

    }
    // destructor is used, so the program is ill-formed.
— end example]

```

10.1.7.3 Elaborated type specifiers

[dcl.type.elab]

elaborated-type-specifier:

```

class-key attribute-specifier-seqopt nested-name-specifieropt identifier
class-key simple-template-id
class-key nested-name-specifier templateopt simple-template-id
enum nested-name-specifieropt identifier

```

- ¹ An *attribute-specifier-seq* shall not appear in an *elaborated-type-specifier* unless the latter is the sole constituent of a declaration. If an *elaborated-type-specifier* is the sole constituent of a declaration, the declaration is ill-formed unless it is an explicit specialization (17.7.3), an explicit instantiation (17.7.2) or it has one of the following forms:

```

class-key attribute-specifier-seqopt identifier ;
friend class-key ::opt identifier ;
friend class-key ::opt simple-template-id ;
friend class-key nested-name-specifier identifier ;
friend class-key nested-name-specifier templateopt simple-template-id ;

```

In the first case, the *attribute-specifier-seq*, if any, appertains to the class being declared; the attributes in the *attribute-specifier-seq* are thereafter considered attributes of the class whenever it is named.

- ² 6.4.4 describes how name lookup proceeds for the *identifier* in an *elaborated-type-specifier*. If the *identifier* resolves to a *class-name* or *enum-name*, the *elaborated-type-specifier* introduces it into the declaration the same way a *simple-type-specifier* introduces its *type-name*. If the *identifier* resolves to a *typedef-name* or the *simple-template-id* resolves to an alias template specialization, the *elaborated-type-specifier* is ill-formed. [Note: This implies that, within a class template with a template *type-parameter* T, the declaration

```
friend class T;
```

is ill-formed. However, the similar declaration **friend** T; is allowed (14.3). — end note]

- ³ The *class-key* or **enum** keyword present in the *elaborated-type-specifier* shall agree in kind with the declaration to which the name in the *elaborated-type-specifier* refers. This rule also applies to the form of *elaborated-type-specifier* that declares a *class-name* or **friend** class since it can be construed as referring to the definition of the class. Thus, in any *elaborated-type-specifier*, the **enum** keyword shall be used to refer to an enumeration (10.2), the **union** *class-key* shall be used to refer to a union (Clause 12), and either the **class** or **struct** *class-key* shall be used to refer to a class (Clause 12) declared using the **class** or **struct** *class-key*. [Example:

```

enum class E { a, b };
enum E x = E::a;           // OK

```

— end example]

10.1.7.4 The auto specifier

[dcl.spec.auto]

- ¹ The **auto** and **decltype(auto)** *type-specifiers* are used to designate a placeholder type that will be replaced later by deduction from an initializer. The **auto** *type-specifier* is also used to introduce a function type having a *trailing-return-type* or to signify that a lambda is a generic lambda (8.1.5.1). The **auto** *type-specifier* is also used to introduce a structured binding declaration (11.5).
- ² The placeholder type can appear with a function declarator in the *decl-specifier-seq*, *type-specifier-seq*, *conversion-function-id*, or *trailing-return-type*, in any context where such a declarator is valid. If the function declarator includes a *trailing-return-type* (11.3.5), that *trailing-return-type* specifies the declared return type of the function. Otherwise, the function declarator shall declare a function. If the declared return type of the

function contains a placeholder type, the return type of the function is deduced from non-discarded **return** statements, if any, in the body of the function (9.4.1).

- 3 If the **auto** *type-specifier* appears as one of the *decl-specifiers* in the *decl-specifier-seq* of a *parameter-declaration* of a *lambda-expression*, the *lambda* is a *generic lambda* (8.1.5.1). [Example:

```
auto glambda = [](int i, auto a) { return i; };    // OK: a generic lambda
— end example]
```

- 4 The type of a variable declared using **auto** or **decltype(auto)** is deduced from its initializer. This use is allowed in an initializing declaration (11.6) of a variable. **auto** or **decltype(auto)** shall appear as one of the *decl-specifiers* in the *decl-specifier-seq* and the *decl-specifier-seq* shall be followed by one or more *declarators*, each of which shall be followed by a non-empty *initializer*. In an *initializer* of the form

(*expression-list*)

the *expression-list* shall be a single *assignment-expression*. [Example:

```
auto x = 5;                                // OK: x has type int
const auto *v = &x, u = 6;                // OK: v has type const int*, u has type const int
static auto y = 0.0;                      // OK: y has type double
auto int r;                               // error: auto is not a storage-class-specifier
auto f() -> int;                           // OK: f returns int
auto g() { return 0.0; }                  // OK: g returns double
auto h();                                 // OK: h's return type will be deduced when it is defined
— end example]
```

- 5 A placeholder type can also be used in the *type-specifier-seq* in the *new-type-id* or *type-id* of a *new-expression* (8.3.4) and as a *decl-specifier* of the *parameter-declaration's decl-specifier-seq* in a *template-parameter* (17.1).
- 6 A program that uses **auto** or **decltype(auto)** in a context not explicitly allowed in this section is ill-formed.
- 7 If the *init-declarator-list* contains more than one *init-declarator*, they shall all form declarations of variables. The type of each declared variable is determined by placeholder type deduction (10.1.7.4.1), and if the type that replaces the placeholder type is not the same in each deduction, the program is ill-formed.

[Example:

```
auto x = 5, *y = &x;                      // OK: auto is int
auto a = 5, b = { 1, 2 };                 // error: different types for auto
— end example]
```

- 8 If a function with a declared return type that contains a placeholder type has multiple non-discarded **return** statements, the return type is deduced for each such **return** statement. If the type deduced is not the same in each deduction, the program is ill-formed.
- 9 If a function with a declared return type that uses a placeholder type has no non-discarded **return** statements, the return type is deduced as though from a **return** statement with no operand at the closing brace of the function body. [Example:

```
auto f() { }                               // OK, return type is void
auto* g() { }                             // error, cannot deduce auto* from void()
— end example]
```

- 10 If the type of an entity with an undeduced placeholder type is needed to determine the type of an expression, the program is ill-formed. Once a non-discarded **return** statement has been seen in a function, however, the return type deduced from that statement can be used in the rest of the function, including in other **return** statements. [Example:

```

auto n = n;                // error, n's type is unknown
auto f();
void g() { &f; }           // error, f's return type is unknown
auto sum(int i) {
    if (i == 1)
        return i;         // sum's return type is int
    else
        return sum(i-1)+i; // OK, sum's return type has been deduced
}

```

— end example]

- 11 Return type deduction for a function template with a placeholder in its declared type occurs when the definition is instantiated even if the function body contains a **return** statement with a non-type-dependent operand. [Note: Therefore, any use of a specialization of the function template will cause an implicit instantiation. Any errors that arise from this instantiation are not in the immediate context of the function type and can result in the program being ill-formed (17.8.2). — end note] [Example:

```

template <class T> auto f(T t) { return t; } // return type deduced at instantiation time
typedef decltype(f(1)) fint_t;             // instantiates f<int> to deduce return type
template<class T> auto f(T* t) { return *t; }
void g() { int (*p)(int*) = &f; }          // instantiates both fs to determine return types,
                                           // chooses second

```

— end example]

- 12 Redclarations or specializations of a function or function template with a declared return type that uses a placeholder type shall also use that placeholder, not a deduced type. [Example:

```

auto f();
auto f() { return 42; } // return type is int
auto f();               // OK
int f();                // error, cannot be overloaded with auto f()
decltype(auto) f();     // error, auto and decltype(auto) don't match

template <typename T> auto g(T t) { return t; } // #1
template auto g(int); // OK, return type is int
template char g(char); // error, no matching template
template<> auto g(double); // OK, forward declaration with unknown return type

template <class T> T g(T t) { return t; } // OK, not functionally equivalent to #1
template char g(char); // OK, now there is a matching template
template auto g(float); // still matches #1

void h() { return g(42); } // error, ambiguous

template <typename T> struct A {
    friend T frf(T);
};
auto frf(int i) { return i; } // not a friend of A<int>

```

— end example]

- 13 A function declared with a return type that uses a placeholder type shall not be **virtual** (13.3).
- 14 An explicit instantiation declaration (17.7.2) does not cause the instantiation of an entity declared using a placeholder type, but it also does not prevent that entity from being instantiated as needed to determine its type. [Example:

```

template <typename T> auto f(T t) { return t; }

```

```
extern template auto f(int);    // does not instantiate f<int>
int (*p)(int) = f;            // instantiates f<int> to determine its return type, but an explicit
                               // instantiation definition is still required somewhere in the program
```

— end example]

10.1.7.4.1 Placeholder type deduction

[**decl.type.auto.deduct**]

- ¹ Placeholder type deduction is the process by which a type containing a placeholder type is replaced by a deduced type.
- ² A type *T* containing a placeholder type, and a corresponding initializer *e*, are determined as follows:
 - (2.1) — for a non-discarded **return** statement that occurs in a function declared with a return type that contains a placeholder type, *T* is the declared return type and *e* is the operand of the **return** statement. If the **return** statement has no operand, then *e* is **void()**;
 - (2.2) — for a variable declared with a type that contains a placeholder type, *T* is the declared type of the variable and *e* is the initializer. If the initialization is direct-list-initialization, the initializer shall be a *braced-init-list* containing only a single *assignment-expression* and *e* is the *assignment-expression*;
 - (2.3) — for a non-type template parameter declared with a type that contains a placeholder type, *T* is the declared type of the non-type template parameter and *e* is the corresponding template argument.

In the case of a **return** statement with no operand or with an operand of type **void**, *T* shall be either **decltype(auto)** or *cv auto*.

- ³ If the deduction is for a **return** statement and *e* is a *braced-init-list* (11.6.4), the program is ill-formed.
- ⁴ If the placeholder is the **auto type-specifier**, the deduced type *T'* replacing *T* is determined using the rules for template argument deduction. Obtain *P* from *T* by replacing the occurrences of **auto** with either a new invented type template parameter *U* or, if the initialization is copy-list-initialization, with **std::initializer_list<U>**. Deduce a value for *U* using the rules of template argument deduction from a function call (17.8.2.1), where *P* is a function template parameter type and the corresponding argument is *e*. If the deduction fails, the declaration is ill-formed. Otherwise, *T'* is obtained by substituting the deduced *U* into *P*. [Example:

```
auto x1 = { 1, 2 };           // decltype(x1) is std::initializer_list<int>
auto x2 = { 1, 2.0 };         // error: cannot deduce element type
auto x3{ 1, 2 };              // error: not a single element
auto x4 = { 3 };              // decltype(x4) is std::initializer_list<int>
auto x5{ 3 };                 // decltype(x5) is int
```

— end example]

[Example:

```
const auto &i = expr;
```

The type of *i* is the deduced type of the parameter *u* in the call **f(expr)** of the following invented function template:

```
template <class U> void f(const U& u);
```

— end example]

- ⁵ If the placeholder is the **decltype(auto) type-specifier**, *T* shall be the placeholder alone. The type deduced for *T* is determined as described in 10.1.7.2, as though *e* had been the operand of the **decltype**. [Example:

```
int i;
int&& f();
auto      x2a(i);           // decltype(x2a) is int
decltype(auto) x2d(i);       // decltype(x2d) is int
auto      x3a = i;          // decltype(x3a) is int
decltype(auto) x3d = i;      // decltype(x3d) is int
```

```

auto      x4a = (i);      // decltype(x4a) is int
decltype(auto) x4d = (i);  // decltype(x4d) is int&
auto      x5a = f();      // decltype(x5a) is int
decltype(auto) x5d = f();  // decltype(x5d) is int&&
auto      x6a = { 1, 2 }; // decltype(x6a) is std::initializer_list<int>
decltype(auto) x6d = { 1, 2 }; // error, { 1, 2 } is not an expression
auto      *x7a = &i;      // decltype(x7a) is int*
decltype(auto)*x7d = &i;   // error, declared type is not plain decltype(auto)

```

— end example]

10.1.7.5 Deduced class template specialization types [dcl.type.class.deduct]

- ¹ If a placeholder for a deduced class type appears as a *decl-specifier* in the *decl-specifier-seq* of an initializing declaration (11.6) of a variable, the placeholder is replaced by the return type of the function selected by overload resolution for class template deduction (16.3.1.8). If the *decl-specifier-seq* is followed by an *init-declarator-list* or *member-declarator-list* containing more than one *declarator*, the type that replaces the placeholder shall be the same in each deduction.
- ² A placeholder for a deduced class type can also be used in the *type-specifier-seq* in the *new-type-id* or *type-id* of a *new-expression* (8.3.4), or as the *simple-type-specifier* in an explicit type conversion (functional notation) (8.2.3). A placeholder for a deduced class type shall not appear in any other context.
- ³ [Example:

```

template<class T> struct container {
    container(T t) {}
    template<class Iter> container(Iter beg, Iter end);
};
template<class Iter>
container(Iter b, Iter e) -> container<typename std::iterator_traits<Iter>::value_type>;
std::vector<double> v = { /* ... */ };

container c(7);                // OK, deduces int for T
auto d = container(v.begin(), v.end()); // OK, deduces double for T
container e{5, 6};             // error, int is not an iterator

```

— end example]

10.2 Enumeration declarations [dcl.enum]

- ¹ An enumeration is a distinct type (6.9.2) with named constants. Its name becomes an *enum-name* within its scope.

enum-name:

identifier

enum-specifier:

enum-head { *enumerator-list*_{opt} }

enum-head { *enumerator-list* , }

enum-head:

enum-key *attribute-specifier-seq*_{opt} *enum-head-name*_{opt} *enum-base*_{opt}

enum-head-name:

*nested-name-specifier*_{opt} *identifier*

opaque-enum-declaration:

enum-key *attribute-specifier-seq*_{opt} *nested-name-specifier*_{opt} *identifier* *enum-base*_{opt} ;

```

enum-key:
    enum
    enum class
    enum struct

enum-base:
    : type-specifier-seq

enumerator-list:
    enumerator-definition
    enumerator-list , enumerator-definition

enumerator-definition:
    enumerator
    enumerator = constant-expression

enumerator:
    identifier attribute-specifier-seqopt

```

The optional *attribute-specifier-seq* in the *enum-head* and the *opaque-enum-declaration* appertains to the enumeration; the attributes in that *attribute-specifier-seq* are thereafter considered attributes of the enumeration whenever it is named. A : following “**enum** *nested-name-specifier_{opt}* *identifier*” within the *decl-specifier-seq* of a *member-declaration* is parsed as part of an *enum-base*. [Note: This resolves a potential ambiguity between the declaration of an enumeration with an *enum-base* and the declaration of an unnamed bit-field of enumeration type. [Example:

```

struct S {
    enum E : int {};
    enum E : int {};           // error: redeclaration of enumeration
};

```

— end example] — end note] If an *opaque-enum-declaration* contains a *nested-name-specifier*, the declaration shall be an explicit specialization (17.7.3).

- ² The enumeration type declared with an *enum-key* of only **enum** is an *unscoped enumeration*, and its *enumerators* are *unscoped enumerators*. The *enum-keys* **enum class** and **enum struct** are semantically equivalent; an enumeration type declared with one of these is a *scoped enumeration*, and its *enumerators* are *scoped enumerators*. The optional *identifier* shall not be omitted in the declaration of a *scoped enumeration*. The *type-specifier-seq* of an *enum-base* shall name an integral type; any cv-qualification is ignored. An *opaque-enum-declaration* declaring an *unscoped enumeration* shall not omit the *enum-base*. The identifiers in an *enumerator-list* are declared as constants, and can appear wherever constants are required. An *enumerator-definition* with = gives the associated *enumerator* the value indicated by the *constant-expression*. If the first *enumerator* has no *initializer*, the value of the corresponding constant is zero. An *enumerator-definition* without an *initializer* gives the *enumerator* the value obtained by increasing the value of the previous *enumerator* by one. [Example:

```

enum { a, b, c=0 };
enum { d, e, f=e+2 };

```

defines **a**, **c**, and **d** to be zero, **b** and **e** to be 1, and **f** to be 3. — end example] The optional *attribute-specifier-seq* in an *enumerator* appertains to that *enumerator*.

- ³ An *opaque-enum-declaration* is either a redeclaration of an enumeration in the current scope or a declaration of a new enumeration. [Note: An enumeration declared by an *opaque-enum-declaration* has fixed underlying type and is a complete type. The list of enumerators can be provided in a later redeclaration with an *enum-specifier*. — end note] A *scoped enumeration* shall not be later redeclared as *unscoped* or with a different underlying type. An *unscoped enumeration* shall not be later redeclared as *scoped* and each redeclaration shall include an *enum-base* specifying the same underlying type as in the original declaration.

- ⁴ If the *enum-key* is followed by a *nested-name-specifier*, the *enum-specifier* shall refer to an enumeration that was previously declared directly in the class or namespace to which the *nested-name-specifier* refers (i.e., neither inherited nor introduced by a *using-declaration*), and the *enum-specifier* shall appear in a namespace enclosing the previous declaration.
- ⁵ Each enumeration defines a type that is different from all other types. Each enumeration also has an *underlying type*. The underlying type can be explicitly specified using an *enum-base*. For a scoped enumeration type, the underlying type is `int` if it is not explicitly specified. In both of these cases, the underlying type is said to be *fixed*. Following the closing brace of an *enum-specifier*, each enumerator has the type of its enumeration. If the underlying type is fixed, the type of each enumerator prior to the closing brace is the underlying type and the *constant-expression* in the *enumerator-definition* shall be a converted constant expression of the underlying type (8.20). If the underlying type is not fixed, the type of each enumerator prior to the closing brace is determined as follows:
- (5.1) — If an initializer is specified for an enumerator, the *constant-expression* shall be an integral constant expression (8.20). If the expression has unscoped enumeration type, the enumerator has the underlying type of that enumeration type, otherwise it has the same type as the expression.
 - (5.2) — If no initializer is specified for the first enumerator, its type is an unspecified signed integral type.
 - (5.3) — Otherwise the type of the enumerator is the same as that of the preceding enumerator unless the incremented value is not representable in that type, in which case the type is an unspecified integral type sufficient to contain the incremented value. If no such type exists, the program is ill-formed.
- ⁶ An enumeration whose underlying type is fixed is an incomplete type from its point of declaration (6.3.2) to immediately after its *enum-base* (if any), at which point it becomes a complete type. An enumeration whose underlying type is not fixed is an incomplete type from its point of declaration to immediately after the closing `}` of its *enum-specifier*, at which point it becomes a complete type.
- ⁷ For an enumeration whose underlying type is not fixed, the underlying type is an integral type that can represent all the enumerator values defined in the enumeration. If no integral type can represent all the enumerator values, the enumeration is ill-formed. It is implementation-defined which integral type is used as the underlying type except that the underlying type shall not be larger than `int` unless the value of an enumerator cannot fit in an `int` or `unsigned int`. If the *enumerator-list* is empty, the underlying type is as if the enumeration had a single enumerator with value 0.
- ⁸ For an enumeration whose underlying type is fixed, the values of the enumeration are the values of the underlying type. Otherwise, for an enumeration where $e_{\min}$ is the smallest enumerator and $e_{\max}$ is the largest, the values of the enumeration are the values in the range $b_{\min}$ to $b_{\max}$, defined as follows: Let K be 1 for a two's complement representation and 0 for a ones' complement or sign-magnitude representation. $b_{\max}$ is the smallest value greater than or equal to $\max(|e_{\min}| - K, |e_{\max}|)$ and equal to $2^M - 1$, where M is a non-negative integer. $b_{\min}$ is zero if $e_{\min}$ is non-negative and $-(b_{\max} + K)$ otherwise. The size of the smallest bit-field large enough to hold all the values of the enumeration type is $\max(M, 1)$ if $b_{\min}$ is zero and $M + 1$ otherwise. It is possible to define an enumeration that has values not defined by any of its enumerators. If the *enumerator-list* is empty, the values of the enumeration are as if the enumeration had a single enumerator with value 0.⁹⁶
- ⁹ Two enumeration types are *layout-compatible enumerations* if they have the same underlying type.
- ¹⁰ The value of an enumerator or an object of an unscoped enumeration type is converted to an integer by integral promotion (7.6). [*Example*:
- ```
enum color { red, yellow, green=20, blue };
color col = red;
color* cp = &col;
```

---

<sup>96</sup>) This set of values is used to define promotion and conversion semantics for the enumeration type. It does not preclude an expression of enumeration type from having a value that falls outside this range.



```
 if (*cp == blue) // ...
```

makes `color` a type describing various colors, and then declares `col` as an object of that type, and `cp` as a pointer to an object of that type. The possible values of an object of type `color` are `red`, `yellow`, `green`, `blue`; these values can be converted to the integral values 0, 1, 20, and 21. Since enumerations are distinct types, objects of type `color` can be assigned only values of type `color`.

```
 color c = 1; // error: type mismatch, no conversion from int to color
 int i = yellow; // OK: yellow converted to integral value 1, integral promotion
```

Note that this implicit `enum` to `int` conversion is not provided for a scoped enumeration:

```
enum class Col { red, yellow, green };
int x = Col::red; // error: no Col to int conversion
Col y = Col::red;
if (y) { } // error: no Col to bool conversion
```

— end example]

- <sup>11</sup> Each *enum-name* and each unscoped *enumerator* is declared in the scope that immediately contains the *enum-specifier*. Each scoped *enumerator* is declared in the scope of the enumeration. These names obey the scope rules defined for all names in 6.3 and 6.4. [Example:

```
enum direction { left='l', right='r' };

void g() {
 direction d; // OK
 d = left; // OK
 d = direction::right; // OK
}

enum class altitude { high='h', low='l' };

void h() {
 altitude a; // OK
 a = high; // error: high not in scope
 a = altitude::low; // OK
}
```

— end example] An enumerator declared in class scope can be referred to using the class member access operators `::`, `.` (dot) and `->` (arrow), see 8.2.5. [Example:

```
struct X {
 enum direction { left='l', right='r' };
 int f(int i) { return i==left ? 0 : i==right ? 1 : 2; }
};

void g(X* p) {
 direction d; // error: direction not in scope
 int i;
 i = p->f(left); // error: left not in scope
 i = p->f(X::right); // OK
 i = p->f(p->left); // OK
 // ...
}
```

— end example]

- <sup>12</sup> If an *enum-head* contains a *nested-name-specifier*, the *enum-specifier* shall refer to an enumeration that was previously declared directly in the class or namespace to which the *nested-name-specifier* refers, or in an



element of the inline namespace set (10.3.1) of that namespace (i.e., not merely inherited or introduced by a *using-declaration*), and the *enum-specifier* shall appear in a namespace enclosing the previous declaration. In such cases, the *nested-name-specifier* of the *enum-head* of the definition shall not begin with a *decltype-specifier*.

### 10.3 Namespaces

[basic.namespace]

- <sup>1</sup> A namespace is an optionally-named declarative region. The name of a namespace can be used to access entities declared in that namespace; that is, the members of the namespace. Unlike other declarative regions, the definition of a namespace can be split over several parts of one or more translation units.
- <sup>2</sup> The outermost declarative region of a translation unit is a namespace; see 6.3.6.

#### 10.3.1 Namespace definition

[namespace.def]

```
namespace-name:
 identifier
 namespace-alias

namespace-definition:
 named-namespace-definition
 unnamed-namespace-definition
 nested-namespace-definition

named-namespace-definition:
 inlineopt namespace attribute-specifier-seqopt identifier { namespace-body }

unnamed-namespace-definition:
 inlineopt namespace attribute-specifier-seqopt { namespace-body }

nested-namespace-definition:
 namespace enclosing-namespace-specifier :: identifier { namespace-body }

enclosing-namespace-specifier:
 identifier
 enclosing-namespace-specifier :: identifier

namespace-body:
 declaration-seqopt
```

- <sup>1</sup> Every *namespace-definition* shall appear in the global scope or in a namespace scope (6.3.6).
- <sup>2</sup> In a *named-namespace-definition*, the *identifier* is the name of the namespace. If the *identifier*, when looked up (6.4.1), refers to a *namespace-name* (but not a *namespace-alias*) that was introduced in the namespace in which the *named-namespace-definition* appears or that was introduced in a member of the inline namespace set of that namespace, the *namespace-definition* *extends* the previously-declared namespace. Otherwise, the *identifier* is introduced as a *namespace-name* into the declarative region in which the *named-namespace-definition* appears.
- <sup>3</sup> Because a *namespace-definition* contains *declarations* in its *namespace-body* and a *namespace-definition* is itself a *declaration*, it follows that *namespace-definitions* can be nested. [Example:

```
namespace Outer {
 int i;
 namespace Inner {
 void f() { i++; } // Outer::i
 int i;
 void g() { i++; } // Inner::i
 }
}
```

— end example]

- <sup>4</sup> The *enclosing namespaces* of a declaration are those namespaces in which the declaration lexically appears,

except for a redeclaration of a namespace member outside its original namespace (e.g., a definition as specified in 10.3.1.2). Such a redeclaration has the same enclosing namespaces as the original declaration.

[Example:

```
namespace Q {
 namespace V {
 void f(); // enclosing namespaces are the global namespace, Q, and Q::V
 class C { void m(); };
 }
 void V::f() { // enclosing namespaces are the global namespace, Q, and Q::V
 extern void h(); // ... so this declares Q::V::h
 }
 void V::C::m() { // enclosing namespaces are the global namespace, Q, and Q::V
 }
}
```

— end example]

- <sup>5</sup> If the optional initial **inline** keyword appears in a *namespace-definition* for a particular namespace, that namespace is declared to be an *inline namespace*. The **inline** keyword may be used on a *namespace-definition* that extends a namespace only if it was previously used on the *namespace-definition* that initially declared the *namespace-name* for that namespace.
- <sup>6</sup> The optional *attribute-specifier-seq* in a *named-namespace-definition* appertains to the namespace being defined or extended.
- <sup>7</sup> Members of an inline namespace can be used in most respects as though they were members of the enclosing namespace. Specifically, the inline namespace and its enclosing namespace are both added to the set of associated namespaces used in argument-dependent lookup (6.4.2) whenever one of them is, and a *using-directive* (10.3.4) that names the inline namespace is implicitly inserted into the enclosing namespace as for an unnamed namespace (10.3.1.1). Furthermore, each member of the inline namespace can subsequently be partially specialized (17.5.5), explicitly instantiated (17.7.2), or explicitly specialized (17.7.3) as though it were a member of the enclosing namespace. Finally, looking up a name in the enclosing namespace via explicit qualification (6.4.3.2) will include members of the inline namespace brought in by the *using-directive* even if there are declarations of that name in the enclosing namespace.
- <sup>8</sup> These properties are transitive: if a namespace N contains an inline namespace M, which in turn contains an inline namespace O, then the members of O can be used as though they were members of M or N. The *inline namespace set* of N is the transitive closure of all inline namespaces in N. The *enclosing namespace set* of O is the set of namespaces consisting of the innermost non-inline namespace enclosing an inline namespace O, together with any intervening inline namespaces.
- <sup>9</sup> A *nested-namespace-definition* with an *enclosing-namespace-specifier* E, *identifier* I and *namespace-body* B is equivalent to

```
namespace E { namespace I { B } }
```

[Example:

```
namespace A::B::C {
 int i;
}
```

The above has the same effect as:

```
namespace A {
 namespace B {
 namespace C {
 int i;
 }
 }
}
```

```

 }
 }
— end example]

```

### 10.3.1.1 Unnamed namespaces

[namespace.unnamed]

- <sup>1</sup> An *unnamed-namespace-definition* behaves as if it were replaced by

```

inlineopt namespace unique { /* empty body */ }
using namespace unique ;
namespace unique { namespace-body }

```

where `inline` appears if and only if it appears in the *unnamed-namespace-definition* and all occurrences of *unique* in a translation unit are replaced by the same identifier, and this identifier differs from all other identifiers in the translation unit. The optional *attribute-specifier-seq* in the *unnamed-namespace-definition* appertains to *unique*. [Example:

```

namespace { int i; } // unique::i
void f() { i++; } // unique::i++

namespace A {
 namespace {
 int i; // A::unique::i
 int j; // A::unique::j
 }
 void g() { i++; } // A::unique::i++
}

using namespace A;
void h() {
 i++; // error: unique::i or A::unique::i
 A::i++; // A::unique::i
 j++; // A::unique::j
}

```

— end example]

### 10.3.1.2 Namespace member definitions

[namespace.memdef]

- <sup>1</sup> A declaration in a namespace N (excluding declarations in nested scopes) whose *declarator-id* is an *unqualified-id* (11.3), whose *class-head-name* (Clause 12) or *enum-head-name* (10.2) is an *identifier*, or whose *elaborated-type-specifier* is of the form *class-key attribute-specifier-seq<sub>opt</sub> identifier* (10.1.7.3), or that is an *opaque-enum-declaration*, declares (or redeclares) its *unqualified-id* or *identifier* as a member of N. [Note: An explicit instantiation (17.7.2) or explicit specialization (17.7.3) of a template does not introduce a name and thus may be declared using an *unqualified-id* in a member of the enclosing namespace set, if the primary template is declared in an inline namespace. — end note] [Example:

```

namespace X {
 void f() { /* ... */ } // OK: introduces X::f()

 namespace M {
 void g(); // OK: introduces X::M::g()
 }
 using M::g;
 void g(); // error: conflicts with X::M::g()
}

```

— end example]

- <sup>2</sup> Members of a named namespace can also be defined outside that namespace by explicit qualification (6.4.3.2) of the name being defined, provided that the entity being defined was already declared in the namespace and the definition appears after the point of declaration in a namespace that encloses the declaration's namespace. [Example:

```
namespace Q {
 namespace V {
 void f();
 }
 void V::f() { /* ... */ } // OK
 void V::g() { /* ... */ } // error: g() is not yet a member of V
 namespace V {
 void g();
 }
}

namespace R {
 void Q::V::g() { /* ... */ } // error: R doesn't enclose Q
}
```

— end example]

- <sup>3</sup> If a **friend** declaration in a non-local class first declares a class, function, class template or function template<sup>97</sup> the friend is a member of the innermost enclosing namespace. The **friend** declaration does not by itself make the name visible to unqualified lookup (6.4.1) or qualified lookup (6.4.3). [Note: The name of the friend will be visible in its namespace if a matching declaration is provided at namespace scope (either before or after the class definition granting friendship). — end note] If a friend function or function template is called, its name may be found by the name lookup that considers functions from namespaces and classes associated with the types of the function arguments (6.4.2). If the name in a **friend** declaration is neither qualified nor a *template-id* and the declaration is a function or an *elaborated-type-specifier*, the lookup to determine whether the entity has been previously declared shall not consider any scopes outside the innermost enclosing namespace. [Note: The other forms of **friend** declarations cannot declare a new member of the innermost enclosing namespace and thus follow the usual lookup rules. — end note] [Example:

```
// Assume f and g have not yet been declared.
void h(int);
template <class T> void f2(T);
namespace A {
 class X {
 friend void f(X); // A::f(X) is a friend
 class Y {
 friend void g(); // A::g is a friend
 friend void h(int); // A::h is a friend
 // ::h not considered
 friend void f2<>(int); // ::f2<>(int) is a friend
 };
 };

 // A::f, A::g and A::h are not visible here
 X x;
 void g() { f(x); } // definition of A::g
 void f(X) { /* ... */ } // definition of A::f
 void h(int) { /* ... */ } // definition of A::h
 // A::f, A::g and A::h are visible here and known to be friends
}
```

<sup>97</sup>) this implies that the name of the class or function is unqualified.

```

using A::x;

void h() {
 A::f(x);
 A::X::f(x); // error: f is not a member of A::X
 A::X::Y::g(); // error: g is not a member of A::X::Y
}

```

— end example]

### 10.3.2 Namespace alias

[namespace.alias]

- <sup>1</sup> A *namespace-alias-definition* declares an alternate name for a namespace according to the following grammar:

```

namespace-alias:
 identifier

namespace-alias-definition:
 namespace identifier = qualified-namespace-specifier ;

qualified-namespace-specifier:
 nested-name-specifieropt namespace-name

```

- <sup>2</sup> The *identifier* in a *namespace-alias-definition* is a synonym for the name of the namespace denoted by the *qualified-namespace-specifier* and becomes a *namespace-alias*. [Note: When looking up a *namespace-name* in a *namespace-alias-definition*, only namespace names are considered, see 6.4.6. — end note]
- <sup>3</sup> In a declarative region, a *namespace-alias-definition* can be used to redefine a *namespace-alias* declared in that declarative region to refer only to the namespace to which it already refers. [Example: The following declarations are well-formed:

```

namespace Company_with_very_long_name { /* ... */ }
namespace CWVLN = Company_with_very_long_name;
namespace CWVLN = Company_with_very_long_name; // OK: duplicate
namespace CWVLN = CWVLN;

```

— end example]

### 10.3.3 The using declaration

[namespace.udecl]

```

using-declaration:
 using using-declarator-list ;

using-declarator-list:
 using-declarator ...opt
 using-declarator-list , using-declarator ...opt

using-declarator:
 typenameopt nested-name-specifier unqualified-id

```

- <sup>1</sup> Each *using-declarator* in a *using-declaration*<sup>98</sup> introduces a set of declarations into the declarative region in which the *using-declaration* appears. The set of declarations introduced by the *using-declarator* is found by performing qualified name lookup (6.4.3, 13.2) for the name in the *using-declarator*, excluding functions that are hidden as described below. If the *using-declarator* does not name a constructor, the *unqualified-id* is declared in the declarative region in which the *using-declaration* appears as a synonym for each declaration introduced by the *using-declarator*. [Note: Only the specified name is so declared; specifying an enumeration name in a *using-declaration* does not declare its enumerators in the *using-declaration*'s declarative region.

<sup>98</sup>) A *using-declaration* with more than one *using-declarator* is equivalent to a corresponding sequence of *using-declarations* with one *using-declarator* each.

— *end note*] If the *using-declarator* names a constructor, it declares that the class *inherits* the set of constructor declarations introduced by the *using-declarator* from the nominated base class.

- <sup>2</sup> Every *using-declaration* is a *declaration* and a *member-declaration* and can therefore be used in a class definition. [ *Example*:

```
struct B {
 void f(char);
 void g(char);
 enum E { e };
 union { int x; };
};

struct D : B {
 using B::f;
 void f(int) { f('c'); } // calls B::f(char)
 void g(int) { g('c'); } // recursively calls D::g(int)
};
```

— *end example*]

- <sup>3</sup> In a *using-declaration* used as a *member-declaration*, each *using-declarator*'s *nested-name-specifier* shall name a base class of the class being defined. If a *using-declarator* names a constructor, its *nested-name-specifier* shall name a direct base class of the class being defined. [ *Example*:

```
template <typename... bases>
struct X : bases... {
 using bases::g...;
};

X<B, D> x; // OK: B::g and D::g introduced
```

— *end example*] [ *Example*:

```
class C {
 int g();
};

class D2 : public B {
 using B::f; // OK: B is a base of D2
 using B::e; // OK: e is an enumerator of base B
 using B::x; // OK: x is a union member of base B
 using C::g; // error: C isn't a base of D2
};
```

— *end example*]

- <sup>4</sup> [ *Note*: Since destructors do not have names, a *using-declaration* cannot refer to a destructor for a base class. Since specializations of member templates for conversion functions are not found by name lookup, they are not considered when a *using-declaration* specifies a conversion function (17.5.2). — *end note*] If a constructor or assignment operator brought from a base class into a derived class has the signature of a copy/move constructor or assignment operator for the derived class (15.8), the *using-declaration* does not by itself suppress the implicit declaration of the derived class member; the member from the base class is hidden or overridden by the implicitly-declared copy/move constructor or assignment operator of the derived class, as described below.
- <sup>5</sup> A *using-declaration* shall not name a *template-id*. [ *Example*:

```
struct A {
 template <class T> void f(T);
```

```

 template <class T> struct X { };
};
struct B : A {
 using A::f<double>; // ill-formed
 using A::X<int>; // ill-formed
};

```

— end example]

<sup>6</sup> A *using-declaration* shall not name a namespace.

<sup>7</sup> A *using-declaration* shall not name a scoped enumerator.

<sup>8</sup> A *using-declaration* that names a class member shall be a *member-declaration*. [Example:

```

struct X {
 int i;
 static int s;
};

void f() {
 using X::i; // error: X::i is a class member and this is not a member declaration.
 using X::s; // error: X::s is a class member and this is not a member declaration.
}

```

— end example]

<sup>9</sup> Members declared by a *using-declaration* can be referred to by explicit qualification just like other member names (6.4.3.2). [Example:

```

void f();

namespace A {
 void g();
}

namespace X {
 using ::f; // global f
 using A::g; // A's g
}

void h()
{
 X::f(); // calls ::f
 X::g(); // calls A::g
}

```

— end example]

<sup>10</sup> A *using-declaration* is a *declaration* and can therefore be used repeatedly where (and only where) multiple declarations are allowed. [Example:

```

namespace A {
 int i;
}

namespace A1 {
 using A::i, A::i; // OK: double declaration
}

struct B {

```

```

 int i;
};

struct X : B {
 using B::i, B::i; // error: double member declaration
};

```

— end example]

- <sup>11</sup> [Note: For a *using-declaration* whose *nested-name-specifier* names a namespace, members added to the namespace after the *using-declaration* are not in the set of introduced declarations, so they are not considered when a use of the name is made. Thus, additional overloads added after the *using-declaration* are ignored, but default function arguments (11.3.6), default template arguments (17.1), and template specializations (17.5.5, 17.7.3) are considered. — end note] [Example:

```

namespace A {
 void f(int);
}

using A::f; // f is a synonym for A::f; that is, for A::f(int).
namespace A {
 void f(char);
}

void foo() {
 f('a'); // calls f(int), even though f(char) exists.
}

void bar() {
 using A::f; // f is a synonym for A::f; that is, for A::f(int) and A::f(char).
 f('a'); // calls f(char)
}

```

— end example]

- <sup>12</sup> [Note: Partial specializations of class templates are found by looking up the primary class template and then considering all partial specializations of that template. If a *using-declaration* names a class template, partial specializations introduced after the *using-declaration* are effectively visible because the primary template is visible (17.5.5). — end note]
- <sup>13</sup> Since a *using-declaration* is a declaration, the restrictions on declarations of the same name in the same declarative region (6.3) also apply to *using-declarations*. [Example:

```

namespace A {
 int x;
}

namespace B {
 int i;
 struct g { };
 struct x { };
 void f(int);
 void f(double);
 void g(char); // OK: hides struct g
}

void func() {
 int i;
}

```



```

using B::i; // error: i declared twice
void f(char);
using B::f; // OK: each f is a function
f(3.5); // calls B::f(double)
using B::g;
g('a'); // calls B::g(char)
struct g g1; // g1 has class type B::g
using B::x;
using A::x; // OK: hides struct B::x
x = 99; // assigns to A::x
struct x x1; // x1 has class type B::x
}

```

— end example]

- <sup>14</sup> If a function declaration in namespace scope or block scope has the same name and the same parameter-type-list (11.3.5) as a function introduced by a *using-declaration*, and the declarations do not declare the same function, the program is ill-formed. If a function template declaration in namespace scope has the same name, parameter-type-list, return type, and template parameter list as a function template introduced by a *using-declaration*, the program is ill-formed. [Note: Two *using-declarations* may introduce functions with the same name and the same parameter-type-list. If, for a call to an unqualified function name, function overload resolution selects the functions introduced by such *using-declarations*, the function call is ill-formed. [Example:

```

namespace B {
 void f(int);
 void f(double);
}
namespace C {
 void f(int);
 void f(double);
 void f(char);
}

void h() {
 using B::f; // B::f(int) and B::f(double)
 using C::f; // C::f(int), C::f(double), and C::f(char)
 f('h'); // calls C::f(char)
 f(1); // error: ambiguous: B::f(int) or C::f(int)?
 void f(int); // error: f(int) conflicts with C::f(int) and B::f(int)
}

```

— end example] — end note]

- <sup>15</sup> When a *using-declarator* brings declarations from a base class into a derived class, member functions and member function templates in the derived class override and/or hide member functions and member function templates with the same name, parameter-type-list (11.3.5), cv-qualification, and *ref-qualifier* (if any) in a base class (rather than conflicting). Such hidden or overridden declarations are excluded from the set of declarations introduced by the *using-declarator*. [Example:

```

struct B {
 virtual void f(int);
 virtual void f(char);
 void g(int);
 void h(int);
};

```

```

struct D : B {
 using B::f;
 void f(int); // OK: D::f(int) overrides B::f(int);

 using B::g;
 void g(char); // OK

 using B::h;
 void h(int); // OK: D::h(int) hides B::h(int)
};

void k(D* p)
{
 p->f(1); // calls D::f(int)
 p->f('a'); // calls B::f(char)
 p->g(1); // calls B::g(int)
 p->g('a'); // calls D::g(char)
}

struct B1 {
 B1(int);
};

struct B2 {
 B2(int);
};

struct D1 : B1, B2 {
 using B1::B1;
 using B2::B2;
};
D1 d1(0); // ill-formed: ambiguous

struct D2 : B1, B2 {
 using B1::B1;
 using B2::B2;
 D2(int); // OK: D2::D2(int) hides B1::B1(int) and B2::B2(int)
};
D2 d2(0); // calls D2::D2(int)
— end example]

```

- <sup>16</sup> For the purpose of overload resolution, the functions that are introduced by a *using-declaration* into a derived class are treated as though they were members of the derived class. In particular, the implicit `this` parameter shall be treated as if it were a pointer to the derived class rather than to the base class. This has no effect on the type of the function, and in all other respects the function remains a member of the base class. Likewise, constructors that are introduced by a *using-declaration* are treated as though they were constructors of the derived class when looking up the constructors of the derived class (6.4.3.1) or forming a set of overload candidates (16.3.1.3, 16.3.1.4, 16.3.1.7). If such a constructor is selected to perform the initialization of an object of class type, all subobjects other than the base class from which the constructor originated are implicitly initialized (15.6.3).
- <sup>17</sup> In a *using-declarator* that does not name a constructor, all members of the set of introduced declarations shall be accessible. In a *using-declarator* that names a constructor, no access check is performed. In particular, if a derived class uses a *using-declarator* to access a member of a base class, the member name shall be accessible. If the name is that of an overloaded member function, then all functions named shall be accessible. The base

class members mentioned by a *using-declarator* shall be visible in the scope of at least one of the direct base classes of the class where the *using-declarator* is specified.

- 18 [ *Note:* Because a *using-declarator* designates a base class member (and not a member subobject or a member function of a base class subobject), a *using-declarator* cannot be used to resolve inherited member ambiguities. [ *Example:*

```
struct A { int x(); };
struct B : A { };
struct C : A {
 using A::x;
 int x(int);
};

struct D : B, C {
 using C::x;
 int x(double);
};

int f(D* d) {
 return d->x(); // error: overload resolution selects A::x, but A is an ambiguous base class
}
```

— end example] — end note]

- 19 A synonym created by a *using-declaration* has the usual accessibility for a *member-declaration*. A *using-declarator* that names a constructor does not create a synonym; instead, the additional constructors are accessible if they would be accessible when used to construct an object of the corresponding base class, and the accessibility of the *using-declaration* is ignored. [ *Example:*

```
class A {
private:
 void f(char);
public:
 void f(int);
protected:
 void g();
};

class B : public A {
 using A::f; // error: A::f(char) is inaccessible
public:
 using A::g; // B::g is a public synonym for A::g
};
```

— end example]

- 20 If a *using-declarator* uses the keyword **typename** and specifies a dependent name (17.6.2), the name introduced by the *using-declaration* is treated as a *typedef-name* (10.1.3).

### 10.3.4 Using directive

[namespace.udir]

*using-directive:*

*attribute-specifier-seq<sub>opt</sub>* **using** **namespace** *nested-name-specifier<sub>opt</sub>* *namespace-name* ;

- 1 A *using-directive* shall not appear in class scope, but may appear in namespace scope or in block scope. [ *Note:* When looking up a *namespace-name* in a *using-directive*, only namespace names are considered, see 6.4.6. — end note ] The optional *attribute-specifier-seq* appertains to the *using-directive*.
- 2 A *using-directive* specifies that the names in the nominated namespace can be used in the scope in which the *using-directive* appears after the *using-directive*. During unqualified name lookup (6.4.1), the names appear

as if they were declared in the nearest enclosing namespace which contains both the *using-directive* and the nominated namespace. [ *Note:* In this context, “contains” means “contains directly or indirectly”. — *end note* ]

- <sup>3</sup> A *using-directive* does not add any members to the declarative region in which it appears. [ *Example:*

```
namespace A {
 int i;
 namespace B {
 namespace C {
 int i;
 }
 using namespace A::B::C;
 void f1() {
 i = 5; // OK, C::i visible in B and hides A::i
 }
 }
 namespace D {
 using namespace B;
 using namespace C;
 void f2() {
 i = 5; // ambiguous, B::C::i or A::i?
 }
 }
 void f3() {
 i = 5; // uses A::i
 }
}
void f4() {
 i = 5; // ill-formed; neither i is visible
}
```

— *end example* ]

- <sup>4</sup> For unqualified lookup (6.4.1), the *using-directive* is transitive: if a scope contains a *using-directive* that nominates a second namespace that itself contains *using-directives*, the effect is as if the *using-directives* from the second namespace also appeared in the first. [ *Note:* For qualified lookup, see 6.4.3.2. — *end note* ] [ *Example:*

```
namespace M {
 int i;
}

namespace N {
 int i;
 using namespace M;
}

void f() {
 using namespace N;
 i = 7; // error: both M::i and N::i are visible
}
```

For another example,

```
namespace A {
 int i;
}
```

```

namespace B {
 int i;
 int j;
 namespace C {
 namespace D {
 using namespace A;
 int j;
 int k;
 int a = i; // B::i hides A::i
 }
 using namespace D;
 int k = 89; // no problem yet
 int l = k; // ambiguous: C::k or D::k
 int m = i; // B::i hides A::i
 int n = j; // D::j hides B::j
 }
}

```

— end example]

- <sup>5</sup> If a namespace is extended (10.3.1) after a *using-directive* for that namespace is given, the additional members of the extended namespace and the members of namespaces nominated by *using-directives* in the extending *namespace-definition* can be used after the extending *namespace-definition*.
- <sup>6</sup> If name lookup finds a declaration for a name in two different namespaces, and the declarations do not declare the same entity and do not declare functions, the use of the name is ill-formed. [ *Note:* In particular, the name of a variable, function or enumerator does not hide the name of a class or enumeration declared in a different namespace. For example,

```

namespace A {
 class X { };
 extern "C" int g();
 extern "C++" int h();
}
namespace B {
 void X(int);
 extern "C" int g();
 extern "C++" int h(int);
}
using namespace A;
using namespace B;

void f() {
 X(1); // error: name X found in two namespaces
 g(); // OK: name g refers to the same entity
 h(); // OK: overload resolution selects A::h
}

```

— end note]

- <sup>7</sup> During overload resolution, all functions from the transitive search are considered for argument matching. The set of declarations found by the transitive search is unordered. [ *Note:* In particular, the order in which namespaces were considered and the relationships among the namespaces implied by the *using-directives* do not cause preference to be given to any of the declarations found by the search. — end note] An ambiguity exists if the best match finds two functions with the same signature, even if one is in a namespace reachable

through *using-directives* in the namespace of the other.<sup>99</sup> [Example:

```
namespace D {
 int d1;
 void f(char);
}
using namespace D;

int d1; // OK: no conflict with D::d1

namespace E {
 int e;
 void f(int);
}

namespace D { // namespace extension
 int d2;
 using namespace E;
 void f(int);
}

void f() {
 d1++; // error: ambiguous ::d1 or D::d1?
 ::d1++; // OK
 D::d1++; // OK
 d2++; // OK: D::d2
 e++; // OK: E::e
 f(1); // error: ambiguous: D::f(int) or E::f(int)?
 f('a'); // OK: D::f(char)
}
```

— end example]

## 10.4 The asm declaration

[dcl.asm]

- <sup>1</sup> An **asm** declaration has the form

*asm-definition*:  
*attribute-specifier-seq<sub>opt</sub>* **asm** ( *string-literal* ) ;

The **asm** declaration is conditionally-supported; its meaning is implementation-defined. The optional *attribute-specifier-seq* in an *asm-definition* appertains to the **asm** declaration. [Note: Typically it is used to pass information through the implementation to an assembler. — end note]

## 10.5 Linkage specifications

[dcl.link]

- <sup>1</sup> All function types, function names with external linkage, and variable names with external linkage have a *language linkage*. [Note: Some of the properties associated with an entity with language linkage are specific to each implementation and are not described here. For example, a particular language linkage may be associated with a particular form of representing names of objects and functions with external linkage, or with a particular calling convention, etc. — end note] The default language linkage of all function types, function names, and variable names is C++ language linkage. Two function types with different language linkages are distinct types even if they are otherwise identical.
- <sup>2</sup> Linkage (6.5) between C++ and non-C++ code fragments can be achieved using a *linkage-specification*:

<sup>99</sup> During name lookup in a class hierarchy, some ambiguities may be resolved by considering whether one member hides the other along some paths (13.2). There is no such disambiguation when considering the set of names found as a result of following *using-directives*.

*linkage-specification:*

```
extern string-literal { declaration-seqopt }
extern string-literal declaration
```

The *string-literal* indicates the required language linkage. This International Standard specifies the semantics for the *string-literals* "C" and "C++". Use of a *string-literal* other than "C" or "C++" is conditionally-supported, with implementation-defined semantics. [ *Note:* Therefore, a linkage-specification with a *string-literal* that is unknown to the implementation requires a diagnostic. — *end note* ] [ *Note:* It is recommended that the spelling of the *string-literal* be taken from the document defining that language. For example, *Ada* (not *ADA*) and *Fortran* or *FORTTRAN*, depending on the vintage. — *end note* ]

- <sup>3</sup> Every implementation shall provide for linkage to functions written in the C programming language, "C", and linkage to C++ functions, "C++". [ *Example:*

```
complex sqrt(complex); // C++ linkage by default
extern "C" {
 double sqrt(double); // C linkage
}
```

— *end example* ]

- <sup>4</sup> Linkage specifications nest. When linkage specifications nest, the innermost one determines the language linkage. A linkage specification does not establish a scope. A *linkage-specification* shall occur only in namespace scope (6.3). In a *linkage-specification*, the specified language linkage applies to the function types of all function declarators, function names with external linkage, and variable names with external linkage declared within the *linkage-specification*. [ *Example:*

```
extern "C" // the name f1 and its function type have C language linkage;
 void f1(void(*pf)(int)); // pf is a pointer to a C function

extern "C" typedef void FUNC();
FUNC f2; // the name f2 has C++ language linkage and the
 // function's type has C language linkage

extern "C" FUNC f3; // the name of function f3 and the function's type have C language linkage

void (*pf2)(FUNC*); // the name of the variable pf2 has C++ linkage and the type
 // of pf2 is "pointer to C++ function that takes one parameter of type
 // pointer to C function"

extern "C" {
 static void f4(); // the name of the function f4 has internal linkage (not C language linkage)
 // and the function's type has C language linkage.
}

extern "C" void f5() {
 extern void f4(); // OK: Name linkage (internal) and function type linkage (C language linkage)
 // obtained from previous declaration.
}

extern void f4(); // OK: Name linkage (internal) and function type linkage (C language linkage)
 // obtained from previous declaration.

void f6() {
 extern void f4(); // OK: Name linkage (internal) and function type linkage (C language linkage)
 // obtained from previous declaration.
}
```

— *end example* ] A C language linkage is ignored in determining the language linkage of the names of class

members and the function type of class member functions. [ *Example:*

```
extern "C" typedef void FUNC_c();

class C {
 void mf1(FUNC_c*); // the name of the function mf1 and the member function's type have
 // C++ language linkage; the parameter has type "pointer to C function"

 FUNC_c mf2; // the name of the function mf2 and the member function's type have
 // C++ language linkage

 static FUNC_c* q; // the name of the data member q has C++ language linkage and
 // the data member's type is "pointer to C function"
};

extern "C" {
 class X {
 void mf(); // the name of the function mf and the member function's type have
 // C++ language linkage

 void mf2(void(*)()); // the name of the function mf2 has C++ language linkage;
 // the parameter has type "pointer to C function"
 };
}
```

— *end example*]

- 5 If two declarations declare functions with the same name and parameter-type-list (11.3.5) to be members of the same namespace or declare objects with the same name to be members of the same namespace and the declarations give the names different language linkages, the program is ill-formed; no diagnostic is required if the declarations appear in different translation units. Except for functions with C++ linkage, a function declaration without a linkage specification shall not precede the first linkage specification for that function. A function can be declared without a linkage specification after an explicit linkage specification has been seen; the linkage explicitly specified in the earlier declaration is not affected by such a function declaration.
- 6 At most one function with a particular name can have C language linkage. Two declarations for a function with C language linkage with the same function name (ignoring the namespace names that qualify it) that appear in different namespace scopes refer to the same function. Two declarations for a variable with C language linkage with the same name (ignoring the namespace names that qualify it) that appear in different namespace scopes refer to the same variable. An entity with C language linkage shall not be declared with the same name as a variable in global scope, unless both declarations denote the same entity; no diagnostic is required if the declarations appear in different translation units. A variable with C language linkage shall not be declared with the same name as a function with C language linkage (ignoring the namespace names that qualify the respective names); no diagnostic is required if the declarations appear in different translation units. [ *Note:* Only one definition for an entity with a given name with C language linkage may appear in the program (see 6.2); this implies that such an entity must not be defined in more than one namespace scope. — *end note* ] [ *Example:*

```
int x;
namespace A {
 extern "C" int f();
 extern "C" int g() { return 1; }
 extern "C" int h();
 extern "C" int x(); // ill-formed: same name as global-space object x
}

namespace B {
```



```

extern "C" int f(); // A::f and B::f refer to the same function
extern "C" int g() { return 1; } // ill-formed, the function g with C language linkage has two definitions
}

int A::f() { return 98; } // definition for the function f with C language linkage
extern "C" int h() { return 97; } // definition for the function h with C language linkage
 // A::h and ::h refer to the same function

```

— end example]

- <sup>7</sup> A declaration directly contained in a *linkage-specification* is treated as if it contains the **extern** specifier (10.1.1) for the purpose of determining the linkage of the declared name and whether it is a definition. Such a declaration shall not specify a storage class. [ *Example:*

```

extern "C" double f();
static double f(); // error
extern "C" int i; // declaration
extern "C" {
 int i; // definition
}
extern "C" static void g(); // error

```

— end example]

- <sup>8</sup> [ *Note:* Because the language linkage is part of a function type, when indirecting through a pointer to C function, the function to which the resulting lvalue refers is considered a C function. — end note ]
- <sup>9</sup> Linkage from C++ to objects defined in other languages and to objects defined in C++ from other languages is implementation-defined and language-dependent. Only where the object layout strategies of two language implementations are similar enough can such linkage be achieved.

## 10.6 Attributes

[dcl.attr]

### 10.6.1 Attribute syntax and semantics

[dcl.attr.grammar]

- <sup>1</sup> Attributes specify additional information for various source constructs such as types, variables, names, blocks, or translation units.

```

attribute-specifier-seq:
 attribute-specifier-seqopt attribute-specifier

attribute-specifier:
 [[attribute-using-prefixopt attribute-list]]
 alignment-specifier

alignment-specifier:
 alignas (type-id ...opt)
 alignas (constant-expression ...opt)

attribute-using-prefix:
 using attribute-namespace :

attribute-list:
 attributeopt
 attribute-list , attributeopt
 attribute ...
 attribute-list , attribute ...

attribute:
 attribute-token attribute-argument-clauseopt

```

*attribute-token*:  
     *identifier*  
     *attribute-scoped-token*  
  
*attribute-scoped-token*:  
     *attribute-namespace* :: *identifier*  
  
*attribute-namespace*:  
     *identifier*  
  
*attribute-argument-clause*:  
     ( *balanced-token-seq<sub>opt</sub>* )  
  
*balanced-token-seq*:  
     *balanced-token*  
     *balanced-token-seq* *balanced-token*  
  
*balanced-token*:  
     ( *balanced-token-seq<sub>opt</sub>* )  
     [ *balanced-token-seq<sub>opt</sub>* ]  
     { *balanced-token-seq<sub>opt</sub>* }  
     any *token* other than a parenthesis, a bracket, or a brace

- <sup>2</sup> If an *attribute-specifier* contains an *attribute-using-prefix*, the *attribute-list* following that *attribute-using-prefix* shall not contain an *attribute-scoped-token* and every *attribute-token* in that *attribute-list* is treated as if its *identifier* were prefixed with N::, where N is the *attribute-namespace* specified in the *attribute-using-prefix*. [Note: This rule imposes no constraints on how an *attribute-using-prefix* affects the tokens in an *attribute-argument-clause*. — end note] [Example:

```

[[using CC: opt(1), debug]] // same as [[CC::opt(1), CC::debug]]
void f() {}
[[using CC: opt(1)]] [[CC::debug]] // same as [[CC::opt(1)]] [[CC::debug]]
void g() {}
[[using CC: CC::opt(1)]] // error: cannot combine using and scoped attribute token
void h() {}
— end example]

```

- <sup>3</sup> [Note: For each individual attribute, the form of the *balanced-token-seq* will be specified. — end note]
- <sup>4</sup> In an *attribute-list*, an ellipsis may appear only if that *attribute*'s specification permits it. An *attribute* followed by an ellipsis is a pack expansion (17.5.3). An *attribute-specifier* that contains no *attributes* has no effect. The order in which the *attribute-tokens* appear in an *attribute-list* is not significant. If a keyword (5.11) or an alternative token (5.5) that satisfies the syntactic requirements of an *identifier* (5.10) is contained in an *attribute-token*, it is considered an identifier. No name lookup (6.4) is performed on any of the identifiers contained in an *attribute-token*. The *attribute-token* determines additional requirements on the *attribute-argument-clause* (if any).
- <sup>5</sup> Each *attribute-specifier-seq* is said to *appertain* to some entity or statement, identified by the syntactic context where it appears (Clause 9, Clause 10, Clause 11). If an *attribute-specifier-seq* that appertains to some entity or statement contains an *attribute* or *alignment-specifier* that is not allowed to apply to that entity or statement, the program is ill-formed. If an *attribute-specifier-seq* appertains to a friend declaration (14.3), that declaration shall be a definition. No *attribute-specifier-seq* shall appertain to an explicit instantiation (17.7.2).
- <sup>6</sup> For an *attribute-token* (including an *attribute-scoped-token*) not specified in this International Standard, the behavior is implementation-defined. Any *attribute-token* that is not recognized by the implementation is ignored. [Note: Each implementation should choose a distinctive name for the *attribute-namespace* in an *attribute-scoped-token*. — end note]
- <sup>7</sup> Two consecutive left square bracket tokens shall appear only when introducing an *attribute-specifier* or within the *balanced-token-seq* of an *attribute-argument-clause*. [Note: If two consecutive left square brackets appear

where an *attribute-specifier* is not allowed, the program is ill-formed even if the brackets match an alternative grammar production. — *end note*] [Example:

```
int p[10];
void f() {
 int x = 42, y[5];
 int(p[[x] { return x; }()]); // error: invalid attribute on a nested declarator-id and
 // not a function-style cast of an element of p.
 y[[{ return 2; }()] = 2; // error even though attributes are not allowed in this context.
 int i [[vendor::attr([[[]]])]]; // well-formed implementation-defined attribute.
}
```

— *end example*]

### 10.6.2 Alignment specifier

[dcl.align]

- <sup>1</sup> An *alignment-specifier* may be applied to a variable or to a class data member, but it shall not be applied to a bit-field, a function parameter, or an *exception-declaration* (18.3). An *alignment-specifier* may also be applied to the declaration or definition of a class (in an *elaborated-type-specifier* (10.1.7.3) or *class-head* (Clause 12), respectively) and to the declaration or definition of an enumeration (in an *opaque-enum-declaration* or *enum-head*, respectively (10.2)). An *alignment-specifier* with an ellipsis is a pack expansion (17.5.3).
- <sup>2</sup> When the *alignment-specifier* is of the form `alignas( constant-expression )`:
  - (2.1) — the *constant-expression* shall be an integral constant expression
  - (2.2) — if the constant expression does not evaluate to an alignment value (6.11), or evaluates to an extended alignment and the implementation does not support that alignment in the context of the declaration, the program is ill-formed.
- <sup>3</sup> An *alignment-specifier* of the form `alignas( type-id )` has the same effect as `alignas(alignof( type-id ))` (8.3.6).
- <sup>4</sup> The alignment requirement of an entity is the strictest nonzero alignment specified by its *alignment-specifiers*, if any; otherwise, the *alignment-specifiers* have no effect.
- <sup>5</sup> The combined effect of all *alignment-specifiers* in a declaration shall not specify an alignment that is less strict than the alignment that would be required for the entity being declared if all *alignment-specifiers* appertaining to that entity were omitted. [Example:

```
struct alignas(8) S {};
struct alignas(1) U {
 S s;
}; // error: U specifies an alignment that is less strict than if the alignas(1) were omitted.
```

— *end example*]

- <sup>6</sup> If the defining declaration of an entity has an *alignment-specifier*, any non-defining declaration of that entity shall either specify equivalent alignment or have no *alignment-specifier*. Conversely, if any declaration of an entity has an *alignment-specifier*, every defining declaration of that entity shall specify an equivalent alignment. No diagnostic is required if declarations of an entity have different *alignment-specifiers* in different translation units. [Example:

```
// Translation unit #1:
struct S { int x; } s, *p = &s;

// Translation unit #2:
struct alignas(16) S; // error: definition of S lacks alignment, no diagnostic required
extern S* p;
```

— *end example*]

- <sup>7</sup> [*Example*: An aligned buffer with an alignment requirement of **A** and holding **N** elements of type **T** can be declared as:

```
alignas(T) alignas(A) T buffer[N];
```

Specifying `alignas(T)` ensures that the final requested alignment will not be weaker than `alignof(T)`, and therefore the program will not be ill-formed. — *end example*]

- <sup>8</sup> [*Example*:

```
alignas(double) void f(); // error: alignment applied to function
alignas(double) unsigned char c[sizeof(double)]; // array of characters, suitably aligned for a double
extern unsigned char c[sizeof(double)]; // no alignas necessary
alignas(float)
 extern unsigned char c[sizeof(double)]; // error: different alignment in declaration
```

— *end example*]

### 10.6.3 Carries dependency attribute

[**dcl.attr.depend**]

- <sup>1</sup> The *attribute-token* `carries_dependency` specifies dependency propagation into and out of functions. It shall appear at most once in each *attribute-list* and no *attribute-argument-clause* shall be present. The attribute may be applied to the *declarator-id* of a *parameter-declaration* in a function declaration or lambda, in which case it specifies that the initialization of the parameter carries a dependency to (4.7) each lvalue-to-rvalue conversion (7.1) of that object. The attribute may also be applied to the *declarator-id* of a function declaration, in which case it specifies that the return value, if any, carries a dependency to the evaluation of the function call expression.
- <sup>2</sup> The first declaration of a function shall specify the `carries_dependency` attribute for its *declarator-id* if any declaration of the function specifies the `carries_dependency` attribute. Furthermore, the first declaration of a function shall specify the `carries_dependency` attribute for a parameter if any declaration of that function specifies the `carries_dependency` attribute for that parameter. If a function or one of its parameters is declared with the `carries_dependency` attribute in its first declaration in one translation unit and the same function or one of its parameters is declared without the `carries_dependency` attribute in its first declaration in another translation unit, the program is ill-formed, no diagnostic required.
- <sup>3</sup> [*Note*: The `carries_dependency` attribute does not change the meaning of the program, but may result in generation of more efficient code. — *end note*]
- <sup>4</sup> [*Example*:

```
/* Translation unit A. */

struct foo { int* a; int* b; };
std::atomic<struct foo*> foo_head[10];
int foo_array[10][10];

[[carries_dependency]] struct foo* f(int i) {
 return foo_head[i].load(memory_order_consume);
}

int g(int* x, int* y [[carries_dependency]]) {
 return kill_dependency(foo_array[*x][*y]);
}

/* Translation unit B. */

[[carries_dependency]] struct foo* f(int i);
int g(int* x, int* y [[carries_dependency]]);
```

```

int c = 3;

void h(int i) {
 struct foo* p;

 p = f(i);
 do_something_with(g(&c, p->a));
 do_something_with(g(p->a, &c));
}

```

The `carries_dependency` attribute on function `f` means that the return value carries a dependency out of `f`, so that the implementation need not constrain ordering upon return from `f`. Implementations of `f` and its caller may choose to preserve dependencies instead of emitting hardware memory ordering instructions (a.k.a. fences).

Function `g`'s second parameter has a `carries_dependency` attribute, but its first parameter does not. Therefore, function `h`'s first call to `g` carries a dependency into `g`, but its second call does not. The implementation might need to insert a fence prior to the second call to `g`.

— *end example*]

#### 10.6.4 Deprecated attribute

[**dcl.attr.deprecated**]

- <sup>1</sup> The *attribute-token* **deprecated** can be used to mark names and entities whose use is still allowed, but is discouraged for some reason. [*Note*: In particular, **deprecated** is appropriate for names and entities that are deemed obsolescent or unsafe. — *end note*] It shall appear at most once in each *attribute-list*. An *attribute-argument-clause* may be present and, if present, it shall have the form:

( *string-literal* )

[*Note*: The *string-literal* in the *attribute-argument-clause* could be used to explain the rationale for deprecation and/or to suggest a replacing entity. — *end note*]

- <sup>2</sup> The attribute may be applied to the declaration of a class, a *typedef-name*, a variable, a non-static data member, a function, a namespace, an enumeration, an enumerator, or a template specialization.
- <sup>3</sup> A name or entity declared without the **deprecated** attribute can later be redeclared with the attribute and vice-versa. [*Note*: Thus, an entity initially declared without the attribute can be marked as deprecated by a subsequent redeclaration. However, after an entity is marked as deprecated, later redeclarations do not un-deprecate the entity. — *end note*] Redclarations using different forms of the attribute (with or without the *attribute-argument-clause* or with different *attribute-argument-clauses*) are allowed.
- <sup>4</sup> [*Note*: Implementations may use the **deprecated** attribute to produce a diagnostic message in case the program refers to a name or entity other than to declare it, after a declaration that specifies the attribute. The diagnostic message may include the text provided within the *attribute-argument-clause* of any **deprecated** attribute applied to the name or entity. — *end note*]

#### 10.6.5 Fallthrough attribute

[**dcl.attr.fallthrough**]

- <sup>1</sup> The *attribute-token* **fallthrough** may be applied to a null statement (9.2); such a statement is a fallthrough statement. The *attribute-token* **fallthrough** shall appear at most once in each *attribute-list* and no *attribute-argument-clause* shall be present. A fallthrough statement may only appear within an enclosing **switch** statement (9.4.2). The next statement that would be executed after a fallthrough statement shall be a labeled statement whose label is a case label or default label for the same **switch** statement. The program is ill-formed if there is no such statement.
- <sup>2</sup> [*Note*: The use of a fallthrough statement is intended to suppress a warning that an implementation might otherwise issue for a case or default label that is reachable from another case or default label along some

path of execution. Implementations are encouraged to issue a warning if a fallthrough statement is not dynamically reachable. — *end note*]

3 [Example:

```
void f(int n) {
 void g(), h(), i();
 switch (n) {
 case 1:
 case 2:
 g();
 [[fallthrough]];
 case 3:
 h();
 case 4:
 i();
 [[fallthrough]];
 }
}
```

*// warning on fallthrough discouraged*  
*// implementation may warn on fallthrough*  
*// ill-formed*

— *end example*]

### 10.6.6 Maybe unused attribute

[**dcl.attr.unused**]

- 1 The *attribute-token* **maybe\_unused** indicates that a name or entity is possibly intentionally unused. It shall appear at most once in each *attribute-list* and no *attribute-argument-clause* shall be present.
- 2 The attribute may be applied to the declaration of a class, a *typedef-name*, a variable, a non-static data member, a function, an enumeration, or an enumerator.
- 3 [Note: For an entity marked **maybe\_unused**, implementations are encouraged not to emit a warning that the entity is unused, or that the entity is used despite the presence of the attribute. — *end note*]
- 4 A name or entity declared without the **maybe\_unused** attribute can later be redeclared with the attribute and vice versa. An entity is considered marked after the first declaration that marks it.
- 5 [Example:

```
[[maybe_unused]] void f([[maybe_unused]] bool thing1,
 [[maybe_unused]] bool thing2) {
 [[maybe_unused]] bool b = thing1 && thing2;
 assert(b);
}
```

Implementations are encouraged not to warn that **b** is unused, whether or not **NDEBUG** is defined. — *end example*]

### 10.6.7 Nodiscard attribute

[**dcl.attr.nodiscard**]

- 1 The *attribute-token* **nodiscard** may be applied to the *declarator-id* in a function declaration or to the declaration of a class or enumeration. It shall appear at most once in each *attribute-list* and no *attribute-argument-clause* shall be present.
- 2 [Note: A nodiscard call is a function call expression that calls a function previously declared **nodiscard**, or whose return type is a possibly cv-qualified class or enumeration type marked **nodiscard**. Appearance of a nodiscard call as a potentially-evaluated discarded-value expression (Clause 8) is discouraged unless explicitly cast to **void**. Implementations are encouraged to issue a warning in such cases. This is typically because discarding the return value of a nodiscard call has surprising consequences. — *end note*]
- 3 [Example:

```
struct [[nodiscard]] error_info { /* ... */};
```

```

error_info enable_missile_safety_mode();
void launch_missiles();
void test_missiles() {
 enable_missile_safety_mode(); // warning encouraged
 launch_missiles();
}
error_info &foo();
void f() { foo(); } // warning not encouraged: not a nodiscard call, because neither
 // the (reference) return type nor the function is declared nodiscard

```

— end example]

### 10.6.8 Noreturn attribute

[**dcl.attr.noreturn**]

- <sup>1</sup> The *attribute-token* **noreturn** specifies that a function does not return. It shall appear at most once in each *attribute-list* and no *attribute-argument-clause* shall be present. The attribute may be applied to the *declarator-id* in a function declaration. The first declaration of a function shall specify the **noreturn** attribute if any declaration of that function specifies the **noreturn** attribute. If a function is declared with the **noreturn** attribute in one translation unit and the same function is declared without the **noreturn** attribute in another translation unit, the program is ill-formed, no diagnostic required.
- <sup>2</sup> If a function **f** is called where **f** was previously declared with the **noreturn** attribute and **f** eventually returns, the behavior is undefined. [*Note*: The function may terminate by throwing an exception. — end note]  
[*Note*: Implementations are encouraged to issue a warning if a function marked [**noreturn**] might return. — end note]
- <sup>3</sup> [*Example*:

```

[[noreturn]] void f() {
 throw "error"; // OK
}

[[noreturn]] void q(int i) { // behavior is undefined if called with an argument <= 0
 if (i > 0)
 throw "positive";
}

```

— end example]

# 11 Declarators

[dcl.decl]

- <sup>1</sup> A declarator declares a single variable, function, or type, within a declaration. The *init-declarator-list* appearing in a declaration is a comma-separated sequence of declarators, each of which can have an initializer.

*init-declarator-list*:  
*init-declarator*  
*init-declarator-list* , *init-declarator*  
*init-declarator*:  
*declarator* *initializer<sub>opt</sub>*

- <sup>2</sup> The three components of a *simple-declaration* are the attributes (10.6), the specifiers (*decl-specifier-seq*; 10.1) and the declarators (*init-declarator-list*). The specifiers indicate the type, storage class or other properties of the entities being declared. The declarators specify the names of these entities and (optionally) modify the type of the specifiers with operators such as \* (pointer to) and () (function returning). Initial values can also be specified in a declarator; initializers are discussed in 11.6 and 15.6.
- <sup>3</sup> Each *init-declarator* in a declaration is analyzed separately as if it was in a declaration by itself. [ *Note*: A declaration with several declarators is usually equivalent to the corresponding sequence of declarations each with a single declarator. That is

```
T D1, D2, ... Dn;
```

is usually equivalent to

```
T D1; T D2; ... T Dn;
```

where T is a *decl-specifier-seq* and each Di is an *init-declarator*. One exception is when a name introduced by one of the *declarators* hides a type name used by the *decl-specifiers*, so that when the same *decl-specifiers* are used in a subsequent declaration, they do not have the same meaning, as in

```
struct S { ... };
S S, T; // declare two instances of struct S
```

which is not equivalent to

```
struct S { ... };
S S;
S T; // error
```

Another exception is when T is *auto* (10.1.7.4), for example:

```
auto i = 1, j = 2.0; // error: deduced types for i and j do not match
```

as opposed to

```
auto i = 1; // OK: i deduced to have type int
auto j = 2.0; // OK: j deduced to have type double
```

— end note ]

- <sup>4</sup> Declarators have the syntax

*declarator*:  
*ptr-declarator*  
*noPtr-declarator* *parameters-and-qualifiers* *trailing-return-type*  
*ptr-declarator*:  
*noPtr-declarator*  
*ptr-operator* *ptr-declarator*



*noptr-declarator*:  
*declarator-id* *attribute-specifier-seq*<sub>opt</sub>  
*noptr-declarator* *parameters-and-qualifiers*  
*noptr-declarator* [ *constant-expression*<sub>opt</sub> ] *attribute-specifier-seq*<sub>opt</sub>  
( *ptr-declarator* )

*parameters-and-qualifiers*:  
( *parameter-declaration-clause* ) *cv-qualifier-seq*<sub>opt</sub>  
*ref-qualifier*<sub>opt</sub> *noexcept-specifier*<sub>opt</sub> *attribute-specifier-seq*<sub>opt</sub>

*trailing-return-type*:  
-> *type-id*

*ptr-operator*:  
\* *attribute-specifier-seq*<sub>opt</sub> *cv-qualifier-seq*<sub>opt</sub>  
& *attribute-specifier-seq*<sub>opt</sub>  
&& *attribute-specifier-seq*<sub>opt</sub>  
*nested-name-specifier* \* *attribute-specifier-seq*<sub>opt</sub> *cv-qualifier-seq*<sub>opt</sub>

*cv-qualifier-seq*:  
*cv-qualifier* *cv-qualifier-seq*<sub>opt</sub>

*cv-qualifier*:  
**const**  
**volatile**

*ref-qualifier*:  
&  
&&

*declarator-id*:  
...<sub>opt</sub> *id-expression*

## 11.1 Type names

[dcl.name]

- <sup>1</sup> To specify type conversions explicitly, and as an argument of **sizeof**, **alignof**, **new**, or **typeid**, the name of a type shall be specified. This can be done with a *type-id*, which is syntactically a declaration for a variable or function of that type that omits the name of the entity.

*type-id*:  
*type-specifier-seq* *abstract-declarator*<sub>opt</sub>

*defining-type-id*:  
*defining-type-specifier-seq* *abstract-declarator*<sub>opt</sub>

*abstract-declarator*:  
*ptr-abstract-declarator*  
*noptr-abstract-declarator*<sub>opt</sub> *parameters-and-qualifiers* *trailing-return-type*  
*abstract-pack-declarator*

*ptr-abstract-declarator*:  
*noptr-abstract-declarator*  
*ptr-operator* *ptr-abstract-declarator*<sub>opt</sub>

*noptr-abstract-declarator*:  
*noptr-abstract-declarator*<sub>opt</sub> *parameters-and-qualifiers*  
*noptr-abstract-declarator*<sub>opt</sub> [ *constant-expression*<sub>opt</sub> ] *attribute-specifier-seq*<sub>opt</sub>  
( *ptr-abstract-declarator* )

*abstract-pack-declarator*:  
*noptr-abstract-pack-declarator*  
*ptr-operator* *abstract-pack-declarator*

```

nopt-abstract-pack-declarator:
 nopt-abstract-pack-declarator parameters-and-qualifiers
 nopt-abstract-pack-declarator [constant-expressionopt] attribute-specifier-seqopt
 ...

```

It is possible to identify uniquely the location in the *abstract-declarator* where the identifier would appear if the construction were a declarator in a declaration. The named type is then the same as the type of the hypothetical identifier. [ *Example*:

```

int // int i
int * // int *pi
int *[3] // int *p[3]
int (*)[3] // int (*p3i)[3]
int *() // int *f()
int (*)(double) // int (*pf)(double)

```

name respectively the types “**int**”, “pointer to **int**”, “array of 3 pointers to **int**”, “pointer to array of 3 **int**”, “function of (no parameters) returning pointer to **int**”, and “pointer to a function of (**double**) returning **int**”. — *end example*]

- <sup>2</sup> A type can also be named (often more easily) by using a **typedef** (10.1.3).

## 11.2 Ambiguity resolution

[**dcl.ambig.res**]

- <sup>1</sup> The ambiguity arising from the similarity between a function-style cast and a declaration mentioned in 9.8 can also occur in the context of a declaration. In that context, the choice is between a function declaration with a redundant set of parentheses around a parameter name and an object declaration with a function-style cast as the initializer. Just as for the ambiguities mentioned in 9.8, the resolution is to consider any construct that could possibly be a declaration a declaration. [ *Note*: A declaration can be explicitly disambiguated by adding parentheses around the argument. The ambiguity can be avoided by use of copy-initialization or list-initialization syntax, or by use of a non-function-style cast. — *end note* ] [ *Example*:

```

struct S {
 S(int);
};

void foo(double a) {
 S w(int(a)); // function declaration
 S x(int()); // function declaration
 S y((int(a))); // object declaration
 S y((int)a); // object declaration
 S z = int(a); // object declaration
}

```

— *end example*]

- <sup>2</sup> An ambiguity can arise from the similarity between a function-style cast and a *type-id*. The resolution is that any construct that could possibly be a *type-id* in its syntactic context shall be considered a *type-id*. [ *Example*:

```

template <class T> struct X {};
template <int N> struct Y {};
X<int(>) a; // type-id
X<int(1)> b; // expression (ill-formed)
Y<int(>) c; // type-id (ill-formed)
Y<int(1)> d; // expression

void foo(signed char a) {
 sizeof(int(>)); // type-id (ill-formed)
}

```

```

sizeof(int(a)); // expression
sizeof(int(unsigned(a))); // type-id (ill-formed)

(int())+1; // type-id (ill-formed)
(int(a))+1; // expression
(int(unsigned(a)))+1; // type-id (ill-formed)
}

```

— end example]

- <sup>3</sup> Another ambiguity arises in a *parameter-declaration-clause* when a *type-name* is nested in parentheses. In this case, the choice is between the declaration of a parameter of type pointer to function and the declaration of a parameter with redundant parentheses around the *declarator-id*. The resolution is to consider the *type-name* as a *simple-type-specifier* rather than a *declarator-id*. [Example:

```

class C { };
void f(int(C)) { } // void f(int(*fp)(C c)) { }
 // not: void f(int C) { }

int g(C);

void foo() {
 f(1); // error: cannot convert 1 to function pointer
 f(g); // OK
}

```

For another example,

```

class C { };
void h(int *(C[10])); // void h(int *(*_fp)(C _parm[10]));
 // not: void h(int *C[10]);

```

— end example]

### 11.3 Meaning of declarators

[dcl.meaning]

- <sup>1</sup> A declarator contains exactly one *declarator-id*; it names the identifier that is declared. An *unqualified-id* occurring in a *declarator-id* shall be a simple *identifier* except for the declaration of some special functions (15.1, 15.3, 15.4, 16.5) and for the declaration of template specializations or partial specializations (17.7). When the *declarator-id* is qualified, the declaration shall refer to a previously declared member of the class or namespace to which the qualifier refers (or, in the case of a namespace, of an element of the inline namespace set of that namespace (10.3.1)) or to a specialization thereof; the member shall not merely have been introduced by a *using-declaration* in the scope of the class or namespace nominated by the *nested-name-specifier* of the *declarator-id*. The *nested-name-specifier* of a qualified *declarator-id* shall not begin with a *decltype-specifier*. [Note: If the qualifier is the global :: scope resolution operator, the *declarator-id* refers to a name declared in the global namespace scope. — end note] The optional *attribute-specifier-seq* following a *declarator-id* appertains to the entity that is declared.
- <sup>2</sup> A **static**, **thread\_local**, **extern**, **mutable**, **friend**, **inline**, **virtual**, **constexpr**, **explicit**, or **typedef** specifier applies directly to each *declarator-id* in an *init-declarator-list* or *member-declarator-list*; the type specified for each *declarator-id* depends on both the *decl-specifier-seq* and its *declarator*.
- <sup>3</sup> Thus, a declaration of a particular identifier has the form
- T D
- where T is of the form *attribute-specifier-seq<sub>opt</sub> decl-specifier-seq* and D is a declarator. Following is a recursive procedure for determining the type specified for the contained *declarator-id* by such a declaration.
- <sup>4</sup> First, the *decl-specifier-seq* determines a type. In a declaration

T D

the *decl-specifier-seq* T determines the type T. [*Example:* In the declaration

```
int unsigned i;
```

the type specifiers `int unsigned` determine the type “`unsigned int`” (10.1.7.2). — *end example*]

<sup>5</sup> In a declaration *attribute-specifier-seq<sub>opt</sub>* T D where D is an unadorned identifier the type of this identifier is “T”.

<sup>6</sup> In a declaration T D where D has the form

```
(D1)
```

the type of the contained *declarator-id* is the same as that of the contained *declarator-id* in the declaration

```
T D1
```

Parentheses do not alter the type of the embedded *declarator-id*, but they can alter the binding of complex declarators.

### 11.3.1 Pointers

[**dcl.ptr**]

<sup>1</sup> In a declaration T D where D has the form

```
* attribute-specifier-seqopt cv-qualifier-seqopt D1
```

and the type of the identifier in the declaration T D1 is “*derived-declarator-type-list* T”, then the type of the identifier of D is “*derived-declarator-type-list* cv-qualifier-seq pointer to T”. The *cv-qualifiers* apply to the pointer and not to the object pointed to. Similarly, the optional *attribute-specifier-seq* (10.6.1) appertains to the pointer and not to the object pointed to.

<sup>2</sup> [*Example:* The declarations

```
const int ci = 10, *pc = &ci, *const cpc = pc, **ppc;
int i, *p, *const cp = &i;
```

declare `ci`, a constant integer; `pc`, a pointer to a constant integer; `cpc`, a constant pointer to a constant integer; `ppc`, a pointer to a pointer to a constant integer; `i`, an integer; `p`, a pointer to integer; and `cp`, a constant pointer to integer. The value of `ci`, `cpc`, and `cp` cannot be changed after initialization. The value of `pc` can be changed, and so can the object pointed to by `cp`. Examples of some correct operations are

```
i = ci;
*cp = ci;
pc++;
pc = cpc;
pc = p;
ppc = &pc;
```

Examples of ill-formed operations are

```
ci = 1; // error
ci++; // error
*pc = 2; // error
cp = &ci; // error
cpc++; // error
p = pc; // error
ppc = &p; // error
```

Each is unacceptable because it would either change the value of an object declared `const` or allow it to be changed through a cv-unqualified pointer later, for example:

```
*ppc = &ci; // OK, but would make p point to ci because of previous error
*p = 5; // clobber ci
```

— *end example*]

<sup>3</sup> See also 8.18 and 11.6.

<sup>4</sup> [ *Note*: Forming a pointer to reference type is ill-formed; see 11.3.2. Forming a function pointer type is ill-formed if the function type has *cv-qualifiers* or a *ref-qualifier*; see 11.3.5. Since the address of a bit-field (12.2.4) cannot be taken, a pointer can never point to a bit-field. — *end note*]

### 11.3.2 References

[dcl.ref]

<sup>1</sup> In a declaration `T D` where `D` has either of the forms

```
& attribute-specifier-seqopt D1
&& attribute-specifier-seqopt D1
```

and the type of the identifier in the declaration `T D1` is “*derived-declarator-type-list T*”, then the type of the identifier of `D` is “*derived-declarator-type-list reference to T*”. The optional *attribute-specifier-seq* appertains to the reference type. Cv-qualified references are ill-formed except when the cv-qualifiers are introduced through the use of a *typedef-name* (10.1.3, 17.1) or *decltype-specifier* (10.1.7.2), in which case the cv-qualifiers are ignored. [ *Example*:

```
typedef int& A;
const A aref = 3; // ill-formed; lvalue reference to non-const initialized with rvalue
```

The type of `aref` is “lvalue reference to `int`”, not “lvalue reference to `const int`”. — *end example*] [ *Note*: A reference can be thought of as a name of an object. — *end note*] A declarator that specifies the type “reference to *cv void*” is ill-formed.

<sup>2</sup> A reference type that is declared using `&` is called an *lvalue reference*, and a reference type that is declared using `&&` is called an *rvalue reference*. Lvalue references and rvalue references are distinct types. Except where explicitly noted, they are semantically equivalent and commonly referred to as references.

<sup>3</sup> [ *Example*:

```
void f(double& a) { a += 3.14; }
// ...
double d = 0;
f(d);
```

declares `a` to be a reference parameter of `f` so the call `f(d)` will add 3.14 to `d`.

```
int v[20];
// ...
int& g(int i) { return v[i]; }
// ...
g(3) = 7;
```

declares the function `g()` to return a reference to an integer so `g(3)=7` will assign 7 to the fourth element of the array `v`. For another example,

```
struct link {
 link* next;
};

link* first;

void h(link*& p) { // p is a reference to pointer
 p->next = first;
 first = p;
 p = 0;
}
```

```

void k() {
 link* q = new link;
 h(q);
}

```

declares `p` to be a reference to a pointer to `link` so `h(q)` will leave `q` with the value zero. See also 11.6.3. — *end example*]

- <sup>4</sup> It is unspecified whether or not a reference requires storage (6.7).
- <sup>5</sup> There shall be no references to references, no arrays of references, and no pointers to references. The declaration of a reference shall contain an *initializer* (11.6.3) except when the declaration contains an explicit **extern** specifier (10.1.1), is a class member (12.2) declaration within a class definition, or is the declaration of a parameter or a return type (11.3.5); see 6.1. A reference shall be initialized to refer to a valid object or function. [ *Note*: In particular, a null reference cannot exist in a well-defined program, because the only way to create such a reference would be to bind it to the “object” obtained by indirection through a null pointer, which causes undefined behavior. As described in 12.2.4, a reference cannot be bound directly to a bit-field. — *end note*]
- <sup>6</sup> If a *typedef-name* (10.1.3, 17.1) or a *decltype-specifier* (10.1.7.2) denotes a type `TR` that is a reference to a type `T`, an attempt to create the type “lvalue reference to *cv* `TR`” creates the type “lvalue reference to `T`”, while an attempt to create the type “rvalue reference to *cv* `TR`” creates the type `TR`. [ *Note*: This rule is known as reference collapsing. — *end note* ] [ *Example*:

```

int i;
typedef int& LRI;
typedef int&& RRI;

LRI& r1 = i; // r1 has the type int&
const LRI& r2 = i; // r2 has the type int&
const LRI&& r3 = i; // r3 has the type int&

RRI& r4 = i; // r4 has the type int&
RRI&& r5 = i; // r5 has the type int&&

decltype(r2)& r6 = i; // r6 has the type int&
decltype(r2)&& r7 = i; // r7 has the type int&

```

— *end example*]

- <sup>7</sup> [ *Note*: Forming a reference to function type is ill-formed if the function type has *cv-qualifiers* or a *ref-qualifier*; see 11.3.5. — *end note*]

### 11.3.3 Pointers to members

[**dcl.mptr**]

- <sup>1</sup> In a declaration `T D` where `D` has the form

*nested-name-specifier* \* *attribute-specifier-seq<sub>opt</sub>* *cv-qualifier-seq<sub>opt</sub>* `D1`

and the *nested-name-specifier* denotes a class, and the type of the identifier in the declaration `T D1` is “*derived-declarator-type-list* `T`”, then the type of the identifier of `D` is “*derived-declarator-type-list cv-qualifier-seq* pointer to member of class *nested-name-specifier* of type `T`”. The optional *attribute-specifier-seq* (10.6.1) appertains to the pointer-to-member.

- <sup>2</sup> [ *Example*:

```

struct X {
 void f(int);
 int a;
};

```

```

struct Y;

int X::* pmi = &X::a;
void (X::* pmf)(int) = &X::f;
double X::* pmd;
char Y::* pmc;

```

declares `pmi`, `pmf`, `pmd` and `pmc` to be a pointer to a member of `X` of type `int`, a pointer to a member of `X` of type `void(int)`, a pointer to a member of `X` of type `double` and a pointer to a member of `Y` of type `char` respectively. The declaration of `pmd` is well-formed even though `X` has no members of type `double`. Similarly, the declaration of `pmc` is well-formed even though `Y` is an incomplete type. `pmi` and `pmf` can be used like this:

```

X obj;
// ...
obj.*pmi = 7; // assign 7 to an integer member of obj
(obj.*pmf)(7); // call a function member of obj with the argument 7
— end example]

```

- 3 A pointer to member shall not point to a static member of a class (12.2.3), a member with reference type, or “*cv void*”.

[*Note:* See also 8.3 and 8.5. The type “pointer to member” is distinct from the type “pointer”, that is, a pointer to member is declared only by the pointer to member declarator syntax, and never by the pointer declarator syntax. There is no “reference-to-member” type in C++. — *end note*]

### 11.3.4 Arrays

[**dcl.array**]

- 1 In a declaration `T D` where `D` has the form

```
D1 [constant-expressionopt] attribute-specifier-seqopt
```

and the type of the identifier in the declaration `T D1` is “*derived-declarator-type-list T*”, then the type of the identifier of `D` is an array type; if the type of the identifier of `D` contains the *auto type-specifier*, the program is ill-formed. `T` is called the array *element type*; this type shall not be a reference type, *cv void*, a function type or an abstract class type. If the *constant-expression* (8.20) is present, it shall be a converted constant expression of type `std::size_t` and its value shall be greater than zero. The constant expression specifies the *bound* of (number of elements in) the array. If the value of the constant expression is `N`, the array has `N` elements numbered 0 to `N-1`, and the type of the identifier of `D` is “*derived-declarator-type-list array of N T*”. An object of array type contains a contiguously allocated non-empty set of `N` subobjects of type `T`. Except as noted below, if the constant expression is omitted, the type of the identifier of `D` is “*derived-declarator-type-list array of unknown bound of T*”, an incomplete object type. The type “*derived-declarator-type-list array of N T*” is a different type from the type “*derived-declarator-type-list array of unknown bound of T*”, see 6.9. Any type of the form “*cv-qualifier-seq array of N T*” is adjusted to “array of `N cv-qualifier-seq T`”, and similarly for “array of unknown bound of `T`”. The optional *attribute-specifier-seq* appertains to the array. [*Example:*

```

typedef int A[5], AA[2][3];
typedef const A CA; // type is “array of 5 const int”
typedef const AA CAA; // type is “array of 2 array of 3 const int”

```

— *end example*] [*Note:* An “array of `N cv-qualifier-seq T`” has *cv-qualified* type; see 6.9.3. — *end note*]

- 2 An array can be constructed from one of the fundamental types (except `void`), from a pointer, from a pointer to member, from a class, from an enumeration type, or from another array.
- 3 When several “array of” specifications are adjacent, a multidimensional array type is created; only the first of the constant expressions that specify the bounds of the arrays may be omitted. In addition to declarations in which an incomplete object type is allowed, an array bound may be omitted in some cases in the declaration of a function parameter (11.3.5). An array bound may also be omitted when the declarator is followed by an

*initializer* (11.6) or when a declarator for a static data member is followed by a *brace-or-equal-initializer* (12.2). In both cases the bound is calculated from the number of initial elements (say, *N*) supplied (11.6.1), and the type of the identifier of *D* is “array of *N* *T*”. Furthermore, if there is a preceding declaration of the entity in the same scope in which the bound was specified, an omitted array bound is taken to be the same as in that earlier declaration, and similarly for the definition of a static data member of a class.

<sup>4</sup> [Example:

```
float fa[17], *afp[17];
```

declares an array of `float` numbers and an array of pointers to `float` numbers. For another example,

```
static int x3d[3][5][7];
```

declares a static three-dimensional array of integers, with rank  $3 \times 5 \times 7$ . In complete detail, `x3d` is an array of three items; each item is an array of five arrays; each of the latter arrays is an array of seven integers. Any of the expressions `x3d`, `x3d[i]`, `x3d[i][j]`, `x3d[i][j][k]` can reasonably appear in an expression. Finally,

```
extern int x[10];
struct S {
 static int y[10];
};
```

```
int x[]; // OK: bound is 10
int S::y[]; // OK: bound is 10
```

```
void f() {
 extern int x[];
 int i = sizeof(x); // error: incomplete object type
}
```

— end example]

<sup>5</sup> [Note: Conversions affecting expressions of array type are described in 7.2. Objects of array types cannot be modified, see 6.10. — end note]

<sup>6</sup> [Note: Except where it has been declared for a class (16.5.5), the subscript operator `[]` is interpreted in such a way that `E1[E2]` is identical to `*((E1)+(E2))` (8.2.1). Because of the conversion rules that apply to `+`, if `E1` is an array and `E2` an integer, then `E1[E2]` refers to the `E2`-th member of `E1`. Therefore, despite its asymmetric appearance, subscripting is a commutative operation. — end note]

<sup>7</sup> [Note: A consistent rule is followed for multidimensional arrays. If `E` is an  $n$ -dimensional array of rank  $i \times j \times \dots \times k$ , then `E` appearing in an expression that is subject to the array-to-pointer conversion (7.2) is converted to a pointer to an  $(n - 1)$ -dimensional array with rank  $j \times \dots \times k$ . If the `*` operator, either explicitly or implicitly as a result of subscripting, is applied to this pointer, the result is the pointed-to  $(n - 1)$ -dimensional array, which itself is immediately converted into a pointer. [Example: Consider

```
int x[3][5];
```

Here `x` is a  $3 \times 5$  array of integers. When `x` appears in an expression, it is converted to a pointer to (the first of three) five-membered arrays of integers. In the expression `x[i]` which is equivalent to `*(x+i)`, `x` is first converted to a pointer as described; then `x+i` is converted to the type of `x`, which involves multiplying `i` by the length of the object to which the pointer points, namely five integer objects. The results are added and indirection applied to yield an array (of five integers), which in turn is converted to a pointer to the first of the integers. If there is another subscript the same argument applies again; this time the result is an integer.

— end example] — end note]

<sup>8</sup> [Note: It follows from all this that arrays in C++ are stored row-wise (last subscript varies fastest) and that the first subscript in the declaration helps determine the amount of storage consumed by an array but plays no other part in subscript calculations. — end note]



## 11.3.5 Functions

[decl.fct]

- <sup>1</sup> In a declaration *T D* where *D* has the form

*D1* ( *parameter-declaration-clause* ) *cv-qualifier-seq*<sub>opt</sub>  
*ref-qualifier*<sub>opt</sub> *noexcept-specifier*<sub>opt</sub> *attribute-specifier-seq*<sub>opt</sub>

and the type of the contained *declarator-id* in the declaration *T D1* is “*derived-declarator-type-list T*”, the type of the *declarator-id* in *D* is “*derived-declarator-type-list noexcept*<sub>opt</sub> function of (*parameter-declaration-clause*) *cv-qualifier-seq*<sub>opt</sub> *ref-qualifier*<sub>opt</sub> returning *T*”, where the optional **noexcept** is present if and only if the exception specification (18.4) is non-throwing. The optional *attribute-specifier-seq* appertains to the function type.

- <sup>2</sup> In a declaration *T D* where *D* has the form

*D1* ( *parameter-declaration-clause* ) *cv-qualifier-seq*<sub>opt</sub>  
*ref-qualifier*<sub>opt</sub> *noexcept-specifier*<sub>opt</sub> *attribute-specifier-seq*<sub>opt</sub> *trailing-return-type*

and the type of the contained *declarator-id* in the declaration *T D1* is “*derived-declarator-type-list T*”, *T* shall be the single *type-specifier* **auto**. The type of the *declarator-id* in *D* is “*derived-declarator-type-list noexcept*<sub>opt</sub> function of (*parameter-declaration-clause*) *cv-qualifier-seq*<sub>opt</sub> *ref-qualifier*<sub>opt</sub> returning *U*”, where *U* is the type specified by the *trailing-return-type*, and where the optional **noexcept** is present if and only if the exception specification is non-throwing. The optional *attribute-specifier-seq* appertains to the function type.

- <sup>3</sup> A type of either form is a *function type*.<sup>100</sup>

*parameter-declaration-clause*:  
*parameter-declaration-list*<sub>opt</sub> ...<sub>opt</sub>  
*parameter-declaration-list* , ...

*parameter-declaration-list*:  
*parameter-declaration*  
*parameter-declaration-list* , *parameter-declaration*

*parameter-declaration*:  
*attribute-specifier-seq*<sub>opt</sub> *decl-specifier-seq* *declarator*  
*attribute-specifier-seq*<sub>opt</sub> *decl-specifier-seq* *declarator* = *initializer-clause*  
*attribute-specifier-seq*<sub>opt</sub> *decl-specifier-seq* *abstract-declarator*<sub>opt</sub>  
*attribute-specifier-seq*<sub>opt</sub> *decl-specifier-seq* *abstract-declarator*<sub>opt</sub> = *initializer-clause*

The optional *attribute-specifier-seq* in a *parameter-declaration* appertains to the parameter.

- <sup>4</sup> The *parameter-declaration-clause* determines the arguments that can be specified, and their processing, when the function is called. [ *Note*: The *parameter-declaration-clause* is used to convert the arguments specified on the function call; see 8.2.2. — *end note* ] If the *parameter-declaration-clause* is empty, the function takes no arguments. A parameter list consisting of a single unnamed parameter of non-dependent type **void** is equivalent to an empty parameter list. Except for this special case, a parameter shall not have type *cv void*. If the *parameter-declaration-clause* terminates with an ellipsis or a function parameter pack (17.5.3), the number of arguments shall be equal to or greater than the number of parameters that do not have a default argument and are not function parameter packs. Where syntactically correct and where “...” is not part of an *abstract-declarator*, “ , ... ” is synonymous with “...”. [ *Example*: The declaration

```
int printf(const char*, ...);
```

declares a function that can be called with varying numbers and types of arguments.

```
printf("hello world");
printf("a=%d b=%d", a, b);
```

However, the first argument must be of a type that can be converted to a **const char\*** — *end example* ] [ *Note*: The standard header <stdarg.h> contains a mechanism for accessing arguments passed using the

100) As indicated by syntax, *cv-qualifiers* are a significant component in function return types.

ellipsis (see 8.2.2 and 21.10). — *end note*]

- 5 A single name can be used for several different functions in a single scope; this is function overloading (Clause 16). All declarations for a function shall agree exactly in both the return type and the parameter-type-list. The type of a function is determined using the following rules. The type of each parameter (including function parameter packs) is determined from its own *decl-specifier-seq* and *declarator*. After determining the type of each parameter, any parameter of type “array of T” or of function type T is adjusted to be “pointer to T”. After producing the list of parameter types, any top-level *cv-qualifiers* modifying a parameter type are deleted when forming the function type. The resulting list of transformed parameter types and the presence or absence of the ellipsis or a function parameter pack is the function’s *parameter-type-list*. [ *Note*: This transformation does not affect the types of the parameters. For example, `int(*) (const int p, decltype(p)*)` and `int(*) (int, const int*)` are identical types. — *end note*]
- 6 A function type with a *cv-qualifier-seq* or a *ref-qualifier* (including a type named by *typedef-name* (10.1.3, 17.1)) shall appear only as:
  - (6.1) — the function type for a non-static member function,
  - (6.2) — the function type to which a pointer to member refers,
  - (6.3) — the top-level function type of a function typedef declaration or *alias-declaration*,
  - (6.4) — the *type-id* in the default argument of a *type-parameter* (17.1), or
  - (6.5) — the *type-id* of a *template-argument* for a *type-parameter* (17.3.1).

[ *Example*:

```
typedef int FIC(int) const;
FIC f; // ill-formed: does not declare a member function
struct S {
 FIC f; // OK
};
FIC S::*pm = &S::f; // OK
```

— *end example*]

- 7 The effect of a *cv-qualifier-seq* in a function declarator is not the same as adding cv-qualification on top of the function type. In the latter case, the cv-qualifiers are ignored. [ *Note*: A function type that has a *cv-qualifier-seq* is not a cv-qualified type; there are no cv-qualified function types. — *end note* ] [ *Example*:

```
typedef void F();
struct S {
 const F f; // OK: equivalent to: void f();
};
```

— *end example*]

- 8 The return type, the parameter-type-list, the *ref-qualifier*, the *cv-qualifier-seq*, and the exception specification, but not the default arguments (11.3.6), are part of the function type. [ *Note*: Function types are checked during the assignments and initializations of pointers to functions, references to functions, and pointers to member functions. — *end note* ]

- 9 [ *Example*: The declaration

```
int fseek(FILE*, long, int);
```

declares a function taking three arguments of the specified types, and returning `int` (10.1.7). — *end example* ]

- 10 Functions shall not have a return type of type array or function, although they may have a return type of type pointer or reference to such things. There shall be no arrays of functions, although there can be arrays of pointers to functions.

- <sup>11</sup> Types shall not be defined in return or parameter types. The type of a parameter or the return type for a function definition shall not be an incomplete (possibly cv-qualified) class type in the context of the function definition unless the function is deleted (11.4.3).

- <sup>12</sup> A typedef of function type may be used to declare a function but shall not be used to define a function (11.4).

[*Example:*

```
typedef void F();
F fv; // OK: equivalent to void fv();
F fv { } // ill-formed
void fv() { } // OK: definition of fv
```

— *end example*]

- <sup>13</sup> An identifier can optionally be provided as a parameter name; if present in a function definition (11.4), it names a parameter. [*Note:* In particular, parameter names are also optional in function definitions and names used for a parameter in different declarations and the definition of a function need not be the same. If a parameter name is present in a function declaration that is not a definition, it cannot be used outside of its function declarator because that is the extent of its potential scope (6.3.4). — *end note*]

- <sup>14</sup> [*Example:* The declaration

```
int i,
 *pi,
 f(),
 *fpi(int),
 (*pif)(const char*, const char*),
 (*fpif(int))(int);
```

declares an integer `i`, a pointer `pi` to an integer, a function `f` taking no arguments and returning an integer, a function `fpi` taking an integer argument and returning a pointer to an integer, a pointer `pif` to a function which takes two pointers to constant characters and returns an integer, a function `fpif` taking an integer argument and returning a pointer to a function that takes an integer argument and returns an integer. It is especially useful to compare `fpi` and `pif`. The binding of `*fpi(int)` is `*(fpi(int))`, so the declaration suggests, and the same construction in an expression requires, the calling of a function `fpi`, and then using indirection through the (pointer) result to yield an integer. In the declarator `(*pif)(const char*, const char*)`, the extra parentheses are necessary to indicate that indirection through a pointer to a function yields a function, which is then called. — *end example*] [*Note:* Typedefs and *trailing-return-types* are sometimes convenient when the return type of a function is complex. For example, the function `fpif` above could have been declared

```
typedef int IFUNC(int);
IFUNC* fpif(int);
```

or

```
auto fpif(int)->int(*) (int);
```

A *trailing-return-type* is most useful for a type that would be more complicated to specify before the *declarator-id*:

```
template <class T, class U> auto add(T t, U u) -> decltype(t + u);
```

rather than

```
template <class T, class U> decltype((* (T*)0) + (* (U*)0)) add(T t, U u);
```

— *end note*]

- <sup>15</sup> A *non-template function* is a function that is not a function template specialization. [*Note:* A function template is not a function. — *end note*]

- <sup>16</sup> A *declarator-id* or *abstract-declarator* containing an ellipsis shall only be used in a *parameter-declaration*. Such a *parameter-declaration* is a parameter pack (17.5.3). When it is part of a *parameter-declaration-clause*, the parameter pack is a function parameter pack (17.5.3). [ *Note*: Otherwise, the *parameter-declaration* is part of a *template-parameter-list* and the parameter pack is a template parameter pack; see 17.1. — *end note* ] A function parameter pack is a pack expansion (17.5.3). [ *Example*:

```
template<typename... T> void f(T (* ...t)(int, int));
```

```
int add(int, int);
float subtract(int, int);
```

```
void g() {
 f(add, subtract);
}
```

— *end example*]

- <sup>17</sup> There is a syntactic ambiguity when an ellipsis occurs at the end of a *parameter-declaration-clause* without a preceding comma. In this case, the ellipsis is parsed as part of the *abstract-declarator* if the type of the parameter either names a template parameter pack that has not been expanded or contains `auto`; otherwise, it is parsed as part of the *parameter-declaration-clause*.<sup>101</sup>

### 11.3.6 Default arguments

[dcl.fct.default]

- <sup>1</sup> If an *initializer-clause* is specified in a *parameter-declaration* this *initializer-clause* is used as a default argument. Default arguments will be used in calls where trailing arguments are missing.

- <sup>2</sup> [ *Example*: The declaration

```
void point(int = 3, int = 4);
```

declares a function that can be called with zero, one, or two arguments of type `int`. It can be called in any of these ways:

```
point(1,2); point(1); point();
```

The last two calls are equivalent to `point(1,4)` and `point(3,4)`, respectively. — *end example*]

- <sup>3</sup> A default argument shall be specified only in the *parameter-declaration-clause* of a function declaration or *lambda-declarator* or in a *template-parameter* (17.1); in the latter case, the *initializer-clause* shall be an *assignment-expression*. A default argument shall not be specified for a parameter pack. If it is specified in a *parameter-declaration-clause*, it shall not occur within a *declarator* or *abstract-declarator* of a *parameter-declaration*.<sup>102</sup>

- <sup>4</sup> For non-template functions, default arguments can be added in later declarations of a function in the same scope. Declarations in different scopes have completely distinct sets of default arguments. That is, declarations in inner scopes do not acquire default arguments from declarations in outer scopes, and vice versa. In a given function declaration, each parameter subsequent to a parameter with a default argument shall have a default argument supplied in this or a previous declaration or shall be a function parameter pack. A default argument shall not be redefined by a later declaration (not even to the same value). [ *Example*:

```
void g(int = 0, ...); // OK, ellipsis is not a parameter so it can follow
 // a parameter with a default argument

void f(int, int);
void f(int, int = 7);
```

101) One can explicitly disambiguate the parse either by introducing a comma (so the ellipsis will be parsed as part of the *parameter-declaration-clause*) or by introducing a name for the parameter (so the ellipsis will be parsed as part of the *declarator-id*).

102) This means that default arguments cannot appear, for example, in declarations of pointers to functions, references to functions, or `typedef` declarations.

```

void h() {
 f(3); // OK, calls f(3, 7)
 void f(int = 1, int); // error: does not use default from surrounding scope
}
void m() {
 void f(int, int); // has no defaults
 f(4); // error: wrong number of arguments
 void f(int, int = 5); // OK
 f(4); // OK, calls f(4, 5);
 void f(int, int = 5); // error: cannot redefine, even to same value
}
void n() {
 f(6); // OK, calls f(6, 7)
}

```

— *end example*] For a given inline function defined in different translation units, the accumulated sets of default arguments at the end of the translation units shall be the same; see 6.2. If a friend declaration specifies a default argument expression, that declaration shall be a definition and shall be the only declaration of the function or function template in the translation unit.

- <sup>5</sup> The default argument has the same semantic constraints as the initializer in a declaration of a variable of the parameter type, using the copy-initialization semantics (11.6). The names in the default argument are bound, and the semantic constraints are checked, at the point where the default argument appears. Name lookup and checking of semantic constraints for default arguments in function templates and in member functions of class templates are performed as described in 17.7.1. [*Example:* In the following code, *g* will be called with the value *f*(2):

```

int a = 1;
int f(int);
int g(int x = f(a)); // default argument: f(::a)

void h() {
 a = 2;
 {
 int a = 3;
 g(); // g(f(::a))
 }
}

```

— *end example*] [*Note:* In member function declarations, names in default arguments are looked up as described in 6.4.1. Access checking applies to names in default arguments as described in Clause 14. — *end note*]

- <sup>6</sup> Except for member functions of class templates, the default arguments in a member function definition that appears outside of the class definition are added to the set of default arguments provided by the member function declaration in the class definition; the program is ill-formed if a default constructor (15.1), copy or move constructor, or copy or move assignment operator (15.8) is so declared. Default arguments for a member function of a class template shall be specified on the initial declaration of the member function within the class template. [*Example:*

```

class C {
 void f(int i = 3);
 void g(int i, int j = 99);
};

void C::f(int i = 3) {} // error: default argument already specified in class scope
void C::g(int i = 88, int j) {} // in this translation unit, C::g can be called with no argument

```

— *end example*]

- 7 A local variable shall not appear as a potentially-evaluated expression in a default argument. [ *Example:*

```
void f() {
 int i;
 extern void g(int x = i); // error
 extern void h(int x = sizeof(i)); // OK
 // ...
}
```

— *end example*]

- 8 [ *Note:* The keyword `this` may not appear in a default argument of a member function; see 8.1.2. [ *Example:*

```
class A {
 void f(A* p = this) { } // error
};
```

— *end example*] — *end note*]

- 9 A default argument is evaluated each time the function is called with no argument for the corresponding parameter. A parameter shall not appear as a potentially-evaluated expression in a default argument. Parameters of a function declared before a default argument are in scope and can hide namespace and class member names. [ *Example:*

```
int a;
int f(int a, int b = a); // error: parameter a used as default argument
typedef int I;
int g(float I, int b = I(2)); // error: parameter I found
int h(int a, int b = sizeof(a)); // OK, unevaluated operand
```

— *end example*] A non-static member shall not appear in a default argument unless it appears as the *id-expression* of a class member access expression (8.2.5) or unless it is used to form a pointer to member (8.3.1). [ *Example:* The declaration of `X::mem1()` in the following example is ill-formed because no object is supplied for the non-static member `X::a` used as an initializer.

```
int b;
class X {
 int a;
 int mem1(int i = a); // error: non-static member a used as default argument
 int mem2(int i = b); // OK; use X::b
 static int b;
};
```

The declaration of `X::mem2()` is meaningful, however, since no object is needed to access the static member `X::b`. Classes, objects, and members are described in Clause 12. — *end example*] A default argument is not part of the type of a function. [ *Example:*

```
int f(int = 0);

void h() {
 int j = f(1);
 int k = f(); // OK, means f(0)
}

int (*p1)(int) = &f;
int (*p2)() = &f; // error: type mismatch
```

— *end example*] When a declaration of a function is introduced by way of a *using-declaration* (10.3.3), any default argument information associated with the declaration is made known as well. If the function is

redeclared thereafter in the namespace with additional default arguments, the additional arguments are also known at any point following the redeclaration where the *using-declaration* is in scope.

- <sup>10</sup> A virtual function call (13.3) uses the default arguments in the declaration of the virtual function determined by the static type of the pointer or reference denoting the object. An overriding function in a derived class does not acquire default arguments from the function it overrides. [ *Example:*

```
struct A {
 virtual void f(int a = 7);
};
struct B : public A {
 void f(int a);
};
void m() {
 B* pb = new B;
 A* pa = pb;
 pa->f(); // OK, calls pa->B::f(7)
 pb->f(); // error: wrong number of arguments for B::f()
}
```

— end example]

## 11.4 Function definitions

[dcl.fct.def]

### 11.4.1 In general

[dcl.fct.def.general]

- <sup>1</sup> Function definitions have the form

*function-definition:*  
*attribute-specifier-seq<sub>opt</sub> decl-specifier-seq<sub>opt</sub> declarator virt-specifier-seq<sub>opt</sub> function-body*

*function-body:*  
*ctor-initializer<sub>opt</sub> compound-statement*  
*function-try-block*  
 = **default** ;  
 = **delete** ;

Any informal reference to the body of a function should be interpreted as a reference to the non-terminal *function-body*. The optional *attribute-specifier-seq* in a *function-definition* appertains to the function. A *virt-specifier-seq* can be part of a *function-definition* only if it is a *member-declaration* (12.2).

- <sup>2</sup> In a *function-definition*, either **void declarator ;** or *declarator ;* shall be a well-formed function declaration as described in 11.3.5. A function shall be defined only in namespace or class scope.
- <sup>3</sup> [ *Example:* A simple example of a complete function definition is

```
int max(int a, int b, int c) {
 int m = (a > b) ? a : b;
 return (m > c) ? m : c;
}
```

Here **int** is the *decl-specifier-seq*; **max(int a, int b, int c)** is the *declarator*; **{ /\* ... \*/ }** is the *function-body*. — end example]

- <sup>4</sup> A *ctor-initializer* is used only in a constructor; see 15.1 and 15.6.
- <sup>5</sup> [ *Note:* A *cv-qualifier-seq* affects the type of **this** in the body of a member function; see 11.3.2. — end note ]
- <sup>6</sup> [ *Note:* Unused parameters need not be named. For example,

```
void print(int a, int) {
 std::printf("a = %d\n", a);
}
```

— *end note*]

<sup>7</sup> In the *function-body*, a *function-local predefined variable* denotes a block-scope object of static storage duration that is implicitly defined (see 6.3.3).

<sup>8</sup> The function-local predefined variable `__func__` is defined as if a definition of the form

```
static const char __func__[] = "function-name";
```

had been provided, where *function-name* is an implementation-defined string. It is unspecified whether such a variable has an address distinct from that of any other object in the program.<sup>103</sup> [*Example:*

```
struct S {
 S() : s(__func__) { } // OK
 const char* s;
};
void f(const char* s = __func__); // error: __func__ is undeclared
```

— *end example*]

### 11.4.2 Explicitly-defaulted functions

[**dcl.fct.def.default**]

<sup>1</sup> A function definition of the form:

```
attribute-specifier-seqopt decl-specifier-seqopt declarator virt-specifier-seqopt = default ;
```

is called an *explicitly-defaulted* definition. A function that is explicitly defaulted shall

- (1.1) — be a special member function,
- (1.2) — have the same declared function type (except for possibly differing *ref-qualifiers* and except that in the case of a copy constructor or copy assignment operator, the parameter type may be “reference to non-const T”, where T is the name of the member function’s class) as if it had been implicitly declared, and
- (1.3) — not have default arguments.

<sup>2</sup> An explicitly-defaulted function that is not defined as deleted may be declared **constexpr** only if it would have been implicitly declared as **constexpr**. If a function is explicitly defaulted on its first declaration, it is implicitly considered to be **constexpr** if the implicit declaration would be.

<sup>3</sup> If a function that is explicitly defaulted is declared with a *noexcept-specifier* that does not produce the same exception specification as the implicit declaration (18.4), then

- (3.1) — if the function is explicitly defaulted on its first declaration, it is defined as deleted;
- (3.2) — otherwise, the program is ill-formed.

<sup>4</sup> [*Example:*

```
struct S {
 constexpr S() = default; // ill-formed: implicit S() is not constexpr
 S(int a = 0) = default; // ill-formed: default argument
 void operator=(const S&) = default; // ill-formed: non-matching return type
 ~S() noexcept(false) = default; // deleted: exception specification does not match
private:
 int i;
 S(S&); // OK: private copy constructor
};
S::S(S&) = default; // OK: defines copy constructor
```

— *end example*]

<sup>103</sup> Implementations are permitted to provide additional predefined variables with names that are reserved to the implementation (5.10). If a predefined variable is not odr-used (6.2), its string value need not be present in the program image.



- <sup>5</sup> Explicitly-defaulted functions and implicitly-declared functions are collectively called *defaulted* functions, and the implementation shall provide implicit definitions for them (15.1 15.4, 15.8), which might mean defining them as deleted. A function is *user-provided* if it is user-declared and not explicitly defaulted or deleted on its first declaration. A user-provided explicitly-defaulted function (i.e., explicitly defaulted after its first declaration) is defined at the point where it is explicitly defaulted; if such a function is implicitly defined as deleted, the program is ill-formed. [ *Note:* Declaring a function as defaulted after its first declaration can provide efficient execution and concise definition while enabling a stable binary interface to an evolving code base. — *end note* ]

- <sup>6</sup> [ *Example:*

```
struct trivial {
 trivial() = default;
 trivial(const trivial&) = default;
 trivial(trivial&&) = default;
 trivial& operator=(const trivial&) = default;
 trivial& operator=(trivial&&) = default;
 ~trivial() = default;
};

struct nontrivial1 {
 nontrivial1();
};
nontrivial1::nontrivial1() = default; // not first declaration
```

— *end example* ]

### 11.4.3 Deleted definitions

[dcl.fct.def.delete]

- <sup>1</sup> A function definition of the form:

*attribute-specifier-seq<sub>opt</sub>* *decl-specifier-seq<sub>opt</sub>* *declarator* *virt-specifier-seq<sub>opt</sub>* = delete ;

is called a *deleted definition*. A function with a deleted definition is also called a *deleted function*.

- <sup>2</sup> A program that refers to a deleted function implicitly or explicitly, other than to declare it, is ill-formed. [ *Note:* This includes calling the function implicitly or explicitly and forming a pointer or pointer-to-member to the function. It applies even for references in expressions that are not potentially-evaluated. If a function is overloaded, it is referenced only if the function is selected by overload resolution. The implicit odr-use (6.2) of a virtual function does not, by itself, constitute a reference. — *end note* ]

- <sup>3</sup> [ *Example:* One can enforce non-default-initialization and non-integral initialization with

```
struct onlydouble {
 onlydouble() = delete; // OK, but redundant
 onlydouble(std::intmax_t) = delete;
 onlydouble(double);
};
```

— *end example* ]

[ *Example:* One can prevent use of a class in certain *new-expressions* by using deleted definitions of a user-declared operator *new* for that class.

```
struct sometype {
 void* operator new(std::size_t) = delete;
 void* operator new[] (std::size_t) = delete;
};
sometype* p = new sometype; // error, deleted class operator new
sometype* q = new sometype[3]; // error, deleted class operator new[]
```

— *end example*]

[*Example*: One can make a class uncopyable, i.e. move-only, by using deleted definitions of the copy constructor and copy assignment operator, and then providing defaulted definitions of the move constructor and move assignment operator.

```
struct moveonly {
 moveonly() = default;
 moveonly(const moveonly&) = delete;
 moveonly(moveonly&&) = default;
 moveonly& operator=(const moveonly&) = delete;
 moveonly& operator=(moveonly&&) = default;
 ~moveonly() = default;
};
moveonly* p;
moveonly q(*p); // error, deleted copy constructor
```

— *end example*]

- <sup>4</sup> A deleted function is implicitly an inline function (10.1.6). [ *Note*: The one-definition rule (6.2) applies to deleted definitions. — *end note* ] A deleted definition of a function shall be the first declaration of the function or, for an explicit specialization of a function template, the first declaration of that specialization. An implicitly declared allocation or deallocation function (6.7.4) shall not be defined as deleted. [ *Example*:

```
struct sometype {
 sometype();
};
sometype::sometype() = delete; // ill-formed; not first declaration
```

— *end example*]

## 11.5 Structured binding declarations

[**dcl.struct.bind**]

- <sup>1</sup> A structured binding declaration introduces the *identifiers*  $v_0, v_1, v_2, \dots$  of the *identifier-list* as names (6.3.1), called *structured bindings*. Let *cv* denote the *cv-qualifiers* in the *decl-specifier-seq*. First, a variable with a unique name *e* is introduced. If the *assignment-expression* in the *initializer* has array type *A* and no *ref-qualifier* is present, *e* has type *cv A* and each element is copy-initialized or direct-initialized from the corresponding element of the *assignment-expression* as specified by the form of the *initializer*. Otherwise, *e* is defined as-if by

*attribute-specifier-seq<sub>opt</sub> decl-specifier-seq ref-qualifier<sub>opt</sub> e initializer ;*

where the declaration is never interpreted as a function declaration and the parts of the declaration other than the *declarator-id* are taken from the corresponding structured binding declaration. The type of the *id-expression* *e* is called *E*. [ *Note*: *E* is never a reference type (Clause 8). — *end note* ]

- <sup>2</sup> If *E* is an array type with element type *T*, the number of elements in the *identifier-list* shall be equal to the number of elements of *E*. Each  $v_i$  is the name of an lvalue that refers to the element *i* of the array and whose type is *T*; the referenced type is *T*. [ *Note*: The top-level *cv-qualifiers* of *T* are *cv*. — *end note* ] [ *Example*:

```
auto f() -> int(&)[2];
auto [x, y] = f(); // x and y refer to elements in a copy of the array return value
auto& [xr, yr] = f(); // xr and yr refer to elements in the array referred to by f's return value
```

— *end example*]

- <sup>3</sup> Otherwise, if the *qualified-id* `std::tuple_size<E>` names a complete type, the expression `std::tuple_size<E>::value` shall be a well-formed integral constant expression and the number of elements in the *identifier-list* shall be equal to the value of that expression. The *unqualified-id* `get` is looked up in the scope of *E* by class member access lookup (6.4.5), and if that finds at least one declaration, the initializer is `e.get<i>()`.

Otherwise, the initializer is `get<i>(e)`, where `get` is looked up in the associated namespaces (6.4.2). In either case, `get<i>` is interpreted as a *template-id*. [ *Note*: Ordinary unqualified lookup (6.4.1) is not performed. — *end note* ] In either case, `e` is an lvalue if the type of the entity `e` is an lvalue reference and an xvalue otherwise. Given the type  $T_i$  designated by `std::tuple_element<i, E>::type`, each  $v_i$  is a variable of type “reference to  $T_i$ ” initialized with the initializer, where the reference is an lvalue reference if the initializer is an lvalue and an rvalue reference otherwise; the referenced type is  $T_i$ .

- <sup>4</sup> Otherwise, all of `E`’s non-static data members shall be public direct members of `E` or of the same unambiguous public base class of `E`, `E` shall not have an anonymous union member, and the number of elements in the *identifier-list* shall be equal to the number of non-static data members of `E`. Designating the non-static data members of `E` as  $m_0, m_1, m_2, \dots$  (in declaration order), each  $v_i$  is the name of an lvalue that refers to the member  $m_i$  of `e` and whose type is *cv*  $T_i$ , where  $T_i$  is the declared type of that member; the referenced type is *cv*  $T_i$ . The lvalue is a bit-field if that member is a bit-field. [ *Example*:

```
struct S { int x1 : 2; volatile double y1; };
S f();
const auto [x, y] = f();
```

The type of the *id-expression* `x` is “`const int`”, the type of the *id-expression* `y` is “`const volatile double`”. — *end example*]

## 11.6 Initializers

[**dcl.init**]

- <sup>1</sup> A declarator can specify an initial value for the identifier being declared. The identifier designates a variable being initialized. The process of initialization described in the remainder of 11.6 applies also to initializations specified by other syntactic contexts, such as the initialization of function parameters (8.2.2) or the initialization of return values (9.6.3).

*initializer*:

*brace-or-equal-initializer*  
( *expression-list* )

*brace-or-equal-initializer*:  
= *initializer-clause*  
*braced-init-list*

*initializer-clause*:  
*assignment-expression*  
*braced-init-list*

*initializer-list*:  
*initializer-clause* ... *opt*  
*initializer-list* , *initializer-clause* ... *opt*

*braced-init-list*:  
{ *initializer-list* , *opt* }  
{ }

*expr-or-braced-init-list*:  
*expression*  
*braced-init-list*

- <sup>2</sup> Except for objects declared with the `constexpr` specifier, for which see 10.1.5, an *initializer* in the definition of a variable can consist of arbitrary expressions involving literals and previously declared variables and functions, regardless of the variable’s storage duration. [ *Example*:

```
int f(int);
int a = 2;
int b = f(a);
int c(b);
```

— *end example*]

3 [ *Note*: Default arguments are more restricted; see 11.3.6. — *end note* ]

4 [ *Note*: The order of initialization of variables with static storage duration is described in 6.6 and 9.7. — *end note* ]

5 A declaration of a block-scope variable with external or internal linkage that has an *initializer* is ill-formed.

6 To *zero-initialize* an object or reference of type T means:

- (6.1) — if T is a scalar type (6.9), the object is initialized to the value obtained by converting the integer literal 0 (zero) to T;<sup>104</sup>
- (6.2) — if T is a (possibly cv-qualified) non-union class type, each non-static data member, each non-virtual base class subobject, and, if the object is not a base class subobject, each virtual base class subobject is zero-initialized and padding is initialized to zero bits;
- (6.3) — if T is a (possibly cv-qualified) union type, the object's first non-static named data member is zero-initialized and padding is initialized to zero bits;
- (6.4) — if T is an array type, each element is zero-initialized;
- (6.5) — if T is a reference type, no initialization is performed.

7 To *default-initialize* an object of type T means:

- (7.1) — If T is a (possibly cv-qualified) class type (Clause 12), constructors are considered. The applicable constructors are enumerated (16.3.1.3), and the best one for the *initializer* () is chosen through overload resolution (16.3). The constructor thus selected is called, with an empty argument list, to initialize the object.
- (7.2) — If T is an array type, each element is default-initialized.
- (7.3) — Otherwise, no initialization is performed.

A class type T is *const-default-constructible* if default-initialization of T would invoke a user-provided constructor of T (not inherited from a base class) or if

- (7.4) — each direct non-variant non-static data member M of T has a default member initializer or, if M is of class type X (or array thereof), X is const-default-constructible,
- (7.5) — if T is a union with at least one non-static data member, exactly one variant member has a default member initializer,
- (7.6) — if T is not a union, for each anonymous union member with at least one non-static data member (if any), exactly one non-static data member has a default member initializer, and
- (7.7) — each potentially constructed base class of T is const-default-constructible.

If a program calls for the default-initialization of an object of a const-qualified type T, T shall be a const-default-constructible class type or array thereof.

8 To *value-initialize* an object of type T means:

- (8.1) — if T is a (possibly cv-qualified) class type (Clause 12) with either no default constructor (15.1) or a default constructor that is user-provided or deleted, then the object is default-initialized;
- (8.2) — if T is a (possibly cv-qualified) class type without a user-provided or deleted default constructor, then the object is zero-initialized and the semantic constraints for default-initialization are checked, and if T has a non-trivial default constructor, the object is default-initialized;
- (8.3) — if T is an array type, then each element is value-initialized;

<sup>104</sup> As specified in 7.11, converting an integer literal whose value is 0 to a pointer type results in a null pointer value.

(8.4) — otherwise, the object is zero-initialized.

9 A program that calls for default-initialization or value-initialization of an entity of reference type is ill-formed.

10 [ *Note*: Every object of static storage duration is zero-initialized at program startup before any other initialization takes place. In some cases, additional initialization is done later. — *end note* ]

11 An object whose initializer is an empty set of parentheses, i.e., `()`, shall be value-initialized.

[ *Note*: Since `()` is not permitted by the syntax for *initializer*,

```
X a();
```

is not the declaration of an object of class `X`, but the declaration of a function taking no argument and returning an `X`. The form `()` is permitted in certain other initialization contexts (8.3.4, 8.2.3, 15.6.2). — *end note* ]

12 If no initializer is specified for an object, the object is default-initialized. When storage for an object with automatic or dynamic storage duration is obtained, the object has an *indeterminate value*, and if no initialization is performed for the object, that object retains an indeterminate value until that value is replaced (8.18). [ *Note*: Objects with static or thread storage duration are zero-initialized, see 6.6.2. — *end note* ] If an indeterminate value is produced by an evaluation, the behavior is undefined except in the following cases:

(12.1) — If an indeterminate value of unsigned narrow character type (6.9.1) or `std::byte` type (21.2.1) is produced by the evaluation of:

(12.1.1) — the second or third operand of a conditional expression (8.16),

(12.1.2) — the right operand of a comma expression (8.19),

(12.1.3) — the operand of a cast or conversion (7.8, 8.2.3, 8.2.9, 8.4) to an unsigned narrow character type or `std::byte` type (21.2.1), or

(12.1.4) — a discarded-value expression (Clause 8),

then the result of the operation is an indeterminate value.

(12.2) — If an indeterminate value of unsigned narrow character type or `std::byte` type is produced by the evaluation of the right operand of a simple assignment operator (8.18) whose first operand is an lvalue of unsigned narrow character type or `std::byte` type, an indeterminate value replaces the value of the object referred to by the left operand.

(12.3) — If an indeterminate value of unsigned narrow character type is produced by the evaluation of the initialization expression when initializing an object of unsigned narrow character type, that object is initialized to an indeterminate value.

(12.4) — If an indeterminate value of unsigned narrow character type or `std::byte` type is produced by the evaluation of the initialization expression when initializing an object of `std::byte` type, that object is initialized to an indeterminate value.

[ *Example*:

```
int f(bool b) {
 unsigned char c;
 unsigned char d = c; // OK, d has an indeterminate value
 int e = d; // undefined behavior
 return b ? d : 0; // undefined behavior if b is true
}
```

— *end example* ]

13 An initializer for a static member is in the scope of the member's class. [ *Example*:

```
int a;
```

```

struct X {
 static int a;
 static int b;
};

int X::a = 1;
int X::b = a; // X::b = X::a
— end example]

```

- 14 If the entity being initialized does not have class type, the *expression-list* in a parenthesized initializer shall be a single expression.
- 15 The initialization that occurs in the = form of a *brace-or-equal-initializer* or *condition* (9.4), as well as in argument passing, function return, throwing an exception (18.1), handling an exception (18.3), and aggregate member initialization (11.6.1), is called *copy-initialization*. [Note: Copy-initialization may invoke a move (15.8). — end note]
- 16 The initialization that occurs in the forms

```

T x(a);
T x{a};

```

as well as in *new* expressions (8.3.4), *static\_cast* expressions (8.2.9), functional notation type conversions (8.2.3), *mem-initializers* (15.6.2), and the *braced-init-list* form of a *condition* is called *direct-initialization*.

- 17 The semantics of initializers are as follows. The *destination type* is the type of the object or reference being initialized and the *source type* is the type of the initializer expression. If the initializer is not a single (possibly parenthesized) expression, the source type is not defined.
- (17.1) — If the initializer is a (non-parenthesized) *braced-init-list* or is = *braced-init-list*, the object or reference is list-initialized (11.6.4).
  - (17.2) — If the destination type is a reference type, see 11.6.3.
  - (17.3) — If the destination type is an array of characters, an array of `char16_t`, an array of `char32_t`, or an array of `wchar_t`, and the initializer is a string literal, see 11.6.2.
  - (17.4) — If the initializer is (), the object is value-initialized.
  - (17.5) — Otherwise, if the destination type is an array, the program is ill-formed.
  - (17.6) — If the destination type is a (possibly cv-qualified) class type:
    - (17.6.1) — If the initializer expression is a prvalue and the cv-unqualified version of the source type is the same class as the class of the destination, the initializer expression is used to initialize the destination object. [Example: `T x = T(T());` calls the `T` default constructor to initialize `x`. — end example]
    - (17.6.2) — Otherwise, if the initialization is direct-initialization, or if it is copy-initialization where the cv-unqualified version of the source type is the same class as, or a derived class of, the class of the destination, constructors are considered. The applicable constructors are enumerated (16.3.1.3), and the best one is chosen through overload resolution (16.3). The constructor so selected is called to initialize the object, with the initializer expression or *expression-list* as its argument(s). If no constructor applies, or the overload resolution is ambiguous, the initialization is ill-formed.
    - (17.6.3) — Otherwise (i.e., for the remaining copy-initialization cases), user-defined conversion sequences that can convert from the source type to the destination type or (when a conversion function is used) to a derived class thereof are enumerated as described in 16.3.1.4, and the best one is chosen through overload resolution (16.3). If the conversion cannot be done or is ambiguous, the initialization is ill-formed. The function selected is called with the initializer expression as its argument; if the

function is a constructor, the call is a prvalue of the cv-unqualified version of the destination type whose result object is initialized by the constructor. The call is used to direct-initialize, according to the rules above, the object that is the destination of the copy-initialization.

- (17.7) — Otherwise, if the source type is a (possibly cv-qualified) class type, conversion functions are considered. The applicable conversion functions are enumerated (16.3.1.5), and the best one is chosen through overload resolution (16.3). The user-defined conversion so selected is called to convert the initializer expression into the object being initialized. If the conversion cannot be done or is ambiguous, the initialization is ill-formed.
- (17.8) — Otherwise, the initial value of the object being initialized is the (possibly converted) value of the initializer expression. Standard conversions (Clause 7) will be used, if necessary, to convert the initializer expression to the cv-unqualified version of the destination type; no user-defined conversions are considered. If the conversion cannot be done, the initialization is ill-formed. When initializing a bit-field with a value that it cannot represent, the resulting value of the bit-field is implementation-defined. [Note: An expression of type “*cv1* T” can initialize an object of type “*cv2* T” independently of the cv-qualifiers *cv1* and *cv2*.

```
int a;
const int b = a;
int c = b;
```

— end note]

- 18 An *initializer-clause* followed by an ellipsis is a pack expansion (17.5.3).
- 19 If the initializer is a parenthesized *expression-list*, the expressions are evaluated in the order specified for function calls (8.2.2).
- 20 An object whose initialization has completed is deemed to be constructed, even if no constructor of the object’s class is invoked for the initialization. [Note: Such an object might have been value-initialized or initialized by aggregate initialization (11.6.1) or by an inherited constructor (15.6.3). — end note]
- 21 A declaration that specifies the initialization of a variable, whether from an explicit initializer or by default-initialization, is called the *initializing declaration* of that variable. [Note: In most cases this is the defining declaration (6.1) of the variable, but the initializing declaration of a non-inline static data member (12.2.3.2) might be the declaration within the class definition and not the definition at namespace scope. — end note]

### 11.6.1 Aggregates

[dcl.init.aggr]

1 An *aggregate* is an array or a class (Clause 12) with

- (1.1) — no user-provided, **explicit**, or inherited constructors (15.1),
- (1.2) — no private or protected non-static data members (Clause 14),
- (1.3) — no virtual functions (13.3), and
- (1.4) — no virtual, private, or protected base classes (13.1).

[Note: Aggregate initialization does not allow accessing protected and private base class’ members or constructors. — end note]

2 The *elements* of an aggregate are:

- (2.1) — for an array, the array elements in increasing subscript order, or
- (2.2) — for a class, the direct base classes in declaration order, followed by the direct non-static data members (12.2) that are not members of an anonymous union, in declaration order.

3 When an aggregate is initialized by an initializer list as specified in 11.6.4, the elements of the initializer list are taken as initializers for the elements of the aggregate, in order. Each element is copy-initialized from the corresponding *initializer-clause*. If the *initializer-clause* is an expression and a narrowing conversion (11.6.4)

is required to convert the expression, the program is ill-formed. [ *Note:* If an *initializer-clause* is itself an initializer list, the element is list-initialized, which will result in a recursive application of the rules in this section if the element is an aggregate. — *end note* ] [ *Example:*

```
struct A {
 int x;
 struct B {
 int i;
 int j;
 } b;
} a = { 1, { 2, 3 } };
```

initializes `a.x` with 1, `a.b.i` with 2, `a.b.j` with 3.

```
struct base1 { int b1, b2 = 42; };
struct base2 {
 base2() {
 b3 = 42;
 }
 int b3;
};
struct derived : base1, base2 {
 int d;
};

derived d1{{1, 2}, {}, 4};
derived d2{{}, {}, 4};
```

initializes `d1.b1` with 1, `d1.b2` with 2, `d1.b3` with 42, `d1.d` with 4, and `d2.b1` with 0, `d2.b2` with 42, `d2.b3` with 42, `d2.d` with 4. — *end example*]

- <sup>4</sup> An aggregate that is a class can also be initialized with a single expression not enclosed in braces, as described in 11.6.
- <sup>5</sup> An array of unknown bound initialized with a brace-enclosed *initializer-list* containing *n* *initializer-clauses*, where *n* shall be greater than zero, is defined as having *n* elements (11.3.4). [ *Example:*

```
int x[] = { 1, 3, 5 };
```

declares and initializes `x` as a one-dimensional array that has three elements since no size was specified and there are three initializers. — *end example*] An empty initializer list `{}` shall not be used as the *initializer-clause* for an array of unknown bound.<sup>105</sup> [ *Note:* A default member initializer does not determine the bound for a member array of unknown bound. Since the default member initializer is ignored if a suitable *mem-initializer* is present (15.6.2), the default member initializer is not considered to initialize the array of unknown bound. [ *Example:*

```
struct S {
 int y[] = { 0 }; // error: non-static data member of incomplete type
};
```

— *end example*] — *end note*]

- <sup>6</sup> [ *Note:* Static data members and unnamed bit-fields are not considered elements of the aggregate. [ *Example:*

```
struct A {
 int i;
 static int s;
 int j;
 int :17;
```

<sup>105</sup>) The syntax provides for empty *initializer-lists*, but nonetheless C++ does not have zero length arrays.



```
 int k;
} a = { 1, 2, 3 };
```

Here, the second initializer 2 initializes `a.j` and not the static data member `A::s`, and the third initializer 3 initializes `a.k` and not the unnamed bit-field before it. — *end example*] — *end note*

- 7 An *initializer-list* is ill-formed if the number of *initializer-clauses* exceeds the number of elements to initialize. [ *Example*:

```
char cv[4] = { 'a', 's', 'd', 'f', 0 }; // error
```

is ill-formed. — *end example*]

- 8 If there are fewer *initializer-clauses* in the list than there are elements in a non-union aggregate, then each element not explicitly initialized is initialized as follows:

- (8.1) — If the element has a default member initializer (12.2), the element is initialized from that initializer.
- (8.2) — Otherwise, if the element is not a reference, the element is copy-initialized from an empty initializer list (11.6.4).
- (8.3) — Otherwise, the program is ill-formed.

If the aggregate is a union and the initializer list is empty, then

- (8.4) — if any variant member has a default member initializer, that member is initialized from its default member initializer;
- (8.5) — otherwise, the first member of the union (if any) is copy-initialized from an empty initializer list.

[ *Example*:

```
struct S { int a; const char* b; int c; int d = b[a]; };
S ss = { 1, "asdf" };
```

initializes `ss.a` with 1, `ss.b` with "asdf", `ss.c` with the value of an expression of the form `int{}` (that is, 0), and `ss.d` with the value of `ss.b[ss.a]` (that is, 's'), and in

```
struct X { int i, j, k = 42; };
X a[] = { 1, 2, 3, 4, 5, 6 };
X b[2] = { { 1, 2, 3 }, { 4, 5, 6 } };
```

`a` and `b` have the same value — *end example*]

- 9 If a reference member is initialized from its default member initializer and a potentially-evaluated subexpression thereof is an aggregate initialization that would use that default member initializer, the program is ill-formed. [ *Example*:

```
struct A;
extern A a;
struct A {
 const A& a1 { A{a,a} }; // OK
 const A& a2 { A{} }; // error
};
A a{a,a}; // OK
```

— *end example*]

- 10 If an aggregate class `C` contains a subaggregate element `e` with no elements, the *initializer-clause* for `e` shall not be omitted from an *initializer-list* for an object of type `C` unless the *initializer-clauses* for all elements of `C` following `e` are also omitted. [ *Example*:

```
struct S { } s;
struct A {
 S s1;
```

```

 int i1;
 S s2;
 int i2;
 S s3;
 int i3;
} a = {
 { }, // Required initialization
 0,
 s, // Required initialization
 0
}; // Initialization not required for A::s3 because A::i3 is also not initialized
— end example]
```

- <sup>11</sup> When initializing a multi-dimensional array, the *initializer-clauses* initialize the elements with the last (rightmost) index of the array varying the fastest (11.3.4). [ *Example:*

```

 int x[2][2] = { 3, 1, 4, 2 };
initializes x[0][0] to 3, x[0][1] to 1, x[1][0] to 4, and x[1][1] to 2. On the other hand,

 float y[4][3] = {
 { 1 }, { 2 }, { 3 }, { 4 }
 };
initializes the first column of y (regarded as a two-dimensional array) and leaves the rest zero. — end
example]
```

- <sup>12</sup> Braces can be elided in an *initializer-list* as follows. If the *initializer-list* begins with a left brace, then the succeeding comma-separated list of *initializer-clauses* initializes the elements of a subaggregate; it is erroneous for there to be more *initializer-clauses* than elements. If, however, the *initializer-list* for a subaggregate does not begin with a left brace, then only enough *initializer-clauses* from the list are taken to initialize the elements of the subaggregate; any remaining *initializer-clauses* are left to initialize the next element of the aggregate of which the current subaggregate is an element. [ *Example:*

```

 float y[4][3] = {
 { 1, 3, 5 },
 { 2, 4, 6 },
 { 3, 5, 7 },
 };

```

is a completely-braced initialization: 1, 3, and 5 initialize the first row of the array y[0], namely y[0][0], y[0][1], and y[0][2]. Likewise the next two lines initialize y[1] and y[2]. The initializer ends early and therefore y[3]'s elements are initialized as if explicitly initialized with an expression of the form `float()`, that is, are initialized with 0.0. In the following example, braces in the *initializer-list* are elided; however the *initializer-list* has the same effect as the completely-braced *initializer-list* of the above example,

```

 float y[4][3] = {
 1, 3, 5, 2, 4, 6, 3, 5, 7
 };

```

The initializer for y begins with a left brace, but the one for y[0] does not, therefore three elements from the list are used. Likewise the next three are taken successively for y[1] and y[2]. — end example]

- <sup>13</sup> All implicit type conversions (Clause 7) are considered when initializing the element with an *assignment-expression*. If the *assignment-expression* can initialize an element, the element is initialized. Otherwise, if the element is itself a subaggregate, brace elision is assumed and the *assignment-expression* is considered for the initialization of the first element of the subaggregate. [ *Note:* As specified above, brace elision cannot apply to subaggregates with no elements; an *initializer-clause* for the entire subobject is required. — end note]

[ *Example:*

```

struct A {
 int i;
 operator int();
};
struct B {
 A a1, a2;
 int z;
};
A a;
B b = { 4, a, a };

```

Braces are elided around the *initializer-clause* for `b.a1.i`. `b.a1.i` is initialized with 4, `b.a2` is initialized with `a`, `b.z` is initialized with whatever `a.operator int()` returns. — *end example*]

- 14 [ *Note*: An aggregate array or an aggregate class may contain elements of a class type with a user-provided constructor (15.1). Initialization of these aggregate objects is described in 15.6.1. — *end note*]
- 15 [ *Note*: Whether the initialization of aggregates with static storage duration is static or dynamic is specified in 6.6.2, 6.6.3, and 9.7. — *end note*]
- 16 When a union is initialized with a brace-enclosed initializer, the braces shall only contain an *initializer-clause* for the first non-static data member of the union. [ *Example*:

```

union u { int a; const char* b; };
u a = { 1 };
u b = a;
u c = 1; // error
u d = { 0, "asdf" }; // error
u e = { "asdf" }; // error

```

— *end example*]

- 17 [ *Note*: As described above, the braces around the *initializer-clause* for a union member can be omitted if the union is a member of another aggregate. — *end note*]

### 11.6.2 Character arrays

[dcl.init.string]

- 1 An array of narrow character type (6.9.1), `char16_t` array, `char32_t` array, or `wchar_t` array can be initialized by a narrow string literal, `char16_t` string literal, `char32_t` string literal, or wide string literal, respectively, or by an appropriately-typed string literal enclosed in braces (5.13.5). Successive characters of the value of the string literal initialize the elements of the array. [ *Example*:

```
char msg[] = "Syntax error on line %s\n";
```

shows a character array whose members are initialized with a *string-literal*. Note that because `'\n'` is a single character and because a trailing `'\0'` is appended, `sizeof(msg)` is 25. — *end example*]

- 2 There shall not be more initializers than there are array elements. [ *Example*:

```
char cv[4] = "asdf"; // error
```

is ill-formed since there is no space for the implied trailing `'\0'`. — *end example*]

- 3 If there are fewer initializers than there are array elements, each element not explicitly initialized shall be zero-initialized (11.6).

### 11.6.3 References

[dcl.init.ref]

- 1 A variable whose declared type is “reference to type T” (11.3.2) shall be initialized. [ *Example*:

```

int g(int) noexcept;
void f() {
 int i;

```

```

int& r = i; // r refers to i
r = 1; // the value of i becomes 1
int* p = &r; // p points to i
int& rr = r; // rr refers to what r refers to, that is, to i
int (&rg)(int) = g; // rg refers to the function g
rg(i); // calls function g
int a[3];
int (&ra)[3] = a; // ra refers to the array a
ra[1] = i; // modifies a[1]
}

```

— end example]

- <sup>2</sup> A reference cannot be changed to refer to another object after initialization. [ *Note:* Assignment to a reference assigns to the object referred to by the reference (8.18). — end note ] Argument passing (8.2.2) and function value return (9.6.3) are initializations.
- <sup>3</sup> The initializer can be omitted for a reference only in a parameter declaration (11.3.5), in the declaration of a function return type, in the declaration of a class member within its class definition (12.2), and where the **extern** specifier is explicitly used. [ *Example:*

```

int& r1; // error: initializer missing
extern int& r2; // OK

```

— end example]

- <sup>4</sup> Given types “*cv1* T1” and “*cv2* T2”, “*cv1* T1” is *reference-related* to “*cv2* T2” if T1 is the same type as T2, or T1 is a base class of T2. “*cv1* T1” is *reference-compatible* with “*cv2* T2” if

(4.1) — T1 is reference-related to T2, or

(4.2) — T2 is “**noexcept** function” and T1 is “function”, where the function types are otherwise the same,

and *cv1* is the same cv-qualification as, or greater cv-qualification than, *cv2*. In all cases where the reference-related or reference-compatible relationship of two types is used to establish the validity of a reference binding, and T1 is a base class of T2, a program that necessitates such a binding is ill-formed if T1 is an inaccessible (Clause 14) or ambiguous (13.2) base class of T2.

- <sup>5</sup> A reference to type “*cv1* T1” is initialized by an expression of type “*cv2* T2” as follows:

(5.1) — If the reference is an lvalue reference and the initializer expression

(5.1.1) — is an lvalue (but is not a bit-field), and “*cv1* T1” is reference-compatible with “*cv2* T2”, or

(5.1.2) — has a class type (i.e., T2 is a class type), where T1 is not reference-related to T2, and can be converted to an lvalue of type “*cv3* T3”, where “*cv1* T1” is reference-compatible with “*cv3* T3”<sup>106</sup> (this conversion is selected by enumerating the applicable conversion functions (16.3.1.6) and choosing the best one through overload resolution (16.3)),

then the reference is bound to the initializer expression lvalue in the first case and to the lvalue result of the conversion in the second case (or, in either case, to the appropriate base class subobject of the object). [ *Note:* The usual lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions are not needed, and therefore are suppressed, when such direct bindings to lvalues are done. — end note ]

[ *Example:*

```

double d = 2.0;
double& rd = d; // rd refers to d
const double& rcd = d; // rcd refers to d

```

<sup>106</sup>) This requires a conversion function (15.3.2) returning a reference type.

```

struct A { };
struct B : A { operator int&(); } b;
A& ra = b; // ra refers to A subobject in b
const A& rca = b; // rca refers to A subobject in b
int& ir = B(); // ir refers to the result of B::operator int&

```

— end example]

- (5.2) — Otherwise, the reference shall be an lvalue reference to a non-volatile const type (i.e., *cv1* shall be `const`), or the reference shall be an rvalue reference. [Example:

```

double& rd2 = 2.0; // error: not an lvalue and reference not const
int i = 2;
double& rd3 = i; // error: type mismatch and reference not const

```

— end example]

- (5.2.1) — If the initializer expression

- (5.2.1.1) — is an rvalue (but not a bit-field) or function lvalue and “*cv1 T1*” is reference-compatible with “*cv2 T2*”, or

- (5.2.1.2) — has a class type (i.e., *T2* is a class type), where *T1* is not reference-related to *T2*, and can be converted to an rvalue or function lvalue of type “*cv3 T3*”, where “*cv1 T1*” is reference-compatible with “*cv3 T3*” (see 16.3.1.6),

then the value of the initializer expression in the first case and the result of the conversion in the second case is called the converted initializer. If the converted initializer is a prvalue, its type *T4* is adjusted to type “*cv1 T4*” (7.5) and the temporary materialization conversion (7.4) is applied. In any case, the reference is bound to the resulting glvalue (or to an appropriate base class subobject).

[Example:

```

struct A { };
struct B : A { } b;
extern B f();
const A& rca2 = f(); // bound to the A subobject of the B rvalue.
A&& rra = f(); // same as above
struct X {
 operator B();
 operator int&();
} x;
const A& r = x; // bound to the A subobject of the result of the conversion
int i2 = 42;
int&& rri = static_cast<int&&>(i2); // bound directly to i2
B&& rrb = x; // bound directly to the result of operator B

```

— end example]

- (5.2.2) — Otherwise:

- (5.2.2.1) — If *T1* or *T2* is a class type and *T1* is not reference-related to *T2*, user-defined conversions are considered using the rules for copy-initialization of an object of type “*cv1 T1*” by user-defined conversion (11.6, 16.3.1.4, 16.3.1.5); the program is ill-formed if the corresponding non-reference copy-initialization would be ill-formed. The result of the call to the conversion function, as described for the non-reference copy-initialization, is then used to direct-initialize the reference. For this direct-initialization, user-defined conversions are not considered.
- (5.2.2.2) — Otherwise, the initializer expression is implicitly converted to a prvalue of type “*cv1 T1*”. The temporary materialization conversion is applied and the reference is bound to the result.

If T1 is reference-related to T2:

- (5.2.2.3) — *cv1* shall be the same cv-qualification as, or greater cv-qualification than, *cv2*; and
- (5.2.2.4) — if the reference is an rvalue reference, the initializer expression shall not be an lvalue.

[*Example:*

```
struct Banana { };
struct Enigma { operator const Banana(); };
struct Alaska { operator Banana&(); };
void enigmatic() {
 typedef const Banana ConstBanana;
 Banana &&banana1 = ConstBanana(); // ill-formed
 Banana &&banana2 = Enigma(); // ill-formed
 Banana &&banana3 = Alaska(); // ill-formed
}

const double& rcd2 = 2; // rcd2 refers to temporary with value 2.0
double&& rrd = 2; // rrd refers to temporary with value 2.0
const volatile int cvi = 1;
const int& r2 = cvi; // error: cv-qualifier dropped
struct A { operator volatile int&(); } a;
const int& r3 = a; // error: cv-qualifier dropped
 // from result of conversion function

double d2 = 1.0;
double&& rrd2 = d2; // error: initializer is lvalue of related type
struct X { operator int&(); };
int&& rri2 = X(); // error: result of conversion function is lvalue of related type
int i3 = 2;
double&& rrd3 = i3; // rrd3 refers to temporary with value 2.0

— end example]
```

In all cases except the last (i.e., implicitly converting the initializer expression to the underlying type of the reference), the reference is said to *bind directly* to the initializer expression.

<sup>6</sup> [Note: 15.2 describes the lifetime of temporaries bound to references. — end note]

#### 11.6.4 List-initialization

[**dcl.init.list**]

<sup>1</sup> *List-initialization* is initialization of an object or reference from a *braced-init-list*. Such an initializer is called an *initializer list*, and the comma-separated *initializer-clauses* of the list are called the *elements* of the initializer list. An initializer list may be empty. List-initialization can occur in direct-initialization or copy-initialization contexts; list-initialization in a direct-initialization context is called *direct-list-initialization* and list-initialization in a copy-initialization context is called *copy-list-initialization*. [Note: List-initialization can be used

- (1.1) — as the initializer in a variable definition (11.6)
- (1.2) — as the initializer in a *new-expression* (8.3.4)
- (1.3) — in a return statement (9.6.3)
- (1.4) — as a *for-range-initializer* (9.5)
- (1.5) — as a function argument (8.2.2)
- (1.6) — as a subscript (8.2.1)
- (1.7) — as an argument to a constructor invocation (11.6, 8.2.3)
- (1.8) — as an initializer for a non-static data member (12.2)

- (1.9) — in a *mem-initializer* (15.6.2)
- (1.10) — on the right-hand side of an assignment (8.18)

[ *Example:*

```
int a = {1};
std::complex<double> z{1,2};
new std::vector<std::string>{"once", "upon", "a", "time"}; // 4 string elements
f({"Nicholas","Annemarie"}); // pass list of two elements
return { "Norah" }; // return list of one element
int* e {}; // initialization to zero / null pointer
x = double{1}; // explicitly construct a double
std::map<std::string,int> anim = { {"bear",4}, {"cassowary",2}, {"tiger",7} };
```

— *end example*] — *end note*]

- <sup>2</sup> A constructor is an *initializer-list constructor* if its first parameter is of type `std::initializer_list<E>` or reference to possibly cv-qualified `std::initializer_list<E>` for some type `E`, and either there are no other parameters or else all other parameters have default arguments (11.3.6). [ *Note:* Initializer-list constructors are favored over other constructors in list-initialization (16.3.1.7). Passing an initializer list as the argument to the constructor template `template<class T> C(T)` of a class `C` does not create an initializer-list constructor, because an initializer list argument causes the corresponding parameter to be a non-deduced context (17.8.2.1). — *end note*] The template `std::initializer_list` is not predefined; if the header `<initializer_list>` is not included prior to a use of `std::initializer_list` — even an implicit use in which the type is not named (10.1.7.4) — the program is ill-formed.
- <sup>3</sup> List-initialization of an object or reference of type `T` is defined as follows:
  - (3.1) — If `T` is an aggregate class and the initializer list has a single element of type *cv U*, where `U` is `T` or a class derived from `T`, the object is initialized from that element (by copy-initialization for copy-list-initialization, or by direct-initialization for direct-list-initialization).
  - (3.2) — Otherwise, if `T` is a character array and the initializer list has a single element that is an appropriately-typed string literal (11.6.2), initialization is performed as described in that section.
  - (3.3) — Otherwise, if `T` is an aggregate, aggregate initialization is performed (11.6.1).
 

[ *Example:*

```
double ad[] = { 1, 2.0 }; // OK
int ai[] = { 1, 2.0 }; // error: narrowing

struct S2 {
 int m1;
 double m2, m3;
};
S2 s21 = { 1, 2, 3.0 }; // OK
S2 s22 { 1.0, 2, 3 }; // error: narrowing
S2 s23 { }; // OK: default to 0,0,0
```

— *end example*]
  - (3.4) — Otherwise, if the initializer list has no elements and `T` is a class type with a default constructor, the object is value-initialized.
  - (3.5) — Otherwise, if `T` is a specialization of `std::initializer_list<E>`, the object is constructed as described below.
  - (3.6) — Otherwise, if `T` is a class type, constructors are considered. The applicable constructors are enumerated and the best one is chosen through overload resolution (16.3, 16.3.1.7). If a narrowing conversion (see below) is required to convert any of the arguments, the program is ill-formed.

[*Example:*

```
struct S {
 S(std::initializer_list<double>); // #1
 S(std::initializer_list<int>); // #2
 S(); // #3
 // ...
};
S s1 = { 1.0, 2.0, 3.0 }; // invoke #1
S s2 = { 1, 2, 3 }; // invoke #2
S s3 = { }; // invoke #3
```

— *end example*]

[*Example:*

```
struct Map {
 Map(std::initializer_list<std::pair<std::string,int>>);
};
Map ship = {{"Sophie",14}, {"Surprise",28}};
```

— *end example*]

[*Example:*

```
struct S {
 // no initializer-list constructors
 S(int, double, double); // #1
 S(); // #2
 // ...
};
S s1 = { 1, 2, 3.0 }; // OK: invoke #1
S s2 { 1.0, 2, 3 }; // error: narrowing
S s3 { }; // OK: invoke #2
```

— *end example*]

- (3.7) — Otherwise, if *T* is an enumeration with a fixed underlying type (10.2), the *initializer-list* has a single element *v*, and the initialization is direct-list-initialization, the object is initialized with the value *T(v)* (8.2.3); if a narrowing conversion is required to convert *v* to the underlying type of *T*, the program is ill-formed. [*Example:*

```
enum byte : unsigned char { };
byte b { 42 }; // OK
byte c = { 42 }; // error
byte d = byte{ 42 }; // OK; same value as b
byte e { -1 }; // error
```

```
struct A { byte b; };
A a1 = { { 42 } }; // error
A a2 = { byte{ 42 } }; // OK
```

```
void f(byte);
f({ 42 }); // error
```

```
enum class Handle : uint32_t { Invalid = 0 };
Handle h { 42 }; // OK
```

— *end example*]

- (3.8) — Otherwise, if the initializer list has a single element of type *E* and either *T* is not a reference type or its



referenced type is reference-related to **E**, the object or reference is initialized from that element (by copy-initialization for copy-list-initialization, or by direct-initialization for direct-list-initialization); if a narrowing conversion (see below) is required to convert the element to **T**, the program is ill-formed.

[ *Example:*

```
int x1 {2}; // OK
int x2 {2.0}; // error: narrowing
```

— *end example*]

- (3.9) — Otherwise, if **T** is a reference type, a prvalue of the type referenced by **T** is generated. The prvalue initializes its result object by copy-list-initialization or direct-list-initialization, depending on the kind of initialization for the reference. The prvalue is then used to direct-initialize the reference. [ *Note:* As usual, the binding will fail and the program is ill-formed if the reference type is an lvalue reference to a non-const type. — *end note* ]

[ *Example:*

```
struct S {
 S(std::initializer_list<double>); // #1
 S(const std::string&); // #2
 // ...
};
const S& r1 = { 1, 2, 3.0 }; // OK: invoke #1
const S& r2 { "Spinach" }; // OK: invoke #2
S& r3 = { 1, 2, 3 }; // error: initializer is not an lvalue
const int& i1 = { 1 }; // OK
const int& i2 = { 1.1 }; // error: narrowing
const int (&iar)[2] = { 1, 2 }; // OK: iar is bound to temporary array
```

— *end example*]

- (3.10) — Otherwise, if the initializer list has no elements, the object is value-initialized.

[ *Example:*

```
int** pp {};
```

// initialized to null pointer

— *end example*]

- (3.11) — Otherwise, the program is ill-formed.

[ *Example:*

```
struct A { int i; int j; };
A a1 { 1, 2 }; // aggregate initialization
A a2 { 1.2 }; // error: narrowing
struct B {
 B(std::initializer_list<int>);
};
B b1 { 1, 2 }; // creates initializer_list<int> and calls constructor
B b2 { 1, 2.0 }; // error: narrowing
struct C {
 C(int i, double j);
};
C c1 = { 1, 2.2 }; // calls constructor with arguments (1, 2.2)
C c2 = { 1.1, 2 }; // error: narrowing
```

```
int j { 1 }; // initialize to 1
int k { }; // initialize to 0
```

— *end example*]

- <sup>4</sup> Within the *initializer-list* of a *braced-init-list*, the *initializer-clauses*, including any that result from pack expansions (17.5.3), are evaluated in the order in which they appear. That is, every value computation and side effect associated with a given *initializer-clause* is sequenced before every value computation and side effect associated with any *initializer-clause* that follows it in the comma-separated list of the *initializer-list*. [ *Note*: This evaluation ordering holds regardless of the semantics of the initialization; for example, it applies when the elements of the *initializer-list* are interpreted as arguments of a constructor call, even though ordinarily there are no sequencing constraints on the arguments of a call. — *end note* ]
- <sup>5</sup> An object of type `std::initializer_list<E>` is constructed from an initializer list as if the implementation generated and materialized (7.4) a prvalue of type “array of  $N$  `const E`”, where  $N$  is the number of elements in the initializer list. Each element of that array is copy-initialized with the corresponding element of the initializer list, and the `std::initializer_list<E>` object is constructed to refer to that array. [ *Note*: A constructor or conversion function selected for the copy shall be accessible (Clause 14) in the context of the initializer list. — *end note* ] If a narrowing conversion is required to initialize any of the elements, the program is ill-formed. [ *Example*:

```
struct X {
 X(std::initializer_list<double> v);
};
X x{ 1,2,3 };
```

The initialization will be implemented in a way roughly equivalent to this:

```
const double __a[3] = {double{1}, double{2}, double{3}};
X x(std::initializer_list<double>(__a, __a+3));
```

assuming that the implementation can construct an `initializer_list` object with a pair of pointers. — *end example* ]

- <sup>6</sup> The array has the same lifetime as any other temporary object (15.2), except that initializing an `initializer_list` object from the array extends the lifetime of the array exactly like binding a reference to a temporary. [ *Example*:

```
typedef std::complex<double> cmplx;
std::vector<cmplx> v1 = { 1, 2, 3 };

void f() {
 std::vector<cmplx> v2{ 1, 2, 3 };
 std::initializer_list<int> i3 = { 1, 2, 3 };
}

struct A {
 std::initializer_list<int> i4;
 A() : i4{ 1, 2, 3 } {} // ill-formed, would create a dangling reference
};
```

For `v1` and `v2`, the `initializer_list` object is a parameter in a function call, so the array created for { 1, 2, 3 } has full-expression lifetime. For `i3`, the `initializer_list` object is a variable, so the array persists for the lifetime of the variable. For `i4`, the `initializer_list` object is initialized in the constructor's *ctor-initializer* as if by binding a temporary array to a reference member, so the program is ill-formed (15.6.2). — *end example* ] [ *Note*: The implementation is free to allocate the array in read-only memory if an explicit array with the same initializer could be so allocated. — *end note* ]

- <sup>7</sup> A *narrowing conversion* is an implicit conversion
- (7.1) — from a floating-point type to an integer type, or
  - (7.2) — from `long double` to `double` or `float`, or from `double` to `float`, except where the source is a constant expression and the actual value after conversion is within the range of values that can be represented

(even if it cannot be represented exactly), or

- (7.3) — from an integer type or unscoped enumeration type to a floating-point type, except where the source is a constant expression and the actual value after conversion will fit into the target type and will produce the original value when converted back to the original type, or
- (7.4) — from an integer type or unscoped enumeration type to an integer type that cannot represent all the values of the original type, except where the source is a constant expression whose value after integral promotions will fit into the target type.

[*Note:* As indicated above, such conversions are not allowed at the top level in list-initializations. — *end note*] [*Example:*

```
int x = 999; // x is not a constant expression
const int y = 999;
const int z = 99;
char c1 = x; // OK, though it might narrow (in this case, it does narrow)
char c2{x}; // error: might narrow
char c3{y}; // error: narrows (assuming char is 8 bits)
char c4{z}; // OK: no narrowing needed
unsigned char uc1 = {5}; // OK: no narrowing needed
unsigned char uc2 = {-1}; // error: narrows
unsigned int ui1 = {-1}; // error: narrows
signed int si1 =
 { (unsigned int)-1 }; // error: narrows
int ii = {2.0}; // error: narrows
float f1 { x }; // error: might narrow
float f2 { 7 }; // OK: 7 can be exactly represented as a float
int f(int);
int a[] =
 { 2, f(2), f(2.0) }; // OK: the double-to-int conversion is not at the top level
```

— *end example*]

## 12 Classes

[class]

- <sup>1</sup> A class is a type. Its name becomes a *class-name* (12.1) within its scope.

*class-name*:  
*identifier*  
*simple-template-id*

*Class-specifiers* and *elaborated-type-specifiers* (10.1.7.3) are used to make *class-names*. An object of a class consists of a (possibly empty) sequence of members and base class objects.

*class-specifier*:  
*class-head* { *member-specification*<sub>opt</sub> }

*class-head*:  
*class-key* *attribute-specifier-seq*<sub>opt</sub> *class-head-name* *class-virt-specifier*<sub>opt</sub> *base-clause*<sub>opt</sub>  
*class-key* *attribute-specifier-seq*<sub>opt</sub> *base-clause*<sub>opt</sub>

*class-head-name*:  
*nested-name-specifier*<sub>opt</sub> *class-name*

*class-virt-specifier*:  
**final**

*class-key*:  
**class**  
**struct**  
**union**

A *class-specifier* whose *class-head* omits the *class-head-name* defines an unnamed class. [ *Note*: An unnamed class thus can't be **final**. — *end note* ]

- <sup>2</sup> A *class-name* is inserted into the scope in which it is declared immediately after the *class-name* is seen. The *class-name* is also inserted into the scope of the class itself; this is known as the *injected-class-name*. For purposes of access checking, the injected-class-name is treated as if it were a public member name. A *class-specifier* is commonly referred to as a class definition. A class is considered defined after the closing brace of its *class-specifier* has been seen even though its member functions are in general not yet defined. The optional *attribute-specifier-seq* appertains to the class; the attributes in the *attribute-specifier-seq* are thereafter considered attributes of the class whenever it is named.
- <sup>3</sup> If a class is marked with the *class-virt-specifier* **final** and it appears as a *class-or-decltype* in a *base-clause* (Clause 13), the program is ill-formed. Whenever a *class-key* is followed by a *class-head-name*, the *identifier* **final**, and a colon or left brace, **final** is interpreted as a *class-virt-specifier*. [ *Example*:

```
struct A;
struct A final {}; // OK: definition of struct A,
 // not value-initialization of variable final

struct X {
 struct C { constexpr operator int() { return 5; } };
 struct B final : C{}; // OK: definition of nested class B,
 // not declaration of a bit-field member final
};
```

— *end example* ]

<sup>4</sup> Complete objects and member subobjects of class type shall have nonzero size.<sup>107</sup> [ *Note*: Class objects can be assigned, passed as arguments to functions, and returned by functions (except objects of classes for which copying or moving has been restricted; see 15.8). Other plausible operators, such as equality comparison, can be defined by the user; see 16.5. — *end note*]

<sup>5</sup> A *union* is a class defined with the *class-key* **union**; it holds at most one data member at a time (12.3). [ *Note*: Aggregates of class type are described in 11.6.1. — *end note*]

<sup>6</sup> A *trivially copyable class* is a class:

- (6.1) — where each copy constructor, move constructor, copy assignment operator, and move assignment operator (15.8, 16.5.3) is either deleted or trivial,
- (6.2) — that has at least one non-deleted copy constructor, move constructor, copy assignment operator, or move assignment operator, and
- (6.3) — that has a trivial, non-deleted destructor (15.4).

A *trivial class* is a class that is trivially copyable and has one or more default constructors (15.1), all of which are either trivial or deleted and at least one of which is not deleted. [ *Note*: In particular, a trivially copyable or trivial class does not have virtual functions or virtual base classes. — *end note*]

<sup>7</sup> A class **S** is a *standard-layout class* if it:

- (7.1) — has no non-static data members of type non-standard-layout class (or array of such types) or reference,
- (7.2) — has no virtual functions (13.3) and no virtual base classes (13.1),
- (7.3) — has the same access control (Clause 14) for all non-static data members,
- (7.4) — has no non-standard-layout base classes,
- (7.5) — has at most one base class subobject of any given type,
- (7.6) — has all non-static data members and bit-fields in the class and its base classes first declared in the same class, and
- (7.7) — has no element of the set  $M(\mathbf{S})$  of types (defined below) as a base class.<sup>108</sup>

$M(\mathbf{X})$  is defined as follows:

- (7.8) — If **X** is a non-union class type with no (possibly inherited (Clause 13)) non-static data members, the set  $M(\mathbf{X})$  is empty.
- (7.9) — If **X** is a non-union class type whose first non-static data member has type  $\mathbf{X}_0$  (where said member may be an anonymous union), the set  $M(\mathbf{X})$  consists of  $\mathbf{X}_0$  and the elements of  $M(\mathbf{X}_0)$ .
- (7.10) — If **X** is a union type, the set  $M(\mathbf{X})$  is the union of all  $M(\mathbf{U}_i)$  and the set containing all  $\mathbf{U}_i$ , where each  $\mathbf{U}_i$  is the type of the  $i$ th non-static data member of **X**.
- (7.11) — If **X** is an array type with element type  $\mathbf{X}_e$ , the set  $M(\mathbf{X})$  consists of  $\mathbf{X}_e$  and the elements of  $M(\mathbf{X}_e)$ .
- (7.12) — If **X** is a non-class, non-array type, the set  $M(\mathbf{X})$  is empty.

[ *Note*:  $M(\mathbf{X})$  is the set of the types of all non-base-class subobjects that are guaranteed in a standard-layout class to be at a zero offset in **X**. — *end note*]

[ *Example*:

```
struct B { int i; }; // standard-layout class
struct C : B { }; // standard-layout class
struct D : C { }; // standard-layout class
struct E : D { char : 4; }; // not a standard-layout class
```

107) Base class subobjects are not so constrained.

108) This ensures that two subobjects that have the same class type and that belong to the same most derived object are not allocated at the same address (8.10).

```

 struct Q {};
 struct S : Q { };
 struct T : Q { };
 struct U : S, T { }; // not a standard-layout class

```

— end example]

- <sup>8</sup> A *standard-layout struct* is a standard-layout class defined with the *class-key* **struct** or the *class-key* **class**. A *standard-layout union* is a standard-layout class defined with the *class-key* **union**.
- <sup>9</sup> [Note: Standard-layout classes are useful for communicating with code written in other programming languages. Their layout is specified in 12.2. — end note]
- <sup>10</sup> A *POD struct*<sup>109</sup> is a non-union class that is both a trivial class and a standard-layout class, and has no non-static data members of type non-POD struct, non-POD union (or array of such types). Similarly, a *POD union* is a union that is both a trivial class and a standard-layout class, and has no non-static data members of type non-POD struct, non-POD union (or array of such types). A *POD class* is a class that is either a POD struct or a POD union.

[Example:

```

 struct N { // neither trivial nor standard-layout
 int i;
 int j;
 virtual ~N();
 };

 struct T { // trivial but not standard-layout
 int i;
 private:
 int j;
 };

 struct SL { // standard-layout but not trivial
 int i;
 int j;
 ~SL();
 };

 struct POD { // both trivial and standard-layout
 int i;
 int j;
 };

```

— end example]

- <sup>11</sup> If a *class-head-name* contains a *nested-name-specifier*, the *class-specifier* shall refer to a class that was previously declared directly in the class or namespace to which the *nested-name-specifier* refers, or in an element of the inline namespace set (10.3.1) of that namespace (i.e., not merely inherited or introduced by a *using-declaration*), and the *class-specifier* shall appear in a namespace enclosing the previous declaration. In such cases, the *nested-name-specifier* of the *class-head-name* of the definition shall not begin with a *decltype-specifier*.

## 12.1 Class names

[class.name]

- <sup>1</sup> A class definition introduces a new type. [Example:

<sup>109</sup>) The acronym POD stands for “plain old data”.

```

struct X { int a; };
struct Y { int a; };
X a1;
Y a2;
int a3;

```

declares three variables of three different types. This implies that

```

a1 = a2; // error: Y assigned to X
a1 = a3; // error: int assigned to X

```

are type mismatches, and that

```

int f(X);
int f(Y);

```

declare an overloaded (Clause 16) function `f()` and not simply a single function `f()` twice. For the same reason,

```

struct S { int a; };
struct S { int a; }; // error, double definition

```

is ill-formed because it defines `S` twice. — *end example*]

- <sup>2</sup> A class declaration introduces the class name into the scope where it is declared and hides any class, variable, function, or other declaration of that name in an enclosing scope (6.3). If a class name is declared in a scope where a variable, function, or enumerator of the same name is also declared, then when both declarations are in scope, the class can be referred to only using an *elaborated-type-specifier* (6.4.4). [ *Example:*

```

struct stat {
 // ...
};

stat gstat; // use plain stat to define variable

int stat(struct stat*); // redeclare stat as function

void f() {
 struct stat* ps; // struct prefix needed to name struct stat
 stat(ps); // call stat()
}

```

— *end example*] A *declaration* consisting solely of *class-key identifier* ; is either a redeclaration of the name in the current scope or a forward declaration of the identifier as a class name. It introduces the class name into the current scope. [ *Example:*

```

struct s { int a; };

void g() {
 struct s; // hide global struct s with a block-scope declaration
 s* p; // refer to local struct s
 struct s { char* p; }; // define local struct s
 struct s; // redeclaration, has no effect
}

```

— *end example*] [ *Note:* Such declarations allow definition of classes that refer to each other. [ *Example:*

```

class Vector;

class Matrix {
 // ...
 friend Vector operator*(const Matrix&, const Vector&);
}

```

```
};

class Vector {
 // ...
 friend Vector operator*(const Matrix&, const Vector&);
};
```

Declaration of `friends` is described in 14.3, operator functions in 16.5. — *end example*] — *end note*]

- <sup>3</sup> [ *Note*: An *elaborated-type-specifier* (10.1.7.3) can also be used as a *type-specifier* as part of a declaration. It differs from a class declaration in that if a class of the elaborated name is in scope the elaborated name will refer to it. — *end note*] [ *Example*:

```
struct s { int a; };

void g(int s) {
 struct s* p = new struct s; // global s
 p->a = s; // parameter s
}
```

— *end example*]

- <sup>4</sup> [ *Note*: The declaration of a class name takes effect immediately after the *identifier* is seen in the class definition or *elaborated-type-specifier*. For example,

```
class A * A;
```

first specifies `A` to be the name of a class and then redefines it as the name of a pointer to an object of that class. This means that the elaborated form `class A` must be used to refer to the class. Such artistry with names can be confusing and is best avoided. — *end note*]

- <sup>5</sup> A *typedef-name* (10.1.3) that names a class type, or a cv-qualified version thereof, is also a *class-name*. If a *typedef-name* that names a cv-qualified class type is used where a *class-name* is required, the cv-qualifiers are ignored. A *typedef-name* shall not be used as the *identifier* in a *class-head*.

## 12.2 Class members

[class.mem]

*member-specification*:

*member-declaration member-specification<sub>opt</sub>*  
*access-specifier* : *member-specification<sub>opt</sub>*

*member-declaration*:

*attribute-specifier-seq<sub>opt</sub>* *decl-specifier-seq<sub>opt</sub>* *member-declarator-list<sub>opt</sub>* ;  
*function-definition*  
*using-declaration*  
*static\_assert-declaration*  
*template-declaration*  
*deduction-guide*  
*alias-declaration*  
*empty-declaration*

*member-declarator-list*:

*member-declarator*  
*member-declarator-list* , *member-declarator*

*member-declarator*:

*declarator virt-specifier-seq<sub>opt</sub>* *pure-specifier<sub>opt</sub>*  
*declarator brace-or-equal-initializer<sub>opt</sub>*  
*identifier<sub>opt</sub>* *attribute-specifier-seq<sub>opt</sub>* : *constant-expression*



```

virt-specifier-seq:
 virt-specifier
 virt-specifier-seq virt-specifier

virt-specifier:
 override
 final

pure-specifier:
 = 0

```

- <sup>1</sup> The *member-specification* in a class definition declares the full set of members of the class; no member can be added elsewhere. A *direct member* of a class *X* is a member of *X* that was first declared within the *member-specification* of *X*, including anonymous union objects (12.3.1) and direct members thereof. Members of a class are data members, member functions (12.2.1), nested types, enumerators, and member templates (17.5.2) and specializations thereof. [ *Note*: A specialization of a static data member template is a static data member. A specialization of a member function template is a member function. A specialization of a member class template is a nested class. — *end note* ]
- <sup>2</sup> A *member-declaration* does not declare new members of the class if it is
  - (2.1) — a friend declaration (14.3),
  - (2.2) — a *static\_assert-declaration*,
  - (2.3) — a *using-declaration* (10.3.3), or
  - (2.4) — an *empty-declaration*.

For any other *member-declaration*, each declared entity that is not an unnamed bit-field (12.2.4) is a member of the class, and each such *member-declaration* shall either declare at least one member name of the class or declare at least one unnamed bit-field.
- <sup>3</sup> A *data member* is a non-function member introduced by a *member-declarator*. A *member function* is a member that is a function. Nested types are classes (12.1, 12.2.5) and enumerations (10.2) declared in the class and arbitrary types declared as members by use of a typedef declaration (10.1.3) or *alias-declaration*. The enumerators of an unscoped enumeration (10.2) defined in the class are members of the class.
- <sup>4</sup> A data member or member function may be declared **static** in its *member-declaration*, in which case it is a *static member* (see 12.2.3) (a *static data member* (12.2.3.2) or *static member function* (12.2.3.1), respectively) of the class. Any other data member or member function is a *non-static member* (a *non-static data member* or *non-static member function* (12.2.2), respectively). [ *Note*: A non-static data member of non-reference type is a member subobject of a class object (4.5). — *end note* ]
- <sup>5</sup> A member shall not be declared twice in the *member-specification*, except that
  - (5.1) — a nested class or member class template can be declared and then later defined, and
  - (5.2) — an enumeration can be introduced with an *opaque-enum-declaration* and later redeclared with an *enum-specifier*.

[ *Note*: A single name can denote several member functions provided their types are sufficiently different (Clause 16). — *end note* ]
- <sup>6</sup> A class is considered a completely-defined object type (6.9) (or complete type) at the closing **}** of the *class-specifier*. Within the class *member-specification*, the class is regarded as complete within function bodies, default arguments, *noexcept-specifiers*, and default member initializers (including such things in nested classes). Otherwise it is regarded as incomplete within its own class *member-specification*.
- <sup>7</sup> In a *member-declarator*, an = immediately following the *declarator* is interpreted as introducing a *pure-specifier* if the *declarator-id* has function type, otherwise it is interpreted as introducing a *brace-or-equal-initializer*. [ *Example*:

```

struct S {
 using T = void();
 T * p = 0; // OK: brace-or-equal-initializer
 virtual T f = 0; // OK: pure-specifier
};

```

— end example]

- 8 A *brace-or-equal-initializer* shall appear only in the declaration of a data member. (For static data members, see 12.2.3.2; for non-static data members, see 15.6.2 and 11.6.1). A *brace-or-equal-initializer* for a non-static data member specifies a *default member initializer* for the member, and shall not directly or indirectly cause the implicit definition of a defaulted default constructor for the enclosing class or the exception specification of that constructor.
- 9 A member shall not be declared with the **extern storage-class-specifier**. Within a class definition, a member shall not be declared with the **thread\_local storage-class-specifier** unless also declared **static**.
- 10 The *decl-specifier-seq* may be omitted in constructor, destructor, and conversion function declarations only; when declaring another kind of member the *decl-specifier-seq* shall contain a *type-specifier* that is not a *cv-qualifier*. The *member-declarator-list* can be omitted only after a *class-specifier* or an *enum-specifier* or in a **friend** declaration (14.3). A *pure-specifier* shall be used only in the declaration of a virtual function (13.3) that is not a **friend** declaration.
- 11 The optional *attribute-specifier-seq* in a *member-declaration* appertains to each of the entities declared by the *member-declarators*; it shall not appear if the optional *member-declarator-list* is omitted.
- 12 A *virt-specifier-seq* shall contain at most one of each *virt-specifier*. A *virt-specifier-seq* shall appear only in the declaration of a virtual member function (13.3).
- 13 Non-static data members shall not have incomplete types. In particular, a class **C** shall not contain a non-static member of class **C**, but it can contain a pointer or reference to an object of class **C**.
- 14 [Note: See 8.1 for restrictions on the use of non-static data members and non-static member functions.  
— end note]
- 15 [Note: The type of a non-static member function is an ordinary function type, and the type of a non-static data member is an ordinary object type. There are no special member function types or data member types.  
— end note]
- 16 [Example: A simple example of a class definition is

```

struct tnode {
 char tword[20];
 int count;
 tnode* left;
 tnode* right;
};

```

which contains an array of twenty characters, an integer, and two pointers to objects of the same type. Once this definition has been given, the declaration

```
tnode s, *sp;
```

declares **s** to be a **tnode** and **sp** to be a pointer to a **tnode**. With these declarations, **sp->count** refers to the **count** member of the object to which **sp** points; **s.left** refers to the **left** subtree pointer of the object **s**; and **s.right->tword[0]** refers to the initial character of the **tword** member of the **right** subtree of **s**.  
— end example]

- 17 Non-static data members of a (non-union) class with the same access control (Clause 14) are allocated so that later members have higher addresses within a class object. The order of allocation of non-static data members with different access control is unspecified (Clause 14). Implementation alignment requirements

might cause two adjacent members not to be allocated immediately after each other; so might requirements for space for managing virtual functions (13.3) and virtual base classes (13.1).

18 If *T* is the name of a class, then each of the following shall have a name different from *T*:

- (18.1) — every static data member of class *T*;
- (18.2) — every member function of class *T* [*Note*: This restriction does not apply to constructors, which do not have names (15.1) — *end note*];
- (18.3) — every member of class *T* that is itself a type;
- (18.4) — every member template of class *T*;
- (18.5) — every enumerator of every member of class *T* that is an unscoped enumerated type; and
- (18.6) — every member of every anonymous union that is a member of class *T*.

19 In addition, if class *T* has a user-declared constructor (15.1), every non-static data member of class *T* shall have a name different from *T*.

20 The *common initial sequence* of two standard-layout struct (Clause 12) types is the longest sequence of non-static data members and bit-fields in declaration order, starting with the first such entity in each of the structs, such that corresponding entities have layout-compatible types and either neither entity is a bit-field or both are bit-fields with the same width. [*Example*:

```
struct A { int a; char b; };
struct B { const int b1; volatile char b2; };
struct C { int c; unsigned : 0; char b; };
struct D { int d; char b : 4; };
struct E { unsigned int e; char b; };
```

The common initial sequence of *A* and *B* comprises all members of either class. The common initial sequence of *A* and *C* and of *A* and *D* comprises the first member in each case. The common initial sequence of *A* and *E* is empty. — *end example*]

21 Two standard-layout struct (Clause 12) types are *layout-compatible classes* if their common initial sequence comprises all members and bit-fields of both classes (6.9).

22 Two standard-layout unions are layout-compatible if they have the same number of non-static data members and corresponding non-static data members (in any order) have layout-compatible types (6.9).

23 In a standard-layout union with an active member (12.3) of struct type *T1*, it is permitted to read a non-static data member *m* of another union member of struct type *T2* provided *m* is part of the common initial sequence of *T1* and *T2*; the behavior is as if the corresponding member of *T1* were nominated. [*Example*:

```
struct T1 { int a, b; };
struct T2 { int c; double d; };
union U { T1 t1; T2 t2; };
int f() {
 U u = { { 1, 2 } }; // active member is t1
 return u.t2.c; // OK, as if u.t1.a were nominated
}
```

— *end example*] [*Note*: Reading a volatile object through a non-volatile glvalue has undefined behavior (10.1.7.1). — *end note*]

24 If a standard-layout class object has any non-static data members, its address is the same as the address of its first non-static data member. Otherwise, its address is the same as the address of its first base class subobject (if any). [*Note*: There might therefore be unnamed padding within a standard-layout struct object, but not at its beginning, as necessary to achieve appropriate alignment. — *end note*] [*Note*: The object and its first subobject are pointer-interconvertible (6.9.2, 8.2.9). — *end note*]

## 12.2.1 Member functions

[class.mfct]

- <sup>1</sup> A member function may be defined (11.4) in its class definition, in which case it is an *inline* member function (10.1.6), or it may be defined outside of its class definition if it has already been declared but not defined in its class definition. A member function definition that appears outside of the class definition shall appear in a namespace scope enclosing the class definition. Except for member function definitions that appear outside of a class definition, and except for explicit specializations of member functions of class templates and member function templates (17.7) appearing outside of the class definition, a member function shall not be redeclared.
- <sup>2</sup> An inline member function (whether static or non-static) may also be defined outside of its class definition provided either its declaration in the class definition or its definition outside of the class definition declares the function as **inline** or **constexpr**. [Note: Member functions of a class in namespace scope have the linkage of that class. Member functions of a local class (12.4) have no linkage. See 6.5. — end note]
- <sup>3</sup> [Note: There can be at most one definition of a non-inline member function in a program. There may be more than one **inline** member function definition in a program. See 6.2 and 10.1.6. — end note]
- <sup>4</sup> If the definition of a member function is lexically outside its class definition, the member function name shall be qualified by its class name using the **::** operator. [Note: A name used in a member function definition (that is, in the *parameter-declaration-clause* including the default arguments (11.3.6) or in the member function body) is looked up as described in 6.4. — end note] [Example:

```

struct X {
 typedef int T;
 static T count;
 void f(T);
};
void X::f(T t = count) { }

```

The member function **f** of class **X** is defined in global scope; the notation **X::f** specifies that the function **f** is a member of class **X** and in the scope of class **X**. In the function definition, the parameter type **T** refers to the typedef member **T** declared in class **X** and the default argument **count** refers to the static data member **count** declared in class **X**. — end example]

- <sup>5</sup> [Note: A **static** local variable or local type in a member function always refers to the same entity, whether or not the member function is **inline**. — end note]
- <sup>6</sup> Previously declared member functions may be mentioned in **friend** declarations.
- <sup>7</sup> Member functions of a local class shall be defined inline in their class definition, if they are defined at all.
- <sup>8</sup> [Note: A member function can be declared (but not defined) using a typedef for a function type. The resulting member function has exactly the same type as it would have if the function declarator were provided explicitly, see 11.3.5. For example,

```

typedef void fv();
typedef void fvc() const;
struct S {
 fv memfunc1; // equivalent to: void memfunc1();
 void memfunc2();
 fvc memfunc3; // equivalent to: void memfunc3() const;
};
fv S::* pmfv1 = &S::memfunc1;
fv S::* pmfv2 = &S::memfunc2;
fvc S::* pmfv3 = &S::memfunc3;

```

Also see 17.3. — end note]

## 12.2.2 Non-static member functions

[class.mfct.non-static]

- <sup>1</sup> A non-static member function may be called for an object of its class type, or for an object of a class derived (Clause 13) from its class type, using the class member access syntax (8.2.5, 16.3.1.1). A non-static member function may also be called directly using the function call syntax (8.2.2, 16.3.1.1) from within the body of a member function of its class or of a class derived from its class.
- <sup>2</sup> If a non-static member function of a class **X** is called for an object that is not of type **X**, or of a type derived from **X**, the behavior is undefined.
- <sup>3</sup> When an *id-expression* (8.1) that is not part of a class member access syntax (8.2.5) and not used to form a pointer to member (8.3.1) is used in a member of class **X** in a context where **this** can be used (8.1.2), if name lookup (6.4) resolves the name in the *id-expression* to a non-static non-type member of some class **C**, and if either the *id-expression* is potentially evaluated or **C** is **X** or a base class of **X**, the *id-expression* is transformed into a class member access expression (8.2.5) using **(\*this)** (12.2.2.1) as the *postfix-expression* to the left of the **.** operator. [ *Note:* If **C** is not **X** or a base class of **X**, the class member access expression is ill-formed. — *end note* ] Similarly during name lookup, when an *unqualified-id* (8.1) used in the definition of a member function for class **X** resolves to a static member, an enumerator or a nested type of class **X** or of a base class of **X**, the *unqualified-id* is transformed into a *qualified-id* (8.1) in which the *nested-name-specifier* names the class of the member function. These transformations do not apply in the template definition context (17.6.2.1). [ *Example:*

```

struct tnode {
 char tword[20];
 int count;
 tnode* left;
 tnode* right;
 void set(const char*, tnode* l, tnode* r);
};

void tnode::set(const char* w, tnode* l, tnode* r) {
 count = strlen(w)+1;
 if (sizeof(tword)<=count)
 perror("tnode string too long");
 strcpy(tword,w);
 left = l;
 right = r;
}

void f(tnode n1, tnode n2) {
 n1.set("abc",&n2,0);
 n2.set("def",0,0);
}

```

In the body of the member function **tnode::set**, the member names **tword**, **count**, **left**, and **right** refer to members of the object for which the function is called. Thus, in the call **n1.set("abc",&n2,0)**, **tword** refers to **n1.tword**, and in the call **n2.set("def",0,0)**, it refers to **n2.tword**. The functions **strlen**, **perror**, and **strcpy** are not members of the class **tnode** and should be declared elsewhere.<sup>110</sup> — *end example*]

- <sup>4</sup> A non-static member function may be declared **const**, **volatile**, or **const volatile**. These *cv-qualifiers* affect the type of the **this** pointer (12.2.2.1). They also affect the function type (11.3.5) of the member function; a member function declared **const** is a *const* member function, a member function declared **volatile** is a *volatile* member function and a member function declared **const volatile** is a *const volatile* member function. [ *Example:*

---

<sup>110</sup> See, for example, **<cstring>** (24.5).

```
struct X {
 void g() const;
 void h() const volatile;
};
```

`X::g` is a **const** member function and `X::h` is a **const volatile** member function. — *end example*]

- <sup>5</sup> A non-static member function may be declared with a *ref-qualifier* (11.3.5); see 16.3.1.  
<sup>6</sup> A non-static member function may be declared *virtual* (13.3) or *pure virtual* (13.4).

### 12.2.2.1 The **this** pointer

[**class.this**]

- <sup>1</sup> In the body of a non-static (12.2.1) member function, the keyword **this** is a prvalue expression whose value is the address of the object for which the function is called. The type of **this** in a member function of a class **X** is **X\***. If the member function is declared **const**, the type of **this** is **const X\***, if the member function is declared **volatile**, the type of **this** is **volatile X\***, and if the member function is declared **const volatile**, the type of **this** is **const volatile X\***. [Note: Thus in a **const** member function, the object for which the function is called is accessed through a **const** access path. — *end note*] [Example:

```
struct s {
 int a;
 int f() const;
 int g() { return a++; }
 int h() const { return a++; } // error
};

int s::f() const { return a; }
```

The `a++` in the body of `s::h` is ill-formed because it tries to modify (a part of) the object for which `s::h()` is called. This is not allowed in a **const** member function because **this** is a pointer to **const**; that is, `*this` has **const** type. — *end example*]

- <sup>2</sup> Similarly, **volatile** semantics (10.1.7.1) apply in **volatile** member functions when accessing the object and its non-static data members.  
<sup>3</sup> A cv-qualified member function can be called on an object-expression (8.2.5) only if the object-expression is as cv-qualified or less-cv-qualified than the member function. [Example:

```
void k(s& x, const s& y) {
 x.f();
 x.g();
 y.f();
 y.g();
} // error
```

The call `y.g()` is ill-formed because `y` is **const** and `s::g()` is a non-**const** member function, that is, `s::g()` is less-qualified than the object-expression `y`. — *end example*]

- <sup>4</sup> Constructors (15.1) and destructors (15.4) shall not be declared **const**, **volatile** or **const volatile**. [Note: However, these functions can be invoked to create and destroy objects with cv-qualified types, see 15.1 and 15.4. — *end note*]

### 12.2.3 Static members

[**class.static**]

- <sup>1</sup> A static member `s` of class **X** may be referred to using the *qualified-id* expression `X::s`; it is not necessary to use the class member access syntax (8.2.5) to refer to a static member. A static member may be referred to using the class member access syntax, in which case the object expression is evaluated. [Example:

```
struct process {
 static void reschedule();
```

```

};
process& g();

void f() {
 process::reschedule(); // OK: no object necessary
 g().reschedule(); // g() is called
}

```

— end example]

- <sup>2</sup> A static member may be referred to directly in the scope of its class or in the scope of a class derived (Clause 13) from its class; in this case, the static member is referred to as if a *qualified-id* expression was used, with the *nested-name-specifier* of the *qualified-id* naming the class scope from which the static member is referenced. [Example:

```

int g();
struct X {
 static int g();
};
struct Y : X {
 static int i;
};
int Y::i = g(); // equivalent to Y::g();

```

— end example]

- <sup>3</sup> If an *unqualified-id* (8.1) is used in the definition of a static member following the member's *declarator-id*, and name lookup (6.4.1) finds that the *unqualified-id* refers to a static member, enumerator, or nested type of the member's class (or of a base class of the member's class), the *unqualified-id* is transformed into a *qualified-id* expression in which the *nested-name-specifier* names the class scope from which the member is referenced. [Note: See 8.1 for restrictions on the use of non-static data members and non-static member functions. — end note]
- <sup>4</sup> Static members obey the usual class member access rules (Clause 14). When used in the declaration of a class member, the **static** specifier shall only be used in the member declarations that appear within the *member-specification* of the class definition. [Note: It cannot be specified in member declarations that appear in namespace scope. — end note]

### 12.2.3.1 Static member functions

[class.static.mfct]

- <sup>1</sup> [Note: The rules described in 12.2.1 apply to static member functions. — end note]
- <sup>2</sup> [Note: A static member function does not have a **this** pointer (12.2.2.1). — end note] A static member function shall not be **virtual**. There shall not be a static and a non-static member function with the same name and the same parameter types (16.1). A static member function shall not be declared **const**, **volatile**, or **const volatile**.

### 12.2.3.2 Static data members

[class.static.data]

- <sup>1</sup> A static data member is not part of the subobjects of a class. If a static data member is declared **thread\_local** there is one copy of the member per thread. If a static data member is not declared **thread\_local** there is one copy of the data member that is shared by all the objects of the class.
- <sup>2</sup> The declaration of a non-inline static data member in its class definition is not a definition and may be of an incomplete type other than *cv void*. The definition for a static data member that is not defined inline in the class definition shall appear in a namespace scope enclosing the member's class definition. In the definition at namespace scope, the name of the static data member shall be qualified by its class name using the **::** operator. The *initializer* expression in the definition of a static data member is in the scope of its class (6.3.7). [Example:



```
class process {
 static process* run_chain;
 static process* running;
};
```

```
process* process::running = get_main();
process* process::run_chain = running;
```

The static data member `run_chain` of class `process` is defined in global scope; the notation `process::run_chain` specifies that the member `run_chain` is a member of class `process` and in the scope of class `process`. In the static data member definition, the *initializer* expression refers to the static data member `running` of class `process`. — *end example*]

[*Note:* Once the static data member has been defined, it exists even if no objects of its class have been created. [*Example:* In the example above, `run_chain` and `running` exist even if no objects of class `process` are created by the program. — *end example*] — *end note*]

- 3 If a non-volatile non-inline `const` static data member is of integral or enumeration type, its declaration in the class definition can specify a *brace-or-equal-initializer* in which every *initializer-clause* that is an *assignment-expression* is a constant expression (8.20). The member shall still be defined in a namespace scope if it is odr-used (6.2) in the program and the namespace scope definition shall not contain an *initializer*. An inline static data member may be defined in the class definition and may specify a *brace-or-equal-initializer*. If the member is declared with the `constexpr` specifier, it may be redeclared in namespace scope with no *initializer* (this usage is deprecated; see D.1). Declarations of other static data members shall not specify a *brace-or-equal-initializer*.
- 4 [*Note:* There shall be exactly one definition of a static data member that is odr-used (6.2) in a program; no diagnostic is required. — *end note*] Unnamed classes and classes contained directly or indirectly within unnamed classes shall not contain static data members.
- 5 [*Note:* Static data members of a class in namespace scope have the linkage of that class (6.5). A local class cannot have static data members (12.4). — *end note*]
- 6 Static data members are initialized and destroyed exactly like non-local variables (6.6.2, 6.6.3, 6.6.4).
- 7 A static data member shall not be `mutable` (10.1.1).

#### 12.2.4 Bit-fields

[**class.bit**]

- 1 A *member-declarator* of the form

*identifier<sub>opt</sub> attribute-specifier-seq<sub>opt</sub> : constant-expression*

specifies a bit-field; its length is set off from the bit-field name by a colon. The optional *attribute-specifier-seq* appertains to the entity being declared. The bit-field attribute is not part of the type of the class member. The *constant-expression* shall be an integral constant expression with a value greater than or equal to zero. The value of the integral constant expression may be larger than the number of bits in the object representation (6.9) of the bit-field's type; in such cases the extra bits are used as padding bits and do not participate in the value representation (6.9) of the bit-field. Allocation of bit-fields within a class object is implementation-defined. Alignment of bit-fields is implementation-defined. Bit-fields are packed into some addressable allocation unit. [*Note:* Bit-fields straddle allocation units on some machines and not on others. Bit-fields are assigned right-to-left on some machines, left-to-right on others. — *end note*]

- 2 A declaration for a bit-field that omits the *identifier* declares an *unnamed bit-field*. Unnamed bit-fields are not members and cannot be initialized. [*Note:* An unnamed bit-field is useful for padding to conform to externally-imposed layouts. — *end note*] As a special case, an unnamed bit-field with a width of zero specifies alignment of the next bit-field at an allocation unit boundary. Only when declaring an unnamed bit-field may the value of the *constant-expression* be equal to zero.



- <sup>3</sup> A bit-field shall not be a static member. A bit-field shall have integral or enumeration type (6.9.1). A `bool` value can successfully be stored in a bit-field of any nonzero size. The address-of operator `&` shall not be applied to a bit-field, so there are no pointers to bit-fields. A non-const reference shall not be bound to a bit-field (11.6.3). [ *Note*: If the initializer for a reference of type `const T&` is an lvalue that refers to a bit-field, the reference is bound to a temporary initialized to hold the value of the bit-field; the reference is not bound to the bit-field directly. See 11.6.3. — *end note* ]
- <sup>4</sup> If the value `true` or `false` is stored into a bit-field of type `bool` of any size (including a one bit bit-field), the original `bool` value and the value of the bit-field shall compare equal. If the value of an enumerator is stored into a bit-field of the same enumeration type and the number of bits in the bit-field is large enough to hold all the values of that enumeration type (10.2), the original enumerator value and the value of the bit-field shall compare equal. [ *Example*:

```
enum BOOL { FALSE=0, TRUE=1 };
struct A {
 BOOL b:1;
};
A a;
void f() {
 a.b = TRUE;
 if (a.b == TRUE) // yields true
 { /* ... */ }
}
```

— *end example* ]

## 12.2.5 Nested class declarations

[**class.nest**]

- <sup>1</sup> A class can be declared within another class. A class declared within another is called a *nested* class. The name of a nested class is local to its enclosing class. The nested class is in the scope of its enclosing class. [ *Note*: See 8.1 for restrictions on the use of non-static data members and non-static member functions. — *end note* ]

[ *Example*:

```
int x;
int y;

struct enclose {
 int x;
 static int s;

 struct inner {
 void f(int i) {
 int a = sizeof(x); // OK: operand of sizeof is an unevaluated operand
 x = i; // error: assign to enclose::x
 s = i; // OK: assign to enclose::s
 ::x = i; // OK: assign to global x
 y = i; // OK: assign to global y
 }
 void g(enclose* p, int i) {
 p->x = i; // OK: assign to enclose::x
 }
 };
};

inner* p = 0; // error: inner not in scope
```

— *end example*]

- <sup>2</sup> Member functions and static data members of a nested class can be defined in a namespace scope enclosing the definition of their class. [*Example:*

```
struct enclose {
 struct inner {
 static int x;
 void f(int i);
 };
};

int enclose::inner::x = 1;

void enclose::inner::f(int i) { /* ... */ }
```

— *end example*]

- <sup>3</sup> If class X is defined in a namespace scope, a nested class Y may be declared in class X and later defined in the definition of class X or be later defined in a namespace scope enclosing the definition of class X. [*Example:*

```
class E {
 class I1; // forward declaration of nested class
 class I2;
 class I1 { }; // definition of nested class
};
class E::I2 { }; // definition of nested class
```

— *end example*]

- <sup>4</sup> Like a member function, a friend function (14.3) defined within a nested class is in the lexical scope of that class; it obeys the same rules for name binding as a static member function of that class (12.2.3), but it has no special access rights to members of an enclosing class.

### 12.2.6 Nested type names

[**class.nested.type**]

- <sup>1</sup> Type names obey exactly the same scope rules as other names. In particular, type names defined within a class definition cannot be used outside their class without qualification. [*Example:*

```
struct X {
 typedef int I;
 class Y { /* ... */ };
 I a;
};

I b; // error
Y c; // error
X::Y d; // OK
X::I e; // OK
```

— *end example*]

### 12.3 Unions

[**class.union**]

- <sup>1</sup> In a union, a non-static data member is *active* if its name refers to an object whose lifetime has begun and has not ended (6.8). At most one of the non-static data members of an object of union type can be active at any time, that is, the value of at most one of the non-static data members can be stored in a union at any time. [*Note:* One special guarantee is made in order to simplify the use of unions: If a standard-layout union contains several standard-layout structs that share a common initial sequence (12.2), and if a non-static data member of an object of this standard-layout union type is active and is one of the standard-layout structs, it

is permitted to inspect the common initial sequence of any of the standard-layout struct members; see 12.2. — *end note*]

- <sup>2</sup> The size of a union is sufficient to contain the largest of its non-static data members. Each non-static data member is allocated as if it were the sole member of a struct. [ *Note*: A union object and its non-static data members are pointer-interconvertible (6.9.2, 8.2.9). As a consequence, all non-static data members of a union object have the same address. — *end note*]
- <sup>3</sup> A union can have member functions (including constructors and destructors), but it shall not have virtual (13.3) functions. A union shall not have base classes. A union shall not be used as a base class. If a union contains a non-static data member of reference type the program is ill-formed. [ *Note*: Absent default member initializers (12.2), if any non-static data member of a union has a non-trivial default constructor (15.1), copy constructor (15.8), move constructor (15.8), copy assignment operator (15.8), move assignment operator (15.8), or destructor (15.4), the corresponding member function of the union must be user-provided or it will be implicitly deleted (11.4.3) for the union. — *end note*]
- <sup>4</sup> [ *Example*: Consider the following union:

```
union U {
 int i;
 float f;
 std::string s;
};
```

Since `std::string` (24.3) declares non-trivial versions of all of the special member functions, `U` will have an implicitly deleted default constructor, copy/move constructor, copy/move assignment operator, and destructor. To use `U`, some or all of these member functions must be user-provided. — *end example*]

- <sup>5</sup> When the left operand of an assignment operator involves a member access expression (8.2.5) that nominates a union member, it may begin the lifetime of that union member, as described below. For an expression `E`, define the set  $S(E)$  of subexpressions of `E` as follows:
  - (5.1) — If `E` is of the form `A.B`,  $S(E)$  contains the elements of  $S(A)$ , and also contains `A.B` if `B` names a union member of a non-class, non-array type, or of a class type with a trivial default constructor that is not deleted, or an array of such types.
  - (5.2) — If `E` is of the form `A[B]` and is interpreted as a built-in array subscripting operator,  $S(E)$  is  $S(A)$  if `A` is of array type,  $S(B)$  if `B` is of array type, and empty otherwise.
  - (5.3) — Otherwise,  $S(E)$  is empty.

In an assignment expression of the form `E1 = E2` that uses either the built-in assignment operator (8.18) or a trivial assignment operator (15.8), for each element `X` of  $S(E1)$ , if modification of `X` would have undefined behavior under 6.8, an object of the type of `X` is implicitly created in the nominated storage; no initialization is performed and the beginning of its lifetime is sequenced after the value computation of the left and right operands and before the assignment. [ *Note*: This ends the lifetime of the previously-active member of the union, if any (6.8). — *end note* ] [ *Example*:

```
union A { int x; int y[4]; };
struct B { A a; };
union C { B b; int k; };
int f() {
 C c; // does not start lifetime of any union member
 c.b.a.y[3] = 4; // OK: S(c.b.a.y[3]) contains c.b and c.b.a.y;
 // creates objects to hold union members c.b and c.b.a.y
 return c.b.a.y[3]; // OK: c.b.a.y refers to newly created object (see 6.8)
}

struct X { const int a; int b; };
```

```

union Y { X x; int k; };
void g() {
 Y y = { { 1, 2 } }; // OK, y.x is active union member (12.2)
 int n = y.x.a;
 y.k = 4; // OK: ends lifetime of y.x, y.k is active member of union
 y.x.b = n; // undefined behavior: y.x.b modified outside its lifetime,
 // S(y.x.b) is empty because X's default constructor is deleted,
 // so union member y.x's lifetime does not implicitly start
}

```

— end example]

- <sup>6</sup> [Note: In general, one must use explicit destructor calls and placement *new-expression* to change the active member of a union. — end note] [Example: Consider an object *u* of a **union** type *U* having non-static data members *m* of type *M* and *n* of type *N*. If *M* has a non-trivial destructor and *N* has a non-trivial constructor (for instance, if they declare or inherit virtual functions), the active member of *u* can be safely switched from *m* to *n* using the destructor and placement *new-expression* as follows:

```

u.m.~M();
new (&u.n) N;

```

— end example]

### 12.3.1 Anonymous unions

[class.union.anon]

- <sup>1</sup> A union of the form

```
union { member-specification } ;
```

is called an *anonymous union*; it defines an unnamed type and an unnamed object of that type called an *anonymous union object*. Each *member-declaration* in the *member-specification* of an anonymous union shall either define a non-static data member or be a *static\_assert-declaration*. [Note: Nested types, anonymous unions, and functions cannot be declared within an anonymous union. — end note] The names of the members of an anonymous union shall be distinct from the names of any other entity in the scope in which the anonymous union is declared. For the purpose of name lookup, after the anonymous union definition, the members of the anonymous union are considered to have been defined in the scope in which the anonymous union is declared. [Example:

```

void f() {
 union { int a; const char* p; };
 a = 1;
 p = "Jennifer";
}

```

Here *a* and *p* are used like ordinary (non-member) variables, but since they are union members they have the same address. — end example]

- <sup>2</sup> Anonymous unions declared in a named namespace or in the global namespace shall be declared **static**. Anonymous unions declared at block scope shall be declared with any storage class allowed for a block-scope variable, or with no storage class. A storage class is not allowed in a declaration of an anonymous union in a class scope. An anonymous union shall not have **private** or **protected** members (Clause 14). An anonymous union shall not have member functions.
- <sup>3</sup> A union for which objects, pointers, or references are declared is not an anonymous union. [Example:

```

void f() {
 union { int aa; char* p; } obj, *ptr = &obj;
 aa = 1; // error
 ptr->aa = 1; // OK
}

```

The assignment to plain `aa` is ill-formed since the member name is not visible outside the union, and even if it were visible, it is not associated with any particular object. — *end example*] [Note: Initialization of unions with no user-declared constructors is described in 11.6.1. — *end note*]

- <sup>4</sup> A *union-like class* is a union or a class that has an anonymous union as a direct member. A union-like class `X` has a set of *variant members*. If `X` is a union, a non-static data member of `X` that is not an anonymous union is a variant member of `X`. In addition, a non-static data member of an anonymous union that is a member of `X` is also a variant member of `X`. At most one variant member of a union may have a default member initializer. [Example:

```
union U {
 int x = 0;
 union {
 int k;
 };
 union {
 int z;
 int y = 1; // error: initialization for second variant member of U
 };
};
```

— *end example*]

## 12.4 Local class declarations

[class.local]

- <sup>1</sup> A class can be declared within a function definition; such a class is called a *local class*. The name of a local class is local to its enclosing scope. The local class is in the scope of the enclosing scope, and has the same access to names outside the function as does the enclosing function. Declarations in a local class shall not odr-use (6.2) a variable with automatic storage duration from an enclosing scope. [Example:

```
int x;
void f() {
 static int s;
 int x;
 const int N = 5;
 extern int q();

 struct local {
 int g() { return x; } // error: odr-use of automatic variable x
 int h() { return s; } // OK
 int k() { return ::x; } // OK
 int l() { return q(); } // OK
 int m() { return N; } // OK: not an odr-use
 int* n() { return &N; } // error: odr-use of automatic variable N
 };
}

local* p = 0; // error: local not in scope
```

— *end example*]

- <sup>2</sup> An enclosing function has no special access to members of the local class; it obeys the usual access rules (Clause 14). Member functions of a local class shall be defined within their class definition, if they are defined at all.
- <sup>3</sup> If class `X` is a local class a nested class `Y` may be declared in class `X` and later defined in the definition of class `X` or be later defined in the same scope as the definition of class `X`. A class nested within a local class is a local class.

- <sup>4</sup> A local class shall not have static data members.

# 13 Derived classes

[class.derived]

- <sup>1</sup> A list of base classes can be specified in a class definition using the notation:

```

base-clause:
 : base-specifier-list

base-specifier-list:
 base-specifier ...opt
 base-specifier-list , base-specifier ...opt

base-specifier:
 attribute-specifier-seqopt class-or-decltype
 attribute-specifier-seqopt virtual access-specifieropt class-or-decltype
 attribute-specifier-seqopt access-specifier virtualopt class-or-decltype

class-or-decltype:
 nested-name-specifieropt class-name
 nested-name-specifier template simple-template-id
 decltype-specifier

access-specifier:
 private
 protected
 public

```

The optional *attribute-specifier-seq* appertains to the *base-specifier*.

- <sup>2</sup> A *class-or-decltype* shall denote a class type that is not an incompletely defined class (Clause 12). The class denoted by the *class-or-decltype* of a *base-specifier* is called a *direct base class* for the class being defined. During the lookup for a base class name, non-type names are ignored (6.3.10). If the name found is not a *class-name*, the program is ill-formed. A class B is a base class of a class D if it is a direct base class of D or a direct base class of one of D's base classes. A class is an *indirect* base class of another if it is a base class but not a direct base class. A class is said to be (directly or indirectly) *derived* from its (direct or indirect) base classes. [Note: See Clause 14 for the meaning of *access-specifier*. — end note] Unless redeclared in the derived class, members of a base class are also considered to be members of the derived class. Members of a base class other than constructors are said to be *inherited* by the derived class. Constructors of a base class can also be inherited as described in 10.3.3. Inherited members can be referred to in expressions in the same manner as other members of the derived class, unless their names are hidden or ambiguous (13.2). [Note: The scope resolution operator :: (8.1) can be used to refer to a direct or indirect base member explicitly. This allows access to a name that has been redeclared in the derived class. A derived class can itself serve as a base class subject to access control; see 14.2. A pointer to a derived class can be implicitly converted to a pointer to an accessible unambiguous base class (7.11). An lvalue of a derived class type can be bound to a reference to an accessible unambiguous base class (11.6.3). — end note]
- <sup>3</sup> The *base-specifier-list* specifies the type of the *base class subobjects* contained in an object of the derived class type. [Example:

```

struct Base {
 int a, b, c;
};

struct Derived : Base {
 int b;
};

```

```
struct Derived2 : Derived {
 int c;
};
```

Here, an object of class `Derived2` will have a subobject of class `Derived` which in turn will have a subobject of class `Base`. — *end example*

- <sup>4</sup> A *base-specifier* followed by an ellipsis is a pack expansion (17.5.3).
- <sup>5</sup> The order in which the base class subobjects are allocated in the most derived object (4.5) is unspecified. [ *Note:* A derived class and its base class subobjects can be represented by a directed acyclic graph (DAG) where an arrow means “directly derived from”. An arrow need not have a physical representation in memory. A DAG of subobjects is often referred to as a “subobject lattice”.



Figure 2 — Directed acyclic graph

— *end note*

- <sup>6</sup> [ *Note:* Initialization of objects representing base classes can be specified in constructors; see 15.6.2. — *end note* ]
- <sup>7</sup> [ *Note:* A base class subobject might have a layout (6.7) different from the layout of a most derived object of the same type. A base class subobject might have a polymorphic behavior (15.7) different from the polymorphic behavior of a most derived object of the same type. A base class subobject may be of zero size (Clause 12); however, two subobjects that have the same class type and that belong to the same most derived object must not be allocated at the same address (8.10). — *end note* ]

### 13.1 Multiple base classes

[class.mi]

- <sup>1</sup> A class can be derived from any number of base classes. [ *Note:* The use of more than one direct base class is often called multiple inheritance. — *end note* ] [ *Example:*

```
class A { /* ... */ };
class B { /* ... */ };
class C { /* ... */ };
class D : public A, public B, public C { /* ... */ };
```

— *end example*

- <sup>2</sup> [ *Note:* The order of derivation is not significant except as specified by the semantics of initialization by constructor (15.6.2), cleanup (15.4), and storage layout (12.2, 14.1). — *end note* ]
- <sup>3</sup> A class shall not be specified as a direct base class of a derived class more than once. [ *Note:* A class can be an indirect base class more than once and can be a direct and an indirect base class. There are limited things that can be done with such a class. The non-static data members and member functions of the direct base class cannot be referred to in the scope of the derived class. However, the static members, enumerations and types can be unambiguously referred to. — *end note* ] [ *Example:*

```
class X { /* ... */ };
class Y : public X, public X { /* ... */ }; // ill-formed
```



```

class L { public: int next; /* ... */ };
class A : public L { /* ... */ };
class B : public L { /* ... */ };
class C : public A, public B { void f(); /* ... */ }; // well-formed
class D : public A, public L { void f(); /* ... */ }; // well-formed

```

— end example]

- <sup>4</sup> A base class specifier that does not contain the keyword **virtual** specifies a *non-virtual base class*. A base class specifier that contains the keyword **virtual** specifies a *virtual base class*. For each distinct occurrence of a non-virtual base class in the class lattice of the most derived class, the most derived object (4.5) shall contain a corresponding distinct base class subobject of that type. For each distinct base class that is specified virtual, the most derived object shall contain a single base class subobject of that type.
- <sup>5</sup> [Note: For an object of class type C, each distinct occurrence of a (non-virtual) base class L in the class lattice of C corresponds one-to-one with a distinct L subobject within the object of type C. Given the class C defined above, an object of class C will have two subobjects of class L as shown in Figure 3.




Figure 3 — Non-virtual base

In such lattices, explicit qualification can be used to specify which subobject is meant. The body of function C::f could refer to the member next of each L subobject:

```

void C::f() { A::next = B::next; } // well-formed

```

Without the A:: or B:: qualifiers, the definition of C::f above would be ill-formed because of ambiguity (13.2).

— end note]

- <sup>6</sup> [Note: In contrast, consider the case with a virtual base class:

```

class V { /* ... */ };
class A : virtual public V { /* ... */ };
class B : virtual public V { /* ... */ };
class C : public A, public B { /* ... */ };

```




Figure 4 — Virtual base

For an object c of class type C, a single subobject of type V is shared by every base class subobject of c

that has a **virtual** base class of type V. Given the class C defined above, an object of class C will have one subobject of class V, as shown in Figure 4. — *end note*]

- <sup>7</sup> [ *Note*: A class can have both virtual and non-virtual base classes of a given type.

```
class B { /* ... */ };
class X : virtual public B { /* ... */ };
class Y : virtual public B { /* ... */ };
class Z : public B { /* ... */ };
class AA : public X, public Y, public Z { /* ... */ };
```

For an object of class AA, all **virtual** occurrences of base class B in the class lattice of AA correspond to a single B subobject within the object of type AA, and every other occurrence of a (non-virtual) base class B in the class lattice of AA corresponds one-to-one with a distinct B subobject within the object of type AA. Given the class AA defined above, class AA has two subobjects of class B: Z's B and the virtual B shared by X and Y, as shown in Figure 5.




Figure 5 — Virtual and non-virtual base

— *end note*]

### 13.2 Member name lookup

[**class.member.lookup**]

- <sup>1</sup> Member name lookup determines the meaning of a name (*id-expression*) in a class scope (6.3.7). Name lookup can result in an *ambiguity*, in which case the program is ill-formed. For an *id-expression*, name lookup begins in the class scope of **this**; for a *qualified-id*, name lookup begins in the scope of the *nested-name-specifier*. Name lookup takes place before access control (6.4, Clause 14).
- <sup>2</sup> The following steps define the result of name lookup for a member name **f** in a class scope **C**.
- <sup>3</sup> The *lookup set* for **f** in **C**, called  $S(f, C)$ , consists of two component sets: the *declaration set*, a set of members named **f**; and the *subobject set*, a set of subobjects where declarations of these members (possibly including *using-declarations*) were found. In the declaration set, *using-declarations* are replaced by the set of designated members that are not hidden or overridden by members of the derived class (10.3.3), and type declarations (including injected-class-names) are replaced by the types they designate.  $S(f, C)$  is calculated as follows:
- <sup>4</sup> If **C** contains a declaration of the name **f**, the declaration set contains every declaration of **f** declared in **C** that satisfies the requirements of the language construct in which the lookup occurs. [ *Note*: Looking up a name in an *elaborated-type-specifier* (6.4.4) or *base-specifier* (Clause 13), for instance, ignores all non-type declarations, while looking up a name in a *nested-name-specifier* (6.4.3) ignores function, variable, and enumerator declarations. As another example, looking up a name in a *using-declaration* (10.3.3) includes the declaration of a class or enumeration that would ordinarily be hidden by another declaration of that name in the same scope. — *end note* ] If the resulting declaration set is not empty, the subobject set contains **C** itself, and calculation is complete.
- <sup>5</sup> Otherwise (i.e., **C** does not contain a declaration of **f** or the resulting declaration set is empty),  $S(f, C)$  is initially empty. If **C** has base classes, calculate the lookup set for **f** in each direct base class subobject  $B_i$ , and merge each such lookup set  $S(f, B_i)$  in turn into  $S(f, C)$ .

- 6 The following steps define the result of merging lookup set  $S(f, B_i)$  into the intermediate  $S(f, C)$ :
- (6.1) — If each of the subobject members of  $S(f, B_i)$  is a base class subobject of at least one of the subobject members of  $S(f, C)$ , or if  $S(f, B_i)$  is empty,  $S(f, C)$  is unchanged and the merge is complete. Conversely, if each of the subobject members of  $S(f, C)$  is a base class subobject of at least one of the subobject members of  $S(f, B_i)$ , or if  $S(f, C)$  is empty, the new  $S(f, C)$  is a copy of  $S(f, B_i)$ .
  - (6.2) — Otherwise, if the declaration sets of  $S(f, B_i)$  and  $S(f, C)$  differ, the merge is ambiguous: the new  $S(f, C)$  is a lookup set with an invalid declaration set and the union of the subobject sets. In subsequent merges, an invalid declaration set is considered different from any other.
  - (6.3) — Otherwise, the new  $S(f, C)$  is a lookup set with the shared set of declarations and the union of the subobject sets.
- 7 The result of name lookup for **f** in **C** is the declaration set of  $S(f, C)$ . If it is an invalid set, the program is ill-formed. [ *Example:*

```

struct A { int x; }; // S(x,A) = { { A::x }, { A } }
struct B { float x; }; // S(x,B) = { { B::x }, { B } }
struct C: public A, public B { }; // S(x,C) = { invalid, { A in C, B in C } }
struct D: public virtual C { }; // S(x,D) = S(x,C)
struct E: public virtual C { char x; }; // S(x,E) = { { E::x }, { E } }
struct F: public D, public E { }; // S(x,F) = S(x,E)

int main() {
 F f;
 f.x = 0; // OK, lookup finds E::x
}

```

$S(x, F)$  is unambiguous because the **A** and **B** base class subobjects of **D** are also base class subobjects of **E**, so  $S(x, D)$  is discarded in the first merge step. — *end example*]

- 8 If the name of an overloaded function is unambiguously found, overload resolution (16.3) also takes place before access control. Ambiguities can often be resolved by qualifying a name with its class name. [ *Example:*

```

struct A {
 int f();
};

struct B {
 int f();
};

struct C : A, B {
 int f() { return A::f() + B::f(); }
};

```

— *end example*]

- 9 [ *Note:* A static member, a nested type or an enumerator defined in a base class **T** can unambiguously be found even if an object has more than one base class subobject of type **T**. Two base class subobjects share the non-static member subobjects of their common virtual base classes. — *end note* ] [ *Example:*

```

struct V {
 int v;
};

struct A {
 int a;
 static int s;
 enum { e };
};

struct B : A, virtual V { };

```

```

struct C : A, virtual V { };
struct D : B, C { };

void f(D* pd) {
 pd->v++; // OK: only one v (virtual)
 pd->s++; // OK: only one s (static)
 int i = pd->e; // OK: only one e (enumerator)
 pd->a++; // error, ambiguous: two as in D
}

```

— end example]

- <sup>10</sup> [Note: When virtual base classes are used, a hidden declaration can be reached along a path through the subobject lattice that does not pass through the hiding declaration. This is not an ambiguity. The identical use with non-virtual base classes is an ambiguity; in that case there is no unique instance of the name that hides all the others. — end note] [Example:

```

struct V { int f(); int x; };
struct W { int g(); int y; };
struct B : virtual V, W {
 int f(); int x;
 int g(); int y;
};
struct C : virtual V, W { };

struct D : B, C { void glorp(); };

```




Figure 6 — Name lookup

The names declared in V and the left-hand instance of W are hidden by those in B, but the names declared in the right-hand instance of W are not hidden at all.

```

void D::glorp() {
 x++; // OK: B::x hides V::x
 f(); // OK: B::f() hides V::f()
 y++; // error: B::y and C's W::y
 g(); // error: B::g() and C's W::g()
}

```

— end example]

- <sup>11</sup> An explicit or implicit conversion from a pointer to or an expression designating an object of a derived class to a pointer or reference to one of its base classes shall unambiguously refer to a unique object representing the base class. [Example:

```

struct V { };
struct A { };
struct B : A, virtual V { };
struct C : A, virtual V { };

```

```

struct D : B, C { };

void g() {
 D d;
 B* pb = &d;
 A* pa = &d; // error, ambiguous: C's A or B's A?
 V* pv = &d; // OK: only one V subobject
}

```

— end example]

- <sup>12</sup> [Note: Even if the result of name lookup is unambiguous, use of a name found in multiple subobjects might still be ambiguous (7.12, 8.2.5, 14.2). — end note] [Example:

```

struct B1 {
 void f();
 static void f(int);
 int i;
};
struct B2 {
 void f(double);
};
struct I1: B1 { };
struct I2: B1 { };

struct D: I1, I2, B2 {
 using B1::f;
 using B2::f;
 void g() {
 f(); // Ambiguous conversion of this
 f(0); // Unambiguous (static)
 f(0.0); // Unambiguous (only one B2)
 int B1::* mpB1 = &D::i; // Unambiguous
 int D::* mpD = &D::i; // Ambiguous conversion
 }
};

```

— end example]

### 13.3 Virtual functions

[class.virtual]

- <sup>1</sup> [Note: Virtual functions support dynamic binding and object-oriented programming. — end note] A class that declares or inherits a virtual function is called a *polymorphic class*.
- <sup>2</sup> If a virtual member function **vf** is declared in a class **Base** and in a class **Derived**, derived directly or indirectly from **Base**, a member function **vf** with the same name, parameter-type-list (11.3.5), cv-qualification, and ref-qualifier (or absence of same) as **Base::vf** is declared, then **Derived::vf** is also virtual (whether or not it is so declared) and it *overrides*<sup>111</sup> **Base::vf**. For convenience we say that any virtual function overrides itself. A virtual member function **C::vf** of a class object **S** is a *final overrider* unless the most derived class (4.5) of which **S** is a base class subobject (if any) declares or inherits another member function that overrides **vf**. In a derived class, if a virtual member function of a base class subobject has more than one final overrider the program is ill-formed. [Example:

```

struct A {
 virtual void f();
}

```

<sup>111</sup> A function with the same name but a different parameter list (Clause 16) as a virtual function is not necessarily virtual and does not override. The use of the **virtual** specifier in the declaration of an overriding function is legal but redundant (has empty semantics). Access control (Clause 14) is not considered in determining overriding.

```

};
struct B : virtual A {
 virtual void f();
};
struct C : B , virtual A {
 using A::f;
};

void foo() {
 C c;
 c.f(); // calls B::f, the final override
 c.C::f(); // calls A::f because of the using-declaration
}

```

— end example]

[Example:

```

struct A { virtual void f(); };
struct B : A { };
struct C : A { void f(); };
struct D : B, C { }; // OK: A::f and C::f are the final overrides
 // for the B and C subobjects, respectively

```

— end example]

- <sup>3</sup> [Note: A virtual member function does not have to be visible to be overridden, for example,

```

struct B {
 virtual void f();
};
struct D : B {
 void f(int);
};
struct D2 : D {
 void f();
};

```

the function `f(int)` in class `D` hides the virtual function `f()` in its base class `B`; `D::f(int)` is not a virtual function. However, `f()` declared in class `D2` has the same name and the same parameter list as `B::f()`, and therefore is a virtual function that overrides the function `B::f()` even though `B::f()` is not visible in class `D2`. — end note]

- <sup>4</sup> If a virtual function `f` in some class `B` is marked with the *virt-specifier* `final` and in a class `D` derived from `B` a function `D::f` overrides `B::f`, the program is ill-formed. [Example:

```

struct B {
 virtual void f() const final;
};

struct D : B {
 void f() const; // error: D::f attempts to override final B::f
};

```

— end example]

- <sup>5</sup> If a virtual function is marked with the *virt-specifier* `override` and does not override a member function of a base class, the program is ill-formed. [Example:

```

struct B {
 virtual void f(int);
};

```

```
};

struct D : B {
 virtual void f(long) override; // error: wrong signature overriding B::f
 virtual void f(int) override; // OK
};
```

— end example]

- 6 Even though destructors are not inherited, a destructor in a derived class overrides a base class destructor declared virtual; see 15.4 and 15.5.
- 7 The return type of an overriding function shall be either identical to the return type of the overridden function or *covariant* with the classes of the functions. If a function `D::f` overrides a function `B::f`, the return types of the functions are covariant if they satisfy the following criteria:
- (7.1) — both are pointers to classes, both are lvalue references to classes, or both are rvalue references to classes<sup>112</sup>
  - (7.2) — the class in the return type of `B::f` is the same class as the class in the return type of `D::f`, or is an unambiguous and accessible direct or indirect base class of the class in the return type of `D::f`
  - (7.3) — both pointers or references have the same cv-qualification and the class type in the return type of `D::f` has the same cv-qualification as or less cv-qualification than the class type in the return type of `B::f`.
- 8 If the class type in the covariant return type of `D::f` differs from that of `B::f`, the class type in the return type of `D::f` shall be complete at the point of declaration of `D::f` or shall be the class type `D`. When the overriding function is called as the final overrider of the overridden function, its result is converted to the type returned by the (statically chosen) overridden function (8.2.2). [Example:

```
class B { };
class D : private B { friend class Derived; };
struct Base {
 virtual void vf1();
 virtual void vf2();
 virtual void vf3();
 virtual B* vf4();
 virtual B* vf5();
 void f();
};

struct No_good : public Base {
 D* vf4(); // error: B (base class of D) inaccessible
};

class A;
struct Derived : public Base {
 void vf1(); // virtual and overrides Base::vf1()
 void vf2(int); // not virtual, hides Base::vf2()
 char vf3(); // error: invalid difference in return type only
 D* vf4(); // OK: returns pointer to derived class
 A* vf5(); // error: returns pointer to incomplete class
 void f();
};

void g() {
 Derived d;
```

112) Multi-level pointers to classes or references to multi-level pointers to classes are not allowed.

```

Base* bp = &d; // standard conversion:
 // Derived* to Base*
bp->vf1(); // calls Derived::vf1()
bp->vf2(); // calls Base::vf2()
bp->f(); // calls Base::f() (not virtual)
B* p = bp->vf4(); // calls Derived::pf() and converts the
 // result to B*

Derived* dp = &d;
D* q = dp->vf4(); // calls Derived::pf() and does not
 // convert the result to B*
dp->vf2(); // ill-formed: argument mismatch
}

```

— end example]

- <sup>9</sup> [Note: The interpretation of the call of a virtual function depends on the type of the object for which it is called (the dynamic type), whereas the interpretation of a call of a non-virtual member function depends only on the type of the pointer or reference denoting that object (the static type) (8.2.2). — end note]
- <sup>10</sup> [Note: The **virtual** specifier implies membership, so a virtual function cannot be a non-member (10.1.2) function. Nor can a virtual function be a static member, since a virtual function call relies on a specific object for determining which function to invoke. A virtual function declared in one class can be declared a **friend** in another class. — end note]
- <sup>11</sup> A virtual function declared in a class shall be defined, or declared pure (13.4) in that class, or both; no diagnostic is required (6.2).
- <sup>12</sup> [Example: Here are some uses of virtual functions with multiple base classes:

```

struct A {
 virtual void f();
};

struct B1 : A { // note non-virtual derivation
 void f();
};

struct B2 : A {
 void f();
};

struct D : B1, B2 { // D has two separate A subobjects
};

void foo() {
 D d;
 // A* ap = &d; // would be ill-formed: ambiguous
 B1* b1p = &d;
 A* ap = b1p;
 D* dp = &d;
 ap->f(); // calls D::B1::f
 dp->f(); // ill-formed: ambiguous
}

```

In class D above there are two occurrences of class A and hence two occurrences of the virtual member function A::f. The final overrider of B1::A::f is B1::f and the final overrider of B2::A::f is B2::f. — end example]

- <sup>13</sup> [Example: The following example shows a function that does not have a unique final overrider:



```

struct A {
 virtual void f();
};

struct VB1 : virtual A { // note virtual derivation
 void f();
};

struct VB2 : virtual A {
 void f();
};

struct Error : VB1, VB2 { // ill-formed
};

struct Okay : VB1, VB2 {
 void f();
};

```

Both `VB1::f` and `VB2::f` override `A::f` but there is no overrider of both of them in class `Error`. This example is therefore ill-formed. Class `Okay` is well formed, however, because `Okay::f` is a final overrider. — *end example*]

- <sup>14</sup> [*Example*: The following example uses the well-formed classes from above.

```

struct VB1a : virtual A { // does not declare f
};

struct Da : VB1a, VB2 {
};

void foe() {
 VB1a* vb1ap = new Da;
 vb1ap->f(); // calls VB2::f
}

```

— *end example*]

- <sup>15</sup> Explicit qualification with the scope operator (8.1) suppresses the virtual call mechanism. [*Example*:

```

class B { public: virtual void f(); };
class D : public B { public: void f(); };

void D::f() { /* ... */ B::f(); }

```

Here, the function call in `D::f` really does call `B::f` and not `D::f`. — *end example*]

- <sup>16</sup> A function with a deleted definition (11.4) shall not override a function that does not have a deleted definition. Likewise, a function that does not have a deleted definition shall not override a function with a deleted definition.

## 13.4 Abstract classes

[**class.abstract**]

- <sup>1</sup> [*Note*: The abstract class mechanism supports the notion of a general concept, such as a **shape**, of which only more concrete variants, such as **circle** and **square**, can actually be used. An abstract class can also be used to define an interface for which derived classes provide a variety of implementations. — *end note*]
- <sup>2</sup> An *abstract class* is a class that can be used only as a base class of some other class; no objects of an abstract class can be created except as subobjects of a class derived from it. A class is abstract if it has at least one *pure virtual function*. [*Note*: Such a function might be inherited: see below. — *end note*] A virtual

function is specified *pure* by using a *pure-specifier* (12.2) in the function declaration in the class definition. A pure virtual function need be defined only if called with, or as if with (15.4), the *qualified-id* syntax (8.1).  
[Example:

```
class point { /* ... */ };
class shape { // abstract class
 point center;
public:
 point where() { return center; }
 void move(point p) { center=p; draw(); }
 virtual void rotate(int) = 0; // pure virtual
 virtual void draw() = 0; // pure virtual
};
```

— end example] [Note: A function declaration cannot provide both a *pure-specifier* and a definition — end note] [Example:

```
struct C {
 virtual void f() = 0 { }; // ill-formed
};
```

— end example]

- <sup>3</sup> An abstract class shall not be used as a parameter type, as a function return type, or as the type of an explicit conversion. Pointers and references to an abstract class can be declared. [Example:

```
shape x; // error: object of abstract class
shape* p; // OK
shape f(); // error
void g(shape); // error
shape& h(shape&); // OK
```

— end example]

- <sup>4</sup> A class is abstract if it contains or inherits at least one pure virtual function for which the final overrider is pure virtual. [Example:

```
class ab_circle : public shape {
 int radius;
public:
 void rotate(int) { }
 // ab_circle::draw() is a pure virtual
};
```

Since `shape::draw()` is a pure virtual function `ab_circle::draw()` is a pure virtual by default. The alternative declaration,

```
class circle : public shape {
 int radius;
public:
 void rotate(int) { }
 void draw(); // a definition is required somewhere
};
```

would make class `circle` non-abstract and a definition of `circle::draw()` must be provided. — end example]

- <sup>5</sup> [Note: An abstract class can be derived from a class that is not abstract, and a pure virtual function may override a virtual function which is not pure. — end note]
- <sup>6</sup> Member functions can be called from a constructor (or destructor) of an abstract class; the effect of making a virtual call (13.3) to a pure virtual function directly or indirectly for the object being created (or destroyed)

from such a constructor (or destructor) is undefined.

# 14 Member access control [class.access]

<sup>1</sup> A member of a class can be

- (1.1) — **private**; that is, its name can be used only by members and friends of the class in which it is declared.
- (1.2) — **protected**; that is, its name can be used only by members and friends of the class in which it is declared, by classes derived from that class, and by their friends (see 14.4).
- (1.3) — **public**; that is, its name can be used anywhere without access restriction.

<sup>2</sup> A member of a class can also access all the names to which the class has access. A local class of a member function may access the same names that the member function itself may access.<sup>113</sup>

<sup>3</sup> Members of a class defined with the keyword **class** are **private** by default. Members of a class defined with the keywords **struct** or **union** are **public** by default. [*Example:*

```
class X {
 int a; // X::a is private by default
};

struct S {
 int a; // S::a is public by default
};

— end example]
```

<sup>4</sup> Access control is applied uniformly to all names, whether the names are referred to from declarations or expressions. [*Note:* Access control applies to names nominated by **friend** declarations (14.3) and *using-declarations* (10.3.3). — end note] In the case of overloaded function names, access control is applied to the function selected by overload resolution. [*Note:* Because access control applies to names, if access control is applied to a typedef name, only the accessibility of the typedef name itself is considered. The accessibility of the entity referred to by the typedef is not considered. For example,

```
class A {
 class B { };
public:
 typedef B BB;
};

void f() {
 A::BB x; // OK, typedef name A::BB is public
 A::B y; // access error, A::B is private
}

— end note]
```

<sup>5</sup> It should be noted that it is *access* to members and base classes that is controlled, not their *visibility*. Names of members are still visible, and implicit conversions to base classes are still considered, when those members and base classes are inaccessible. The interpretation of a given construct is established without regard to access control. If the interpretation established makes use of inaccessible member names or base classes, the construct is ill-formed.

<sup>6</sup> All access controls in Clause 14 affect the ability to access a class member name from the declaration of a particular entity, including parts of the declaration preceding the name of the entity being declared and, if

<sup>113</sup>) Access permissions are thus transitive and cumulative to nested and local classes.

the entity is a class, the definitions of members of the class appearing outside the class's *member-specification*.  
 [ *Note*: This access also applies to implicit references to constructors, conversion functions, and destructors.  
 — *end note* ]

<sup>7</sup> [ *Example*:

```
class A {
 typedef int I; // private member
 I f();
 friend I g(I);
 static I x;
 template<int> struct Q;
 template<int> friend struct R;
protected:
 struct B { };
};

A::I A::f() { return 0; }
A::I g(A::I p = A::x);
A::I g(A::I p) { return 0; }
A::I A::x = 0;
template<A::I> struct A::Q { };
template<A::I> struct R { };

struct D: A::B, A { };
```

Here, all the uses of `A::I` are well-formed because `A::f`, `A::x`, and `A::Q` are members of class `A` and `g` and `R` are friends of class `A`. This implies, for example, that access checking on the first use of `A::I` must be deferred until it is determined that this use of `A::I` is as the return type of a member of class `A`. Similarly, the use of `A::B` as a *base-specifier* is well-formed because `D` is derived from `A`, so checking of *base-specifiers* must be deferred until the entire *base-specifier-list* has been seen. — *end example* ]

- <sup>8</sup> The names in a default argument (11.3.6) are bound at the point of declaration, and access is checked at that point rather than at any points of use of the default argument. Access checking for default arguments in function templates and in member functions of class templates is performed as described in 17.7.1.
- <sup>9</sup> The names in a default *template-argument* (17.1) have their access checked in the context in which they appear rather than at any points of use of the default *template-argument*. [ *Example*:

```
class B { };
template <class T> class C {
protected:
 typedef T TT;
};

template <class U, class V = typename U::TT>
class D : public U { };

D <C >* d; // access error, C::TT is protected
— end example]
```

## 14.1 Access specifiers

[class.access.spec]

- <sup>1</sup> Member declarations can be labeled by an *access-specifier* (Clause 13):

*access-specifier* : *member-specification*<sub>opt</sub>

An *access-specifier* specifies the access rules for members following it until the end of the class or until another *access-specifier* is encountered. [ *Example*:

```

class X {
 int a; // X::a is private by default: class used
public:
 int b; // X::b is public
 int c; // X::c is public
};

```

— end example]

- <sup>2</sup> Any number of access specifiers is allowed and no particular order is required. [ *Example:*

```

struct S {
 int a; // S::a is public by default: struct used
protected:
 int b; // S::b is protected
private:
 int c; // S::c is private
public:
 int d; // S::d is public
};

```

— end example]

- <sup>3</sup> [ *Note:* The effect of access control on the order of allocation of data members is described in 12.2. — end note]

- <sup>4</sup> When a member is redeclared within its class definition, the access specified at its redeclaration shall be the same as at its initial declaration. [ *Example:*

```

struct S {
 class A;
 enum E : int;
private:
 class A { }; // error: cannot change access
 enum E : int { e0 }; // error: cannot change access
};

```

— end example]

- <sup>5</sup> [ *Note:* In a derived class, the lookup of a base class name will find the injected-class-name instead of the name of the base class in the scope in which it was declared. The injected-class-name might be less accessible than the name of the base class in the scope in which it was declared. — end note]

[ *Example:*

```

class A { };
class B : private A { };
class C : public B {
 A* p; // error: injected-class-name A is inaccessible
 ::A* q; // OK
};

```

— end example]

## 14.2 Accessibility of base classes and base class members [class.access.base]

- <sup>1</sup> If a class is declared to be a base class (Clause 13) for another class using the **public** access specifier, the **public** members of the base class are accessible as **public** members of the derived class and **protected** members of the base class are accessible as **protected** members of the derived class. If a class is declared to be a base class for another class using the **protected** access specifier, the **public** and **protected** members of the base class are accessible as **protected** members of the derived class. If a class is declared to be a base

class for another class using the **private** access specifier, the **public** and **protected** members of the base class are accessible as **private** members of the derived class<sup>114</sup>.

- <sup>2</sup> In the absence of an *access-specifier* for a base class, **public** is assumed when the derived class is defined with the *class-key struct* and **private** is assumed when the class is defined with the *class-key class*. [ *Example:*

```
class B { /* ... */ };
class D1 : private B { /* ... */ };
class D2 : public B { /* ... */ };
class D3 : B { /* ... */ }; // B private by default
struct D4 : public B { /* ... */ };
struct D5 : private B { /* ... */ };
struct D6 : B { /* ... */ }; // B public by default
class D7 : protected B { /* ... */ };
struct D8 : protected B { /* ... */ };
```

Here B is a public base of D2, D4, and D6, a private base of D1, D3, and D5, and a protected base of D7 and D8. — *end example*]

- <sup>3</sup> [ *Note:* A member of a private base class might be inaccessible as an inherited member name, but accessible directly. Because of the rules on pointer conversions (7.11) and explicit casts (8.4), a conversion from a pointer to a derived class to a pointer to an inaccessible base class might be ill-formed if an implicit conversion is used, but well-formed if an explicit cast is used. For example,

```
class B {
public:
 int mi; // non-static member
 static int si; // static member
};
class D : private B {
};
class DD : public D {
 void f();
};

void DD::f() {
 mi = 3; // error: mi is private in D
 si = 3; // error: si is private in D
 ::B b;
 b.mi = 3; // OK (b.mi is different from this->mi)
 b.si = 3; // OK (b.si is different from this->si)
 ::B::si = 3; // OK
 ::B* bp1 = this; // error: B is a private base class
 ::B* bp2 = (::B*)this; // OK with cast
 bp2->mi = 3; // OK: access through a pointer to B.
}
```

— *end note*]

- <sup>4</sup> A base class B of N is *accessible* at R, if
- (4.1) — an invented public member of B would be a public member of N, or
  - (4.2) — R occurs in a member or friend of class N, and an invented public member of B would be a private or protected member of N, or
  - (4.3) — R occurs in a member or friend of a class P derived from N, and an invented public member of B would

<sup>114</sup> As specified previously in Clause 14, private members of a base class remain inaccessible even to derived classes unless **friend** declarations within the base class definition are used to grant access explicitly.

be a private or protected member of P, or

- (4.4) — there exists a class S such that B is a base class of S accessible at R and S is a base class of N accessible at R.

[Example:

```
class B {
public:
 int m;
};

class S: private B {
 friend class N;
};

class N: private S {
 void f() {
 B* p = this; // OK because class S satisfies the fourth condition above: B is a base class of N
 // accessible in f() because B is an accessible base class of S and S is an accessible
 // base class of N.
 }
};
```

— end example]

- <sup>5</sup> If a base class is accessible, one can implicitly convert a pointer to a derived class to a pointer to that base class (7.11, 7.12). [Note: It follows that members and friends of a class X can implicitly convert an X\* to a pointer to a private or protected immediate base class of X. — end note] The access to a member is affected by the class in which the member is named. This naming class is the class in which the member name was looked up and found. [Note: This class can be explicit, e.g., when a *qualified-id* is used, or implicit, e.g., when a class member access operator (8.2.5) is used (including cases where an implicit “this->” is added). If both a class member access operator and a *qualified-id* are used to name the member (as in p->T::m), the class naming the member is the class denoted by the *nested-name-specifier* of the *qualified-id* (that is, T). — end note] A member m is accessible at the point R when named in class N if

- (5.1) — m as a member of N is public, or
- (5.2) — m as a member of N is private, and R occurs in a member or friend of class N, or
- (5.3) — m as a member of N is protected, and R occurs in a member or friend of class N, or in a member of a class P derived from N, where m as a member of P is public, private, or protected, or
- (5.4) — there exists a base class B of N that is accessible at R, and m is accessible at R when named in class B.

[Example:

```
class B;
class A {
private:
 int i;
 friend void f(B*);
};
class B : public A { };
void f(B* p) {
 p->i = 1; // OK: B* can be implicitly converted to A*, and f has access to i in A
}
```

— end example]

- <sup>6</sup> If a class member access operator, including an implicit “this->”, is used to access a non-static data member



or non-static member function, the reference is ill-formed if the left operand (considered as a pointer in the “.” operator case) cannot be implicitly converted to a pointer to the naming class of the right operand. [ *Note*: This requirement is in addition to the requirement that the member be accessible as named. — *end note* ]

### 14.3 Friends

[**class.friend**]

- <sup>1</sup> A friend of a class is a function or class that is given permission to use the private and protected member names from the class. A class specifies its friends, if any, by way of friend declarations. Such declarations give special access rights to the friends, but they do not make the nominated friends members of the befriending class. [ *Example*: The following example illustrates the differences between members and friends:

```
class X {
 int a;
 friend void friend_set(X*, int);
public:
 void member_set(int);
};

void friend_set(X* p, int i) { p->a = i; }
void X::member_set(int i) { a = i; }

void f() {
 X obj;
 friend_set(&obj, 10);
 obj.member_set(10);
}
```

— *end example*]

- <sup>2</sup> Declaring a class to be a friend implies that the names of private and protected members from the class granting friendship can be accessed in the *base-specifiers* and member declarations of the befriended class. [ *Example*:

```
class A {
 class B { };
 friend class X;
};

struct X : A::B {
 A::B mx;
 class Y {
 A::B my;
 };
};
```

// OK: A::B accessible to friend  
// OK: A::B accessible to member of friend  
// OK: A::B accessible to nested member of friend

— *end example*] [ *Example*:

```
class X {
 enum { a=100 };
 friend class Y;
};

class Y {
 int v[X::a];
};

class Z {
 int v[X::a];
};
```

// OK, Y is a friend of X  
// error: X::a is private

```
};
```

— end example]

A class shall not be defined in a friend declaration. [ *Example:*

```
class A {
 friend class B { }; // error: cannot define class in friend declaration
};
```

— end example]

- <sup>3</sup> A **friend** declaration that does not declare a function shall have one of the following forms:

```
friend elaborated-type-specifier ;
friend simple-type-specifier ;
friend typename-specifier ;
```

[ *Note:* A **friend** declaration may be the *declaration* in a *template-declaration* (Clause 17, 17.5.4). — end note] If the type specifier in a **friend** declaration designates a (possibly cv-qualified) class type, that class is declared as a friend; otherwise, the **friend** declaration is ignored. [ *Example:*

```
class C;
typedef C Ct;

class X1 {
 friend C; // OK: class C is a friend
};

class X2 {
 friend Ct; // OK: class C is a friend
 friend D; // error: no type-name D in scope
 friend class D; // OK: elaborated-type-specifier declares new class
};

template <typename T> class R {
 friend T;
};

R<C> rc; // class C is a friend of R<C>
R<int> Ri; // OK: "friend int;" is ignored
```

— end example]

- <sup>4</sup> A function first declared in a friend declaration has the linkage of the namespace of which it is a member (6.5). Otherwise, the function retains its previous linkage (10.1.1).
- <sup>5</sup> When a **friend** declaration refers to an overloaded name or operator, only the function specified by the parameter types becomes a friend. A member function of a class X can be a friend of a class Y. [ *Example:*

```
class Y {
 friend char* X::foo(int);
 friend X::X(char); // constructors can be friends
 friend X::~X(); // destructors can be friends
};
```

— end example]

- <sup>6</sup> A function can be defined in a friend declaration of a class if and only if the class is a non-local class (12.4), the function name is unqualified, and the function has namespace scope. [ *Example:*

```
class M {
 friend void f() { } // definition of global f, a friend of M,
```

*// not the definition of a member function*

};

— end example]

- 7 Such a function is implicitly an inline function (10.1.6). A **friend** function defined in a class is in the (lexical) scope of the class in which it is defined. A friend function defined outside the class is not (6.4.1).
- 8 No *storage-class-specifier* shall appear in the *decl-specifier-seq* of a friend declaration.
- 9 A name nominated by a friend declaration shall be accessible in the scope of the class containing the friend declaration. The meaning of the friend declaration is the same whether the friend declaration appears in the **private**, **protected** or **public** (12.2) portion of the class *member-specification*.
- 10 Friendship is neither inherited nor transitive. [ *Example:*

```
class A {
 friend class B;
 int a;
};

class B {
 friend class C;
};

class C {
 void f(A* p) {
 p->a++;
 }
};

class D : public B {
 void f(A* p) {
 p->a++;
 }
};
```

*// error: C is not a friend of A despite being a friend of a friend*

*// error: D is not a friend of A despite being derived from a friend*

— end example]

- 11 If a friend declaration appears in a local class (12.4) and the name specified is an unqualified name, a prior declaration is looked up without considering scopes that are outside the innermost enclosing non-class scope. For a friend function declaration, if there is no prior declaration, the program is ill-formed. For a friend class declaration, if there is no prior declaration, the class that is specified belongs to the innermost enclosing non-class scope, but if it is subsequently referenced, its name is not found by name lookup until a matching declaration is provided in the innermost enclosing non-class scope. [ *Example:*

```
class X;
void a();
void f() {
 class Y;
 extern void b();
 class A {
 friend class X; // OK, but X is a local class, not ::X
 friend class Y; // OK
 friend class Z; // OK, introduces local class Z
 friend void a(); // error, ::a is not considered
 friend void b(); // OK
 friend void c(); // error
 };
```

```

 X* px; // OK, but ::X is found
 Z* pz; // error, no Z is found
}

```

— end example]

#### 14.4 Protected member access

[class.protected]

- <sup>1</sup> An additional access check beyond those described earlier in Clause 14 is applied when a non-static data member or non-static member function is a protected member of its naming class (14.2)<sup>115</sup> As described earlier, access to a protected member is granted because the reference occurs in a friend or member of some class C. If the access is to form a pointer to member (8.3.1), the *nested-name-specifier* shall denote C or a class derived from C. All other accesses involve a (possibly implicit) object expression (8.2.5). In this case, the class of the object expression shall be C or a class derived from C. [Example:

```

class B {
protected:
 int i;
 static int j;
};

class D1 : public B {
};

class D2 : public B {
 friend void fr(B*, D1*, D2*);
 void mem(B*, D1*);
};

void fr(B* pb, D1* p1, D2* p2) {
 pb->i = 1; // ill-formed
 p1->i = 2; // ill-formed
 p2->i = 3; // OK (access through a D2)
 p2->B::i = 4; // OK (access through a D2, even though naming class is B)
 int B::* pmi_B = &B::i; // ill-formed
 int B::* pmi_B2 = &D2::i; // OK (type of &D2::i is int B::*)
 B::j = 5; // ill-formed (not a friend of naming class B)
 D2::j = 6; // OK (because refers to static member)
}

void D2::mem(B* pb, D1* p1) {
 pb->i = 1; // ill-formed
 p1->i = 2; // ill-formed
 i = 3; // OK (access through this)
 B::i = 4; // OK (access through this, qualification ignored)
 int B::* pmi_B = &B::i; // ill-formed
 int B::* pmi_B2 = &D2::i; // OK
 j = 5; // OK (because j refers to static member)
 B::j = 6; // OK (because B::j refers to static member)
}

void g(B* pb, D1* p1, D2* p2) {
 pb->i = 1; // ill-formed
 p1->i = 2; // ill-formed
 p2->i = 3; // ill-formed
}

```

115) This additional check does not apply to other members, e.g., static data members or enumerator member constants.

```

}
— end example]

```

## 14.5 Access to virtual functions

[class.access.virt]

- <sup>1</sup> The access rules (Clause 14) for a virtual function are determined by its declaration and are not affected by the rules for a function that later overrides it. [*Example:*

```

class B {
public:
 virtual int f();
};

class D : public B {
private:
 int f();
};

void f() {
 D d;
 B* pb = &d;
 D* pd = &d;

 pb->f(); // OK: B::f() is public, D::f() is invoked
 pd->f(); // error: D::f() is private
}

```

— end example]

- <sup>2</sup> Access is checked at the call point using the type of the expression used to denote the object for which the member function is called (B\* in the example above). The access of the member function in the class in which it was defined (D in the example above) is in general not known.

## 14.6 Multiple access

[class.paths]

- <sup>1</sup> If a name can be reached by several paths through a multiple inheritance graph, the access is that of the path that gives most access. [*Example:*

```

class W { public: void f(); };
class A : private virtual W { };
class B : public virtual W { };
class C : public A, public B {
 void f() { W::f(); } // OK
};

```

Since W::f() is available to C::f() along the public path through B, access is allowed. — end example]

## 14.7 Nested classes

[class.access.nest]

- <sup>1</sup> A nested class is a member and as such has the same access rights as any other member. The members of an enclosing class have no special access to members of a nested class; the usual access rules (Clause 14) shall be obeyed. [*Example:*

```

class E {
 int x;
 class B { };

 class I {
 B b; // OK: E::I can access E::B
 };
};

```

```
 int y;
 void f(E* p, int i) {
 p->x = i; // OK: E::I can access E::x
 }
};

int g(I* p) {
 return p->y; // error: I::y is private
}
};
—end example]
```

# 15 Special member functions [special]

- <sup>1</sup> The default constructor (15.1), copy constructor and copy assignment operator (15.8), move constructor and move assignment operator (15.8), and destructor (15.4) are *special member functions*. [Note: The implementation will implicitly declare these member functions for some class types when the program does not explicitly declare them. The implementation will implicitly define them if they are odr-used (6.2). See 15.1, 15.4 and 15.8. — end note] An implicitly-declared special member function is declared at the closing } of the *class-specifier*. Programs shall not define implicitly-declared special member functions.
- <sup>2</sup> Programs may explicitly refer to implicitly-declared special member functions. [Example: A program may explicitly call, take the address of, or form a pointer to member to an implicitly-declared special member function.

```

struct A { }; // implicitly declared A::operator=
struct B : A {
 B& operator=(const B &);
};
B& B::operator=(const B& s) {
 this->A::operator=(s); // well formed
 return *this;
}

```

— end example]

- <sup>3</sup> [Note: The special member functions affect the way objects of class type are created, copied, moved, and destroyed, and how values can be converted to values of other types. Often such special member functions are called implicitly. — end note]
- <sup>4</sup> Special member functions obey the usual access rules (Clause 14). [Example: Declaring a constructor **protected** ensures that only derived classes and friends can create objects using it. — end example]
- <sup>5</sup> For a class, its non-static data members, its non-virtual direct base classes, and, if the class is not abstract (13.4), its virtual base classes are called its *potentially constructed subobjects*.

## 15.1 Constructors [class.ctor]

- <sup>1</sup> Constructors do not have names. In a declaration of a constructor, the *declarator* is a function declarator (11.3.5) of the form

*ptr-declarator* ( *parameter-declaration-clause* ) *noexcept-specifier<sub>opt</sub>* *attribute-specifier-seq<sub>opt</sub>*

where the *ptr-declarator* consists solely of an *id-expression*, an optional *attribute-specifier-seq*, and optional surrounding parentheses, and the *id-expression* has one of the following forms:

- (1.1) — in a *member-declaration* that belongs to the *member-specification* of a class but is not a friend declaration (14.3), the *id-expression* is the injected-class-name (Clause 12) of the immediately-enclosing class;
- (1.2) — in a *member-declaration* that belongs to the *member-specification* of a class template but is not a friend declaration, the *id-expression* is a *class-name* that names the current instantiation (17.6.2.1) of the immediately-enclosing class template; or
- (1.3) — in a declaration at namespace scope or in a friend declaration, the *id-expression* is a *qualified-id* that names a constructor (6.4.3.1).

The *class-name* shall not be a *typedef-name*. In a constructor declaration, each *decl-specifier* in the optional *decl-specifier-seq* shall be **friend**, **inline**, **explicit**, or **constexpr**. [ *Example*:

```
struct S {
 S(); // declares the constructor
};

S::S() { } // defines the constructor
— end example]
```

- 2 A constructor is used to initialize objects of its class type. Because constructors do not have names, they are never found during name lookup; however an explicit type conversion using the functional notation (8.2.3) will cause a constructor to be called to initialize an object. [ *Note*: For initialization of objects of class type see 15.6. — *end note*]
- 3 A constructor can be invoked for a **const**, **volatile** or **const volatile** object. **const** and **volatile** semantics (10.1.7.1) are not applied on an object under construction. They come into effect when the constructor for the most derived object (4.5) ends.
- 4 A *default* constructor for a class **X** is a constructor of class **X** for which each parameter that is not a function parameter pack has a default argument (including the case of a constructor with no parameters). If there is no user-declared constructor for class **X**, a non-explicit constructor having no parameters is implicitly declared as defaulted (11.4). An implicitly-declared default constructor is an **inline public** member of its class.
- 5 A defaulted default constructor for class **X** is defined as deleted if:
  - (5.1) — **X** is a union that has a variant member with a non-trivial default constructor and no variant member of **X** has a default member initializer,
  - (5.2) — **X** is a non-union class that has a variant member **M** with a non-trivial default constructor and no variant member of the anonymous union containing **M** has a default member initializer,
  - (5.3) — any non-static data member with no default member initializer (12.2) is of reference type,
  - (5.4) — any non-variant non-static data member of const-qualified type (or array thereof) with no *brace-or-equal-initializer* does not have a user-provided default constructor,
  - (5.5) — **X** is a union and all of its variant members are of const-qualified type (or array thereof),
  - (5.6) — **X** is a non-union class and all members of any anonymous union member are of const-qualified type (or array thereof),
  - (5.7) — any potentially constructed subobject, except for a non-static data member with a *brace-or-equal-initializer*, has class type **M** (or array thereof) and either **M** has no default constructor or overload resolution (16.3) as applied to find **M**'s corresponding constructor results in an ambiguity or in a function that is deleted or inaccessible from the defaulted default constructor, or
  - (5.8) — any potentially constructed subobject has a type with a destructor that is deleted or inaccessible from the defaulted default constructor.
- 6 A default constructor is *trivial* if it is not user-provided and if:
  - (6.1) — its class has no virtual functions (13.3) and no virtual base classes (13.1), and
  - (6.2) — no non-static data member of its class has a default member initializer (12.2), and
  - (6.3) — all the direct base classes of its class have trivial default constructors, and
  - (6.4) — for all the non-static data members of its class that are of class type (or array thereof), each such class has a trivial default constructor.

Otherwise, the default constructor is *non-trivial*.



- <sup>7</sup> A default constructor that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used (6.2) to create an object of its class type (4.5) or when it is explicitly defaulted after its first declaration. The implicitly-defined default constructor performs the set of initializations of the class that would be performed by a user-written default constructor for that class with no *ctor-initializer* (15.6.2) and an empty *compound-statement*. If that user-written default constructor would be ill-formed, the program is ill-formed. If that user-written default constructor would satisfy the requirements of a constexpr constructor (10.1.5), the implicitly-defined default constructor is **constexpr**. Before the defaulted default constructor for a class is implicitly defined, all the non-user-provided default constructors for its base classes and its non-static data members shall have been implicitly defined. [ *Note*: An implicitly-declared default constructor has an exception specification (18.4). An explicitly-defaulted definition might have an implicit exception specification, see 11.4. — *end note* ]
- <sup>8</sup> Default constructors are called implicitly to create class objects of static, thread, or automatic storage duration (6.7.1, 6.7.2, 6.7.3) defined without an initializer (11.6), are called to create class objects of dynamic storage duration (6.7.4) created by a *new-expression* in which the *new-initializer* is omitted (8.3.4), or are called when the explicit type conversion syntax (8.2.3) is used. A program is ill-formed if the default constructor for an object is implicitly used and the constructor is not accessible (Clause 14).
- <sup>9</sup> [ *Note*: 15.6.2 describes the order in which constructors for base classes and non-static data members are called and describes how arguments can be specified for the calls to these constructors. — *end note* ]
- <sup>10</sup> A **return** statement in the body of a constructor shall not specify a return value. The address of a constructor shall not be taken.
- <sup>11</sup> A functional notation type conversion (8.2.3) can be used to create new objects of its type. [ *Note*: The syntax looks like an explicit call of the constructor. — *end note* ] [ *Example*:

```
complex zz = complex(1,2.3);
cprint(complex(7.8,1.2));
```

— *end example* ]

- <sup>12</sup> An object created in this way is unnamed. [ *Note*: 15.2 describes the lifetime of temporary objects. — *end note* ] [ *Note*: Explicit constructor calls do not yield lvalues, see 6.10. — *end note* ]
- <sup>13</sup> [ *Note*: Some language constructs have special semantics when used during construction; see 15.6.2 and 15.7. — *end note* ]
- <sup>14</sup> During the construction of an object, if the value of the object or any of its subobjects is accessed through a glvalue that is not obtained, directly or indirectly, from the constructor's **this** pointer, the value of the object or subobject thus obtained is unspecified. [ *Example*:

```
struct C;
void no_opt(C*);

struct C {
 int c;
 C() : c(0) { no_opt(this); }
};

const C cobj;

void no_opt(C* cptr) {
 int i = cobj.c * 100; // value of cobj.c is unspecified
 cptr->c = 1;
 cout << cobj.c * 100 // value of cobj.c is unspecified
 << '\n';
}
```

```

extern struct D d;
struct D {
 D(int a) : a(a), b(d.a) {}
 int a, b;
};
D d = D(1); // value of d.b is unspecified
— end example]

```

## 15.2 Temporary objects

[class.temporary]

<sup>1</sup> Temporary objects are created

- (1.1) — when a prvalue is materialized so that it can be used as a glvalue (7.4),
- (1.2) — when needed by the implementation to pass or return an object of trivially-copyable type (see below), and
- (1.3) — when throwing an exception (18.1). [ *Note*: The lifetime of exception objects is described in 18.1. — *end note* ]

Even when the creation of the temporary object is unevaluated (Clause 8), all the semantic restrictions shall be respected as if the temporary object had been created and later destroyed. [ *Note*: This includes accessibility (Clause 14) and whether it is deleted, for the constructor selected and for the destructor. However, in the special case of the operand of a *decltype-specifier* (8.2.2), no temporary is introduced, so the foregoing does not apply to such a prvalue. — *end note* ]

<sup>2</sup> The materialization of a temporary object is generally delayed as long as possible in order to avoid creating unnecessary temporary objects. [ *Note*: Temporary objects are materialized:

- (2.1) — when binding a reference to a prvalue (11.6.3, 8.2.3, 8.2.7, 8.2.9, 8.2.11, 8.4),
- (2.2) — when performing member access on a class prvalue (8.2.5, 8.5),
- (2.3) — when performing an array-to-pointer conversion or subscripting on an array prvalue (7.2, 8.2.1),
- (2.4) — when initializing an object of type `std::initializer_list<T>` from a *braced-init-list* (11.6.4),
- (2.5) — for certain unevaluated operands (8.2.8, 8.3.3), and
- (2.6) — when a prvalue appears as a discarded-value expression (Clause 8).

— *end note* ] [ *Example*: Consider the following code:

```

class X {
public:
 X(int);
 X(const X&);
 X& operator=(const X&);
 ~X();
};

class Y {
public:
 Y(int);
 Y(Y&&);
 ~Y();
};

X f(X);
Y g(Y);

```

```

void h() {
 X a(1);
 X b = f(X(2));
 Y c = g(Y(3));
 a = f(a);
}

```

`X(2)` is constructed in the space used to hold `f()`'s argument and `Y(3)` is constructed in the space used to hold `g()`'s argument. Likewise, `f()`'s result is constructed directly in `b` and `g()`'s result is constructed directly in `c`. On the other hand, the expression `a = f(a)` requires a temporary for the result of `f(a)`, which is materialized so that the reference parameter of `A::operator=(const A&)` can bind to it. — *end example*]

- 3 When an object of class type `X` is passed to or returned from a function, if each copy constructor, move constructor, and destructor of `X` is either trivial or deleted, and `X` has at least one non-deleted copy or move constructor, implementations are permitted to create a temporary object to hold the function parameter or result object. The temporary object is constructed from the function argument or return value, respectively, and the function's parameter or return object is initialized as if by using the non-deleted trivial constructor to copy the temporary (even if that constructor is inaccessible or would not be selected by overload resolution to perform a copy or move of the object). [ *Note*: This latitude is granted to allow objects of class type to be passed to or returned from functions in registers. — *end note* ]
- 4 When an implementation introduces a temporary object of a class that has a non-trivial constructor (15.1, 15.8), it shall ensure that a constructor is called for the temporary object. Similarly, the destructor shall be called for a temporary with a non-trivial destructor (15.4). Temporary objects are destroyed as the last step in evaluating the full-expression (4.6) that (lexically) contains the point where they were created. This is true even if that evaluation ends in throwing an exception. The value computations and side effects of destroying a temporary object are associated only with the full-expression, not with any specific subexpression.
- 5 There are three contexts in which temporaries are destroyed at a different point than the end of the full-expression. The first context is when a default constructor is called to initialize an element of an array with no corresponding initializer (11.6). The second context is when a copy constructor is called to copy an element of an array while the entire array is copied (8.1.5.2, 15.8). In either case, if the constructor has one or more default arguments, the destruction of every temporary created in a default argument is sequenced before the construction of the next array element, if any.
- 6 The third context is when a reference is bound to a temporary.<sup>116</sup> The temporary to which the reference is bound or the temporary that is the complete object of a subobject to which the reference is bound persists for the lifetime of the reference except:
  - (6.1) — A temporary object bound to a reference parameter in a function call (8.2.2) persists until the completion of the full-expression containing the call.
  - (6.2) — The lifetime of a temporary bound to the returned value in a function return statement (9.6.3) is not extended; the temporary is destroyed at the end of the full-expression in the return statement.
  - (6.3) — A temporary bound to a reference in a *new-initializer* (8.3.4) persists until the completion of the full-expression containing the *new-initializer*. [ *Example*:
 

```

 struct S { int mi; const std::pair<int,int>& mp; };
 S a { 1, {2,3} };
 S* p = new S{ 1, {2,3} }; // Creates dangling reference

```

 — *end example* ] [ *Note*: This may introduce a dangling reference, and implementations are encouraged to issue a warning in such a case. — *end note* ]

<sup>116</sup> The same rules apply to initialization of an `initializer_list` object (11.6.4) with its underlying temporary array.

- <sup>7</sup> The destruction of a temporary whose lifetime is not extended by being bound to a reference is sequenced before the destruction of every temporary which is constructed earlier in the same full-expression. If the lifetime of two or more temporaries to which references are bound ends at the same point, these temporaries are destroyed at that point in the reverse order of the completion of their construction. In addition, the destruction of temporaries bound to references shall take into account the ordering of destruction of objects with static, thread, or automatic storage duration (6.7.1, 6.7.2, 6.7.3); that is, if `obj1` is an object with the same storage duration as the temporary and created before the temporary is created the temporary shall be destroyed before `obj1` is destroyed; if `obj2` is an object with the same storage duration as the temporary and created after the temporary is created the temporary shall be destroyed after `obj2` is destroyed.

- <sup>8</sup> [Example:

```
struct S {
 S();
 S(int);
 friend S operator+(const S&, const S&);
 ~S();
};
S obj1;
const S& cr = S(16)+S(23);
S obj2;
```

the expression `S(16) + S(23)` creates three temporaries: a first temporary `T1` to hold the result of the expression `S(16)`, a second temporary `T2` to hold the result of the expression `S(23)`, and a third temporary `T3` to hold the result of the addition of these two expressions. The temporary `T3` is then bound to the reference `cr`. It is unspecified whether `T1` or `T2` is created first. On an implementation where `T1` is created before `T2`, `T2` shall be destroyed before `T1`. The temporaries `T1` and `T2` are bound to the reference parameters of `operator+`; these temporaries are destroyed at the end of the full-expression containing the call to `operator+`. The temporary `T3` bound to the reference `cr` is destroyed at the end of `cr`'s lifetime, that is, at the end of the program. In addition, the order in which `T3` is destroyed takes into account the destruction order of other objects with static storage duration. That is, because `obj1` is constructed before `T3`, and `T3` is constructed before `obj2`, `obj2` shall be destroyed before `T3`, and `T3` shall be destroyed before `obj1`. — end example]

### 15.3 Conversions

[class.conv]

- <sup>1</sup> Type conversions of class objects can be specified by constructors and by conversion functions. These conversions are called *user-defined conversions* and are used for implicit type conversions (Clause 7), for initialization (11.6), and for explicit type conversions (8.4, 8.2.9).
- <sup>2</sup> User-defined conversions are applied only where they are unambiguous (13.2, 15.3.2). Conversions obey the access control rules (Clause 14). Access control is applied after ambiguity resolution (6.4).
- <sup>3</sup> [Note: See 16.3 for a discussion of the use of conversions in function calls as well as examples below. — end note]
- <sup>4</sup> At most one user-defined conversion (constructor or conversion function) is implicitly applied to a single value. [Example:

```
struct X {
 operator int();
};

struct Y {
 operator X();
};

Y a;
int b = a; // error, a.operator X().operator int() not tried
```

```
int c = X(a); // OK: a.operator X().operator int()
— end example]
```

- <sup>5</sup> User-defined conversions are used implicitly only if they are unambiguous. A conversion function in a derived class does not hide a conversion function in a base class unless the two functions convert to the same type. Function overload resolution (16.3.3) selects the best conversion function to perform the conversion. [Example:

```
struct X {
 operator int();
};

struct Y : X {
 operator char();
};

void f(Y& a) {
 if (a) { // ill-formed: X::operator int() or Y::operator char()
 }
}
— end example]
```

### 15.3.1 Conversion by constructor

[class.conv.ctor]

- <sup>1</sup> A constructor declared without the *function-specifier* `explicit` specifies a conversion from the types of its parameters (if any) to the type of its class. Such a constructor is called a *converting constructor*. [Example:

```
struct X {
 X(int);
 X(const char*, int =0);
 X(int, int);
};

void f(X arg) {
 X a = 1; // a = X(1)
 X b = "Jessie"; // b = X("Jessie",0)
 a = 2; // a = X(2)
 f(3); // f(X(3))
 f({1, 2}); // f(X(1,2))
}
— end example]
```

- <sup>2</sup> [Note: An explicit constructor constructs objects just like non-explicit constructors, but does so only where the direct-initialization syntax (11.6) or where casts (8.2.9, 8.4) are explicitly used; see also 16.3.1.4. A default constructor may be an explicit constructor; such a constructor will be used to perform default-initialization or value-initialization (11.6). [Example:

```
struct Z {
 explicit Z();
 explicit Z(int);
 explicit Z(int, int);
};

Z a; // OK: default-initialization performed
Z b{}; // OK: direct initialization syntax used
Z c = {}; // error: copy-list-initialization
```

```

Z a1 = 1; // error: no implicit conversion
Z a3 = Z(1); // OK: direct initialization syntax used
Z a2(1); // OK: direct initialization syntax used
Z* p = new Z(1); // OK: direct initialization syntax used
Z a4 = (Z)1; // OK: explicit cast used
Z a5 = static_cast<Z>(1); // OK: explicit cast used
Z a6 = { 3, 4 }; // error: no implicit conversion

```

— end example] — end note]

- <sup>3</sup> A non-explicit copy/move constructor (15.8) is a converting constructor. [ *Note:* An implicitly-declared copy/move constructor is not an explicit constructor; it may be called for implicit type conversions. — end note]

### 15.3.2 Conversion functions

[class.conv.fct]

- <sup>1</sup> A member function of a class **X** having no parameters with a name of the form

```

conversion-function-id:
 operator conversion-type-id

conversion-type-id:
 type-specifier-seq conversion-declaratoropt

conversion-declarator:
 ptr-operator conversion-declaratoropt

```

specifies a conversion from **X** to the type specified by the *conversion-type-id*. Such functions are called *conversion functions*. A *decl-specifier* in the *decl-specifier-seq* of a conversion function (if any) shall be neither a *defining-type-specifier* nor **static**. The type of the conversion function (11.3.5) is “function taking no parameter returning *conversion-type-id*”. A conversion function is never used to convert a (possibly cv-qualified) object to the (possibly cv-qualified) same object type (or a reference to it), to a (possibly cv-qualified) base class of that type (or a reference to it), or to (possibly cv-qualified) void.<sup>117</sup> [ *Example:*

```

struct X {
 operator int();
 operator auto() -> short; // error: trailing return type
};

void f(X a) {
 int i = int(a);
 i = (int)a;
 i = a;
}

```

In all three cases the value assigned will be converted by **X::operator int()**. — end example]

- <sup>2</sup> A conversion function may be explicit (10.1.2), in which case it is only considered as a user-defined conversion for direct-initialization (11.6). Otherwise, user-defined conversions are not restricted to use in assignments and initializations. [ *Example:*

```

class Y { };
struct Z {
 explicit operator Y() const;
};

```

<sup>117</sup> These conversions are considered as standard conversions for the purposes of overload resolution (16.3.3.1, 16.3.3.1.4) and therefore initialization (11.6) and explicit casts (8.2.9). A conversion to **void** does not invoke any conversion function (8.2.9). Even though never directly called to perform a conversion, such conversion functions can be declared and can potentially be reached through a call to a virtual conversion function in a base class.

```
void h(Z z) {
 Y y1(z); // OK: direct-initialization
 Y y2 = z; // ill-formed: copy-initialization
 Y y3 = (Y)z; // OK: cast notation
}
```

```
void g(X a, X b) {
 int i = (a) ? 1+a : 0;
 int j = (a&&b) ? a+b : i;
 if (a) {
 }
}
```

— end example]

- <sup>3</sup> The *conversion-type-id* shall not represent a function type nor an array type. The *conversion-type-id* in a *conversion-function-id* is the longest sequence of tokens that could possibly form a *conversion-type-id*. [Note: This prevents ambiguities between the declarator operator *\** and its expression counterparts. [Example:

```
&ac.operator int*i; // syntax error:
 // parsed as: &(ac.operator int *)i
 // not as: &(ac.operator int)*i
```

The *\** is the pointer declarator and not the multiplication operator. — end example] This rule also prevents ambiguities for attributes. [Example:

```
operator int [[noreturn]] (); // error: noreturn attribute applied to a type
```

— end example] — end note]

- <sup>4</sup> Conversion functions are inherited.  
<sup>5</sup> Conversion functions can be virtual.  
<sup>6</sup> A conversion function template shall not have a deduced return type (10.1.7.4). [Example:

```
struct S {
 operator auto() const { return 10; } // OK
 template<class T>
 operator auto() const { return 1.2; } // error: conversion function template
};
```

— end example]

## 15.4 Destructors

[class.dtor]

- <sup>1</sup> In a declaration of a destructor, the *declarator* is a function declarator (11.3.5) of the form

*ptr-declarator* ( *parameter-declaration-clause* ) *noexcept-specifier<sub>opt</sub>* *attribute-specifier-seq<sub>opt</sub>*

where the *ptr-declarator* consists solely of an *id-expression*, an optional *attribute-specifier-seq*, and optional surrounding parentheses, and the *id-expression* has one of the following forms:

- (1.1) — in a *member-declaration* that belongs to the *member-specification* of a class but is not a friend declaration (14.3), the *id-expression* is *~class-name* and the *class-name* is the injected-class-name (Clause 12) of the immediately-enclosing class;
- (1.2) — in a *member-declaration* that belongs to the *member-specification* of a class template but is not a friend declaration, the *id-expression* is *~class-name* and the *class-name* names the current instantiation (17.6.2.1) of the immediately-enclosing class template; or
- (1.3) — in a declaration at namespace scope or in a friend declaration, the *id-expression* is *nested-name-specifier ~class-name* and the *class-name* names the same class as the *nested-name-specifier*.

The *class-name* shall not be a *typedef-name*. A destructor shall take no arguments (11.3.5). Each *decl-specifier* of the *decl-specifier-seq* of a destructor declaration (if any) shall be **friend**, **inline**, or **virtual**.

- <sup>2</sup> A destructor is used to destroy objects of its class type. The address of a destructor shall not be taken. A destructor can be invoked for a **const**, **volatile** or **const volatile** object. **const** and **volatile** semantics (10.1.7.1) are not applied on an object under destruction. They stop being in effect when the destructor for the most derived object (4.5) starts.
- <sup>3</sup> [Note: A declaration of a destructor that does not have a *noexcept-specifier* has the same exception specification as if had been implicitly declared (18.4). — end note]
- <sup>4</sup> If a class has no user-declared destructor, a destructor is implicitly declared as defaulted (11.4). An implicitly-declared destructor is an **inline public** member of its class.
- <sup>5</sup> A defaulted destructor for a class **X** is defined as deleted if:
  - (5.1) — **X** is a union-like class that has a variant member with a non-trivial destructor,
  - (5.2) — any potentially constructed subobject has class type **M** (or array thereof) and **M** has a deleted destructor or a destructor that is inaccessible from the defaulted destructor,
  - (5.3) — or, for a virtual destructor, lookup of the non-array deallocation function results in an ambiguity or in a function that is deleted or inaccessible from the defaulted destructor.
- <sup>6</sup> A destructor is trivial if it is not user-provided and if:
  - (6.1) — the destructor is not **virtual**,
  - (6.2) — all of the direct base classes of its class have trivial destructors, and
  - (6.3) — for all of the non-static data members of its class that are of class type (or array thereof), each such class has a trivial destructor.Otherwise, the destructor is *non-trivial*.
- <sup>7</sup> A destructor that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used (6.2) or when it is explicitly defaulted after its first declaration.
- <sup>8</sup> Before the defaulted destructor for a class is implicitly defined, all the non-user-provided destructors for its base classes and its non-static data members shall have been implicitly defined.
- <sup>9</sup> After executing the body of the destructor and destroying any automatic objects allocated within the body, a destructor for class **X** calls the destructors for **X**'s direct non-variant non-static data members, the destructors for **X**'s non-virtual direct base classes and, if **X** is the type of the most derived class (15.6.2), its destructor calls the destructors for **X**'s virtual base classes. All destructors are called as if they were referenced with a qualified name, that is, ignoring any possible virtual overriding destructors in more derived classes. Bases and members are destroyed in the reverse order of the completion of their constructor (see 15.6.2). A **return** statement (9.6.3) in a destructor might not directly return to the caller; before transferring control to the caller, the destructors for the members and bases are called. Destructors for elements of an array are called in reverse order of their construction (see 15.6).
- <sup>10</sup> A destructor can be declared **virtual** (13.3) or pure **virtual** (13.4); if any objects of that class or any derived class are created in the program, the destructor shall be defined. If a class has a base class with a virtual destructor, its destructor (whether user- or implicitly-declared) is virtual.
- <sup>11</sup> [Note: Some language constructs have special semantics when used during destruction; see 15.7. — end note]
- <sup>12</sup> A destructor is invoked implicitly
  - (12.1) — for a constructed object with static storage duration (6.7.1) at program termination (6.6.4),
  - (12.2) — for a constructed object with thread storage duration (6.7.2) at thread exit,



- (12.3) — for a constructed object with automatic storage duration (6.7.3) when the block in which an object is created exits (9.7),
- (12.4) — for a constructed temporary object when its lifetime ends (7.4, 15.2).

In each case, the context of the invocation is the context of the construction of the object. A destructor is also invoked implicitly through use of a *delete-expression* (8.3.5) for a constructed object allocated by a *new-expression* (8.3.4); the context of the invocation is the *delete-expression*. [Note: An array of class type contains several subobjects for each of which the destructor is invoked. — end note] A destructor can also be invoked explicitly. A destructor is *potentially invoked* if it is invoked or as specified in 8.3.4, 15.6.2, and 18.1. A program is ill-formed if a destructor that is potentially invoked is deleted or not accessible from the context of the invocation.

- 13 At the point of definition of a virtual destructor (including an implicit definition (15.8)), the non-array deallocation function is determined as if for the expression `delete this` appearing in a non-virtual destructor of the destructor's class (see 8.3.5). If the lookup fails or if the deallocation function has a deleted definition (11.4), the program is ill-formed. [Note: This assures that a deallocation function corresponding to the dynamic type of an object is available for the *delete-expression* (15.5). — end note]
- 14 In an explicit destructor call, the destructor is specified by a `~` followed by a *type-name* or *decltype-specifier* that denotes the destructor's class type. The invocation of a destructor is subject to the usual rules for member functions (12.2.1); that is, if the object is not of the destructor's class type and not of a class derived from the destructor's class type (including when the destructor is invoked via a null pointer value), the program has undefined behavior. [Note: Invoking `delete` on a null pointer does not call the destructor; see 8.3.5. — end note] [Example:

```
struct B {
 virtual ~B() { }
};
struct D : B {
 ~D() { }
};

D D_object;
typedef B B_alias;
B* B_ptr = &D_object;

void f() {
 D_object.B::~~B(); // calls B's destructor
 B_ptr->~B(); // calls D's destructor
 B_ptr->~B_alias(); // calls D's destructor
 B_ptr->B_alias::~~B(); // calls B's destructor
 B_ptr->B_alias::~~B_alias(); // calls B's destructor
}
```

— end example] [Note: An explicit destructor call must always be written using a member access operator (8.2.5) or a *qualified-id* (8.1); in particular, the *unary-expression* `~X()` in a member function is not an explicit destructor call (8.3.1). — end note]

- 15 [Note: Explicit calls of destructors are rarely needed. One use of such calls is for objects placed at specific addresses using a placement *new-expression*. Such use of explicit placement and destruction of objects can be necessary to cope with dedicated hardware resources and for writing memory management facilities. For example,

```
void* operator new(std::size_t, void* p) { return p; }
struct X {
 X(int);
```

```

 ~X();
};
void f(X* p);

void g() {
 // rare, specialized use:
 char* buf = new char[sizeof(X)];
 X* p = new(buf) X(222); // use buf[] and initialize
 f(p);
 p->X::~~X(); // cleanup
}

```

— end note]

- <sup>16</sup> Once a destructor is invoked for an object, the object no longer exists; the behavior is undefined if the destructor is invoked for an object whose lifetime has ended (6.8). [Example: If the destructor for an automatic object is explicitly invoked, and the block is subsequently left in a manner that would ordinarily invoke implicit destruction of the object, the behavior is undefined. — end example]
- <sup>17</sup> [Note: The notation for explicit call of a destructor can be used for any scalar type name (8.2.4). Allowing this makes it possible to write code without having to know if a destructor exists for a given type. For example:

```

typedef int I;
I* p;
p->I::~~I();

```

— end note]

## 15.5 Free store

[class.free]

- <sup>1</sup> Any allocation function for a class T is a static member (even if not explicitly declared **static**).

- <sup>2</sup> [Example:

```

class Arena;
struct B {
 void* operator new(std::size_t, Arena*);
};
struct D1 : B {
};

Arena* ap;
void foo(int i) {
 new (ap) D1; // calls B::operator new(std::size_t, Arena*)
 new D1[i]; // calls ::operator new[](std::size_t)
 new D1; // ill-formed: ::operator new(std::size_t) hidden
}

```

— end example]

- <sup>3</sup> When an object is deleted with a *delete-expression* (8.3.5), a deallocation function (**operator delete()** for non-array objects or **operator delete[]()** for arrays) is (implicitly) called to reclaim the storage occupied by the object (6.7.4.2).
- <sup>4</sup> Class-specific deallocation function lookup is a part of general deallocation function lookup (8.3.5) and occurs as follows. If the *delete-expression* is used to deallocate a class object whose static type has a virtual destructor, the deallocation function is the one selected at the point of definition of the dynamic type's virtual destructor (15.4).<sup>118</sup> Otherwise, if the *delete-expression* is used to deallocate an object of class T or array thereof, the static and dynamic types of the object shall be identical and the deallocation function's

<sup>118</sup> A similar provision is not needed for the array version of **operator delete** because 8.3.5 requires that in this situation, the

name is looked up in the scope of T. If this lookup fails to find the name, general deallocation function lookup (8.3.5) continues. If the result of the lookup is ambiguous or inaccessible, or if the lookup selects a placement deallocation function, the program is ill-formed.

- <sup>5</sup> Any deallocation function for a class X is a static member (even if not explicitly declared `static`). [*Example:*

```
class X {
 void operator delete(void*);
 void operator delete[](void*, std::size_t);
};

class Y {
 void operator delete(void*, std::size_t);
 void operator delete[](void*);
};
```

— *end example*]

- <sup>6</sup> Since member allocation and deallocation functions are `static` they cannot be virtual. [*Note:* However, when the *cast-expression* of a *delete-expression* refers to an object of class type, because the deallocation function actually called is looked up in the scope of the class that is the dynamic type of the object, if the destructor is virtual, the effect is the same. For example,

```
struct B {
 virtual ~B();
 void operator delete(void*, std::size_t);
};

struct D : B {
 void operator delete(void*);
};

void f() {
 B* bp = new D;
 delete bp; // 1: uses D::operator delete(void*)
}
```

Here, storage for the non-array object of class D is deallocated by `D::operator delete()`, due to the virtual destructor. — *end note*] [*Note:* Virtual destructors have no effect on the deallocation function actually called when the *cast-expression* of a *delete-expression* refers to an array of objects of class type. For example,

```
struct B {
 virtual ~B();
 void operator delete[](void*, std::size_t);
};

struct D : B {
 void operator delete[](void*, std::size_t);
};

void f(int i) {
 D* dp = new D[i];
 delete [] dp; // uses D::operator delete[](void*, std::size_t)
 B* bp = new D[i];
 delete[] bp; // undefined behavior
}
```

---

static type of the object to be deleted be the same as its dynamic type.

— end note]

- <sup>7</sup> Access to the deallocation function is checked statically. Hence, even though a different one might actually be executed, the statically visible deallocation function is required to be accessible. [ *Example:* For the call on line “// 1” above, if `B::operator delete()` had been `private`, the delete expression would have been ill-formed. — end example]
- <sup>8</sup> [ *Note:* If a deallocation function has no explicit *noexcept-specifier*, it has a non-throwing exception specification (18.4). — end note]

## 15.6 Initialization

[class.init]

- <sup>1</sup> When no initializer is specified for an object of (possibly cv-qualified) class type (or array thereof), or the initializer has the form `()`, the object is initialized as specified in 11.6.
- <sup>2</sup> An object of class type (or array thereof) can be explicitly initialized; see 15.6.1 and 15.6.2.
- <sup>3</sup> When an array of class objects is initialized (either explicitly or implicitly) and the elements are initialized by constructor, the constructor shall be called for each element of the array, following the subscript order; see 11.3.4. [ *Note:* Destructors for the array elements are called in reverse order of their construction. — end note]

### 15.6.1 Explicit initialization

[class.expl.init]

- <sup>1</sup> An object of class type can be initialized with a parenthesized *expression-list*, where the *expression-list* is construed as an argument list for a constructor that is called to initialize the object. Alternatively, a single *assignment-expression* can be specified as an *initializer* using the `=` form of initialization. Either direct-initialization semantics or copy-initialization semantics apply; see 11.6. [ *Example:*

```
struct complex {
 complex();
 complex(double);
 complex(double,double);
};

complex sqrt(complex,complex);

complex a(1); // initialize by a call of complex(double)
complex b = a; // initialize by a copy of a
complex c = complex(1,2); // construct complex(1,2) using complex(double,double),
 // copy/move it into c
complex d = sqrt(b,c); // call sqrt(complex,complex) and copy/move the result into d
complex e; // initialize by a call of complex()
complex f = 3; // construct complex(3) using complex(double), copy/move it into f
complex g = { 1, 2 }; // initialize by a call of complex(double, double)
```

— end example] [ *Note:* Overloading of the assignment operator (16.5.3) has no effect on initialization. — end note]

- <sup>2</sup> An object of class type can also be initialized by a *braced-init-list*. List-initialization semantics apply; see 11.6 and 11.6.4. [ *Example:*

```
complex v[6] = { 1, complex(1,2), complex(), 2 };
```

Here, `complex::complex(double)` is called for the initialization of `v[0]` and `v[3]`, `complex::complex(double, double)` is called for the initialization of `v[1]`, `complex::complex()` is called for the initialization of `v[2]`, `v[4]`, and `v[5]`. For another example,

```
struct X {
 int i;
```

```
float f;
complex c;
} x = { 99, 88.8, 77.7 };
```

Here, `x.i` is initialized with 99, `x.f` is initialized with 88.8, and `complex::complex(double)` is called for the initialization of `x.c`. — *end example*] [Note: Braces can be elided in the *initializer-list* for any aggregate, even if the aggregate has members of a class type with user-defined type conversions; see 11.6.1. — *end note*]

- 3 [Note: If `T` is a class type with no default constructor, any declaration of an object of type `T` (or array thereof) is ill-formed if no *initializer* is explicitly specified (see 15.6 and 11.6). — *end note*]
- 4 [Note: The order in which objects with static or thread storage duration are initialized is described in 6.6.3 and 9.7. — *end note*]

## 15.6.2 Initializing bases and members

[class.base.init]

- 1 In the definition of a constructor for a class, initializers for direct and virtual base class subobjects and non-static data members can be specified by a *ctor-initializer*, which has the form

```
ctor-initializer:
 : mem-initializer-list

mem-initializer-list:
 mem-initializer ...opt
 mem-initializer-list , mem-initializer ...opt

mem-initializer:
 mem-initializer-id (expression-listopt)
 mem-initializer-id braced-init-list

mem-initializer-id:
 class-or-decltype
 identifier
```

- 2 In a *mem-initializer-id* an initial unqualified *identifier* is looked up in the scope of the constructor's class and, if not found in that scope, it is looked up in the scope containing the constructor's definition. [Note: If the constructor's class contains a member with the same name as a direct or virtual base class of the class, a *mem-initializer-id* naming the member or base class and composed of a single identifier refers to the class member. A *mem-initializer-id* for the hidden base class may be specified using a qualified name. — *end note*] Unless the *mem-initializer-id* names the constructor's class, a non-static data member of the constructor's class, or a direct or virtual base of that class, the *mem-initializer* is ill-formed.
- 3 A *mem-initializer-list* can initialize a base class using any *class-or-decltype* that denotes that base class type. [Example:

```
struct A { A(); };
typedef A global_A;
struct B { };
struct C: public A, public B { C(); };
C::C(): global_A() { } // mem-initializer for base A
```

— *end example*]

- 4 If a *mem-initializer-id* is ambiguous because it designates both a direct non-virtual base class and an inherited virtual base class, the *mem-initializer* is ill-formed. [Example:

```
struct A { A(); };
struct B: public virtual A { };
struct C: public A, public B { C(); };
C::C(): A() { } // ill-formed: which A?
```

— *end example*]

- <sup>5</sup> A *ctor-initializer* may initialize a variant member of the constructor's class. If a *ctor-initializer* specifies more than one *mem-initializer* for the same member or for the same base class, the *ctor-initializer* is ill-formed.
- <sup>6</sup> A *mem-initializer-list* can delegate to another constructor of the constructor's class using any *class-or-decltype* that denotes the constructor's class itself. If a *mem-initializer-id* designates the constructor's class, it shall be the only *mem-initializer*; the constructor is a *delegating constructor*, and the constructor selected by the *mem-initializer* is the *target constructor*. The target constructor is selected by overload resolution. Once the target constructor returns, the body of the delegating constructor is executed. If a constructor delegates to itself directly or indirectly, the program is ill-formed, no diagnostic required. [ *Example*:

```
struct C {
 C(int) { } // #1: non-delegating constructor
 C(): C(42) { } // #2: delegates to #1
 C(char c) : C(42.0) { } // #3: ill-formed due to recursion with #4
 C(double d) : C('a') { } // #4: ill-formed due to recursion with #3
};
```

— *end example*]

- <sup>7</sup> The *expression-list* or *braced-init-list* in a *mem-initializer* is used to initialize the designated subobject (or, in the case of a delegating constructor, the complete class object) according to the initialization rules of 11.6 for direct-initialization. [ *Example*:

```
struct B1 { B1(int); /* ... */ };
struct B2 { B2(int); /* ... */ };
struct D : B1, B2 {
 D(int);
 B1 b;
 const int c;
};

D::D(int a) : B2(a+1), B1(a+2), c(a+3), b(a+4) { /* ... */ }
D d(10);
```

— *end example*] [ *Note*: The initialization performed by each *mem-initializer* constitutes a full-expression (4.6). Any expression in a *mem-initializer* is evaluated as part of the full-expression that performs the initialization.

— *end note*] A *mem-initializer* where the *mem-initializer-id* denotes a virtual base class is ignored during execution of a constructor of any class that is not the most derived class.

- <sup>8</sup> A temporary expression bound to a reference member in a *mem-initializer* is ill-formed. [ *Example*:

```
struct A {
 A() : v(42) { } // error
 const int& v;
};
```

— *end example*]

- <sup>9</sup> In a non-delegating constructor, if a given potentially constructed subobject is not designated by a *mem-initializer-id* (including the case where there is no *mem-initializer-list* because the constructor has no *ctor-initializer*), then

- (9.1) — if the entity is a non-static data member that has a default member initializer (12.2) and either
- (9.1.1) — the constructor's class is a union (12.3), and no other variant member of that union is designated by a *mem-initializer-id* or
- (9.1.2) — the constructor's class is not a union, and, if the entity is a member of an anonymous union, no other member of that union is designated by a *mem-initializer-id*,

the entity is initialized from its default member initializer as specified in 11.6;

- (9.2) — otherwise, if the entity is an anonymous union or a variant member (12.3.1), no initialization is performed;
- (9.3) — otherwise, the entity is default-initialized (11.6).

[*Note:* An abstract class (13.4) is never a most derived class, thus its constructors never initialize virtual base classes, therefore the corresponding *mem-initializers* may be omitted. — *end note*] An attempt to initialize more than one non-static data member of a union renders the program ill-formed. [*Note:* After the call to a constructor for class **X** for an object with automatic or dynamic storage duration has completed, if the constructor was not invoked as part of value-initialization and a member of **X** is neither initialized nor given a value during execution of the *compound-statement* of the body of the constructor, the member has an indeterminate value. — *end note*] [*Example:*

```
struct A {
 A();
};

struct B {
 B(int);
};

struct C {
 C() { } // initializes members as follows:
 A a; // OK: calls A::A()
 const B b; // error: B has no default constructor
 int i; // OK: i has indeterminate value
 int j = 5; // OK: j has the value 5
};
```

— *end example*]

- 10 If a given non-static data member has both a default member initializer and a *mem-initializer*, the initialization specified by the *mem-initializer* is performed, and the non-static data member's default member initializer is ignored. [*Example:* Given

```
struct A {
 int i = /* some integer expression with side effects */ ;
 A(int arg) : i(arg) { }
 // ...
};
```

the **A(int)** constructor will simply initialize **i** to the value of **arg**, and the side effects in **i**'s default member initializer will not take place. — *end example*]

- 11 A temporary expression bound to a reference member from a default member initializer is ill-formed. [*Example:*

```
struct A {
 A() = default; // OK
 A(int v) : v(v) { } // OK
 const int& v = 42; // OK
};
A a1; // error: ill-formed binding of temporary to reference
A a2(1); // OK, unfortunately
```

— *end example*]

<sup>12</sup> In a non-delegating constructor, the destructor for each potentially constructed subobject of class type is potentially invoked (15.4). [ *Note*: This provision ensures that destructors can be called for fully-constructed subobjects in case an exception is thrown (18.2). — *end note* ]

<sup>13</sup> In a non-delegating constructor, initialization proceeds in the following order:

- (13.1) — First, and only for the constructor of the most derived class (4.5), virtual base classes are initialized in the order they appear on a depth-first left-to-right traversal of the directed acyclic graph of base classes, where “left-to-right” is the order of appearance of the base classes in the derived class *base-specifier-list*.
- (13.2) — Then, direct base classes are initialized in declaration order as they appear in the *base-specifier-list* (regardless of the order of the *mem-initializers*).
- (13.3) — Then, non-static data members are initialized in the order they were declared in the class definition (again regardless of the order of the *mem-initializers*).
- (13.4) — Finally, the *compound-statement* of the constructor body is executed.

[ *Note*: The declaration order is mandated to ensure that base and member subobjects are destroyed in the reverse order of initialization. — *end note* ]

<sup>14</sup> [ *Example*:

```

struct V {
 V();
 V(int);
};

struct A : virtual V {
 A();
 A(int);
};

struct B : virtual V {
 B();
 B(int);
};

struct C : A, B, virtual V {
 C();
 C(int);
};

A::A(int i) : V(i) { /* ... */ }
B::B(int i) { /* ... */ }
C::C(int i) { /* ... */ }

V v(1); // use V(int)
A a(2); // use V(int)
B b(3); // use V()
C c(4); // use V()

```

— *end example* ]

<sup>15</sup> Names in the *expression-list* or *braced-init-list* of a *mem-initializer* are evaluated in the scope of the constructor for which the *mem-initializer* is specified. [ *Example*:

```

class X {
 int a;
 int b;

```



```

 int i;
 int j;
public:
 const int& r;
 X(int i): r(a), b(i), i(i), j(this->i) { }
};

```

initializes `X::r` to refer to `X::a`, initializes `X::b` with the value of the constructor parameter `i`, initializes `X::i` with the value of the constructor parameter `i`, and initializes `X::j` with the value of `X::i`; this takes place each time an object of class `X` is created. — *end example*] [Note: Because the *mem-initializer* are evaluated in the scope of the constructor, the `this` pointer can be used in the *expression-list* of a *mem-initializer* to refer to the object being initialized. — *end note*]

- <sup>16</sup> Member functions (including virtual member functions, 13.3) can be called for an object under construction. Similarly, an object under construction can be the operand of the `typeid` operator (8.2.8) or of a `dynamic_cast` (8.2.7). However, if these operations are performed in a *ctor-initializer* (or in a function called directly or indirectly from a *ctor-initializer*) before all the *mem-initializers* for base classes have completed, the program has undefined behavior. [Example:

```

class A {
public:
 A(int);
};

class B : public A {
 int j;
public:
 int f();
 B() : A(f()), // undefined: calls member function but base A not yet initialized
 j(f()) { } // well-defined: bases are all initialized
};

class C {
public:
 C(int);
};

class D : public B, C {
 int i;
public:
 D() : C(f()), // undefined: calls member function but base C not yet initialized
 i(f()) { } // well-defined: bases are all initialized
};

```

— *end example*]

- <sup>17</sup> [Note: 15.7 describes the result of virtual function calls, `typeid` and `dynamic_casts` during construction for the well-defined cases; that is, describes the *polymorphic behavior* of an object under construction. — *end note*]
- <sup>18</sup> A *mem-initializer* followed by an ellipsis is a pack expansion (17.5.3) that initializes the base classes specified by a pack expansion in the *base-specifier-list* for the class. [Example:

```

template<class... Mixins>
class X : public Mixins... {
public:
 X(const Mixins&... mixins) : Mixins(mixins)... { }
};

```

— *end example*]

### 15.6.3 Initialization by inherited constructor

[**class.inhctor.init**]

- <sup>1</sup> When a constructor for type B is invoked to initialize an object of a different type D (that is, when the constructor was inherited (10.3.3)), initialization proceeds as if a defaulted default constructor were used to initialize the D object and each base class subobject from which the constructor was inherited, except that the B subobject is initialized by the invocation of the inherited constructor. The complete initialization is considered to be a single function call; in particular, the initialization of the inherited constructor's parameters is sequenced before the initialization of any part of the D object. [*Example:*

```
struct B1 {
 B1(int, ...) { }
};

struct B2 {
 B2(double) { }
};

int get();

struct D1 : B1 {
 using B1::B1; // inherits B1(int, ...)
 int x;
 int y = get();
};

void test() {
 D1 d(2, 3, 4); // OK: B1 is initialized by calling B1(2, 3, 4),
 // then d.x is default-initialized (no initialization is performed),
 // then d.y is initialized by calling get()
 D1 e; // error: D1 has a deleted default constructor
}

struct D2 : B2 {
 using B2::B2;
 B1 b;
};

D2 f(1.0); // error: B1 has a deleted default constructor

struct W { W(int); };
struct X : virtual W { using W::W; X() = delete; };
struct Y : X { using X::X; };
struct Z : Y, virtual W { using Y::Y; };
Z z(0); // OK: initialization of Y does not invoke default constructor of X

template<class T> struct Log : T {
 using T::T; // inherits all constructors from class T
 ~Log() { std::clog << "Destroying wrapper" << std::endl; }
};
```

Class template Log wraps any class and forwards all of its constructors, while writing a message to the standard log whenever an object of class Log is destroyed. — *end example*]

- <sup>2</sup> If the constructor was inherited from multiple base class subobjects of type B, the program is ill-formed. [*Example:*

```

struct A { A(int); };
struct B : A { using A::A; };

struct C1 : B { using B::B; };
struct C2 : B { using B::B; };

struct D1 : C1, C2 {
 using C1::C1;
 using C2::C2;
};

struct V1 : virtual B { using B::B; };
struct V2 : virtual B { using B::B; };

struct D2 : V1, V2 {
 using V1::V1;
 using V2::V2;
};

D1 d1(0); // ill-formed: ambiguous
D2 d2(0); // OK: initializes virtual B base class, which initializes the A base class
 // then initializes the V1 and V2 base classes as if by a defaulted default constructor

struct M { M(); M(int); };
struct N : M { using M::M; };
struct O : M {};
struct P : N, O { using N::N; using O::O; };
P p(0); // OK: use M(0) to initialize N's base class,
 // use M() to initialize O's base class

```

— end example]

- <sup>3</sup> When an object is initialized by an inherited constructor, initialization of the object is complete when the initialization of all subobjects is complete.

## 15.7 Construction and destruction

[class.ctor]

- <sup>1</sup> For an object with a non-trivial constructor, referring to any non-static member or base class of the object before the constructor begins execution results in undefined behavior. For an object with a non-trivial destructor, referring to any non-static member or base class of the object after the destructor finishes execution results in undefined behavior. [Example:

```

struct X { int i; };
struct Y : X { Y(); }; // non-trivial
struct A { int a; };
struct B : public A { int j; Y y; }; // non-trivial

extern B bobj;
B* pb = &bobj; // OK
int* p1 = &bobj.a; // undefined, refers to base class member
int* p2 = &bobj.y.i; // undefined, refers to member's member

A* pa = &bobj; // undefined, upcast to a base class type
B bobj; // definition of bobj

extern X xobj;
int* p3 = &xobj.i; // OK, X is a trivial class

```

```
X xobj;
```

For another example,

```
struct W { int j; };
struct X : public virtual W { };
struct Y {
 int* p;
 X x;
 Y() : p(&x.j) { // undefined, x is not yet constructed
 }
};
```

— end example]

- <sup>2</sup> To explicitly or implicitly convert a pointer (a glvalue) referring to an object of class **X** to a pointer (reference) to a direct or indirect base class **B** of **X**, the construction of **X** and the construction of all of its direct or indirect bases that directly or indirectly derive from **B** shall have started and the destruction of these classes shall not have completed, otherwise the conversion results in undefined behavior. To form a pointer to (or access the value of) a direct non-static member of an object **obj**, the construction of **obj** shall have started and its destruction shall not have completed, otherwise the computation of the pointer value (or accessing the member value) results in undefined behavior. [ *Example:*

```
struct A { };
struct B : virtual A { };
struct C : B { };
struct D : virtual A { D(A*); };
struct X { X(A*); };

struct E : C, D, X {
 E() : D(this), // undefined: upcast from E* to A* might use path E* → D* → A*
 // but D is not constructed

 // “D((C*)this)” would be defined: E* → C* is defined because E() has started,
 // and C* → A* is defined because C is fully constructed

 X(this) {} // defined: upon construction of X, C/B/D/A sublattice is fully constructed
};
```

— end example]

- <sup>3</sup> Member functions, including virtual functions (13.3), can be called during construction or destruction (15.6.2). When a virtual function is called directly or indirectly from a constructor or from a destructor, including during the construction or destruction of the class’s non-static data members, and the object to which the call applies is the object (call it **x**) under construction or destruction, the function called is the final overrider in the constructor’s or destructor’s class and not one overriding it in a more-derived class. If the virtual function call uses an explicit class member access (8.2.5) and the object expression refers to the complete object of **x** or one of that object’s base class subobjects but not **x** or one of its base class subobjects, the behavior is undefined. [ *Example:*

```
struct V {
 virtual void f();
 virtual void g();
};

struct A : virtual V {
 virtual void f();
};
```

```

struct B : virtual V {
 virtual void g();
 B(V*, A*);
};

struct D : A, B {
 virtual void f();
 virtual void g();
 D() : B((A*)this, this) { }
};

B::B(V* v, A* a) {
 f(); // calls V::f, not A::f
 g(); // calls B::g, not D::g
 v->g(); // v is base of B, the call is well-defined, calls B::g
 a->f(); // undefined behavior, a's type not a base of B
}

```

— end example]

- <sup>4</sup> The `typeid` operator (8.2.8) can be used during construction or destruction (15.6.2). When `typeid` is used in a constructor (including the *mem-initializer* or default member initializer (12.2) for a non-static data member) or in a destructor, or used in a function called (directly or indirectly) from a constructor or destructor, if the operand of `typeid` refers to the object under construction or destruction, `typeid` yields the `std::type_info` object representing the constructor or destructor's class. If the operand of `typeid` refers to the object under construction or destruction and the static type of the operand is neither the constructor or destructor's class nor one of its bases, the behavior is undefined.
- <sup>5</sup> `dynamic_casts` (8.2.7) can be used during construction or destruction (15.6.2). When a `dynamic_cast` is used in a constructor (including the *mem-initializer* or default member initializer for a non-static data member) or in a destructor, or used in a function called (directly or indirectly) from a constructor or destructor, if the operand of the `dynamic_cast` refers to the object under construction or destruction, this object is considered to be a most derived object that has the type of the constructor or destructor's class. If the operand of the `dynamic_cast` refers to the object under construction or destruction and the static type of the operand is not a pointer to or object of the constructor or destructor's own class or one of its bases, the `dynamic_cast` results in undefined behavior. [Example:

```

struct V {
 virtual void f();
};

struct A : virtual V { };

struct B : virtual V {
 B(V*, A*);
};

struct D : A, B {
 D() : B((A*)this, this) { }
};

B::B(V* v, A* a) {
 typeid(*this); // type_info for B
 typeid(*v); // well-defined: *v has type V, a base of B yields type_info for B
 typeid(*a); // undefined behavior: type A not a base of B
}

```

```

 dynamic_cast<B*>(v); // well-defined: v of type V*, V base of B results in B*
 dynamic_cast<B*>(a); // undefined behavior, a has type A*, A not a base of B
}

```

— end example]

## 15.8 Copying and moving class objects

[class.copy]

- <sup>1</sup> A class object can be copied or moved in two ways: by initialization (15.1, 11.6), including for function argument passing (8.2.2) and for function value return (9.6.3); and by assignment (8.18). Conceptually, these two operations are implemented by a copy/move constructor (15.1) and copy/move assignment operator (16.5.3).
- <sup>2</sup> A program is ill-formed if the copy/move constructor or the copy/move assignment operator for an object is implicitly odr-used and the special member function is not accessible (Clause 14). [Note: Copying/moving one object into another using the copy/move constructor or the copy/move assignment operator does not change the layout or size of either object. — end note]

### 15.8.1 Copy/move constructors

[class.copy.ctor]

- <sup>1</sup> A non-template constructor for class X is a copy constructor if its first parameter is of type X&, const X&, volatile X& or const volatile X&, and either there are no other parameters or else all other parameters have default arguments (11.3.6). [Example: X::X(const X&) and X::X(X&,int=1) are copy constructors.

```

struct X {
 X(int);
 X(const X&, int = 1);
};
X a(1); // calls X(int);
X b(a, 0); // calls X(const X&, int);
X c = b; // calls X(const X&, int);

```

— end example]

- <sup>2</sup> A non-template constructor for class X is a move constructor if its first parameter is of type X&&, const X&&, volatile X&&, or const volatile X&&, and either there are no other parameters or else all other parameters have default arguments (11.3.6). [Example: Y::Y(Y&&) is a move constructor.

```

struct Y {
 Y(const Y&);
 Y(Y&&);
};
extern Y f(int);
Y d(f(1)); // calls Y(Y&&)
Y e = d; // calls Y(const Y&)

```

— end example]

- <sup>3</sup> [Note: All forms of copy/move constructor may be declared for a class. [Example:

```

struct X {
 X(const X&);
 X(X&); // OK
 X(X&&);
 X(const X&&); // OK, but possibly not sensible
};

```

— end example] — end note]

- <sup>4</sup> [Note: If a class X only has a copy constructor with a parameter of type X&, an initializer of type const X or volatile X cannot initialize an object of type (possibly cv-qualified) X. [Example:

```

struct X {
 X(); // default constructor
 X(X&); // copy constructor with a non-const parameter
};
const X cx;
X x = cx; // error: X::X(X&) cannot copy cx into x
— end example] — end note]

```

- 5 A declaration of a constructor for a class **X** is ill-formed if its first parameter is of type (optionally cv-qualified) **X** and either there are no other parameters or else all other parameters have default arguments. A member function template is never instantiated to produce such a constructor signature. [ *Example:*

```

struct S {
 template<typename T> S(T);
 S();
};

S g;

void h() {
 S a(g); // does not instantiate the member template to produce S::S<S>(S);
 // uses the implicitly declared copy constructor
}
— end example]

```

- 6 If the class definition does not explicitly declare a copy constructor, a non-explicit one is declared *implicitly*. If the class definition declares a move constructor or move assignment operator, the implicitly declared copy constructor is defined as deleted; otherwise, it is defined as defaulted (11.4). The latter case is deprecated if the class has a user-declared copy assignment operator or a user-declared destructor.
- 7 The implicitly-declared copy constructor for a class **X** will have the form

```
X::X(const X&)
```

if each potentially constructed subobject of a class type **M** (or array thereof) has a copy constructor whose first parameter is of type `const M&` or `const volatile M&`.<sup>119</sup> Otherwise, the implicitly-declared copy constructor will have the form

```
X::X(X&)
```

- 8 If the definition of a class **X** does not explicitly declare a move constructor, a non-explicit one will be implicitly declared as defaulted if and only if
- (8.1) — **X** does not have a user-declared copy constructor,
  - (8.2) — **X** does not have a user-declared copy assignment operator,
  - (8.3) — **X** does not have a user-declared move assignment operator, and
  - (8.4) — **X** does not have a user-declared destructor.

[ *Note:* When the move constructor is not implicitly declared or explicitly supplied, expressions that otherwise would have invoked the move constructor may instead invoke a copy constructor. — end note]

- 9 The implicitly-declared move constructor for class **X** will have the form

```
X::X(X&&)
```

- 10 An implicitly-declared copy/move constructor is an `inline public` member of its class. A defaulted

<sup>119</sup>) This implies that the reference parameter of the implicitly-declared copy constructor cannot bind to a `volatile lvalue`; see C.1.9.

copy/move constructor for a class **X** is defined as deleted (11.4.3) if **X** has:

- (10.1) — a variant member with a non-trivial corresponding constructor and **X** is a union-like class,
- (10.2) — a potentially constructed subobject type **M** (or array thereof) that cannot be copied/moved because overload resolution (16.3), as applied to find **M**'s corresponding constructor, results in an ambiguity or a function that is deleted or inaccessible from the defaulted constructor,
- (10.3) — any potentially constructed subobject of a type with a destructor that is deleted or inaccessible from the defaulted constructor, or,
- (10.4) — for the copy constructor, a non-static data member of rvalue reference type.

A defaulted move constructor that is defined as deleted is ignored by overload resolution (16.3, 16.4). [ *Note:* A deleted move constructor would otherwise interfere with initialization from an rvalue which can use the copy constructor instead. — *end note* ]

11 A copy/move constructor for class **X** is trivial if it is not user-provided and if:

- (11.1) — class **X** has no virtual functions (13.3) and no virtual base classes (13.1), and
- (11.2) — the constructor selected to copy/move each direct base class subobject is trivial, and
- (11.3) — for each non-static data member of **X** that is of class type (or array thereof), the constructor selected to copy/move that member is trivial;

otherwise the copy/move constructor is *non-trivial*.

12 A copy/move constructor that is defaulted and not defined as deleted is *implicitly defined* if it is odr-used (6.2) or when it is explicitly defaulted after its first declaration. [ *Note:* The copy/move constructor is implicitly defined even if the implementation elided its odr-use (6.2, 15.2). — *end note* ] If the implicitly-defined constructor would satisfy the requirements of a constexpr constructor (10.1.5), the implicitly-defined constructor is **constexpr**.

13 Before the defaulted copy/move constructor for a class is implicitly defined, all non-user-provided copy/move constructors for its potentially constructed subobjects shall have been implicitly defined. [ *Note:* An implicitly-declared copy/move constructor has an implied exception specification (18.4). — *end note* ]

14 The implicitly-defined copy/move constructor for a non-union class **X** performs a memberwise copy/move of its bases and members. [ *Note:* Default member initializers of non-static data members are ignored. See also the example in 15.6.2. — *end note* ] The order of initialization is the same as the order of initialization of bases and members in a user-defined constructor (see 15.6.2). Let **x** be either the parameter of the constructor or, for the move constructor, an xvalue referring to the parameter. Each base or non-static data member is copied/moved in the manner appropriate to its type:

- (14.1) — if the member is an array, each element is direct-initialized with the corresponding subobject of **x**;
- (14.2) — if a member **m** has rvalue reference type **T&&**, it is direct-initialized with `static_cast<T&&>(x.m)`;
- (14.3) — otherwise, the base or member is direct-initialized with the corresponding base or member of **x**.

Virtual base class subobjects shall be initialized only once by the implicitly-defined copy/move constructor (see 15.6.2).

15 The implicitly-defined copy/move constructor for a union **X** copies the object representation (6.9) of **X**.

## 15.8.2 Copy/move assignment operator

[**class.copy.assign**]

1 A user-declared *copy* assignment operator **X::operator=** is a non-static non-template member function of class **X** with exactly one parameter of type **X**, **X&**, **const X&**, **volatile X&** or **const volatile X&**.<sup>120</sup> [ *Note:*

<sup>120</sup>) Because a template assignment operator or an assignment operator taking an rvalue reference parameter is never a copy assignment operator, the presence of such an assignment operator does not suppress the implicit declaration of a copy assignment operator. Such assignment operators participate in overload resolution with other assignment operators, including



An overloaded assignment operator must be declared to have only one parameter; see 16.5.3. — *end note*]  
 [Note: More than one form of copy assignment operator may be declared for a class. — *end note*] [Note: If a class X only has a copy assignment operator with a parameter of type X&, an expression of type const X cannot be assigned to an object of type X. [Example:

```
struct X {
 X();
 X& operator=(X&);
};
const X cx;
X x;
void f() {
 x = cx; // error: X::operator=(X&) cannot assign cx into x
}
```

— *end example*] — *end note*]

- <sup>2</sup> If the class definition does not explicitly declare a copy assignment operator, one is declared *implicitly*. If the class definition declares a move constructor or move assignment operator, the implicitly declared copy assignment operator is defined as deleted; otherwise, it is defined as defaulted (11.4). The latter case is deprecated if the class has a user-declared copy constructor or a user-declared destructor. The implicitly-declared copy assignment operator for a class X will have the form

```
X& X::operator=(const X&)
```

if

- (2.1) — each direct base class B of X has a copy assignment operator whose parameter is of type const B&, const volatile B& or B, and
- (2.2) — for all the non-static data members of X that are of a class type M (or array thereof), each such class type has a copy assignment operator whose parameter is of type const M&, const volatile M& or M.<sup>121</sup>

Otherwise, the implicitly-declared copy assignment operator will have the form

```
X& X::operator=(X&)
```

- <sup>3</sup> A user-declared move assignment operator X::operator= is a non-static non-template member function of class X with exactly one parameter of type X&&, const X&&, volatile X&&, or const volatile X&&. [Note: An overloaded assignment operator must be declared to have only one parameter; see 16.5.3. — *end note*] [Note: More than one form of move assignment operator may be declared for a class. — *end note*]
- <sup>4</sup> If the definition of a class X does not explicitly declare a move assignment operator, one will be implicitly declared as defaulted if and only if

- (4.1) — X does not have a user-declared copy constructor,
- (4.2) — X does not have a user-declared move constructor,
- (4.3) — X does not have a user-declared copy assignment operator, and
- (4.4) — X does not have a user-declared destructor.

[Example: The class definition

```
struct S {
 int a;
 S& operator=(const S&) = default;
};
```

---

copy assignment operators, and, if selected, will be used to assign an object.

<sup>121</sup>) This implies that the reference parameter of the implicitly-declared copy assignment operator cannot bind to a volatile lvalue; see C.1.9.

will not have a default move assignment operator implicitly declared because the copy assignment operator has been user-declared. The move assignment operator may be explicitly defaulted.

```
struct S {
 int a;
 S& operator=(const S&) = default;
 S& operator=(S&&) = default;
};
```

— *end example*]

- 5 The implicitly-declared move assignment operator for a class **X** will have the form

```
X& X::operator=(X&&);
```

- 6 The implicitly-declared copy/move assignment operator for class **X** has the return type **X&**; it returns the object for which the assignment operator is invoked, that is, the object assigned to. An implicitly-declared copy/move assignment operator is an **inline public** member of its class.

- 7 A defaulted copy/move assignment operator for class **X** is defined as deleted if **X** has:

- (7.1) — a variant member with a non-trivial corresponding assignment operator and **X** is a union-like class, or
- (7.2) — a non-static data member of **const** non-class type (or array thereof), or
- (7.3) — a non-static data member of reference type, or
- (7.4) — a direct non-static data member of class type **M** (or array thereof) or a direct base class **M** that cannot be copied/moved because overload resolution (16.3), as applied to find **M**'s corresponding assignment operator, results in an ambiguity or a function that is deleted or inaccessible from the defaulted assignment operator.

A defaulted move assignment operator that is defined as deleted is ignored by overload resolution (16.3, 16.4).

- 8 Because a copy/move assignment operator is implicitly declared for a class if not declared by the user, a base class copy/move assignment operator is always hidden by the corresponding assignment operator of a derived class (16.5.3). A *using-declaration* (10.3.3) that brings in from a base class an assignment operator with a parameter type that could be that of a copy/move assignment operator for the derived class is not considered an explicit declaration of such an operator and does not suppress the implicit declaration of the derived class operator; the operator introduced by the *using-declaration* is hidden by the implicitly-declared operator in the derived class.

- 9 A copy/move assignment operator for class **X** is trivial if it is not user-provided and if:

- (9.1) — class **X** has no virtual functions (13.3) and no virtual base classes (13.1), and
- (9.2) — the assignment operator selected to copy/move each direct base class subobject is trivial, and
- (9.3) — for each non-static data member of **X** that is of class type (or array thereof), the assignment operator selected to copy/move that member is trivial;

otherwise the copy/move assignment operator is *non-trivial*.

- 10 A copy/move assignment operator for a class **X** that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used (6.2) (e.g., when it is selected by overload resolution to assign to an object of its class type) or when it is explicitly defaulted after its first declaration. The implicitly-defined copy/move assignment operator is **constexpr** if

- (10.1) — **X** is a literal type, and
- (10.2) — the assignment operator selected to copy/move each direct base class subobject is a **constexpr** function, and
- (10.3) — for each non-static data member of **X** that is of class type (or array thereof), the assignment operator

selected to copy/move that member is a constexpr function.

- 11 Before the defaulted copy/move assignment operator for a class is implicitly defined, all non-user-provided copy/move assignment operators for its direct base classes and its non-static data members shall have been implicitly defined. [ *Note*: An implicitly-declared copy/move assignment operator has an implied exception specification (18.4). — *end note* ]
- 12 The implicitly-defined copy/move assignment operator for a non-union class *X* performs memberwise copy-/move assignment of its subobjects. The direct base classes of *X* are assigned first, in the order of their declaration in the *base-specifier-list*, and then the immediate non-static data members of *X* are assigned, in the order in which they were declared in the class definition. Let *x* be either the parameter of the function or, for the move operator, an xvalue referring to the parameter. Each subobject is assigned in the manner appropriate to its type:
  - (12.1) — if the subobject is of class type, as if by a call to `operator=` with the subobject as the object expression and the corresponding subobject of *x* as a single function argument (as if by explicit qualification; that is, ignoring any possible virtual overriding functions in more derived classes);
  - (12.2) — if the subobject is an array, each element is assigned, in the manner appropriate to the element type;
  - (12.3) — if the subobject is of scalar type, the built-in assignment operator is used.

It is unspecified whether subobjects representing virtual base classes are assigned more than once by the implicitly-defined copy/move assignment operator. [ *Example*:

```
struct V { };
struct A : virtual V { };
struct B : virtual V { };
struct C : B, A { };
```

It is unspecified whether the virtual base class subobject *V* is assigned twice by the implicitly-defined copy/move assignment operator for *C*. — *end example*]

- 13 The implicitly-defined copy assignment operator for a union *X* copies the object representation (6.9) of *X*.

### 15.8.3 Copy/move elision

[**class.copy.elision**]

- 1 When certain criteria are met, an implementation is allowed to omit the copy/move construction of a class object, even if the constructor selected for the copy/move operation and/or the destructor for the object have side effects. In such cases, the implementation treats the source and target of the omitted copy/move operation as simply two different ways of referring to the same object. If the first parameter of the selected constructor is an rvalue reference to the object's type, the destruction of that object occurs when the target would have been destroyed; otherwise, the destruction occurs at the later of the times when the two objects would have been destroyed without the optimization.<sup>122</sup> This elision of copy/move operations, called *copy elision*, is permitted in the following circumstances (which may be combined to eliminate multiple copies):
  - (1.1) — in a **return** statement in a function with a class return type, when the *expression* is the name of a non-volatile automatic object (other than a function parameter or a variable introduced by the *exception-declaration* of a *handler* (18.3)) with the same type (ignoring cv-qualification) as the function return type, the copy/move operation can be omitted by constructing the automatic object directly into the function call's return object
  - (1.2) — in a *throw-expression* (8.17), when the operand is the name of a non-volatile automatic object (other than a function or catch-clause parameter) whose scope does not extend beyond the end of the innermost enclosing *try-block* (if there is one), the copy/move operation from the operand to the exception object (18.1) can be omitted by constructing the automatic object directly into the exception object

<sup>122</sup>) Because only one object is destroyed instead of two, and one copy/move constructor is not executed, there is still one object destroyed for each one constructed.

- (1.3) — when the *exception-declaration* of an exception handler (Clause 18) declares an object of the same type (except for cv-qualification) as the exception object (18.1), the copy operation can be omitted by treating the *exception-declaration* as an alias for the exception object if the meaning of the program will be unchanged except for the execution of constructors and destructors for the object declared by the *exception-declaration*. [Note: There cannot be a move from the exception object because it is always an lvalue. — end note]

Copy elision is required where an expression is evaluated in a context requiring a constant expression (8.20) and in constant initialization (6.6.2). [Note: Copy elision might not be performed if the same expression is evaluated in another context. — end note]

<sup>2</sup> [Example:

```
class Thing {
public:
 Thing();
 ~Thing();
 Thing(const Thing&);
};

Thing f() {
 Thing t;
 return t;
}

Thing t2 = f();

struct A {
 void *p;
 constexpr A(): p(this) {}
};

constexpr A g() {
 A a;
 return a;
}

constexpr A a; // well-formed, a.p points to a
constexpr A b = g(); // well-formed, b.p points to b

void g() {
 A c = g(); // well-formed, c.p may point to c or to an ephemeral temporary
}
```

Here the criteria for elision can eliminate the copying of the local automatic object `t` into the result object for the function call `f()`, which is the global object `t2`. Effectively, the construction of the local object `t` can be viewed as directly initializing the global object `t2`, and that object's destruction will occur at program exit. Adding a move constructor to `Thing` has the same effect, but it is the move construction from the local automatic object to `t2` that is elided. — end example]

<sup>3</sup> In the following copy-initialization contexts, a move operation might be used instead of a copy operation:

- (3.1) — If the *expression* in a **return** statement (9.6.3) is a (possibly parenthesized) *id-expression* that names an object with automatic storage duration declared in the body or *parameter-declaration-clause* of the innermost enclosing function or *lambda-expression*, or
- (3.2) — if the operand of a *throw-expression* (8.17) is the name of a non-volatile automatic object (other than

a function or catch-clause parameter) whose scope does not extend beyond the end of the innermost enclosing *try-block* (if there is one),

overload resolution to select the constructor for the copy is first performed as if the object were designated by an rvalue. If the first overload resolution fails or was not performed, or if the type of the first parameter of the selected constructor is not an rvalue reference to the object's type (possibly cv-qualified), overload resolution is performed again, considering the object as an lvalue. [ *Note:* This two-stage overload resolution must be performed regardless of whether copy elision will occur. It determines the constructor to be called if elision is not performed, and the selected constructor must be accessible even if the call is elided. — *end note* ]

<sup>4</sup> [ *Example:*

```
class Thing {
public:
 Thing();
 ~Thing();
 Thing(Thing&&);
private:
 Thing(const Thing&);
};

Thing f(bool b) {
 Thing t;
 if (b)
 throw t; // OK: Thing(Thing&&) used (or elided) to throw t
 return t; // OK: Thing(Thing&&) used (or elided) to return t
}

Thing t2 = f(false); // OK: no extra copy/move performed, t2 constructed by call to f

struct Weird {
 Weird();
 Weird(Weird&);
};

Weird g() {
 Weird w;
 return w; // OK: first overload resolution fails, second overload resolution selects Weird(Weird&)
}

— end example]
```

# 16 Overloading

[over]

- <sup>1</sup> When two or more different declarations are specified for a single name in the same scope, that name is said to be *overloaded*. By extension, two declarations in the same scope that declare the same name but with different types are called *overloaded declarations*. Only function and function template declarations can be overloaded; variable and type declarations cannot be overloaded.
- <sup>2</sup> When an overloaded function name is used in a call, which overloaded function declaration is being referenced is determined by comparing the types of the arguments at the point of use with the types of the parameters in the overloaded declarations that are visible at the point of use. This function selection process is called *overload resolution* and is defined in 16.3. [Example:

```
double abs(double);
int abs(int);

abs(1); // calls abs(int);
abs(1.0); // calls abs(double);

— end example]
```

## 16.1 Overloadable declarations

[over.load]

- <sup>1</sup> Not all function declarations can be overloaded. Those that cannot be overloaded are specified here. A program is ill-formed if it contains two such non-overloadable declarations in the same scope. [Note: This restriction applies to explicit declarations in a scope, and between such declarations and declarations made through a *using-declaration* (10.3.3). It does not apply to sets of functions fabricated as a result of name lookup (e.g., because of *using-directives*) or overload resolution (e.g., for operator functions). — end note]
- <sup>2</sup> Certain function declarations cannot be overloaded:
  - (2.1) — Function declarations that differ only in the return type, the exception specification (18.4), or both cannot be overloaded.
  - (2.2) — Member function declarations with the same name and the same parameter-type-list (11.3.5) cannot be overloaded if any of them is a **static** member function declaration (12.2.3). Likewise, member function template declarations with the same name, the same parameter-type-list, and the same template parameter lists cannot be overloaded if any of them is a **static** member function template declaration. The types of the implicit object parameters constructed for the member functions for the purpose of overload resolution (16.3.1) are not considered when comparing parameter-type-lists for enforcement of this rule. In contrast, if there is no **static** member function declaration among a set of member function declarations with the same name and the same parameter-type-list, then these member function declarations can be overloaded if they differ in the type of their implicit object parameter. [Example: The following illustrates this distinction:

```
class X {
 static void f();
 void f(); // ill-formed
 void f() const; // ill-formed
 void f() const volatile; // ill-formed
 void g();
 void g() const; // OK: no static g
 void g() const volatile; // OK: no static g
};
```

— *end example*]

- (2.3) — Member function declarations with the same name and the same parameter-type-list (11.3.5) as well as member function template declarations with the same name, the same parameter-type-list, and the same template parameter lists cannot be overloaded if any of them, but not all, have a *ref-qualifier* (11.3.5). [ *Example*:

```
class Y {
 void h() &;
 void h() const &; // OK
 void h() &&; // OK, all declarations have a ref-qualifier
 void i() &;
 void i() const; // ill-formed, prior declaration of i
 // has a ref-qualifier
};
```

— *end example*]

- <sup>3</sup> [ *Note*: As specified in 11.3.5, function declarations that have equivalent parameter declarations declare the same function and therefore cannot be overloaded:

- (3.1) — Parameter declarations that differ only in the use of equivalent typedef “types” are equivalent. A typedef is not a separate type, but only a synonym for another type (10.1.3). [ *Example*:

```
typedef int Int;

void f(int i);
void f(Int i); // OK: redeclaration of f(int)
void f(int i) { /* ... */ }
void f(Int i) { /* ... */ } // error: redefinition of f(int)
```

— *end example*]

Enumerations, on the other hand, are distinct types and can be used to distinguish overloaded function declarations. [ *Example*:

```
enum E { a };

void f(int i) { /* ... */ }
void f(E i) { /* ... */ }
```

— *end example*]

- (3.2) — Parameter declarations that differ only in a pointer \* versus an array [] are equivalent. That is, the array declaration is adjusted to become a pointer declaration (11.3.5). Only the second and subsequent array dimensions are significant in parameter types (11.3.4). [ *Example*:

```
int f(char*);
int f(char[]); // same as f(char*);
int f(char[7]); // same as f(char*);
int f(char[9]); // same as f(char*);

int g(char(*)[10]);
int g(char[5][10]); // same as g(char(*)[10]);
int g(char[7][10]); // same as g(char(*)[10]);
int g(char(*)[20]); // different from g(char(*)[10]);
```

— *end example*]

- (3.3) — Parameter declarations that differ only in that one is a function type and the other is a pointer to the same function type are equivalent. That is, the function type is adjusted to become a pointer to function type (11.3.5). [ *Example*:

```

void h(int());
void h(int (*)()); // redeclaration of h(int())
void h(int x()) { } // definition of h(int())
void h(int (*x)()) { } // ill-formed: redefinition of h(int())

```

— end example]

- (3.4) — Parameter declarations that differ only in the presence or absence of **const** and/or **volatile** are equivalent. That is, the **const** and **volatile** type-specifiers for each parameter type are ignored when determining which function is being declared, defined, or called. [ *Example:*

```

typedef const int cInt;

int f (int);
int f (const int); // redeclaration of f(int)
int f (int) { /* ... */ } // definition of f(int)
int f (cInt) { /* ... */ } // error: redefinition of f(int)

```

— end example]

Only the **const** and **volatile** type-specifiers at the outermost level of the parameter type specification are ignored in this fashion; **const** and **volatile** type-specifiers buried within a parameter type specification are significant and can be used to distinguish overloaded function declarations.<sup>123</sup> In particular, for any type T, “pointer to T”, “pointer to **const** T”, and “pointer to **volatile** T” are considered distinct parameter types, as are “reference to T”, “reference to **const** T”, and “reference to **volatile** T”.

- (3.5) — Two parameter declarations that differ only in their default arguments are equivalent. [ *Example:* Consider the following:

```

void f (int i, int j);
void f (int i, int j = 99); // OK: redeclaration of f(int, int)
void f (int i = 88, int j); // OK: redeclaration of f(int, int)
void f (); // OK: overloaded declaration of f

void prog () {
 f (1, 2); // OK: call f(int, int)
 f (1); // OK: call f(int, int)
 f (); // Error: f(int, int) or f()?
}

```

— end example]

— end note]

## 16.2 Declaration matching

[over.dcl]

- <sup>1</sup> Two function declarations of the same name refer to the same function if they are in the same scope and have equivalent parameter declarations (16.1). A function member of a derived class is *not* in the same scope as a function member of the same name in a base class. [ *Example:*

```

struct B {
 int f(int);
};

struct D : B {
 int f(const char*);
}

```

123) When a parameter type includes a function type, such as in the case of a parameter type that is a pointer to function, the **const** and **volatile** type-specifiers at the outermost level of the parameter type specifications for the inner function type are also ignored.



```
};
```

Here `D::f(const char*)` hides `B::f(int)` rather than overloading it.

```
void h(D* pd) {
 pd->f(1); // error:
 // D::f(const char*) hides B::f(int)
 pd->B::f(1); // OK
 pd->f("Ben"); // OK, calls D::f
}
```

— end example]

- 2 A locally declared function is not in the same scope as a function in a containing scope. [Example:

```
void f(const char*);
void g() {
 extern void f(int);
 f("asdf"); // error: f(int) hides f(const char*)
 // so there is no f(const char*) in this scope
}
```

```
void caller () {
 extern void callee(int, int);
 {
 extern void callee(int); // hides callee(int, int)
 callee(88, 99); // error: only callee(int) in scope
 }
}
```

— end example]

- 3 Different versions of an overloaded member function can be given different access rules. [Example:

```
class buffer {
private:
 char* p;
 int size;
protected:
 buffer(int s, char* store) { size = s; p = store; }
public:
 buffer(int s) { p = new char[size = s]; }
};
```

— end example]

### 16.3 Overload resolution

[over.match]

- <sup>1</sup> Overload resolution is a mechanism for selecting the best function to call given a list of expressions that are to be the arguments of the call and a set of *candidate functions* that can be called based on the context of the call. The selection criteria for the best function are the number of arguments, how well the arguments match the parameter-type-list of the candidate function, how well (for non-static member functions) the object matches the implicit object parameter, and certain other properties of the candidate function. [Note: The function selected by overload resolution is not guaranteed to be appropriate for the context. Other restrictions, such as the accessibility of the function, can make its use in the calling context ill-formed. — end note]
- <sup>2</sup> Overload resolution selects the function to call in seven distinct contexts within the language:
- (2.1) — invocation of a function named in the function call syntax (16.3.1.1.1);
  - (2.2) — invocation of a function call operator, a pointer-to-function conversion function, a reference-to-pointer-

to-function conversion function, or a reference-to-function conversion function on a class object named in the function call syntax (16.3.1.1.2);

- (2.3) — invocation of the operator referenced in an expression (16.3.1.2);
- (2.4) — invocation of a constructor for default- or direct-initialization (11.6) of a class object (16.3.1.3);
- (2.5) — invocation of a user-defined conversion for copy-initialization (11.6) of a class object (16.3.1.4);
- (2.6) — invocation of a conversion function for initialization of an object of a non-class type from an expression of class type (16.3.1.5); and
- (2.7) — invocation of a conversion function for conversion to a glvalue or class prvalue to which a reference (11.6.3) will be directly bound (16.3.1.6).

Each of these contexts defines the set of candidate functions and the list of arguments in its own unique way. But, once the candidate functions and argument lists have been identified, the selection of the best function is the same in all cases:

- (2.8) — First, a subset of the candidate functions (those that have the proper number of arguments and meet certain other conditions) is selected to form a set of viable functions (16.3.2).
  - (2.9) — Then the best viable function is selected based on the implicit conversion sequences (16.3.3.1) needed to match each argument to the corresponding parameter of each viable function.
- 3 If a best viable function exists and is unique, overload resolution succeeds and produces it as the result. Otherwise overload resolution fails and the invocation is ill-formed. When overload resolution succeeds, and the best viable function is not accessible (Clause 14) in the context in which it is used, the program is ill-formed.

### 16.3.1 Candidate functions and argument lists

[over.match.funcs]

- 1 The subclauses of 16.3.1 describe the set of candidate functions and the argument list submitted to overload resolution in each of the seven contexts in which overload resolution is used. The source transformations and constructions defined in these subclauses are only for the purpose of describing the overload resolution process. An implementation is not required to use such transformations and constructions.
- 2 The set of candidate functions can contain both member and non-member functions to be resolved against the same argument list. So that argument and parameter lists are comparable within this heterogeneous set, a member function is considered to have an extra parameter, called the *implicit object parameter*, which represents the object for which the member function has been called. For the purposes of overload resolution, both static and non-static member functions have an implicit object parameter, but constructors do not.
- 3 Similarly, when appropriate, the context can construct an argument list that contains an *implied object argument* to denote the object to be operated on. Since arguments and parameters are associated by position within their respective lists, the convention is that the implicit object parameter, if present, is always the first parameter and the implied object argument, if present, is always the first argument.
- 4 For non-static member functions, the type of the implicit object parameter is
  - (4.1) — “lvalue reference to *cv* **X**” for functions declared without a *ref-qualifier* or with the *& ref-qualifier*
  - (4.2) — “rvalue reference to *cv* **X**” for functions declared with the *&& ref-qualifier*

where **X** is the class of which the function is a member and *cv* is the cv-qualification on the member function declaration. [ *Example:* For a **const** member function of class **X**, the extra parameter is assumed to have type “reference to **const** **X**”. — *end example* ] For conversion functions, the function is considered to be a member of the class of the implied object argument for the purpose of defining the type of the implicit object parameter. For non-conversion functions introduced by a *using-declaration* into a derived class, the function is considered to be a member of the derived class for the purpose of defining the type of the implicit object parameter. For static member functions, the implicit object parameter is considered to match any

object (since if the function is selected, the object is discarded). [ *Note*: No actual type is established for the implicit object parameter of a static member function, and no attempt will be made to determine a conversion sequence for that parameter (16.3.3). — *end note*]

- 5 During overload resolution, the implied object argument is indistinguishable from other arguments. The implicit object parameter, however, retains its identity since no user-defined conversions can be applied to achieve a type match with it. For non-static member functions declared without a *ref-qualifier*, an additional rule applies:
  - (5.1) — even if the implicit object parameter is not const-qualified, an rvalue can be bound to the parameter as long as in all other respects the argument can be converted to the type of the implicit object parameter. [ *Note*: The fact that such an argument is an rvalue does not affect the ranking of implicit conversion sequences (16.3.3.2). — *end note*]
- 6 Because other than in list-initialization only one user-defined conversion is allowed in an implicit conversion sequence, special rules apply when selecting the best user-defined conversion (16.3.3, 16.3.3.1). [ *Example*:

```
class T {
public:
 T();
};

class C : T {
public:
 C(int);
};
T a = 1; // ill-formed: T(C(1)) not tried
```

— *end example*]

- 7 In each case where a candidate is a function template, candidate function template specializations are generated using template argument deduction (17.8.3, 17.8.2). Those candidates are then handled as candidate functions in the usual way.<sup>124</sup> A given name can refer to one or more function templates and also to a set of overloaded non-template functions. In such a case, the candidate functions generated from each function template are combined with the set of non-template candidate functions.
- 8 A defaulted move constructor or assignment operator (15.8) that is defined as deleted is excluded from the set of candidate functions in all contexts.

### 16.3.1.1 Function call syntax

[over.match.call]

- 1 In a function call (8.2.2)

*postfix-expression* ( *expression-list*<sub>opt</sub> )

if the *postfix-expression* denotes a set of overloaded functions and/or function templates, overload resolution is applied as specified in 16.3.1.1.1. If the *postfix-expression* denotes an object of class type, overload resolution is applied as specified in 16.3.1.1.2.

- 2 If the *postfix-expression* denotes the address of a set of overloaded functions and/or function templates, overload resolution is applied using that set as described above. If the function selected by overload resolution is a non-static member function, the program is ill-formed. [ *Note*: The resolution of the address of an overload set in other contexts is described in 16.4. — *end note*]

<sup>124</sup>) The process of argument deduction fully determines the parameter types of the function template specializations, i.e., the parameters of function template specializations contain no template parameter types. Therefore, except where specified otherwise, function template specializations and non-template functions (11.3.5) are treated equivalently for the remainder of overload resolution.

**16.3.1.1.1 Call to named function****[over.call.func]**

- <sup>1</sup> Of interest in 16.3.1.1.1 are only those function calls in which the *postfix-expression* ultimately contains a name that denotes one or more functions that might be called. Such a *postfix-expression*, perhaps nested arbitrarily deep in parentheses, has one of the following forms:

*postfix-expression*:

```

postfix-expression . id-expression
postfix-expression -> id-expression
primary-expression
```

These represent two syntactic subcategories of function calls: qualified function calls and unqualified function calls.

- <sup>2</sup> In qualified function calls, the name to be resolved is an *id-expression* and is preceded by an -> or . operator. Since the construct A->B is generally equivalent to (\*A).B, the rest of Clause 16 assumes, without loss of generality, that all member function calls have been normalized to the form that uses an object and the . operator. Furthermore, Clause 16 assumes that the *postfix-expression* that is the left operand of the . operator has type “cv T” where T denotes a class<sup>125</sup>. Under this assumption, the *id-expression* in the call is looked up as a member function of T following the rules for looking up names in classes (13.2). The function declarations found by that lookup constitute the set of candidate functions. The argument list is the *expression-list* in the call augmented by the addition of the left operand of the . operator in the normalized member function call as the implied object argument (16.3.1).
- <sup>3</sup> In unqualified function calls, the name is not qualified by an -> or . operator and has the more general form of a *primary-expression*. The name is looked up in the context of the function call following the normal rules for name lookup in function calls (6.4). The function declarations found by that lookup constitute the set of candidate functions. Because of the rules for name lookup, the set of candidate functions consists (1) entirely of non-member functions or (2) entirely of member functions of some class T. In case (1), the argument list is the same as the *expression-list* in the call. In case (2), the argument list is the *expression-list* in the call augmented by the addition of an implied object argument as in a qualified function call. If the keyword **this** (12.2.2.1) is in scope and refers to class T, or a derived class of T, then the implied object argument is (\*this). If the keyword **this** is not in scope or refers to another class, then a contrived object of type T becomes the implied object argument<sup>126</sup>. If the argument list is augmented by a contrived object and overload resolution selects one of the non-static member functions of T, the call is ill-formed.

**16.3.1.1.2 Call to object of class type****[over.call.object]**

- <sup>1</sup> If the *primary-expression* E in the function call syntax evaluates to a class object of type “cv T”, then the set of candidate functions includes at least the function call operators of T. The function call operators of T are obtained by ordinary lookup of the name **operator()** in the context of (E).**operator()**.
- <sup>2</sup> In addition, for each non-explicit conversion function declared in T of the form

```
operator conversion-type-id () cv-qualifier ref-qualifieropt noexcept-specifieropt attribute-specifier-seqopt ;
```

where *cv-qualifier* is the same cv-qualification as, or a greater cv-qualification than, *cv*, and where *conversion-type-id* denotes the type “pointer to function of (P<sub>1</sub>, ..., P<sub>n</sub>) returning R”, or the type “reference to pointer to function of (P<sub>1</sub>, ..., P<sub>n</sub>) returning R”, or the type “reference to function of (P<sub>1</sub>, ..., P<sub>n</sub>) returning R”, a *surrogate call function* with the unique name *call-function* and having the form

```
R call-function (conversion-type-id F, P1 a1, ..., Pn an) { return F (a1, ..., an); }
```

is also considered as a candidate function. Similarly, surrogate call functions are added to the set of candidate functions for each non-explicit conversion function declared in a base class of T provided the function is not

<sup>125</sup>) Note that cv-qualifiers on the type of objects are significant in overload resolution for both glvalue and class prvalue objects.

<sup>126</sup>) An implied object argument must be contrived to correspond to the implicit object parameter attributed to member functions during overload resolution. It is not used in the call to the selected function. Since the member functions all have the same implicit object parameter, the contrived object will not be the cause to select or reject a function.

hidden within T by another intervening declaration<sup>127</sup>.

- <sup>3</sup> If such a surrogate call function is selected by overload resolution, the corresponding conversion function will be called to convert E to the appropriate function pointer or reference, and the function will then be invoked with the arguments of the call. If the conversion function cannot be called (e.g., because of an ambiguity), the program is ill-formed.
- <sup>4</sup> The argument list submitted to overload resolution consists of the argument expressions present in the function call syntax preceded by the implied object argument (E). [Note: When comparing the call against the function call operators, the implied object argument is compared against the implicit object parameter of the function call operator. When comparing the call against a surrogate call function, the implied object argument is compared against the first parameter of the surrogate call function. The conversion function from which the surrogate call function was derived will be used in the conversion sequence for that parameter since it converts the implied object argument to the appropriate function pointer or reference required by that first parameter. — end note] [Example:

```
int f1(int);
int f2(float);
typedef int (*fp1)(int);
typedef int (*fp2)(float);
struct A {
 operator fp1() { return f1; }
 operator fp2() { return f2; }
} a;
int i = a(1); // calls f1 via pointer returned from conversion function
— end example]
```

### 16.3.1.2 Operators in expressions

[over.match.oper]

- <sup>1</sup> If no operand of an operator in an expression has a type that is a class or an enumeration, the operator is assumed to be a built-in operator and interpreted according to Clause 8. [Note: Because ., .\*, and :: cannot be overloaded, these operators are always built-in operators interpreted according to Clause 8. ?: cannot be overloaded, but the rules in this subclause are used to determine the conversions to be applied to the second and third operands when they have class or enumeration type (8.16). — end note] [Example:

```
struct String {
 String (const String&);
 String (const char*);
 operator const char* ();
};
String operator + (const String&, const String&);

void f() {
 const char* p= "one" + "two"; // ill-formed because neither operand has class or enumeration type
 int I = 1 + 1; // always evaluates to 2 even if class or enumeration types exist
 // that would perform the operation.
}
— end example]
```

- <sup>2</sup> If either operand has a type that is a class or an enumeration, a user-defined operator function might be declared that implements this operator or a user-defined conversion can be necessary to convert the operand to a type that is appropriate for a built-in operator. In this case, overload resolution is used to determine which operator function or built-in operator is to be invoked to implement the operator. Therefore, the operator

127) Note that this construction can yield candidate call functions that cannot be differentiated one from the other by overload resolution because they have identical declarations or differ only in their return type. The call will be ambiguous if overload resolution cannot select a match to the call that is uniquely better than such undifferentiable functions.

notation is first transformed to the equivalent function-call notation as summarized in Table 12 (where @ denotes one of the operators covered in the specified subclause). However, the operands are sequenced in the order prescribed for the built-in operator (Clause 8).

Table 12 — Relationship between operator and function call notation

| Subclause | Expression | As member function | As non-member function |
|-----------|------------|--------------------|------------------------|
| 16.5.1    | @a         | (a).operator@ ( )  | operator@(a)           |
| 16.5.2    | a@b        | (a).operator@ (b)  | operator@(a, b)        |
| 16.5.3    | a=b        | (a).operator= (b)  |                        |
| 16.5.5    | a[b]       | (a).operator[] (b) |                        |
| 16.5.6    | a->        | (a).operator->( )  |                        |
| 16.5.7    | a@         | (a).operator@ (0)  | operator@(a, 0)        |

- <sup>3</sup> For a unary operator @ with an operand of a type whose cv-unqualified version is T1, and for a binary operator @ with a left operand of a type whose cv-unqualified version is T1 and a right operand of a type whose cv-unqualified version is T2, three sets of candidate functions, designated *member candidates*, *non-member candidates* and *built-in candidates*, are constructed as follows:
- (3.1) — If T1 is a complete class type or a class currently being defined, the set of member candidates is the result of the qualified lookup of T1::operator@ (16.3.1.1.1); otherwise, the set of member candidates is empty.
  - (3.2) — The set of non-member candidates is the result of the unqualified lookup of operator@ in the context of the expression according to the usual rules for name lookup in unqualified function calls (6.4.2) except that all member functions are ignored. However, if no operand has a class type, only those non-member functions in the lookup set that have a first parameter of type T1 or “reference to cv T1”, when T1 is an enumeration type, or (if there is a right operand) a second parameter of type T2 or “reference to cv T2”, when T2 is an enumeration type, are candidate functions.
  - (3.3) — For the operator ,, the unary operator &, or the operator ->, the built-in candidates set is empty. For all other operators, the built-in candidates include all of the candidate operator functions defined in 16.6 that, compared to the given operator,
    - (3.3.1) — have the same operator name, and
    - (3.3.2) — accept the same number of operands, and
    - (3.3.3) — accept operand types to which the given operand or operands can be converted according to 16.3.3.1, and
    - (3.3.4) — do not have the same parameter-type-list as any non-member candidate that is not a function template specialization.
- <sup>4</sup> For the built-in assignment operators, conversions of the left operand are restricted as follows:
- (4.1) — no temporaries are introduced to hold the left operand, and
  - (4.2) — no user-defined conversions are applied to the left operand to achieve a type match with the left-most parameter of a built-in candidate.
- <sup>5</sup> For all other operators, no such restrictions apply.
- <sup>6</sup> The set of candidate functions for overload resolution is the union of the member candidates, the non-member candidates, and the built-in candidates. The argument list contains all of the operands of the operator. The best function from the set of candidate functions is selected according to 16.3.2 and 16.3.3.<sup>128</sup> [Example:

<sup>128</sup>) If the set of candidate functions is empty, overload resolution is unsuccessful.

```

struct A {
 operator int();
};
A operator+(const A&, const A&);
void m() {
 A a, b;
 a + b; // operator+(a, b) chosen over int(a) + int(b)
}

```

— end example]

- <sup>7</sup> If a built-in candidate is selected by overload resolution, the operands of class type are converted to the types of the corresponding parameters of the selected operation function, except that the second standard conversion sequence of a user-defined conversion sequence (16.3.3.1.2) is not applied. Then the operator is treated as the corresponding built-in operator and interpreted according to Clause 8. [ *Example:*

```

struct X {
 operator double();
};

struct Y {
 operator int*();
};

int *a = Y() + 100.0; // error: pointer arithmetic requires integral operand
int *b = Y() + X(); // error: pointer arithmetic requires integral operand

```

— end example]

- <sup>8</sup> The second operand of operator -> is ignored in selecting an **operator->** function, and is not an argument when the **operator->** function is called. When **operator->** returns, the operator -> is applied to the value returned, with the original second operand.<sup>129</sup>
- <sup>9</sup> If the operator is the operator ,, the unary operator &, or the operator ->, and there are no viable functions, then the operator is assumed to be the built-in operator and interpreted according to Clause 8.
- <sup>10</sup> [ *Note:* The lookup rules for operators in expressions are different than the lookup rules for operator function names in a function call, as shown in the following example:

```

struct A { };
void operator + (A, A);

struct B {
 void operator + (B);
 void f ();
};

A a;

void B::f() {
 operator+ (a,a); // error: global operator hidden by member
 a + a; // OK: calls global operator+
}

```

— end note]

---

<sup>129</sup> If the value returned by the **operator->** function has class type, this may result in selecting and calling another **operator->** function. The process repeats until an **operator->** function returns a value of non-class type.



**16.3.1.3 Initialization by constructor****[over.match.ctor]**

- <sup>1</sup> When objects of class type are direct-initialized (11.6), copy-initialized from an expression of the same or a derived class type (11.6), or default-initialized (11.6), overload resolution selects the constructor. For direct-initialization or default-initialization that is not in the context of copy-initialization, the candidate functions are all the constructors of the class of the object being initialized. For copy-initialization, the candidate functions are all the converting constructors (15.3.1) of that class. The argument list is the *expression-list* or *assignment-expression* of the *initializer*.

**16.3.1.4 Copy-initialization of class by user-defined conversion****[over.match.copy]**

- <sup>1</sup> Under the conditions specified in 11.6, as part of a copy-initialization of an object of class type, a user-defined conversion can be invoked to convert an initializer expression to the type of the object being initialized. Overload resolution is used to select the user-defined conversion to be invoked. [Note: The conversion performed for indirect binding to a reference to a possibly cv-qualified class type is determined in terms of a corresponding non-reference copy-initialization. — end note] Assuming that “*cv1 T*” is the type of the object being initialized, with T a class type, the candidate functions are selected as follows:
- (1.1) — The converting constructors (15.3.1) of T are candidate functions.
  - (1.2) — When the type of the initializer expression is a class type “*cv S*”, the non-explicit conversion functions of S and its base classes are considered. When initializing a temporary to be bound to the first parameter of a constructor where the parameter is of type “reference to possibly *cv*-qualified T” and the constructor is called with a single argument in the context of direct-initialization of an object of type “*cv2 T*”, explicit conversion functions are also considered. Those that are not hidden within S and yield a type whose cv-unqualified version is the same type as T or is a derived class thereof are candidate functions. Conversion functions that return “reference to X” return lvalues or xvalues, depending on the type of reference, of type X and are therefore considered to yield X for this process of selecting candidate functions.
- <sup>2</sup> In both cases, the argument list has one argument, which is the initializer expression. [Note: This argument will be compared against the first parameter of the constructors and against the implicit object parameter of the conversion functions. — end note]

**16.3.1.5 Initialization by conversion function****[over.match.conv]**

- <sup>1</sup> Under the conditions specified in 11.6, as part of an initialization of an object of non-class type, a conversion function can be invoked to convert an initializer expression of class type to the type of the object being initialized. Overload resolution is used to select the conversion function to be invoked. Assuming that “*cv1 T*” is the type of the object being initialized, and “*cv S*” is the type of the initializer expression, with S a class type, the candidate functions are selected as follows:
- (1.1) — The conversion functions of S and its base classes are considered. Those non-explicit conversion functions that are not hidden within S and yield type T or a type that can be converted to type T via a standard conversion sequence (16.3.3.1.1) are candidate functions. For direct-initialization, those explicit conversion functions that are not hidden within S and yield type T or a type that can be converted to type T with a qualification conversion (7.5) are also candidate functions. Conversion functions that return a cv-qualified type are considered to yield the cv-unqualified version of that type for this process of selecting candidate functions. Conversion functions that return “reference to *cv2 X*” return lvalues or xvalues, depending on the type of reference, of type “*cv2 X*” and are therefore considered to yield X for this process of selecting candidate functions.
- <sup>2</sup> The argument list has one argument, which is the initializer expression. [Note: This argument will be compared against the implicit object parameter of the conversion functions. — end note]



**16.3.1.6 Initialization by conversion function for direct reference binding** [over.match.ref]

- <sup>1</sup> Under the conditions specified in 11.6.3, a reference can be bound directly to a glvalue or class prvalue that is the result of applying a conversion function to an initializer expression. Overload resolution is used to select the conversion function to be invoked. Assuming that “reference to *cv1* T” is the type of the reference being initialized, and “*cv* S” is the type of the initializer expression, with S a class type, the candidate functions are selected as follows:
  - (1.1) — The conversion functions of S and its base classes are considered. Those non-explicit conversion functions that are not hidden within S and yield type “lvalue reference to *cv2* T2” (when initializing an lvalue reference or an rvalue reference to function) or “*cv2* T2” or “rvalue reference to *cv2* T2” (when initializing an rvalue reference or an lvalue reference to function), where “*cv1* T” is reference-compatible (11.6.3) with “*cv2* T2”, are candidate functions. For direct-initialization, those explicit conversion functions that are not hidden within S and yield type “lvalue reference to *cv2* T2” or “*cv2* T2” or “rvalue reference to *cv2* T2”, respectively, where T2 is the same type as T or can be converted to type T with a qualification conversion (7.5), are also candidate functions.
- <sup>2</sup> The argument list has one argument, which is the initializer expression. [Note: This argument will be compared against the implicit object parameter of the conversion functions. — end note]

**16.3.1.7 Initialization by list-initialization** [over.match.list]

- <sup>1</sup> When objects of non-aggregate class type T are list-initialized such that 11.6.4 specifies that overload resolution is performed according to the rules in this section, overload resolution selects the constructor in two phases:
  - (1.1) — Initially, the candidate functions are the initializer-list constructors (11.6.4) of the class T and the argument list consists of the initializer list as a single argument.
  - (1.2) — If no viable initializer-list constructor is found, overload resolution is performed again, where the candidate functions are all the constructors of the class T and the argument list consists of the elements of the initializer list.

If the initializer list has no elements and T has a default constructor, the first phase is omitted. In copy-list-initialization, if an **explicit** constructor is chosen, the initialization is ill-formed. [Note: This differs from other situations (16.3.1.3, 16.3.1.4), where only converting constructors are considered for copy-initialization. This restriction only applies if this initialization is part of the final result of overload resolution. — end note]

**16.3.1.8 Class template argument deduction** [over.match.class.deduct]

- <sup>1</sup> A set of functions and function templates is formed comprising:
  - (1.1) — For each constructor of the primary class template designated by the *template-name*, if the template is defined, a function template with the following properties:
    - (1.1.1) — The template parameters are the template parameters of the class template followed by the template parameters (including default template arguments) of the constructor, if any.
    - (1.1.2) — The types of the function parameters are those of the constructor.
    - (1.1.3) — The return type is the class template specialization designated by the *template-name* and template arguments corresponding to the template parameters obtained from the class template.
  - (1.2) — If the primary class template C is not defined or does not declare any constructors, an additional function template derived as above from a hypothetical constructor C().
  - (1.3) — An additional function template derived as above from a hypothetical constructor C(C), called the *copy deduction candidate*.
  - (1.4) — For each *deduction-guide*, a function or function template with the following properties:
    - (1.4.1) — The template parameters, if any, and function parameters are those of the *deduction-guide*.

(1.4.2) — The return type is the *simple-template-id* of the *deduction-guide*.

- <sup>2</sup> Initialization and overload resolution are performed as described in 11.6 and 16.3.1.3, 16.3.1.4, or 16.3.1.7 (as appropriate for the type of initialization performed) for an object of a hypothetical class type, where the selected functions and function templates are considered to be the constructors of that class type for the purpose of forming an overload set, and the initializer is provided by the context in which class template argument deduction was performed. Each such notional constructor is considered to be explicit if the function or function template was generated from a constructor or *deduction-guide* that was declared **explicit**. All such notional constructors are considered to be public members of the hypothetical class type.

<sup>3</sup> [Example:

```
template <class T> struct A {
 explicit A(const T&, ...) noexcept; // #1
 A(T&&, ...); // #2
};

int i;
A a1 = { i, i }; // error: explicit constructor #1 selected in copy-list-initialization during deduction,
 // cannot deduce from non-forwarding rvalue reference in #2

A a2{i, i}; // OK, #1 deduces to A<int> and also initializes
A a3{0, i}; // OK, #2 deduces to A<int> and also initializes
A a4 = {0, i}; // OK, #2 deduces to A<int> and also initializes

template <class T> A(const T&, const T&) -> A<T&&>; // #3
template <class T> explicit A(T&&, T&&) -> A<T>; // #4

A a5 = {0, 1}; // error: explicit deduction guide #4 selected in copy-list-initialization during deduction
A a6{0,1}; // OK, #4 deduces to A<int> and #2 initializes
A a7 = {0, i}; // error: #3 deduces to A<int&&>, #1 and #2 declare same constructor
A a8{0,i}; // error: #3 deduces to A<int&&>, #1 and #2 declare same constructor

template <class T> struct B {
 template <class U> using TA = T;
 template <class U> B(U, TA<U>);
};

B b{(int*)0, (char*)0}; // OK, deduces B<char*>
```

— end example]

### 16.3.2 Viable functions

[over.match.viable]

- <sup>1</sup> From the set of candidate functions constructed for a given context (16.3.1), a set of viable functions is chosen, from which the best function will be selected by comparing argument conversion sequences for the best fit (16.3.3). The selection of viable functions considers relationships between arguments and function parameters other than the ranking of conversion sequences.
- <sup>2</sup> First, to be a viable function, a candidate function shall have enough parameters to agree in number with the arguments in the list.
- (2.1) — If there are  $m$  arguments in the list, all candidate functions having exactly  $m$  parameters are viable.
- (2.2) — A candidate function having fewer than  $m$  parameters is viable only if it has an ellipsis in its parameter list (11.3.5). For the purposes of overload resolution, any argument for which there is no corresponding parameter is considered to “match the ellipsis” (16.3.3.1.3) .
- (2.3) — A candidate function having more than  $m$  parameters is viable only if the  $(m+1)$ -st parameter has a

default argument (11.3.6).<sup>130</sup> For the purposes of overload resolution, the parameter list is truncated on the right, so that there are exactly  $m$  parameters.

- <sup>3</sup> Second, for  $F$  to be a viable function, there shall exist for each argument an *implicit conversion sequence* (16.3.3.1) that converts that argument to the corresponding parameter of  $F$ . If the parameter has reference type, the implicit conversion sequence includes the operation of binding the reference, and the fact that an lvalue reference to non-`const` cannot be bound to an rvalue and that an rvalue reference cannot be bound to an lvalue can affect the viability of the function (see 16.3.3.1.4).

### 16.3.3 Best viable function

[over.match.best]

- <sup>1</sup> Define  $ICS_i(F)$  as follows:

- (1.1) — If  $F$  is a static member function,  $ICS_1(F)$  is defined such that  $ICS_1(F)$  is neither better nor worse than  $ICS_1(G)$  for any function  $G$ , and, symmetrically,  $ICS_1(G)$  is neither better nor worse than  $ICS_1(F)$ ;<sup>131</sup> otherwise,
- (1.2) — let  $ICS_i(F)$  denote the implicit conversion sequence that converts the  $i$ -th argument in the list to the type of the  $i$ -th parameter of viable function  $F$ . 16.3.3.1 defines the implicit conversion sequences and 16.3.3.2 defines what it means for one implicit conversion sequence to be a better conversion sequence or worse conversion sequence than another.

Given these definitions, a viable function  $F_1$  is defined to be a *better* function than another viable function  $F_2$  if for all arguments  $i$ ,  $ICS_i(F_1)$  is not a worse conversion sequence than  $ICS_i(F_2)$ , and then

- (1.3) — for some argument  $j$ ,  $ICS_j(F_1)$  is a better conversion sequence than  $ICS_j(F_2)$ , or, if not that,
- (1.4) — the context is an initialization by user-defined conversion (see 11.6, 16.3.1.5, and 16.3.1.6) and the standard conversion sequence from the return type of  $F_1$  to the destination type (i.e., the type of the entity being initialized) is a better conversion sequence than the standard conversion sequence from the return type of  $F_2$  to the destination type [ *Example*:

```
struct A {
 A();
 operator int();
 operator double();
} a;
int i = a; // a.operator int() followed by no conversion is better than
 // a.operator double() followed by a conversion to int
float x = a; // ambiguous: both possibilities require conversions,
 // and neither is better than the other
```

— *end example*] or, if not that,

- (1.5) — the context is an initialization by conversion function for direct reference binding (16.3.1.6) of a reference to function type, the return type of  $F_1$  is the same kind of reference (i.e. lvalue or rvalue) as the reference being initialized, and the return type of  $F_2$  is not [ *Example*:

```
template <class T> struct A {
 operator T&(); // #1
 operator T&&(); // #2
};
typedef int Fn();
A<Fn> a;
Fn& lf = a; // calls #1
Fn&& rf = a; // calls #2
```

<sup>130</sup>) According to 11.3.6, parameters following the  $(m+1)$ -st parameter must also have default arguments.

<sup>131</sup>) If a function is a static member function, this definition means that the first argument, the implied object argument, has no effect in the determination of whether the function is better or worse than any other function.

— *end example*] or, if not that,

- (1.6) — F1 is not a function template specialization and F2 is a function template specialization, or, if not that,
  - (1.7) — F1 and F2 are function template specializations, and the function template for F1 is more specialized than the template for F2 according to the partial ordering rules described in 17.5.6.2, or, if not that,
  - (1.8) — F1 is generated from a *deduction-guide* (16.3.1.8) and F2 is not, or, if not that,
  - (1.9) — F1 is the copy deduction candidate (16.3.1.8) and F2 is not, or, if not that,
  - (1.10) — F1 is generated from a non-template constructor and F2 is generated from a constructor template.
- [ *Example*:

```
template <class T> struct A {
 using value_type = T;
 A(value_type); // #1
 A(const A&); // #2
 A(T, T, int); // #3
 template<class U>
 A(int, T, U); // #4
 // #5 is the copy deduction candidate, A(A)
};

A x(1, 2, 3); // uses #3, generated from a non-template constructor

template <class T>
A(T) -> A<T>; // #6, less specialized than #5

A a(42); // uses #6 to deduce A<int> and #1 to initialize
A b = a; // uses #5 to deduce A<int> and #2 to initialize

template <class T>
A(A<T>) -> A<A<T>>; // #7, as specialized as #5

A b2 = a; // uses #7 to deduce A<A<int>> and #1 to initialize
```

— *end example*]

- <sup>2</sup> If there is exactly one viable function that is a better function than all other viable functions, then it is the one selected by overload resolution; otherwise the call is ill-formed.<sup>132</sup> [ *Example*:

```
void Fcn(const int*, short);
void Fcn(int*, int);

int i;
short s = 0;

void f() {
 Fcn(&i, s); // is ambiguous because &i → int* is better than &i → const int*
 // but s → short is also better than s → int

 Fcn(&i, 1L); // calls Fcn(int*, int), because &i → int* is better than &i → const int*
 // and 1L → short and 1L → int are indistinguishable
```

132) The algorithm for selecting the best viable function is linear in the number of viable functions. Run a simple tournament to find a function W that is not worse than any opponent it faced. Although another function F that W did not face might be at least as good as W, F cannot be the best function because at some point in the tournament F encountered another function G such that F was not better than G. Hence, W is either the best function or there is no best function. So, make a second pass over the viable functions to verify that W is better than all other functions.

```

 Fcn(&i, 'c'); // calls Fcn(int*, int), because &i → int* is better than &i → const int*
 // and c → int is better than c → short
}

```

— end example]

- <sup>3</sup> If the best viable function resolves to a function for which multiple declarations were found, and if at least two of these declarations — or the declarations they refer to in the case of *using-declarations* — specify a default argument that made the function viable, the program is ill-formed. [ *Example*:

```

namespace A {
 extern "C" void f(int = 5);
}
namespace B {
 extern "C" void f(int = 5);
}

using A::f;
using B::f;

void use() {
 f(3); // OK, default argument was not used for viability
 f(); // Error: found default argument twice
}

```

— end example]

### 16.3.3.1 Implicit conversion sequences

[over.best.ics]

- <sup>1</sup> An *implicit conversion sequence* is a sequence of conversions used to convert an argument in a function call to the type of the corresponding parameter of the function being called. The sequence of conversions is an implicit conversion as defined in Clause 7, which means it is governed by the rules for initialization of an object or reference by a single expression (11.6, 11.6.3).
- <sup>2</sup> Implicit conversion sequences are concerned only with the type, cv-qualification, and value category of the argument and how these are converted to match the corresponding properties of the parameter. Other properties, such as the lifetime, storage class, alignment, accessibility of the argument, whether the argument is a bit-field, and whether a function is deleted (11.4.3), are ignored. So, although an implicit conversion sequence can be defined for a given argument-parameter pair, the conversion from the argument to the parameter might still be ill-formed in the final analysis.
- <sup>3</sup> A well-formed implicit conversion sequence is one of the following forms:
- (3.1) — a *standard conversion sequence* (16.3.3.1.1),
  - (3.2) — a *user-defined conversion sequence* (16.3.3.1.2), or
  - (3.3) — an *ellipsis conversion sequence* (16.3.3.1.3).
- <sup>4</sup> However, if the target is
- (4.1) — the first parameter of a constructor or
  - (4.2) — the implicit object parameter of a user-defined conversion function
- and the constructor or user-defined conversion function is a candidate by
- (4.3) — 16.3.1.3, when the argument is the temporary in the second step of a class copy-initialization,
  - (4.4) — 16.3.1.4, 16.3.1.5, or 16.3.1.6 (in all cases), or
  - (4.5) — the second phase of 16.3.1.7 when the initializer list has exactly one element that is itself an initializer list, and the target is the first parameter of a constructor of class X, and the conversion is to X or

reference to *cv* X,

user-defined conversion sequences are not considered. [ *Note:* These rules prevent more than one user-defined conversion from being applied during overload resolution, thereby avoiding infinite recursion. — *end note* ]  
[ *Example:*

```
struct Y { Y(int); };
struct A { operator int(); };
Y y1 = A(); // error: A::operator int() is not a candidate

struct X { };
struct B { operator X(); };
B b;
X x({b}); // error: B::operator X() is not a candidate
```

— *end example*]

- 5 For the case where the parameter type is a reference, see 16.3.3.1.4.
- 6 When the parameter type is not a reference, the implicit conversion sequence models a copy-initialization of the parameter from the argument expression. The implicit conversion sequence is the one required to convert the argument expression to a prvalue of the type of the parameter. [ *Note:* When the parameter has a class type, this is a conceptual conversion defined for the purposes of Clause 16; the actual initialization is defined in terms of constructors and is not a conversion. — *end note* ] Any difference in top-level cv-qualification is subsumed by the initialization itself and does not constitute a conversion. [ *Example:* A parameter of type A can be initialized from an argument of type `const A`. The implicit conversion sequence for that case is the identity sequence; it contains no “conversion” from `const A` to A. — *end example* ] When the parameter has a class type and the argument expression has the same type, the implicit conversion sequence is an identity conversion. When the parameter has a class type and the argument expression has a derived class type, the implicit conversion sequence is a derived-to-base Conversion from the derived class to the base class. [ *Note:* There is no such standard conversion; this derived-to-base Conversion exists only in the description of implicit conversion sequences. — *end note* ] A derived-to-base Conversion has Conversion rank (16.3.3.1.1).
- 7 In all contexts, when converting to the implicit object parameter or when converting to the left operand of an assignment operation only standard conversion sequences are allowed.
- 8 If no conversions are required to match an argument to a parameter type, the implicit conversion sequence is the standard conversion sequence consisting of the identity conversion (16.3.3.1.1).
- 9 If no sequence of conversions can be found to convert an argument to a parameter type, an implicit conversion sequence cannot be formed.
- 10 If several different sequences of conversions exist that each convert the argument to the parameter type, the implicit conversion sequence associated with the parameter is defined to be the unique conversion sequence designated the *ambiguous conversion sequence*. For the purpose of ranking implicit conversion sequences as described in 16.3.3.2, the ambiguous conversion sequence is treated as a user-defined conversion sequence that is indistinguishable from any other user-defined conversion sequence. [ *Note:* This rule prevents a function from becoming non-viable because of an ambiguous conversion sequence for one of its parameters. [ *Example:*

```
class B;
class A { A (B&); };
class B { operator A (); };
class C { C (B&); };
void f(A) { }
void f(C) { }
B b;
f(b); // ill-formed: ambiguous because there is a conversion b → C (via constructor)
```

```

// and an (ambiguous) conversion b → A (via constructor or conversion function)
void f(B) { }
f(b); // OK, unambiguous

```

— end example] — end note] If a function that uses the ambiguous conversion sequence is selected as the best viable function, the call will be ill-formed because the conversion of one of the arguments in the call is ambiguous.

- <sup>11</sup> The three forms of implicit conversion sequences mentioned above are defined in the following subclauses.

#### 16.3.3.1.1 Standard conversion sequences [over.ics.scs]

- <sup>1</sup> Table 13 summarizes the conversions defined in Clause 7 and partitions them into four disjoint categories: Lvalue Transformation, Qualification Adjustment, Promotion, and Conversion. [ *Note:* These categories are orthogonal with respect to value category, cv-qualification, and data representation: the Lvalue Transformations do not change the cv-qualification or data representation of the type; the Qualification Adjustments do not change the value category or data representation of the type; and the Promotions and Conversions do not change the value category or cv-qualification of the type. — end note ]
- <sup>2</sup> [ *Note:* As described in Clause 7, a standard conversion sequence is either the Identity conversion by itself (that is, no conversion) or consists of one to three conversions from the other four categories. If there are two or more conversions in the sequence, the conversions are applied in the canonical order: **Lvalue Transformation, Promotion or Conversion, Qualification Adjustment**. — end note ]
- <sup>3</sup> Each conversion in Table 13 also has an associated rank (Exact Match, Promotion, or Conversion). These are used to rank standard conversion sequences (16.3.3.2). The rank of a conversion sequence is determined by considering the rank of each conversion in the sequence and the rank of any reference binding (16.3.3.1.4). If any of those has Conversion rank, the sequence has Conversion rank; otherwise, if any of those has Promotion rank, the sequence has Promotion rank; otherwise, the sequence has Exact Match rank.

Table 13 — Conversions

| Conversion                     | Category                 | Rank        | Subclause |
|--------------------------------|--------------------------|-------------|-----------|
| No conversions required        | Identity                 | Exact Match |           |
| Lvalue-to-rvalue conversion    | Lvalue Transformation    |             | 7.1       |
| Array-to-pointer conversion    |                          |             | 7.2       |
| Function-to-pointer conversion |                          |             | 7.3       |
| Qualification conversions      | Qualification Adjustment |             | 7.5       |
| Function pointer conversion    |                          |             | 7.13      |
| Integral promotions            | Promotion                | Promotion   | 7.6       |
| Floating-point promotion       |                          |             | 7.7       |
| Integral conversions           | Conversion               | Conversion  | 7.8       |
| Floating-point conversions     |                          |             | 7.9       |
| Floating-integral conversions  |                          |             | 7.10      |
| Pointer conversions            |                          |             | 7.11      |
| Pointer to member conversions  |                          |             | 7.12      |
| Boolean conversions            |                          |             | 7.14      |

#### 16.3.3.1.2 User-defined conversion sequences [over.ics.user]

- <sup>1</sup> A user-defined conversion sequence consists of an initial standard conversion sequence followed by a user-defined conversion (15.3) followed by a second standard conversion sequence. If the user-defined conversion is specified by a constructor (15.3.1), the initial standard conversion sequence converts the source type to the type required by the argument of the constructor. If the user-defined conversion is specified by a conversion



function (15.3.2), the initial standard conversion sequence converts the source type to the implicit object parameter of the conversion function.

- <sup>2</sup> The second standard conversion sequence converts the result of the user-defined conversion to the target type for the sequence. Since an implicit conversion sequence is an initialization, the special rules for initialization by user-defined conversion apply when selecting the best user-defined conversion for a user-defined conversion sequence (see 16.3.3 and 16.3.3.1).
- <sup>3</sup> If the user-defined conversion is specified by a specialization of a conversion function template, the second standard conversion sequence shall have exact match rank.
- <sup>4</sup> A conversion of an expression of class type to the same class type is given Exact Match rank, and a conversion of an expression of class type to a base class of that type is given Conversion rank, in spite of the fact that a constructor (i.e., a user-defined conversion function) is called for those cases.

#### 16.3.3.1.3 Ellipsis conversion sequences

[over.ics.ellipsis]

- <sup>1</sup> An ellipsis conversion sequence occurs when an argument in a function call is matched with the ellipsis parameter specification of the function called (see 8.2.2).

#### 16.3.3.1.4 Reference binding

[over.ics.ref]

- <sup>1</sup> When a parameter of reference type binds directly (11.6.3) to an argument expression, the implicit conversion sequence is the identity conversion, unless the argument expression has a type that is a derived class of the parameter type, in which case the implicit conversion sequence is a derived-to-base Conversion (16.3.3.1). [Example:

```
struct A {};
struct B : public A {} b;
int f(A&);
int f(B&);
int i = f(b); // calls f(B&), an exact match, rather than f(A&), a conversion
```

— end example] If the parameter binds directly to the result of applying a conversion function to the argument expression, the implicit conversion sequence is a user-defined conversion sequence (16.3.3.1.2), with the second standard conversion sequence either an identity conversion or, if the conversion function returns an entity of a type that is a derived class of the parameter type, a derived-to-base Conversion.

- <sup>2</sup> When a parameter of reference type is not bound directly to an argument expression, the conversion sequence is the one required to convert the argument expression to the referenced type according to 16.3.3.1. Conceptually, this conversion sequence corresponds to copy-initializing a temporary of the referenced type with the argument expression. Any difference in top-level cv-qualification is subsumed by the initialization itself and does not constitute a conversion.
- <sup>3</sup> Except for an implicit object parameter, for which see 16.3.1, a standard conversion sequence cannot be formed if it requires binding an lvalue reference other than a reference to a non-volatile **const** type to an rvalue or binding an rvalue reference to an lvalue other than a function lvalue. [Note: This means, for example, that a candidate function cannot be a viable function if it has a non-**const** lvalue reference parameter (other than the implicit object parameter) and the corresponding argument would require a temporary to be created to initialize the lvalue reference (see 11.6.3). — end note]
- <sup>4</sup> Other restrictions on binding a reference to a particular argument that are not based on the types of the reference and the argument do not affect the formation of a standard conversion sequence, however. [Example: A function with an “lvalue reference to **int**” parameter can be a viable candidate even if the corresponding argument is an **int** bit-field. The formation of implicit conversion sequences treats the **int** bit-field as an **int** lvalue and finds an exact match with the parameter. If the function is selected by overload resolution, the call will nonetheless be ill-formed because of the prohibition on binding a non-**const** lvalue reference to a bit-field (11.6.3). — end example]



**16.3.3.1.5 List-initialization sequence****[over.ics.list]**

- <sup>1</sup> When an argument is an initializer list (11.6.4), it is not an expression and special rules apply for converting it to a parameter type.
- <sup>2</sup> If the parameter type is an aggregate class **X** and the initializer list has a single element of type *cv* **U**, where **U** is **X** or a class derived from **X**, the implicit conversion sequence is the one required to convert the element to the parameter type.
- <sup>3</sup> Otherwise, if the parameter type is a character array<sup>133</sup> and the initializer list has a single element that is an appropriately-typed string literal (11.6.2), the implicit conversion sequence is the identity conversion.
- <sup>4</sup> Otherwise, if the parameter type is `std::initializer_list<X>` and all the elements of the initializer list can be implicitly converted to **X**, the implicit conversion sequence is the worst conversion necessary to convert an element of the list to **X**, or if the initializer list has no elements, the identity conversion. This conversion can be a user-defined conversion even in the context of a call to an initializer-list constructor. [ *Example:*

```
void f(std::initializer_list<int>);
f({}); // OK: f(initializer_list<int>) identity conversion
f({1,2,3}); // OK: f(initializer_list<int>) identity conversion
f({'a','b'}); // OK: f(initializer_list<int>) integral promotion
f({1.0}); // error: narrowing
```

```
struct A {
 A(std::initializer_list<double>); // #1
 A(std::initializer_list<complex<double>>); // #2
 A(std::initializer_list<std::string>); // #3
};
A a{ 1.0, 2.0 }; // OK, uses #1
```

```
void g(A);
g({ "foo", "bar" }); // OK, uses #3
```

```
typedef int IA[3];
void h(const IA&);
h({ 1, 2, 3 }); // OK: identity conversion
```

— *end example*]

- <sup>5</sup> Otherwise, if the parameter type is “array of **N** **X**”, if there exists an implicit conversion sequence for each element of the array from the corresponding element of the initializer list (or from `{}` if there is no such element), the implicit conversion sequence is the worst such implicit conversion sequence.
- <sup>6</sup> Otherwise, if the parameter is a non-aggregate class **X** and overload resolution per 16.3.1.7 chooses a single best constructor **C** of **X** to perform the initialization of an object of type **X** from the argument initializer list:
  - (6.1) — If **C** is not an initializer-list constructor and the initializer list has a single element of type *cv* **U**, where **U** is **X** or a class derived from **X**, the implicit conversion sequence has Exact Match rank if **U** is **X**, or Conversion rank if **U** is derived from **X**.
  - (6.2) — Otherwise, the implicit conversion sequence is a user-defined conversion sequence with the second standard conversion sequence an identity conversion.

If multiple constructors are viable but none is better than the others, the implicit conversion sequence is the ambiguous conversion sequence. User-defined conversions are allowed for conversion of the initializer list elements to the constructor parameter types except as noted in 16.3.3.1. [ *Example:*

```
struct A {
 A(std::initializer_list<int>);
```

---

133) Since there are no parameters of array type, this will only occur as the referenced type of a reference parameter.

```

};
void f(A);
f({'a', 'b'}); // OK: f(A(std::initializer_list<int>)) user-defined conversion

struct B {
 B(int, double);
};
void g(B);
g({'a', 'b'}); // OK: g(B(int, double)) user-defined conversion
g({1.0, 1.0}); // error: narrowing

void f(B);
f({'a', 'b'}); // error: ambiguous f(A) or f(B)

struct C {
 C(std::string);
};
void h(C);
h({"foo"}); // OK: h(C(std::string("foo")))

struct D {
 D(A, C);
};
void i(D);
i({ {1,2}, {"bar"} }); // OK: i(D(A(std::initializer_list<int>{1,2}), C(std::string("bar"))))

```

— end example]

- <sup>7</sup> Otherwise, if the parameter has an aggregate type which can be initialized from the initializer list according to the rules for aggregate initialization (11.6.1), the implicit conversion sequence is a user-defined conversion sequence with the second standard conversion sequence an identity conversion. [Example:

```

struct A {
 int m1;
 double m2;
};

void f(A);
f({'a', 'b'}); // OK: f(A(int,double)) user-defined conversion
f({1.0}); // error: narrowing

```

— end example]

- <sup>8</sup> Otherwise, if the parameter is a reference, see 16.3.3.1.4. [Note: The rules in this section will apply for initializing the underlying temporary for the reference. — end note] [Example:

```

struct A {
 int m1;
 double m2;
};

void f(const A&);
f({'a', 'b'}); // OK: f(A(int,double)) user-defined conversion
f({1.0}); // error: narrowing

```

```

void g(const double &);
g({1}); // same conversion as int to double

```

— end example]

<sup>9</sup> Otherwise, if the parameter type is not a class:

- (9.1) — if the initializer list has one element that is not itself an initializer list, the implicit conversion sequence is the one required to convert the element to the parameter type; [ *Example:*

```
void f(int);
f({'a'}); // OK: same conversion as char to int
f({1.0}); // error: narrowing
```

— *end example*]

- (9.2) — if the initializer list has no elements, the implicit conversion sequence is the identity conversion. [ *Example:*

```
void f(int);
f({}); // OK: identity conversion
```

— *end example*]

<sup>10</sup> In all cases other than those enumerated above, no conversion is possible.

### 16.3.3.2 Ranking implicit conversion sequences

[over.ics.rank]

<sup>1</sup> This subclause defines a partial ordering of implicit conversion sequences based on the relationships *better conversion sequence* and *better conversion*. If an implicit conversion sequence S1 is defined by these rules to be a better conversion sequence than S2, then it is also the case that S2 is a *worse conversion sequence* than S1. If conversion sequence S1 is neither better than nor worse than conversion sequence S2, S1 and S2 are said to be *indistinguishable conversion sequences*.

<sup>2</sup> When comparing the basic forms of implicit conversion sequences (as defined in 16.3.3.1)

- (2.1) — a standard conversion sequence (16.3.3.1.1) is a better conversion sequence than a user-defined conversion sequence or an ellipsis conversion sequence, and

- (2.2) — a user-defined conversion sequence (16.3.3.1.2) is a better conversion sequence than an ellipsis conversion sequence (16.3.3.1.3).

<sup>3</sup> Two implicit conversion sequences of the same form are indistinguishable conversion sequences unless one of the following rules applies:

- (3.1) — List-initialization sequence L1 is a better conversion sequence than list-initialization sequence L2 if

- (3.1.1) — L1 converts to `std::initializer_list<X>` for some X and L2 does not, or, if not that,

- (3.1.2) — L1 converts to type “array of N1 T”, L2 converts to type “array of N2 T”, and N1 is smaller than N2,

even if one of the other rules in this paragraph would otherwise apply. [ *Example:*

```
void f1(int); // #1
void f1(std::initializer_list<long>); // #2
void g1() { f1({42}); } // chooses #2
```

```
void f2(std::pair<const char*, const char*>); // #3
void f2(std::initializer_list<std::string>); // #4
void g2() { f2({"foo","bar"}); } // chooses #4
```

— *end example*]

- (3.2) — Standard conversion sequence S1 is a better conversion sequence than standard conversion sequence S2 if

- (3.2.1) — S1 is a proper subsequence of S2 (comparing the conversion sequences in the canonical form defined by 16.3.3.1.1, excluding any Lvalue Transformation; the identity conversion sequence is considered to be a subsequence of any non-identity conversion sequence) or, if not that,

- (3.2.2) — the rank of **S1** is better than the rank of **S2**, or **S1** and **S2** have the same rank and are distinguishable by the rules in the paragraph below, or, if not that,

- (3.2.3) — **S1** and **S2** are reference bindings (11.6.3) and neither refers to an implicit object parameter of a non-static member function declared without a *ref-qualifier*, and **S1** binds an rvalue reference to an rvalue and **S2** binds an lvalue reference [ *Example*:

```
int i;
int f1();
int&& f2();
int g(const int&);
int g(const int&&);
int j = g(i); // calls g(const int&)
int k = g(f1()); // calls g(const int&&)
int l = g(f2()); // calls g(const int&&)

struct A {
 A& operator<<(int);
 void p() &;
 void p() &&;
};
A& operator<<(A&&, char);
A() << 1; // calls A::operator<<(int)
A() << 'c'; // calls operator<<(A&&, char)
A a;
a << 1; // calls A::operator<<(int)
a << 'c'; // calls A::operator<<(int)
A().p(); // calls A::p()&&
a.p(); // calls A::p()&
```

— *end example*] or, if not that,

- (3.2.4) — **S1** and **S2** are reference bindings (11.6.3) and **S1** binds an lvalue reference to a function lvalue and **S2** binds an rvalue reference to a function lvalue [ *Example*:

```
int f(void(&)()); // #1
int f(void(&&)()); // #2
void g();
int i1 = f(g); // calls #1
```

— *end example*] or, if not that,

- (3.2.5) — **S1** and **S2** differ only in their qualification conversion and yield similar types **T1** and **T2** (7.5), respectively, and the cv-qualification signature of type **T1** is a proper subset of the cv-qualification signature of type **T2** [ *Example*:

```
int f(const volatile int *);
int f(const int *);
int i;
int j = f(&i); // calls f(const int*)
```

— *end example*] or, if not that,

- (3.2.6) — **S1** and **S2** are reference bindings (11.6.3), and the types to which the references refer are the same type except for top-level cv-qualifiers, and the type to which the reference initialized by **S2** refers is more cv-qualified than the type to which the reference initialized by **S1** refers. [ *Example*:

```
int f(const int &);
int f(int &);
int g(const int &);
```

```

int g(int);

int i;
int j = f(i); // calls f(int &)
int k = g(i); // ambiguous

struct X {
 void f() const;
 void f();
};
void g(const X& a, X b) {
 a.f(); // calls X::f() const
 b.f(); // calls X::f()
}

```

— end example]

- (3.3) — User-defined conversion sequence U1 is a better conversion sequence than another user-defined conversion sequence U2 if they contain the same user-defined conversion function or constructor or they initialize the same class in an aggregate initialization and in either case the second standard conversion sequence of U1 is better than the second standard conversion sequence of U2. [Example:

```

struct A {
 operator short();
} a;
int f(int);
int f(float);
int i = f(a); // calls f(int), because short → int is
 // better than short → float.

```

— end example]

- <sup>4</sup> Standard conversion sequences are ordered by their ranks: an Exact Match is a better conversion than a Promotion, which is a better conversion than a Conversion. Two conversion sequences with the same rank are indistinguishable unless one of the following rules applies:

- (4.1) — A conversion that does not convert a pointer, a pointer to member, or `std::nullptr_t` to `bool` is better than one that does.
- (4.2) — A conversion that promotes an enumeration whose underlying type is fixed to its underlying type is better than one that promotes to the promoted underlying type, if the two are different.
- (4.3) — If class B is derived directly or indirectly from class A, conversion of `B*` to `A*` is better than conversion of `B*` to `void*`, and conversion of `A*` to `void*` is better than conversion of `B*` to `void*`.
- (4.4) — If class B is derived directly or indirectly from class A and class C is derived directly or indirectly from B,
- (4.4.1) — conversion of `C*` to `B*` is better than conversion of `C*` to `A*`, [Example:

```

struct A {};
struct B : public A {};
struct C : public B {};
C* pc;
int f(A*);
int f(B*);
int i = f(pc); // calls f(B*)

```

— end example]

- (4.4.2) — binding of an expression of type C to a reference to type B is better than binding an expression of type C to a reference to type A,

- (4.4.3) — conversion of  $A::*$  to  $B::*$  is better than conversion of  $A::*$  to  $C::*$ ,
- (4.4.4) — conversion of  $C$  to  $B$  is better than conversion of  $C$  to  $A$ ,
- (4.4.5) — conversion of  $B*$  to  $A*$  is better than conversion of  $C*$  to  $A*$ ,
- (4.4.6) — binding of an expression of type  $B$  to a reference to type  $A$  is better than binding an expression of type  $C$  to a reference to type  $A$ ,
- (4.4.7) — conversion of  $B::*$  to  $C::*$  is better than conversion of  $A::*$  to  $C::*$ , and
- (4.4.8) — conversion of  $B$  to  $A$  is better than conversion of  $C$  to  $A$ .

[*Note:* Compared conversion sequences will have different source types only in the context of comparing the second standard conversion sequence of an initialization by user-defined conversion (see 16.3.3); in all other contexts, the source types will be the same and the target types will be different. — *end note*]

## 16.4 Address of overloaded function

[over.over]

- <sup>1</sup> A use of an overloaded function name without arguments is resolved in certain contexts to a function, a pointer to function or a pointer to member function for a specific function from the overload set. A function template name is considered to name a set of overloaded functions in such contexts. A function with type  $F$  is selected for the function type  $FT$  of the target type required in the context if  $F$  (after possibly applying the function pointer conversion (7.13)) is identical to  $FT$ . [*Note:* That is, the class of which the function is a member is ignored when matching a pointer-to-member-function type. — *end note*] The target can be
  - (1.1) — an object or reference being initialized (11.6, 11.6.3, 11.6.4),
  - (1.2) — the left side of an assignment (8.18),
  - (1.3) — a parameter of a function (8.2.2),
  - (1.4) — a parameter of a user-defined operator (16.5),
  - (1.5) — the return value of a function, operator function, or conversion (9.6.3),
  - (1.6) — an explicit type conversion (8.2.3, 8.2.9, 8.4), or
  - (1.7) — a non-type *template-parameter* (17.3.2).

The overloaded function name can be preceded by the  $\&$  operator. An overloaded function name shall not be used without arguments in contexts other than those listed. [*Note:* Any redundant set of parentheses surrounding the overloaded function name is ignored (8.1). — *end note*]

- <sup>2</sup> If the name is a function template, template argument deduction is done (17.8.2.2), and if the argument deduction succeeds, the resulting template argument list is used to generate a single function template specialization, which is added to the set of overloaded functions considered. [*Note:* As described in 17.8.1, if deduction fails and the function template name is followed by an explicit template argument list, the *template-id* is then examined to see whether it identifies a single function template specialization. If it does, the *template-id* is considered to be an lvalue for that function template specialization. The target type is not used in that determination. — *end note*]
- <sup>3</sup> Non-member functions and static member functions match targets of function pointer type or reference to function type. Non-static member functions match targets of pointer to member function type. If a non-static member function is selected, the reference to the overloaded function name is required to have the form of a pointer to member as described in 8.3.1.
- <sup>4</sup> If more than one function is selected, any function template specializations in the set are eliminated if the set also contains a function that is not a function template specialization, and any given function template specialization  $F1$  is eliminated if the set contains a second function template specialization whose function template is more specialized than the function template of  $F1$  according to the partial ordering rules of 17.5.6.2. After such eliminations, if any, there shall remain exactly one selected function.

<sup>5</sup> [Example:

```
int f(double);
int f(int);
int (*pfd)(double) = &f; // selects f(double)
int (*pfi)(int) = &f; // selects f(int)
int (*pfe)(...) = &f; // error: type mismatch
int (&rfi)(int) = f; // selects f(int)
int (&rfd)(double) = f; // selects f(double)
void g() {
 (int (*)(int))&f; // cast expression as selector
}
```

The initialization of `pfe` is ill-formed because no `f()` with type `int(...)` has been declared, and not because of any ambiguity. For another example,

```
struct X {
 int f(int);
 static int f(long);
};

int (X::*p1)(int) = &X::f; // OK
int (*p2)(int) = &X::f; // error: mismatch
int (*p3)(long) = &X::f; // OK
int (X::*p4)(long) = &X::f; // error: mismatch
int (X::*p5)(int) = &(X::f); // error: wrong syntax for
// pointer to member
int (*p6)(long) = &(X::f); // OK
```

— end example]

<sup>6</sup> [Note: If `f()` and `g()` are both overloaded functions, the cross product of possibilities must be considered to resolve `f(&g)`, or the equivalent expression `f(g)`. — end note]

<sup>7</sup> [Note: Even if `B` is a public base of `D`, we have

```
D* f();
B* (*p1)() = &f; // error

void g(D*);
void (*p2)(B*) = &g; // error
```

— end note]

## 16.5 Overloaded operators

[over.oper]

<sup>1</sup> A function declaration having one of the following *operator-function-ids* as its name declares an *operator function*. A function template declaration having one of the following *operator-function-ids* as its name declares an *operator function template*. A specialization of an operator function template is also an operator function. An operator function is said to *implement* the operator named in its *operator-function-id*.

*operator-function-id*:

`operator operator`

*operator*: one of

|                    |                     |                         |                       |                       |                        |                        |                     |                    |
|--------------------|---------------------|-------------------------|-----------------------|-----------------------|------------------------|------------------------|---------------------|--------------------|
| <code>new</code>   | <code>delete</code> | <code>new[]</code>      | <code>delete[]</code> |                       |                        |                        |                     |                    |
| <code>+</code>     | <code>-</code>      | <code>*</code>          | <code>/</code>        | <code>%</code>        | <code>^</code>         | <code>&amp;</code>     | <code> </code>      | <code>~</code>     |
| <code>!</code>     | <code>=</code>      | <code>&lt;</code>       | <code>&gt;</code>     | <code>+=</code>       | <code>-=</code>        | <code>*=</code>        | <code>/=</code>     | <code>%=</code>    |
| <code>^=</code>    | <code>&amp;=</code> | <code> =</code>         | <code>&lt;&lt;</code> | <code>&gt;&gt;</code> | <code>&gt;&gt;=</code> | <code>&lt;&lt;=</code> | <code>==</code>     | <code>!=</code>    |
| <code>&lt;=</code> | <code>&gt;=</code>  | <code>&amp;&amp;</code> | <code>  </code>       | <code>++</code>       | <code>--</code>        | <code>,</code>         | <code>-&gt;*</code> | <code>-&gt;</code> |
| <code>()</code>    | <code>[]</code>     |                         |                       |                       |                        |                        |                     |                    |

[*Note:* The last two operators are function call (8.2.2) and subscripting (8.2.1). The operators `new[]`, `delete[]`, `()`, and `[]` are formed from more than one token. — *end note*]

- <sup>2</sup> Both the unary and binary forms of

`+` `-` `*` `&`

can be overloaded.

- <sup>3</sup> The following operators cannot be overloaded:

`.` `.*` `::` `?:`

nor can the preprocessing symbols `#` and `##` (Clause 19).

- <sup>4</sup> Operator functions are usually not called directly; instead they are invoked to evaluate the operators they implement (16.5.1 – 16.5.7). They can be explicitly called, however, using the *operator-function-id* as the name of the function in the function call syntax (8.2.2). [*Example:*

```
complex z = a.operator+(b); // complex z = a+b;
void* p = operator new(sizeof(int)*n);
```

— *end example*]

- <sup>5</sup> The allocation and deallocation functions, `operator new`, `operator new[]`, `operator delete` and `operator delete[]`, are described completely in 6.7.4. The attributes and restrictions found in the rest of this subclause do not apply to them unless explicitly stated in 6.7.4.
- <sup>6</sup> An operator function shall either be a non-static member function or be a non-member function that has at least one parameter whose type is a class, a reference to a class, an enumeration, or a reference to an enumeration. It is not possible to change the precedence, grouping, or number of operands of operators. The meaning of the operators `=`, (unary) `&`, and `,` (comma), predefined for each type, can be changed for specific class and enumeration types by defining operator functions that implement these operators. Operator functions are inherited in the same manner as other base class functions.
- <sup>7</sup> The identities among certain predefined operators applied to basic types (for example, `++a`  $\equiv$  `a+=1`) need not hold for operator functions. Some predefined operators, such as `+=`, require an operand to be an lvalue when applied to basic types; this is not required by operator functions.
- <sup>8</sup> An operator function cannot have default arguments (11.3.6), except where explicitly stated below. Operator functions cannot have more or fewer parameters than the number required for the corresponding operator, as described in the rest of this subclause.
- <sup>9</sup> Operators not mentioned explicitly in subclauses 16.5.3 through 16.5.7 act as ordinary unary and binary operators obeying the rules of 16.5.1 or 16.5.2.

### 16.5.1 Unary operators

[over.unary]

- <sup>1</sup> A prefix unary operator shall be implemented by a non-static member function (12.2.1) with no parameters or a non-member function with one parameter. Thus, for any prefix unary operator `@`, `@x` can be interpreted as either `x.operator@()` or `operator@(x)`. If both forms of the operator function have been declared, the rules in 16.3.1.2 determine which, if any, interpretation is used. See 16.5.7 for an explanation of the postfix unary operators `++` and `--`.
- <sup>2</sup> The unary and binary forms of the same operator are considered to have the same name. [*Note:* Consequently, a unary operator can hide a binary operator from an enclosing scope, and vice versa. — *end note*]

### 16.5.2 Binary operators

[over.binary]

- <sup>1</sup> A binary operator shall be implemented either by a non-static member function (12.2.1) with one parameter or by a non-member function with two parameters. Thus, for any binary operator `@`, `x@y` can be interpreted as either `x.operator@(y)` or `operator@(x,y)`. If both forms of the operator function have been declared,



the rules in 16.3.1.2 determine which, if any, interpretation is used.

### 16.5.3 Assignment

[over.ass]

- <sup>1</sup> An assignment operator shall be implemented by a non-static member function with exactly one parameter. Because a copy assignment operator `operator=` is implicitly declared for a class if not declared by the user (15.8), a base class assignment operator is always hidden by the copy assignment operator of the derived class.
- <sup>2</sup> Any assignment operator, even the copy and move assignment operators, can be virtual. [ *Note:* For a derived class D with a base class B for which a virtual copy/move assignment has been declared, the copy/move assignment operator in D does not override B's virtual copy/move assignment operator. [ *Example:*

```
struct B {
 virtual int operator= (int);
 virtual B& operator= (const B&);
};
struct D : B {
 virtual int operator= (int);
 virtual D& operator= (const B&);
};

D dobj1;
D dobj2;
B* bptr = &dobj1;
void f() {
 bptr->operator=(99); // calls D::operator=(int)
 *bptr = 99; // ditto
 bptr->operator=(dobj2); // calls D::operator=(const B&)
 *bptr = dobj2; // ditto
 dobj1 = dobj2; // calls implicitly-declared D::operator=(const D&)
}
```

— end example] — end note]

### 16.5.4 Function call

[over.call]

- <sup>1</sup> `operator()` shall be a non-static member function with an arbitrary number of parameters. It can have default arguments. It implements the function call syntax

*postfix-expression* ( *expression-list<sub>opt</sub>* )

where the *postfix-expression* evaluates to a class object and the possibly empty *expression-list* matches the parameter list of an `operator()` member function of the class. Thus, a call `x(arg1, ...)` is interpreted as `x.operator()(arg1, ...)` for a class object `x` of type `T` if `T::operator()(T1, T2, T3)` exists and if the operator is selected as the best match function by the overload resolution mechanism (16.3.3).

### 16.5.5 Subscripting

[over.sub]

- <sup>1</sup> `operator[]` shall be a non-static member function with exactly one parameter. It implements the subscripting syntax

*postfix-expression* [ *expr-or-braced-init-list* ]

Thus, a subscripting expression `x[y]` is interpreted as `x.operator[](y)` for a class object `x` of type `T` if `T::operator[](T1)` exists and if the operator is selected as the best match function by the overload resolution mechanism (16.3.3). [ *Example:*

```
struct X {
 Z operator[](std::initializer_list<int>);
}
```

```

};
X x;
x[{1,2,3}] = 7; // OK: meaning x.operator[]({1,2,3})
int a[10];
a[{1,2,3}] = 7; // error: built-in subscript operator
— end example]

```

### 16.5.6 Class member access

[over.ref]

- <sup>1</sup> **operator->** shall be a non-static member function taking no parameters. It implements the class member access syntax that uses **->**.

```

postfix-expression -> templateopt id-expression
postfix-expression -> pseudo-destructor-name

```

An expression **x->m** is interpreted as **(x.operator->())->m** for a class object **x** of type **T** if **T::operator->()** exists and if the operator is selected as the best match function by the overload resolution mechanism (16.3).

### 16.5.7 Increment and decrement

[over.inc]

- <sup>1</sup> The user-defined function called **operator++** implements the prefix and postfix **++** operator. If this function is a non-static member function with no parameters, or a non-member function with one parameter, it defines the prefix increment operator **++** for objects of that type. If the function is a non-static member function with one parameter (which shall be of type **int**) or a non-member function with two parameters (the second of which shall be of type **int**), it defines the postfix increment operator **++** for objects of that type. When the postfix increment is called as a result of using the **++** operator, the **int** argument will have value zero.<sup>134</sup>

[Example:

```

struct X {
 X& operator++(); // prefix ++a
 X operator++(int); // postfix a++
};

struct Y { };
Y& operator++(Y&); // prefix ++b
Y operator++(Y&, int); // postfix b++

void f(X a, Y b) {
 ++a; // a.operator++();
 a++; // a.operator++(0);
 ++b; // operator++(b);
 b++; // operator++(b, 0);

 a.operator++(); // explicit call: like ++a;
 a.operator++(0); // explicit call: like a++;
 operator++(b); // explicit call: like ++b;
 operator++(b, 0); // explicit call: like b++;
}

```

— end example]

- <sup>2</sup> The prefix and postfix decrement operators **--** are handled analogously.

<sup>134</sup>) Calling **operator++** explicitly, as in expressions like **a.operator++(2)**, has no special properties: The argument to **operator++** is 2.

## 16.5.8 User-defined literals

[over.literal]

*literal-operator-id*:**operator** *string-literal identifier***operator** *user-defined-string-literal*

- <sup>1</sup> The *string-literal* or *user-defined-string-literal* in a *literal-operator-id* shall have no *encoding-prefix* and shall contain no characters other than the implicit terminating `'\0'`. The *ud-suffix* of the *user-defined-string-literal* or the *identifier* in a *literal-operator-id* is called a *literal suffix identifier*. Some literal suffix identifiers are reserved for future standardization; see 20.5.4.3.5. A declaration whose *literal-operator-id* uses such a literal suffix identifier is ill-formed, no diagnostic required.
- <sup>2</sup> A declaration whose *declarator-id* is a *literal-operator-id* shall be a declaration of a namespace-scope function or function template (it could be a friend function (14.3)), an explicit instantiation or specialization of a function template, or a *using-declaration* (10.3.3). A function declared with a *literal-operator-id* is a *literal operator*. A function template declared with a *literal-operator-id* is a *literal operator template*.
- <sup>3</sup> The declaration of a literal operator shall have a *parameter-declaration-clause* equivalent to one of the following:

```

const char*
unsigned long long int
long double
char
wchar_t
char16_t
char32_t
const char*, std::size_t
const wchar_t*, std::size_t
const char16_t*, std::size_t
const char32_t*, std::size_t

```

If a parameter has a default argument (11.3.6), the program is ill-formed.

- <sup>4</sup> A *raw literal operator* is a literal operator with a single parameter whose type is `const char*`.
- <sup>5</sup> The declaration of a literal operator template shall have an empty *parameter-declaration-clause* and its *template-parameter-list* shall have a single *template-parameter* that is a non-type template parameter pack (17.5.3) with element type `char`.
- <sup>6</sup> Literal operators and literal operator templates shall not have C language linkage.
- <sup>7</sup> [ *Note*: Literal operators and literal operator templates are usually invoked implicitly through user-defined literals (5.13.8). However, except for the constraints described above, they are ordinary namespace-scope functions and function templates. In particular, they are looked up like ordinary functions and function templates and they follow the same overload resolution rules. Also, they can be declared `inline` or `constexpr`, they may have internal or external linkage, they can be called explicitly, their addresses can be taken, etc. — *end note* ]
- <sup>8</sup> [ *Example*:

```

void operator "" _km(long double); // OK
string operator "" _i18n(const char*, std::size_t); // OK
template <char...> double operator "" _\u03C0(); // OK: UCN for lowercase pi
float operator "" _e(const char*); // OK
float operator "" E(const char*); // error: reserved literal suffix (20.5.4.3.5, 5.13.8)
double operator "" _Bq(long double); // OK: does not use the reserved identifier _Bq (5.10)
double operator "" Bq(long double); // uses the reserved identifier _Bq (5.10)
float operator "" B(const char*); // error: non-empty string-literal
string operator "" 5X(const char*, std::size_t); // error: invalid literal suffix identifier

```

```
double operator "" _miles(double); // error: invalid parameter-declaration-clause
template <char...> int operator "" _j(const char*); // error: invalid parameter-declaration-clause
extern "C" void operator "" _m(long double); // error: C language linkage
```

— end example]

## 16.6 Built-in operators

[over.built]

- <sup>1</sup> The candidate operator functions that represent the built-in operators defined in Clause 8 are specified in this subclause. These candidate functions participate in the operator overload resolution process as described in 16.3.1.2 and are used for no other purpose. [ *Note*: Because built-in operators take only operands with non-class type, and operator overload resolution occurs only when an operand expression originally has class or enumeration type, operator overload resolution can resolve to a built-in operator only when an operand has a class type that has a user-defined conversion to a non-class type appropriate for the operator, or when an operand has an enumeration type that can be converted to a type appropriate for the operator. Also note that some of the candidate operator functions given in this subclause are more permissive than the built-in operators themselves. As described in 16.3.1.2, after a built-in operator is selected by overload resolution the expression is subject to the requirements for the built-in operator given in Clause 8, and therefore to any additional semantic constraints given there. If there is a user-written candidate with the same name and parameter types as a built-in candidate operator function, the built-in operator function is hidden and is not included in the set of candidate functions. — end note ]
- <sup>2</sup> In this subclause, the term *promoted integral type* is used to refer to those integral types which are preserved by integral promotion (7.6) (including e.g. `int` and `long` but excluding e.g. `char`). Similarly, the term *promoted arithmetic type* refers to floating types plus promoted integral types. [ *Note*: In all cases where a promoted integral type or promoted arithmetic type is required, an operand of enumeration type will be acceptable by way of the integral promotions. — end note ]
- <sup>3</sup> In the remainder of this section, *vk* represents either `volatile` or no cv-qualifier.
- <sup>4</sup> For every pair (*T*, *vk*), where *T* is an arithmetic type other than `bool`, there exist candidate operator functions of the form

```
vk T& operator++(vk T&);
T operator++(vk T&, int);
```
- <sup>5</sup> For every pair (*T*, *vk*), where *T* is an arithmetic type other than `bool`, there exist candidate operator functions of the form

```
vk T& operator--(vk T&);
T operator--(vk T&, int);
```
- <sup>6</sup> For every pair (*T*, *vk*), where *T* is a cv-qualified or cv-unqualified object type, there exist candidate operator functions of the form

```
T*vk& operator++(T*vk&);
T*vk& operator--(T*vk&);
T* operator++(T*vk&, int);
T* operator--(T*vk&, int);
```
- <sup>7</sup> For every cv-qualified or cv-unqualified object type *T*, there exist candidate operator functions of the form

```
T& operator*(T*);
```
- <sup>8</sup> For every function type *T* that does not have cv-qualifiers or a *ref-qualifier*, there exist candidate operator functions of the form

```
T& operator*(T*);
```
- <sup>9</sup> For every type *T* there exist candidate operator functions of the form

```
T* operator+(T*);
```

- <sup>10</sup> For every promoted arithmetic type  $T$ , there exist candidate operator functions of the form

```
 T operator+(T);
 T operator-(T);
```

- <sup>11</sup> For every promoted integral type  $T$ , there exist candidate operator functions of the form

```
 T operator~(T);
```

- <sup>12</sup> For every quintuple  $(C1, C2, T, cv1, cv2)$ , where  $C2$  is a class type,  $C1$  is the same type as  $C2$  or is a derived class of  $C2$ , and  $T$  is an object type or a function type, there exist candidate operator functions of the form

```
 $cv12$ $T\&$ operator->*($cv1$ $C1*$, $cv2$ T $C2::*$);
```

where  $cv12$  is the union of  $cv1$  and  $cv2$ . The return type is shown for exposition only; see 8.5 for the determination of the operator's result type.

- <sup>13</sup> For every pair of promoted arithmetic types  $L$  and  $R$ , there exist candidate operator functions of the form

```
 LR operator*(L , R);
 LR operator/(L , R);
 LR operator+(L , R);
 LR operator-(L , R);
bool operator<(L , R);
bool operator>(L , R);
bool operator<=(L , R);
bool operator>=(L , R);
bool operator==(L , R);
bool operator!=(L , R);
```

where  $LR$  is the result of the usual arithmetic conversions between types  $L$  and  $R$ .

- <sup>14</sup> For every cv-qualified or cv-unqualified object type  $T$  there exist candidate operator functions of the form

```
 $T*$ operator+($T*$, std::ptrdiff_t);
 $T\&$ operator[]($T*$, std::ptrdiff_t);
 $T*$ operator-($T*$, std::ptrdiff_t);
 $T*$ operator+(std::ptrdiff_t, $T*$);
 $T\&$ operator[](std::ptrdiff_t, $T*$);
```

- <sup>15</sup> For every  $T$ , where  $T$  is a pointer to object type, there exist candidate operator functions of the form

```
std::ptrdiff_t operator-(T , T);
```

- <sup>16</sup> For every  $T$ , where  $T$  is an enumeration type or a pointer type, there exist candidate operator functions of the form

```
bool operator<(T , T);
bool operator>(T , T);
bool operator<=(T , T);
bool operator>=(T , T);
bool operator==(T , T);
bool operator!=(T , T);
```

- <sup>17</sup> For every pointer to member type  $T$  or type `std::nullptr_t` there exist candidate operator functions of the form

```
bool operator==(T , T);
bool operator!=(T , T);
```

- <sup>18</sup> For every pair of promoted integral types  $L$  and  $R$ , there exist candidate operator functions of the form

```
 LR operator%(L , R);
 LR operator&(L , R);
 LR operator^(L , R);
```

```

LR operator|(L, R);
L operator<<(L, R);
L operator>>(L, R);

```

where  $LR$  is the result of the usual arithmetic conversions between types  $L$  and  $R$ .

- 19 For every triple  $(L, vq, R)$ , where  $L$  is an arithmetic type, and  $R$  is a promoted arithmetic type, there exist candidate operator functions of the form

```

vq L& operator=(vq L&, R);
vq L& operator*=(vq L&, R);
vq L& operator/=(vq L&, R);
vq L& operator+=(vq L&, R);
vq L& operator-=(vq L&, R);

```

- 20 For every pair  $(T, vq)$ , where  $T$  is any type, there exist candidate operator functions of the form

```

T*vq& operator=(T*vq&, T*);

```

- 21 For every pair  $(T, vq)$ , where  $T$  is an enumeration or pointer to member type, there exist candidate operator functions of the form

```

vq T& operator=(vq T&, T);

```

- 22 For every pair  $(T, vq)$ , where  $T$  is a cv-qualified or cv-unqualified object type, there exist candidate operator functions of the form

```

T*vq& operator+=(T*vq&, std::ptrdiff_t);
T*vq& operator-=(T*vq&, std::ptrdiff_t);

```

- 23 For every triple  $(L, vq, R)$ , where  $L$  is an integral type, and  $R$  is a promoted integral type, there exist candidate operator functions of the form

```

vq L& operator%=(vq L&, R);
vq L& operator<<=(vq L&, R);
vq L& operator>>=(vq L&, R);
vq L& operator&=(vq L&, R);
vq L& operator^=(vq L&, R);
vq L& operator|=(vq L&, R);

```

- 24 There also exist candidate operator functions of the form

```

bool operator!(bool);
bool operator&&(bool, bool);
bool operator||(bool, bool);

```

- 25 For every pair of promoted arithmetic types  $L$  and  $R$ , there exist candidate operator functions of the form

```

LR operator?:(bool, L, R);

```

where  $LR$  is the result of the usual arithmetic conversions between types  $L$  and  $R$ . [Note: As with all these descriptions of candidate functions, this declaration serves only to describe the built-in operator for purposes of overload resolution. The operator “?:” cannot be overloaded. —end note]

- 26 For every type  $T$ , where  $T$  is a pointer, pointer-to-member, or scoped enumeration type, there exist candidate operator functions of the form

```

T operator?:(bool, T, T);

```

# 17 Templates

[temp]

- <sup>1</sup> A *template* defines a family of classes, functions, or variables, or an alias for a family of types.

*template-declaration*:

**template** < *template-parameter-list* > *declaration*

*template-parameter-list*:

*template-parameter*

*template-parameter-list* , *template-parameter*

[*Note*: The > token following the *template-parameter-list* of a *template-declaration* may be the product of replacing a >> token by two consecutive > tokens (17.2). — *end note*]

The *declaration* in a *template-declaration* shall

- (1.1) — declare or define a function, a class, or a variable, or
- (1.2) — define a member function, a member class, a member enumeration, or a static data member of a class template or of a class nested within a class template, or
- (1.3) — define a member template of a class or class template, or
- (1.4) — be a *deduction-guide*, or
- (1.5) — be an *alias-declaration*.

A *template-declaration* is a *declaration*. A *template-declaration* is also a definition if its *declaration* defines a function, a class, a variable, or a static data member. A declaration introduced by a template declaration of a variable is a *variable template*. A variable template at class scope is a *static data member template*.

[*Example*:

```
template<class T>
 constexpr T pi = T(3.1415926535897932385L);
template<class T>
T circular_area(T r) {
 return pi<T> * r * r;
}
struct matrix_constants {
 template<class T>
 using pauli = hermitian_matrix<T, 2>;
 template<class T>
 constexpr pauli<T> sigma1 = { { 0, 1 }, { 1, 0 } };
 template<class T>
 constexpr pauli<T> sigma2 = { { 0, -1i }, { 1i, 0 } };
 template<class T>
 constexpr pauli<T> sigma3 = { { 1, 0 }, { 0, -1 } };
};
```

— *end example*]

- <sup>2</sup> A *template-declaration* can appear only as a namespace scope or class scope declaration. In a function template declaration, the last component of the *declarator-id* shall not be a *template-id*. [*Note*: That last component may be an *identifier*, an *operator-function-id*, a *conversion-function-id*, or a *literal-operator-id*. In a class template declaration, if the class name is a *simple-template-id*, the declaration declares a class template partial specialization (17.5.5). — *end note*]

- <sup>3</sup> In a *template-declaration*, explicit specialization, or explicit instantiation the *init-declarator-list* in the declaration shall contain at most one declarator. When such a declaration is used to declare a class template, no declarator is permitted.
- <sup>4</sup> A template name has linkage (6.5). Specializations (explicit or implicit) of a template that has internal linkage are distinct from all specializations in other translation units. A template, a template explicit specialization (17.7.3), and a class template partial specialization shall not have C linkage. Use of a linkage specification other than "C" or "C++" with any of these constructs is conditionally-supported, with implementation-defined semantics. Template definitions shall obey the one-definition rule (6.2). [ *Note*: Default arguments for function templates and for member functions of class templates are considered definitions for the purpose of template instantiation (17.5) and must also obey the one-definition rule. — *end note* ]
- <sup>5</sup> A class template shall not have the same name as any other template, class, function, variable, enumeration, enumerator, namespace, or type in the same scope (6.3), except as specified in 17.5.5. Except that a function template can be overloaded either by non-template functions (11.3.5) with the same name or by other function templates with the same name (17.8.3), a template name declared in namespace scope or in class scope shall be unique in that scope.
- <sup>6</sup> A *templated entity* is
- (6.1) — a template,
  - (6.2) — an entity defined (6.1) or created (15.2) in a templated entity,
  - (6.3) — a member of a templated entity,
  - (6.4) — an enumerator for an enumeration that is a templated entity, or
  - (6.5) — the closure type of a *lambda-expression* (8.1.5.1) appearing in the declaration of a templated entity.
- [ *Note*: A local class, a local variable, or a friend function defined in a templated entity is a templated entity. — *end note* ]
- <sup>7</sup> A function template, member function of a class template, variable template, or static data member of a class template shall be defined in every translation unit in which it is implicitly instantiated (17.7.1) unless the corresponding specialization is explicitly instantiated (17.7.2) in some translation unit; no diagnostic is required.

## 17.1 Template parameters

[temp.param]

- <sup>1</sup> The syntax for *template-parameters* is:

```

template-parameter:
 type-parameter
 parameter-declaration

type-parameter:
 type-parameter-key ...opt identifieropt
 type-parameter-key identifieropt = type-id
 template < template-parameter-list > type-parameter-key ...opt identifieropt
 template < template-parameter-list > type-parameter-key identifieropt = id-expression

type-parameter-key:
 class
 typename

```

[ *Note*: The > token following the *template-parameter-list* of a *type-parameter* may be the product of replacing a >> token by two consecutive > tokens (17.2). — *end note* ]

- <sup>2</sup> There is no semantic difference between **class** and **typename** in a *type-parameter-key*. **typename** followed by an *unqualified-id* names a template type parameter. **typename** followed by a *qualified-id* denotes the type in



a non-type<sup>135</sup> *parameter-declaration*. A *template-parameter* of the form *class identifier* is a *type-parameter*.  
 [Example:

```
class T { /* ... */ };
int i;

template<class T, T i> void f(T t) {
 T t1 = i; // template-parameters T and i
 ::T t2 = ::i; // global namespace members T and i
}
```

Here, the template *f* has a *type-parameter* called *T*, rather than an unnamed non-type *template-parameter* of class *T*. — end example] A storage class shall not be specified in a *template-parameter* declaration. Types shall not be defined in a *template-parameter* declaration.

- <sup>3</sup> A *type-parameter* whose identifier does not follow an ellipsis defines its *identifier* to be a *typedef-name* (if declared without `template`) or *template-name* (if declared with `template`) in the scope of the template declaration. [Note: A template argument may be a class template or alias template. For example,

```
template<class T> class myarray { /* ... */ };

template<class K, class V, template<class T> class C = myarray>
class Map {
 C<K> key;
 C<V> value;
};
```

— end note]

- <sup>4</sup> A non-type *template-parameter* shall have one of the following (optionally cv-qualified) types:

- (4.1) — integral or enumeration type,
- (4.2) — pointer to object or pointer to function,
- (4.3) — lvalue reference to object or lvalue reference to function,
- (4.4) — pointer to member,
- (4.5) — `std::nullptr_t`, or
- (4.6) — a type that contains a placeholder type (10.1.7.4).

- <sup>5</sup> [Note: Other types are disallowed either explicitly below or implicitly by the rules governing the form of *template-arguments* (17.3). — end note] The top-level *cv-qualifiers* on the *template-parameter* are ignored when determining its type.

- <sup>6</sup> A non-type non-reference *template-parameter* is a prvalue. It shall not be assigned to or in any other way have its value changed. A non-type non-reference *template-parameter* cannot have its address taken. When a non-type non-reference *template-parameter* is used as an initializer for a reference, a temporary is always used. [Example:

```
template<const X& x, int i> void f() {
 i++; // error: change of template-parameter value

 &x; // OK
 &i; // error: address of non-reference template-parameter

 int& ri = i; // error: non-const reference bound to temporary
 const int& cri = i; // OK: const reference bound to temporary
```

135) Since template *template-parameters* and template *template-arguments* are treated as types for descriptive purposes, the terms *non-type parameter* and *non-type argument* are used to refer to non-type, non-template parameters and arguments.

```
 }
```

— end example]

- 7 A non-type *template-parameter* shall not be declared to have floating-point, class, or void type. [ *Example:*

```
template<double d> class X; // error
template<double* pd> class Y; // OK
template<double& rd> class Z; // OK
```

— end example]

- 8 A non-type *template-parameter* of type “array of T” or of function type T is adjusted to be of type “pointer to T”. [ *Example:*

```
template<int* a> struct R { /* ... */ };
template<int b[5]> struct S { /* ... */ };
int p;
R<&p> w; // OK
S<&p> x; // OK due to parameter adjustment
int v[5];
R<v> y; // OK due to implicit argument conversion
S<v> z; // OK due to both adjustment and conversion
```

— end example]

- 9 A default *template-argument* is a *template-argument* (17.3) specified after = in a *template-parameter*. A default *template-argument* may be specified for any kind of *template-parameter* (type, non-type, template) that is not a template parameter pack (17.5.3). A default *template-argument* may be specified in a template declaration. A default *template-argument* shall not be specified in the *template-parameter-lists* of the definition of a member of a class template that appears outside of the member’s class. A default *template-argument* shall not be specified in a friend class template declaration. If a friend function template declaration specifies a default *template-argument*, that declaration shall be a definition and shall be the only declaration of the function template in the translation unit.

- 10 The set of default *template-arguments* available for use is obtained by merging the default arguments from all prior declarations of the template in the same way default function arguments are (11.3.6). [ *Example:*

```
template<class T1, class T2 = int> class A;
template<class T1 = int, class T2> class A;
```

is equivalent to

```
template<class T1 = int, class T2 = int> class A;
```

— end example]

- 11 If a *template-parameter* of a class template, variable template, or alias template has a default *template-argument*, each subsequent *template-parameter* shall either have a default *template-argument* supplied or be a template parameter pack. If a *template-parameter* of a primary class template, primary variable template, or alias template is a template parameter pack, it shall be the last *template-parameter*. A template parameter pack of a function template shall not be followed by another template parameter unless that template parameter can be deduced from the parameter-type-list (11.3.5) of the function template or has a default argument (17.8.2). A template parameter of a deduction guide template (17.9) that does not have a default argument shall be deducible from the parameter-type-list of the deduction guide template. [ *Example:*

```
template<class T1 = int, class T2> class B; // error

// U can be neither deduced from the parameter-type-list nor specified
template<class... T, class... U> void f() { } // error
template<class... T, class U> void g() { } // error
```

— end example]

- <sup>12</sup> A *template-parameter* shall not be given default arguments by two different declarations in the same scope. [Example:

```
template<class T = int> class X;
template<class T = int> class X { /* ... */ }; // error
```

— end example]

- <sup>13</sup> When parsing a default *template-argument* for a non-type *template-parameter*, the first non-nested > is taken as the end of the *template-parameter-list* rather than a greater-than operator. [Example:

```
template<int i = 3 > 4 > // syntax error
class X { /* ... */ };
```

```
template<int i = (3 > 4) > // OK
class Y { /* ... */ };
```

— end example]

- <sup>14</sup> A *template-parameter* of a template *template-parameter* is permitted to have a default *template-argument*. When such default arguments are specified, they apply to the template *template-parameter* in the scope of the template *template-parameter*. [Example:

```
template <class T = float> struct B {};
template <template <class TT = float> class T> struct A {
 inline void f();
 inline void g();
};
template <template <class TT> class T> void A<T>::f() {
 T<> t; // error - TT has no default template argument
}
template <template <class TT = char> class T> void A<T>::g() {
 T<> t; // OK - T<char>
}
}
```

— end example]

- <sup>15</sup> If a *template-parameter* is a *type-parameter* with an ellipsis prior to its optional *identifier* or is a *parameter-declaration* that declares a parameter pack (11.3.5), then the *template-parameter* is a template parameter pack (17.5.3). A template parameter pack that is a *parameter-declaration* whose type contains one or more unexpanded parameter packs is a pack expansion. Similarly, a template parameter pack that is a *type-parameter* with a *template-parameter-list* containing one or more unexpanded parameter packs is a pack expansion. A template parameter pack that is a pack expansion shall not expand a parameter pack declared in the same *template-parameter-list*. [Example:

```
template <class... Types> class Tuple; // Types is a template type parameter pack
// but not a pack expansion
template <class T, int... Dims> struct multi_array; // Dims is a non-type template parameter pack
// but not a pack expansion
template<class... T> struct value_holder {
 template<T... Values> struct apply { }; // Values is a non-type template parameter pack
// and a pack expansion
};
template<class... T, T... Values> struct static_array; // error: Values expands template type parameter
// pack T within the same template parameter list
```

— end example]

## 17.2 Names of template specializations

[temp.names]

- <sup>1</sup> A template specialization (17.7) can be referred to by a *template-id*:

```

simple-template-id:
 template-name < template-argument-listopt >

template-id:
 simple-template-id
 operator-function-id < template-argument-listopt >
 literal-operator-id < template-argument-listopt >

template-name:
 identifier

template-argument-list:
 template-argument ...opt
 template-argument-list , template-argument ...opt

template-argument:
 constant-expression
 type-id
 id-expression

```

[*Note*: The name lookup rules (6.4) are used to associate the use of a name with a template declaration; that is, to identify a name as a *template-name*. — *end note*]

- <sup>2</sup> For a *template-name* to be explicitly qualified by the template arguments, the name must be known to refer to a template.
- <sup>3</sup> After name lookup (6.4) finds that a name is a *template-name* or that an *operator-function-id* or a *literal-operator-id* refers to a set of overloaded functions any member of which is a function template, if this is followed by a <, the < is always taken as the delimiter of a *template-argument-list* and never as the less-than operator. When parsing a *template-argument-list*, the first non-nested ><sup>136</sup> is taken as the ending delimiter rather than a greater-than operator. Similarly, the first non-nested >> is treated as two consecutive but distinct > tokens, the first of which is taken as the end of the *template-argument-list* and completes the *template-id*. [*Note*: The second > token produced by this replacement rule may terminate an enclosing *template-id* construct or it may be part of a different construct (e.g. a cast). — *end note*] [*Example*:

```

template<int i> class X { /* ... */ };

X< 1>2 > x1; // syntax error
X<(1>2)> x2; // OK

template<class T> class Y { /* ... */ };
Y<X<1>>> x3; // OK, same as Y<X<1> > x3;
Y<X<6>>>1>>> x4; // syntax error
Y<X<(6>>>1)>>> x5; // OK

```

— *end example*]

- <sup>4</sup> The keyword **template** is said to appear at the top level in a *qualified-id* if it appears outside of a *template-argument-list* or *decltype-specifier*. In a *qualified-id* of a *declarator-id* or in a *qualified-id* formed by a *class-head-name* (Clause 12) or *enum-head-name* (10.2), the keyword **template** shall not appear at the top level. In a *qualified-id* used as the name in a *typename-specifier* (17.6), *elaborated-type-specifier* (10.1.7.3), *using-declaration* (10.3.3), or *class-or-decltype* (Clause 13), an optional keyword **template** appearing at the top level is ignored. In these contexts, a < token is always assumed to introduce a *template-argument-list*. In all other contexts, when naming a template specialization of a member of an unknown specialization (17.6.2.1),

<sup>136</sup> A > that encloses the *type-id* of a `dynamic_cast`, `static_cast`, `reinterpret_cast` or `const_cast`, or which encloses the *template-arguments* of a subsequent *template-id*, is considered nested for the purpose of this description.

the member template name shall be prefixed by the keyword `template`. [*Example:*

```
struct X {
 template<std::size_t> X* alloc();
 template<std::size_t> static X* adjust();
};
template<class T> void f(T* p) {
 T* p1 = p->alloc<200>(); // ill-formed: < means less than
 T* p2 = p->template alloc<200>(); // OK: < starts template argument list
 T::adjust<100>(); // ill-formed: < means less than
 T::template adjust<100>(); // OK: < starts template argument list
}
```

— *end example*]

- <sup>5</sup> A name prefixed by the keyword `template` shall be a *template-id* or the name shall refer to a class template or an alias template. [*Note:* The keyword `template` may not be applied to non-template members of class templates. — *end note*] [*Note:* As is the case with the `typename` prefix, the `template` prefix is allowed in cases where it is not strictly necessary; i.e., when the *nested-name-specifier* or the expression on the left of the `->` or `.` is not dependent on a *template-parameter*, or the use does not appear in the scope of a template.

— *end note*] [*Example:*

```
template <class T> struct A {
 void f(int);
 template <class U> void f(U);
};

template <class T> void f(T t) {
 A<T> a;
 a.template f<>(t); // OK: calls template
 a.template f(t); // error: not a template-id
}

template <class T> struct B {
 template <class T2> struct C { };
};

// OK: T::template C names a class template:
template <class T, template <class X> class TT = T::template C> struct D { };
D<B<int>> > db;
```

— *end example*]

- <sup>6</sup> A *simple-template-id* that names a class template specialization is a *class-name* (Clause 12).
- <sup>7</sup> A *template-id* that names an alias template specialization is a *type-name*.

### 17.3 Template arguments

[temp.arg]

- <sup>1</sup> There are three forms of *template-argument*, corresponding to the three forms of *template-parameter*: type, non-type and template. The type and form of each *template-argument* specified in a *template-id* shall match the type and form specified for the corresponding parameter declared by the template in its *template-parameter-list*. When the parameter declared by the template is a template parameter pack (17.5.3), it will correspond to zero or more *template-arguments*. [*Example:*

```
template<class T> class Array {
 T* v;
 int sz;
public:
```

```

 explicit Array(int);
 T& operator[](int);
 T& elem(int i) { return v[i]; }
};

Array<int> v1(20);
typedef std::complex<double> dcomplex; // std::complex is a standard library template
Array<dcomplex> v2(30);
Array<dcomplex> v3(40);

void bar() {
 v1[3] = 7;
 v2[3] = v3.elem(4) = dcomplex(7,8);
}

```

— end example]

- <sup>2</sup> In a *template-argument*, an ambiguity between a *type-id* and an expression is resolved to a *type-id*, regardless of the form of the corresponding *template-parameter*.<sup>137</sup> [Example:

```

template<class T> void f();
template<int I> void f();

void g() {
 f<int()>(); // int() is a type-id: call the first f()
}

```

— end example]

- <sup>3</sup> The name of a *template-argument* shall be accessible at the point where it is used as a *template-argument*. [Note: If the name of the *template-argument* is accessible at the point where it is used as a *template-argument*, there is no further access restriction in the resulting instantiation where the corresponding *template-parameter* name is used. — end note] [Example:

```

template<class T> class X {
 static T t;
};

class Y {
private:
 struct S { /* ... */ };
 X<S> x; // OK: S is accessible
 // X<Y::S> has a static member of type Y::S
 // OK: even though Y::S is private
};

X<Y::S> y; // error: S not accessible

```

— end example] For a *template-argument* that is a class type or a class template, the template definition has no special access rights to the members of the *template-argument*. [Example:

```

template <template <class TT> class T> class A {
 typename T<int>::S s;
};

template <class U> class B {
private:

```

<sup>137</sup>) There is no such ambiguity in a default *template-argument* because the form of the *template-parameter* determines the allowable forms of the *template-argument*.

```
 struct S { /* ... */ };
};
```

```
A b; // ill-formed: A has no access to B::S
```

— end example]

- <sup>4</sup> When template argument packs or default *template-arguments* are used, a *template-argument* list can be empty. In that case the empty <> brackets shall still be used as the *template-argument-list*. [Example:

```
template<class T = char> class String;
String<>* p; // OK: String<char>
String* q; // syntax error
template<class ... Elements> class Tuple;
Tuple<>* t; // OK: Elements is empty
Tuple* u; // syntax error
```

— end example]

- <sup>5</sup> An explicit destructor call (15.4) for an object that has a type that is a class template specialization may explicitly specify the *template-arguments*. [Example:

```
template<class T> struct A {
 ~A();
};
void f(A<int>* p, A<int>* q) {
 p->A<int>::~~A(); // OK: destructor call
 q->A<int>::~~A<int>(); // OK: destructor call
}
```

— end example]

- <sup>6</sup> If the use of a *template-argument* gives rise to an ill-formed construct in the instantiation of a template specialization, the program is ill-formed.
- <sup>7</sup> When the template in a *template-id* is an overloaded function template, both non-template functions in the overload set and function templates in the overload set for which the *template-arguments* do not match the *template-parameters* are ignored. If none of the function templates have matching *template-parameters*, the program is ill-formed.
- <sup>8</sup> When a *simple-template-id* does not name a function, a default *template-argument* is implicitly instantiated (17.7.1) when the value of that default argument is needed. [Example:

```
template<typename T, typename U = int> struct S { };
S<bool>* p; // the type of p is S<bool, int>*
```

The default argument for U is instantiated to form the type S<bool, int>\*. — end example]

- <sup>9</sup> A *template-argument* followed by an ellipsis is a pack expansion (17.5.3).

### 17.3.1 Template type arguments

[temp.arg.type]

- <sup>1</sup> A *template-argument* for a *template-parameter* which is a type shall be a *type-id*.

- <sup>2</sup> [Example:

```
template <class T> class X { };
template <class T> void f(T t) { }
struct { } unnamed_obj;

void f() {
 struct A { };
 enum { e1 };
}
```

```

typedef struct { } B;
B b;
X<A> x1; // OK
X<A*> x2; // OK
X x3; // OK
f(e1); // OK
f(unnamed_obj); // OK
f(b); // OK
}

```

— end example] [Note: A template type argument may be an incomplete type (6.9). — end note]

### 17.3.2 Template non-type arguments [temp.arg.nontype]

<sup>1</sup> If the type of a *template-parameter* contains a placeholder type (10.1.7.4, 17.1), the deduced parameter type is determined from the type of the *template-argument* by placeholder type deduction (10.1.7.4.1). If a deduced parameter type is not permitted for a *template-parameter* declaration (17.1), the program is ill-formed.

<sup>2</sup> A *template-argument* for a non-type *template-parameter* shall be a converted constant expression (8.20) of the type of the *template-parameter*. For a non-type *template-parameter* of reference or pointer type, the value of the constant expression shall not refer to (or for a pointer type, shall not be the address of):

- (2.1) — a subobject (4.5),
- (2.2) — a temporary object (15.2),
- (2.3) — a string literal (5.13.5),
- (2.4) — the result of a `typeid` expression (8.2.8), or
- (2.5) — a predefined `__func__` variable (11.4.1).

[Note: If the *template-argument* represents a set of overloaded functions (or a pointer or member pointer to such), the matching function is selected from the set (16.4). — end note]

<sup>3</sup> [Example:

```

template<const int* pci> struct X { /* ... */ };
int ai[10];
X<ai> xi; // array to pointer and qualification conversions

struct Y { /* ... */ };
template<const Y& b> struct Z { /* ... */ };
Y y;
Z<y> z; // no conversion, but note extra cv-qualification

template<int (&pa)[5]> struct W { /* ... */ };
int b[5];
W w; // no conversion

void f(char);
void f(int);

template<void (*pf)(int)> struct A { /* ... */ };

A<&f> a; // selects f(int)

template<auto n> struct B { /* ... */ };
B<5> b1; // OK: template parameter type is int
B<'a'> b2; // OK: template parameter type is char
B<2.5> b3; // error: template parameter type cannot be double

```



— end example]

- <sup>4</sup> [Note: A string literal (5.13.5) is not an acceptable *template-argument*. [Example:

```
template<class T, const char* p> class X {
 /* ... */
};

X<int, "Studebaker"> x1; // error: string literal as template-argument

const char p[] = "Vivisectionist";
X<int,p> x2; // OK
```

— end example] — end note]

- <sup>5</sup> [Note: The address of an array element or non-static data member is not an acceptable *template-argument*. [Example:

```
template<int* p> class X { };

int a[10];
struct S { int m; static int s; } s;

X<&a[2]> x3; // error: address of array element
X<&s.m> x4; // error: address of non-static member
X<&s.s> x5; // OK: address of static member
X<&S::s> x6; // OK: address of static member
```

— end example] — end note]

- <sup>6</sup> [Note: A temporary object is not an acceptable *template-argument* when the corresponding *template-parameter* has reference type. [Example:

```
template<const int& CRI> struct B { /* ... */ };

B<1> b2; // error: temporary would be required for template argument

int c = 1;
B<c> b1; // OK
```

— end example] — end note]

### 17.3.3 Template template arguments

[temp.arg.template]

- <sup>1</sup> A *template-argument* for a template *template-parameter* shall be the name of a class template or an alias template, expressed as *id-expression*. When the *template-argument* names a class template, only primary class templates are considered when matching the template template argument with the corresponding parameter; partial specializations are not considered even if their parameter lists match that of the template template parameter.
- <sup>2</sup> Any partial specializations (17.5.5) associated with the primary class template or primary variable template are considered when a specialization based on the template *template-parameter* is instantiated. If a specialization is not visible at the point of instantiation, and it would have been selected had it been visible, the program is ill-formed, no diagnostic required. [Example:

```
template<class T> class A { // primary template
 int x;
};
template<class T> class A<T*> { // partial specialization
 long x;
};
```

```

template<template<class U> class V> class C {
 V<int> y;
 V<int*> z;
};
C<A> c; // V<int> within C<A> uses the primary template, so c.y.x has type int
 // V<int*> within C<A> uses the partial specialization, so c.z.x has type long

```

— end example]

- <sup>3</sup> A *template-argument* matches a template *template-parameter* P when P is at least as specialized as the *template-argument* A. If P contains a parameter pack, then A also matches P if each of A's template parameters matches the corresponding template parameter in the *template-parameter-list* of P. Two template parameters match if they are of the same kind (type, non-type, template), for non-type *template-parameters*, their types are equivalent (17.5.6.1), and for template *template-parameters*, each of their corresponding *template-parameters* matches, recursively. When P's *template-parameter-list* contains a template parameter pack (17.5.3), the template parameter pack will match zero or more template parameters or template parameter packs in the *template-parameter-list* of A with the same type and form as the template parameter pack in P (ignoring whether those template parameters are template parameter packs).

[Example:

```

template<class T> class A { /* ... */ };
template<class T, class U = T> class B { /* ... */ };
template<class ... Types> class C { /* ... */ };
template<auto n> class D { /* ... */ };
template<template<class>> class P> class X { /* ... */ };
template<template<class ...> class Q> class Y { /* ... */ };
template<template<int> class R> class Z { /* ... */ };

```

```

X<A> xa; // OK
X xb; // OK
X<C> xc; // OK
Y<A> ya; // OK
Y yb; // OK
Y<C> yc; // OK
Z<D> zd; // OK

```

— end example]

[Example:

```

template <class T> struct eval;

template <template <class, class...> class TT, class T1, class... Rest>
struct eval<TT<T1, Rest...>> { };

template <class T1> struct A;
template <class T1, class T2> struct B;
template <int N> struct C;
template <class T1, int N> struct D;
template <class T1, class T2, int N = 17> struct E;

eval<A<int>>> eA; // OK: matches partial specialization of eval
eval<B<int, float>>> eB; // OK: matches partial specialization of eval
eval<C<17>>> eC; // error: C does not match TT in partial specialization
eval<D<int, 17>>> eD; // error: D does not match TT in partial specialization
eval<E<int, float>>> eE; // error: E does not match TT in partial specialization

```

— end example]

- <sup>4</sup> A template *template-parameter* P is at least as specialized as a template *template-argument* A if, given the following rewrite to two function templates, the function template corresponding to P is at least as specialized as the function template corresponding to A according to the partial ordering rules for function templates (17.5.6.2). Given an invented class template X with the template parameter list of A (including default arguments):

- (4.1) — Each of the two function templates has the same template parameters, respectively, as P or A.
- (4.2) — Each function template has a single function parameter whose type is a specialization of X with template arguments corresponding to the template parameters from the respective function template where, for each template parameter PP in the template parameter list of the function template, a corresponding template argument AA is formed. If PP declares a parameter pack, then AA is the pack expansion PP... (17.5.3); otherwise, AA is the *id-expression* PP.

If the rewrite produces an invalid type, then P is not at least as specialized as A.

## 17.4 Type equivalence

[temp.type]

- <sup>1</sup> Two *template-ids* refer to the same class, function, or variable if

- (1.1) — their *template-names*, *operator-function-ids*, or *literal-operator-ids* refer to the same template and
- (1.2) — their corresponding type *template-arguments* are the same type and
- (1.3) — their corresponding non-type template arguments of integral or enumeration type have identical values and
- (1.4) — their corresponding non-type *template-arguments* of pointer type refer to the same object or function or are both the null pointer value and
- (1.5) — their corresponding non-type *template-arguments* of pointer-to-member type refer to the same class member or are both the null member pointer value and
- (1.6) — their corresponding non-type *template-arguments* of reference type refer to the same object or function and
- (1.7) — their corresponding template *template-arguments* refer to the same template.

[Example:

```
template<class E, int size> class buffer { /* ... */ };
buffer<char,2*512> x;
buffer<char,1024> y;
```

declares x and y to be of the same type, and

```
template<class T, void(*err_fct)()> class list { /* ... */ };
list<int,&error_handler1> x1;
list<int,&error_handler2> x2;
list<int,&error_handler2> x3;
list<char,&error_handler2> x4;
```

declares x2 and x3 to be of the same type. Their type differs from the types of x1 and x4.

```
template<class T> struct X { };
template<class> struct Y { };
template<class T> using Z = Y<T>;
X<Y<int>> > y;
X<Z<int>> > z;
```

declares y and z to be of the same type. — end example]

- <sup>2</sup> If an expression *e* is type-dependent (17.6.2.2), `decltype(e)` denotes a unique dependent type. Two such *decltype-specifiers* refer to the same type only if their *expressions* are equivalent (17.5.6.1). [Note: However,

such a type may be aliased, e.g., by a *typedef-name*. — end note]

## 17.5 Template declarations

[temp.decls]

- <sup>1</sup> A *template-id*, that is, the *template-name* followed by a *template-argument-list* shall not be specified in the declaration of a primary template declaration. [Example:

```
template<class T1, class T2, int I> class A<T1, T2, I> { }; // error
template<class T1, int I> void sort<T1, I>(T1 data[I]); // error
```

— end example] [Note: However, this syntax is allowed in class template partial specializations (17.5.5). — end note]

- <sup>2</sup> For purposes of name lookup and instantiation, default arguments and *noexcept-specifiers* of function templates and default arguments and *noexcept-specifiers* of member functions of class templates are considered definitions; each default argument or *noexcept-specifier* is a separate definition which is unrelated to the function template definition or to any other default arguments or *noexcept-specifiers*. For the purpose of instantiation, the substatements of a *constexpr* if statement (9.4.1) are considered definitions.
- <sup>3</sup> Because an *alias-declaration* cannot declare a *template-id*, it is not possible to partially or explicitly specialize an alias template.

### 17.5.1 Class templates

[temp.class]

- <sup>1</sup> A *class template* defines the layout and operations for an unbounded set of related types.
- <sup>2</sup> [Example: A single class template `List` might provide an unbounded set of class definitions: one class `List<T>` for every type `T`, each describing a linked list of elements of type `T`. Similarly, a class template `Array` describing a contiguous, dynamic array might be defined like this:

```
template<class T> class Array {
 T* v;
 int sz;
public:
 explicit Array(int);
 T& operator[](int);
 T& elem(int i) { return v[i]; }
};
```

The prefix `template<class T>` specifies that a template is being declared and that a *type-name* `T` may be used in the declaration. In other words, `Array` is a parameterized type with `T` as its parameter. — end example]

- <sup>3</sup> When a member function, a member class, a member enumeration, a static data member or a member template of a class template is defined outside of the class template definition, the member definition is defined as a template definition in which the *template-parameters* are those of the class template. The names of the template parameters used in the definition of the member may be different from the template parameter names used in the class template definition. The template argument list following the class template name in the member definition shall name the parameters in the same order as the one used in the template parameter list of the member. Each template parameter pack shall be expanded with an ellipsis in the template argument list. [Example:

```
template<class T1, class T2> struct A {
 void f1();
 void f2();
};

template<class T2, class T1> void A<T2,T1>::f1() { } // OK
template<class T2, class T1> void A<T1,T2>::f2() { } // error
```

```
template<class ... Types> struct B {
 void f3();
 void f4();
};
```

```
template<class ... Types> void B<Types ...>::f3() { } // OK
template<class ... Types> void B<Types>::f4() { } // error
```

— end example]

- <sup>4</sup> In a redeclaration, partial specialization, explicit specialization or explicit instantiation of a class template, the *class-key* shall agree in kind with the original class template declaration (10.1.7.3).

### 17.5.1.1 Member functions of class templates [temp.mem.func]

- <sup>1</sup> A member function of a class template may be defined outside of the class template definition in which it is declared. [Example:

```
template<class T> class Array {
 T* v;
 int sz;
public:
 explicit Array(int);
 T& operator[] (int);
 T& elem(int i) { return v[i]; }
};
```

declares three function templates. The subscript function might be defined like this:

```
template<class T> T& Array<T>::operator[] (int i) {
 if (i<0 || sz<=i) error("Array: range error");
 return v[i];
}
```

— end example]

- <sup>2</sup> The *template-arguments* for a member function of a class template are determined by the *template-arguments* of the type of the object for which the member function is called. [Example: The *template-argument* for `Array<T>::operator[]()` will be determined by the `Array` to which the subscripting operation is applied.

```
Array<int> v1(20);
Array<dcomplex> v2(30);

v1[3] = 7; // Array<int>::operator[]()
v2[3] = dcomplex(7,8); // Array<dcomplex>::operator[]()
```

— end example]

### 17.5.1.2 Member classes of class templates [temp.mem.class]

- <sup>1</sup> A member class of a class template may be defined outside the class template definition in which it is declared. [Note: The member class must be defined before its first use that requires an instantiation (17.7.1). For example,

```
template<class T> struct A {
 class B;
};
A<int>::B* b1; // OK: requires A to be defined but not A::B
template<class T> class A<T>::B { };
A<int>::B b2; // OK: requires A::B to be defined
```

— end note]

**17.5.1.3 Static data members of class templates****[temp.static]**

- <sup>1</sup> A definition for a static data member or static data member template may be provided in a namespace scope enclosing the definition of the static member's class template. [ *Example:*

```
template<class T> class X {
 static T s;
};
template<class T> T X<T>::s = 0;

struct limits {
 template<class T>
 static const T min; // declaration
};

template<class T>
 const T limits::min = { }; // definition
```

— *end example*]

- <sup>2</sup> An explicit specialization of a static data member declared as an array of unknown bound can have a different bound from its definition, if any. [ *Example:*

```
template <class T> struct A {
 static int i[];
};
template <class T> int A<T>::i[4]; // 4 elements
template <> int A<int>::i[] = { 1 }; // OK: 1 element
```

— *end example*]

**17.5.1.4 Enumeration members of class templates****[temp.mem.enum]**

- <sup>1</sup> An enumeration member of a class template may be defined outside the class template definition. [ *Example:*

```
template<class T> struct A {
 enum E : T;
};
A<int> a;
template<class T> enum A<T>::E : T { e1, e2 };
A<int>::E e = A<int>::e1;
```

— *end example*]

**17.5.2 Member templates****[temp.mem]**

- <sup>1</sup> A template can be declared within a class or class template; such a template is called a member template. A member template can be defined within or outside its class definition or class template definition. A member template of a class template that is defined outside of its class template definition shall be specified with the *template-parameters* of the class template followed by the *template-parameters* of the member template. [ *Example:*

```
template<class T> struct string {
 template<class T2> int compare(const T2&);
 template<class T2> string(const string<T2>& s) { /* ... */ }
};

template<class T> template<class T2> int string<T>::compare(const T2& s) {
}
```

— *end example*]

- <sup>2</sup> A local class of non-closure type shall not have member templates. Access control rules (Clause 14) apply to member template names. A destructor shall not be a member template. A non-template member function (11.3.5) with a given name and type and a member function template of the same name, which could be used to generate a specialization of the same type, can both be declared in a class. When both exist, a use of that name and type refers to the non-template member unless an explicit template argument list is supplied. [*Example:*

```
template <class T> struct A {
 void f(int);
 template <class T2> void f(T2);
};

template <> void A<int>::f(int) { } // non-template member function
template <> template <> void A<int>::f<>(int) { } // member function template specialization

int main() {
 A<char> ac;
 ac.f(1); // non-template
 ac.f('c'); // template
 ac.f<>(1); // template
}
```

— end example]

- <sup>3</sup> A member function template shall not be virtual. [*Example:*

```
template <class T> struct AA {
 template <class C> virtual void g(C); // error
 virtual void f(); // OK
};
```

— end example]

- <sup>4</sup> A specialization of a member function template does not override a virtual function from a base class. [*Example:*

```
class B {
 virtual void f(int);
};

class D : public B {
 template <class T> void f(T); // does not override B::f(int)
 void f(int i) { f<>(i); } // overriding function that calls the template instantiation
};
```

— end example]

- <sup>5</sup> A specialization of a conversion function template is referenced in the same way as a non-template conversion function that converts to the same type. [*Example:*

```
struct A {
 template <class T> operator T*();
};

template <class T> A::operator T*(){ return 0; }
template <> A::operator char*(){ return 0; } // specialization
template A::operator void*(); // explicit instantiation

int main() {
 A a;
 int* ip;
```

```
 ip = a.operator int*(); // explicit call to template operator A::operator int*()
}
```

— end example] [Note: Because the explicit template argument list follows the function template name, and because conversion member function templates and constructor member function templates are called without using a function name, there is no way to provide an explicit template argument list for these function templates. — end note]

- 6 A specialization of a conversion function template is not found by name lookup. Instead, any conversion function templates visible in the context of the use are considered. For each such operator, if argument deduction succeeds (17.8.2.3), the resulting specialization is used as if found by name lookup.
- 7 A *using-declaration* in a derived class cannot refer to a specialization of a conversion function template in a base class.
- 8 Overload resolution (16.3.3.2) and partial ordering (17.5.6.2) are used to select the best conversion function among multiple specializations of conversion function templates and/or non-template conversion functions.

### 17.5.3 Variadic templates

[temp.variadic]

- 1 A *template parameter pack* is a template parameter that accepts zero or more template arguments. [Example:

```
template<class ... Types> struct Tuple { };

Tuple<> t0; // Types contains no arguments
Tuple<int> t1; // Types contains one argument: int
Tuple<int, float> t2; // Types contains two arguments: int and float
Tuple<0> error; // error: 0 is not a type
```

— end example]

- 2 A *function parameter pack* is a function parameter that accepts zero or more function arguments. [Example:

```
template<class ... Types> void f(Types ... args);

f(); // OK: args contains no arguments
f(1); // OK: args contains one argument: int
f(2, 1.0); // OK: args contains two arguments: int and double
```

— end example]

- 3 A *parameter pack* is either a template parameter pack or a function parameter pack.
- 4 A *pack expansion* consists of a *pattern* and an ellipsis, the instantiation of which produces zero or more instantiations of the pattern in a list (described below). The form of the pattern depends on the context in which the expansion occurs. Pack expansions can occur in the following contexts:
  - (4.1) — In a function parameter pack (11.3.5); the pattern is the *parameter-declaration* without the ellipsis.
  - (4.2) — In a *using-declaration* (10.3.3); the pattern is a *using-declarator*.
  - (4.3) — In a template parameter pack that is a pack expansion (17.1):
    - (4.3.1) — if the template parameter pack is a *parameter-declaration*; the pattern is the *parameter-declaration* without the ellipsis;
    - (4.3.2) — if the template parameter pack is a *type-parameter* with a *template-parameter-list*; the pattern is the corresponding *type-parameter* without the ellipsis.
  - (4.4) — In an *initializer-list* (11.6); the pattern is an *initializer-clause*.
  - (4.5) — In a *base-specifier-list* (Clause 13); the pattern is a *base-specifier*.
  - (4.6) — In a *mem-initializer-list* (15.6.2) for a *mem-initializer* whose *mem-initializer-id* denotes a base class; the pattern is the *mem-initializer*.



- (4.7) — In a *template-argument-list* (17.3); the pattern is a *template-argument*.
- (4.8) — In an *attribute-list* (10.6.1); the pattern is an *attribute*.
- (4.9) — In an *alignment-specifier* (10.6.2); the pattern is the *alignment-specifier* without the ellipsis.
- (4.10) — In a *capture-list* (8.1.5); the pattern is a *capture*.
- (4.11) — In a `sizeof...` expression (8.3.3); the pattern is an *identifier*.
- (4.12) — In a *fold-expression* (8.1.6); the pattern is the *cast-expression* that contains an unexpanded parameter pack.

[*Example:*

```
template<class ... Types> void f(Types ... rest);
template<class ... Types> void g(Types ... rest) {
 f(&rest ...); // “&rest ...” is a pack expansion; “&rest” is its pattern
}
```

— *end example*]

- 5 For the purpose of determining whether a parameter pack satisfies a rule regarding entities other than parameter packs, the parameter pack is considered to be the entity that would result from an instantiation of the pattern in which it appears.
- 6 A parameter pack whose name appears within the pattern of a pack expansion is expanded by that pack expansion. An appearance of the name of a parameter pack is only expanded by the innermost enclosing pack expansion. The pattern of a pack expansion shall name one or more parameter packs that are not expanded by a nested pack expansion; such parameter packs are called *unexpanded parameter packs* in the pattern. All of the parameter packs expanded by a pack expansion shall have the same number of arguments specified. An appearance of a name of a parameter pack that is not expanded is ill-formed. [*Example:*

```
template<typename...> struct Tuple {};
template<typename T1, typename T2> struct Pair {};

template<class ... Args1> struct zip {
 template<class ... Args2> struct with {
 typedef Tuple<Pair<Args1, Args2> ... > type;
 };
};

typedef zip<short, int>::with<unsigned short, unsigned>::type T1;
// T1 is Tuple<Pair<short, unsigned short>, Pair<int, unsigned>>
typedef zip<short>::with<unsigned short, unsigned>::type T2;
// error: different number of arguments specified for Args1 and Args2

template<class ... Args>
void g(Args ... args) {
 f(const_cast<const Args*>(&args)...); // OK: Args is expanded by the function parameter pack args
 f(5 ...); // OK: “Args” and “args” are expanded
 f(args); // error: pattern does not contain any parameter packs
 f(h(args ...) + args ...); // error: parameter pack “args” is not expanded
 // OK: first “args” expanded within h,
 // second “args” expanded within f
}
```

— *end example*]

- 7 The instantiation of a pack expansion that is neither a `sizeof...` expression nor a *fold-expression* produces a list  $E_1, E_2, \dots, E_N$ , where  $N$  is the number of elements in the pack expansion parameters. Each  $E_i$  is generated by instantiating the pattern and replacing each pack expansion parameter with its  $i$ th element. Such an

element, in the context of the instantiation, is interpreted as follows:

- (7.1) — if the pack is a template parameter pack, the element is a template parameter (17.1) of the corresponding kind (type or non-type) designating the type or value from the template argument; otherwise,
- (7.2) — if the pack is a function parameter pack, the element is an *id-expression* designating the function parameter that resulted from the instantiation of the pattern where the pack is declared.

All of the  $E_i$  become elements in the enclosing list. [ *Note:* The variety of list varies with the context: *expression-list*, *base-specifier-list*, *template-argument-list*, etc. — *end note* ] When  $N$  is zero, the instantiation of the expansion produces an empty list. Such an instantiation does not alter the syntactic interpretation of the enclosing construct, even in cases where omitting the list entirely would otherwise be ill-formed or would result in an ambiguity in the grammar. [ *Example:*

```
template<class... T> struct X : T... { };
template<class... T> void f(T... values) {
 X<T...> x(values...);
}

template void f<>(); // OK: X<> has no base classes
 // x is a variable of type X<> that is value-initialized
```

— *end example*]

- 8 The instantiation of a `sizeof... expression` (8.3.3) produces an integral constant containing the number of elements in the parameter pack it expands.
- 9 The instantiation of a *fold-expression* produces:
  - (9.1) —  $((E_1 \text{ op } E_2) \text{ op } \dots) \text{ op } E_N$  for a unary left fold,
  - (9.2) —  $E_1 \text{ op } (\dots \text{ op } (E_{N-1} \text{ op } E_N))$  for a unary right fold,
  - (9.3) —  $((E \text{ op } E_1) \text{ op } E_2) \text{ op } \dots) \text{ op } E_N$  for a binary left fold, and
  - (9.4) —  $E_1 \text{ op } (\dots \text{ op } (E_{N-1} \text{ op } (E_N \text{ op } E)))$  for a binary right fold.

In each case, *op* is the *fold-operator*,  $N$  is the number of elements in the pack expansion parameters, and each  $E_i$  is generated by instantiating the pattern and replacing each pack expansion parameter with its  $i$ th element. For a binary fold-expression,  $E$  is generated by instantiating the *cast-expression* that did not contain an unexpanded parameter pack. [ *Example:*

```
template<typename ...Args>
bool all(Args ...args) { return (... && args); }

bool b = all(true, true, true, false);
```

Within the instantiation of `all`, the returned expression expands to  $((\text{true} \ \&\& \ \text{true}) \ \&\& \ \text{true}) \ \&\& \ \text{false}$ , which evaluates to `false`. — *end example* ] If  $N$  is zero for a unary fold-expression, the value of the expression is shown in Table 14; if the operator is not listed in Table 14, the instantiation is ill-formed.

Table 14 — Value of folding empty sequences

| Operator                | Value when parameter pack is empty |
|-------------------------|------------------------------------|
| <code>&amp;&amp;</code> | <code>true</code>                  |
| <code>  </code>         | <code>false</code>                 |
| <code>,</code>          | <code>void()</code>                |

## 17.5.4 Friends

[temp.friend]

- <sup>1</sup> A friend of a class or class template can be a function template or class template, a specialization of a function template or class template, or a non-template function or class. For a friend function declaration that is not a template declaration:
- (1.1) — if the name of the friend is a qualified or unqualified *template-id*, the friend declaration refers to a specialization of a function template, otherwise,
  - (1.2) — if the name of the friend is a *qualified-id* and a matching non-template function is found in the specified class or namespace, the friend declaration refers to that function, otherwise,
  - (1.3) — if the name of the friend is a *qualified-id* and a matching function template is found in the specified class or namespace, the friend declaration refers to the deduced specialization of that function template (17.8.2.6), otherwise,
  - (1.4) — the name shall be an *unqualified-id* that declares (or redeclares) a non-template function.

[Example:

```
template<class T> class task;
template<class T> task<T>* preempt(task<T>*);

template<class T> class task {
 friend void next_time();
 friend void process(task<T>*);
 friend task<T>* preempt<T>(task<T>*);
 template<class C> friend int func(C);

 friend class task<int>;
 template<class P> friend class frd;
};
```

Here, each specialization of the `task` class template has the function `next_time` as a friend; because `process` does not have explicit *template-arguments*, each specialization of the `task` class template has an appropriately typed function `process` as a friend, and this friend is not a function template specialization; because the friend `preempt` has an explicit *template-argument* `T`, each specialization of the `task` class template has the appropriate specialization of the function template `preempt` as a friend; and each specialization of the `task` class template has all specializations of the function template `func` as friends. Similarly, each specialization of the `task` class template has the class template specialization `task<int>` as a friend, and has all specializations of the class template `frd` as friends. — end example]

- <sup>2</sup> A friend template may be declared within a class or class template. A friend function template may be defined within a class or class template, but a friend class template may not be defined in a class or class template. In these cases, all specializations of the friend class or friend function template are friends of the class or class template granting friendship. [Example:

```
class A {
 template<class T> friend class B; // OK
 template<class T> friend void f(T){ /* ... */ } // OK
};
```

— end example]

- <sup>3</sup> A template friend declaration specifies that all specializations of that template, whether they are implicitly instantiated (17.7.1), partially specialized (17.5.5) or explicitly specialized (17.7.3), are friends of the class containing the template friend declaration. [Example:

```
class X {
 template<class T> friend struct A;
 class Y { };
};
```

```
};

template<class T> struct A { X::Y ab; }; // OK
template<class T> struct A<T*> { X::Y ab; }; // OK
```

— end example]

- <sup>4</sup> A member of a class template may be declared to be a friend of a non-template class. In this case, the corresponding member of every specialization of the primary class template and class template partial specializations thereof is a friend of the class granting friendship. For explicit specializations and specializations of partial specializations, the corresponding member is the member (if any) that has the same name, kind (type, function, class template, or function template), template parameters, and signature as the member of the class template instantiation that would otherwise have been generated. [ *Example:*

```
template<class T> struct A {
 struct B { };
 void f();
 struct D {
 void g();
 };
};

template<> struct A<int> {
 struct B { };
 int f();
 struct D {
 void g();
 };
};

class C {
 template<class T> friend struct A<T>::B; // grants friendship to A<int>::B even though
 // it is not a specialization of A<T>::B
 template<class T> friend void A<T>::f(); // does not grant friendship to A<int>::f()
 // because its return type does not match
 template<class T> friend void A<T>::D::g(); // does not grant friendship to A<int>::D::g()
 // because A<int>::D is not a specialization of A<T>::D
};
```

— end example]

- <sup>5</sup> [ *Note:* A friend declaration may first declare a member of an enclosing namespace scope (17.6.5). — end note]

- <sup>6</sup> A friend template shall not be declared in a local class.

- <sup>7</sup> Friend declarations shall not declare partial specializations. [ *Example:*

```
template<class T> class A { };
class X {
 template<class T> friend class A<T*>; // error
};
```

— end example]

- <sup>8</sup> When a friend declaration refers to a specialization of a function template, the function parameter declarations shall not include default arguments, nor shall the inline specifier be used in such a declaration.

### 17.5.5 Class template partial specializations [temp.class.spec]

- <sup>1</sup> A *primary class template* declaration is one in which the class template name is an identifier. A template declaration in which the class template name is a *simple-template-id* is a *partial specialization* of the class template named in the *simple-template-id*. A partial specialization of a class template provides an alternative definition of the template that is used instead of the primary definition when the arguments in a specialization match those given in the partial specialization (17.5.5.1). The primary template shall be declared before any specializations of that template. A partial specialization shall be declared before the first use of a class template specialization that would make use of the partial specialization as the result of an implicit or explicit instantiation in every translation unit in which such a use occurs; no diagnostic is required.
- <sup>2</sup> Each class template partial specialization is a distinct template and definitions shall be provided for the members of a template partial specialization (17.5.5.3).

<sup>3</sup> [Example:

```
template<class T1, class T2, int I> class A { };
template<class T, int I> class A<T, T*, I> { };
template<class T1, class T2, int I> class A<T1*, T2, I> { };
template<class T> class A<int, T*, 5> { };
template<class T1, class T2, int I> class A<T1, T2*, I> { };
```

The first declaration declares the primary (unspecialized) class template. The second and subsequent declarations declare partial specializations of the primary template. — end example]

- <sup>4</sup> The template parameters are specified in the angle bracket enclosed list that immediately follows the keyword **template**. For partial specializations, the template argument list is explicitly written immediately following the class template name. For primary templates, this list is implicitly described by the template parameter list. Specifically, the order of the template arguments is the sequence in which they appear in the template parameter list. [Example: The template argument list for the primary template in the example above is <T1, T2, I>. — end example] [Note: The template argument list shall not be specified in the primary template declaration. For example,

```
template<class T1, class T2, int I>
class A<T1, T2, I> { }; // error
```

— end note]

- <sup>5</sup> A class template partial specialization may be declared in any scope in which the corresponding primary template may be defined (10.3.1.2, 12.2, 17.5.2). [Example:

```
template<class T> struct A {
 struct C {
 template<class T2> struct B { };
 template<class T2> struct B<T2**> { }; // partial specialization #1
 };
};

// partial specialization of A<T>::C::B<T2>
template<class T> template<class T2>
struct A<T>::C::B<T2*> { }; // #2

A<short>::C::B<int*> absip; // uses partial specialization #2
```

— end example]

- <sup>6</sup> Partial specialization declarations themselves are not found by name lookup. Rather, when the primary template name is used, any previously-declared partial specializations of the primary template are also considered. One consequence is that a *using-declaration* which refers to a class template does not restrict the set of partial specializations which may be found through the *using-declaration*. [Example:

```

namespace N {
 template<class T1, class T2> class A { }; // primary template
}

using N::A; // refers to the primary template

namespace N {
 template<class T> class A<T, T*> { }; // partial specialization
}

A<int,int*> a; // uses the partial specialization, which is found through the using-declaration
 // which refers to the primary template

— end example]

```

<sup>7</sup> A non-type argument is non-specialized if it is the name of a non-type parameter. All other non-type arguments are specialized.

<sup>8</sup> Within the argument list of a class template partial specialization, the following restrictions apply:

- (8.1) — The type of a template parameter corresponding to a specialized non-type argument shall not be dependent on a parameter of the specialization. [ *Example:*

```

template <class T, T t> struct C {};
template <class T> struct C<T, 1>; // error

```

```

template< int X, int (*array_ptr)[X] > class A {};
int array[5];
template< int X > class A<X,&array> { }; // error

```

— end example]

- (8.2) — The specialization shall be more specialized than the primary template (17.5.5.2).
- (8.3) — The template parameter list of a specialization shall not contain default template argument values.<sup>138</sup>
- (8.4) — An argument shall not contain an unexpanded parameter pack. If an argument is a pack expansion (17.5.3), it shall be the last argument in the template argument list.

#### 17.5.5.1 Matching of class template partial specializations [temp.class.spec.match]

<sup>1</sup> When a class template is used in a context that requires an instantiation of the class, it is necessary to determine whether the instantiation is to be generated using the primary template or one of the partial specializations. This is done by matching the template arguments of the class template specialization with the template argument lists of the partial specializations.

- (1.1) — If exactly one matching specialization is found, the instantiation is generated from that specialization.
- (1.2) — If more than one matching specialization is found, the partial order rules (17.5.5.2) are used to determine whether one of the specializations is more specialized than the others. If none of the specializations is more specialized than all of the other matching specializations, then the use of the class template is ambiguous and the program is ill-formed.
- (1.3) — If no matches are found, the instantiation is generated from the primary template.

<sup>2</sup> A partial specialization matches a given actual template argument list if the template arguments of the partial specialization can be deduced from the actual template argument list (17.8.2). [ *Example:*

```

template<class T1, class T2, int I> class A { }; // #1
template<class T, int I> class A<T, T*, I> { }; // #2
template<class T1, class T2, int I> class A<T1*, T2, I> { }; // #3

```

<sup>138</sup>) There is no way in which they could be used.

```

template<class T> class A<int, T*, 5> { }; // #4
template<class T1, class T2, int I> class A<T1, T2*, I> { }; // #5

A<int, int, 1> a1; // uses #1
A<int, int*, 1> a2; // uses #2, T is int, I is 1
A<int, char*, 5> a3; // uses #4, T is char
A<int, char*, 1> a4; // uses #5, T1 is int, T2 is char, I is 1
A<int*, int*, 2> a5; // ambiguous: matches #3 and #5

```

— end example]

- <sup>3</sup> If the template arguments of a partial specialization cannot be deduced because of the structure of its *template-parameter-list* and the *template-id*, the program is ill-formed. [Example:

```

template <int I, int J> struct A { };
template <int I> struct A<I+5, I*2> { }; // error

template <int I> struct A<I, I> { }; // OK

template <int I, int J, int K> struct B { };
template <int I> struct B<I, I*2, 2> { }; // OK

```

— end example]

- <sup>4</sup> In a type name that refers to a class template specialization, (e.g., `A<int, int, 1>`) the argument list shall match the template parameter list of the primary template. The template arguments of a specialization are deduced from the arguments of the primary template.

#### 17.5.5.2 Partial ordering of class template specializations

[temp.class.order]

- <sup>1</sup> For two class template partial specializations, the first is *more specialized* than the second if, given the following rewrite to two function templates, the first function template is more specialized than the second according to the ordering rules for function templates (17.5.6.2):

- (1.1) — Each of the two function templates has the same template parameters as the corresponding partial specialization.
- (1.2) — Each function template has a single function parameter whose type is a class template specialization where the template arguments are the corresponding template parameters from the function template for each template argument in the *template-argument-list* of the *simple-template-id* of the partial specialization.

- <sup>2</sup> [Example:

```

template<int I, int J, class T> class X { };
template<int I, int J> class X<I, J, int> { }; // #1
template<int I> class X<I, I, int> { }; // #2

template<int I0, int J0> void f(X<I0, J0, int>); // A
template<int I0> void f(X<I0, I0, int>); // B

template <auto v> class Y { };
template <auto* p> class Y<p> { }; // #3
template <auto** pp> class Y<pp> { }; // #4

template <auto* p0> void g(Y<p0>); // C
template <auto** pp0> void g(Y<pp0>); // D

```

According to the ordering rules for function templates, the function template *B* is more specialized than the function template *A* and the function template *D* is more specialized than the function template *C*.

Therefore, the partial specialization #2 is more specialized than the partial specialization #1 and the partial specialization #4 is more specialized than the partial specialization #3. — *end example*]

### 17.5.5.3 Members of class template specializations [temp.class.spec.mfunc]

- <sup>1</sup> The template parameter list of a member of a class template partial specialization shall match the template parameter list of the class template partial specialization. The template argument list of a member of a class template partial specialization shall match the template argument list of the class template partial specialization. A class template specialization is a distinct template. The members of the class template partial specialization are unrelated to the members of the primary template. Class template partial specialization members that are used in a way that requires a definition shall be defined; the definitions of members of the primary template are never used as definitions for members of a class template partial specialization. An explicit specialization of a member of a class template partial specialization is declared in the same way as an explicit specialization of the primary template. [ *Example*:

```
// primary class template
template<class T, int I> struct A {
 void f();
};

// member of primary class template
template<class T, int I> void A<T,I>::f() { }

// class template partial specialization
template<class T> struct A<T,2> {
 void f();
 void g();
 void h();
};

// member of class template partial specialization
template<class T> void A<T,2>::g() { }

// explicit specialization
template<> void A<char,2>::h() { }

int main() {
 A<char,0> a0;
 A<char,2> a2;
 a0.f(); // OK, uses definition of primary template's member
 a2.g(); // OK, uses definition of partial specialization's member
 a2.h(); // OK, uses definition of explicit specialization's member
 a2.f(); // ill-formed, no definition of f for A<T,2>; the primary template is not used here
}
```

— *end example*]

- <sup>2</sup> If a member template of a class template is partially specialized, the member template partial specializations are member templates of the enclosing class template; if the enclosing class template is instantiated (17.7.1, 17.7.2), a declaration for every member template partial specialization is also instantiated as part of creating the members of the class template specialization. If the primary member template is explicitly specialized for a given (implicit) specialization of the enclosing class template, the partial specializations of the member template are ignored for this specialization of the enclosing class template. If a partial specialization of the member template is explicitly specialized for a given (implicit) specialization of the enclosing class template, the primary member template and its other partial specializations are still considered for this specialization of the enclosing class template. [ *Example*:



```

template<class T> struct A {
 template<class T2> struct B {}; // #1
 template<class T2> struct B<T2*> {}; // #2
};

template<> template<class T2> struct A<short>::B {}; // #3

A<char>::B<int*> abcip; // uses #2
A<short>::B<int*> absip; // uses #3
A<char>::B<int> abci; // uses #1
— end example]

```

## 17.5.6 Function templates

[temp.fct]

- <sup>1</sup> A function template defines an unbounded set of related functions. [ *Example:* A family of sort functions might be declared like this:

```

template<class T> class Array { };
template<class T> void sort(Array<T>&);
— end example]

```

- <sup>2</sup> A function template can be overloaded with other function templates and with non-template functions (11.3.5). A non-template function is not related to a function template (i.e., it is never considered to be a specialization), even if it has the same name and type as a potentially generated function template specialization.<sup>139</sup>

### 17.5.6.1 Function template overloading

[temp.over.link]

- <sup>1</sup> It is possible to overload function templates so that two different function template specializations have the same type. [ *Example:*

```

// translation unit 1:
template<class T>
void f(T*);
void g(int* p) {
 f(p); // calls f<int*>(int*)
}

// translation unit 2:
template<class T>
void f(T);
void h(int* p) {
 f(p); // calls f<int*>(int*)
}
— end example]

```

- <sup>2</sup> Such specializations are distinct functions and do not violate the one-definition rule (6.2).
- <sup>3</sup> The signature of a function template is defined in Clause 3. The names of the template parameters are significant only for establishing the relationship between the template parameters and the rest of the signature. [ *Note:* Two distinct function templates may have identical function return types and function parameter lists, even if overload resolution alone cannot distinguish them.

```

template<class T> void f();
template<int I> void f(); // OK: overloads the first template
 // distinguishable with an explicit template argument list
— end note]

```

- <sup>4</sup> When an expression that references a template parameter is used in the function parameter list or the return type in the declaration of a function template, the expression that references the template parameter is part of the signature of the function template. This is necessary to permit a declaration of a function template in one translation unit to be linked with another declaration of the function template in another translation

<sup>139</sup>) That is, declarations of non-template functions do not merely guide overload resolution of function template specializations with the same name. If such a non-template function is odr-used (6.2) in a program, it must be defined; it will not be implicitly instantiated using the function template definition.

unit and, conversely, to ensure that function templates that are intended to be distinct are not linked with one another. [ *Example:*

```
template <int I, int J> A<I+J> f(A<I>, A<J>); // #1
template <int K, int L> A<K+L> f(A<K>, A<L>); // same as #1
template <int I, int J> A<I-J> f(A<I>, A<J>); // different from #1
```

— *end example*] [ *Note:* Most expressions that use template parameters use non-type template parameters, but it is possible for an expression to reference a type parameter. For example, a template type parameter can be used in the `sizeof` operator. — *end note*]

- 5 Two expressions involving template parameters are considered *equivalent* if two function definitions containing the expressions would satisfy the one-definition rule (6.2), except that the tokens used to name the template parameters may differ as long as a token used to name a template parameter in one expression is replaced by another token that names the same template parameter in the other expression. For determining whether two dependent names (17.6.2) are equivalent, only the name itself is considered, not the result of name lookup in the context of the template. If multiple declarations of the same function template differ in the result of this name lookup, the result for the first declaration is used. [ *Example:*

```
template <int I, int J> void f(A<I+J>); // #1
template <int K, int L> void f(A<K+L>); // same as #1

template <class T> decltype(g(T())) h();
int g(int);
template <class T> decltype(g(T())) h() // redeclaration of h() uses the earlier lookup
{ return g(T()); } // ...although the lookup here does find g(int)
int i = h<int>(); // template argument substitution fails; g(int)
 // was not in scope at the first declaration of h()
```

— *end example*] Two expressions involving template parameters that are not equivalent are *functionally equivalent* if, for any given set of template arguments, the evaluation of the expression results in the same value.

- 6 Two function templates are *equivalent* if they are declared in the same scope, have the same name, have identical template parameter lists, and have return types and parameter lists that are equivalent using the rules described above to compare expressions involving template parameters. Two function templates are *functionally equivalent* if they are equivalent except that one or more expressions that involve template parameters in the return types and parameter lists are functionally equivalent using the rules described above to compare expressions involving template parameters. If a program contains declarations of function templates that are functionally equivalent but not equivalent, the program is ill-formed, no diagnostic required.
- 7 [ *Note:* This rule guarantees that equivalent declarations will be linked with one another, while not requiring implementations to use heroic efforts to guarantee that functionally equivalent declarations will be treated as distinct. For example, the last two declarations are functionally equivalent and would cause a program to be ill-formed:

```
// Guaranteed to be the same
template <int I> void f(A<I>, A<I+10>);
template <int I> void f(A<I>, A<I+10>);

// Guaranteed to be different
template <int I> void f(A<I>, A<I+10>);
template <int I> void f(A<I>, A<I+11>);

// Ill-formed, no diagnostic required
template <int I> void f(A<I>, A<I+10>);
template <int I> void f(A<I>, A<I+1+2+3+4>);
```

— end note]

### 17.5.6.2 Partial ordering of function templates

[temp.func.order]

- <sup>1</sup> If a function template is overloaded, the use of a function template specialization might be ambiguous because template argument deduction (17.8.2) may associate the function template specialization with more than one function template declaration. *Partial ordering* of overloaded function template declarations is used in the following contexts to select the function template to which a function template specialization refers:

- (1.1) — during overload resolution for a call to a function template specialization (16.3.3);
- (1.2) — when the address of a function template specialization is taken;
- (1.3) — when a placement operator delete that is a function template specialization is selected to match a placement operator new (6.7.4.2, 8.3.4);
- (1.4) — when a friend function declaration (17.5.4), an explicit instantiation (17.7.2) or an explicit specialization (17.7.3) refers to a function template specialization.

- <sup>2</sup> Partial ordering selects which of two function templates is more specialized than the other by transforming each template in turn (see next paragraph) and performing template argument deduction using the function type. The deduction process determines whether one of the templates is more specialized than the other. If so, the more specialized template is the one chosen by the partial ordering process.

- <sup>3</sup> To produce the transformed template, for each type, non-type, or template template parameter (including template parameter packs (17.5.3) thereof) synthesize a unique type, value, or class template respectively and substitute it for each occurrence of that parameter in the function type of the template. [Note: The type replacing the placeholder in the type of the value synthesized for a non-type template parameter is also a unique synthesized type. — end note] If only one of the function templates *M* is a non-static member of some class *A*, *M* is considered to have a new first parameter inserted in its function parameter list. Given *cv* as the cv-qualifiers of *M* (if any), the new parameter is of type “rvalue reference to *cv A*” if the optional *ref-qualifier* of *M* is *&&* or if *M* has no *ref-qualifier* and the first parameter of the other template has rvalue reference type. Otherwise, the new parameter is of type “lvalue reference to *cv A*”. [Note: This allows a non-static member to be ordered with respect to a non-member function and for the results to be equivalent to the ordering of two equivalent non-members. — end note] [Example:

```
struct A { };
template<class T> struct B {
 template<class R> int operator*(R&); // #1
};

template<class T, class R> int operator*(T&, R&); // #2

// The declaration of B::operator* is transformed into the equivalent of
// template<class R> int operator*(B<A>&, R&); // #1a

int main() {
 A a;
 B<A> b;
 b * a; // calls #1a
}
```

— end example]

- <sup>4</sup> Using the transformed function template’s function type, perform type deduction against the other template as described in 17.8.2.4.

[Example:

```
template<class T> struct A { A(); };
```

```

template<class T> void f(T);
template<class T> void f(T*);
template<class T> void f(const T*);

template<class T> void g(T);
template<class T> void g(T&);

template<class T> void h(const T&);
template<class T> void h(A<T>&);

void m() {
 const int* p;
 f(p); // f(const T*) is more specialized than f(T) or f(T*)
 float x;
 g(x); // ambiguous: g(T) or g(T&)
 A<int> z;
 h(z); // overload resolution selects h(A<T>&)
 const A<int> z2;
 h(z2); // h(const T&) is called because h(A<T>&) is not callable
}

```

— end example]

- <sup>5</sup> [Note: Since partial ordering in a call context considers only parameters for which there are explicit call arguments, some parameters are ignored (namely, function parameter packs, parameters with default arguments, and ellipsis parameters). [Example:

```

template<class T> void f(T); // #1
template<class T> void f(T*, int=1); // #2
template<class T> void g(T); // #3
template<class T> void g(T*, ...); // #4

int main() {
 int* ip;
 f(ip); // calls #2
 g(ip); // calls #4
}

```

— end example] [Example:

```

template<class T, class U> struct A { };

template<class T, class U> void f(U, A<U, T>* p = 0); // #1
template<class T, class U> void f(U, A<U, U>* p = 0); // #2
template<class T> void g(T, T = T()); // #3
template<class T, class... U> void g(T, U ...); // #4

void h() {
 f<int>(42, (A<int, int>*)0); // calls #2
 f<int>(42); // error: ambiguous
 g(42); // error: ambiguous
}

```

— end example] [Example:

```

template<class T, class... U> void f(T, U...); // #1
template<class T> void f(T); // #2
template<class T, class... U> void g(T*, U...); // #3

```

```

template<class T > void g(T); // #4

void h(int i) {
 f(&i); // error: ambiguous
 g(&i); // OK: calls #3
}
— end example] — end note]

```

### 17.5.7 Alias templates

[temp.alias]

- <sup>1</sup> A *template-declaration* in which the *declaration* is an *alias-declaration* (Clause 10) declares the *identifier* to be an *alias template*. An alias template is a name for a family of types. The name of the alias template is a *template-name*.
- <sup>2</sup> When a *template-id* refers to the specialization of an alias template, it is equivalent to the associated type obtained by substitution of its *template-arguments* for the *template-parameters* in the *type-id* of the alias template. [Note: An alias template name is never deduced. — end note] [Example:

```

template<class T> struct Alloc { /* ... */ };
template<class T> using Vec = vector<T, Alloc<T>>;
Vec<int> v; // same as vector<int, Alloc<int>> v;

template<class T>
 void process(Vec<T>& v)
 { /* ... */ }

template<class T>
 void process(vector<T, Alloc<T>>& w)
 { /* ... */ } // error: redefinition

template<template<class> class TT>
 void f(TT<int>);

f(v); // error: Vec not deduced

template<template<class,class> class TT>
 void g(TT<int, Alloc<int>>>);
g(v); // OK: TT = vector
— end example]

```

- <sup>3</sup> However, if the *template-id* is dependent, subsequent template argument substitution still applies to the *template-id*. [Example:

```

template<typename...> using void_t = void;
template<typename T> void_t<typename T::foo> f();
f<int>(); // error, int does not have a nested type foo
— end example]

```

- <sup>4</sup> The *type-id* in an alias template declaration shall not refer to the alias template being declared. The type produced by an alias template specialization shall not directly or indirectly make use of that specialization. [Example:

```

template <class T> struct A;
template <class T> using B = typename A<T>::U;
template <class T> struct A {
 typedef B<T> U;
};

```

```
B<short> b; // error: instantiation of B<short> uses own type via A<short>::U
— end example]
```

## 17.6 Name resolution

[temp.res]

<sup>1</sup> Three kinds of names can be used within a template definition:

- (1.1) — The name of the template itself, and names declared within the template itself.
- (1.2) — Names dependent on a *template-parameter* (17.6.2).
- (1.3) — Names from scopes which are visible within the template definition.

<sup>2</sup> A name used in a template declaration or definition and that is dependent on a *template-parameter* is assumed not to name a type unless the applicable name lookup finds a type name or the name is qualified by the keyword **typename**. [Example:

```
// no B declared here

class X;

template<class T> class Y {
 class Z; // forward declaration of member class

 void f() {
 X* a1; // declare pointer to X
 T* a2; // declare pointer to T
 Y* a3; // declare pointer to Y<T>
 Z* a4; // declare pointer to Z
 typedef typename T::A TA;
 TA* a5; // declare pointer to T's A
 typename T::A* a6; // declare pointer to T's A
 T::A* a7; // T::A is not a type name:
 // multiplication of T::A by a7; ill-formed, no visible declaration of a7
 B* a8; // B is not a type name:
 // multiplication of B by a8; ill-formed, no visible declarations of B and a8
 }
};
```

— end example]

<sup>3</sup> When a *qualified-id* is intended to refer to a type that is not a member of the current instantiation (17.6.2.1) and its *nested-name-specifier* refers to a dependent type, it shall be prefixed by the keyword **typename**, forming a *typename-specifier*. If the *qualified-id* in a *typename-specifier* does not denote a type or a class template, the program is ill-formed.

*typename-specifier*:

```
typename nested-name-specifier identifier
typename nested-name-specifier templateopt simple-template-id
```

<sup>4</sup> If a specialization of a template is instantiated for a set of *template-arguments* such that the *qualified-id* prefixed by **typename** does not denote a type or a class template, the specialization is ill-formed. The usual qualified name lookup (6.4.3) is used to find the *qualified-id* even in the presence of **typename**. [Example:

```
struct A {
 struct X { };
 int X;
};
struct B {
 struct X { };
```

```

};
template<class T> void f(T t) {
 typename T::X x;
}
void foo() {
 A a;
 B b;
 f(b); // OK: T::X refers to B::X
 f(a); // error: T::X refers to the data member A::X not the struct A::X
}

```

— end example]

- <sup>5</sup> A qualified name used as the name in a *class-or-decltype* (Clause 13) or an *elaborated-type-specifier* is implicitly assumed to name a type, without the use of the **typename** keyword. In a *nested-name-specifier* that immediately contains a *nested-name-specifier* that depends on a template parameter, the *identifier* or *simple-template-id* is implicitly assumed to name a type, without the use of the **typename** keyword. [ *Note*: The **typename** keyword is not permitted by the syntax of these constructs. — end note]
- <sup>6</sup> If, for a given set of template arguments, a specialization of a template is instantiated that refers to a *qualified-id* that denotes a type or a class template, and the *qualified-id* refers to a member of an unknown specialization, the *qualified-id* shall either be prefixed by **typename** or shall be used in a context in which it implicitly names a type as described above. [ *Example*:

```

template <class T> void f(int i) {
 T::x * i; // T::x must not be a type
}

struct Foo {
 typedef int x;
};

struct Bar {
 static int const x = 5;
};

int main() {
 f<Bar>(1); // OK
 f<Foo>(1); // error: Foo::x is a type
}

```

— end example]

- <sup>7</sup> Within the definition of a class template or within the definition of a member of a class template following the *declarator-id*, the keyword **typename** is not required when referring to the name of a previously declared member of the class template that declares a type or a class template. [ *Note*: Such names can be found using unqualified name lookup (6.4.1), class member lookup (6.4.3.1) into the current instantiation (17.6.2.1), or class member access expression lookup (6.4.5) when the type of the object expression is the current instantiation (17.6.2.2). — end note] [ *Example*:

```

template<class T> struct A {
 typedef int B;
 B b; // OK, no typename required
};

```

— end example]

- <sup>8</sup> Knowing which names are type names allows the syntax of every template to be checked. The program is ill-formed, no diagnostic required, if:

- (8.1) — no valid specialization can be generated for a template or a substatement of a constexpr if statement (9.4.1) within a template and the template is not instantiated, or
  - (8.2) — every valid specialization of a variadic template requires an empty template parameter pack, or
  - (8.3) — a hypothetical instantiation of a template immediately following its definition would be ill-formed due to a construct that does not depend on a template parameter, or
  - (8.4) — the interpretation of such a construct in the hypothetical instantiation is different from the interpretation of the corresponding construct in any actual instantiation of the template. [ *Note*: This can happen in situations including the following:
    - (8.4.1) — a type used in a non-dependent name is incomplete at the point at which a template is defined but is complete at the point at which an instantiation is performed, or
    - (8.4.2) — lookup for a name in the template definition found a *using-declaration*, but the lookup in the corresponding scope in the instantiation does not find any declarations because the *using-declaration* was a pack expansion and the corresponding pack is empty, or
    - (8.4.3) — an instantiation uses a default argument or default template argument that had not been defined at the point at which the template was defined, or
    - (8.4.4) — constant expression evaluation (8.20) within the template instantiation uses
      - (8.4.4.1) — the value of a **const** object of integral or unscoped enumeration type or
      - (8.4.4.2) — the value of a **constexpr** object or
      - (8.4.4.3) — the value of a reference or
      - (8.4.4.4) — the definition of a constexpr function,
 and that entity was not defined when the template was defined, or
    - (8.4.5) — a class template specialization or variable template specialization that is specified by a non-dependent *simple-template-id* is used by the template, and either it is instantiated from a partial specialization that was not defined when the template was defined or it names an explicit specialization that was not declared when the template was defined.
- *end note*]

Otherwise, no diagnostic shall be issued for a template for which a valid specialization can be generated. [ *Note*: If a template is instantiated, errors will be diagnosed according to the other rules in this International Standard. Exactly when these errors are diagnosed is a quality of implementation issue. — *end note* ]

[ *Example*:

```
int j;
template<class T> class X {
 void f(T t, int i, char* p) {
 t = i; // diagnosed if X::f is instantiated, and the assignment to t is an error
 p = i; // may be diagnosed even if X::f is not instantiated
 p = j; // may be diagnosed even if X::f is not instantiated
 }
 void g(T t) {
 +; // may be diagnosed even if X::g is not instantiated
 }
};

template<class... T> struct A {
 void operator++(int, T... t); // error: too many parameters
};
template<class... T> union X : T... { }; // error: union with base class
```



```
template<class... T> struct A : T..., T... { }; // error: duplicate base class
— end example]
```

- <sup>9</sup> When looking for the declaration of a name used in a template definition, the usual lookup rules (6.4.1, 6.4.2) are used for non-dependent names. The lookup of names dependent on the template parameters is postponed until the actual template argument is known (17.6.2). [ *Example:*

```
#include <iostream>
using namespace std;

template<class T> class Set {
 T* p;
 int cnt;
public:
 Set();
 Set<T>(const Set<T>&);
 void printall() {
 for (int i = 0; i<cnt; i++)
 cout << p[i] << '\n';
 }
};
```

in the example, *i* is the local variable *i* declared in `printall`, *cnt* is the member *cnt* declared in `Set`, and `cout` is the standard output stream declared in `iostream`. However, not every declaration can be found this way; the resolution of some names must be postponed until the actual *template-arguments* are known. For example, even though the name `operator<<` is known within the definition of `printall()` and a declaration of it can be found in `<iostream>`, the actual declaration of `operator<<` needed to print `p[i]` cannot be known until it is known what type *T* is (17.6.2). — *end example*]

- <sup>10</sup> If a name does not depend on a *template-parameter* (as defined in 17.6.2), a declaration (or set of declarations) for that name shall be in scope at the point where the name appears in the template definition; the name is bound to the declaration (or declarations) found at that point and this binding is not affected by declarations that are visible at the point of instantiation. [ *Example:*

```
void f(char);

template<class T> void g(T t) {
 f(1); // f(char)
 f(T(1)); // dependent
 f(t); // dependent
 dd++; // not dependent; error: declaration for dd not found
}

enum E { e };
void f(E);

double dd;
void h() {
 g(e); // will cause one call of f(char) followed by two calls of f(E)
 g('a'); // will cause three calls of f(char)
}
```

— *end example*]

- <sup>11</sup> [ *Note:* For purposes of name lookup, default arguments and *noexcept-specifiers* of function templates and default arguments and *noexcept-specifiers* of member functions of class templates are considered definitions (17.5). — *end note*]

### 17.6.1 Locally declared names [temp.local]

- <sup>1</sup> Like normal (non-template) classes, class templates have an injected-class-name (Clause 12). The injected-class-name can be used as a *template-name* or a *type-name*. When it is used with a *template-argument-list*, as a *template-argument* for a template *template-parameter*, or as the final identifier in the *elaborated-type-specifier* of a friend class template declaration, it refers to the class template itself. Otherwise, it is equivalent to the *template-name* followed by the *template-parameters* of the class template enclosed in `<>`.
- <sup>2</sup> Within the scope of a class template specialization or partial specialization, when the injected-class-name is used as a *type-name*, it is equivalent to the *template-name* followed by the *template-arguments* of the class template specialization or partial specialization enclosed in `<>`. [Example:

```
template<template<class> class T> class A { };
template<class T> class Y;
template<> class Y<int> {
 Y* p; // meaning Y<int>
 Y<char>* q; // meaning Y<char>
 A<Y>* a; // meaning A<::Y>
 class B {
 template<class> friend class Y; // meaning ::Y
 };
};
```

— end example]

- <sup>3</sup> The injected-class-name of a class template or class template specialization can be used either as a *template-name* or a *type-name* wherever it is in scope. [Example:

```
template <class T> struct Base {
 Base* p;
};

template <class T> struct Derived: public Base<T> {
 typename Derived::Base* p; // meaning Derived::Base<T>
};

template<class T, template<class> class U = T::template Base> struct Third { };
Third<Base<int>> > t; // OK: default argument uses injected-class-name as a template
```

— end example]

- <sup>4</sup> A lookup that finds an injected-class-name (13.2) can result in an ambiguity in certain cases (for example, if it is found in more than one base class). If all of the injected-class-names that are found refer to specializations of the same class template, and if the name is used as a *template-name*, the reference refers to the class template itself and not a specialization thereof, and is not ambiguous. [Example:

```
template <class T> struct Base { };
template <class T> struct Derived: Base<int>, Base<char> {
 typename Derived::Base b; // error: ambiguous
 typename Derived::Base<double> d; // OK
};
```

— end example]

- <sup>5</sup> When the normal name of the template (i.e., the name from the enclosing scope, not the injected-class-name) is used, it always refers to the class template itself and not a specialization of the template. [Example:

```
template<class T> class X {
 X* p; // meaning X<T>
 X<T>* p2;
 X<int>* p3;
```

```

 ::X* p4; // error: missing template argument list
 // ::X does not refer to the injected-class-name
};

```

— end example]

- <sup>6</sup> A *template-parameter* shall not be redeclared within its scope (including nested scopes). A *template-parameter* shall not have the same name as the template name. [Example:

```

template<class T, int i> class Y {
 int T; // error: template-parameter redeclared
 void f() {
 char T; // error: template-parameter redeclared
 }
};

template<class X> class X; // error: template-parameter redeclared

```

— end example]

- <sup>7</sup> In the definition of a member of a class template that appears outside of the class template definition, the name of a member of the class template hides the name of a *template-parameter* of any enclosing class templates (but not a *template-parameter* of the member if the member is a class or function template). [Example:

```

template<class T> struct A {
 struct B { /* ... */ };
 typedef void C;
 void f();
 template<class U> void g(U);
};

template<class B> void A::f() {
 B b; // A's B, not the template parameter
}

template<class B> template<class C> void A::g(C) {
 B b; // A's B, not the template parameter
 C c; // the template parameter C, not A's C
}

```

— end example]

- <sup>8</sup> In the definition of a member of a class template that appears outside of the namespace containing the class template definition, the name of a *template-parameter* hides the name of a member of this namespace. [Example:

```

namespace N {
 class C { };
 template<class T> class B {
 void f(T);
 };
}

template<class C> void N::B<C>::f(C) {
 C b; // C is the template parameter, not N::C
}

```

— end example]

- <sup>9</sup> In the definition of a class template or in the definition of a member of such a template that appears outside

of the template definition, for each non-dependent base class (17.6.2.1), if the name of the base class or the name of a member of the base class is the same as the name of a *template-parameter*, the base class name or member name hides the *template-parameter* name (6.3.10). [ *Example*:

```
struct A {
 struct B { /* ... */ };
 int a;
 int Y;
};

template<class B, class a> struct X : A {
 B b; // A's B
 a b; // error: A's a isn't a type name
};
```

— *end example*]

## 17.6.2 Dependent names

[temp.dep]

- <sup>1</sup> Inside a template, some constructs have semantics which may differ from one instantiation to another. Such a construct *depends* on the template parameters. In particular, types and expressions may depend on the type and/or value of template parameters (as determined by the template arguments) and this determines the context for name lookup for certain names. An expressions may be *type-dependent* (that is, its type may depend on a template parameter) or *value-dependent* (that is, its value when evaluated as a constant expression (8.20) may depend on a template parameter) as described in this subclause. In an expression of the form:

*postfix-expression* ( *expression-list*<sub>opt</sub> )

where the *postfix-expression* is an *unqualified-id*, the *unqualified-id* denotes a *dependent name* if

- (1.1) — any of the expressions in the *expression-list* is a pack expansion (17.5.3),
- (1.2) — any of the expressions or *braced-init-lists* in the *expression-list* is type-dependent (17.6.2.2), or
- (1.3) — the *unqualified-id* is a *template-id* in which any of the template arguments depends on a template parameter.

If an operand of an operator is a type-dependent expression, the operator also denotes a dependent name. Such names are unbound and are looked up at the point of the template instantiation (17.6.4.1) in both the context of the template definition and the context of the point of instantiation.

- <sup>2</sup> [ *Example*:

```
template<class T> struct X : B<T> {
 typename T::A* pa;
 void f(B<T>* pb) {
 static int i = B<T>::i;
 pb->j++;
 }
};
```

the base class name B<T>, the type name T::A, the names B<T>::i and pb->j explicitly depend on the *template-parameter*. — *end example*]

- <sup>3</sup> In the definition of a class or class template, the scope of a dependent base class (17.6.2.1) is not examined during unqualified name lookup either at the point of definition of the class template or member or during an instantiation of the class template or member. [ *Example*:

```
typedef double A;
template<class T> class B {
 typedef int A;
```

```
};
template<class T> struct X : B<T> {
 A a; // a has type double
};
```

The type name A in the definition of X<T> binds to the typedef name defined in the global namespace scope, not to the typedef name defined in the base class B<T>. — *end example*] [Example:

```
struct A {
 struct B { /* ... */ };
 int a;
 int Y;
};

int a;

template<class T> struct Y : T {
 struct B { /* ... */ };
 B b; // The B defined in Y
 void f(int i) { a = i; } // ::a
 Y* p; // Y<T>
};

Y<A> ya;
```

The members A::B, A::a, and A::Y of the template argument A do not affect the binding of names in Y<A>. — *end example*]

### 17.6.2.1 Dependent types

[temp.dep.type]

- 1 A name refers to the *current instantiation* if it is
  - (1.1) — in the definition of a class template, a nested class of a class template, a member of a class template, or a member of a nested class of a class template, the injected-class-name (Clause 12) of the class template or nested class,
  - (1.2) — in the definition of a primary class template or a member of a primary class template, the name of the class template followed by the template argument list of the primary template (as described below) enclosed in <> (or an equivalent template alias specialization),
  - (1.3) — in the definition of a nested class of a class template, the name of the nested class referenced as a member of the current instantiation, or
  - (1.4) — in the definition of a partial specialization or a member of a partial specialization, the name of the class template followed by the template argument list of the partial specialization enclosed in <> (or an equivalent template alias specialization). If the *n*th template parameter is a parameter pack, the *n*th template argument is a pack expansion (17.5.3) whose pattern is the name of the parameter pack.
- 2 The template argument list of a primary template is a template argument list in which the *n*th template argument has the value of the *n*th template parameter of the class template. If the *n*th template parameter is a template parameter pack (17.5.3), the *n*th template argument is a pack expansion (17.5.3) whose pattern is the name of the template parameter pack.
- 3 A template argument that is equivalent to a template parameter (i.e., has the same constant value or the same type as the template parameter) can be used in place of that template parameter in a reference to the current instantiation. In the case of a non-type template argument, the argument must have been given the value of the template parameter and not an expression in which the template parameter appears as a subexpression. [Example:

```
template <class T> class A {
```

```

A* p1; // A is the current instantiation
A<T>* p2; // A<T> is the current instantiation
A<T*> p3; // A<T*> is not the current instantiation
::A<T>* p4; // ::A<T> is the current instantiation
class B {
 B* p1; // B is the current instantiation
 A<T>::B* p2; // A<T>::B is the current instantiation
 typename A<T*>::B* p3; // A<T*>::B is not the current instantiation
};

};

template <class T> class A<T*> {
 A<T*>* p1; // A<T*> is the current instantiation
 A<T>* p2; // A<T> is not the current instantiation
};

template <class T1, class T2, int I> struct B {
 B<T1, T2, I>* b1; // refers to the current instantiation
 B<T2, T1, I>* b2; // not the current instantiation
 typedef T1 my_T1;
 static const int my_I = I;
 static const int my_I2 = I+0;
 static const int my_I3 = my_I;
 B<my_T1, T2, my_I>* b3; // refers to the current instantiation
 B<my_T1, T2, my_I2>* b4; // not the current instantiation
 B<my_T1, T2, my_I3>* b5; // refers to the current instantiation
};

```

— end example]

- <sup>4</sup> A *dependent base class* is a base class that is a dependent type and is not the current instantiation. [Note: A base class can be the current instantiation in the case of a nested class naming an enclosing class as a base. [Example:

```

template<class T> struct A {
 typedef int M;
 struct B {
 typedef void M;
 struct C;
 };
};

template<class T> struct A<T>::B::C : A<T> {
 M m; // OK, A<T>::M
};

```

— end example] — end note]

- <sup>5</sup> A name is a *member of the current instantiation* if it is
- (5.1) — An unqualified name that, when looked up, refers to at least one member of a class that is the current instantiation or a non-dependent base class thereof. [Note: This can only occur when looking up a name in a scope enclosed by the definition of a class template. — end note]
  - (5.2) — A *qualified-id* in which the *nested-name-specifier* refers to the current instantiation and that, when looked up, refers to at least one member of a class that is the current instantiation or a non-dependent base class thereof. [Note: If no such member is found, and the current instantiation has any dependent base classes, then the *qualified-id* is a member of an unknown specialization; see below. — end note]

- (5.3) — An *id-expression* denoting the member in a class member access expression (8.2.5) for which the type of the object expression is the current instantiation, and the *id-expression*, when looked up (6.4.5), refers to at least one member of a class that is the current instantiation or a non-dependent base class thereof. [ *Note*: If no such member is found, and the current instantiation has any dependent base classes, then the *id-expression* is a member of an unknown specialization; see below. — *end note* ]

[ *Example*:

```
template <class T> class A {
 static const int i = 5;
 int n1[i]; // i refers to a member of the current instantiation
 int n2[A::i]; // A::i refers to a member of the current instantiation
 int n3[A<T>::i]; // A<T>::i refers to a member of the current instantiation
 int f();
};

template <class T> int A<T>::f() {
 return i; // i refers to a member of the current instantiation
}
```

— *end example*]

A name is a *dependent member of the current instantiation* if it is a member of the current instantiation that, when looked up, refers to at least one member of a class that is the current instantiation.

- 6 A name is a *member of an unknown specialization* if it is
- (6.1) — A *qualified-id* in which the *nested-name-specifier* names a dependent type that is not the current instantiation.
- (6.2) — A *qualified-id* in which the *nested-name-specifier* refers to the current instantiation, the current instantiation has at least one dependent base class, and name lookup of the *qualified-id* does not find any member of a class that is the current instantiation or a non-dependent base class thereof.
- (6.3) — An *id-expression* denoting the member in a class member access expression (8.2.5) in which either
- (6.3.1) — the type of the object expression is the current instantiation, the current instantiation has at least one dependent base class, and name lookup of the *id-expression* does not find a member of a class that is the current instantiation or a non-dependent base class thereof; or
- (6.3.2) — the type of the object expression is dependent and is not the current instantiation.
- 7 If a *qualified-id* in which the *nested-name-specifier* refers to the current instantiation is not a member of the current instantiation or a member of an unknown specialization, the program is ill-formed even if the template containing the *qualified-id* is not instantiated; no diagnostic required. Similarly, if the *id-expression* in a class member access expression for which the type of the object expression is the current instantiation does not refer to a member of the current instantiation or a member of an unknown specialization, the program is ill-formed even if the template containing the member access expression is not instantiated; no diagnostic required. [ *Example*:

```
template<class T> class A {
 typedef int type;
 void f() {
 A<T>::type i; // OK: refers to a member of the current instantiation
 typename A<T>::other j; // error: neither a member of the current instantiation nor
 // a member of an unknown specialization
 }
};
```

— *end example*]

- <sup>8</sup> If, for a given set of template arguments, a specialization of a template is instantiated that refers to a member of the current instantiation with a *qualified-id* or class member access expression, the name in the *qualified-id* or class member access expression is looked up in the template instantiation context. If the result of this lookup differs from the result of name lookup in the template definition context, name lookup is ambiguous.

[*Example:*

```

 struct A {
 int m;
 };

 struct B {
 int m;
 };

 template<typename T>
 struct C : A, T {
 int f() { return this->m; } // finds A::m in the template definition context
 int g() { return m; } // finds A::m in the template definition context
 };

 template int C::f(); // error: finds both A::m and B::m
 template int C::g(); // OK: transformation to class member access syntax
 // does not occur in the template definition context; see 12.2.2

```

— *end example*]

- <sup>9</sup> A type is dependent if it is
- (9.1) — a template parameter,
  - (9.2) — a member of an unknown specialization,
  - (9.3) — a nested class or enumeration that is a dependent member of the current instantiation,
  - (9.4) — a cv-qualified type where the cv-unqualified type is dependent,
  - (9.5) — a compound type constructed from any dependent type,
  - (9.6) — an array type whose element type is dependent or whose bound (if any) is value-dependent,
  - (9.7) — a function type whose exception specification is value-dependent,
  - (9.8) — a *simple-template-id* in which either the template name is a template parameter or any of the template arguments is a dependent type or an expression that is type-dependent or value-dependent or is a pack expansion [ *Note:* This includes an injected-class-name (Clause 12) of a class template used without a *template-argument-list*. — *end note* ], or
  - (9.9) — denoted by `decltype(expression)`, where *expression* is type-dependent (17.6.2.2).
- <sup>10</sup> [ *Note:* Because typedefs do not introduce new types, but instead simply refer to other types, a name that refers to a typedef that is a member of the current instantiation is dependent only if the type referred to is dependent. — *end note* ]

### 17.6.2.2 Type-dependent expressions

[temp.dep.expr]

- <sup>1</sup> Except as described below, an expression is type-dependent if any subexpression is type-dependent.
- <sup>2</sup> `this` is type-dependent if the class type of the enclosing member function is dependent (17.6.2.1).
- <sup>3</sup> An *id-expression* is type-dependent if it contains
  - (3.1) — an *identifier* associated by name lookup with one or more declarations declared with a dependent type,
  - (3.2) — an *identifier* associated by name lookup with a non-type *template-parameter* declared with a type that



contains a placeholder type (10.1.7.4),

- (3.3) — an *identifier* associated by name lookup with one or more declarations of member functions of the current instantiation declared with a return type that contains a placeholder type,
- (3.4) — an *identifier* associated by name lookup with a structured binding declaration (11.5) whose *brace-or-equal-initializer* is type-dependent,
- (3.5) — the *identifier* `__func__` (11.4.1), where any enclosing function is a template, a member of a class template, or a generic lambda,
- (3.6) — a *template-id* that is dependent,
- (3.7) — a *conversion-function-id* that specifies a dependent type, or
- (3.8) — a *nested-name-specifier* or a *qualified-id* that names a member of an unknown specialization;

or if it names a dependent member of the current instantiation that is a static data member of type “array of unknown bound of T” for some T (17.5.1.3). Expressions of the following forms are type-dependent only if the type specified by the *type-id*, *simple-type-specifier* or *new-type-id* is dependent, even if any subexpression is type-dependent:

```

simple-type-specifier (expression-listopt)
::opt new new-placementopt new-type-id new-initializeropt
::opt new new-placementopt (type-id) new-initializeropt
dynamic_cast < type-id > (expression)
static_cast < type-id > (expression)
const_cast < type-id > (expression)
reinterpret_cast < type-id > (expression)
(type-id) cast-expression

```

- <sup>4</sup> Expressions of the following forms are never type-dependent (because the type of the expression cannot be dependent):

```

literal
postfix-expression . pseudo-destructor-name
postfix-expression -> pseudo-destructor-name
sizeof unary-expression
sizeof (type-id)
sizeof ... (identifier)
alignof (type-id)
typeid (expression)
typeid (type-id)
::opt delete cast-expression
::opt delete [] cast-expression
throw assignment-expressionopt
noexcept (expression)

```

[ *Note*: For the standard library macro `offsetof`, see 21.2. — *end note* ]

- <sup>5</sup> A class member access expression (8.2.5) is type-dependent if the expression refers to a member of the current instantiation and the type of the referenced member is dependent, or the class member access expression refers to a member of an unknown specialization. [ *Note*: In an expression of the form `x.y` or `xp->y` the type of the expression is usually the type of the member `y` of the class of `x` (or the class pointed to by `xp`). However, if `x` or `xp` refers to a dependent type that is not the current instantiation, the type of `y` is always dependent. If `x` or `xp` refers to a non-dependent type or refers to the current instantiation, the type of `y` is the type of the class member access expression. — *end note* ]
- <sup>6</sup> A *braced-init-list* is type-dependent if any element is type-dependent or is a pack expansion.
- <sup>7</sup> A *fold-expression* is type-dependent.

**17.6.2.3 Value-dependent expressions****[temp.dep.constexpr]**

- <sup>1</sup> Except as described below, an expression used in a context where a constant expression is required is value-dependent if any subexpression is value-dependent.
- <sup>2</sup> An *id-expression* is value-dependent if:
  - (2.1) — it is type-dependent,
  - (2.2) — it is the name of a non-type template parameter,
  - (2.3) — it names a static data member that is a dependent member of the current instantiation and is not initialized in a *member-declarator*,
  - (2.4) — it names a static member function that is a dependent member of the current instantiation, or
  - (2.5) — it is a constant with literal type and is initialized with an expression that is value-dependent.

Expressions of the following form are value-dependent if the *unary-expression* or *expression* is type-dependent or the *type-id* is dependent:

```
sizeof unary-expression
sizeof (type-id)
typeid (expression)
typeid (type-id)
alignof (type-id)
noexcept (expression)
```

[*Note:* For the standard library macro `offsetof`, see 21.2. — *end note*]

- <sup>3</sup> Expressions of the following form are value-dependent if either the *type-id* or *simple-type-specifier* is dependent or the *expression* or *cast-expression* is value-dependent:

```
simple-type-specifier (expression-listopt)
static_cast < type-id > (expression)
const_cast < type-id > (expression)
reinterpret_cast < type-id > (expression)
(type-id) cast-expression
```

- <sup>4</sup> Expressions of the following form are value-dependent:

```
sizeof ... (identifier)
fold-expression
```

- <sup>5</sup> An expression of the form *&qualified-id* where the *qualified-id* names a dependent member of the current instantiation is value-dependent. An expression of the form *&cast-expression* is also value-dependent if evaluating *cast-expression* as a core constant expression (8.20) succeeds and the result of the evaluation refers to a templated entity that is an object with static or thread storage duration or a member function.

**17.6.2.4 Dependent template arguments****[temp.dep.temp]**

- <sup>1</sup> A type *template-argument* is dependent if the type it specifies is dependent.
- <sup>2</sup> A non-type *template-argument* is dependent if its type is dependent or the constant expression it specifies is value-dependent.
- <sup>3</sup> Furthermore, a non-type *template-argument* is dependent if the corresponding non-type *template-parameter* is of reference or pointer type and the *template-argument* designates or points to a member of the current instantiation or a member of a dependent type.
- <sup>4</sup> A template *template-argument* is dependent if it names a *template-parameter* or is a *qualified-id* that refers to a member of an unknown specialization.

### 17.6.3 Non-dependent names [temp.nondep]

- <sup>1</sup> Non-dependent names used in a template definition are found using the usual name lookup and bound at the point they are used. [ *Example*:

```
void g(double);
void h();

template<class T> class Z {
public:
 void f() {
 g(1); // calls g(double)
 h++; // ill-formed: cannot increment function; this could be diagnosed
 // either here or at the point of instantiation
 }
};

void g(int); // not in scope at the point of the template definition, not considered for the call g(1)
— end example]
```

### 17.6.4 Dependent name resolution [temp.dep.res]

- <sup>1</sup> In resolving dependent names, names from the following sources are considered:
- (1.1) — Declarations that are visible at the point of definition of the template.
  - (1.2) — Declarations from namespaces associated with the types of the function arguments both from the instantiation context (17.6.4.1) and from the definition context.

#### 17.6.4.1 Point of instantiation [temp.point]

- <sup>1</sup> For a function template specialization, a member function template specialization, or a specialization for a member function or static data member of a class template, if the specialization is implicitly instantiated because it is referenced from within another template specialization and the context from which it is referenced depends on a template parameter, the point of instantiation of the specialization is the point of instantiation of the enclosing specialization. Otherwise, the point of instantiation for such a specialization immediately follows the namespace scope declaration or definition that refers to the specialization.
- <sup>2</sup> If a function template or member function of a class template is called in a way which uses the definition of a default argument of that function template or member function, the point of instantiation of the default argument is the point of instantiation of the function template or member function specialization.
- <sup>3</sup> For a *noexcept-specifier* of a function template specialization or specialization of a member function of a class template, if the *noexcept-specifier* is implicitly instantiated because it is needed by another template specialization and the context that requires it depends on a template parameter, the point of instantiation of the *noexcept-specifier* is the point of instantiation of the specialization that requires it. Otherwise, the point of instantiation for such a *noexcept-specifier* immediately follows the namespace scope declaration or definition that requires the *noexcept-specifier*.
- <sup>4</sup> For a class template specialization, a class member template specialization, or a specialization for a class member of a class template, if the specialization is implicitly instantiated because it is referenced from within another template specialization, if the context from which the specialization is referenced depends on a template parameter, and if the specialization is not instantiated previous to the instantiation of the enclosing template, the point of instantiation is immediately before the point of instantiation of the enclosing template. Otherwise, the point of instantiation for such a specialization immediately precedes the namespace scope declaration or definition that refers to the specialization.
- <sup>5</sup> If a virtual function is implicitly instantiated, its point of instantiation is immediately following the point of

instantiation of its enclosing class template specialization.

- 6 An explicit instantiation definition is an instantiation point for the specialization or specializations specified by the explicit instantiation.
- 7 The instantiation context of an expression that depends on the template arguments is the set of declarations with external linkage declared prior to the point of instantiation of the template specialization in the same translation unit.
- 8 A specialization for a function template, a member function template, or of a member function or static data member of a class template may have multiple points of instantiations within a translation unit, and in addition to the points of instantiation described above, for any such specialization that has a point of instantiation within the translation unit, the end of the translation unit is also considered a point of instantiation. A specialization for a class template has at most one point of instantiation within a translation unit. A specialization for any template may have points of instantiation in multiple translation units. If two different points of instantiation give a template specialization different meanings according to the one-definition rule (6.2), the program is ill-formed, no diagnostic required.

#### 17.6.4.2 Candidate functions

[temp.dep.candidate]

- 1 For a function call where the *postfix-expression* is a dependent name, the candidate functions are found using the usual lookup rules (6.4.1, 6.4.2) except that:
  - (1.1) — For the part of the lookup using unqualified name lookup (6.4.1), only function declarations from the template definition context are found.
  - (1.2) — For the part of the lookup using associated namespaces (6.4.2), only function declarations found in either the template definition context or the template instantiation context are found.

If the call would be ill-formed or would find a better match had the lookup within the associated namespaces considered all the function declarations with external linkage introduced in those namespaces in all translation units, not just considering those declarations found in the template definition and template instantiation contexts, then the program has undefined behavior.

#### 17.6.5 Friend names declared within a class template

[temp.inject]

- 1 Friend classes or functions can be declared within a class template. When a template is instantiated, the names of its friends are treated as if the specialization had been explicitly declared at its point of instantiation.
- 2 As with non-template classes, the names of namespace-scope friend functions of a class template specialization are not visible during an ordinary lookup unless explicitly declared at namespace scope (14.3). Such names may be found under the rules for associated classes (6.4.2).<sup>140</sup> [Example:

```
template<typename T> struct number {
 number(int);
 friend number gcd(number x, number y) { return 0; };
};

void g() {
 number<double> a(3), b(4);
 a = gcd(a,b); // finds gcd because number<double> is an associated class,
 // making gcd visible in its namespace (global scope)
 b = gcd(3,4); // ill-formed; gcd is not visible
}
```

— end example]

<sup>140</sup>) Friend declarations do not introduce new names into any scope, either when the template is declared or when it is instantiated.

## 17.7 Template instantiation and specialization

[temp.spec]

- <sup>1</sup> The act of instantiating a function, a class, a member of a class template or a member template is referred to as *template instantiation*.
- <sup>2</sup> A function instantiated from a function template is called an instantiated function. A class instantiated from a class template is called an instantiated class. A member function, a member class, a member enumeration, or a static data member of a class template instantiated from the member definition of the class template is called, respectively, an instantiated member function, member class, member enumeration, or static data member. A member function instantiated from a member function template is called an instantiated member function. A member class instantiated from a member class template is called an instantiated member class.
- <sup>3</sup> An explicit specialization may be declared for a function template, a class template, a member of a class template or a member template. An explicit specialization declaration is introduced by `template<>`. In an explicit specialization declaration for a class template, a member of a class template or a class member template, the name of the class that is explicitly specialized shall be a *simple-template-id*. In the explicit specialization declaration for a function template or a member function template, the name of the function or member function explicitly specialized may be a *template-id*. [Example:

```

template<class T = int> struct A {
 static int x;
};
template<class U> void g(U) { }

template<> struct A<double> { }; // specialize for T == double
template<> struct A<> { }; // specialize for T == int
template<> void g(char) { } // specialize for U == char
 // U is deduced from the parameter type

template<> void g<int>(int) { } // specialize for U == int
template<> int A<char>::x = 0; // specialize for T == char

template<class T = int> struct B {
 static int x;
};
template<> int B<>::x = 1; // specialize for T == int
— end example]
```

- <sup>4</sup> An instantiated template specialization can be either implicitly instantiated (17.7.1) for a given argument list or be explicitly instantiated (17.7.2). A specialization is a class, function, or class member that is either instantiated or explicitly specialized (17.7.3).
- <sup>5</sup> For a given template and a given set of *template-arguments*,
  - (5.1) — an explicit instantiation definition shall appear at most once in a program,
  - (5.2) — an explicit specialization shall be defined at most once in a program (according to 6.2), and
  - (5.3) — both an explicit instantiation and a declaration of an explicit specialization shall not appear in a program unless the explicit instantiation follows a declaration of the explicit specialization.

An implementation is not required to diagnose a violation of this rule.

- <sup>6</sup> Each class template specialization instantiated from a template has its own copy of any static members. [Example:

```

template<class T> class X {
 static T s;
};
template<class T> T X<T>::s = 0;
X<int> aa;
```

```
X<char*> bb;
```

X<int> has a static member `s` of type `int` and X<char\*> has a static member `s` of type `char*`. — *end example*]

- <sup>7</sup> If a function declaration acquired its function type through a dependent type (17.6.2.1) without using the syntactic form of a function declarator, the program is ill-formed. [ *Example:*

```
template<class T> struct A {
 static T t;
};
typedef int function();
A<function> a; // ill-formed: would declare A<function>::t as a static member function
```

— *end example*]

### 17.7.1 Implicit instantiation

[temp.inst]

- <sup>1</sup> Unless a class template specialization has been explicitly instantiated (17.7.2) or explicitly specialized (17.7.3), the class template specialization is implicitly instantiated when the specialization is referenced in a context that requires a completely-defined object type or when the completeness of the class type affects the semantics of the program. [ *Note:* In particular, if the semantics of an expression depend on the member or base class lists of a class template specialization, the class template specialization is implicitly generated. For instance, deleting a pointer to class type depends on whether or not the class declares a destructor, and a conversion between pointers to class type depends on the inheritance relationship between the two classes involved. — *end note* ] [ *Example:*

```
template<class T> class B { /* ... */ };
template<class T> class D : public B<T> { /* ... */ };

void f(void*);
void f(B<int>*);

void g(D<int>* p, D<char>* pp, D<double>* ppp) {
 f(p); // instantiation of D<int> required: call f(B<int>*)
 B<char>* q = pp; // instantiation of D<char> required: convert D<char>* to B<char>*
 delete ppp; // instantiation of D<double> required
}
```

— *end example* ] If a class template has been declared, but not defined, at the point of instantiation (17.6.4.1), the instantiation yields an incomplete class type (6.9). [ *Example:*

```
template<class T> class X;
X<char> ch; // error: incomplete type X<char>
```

— *end example* ] [ *Note:* Within a template declaration, a local class (12.4) or enumeration and the members of a local class are never considered to be entities that can be separately instantiated (this includes their default arguments, *noexcept-specifiers*, and non-static data member initializers, if any). As a result, the dependent names are looked up, the semantic constraints are checked, and any templates used are instantiated as part of the instantiation of the entity within which the local class or enumeration is declared. — *end note* ]

- <sup>2</sup> The implicit instantiation of a class template specialization causes the implicit instantiation of the declarations, but not of the definitions, default arguments, or *noexcept-specifiers* of the class member functions, member classes, scoped member enumerations, static data members, member templates, and friends; and it causes the implicit instantiation of the definitions of unscoped member enumerations and member anonymous unions. However, for the purpose of determining whether an instantiated redeclaration is valid according to 6.2 and 12.2, a declaration that corresponds to a definition in the template is considered to be a definition. [ *Example:*

```

template<class T, class U>
struct Outer {
 template<class X, class Y> struct Inner;
 template<class Y> struct Inner<T, Y>; // #1a
 template<class Y> struct Inner<T, Y> { }; // #1b; OK: valid redeclaration of #1a
 template<class Y> struct Inner<U, Y> { }; // #2
};

```

```

Outer<int, int> outer; // error at #2

```

Outer<int, int>::Inner<int, Y> is redeclared at #1b. (It is not defined but noted as being associated with a definition in Outer<T, U>.) #2 is also a redeclaration of #1a. It is noted as associated with a definition, so it is an invalid redeclaration of the same partial specialization.

```

template<typename T> struct Friendly {
 template<typename U> friend int f(U) { return sizeof(T); }
};
Friendly<char> fc;
Friendly<float> ff; // ill-formed: produces second definition of f(U)

```

— end example]

- <sup>3</sup> Unless a member of a class template or a member template has been explicitly instantiated or explicitly specialized, the specialization of the member is implicitly instantiated when the specialization is referenced in a context that requires the member definition to exist; in particular, the initialization (and any associated side effects) of a static data member does not occur unless the static data member is itself used in a way that requires the definition of the static data member to exist.
- <sup>4</sup> Unless a function template specialization has been explicitly instantiated or explicitly specialized, the function template specialization is implicitly instantiated when the specialization is referenced in a context that requires a function definition to exist. A function whose declaration was instantiated from a friend function definition is implicitly instantiated when it is referenced in a context that requires a function definition to exist. Unless a call is to a function template explicit specialization or to a member function of an explicitly specialized class template, a default argument for a function template or a member function of a class template is implicitly instantiated when the function is called in a context that requires the value of the default argument.

- <sup>5</sup> [Example:

```

template<class T> struct Z {
 void f();
 void g();
};

void h() {
 Z<int> a; // instantiation of class Z<int> required
 Z<char>* p; // instantiation of class Z<char> not required
 Z<double>* q; // instantiation of class Z<double> not required

 a.f(); // instantiation of Z<int>::f() required
 p->g(); // instantiation of class Z<char> required, and
 // instantiation of Z<char>::g() required
}

```

Nothing in this example requires class Z<double>, Z<int>::g(), or Z<char>::f() to be implicitly instantiated. — end example]

- <sup>6</sup> Unless a variable template specialization has been explicitly instantiated or explicitly specialized, the variable template specialization is implicitly instantiated when the specialization is used. A default template argument

for a variable template is implicitly instantiated when the variable template is referenced in a context that requires the value of the default argument.

- 7 If the function selected by overload resolution (16.3) can be determined without instantiating a class template definition, it is unspecified whether that instantiation actually takes place. [*Example:*

```
template <class T> struct S {
 operator int();
};

void f(int);
void f(S<int>&);
void f(S<float>);

void g(S<int>& sr) {
 f(sr); // instantiation of S<int> allowed but not required
 // instantiation of S<float> allowed but not required
};
```

— *end example*]

- 8 If a function template or a member function template specialization is used in a way that involves overload resolution, a declaration of the specialization is implicitly instantiated (17.8.3).
- 9 An implementation shall not implicitly instantiate a function template, a variable template, a member template, a non-virtual member function, a member class, a static data member of a class template, or a substatement of a constexpr if statement (9.4.1), unless such instantiation is required. It is unspecified whether or not an implementation implicitly instantiates a virtual member function of a class template if the virtual member function would not otherwise be instantiated. The use of a template specialization in a default argument shall not cause the template to be implicitly instantiated except that a class template may be instantiated where its complete type is needed to determine the correctness of the default argument. The use of a default argument in a function call causes specializations in the default argument to be implicitly instantiated.
- 10 Implicitly instantiated class, function, and variable template specializations are placed in the namespace where the template is defined. Implicitly instantiated specializations for members of a class template are placed in the namespace where the enclosing class template is defined. Implicitly instantiated member templates are placed in the namespace where the enclosing class or class template is defined. [*Example:*

```
namespace N {
 template<class T> class List {
 public:
 T* get();
 };
}

template<class K, class V> class Map {
public:
 N::List<V> lt;
 V get(K);
};

void g(Map<const char*,int>& m) {
 int i = m.get("Nicholas");
}
```

a call of `lt.get()` from `Map<const char*,int>::get()` would place `List<int>::get()` in the namespace `N` rather than in the global namespace. — *end example*]



- <sup>11</sup> If a function template `f` is called in a way that requires a default argument to be used, the dependent names are looked up, the semantics constraints are checked, and the instantiation of any template used in the default argument is done as if the default argument had been an initializer used in a function template specialization with the same scope, the same template parameters and the same access as that of the function template `f` used at that point, except that the scope in which a closure type is declared (8.1.5.1) – and therefore its associated namespaces – remain as determined from the context of the definition for the default argument. This analysis is called *default argument instantiation*. The instantiated default argument is then used as the argument of `f`.

- <sup>12</sup> Each default argument is instantiated independently. [ *Example:*

```
template<class T> void f(T x, T y = ydef(T()), T z = zdef(T()));

class A { };

A zdef(A);

void g(A a, A b, A c) {
 f(a, b, c); // no default argument instantiation
 f(a, b); // default argument z = zdef(T()) instantiated
 f(a); // ill-formed; ydef is not declared
}
```

— *end example*]

- <sup>13</sup> The *noexcept-specifier* of a function template specialization is not instantiated along with the function declaration; it is instantiated when needed (18.4). If such an *noexcept-specifier* is needed but has not yet been instantiated, the dependent names are looked up, the semantics constraints are checked, and the instantiation of any template used in the *noexcept-specifier* is done as if it were being done as part of instantiating the declaration of the specialization at that point.
- <sup>14</sup> [ *Note:* 17.6.4.1 defines the point of instantiation of a template specialization. — *end note* ]
- <sup>15</sup> There is an implementation-defined quantity that specifies the limit on the total depth of recursive instantiations (B), which could involve more than one template. The result of an infinite recursion in instantiation is undefined. [ *Example:*

```
template<class T> class X {
 X<T*>* p; // OK
 X<T*> a; // implicit generation of X<T*> requires
 // the implicit instantiation of X<T*> which requires
 // the implicit instantiation of X<T**> which ...
};
```

— *end example*]

## 17.7.2 Explicit instantiation

[temp.explicit]

- <sup>1</sup> A class, function, variable, or member template specialization can be explicitly instantiated from its template. A member function, member class or static data member of a class template can be explicitly instantiated from the member definition associated with its class template. An explicit instantiation of a function template or member function of a class template shall not use the `inline` or `constexpr` specifiers.
- <sup>2</sup> The syntax for explicit instantiation is:

*explicit-instantiation:*  
**extern<sub>opt</sub> template** *declaration*

There are two forms of explicit instantiation: an explicit instantiation definition and an explicit instantiation declaration. An explicit instantiation declaration begins with the `extern` keyword.

- <sup>3</sup> If the explicit instantiation is for a class or member class, the *elaborated-type-specifier* in the *declaration* shall include a *simple-template-id*. If the explicit instantiation is for a function or member function, the *unqualified-id* in the *declaration* shall be either a *template-id* or, where all template arguments can be deduced, a *template-name* or *operator-function-id*. [Note: The declaration may declare a *qualified-id*, in which case the *unqualified-id* of the *qualified-id* must be a *template-id*. — end note] If the explicit instantiation is for a member function, a member class or a static data member of a class template specialization, the name of the class template specialization in the *qualified-id* for the member name shall be a *simple-template-id*. If the explicit instantiation is for a variable, the *unqualified-id* in the declaration shall be a *template-id*. An explicit instantiation shall appear in an enclosing namespace of its template. If the name declared in the explicit instantiation is an unqualified name, the explicit instantiation shall appear in the namespace where its template is declared or, if that namespace is inline (10.3.1), any namespace from its enclosing namespace set. [Note: Regarding qualified names in declarators, see 11.3. — end note] [Example:

```
template<class T> class Array { void mf(); };
template class Array<char>;
template void Array<int>::mf();

template<class T> void sort(Array<T>& v) { /* ... */ }
template void sort(Array<char>&); // argument is deduced here

namespace N {
 template<class T> void f(T&) { }
}
template void N::f<int>(int&);
```

— end example]

- <sup>4</sup> A declaration of a function template, a variable template, a member function or static data member of a class template, or a member function template of a class or class template shall precede an explicit instantiation of that entity. A definition of a class template, a member class of a class template, or a member class template of a class or class template shall precede an explicit instantiation of that entity unless the explicit instantiation is preceded by an explicit specialization of the entity with the same template arguments. If the *declaration* of the explicit instantiation names an implicitly-declared special member function (Clause 15), the program is ill-formed.
- <sup>5</sup> For a given set of template arguments, if an explicit instantiation of a template appears after a declaration of an explicit specialization for that template, the explicit instantiation has no effect. Otherwise, for an explicit instantiation definition the definition of a function template, a variable template, a member function template, or a member function or static data member of a class template shall be present in every translation unit in which it is explicitly instantiated.
- <sup>6</sup> An explicit instantiation of a class, function template, or variable template specialization is placed in the namespace in which the template is defined. An explicit instantiation for a member of a class template is placed in the namespace where the enclosing class template is defined. An explicit instantiation for a member template is placed in the namespace where the enclosing class or class template is defined. [Example:

```
namespace N {
 template<class T> class Y { void mf() { } };
}

template class Y<int>; // error: class template Y not visible in the global namespace

using N::Y;
template class Y<int>; // error: explicit instantiation outside of the namespace of the template

template class N::Y<char*>; // OK: explicit instantiation in namespace N
```

```
template void N::Y<double>::mf(); // OK: explicit instantiation in namespace N
```

— end example]

- 7 A trailing *template-argument* can be left unspecified in an explicit instantiation of a function template specialization or of a member function template specialization provided it can be deduced from the type of a function parameter (17.8.2). [ *Example:*

```
template<class T> class Array { /* ... */ };
template<class T> void sort(Array<T>& v) { /* ... */ }
```

```
// instantiate sort(Array<int>&) – template-argument deduced
template void sort<>(Array<int>&);
```

— end example]

- 8 An explicit instantiation that names a class template specialization is also an explicit instantiation of the same kind (declaration or definition) of each of its members (not including members inherited from base classes and members that are templates) that has not been previously explicitly specialized in the translation unit containing the explicit instantiation, except as described below. [ *Note:* In addition, it will typically be an explicit instantiation of certain implementation-dependent data about the class. — end note]
- 9 An explicit instantiation definition that names a class template specialization explicitly instantiates the class template specialization and is an explicit instantiation definition of only those members that have been defined at the point of instantiation.
- 10 Except for inline functions and variables, declarations with types deduced from their initializer or return value (10.1.7.4), `const` variables of literal types, variables of reference types, and class template specializations, explicit instantiation declarations have the effect of suppressing the implicit instantiation of the entity to which they refer. [ *Note:* The intent is that an inline function that is the subject of an explicit instantiation declaration will still be implicitly instantiated when odr-used (6.2) so that the body can be considered for inlining, but that no out-of-line copy of the inline function would be generated in the translation unit. — end note]
- 11 If an entity is the subject of both an explicit instantiation declaration and an explicit instantiation definition in the same translation unit, the definition shall follow the declaration. An entity that is the subject of an explicit instantiation declaration and that is also used in a way that would otherwise cause an implicit instantiation (17.7.1) in the translation unit shall be the subject of an explicit instantiation definition somewhere in the program; otherwise the program is ill-formed, no diagnostic required. [ *Note:* This rule does apply to inline functions even though an explicit instantiation declaration of such an entity has no other normative effect. This is needed to ensure that if the address of an inline function is taken in a translation unit in which the implementation chose to suppress the out-of-line body, another translation unit will supply the body. — end note] An explicit instantiation declaration shall not name a specialization of a template with internal linkage.
- 12 The usual access checking rules do not apply to names used to specify explicit instantiations. [ *Note:* In particular, the template arguments and names used in the function declarator (including parameter types, return types and exception specifications) may be private types or objects which would normally not be accessible and the template may be a member template or member function which would not normally be accessible. — end note]
- 13 An explicit instantiation does not constitute a use of a default argument, so default argument instantiation is not done. [ *Example:*
- ```
char* p = 0;
template<class T> T g(T x = &p) { return x; }
template int g<int>(int);           // OK even though &p isn't an int.
```
- end example]

17.7.3 Explicit specialization**[temp.expl.spec]**

¹ An explicit specialization of any of the following:

- (1.1) — function template
- (1.2) — class template
- (1.3) — variable template
- (1.4) — member function of a class template
- (1.5) — static data member of a class template
- (1.6) — member class of a class template
- (1.7) — member enumeration of a class template
- (1.8) — member class template of a class or class template
- (1.9) — member function template of a class or class template

can be declared by a declaration introduced by `template<>`; that is:

explicit-specialization:

`template < > declaration`

[*Example:*

```
template<class T> class stream;

template<> class stream<char> { /* ... */ };

template<class T> class Array { /* ... */ };
template<class T> void sort(Array<T>& v) { /* ... */ }

template<> void sort<char*>(Array<char*>&);
```

Given these declarations, `stream<char>` will be used as the definition of streams of `chars`; other streams will be handled by class template specializations instantiated from the class template. Similarly, `sort<char*>` will be used as the sort function for arguments of type `Array<char*>`; other `Array` types will be sorted by functions generated from the template. — *end example*]

² An explicit specialization may be declared in any scope in which the corresponding primary template may be defined (10.3.1.2, 12.2, 17.5.2).

³ A declaration of a function template, class template, or variable template being explicitly specialized shall precede the declaration of the explicit specialization. [*Note:* A declaration, but not a definition of the template is required. — *end note*] The definition of a class or class template shall precede the declaration of an explicit specialization for a member template of the class or class template. [*Example:*

```
template<> class X<int> { /* ... */ };           // error: X not a template

template<class T> class X;

template<> class X<char*> { /* ... */ };         // OK: X is a template
— end example]
```

⁴ A member function, a member function template, a member class, a member enumeration, a member class template, a static data member, or a static data member template of a class template may be explicitly specialized for a class specialization that is implicitly instantiated; in this case, the definition of the class template shall precede the explicit specialization for the member of the class template. If such an explicit specialization for the member of a class template names an implicitly-declared special member function (Clause 15), the program is ill-formed.

- ⁵ A member of an explicitly specialized class is not implicitly instantiated from the member declaration of the class template; instead, the member of the class template specialization shall itself be explicitly defined if its definition is required. In this case, the definition of the class template explicit specialization shall be in scope at the point at which the member is defined. The definition of an explicitly specialized class is unrelated to the definition of a generated specialization. That is, its members need not have the same names, types, etc. as the members of a generated specialization. Members of an explicitly specialized class template are defined in the same manner as members of normal classes, and not using the `template<>` syntax. The same is true when defining a member of an explicitly specialized member class. However, `template<>` is used in defining a member of an explicitly specialized member class template that is specialized as a class template. [*Example:*

```
template<class T> struct A {
    struct B { };
    template<class U> struct C { };
};

template<> struct A<int> {
    void f(int);
};

void h() {
    A<int> a;
    a.f(16);           // A<int>::f must be defined somewhere
}

// template<> not used for a member of an explicitly specialized class template
void A<int>::f(int) { /* ... */ }

template<> struct A<char>::B {
    void f();
};
// template<> also not used when defining a member of an explicitly specialized member class
void A<char>::B::f() { /* ... */ }

template<> template<class U> struct A<char>::C {
    void f();
};
// template<> is used when defining a member of an explicitly specialized member class template
// specialized as a class template
template<>
template<class U> void A<char>::C<U>::f() { /* ... */ }

template<> struct A<short>::B {
    void f();
};
template<> void A<short>::B::f() { /* ... */ }           // error: template<> not permitted

template<> template<class U> struct A<short>::C {
    void f();
};
template<class U> void A<short>::C<U>::f() { /* ... */ } // error: template<> required

— end example]
```

- ⁶ If a template, a member template or a member of a class template is explicitly specialized then that specialization shall be declared before the first use of that specialization that would cause an implicit instantiation to take place, in every translation unit in which such a use occurs; no diagnostic is required. If

the program does not provide a definition for an explicit specialization and either the specialization is used in a way that would cause an implicit instantiation to take place or the member is a virtual member function, the program is ill-formed, no diagnostic required. An implicit instantiation is never generated for an explicit specialization that is declared but not defined. [*Example:*

```
class String { };
template<class T> class Array { /* ... */ };
template<class T> void sort(Array<T>& v) { /* ... */ }

void f(Array<String>& v) {
    sort(v);           // use primary template sort(Array<T>&), T is String
}

template<> void sort<String>(Array<String>& v);    // error: specialization after use of primary template
template<> void sort<>(Array<char*>& v);           // OK: sort<char*> not yet used
template<class T> struct A {
    enum E : T;
    enum class S : T;
};
template<> enum A<int>::E : int { eint };          // OK
template<> enum class A<int>::S : int { sint };     // OK
template<class T> enum A<T>::E : T { eT };
template<class T> enum class A<T>::S : T { sT };
template<> enum A<char>::E : char { echar };       // ill-formed, A<char>::E was instantiated
                                                    // when A<char> was instantiated
template<> enum class A<char>::S : char { schar };  // OK

— end example]
```

- ⁷ The placement of explicit specialization declarations for function templates, class templates, variable templates, member functions of class templates, static data members of class templates, member classes of class templates, member enumerations of class templates, member class templates of class templates, member function templates of class templates, static data member templates of class templates, member functions of member templates of class templates, member functions of member templates of non-template classes, static data member templates of non-template classes, member function templates of member classes of class templates, etc., and the placement of partial specialization declarations of class templates, variable templates, member class templates of non-template classes, static data member templates of non-template classes, member class templates of class templates, etc., can affect whether a program is well-formed according to the relative positioning of the explicit specialization declarations and their points of instantiation in the translation unit as specified above and below. When writing a specialization, be careful about its location; or to make it compile will be such a trial as to kindle its self-immolation.

- ⁸ A template explicit specialization is in the scope of the namespace in which the template was defined. [*Example:*

```
namespace N {
    template<class T> class X { /* ... */ };
    template<class T> class Y { /* ... */ };

    template<> class X<int> { /* ... */ };          // OK: specialization in same namespace
    template<> class Y<double>;                     // forward-declare intent to specialize for double
}

template<> class N::Y<double> { /* ... */ };        // OK: specialization in enclosing namespace
template<> class N::Y<short> { /* ... */ };         // OK: specialization in enclosing namespace

— end example]
```

- ⁹ A *simple-template-id* that names a class template explicit specialization that has been declared but not defined can be used exactly like the names of other incompletely-defined classes (6.9). [*Example:*

```
template<class T> class X;                // X is a class template
template<> class X<int>;

X<int>* p;                               // OK: pointer to declared class X<int>
X<int> x;                                // error: object of incomplete class X<int>

— end example]
```

- ¹⁰ A trailing *template-argument* can be left unspecified in the *template-id* naming an explicit function template specialization provided it can be deduced from the function argument type. [*Example:*

```
template<class T> class Array { /* ... */ };
template<class T> void sort(Array<T>& v);

// explicit specialization for sort(Array<int>&)
// with deduced template-argument of type int
template<> void sort(Array<int>&);

— end example]
```

- ¹¹ A function with the same name as a template and a type that exactly matches that of a template specialization is not an explicit specialization (17.5.6).
- ¹² An explicit specialization of a function or variable template is inline only if it is declared with the **inline** specifier or defined as deleted, and independently of whether its function or variable template is inline. [*Example:*

```
template<class T> void f(T) { /* ... */ }
template<class T> inline T g(T) { /* ... */ }

template<> inline void f<>(int) { /* ... */ } // OK: inline
template<> int g<>(int) { /* ... */ }         // OK: not inline

— end example]
```

- ¹³ An explicit specialization of a static data member of a template or an explicit specialization of a static data member template is a definition if the declaration includes an initializer; otherwise, it is a declaration. [*Note:* The definition of a static data member of a template that requires default-initialization must use a *braced-init-list*:

```
template<> X Q<int>::x;                    // declaration
template<> X Q<int>::x ();                  // error: declares a function
template<> X Q<int>::x { };                 // definition

— end note]
```

- ¹⁴ A member or a member template of a class template may be explicitly specialized for a given implicit instantiation of the class template, even if the member or member template is defined in the class template definition. An explicit specialization of a member or member template is specified using the syntax for explicit specialization. [*Example:*

```
template<class T> struct A {
    void f(T);
    template<class X1> void g1(T, X1);
    template<class X2> void g2(T, X2);
    void h(T) { }
};

// specialization
```

```

template<> void A<int>::f(int);

// out of class member template definition
template<class T> template<class X1> void A<T>::g1(T, X1) { }

// member template specialization
template<> template<class X1> void A<int>::g1(int, X1);

// member template specialization
template<> template<>
    void A<int>::g1(int, char);           // X1 deduced as char
template<> template<>
    void A<int>::g2<char>(int, char);     // X2 specified as char

// member specialization even if defined in class definition
template<> void A<int>::h(int) { }

```

— end example]

- 15 A member or a member template may be nested within many enclosing class templates. In an explicit specialization for such a member, the member declaration shall be preceded by a `template<>` for each enclosing class template that is explicitly specialized. [*Example:*

```

template<class T1> class A {
    template<class T2> class B {
        void mf();
    };
};
template<> template<> class A<int>::B<double>;
template<> template<> void A<char>::B<char>::mf();

```

— end example]

- 16 In an explicit specialization declaration for a member of a class template or a member template that appears in namespace scope, the member template and some of its enclosing class templates may remain unspecialized, except that the declaration shall not explicitly specialize a class member template if its enclosing class templates are not explicitly specialized as well. In such explicit specialization declaration, the keyword `template` followed by a *template-parameter-list* shall be provided instead of the `template<>` preceding the explicit specialization declaration of the member. The types of the *template-parameters* in the *template-parameter-list* shall be the same as those specified in the primary template definition. [*Example:*

```

template <class T1> class A {
    template<class T2> class B {
        template<class T3> void mf1(T3);
        void mf2();
    };
};
template <> template <class X>
    class A<int>::B {
        template <class T> void mf1(T);
    };
template <> template <> template<class T>
    void A<int>::B<double>::mf1(T t) { }
template <class Y> template <>
    void A<Y>::B<double>::mf2() { }           // ill-formed; B<double> is specialized but
                                              // its enclosing class template A is not

```

— end example]

- 17 A specialization of a member function template, member class template, or static data member template of a non-specialized class template is itself a template.
- 18 An explicit specialization declaration shall not be a friend declaration.
- 19 Default function arguments shall not be specified in a declaration or a definition for one of the following explicit specializations:
- (19.1) — the explicit specialization of a function template;
 - (19.2) — the explicit specialization of a member function template;
 - (19.3) — the explicit specialization of a member function of a class template where the class template specialization to which the member function specialization belongs is implicitly instantiated. [*Note*: Default function arguments may be specified in the declaration or definition of a member function of a class template specialization that is explicitly specialized. — *end note*]

17.8 Function template specializations

[temp.fct.spec]

- 1 A function instantiated from a function template is called a function template specialization; so is an explicit specialization of a function template. Template arguments can be explicitly specified when naming the function template specialization, deduced from the context (e.g., deduced from the function arguments in a call to the function template specialization, see 17.8.2), or obtained from default template arguments.
- 2 Each function template specialization instantiated from a template has its own copy of any static variable.
- [*Example*:

```
template<class T> void f(T* p) {
    static T s;
};

void g(int a, char* b) {
    f(&a);           // calls f<int>(int*)
    f(&b);           // calls f<char*>(char**)
}
```

Here `f<int>(int*)` has a static variable `s` of type `int` and `f<char*>(char**)` has a static variable `s` of type `char*`. — *end example*]

17.8.1 Explicit template argument specification

[temp.arg.explicit]

- 1 Template arguments can be specified when referring to a function template specialization by qualifying the function template name with the list of *template-arguments* in the same way as *template-arguments* are specified in uses of a class template specialization. [*Example*:

```
template<class T> void sort(Array<T>& v);
void f(Array<dcomplex>& cv, Array<int>& ci) {
    sort<dcomplex>(cv);           // sort(Array<dcomplex>&)
    sort<int>(ci);               // sort(Array<int>&)
}
```

and

```
template<class U, class V> U convert(V v);

void g(double d) {
    int i = convert<int,double>(d); // int convert(double)
    char c = convert<char,double>(d); // char convert(double)
}
```

— *end example*]

- ² A template argument list may be specified when referring to a specialization of a function template
- (2.1) — when a function is called,
 - (2.2) — when the address of a function is taken, when a function initializes a reference to function, or when a pointer to member function is formed,
 - (2.3) — in an explicit specialization,
 - (2.4) — in an explicit instantiation, or
 - (2.5) — in a friend declaration.

- ³ Trailing template arguments that can be deduced (17.8.2) or obtained from default *template-arguments* may be omitted from the list of explicit *template-arguments*. A trailing template parameter pack (17.5.3) not otherwise deduced will be deduced to an empty sequence of template arguments. If all of the template arguments can be deduced, they may all be omitted; in this case, the empty template argument list <> itself may also be omitted. In contexts where deduction is done and fails, or in contexts where deduction is not done, if a template argument list is specified and it, along with any default template arguments, identifies a single function template specialization, then the *template-id* is an lvalue for the function template specialization. [Example:

```
template<class X, class Y> X f(Y);
template<class X, class Y, class ... Z> X g(Y);
void h() {
    int i = f<int>(5.6);           // Y is deduced to be double
    int j = f(5.6);               // ill-formed: X cannot be deduced
    f<void>(f<int, bool>);         // Y for outer f deduced to be int (*) (bool)
    f<void>(f<int>);               // ill-formed: f<int> does not denote a single function template specialization
    int k = g<int>(5.6);           // Y is deduced to be double, Z is deduced to an empty sequence
    f<void>(g<int, bool>);         // Y for outer f is deduced to be int (*) (bool),
                                   // Z is deduced to an empty sequence
}
```

— end example]

- ⁴ [Note: An empty template argument list can be used to indicate that a given use refers to a specialization of a function template even when a non-template function (11.3.5) is visible that would otherwise be used. For example:

```
template <class T> int f(T);      // #1
int f(int);                     // #2
int k = f(1);                   // uses #2
int l = f<>(1);                  // uses #1
```

— end note]

- ⁵ Template arguments that are present shall be specified in the declaration order of their corresponding *template-parameters*. The template argument list shall not specify more *template-arguments* than there are corresponding *template-parameters* unless one of the *template-parameters* is a template parameter pack. [Example:

```
template<class X, class Y, class Z> X f(Y,Z);
template<class ... Args> void f2();
void g() {
    f<int,const char*,double>("aa",3.0);
    f<int,const char*>("aa",3.0); // Z is deduced to be double
    f<int>("aa",3.0);             // Y is deduced to be const char*, and Z is deduced to be double
    f("aa",3.0);                 // error: X cannot be deduced
    f2<char, short, int, long>(); // OK
}
```

— *end example*]

- ⁶ Implicit conversions (Clause 7) will be performed on a function argument to convert it to the type of the corresponding function parameter if the parameter type contains no *template-parameters* that participate in template argument deduction. [*Note:* Template parameters do not participate in template argument deduction if they are explicitly specified. For example,

```
template<class T> void f(T);

class Complex {
    Complex(double);
};

void g() {
    f<Complex>(1);    // OK, means f<Complex>(Complex(1))
}
```

— *end note*]

- ⁷ [*Note:* Because the explicit template argument list follows the function template name, and because conversion member function templates and constructor member function templates are called without using a function name, there is no way to provide an explicit template argument list for these function templates. — *end note*]

- ⁸ [*Note:* For simple function names, argument dependent lookup (6.4.2) applies even when the function name is not visible within the scope of the call. This is because the call still has the syntactic form of a function call (6.4.1). But when a function template with explicit template arguments is used, the call does not have the correct syntactic form unless there is a function template with that name visible at the point of the call. If no such name is visible, the call is not syntactically well-formed and argument-dependent lookup does not apply. If some such name is visible, argument dependent lookup applies and additional function templates may be found in other namespaces. [*Example:*

```
namespace A {
    struct B { };
    template<int X> void f(B);
}
namespace C {
    template<class T> void f(T t);
}
void g(A::B b) {
    f<3>(b);           // ill-formed: not a function call
    A::f<3>(b);        // well-formed
    C::f<3>(b);        // ill-formed; argument dependent lookup applies only to unqualified names
    using C::f;
    f<3>(b);           // well-formed because C::f is visible; then A::f is found by argument dependent lookup
}
```

— *end example*] — *end note*]

- ⁹ Template argument deduction can extend the sequence of template arguments corresponding to a template parameter pack, even when the sequence contains explicitly specified template arguments. [*Example:*

```
template<class ... Types> void f(Types ... values);

void g() {
    f<int*, float*>(0, 0, 0);    // Types is deduced to the sequence int*, float*, int
}
```

— *end example*]

17.8.2 Template argument deduction

[temp.deduct]

- ¹ When a function template specialization is referenced, all of the template arguments shall have values. The values can be explicitly specified or, in some cases, be deduced from the use or obtained from default *template-arguments*. [*Example*:

```
void f(Array<dcomplex>& cv, Array<int>& ci) {
    sort(cv);                // calls sort(Array<dcomplex>&)
    sort(ci);                // calls sort(Array<int>&)
}
```

and

```
void g(double d) {
    int i = convert<int>(d);   // calls convert<int,double>(double)
    int c = convert<char>(d);  // calls convert<char,double>(double)
}
```

— *end example*]

- ² When an explicit template argument list is specified, the template arguments must be compatible with the template parameter list and must result in a valid function type as described below; otherwise type deduction fails. Specifically, the following steps are performed when evaluating an explicitly specified template argument list with respect to a given function template:
- (2.1) — The specified template arguments must match the template parameters in kind (i.e., type, non-type, template). There must not be more arguments than there are parameters unless at least one parameter is a template parameter pack, and there shall be an argument for each non-pack parameter. Otherwise, type deduction fails.
 - (2.2) — Non-type arguments must match the types of the corresponding non-type template parameters, or must be convertible to the types of the corresponding non-type parameters as specified in 17.3.2, otherwise type deduction fails.
 - (2.3) — The specified template argument values are substituted for the corresponding template parameters as specified below.
- ³ After this substitution is performed, the function parameter type adjustments described in 11.3.5 are performed. [*Example*: A parameter type of “void (const int, int[5])” becomes “void(*) (int,int*)”. — *end example*] [*Note*: A top-level qualifier in a function parameter declaration does not affect the function type but still affects the type of the function parameter variable within the function. — *end note*] [*Example*:

```
template <class T> void f(T t);
template <class X> void g(const X x);
template <class Z> void h(Z, Z*);

int main() {
    // #1: function type is f(int), t is non const
    f<int>(1);

    // #2: function type is f(int), t is const
    f<const int>(1);

    // #3: function type is g(int), x is const
    g<int>(1);

    // #4: function type is g(int), x is const
    g<const int>(1);

    // #5: function type is h(int, const int*)
    h(1, 1);
}
```

```
    h<const int>(1,0);
}
```

— end example]

- 4 [*Note*: `f<int>(1)` and `f<const int>(1)` call distinct functions even though both of the functions called have the same function type. — end note]
- 5 The resulting substituted and adjusted function type is used as the type of the function template for template argument deduction. If a template argument has not been deduced and its corresponding template parameter has a default argument, the template argument is determined by substituting the template arguments determined for preceding template parameters into the default argument. If the substitution results in an invalid type, as described above, type deduction fails. [*Example*:

```
template <class T, class U = double>
void f(T t = 0, U u = 0);

void g() {
    f(1, 'c');           // f<int,char>(1,'c')
    f(1);                // f<int,double>(1,0)
    f();                 // error: T cannot be deduced
    f<int>();             // f<int,double>(0,0)
    f<int,char>();        // f<int,char>(0,0)
}
```

— end example]

When all template arguments have been deduced or obtained from default template arguments, all uses of template parameters in the template parameter list of the template and the function type are replaced with the corresponding deduced or default argument values. If the substitution results in an invalid type, as described above, type deduction fails.

- 6 At certain points in the template argument deduction process it is necessary to take a function type that makes use of template parameters and replace those template parameters with the corresponding template arguments. This is done at the beginning of template argument deduction when any explicitly specified template arguments are substituted into the function type, and again at the end of template argument deduction when any template arguments that were deduced or obtained from default arguments are substituted.
- 7 The substitution occurs in all types and expressions that are used in the function type and in template parameter declarations. The expressions include not only constant expressions such as those that appear in array bounds or as nontype template arguments but also general expressions (i.e., non-constant expressions) inside `sizeof`, `decltype`, and other contexts that allow non-constant expressions. The substitution proceeds in lexical order and stops when a condition that causes deduction to fail is encountered. [*Note*: The equivalent substitution in exception specifications is done only when the *noexcept-specifier* is instantiated, at which point a program is ill-formed if the substitution results in an invalid type or expression. — end note]
- [*Example*:

```
template <class T> struct A { using X = typename T::X; };
template <class T> typename T::X f(typename A<T>::X);
template <class T> void f(...) { }
template <class T> auto g(typename A<T>::X) -> typename T::X;
template <class T> void g(...) { }

void h() {
    f<int>(0);           // OK, substituting return type causes deduction to fail
    g<int>(0);           // error, substituting parameter type instantiates A<int>
}
```

— *end example*]

- ⁸ If a substitution results in an invalid type or expression, type deduction fails. An invalid type or expression is one that would be ill-formed, with a diagnostic required, if written using the substituted arguments. [*Note*: If no diagnostic is required, the program is still ill-formed. Access checking is done as part of the substitution process. — *end note*] Only invalid types and expressions in the immediate context of the function type and its template parameter types can result in a deduction failure. [*Note*: The substitution into types and expressions can result in effects such as the instantiation of class template specializations and/or function template specializations, the generation of implicitly-defined functions, etc. Such effects are not in the “immediate context” and can result in the program being ill-formed. — *end note*]

[*Example*:

```
struct X { };
struct Y {
    Y(X){}
};

template <class T> auto f(T t1, T t2) -> decltype(t1 + t2);    // #1
X f(Y, Y);           // #2

X x1, x2;
X x3 = f(x1, x2);    // deduction fails on #1 (cannot add X+X), calls #2
```

— *end example*]

[*Note*: Type deduction may fail for the following reasons:

- (8.1) — Attempting to instantiate a pack expansion containing multiple parameter packs of differing lengths.
- (8.2) — Attempting to create an array with an element type that is `void`, a function type, a reference type, or an abstract class type, or attempting to create an array with a size that is zero or negative. [*Example*:

```
template <class T> int f(T[5]);
int I = f<int>(0);
int j = f<void>(0);           // invalid array
```

— *end example*]
- (8.3) — Attempting to use a type that is not a class or enumeration type in a qualified name. [*Example*:

```
template <class T> int f(typename T::B*);
int i = f<int>(0);
```

— *end example*]
- (8.4) — Attempting to use a type in a *nested-name-specifier* of a *qualified-id* when that type does not contain the specified member, or
 - (8.4.1) — the specified member is not a type where a type is required, or
 - (8.4.2) — the specified member is not a template where a template is required, or
 - (8.4.3) — the specified member is not a non-type where a non-type is required.

[*Example*:

```
template <int I> struct X { };
template <template <class T> class> struct Z { };
template <class T> void f(typename T::Y*){}
template <class T> void g(X<T::N>*){}
template <class T> void h(Z<T::template TT>*){}
struct A {};
struct B { int Y; };
```

```

struct C {
    typedef int N;
};
struct D {
    typedef int TT;
};

int main() {
    // Deduction fails in each of these cases:
    f<A>(0);           // A does not contain a member Y
    f<B>(0);           // The Y member of B is not a type
    g<C>(0);           // The N member of C is not a non-type
    h<D>(0);           // The TT member of D is not a template
}

```

— end example]

(8.5) — Attempting to create a pointer to reference type.

(8.6) — Attempting to create a reference to void.

(8.7) — Attempting to create “pointer to member of T” when T is not a class type. [*Example:*

```

template <class T> int f(int T::*);
int i = f<int>(0);

```

— end example]

(8.8) — Attempting to give an invalid type to a non-type template parameter. [*Example:*

```

template <class T, T> struct S {};
template <class T> int f(S<T, T()>*>);
struct X {};
int i0 = f<X>(0);

```

— end example]

(8.9) — Attempting to perform an invalid conversion in either a template argument expression, or an expression used in the function declaration. [*Example:*

```

template <class T, T*> int f(int);
int i2 = f<int, 1>(0);           // can't conv 1 to int*

```

— end example]

(8.10) — Attempting to create a function type in which a parameter has a type of void, or in which the return type is a function type or array type.

(8.11) — Attempting to create a function type in which a parameter type or the return type is an abstract class type (13.4).

— end note]

9 [*Example:* In the following example, assuming a **signed char** cannot represent the value 1000, a narrowing conversion (11.6.4) would be required to convert the *template-argument* of type **int** to **signed char**, therefore substitution fails for the second template (17.3.2).

```

template <int> int f(int);
template <signed char> int f(int);
int i1 = f<1000>(0);           // OK
int i2 = f<1>(0);              // ambiguous; not narrowing

```

— end example]

17.8.2.1 Deducing template arguments from a function call [temp.deduct.call]

- ¹ Template argument deduction is done by comparing each function template parameter type (call it *P*) that contains *template-parameters* that participate in template argument deduction with the type of the corresponding argument of the call (call it *A*) as described below. If removing references and cv-qualifiers from *P* gives `std::initializer_list<P'>` or `P'[N]` for some *P'* and *N* and the argument is a non-empty initializer list (11.6.4), then deduction is performed instead for each element of the initializer list, taking *P'* as a function template parameter type and the initializer element as its argument, and in the `P'[N]` case, if *N* is a non-type template parameter, *N* is deduced from the length of the initializer list. Otherwise, an initializer list argument causes the parameter to be considered a non-deduced context (17.8.2.5). [*Example*:

```
template<class T> void f(std::initializer_list<T>);
f({1,2,3});           // T deduced to int
f({1,"asdf"});       // error: T deduced to both int and const char*

template<class T> void g(T);
g({1,2,3});           // error: no argument deduced for T

template<class T, int N> void h(T const(&)[N]);
h({1,2,3});           // T deduced to int, N deduced to 3

template<class T> void j(T const(&)[3]);
j({42});              // T deduced to int, array bound not considered

struct Aggr { int i; int j; };
template<int N> void k(Aggr const(&)[N]);
k({1,2,3});           // error: deduction fails, no conversion from int to Aggr
k({{1},{2},{3}});    // OK, N deduced to 3

template<int M, int N> void m(int const(&)[M][N]);
m({{1,2},{3,4}});    // M and N both deduced to 2

template<class T, int N> void n(T const(&)[N], T);
n({{1},{2},{3}},Aggr()); // OK, T is Aggr, N is 3
```

— *end example*] For a function parameter pack that occurs at the end of the *parameter-declaration-list*, deduction is performed for each remaining argument of the call, taking the type *P* of the *declarator-id* of the function parameter pack as the corresponding function template parameter type. Each deduction deduces template arguments for subsequent positions in the template parameter packs expanded by the function parameter pack. When a function parameter pack appears in a non-deduced context (17.8.2.5), the type of that parameter pack is never deduced. [*Example*:

```
template<class ... Types> void f(Types& ...);
template<class T1, class ... Types> void g(T1, Types ...);
template<class T1, class ... Types> void g1(Types ..., T1);

void h(int x, float& y) {
    const int z = x;
    f(x, y, z);           // Types is deduced to int, float, const int
    g(x, y, z);           // T1 is deduced to int; Types is deduced to float, int
    g1(x, y, z);          // error: Types is not deduced
    g1<int, int, int>(x, y, z); // OK, no deduction occurs
}
```

— *end example*]

- ² If *P* is not a reference type:

- (2.1) — If *A* is an array type, the pointer type produced by the array-to-pointer standard conversion (7.2) is used in place of *A* for type deduction; otherwise,
- (2.2) — If *A* is a function type, the pointer type produced by the function-to-pointer standard conversion (7.3) is used in place of *A* for type deduction; otherwise,
- (2.3) — If *A* is a cv-qualified type, the top-level cv-qualifiers of *A*'s type are ignored for type deduction.

³ If *P* is a cv-qualified type, the top-level cv-qualifiers of *P*'s type are ignored for type deduction. If *P* is a reference type, the type referred to by *P* is used for type deduction. [*Example*:

```
template<class T> int f(const T&);
int n1 = f(5);           // calls f<int>(const int&)
const int i = 0;
int n2 = f(i);           // calls f<int>(const int&)
template <class T> int g(volatile T&);
int n3 = g(i);           // calls g<const int>(const volatile int&)
```

— *end example*] A *forwarding reference* is an rvalue reference to a cv-unqualified template parameter that does not represent a template parameter of a class template (during class template argument deduction (16.3.1.8)). If *P* is a forwarding reference and the argument is an lvalue, the type “lvalue reference to *A*” is used in place of *A* for type deduction. [*Example*:

```
template <class T> int f(T&& heisenreference);
template <class T> int g(const T&&);
int i;
int n1 = f(i);           // calls f<int>(int&)
int n2 = f(0);           // calls f<int>(int&&)
int n3 = g(i);           // error: would call g<int>(const int&&), which
                        // would bind an rvalue reference to an lvalue

template <class T> struct A {
    template <class U>
        A(T&&, U&&, int*);           // #1: T&& is not a forwarding reference.
                                    // U&& is a forwarding reference.
    A(T&&, int*);                     // #2
};

template <class T> A(T&&, int*) -> A<T>; // #3: T&& is a forwarding reference.

int *ip;
A a{i, 0, ip};           // error: cannot deduce from #1
A a0{0, 0, ip};          // uses #1 to deduce A<int> and #1 to initialize
A a2{i, ip};             // uses #3 to deduce A<int&& and #2 to initialize
```

— *end example*]

⁴ In general, the deduction process attempts to find template argument values that will make the deduced *A* identical to *A* (after the type *A* is transformed as described above). However, there are three cases that allow a difference:

- (4.1) — If the original *P* is a reference type, the deduced *A* (i.e., the type referred to by the reference) can be more cv-qualified than the transformed *A*.
- (4.2) — The transformed *A* can be another pointer or pointer to member type that can be converted to the deduced *A* via a function pointer conversion (7.13) and/or qualification conversion (7.5).
- (4.3) — If *P* is a class and *P* has the form *simple-template-id*, then the transformed *A* can be a derived class of the deduced *A*. Likewise, if *P* is a pointer to a class of the form *simple-template-id*, the transformed *A* can be a pointer to a derived class pointed to by the deduced *A*.

- 5 These alternatives are considered only if type deduction would otherwise fail. If they yield more than one possible deduced A, the type deduction fails. [Note: If a *template-parameter* is not used in any of the function parameters of a function template, or is used only in a non-deduced context, its corresponding *template-argument* cannot be deduced from a function call and the *template-argument* must be explicitly specified. — end note]
- 6 When P is a function type, function pointer type, or pointer to member function type:
- (6.1) — If the argument is an overload set containing one or more function templates, the parameter is treated as a non-deduced context.
- (6.2) — If the argument is an overload set (not containing function templates), trial argument deduction is attempted using each of the members of the set. If deduction succeeds for only one of the overload set members, that member is used as the argument value for the deduction. If deduction succeeds for more than one member of the overload set the parameter is treated as a non-deduced context.
- 7 [Example:
- ```
// Only one function of an overload set matches the call so the function parameter is a deduced context.
template <class T> int f(T (*p)(T));
int g(int);
int g(char);
int i = f(g); // calls f(int (*)(int))
```
- end example]
- 8 [Example:
- ```
// Ambiguous deduction causes the second function parameter to be a non-deduced context.
template <class T> int f(T, T (*p)(T));
int g(int);
char g(char);
int i = f(1, g);        // calls f(int, int (*)(int))
```
- end example]
- 9 [Example:
- ```
// The overload set contains a template, causing the second function parameter to be a non-deduced context.
template <class T> int f(T, T (*p)(T));
char g(char);
template <class T> T g(T);
int i = f(1, g); // calls f(int, int (*)(int))
```
- end example]
- 10 If deduction succeeds for all parameters that contain *template-parameters* that participate in template argument deduction, and all template arguments are explicitly specified, deduced, or obtained from default template arguments, remaining parameters are then compared with the corresponding arguments. For each remaining parameter P with a type that was non-dependent before substitution of any explicitly-specified template arguments, if the corresponding argument A cannot be implicitly converted to P, deduction fails. [Note: Parameters with dependent types in which no *template-parameters* participate in template argument deduction, and parameters that became non-dependent due to substitution of explicitly-specified template arguments, will be checked during overload resolution. — end note] [Example:

```
template <class T> struct Z {
 typedef typename T::x xx;
};
template <class T> typename Z<T>::xx f(void *, T); // #1
template <class T> void f(int, T); // #2
struct A {} a;
```

```

 int main() {
 f(1, a); // OK, deduction fails for #1 because there is no conversion from int to void*
 }
— end example]

```

### 17.8.2.2 Deducing template arguments taking the address of a function template [temp.deduct.funcaddr]

- <sup>1</sup> Template arguments can be deduced from the type specified when taking the address of an overloaded function (16.4). The function template’s function type and the specified type are used as the types of P and A, and the deduction is done as described in 17.8.2.5.
- <sup>2</sup> A placeholder type (10.1.7.4) in the return type of a function template is a non-deduced context. If template argument deduction succeeds for such a function, the return type is determined from instantiation of the function body.

### 17.8.2.3 Deducing conversion function template arguments [temp.deduct.conv]

- <sup>1</sup> Template argument deduction is done by comparing the return type of the conversion function template (call it P) with the type that is required as the result of the conversion (call it A; see 11.6, 16.3.1.5, and 16.3.1.6 for the determination of that type) as described in 17.8.2.5.
- <sup>2</sup> If P is a reference type, the type referred to by P is used in place of P for type deduction and for any further references to or transformations of P in the remainder of this section.
- <sup>3</sup> If A is not a reference type:
  - (3.1) — If P is an array type, the pointer type produced by the array-to-pointer standard conversion (7.2) is used in place of P for type deduction; otherwise,
  - (3.2) — If P is a function type, the pointer type produced by the function-to-pointer standard conversion (7.3) is used in place of P for type deduction; otherwise,
  - (3.3) — If P is a cv-qualified type, the top-level cv-qualifiers of P’s type are ignored for type deduction.
- <sup>4</sup> If A is a cv-qualified type, the top-level cv-qualifiers of A’s type are ignored for type deduction. If A is a reference type, the type referred to by A is used for type deduction.
- <sup>5</sup> In general, the deduction process attempts to find template argument values that will make the deduced A identical to A. However, there are four cases that allow a difference:
  - (5.1) — If the original A is a reference type, A can be more cv-qualified than the deduced A (i.e., the type referred to by the reference)
  - (5.2) — If the original A is a function pointer type, A can be “pointer to function” even if the deduced A is “pointer to noexcept function”.
  - (5.3) — If the original A is a pointer to member function type, A can be “pointer to member of type function” even if the deduced A is “pointer to member of type noexcept function”.
  - (5.4) — The deduced A can be another pointer or pointer to member type that can be converted to A via a qualification conversion.
- <sup>6</sup> These alternatives are considered only if type deduction would otherwise fail. If they yield more than one possible deduced A, the type deduction fails.
- <sup>7</sup> When the deduction process requires a qualification conversion for a pointer or pointer to member type as described above, the following process is used to determine the deduced template argument values:

If A is a type

$cv_{1,0}$  “pointer to ...”  $cv_{1,n-1}$  “pointer to”  $cv_{1,n}$  T1

and P is a type

$cv_{2,0}$  “pointer to ...”  $cv_{2,n-1}$  “pointer to”  $cv_{2,n}$  T2,

then the cv-unqualified T1 and T2 are used as the types of A and P respectively for type deduction.  
[ *Example:*

```
struct A {
 template <class T> operator T***();
};
A a;
const int * const * const * p1 = a; // T is deduced as int, not const int
```

— *end example*]

#### 17.8.2.4 Deducing template arguments during partial ordering [temp.deduct.partial]

- <sup>1</sup> Template argument deduction is done by comparing certain types associated with the two function templates being compared.
- <sup>2</sup> Two sets of types are used to determine the partial ordering. For each of the templates involved there is the original function type and the transformed function type. [ *Note:* The creation of the transformed type is described in 17.5.6.2. — *end note* ] The deduction process uses the transformed type as the argument template and the original type of the other template as the parameter template. This process is done twice for each type involved in the partial ordering comparison: once using the transformed template-1 as the argument template and template-2 as the parameter template and again using the transformed template-2 as the argument template and template-1 as the parameter template.
- <sup>3</sup> The types used to determine the ordering depend on the context in which the partial ordering is done:
  - (3.1) — In the context of a function call, the types used are those function parameter types for which the function call has arguments.<sup>141</sup>
  - (3.2) — In the context of a call to a conversion function, the return types of the conversion function templates are used.
  - (3.3) — In other contexts (17.5.6.2) the function template’s function type is used.
- <sup>4</sup> Each type nominated above from the parameter template and the corresponding type from the argument template are used as the types of P and A. If a particular P contains no *template-parameters* that participate in template argument deduction, that P is not used to determine the ordering.
- <sup>5</sup> Before the partial ordering is done, certain transformations are performed on the types used for partial ordering:
  - (5.1) — If P is a reference type, P is replaced by the type referred to.
  - (5.2) — If A is a reference type, A is replaced by the type referred to.
- <sup>6</sup> If both P and A were reference types (before being replaced with the type referred to above), determine which of the two types (if any) is more cv-qualified than the other; otherwise the types are considered to be equally cv-qualified for partial ordering purposes. The result of this determination will be used below.
- <sup>7</sup> Remove any top-level cv-qualifiers:
  - (7.1) — If P is a cv-qualified type, P is replaced by the cv-unqualified version of P.
  - (7.2) — If A is a cv-qualified type, A is replaced by the cv-unqualified version of A.
- <sup>8</sup> Using the resulting types P and A, the deduction is then done as described in 17.8.2.5. If P is a function parameter pack, the type A of each remaining parameter type of the argument template is compared with the

<sup>141</sup>) Default arguments are not considered to be arguments in this context; they only become arguments after a function has been selected.

type *P* of the *declarator-id* of the function parameter pack. Each comparison deduces template arguments for subsequent positions in the template parameter packs expanded by the function parameter pack. Similarly, if *A* was transformed from a function parameter pack, it is compared with each remaining parameter type of the parameter template. If deduction succeeds for a given type, the type from the argument template is considered to be at least as specialized as the type from the parameter template. [ *Example:*

```
template<class... Args> void f(Args... args); // #1
template<class T1, class... Args> void f(T1 a1, Args... args); // #2
template<class T1, class T2> void f(T1 a1, T2 a2); // #3

f(); // calls #1
f(1, 2, 3); // calls #2
f(1, 2); // calls #3; non-variadic template #3 is more specialized
 // than the variadic templates #1 and #2
```

— *end example*]

- <sup>9</sup> If, for a given type, deduction succeeds in both directions (i.e., the types are identical after the transformations above) and both *P* and *A* were reference types (before being replaced with the type referred to above):
- (9.1) — if the type from the argument template was an lvalue reference and the type from the parameter template was not, the parameter type is not considered to be at least as specialized as the argument type; otherwise,
- (9.2) — if the type from the argument template is more cv-qualified than the type from the parameter template (as described above), the parameter type is not considered to be at least as specialized as the argument type.
- <sup>10</sup> Function template *F* is *at least as specialized as* function template *G* if, for each pair of types used to determine the ordering, the type from *F* is at least as specialized as the type from *G*. *F* is *more specialized than* *G* if *F* is at least as specialized as *G* and *G* is not at least as specialized as *F*.
- <sup>11</sup> If, after considering the above, function template *F* is at least as specialized as function template *G* and vice-versa, and if *G* has a trailing parameter pack for which *F* does not have a corresponding parameter, and if *F* does not have a trailing parameter pack, then *F* is more specialized than *G*.
- <sup>12</sup> In most cases, all template parameters must have values in order for deduction to succeed, but for partial ordering purposes a template parameter may remain without a value provided it is not used in the types being used for partial ordering. [ *Note:* A template parameter used in a non-deduced context is considered used. — *end note* ] [ *Example:*

```
template <class T> T f(int); // #1
template <class T, class U> T f(U); // #2
void g() {
 f<int>(1); // calls #1
}
```

— *end example*]

- <sup>13</sup> [ *Note:* Partial ordering of function templates containing template parameter packs is independent of the number of deduced arguments for those template parameter packs. — *end note* ] [ *Example:*

```
template<class ...> struct Tuple { };
template<class ... Types> void g(Tuple<Types ...>); // #1
template<class T1, class ... Types> void g(Tuple<T1, Types ...>); // #2
template<class T1, class ... Types> void g(Tuple<T1, Types& ...>); // #3

g(Tuple<>()); // calls #1
g(Tuple<int, float>()); // calls #2
g(Tuple<int, float&>()); // calls #3
```

```
g(Tuple<int>()); // calls #3
— end example]
```

### 17.8.2.5 Deducing template arguments from a type

[temp.deduct.type]

- <sup>1</sup> Template arguments can be deduced in several different contexts, but in each case a type that is specified in terms of template parameters (call it *P*) is compared with an actual type (call it *A*), and an attempt is made to find template argument values (a type for a type parameter, a value for a non-type parameter, or a template for a template parameter) that will make *P*, after substitution of the deduced values (call it the deduced *A*), compatible with *A*.
- <sup>2</sup> In some cases, the deduction is done using a single set of types *P* and *A*, in other cases, there will be a set of corresponding types *P* and *A*. Type deduction is done independently for each *P/A* pair, and the deduced template argument values are then combined. If type deduction cannot be done for any *P/A* pair, or if for any pair the deduction leads to more than one possible set of deduced values, or if different pairs yield different deduced values, or if any template argument remains neither deduced nor explicitly specified, template argument deduction fails. The type of a type parameter is only deduced from an array bound if it is not otherwise deduced.
- <sup>3</sup> A given type *P* can be composed from a number of other types, templates, and non-type values:
  - (3.1) — A function type includes the types of each of the function parameters and the return type.
  - (3.2) — A pointer to member type includes the type of the class object pointed to and the type of the member pointed to.
  - (3.3) — A type that is a specialization of a class template (e.g., *A<int>*) includes the types, templates, and non-type values referenced by the template argument list of the specialization.
  - (3.4) — An array type includes the array element type and the value of the array bound.
- <sup>4</sup> In most cases, the types, templates, and non-type values that are used to compose *P* participate in template argument deduction. That is, they may be used to determine the value of a template argument, and the value so determined must be consistent with the values determined elsewhere. In certain contexts, however, the value does not participate in type deduction, but instead uses the values of template arguments that were either deduced elsewhere or explicitly specified. If a template parameter is used only in non-deduced contexts and is not explicitly specified, template argument deduction fails. [Note: Under 17.8.2.1 and 17.8.2.4, if *P* contains no *template-parameters* that appear in deduced contexts, no deduction is done, so *P* and *A* need not have the same form. — end note]
- <sup>5</sup> The non-deduced contexts are:
  - (5.1) — The *nested-name-specifier* of a type that was specified using a *qualified-id*.
  - (5.2) — The *expression* of a *decltype-specifier*.
  - (5.3) — A non-type template argument or an array bound in which a subexpression references a template parameter.
  - (5.4) — A template parameter used in the parameter type of a function parameter that has a default argument that is being used in the call for which argument deduction is being done.
  - (5.5) — A function parameter for which argument deduction cannot be done because the associated function argument is a function, or a set of overloaded functions (16.4), and one or more of the following apply:
    - (5.5.1) — more than one function matches the function parameter type (resulting in an ambiguous deduction), or
    - (5.5.2) — no function matches the function parameter type, or
    - (5.5.3) — the set of functions supplied as an argument contains one or more function templates.

- (5.6) — A function parameter for which the associated argument is an initializer list (11.6.4) but the parameter does not have a type for which deduction from an initializer list is specified (17.8.2.1). [ *Example:*

```
template<class T> void g(T);
g({1,2,3}); // error: no argument deduced for T
```

— *end example*]

- (5.7) — A function parameter pack that does not occur at the end of the *parameter-declaration-list*.

- 6 When a type name is specified in a way that includes a non-deduced context, all of the types that comprise that type name are also non-deduced. However, a compound type can include both deduced and non-deduced types. [ *Example:* If a type is specified as `A<T>::B<T2>`, both `T` and `T2` are non-deduced. Likewise, if a type is specified as `A<I+J>::X<T>`, `I`, `J`, and `T` are non-deduced. If a type is specified as `void f(typename A<T>::B, A<T>)`, the `T` in `A<T>::B` is non-deduced but the `T` in `A<T>` is deduced. — *end example*]

- 7 [ *Example:* Here is an example in which different parameter/argument pairs produce inconsistent template argument deductions:

```
template<class T> void f(T x, T y) { /* ... */ }
struct A { /* ... */ };
struct B : A { /* ... */ };
void g(A a, B b) {
 f(a,b); // error: T could be A or B
 f(b,a); // error: T could be A or B
 f(a,a); // OK: T is A
 f(b,b); // OK: T is B
}
```

Here is an example where two template arguments are deduced from a single function parameter/argument pair. This can lead to conflicts that cause type deduction to fail:

```
template <class T, class U> void f(T (*)(T, U, U));

int g1(int, float, float);
char g2(int, float, float);
int g3(int, char, float);

void r() {
 f(g1); // OK: T is int and U is float
 f(g2); // error: T could be char or int
 f(g3); // error: U could be char or float
}
```

Here is an example where a qualification conversion applies between the argument type on the function call and the deduced template argument type:

```
template<class T> void f(const T*) { }
int* p;
void s() {
 f(p); // f(const int*)
}
```

Here is an example where the template argument is used to instantiate a derived class type of the corresponding function parameter type:

```
template <class T> struct B { };
template <class T> struct D : public B<T> {};
struct D2 : public B<int> {};
template <class T> void f(B<T>&){}
void t() {
```

```

 D<int> d;
 D2 d2;
 f(d); // calls f(B<int>&)
 f(d2); // calls f(B<int>&)
}

```

— *end example*]

- <sup>8</sup> A template type argument *T*, a template template argument *TT* or a template non-type argument *i* can be deduced if *P* and *A* have one of the following forms:

```

T
cv-list T
T*
T&
T&&
T[integer-constant]
template-name<T> (where template-name refers to a class template)
type(T)
T()
T(T)
T type::*
type T::*
T T::*
T (type::*)()
type (T::*)()
type (type::*)(T)
type (T::*)(T)
T (type::*)(T)
T (T::*)()
T (T::*)(T)
type[i]
template-name<i> (where template-name refers to a class template)
TT<T>
TT<i>
TT<>

```

where (T) represents a parameter-type-list (11.3.5) where at least one parameter type contains a T, and () represents a parameter-type-list where no parameter type contains a T. Similarly, <T> represents template argument lists where at least one argument contains a T, <i> represents template argument lists where at least one argument contains an i and <> represents template argument lists where no argument contains a T or an i.

- <sup>9</sup> If *P* has a form that contains <T> or <i>, then each argument *P<sub>i</sub>* of the respective template argument list of *P* is compared with the corresponding argument *A<sub>i</sub>* of the corresponding template argument list of *A*. If the template argument list of *P* contains a pack expansion that is not the last template argument, the entire template argument list is a non-deduced context. If *P<sub>i</sub>* is a pack expansion, then the pattern of *P<sub>i</sub>* is compared with each remaining argument in the template argument list of *A*. Each comparison deduces template arguments for subsequent positions in the template parameter packs expanded by *P<sub>i</sub>*. During partial ordering (17.8.2.4), if *A<sub>i</sub>* was originally a pack expansion:

- (9.1) — if *P* does not contain a template argument corresponding to *A<sub>i</sub>* then *A<sub>i</sub>* is ignored;
- (9.2) — otherwise, if *P<sub>i</sub>* is not a pack expansion, template argument deduction fails.

[ *Example*:

```

template<class T1, class... Z> class S; // #1
template<class T1, class... Z> class S<T1, const Z&...> { }; // #2

```



```

template<class T1, class T2> class S<T1, const T2&> { }; // #3
S<int, const int&> s; // both #2 and #3 match; #3 is more specialized

template<class T, class... U> struct A { }; // #1
template<class T1, class T2, class... U> struct A<T1, T2*, U...> { }; // #2
template<class T1, class T2> struct A<T1, T2> { }; // #3
template struct A<int, int*>; // selects #2

```

— end example]

- <sup>10</sup> Similarly, if P has a form that contains (T), then each parameter type  $P_i$  of the respective parameter-type-list (11.3.5) of P is compared with the corresponding parameter type  $A_i$  of the corresponding parameter-type-list of A. If P and A are function types that originated from deduction when taking the address of a function template (17.8.2.2) or when deducing template arguments from a function declaration (17.8.2.6) and  $P_i$  and  $A_i$  are parameters of the top-level parameter-type-list of P and A, respectively,  $P_i$  is adjusted if it is a forwarding reference (17.8.2.1) and  $A_i$  is an lvalue reference, in which case the type of  $P_i$  is changed to be the template parameter type (i.e.,  $T\&\&$  is changed to simply T). [Note: As a result, when  $P_i$  is  $T\&\&$  and  $A_i$  is  $X\&$ , the adjusted  $P_i$  will be T, causing T to be deduced as  $X\&$ . — end note] [Example:

```

template <class T> void f(T&&);
template <> void f(int&) { } // #1
template <> void f(int&&) { } // #2
void g(int i) {
 f(i); // calls f<int&>(int&), i.e., #1
 f(0); // calls f<int>(int&&), i.e., #2
}

```

— end example]

If the *parameter-declaration* corresponding to  $P_i$  is a function parameter pack, then the type of its *declarator-id* is compared with each remaining parameter type in the parameter-type-list of A. Each comparison deduces template arguments for subsequent positions in the template parameter packs expanded by the function parameter pack. During partial ordering (17.8.2.4), if  $A_i$  was originally a function parameter pack:

- (10.1) — if P does not contain a function parameter type corresponding to  $A_i$  then  $A_i$  is ignored;
- (10.2) — otherwise, if  $P_i$  is not a function parameter pack, template argument deduction fails.

[Example:

```

template<class T, class... U> void f(T*, U...) { } // #1
template<class T> void f(T) { } // #2
template void f(int*); // selects #1

```

— end example]

- <sup>11</sup> These forms can be used in the same way as T is for further composition of types. [Example:

```
X<int> (*) (char[6])
```

is of the form

```
template-name<T> (*) (type [i])
```

which is a variant of

```
type (*) (T)
```

where type is  $X<int>$  and T is  $char[6]$ . — end example]

- <sup>12</sup> Template arguments cannot be deduced from function arguments involving constructs other than the ones specified above.
- <sup>13</sup> When the value of the argument corresponding to a non-type template parameter P that is declared with a

dependent type is deduced from an expression, the template parameters in the type of P are deduced from the type of the value. [ *Example:*

```
template<long n> struct A { };

template<typename T> struct C;
template<typename T, T n> struct C<A<n>> {
 using Q = T;
};

using R = long;
using R = C<A<2>>::Q; // OK; T was deduced to long from the
 // template argument value in the type A<2>
```

— *end example*] The type of N in the type T[N] is `std::size_t`. [ *Example:*

```
template<typename T> struct S;
template<typename T, T n> struct S<int[n]> {
 using Q = T;
};

using V = decltype(sizeof 0);
using V = S<int[42]>::Q; // OK; T was deduced to std::size_t from the type int[42]
```

— *end example*]

<sup>14</sup> [ *Example:*

```
template<class T, T i> void f(int (&a)[i]);
int v[10];
void g() {
 f(v); // OK: T is std::size_t
}
```

— *end example*]

<sup>15</sup> [ *Note:* Except for reference and pointer types, a major array bound is not part of a function parameter type and cannot be deduced from an argument:

```
template<int i> void f1(int a[10][i]);
template<int i> void f2(int a[i][20]);
template<int i> void f3(int (&a)[i][20]);

void g() {
 int v[10][20];
 f1(v); // OK: i deduced to be 20
 f1<20>(v); // OK
 f2(v); // error: cannot deduce template-argument i
 f2<10>(v); // OK
 f3(v); // OK: i deduced to be 10
}
```

— *end note*]

<sup>16</sup> [ *Note:* If, in the declaration of a function template with a non-type template parameter, the non-type template parameter is used in a subexpression in the function parameter list, the expression is a non-deduced context as specified above. [ *Example:*

```
template <int i> class A { /* ... */ };
template <int i> void g(A<i+1>);
template <int i> void f(A<i>, A<i+1>);
```

```

void k() {
 A<1> a1;
 A<2> a2;
 g(a1); // error: deduction fails for expression i+1
 g<0>(a1); // OK
 f(a1, a2); // OK
}

```

— end example] — end note]

- <sup>17</sup> [Note: Template parameters do not participate in template argument deduction if they are used only in non-deduced contexts. For example,

```

template<int i, typename T>
T deduce(typename A<T>::X x, // T is not deduced here
 T t, // but T is deduced here
 typename B<i>::Y y); // i is not deduced here

A<int> a;
B<77> b;

int x = deduce<77>(a.xm, 62, b.ym);
// T is deduced to be int, a.xm must be convertible to A<int>::X
// i is explicitly specified to be 77, b.ym must be convertible to B<77>::Y

```

— end note]

- <sup>18</sup> If P has a form that contains <i>, and if the type of i differs from the type of the corresponding template parameter of the template named by the enclosing *simple-template-id*, deduction fails. If P has a form that contains [i], and if the type of i is not an integral type, deduction fails.<sup>142</sup> [Example:

```

template<int i> class A { /* ... */ };
template<short s> void f(A<s>);
void k1() {
 A<1> a;
 f(a); // error: deduction fails for conversion from int to short
 f<1>(a); // OK
}

template<const short cs> class B { };
template<short s> void g(B<s>);
void k2() {
 B<1> b;
 g(b); // OK: cv-qualifiers are ignored on template parameter types
}

```

— end example]

- <sup>19</sup> A *template-argument* can be deduced from a function, pointer to function, or pointer to member function type.

[Example:

```

template<class T> void f(void*)(T,int));
template<class T> void foo(T,int);
void g(int,int);
void g(char,int);

void h(int,int,int);

```

<sup>142</sup>) Although the *template-argument* corresponding to a *template-parameter* of type `bool` may be deduced from an array bound, the resulting value will always be `true` because the array bound will be nonzero.

```

void h(char,int);
int m() {
 f(&g); // error: ambiguous
 f(&h); // OK: void h(char,int) is a unique match
 f(&foo); // error: type deduction fails because foo is a template
}

```

— end example]

- 20 A template *type-parameter* cannot be deduced from the type of a function default argument. [ *Example:*

```

template <class T> void f(T = 5, T = 7);
void g() {
 f(1); // OK: call f<int>(1,7)
 f(); // error: cannot deduce T
 f<int>(); // OK: call f<int>(5,7)
}

```

— end example]

- 21 The *template-argument* corresponding to a template *template-parameter* is deduced from the type of the *template-argument* of a class template specialization used in the argument list of a function call. [ *Example:*

```

template <template <class T> class X> struct A { };
template <template <class T> class X> void f(A<X>) { }
template<class T> struct B { };
A ab;
f(ab); // calls f(A)

```

— end example]

- 22 [ *Note:* Template argument deduction involving parameter packs (17.5.3) can deduce zero or more arguments for each parameter pack. — end note] [ *Example:*

```

template<class> struct X { };
template<class R, class ... ArgTypes> struct X<R(int, ArgTypes ...)> { };
template<class ... Types> struct Y { };
template<class T, class ... Types> struct Y<T, Types& ...> { };

template<class ... Types> int f(void (*)(Types ...));
void g(int, float);

X<int> x1; // uses primary template
X<int(int, float, double)> x2; // uses partial specialization; ArgTypes contains float, double
X<int(float, int)> x3; // uses primary template
Y<> y1; // use primary template; Types is empty
Y<int&, float&, double&> y2; // uses partial specialization; T is int&, Types contains float, double
Y<int, float, double> y3; // uses primary template; Types contains int, float, double
int fv = f(g); // OK; Types contains int, float

```

— end example]

### 17.8.2.6 Deducing template arguments from a function declaration [temp.deduct.decl]

- <sup>1</sup> In a declaration whose *declarator-id* refers to a specialization of a function template, template argument deduction is performed to identify the specialization to which the declaration refers. Specifically, this is done for explicit instantiations (17.7.2), explicit specializations (17.7.3), and certain friend declarations (17.5.4). This is also done to determine whether a deallocation function template specialization matches a placement **operator new** (6.7.4.2, 8.3.4). In all these cases, P is the type of the function template being considered as a potential match and A is either the function type from the declaration or the type of the deallocation function that would match the placement **operator new** as described in 8.3.4. The deduction is done as

described in 17.8.2.5.

- <sup>2</sup> If, for the set of function templates so considered, there is either no match or more than one match after partial ordering has been considered (17.5.6.2), deduction fails and, in the declaration cases, the program is ill-formed.

### 17.8.3 Overload resolution

[temp.over]

- <sup>1</sup> A function template can be overloaded either by (non-template) functions of its name or by (other) function templates of the same name. When a call to that name is written (explicitly, or implicitly using the operator notation), template argument deduction (17.8.2) and checking of any explicit template arguments (17.3) are performed for each function template to find the template argument values (if any) that can be used with that function template to instantiate a function template specialization that can be invoked with the call arguments. For each function template, if the argument deduction and checking succeeds, the *template-arguments* (deduced and/or explicit) are used to synthesize the declaration of a single function template specialization which is added to the candidate functions set to be used in overload resolution. If, for a given function template, argument deduction fails or the synthesized function template specialization would be ill-formed, no such function is added to the set of candidate functions for that template. The complete set of candidate functions includes all the synthesized declarations and all of the non-template overloaded functions of the same name. The synthesized declarations are treated like any other functions in the remainder of overload resolution, except as explicitly noted in 16.3.3.<sup>143</sup>

- <sup>2</sup> [Example:

```
template<class T> T max(T a, T b) { return a>b?a:b; }

void f(int a, int b, char c, char d) {
 int m1 = max(a,b); // max(int a, int b)
 char m2 = max(c,d); // max(char a, char b)
 int m3 = max(a,c); // error: cannot generate max(int,char)
}
```

Adding the non-template function

```
int max(int,int);
```

to the example above would resolve the third call, by providing a function that could be called for `max(a,c)` after using the standard conversion of `char` to `int` for `c`. — end example]

- <sup>3</sup> [Example: Here is an example involving conversions on a function argument involved in *template-argument* deduction:

```
template<class T> struct B { /* ... */ };
template<class T> struct D : public B<T> { /* ... */ };
template<class T> void f(B<T>&);

void g(B<int>& bi, D<int>& di) {
 f(bi); // f(bi)
 f(di); // f((B<int>&)di)
}
```

— end example]

- <sup>4</sup> [Example: Here is an example involving conversions on a function argument not involved in *template-parameter* deduction:

<sup>143</sup>) The parameters of function template specializations contain no template parameter types. The set of conversions allowed on deduced arguments is limited, because the argument deduction process produces function templates with parameters that either match the call arguments exactly or differ only in ways that can be bridged by the allowed limited conversions. Non-deduced arguments allow the full range of conversions. Note also that 16.3.3 specifies that a non-template function will be given preference over a template specialization if the two functions are otherwise equally good candidates for an overload match.

```

template<class T> void f(T*,int); // #1
template<class T> void f(T,char); // #2

void h(int* pi, int i, char c) {
 f(pi,i); // #1: f<int>(pi,i)
 f(pi,c); // #2: f<int*>(pi,c)

 f(i,c); // #2: f<int>(i,c);
 f(i,i); // #2: f<int>(i,char(i))
}

```

— end example]

- <sup>5</sup> Only the signature of a function template specialization is needed to enter the specialization in a set of candidate functions. Therefore only the function template declaration is needed to resolve a call for which a template specialization is a candidate. [ *Example:*

```

template<class T> void f(T); // declaration

void g() {
 f("Annemarie"); // call of f<const char*>
}

```

The call of `f` is well-formed even if the template `f` is only declared and not defined at the point of the call. The program will be ill-formed unless a specialization for `f<const char*>`, either implicitly or explicitly generated, is present in some translation unit. — end example]

## 17.9 Deduction guides

[temp.deduct.guide]

- <sup>1</sup> Deduction guides are used when a *template-name* appears as a type specifier for a deduced class type (10.1.7.5). Deduction guides are not found by name lookup. Instead, when performing class template argument deduction (16.3.1.8), any deduction guides declared for the class template are considered.

*deduction-guide:*

```
explicitopt template-name (parameter-declaration-clause) -> simple-template-id ;
```

- <sup>2</sup> [ *Example:*

```

template<class T, class D = int>
struct S {
 T data;
};
template<class U>
S(U) -> S<typename U::type>;

struct A {
 using type = short;
 operator type();
};
S x{A()}; // x is of type S<short, int>

```

— end example]

- <sup>3</sup> The same restrictions apply to the *parameter-declaration-clause* of a deduction guide as in a function declaration (11.3.5). The *simple-template-id* shall name a class template specialization. The *template-name* shall be the same *identifier* as the *template-name* of the *simple-template-id*. A *deduction-guide* shall be declared in the same scope as the corresponding class template and, for a member class template, with the same access. Two deduction guide declarations in the same translation unit for the same class template shall not have equivalent *parameter-declaration-clauses*.

# 18 Exception handling [except]

- <sup>1</sup> Exception handling provides a way of transferring control and information from a point in the execution of a thread to an exception handler associated with a point previously passed by the execution. A handler will be invoked only by throwing an exception in code executed in the handler's try block or in functions called from the handler's try block.

```

try-block:
 try compound-statement handler-seq

function-try-block:
 try ctor-initializeropt compound-statement handler-seq

handler-seq:
 handler handler-seqopt

handler:
 catch (exception-declaration) compound-statement

exception-declaration:
 attribute-specifier-seqopt type-specifier-seq declarator
 attribute-specifier-seqopt type-specifier-seq abstract-declaratoropt
 ...

```

The optional *attribute-specifier-seq* in an *exception-declaration* appertains to the parameter of the catch clause (18.3).

- <sup>2</sup> A *try-block* is a *statement* (Clause 9). [Note: Within this Clause “try block” is taken to mean both *try-block* and *function-try-block*. — end note]
- <sup>3</sup> A **goto** or **switch** statement shall not be used to transfer control into a try block or into a handler. [Example:

```

void f() {
 goto 11; // ill-formed
 goto 12; // ill-formed
 try {
 goto 11; // OK
 goto 12; // ill-formed
 11: ;
 } catch (...) {
 12: ;
 goto 11; // ill-formed
 goto 12; // OK
 }
}

```

— end example] A **goto**, **break**, **return**, or **continue** statement can be used to transfer control out of a try block or handler. When this happens, each variable declared in the try block will be destroyed in the context that directly contains its declaration. [Example:

```

lab: try {
 T1 t1;
 try {
 T2 t2;
 if (condition)
 goto lab;
 }
}

```

```

 } catch(...) { /* handler 2 */ }
 } catch(...) { /* handler 1 */ }

```

Here, executing `goto lab;` will destroy first `t2`, then `t1`, assuming the *condition* does not declare a variable. Any exception thrown while destroying `t2` will result in executing **handler 2**; any exception thrown while destroying `t1` will result in executing **handler 1**. — *end example*]

- <sup>4</sup> A *function-try-block* associates a *handler-seq* with the *ctor-initializer*, if present, and the *compound-statement*. An exception thrown during the execution of the *compound-statement* or, for constructors and destructors, during the initialization or destruction, respectively, of the class's subobjects, transfers control to a handler in a *function-try-block* in the same way as an exception thrown during the execution of a *try-block* transfers control to other handlers. [ *Example*:

```

int f(int);
class C {
 int i;
 double d;
public:
 C(int, double);
};

C::C(int ii, double id)
try : i(f(ii)), d(id) {
 // constructor statements
} catch (...) {
 // handles exceptions thrown from the ctor-initializer and from the constructor statements
}

```

— *end example*]

- <sup>5</sup> In this section, “before” and “after” refer to the “sequenced before” relation (4.6).

## 18.1 Throwing an exception

[**except.throw**]

- <sup>1</sup> Throwing an exception transfers control to a handler. [ *Note*: An exception can be thrown from one of the following contexts: *throw-expressions* (8.17), allocation functions (6.7.4.1), `dynamic_cast` (8.2.7), `typeid` (8.2.8), *new-expressions* (8.3.4), and standard library functions (20.4.1.4). — *end note*] An object is passed and the type of that object determines which handlers can catch it. [ *Example*:

```

 throw "Help!";

```

can be caught by a *handler* of `const char*` type:

```

try {
 // ...
} catch(const char* p) {
 // handle character string exceptions here
}

```

and

```

class Overflow {
public:
 Overflow(char,double,double);
};

void f(double x) {
 throw Overflow('+',x,3.45e107);
}

```

can be caught by a handler for exceptions of type `Overflow`:



```

try {
 f(1.2);
} catch(Overflow& oo) {
 // handle exceptions of type Overflow here
}

```

— end example]

- 2 When an exception is thrown, control is transferred to the nearest handler with a matching type (18.3); “nearest” means the handler for which the *compound-statement* or *ctor-initializer* following the **try** keyword was most recently entered by the thread of control and not yet exited.
- 3 Throwing an exception copy-initializes (11.6, 15.8) a temporary object, called the *exception object*. An lvalue denoting the temporary is used to initialize the variable declared in the matching *handler* (18.3). If the type of the exception object would be an incomplete type or a pointer to an incomplete type other than *cv void* the program is ill-formed.
- 4 The memory for the exception object is allocated in an unspecified way, except as noted in 6.7.4.1. If a handler exits by rethrowing, control is passed to another handler for the same exception object. The points of potential destruction for the exception object are:
  - (4.1) — when an active handler for the exception exits by any means other than rethrowing, immediately after the destruction of the object (if any) declared in the *exception-declaration* in the handler;
  - (4.2) — when an object of type `std::exception_ptr` (21.8.6) that refers to the exception object is destroyed, before the destructor of `std::exception_ptr` returns.

Among all points of potential destruction for the exception object, there is an unspecified last one where the exception object is destroyed. All other points happen before that last one (4.7.1). [ *Note*: No other thread synchronization is implied in exception handling. — end note ] The implementation may then deallocate the memory for the exception object; any such deallocation is done in an unspecified way. [ *Note*: A thrown exception does not propagate to other threads unless caught, stored, and rethrown using appropriate library functions; see 21.8.6 and 33.6. — end note ]

- 5 When the thrown object is a class object, the constructor selected for the copy-initialization as well as the constructor selected for a copy-initialization considering the thrown object as an lvalue shall be non-deleted and accessible, even if the copy/move operation is elided (15.8). The destructor is potentially invoked (15.4).
- 6 An exception is considered caught when a handler for that exception becomes active (18.3). [ *Note*: An exception can have active handlers and still be considered uncaught if it is rethrown. — end note ]
- 7 If the exception handling mechanism handling an uncaught exception (18.5.2) directly invokes a function that exits via an exception, `std::terminate` is called (18.5.1). [ *Example*:

```

struct C {
 C() { }
 C(const C&) {
 if (std::uncaught_exceptions()) {
 throw 0; // throw during copy to handler's exception-declaration object (18.3)
 }
 }
};

int main() {
 try {
 throw C(); // calls std::terminate() if construction of the handler's
 // exception-declaration object is not elided (15.8)
 } catch(C) { }
}

```

— *end example*] [Note: Consequently, destructors should generally catch exceptions and not let them propagate. — *end note*]

## 18.2 Constructors and destructors

[except.ctor]

- <sup>1</sup> As control passes from the point where an exception is thrown to a handler, destructors are invoked by a process, specified in this section, called *stack unwinding*.
- <sup>2</sup> The destructor is invoked for each automatic object of class type constructed, but not yet destroyed, since the try block was entered. If an exception is thrown during the destruction of temporaries or local variables for a **return** statement (9.6.3), the destructor for the returned object (if any) is also invoked. The objects are destroyed in the reverse order of the completion of their construction. [Example:

```
struct A { };

struct Y { ~Y() noexcept(false) { throw 0; } };

A f() {
 try {
 A a;
 Y y;
 A b;
 return {}; // #1
 } catch (...) {
 }
 return {}; // #2
}
```

At #1, the returned object of type **A** is constructed. Then, the local variable **b** is destroyed (9.6). Next, the local variable **y** is destroyed, causing stack unwinding, resulting in the destruction of the returned object, followed by the destruction of the local variable **a**. Finally, the returned object is constructed again at #2. — *end example*]

- <sup>3</sup> If the initialization or destruction of an object other than by delegating constructor is terminated by an exception, the destructor is invoked for each of the object's direct subobjects and, for a complete object, virtual base class subobjects, whose initialization has completed (11.6) and whose destructor has not yet begun execution, except that in the case of destruction, the variant members of a union-like class are not destroyed. The subobjects are destroyed in the reverse order of the completion of their construction. Such destruction is sequenced before entering a handler of the *function-try-block* of the constructor or destructor, if any.
- <sup>4</sup> If the *compound-statement* of the *function-body* of a delegating constructor for an object exits via an exception, the object's destructor is invoked. Such destruction is sequenced before entering a handler of the *function-try-block* of a delegating constructor for that object, if any.
- <sup>5</sup> [Note: If the object was allocated by a *new-expression* (8.3.4), the matching deallocation function (6.7.4.2), if any, is called to free the storage occupied by the object. — *end note*]

## 18.3 Handling an exception

[except.handle]

- <sup>1</sup> The *exception-declaration* in a *handler* describes the type(s) of exceptions that can cause that *handler* to be entered. The *exception-declaration* shall not denote an incomplete type, an abstract class type, or an rvalue reference type. The *exception-declaration* shall not denote a pointer or reference to an incomplete type, other than **void\***, **const void\***, **volatile void\***, or **const volatile void\***.
- <sup>2</sup> A handler of type “array of **T**” or function type **T** is adjusted to be of type “pointer to **T**”.
- <sup>3</sup> A *handler* is a match for an exception object of type **E** if

- (3.1) — The *handler* is of type *cv* T or *cv* T& and E and T are the same type (ignoring the top-level *cv-qualifiers*), or
- (3.2) — the *handler* is of type *cv* T or *cv* T& and T is an unambiguous public base class of E, or
- (3.3) — the *handler* is of type *cv* T or *const* T& where T is a pointer or pointer to member type and E is a pointer or pointer to member type that can be converted to T by one or more of
  - (3.3.1) — a standard pointer conversion (7.11) not involving conversions to pointers to private or protected or ambiguous classes
  - (3.3.2) — a function pointer conversion (7.13)
  - (3.3.3) — a qualification conversion (7.5), or
- (3.4) — the *handler* is of type *cv* T or *const* T& where T is a pointer or pointer to member type and E is `std::nullptr_t`.

[*Note:* A *throw-expression* whose operand is an integer literal with value zero does not match a handler of pointer or pointer to member type. A handler of reference to array or function type is never a match for any exception object (8.17). — *end note*]

[*Example:*

```
class Matherr { /* ... */ virtual void vf(); };
class Overflow: public Matherr { /* ... */ };
class Underflow: public Matherr { /* ... */ };
class Zerodivide: public Matherr { /* ... */ };

void f() {
 try {
 g();
 } catch (Overflow oo) {
 // ...
 } catch (Matherr mm) {
 // ...
 }
}
```

Here, the `Overflow` handler will catch exceptions of type `Overflow` and the `Matherr` handler will catch exceptions of type `Matherr` and of all types publicly derived from `Matherr` including exceptions of type `Underflow` and `Zerodivide`. — *end example*]

- 4 The handlers for a try block are tried in order of appearance. [*Note:* This makes it possible to write handlers that can never be executed, for example by placing a handler for a final derived class after a handler for a corresponding unambiguous public base class. — *end note*]
- 5 A ... in a handler's *exception-declaration* functions similarly to ... in a function parameter declaration; it specifies a match for any exception. If present, a ... handler shall be the last handler for its try block.
- 6 If no match is found among the handlers for a try block, the search for a matching handler continues in a dynamically surrounding try block of the same thread.
- 7 A handler is considered active when initialization is complete for the parameter (if any) of the catch clause. [*Note:* The stack will have been unwound at that point. — *end note*] Also, an implicit handler is considered active when `std::terminate()` is entered due to a throw. A handler is no longer considered active when the catch clause exits.
- 8 The exception with the most recently activated handler that is still active is called the *currently handled exception*.
- 9 If no matching handler is found, the function `std::terminate()` is called; whether or not the stack is

unwound before this call to `std::terminate()` is implementation-defined (18.5.1).

- 10 Referring to any non-static member or base class of an object in the handler for a *function-try-block* of a constructor or destructor for that object results in undefined behavior.
- 11 The scope and lifetime of the parameters of a function or constructor extend into the handlers of a *function-try-block*.
- 12 Exceptions thrown in destructors of objects with static storage duration or in constructors of namespace-scope objects with static storage duration are not caught by a *function-try-block* on the `main` function (6.6.1). Exceptions thrown in destructors of objects with thread storage duration or in constructors of namespace-scope objects with thread storage duration are not caught by a *function-try-block* on the initial function of the thread.
- 13 If a return statement appears in a handler of the *function-try-block* of a constructor, the program is ill-formed.
- 14 The currently handled exception is rethrown if control reaches the end of a handler of the *function-try-block* of a constructor or destructor. Otherwise, flowing off the end of the *compound-statement* of a handler of a *function-try-block* is equivalent to flowing off the end of the *compound-statement* of that function (see 9.6.3).
- 15 The variable declared by the *exception-declaration*, of type *cv* T or *cv* T&, is initialized from the exception object, of type E, as follows:
  - (15.1) — if T is a base class of E, the variable is copy-initialized (11.6) from the corresponding base class subobject of the exception object;
  - (15.2) — otherwise, the variable is copy-initialized (11.6) from the exception object.

The lifetime of the variable ends when the handler exits, after the destruction of any automatic objects initialized within the handler.

- 16 When the handler declares an object, any changes to that object will not affect the exception object. When the handler declares a reference to an object, any changes to the referenced object are changes to the exception object and will have effect should that object be rethrown.

## 18.4 Exception specifications

[except.spec]

- 1 The predicate indicating whether a function cannot exit via an exception is called the *exception specification* of the function. If the predicate is false, the function has a *potentially-throwing exception specification*, otherwise it has a *non-throwing exception specification*. The exception specification is either defined implicitly, or defined explicitly by using a *noexcept-specifier* as a suffix of a function declarator (11.3.5).

*noexcept-specifier*:

```
noexcept (constant-expression)
noexcept
throw ()
```

- 2 In a *noexcept-specifier*, the *constant-expression*, if supplied, shall be a contextually converted constant expression of type `bool` (8.20); that constant expression is the exception specification of the function type in which the *noexcept-specifier* appears. A `(` token that follows `noexcept` is part of the *noexcept-specifier* and does not commence an initializer (11.6). The *noexcept-specifier* `noexcept` without a *constant-expression* is equivalent to the *noexcept-specifier* `noexcept(true)`. The *noexcept-specifier* `throw()` is deprecated (D.3), and equivalent to the *noexcept-specifier* `noexcept(true)`.
- 3 If a declaration of a function does not have a *noexcept-specifier*, the declaration has a potentially throwing exception specification unless it is a destructor or a deallocation function or is defaulted on its first declaration, in which cases the exception specification is as specified below and no other declaration for that function shall have a *noexcept-specifier*. In an explicit instantiation (17.7.2) a *noexcept-specifier* may be specified, but is not required. If a *noexcept-specifier* is specified in an explicit instantiation directive, the exception specification shall be the same as the exception specification of all other declarations of that function. A diagnostic is

required only if the exception specifications are not the same within a single translation unit.

- 4 If a virtual function has a non-throwing exception specification, all declarations, including the definition, of any function that overrides that virtual function in any derived class shall have a non-throwing exception specification, unless the overriding function is defined as deleted. [ *Example:*

```
struct B {
 virtual void f() noexcept;
 virtual void g();
 virtual void h() noexcept = delete;
};

struct D: B {
 void f(); // ill-formed
 void g() noexcept; // OK
 void h() = delete; // OK
};
```

The declaration of `D::f` is ill-formed because it has a potentially-throwing exception specification, whereas `B::f` has a non-throwing exception specification. — *end example*]

- 5 Whenever an exception is thrown and the search for a handler (18.3) encounters the outermost block of a function with a non-throwing exception specification, the function `std::terminate()` is called (18.5.1). [ *Note:* An implementation shall not reject an expression merely because, when executed, it throws or might throw an exception from a function with a non-throwing exception specification. — *end note* ] [ *Example:*

```
extern void f(); // potentially-throwing

void g() noexcept {
 f(); // valid, even if f throws
 throw 42; // valid, effectively a call to std::terminate
}
```

The call to `f` is well-formed even though, when called, `f` might throw an exception. — *end example*]

- 6 An expression `e` is *potentially-throwing* if

- (6.1) — `e` is a function call (8.2.2) whose *postfix-expression* has a function type, or a pointer-to-function type, with a potentially-throwing exception specification, or
- (6.2) — `e` implicitly invokes a function (such as an overloaded operator, an allocation function in a *new-expression*, a constructor for a function argument, or a destructor if `e` is a full-expression (4.6)) that is potentially-throwing, or
- (6.3) — `e` is a *throw-expression* (8.17), or
- (6.4) — `e` is a `dynamic_cast` expression that casts to a reference type and requires a runtime check (8.2.7), or
- (6.5) — `e` is a `typeid` expression applied to a (possibly parenthesized) built-in unary `*` operator applied to a pointer to a polymorphic class type (8.2.8), or
- (6.6) — any of the immediate subexpressions (4.6) of `e` is potentially-throwing.

- 7 An implicitly-declared constructor for a class `X`, or a constructor without a *noexcept-specifier* that is defaulted on its first declaration, has a potentially-throwing exception specification if and only if any of the following constructs is potentially-throwing:

- (7.1) — a constructor selected by overload resolution in the implicit definition of the constructor for class `X` to initialize a potentially constructed subobject, or
- (7.2) — a subexpression of such an initialization, such as a default argument expression, or,
- (7.3) — for a default constructor, a default member initializer.

[*Note:* Even though destructors for fully-constructed subobjects are invoked when an exception is thrown during the execution of a constructor (18.2), their exception specifications do not contribute to the exception specification of the constructor, because an exception thrown from such a destructor would call `std::terminate` rather than escape the constructor (18.1, 18.5.1). — *end note*]

- 8 The exception specification for an implicitly-declared destructor, or a destructor without a *noexcept-specifier*, is potentially-throwing if and only if any of the destructors for any of its potentially constructed subobjects is potentially throwing.
- 9 The exception specification for an implicitly-declared assignment operator, or an assignment-operator without a *noexcept-specifier* that is defaulted on its first declaration, is potentially-throwing if and only if the invocation of any assignment operator in the implicit definition is potentially-throwing.
- 10 A deallocation function (6.7.4.2) with no explicit *noexcept-specifier* has a non-throwing exception specification.
- 11 [*Example:*

```

struct A {
 A(int = (A(5), 0)) noexcept;
 A(const A&) noexcept;
 A(A&&) noexcept;
 ~A();
};
struct B {
 B() throw();
 B(const B&) = default; // implicit exception specification is noexcept(true)
 B(B&&, int = (throw Y(), 0)) noexcept;
 ~B() noexcept(false);
};
int n = 7;
struct D : public A, public B {
 int * p = new int[n];
 // D::D() potentially-throwing, as the new operator may throw bad_alloc or bad_array_new_length
 // D::D(const D&) non-throwing
 // D::D(D&&) potentially-throwing, as the default argument for B's constructor may throw
 // D:: D() potentially-throwing
};

```

Furthermore, if `A::~~A()` were virtual, the program would be ill-formed since a function that overrides a virtual function from a base class shall not have a potentially-throwing exception specification if the base class function has a non-throwing exception specification. — *end example*]

- 12 An exception specification is considered to be *needed* when:
  - (12.1) — in an expression, the function is the unique lookup result or the selected member of a set of overloaded functions (6.4, 16.3, 16.4);
  - (12.2) — the function is odr-used (6.2) or, if it appears in an unevaluated operand, would be odr-used if the expression were potentially-evaluated;
  - (12.3) — the exception specification is compared to that of another declaration (e.g., an explicit specialization or an overriding virtual function);
  - (12.4) — the function is defined; or
  - (12.5) — the exception specification is needed for a defaulted special member function that calls the function.

[*Note:* A defaulted declaration does not require the exception specification of a base member function to be evaluated until the implicit exception specification of the derived function is needed, but an explicit *noexcept-specifier* needs the implicit exception specification to compare against. — *end note*]

The exception specification of a defaulted special member function is evaluated as described above only when needed; similarly, the *noexcept-specifier* of a specialization of a function template or member function of a class template is instantiated only when needed.

## 18.5 Special functions

[except.special]

- <sup>1</sup> The function `std::terminate()` (18.5.1) is used by the exception handling mechanism for coping with errors related to the exception handling mechanism itself. The function `std::current_exception()` (21.8.6) and the class `std::nested_exception` (21.8.7) can be used by a program to capture the currently handled exception.

### 18.5.1 The `std::terminate()` function

[except.terminate]

- <sup>1</sup> In some situations exception handling must be abandoned for less subtle error handling techniques. [ *Note:* These situations are:
- (1.1) — when the exception handling mechanism, after completing the initialization of the exception object but before activation of a handler for the exception (18.1), calls a function that exits via an exception, or
  - (1.2) — when the exception handling mechanism cannot find a handler for a thrown exception (18.3), or
  - (1.3) — when the search for a handler (18.3) encounters the outermost block of a function with a non-throwing exception specification (18.4), or
  - (1.4) — when the destruction of an object during stack unwinding (18.2) terminates by throwing an exception, or
  - (1.5) — when initialization of a non-local variable with static or thread storage duration (6.6.3) exits via an exception, or
  - (1.6) — when destruction of an object with static or thread storage duration exits via an exception (6.6.4), or
  - (1.7) — when execution of a function registered with `std::atexit` or `std::at_quick_exit` exits via an exception (21.5), or
  - (1.8) — when a *throw-expression* (8.17) with no operand attempts to rethrow an exception and no exception is being handled (18.1), or
  - (1.9) — when the function `std::nested_exception::rethrow_nested` is called for an object that has captured no exception (21.8.7), or
  - (1.10) — when execution of the initial function of a thread exits via an exception (33.3.2.2), or
  - (1.11) — for a parallel algorithm whose `ExecutionPolicy` specifies such behavior (23.19.4, 23.19.5, 23.19.6), when execution of an element access function (28.4.1) of the parallel algorithm exits via an exception (28.4.4), or
  - (1.12) — when the destructor or the copy assignment operator is invoked on an object of type `std::thread` that refers to a joinable thread (33.3.2.3, 33.3.2.4), or
  - (1.13) — when a call to a `wait()`, `wait_until()`, or `wait_for()` function on a condition variable (33.5.3, 33.5.4) fails to meet a postcondition.
- *end note*]

- <sup>2</sup> In such cases, `std::terminate()` is called (21.8.4). In the situation where no matching handler is found, it is implementation-defined whether or not the stack is unwound before `std::terminate()` is called. In the situation where the search for a handler (18.3) encounters the outermost block of a function with a non-throwing exception specification (18.4), it is implementation-defined whether the stack is unwound, unwound partially, or not unwound at all before `std::terminate()` is called. In all other situations, the stack shall not be unwound before `std::terminate()` is called. An implementation is not permitted to finish

stack unwinding prematurely based on a determination that the unwind process will eventually cause a call to `std::terminate()`.

### 18.5.2 The `std::uncaught_exceptions()` function [except.uncaught]

- <sup>1</sup> An exception is considered uncaught after completing the initialization of the exception object (18.1) until completing the activation of a handler for the exception (18.3). This includes stack unwinding. If an exception is rethrown (8.17, 21.8.6), it is considered uncaught from the point of rethrow until the rethrown exception is caught. The function `std::uncaught_exceptions()` (21.8.5) returns the number of uncaught exceptions in the current thread.



# 19 Preprocessing directives

[cpp]

- <sup>1</sup> A *preprocessing directive* consists of a sequence of preprocessing tokens that satisfies the following constraints: The first token in the sequence is a # preprocessing token that (at the start of translation phase 4) is either the first character in the source file (optionally after white space containing no new-line characters) or that follows white space containing at least one new-line character. The last token in the sequence is the first new-line character that follows the first token in the sequence.<sup>144</sup> A new-line character ends the preprocessing directive even if it occurs within what would otherwise be an invocation of a function-like macro.

```

preprocessing-file:
 groupopt

group:
 group-part
 group group-part

group-part:
 control-line
 if-section
 text-line
 # conditionally-supported-directive

control-line:
 # include pp-tokens new-line
 # define identifier replacement-list new-line
 # define identifier lparen identifier-listopt) replacement-list new-line
 # define identifier lparen ...) replacement-list new-line
 # define identifier lparen identifier-list , ...) replacement-list new-line
 # undef identifier new-line
 # line pp-tokens new-line
 # error pp-tokensopt new-line
 # pragma pp-tokensopt new-line
 # new-line

if-section:
 if-group elif-groupsopt else-groupopt endif-line

if-group:
 # if constant-expression new-line groupopt
 # ifdef identifier new-line groupopt
 # ifndef identifier new-line groupopt

elif-groups:
 elif-group
 elif-groups elif-group

elif-group:
 # elif constant-expression new-line groupopt

else-group:
 # else new-line groupopt

```

144) Thus, preprocessing directives are commonly called “lines”. These “lines” have no other syntactic significance, as all white space is equivalent except in certain situations during preprocessing (see the # character string literal creation operator in 19.3.2, for example).

*endif-line*:  
     **# endif**            *new-line*

*text-line*:  
     *pp-tokens<sub>opt</sub>* *new-line*

*conditionally-supported-directive*:  
     *pp-tokens* *new-line*

*lparen*:  
     a ( character not immediately preceded by white-space

*identifier-list*:  
     *identifier*  
     *identifier-list* , *identifier*

*replacement-list*:  
     *pp-tokens<sub>opt</sub>*

*pp-tokens*:  
     *preprocessing-token*  
     *pp-tokens* *preprocessing-token*

*new-line*:  
     the new-line character

- <sup>2</sup> A text line shall not begin with a **#** preprocessing token. A *conditionally-supported-directive* shall not begin with any of the directive names appearing in the syntax. A *conditionally-supported-directive* is conditionally-supported with implementation-defined semantics.
- <sup>3</sup> When in a group that is skipped (19.1), the directive syntax is relaxed to allow any sequence of preprocessing tokens to occur between the directive name and the following new-line character.
- <sup>4</sup> The only white-space characters that shall appear between preprocessing tokens within a preprocessing directive (from just after the introducing **#** preprocessing token through just before the terminating new-line character) are space and horizontal-tab (including spaces that have replaced comments or possibly other white-space characters in translation phase 3).
- <sup>5</sup> The implementation can process and skip sections of source files conditionally, include other source files, and replace macros. These capabilities are called *preprocessing*, because conceptually they occur before translation of the resulting translation unit.
- <sup>6</sup> The preprocessing tokens within a preprocessing directive are not subject to macro expansion unless otherwise stated.

[ *Example*: In:

```
#define EMPTY
EMPTY # include <file.h>
```

the sequence of preprocessing tokens on the second line is *not* a preprocessing directive, because it does not begin with a **#** at the start of translation phase 4, even though it will do so after the macro **EMPTY** has been replaced. — *end example* ]

## 19.1 Conditional inclusion

[cpp.cond]

*defined-macro-expression*:  
     **defined** *identifier*  
     **defined** ( *identifier* )

*h-preprocessing-token*:  
     any *preprocessing-token* other than >

```

h-pp-tokens:
 h-preprocessing-token
 h-pp-tokens h-preprocessing-token

has-include-expression:
 __has_include (< h-char-sequence >)
 __has_include (" q-char-sequence ")
 __has_include (string-literal)
 __has_include (< h-pp-tokens >)

```

- <sup>1</sup> The expression that controls conditional inclusion shall be an integral constant expression except that identifiers (including those lexically identical to keywords) are interpreted as described below<sup>145</sup> and it may contain zero or more *defined-macro-expressions* and/or *has-include-expressions* as unary operator expressions.
- <sup>2</sup> A *defined-macro-expression* evaluates to 1 if the identifier is currently defined as a macro name (that is, if it is predefined or if it has been the subject of a **#define** preprocessing directive without an intervening **#undef** directive with the same subject identifier), 0 if it is not.
- <sup>3</sup> The third and fourth forms of *has-include-expression* are considered only if neither of the first or second forms matches, in which case the preprocessing tokens are processed just as in normal text.
- <sup>4</sup> The header or source file identified by the parenthesized preprocessing token sequence in each contained *has-include-expression* is searched for as if that preprocessing token sequence were the *pp-tokens* in a **#include** directive, except that no further macro expansion is performed. If such a directive would not satisfy the syntactic requirements of a **#include** directive, the program is ill-formed. The *has-include-expression* evaluates to 1 if the search for the source file succeeds, and to 0 if the search fails.
- <sup>5</sup> The **#ifdef** and **#ifndef** directives, and the **defined** conditional inclusion operator, shall treat **\_\_has\_include** as if it were the name of a defined macro. The identifier **\_\_has\_include** shall not appear in any context not mentioned in this section.
- <sup>6</sup> Each preprocessing token that remains (in the list of preprocessing tokens that will become the controlling expression) after all macro replacements have occurred shall be in the lexical form of a token (5.6).
- <sup>7</sup> Preprocessing directives of the forms

```

if constant-expression new-line groupopt
elif constant-expression new-line groupopt

```

 check whether the controlling constant expression evaluates to nonzero.
- <sup>8</sup> Prior to evaluation, macro invocations in the list of preprocessing tokens that will become the controlling constant expression are replaced (except for those macro names modified by the **defined** unary operator), just as in normal text. If the token **defined** is generated as a result of this replacement process or use of the **defined** unary operator does not match one of the two specified forms prior to macro replacement, the behavior is undefined.
- <sup>9</sup> After all replacements due to macro expansion and evaluations of *defined-macro-expressions* and *has-include-expressions* have been performed, all remaining identifiers and keywords, except for **true** and **false**, are replaced with the *pp-number* 0, and then each preprocessing token is converted into a token. [ *Note*: An alternative token (5.5) is not an identifier, even when its spelling consists entirely of letters and underscores. Therefore it is not subject to this replacement. — *end note* ]
- <sup>10</sup> The resulting tokens comprise the controlling constant expression which is evaluated according to the rules of 8.20 using arithmetic that has at least the ranges specified in 21.3. For the purposes of this token conversion and evaluation all signed and unsigned integer types act as if they have the same representation as, respectively, **intmax\_t** or **uintmax\_t** (21.4). [ *Note*: Thus on an implementation where **std::numeric\_**

145) Because the controlling constant expression is evaluated during translation phase 4, all identifiers either are or are not macro names — there simply are no keywords, enumeration constants, etc.

`limits<int>::max()` is 0x7FFF and `std::numeric_limits<unsigned int>::max()` is 0xFFFF, the integer literal 0x8000 is signed and positive within a `#if` expression even though it is unsigned in translation phase 7 (5.2). — *end note*] This includes interpreting character literals, which may involve converting escape sequences into execution character set members. Whether the numeric value for these character literals matches the value obtained when an identical character literal occurs in an expression (other than within a `#if` or `#elif` directive) is implementation-defined. [ *Note:* Thus, the constant expression in the following `#if` directive and `if` statement is not guaranteed to evaluate to the same value in these two contexts:

```
#if 'z' - 'a' == 25
if ('z' - 'a' == 25)
```

— *end note*] Also, whether a single-character character literal may have a negative value is implementation-defined. Each subexpression with type `bool` is subjected to integral promotion before processing continues.

- 11 Preprocessing directives of the forms

```
ifdef identifier new-line groupopt
ifndef identifier new-line groupopt
```

check whether the identifier is or is not currently defined as a macro name. Their conditions are equivalent to `#if defined identifier` and `#if !defined identifier` respectively.

- 12 Each directive's condition is checked in order. If it evaluates to false (zero), the group that it controls is skipped: directives are processed only through the name that determines the directive in order to keep track of the level of nested conditionals; the rest of the directives' preprocessing tokens are ignored, as are the other preprocessing tokens in the group. Only the first group whose control condition evaluates to true (nonzero) is processed; any following groups are skipped and their controlling directives are processed as if they were in a group that is skipped. If none of the conditions evaluates to true, and there is a `#else` directive, the group controlled by the `#else` is processed; lacking a `#else` directive, all the groups until the `#endif` are skipped.<sup>146</sup>

[ *Example:* This demonstrates a way to include a library optional facility only if it is available:

```
#if __has_include(<optional>)
include <optional>
define have_optional 1
#elif __has_include(<experimental/optional>)
include <experimental/optional>
define have_optional 1
define experimental_optional 1
#else
define have_optional 0
#endif
```

— *end example*]

## 19.2 Source file inclusion

[**cpp.include**]

- <sup>1</sup> A `#include` directive shall identify a header or source file that can be processed by the implementation.  
<sup>2</sup> A preprocessing directive of the form

```
include < h-char-sequence > new-line
```

searches a sequence of implementation-defined places for a header identified uniquely by the specified sequence between the < and > delimiters, and causes the replacement of that directive by the entire contents of the header. How the places are specified or the header identified is implementation-defined.

- <sup>3</sup> A preprocessing directive of the form

<sup>146</sup>) As indicated by the syntax, a preprocessing token shall not follow a `#else` or `#endif` directive before the terminating new-line character. However, comments may appear anywhere in a source file, including within a preprocessing directive.

```
include " q-char-sequence " new-line
```

causes the replacement of that directive by the entire contents of the source file identified by the specified sequence between the " delimiters. The named source file is searched for in an implementation-defined manner. If this search is not supported, or if the search fails, the directive is reprocessed as if it read

```
include < h-char-sequence > new-line
```

with the identical contained sequence (including > characters, if any) from the original directive.

- <sup>4</sup> A preprocessing directive of the form

```
include pp-tokens new-line
```

(that does not match one of the two previous forms) is permitted. The preprocessing tokens after **include** in the directive are processed just as in normal text (i.e., each identifier currently defined as a macro name is replaced by its replacement list of preprocessing tokens). If the directive resulting after all replacements does not match one of the two previous forms, the behavior is undefined.<sup>147</sup> The method by which a sequence of preprocessing tokens between a < and a > preprocessing token pair or a pair of " characters is combined into a single header name preprocessing token is implementation-defined.

- <sup>5</sup> The implementation shall provide unique mappings for sequences consisting of one or more *nondigits* or *digits* (5.10) followed by a period (.) and a single *nondigit*. The first character shall not be a *digit*. The implementation may ignore distinctions of alphabetical case.
- <sup>6</sup> A **#include** preprocessing directive may appear in a source file that has been read because of a **#include** directive in another file, up to an implementation-defined nesting limit.
- <sup>7</sup> [ *Note:* Although an implementation may provide a mechanism for making arbitrary source files available to the < > search, in general programmers should use the < > form for headers provided with the implementation, and the " " form for sources outside the control of the implementation. For instance:

```
#include <stdio.h>
#include <unistd.h>
#include "usefullib.h"
#include "myprog.h"
```

— *end note*]

- <sup>8</sup> [ *Example:* This illustrates macro-replaced **#include** directives:

```
#if VERSION == 1
 #define INCFILE "vers1.h"
#elif VERSION == 2
 #define INCFILE "vers2.h" // and so on
#else
 #define INCFILE "versN.h"
#endif
#include INCFILE
```

— *end example*]

### 19.3 Macro replacement

[cpp.replace]

- <sup>1</sup> Two replacement lists are identical if and only if the preprocessing tokens in both have the same number, ordering, spelling, and white-space separation, where all white-space separations are considered identical.
- <sup>2</sup> An identifier currently defined as an object-like macro (see below) may be redefined by another **#define** preprocessing directive provided that the second definition is an object-like macro definition and the two replacement lists are identical, otherwise the program is ill-formed. Likewise, an identifier currently defined as

<sup>147</sup> Note that adjacent string literals are not concatenated into a single string literal (see the translation phases in 5.2); thus, an expansion that results in two string literals is an invalid directive.

a function-like macro (see below) may be redefined by another **#define** preprocessing directive provided that the second definition is a function-like macro definition that has the same number and spelling of parameters, and the two replacement lists are identical, otherwise the program is ill-formed.

- 3 There shall be white-space between the identifier and the replacement list in the definition of an object-like macro.
- 4 If the *identifier-list* in the macro definition does not end with an ellipsis, the number of arguments (including those arguments consisting of no preprocessing tokens) in an invocation of a function-like macro shall equal the number of parameters in the macro definition. Otherwise, there shall be more arguments in the invocation than there are parameters in the macro definition (excluding the ...). There shall exist a ) preprocessing token that terminates the invocation.
- 5 The identifier `__VA_ARGS__` shall occur only in the *replacement-list* of a function-like macro that uses the ellipsis notation in the parameters.
- 6 A parameter identifier in a function-like macro shall be uniquely declared within its scope.
- 7 The identifier immediately following the **define** is called the *macro name*. There is one name space for macro names. Any white-space characters preceding or following the replacement list of preprocessing tokens are not considered part of the replacement list for either form of macro.
- 8 If a # preprocessing token, followed by an identifier, occurs lexically at the point at which a preprocessing directive could begin, the identifier is not subject to macro replacement.
- 9 A preprocessing directive of the form

```
define identifier replacement-list new-line
```

defines an *object-like macro* that causes each subsequent instance of the macro name<sup>148</sup> to be replaced by the replacement list of preprocessing tokens that constitute the remainder of the directive.<sup>149</sup> The replacement list is then rescanned for more macro names as specified below.

- 10 A preprocessing directive of the form

```
define identifier lparen identifier-listopt) replacement-list new-line
define identifier lparen ...) replacement-list new-line
define identifier lparen identifier-list , ...) replacement-list new-line
```

defines a *function-like macro* with parameters, whose use is similar syntactically to a function call. The parameters are specified by the optional list of identifiers, whose scope extends from their declaration in the identifier list until the new-line character that terminates the **#define** preprocessing directive. Each subsequent instance of the function-like macro name followed by a ( as the next preprocessing token introduces the sequence of preprocessing tokens that is replaced by the replacement list in the definition (an invocation of the macro). The replaced sequence of preprocessing tokens is terminated by the matching ) preprocessing token, skipping intervening matched pairs of left and right parenthesis preprocessing tokens. Within the sequence of preprocessing tokens making up an invocation of a function-like macro, new-line is considered a normal white-space character.

- 11 The sequence of preprocessing tokens bounded by the outside-most matching parentheses forms the list of arguments for the function-like macro. The individual arguments within the list are separated by comma preprocessing tokens, but comma preprocessing tokens between matching inner parentheses do not separate arguments. If there are sequences of preprocessing tokens within the list of arguments that would otherwise act as preprocessing directives,<sup>150</sup> the behavior is undefined.

148) Since, by macro-replacement time, all character literals and string literals are preprocessing tokens, not sequences possibly containing identifier-like subsequences (see 5.2, translation phases), they are never scanned for macro names or parameters.

149) An alternative token (5.5) is not an identifier, even when its spelling consists entirely of letters and underscores. Therefore it is not possible to define a macro whose name is the same as that of an alternative token.

150) A *conditionally-supported-directive* is a preprocessing directive regardless of whether the implementation supports it.

- <sup>12</sup> If there is a ... immediately preceding the ) in the function-like macro definition, then the trailing arguments, including any separating comma preprocessing tokens, are merged to form a single item: the *variable arguments*. The number of arguments so combined is such that, following merger, the number of arguments is one more than the number of parameters in the macro definition (excluding the ...).

### 19.3.1 Argument substitution

[cpp.subst]

- <sup>1</sup> After the arguments for the invocation of a function-like macro have been identified, argument substitution takes place. A parameter in the replacement list, unless preceded by a # or ## preprocessing token or followed by a ## preprocessing token (see below), is replaced by the corresponding argument after all macros contained therein have been expanded. Before being substituted, each argument's preprocessing tokens are completely macro replaced as if they formed the rest of the preprocessing file; no other preprocessing tokens are available.
- <sup>2</sup> An identifier `__VA_ARGS__` that occurs in the replacement list shall be treated as if it were a parameter, and the variable arguments shall form the preprocessing tokens used to replace it.

### 19.3.2 The # operator

[cpp.stringize]

- <sup>1</sup> Each # preprocessing token in the replacement list for a function-like macro shall be followed by a parameter as the next preprocessing token in the replacement list.
- <sup>2</sup> A *character string literal* is a *string-literal* with no prefix. If, in the replacement list, a parameter is immediately preceded by a # preprocessing token, both are replaced by a single character string literal preprocessing token that contains the spelling of the preprocessing token sequence for the corresponding argument. Each occurrence of white space between the argument's preprocessing tokens becomes a single space character in the character string literal. White space before the first preprocessing token and after the last preprocessing token comprising the argument is deleted. Otherwise, the original spelling of each preprocessing token in the argument is retained in the character string literal, except for special handling for producing the spelling of string literals and character literals: a \ character is inserted before each " and \ character of a character literal or string literal (including the delimiting " characters). If the replacement that results is not a valid character string literal, the behavior is undefined. The character string literal corresponding to an empty argument is "". The order of evaluation of # and ## operators is unspecified.

### 19.3.3 The ## operator

[cpp.concat]

- <sup>1</sup> A ## preprocessing token shall not occur at the beginning or at the end of a replacement list for either form of macro definition.
- <sup>2</sup> If, in the replacement list of a function-like macro, a parameter is immediately preceded or followed by a ## preprocessing token, the parameter is replaced by the corresponding argument's preprocessing token sequence; however, if an argument consists of no preprocessing tokens, the parameter is replaced by a placemaker preprocessing token instead.<sup>151</sup>
- <sup>3</sup> For both object-like and function-like macro invocations, before the replacement list is reexamined for more macro names to replace, each instance of a ## preprocessing token in the replacement list (not from an argument) is deleted and the preceding preprocessing token is concatenated with the following preprocessing token. Placemaker preprocessing tokens are handled specially: concatenation of two placemarkers results in a single placemaker preprocessing token, and concatenation of a placemaker with a non-placemaker preprocessing token results in the non-placemaker preprocessing token. If the result is not a valid preprocessing token, the behavior is undefined. The resulting token is available for further macro replacement. The order of evaluation of ## operators is unspecified.

[Example: In the following fragment:

```
#define hash_hash # ## #
```

<sup>151</sup>) Placemaker preprocessing tokens do not appear in the syntax because they are temporary entities that exist only within translation phase 4.



```

#define mkstr(a) # a
#define in_between(a) mkstr(a)
#define join(c, d) in_between(c hash_hash d)
char p[] = join(x, y); // equivalent to char p[] = "x ## y";

```

The expansion produces, at various stages:

```

join(x, y)
in_between(x hash_hash y)
in_between(x ## y)
mkstr(x ## y)
"x ## y"

```

In other words, expanding `hash_hash` produces a new token, consisting of two adjacent sharp signs, but this new token is not the `##` operator. — *end example*]

### 19.3.4 Rescanning and further replacement [cpp.rescan]

- 1 After all parameters in the replacement list have been substituted and `#` and `##` processing has taken place, all placemaker preprocessing tokens are removed. Then the resulting preprocessing token sequence is rescanned, along with all subsequent preprocessing tokens of the source file, for more macro names to replace.
- 2 If the name of the macro being replaced is found during this scan of the replacement list (not including the rest of the source file's preprocessing tokens), it is not replaced. Furthermore, if any nested replacements encounter the name of the macro being replaced, it is not replaced. These nonreplaced macro name preprocessing tokens are no longer available for further replacement even if they are later (re)examined in contexts in which that macro name preprocessing token would otherwise have been replaced.
- 3 The resulting completely macro-replaced preprocessing token sequence is not processed as a preprocessing directive even if it resembles one, but all pragma unary operator expressions within it are then processed as specified in 19.9 below.

### 19.3.5 Scope of macro definitions [cpp.scope]

- 1 A macro definition lasts (independent of block structure) until a corresponding `#undef` directive is encountered or (if none is encountered) until the end of the translation unit. Macro definitions have no significance after translation phase 4.
- 2 A preprocessing directive of the form

```
undef identifier new-line
```

causes the specified identifier no longer to be defined as a macro name. It is ignored if the specified identifier is not currently defined as a macro name.

- 3 [ *Example:* The simplest use of this facility is to define a “manifest constant”, as in

```

#define TABSIZE 100
int table[TABSIZE];

```

— *end example*]

- 4 [ *Example:* The following defines a function-like macro whose value is the maximum of its arguments. It has the advantages of working for any compatible types of the arguments and of generating in-line code without the overhead of function calling. It has the disadvantages of evaluating one or the other of its arguments a second time (including side effects) and generating more code than a function if invoked several times. It also cannot have its address taken, as it has none.

```
#define max(a, b) ((a) > (b) ? (a) : (b))
```

The parentheses ensure that the arguments and the resulting expression are bound properly. — *end example*]

- 5 [ *Example:* To illustrate the rules for redefinition and reexamination, the sequence



```

#define x 3
#define f(a) f(x * (a))
#undef x
#define x 2
#define g f
#define z z[0]
#define h g(~
#define m(a) a(w)
#define w 0,1
#define t(a) a
#define p() int
#define q(x) x
#define r(x,y) x ## y
#define str(x) # x

f(y+1) + f(f(z)) % t(t(g)(0) + t)(1);
g(x+(3,4)-w) | h 5) & m
 (f)~m(m);
p() i[q()] = { q(1), r(2,3), r(4,), r(,5), r(,) };
char c[2][6] = { str(hello), str() };

```

results in

```

f(2 * (y+1)) + f(2 * (f(2 * (z[0])))) % f(2 * (0)) + t(1);
f(2 * (2+(3,4)-0,1)) | f(2 * (~ 5)) & f(2 * (0,1))~m(0,1);
int i[] = { 1, 23, 4, 5, };
char c[2][6] = { "hello", "" };

```

— end example]

- <sup>6</sup> [Example: To illustrate the rules for creating character string literals and concatenating tokens, the sequence

```

#define str(s) # s
#define xstr(s) str(s)
#define debug(s, t) printf("x" # s " = %d, x" # t " = %s", \
 x ## s, x ## t)
#define INCFILE(n) vers ## n
#define glue(a, b) a ## b
#define xglue(a, b) glue(a, b)
#define HIGHLOW "hello"
#define LOW LOW ", world"

debug(1, 2);
fputs(str(strncmp("abc\0d", "abc", '\4')
 == 0) str(: @\n), s);
#include xstr(INCFILE(2).h)
glue(HIGH, LOW);
xglue(HIGH, LOW)

```

results in

```

printf("x" "1" " = %d, x" "2" " = %s", x1, x2);
fputs("strncmp(\"abc\\0d\", \"abc\", '\\4') == 0" ": @\n", s);
#include "vers2.h" (after macro replacement, before file access)
"hello";
"hello" ", world"

```

or, after concatenation of the character string literals,

```

printf("x1= %d, x2= %s", x1, x2);

```

```
fputs("strcmp(\"abc\\0d\", \"abc\", '\\4') == 0: @\\n", s);
#include "vers2.h" (after macro replacement, before file access)
"hello";
"hello, world"
```

Space around the # and ## tokens in the macro definition is optional. — *end example*

- <sup>7</sup> [ *Example:* To illustrate the rules for placemark preprocessing tokens, the sequence

```
#define t(x,y,z) x ## y ## z
int j[] = { t(1,2,3), t(,4,5), t(6,,7), t(8,9,),
 t(10,,), t(,11,), t(,12), t(,,) };
```

results in

```
int j[] = { 123, 45, 67, 89,
 10, 11, 12, };
```

— *end example*

- <sup>8</sup> [ *Example:* To demonstrate the redefinition rules, the following sequence is valid.

```
#define OBJ_LIKE (1-1)
#define OBJ_LIKE /* white space */ (1-1) /* other */
#define FUNC_LIKE(a) (a)
#define FUNC_LIKE(a)(/* note the white space */ \
 a /* other stuff on this line
 */)
```

But the following redefinitions are invalid:

```
#define OBJ_LIKE (0) // different token sequence
#define OBJ_LIKE (1 - 1) // different white space
#define FUNC_LIKE(b) (a) // different parameter usage
#define FUNC_LIKE(b) (b) // different parameter spelling
```

— *end example*

- <sup>9</sup> [ *Example:* Finally, to show the variable argument list macro facilities:

```
#define debug(...) fprintf(stderr, __VA_ARGS__)
#define showlist(...) puts(#__VA_ARGS__)
#define report(test, ...) ((test) ? puts(#test) : printf(__VA_ARGS__))
debug("Flag");
debug("X = %d\\n", x);
showlist(The first, second, and third items.);
report(x>y, "x is %d but y is %d", x, y);
```

results in

```
fprintf(stderr, "Flag");
fprintf(stderr, "X = %d\\n", x);
puts("The first, second, and third items.");
((x>y) ? puts("x>y") : printf("x is %d but y is %d", x, y));
```

— *end example*

## 19.4 Line control

[cpp.line]

- <sup>1</sup> The string literal of a #line directive, if present, shall be a character string literal.
- <sup>2</sup> The *line number* of the current source line is one greater than the number of new-line characters read or introduced in translation phase 1 (5.2) while processing the source file to the current token.
- <sup>3</sup> A preprocessing directive of the form

**# line** *digit-sequence new-line*

causes the implementation to behave as if the following sequence of source lines begins with a source line that has a line number as specified by the digit sequence (interpreted as a decimal integer). If the digit sequence specifies zero or a number greater than 2147483647, the behavior is undefined.

- <sup>4</sup> A preprocessing directive of the form

**# line** *digit-sequence* " *s-char-sequence<sub>opt</sub>* " *new-line*

sets the presumed line number similarly and changes the presumed name of the source file to be the contents of the character string literal.

- <sup>5</sup> A preprocessing directive of the form

**# line** *pp-tokens new-line*

(that does not match one of the two previous forms) is permitted. The preprocessing tokens after **line** on the directive are processed just as in normal text (each identifier currently defined as a macro name is replaced by its replacement list of preprocessing tokens). If the directive resulting after all replacements does not match one of the two previous forms, the behavior is undefined; otherwise, the result is processed as appropriate.

## 19.5 Error directive

[cpp.error]

- <sup>1</sup> A preprocessing directive of the form

**# error** *pp-tokens<sub>opt</sub> new-line*

causes the implementation to produce a diagnostic message that includes the specified sequence of preprocessing tokens, and renders the program ill-formed.

## 19.6 Pragma directive

[cpp.pragma]

- <sup>1</sup> A preprocessing directive of the form

**# pragma** *pp-tokens<sub>opt</sub> new-line*

causes the implementation to behave in an implementation-defined manner. The behavior might cause translation to fail or cause the translator or the resulting program to behave in a non-conforming manner. Any pragma that is not recognized by the implementation is ignored.

## 19.7 Null directive

[cpp.null]

- <sup>1</sup> A preprocessing directive of the form

**# new-line**

has no effect.

## 19.8 Predefined macro names

[cpp.predefined]

- <sup>1</sup> The following macro names shall be defined by the implementation:

**\_\_cplusplus**

The integer literal 201703L.<sup>152</sup>

**\_\_DATE\_\_**

The date of translation of the source file: a character string literal of the form "Mmm dd yyyy", where the names of the months are the same as those generated by the **asctime** function, and the first character of **dd** is a space character if the value is less than 10. If the date of translation is not available, an implementation-defined valid date shall be supplied.

<sup>152</sup>) It is intended that future versions of this International Standard will replace the value of this macro with a greater value. Non-conforming compilers should use a value with at most five decimal digits.

`__FILE__`

The presumed name of the current source file (a character string literal).<sup>153</sup>

`__LINE__`

The presumed line number (within the current source file) of the current source line (an integer literal).<sup>154</sup>

`__STDC_HOSTED__`

The integer literal 1 if the implementation is a hosted implementation or the integer literal 0 if it is not.

`__STDCPP_DEFAULT_NEW_ALIGNMENT__`

An integer literal of type `std::size_t` whose value is the alignment guaranteed by a call to `operator new(std::size_t)` or `operator new[](std::size_t)`. [*Note: Larger alignments will be passed to `operator new(std::size_t, std::align_val_t)`, etc. (8.3.4). — end note*]

`__TIME__`

The time of translation of the source file: a character string literal of the form "`hh:mm:ss`" as in the time generated by the `asctime` function. If the time of translation is not available, an implementation-defined valid time shall be supplied.

- 2 The following macro names are conditionally defined by the implementation:

`__STDC__`

Whether `__STDC__` is predefined and if so, what its value is, are implementation-defined.

`__STDC_MB_MIGHT_NEQ_WC__`

The integer literal 1, intended to indicate that, in the encoding for `wchar_t`, a member of the basic character set need not have a code value equal to its value when used as the lone character in an ordinary character literal.

`__STDC_VERSION__`

Whether `__STDC_VERSION__` is predefined and if so, what its value is, are implementation-defined.

`__STDC_ISO_10646__`

An integer literal of the form `yyyymmL` (for example, `199712L`). If this symbol is defined, then every character in the Unicode required set, when stored in an object of type `wchar_t`, has the same value as the short identifier of that character. The *Unicode required set* consists of all the characters that are defined by ISO/IEC 10646, along with all amendments and technical corrigenda as of the specified year and month.

`__STDCPP_STRICT_POINTER_SAFETY__`

Defined, and has the value integer literal 1, if and only if the implementation has strict pointer safety (6.7.4.3).

`__STDCPP_THREADS__`

Defined, and has the value integer literal 1, if and only if a program can have more than one thread of execution (4.7).

- 3 The values of the predefined macros (except for `__FILE__` and `__LINE__`) remain constant throughout the translation unit.
- 4 If any of the pre-defined macro names in this subclause, or the identifier `defined`, is the subject of a `#define` or a `#undef` preprocessing directive, the behavior is undefined. Any other predefined macro names shall begin with a leading underscore followed by an uppercase letter or a second underscore.

153) The presumed source file name can be changed by the `#line` directive.

154) The presumed line number can be changed by the `#line` directive.

## 19.9 Pragma operator

[cpp.pragma.op]

- <sup>1</sup> A unary operator expression of the form:

```
_Pragma (string-literal)
```

is processed as follows: The string literal is *destringized* by deleting the L prefix, if present, deleting the leading and trailing double-quotes, replacing each escape sequence `\` by a double-quote, and replacing each escape sequence `\\` by a single backslash. The resulting sequence of characters is processed through translation phase 3 to produce preprocessing tokens that are executed as if they were the *pp-tokens* in a pragma directive. The original four preprocessing tokens in the unary operator expression are removed.

- <sup>2</sup> [ *Example*:

```
#pragma listing on "..\listing.dir"
```

can also be expressed as:

```
_Pragma ("listing on \"..\listing.dir\"")
```

The latter form is processed in the same way whether it appears literally as shown, or results from macro replacement, as in:

```
#define LISTING(x) PRAGMA(listing on #x)
#define PRAGMA(x) _Pragma(#x)
```

```
LISTING(..\listing.dir)
```

— *end example*]

## 20 Library introduction

[library]

### 20.1 General

[library.general]

- <sup>1</sup> This Clause describes the contents of the *C++ standard library*, how a well-formed C++ program makes use of the library, and how a conforming implementation may provide the entities in the library.
- <sup>2</sup> The following subclauses describe the definitions (20.3), method of description (20.4), and organization (20.5.1) of the library. Clause 20.5, Clauses 21 through 33, and Annex D specify the contents of the library, as well as library requirements and constraints on both well-formed C++ programs and conforming implementations.
- <sup>3</sup> Detailed specifications for each of the components in the library are in Clauses 21–33, as shown in Table 15.

Table 15 — Library categories

| Clause | Category                    |
|--------|-----------------------------|
| 21     | Language support library    |
| 22     | Diagnostics library         |
| 23     | General utilities library   |
| 24     | Strings library             |
| 25     | Localization library        |
| 26     | Containers library          |
| 27     | Iterators library           |
| 28     | Algorithms library          |
| 29     | Numerics library            |
| 30     | Input/output library        |
| 31     | Regular expressions library |
| 32     | Atomic operations library   |
| 33     | Thread support library      |

- <sup>4</sup> The language support library (Clause 21) provides components that are required by certain parts of the C++ language, such as memory allocation (8.3.4, 8.3.5) and exception processing (Clause 18).
- <sup>5</sup> The diagnostics library (Clause 22) provides a consistent framework for reporting errors in a C++ program, including predefined exception classes.
- <sup>6</sup> The general utilities library (Clause 23) includes components used by other library elements, such as a predefined storage allocator for dynamic storage management (6.7.4), and components used as infrastructure in C++ programs, such as tuples, function wrappers, and time facilities.
- <sup>7</sup> The strings library (Clause 24) provides support for manipulating text represented as sequences of type `char`, sequences of type `char16_t`, sequences of type `char32_t`, sequences of type `wchar_t`, and sequences of any other character-like type.
- <sup>8</sup> The localization library (Clause 25) provides extended internationalization support for text processing.
- <sup>9</sup> The containers (Clause 26), iterators (Clause 27), and algorithms (Clause 28) libraries provide a C++ program with access to a subset of the most widely used algorithms and data structures.
- <sup>10</sup> The numerics library (Clause 29) provides numeric algorithms and complex number components that extend support for numeric processing. The `valarray` component provides support for *n*-at-a-time processing, potentially implemented as parallel operations on platforms that support such processing. The random

number component provides facilities for generating pseudo-random numbers.

- <sup>11</sup> The input/output library (Clause 30) provides the `iostream` components that are the primary mechanism for C++ program input and output. They can be used with other elements of the library, particularly strings, locales, and iterators.
- <sup>12</sup> The regular expressions library (Clause 31) provides regular expression matching and searching.
- <sup>13</sup> The atomic operations library (Clause 32) allows more fine-grained concurrent access to shared data than is possible with locks.
- <sup>14</sup> The thread support library (Clause 33) provides components to create and manage threads, including mutual exclusion and interthread communication.

## 20.2 The C standard library

[library.c]

- <sup>1</sup> The C++ standard library also makes available the facilities of the C standard library, suitably adjusted to ensure static type safety.
- <sup>2</sup> The descriptions of many library functions rely on the C standard library for the semantics of those functions. In some cases, the signatures specified in this International Standard may be different from the signatures in the C standard library, and additional overloads may be declared in this International Standard, but the behavior and the preconditions (including any preconditions implied by the use of an ISO C `restrict` qualifier) are the same unless otherwise stated.

## 20.3 Definitions

[definitions]

- <sup>1</sup> [Note: Clause 3 defines additional terms used elsewhere in this International Standard. — end note]

### 20.3.1

[defns.arbitrary.stream]

#### arbitrary-positional stream

a stream (described in Clause 30) that can seek to any integral position within the length of the stream

[Note: Every arbitrary-positional stream is also a repositional stream. — end note]

### 20.3.2

[defns.character]

#### character

{Clauses 24, 25, 30, and 31} any object which, when treated sequentially, can represent text

[Note: The term does not mean only `char`, `char16_t`, `char32_t`, and `wchar_t` objects, but any value that can be represented by a type that provides the definitions specified in these Clauses. — end note]

### 20.3.3

[defns.character.container]

#### character container type

a class or a type used to represent a *character*

[Note: It is used for one of the template parameters of the `string`, `iostream`, and regular expression class templates. A character container type is a POD (6.9) type. — end note]

### 20.3.4

[defns.comparison]

#### comparison function

an operator function (16.5) for any of the equality (8.10) or relational (8.9) operators

### 20.3.5

[defns.component]

#### component

a group of library entities directly related as members, parameters, or return types

[Note: For example, the class template `basic_string` and the non-member function templates that operate on strings are referred to as the *string component*. — end note]

**20.3.6** [defns.const.subexpr]**constant subexpression**

an expression whose evaluation as subexpression of a *conditional-expression* CE (8.16) would not prevent CE from being a core constant expression (8.20)

**20.3.7** [defns.deadlock]**deadlock**

one or more threads are unable to continue execution because each is blocked waiting for one or more of the others to satisfy some condition

**20.3.8** [defns.default.behavior.impl]**default behavior**

⟨implementation⟩ any specific behavior provided by the implementation, within the scope of the *required behavior*

**20.3.9** [defns.default.behavior.func]**default behavior**

⟨specification⟩ a description of *replacement function* and *handler function* semantics

**20.3.10** [defns.direct-non-list-init]**direct-non-list-initialization**

a direct-initialization (11.6) that is not list-initialization (11.6.4)

**20.3.11** [defns.handler]**handler function**

a *non-reserved function* whose definition may be provided by a C++ program

[ *Note*: A C++ program may designate a handler function at various points in its execution by supplying a pointer to the function when calling any of the library functions that install handler functions (Clause 21). — *end note* ]

**20.3.12** [defns.iostream.templates]**iostream class templates**

templates, defined in Clause 30, that take two template arguments

[ *Note*: The arguments are named `charT` and `traits`. The argument `charT` is a character container class, and the argument `traits` is a class which defines additional characteristics and functions of the character type represented by `charT` necessary to implement the iostream class templates. — *end note* ]

**20.3.13** [defns.modifier]**modifier function**

a class member function (12.2.1) other than a constructor, assignment operator, or destructor that alters the state of an object of the class

**20.3.14** [defns.move.assign]**move assignment**

assignment of an rvalue of some object type to a modifiable lvalue of the same type

**20.3.15** [defns.move.constr]**move construction**

direct-initialization of an object of some type with an rvalue of the same type

**20.3.16** [defns.ntcts]**NTCTS**

a sequence of values that have *character type* that precede the terminating null character type value `charT()`



**20.3.17** [defns.observer]**observer function**

a class member function (12.2.1) that accesses the state of an object of the class but does not alter that state  
 [ *Note*: Observer functions are specified as **const** member functions (12.2.2.1). — *end note* ]

**20.3.18** [defns.referenceable]**referenceable type**

an object type, a function type that does not have cv-qualifiers or a *ref-qualifier*, or a reference type [ *Note*: The term describes a type to which a reference can be created, including reference types. — *end note* ]

**20.3.19** [defns.replacement]**replacement function**

a *non-reserved function* whose definition is provided by a C++ program

[ *Note*: Only one definition for such a function is in effect for the duration of the program's execution, as the result of creating the program (5.2) and resolving the definitions of all translation units (6.5). — *end note* ]

**20.3.20** [defns.repositional.stream]**repositional stream**

a stream (described in Clause 30) that can seek to a position that was previously encountered

**20.3.21** [defns.required.behavior]**required behavior**

a description of *replacement function* and *handler function* semantics applicable to both the behavior provided by the implementation and the behavior of any such function definition in the program

[ *Note*: If such a function defined in a C++ program fails to meet the required behavior when it executes, the behavior is undefined. — *end note* ]

**20.3.22** [defns.reserved.function]**reserved function**

a function, specified as part of the C++ standard library, that must be defined by the implementation

[ *Note*: If a C++ program provides a definition for any reserved function, the results are undefined. — *end note* ]

**20.3.23** [defns.stable]**stable algorithm**

an algorithm that preserves, as appropriate to the particular algorithm, the order of elements

[ *Note*: Requirements for stable algorithms are given in 20.5.5.7. — *end note* ]

**20.3.24** [defns.traits]**traits class**

a class that encapsulates a set of types and functions necessary for class templates and function templates to manipulate objects of types for which they are instantiated

**20.3.25** [defns.valid]**valid but unspecified state**

a value of an object that is not specified except that the object's invariants are met and operations on the object behave as specified for its type

[ *Example*: If an object `x` of type `std::vector<int>` is in a valid but unspecified state, `x.empty()` can be called unconditionally, and `x.front()` can be called only if `x.empty()` returns `false`. — *end example* ]

## 20.4 Method of description (Informative) [description]

- <sup>1</sup> This subclause describes the conventions used to specify the C++ standard library. 20.4.1 describes the structure of the normative Clauses 21 through 33 and Annex D. 20.4.2 describes other editorial conventions.

### 20.4.1 Structure of each clause [structure]

#### 20.4.1.1 Elements [structure.elements]

- <sup>1</sup> Each library clause contains the following elements, as applicable:<sup>155</sup>

- (1.1) — Summary
- (1.2) — Requirements
- (1.3) — Detailed specifications
- (1.4) — References to the C standard library

#### 20.4.1.2 Summary [structure.summary]

- <sup>1</sup> The Summary provides a synopsis of the category, and introduces the first-level subclauses. Each subclause also provides a summary, listing the headers specified in the subclause and the library entities provided in each header.
- <sup>2</sup> Paragraphs labeled “Note(s):” or “Example(s):” are informative, other paragraphs are normative.
- <sup>3</sup> The contents of the summary and the detailed specifications include:
  - (3.1) — macros
  - (3.2) — values
  - (3.3) — types
  - (3.4) — classes and class templates
  - (3.5) — functions and function templates
  - (3.6) — objects

#### 20.4.1.3 Requirements [structure.requirements]

- <sup>1</sup> Requirements describe constraints that shall be met by a C++ program that extends the standard library. Such extensions are generally one of the following:
  - (1.1) — Template arguments
  - (1.2) — Derived classes
  - (1.3) — Containers, iterators, and algorithms that meet an interface convention
- <sup>2</sup> The string and iostream components use an explicit representation of operations required of template arguments. They use a class template `char_traits` to define these constraints.
- <sup>3</sup> Interface convention requirements are stated as generally as possible. Instead of stating “class X has to define a member function `operator++()`”, the interface requires “for any object `x` of class X, `++x` is defined”. That is, whether the operator is a member is unspecified.
- <sup>4</sup> Requirements are stated in terms of well-defined expressions that define valid terms of the types that satisfy the requirements. For every set of well-defined expression requirements there is a table that specifies an initial set of the valid expressions and their semantics. Any generic algorithm (Clause 28) that uses the well-defined expression requirements is described in terms of the valid expressions for its template type parameters.
- <sup>5</sup> Template argument requirements are sometimes referenced by name. See 20.4.2.1.

<sup>155</sup>) To save space, items that do not apply to a Clause are omitted. For example, if a Clause does not specify any requirements, there will be no “Requirements” subclause.

- <sup>6</sup> In some cases the semantic requirements are presented as C++ code. Such code is intended as a specification of equivalence of a construct to another construct, not necessarily as the way the construct must be implemented.<sup>156</sup>

#### 20.4.1.4 Detailed specifications

[structure.specifications]

- <sup>1</sup> The detailed specifications each contain the following elements:

- (1.1) — name and brief description
- (1.2) — synopsis (class definition or function declaration, as appropriate)
- (1.3) — restrictions on template arguments, if any
- (1.4) — description of class invariants
- (1.5) — description of function semantics

- <sup>2</sup> Descriptions of class member functions follow the order (as appropriate):<sup>157</sup>

- (2.1) — constructor(s) and destructor
- (2.2) — copying, moving & assignment functions
- (2.3) — comparison functions
- (2.4) — modifier functions
- (2.5) — observer functions
- (2.6) — operators and other non-member functions

- <sup>3</sup> Descriptions of function semantics contain the following elements (as appropriate):<sup>158</sup>

- (3.1) — *Requires*: the preconditions for calling the function
- (3.2) — *Effects*: the actions performed by the function
- (3.3) — *Synchronization*: the synchronization operations (4.7) applicable to the function
- (3.4) — *Postconditions*: the observable results established by the function
- (3.5) — *Returns*: a description of the value(s) returned by the function
- (3.6) — *Throws*: any exceptions thrown by the function, and the conditions that would cause the exception
- (3.7) — *Complexity*: the time and/or space complexity of the function
- (3.8) — *Remarks*: additional semantic constraints on the function
- (3.9) — *Error conditions*: the error conditions for error codes reported by the function

- <sup>4</sup> Whenever the *Effects*: element specifies that the semantics of some function **F** are *Equivalent to* some code sequence, then the various elements are interpreted as follows. If **F**'s semantics specifies a *Requires*: element, then that requirement is logically imposed prior to the *equivalent-to* semantics. Next, the semantics of the code sequence are determined by the *Requires*:, *Effects*:, *Synchronization*:, *Postconditions*:, *Returns*:, *Throws*:, *Complexity*:, *Remarks*:, and *Error conditions*: specified for the function invocations contained in the code sequence. The value returned from **F** is specified by **F**'s *Returns*: element, or if **F** has no *Returns*: element, a non-void return from **F** is specified by the **return** statements in the code sequence. If **F**'s semantics contains a *Throws*:, *Postconditions*:, or *Complexity*: element, then that supersedes any occurrences of that element in the code sequence.

<sup>156</sup>) Although in some cases the code given is unambiguously the optimum implementation.

<sup>157</sup>) To save space, items that do not apply to a class are omitted. For example, if a class does not specify any comparison functions, there will be no "Comparison functions" subclause.

<sup>158</sup>) To save space, items that do not apply to a function are omitted. For example, if a function does not specify any further preconditions, there will be no *Requires*: paragraph.

- <sup>5</sup> For non-reserved replacement and handler functions, Clause 21 specifies two behaviors for the functions in question: their required and default behavior. The *default behavior* describes a function definition provided by the implementation. The *required behavior* describes the semantics of a function definition provided by either the implementation or a C++ program. Where no distinction is explicitly made in the description, the behavior described is the required behavior.
- <sup>6</sup> If the formulation of a complexity requirement calls for a negative number of operations, the actual requirement is zero operations.<sup>159</sup>
- <sup>7</sup> Complexity requirements specified in the library clauses are upper bounds, and implementations that provide better complexity guarantees satisfy the requirements.
- <sup>8</sup> Error conditions specify conditions where a function may fail. The conditions are listed, together with a suitable explanation, as the `enum class errc` constants (22.5).

#### 20.4.1.5 C library

[structure.see.also]

- <sup>1</sup> Paragraphs labeled “SEE ALSO:” contain cross-references to the relevant portions of this International Standard and the ISO C standard.

#### 20.4.2 Other conventions

[conventions]

- <sup>1</sup> This subclause describes several editorial conventions used to describe the contents of the C++ standard library. These conventions are for describing implementation-defined types (20.4.2.1), and member functions (20.4.2.2).

##### 20.4.2.1 Type descriptions

[type.descriptions]

###### 20.4.2.1.1 General

[type.descriptions.general]

- <sup>1</sup> The Requirements subclauses may describe names that are used to specify constraints on template arguments.<sup>160</sup> These names are used in library Clauses to describe the types that may be supplied as arguments by a C++ program when instantiating template components from the library.
- <sup>2</sup> Certain types defined in Clause 30 are used to describe implementation-defined types. They are based on other types, but with added constraints.

###### 20.4.2.1.2 Exposition-only types

[expos.only.types]

- <sup>1</sup> Several types defined in Clauses 21 through 33 and Annex D that are used as function parameter or return types are defined for the purpose of exposition only in order to capture their language linkage. The declarations of such types are followed by a comment ending in *exposition only*. [Example:

```
namespace std {
 extern "C" using some-handler = int(int, void*, double); // exposition only
}
```

The type placeholder *some-handler* can now be used to specify a function that takes a callback parameter with C language linkage. — *end example*]

###### 20.4.2.1.3 Enumerated types

[enumerated.types]

- <sup>1</sup> Several types defined in Clause 30 are *enumerated types*. Each enumerated type may be implemented as an enumeration or as a synonym for an enumeration.<sup>161</sup>
- <sup>2</sup> The enumerated type *enumerated* can be written:

```
enum enumerated { V0, V1, V2, V3, };
```

<sup>159</sup>) This simplifies the presentation of complexity requirements in some cases.

<sup>160</sup>) Examples from 20.5.3 include: `EqualityComparable`, `LessThanComparable`, `CopyConstructible`. Examples from 27.2 include: `InputIterator`, `ForwardIterator`.

<sup>161</sup>) Such as an integer type, with constant integer values (6.9.1).

```

inline const enumerated C0(V0);
inline const enumerated C1(V1);
inline const enumerated C2(V2);
inline const enumerated C3(V3);
.....

```

- <sup>3</sup> Here, the names  $C_0$ ,  $C_1$ , etc. represent *enumerated elements* for this particular enumerated type. All such elements have distinct values.

#### 20.4.2.1.4 Bitmask types

[bitmask.types]

- <sup>1</sup> Several types defined in Clauses 21 through 33 and Annex D are *bitmask types*. Each bitmask type can be implemented as an enumerated type that overloads certain operators, as an integer type, or as a bitset (23.9.2).
- <sup>2</sup> The bitmask type *bitmask* can be written:

```

// For exposition only.
// int_type is an integral type capable of representing all values of the bitmask type.
enum bitmask : int_type {
 V0 = 1 << 0, V1 = 1 << 1, V2 = 1 << 2, V3 = 1 << 3,
};

inline constexpr bitmask C0(V0);
inline constexpr bitmask C1(V1);
inline constexpr bitmask C2(V2);
inline constexpr bitmask C3(V3);
.....

constexpr bitmask operator&(bitmask X, bitmask Y) {
 return static_cast<bitmask>(
 static_cast<int_type>(X) & static_cast<int_type>(Y));
}
constexpr bitmask operator|(bitmask X, bitmask Y) {
 return static_cast<bitmask>(
 static_cast<int_type>(X) | static_cast<int_type>(Y));
}
constexpr bitmask operator^(bitmask X, bitmask Y){
 return static_cast<bitmask>(
 static_cast<int_type>(X) ^ static_cast<int_type>(Y));
}
constexpr bitmask operator~(bitmask X){
 return static_cast<bitmask>(~static_cast<int_type>(X));
}
bitmask&& operator&=(bitmask&& X, bitmask Y){
 X = X & Y; return X;
}
bitmask&& operator|=(bitmask&& X, bitmask Y) {
 X = X | Y; return X;
}
bitmask&& operator^=(bitmask&& X, bitmask Y) {
 X = X ^ Y; return X;
}

```

- <sup>3</sup> Here, the names  $C_0$ ,  $C_1$ , etc. represent *bitmask elements* for this particular bitmask type. All such elements have distinct, nonzero values such that, for any pair  $C_i$  and  $C_j$  where  $i \neq j$ ,  $C_i \& C_i$  is nonzero and  $C_i \& C_j$  is zero. Additionally, the value 0 is used to represent an *empty bitmask*, in which no bitmask elements are set.

<sup>4</sup> The following terms apply to objects and values of bitmask types:

- (4.1) — To *set* a value  $Y$  in an object  $X$  is to evaluate the expression  $X \mid= Y$ .
- (4.2) — To *clear* a value  $Y$  in an object  $X$  is to evaluate the expression  $X \&= \sim Y$ .
- (4.3) — The value  $Y$  *is set* in the object  $X$  if the expression  $X \& Y$  is nonzero.

#### 20.4.2.1.5 Character sequences

[character.seq]

<sup>1</sup> The C standard library makes widespread use of characters and character sequences that follow a few uniform conventions:

- (1.1) — A *letter* is any of the 26 lowercase or 26 uppercase letters in the basic execution character set.
- (1.2) — The *decimal-point character* is the (single-byte) character used by functions that convert between a (single-byte) character sequence and a value of one of the floating-point types. It is used in the character sequence to denote the beginning of a fractional part. It is represented in Clauses 21 through 33 and Annex D by a period, '.', which is also its value in the "C" locale, but may change during program execution by a call to `setlocale(int, const char*)`,<sup>162</sup> or by a change to a `locale` object, as described in Clauses 25.3 and 30.
- (1.3) — A *character sequence* is an array object (11.3.4)  $A$  that can be declared as  $TA[N]$ , where  $T$  is any of the types `char`, `unsigned char`, or `signed char` (6.9.1), optionally qualified by any combination of `const` or `volatile`. The initial elements of the array have defined contents up to and including an element determined by some predicate. A character sequence can be designated by a pointer value  $S$  that points to its first element.

##### 20.4.2.1.5.1 Byte strings

[byte.strings]

- <sup>1</sup> A *null-terminated byte string*, or NTBS, is a character sequence whose highest-addressed element with defined content has the value zero (the *terminating null* character); no other element in the sequence has the value zero.<sup>163</sup>
- <sup>2</sup> The *length* of an NTBS is the number of elements that precede the terminating null character. An *empty* NTBS has a length of zero.
- <sup>3</sup> The *value* of an NTBS is the sequence of values of the elements up to and including the terminating null character.
- <sup>4</sup> A *static* NTBS is an NTBS with static storage duration.<sup>164</sup>

##### 20.4.2.1.5.2 Multibyte strings

[multibyte.strings]

- <sup>1</sup> A *null-terminated multibyte string*, or NTMBS, is an NTBS that constitutes a sequence of valid multibyte characters, beginning and ending in the initial shift state.<sup>165</sup>
- <sup>2</sup> A *static* NTMBS is an NTMBS with static storage duration.

#### 20.4.2.2 Functions within classes

[functions.within.classes]

- <sup>1</sup> For the sake of exposition, Clauses 21 through 33 and Annex D do not describe copy/move constructors, assignment operators, or (non-virtual) destructors with the same apparent semantics as those that can be generated by default (15.1, 15.4, 15.8). It is unspecified whether the implementation provides explicit definitions for such member function signatures, or for virtual destructors that can be generated by default.

<sup>162</sup> declared in `<locale>` (25.5).

<sup>163</sup> Many of the objects manipulated by function signatures declared in `<cstring>` (24.5) are character sequences or NTBSs. The size of some of these character sequences is limited by a length value, maintained separately from the character sequence.

<sup>164</sup> A string literal, such as `"abc"`, is a static NTBS.

<sup>165</sup> An NTBS that contains characters only from the basic execution character set is also an NTMBS. Each multibyte character then consists of a single byte.

- <sup>2</sup> For the sake of exposition, the library clauses sometimes annotate constructors with *EXPLICIT*. Such a constructor is conditionally declared as either explicit or non-explicit (15.3.1). [ *Note*: This is typically implemented by declaring two such constructors, of which at most one participates in overload resolution. — *end note* ]

#### 20.4.2.3 Private members

[objects.within.classes]

- <sup>1</sup> Clauses 21 through 33 and Annex D do not specify the representation of classes, and intentionally omit specification of class members (12.2). An implementation may define static or non-static class members, or both, as needed to implement the semantics of the member functions specified in Clauses 21 through 33 and Annex D.
- <sup>2</sup> For the sake of exposition, some subclauses provide representative declarations, and semantic requirements, for private members of classes that meet the external specifications of the classes. The declarations for such members are followed by a comment that ends with *exposition only*, as in:

```
streambuf* sb; // exposition only
```

- <sup>3</sup> An implementation may use any technique that provides equivalent observable behavior.

### 20.5 Library-wide requirements

[requirements]

- <sup>1</sup> This subclause specifies requirements that apply to the entire C++ standard library. Clauses 21 through 33 and Annex D specify the requirements of individual entities within the library.
- <sup>2</sup> Requirements specified in terms of interactions between threads do not apply to programs having only a single thread of execution.
- <sup>3</sup> Within this subclause, 20.5.1 describes the library's contents and organization, 20.5.2 describes how well-formed C++ programs gain access to library entities, 20.5.3 describes constraints on types and functions used with the C++ standard library, 20.5.4 describes constraints on well-formed C++ programs, and 20.5.5 describes constraints on conforming implementations.

#### 20.5.1 Library contents and organization

[organization]

- <sup>1</sup> 20.5.1.1 describes the entities and macros defined in the C++ standard library. 20.5.1.2 lists the standard library headers and some constraints on those headers. 20.5.1.3 lists requirements for a freestanding implementation of the C++ standard library.

##### 20.5.1.1 Library contents

[contents]

- <sup>1</sup> The C++ standard library provides definitions for the entities and macros described in the synopses of the C++ standard library headers (20.5.1.2).
- <sup>2</sup> All library entities except `operator new` and `operator delete` are defined within the namespace `std` or namespaces nested within namespace `std`.<sup>166</sup> It is unspecified whether names declared in a specific namespace are declared directly in that namespace or in an inline namespace inside that namespace.<sup>167</sup>
- <sup>3</sup> Whenever a name `x` defined in the standard library is mentioned, the name `x` is assumed to be fully qualified as `::std::x`, unless explicitly described otherwise. For example, if the *Effects*: section for library function `F` is described as calling library function `G`, the function `::std::G` is meant.

##### 20.5.1.2 Headers

[headers]

- <sup>1</sup> Each element of the C++ standard library is declared or defined (as appropriate) in a *header*.<sup>168</sup>

<sup>166</sup> The C standard library headers (Annex D.5) also define names within the global namespace, while the C++ headers for C library facilities (20.5.1.2) may also define names within the global namespace.

<sup>167</sup> This gives implementers freedom to use inline namespaces to support multiple configurations of the library.

<sup>168</sup> A header is not necessarily a source file, nor are the sequences delimited by `<` and `>` in header names necessarily valid source file names (19.2).



- <sup>2</sup> The C++ standard library provides the *C++ library headers*, shown in Table 16.

Table 16 — C++ library headers

|                      |                    |                    |                 |
|----------------------|--------------------|--------------------|-----------------|
| <algorithm>          | <future>           | <numeric>          | <strstream>     |
| <any>                | <initializer_list> | <optional>         | <system_error>  |
| <array>              | <iomanip>          | <ostream>          | <thread>        |
| <atomic>             | <ios>              | <queue>            | <tuple>         |
| <bitset>             | <iosfwd>           | <random>           | <type_traits>   |
| <chrono>             | <iostream>         | <ratio>            | <typeindex>     |
| <codecvt>            | <istream>          | <regex>            | <typeinfo>      |
| <complex>            | <iterator>         | <scoped_allocator> | <unordered_map> |
| <condition_variable> | <limits>           | <set>              | <unordered_set> |
| <deque>              | <list>             | <shared_mutex>     | <utility>       |
| <exception>          | <locale>           | <sstream>          | <valarray>      |
| <execution>          | <map>              | <stack>            | <variant>       |
| <filesystem>         | <memory>           | <stdexcept>        | <vector>        |
| <forward_list>       | <memory_resource>  | <streambuf>        |                 |
| <fstream>            | <mutex>            | <string>           |                 |
| <functional>         | <new>              | <string_view>      |                 |

- <sup>3</sup> The facilities of the C standard library are provided in the additional headers shown in Table 17.<sup>169</sup>

Table 17 — C++ headers for C library facilities

|            |             |             |           |           |
|------------|-------------|-------------|-----------|-----------|
| <cassert>  | <cinttypes> | <csignal>   | <cstdio>  | <cwchar>  |
| <ccomplex> | <ciso646>   | <cstdalign> | <cstdlib> | <cwctype> |
| <cctype>   | <climits>   | <cstdarg>   | <cstring> |           |
| <cerrno>   | <locale>    | <cstdbool>  | <ctgmath> |           |
| <cfenv>    | <cmath>     | <cstddef>   | <ctime>   |           |
| <cfloat>   | <csetjmp>   | <cstdint>   | <cuchar>  |           |

- <sup>4</sup> Except as noted in Clauses 20 through 33 and Annex D, the contents of each header *cname* is the same as that of the corresponding header *name.h* as specified in the C standard library (Clause 2). In the C++ standard library, however, the declarations (except for names which are defined as macros in C) are within namespace scope (6.3.6) of the namespace **std**. It is unspecified whether these names (including any overloads added in Clauses 21 through 33 and Annex D) are first declared within the global namespace scope and are then injected into namespace **std** by explicit *using-declarations* (10.3.3).
- <sup>5</sup> Names which are defined as macros in C shall be defined as macros in the C++ standard library, even if C grants license for implementation as functions. [ *Note:* The names defined as macros in C include the following: **assert**, **offsetof**, **setjmp**, **va\_arg**, **va\_end**, and **va\_start**. — *end note* ]
- <sup>6</sup> Names that are defined as functions in C shall be defined as functions in the C++ standard library.<sup>170</sup>
- <sup>7</sup> Identifiers that are keywords or operators in C++ shall not be defined as macros in C++ standard library headers.<sup>171</sup>

<sup>169</sup> It is intentional that there is no C++ header for any of these C headers: **<stdatomic.h>**, **<stdnoreturn.h>**, **<threads.h>**.

<sup>170</sup> This disallows the practice, allowed in C, of providing a masking macro in addition to the function prototype. The only way to achieve equivalent inline behavior in C++ is to provide a definition as an extern inline function.

<sup>171</sup> In particular, including the standard header **<iso646.h>** or **<ciso646>** has no effect.



- <sup>8</sup> [D.5](#), C standard library headers, describes the effects of using the *name.h* (C header) form in a C++ program.<sup>172</sup>
- <sup>9</sup> Annex K of the C standard describes a large number of functions, with associated types and macros, which “promote safer, more secure programming” than many of the traditional C library functions. The names of the functions have a suffix of *\_s*; most of them provide the same service as the C library function with the unsuffixed name, but generally take an additional argument whose value is the size of the result array. If any C++ header is included, it is implementation-defined whether any of these names is declared in the global namespace. (None of them is declared in namespace *std*.)
- <sup>10</sup> Table 18 lists the Annex K names that may be declared in some header. These names are also subject to the restrictions of [20.5.4.3.2](#).

Table 18 — C standard Annex K names

|                                   |                                       |                           |                         |
|-----------------------------------|---------------------------------------|---------------------------|-------------------------|
| <code>abort_handler_s</code>      | <code>mbstowcs_s</code>               | <code>strncat_s</code>    | <code>vswscanf_s</code> |
| <code>asctime_s</code>            | <code>memcpy_s</code>                 | <code>strncpy_s</code>    | <code>vwprintf_s</code> |
| <code>bsearch_s</code>            | <code>memmove_s</code>                | <code>strtok_s</code>     | <code>vscanf_s</code>   |
| <code>constraint_handler_t</code> | <code>memset_s</code>                 | <code>swprintf_s</code>   | <code>wcrtomb_s</code>  |
| <code>ctime_s</code>              | <code>printf_s</code>                 | <code>swscanf_s</code>    | <code>wcscat_s</code>   |
| <code>errno_t</code>              | <code>qsort_s</code>                  | <code>tmpfile_s</code>    | <code>wscpy_s</code>    |
| <code>fopen_s</code>              | <code>RSIZE_MAX</code>                | <code>TMP_MAX_S</code>    | <code>wcsncat_s</code>  |
| <code>fprintf_s</code>            | <code>rsize_t</code>                  | <code>tmpnam_s</code>     | <code>wcsncpy_s</code>  |
| <code>freopen_s</code>            | <code>scanf_s</code>                  | <code>vfprintf_s</code>   | <code>wcsnlen_s</code>  |
| <code>fscanf_s</code>             | <code>set_constraint_handler_s</code> | <code>vfscanf_s</code>    | <code>wcrtombs_s</code> |
| <code>fwprintf_s</code>           | <code>snprintf_s</code>               | <code>vwprintf_s</code>   | <code>wcstok_s</code>   |
| <code>fwscanf_s</code>            | <code>snwprintf_s</code>              | <code>vwscanf_s</code>    | <code>wcstombs_s</code> |
| <code>getenv_s</code>             | <code>sprintf_s</code>                | <code>vprintf_s</code>    | <code>wctomb_s</code>   |
| <code>gets_s</code>               | <code>sscanf_s</code>                 | <code>vscanf_s</code>     | <code>wmemcpy_s</code>  |
| <code>gmtime_s</code>             | <code>strcat_s</code>                 | <code>vsnprintf_s</code>  | <code>wmemmove_s</code> |
| <code>ignore_handler_s</code>     | <code>strcpy_s</code>                 | <code>vsnwprintf_s</code> | <code>wprintf_s</code>  |
| <code>L_tmpnam_s</code>           | <code>strerror_s</code>               | <code>vsprintf_s</code>   | <code>wscanf_s</code>   |
| <code>localtime_s</code>          | <code>strerrorlen_s</code>            | <code>vsscanf_s</code>    |                         |
| <code>mbsrtowcs_s</code>          | <code>strlen_s</code>                 | <code>vswprintf_s</code>  |                         |

### 20.5.1.3 Freestanding implementations

[compliance]

- <sup>1</sup> Two kinds of implementations are defined: *hosted* and *freestanding* ([4.1](#)). For a hosted implementation, this International Standard describes the set of available headers.
- <sup>2</sup> A freestanding implementation has an implementation-defined set of headers. This set shall include at least the headers shown in Table 19.
- <sup>3</sup> The supplied version of the header `<cstdlib>` shall declare at least the functions `abort`, `atexit`, `at_quick_exit`, `exit`, and `quick_exit` ([21.5](#)). The other headers listed in this table shall meet the same requirements as for a hosted implementation.

### 20.5.2 Using the library

[using]

#### 20.5.2.1 Overview

[using.overview]

- <sup>1</sup> This section describes how a C++ program gains access to the facilities of the C++ standard library. [20.5.2.2](#) describes effects during translation phase 4, while [20.5.2.3](#) describes effects during phase 8 ([5.2](#)).

<sup>172</sup> The `“.h”` headers dump all their names into the global namespace, whereas the newer forms keep their names in namespace *std*. Therefore, the newer forms are the preferred forms for all uses except for C++ programs which are intended to be strictly compatible with C.

Table 19 — C++ headers for freestanding implementations

| Subclause    |                           | Header(s)                      |
|--------------|---------------------------|--------------------------------|
|              |                           | <ciso646>                      |
| 21.2         | Types                     | <cstdint>                      |
| 21.3         | Implementation properties | <cfloating> <limits> <climits> |
| 21.4         | Integer types             | <stdint>                       |
| 21.5         | Start and termination     | <cstdlib>                      |
| 21.6         | Dynamic memory management | <new>                          |
| 21.7         | Type identification       | <typeinfo>                     |
| 21.8         | Exception handling        | <exception>                    |
| 21.9         | Initializer lists         | <initializer_list>             |
| 21.10        | Other runtime support     | <cstdarg>                      |
| 23.15        | Type traits               | <type_traits>                  |
| 32           | Atomics                   | <atomic>                       |
| D.4.2, D.4.3 | Deprecated headers        | <cstdalign> <cstdbool>         |

**20.5.2.2 Headers****[using.headers]**

- 1 The entities in the C++ standard library are defined in headers, whose contents are made available to a translation unit when it contains the appropriate `#include` preprocessing directive (19.2).
- 2 A translation unit may include library headers in any order (Clause 5). Each may be included more than once, with no effect different from being included exactly once, except that the effect of including either `<cassert>` or `<assert.h>` depends each time on the lexically current definition of `NDEBUG`.<sup>173</sup>
- 3 A translation unit shall include a header only outside of any declaration or definition, and shall include the header lexically before the first reference in that translation unit to any of the entities declared in that header. No diagnostic is required.

**20.5.2.3 Linkage****[using.linkage]**

- 1 Entities in the C++ standard library have external linkage (6.5). Unless otherwise specified, objects and functions have the default `extern "C++"` linkage (10.5).
- 2 Whether a name from the C standard library declared with external linkage has `extern "C"` or `extern "C++"` linkage is implementation-defined. It is recommended that an implementation use `extern "C++"` linkage for this purpose.<sup>174</sup>
- 3 Objects and functions defined in the library and required by a C++ program are included in the program prior to program startup.
- 4 See also replacement functions (20.5.4.6), runtime changes (20.5.4.7).

**20.5.3 Requirements on types and expressions****[utility.requirements]**

- 1 20.5.3.1 describes requirements on types and expressions used to instantiate templates defined in the C++ standard library. 20.5.3.2 describes the requirements on swappable types and swappable expressions. 20.5.3.3 describes the requirements on pointer-like types that support null values. 20.5.3.4 describes the requirements on hash function objects. 20.5.3.5 describes the requirements on storage allocators.

<sup>173</sup>) This is the same as the C standard library.

<sup>174</sup>) The only reliable way to declare an object or function signature from the C standard library is by including the header that declares it, notwithstanding the latitude granted in 7.1.4 of the C Standard.

**20.5.3.1 Template argument requirements****[utility.arg.requirements]**

- <sup>1</sup> The template definitions in the C++ standard library refer to various named requirements whose details are set out in Tables 20–27. In these tables, **T** is an object or reference type to be supplied by a C++ program instantiating a template; **a**, **b**, and **c** are values of type (possibly **const**) **T**; **s** and **t** are modifiable lvalues of type **T**; **u** denotes an identifier; **rv** is an rvalue of type **T**; and **v** is an lvalue of type (possibly **const**) **T** or an rvalue of type **const T**.
- <sup>2</sup> In general, a default constructor is not required. Certain container class member function signatures specify **T()** as a default argument. **T()** shall be a well-defined expression (11.6) if one of those signatures is called using the default argument (11.3.6).

Table 20 — EqualityComparable requirements [equalitycomparable]

| Expression    | Return type                | Requirement                                                                                                                                                                                                                                                                              |
|---------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>a == b</b> | convertible to <b>bool</b> | <b>==</b> is an equivalence relation, that is, it has the following properties: <ul style="list-style-type: none"> <li>— For all <b>a</b>, <b>a == a</b>.</li> <li>— If <b>a == b</b>, then <b>b == a</b>.</li> <li>— If <b>a == b</b> and <b>b == c</b>, then <b>a == c</b>.</li> </ul> |

Table 21 — LessThanComparable requirements [lessthancomparable]

| Expression      | Return type                | Requirement                                           |
|-----------------|----------------------------|-------------------------------------------------------|
| <b>a &lt; b</b> | convertible to <b>bool</b> | <b>&lt;</b> is a strict weak ordering relation (28.7) |

Table 22 — DefaultConstructible requirements [defaultconstructible]

| Expression               | Post-condition                                                           |
|--------------------------|--------------------------------------------------------------------------|
| <b>T t;</b>              | object <b>t</b> is default-initialized                                   |
| <b>T u{};</b>            | object <b>u</b> is value-initialized or aggregate-initialized            |
| <b>T()</b><br><b>T{}</b> | an object of type <b>T</b> is value-initialized or aggregate-initialized |

Table 23 — MoveConstructible requirements [moveconstructible]

| Expression                                                                                                                                                                                                                                                                   | Post-condition                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <b>T u = rv;</b>                                                                                                                                                                                                                                                             | <b>u</b> is equivalent to the value of <b>rv</b> before the construction     |
| <b>T(rv)</b>                                                                                                                                                                                                                                                                 | <b>T(rv)</b> is equivalent to the value of <b>rv</b> before the construction |
| <b>rv</b> 's state is unspecified [ <i>Note</i> : <b>rv</b> must still meet the requirements of the library component that is using it. The operations listed in those requirements must work as specified whether <b>rv</b> has been moved from or not. — <i>end note</i> ] |                                                                              |

Table 24 — CopyConstructible requirements (in addition to MoveConstructible) [copyconstructible]

| Expression            | Post-condition                                                                  |
|-----------------------|---------------------------------------------------------------------------------|
| <code>T u = v;</code> | the value of <code>v</code> is unchanged and is equivalent to <code>u</code>    |
| <code>T(v)</code>     | the value of <code>v</code> is unchanged and is equivalent to <code>T(v)</code> |

Table 25 — MoveAssignable requirements [moveassignable]

| Expression                                                                                                                                                                                                                                                                                                                                                                 | Return type         | Return value   | Post-condition                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>t = rv</code>                                                                                                                                                                                                                                                                                                                                                        | <code>T&amp;</code> | <code>t</code> | If <code>t</code> and <code>rv</code> do not refer to the same object, <code>t</code> is equivalent to the value of <code>rv</code> before the assignment |
| <code>rv</code> 's state is unspecified. [ <i>Note:</i> <code>rv</code> must still meet the requirements of the library component that is using it, whether or not <code>t</code> and <code>rv</code> refer to the same object. The operations listed in those requirements must work as specified whether <code>rv</code> has been moved from or not. — <i>end note</i> ] |                     |                |                                                                                                                                                           |

Table 26 — CopyAssignable requirements (in addition to MoveAssignable) [copyassignable]

| Expression         | Return type         | Return value   | Post-condition                                                                            |
|--------------------|---------------------|----------------|-------------------------------------------------------------------------------------------|
| <code>t = v</code> | <code>T&amp;</code> | <code>t</code> | <code>t</code> is equivalent to <code>v</code> , the value of <code>v</code> is unchanged |

Table 27 — Destructible requirements [destructible]

| Expression          | Post-condition                                                                   |
|---------------------|----------------------------------------------------------------------------------|
| <code>u.~T()</code> | All resources owned by <code>u</code> are reclaimed, no exception is propagated. |

### 20.5.3.2 Swappable requirements

[swappable.requirements]

- <sup>1</sup> This subclause provides definitions for swappable types and expressions. In these definitions, let `t` denote an expression of type `T`, and let `u` denote an expression of type `U`.
- <sup>2</sup> An object `t` is *swappable with* an object `u` if and only if:
  - (2.1) — the expressions `swap(t, u)` and `swap(u, t)` are valid when evaluated in the context described below, and
  - (2.2) — these expressions have the following effects:
    - (2.2.1) — the object referred to by `t` has the value originally held by `u` and
    - (2.2.2) — the object referred to by `u` has the value originally held by `t`.
- <sup>3</sup> The context in which `swap(t, u)` and `swap(u, t)` are evaluated shall ensure that a binary non-member function named “swap” is selected via overload resolution (16.3) on a candidate set that includes:
  - (3.1) — the two `swap` function templates defined in <utility> (23.2) and
  - (3.2) — the lookup set produced by argument-dependent lookup (6.4.2).

[ *Note:* If `T` and `U` are both fundamental types or arrays of fundamental types and the declarations from the

header `<utility>` are in scope, the overall lookup set described above is equivalent to that of the qualified name lookup applied to the expression `std::swap(t, u)` or `std::swap(u, t)` as appropriate. — *end note*]

[*Note:* It is unspecified whether a library component that has a swappable requirement includes the header `<utility>` to ensure an appropriate evaluation context. — *end note*]

- <sup>4</sup> An rvalue or lvalue `t` is *swappable* if and only if `t` is swappable with any rvalue or lvalue, respectively, of type `T`.
- <sup>5</sup> A type `X` satisfying any of the iterator requirements (27.2) satisfies the requirements of `ValueSwappable` if, for any dereferenceable object `x` of type `X`, `*x` is swappable.

[*Example:* User code can ensure that the evaluation of `swap` calls is performed in an appropriate context under the various conditions as follows:

```
#include <utility>

// Requires: std::forward<T>(t) shall be swappable with std::forward<U>(u).
template <class T, class U>
void value_swap(T&& t, U&& u) {
 using std::swap;
 swap(std::forward<T>(t), std::forward<U>(u)); // OK: uses “swappable with” conditions
 // for rvalues and lvalues
}

// Requires: lvalues of T shall be swappable.
template <class T>
void lv_swap(T& t1, T& t2) {
 using std::swap;
 swap(t1, t2); // OK: uses swappable conditions for
 // lvalues of type T
}

namespace N {
 struct A { int m; };
 struct Proxy { A* a; };
 Proxy proxy(A& a) { return Proxy{ &a }; }

 void swap(A& x, Proxy p) {
 std::swap(x.m, p.a->m); // OK: uses context equivalent to swappable
 // conditions for fundamental types
 }
 void swap(Proxy p, A& x) { swap(x, p); } // satisfy symmetry constraint
}

int main() {
 int i = 1, j = 2;
 lv_swap(i, j);
 assert(i == 2 && j == 1);

 N::A a1 = { 5 }, a2 = { -5 };
 value_swap(a1, proxy(a2));
 assert(a1.m == -5 && a2.m == 5);
}

— end example]
```

**20.5.3.3 NullablePointer requirements****[nullablepointer.requirements]**

- 1 A `NullablePointer` type is a pointer-like type that supports null values. A type `P` meets the requirements of `NullablePointer` if:
  - (1.1) — `P` satisfies the requirements of `EqualityComparable`, `DefaultConstructible`, `CopyConstructible`, `CopyAssignable`, and `Destructible`,
  - (1.2) — lvalues of type `P` are swappable (20.5.3.2),
  - (1.3) — the expressions shown in Table 28 are valid and have the indicated semantics, and
  - (1.4) — `P` satisfies all the other requirements of this subclause.
- 2 A value-initialized object of type `P` produces the null value of the type. The null value shall be equivalent only to itself. A default-initialized object of type `P` may have an indeterminate value. [ *Note*: Operations involving indeterminate values may cause undefined behavior. — *end note* ]
- 3 An object `p` of type `P` can be contextually converted to `bool` (Clause 7). The effect shall be as if `p != nullptr` had been evaluated in place of `p`.
- 4 No operation which is part of the `NullablePointer` requirements shall exit via an exception.
- 5 In Table 28, `u` denotes an identifier, `t` denotes a non-`const` lvalue of type `P`, `a` and `b` denote values of type (possibly `const`) `P`, and `np` denotes a value of type (possibly `const`) `std::nullptr_t`.

Table 28 — `NullablePointer` requirements **[nullablepointer]**

| Expression                                      | Return type                                   | Operational semantics                                 |
|-------------------------------------------------|-----------------------------------------------|-------------------------------------------------------|
| <code>P u(np);</code><br><code>P u = np;</code> |                                               | <i>Postconditions</i> : <code>u == nullptr</code>     |
| <code>P(np)</code>                              |                                               | <i>Postconditions</i> : <code>P(np) == nullptr</code> |
| <code>t = np</code>                             | <code>P&amp;</code>                           | <i>Postconditions</i> : <code>t == nullptr</code>     |
| <code>a != b</code>                             | contextually convertible to <code>bool</code> | <code>!(a == b)</code>                                |
| <code>a == np</code><br><code>np == a</code>    | contextually convertible to <code>bool</code> | <code>a == P()</code>                                 |
| <code>a != np</code><br><code>np != a</code>    | contextually convertible to <code>bool</code> | <code>!(a == np)</code>                               |

**20.5.3.4 Hash requirements****[hash.requirements]**

- 1 A type `H` meets the `Hash` requirements if:
  - (1.1) — it is a function object type (23.14),
  - (1.2) — it satisfies the requirements of `CopyConstructible` and `Destructible` (20.5.3.1), and
  - (1.3) — the expressions shown in Table 29 are valid and have the indicated semantics.
- 2 Given `Key` is an argument type for function objects of type `H`, in Table 29 `h` is a value of type (possibly `const`) `H`, `u` is an lvalue of type `Key`, and `k` is a value of a type convertible to (possibly `const`) `Key`.

**20.5.3.5 Allocator requirements****[allocator.requirements]**

- 1 The library describes a standard set of requirements for *allocators*, which are class-type objects that encapsulate the information about an allocation model. This information includes the knowledge of pointer types, the type of their difference, the type of the size of objects in this allocation model, as well as the memory allocation and deallocation primitives for it. All of the string types (Clause 24), containers (Clause 26) (except array), string buffers and string streams (Clause 30), and `match_results` (Clause 31) are parameterized in terms of allocators.

Table 29 — Hash requirements [hash]

| Expression  | Return type   | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>h(k)</b> | <b>size_t</b> | The value returned shall depend only on the argument <b>k</b> for the duration of the program. [ <i>Note</i> : Thus all evaluations of the expression <b>h(k)</b> with the same value for <b>k</b> yield the same result for a given execution of the program. — <i>end note</i> ]<br>[ <i>Note</i> : For two different values <b>t1</b> and <b>t2</b> , the probability that <b>h(t1)</b> and <b>h(t2)</b> compare equal should be very small, approaching 1.0 / <b>numeric_limits&lt;size_t&gt;::max()</b> . — <i>end note</i> ] |
| <b>h(u)</b> | <b>size_t</b> | Shall not modify <b>u</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

- <sup>2</sup> The class template **allocator\_traits** (23.10.8) supplies a uniform interface to all allocator types. Table 30 describes the types manipulated through allocators. Table 31 describes the requirements on allocator types and thus on types used to instantiate **allocator\_traits**. A requirement is optional if the last column of Table 31 specifies a default for a given expression. Within the standard library **allocator\_traits** template, an optional requirement that is not supplied by an allocator is replaced by the specified default expression. A user specialization of **allocator\_traits** may provide different defaults and may provide defaults for different requirements than the primary template. Within Tables 30 and 31, the use of **move** and **forward** always refers to **std::move** and **std::forward**, respectively.

Table 30 — Descriptive variable definitions

| Variable         | Definition                                                                                                                                                                                 |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>T, U, C</b>   | any <i>cv</i> -unqualified object type (6.9)                                                                                                                                               |
| <b>X</b>         | an Allocator class for type <b>T</b>                                                                                                                                                       |
| <b>Y</b>         | the corresponding Allocator class for type <b>U</b>                                                                                                                                        |
| <b>XX</b>        | the type <b>allocator_traits&lt;X&gt;</b>                                                                                                                                                  |
| <b>YY</b>        | the type <b>allocator_traits&lt;Y&gt;</b>                                                                                                                                                  |
| <b>a, a1, a2</b> | lvalues of type <b>X</b>                                                                                                                                                                   |
| <b>u</b>         | the name of a variable being declared                                                                                                                                                      |
| <b>b</b>         | a value of type <b>Y</b>                                                                                                                                                                   |
| <b>c</b>         | a pointer of type <b>C*</b> through which indirection is valid                                                                                                                             |
| <b>p</b>         | a value of type <b>XX::pointer</b> , obtained by calling <b>a1.allocate</b> , where <b>a1 == a</b>                                                                                         |
| <b>q</b>         | a value of type <b>XX::const_pointer</b> obtained by conversion from a value <b>p</b> .                                                                                                    |
| <b>w</b>         | a value of type <b>XX::void_pointer</b> obtained by conversion from a value <b>p</b>                                                                                                       |
| <b>x</b>         | a value of type <b>XX::const_void_pointer</b> obtained by conversion from a value <b>q</b> or a value <b>w</b>                                                                             |
| <b>y</b>         | a value of type <b>XX::const_void_pointer</b> obtained by conversion from a result value of <b>YY::allocate</b> , or else a value of type (possibly <b>const</b> ) <b>std::nullptr_t</b> . |
| <b>n</b>         | a value of type <b>XX::size_type</b> .                                                                                                                                                     |
| <b>Args</b>      | a template parameter pack                                                                                                                                                                  |
| <b>args</b>      | a function parameter pack with the pattern <b>Args&amp;&amp;</b>                                                                                                                           |

Table 31 — Allocator requirements

| Expression                                                                               | Return type                   | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                              | Default                                                                 |
|------------------------------------------------------------------------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| <code>X::pointer</code>                                                                  |                               |                                                                                                                                                                                                                                                    | <code>T*</code>                                                         |
| <code>X::const_pointer</code>                                                            |                               | <code>X::pointer</code> is convertible to <code>X::const_pointer</code>                                                                                                                                                                            | <code>pointer_traits&lt;X::pointer&gt;::rebind&lt;const T&gt;</code>    |
| <code>X::void_pointer</code><br><code>Y::void_pointer</code>                             |                               | <code>X::pointer</code> is convertible to <code>X::void_pointer</code> .<br><code>X::void_pointer</code> and <code>Y::void_pointer</code> are the same type.                                                                                       | <code>pointer_traits&lt;X::pointer&gt;::rebind&lt;void&gt;</code>       |
| <code>X::const_void_pointer</code><br><code>Y::const_void_pointer</code>                 |                               | <code>X::pointer</code> , <code>X::const_pointer</code> , and <code>X::void_pointer</code> are convertible to <code>X::const_void_pointer</code> .<br><code>X::const_void_pointer</code> and <code>Y::const_void_pointer</code> are the same type. | <code>pointer_traits&lt;X::pointer&gt;::rebind&lt;const void&gt;</code> |
| <code>X::value_type</code>                                                               | Identical to <code>T</code>   |                                                                                                                                                                                                                                                    |                                                                         |
| <code>X::size_type</code>                                                                | unsigned integer type         | a type that can represent the size of the largest object in the allocation model.                                                                                                                                                                  | <code>make_unsigned_t&lt;X::difference_type&gt;</code>                  |
| <code>X::difference_type</code>                                                          | signed integer type           | a type that can represent the difference between any two pointers in the allocation model.                                                                                                                                                         | <code>pointer_traits&lt;X::pointer&gt;::difference_type</code>          |
| <code>typename</code><br><code>X::template</code><br><code>rebind&lt;U&gt;::other</code> | <code>Y</code>                | For all <code>U</code> (including <code>T</code> ), <code>Y::template rebind&lt;T&gt;::other</code> is <code>X</code> .                                                                                                                            | See Note A, below.                                                      |
| <code>*p</code>                                                                          | <code>T&amp;</code>           |                                                                                                                                                                                                                                                    |                                                                         |
| <code>*q</code>                                                                          | <code>const T&amp;</code>     | <code>*q</code> refers to the same object as <code>*p</code>                                                                                                                                                                                       |                                                                         |
| <code>p-&gt;m</code>                                                                     | type of <code>T::m</code>     | <i>Requires:</i> <code>(*p).m</code> is well-defined.<br>equivalent to <code>(*p).m</code>                                                                                                                                                         |                                                                         |
| <code>q-&gt;m</code>                                                                     | type of <code>T::m</code>     | <i>Requires:</i> <code>(*q).m</code> is well-defined.<br>equivalent to <code>(*q).m</code>                                                                                                                                                         |                                                                         |
| <code>static_cast&lt;X::pointer&gt;(w)</code>                                            | <code>X::pointer</code>       | <code>static_cast&lt;X::pointer&gt;(w) == p</code>                                                                                                                                                                                                 |                                                                         |
| <code>static_cast&lt;X::const_pointer&gt;(x)</code>                                      | <code>X::const_pointer</code> | <code>static_cast&lt;X::const_pointer&gt;(x) == q</code>                                                                                                                                                                                           |                                                                         |



Table 31 — Allocator requirements (continued)

| Expression                                                             | Return type               | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                            | Default                                                                                       |
|------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| <code>pointer_traits&lt;<br/>X::pointer<br/>&gt;::pointer_to(r)</code> | <code>X::pointer</code>   |                                                                                                                                                                                                                                                                                                                  |                                                                                               |
| <code>a.allocate(n)</code>                                             | <code>X::pointer</code>   | Memory is allocated for <code>n</code> objects of type <code>T</code> but objects are not constructed. <code>allocate</code> may throw an appropriate exception. <sup>175</sup> [ <i>Note</i> : If <code>n == 0</code> , the return value is unspecified. — <i>end note</i> ]                                    |                                                                                               |
| <code>a.allocate(n, y)</code>                                          | <code>X::pointer</code>   | Same as <code>a.allocate(n)</code> . The use of <code>y</code> is unspecified, but it is intended as an aid to locality.                                                                                                                                                                                         | <code>a.allocate(n)</code>                                                                    |
| <code>a.deallocate(p,n)</code>                                         | (not used)                | <i>Requires</i> : <code>p</code> shall be a value returned by an earlier call to <code>allocate</code> that has not been invalidated by an intervening call to <code>deallocate</code> . <code>n</code> shall match the value passed to <code>allocate</code> to obtain this memory.<br><i>Throws</i> : Nothing. |                                                                                               |
| <code>a.max_size()</code>                                              | <code>X::size_type</code> | the largest value that can meaningfully be passed to <code>X::allocate()</code>                                                                                                                                                                                                                                  | <code>numeric_—<br/>limits&lt;size_—<br/>type&gt;::max()<br/>/ sizeof<br/>(value_type)</code> |
| <code>a1 == a2</code>                                                  | <code>bool</code>         | returns <code>true</code> only if storage allocated from each can be deallocated via the other.<br><code>operator==</code> shall be reflexive, symmetric, and transitive, and shall not exit via an exception.                                                                                                   |                                                                                               |
| <code>a1 != a2</code>                                                  | <code>bool</code>         | same as <code>!(a1 == a2)</code>                                                                                                                                                                                                                                                                                 |                                                                                               |
| <code>a == b</code>                                                    | <code>bool</code>         | same as <code>a == Y::rebind&lt;T&gt;::other(b)</code>                                                                                                                                                                                                                                                           |                                                                                               |
| <code>a != b</code>                                                    | <code>bool</code>         | same as <code>!(a == b)</code>                                                                                                                                                                                                                                                                                   |                                                                                               |
| <code>X u(a);<br/>X u = a;</code>                                      |                           | Shall not exit via an exception.<br><i>Postconditions</i> : <code>u == a</code>                                                                                                                                                                                                                                  |                                                                                               |
| <code>X u(b);</code>                                                   |                           | Shall not exit via an exception.<br><i>Postconditions</i> : <code>Y(u) == b</code> , <code>u == X(b)</code>                                                                                                                                                                                                      |                                                                                               |
| <code>X u(std::move(a));<br/>X u = std::move(a);</code>                |                           | Shall not exit via an exception.<br><i>Postconditions</i> : <code>u</code> is equal to the prior value of <code>a</code> .                                                                                                                                                                                       |                                                                                               |

Table 31 — Allocator requirements (continued)

| Expression                                             | Return type                                                                    | Assertion/note<br>pre-/post-condition                                                                                                                                                                                  | Default                                                          |
|--------------------------------------------------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| <code>X u(std::move(b));</code>                        |                                                                                | Shall not exit via an exception.<br><i>Postconditions:</i> <code>u</code> is equal to the prior value of <code>X(b)</code> .                                                                                           |                                                                  |
| <code>a.construct(c, args)</code>                      | (not used)                                                                     | <i>Effects:</i> Constructs an object of type <code>C</code> at <code>c</code>                                                                                                                                          | <code>::new ((void*)c) C(forward&lt; Args&gt; (args)...) </code> |
| <code>a.destroy(c)</code>                              | (not used)                                                                     | <i>Effects:</i> Destroys the object at <code>c</code>                                                                                                                                                                  | <code>c-&gt;~C()</code>                                          |
| <code>a.select_on_container_copy_construction()</code> | <code>X</code>                                                                 | Typically returns either <code>a</code> or <code>X()</code>                                                                                                                                                            | <code>return a;</code>                                           |
| <code>X::propagate_on_container_copy_assignment</code> | Identical to or derived from <code>true_type</code> or <code>false_type</code> | <code>true_type</code> only if an allocator of type <code>X</code> should be copied when the client container is copy-assigned. See Note B, below.                                                                     | <code>false_type</code>                                          |
| <code>X::propagate_on_container_move_assignment</code> | Identical to or derived from <code>true_type</code> or <code>false_type</code> | <code>true_type</code> only if an allocator of type <code>X</code> should be moved when the client container is move-assigned. See Note B, below.                                                                      | <code>false_type</code>                                          |
| <code>X::propagate_on_container_swap</code>            | Identical to or derived from <code>true_type</code> or <code>false_type</code> | <code>true_type</code> only if an allocator of type <code>X</code> should be swapped when the client container is swapped. See Note B, below.                                                                          | <code>false_type</code>                                          |
| <code>X::is_always_equal</code>                        | Identical to or derived from <code>true_type</code> or <code>false_type</code> | <code>true_type</code> only if the expression <code>a1 == a2</code> is guaranteed to be <code>true</code> for any two (possibly <code>const</code> ) values <code>a1</code> , <code>a2</code> of type <code>X</code> . | <code>is_empty&lt;X&gt;::type</code>                             |

<sup>3</sup> Note A: The member class template `rebind` in the table above is effectively a typedef template. [ *Note:* In general, if the name `Allocator` is bound to `SomeAllocator<T>`, then `Allocator::rebind<U>::other` is the same type as `SomeAllocator<U>`, where `SomeAllocator<T>::value_type` is `T` and `SomeAllocator<U>::value_type` is `U`. — *end note* ] If `Allocator` is a class template instantiation of the form `SomeAllocator<T, Args>`, where `Args` is zero or more type arguments, and `Allocator` does not supply a `rebind` member template, the standard `allocator_traits` template uses `SomeAllocator<U, Args>` in place of `Allocator::rebind<U>::other` by default. For allocator types that are not template instantiations of the above form, no default is provided.

<sup>4</sup> Note B: If `X::propagate_on_container_copy_assignment::value` is `true`, `X` shall satisfy the `CopyAssignable` requirements (Table 26) and the copy operation shall not throw exceptions. If `X::propagate_on_container_move_assignment::value` is `true`, `X` shall satisfy the `MoveAssignable` requirements (Table 25)

175) It is intended that `a.allocate` be an efficient means of allocating a single object of type `T`, even when `sizeof(T)` is small. That is, there is no need for a container to maintain its own free list.

and the move operation shall not throw exceptions. If `X::propagate_on_container_swap::value` is `true`, lvalues of type `X` shall be swappable (20.5.3.2) and the `swap` operation shall not throw exceptions.

- 5 An allocator type `X` shall satisfy the requirements of `CopyConstructible` (20.5.3.1). The `X::pointer`, `X::const_pointer`, `X::void_pointer`, and `X::const_void_pointer` types shall satisfy the requirements of `NullablePointer` (20.5.3.3). No constructor, comparison function, copy operation, move operation, or swap operation on these pointer types shall exit via an exception. `X::pointer` and `X::const_pointer` shall also satisfy the requirements for a random access iterator (27.2.7) and of a contiguous iterator (27.2.1).
- 6 Let `x1` and `x2` denote objects of (possibly different) types `X::void_pointer`, `X::const_void_pointer`, `X::pointer`, or `X::const_pointer`. Then, `x1` and `x2` are *equivalently-valued* pointer values, if and only if both `x1` and `x2` can be explicitly converted to the two corresponding objects `px1` and `px2` of type `X::const_pointer`, using a sequence of `static_casts` using only these four types, and the expression `px1 == px2` evaluates to `true`.
- 7 Let `w1` and `w2` denote objects of type `X::void_pointer`. Then for the expressions

```
w1 == w2
w1 != w2
```

either or both objects may be replaced by an equivalently-valued object of type `X::const_void_pointer` with no change in semantics.

- 8 Let `p1` and `p2` denote objects of type `X::pointer`. Then for the expressions

```
p1 == p2
p1 != p2
p1 < p2
p1 <= p2
p1 >= p2
p1 > p2
p1 - p2
```

either or both objects may be replaced by an equivalently-valued object of type `X::const_pointer` with no change in semantics.

- 9 An allocator may constrain the types on which it can be instantiated and the arguments for which its `construct` or `destroy` members may be called. If a type cannot be used with a particular allocator, the allocator class or the call to `construct` or `destroy` may fail to instantiate.

[*Example:* The following is an allocator class template supporting the minimal interface that satisfies the requirements of Table 31:

```
template <class Tp>
struct SimpleAllocator {
 typedef Tp value_type;
 SimpleAllocator(ctor args);

 template <class T> SimpleAllocator(const SimpleAllocator<T>& other);

 Tp* allocate(std::size_t n);
 void deallocate(Tp* p, std::size_t n);
};

template <class T, class U>
bool operator==(const SimpleAllocator<T>&, const SimpleAllocator<U>&);
template <class T, class U>
bool operator!=(const SimpleAllocator<T>&, const SimpleAllocator<U>&);
```

— *end example*]

- <sup>10</sup> If the alignment associated with a specific over-aligned type is not supported by an allocator, instantiation of the allocator for that type may fail. The allocator also may silently ignore the requested alignment. [ *Note:* Additionally, the member function `allocate` for that type may fail by throwing an object of type `bad_alloc`. — *end note* ]

#### 20.5.3.5.1 Allocator completeness requirements [allocator.requirements.completeness]

- <sup>1</sup> If `X` is an allocator class for type `T`, `X` additionally satisfies the allocator completeness requirements if, whether or not `T` is a complete type:
- (1.1) — `X` is a complete type, and
  - (1.2) — all the member types of `allocator_traits<X>` (23.10.8) other than `value_type` are complete types.

### 20.5.4 Constraints on programs [constraints]

#### 20.5.4.1 Overview [constraints.overview]

- <sup>1</sup> This section describes restrictions on C++ programs that use the facilities of the C++ standard library. The following subclauses specify constraints on the program's use of namespaces (20.5.4.2.1), its use of various reserved names (20.5.4.3), its use of headers (20.5.4.4), its use of standard library classes as base classes (20.5.4.5), its definitions of replacement functions (20.5.4.6), and its installation of handler functions during execution (20.5.4.7).

#### 20.5.4.2 Namespace use [namespace.constraints]

##### 20.5.4.2.1 Namespace `std` [namespace.std]

- <sup>1</sup> The behavior of a C++ program is undefined if it adds declarations or definitions to namespace `std` or to a namespace within namespace `std` unless otherwise specified. A program may add a template specialization for any standard library template to namespace `std` only if the declaration depends on a user-defined type and the specialization meets the standard library requirements for the original template and is not explicitly prohibited.<sup>176</sup>
- <sup>2</sup> The behavior of a C++ program is undefined if it declares
- (2.1) — an explicit specialization of any member function of a standard library class template, or
  - (2.2) — an explicit specialization of any member function template of a standard library class or class template, or
  - (2.3) — an explicit or partial specialization of any member class template of a standard library class or class template, or
  - (2.4) — a deduction guide for any standard library class template.

A program may explicitly instantiate a template defined in the standard library only if the declaration depends on the name of a user-defined type and the instantiation meets the standard library requirements for the original template.

- <sup>3</sup> A translation unit shall not declare namespace `std` to be an inline namespace (10.3.1).

##### 20.5.4.2.2 Namespace `posix` [namespace.posix]

- <sup>1</sup> The behavior of a C++ program is undefined if it adds declarations or definitions to namespace `posix` or to a namespace within namespace `posix` unless otherwise specified. The namespace `posix` is reserved for use by ISO/IEC 9945 and other POSIX standards.

<sup>176</sup>) Any library code that instantiates other library templates must be prepared to work adequately with any user-supplied specialization that meets the minimum requirements of this International Standard.

### 20.5.4.2.3 Namespaces for future standardization [namespace.future]

- <sup>1</sup> Top level namespaces with a name starting with `std` and followed by a non-empty sequence of digits are reserved for future standardization. The behavior of a C++ program is undefined if it adds declarations or definitions to such a namespace. [*Example:* The top level namespace `std2` is reserved for use by future revisions of this International Standard. — *end example*]

### 20.5.4.3 Reserved names [reserved.names]

- <sup>1</sup> The C++ standard library reserves the following kinds of names:

- (1.1) — macros
- (1.2) — global names
- (1.3) — names with external linkage

- <sup>2</sup> If a program declares or defines a name in a context where it is reserved, other than as explicitly allowed by this Clause, its behavior is undefined.

#### 20.5.4.3.1 Zombie names [zombie.names]

- <sup>1</sup> In namespace `std`, the following names are reserved for previous standardization:

- (1.1) — `auto_ptr`,
- (1.2) — `binary_function`,
- (1.3) — `bind1st`,
- (1.4) — `bind2nd`,
- (1.5) — `binder1st`,
- (1.6) — `binder2nd`,
- (1.7) — `const_mem_fun1_ref_t`,
- (1.8) — `const_mem_fun1_t`,
- (1.9) — `const_mem_fun_ref_t`,
- (1.10) — `const_mem_fun_t`,
- (1.11) — `get_unexpected`,
- (1.12) — `mem_fun1_ref_t`,
- (1.13) — `mem_fun1_t`,
- (1.14) — `mem_fun_ref_t`,
- (1.15) — `mem_fun_ref`,
- (1.16) — `mem_fun_t`,
- (1.17) — `mem_fun`,
- (1.18) — `pointer_to_binary_function`,
- (1.19) — `pointer_to_unary_function`,
- (1.20) — `ptr_fun`,
- (1.21) — `random_shuffle`,
- (1.22) — `set_unexpected`,
- (1.23) — `unary_function`,
- (1.24) — `unexpected`, and

(1.25) — `unexpected_handler`.

#### 20.5.4.3.2 Macro names [macro.names]

- <sup>1</sup> A translation unit that includes a standard library header shall not `#define` or `#undef` names declared in any standard library header.
- <sup>2</sup> A translation unit shall not `#define` or `#undef` names lexically identical to keywords, to the identifiers listed in Table 4, or to the *attribute-tokens* described in 10.6.

#### 20.5.4.3.3 External linkage [extern.names]

- <sup>1</sup> Each name declared as an object with external linkage in a header is reserved to the implementation to designate that library object with external linkage,<sup>177</sup> both in namespace `std` and in the global namespace.
- <sup>2</sup> Each global function signature declared with external linkage in a header is reserved to the implementation to designate that function signature with external linkage.<sup>178</sup>
- <sup>3</sup> Each name from the C standard library declared with external linkage is reserved to the implementation for use as a name with `extern "C"` linkage, both in namespace `std` and in the global namespace.
- <sup>4</sup> Each function signature from the C standard library declared with external linkage is reserved to the implementation for use as a function signature with both `extern "C"` and `extern "C++"` linkage,<sup>179</sup> or as a name of namespace scope in the global namespace.

#### 20.5.4.3.4 Types [extern.types]

- <sup>1</sup> For each type `T` from the C standard library,<sup>180</sup> the types `::T` and `std::T` are reserved to the implementation and, when defined, `::T` shall be identical to `std::T`.

#### 20.5.4.3.5 User-defined literal suffixes [usrlit.suffix]

- <sup>1</sup> Literal suffix identifiers (16.5.8) that do not start with an underscore are reserved for future standardization.

#### 20.5.4.4 Headers [alt.headers]

- <sup>1</sup> If a file with a name equivalent to the derived file name for one of the C++ standard library headers is not provided as part of the implementation, and a file with that name is placed in any of the standard places for a source file to be included (19.2), the behavior is undefined.

#### 20.5.4.5 Derived classes [derived.classes]

- <sup>1</sup> Virtual member function signatures defined for a base class in the C++ standard library may be overridden in a derived class defined in the program (13.3).

#### 20.5.4.6 Replacement functions [replacement.functions]

- <sup>1</sup> Clauses 21 through 33 and Annex D describe the behavior of numerous functions defined by the C++ standard library. Under some circumstances, however, certain of these function descriptions also apply to replacement functions defined in the program (20.3).
- <sup>2</sup> A C++ program may provide the definition for any of the following dynamic memory allocation function signatures declared in header `<new>` (6.7.4, 21.6):

<sup>177</sup>) The list of such reserved names includes `errno`, declared or defined in `<cerrno>`.

<sup>178</sup>) The list of such reserved function signatures with external linkage includes `setjmp(jmp_buf)`, declared or defined in `<setjmp>`, and `va_end(va_list)`, declared or defined in `<stdarg>`.

<sup>179</sup>) The function signatures declared in `<cuchar>`, `<wchar>`, and `<cwctype>` are always reserved, notwithstanding the restrictions imposed in subclause 4.5.1 of Amendment 1 to the C Standard for these headers.

<sup>180</sup>) These types are `clock_t`, `div_t`, `FILE`, `fpos_t`, `lconv`, `ldiv_t`, `mbstate_t`, `ptrdiff_t`, `sig_atomic_t`, `size_t`, `time_t`, `tm`, `va_list`, `wctrans_t`, `wctype_t`, and `wint_t`.

```

operator new(std::size_t)
operator new(std::size_t, std::align_val_t)
operator new(std::size_t, const std::nothrow_t&)
operator new(std::size_t, std::align_val_t, const std::nothrow_t&)

operator delete(void*)
operator delete(void*, std::size_t)
operator delete(void*, std::align_val_t)
operator delete(void*, std::size_t, std::align_val_t)
operator delete(void*, const std::nothrow_t&)
operator delete(void*, std::align_val_t, const std::nothrow_t&)

operator new[](std::size_t)
operator new[](std::size_t, std::align_val_t)
operator new[](std::size_t, const std::nothrow_t&)
operator new[](std::size_t, std::align_val_t, const std::nothrow_t&)

operator delete[](void*)
operator delete[](void*, std::size_t)
operator delete[](void*, std::align_val_t)
operator delete[](void*, std::size_t, std::align_val_t)
operator delete[](void*, const std::nothrow_t&)
operator delete[](void*, std::align_val_t, const std::nothrow_t&)

```

- 3 The program's definitions are used instead of the default versions supplied by the implementation (21.6). Such replacement occurs prior to program startup (6.2, 6.6). The program's declarations shall not be specified as `inline`. No diagnostic is required.

#### 20.5.4.7 Handler functions

[handler.functions]

- 1 The C++ standard library provides a default version of the following handler function (Clause 21):

(1.1) — `terminate_handler`

- 2 A C++ program may install different handler functions during execution, by supplying a pointer to a function defined in the program or the library as an argument to (respectively):

(2.1) — `set_new_handler`

(2.2) — `set_terminate`

See also subclauses 21.6.3, Storage allocation errors, and 21.8, Exception handling.

- 3 A C++ program can get a pointer to the current handler function by calling the following functions:

(3.1) — `get_new_handler`

(3.2) — `get_terminate`

- 4 Calling the `set_*` and `get_*` functions shall not incur a data race. A call to any of the `set_*` functions shall synchronize with subsequent calls to the same `set_*` function and to the corresponding `get_*` function.

#### 20.5.4.8 Other functions

[res.on.functions]

- 1 In certain cases (replacement functions, handler functions, operations on types used to instantiate standard library template components), the C++ standard library depends on components supplied by a C++ program. If these components do not meet their requirements, this International Standard places no requirements on the implementation.

- 2 In particular, the effects are undefined in the following cases:

(2.1) — for replacement functions (21.6.2), if the installed replacement function does not implement the semantics of the applicable *Required behavior*: paragraph.

- (2.2) — for handler functions (21.6.3.3, 21.8.4.1), if the installed handler function does not implement the semantics of the applicable *Required behavior*: paragraph
- (2.3) — for types used as template arguments when instantiating a template component, if the operations on the type do not implement the semantics of the applicable *Requirements* subclause (20.5.3.5, 26.2, 27.2, 28.3, 29.3). Operations on such types can report a failure by throwing an exception unless otherwise specified.
- (2.4) — if any replacement function or handler function or destructor operation exits via an exception, unless specifically allowed in the applicable *Required behavior*: paragraph.
- (2.5) — if an incomplete type (6.9) is used as a template argument when instantiating a template component, unless specifically allowed for that component.

#### 20.5.4.9 Function arguments

[res.on.arguments]

- <sup>1</sup> Each of the following applies to all arguments to functions defined in the C++ standard library, unless explicitly stated otherwise.
  - (1.1) — If an argument to a function has an invalid value (such as a value outside the domain of the function or a pointer invalid for its intended use), the behavior is undefined.
  - (1.2) — If a function argument is described as being an array, the pointer actually passed to the function shall have a value such that all address computations and accesses to objects (that would be valid if the pointer did point to the first element of such an array) are in fact valid.
  - (1.3) — If a function argument binds to an rvalue reference parameter, the implementation may assume that this parameter is a unique reference to this argument. [ *Note*: If the parameter is a generic parameter of the form `T&&` and an lvalue of type `A` is bound, the argument binds to an lvalue reference (17.8.2.1) and thus is not covered by the previous sentence. — *end note* ] [ *Note*: If a program casts an lvalue to an xvalue while passing that lvalue to a library function (e.g. by calling the function with the argument `std::move(x)`), the program is effectively asking that function to treat that lvalue as a temporary. The implementation is free to optimize away aliasing checks which might be needed if the argument was an lvalue. — *end note* ]

#### 20.5.4.10 Library object access

[res.on.objects]

- <sup>1</sup> The behavior of a program is undefined if calls to standard library functions from different threads may introduce a data race. The conditions under which this may occur are specified in 20.5.5.9. [ *Note*: Modifying an object of a standard library type that is shared between threads risks undefined behavior unless objects of that type are explicitly specified as being sharable without data races or the user supplies a locking mechanism. — *end note* ]
- <sup>2</sup> If an object of a standard library type is accessed, and the beginning of the object's lifetime (6.8) does not happen before the access, or the access does not happen before the end of the object's lifetime, the behavior is undefined unless otherwise specified. [ *Note*: This applies even to objects such as mutexes intended for thread synchronization. — *end note* ]

#### 20.5.4.11 Requires paragraph

[res.on.required]

- <sup>1</sup> Violation of the preconditions specified in a function's *Requires*: paragraph results in undefined behavior unless the function's *Throws*: paragraph specifies throwing an exception when the precondition is violated.

### 20.5.5 Conforming implementations

[conforming]

#### 20.5.5.1 Overview

[conforming.overview]

- <sup>1</sup> This section describes the constraints upon, and latitude of, implementations of the C++ standard library.



- <sup>2</sup> An implementation's use of headers is discussed in 20.5.5.2, its use of macros in 20.5.5.3, non-member functions in 20.5.5.4, member functions in 20.5.5.5, data race avoidance in 20.5.5.9, access specifiers in 20.5.5.10, class derivation in 20.5.5.11, and exceptions in 20.5.5.12.

### 20.5.5.2 Headers

[res.on.headers]

- <sup>1</sup> A C++ header may include other C++ headers. A C++ header shall provide the declarations and definitions that appear in its synopsis. A C++ header shown in its synopsis as including other C++ headers shall provide the declarations and definitions that appear in the synopses of those other headers.
- <sup>2</sup> Certain types and macros are defined in more than one header. Every such entity shall be defined such that any header that defines it may be included after any other header that also defines it (6.2).
- <sup>3</sup> The C standard library headers (D.5) shall include only their corresponding C++ standard library header, as described in 20.5.1.2.

### 20.5.5.3 Restrictions on macro definitions

[res.on.macro.definitions]

- <sup>1</sup> The names and global function signatures described in 20.5.1.1 are reserved to the implementation.
- <sup>2</sup> All object-like macros defined by the C standard library and described in this Clause as expanding to integral constant expressions are also suitable for use in `#if` preprocessing directives, unless explicitly stated otherwise.

### 20.5.5.4 Non-member functions

[global.functions]

- <sup>1</sup> It is unspecified whether any non-member functions in the C++ standard library are defined as `inline` (10.1.6).
- <sup>2</sup> A call to a non-member function signature described in Clauses 21 through 33 and Annex D shall behave as if the implementation declared no additional non-member function signatures.<sup>181</sup>
- <sup>3</sup> An implementation shall not declare a non-member function signature with additional default arguments.
- <sup>4</sup> Unless otherwise specified, calls made by functions in the standard library to non-operator, non-member functions do not use functions from another namespace which are found through *argument-dependent name lookup* (6.4.2). [Note: The phrase “unless otherwise specified” applies to cases such as the swappable with requirements (20.5.3.2). The exception for overloaded operators allows argument-dependent lookup in cases like that of `ostream_iterator::operator=` (27.6.2.2):

*Effects:*

```
*out_stream << value;
if (delim != 0)
 *out_stream << delim;
return *this;
```

— end note]

### 20.5.5.5 Member functions

[member.functions]

- <sup>1</sup> It is unspecified whether any member functions in the C++ standard library are defined as `inline` (10.1.6).
- <sup>2</sup> For a non-virtual member function described in the C++ standard library, an implementation may declare a different set of member function signatures, provided that any call to the member function that would select an overload from the set of declarations described in this International Standard behaves as if that overload were selected. [Note: For instance, an implementation may add parameters with default values, or replace a member function with default arguments with two or more member functions with equivalent behavior, or add additional signatures for a member function name. — end note]

<sup>181</sup>) A valid C++ program always calls the expected library non-member function. An implementation may also define additional non-member functions that would otherwise not be called by a valid C++ program.

**20.5.5.6 Constexpr functions and constructors** [constexpr.functions]

- <sup>1</sup> This International Standard explicitly requires that certain standard library functions are **constexpr** (10.1.5). An implementation shall not declare any standard library function signature as **constexpr** except for those where it is explicitly required. Within any header that provides any non-defining declarations of constexpr functions or constructors an implementation shall provide corresponding definitions.

**20.5.5.7 Requirements for stable algorithms** [algorithm.stable]

- <sup>1</sup> When the requirements for an algorithm state that it is “stable” without further elaboration, it means:
  - (1.1) — For the *sort* algorithms the relative order of equivalent elements is preserved.
  - (1.2) — For the *remove* and *copy* algorithms the relative order of the elements that are not removed is preserved.
  - (1.3) — For the *merge* algorithms, for equivalent elements in the original two ranges, the elements from the first range (preserving their original order) precede the elements from the second range (preserving their original order).

**20.5.5.8 Reentrancy** [reentrancy]

- <sup>1</sup> Except where explicitly specified in this International Standard, it is implementation-defined which functions in the C++ standard library may be recursively reentered.

**20.5.5.9 Data race avoidance** [res.on.data.races]

- <sup>1</sup> This section specifies requirements that implementations shall meet to prevent data races (4.7). Every standard library function shall meet each requirement unless otherwise specified. Implementations may prevent data races in cases other than those specified below.
- <sup>2</sup> A C++ standard library function shall not directly or indirectly access objects (4.7) accessible by threads other than the current thread unless the objects are accessed directly or indirectly via the function’s arguments, including **this**.
- <sup>3</sup> A C++ standard library function shall not directly or indirectly modify objects (4.7) accessible by threads other than the current thread unless the objects are accessed directly or indirectly via the function’s non-const arguments, including **this**.
- <sup>4</sup> [ *Note*: This means, for example, that implementations can’t use a static object for internal purposes without synchronization because it could cause a data race even in programs that do not explicitly share objects between threads. — *end note* ]
- <sup>5</sup> A C++ standard library function shall not access objects indirectly accessible via its arguments or via elements of its container arguments except by invoking functions required by its specification on those container elements.
- <sup>6</sup> Operations on iterators obtained by calling a standard library container or string member function may access the underlying container, but shall not modify it. [ *Note*: In particular, container operations that invalidate iterators conflict with operations on iterators associated with that container. — *end note* ]
- <sup>7</sup> Implementations may share their own internal objects between threads if the objects are not visible to users and are protected against data races.
- <sup>8</sup> Unless otherwise specified, C++ standard library functions shall perform all operations solely within the current thread if those operations have effects that are visible (4.7) to users.
- <sup>9</sup> [ *Note*: This allows implementations to parallelize operations if there are no visible side effects. — *end note* ]

**20.5.5.10 Protection within classes** [protection.within.classes]

- <sup>1</sup> It is unspecified whether any function signature or class described in Clauses 21 through 33 and Annex D is a **friend** of another class in the C++ standard library.

**20.5.5.11 Derived classes****[derivation]**

- <sup>1</sup> An implementation may derive any class in the C++ standard library from a class with a name reserved to the implementation.
- <sup>2</sup> Certain classes defined in the C++ standard library are required to be derived from other classes in the C++ standard library. An implementation may derive such a class directly from the required base or indirectly through a hierarchy of base classes with names reserved to the implementation.
- <sup>3</sup> In any case:
  - (3.1) — Every base class described as **virtual** shall be virtual;
  - (3.2) — Every base class not specified as **virtual** shall not be virtual;
  - (3.3) — Unless explicitly stated otherwise, types with distinct names shall be distinct types.<sup>182</sup>
- <sup>4</sup> All types specified in the C++ standard library shall be non-**final** types unless otherwise specified.

**20.5.5.12 Restrictions on exception handling****[res.on.exception.handling]**

- <sup>1</sup> Any of the functions defined in the C++ standard library can report a failure by throwing an exception of a type described in its *Throws:* paragraph, or of a type derived from a type named in the *Throws:* paragraph that would be caught by an exception handler for the base type.
- <sup>2</sup> Functions from the C standard library shall not throw exceptions<sup>183</sup> except when such a function calls a program-supplied function that throws an exception.<sup>184</sup>
- <sup>3</sup> Destructor operations defined in the C++ standard library shall not throw exceptions. Every destructor in the C++ standard library shall behave as if it had a non-throwing exception specification.
- <sup>4</sup> Functions defined in the C++ standard library that do not have a *Throws:* paragraph but do have a potentially-throwing exception specification may throw implementation-defined exceptions.<sup>185</sup> Implementations should report errors by throwing exceptions of or derived from the standard exception classes (21.6.3.1, 21.8, 22.2).
- <sup>5</sup> An implementation may strengthen the exception specification for a non-virtual function by adding a non-throwing exception specification.

**20.5.5.13 Restrictions on storage of pointers****[res.on.pointer.storage]**

- <sup>1</sup> Objects constructed by the standard library that may hold a user-supplied pointer value or an integer of type `std::intptr_t` shall store such values in a traceable pointer location (6.7.4.3). [*Note:* Other libraries are strongly encouraged to do the same, since not doing so may result in accidental use of pointers that are not safely derived. Libraries that store pointers outside the user's address space should make it appear that they are stored and retrieved from a traceable pointer location. — *end note*]

**20.5.5.14 Value of error codes****[value.error.codes]**

- <sup>1</sup> Certain functions in the C++ standard library report errors via a `std::error_code` (22.5.3.1) object. That object's `category()` member shall return `std::system_category()` for errors originating from the operating system, or a reference to an implementation-defined `error_category` object for errors originating elsewhere. The implementation shall define the possible values of `value()` for each of these error categories. [*Example:* For operating systems that are based on POSIX, implementations are encouraged to define the `std::system_category()` values as identical to the POSIX `errno` values, with additional values as defined by the operating

<sup>182</sup>) There is an implicit exception to this rule for types that are described as synonyms for basic integral types, such as `size_t` (21.2) and `streamoff` (30.5.2).

<sup>183</sup>) That is, the C library functions can all be treated as if they are marked `noexcept`. This allows implementations to make performance optimizations based on the absence of exceptions at runtime.

<sup>184</sup>) The functions `qsort()` and `bsearch()` (28.8) meet this condition.

<sup>185</sup>) In particular, they can report a failure to allocate storage by throwing an exception of type `bad_alloc`, or a class derived from `bad_alloc` (21.6.3.1).

system's documentation. Implementations for operating systems that are not based on POSIX are encouraged to define values identical to the operating system's values. For errors that do not originate from the operating system, the implementation may provide enums for the associated values. — *end example*]

#### **20.5.5.15 Moved-from state of library types** [lib.types.movedfrom]

- <sup>1</sup> Objects of types defined in the C++ standard library may be moved from (15.8). Move operations may be explicitly specified or implicitly generated. Unless otherwise specified, such moved-from objects shall be placed in a valid but unspecified state.

## 21 Language support library

### [language.support]

#### 21.1 General

[support.general]

- <sup>1</sup> This Clause describes the function signatures that are called implicitly, and the types of objects generated implicitly, during the execution of some C++ programs. It also describes the headers that declare these function signatures and define any related types.
- <sup>2</sup> The following subclauses describe common type definitions used throughout the library, characteristics of the predefined types, functions supporting start and termination of a C++ program, support for dynamic memory management, support for dynamic type identification, support for exception processing, support for initializer lists, and other runtime support, as summarized in Table 32.

Table 32 — Language support library summary

| Subclause                                      | Header(s)                                           |
|------------------------------------------------|-----------------------------------------------------|
| <a href="#">21.2</a> Common definitions        | <cstdlib><br><stdlib.h>                             |
| <a href="#">21.3</a> Implementation properties | <limits><br><climits><br><float.h>                  |
| <a href="#">21.4</a> Integer types             | <stdint.h>                                          |
| <a href="#">21.5</a> Start and termination     | <cstdlib>                                           |
| <a href="#">21.6</a> Dynamic memory management | <new>                                               |
| <a href="#">21.7</a> Type identification       | <typeinfo>                                          |
| <a href="#">21.8</a> Exception handling        | <exception>                                         |
| <a href="#">21.9</a> Initializer lists         | <initializer_list>                                  |
| <a href="#">21.10</a> Other runtime support    | <csignal><br><setjmp.h><br><stdarg.h><br><stdlib.h> |

#### 21.2 Common definitions

[support.types]

##### 21.2.1 Header <cstdlib> synopsis

[cstdlib.syn]

```

namespace std {
 using ptrdiff_t = see below;
 using size_t = see below;
 using max_align_t = see below;
 using nullptr_t = decltype(nullptr);

 enum class byte : unsigned char {};

 // 21.2.5, byte type operations
 template <class IntType>
 constexpr byte& operator<=(byte& b, IntType shift) noexcept;

```

```

template <class IntType>
 constexpr byte operator<<(byte b, IntType shift) noexcept;
template <class IntType>
 constexpr byte& operator>>=(byte& b, IntType shift) noexcept;
template <class IntType>
 constexpr byte operator>>(byte b, IntType shift) noexcept;
constexpr byte& operator|=(byte& l, byte r) noexcept;
constexpr byte operator|(byte l, byte r) noexcept;
constexpr byte& operator&=(byte& l, byte r) noexcept;
constexpr byte operator&(byte l, byte r) noexcept;
constexpr byte& operator^=(byte& l, byte r) noexcept;
constexpr byte operator^(byte l, byte r) noexcept;
constexpr byte operator~(byte b) noexcept;
template <class IntType>
 constexpr IntType to_integer(byte b) noexcept;
}

```

```

#define NULL see below
#define offsetof(P, D) see below

```

- <sup>1</sup> The contents and meaning of the header `<cstddef>` are the same as the C standard library header `<stddef.h>`, except that it does not declare the type `wchar_t`, that it also declares the type `byte` and its associated operations (21.2.5), and as noted in 21.2.3 and 21.2.4.

SEE ALSO: ISO C 7.19

## 21.2.2 Header `<cstdlib>` synopsis

[`cstdlib.syn`]

```

namespace std {
 using size_t = see below;
 using div_t = see below;
 using ldiv_t = see below;
 using lldiv_t = see below;
}

#define NULL see below
#define EXIT_FAILURE see below
#define EXIT_SUCCESS see below
#define RAND_MAX see below
#define MB_CUR_MAX see below

namespace std {
 // Exposition-only function type aliases
 extern "C" using c-atexit-handler = void(); // exposition only
 extern "C++" using atexit-handler = void(); // exposition only
 extern "C" using c-compare-pred = int(const void*, const void*); // exposition only
 extern "C++" using compare-pred = int(const void*, const void*); // exposition only

 // 21.5, start and termination
 [[noreturn]] void abort() noexcept;
 int atexit(c-atexit-handler* func) noexcept;
 int atexit(atexit-handler* func) noexcept;
 int at_quick_exit(c-atexit-handler* func) noexcept;
 int at_quick_exit(atexit-handler* func) noexcept;
 [[noreturn]] void exit(int status);
 [[noreturn]] void _Exit(int status) noexcept;
 [[noreturn]] void quick_exit(int status) noexcept;
}

```

```

char* getenv(const char* name);
int system(const char* string);

// 23.10.11, C library memory allocation
void* aligned_alloc(size_t alignment, size_t size);
void* calloc(size_t nmemb, size_t size);
void free(void* ptr);
void* malloc(size_t size);
void* realloc(void* ptr, size_t size);

double atof(const char* nptr);
int atoi(const char* nptr);
long int atol(const char* nptr);
long long int atoll(const char* nptr);
double strtod(const char* nptr, char** endptr);
float strtof(const char* nptr, char** endptr);
long double strtold(const char* nptr, char** endptr);
long int strtol(const char* nptr, char** endptr, int base);
long long int strtoll(const char* nptr, char** endptr, int base);
unsigned long int strtoul(const char* nptr, char** endptr, int base);
unsigned long long int strtoull(const char* nptr, char** endptr, int base);

// 24.5.6, multibyte / wide string and character conversion functions
int mblen(const char* s, size_t n);
int mbtowc(wchar_t* pwc, const char* s, size_t n);
int wctomb(char* s, wchar_t wchar);
size_t mbstowcs(wchar_t* pwcs, const char* s, size_t n);
size_t wcstombs(char* s, const wchar_t* pwcs, size_t n);

// 28.8, C standard library algorithms
void* bsearch(const void* key, const void* base, size_t nmemb, size_t size,
 c-compare-pred* compar);
void* bsearch(const void* key, const void* base, size_t nmemb, size_t size,
 compare-pred* compar);
void qsort(void* base, size_t nmemb, size_t size, c-compare-pred* compar);
void qsort(void* base, size_t nmemb, size_t size, compare-pred* compar);

// 29.6.9, low-quality random number generation
int rand();
void srand(unsigned int seed);

// 29.9.2, absolute values
int abs(int j);
long int abs(long int j);
long long int abs(long long int j);
float abs(float j);
double abs(double j);
long double abs(long double j);

long int labs(long int j);
long long int llabs(long long int j);

div_t div(int numer, int denom);
ldiv_t div(long int numer, long int denom); // see 20.2

```

```

 lldiv_t div(long long int numer, long long int denom); // see 20.2
 ldiv_t ldiv(long int numer, long int denom);
 lldiv_t lldiv(long long int numer, long long int denom);
}

```

- <sup>1</sup> The contents and meaning of the header `<cstdlib>` are the same as the C standard library header `<stdlib.h>`, except that it does not declare the type `wchar_t`, and except as noted in 21.2.3, 21.2.4, 21.5, 23.10.11, 24.5.6, 28.8, 29.6.9, and 29.9.2. [Note: Several functions have additional overloads in this International Standard, but they have the same behavior as in the C standard library (20.2). — end note]

SEE ALSO: ISO C 7.22

### 21.2.3 Null pointers

[support.types.nullptr]

- <sup>1</sup> The type `nullptr_t` is a synonym for the type of a `nullptr` expression, and it has the characteristics described in 6.9.1 and 7.11. [Note: Although `nullptr`'s address cannot be taken, the address of another `nullptr_t` object that is an lvalue can be taken. — end note]
- <sup>2</sup> The macro `NULL` is an implementation-defined null pointer constant.<sup>186</sup>

### 21.2.4 Sizes, alignments, and offsets

[support.types.layout]

- <sup>1</sup> The macro `offsetof(type, member-designator)` has the same semantics as the corresponding macro in the C standard library header `<stddef.h>`, but accepts a restricted set of *type* arguments in this International Standard. Use of the `offsetof` macro with a *type* other than a standard-layout class (Clause 12) is conditionally-supported.<sup>187</sup> The expression `offsetof(type, member-designator)` is never type-dependent (17.6.2.2) and it is value-dependent (17.6.2.3) if and only if *type* is dependent. The result of applying the `offsetof` macro to a static data member or a function member is undefined. No operation invoked by the `offsetof` macro shall throw an exception and `noexcept(offsetof(type, member-designator))` shall be `true`.
- <sup>2</sup> The type `ptrdiff_t` is an implementation-defined signed integer type that can hold the difference of two subscripts in an array object, as described in 8.7.
- <sup>3</sup> The type `size_t` is an implementation-defined unsigned integer type that is large enough to contain the size in bytes of any object.
- <sup>4</sup> [Note: It is recommended that implementations choose types for `ptrdiff_t` and `size_t` whose integer conversion ranks (7.15) are no greater than that of `signed long int` unless a larger size is necessary to contain all the possible values. — end note]
- <sup>5</sup> The type `max_align_t` is a POD type whose alignment requirement is at least as great as that of every scalar type, and whose alignment requirement is supported in every context.

SEE ALSO: Alignment (6.11), Sizeof (8.3.3), Additive operators (8.7), Free store (15.5), and ISO C 7.19.

### 21.2.5 byte type operations

[support.types.byteops]

```
template <class IntType>
```

```
constexpr byte& operator<<=(byte& b, IntType shift) noexcept;
```

- <sup>1</sup> *Remarks:* This function shall not participate in overload resolution unless `is_integral_v<IntType>` is `true`.

- <sup>2</sup> *Effects:* Equivalent to: `return b = byte(static_cast<unsigned char>(b) << shift);`

```
template <class IntType>
```

```
constexpr byte operator<<(byte b, IntType shift) noexcept;
```

<sup>186</sup> Possible definitions include 0 and 0L, but not `(void*)0`.

<sup>187</sup> Note that `offsetof` is required to work as specified even if unary `operator&` is overloaded for any of the types involved.



3       *Remarks:* This function shall not participate in overload resolution unless `is_integral_v<IntType>` is `true`.

4       *Effects:* Equivalent to: `return byte(static_cast<unsigned char>(b) << shift);`

```
template <class IntType>
constexpr byte& operator>>=(byte& b, IntType shift) noexcept;
```

5       *Remarks:* This function shall not participate in overload resolution unless `is_integral_v<IntType>` is `true`.

6       *Effects:* Equivalent to: `return b = byte(static_cast<unsigned char>(b) >> shift);`

```
template <class IntType>
constexpr byte operator>>(byte b, IntType shift) noexcept;
```

7       *Remarks:* This function shall not participate in overload resolution unless `is_integral_v<IntType>` is `true`.

8       *Effects:* Equivalent to: `return byte(static_cast<unsigned char>(b) >> shift);`

```
constexpr byte& operator|=(byte& l, byte r) noexcept;
```

9       *Effects:* Equivalent to:

```
 return l = byte(static_cast<unsigned char>(l) | static_cast<unsigned char>(r));
```

```
constexpr byte operator|(byte l, byte r) noexcept;
```

10      *Effects:* Equivalent to:

```
 return byte(static_cast<unsigned char>(l) | static_cast<unsigned char>(r));
```

```
constexpr byte& operator&=(byte& l, byte r) noexcept;
```

11      *Effects:* Equivalent to:

```
 return l = byte(static_cast<unsigned char>(l) & static_cast<unsigned char>(r));
```

```
constexpr byte operator&(byte l, byte r) noexcept;
```

12      *Effects:* Equivalent to:

```
 return byte(static_cast<unsigned char>(l) & static_cast<unsigned char>(r));
```

```
constexpr byte& operator^=(byte& l, byte r) noexcept;
```

13      *Effects:* Equivalent to:

```
 return l = byte(static_cast<unsigned char>(l) ^ static_cast<unsigned char>(r));
```

```
constexpr byte operator^(byte l, byte r) noexcept;
```

14      *Effects:* Equivalent to:

```
 return byte(static_cast<unsigned char>(l) ^ static_cast<unsigned char>(r));
```

```
constexpr byte operator~(byte b) noexcept;
```

15      *Effects:* Equivalent to: `return byte(~static_cast<unsigned char>(b));`

```
template <class IntType>
constexpr IntType to_integer(byte b) noexcept;
```

16      *Remarks:* This function shall not participate in overload resolution unless `is_integral_v<IntType>` is `true`.

17      *Effects:* Equivalent to: `return IntType(b);`

## 21.3 Implementation properties

[support.limits]

### 21.3.1 General

[support.limits.general]

- <sup>1</sup> The headers `<limits>` (21.3.2), `<climits>` (21.3.5), and `<cfloat>` (21.3.6) supply characteristics of implementation-dependent arithmetic types (6.9.1).

### 21.3.2 Header `<limits>` synopsis

[limits.syn]

```
namespace std {
 // 21.3.3, floating-point type properties
 enum float_round_style;
 enum float_denorm_style;

 // 21.3.4, class template numeric_limits
 template<class T> class numeric_limits;

 template<> class numeric_limits<bool>;

 template<> class numeric_limits<char>;
 template<> class numeric_limits<signed char>;
 template<> class numeric_limits<unsigned char>;
 template<> class numeric_limits<char16_t>;
 template<> class numeric_limits<char32_t>;
 template<> class numeric_limits<wchar_t>;

 template<> class numeric_limits<short>;
 template<> class numeric_limits<int>;
 template<> class numeric_limits<long>;
 template<> class numeric_limits<long long>;
 template<> class numeric_limits<unsigned short>;
 template<> class numeric_limits<unsigned int>;
 template<> class numeric_limits<unsigned long>;
 template<> class numeric_limits<unsigned long long>;

 template<> class numeric_limits<float>;
 template<> class numeric_limits<double>;
 template<> class numeric_limits<long double>;
}
```

### 21.3.3 Floating-point type properties

[fp.style]

#### 21.3.3.1 Type `float_round_style`

[round.style]

```
namespace std {
 enum float_round_style {
 round_indeterminate = -1,
 round_toward_zero = 0,
 round_to_nearest = 1,
 round_toward_infinity = 2,
 round_toward_neg_infinity = 3
 };
}
```

- <sup>1</sup> The rounding mode for floating-point arithmetic is characterized by the values:

- (1.1) — `round_indeterminate` if the rounding style is indeterminable
- (1.2) — `round_toward_zero` if the rounding style is toward zero
- (1.3) — `round_to_nearest` if the rounding style is to the nearest representable value

- (1.4) — `round_toward_infinity` if the rounding style is toward infinity
- (1.5) — `round_toward_neg_infinity` if the rounding style is toward negative infinity

### 21.3.3.2 Type `float_denorm_style`

[denorm.style]

```
namespace std {
 enum float_denorm_style {
 denorm_indeterminate = -1,
 denorm_absent = 0,
 denorm_present = 1
 };
}
```

- <sup>1</sup> The presence or absence of subnormal numbers (variable number of exponent bits) is characterized by the values:

- (1.1) — `denorm_indeterminate` if it cannot be determined whether or not the type allows subnormal values
- (1.2) — `denorm_absent` if the type does not allow subnormal values
- (1.3) — `denorm_present` if the type does allow subnormal values

### 21.3.4 Class template `numeric_limits`

[numeric.limits]

- <sup>1</sup> The `numeric_limits` class template provides a C++ program with information about various properties of the implementation's representation of the arithmetic types.

```
namespace std {
 template<class T> class numeric_limits {
 public:
 static constexpr bool is_specialized = false;
 static constexpr T min() noexcept { return T(); }
 static constexpr T max() noexcept { return T(); }
 static constexpr T lowest() noexcept { return T(); }

 static constexpr int digits = 0;
 static constexpr int digits10 = 0;
 static constexpr int max_digits10 = 0;
 static constexpr bool is_signed = false;
 static constexpr bool is_integer = false;
 static constexpr bool is_exact = false;
 static constexpr int radix = 0;
 static constexpr T epsilon() noexcept { return T(); }
 static constexpr T round_error() noexcept { return T(); }

 static constexpr int min_exponent = 0;
 static constexpr int min_exponent10 = 0;
 static constexpr int max_exponent = 0;
 static constexpr int max_exponent10 = 0;

 static constexpr bool has_infinity = false;
 static constexpr bool has_quiet_NaN = false;
 static constexpr bool has_signaling_NaN = false;
 static constexpr float_denorm_style has_denorm = denorm_absent;
 static constexpr bool has_denorm_loss = false;
 static constexpr T infinity() noexcept { return T(); }
 static constexpr T quiet_NaN() noexcept { return T(); }
 static constexpr T signaling_NaN() noexcept { return T(); }
 static constexpr T denorm_min() noexcept { return T(); }
 };
}
```

```

static constexpr bool is_iec559 = false;
static constexpr bool is_bounded = false;
static constexpr bool is_modulo = false;

static constexpr bool traps = false;
static constexpr bool tinyness_before = false;
static constexpr float_round_style round_style = round_toward_zero;
};

template<class T> class numeric_limits<const T>;
template<class T> class numeric_limits<volatile T>;
template<class T> class numeric_limits<const volatile T>;
}

```

- 2 For all members declared **static constexpr** in the **numeric\_limits** template, specializations shall define these values in such a way that they are usable as constant expressions.
- 3 The default **numeric\_limits<T>** template shall have all members, but with 0 or **false** values.
- 4 Specializations shall be provided for each arithmetic type, both floating-point and integer, including **bool**. The member **is\_specialized** shall be **true** for all such specializations of **numeric\_limits**.
- 5 The value of each member of a specialization of **numeric\_limits** on a cv-qualified type cv T shall be equal to the value of the corresponding member of the specialization on the unqualified type T.
- 6 Non-arithmetic standard types, such as **complex<T>** (29.5.2), shall not have specializations.

#### 21.3.4.1 **numeric\_limits** members

[**numeric.limits.members**]

- 1 Each member function defined in this subclause is signal-safe (21.10.3).

```
static constexpr T min() noexcept;
```

- 2 Minimum finite value.<sup>188</sup>

- 3 For floating types with subnormal numbers, returns the minimum positive normalized value.

- 4 Meaningful for all specializations in which **is\_bounded** != **false**, or **is\_bounded** == **false** && **is\_signed** == **false**.

```
static constexpr T max() noexcept;
```

- 5 Maximum finite value.<sup>189</sup>

- 6 Meaningful for all specializations in which **is\_bounded** != **false**.

```
static constexpr T lowest() noexcept;
```

- 7 A finite value x such that there is no other finite value y where y < x.<sup>190</sup>

- 8 Meaningful for all specializations in which **is\_bounded** != **false**.

```
static constexpr int digits;
```

- 9 Number of **radix** digits that can be represented without change.

- 10 For integer types, the number of non-sign bits in the representation.

188) Equivalent to **CHAR\_MIN**, **SHRT\_MIN**, **FLT\_MIN**, **DBL\_MIN**, etc.

189) Equivalent to **CHAR\_MAX**, **SHRT\_MAX**, **FLT\_MAX**, **DBL\_MAX**, etc.

190) **lowest()** is necessary because not all floating-point representations have a smallest (most negative) value that is the negative of the largest (most positive) finite value.

11 For floating-point types, the number of `radix` digits in the mantissa.<sup>191</sup>

```
static constexpr int digits10;
```

12 Number of base 10 digits that can be represented without change.<sup>192</sup>

13 Meaningful for all specializations in which `is_bounded != false`.

```
static constexpr int max_digits10;
```

14 Number of base 10 digits required to ensure that values which differ are always differentiated.

15 Meaningful for all floating-point types.

```
static constexpr bool is_signed;
```

16 `true` if the type is signed.

17 Meaningful for all specializations.

```
static constexpr bool is_integer;
```

18 `true` if the type is integer.

19 Meaningful for all specializations.

```
static constexpr bool is_exact;
```

20 `true` if the type uses an exact representation. All integer types are exact, but not all exact types are integer. For example, rational and fixed-exponent representations are exact but not integer.

21 Meaningful for all specializations.

```
static constexpr int radix;
```

22 For floating types, specifies the base or radix of the exponent representation (often 2).<sup>193</sup>

23 For integer types, specifies the base of the representation.<sup>194</sup>

24 Meaningful for all specializations.

```
static constexpr T epsilon() noexcept;
```

25 Machine epsilon: the difference between 1 and the least value greater than 1 that is representable.<sup>195</sup>

26 Meaningful for all floating-point types.

```
static constexpr T round_error() noexcept;
```

27 Measure of the maximum rounding error.<sup>196</sup>

```
static constexpr int min_exponent;
```

28 Minimum negative integer such that `radix` raised to the power of one less than that integer is a normalized floating-point number.<sup>197</sup>

29 Meaningful for all floating-point types.

```
static constexpr int min_exponent10;
```

---

191) Equivalent to `FLT_MANT_DIG`, `DBL_MANT_DIG`, `LDBL_MANT_DIG`.

192) Equivalent to `FLT_DIG`, `DBL_DIG`, `LDBL_DIG`.

193) Equivalent to `FLT_RADIX`.

194) Distinguishes types with bases other than 2 (e.g. BCD).

195) Equivalent to `FLT_EPSILON`, `DBL_EPSILON`, `LDBL_EPSILON`.

196) Rounding error is described in LIA-1 Section 5.2.4 and Annex C Rationale Section C.5.2.4 — Rounding and rounding constants.

197) Equivalent to `FLT_MIN_EXP`, `DBL_MIN_EXP`, `LDBL_MIN_EXP`.

30 Minimum negative integer such that 10 raised to that power is in the range of normalized floating-point numbers.<sup>198</sup>

31 Meaningful for all floating-point types.

```
static constexpr int max_exponent;
```

32 Maximum positive integer such that **radix** raised to the power one less than that integer is a representable finite floating-point number.<sup>199</sup>

33 Meaningful for all floating-point types.

```
static constexpr int max_exponent10;
```

34 Maximum positive integer such that 10 raised to that power is in the range of representable finite floating-point numbers.<sup>200</sup>

35 Meaningful for all floating-point types.

```
static constexpr bool has_infinity;
```

36 **true** if the type has a representation for positive infinity.

37 Meaningful for all floating-point types.

38 Shall be **true** for all specializations in which **is\_iec559** **!= false**.

```
static constexpr bool has_quiet_NaN;
```

39 **true** if the type has a representation for a quiet (non-signaling) “Not a Number”.<sup>201</sup>

40 Meaningful for all floating-point types.

41 Shall be **true** for all specializations in which **is\_iec559** **!= false**.

```
static constexpr bool has_signaling_NaN;
```

42 **true** if the type has a representation for a signaling “Not a Number”.<sup>202</sup>

43 Meaningful for all floating-point types.

44 Shall be **true** for all specializations in which **is\_iec559** **!= false**.

```
static constexpr float_denorm_style has_denorm;
```

45 **denorm\_present** if the type allows subnormal values (variable number of exponent bits)<sup>203</sup>, **denorm\_absent** if the type does not allow subnormal values, and **denorm\_indeterminate** if it is indeterminate at compile time whether the type allows subnormal values.

46 Meaningful for all floating-point types.

```
static constexpr bool has_denorm_loss;
```

47 **true** if loss of accuracy is detected as a denormalization loss, rather than as an inexact result.<sup>204</sup>

```
static constexpr T infinity() noexcept;
```

48 Representation of positive infinity, if available.<sup>205</sup>

198) Equivalent to FLT\_MIN\_10\_EXP, DBL\_MIN\_10\_EXP, LDBL\_MIN\_10\_EXP.

199) Equivalent to FLT\_MAX\_EXP, DBL\_MAX\_EXP, LDBL\_MAX\_EXP.

200) Equivalent to FLT\_MAX\_10\_EXP, DBL\_MAX\_10\_EXP, LDBL\_MAX\_10\_EXP.

201) Required by LIA-1.

202) Required by LIA-1.

203) Required by LIA-1.

204) See ISO/IEC/IEEE 60559.

205) Required by LIA-1.

49 Meaningful for all specializations for which `has_infinity != false`. Required in specializations for which `is_iec559 != false`.

```
static constexpr T quiet_NaN() noexcept;
```

50 Representation of a quiet “Not a Number”, if available.<sup>206</sup>

51 Meaningful for all specializations for which `has_quiet_NaN != false`. Required in specializations for which `is_iec559 != false`.

```
static constexpr T signaling_NaN() noexcept;
```

52 Representation of a signaling “Not a Number”, if available.<sup>207</sup>

53 Meaningful for all specializations for which `has_signaling_NaN != false`. Required in specializations for which `is_iec559 != false`.

```
static constexpr T denorm_min() noexcept;
```

54 Minimum positive subnormal value.<sup>208</sup>

55 Meaningful for all floating-point types.

56 In specializations for which `has_denorm == false`, returns the minimum positive normalized value.

```
static constexpr bool is_iec559;
```

57 `true` if and only if the type adheres to ISO/IEC/IEEE 60559.<sup>209</sup>

58 Meaningful for all floating-point types.

```
static constexpr bool is_bounded;
```

59 `true` if the set of values representable by the type is finite.<sup>210</sup> [*Note: All fundamental types (6.9.1) are bounded. This member would be `false` for arbitrary precision types. — end note*]

60 Meaningful for all specializations.

```
static constexpr bool is_modulo;
```

61 `true` if the type is modulo.<sup>211</sup> A type is modulo if, for any operation involving `+`, `-`, or `*` on values of that type whose result would fall outside the range `[min(), max()]`, the value returned differs from the true value by an integer multiple of `max() - min() + 1`.

62 [*Example: `is_modulo` is `false` for signed integer types (6.9.1) unless an implementation, as an extension to this International Standard, defines signed integer overflow to wrap. — end example*]

63 Meaningful for all specializations.

```
static constexpr bool traps;
```

64 `true` if, at program startup, there exists a value of the type that would cause an arithmetic operation using that value to trap.<sup>212</sup>

65 Meaningful for all specializations.

```
static constexpr bool tinyness_before;
```

---

206) Required by LIA-1.

207) Required by LIA-1.

208) Required by LIA-1.

209) ISO/IEC/IEEE 60559:2011 is the same as IEEE 754-2008.

210) Required by LIA-1.

211) Required by LIA-1.

212) Required by LIA-1.

66 true if tinyness is detected before rounding.<sup>213</sup>

67 Meaningful for all floating-point types.

```
static constexpr float_round_style round_style;
```

68 The rounding style for the type.<sup>214</sup>

69 Meaningful for all floating-point types. Specializations for integer types shall return `round_toward_zero`.

#### 21.3.4.2 numeric\_limits specializations

[numeric.special]

<sup>1</sup> All members shall be provided for all specializations. However, many values are only required to be meaningful under certain conditions (for example, `epsilon()` is only meaningful if `is_integer` is `false`). Any value that is not “meaningful” shall be set to 0 or `false`.

<sup>2</sup> [Example:

```
namespace std {
 template<> class numeric_limits<float> {
 public:
 static constexpr bool is_specialized = true;

 static constexpr float min() noexcept { return 1.17549435E-38F; }
 static constexpr float max() noexcept { return 3.40282347E+38F; }
 static constexpr float lowest() noexcept { return -3.40282347E+38F; }

 static constexpr int digits = 24;
 static constexpr int digits10 = 6;
 static constexpr int max_digits10 = 9;

 static constexpr bool is_signed = true;
 static constexpr bool is_integer = false;
 static constexpr bool is_exact = false;

 static constexpr int radix = 2;
 static constexpr float epsilon() noexcept { return 1.19209290E-07F; }
 static constexpr float round_error() noexcept { return 0.5F; }

 static constexpr int min_exponent = -125;
 static constexpr int min_exponent10 = -37;
 static constexpr int max_exponent = +128;
 static constexpr int max_exponent10 = +38;

 static constexpr bool has_infinity = true;
 static constexpr bool has_quiet_NaN = true;
 static constexpr bool has_signaling_NaN = true;
 static constexpr float_denorm_style has_denorm = denorm_absent;
 static constexpr bool has_denorm_loss = false;

 static constexpr float infinity() noexcept { return value; }
 static constexpr float quiet_NaN() noexcept { return value; }
 static constexpr float signaling_NaN() noexcept { return value; }
 static constexpr float denorm_min() noexcept { return min(); }
```

213) Refer to ISO/IEC/IEEE 60559. Required by LIA-1.

214) Equivalent to FLT\_ROUNDS. Required by LIA-1.



```

static constexpr bool is_iec559 = true;
static constexpr bool is_bounded = true;
static constexpr bool is_modulo = false;
static constexpr bool traps = true;
static constexpr bool tinyness_before = true;

static constexpr float_round_style round_style = round_to_nearest;
};
}

```

— *end example*]

- <sup>3</sup> The specialization for bool shall be provided as follows:

```

namespace std {
 template<> class numeric_limits<bool> {
 public:
 static constexpr bool is_specialized = true;
 static constexpr bool min() noexcept { return false; }
 static constexpr bool max() noexcept { return true; }
 static constexpr bool lowest() noexcept { return false; }

 static constexpr int digits = 1;
 static constexpr int digits10 = 0;
 static constexpr int max_digits10 = 0;

 static constexpr bool is_signed = false;
 static constexpr bool is_integer = true;
 static constexpr bool is_exact = true;
 static constexpr int radix = 2;
 static constexpr bool epsilon() noexcept { return 0; }
 static constexpr bool round_error() noexcept { return 0; }

 static constexpr int min_exponent = 0;
 static constexpr int min_exponent10 = 0;
 static constexpr int max_exponent = 0;
 static constexpr int max_exponent10 = 0;

 static constexpr bool has_infinity = false;
 static constexpr bool has_quiet_NaN = false;
 static constexpr bool has_signaling_NaN = false;
 static constexpr float_denorm_style has_denorm = denorm_absent;
 static constexpr bool has_denorm_loss = false;
 static constexpr bool infinity() noexcept { return 0; }
 static constexpr bool quiet_NaN() noexcept { return 0; }
 static constexpr bool signaling_NaN() noexcept { return 0; }
 static constexpr bool denorm_min() noexcept { return 0; }

 static constexpr bool is_iec559 = false;
 static constexpr bool is_bounded = true;
 static constexpr bool is_modulo = false;

 static constexpr bool traps = false;
 static constexpr bool tinyness_before = false;
 static constexpr float_round_style round_style = round_toward_zero;
 };
}

```

**21.3.5 Header <climits> synopsis****[climits.syn]**

```

#define CHAR_BIT see below
#define SCHAR_MIN see below
#define SCHAR_MAX see below
#define UCHAR_MAX see below
#define CHAR_MIN see below
#define CHAR_MAX see below
#define MB_LEN_MAX see below
#define SHRT_MIN see below
#define SHRT_MAX see below
#define USHRT_MAX see below
#define INT_MIN see below
#define INT_MAX see below
#define UINT_MAX see below
#define LONG_MIN see below
#define LONG_MAX see below
#define ULONG_MAX see below
#define LLONG_MIN see below
#define LLONG_MAX see below
#define ULLONG_MAX see below

```

- <sup>1</sup> The header <climits> defines all macros the same as the C standard library header <limits.h>. [Note: The types of the constants defined by macros in <climits> are not required to match the types to which the macros refer. — end note]

SEE ALSO: ISO C 5.2.4.2.1

**21.3.6 Header <cfloat> synopsis****[cfloat.syn]**

```

#define FLT_ROUNDS see below
#define FLT_EVAL_METHOD see below
#define FLT_HAS_SUBNORM see below
#define DBL_HAS_SUBNORM see below
#define LDBL_HAS_SUBNORM see below
#define FLT_RADIX see below
#define FLT_MANT_DIG see below
#define DBL_MANT_DIG see below
#define LDBL_MANT_DIG see below
#define FLT_DECIMAL_DIG see below
#define DBL_DECIMAL_DIG see below
#define LDBL_DECIMAL_DIG see below
#define DECIMAL_DIG see below
#define FLT_DIG see below
#define DBL_DIG see below
#define LDBL_DIG see below
#define FLT_MIN_EXP see below
#define DBL_MIN_EXP see below
#define LDBL_MIN_EXP see below
#define FLT_MIN_10_EXP see below
#define DBL_MIN_10_EXP see below
#define LDBL_MIN_10_EXP see below
#define FLT_MAX_EXP see below
#define DBL_MAX_EXP see below
#define LDBL_MAX_EXP see below
#define FLT_MAX_10_EXP see below
#define DBL_MAX_10_EXP see below
#define LDBL_MAX_10_EXP see below

```

```

#define FLT_MAX see below
#define DBL_MAX see below
#define LDBL_MAX see below
#define FLT_EPSILON see below
#define DBL_EPSILON see below
#define LDBL_EPSILON see below
#define FLT_MIN see below
#define DBL_MIN see below
#define LDBL_MIN see below
#define FLT_TRUE_MIN see below
#define DBL_TRUE_MIN see below
#define LDBL_TRUE_MIN see below

```

- <sup>1</sup> The header <float> defines all macros the same as the C standard library header <float.h>.

SEE ALSO: ISO C 5.2.4.2.2

## 21.4 Integer types

[cstdint]

### 21.4.1 Header <cstdint> synopsis

[cstdint.syn]

```

namespace std {
 using int8_t = signed integer type; // optional
 using int16_t = signed integer type; // optional
 using int32_t = signed integer type; // optional
 using int64_t = signed integer type; // optional

 using int_fast8_t = signed integer type;
 using int_fast16_t = signed integer type;
 using int_fast32_t = signed integer type;
 using int_fast64_t = signed integer type;

 using int_least8_t = signed integer type;
 using int_least16_t = signed integer type;
 using int_least32_t = signed integer type;
 using int_least64_t = signed integer type;

 using intmax_t = signed integer type;
 using intptr_t = signed integer type; // optional

 using uint8_t = unsigned integer type; // optional
 using uint16_t = unsigned integer type; // optional
 using uint32_t = unsigned integer type; // optional
 using uint64_t = unsigned integer type; // optional

 using uint_fast8_t = unsigned integer type;
 using uint_fast16_t = unsigned integer type;
 using uint_fast32_t = unsigned integer type;
 using uint_fast64_t = unsigned integer type;

 using uint_least8_t = unsigned integer type;
 using uint_least16_t = unsigned integer type;
 using uint_least32_t = unsigned integer type;
 using uint_least64_t = unsigned integer type;

 using uintmax_t = unsigned integer type;
 using uintptr_t = unsigned integer type; // optional
}

```

- <sup>1</sup> The header also defines numerous macros of the form:

```
INT_[FAST LEAST]{8 16 32 64}_MIN
[U]INT_[FAST LEAST]{8 16 32 64}_MAX
INT{MAX PTR}_MIN
[U]INT{MAX PTR}_MAX
{PTRDIFF SIG_ATOMIC_WCHAR WINT}{_MAX _MIN}
SIZE_MAX
```

plus function macros of the form:

```
[U]INT{8 16 32 64 MAX}_C
```

- <sup>2</sup> The header defines all types and macros the same as the C standard library header `<stdint.h>`.

SEE ALSO: ISO C 7.20.

## 21.5 Start and termination

[support.start.term]

- <sup>1</sup> [Note: The header `<stdlib.h>` (21.2.2) declares the functions described in this subclause. — end note]

```
[[noreturn]] void _Exit(int status) noexcept;
```

- <sup>2</sup> *Effects:* This function has the semantics specified in the C standard library.

- <sup>3</sup> *Remarks:* The program is terminated without executing destructors for objects of automatic, thread, or static storage duration and without calling functions passed to `atexit()` (6.6.4). The function `_Exit` is signal-safe (21.10.3).

```
[[noreturn]] void abort() noexcept;
```

- <sup>4</sup> *Effects:* This function has the semantics specified in the C standard library.

- <sup>5</sup> *Remarks:* The program is terminated without executing destructors for objects of automatic, thread, or static storage duration and without calling functions passed to `atexit()` (6.6.4). The function `abort` is signal-safe (21.10.3).

```
int atexit(c-atexit-handler* f) noexcept;
```

```
int atexit(atexit-handler* f) noexcept;
```

- <sup>6</sup> *Effects:* The `atexit()` functions register the function pointed to by `f` to be called without arguments at normal program termination. It is unspecified whether a call to `atexit()` that does not happen before (4.7) a call to `exit()` will succeed. [Note: The `atexit()` functions do not introduce a data race (20.5.5.9). — end note]

- <sup>7</sup> *Implementation limits:* The implementation shall support the registration of at least 32 functions.

- <sup>8</sup> *Returns:* The `atexit()` function returns zero if the registration succeeds, nonzero if it fails.

```
[[noreturn]] void exit(int status);
```

- <sup>9</sup> *Effects:*

- (9.1) — First, objects with thread storage duration and associated with the current thread are destroyed. Next, objects with static storage duration are destroyed and functions registered by calling `atexit` are called.<sup>215</sup> See 6.6.4 for the order of destructions and calls. (Automatic objects are not destroyed as a result of calling `exit()`.)<sup>216</sup>

If control leaves a registered function called by `exit` because the function does not provide a handler for a thrown exception, `std::terminate()` shall be called (18.5.1).

<sup>215</sup>) A function is called for every time it is registered.

<sup>216</sup>) Objects with automatic storage duration are all destroyed in a program whose `main` function (6.6.1) contains no automatic objects and executes the call to `exit()`. Control can be transferred directly to such a `main` function by throwing an exception that is caught in `main`.

- (9.2) — Next, all open C streams (as mediated by the function signatures declared in `<stdio>`) with unwritten buffered data are flushed, all open C streams are closed, and all files created by calling `tmpfile()` are removed.
- (9.3) — Finally, control is returned to the host environment. If `status` is zero or `EXIT_SUCCESS`, an implementation-defined form of the status *successful termination* is returned. If `status` is `EXIT_FAILURE`, an implementation-defined form of the status *unsuccessful termination* is returned. Otherwise the status returned is implementation-defined.<sup>217</sup>

```
int at_quick_exit(c-atexit-handler* f) noexcept;
int at_quick_exit(atexit-handler* f) noexcept;
```

- 10 *Effects:* The `at_quick_exit()` functions register the function pointed to by `f` to be called without arguments when `quick_exit` is called. It is unspecified whether a call to `at_quick_exit()` that does not happen before (4.7) all calls to `quick_exit` will succeed. [Note: The `at_quick_exit()` functions do not introduce a data race (20.5.5.9). — end note] [Note: The order of registration may be indeterminate if `at_quick_exit` was called from more than one thread. — end note] [Note: The `at_quick_exit` registrations are distinct from the `atexit` registrations, and applications may need to call both registration functions with the same argument. — end note]

- 11 *Implementation limits:* The implementation shall support the registration of at least 32 functions.

- 12 *Returns:* Zero if the registration succeeds, nonzero if it fails.

```
[[noreturn]] void quick_exit(int status) noexcept;
```

- 13 *Effects:* Functions registered by calls to `at_quick_exit` are called in the reverse order of their registration, except that a function shall be called after any previously registered functions that had already been called at the time it was registered. Objects shall not be destroyed as a result of calling `quick_exit`. If control leaves a registered function called by `quick_exit` because the function does not provide a handler for a thrown exception, `std::terminate()` shall be called. [Note: A function registered via `at_quick_exit` is invoked by the thread that calls `quick_exit`, which can be a different thread than the one that registered it, so registered functions should not rely on the identity of objects with thread storage duration. — end note] After calling registered functions, `quick_exit` shall call `_Exit(status)`. [Note: The standard file buffers are not flushed. — end note]
- 14 *Remarks:* The function `quick_exit` is signal-safe (21.10.3) when the functions registered with `at_quick_exit` are.

SEE ALSO: 6.6, 6.6.4, ISO C 7.22.4.

## 21.6 Dynamic memory management

[support.dynamic]

- 1 The header `<new>` defines several functions that manage the allocation of dynamic storage in a program. It also defines components for reporting storage management errors.

### 21.6.1 Header `<new>` synopsis

[new.syn]

```
namespace std {
 class bad_alloc;
 class bad_array_new_length;
 enum class align_val_t : size_t {};
 struct nothrow_t { explicit nothrow_t() = default; };
 extern const nothrow_t nothrow;
 using new_handler = void (*);
 new_handler get_new_handler() noexcept;
 new_handler set_new_handler(new_handler new_p) noexcept;
```

<sup>217</sup>) The macros `EXIT_FAILURE` and `EXIT_SUCCESS` are defined in `<stdlib>`.

```

// 21.6.4, pointer optimization barrier
template <class T> constexpr T* launder(T* p) noexcept;

// 21.6.5, hardware interference size
inline constexpr size_t hardware_destructive_interference_size = implementation-defined;
inline constexpr size_t hardware_constructive_interference_size = implementation-defined;
}

void* operator new(std::size_t size);
void* operator new(std::size_t size, std::align_val_t alignment);
void* operator new(std::size_t size, const std::nothrow_t&) noexcept;
void* operator new(std::size_t size, std::align_val_t alignment,
 const std::nothrow_t&) noexcept;
void operator delete(void* ptr) noexcept;
void operator delete(void* ptr, std::size_t size) noexcept;
void operator delete(void* ptr, std::align_val_t alignment) noexcept;
void operator delete(void* ptr, std::size_t size, std::align_val_t alignment) noexcept;
void operator delete(void* ptr, const std::nothrow_t&) noexcept;
void operator delete(void* ptr, std::align_val_t alignment,
 const std::nothrow_t&) noexcept;
void* operator new[](std::size_t size);
void* operator new[](std::size_t size, std::align_val_t alignment);
void* operator new[](std::size_t size, const std::nothrow_t&) noexcept;
void* operator new[](std::size_t size, std::align_val_t alignment,
 const std::nothrow_t&) noexcept;
void operator delete[](void* ptr) noexcept;
void operator delete[](void* ptr, std::size_t size) noexcept;
void operator delete[](void* ptr, std::align_val_t alignment) noexcept;
void operator delete[](void* ptr, std::size_t size, std::align_val_t alignment) noexcept;
void operator delete[](void* ptr, const std::nothrow_t&) noexcept;
void operator delete[](void* ptr, std::align_val_t alignment,
 const std::nothrow_t&) noexcept;

void* operator new (std::size_t size, void* ptr) noexcept;
void* operator new[](std::size_t size, void* ptr) noexcept;
void operator delete (void* ptr, void*) noexcept;
void operator delete[](void* ptr, void*) noexcept;

```

SEE ALSO: 4.4, 6.7.4, 8.3.4, 8.3.5, 15.5, 23.10.

## 21.6.2 Storage allocation and deallocation [new.delete]

- <sup>1</sup> Except where otherwise specified, the provisions of 6.7.4 apply to the library versions of `operator new` and `operator delete`. If the value of an alignment argument passed to any of these functions is not a valid alignment value, the behavior is undefined.

### 21.6.2.1 Single-object forms [new.delete.single]

```

void* operator new(std::size_t size);
void* operator new(std::size_t size, std::align_val_t alignment);

```

- <sup>1</sup> *Effects:* The allocation functions (6.7.4.1) called by a *new-expression* (8.3.4) to allocate `size` bytes of storage. The second form is called for a type with new-extended alignment, and allocates storage with the specified alignment. The first form is called otherwise, and allocates storage suitably aligned to represent any object of that size provided the object's type does not have new-extended alignment.

- <sup>2</sup> *Replaceable:* A C++ program may define functions with either of these function signatures, and thereby

displace the default versions defined by the C++ standard library.

3 *Required behavior:* Return a non-null pointer to suitably aligned storage (6.7.4), or else throw a `bad_alloc` exception. This requirement is binding on any replacement versions of these functions.

4 *Default behavior:*

- (4.1) — Executes a loop: Within the loop, the function first attempts to allocate the requested storage. Whether the attempt involves a call to the C standard library functions `malloc` or `aligned_alloc` is unspecified.
- (4.2) — Returns a pointer to the allocated storage if the attempt is successful. Otherwise, if the current `new_handler` (21.6.3.5) is a null pointer value, throws `bad_alloc`.
- (4.3) — Otherwise, the function calls the current `new_handler` function (21.6.3.3). If the called function returns, the loop repeats.
- (4.4) — The loop terminates when an attempt to allocate the requested storage is successful or when a called `new_handler` function does not return.

```
void* operator new(std::size_t size, const std::nothrow_t&) noexcept;
```

```
void* operator new(std::size_t size, std::align_val_t alignment, const std::nothrow_t&) noexcept;
```

5 *Effects:* Same as above, except that these are called by a placement version of a *new-expression* when a C++ program prefers a null pointer result as an error indication, instead of a `bad_alloc` exception.

6 *Replaceable:* A C++ program may define functions with either of these function signatures, and thereby displace the default versions defined by the C++ standard library.

7 *Required behavior:* Return a non-null pointer to suitably aligned storage (6.7.4), or else return a null pointer. Each of these `nothrow` versions of `operator new` returns a pointer obtained as if acquired from the (possibly replaced) corresponding non-placement function. This requirement is binding on any replacement versions of these functions.

8 *Default behavior:* Calls `operator new(size)`, or `operator new(size, alignment)`, respectively. If the call returns normally, returns the result of that call. Otherwise, returns a null pointer.

9 [ *Example:*

```
T* p1 = new T; // throws bad_alloc if it fails
T* p2 = new(nothrow) T; // returns nullptr if it fails
```

— *end example*]

```
void operator delete(void* ptr) noexcept;
```

```
void operator delete(void* ptr, std::size_t size) noexcept;
```

```
void operator delete(void* ptr, std::align_val_t alignment) noexcept;
```

```
void operator delete(void* ptr, std::size_t size, std::align_val_t alignment) noexcept;
```

10 *Effects:* The deallocation functions (6.7.4.2) called by a *delete-expression* to render the value of `ptr` invalid.

11 *Replaceable:* A C++ program may define functions with any of these function signatures, and thereby displace the default versions defined by the C++ standard library. If a function without a `size` parameter is defined, the program should also define the corresponding function with a `size` parameter. If a function with a `size` parameter is defined, the program shall also define the corresponding version without the `size` parameter. [ *Note:* The default behavior below may change in the future, which will require replacing both deallocation functions when replacing the allocation function. — *end note* ]

12 *Requires:* `ptr` shall be a null pointer or its value shall represent the address of a block of memory allocated by an earlier call to a (possibly replaced) `operator new(std::size_t)` or `operator new(std::size_t, std::align_val_t)` which has not been invalidated by an intervening call to `operator delete`.

- 13 *Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.
- 14 *Requires:* If the `alignment` parameter is not present, `ptr` shall have been returned by an allocation function without an `alignment` parameter. If present, the `alignment` argument shall equal the `alignment` argument passed to the allocation function that returned `ptr`. If present, the `size` argument shall equal the `size` argument passed to the allocation function that returned `ptr`.
- 15 *Required behavior:* A call to an `operator delete` with a `size` parameter may be changed to a call to the corresponding `operator delete` without a `size` parameter, without affecting memory allocation. [ *Note:* A conforming implementation is for `operator delete(void* ptr, std::size_t size)` to simply call `operator delete(ptr)`. — end note ]
- 16 *Default behavior:* The functions that have a `size` parameter forward their other parameters to the corresponding function without a `size` parameter. [ *Note:* See the note in the above *Replaceable:* paragraph. — end note ]
- 17 *Default behavior:* If `ptr` is null, does nothing. Otherwise, reclaims the storage allocated by the earlier call to `operator new`.
- 18 *Remarks:* It is unspecified under what conditions part or all of such reclaimed storage will be allocated by subsequent calls to `operator new` or any of `aligned_alloc`, `calloc`, `malloc`, or `realloc`, declared in `<cstdlib>`.

```
void operator delete(void* ptr, const std::nothrow_t&) noexcept;
void operator delete(void* ptr, std::align_val_t alignment, const std::nothrow_t&) noexcept;
```

- 19 *Effects:* The deallocation functions (6.7.4.2) called by the implementation to render the value of `ptr` invalid when the constructor invoked from a nothrow placement version of the *new-expression* throws an exception.
- 20 *Replaceable:* A C++ program may define functions with either of these function signatures, and thereby displace the default versions defined by the C++ standard library.
- 21 *Requires:* `ptr` shall be a null pointer or its value shall represent the address of a block of memory allocated by an earlier call to a (possibly replaced) `operator new(std::size_t)` or `operator new(std::size_t, std::align_val_t)` which has not been invalidated by an intervening call to `operator delete`.
- 22 *Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.
- 23 *Requires:* If the `alignment` parameter is not present, `ptr` shall have been returned by an allocation function without an `alignment` parameter. If present, the `alignment` argument shall equal the `alignment` argument passed to the allocation function that returned `ptr`.
- 24 *Default behavior:* Calls `operator delete(ptr)`, or `operator delete(ptr, alignment)`, respectively.

### 21.6.2.2 Array forms

[**new.delete.array**]

```
void* operator new[](std::size_t size);
void* operator new[](std::size_t size, std::align_val_t alignment);
```

- 1 *Effects:* The allocation functions (6.7.4.1) called by the array form of a *new-expression* (8.3.4) to allocate `size` bytes of storage. The second form is called for a type with new-extended alignment, and allocates storage with the specified alignment. The first form is called otherwise, and allocates storage suitably aligned to represent any array object of that size or smaller, provided the object's type does not have new-extended alignment.<sup>218</sup>

<sup>218</sup>) It is not the direct responsibility of `operator new[]` or `operator delete[]` to note the repetition count or element size of the array. Those operations are performed elsewhere in the array *new* and *delete* expressions. The array *new* expression, may,



*Replaceable:* A C++ program may define functions with either of these function signatures, and thereby displace the default versions defined by the C++ standard library.

*Required behavior:* Same as for the corresponding single-object forms. This requirement is binding on any replacement versions of these functions.

*Default behavior:* Returns `operator new(size)`, or `operator new(size, alignment)`, respectively.

```
void* operator new[](std::size_t size, const std::nothrow_t&) noexcept;
void* operator new[](std::size_t size, std::align_val_t alignment, const std::nothrow_t&) noexcept;
```

*Effects:* Same as above, except that these are called by a placement version of a *new-expression* when a C++ program prefers a null pointer result as an error indication, instead of a `bad_alloc` exception.

*Replaceable:* A C++ program may define functions with either of these function signatures, and thereby displace the default versions defined by the C++ standard library.

*Required behavior:* Return a non-null pointer to suitably aligned storage (6.7.4), or else return a null pointer. Each of these `nothrow` versions of `operator new[]` returns a pointer obtained as if acquired from the (possibly replaced) corresponding non-placement function. This requirement is binding on any replacement versions of these functions.

*Default behavior:* Calls `operator new[](size)`, or `operator new[](size, alignment)`, respectively. If the call returns normally, returns the result of that call. Otherwise, returns a null pointer.

```
void operator delete[](void* ptr) noexcept;
void operator delete[](void* ptr, std::size_t size) noexcept;
void operator delete[](void* ptr, std::align_val_t alignment) noexcept;
void operator delete[](void* ptr, std::size_t size, std::align_val_t alignment) noexcept;
```

*Effects:* The deallocation functions (6.7.4.2) called by the array form of a *delete-expression* to render the value of `ptr` invalid.

*Replaceable:* A C++ program may define functions with any of these function signatures, and thereby displace the default versions defined by the C++ standard library. If a function without a `size` parameter is defined, the program should also define the corresponding function with a `size` parameter. If a function with a `size` parameter is defined, the program shall also define the corresponding version without the `size` parameter. [Note: The default behavior below may change in the future, which will require replacing both deallocation functions when replacing the allocation function. — end note]

*Requires:* `ptr` shall be a null pointer or its value shall represent the address of a block of memory allocated by an earlier call to a (possibly replaced) `operator new[](std::size_t)` or `operator new[](std::size_t, std::align_val_t)` which has not been invalidated by an intervening call to `operator delete[]`.

*Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.

*Requires:* If the `alignment` parameter is not present, `ptr` shall have been returned by an allocation function without an `alignment` parameter. If present, the `alignment` argument shall equal the `alignment` argument passed to the allocation function that returned `ptr`. If present, the `size` argument shall equal the `size` argument passed to the allocation function that returned `ptr`.

*Required behavior:* A call to an `operator delete[]` with a `size` parameter may be changed to a call to the corresponding `operator delete[]` without a `size` parameter, without affecting memory allocation. [Note: A conforming implementation is for `operator delete[](void* ptr, std::size_t size)` to simply call `operator delete[](ptr)`. — end note]

---

however, increase the `size` argument to `operator new[]` to obtain space to store supplemental information.

- 15 *Default behavior:* The functions that have a `size` parameter forward their other parameters to the corresponding function without a `size` parameter. The functions that do not have a `size` parameter forward their parameters to the corresponding `operator delete` (single-object) function.

```
void operator delete[](void* ptr, const std::nothrow_t&) noexcept;
void operator delete[](void* ptr, std::align_val_t alignment, const std::nothrow_t&) noexcept;
```

- 16 *Effects:* The deallocation functions (6.7.4.2) called by the implementation to render the value of `ptr` invalid when the constructor invoked from a `nothrow` placement version of the array *new-expression* throws an exception.
- 17 *Replaceable:* A C++ program may define functions with either of these function signatures, and thereby displace the default versions defined by the C++ standard library.
- 18 *Requires:* `ptr` shall be a null pointer or its value shall represent the address of a block of memory allocated by an earlier call to a (possibly replaced) `operator new[](std::size_t)` or `operator new[](std::size_t, std::align_val_t)` which has not been invalidated by an intervening call to `operator delete[]`.
- 19 *Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.
- 20 *Requires:* If the `alignment` parameter is not present, `ptr` shall have been returned by an allocation function without an `alignment` parameter. If present, the `alignment` argument shall equal the `alignment` argument passed to the allocation function that returned `ptr`.
- 21 *Default behavior:* Calls `operator delete[](ptr)`, or `operator delete[](ptr, alignment)`, respectively.

### 21.6.2.3 Non-allocating forms

[`new.delete.placement`]

- 1 These functions are reserved; a C++ program may not define functions that displace the versions in the C++ standard library (20.5.4). The provisions of 6.7.4 do not apply to these reserved placement forms of `operator new` and `operator delete`.

```
void* operator new(std::size_t size, void* ptr) noexcept;
```

- 2 *Returns:* `ptr`.

- 3 *Remarks:* Intentionally performs no other action.

- 4 [*Example:* This can be useful for constructing an object at a known address:

```
void* place = operator new(sizeof(Something));
Something* p = new (place) Something();
```

— *end example*]

```
void* operator new[](std::size_t size, void* ptr) noexcept;
```

- 5 *Returns:* `ptr`.

- 6 *Remarks:* Intentionally performs no other action.

```
void operator delete(void* ptr, void*) noexcept;
```

- 7 *Effects:* Intentionally performs no action.

- 8 *Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.

- 9 *Remarks:* Default function called when any part of the initialization in a placement *new-expression* that invokes the library's non-array placement operator `new` terminates by throwing an exception (8.3.4).

```
void operator delete[](void* ptr, void*) noexcept;
```

10 *Effects:* Intentionally performs no action.

11 *Requires:* If an implementation has strict pointer safety (6.7.4.3) then `ptr` shall be a safely-derived pointer.

12 *Remarks:* Default function called when any part of the initialization in a placement *new-expression* that invokes the library's array placement operator `new` terminates by throwing an exception (8.3.4).

#### 21.6.2.4 Data races

[new.delete.dataraces]

- 1 For purposes of determining the existence of data races, the library versions of `operator new`, user replacement versions of global `operator new`, the C standard library functions `aligned_alloc`, `calloc`, and `malloc`, the library versions of `operator delete`, user replacement versions of `operator delete`, the C standard library function `free`, and the C standard library function `realloc` shall not introduce a data race (20.5.5.9). Calls to these functions that allocate or deallocate a particular unit of storage shall occur in a single total order, and each such deallocation call shall happen before (4.7) the next allocation (if any) in this order.

### 21.6.3 Storage allocation errors

[alloc.errors]

#### 21.6.3.1 Class `bad_alloc`

[bad.alloc]

```
namespace std {
 class bad_alloc : public exception {
 public:
 bad_alloc() noexcept;
 bad_alloc(const bad_alloc&) noexcept;
 bad_alloc& operator=(const bad_alloc&) noexcept;
 const char* what() const noexcept override;
 };
}
```

- 1 The class `bad_alloc` defines the type of objects thrown as exceptions by the implementation to report a failure to allocate storage.

```
bad_alloc() noexcept;
```

- 2 *Effects:* Constructs an object of class `bad_alloc`.

```
bad_alloc(const bad_alloc&) noexcept;
bad_alloc& operator=(const bad_alloc&) noexcept;
```

- 3 *Effects:* Copies an object of class `bad_alloc`.

```
const char* what() const noexcept override;
```

- 4 *Returns:* An implementation-defined NTBS.

- 5 *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4).

#### 21.6.3.2 Class `bad_array_new_length`

[new.badlength]

```
namespace std {
 class bad_array_new_length : public bad_alloc {
 public:
 bad_array_new_length() noexcept;
 const char* what() const noexcept override;
 };
}
```

- <sup>1</sup> The class `bad_array_new_length` defines the type of objects thrown as exceptions by the implementation to report an attempt to allocate an array of size less than zero or greater than an implementation-defined limit (8.3.4).

```
bad_array_new_length() noexcept;
```

- <sup>2</sup> *Effects:* constructs an object of class `bad_array_new_length`.

```
const char* what() const noexcept override;
```

- <sup>3</sup> *Returns:* An implementation-defined NTBS.

- <sup>4</sup> *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4).

### 21.6.3.3 Type `new_handler` [new.handler]

```
using new_handler = void (*)();
```

- <sup>1</sup> The type of a *handler function* to be called by `operator new()` or `operator new[]()` (21.6.2) when they cannot satisfy a request for additional storage.

- <sup>2</sup> *Required behavior:* A `new_handler` shall perform one of the following:

- (2.1) — make more storage available for allocation and then return;
- (2.2) — throw an exception of type `bad_alloc` or a class derived from `bad_alloc`;
- (2.3) — terminate execution of the program without returning to the caller.

### 21.6.3.4 `set_new_handler` [set.new.handler]

```
new_handler set_new_handler(new_handler new_p) noexcept;
```

- <sup>1</sup> *Effects:* Establishes the function designated by `new_p` as the current `new_handler`.

- <sup>2</sup> *Returns:* The previous `new_handler`.

- <sup>3</sup> *Remarks:* The initial `new_handler` is a null pointer.

### 21.6.3.5 `get_new_handler` [get.new.handler]

```
new_handler get_new_handler() noexcept;
```

- <sup>1</sup> *Returns:* The current `new_handler`. [Note: This may be a null pointer value. — end note]

### 21.6.4 Pointer optimization barrier [ptr.laundry]

```
template <class T> constexpr T* laundry(T* p) noexcept;
```

- <sup>1</sup> *Requires:* `p` represents the address *A* of a byte in memory. An object *X* that is within its lifetime (6.8) and whose type is similar (7.5) to `T` is located at the address *A*. All bytes of storage that would be reachable through the result are reachable through `p` (see below).

- <sup>2</sup> *Returns:* A value of type `T *` that points to *X*.

- <sup>3</sup> *Remarks:* An invocation of this function may be used in a core constant expression whenever the value of its argument may be used in a core constant expression. A byte of storage is reachable through a pointer value that points to an object *Y* if it is within the storage occupied by *Y*, an object that is pointer-interconvertible with *Y*, or the immediately-enclosing array object if *Y* is an array element. The program is ill-formed if `T` is a function type or `cv void`.

- <sup>4</sup> [Note: If a new object is created in storage occupied by an existing object of the same type, a pointer to the original object can be used to refer to the new object unless the type contains `const` or reference

members; in the latter cases, this function can be used to obtain a usable pointer to the new object. See 6.8. — *end note*

5 [ *Example:*

```

 struct X { const int n; };
 X *p = new X{3};
 const int a = p->n;
 new (p) X{5}; // p does not point to new object (6.8) because X::n is const
 const int b = p->n; // undefined behavior
 const int c = std::launder(p)->n; // OK

```

— *end example*]

### 21.6.5 Hardware interference size

[hardware.interference]

```
inline constexpr size_t hardware_destructive_interference_size = implementation-defined;
```

- <sup>1</sup> This number is the minimum recommended offset between two concurrently-accessed objects to avoid additional performance degradation due to contention introduced by the implementation. It shall be at least `alignof(max_align_t)`.

[ *Example:*

```

 struct keep_apart {
 alignas(hardware_destructive_interference_size) atomic<int> cat;
 alignas(hardware_destructive_interference_size) atomic<int> dog;
 };

```

— *end example*]

```
inline constexpr size_t hardware_constructive_interference_size = implementation-defined;
```

- <sup>2</sup> This number is the maximum recommended size of contiguous memory occupied by two objects accessed with temporal locality by concurrent threads. It shall be at least `alignof(max_align_t)`.

[ *Example:*

```

 struct together {
 atomic<int> dog;
 int puppy;
 };
 struct kennel {
 // Other data members...
 alignas(sizeof(together)) together pack;
 // Other data members...
 };
 static_assert(sizeof(together) <= hardware_constructive_interference_size);

```

— *end example*]

### 21.7 Type identification

[support.rtti]

- <sup>1</sup> The header `<typeinfo>` defines a type associated with type information generated by the implementation. It also defines two types for reporting dynamic type identification errors.

#### 21.7.1 Header `<typeinfo>` synopsis

[typeinfo.syn]

```

namespace std {
 class type_info;
 class bad_cast;
 class bad_typeid;
}

```

SEE ALSO: [8.2.7](#), [8.2.8](#).

## 21.7.2 Class `type_info`

[[type.info](#)]

```
namespace std {
 class type_info {
 public:
 virtual ~type_info();
 bool operator==(const type_info& rhs) const noexcept;
 bool operator!=(const type_info& rhs) const noexcept;
 bool before(const type_info& rhs) const noexcept;
 size_t hash_code() const noexcept;
 const char* name() const noexcept;

 type_info(const type_info& rhs) = delete; // cannot be copied
 type_info& operator=(const type_info& rhs) = delete; // cannot be copied
 };
}
```

- <sup>1</sup> The class `type_info` describes type information generated by the implementation. Objects of this class effectively store a pointer to a name for the type, and an encoded value suitable for comparing two types for equality or collating order. The names, encoding rule, and collating sequence for types are all unspecified and may differ between programs.

```
bool operator==(const type_info& rhs) const noexcept;
```

- <sup>2</sup> *Effects:* Compares the current object with `rhs`.

- <sup>3</sup> *Returns:* `true` if the two values describe the same type.

```
bool operator!=(const type_info& rhs) const noexcept;
```

- <sup>4</sup> *Returns:* `!(*this == rhs)`.

```
bool before(const type_info& rhs) const noexcept;
```

- <sup>5</sup> *Effects:* Compares the current object with `rhs`.

- <sup>6</sup> *Returns:* `true` if `*this` precedes `rhs` in the implementation's collation order.

```
size_t hash_code() const noexcept;
```

- <sup>7</sup> *Returns:* An unspecified value, except that within a single execution of the program, it shall return the same value for any two `type_info` objects which compare equal.

- <sup>8</sup> *Remarks:* An implementation should return different values for two `type_info` objects which do not compare equal.

```
const char* name() const noexcept;
```

- <sup>9</sup> *Returns:* An implementation-defined NTBS.

- <sup>10</sup> *Remarks:* The message may be a null-terminated multibyte string ([20.4.2.1.5.2](#)), suitable for conversion and display as a `wstring` ([24.3](#), [25.4.1.4](#))

## 21.7.3 Class `bad_cast`

[[bad.cast](#)]

```
namespace std {
 class bad_cast : public exception {
 public:
 bad_cast() noexcept;
 bad_cast(const bad_cast&) noexcept;
 bad_cast& operator=(const bad_cast&) noexcept;
```

```

 const char* what() const noexcept override;
 };
}

```

- <sup>1</sup> The class `bad_cast` defines the type of objects thrown as exceptions by the implementation to report the execution of an invalid `dynamic_cast` expression (8.2.7).

```
bad_cast() noexcept;
```

- <sup>2</sup> *Effects:* Constructs an object of class `bad_cast`.

```
bad_cast(const bad_cast&) noexcept;
bad_cast& operator=(const bad_cast&) noexcept;
```

- <sup>3</sup> *Effects:* Copies an object of class `bad_cast`.

```
const char* what() const noexcept override;
```

- <sup>4</sup> *Returns:* An implementation-defined NTBS.

- <sup>5</sup> *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4)

#### 21.7.4 Class `bad_typeid`

[`bad.typeid`]

```

namespace std {
 class bad_typeid : public exception {
 public:
 bad_typeid() noexcept;
 bad_typeid(const bad_typeid&) noexcept;
 bad_typeid& operator=(const bad_typeid&) noexcept;
 const char* what() const noexcept override;
 };
}

```

- <sup>1</sup> The class `bad_typeid` defines the type of objects thrown as exceptions by the implementation to report a null pointer in a `typeid` expression (8.2.8).

```
bad_typeid() noexcept;
```

- <sup>2</sup> *Effects:* Constructs an object of class `bad_typeid`.

```
bad_typeid(const bad_typeid&) noexcept;
bad_typeid& operator=(const bad_typeid&) noexcept;
```

- <sup>3</sup> *Effects:* Copies an object of class `bad_typeid`.

```
const char* what() const noexcept override;
```

- <sup>4</sup> *Returns:* An implementation-defined NTBS.

- <sup>5</sup> *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4)

### 21.8 Exception handling

[`support.exception`]

- <sup>1</sup> The header `<exception>` defines several types and functions related to the handling of exceptions in a C++ program.

#### 21.8.1 Header `<exception>` synopsis

[`exception.syn`]

```

namespace std {
 class exception;
}

```

```

class bad_exception;
class nested_exception;

using terminate_handler = void (*)();
terminate_handler get_terminate() noexcept;
terminate_handler set_terminate(terminate_handler f) noexcept;
[[noreturn]] void terminate() noexcept;

int uncaught_exceptions() noexcept;

using exception_ptr = unspecified;

exception_ptr current_exception() noexcept;
[[noreturn]] void rethrow_exception(exception_ptr p);
template<class E> exception_ptr make_exception_ptr(E e) noexcept;

template <class T> [[noreturn]] void throw_with_nested(T&& t);
template <class E> void rethrow_if_nested(const E& e);
}

```

SEE ALSO: [18.5](#).

## 21.8.2 Class exception

[exception]

```

namespace std {
 class exception {
 public:
 exception() noexcept;
 exception(const exception&) noexcept;
 exception& operator=(const exception&) noexcept;
 virtual ~exception();
 virtual const char* what() const noexcept;
 };
}

```

- <sup>1</sup> The class `exception` defines the base class for the types of objects thrown as exceptions by C++ standard library components, and certain expressions, to report errors detected during program execution.
- <sup>2</sup> Each standard library class `T` that derives from class `exception` shall have a publicly accessible copy constructor and a publicly accessible copy assignment operator that do not exit with an exception. These member functions shall meet the following postcondition: If two objects `lhs` and `rhs` both have dynamic type `T` and `lhs` is a copy of `rhs`, then `strcmp(lhs.what(), rhs.what())` shall equal 0.

```
exception() noexcept;
```

- <sup>3</sup> *Effects:* Constructs an object of class `exception`.

```
exception(const exception& rhs) noexcept;
exception& operator=(const exception& rhs) noexcept;
```

- <sup>4</sup> *Effects:* Copies an `exception` object.

- <sup>5</sup> *Postconditions:* If `*this` and `rhs` both have dynamic type `exception` then the value of the expression `strcmp(what(), rhs.what())` shall equal 0.

```
virtual ~exception();
```

- <sup>6</sup> *Effects:* Destroys an object of class `exception`.

```
virtual const char* what() const noexcept;
```



*Returns:* An implementation-defined NTBS.

*Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4). The return value remains valid until the exception object from which it is obtained is destroyed or a non-`const` member function of the exception object is called.

### 21.8.3 Class `bad_exception`

[`bad.exception`]

```
namespace std {
 class bad_exception : public exception {
 public:
 bad_exception() noexcept;
 bad_exception(const bad_exception&) noexcept;
 bad_exception& operator=(const bad_exception&) noexcept;
 const char* what() const noexcept override;
 };
}
```

- <sup>1</sup> The class `bad_exception` defines the type of the object referenced by the `exception_ptr` returned from a call to `current_exception` (21.8.6) when the currently active exception object fails to copy.

```
bad_exception() noexcept;
```

- <sup>2</sup> *Effects:* Constructs an object of class `bad_exception`.

```
bad_exception(const bad_exception&) noexcept;
bad_exception& operator=(const bad_exception&) noexcept;
```

- <sup>3</sup> *Effects:* Copies an object of class `bad_exception`.

```
const char* what() const noexcept override;
```

- <sup>4</sup> *Returns:* An implementation-defined NTBS.

- <sup>5</sup> *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a `wstring` (24.3, 25.4.1.4).

### 21.8.4 Abnormal termination

[`exception.terminate`]

#### 21.8.4.1 Type `terminate_handler`

[`terminate.handler`]

```
using terminate_handler = void (*)();
```

- <sup>1</sup> The type of a *handler function* to be called by `std::terminate()` when terminating exception processing.

- <sup>2</sup> *Required behavior:* A `terminate_handler` shall terminate execution of the program without returning to the caller.

- <sup>3</sup> *Default behavior:* The implementation's default `terminate_handler` calls `abort()`.

#### 21.8.4.2 `set_terminate`

[`set.terminate`]

```
terminate_handler set_terminate(terminate_handler f) noexcept;
```

- <sup>1</sup> *Effects:* Establishes the function designated by `f` as the current handler function for terminating exception processing.

- <sup>2</sup> *Remarks:* It is unspecified whether a null pointer value designates the default `terminate_handler`.

- <sup>3</sup> *Returns:* The previous `terminate_handler`.

#### 21.8.4.3 `get_terminate`

[`get.terminate`]

```
terminate_handler get_terminate() noexcept;
```

- 1 *Returns:* The current `terminate_handler`. [*Note:* This may be a null pointer value. — *end note*]

#### 21.8.4.4 `terminate`

[`terminate`]

```
[[noreturn]] void terminate() noexcept;
```

- 1 *Remarks:* Called by the implementation when exception handling must be abandoned for any of several reasons (18.5.1). May also be called directly by the program.
- 2 *Effects:* Calls a `terminate_handler` function. It is unspecified which `terminate_handler` function will be called if an exception is active during a call to `set_terminate`. Otherwise calls the current `terminate_handler` function. [*Note:* A default `terminate_handler` is always considered a callable handler in this context. — *end note*]

#### 21.8.5 `uncaught_exceptions`

[`uncaught_exceptions`]

```
int uncaught_exceptions() noexcept;
```

- 1 *Returns:* The number of uncaught exceptions (18.5.2).
- 2 *Remarks:* When `uncaught_exceptions() > 0`, throwing an exception can result in a call of `std::terminate()` (18.5.1).

#### 21.8.6 Exception propagation

[`propagation`]

```
using exception_ptr = unspecified;
```

- 1 The type `exception_ptr` can be used to refer to an exception object.
- 2 `exception_ptr` shall satisfy the requirements of `NullablePointer` (20.5.3.3).
- 3 Two non-null values of type `exception_ptr` are equivalent and compare equal if and only if they refer to the same exception.
- 4 The default constructor of `exception_ptr` produces the null value of the type.
- 5 `exception_ptr` shall not be implicitly convertible to any arithmetic, enumeration, or pointer type.
- 6 [*Note:* An implementation might use a reference-counted smart pointer as `exception_ptr`. — *end note*]
- 7 For purposes of determining the presence of a data race, operations on `exception_ptr` objects shall access and modify only the `exception_ptr` objects themselves and not the exceptions they refer to. Use of `rethrow_exception` on `exception_ptr` objects that refer to the same exception object shall not introduce a data race. [*Note:* If `rethrow_exception` rethrows the same exception object (rather than a copy), concurrent access to that rethrown exception object may introduce a data race. Changes in the number of `exception_ptr` objects that refer to a particular exception do not introduce a data race. — *end note*]

```
exception_ptr current_exception() noexcept;
```

- 8 *Returns:* An `exception_ptr` object that refers to the currently handled exception (18.3) or a copy of the currently handled exception, or a null `exception_ptr` object if no exception is being handled. The referenced object shall remain valid at least as long as there is an `exception_ptr` object that refers to it. If the function needs to allocate memory and the attempt fails, it returns an `exception_ptr` object that refers to an instance of `bad_alloc`. It is unspecified whether the return values of two successive calls to `current_exception` refer to the same exception object. [*Note:* That is, it is unspecified whether `current_exception` creates a new copy each time it is called. — *end note*] If the attempt to copy the current exception object throws an exception, the function returns an `exception_ptr` object that

refers to the thrown exception or, if this is not possible, to an instance of `bad_exception`. [Note: The copy constructor of the thrown exception may also fail, so the implementation is allowed to substitute a `bad_exception` object to avoid infinite recursion. — end note]

```
[[noreturn]] void rethrow_exception(exception_ptr p);
```

9 *Requires:* `p` shall not be a null pointer.

10 *Throws:* The exception object to which `p` refers.

```
template<class E> exception_ptr make_exception_ptr(E e) noexcept;
```

11 *Effects:* Creates an `exception_ptr` object that refers to a copy of `e`, as if:

```
try {
 throw e;
} catch(...) {
 return current_exception();
}
```

12 [Note: This function is provided for convenience and efficiency reasons. — end note]

## 21.8.7 nested\_exception

[except.nested]

```
namespace std {
 class nested_exception {
 public:
 nested_exception() noexcept;
 nested_exception(const nested_exception&) noexcept = default;
 nested_exception& operator=(const nested_exception&) noexcept = default;
 virtual ~nested_exception() = default;

 // access functions
 [[noreturn]] void rethrow_nested() const;
 exception_ptr nested_ptr() const noexcept;
 };

 template<class T> [[noreturn]] void throw_with_nested(T&& t);
 template <class E> void rethrow_if_nested(const E& e);
}
```

1 The class `nested_exception` is designed for use as a mixin through multiple inheritance. It captures the currently handled exception and stores it for later use.

2 [Note: `nested_exception` has a virtual destructor to make it a polymorphic class. Its presence can be tested for with `dynamic_cast`. — end note]

```
nested_exception() noexcept;
```

3 *Effects:* The constructor calls `current_exception()` and stores the returned value.

```
[[noreturn]] void rethrow_nested() const;
```

4 *Effects:* If `nested_ptr()` returns a null pointer, the function calls `std::terminate()`. Otherwise, it throws the stored exception captured by `*this`.

```
exception_ptr nested_ptr() const noexcept;
```

5 *Returns:* The stored exception captured by this `nested_exception` object.

```
template <class T> [[noreturn]] void throw_with_nested(T&& t);
```

- 6       Let U be `decay_t<T>`.
- 7       *Requires:* U shall be CopyConstructible.
- 8       *Throws:* If `is_class_v<U> && !is_final_v<U> && !is_base_of_v<nested_exception, U>` is true, an exception of unspecified type that is publicly derived from both U and `nested_exception` and constructed from `std::forward<T>(t)`, otherwise `std::forward<T>(t)`.
- ```
template <class E> void rethrow_if_nested(const E& e);
```
- 9 *Effects:* If E is not a polymorphic class type, or if `nested_exception` is an inaccessible or ambiguous base class of E, there is no effect. Otherwise, performs:
- ```
 if (auto p = dynamic_cast<const nested_exception*>(addressof(e)))
 p->rethrow_nested();
```

## 21.9 Initializer lists

[support.initlist]

- <sup>1</sup> The header `<initializer_list>` defines a class template and several support functions related to list-initialization (see 11.6.4). All functions specified in this subclause are signal-safe (21.10.3).

### 21.9.1 Header `<initializer_list>` synopsis

[initializer\_list.syn]

```
namespace std {
 template<class E> class initializer_list {
 public:
 using value_type = E;
 using reference = const E&;
 using const_reference = const E&;
 using size_type = size_t;

 using iterator = const E*;
 using const_iterator = const E*;

 constexpr initializer_list() noexcept;

 constexpr size_t size() const noexcept; // number of elements
 constexpr const E* begin() const noexcept; // first element
 constexpr const E* end() const noexcept; // one past the last element
 };

 // 21.9.4, initializer list range access
 template<class E> constexpr const E* begin(initializer_list<E> il) noexcept;
 template<class E> constexpr const E* end(initializer_list<E> il) noexcept;
}
```

- <sup>1</sup> An object of type `initializer_list<E>` provides access to an array of objects of type `const E`. [Note: A pair of pointers or a pointer plus a length would be obvious representations for `initializer_list`. `initializer_list` is used to implement initializer lists as specified in 11.6.4. Copying an initializer list does not copy the underlying elements. — end note]
- <sup>2</sup> If an explicit specialization or partial specialization of `initializer_list` is declared, the program is ill-formed.

### 21.9.2 Initializer list constructors

[support.initlist.cons]

- ```
constexpr initializer_list() noexcept;
```
- ¹ *Effects:* Constructs an empty `initializer_list` object.
- ² *Postconditions:* `size() == 0`.

21.9.3 Initializer list access**[support.initlist.access]**

```
constexpr const E* begin() const noexcept;
```

- ¹ *Returns:* A pointer to the beginning of the array. If `size() == 0` the values of `begin()` and `end()` are unspecified but they shall be identical.

```
constexpr const E* end() const noexcept;
```

- ² *Returns:* `begin() + size()`.

```
constexpr size_t size() const noexcept;
```

- ³ *Returns:* The number of elements in the array.

- ⁴ *Complexity:* Constant time.

21.9.4 Initializer list range access**[support.initlist.range]**

```
template<class E> constexpr const E* begin(initializer_list<E> il) noexcept;
```

- ¹ *Returns:* `il.begin()`.

```
template<class E> constexpr const E* end(initializer_list<E> il) noexcept;
```

- ² *Returns:* `il.end()`.

21.10 Other runtime support**[support.runtime]**

- ¹ Headers `<csetjmp>` (nonlocal jumps), `<csignal>` (signal handling), `<cstdarg>` (variable arguments), and `<cstdlib>` (runtime environment `getenv`, `system`), provide further compatibility with C code.
- ² Calls to the function `getenv` (21.2.2) shall not introduce a data race (20.5.5.9) provided that nothing modifies the environment. [*Note:* Calls to the POSIX functions `setenv` and `putenv` modify the environment. — *end note*]
- ³ A call to the `setlocale` function (25.5) may introduce a data race with other calls to the `setlocale` function or with calls to functions that are affected by the current C locale. The implementation shall behave as if no library function other than `locale::global` calls the `setlocale` function.

21.10.1 Header `<cstdarg>` synopsis**[cstdarg.syn]**

```
namespace std {
    using va_list = see below;
}

#define va_arg(V, P) see below
#define va_copy(VDST, VSRC) see below
#define va_end(V) see below
#define va_start(V, P) see below
```

- ¹ The contents of the header `<cstdarg>` are the same as the C standard library header `<stdarg.h>`, with the following changes: The restrictions that ISO C places on the second parameter to the `va_start` macro in header `<stdarg.h>` are different in this International Standard. The parameter `parmN` is the rightmost parameter in the variable parameter list of the function definition (the one just before the ...).²¹⁹ If the parameter `parmN` is a pack expansion (17.5.3) or an entity resulting from a lambda capture (8.1.5), the program is ill-formed, no diagnostic required. If the parameter `parmN` is of a reference type, or of a type that is not compatible with the type that results when passing an argument for which there is no parameter, the behavior is undefined.

²¹⁹ Note that `va_start` is required to work as specified even if unary `operator&` is overloaded for the type of `parmN`.

SEE ALSO: ISO C 7.16.1.1.

21.10.2 Header <csetjmp> synopsis

[csetjmp.syn]

```
namespace std {
    using jmp_buf = see below;
    [[noreturn]] void longjmp(jmp_buf env, int val);
}
```

```
#define setjmp(env) see below
```

- ¹ The contents of the header <csetjmp> are the same as the C standard library header <setjmp.h>.
- ² The function signature `longjmp(jmp_buf jbuf, int val)` has more restricted behavior in this International Standard. A `setjmp/longjmp` call pair has undefined behavior if replacing the `setjmp` and `longjmp` by `catch` and `throw` would invoke any non-trivial destructors for any automatic objects.

SEE ALSO: ISO C 7.13.

21.10.3 Header <csignal> synopsis

[csignal.syn]

```
namespace std {
    using sig_atomic_t = see below;

    // 21.10.4, signal handlers
    extern "C" using signal_handler = void(int); // exposition only
    signal_handler* signal(int sig, signal_handler* func);

    int raise(int sig);
}

#define SIG_DFL see below
#define SIG_ERR see below
#define SIG_IGN see below
#define SIGABRT see below
#define SIGFPE see below
#define SIGILL see below
#define SIGINT see below
#define SIGSEGV see below
#define SIGTERM see below
```

- ¹ The contents of the header <csignal> are the same as the C standard library header <signal.h>.

21.10.4 Signal handlers

[support.signal]

- ¹ A call to the function `signal` synchronizes with any resulting invocation of the signal handler so installed.
- ² A *plain lock-free atomic operation* is an invocation of a function `f` from Clause 32, such that:
 - (2.1) — `f` is the function `atomic_is_lock_free()`, or
 - (2.2) — `f` is the member function `is_lock_free()`, or
 - (2.3) — `f` is a non-static member function invoked on an object `A`, such that `A.is_lock_free()` yields `true`, or
 - (2.4) — `f` is a non-member function, and for every pointer-to-atomic argument `A` passed to `f`, `atomic_is_lock_free(A)` yields `true`.
- ³ An evaluation is *signal-safe* unless it includes one of the following:
 - (3.1) — a call to any standard library function, except for plain lock-free atomic operations and functions explicitly identified as signal-safe. [*Note:* This implicitly excludes the use of `new` and `delete` expressions that rely on a library-provided memory allocator. — *end note*]

- (3.2) — an access to an object with thread storage duration;
- (3.3) — a `dynamic_cast` expression;
- (3.4) — throwing of an exception;
- (3.5) — control entering a *try-block* or *function-try-block*;
- (3.6) — initialization of a variable with static storage duration requiring dynamic initialization (6.6.3, 9.7)²²⁰; or
- (3.7) — waiting for the completion of the initialization of a variable with static storage duration (9.7).

A signal handler invocation has undefined behavior if it includes an evaluation that is not signal-safe.

- ⁴ The function `signal` is signal-safe if it is invoked with the first argument equal to the signal number corresponding to the signal that caused the invocation of the handler.

SEE ALSO: ISO C 7.14.

²²⁰) Such initialization might occur because it is the first odr-use (6.2) of that variable.

22 Diagnostics library

[diagnostics]

22.1 General

[diagnostics.general]

- ¹ This Clause describes components that C++ programs may use to detect and report error conditions.
- ² The following subclauses describe components for reporting several kinds of exceptional conditions, documenting program assertions, and a global variable for error number codes, as summarized in Table 33.

Table 33 — Diagnostics library summary

	Subclause	Header(s)
22.2	Exception classes	<stdexcept>
22.3	Assertions	<cassert>
22.4	Error numbers	<cerrno>
22.5	System error support	<system_error>

22.2 Exception classes

[std.exceptions]

- ¹ The C++ standard library provides classes to be used to report certain errors ([20.5.5.12](#)) in C++ programs. In the error model reflected in these classes, errors are divided into two broad categories: *logic* errors and *runtime* errors.
- ² The distinguishing characteristic of logic errors is that they are due to errors in the internal logic of the program. In theory, they are preventable.
- ³ By contrast, runtime errors are due to events beyond the scope of the program. They cannot be easily predicted in advance. The header <stdexcept> defines several types of predefined exceptions for reporting errors in a C++ program. These exceptions are related by inheritance.

22.2.1 Header <stdexcept> synopsis

[stdexcept.syn]

```

namespace std {
    class logic_error;
        class domain_error;
        class invalid_argument;
        class length_error;
        class out_of_range;
    class runtime_error;
        class range_error;
        class overflow_error;
        class underflow_error;
}

```

22.2.2 Class logic_error

[logic.error]

```

namespace std {
    class logic_error : public exception {
    public:
        explicit logic_error(const string& what_arg);
        explicit logic_error(const char* what_arg);
    };
}

```


- ¹ The class `logic_error` defines the type of objects thrown as exceptions to report errors presumably detectable before the program executes, such as violations of logical preconditions or class invariants.

```
logic_error(const string& what_arg);
```

- ² *Effects:* Constructs an object of class `logic_error`.

- ³ *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
logic_error(const char* what_arg);
```

- ⁴ *Effects:* Constructs an object of class `logic_error`.

- ⁵ *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.2.3 Class `domain_error`

[domain.error]

```
namespace std {
    class domain_error : public logic_error {
    public:
        explicit domain_error(const string& what_arg);
        explicit domain_error(const char* what_arg);
    };
}
```

- ¹ The class `domain_error` defines the type of objects thrown as exceptions by the implementation to report domain errors.

```
domain_error(const string& what_arg);
```

- ² *Effects:* Constructs an object of class `domain_error`.

- ³ *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
domain_error(const char* what_arg);
```

- ⁴ *Effects:* Constructs an object of class `domain_error`.

- ⁵ *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.2.4 Class `invalid_argument`

[invalid.argument]

```
namespace std {
    class invalid_argument : public logic_error {
    public:
        explicit invalid_argument(const string& what_arg);
        explicit invalid_argument(const char* what_arg);
    };
}
```

- ¹ The class `invalid_argument` defines the type of objects thrown as exceptions to report an invalid argument.

```
invalid_argument(const string& what_arg);
```

- ² *Effects:* Constructs an object of class `invalid_argument`.

- ³ *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
invalid_argument(const char* what_arg);
```

- ⁴ *Effects:* Constructs an object of class `invalid_argument`.

- ⁵ *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.2.5 Class `length_error`

[length.error]

```

namespace std {
    class length_error : public logic_error {
    public:
        explicit length_error(const string& what_arg);
        explicit length_error(const char* what_arg);
    };
}

```

- 1 The class `length_error` defines the type of objects thrown as exceptions to report an attempt to produce an object whose length exceeds its maximum allowable size.

```
length_error(const string& what_arg);
```

- 2 *Effects:* Constructs an object of class `length_error`.

- 3 *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
length_error(const char* what_arg);
```

- 4 *Effects:* Constructs an object of class `length_error`.

- 5 *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.2.6 Class `out_of_range`

[out.of.range]

```

namespace std {
    class out_of_range : public logic_error {
    public:
        explicit out_of_range(const string& what_arg);
        explicit out_of_range(const char* what_arg);
    };
}

```

- 1 The class `out_of_range` defines the type of objects thrown as exceptions to report an argument value not in its expected range.

```
out_of_range(const string& what_arg);
```

- 2 *Effects:* Constructs an object of class `out_of_range`.

- 3 *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
out_of_range(const char* what_arg);
```

- 4 *Effects:* Constructs an object of class `out_of_range`.

- 5 *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.2.7 Class `runtime_error`

[runtime.error]

```

namespace std {
    class runtime_error : public exception {
    public:
        explicit runtime_error(const string& what_arg);
        explicit runtime_error(const char* what_arg);
    };
}

```

- 1 The class `runtime_error` defines the type of objects thrown as exceptions to report errors presumably detectable only when the program executes.

```
runtime_error(const string& what_arg);
```

- 2 *Effects:* Constructs an object of class `runtime_error`.

3 *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0.`
`runtime_error(const char* what_arg);`
4 *Effects:* Constructs an object of class `runtime_error`.
5 *Postconditions:* `strcmp(what(), what_arg) == 0.`

22.2.8 Class `range_error`

[`range.error`]

```
namespace std {
    class range_error : public runtime_error {
    public:
        explicit range_error(const string& what_arg);
        explicit range_error(const char* what_arg);
    };
}
```

1 The class `range_error` defines the type of objects thrown as exceptions to report range errors in internal computations.

```
range_error(const string& what_arg);
```

2 *Effects:* Constructs an object of class `range_error`.
3 *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0.`
`range_error(const char* what_arg);`
4 *Effects:* Constructs an object of class `range_error`.
5 *Postconditions:* `strcmp(what(), what_arg) == 0.`

22.2.9 Class `overflow_error`

[`overflow.error`]

```
namespace std {
    class overflow_error : public runtime_error {
    public:
        explicit overflow_error(const string& what_arg);
        explicit overflow_error(const char* what_arg);
    };
}
```

1 The class `overflow_error` defines the type of objects thrown as exceptions to report an arithmetic overflow error.

```
overflow_error(const string& what_arg);
```

2 *Effects:* Constructs an object of class `overflow_error`.
3 *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0.`
`overflow_error(const char* what_arg);`
4 *Effects:* Constructs an object of class `overflow_error`.
5 *Postconditions:* `strcmp(what(), what_arg) == 0.`

22.2.10 Class `underflow_error`

[`underflow.error`]

```
namespace std {
    class underflow_error : public runtime_error {
    public:
        explicit underflow_error(const string& what_arg);
    };
}
```

```

        explicit underflow_error(const char* what_arg);
    };
}

```

- ¹ The class `underflow_error` defines the type of objects thrown as exceptions to report an arithmetic underflow error.

```
underflow_error(const string& what_arg);
```

- ² *Effects:* Constructs an object of class `underflow_error`.

- ³ *Postconditions:* `strcmp(what(), what_arg.c_str()) == 0`.

```
underflow_error(const char* what_arg);
```

- ⁴ *Effects:* Constructs an object of class `underflow_error`.

- ⁵ *Postconditions:* `strcmp(what(), what_arg) == 0`.

22.3 Assertions [assertions]

- ¹ The header `<cassert>` provides a macro for documenting C++ program assertions and a mechanism for disabling the assertion checks.

22.3.1 Header `<cassert>` synopsis [cassert.syn]

```
#define assert(E) see below
```

- ¹ The contents are the same as the C standard library header `<assert.h>`, except that a macro named `static_assert` is not defined.

SEE ALSO: ISO C 7.2.

22.3.2 The `assert` macro [assertions.assert]

- ¹ An expression `assert(E)` is a constant subexpression (20.3.6), if

- (1.1) — `NDEBUG` is defined at the point where `assert` is last defined or redefined, or
- (1.2) — `E` contextually converted to `bool` (Clause 7) is a constant subexpression that evaluates to the value `true`.

22.4 Error numbers [errno]

- ¹ The contents of the header `<cerrno>` are the same as the POSIX header `<errno.h>`, except that `errno` shall be defined as a macro. [Note: The intent is to remain in close alignment with the POSIX standard. — end note] A separate `errno` value shall be provided for each thread.

22.4.1 Header `<cerrno>` synopsis [cerrno.syn]

```
#define errno see below
```

```
#define E2BIG see below
```

```
#define EACCES see below
```

```
#define EADDRINUSE see below
```

```
#define EADDRNOTAVAIL see below
```

```
#define EAFNOSUPPORT see below
```

```
#define EAGAIN see below
```

```
#define EALREADY see below
```

```
#define EBADF see below
```

```
#define EBADMSG see below
```

```
#define EBUSY see below
```

```
#define ECANCELED see below
```

```
#define ECHILD see below
#define ECONNABORTED see below
#define ECONNREFUSED see below
#define ECONNRESET see below
#define EDEADLK see below
#define EDESTADDRREQ see below
#define EDOM see below
#define EEXIST see below
#define EFAULT see below
#define EFBIG see below
#define EHOSTUNREACH see below
#define EIDRM see below
#define EILSEQ see below
#define EINPROGRESS see below
#define EINTR see below
#define EINVAL see below
#define EIO see below
#define EISCONN see below
#define EISDIR see below
#define ELOOP see below
#define EMFILE see below
#define EMLINK see below
#define EMSGSIZE see below
#define ENAMETOOLONG see below
#define ENETDOWN see below
#define ENETRESET see below
#define ENETUNREACH see below
#define ENFILE see below
#define ENOBUFS see below
#define ENODATA see below
#define ENODEV see below
#define ENOENT see below
#define ENOEXEC see below
#define ENOLCK see below
#define ENOLINK see below
#define ENOMEM see below
#define ENOMSG see below
#define ENOPROTOOPT see below
#define ENOSPC see below
#define ENOSR see below
#define ENOSTR see below
#define ENOSYS see below
#define NOTCONN see below
#define ENOTDIR see below
#define ENOTEMPTY see below
#define ENOTRECOVERABLE see below
#define ENOTSOCK see below
#define ENOTSUP see below
#define ENOTTY see below
#define ENXIO see below
#define EOPNOTSUPP see below
#define EOVERFLOW see below
#define EOWNERDEAD see below
#define EPERM see below
#define EPIPE see below
```

```

#define EPROTO see below
#define EPROTONOSUPPORT see below
#define EPROTOTYPE see below
#define ERANGE see below
#define EROFS see below
#define ESPIPE see below
#define ESRCH see below
#define ETIME see below
#define ETIMEDOUT see below
#define ETXTBSY see below
#define EWOULDBLOCK see below
#define EXDEV see below

```

- ¹ The meaning of the macros in this header is defined by the POSIX standard.

SEE ALSO: ISO C 7.5.

22.5 System error support

[syserr]

- ¹ This subclause describes components that the standard library and C++ programs may use to report error conditions originating from the operating system or other low-level application program interfaces.
- ² Components described in this subclause shall not change the value of `errno` (22.4). Implementations should leave the error states provided by other libraries unchanged.

22.5.1 Header <system_error> synopsis

[system__error.syn]

```

namespace std {
    class error_category;
    const error_category& generic_category() noexcept;
    const error_category& system_category() noexcept;

    class error_code;
    class error_condition;
    class system_error;

    template <class T>
    struct is_error_code_enum : public false_type {};

    template <class T>
    struct is_error_condition_enum : public false_type {};

    enum class errc {
        address_family_not_supported,    // EAFNOSUPPORT
        address_in_use,                  // EADDRINUSE
        address_not_available,           // EADDRNOTAVAIL
        already_connected,               // EISCONN
        argument_list_too_long,          // E2BIG
        argument_out_of_domain,          // EDOM
        bad_address,                     // EFAULT
        bad_file_descriptor,             // EBADF
        bad_message,                     // EBADMSG
        broken_pipe,                     // EPIPE
        connection_aborted,              // ECONNABORTED
        connection_already_in_progress,  // EALREADY
        connection_refused,              // ECONNREFUSED
        connection_reset,                // ECONNRESET
        cross_device_link,               // EXDEV
    };

```

destination_address_required,	// EDESTADDRREQ
device_or_resource_busy,	// EBUSY
directory_not_empty,	// ENOTEMPTY
executable_format_error,	// ENOEXEC
file_exists,	// EEXIST
file_too_large,	// EFBIG
filename_too_long,	// ENAMETOOLONG
function_not_supported,	// ENOSYS
host_unreachable,	// EHOSTUNREACH
identifier_removed,	// EIDRM
illegal_byte_sequence,	// EILSEQ
inappropriate_io_control_operation,	// ENOTTY
interrupted,	// EINTR
invalid_argument,	// EINVAL
invalid_seek,	// ESPIPE
io_error,	// EIO
is_a_directory,	// EISDIR
message_size,	// EMSGSIZE
network_down,	// ENETDOWN
network_reset,	// ENETRESET
network_unreachable,	// ENETUNREACH
no_buffer_space,	// ENOBUFS
no_child_process,	// ECHILD
no_link,	// ENOLINK
no_lock_available,	// ENOLCK
no_message_available,	// ENODATA
no_message,	// ENOMSG
no_protocol_option,	// ENOPROTOOPT
no_space_on_device,	// ENOSPC
no_stream_resources,	// ENOSR
no_such_device_or_address,	// ENXIO
no_such_device,	// ENODEV
no_such_file_or_directory,	// ENOENT
no_such_process,	// ESRCH
not_a_directory,	// ENOTDIR
not_a_socket,	// ENOTSOCK
not_a_stream,	// ENOSTR
not_connected,	// ENOTCONN
not_enough_memory,	// ENOMEM
not_supported,	// ENOTSUP
operation_canceled,	// ECANCELED
operation_in_progress,	// EINPROGRESS
operation_not_permitted,	// EPERM
operation_not_supported,	// EOPNOTSUPP
operation_would_block,	// EWOULDBLOCK
owner_dead,	// EOWNERDEAD
permission_denied,	// EACCES
protocol_error,	// EPROTO
protocol_not_supported,	// EPROTONOSUPPORT
read_only_file_system,	// EROFS
resource_deadlock_would_occur,	// EDEADLK
resource_unavailable_try_again,	// EAGAIN
result_out_of_range,	// ERANGE
state_not_recoverable,	// ENOTRECOVERABLE
stream_timeout,	// ETIME

```

    text_file_busy,           // ETXTBSY
    timed_out,               // ETIMEDOUT
    too_many_files_open_in_system, // ENFILE
    too_many_files_open,     // EMFILE
    too_many_links,          // EMLINK
    too_many_symbolic_link_levels, // ELOOP
    value_too_large,         // EOVERFLOW
    wrong_protocol_type,     // EPROTOTYPE
};

template <> struct is_error_condition_enum<errc> : true_type {};

// 22.5.3.5, non-member functions
error_code make_error_code(errc e) noexcept;

template <class charT, class traits>
    basic_ostream<charT, traits>&
        operator<< (basic_ostream<charT, traits>& os, const error_code& ec);

// 22.5.4.5, non-member functions
error_condition make_error_condition(errc e) noexcept;

// 22.5.5, comparison functions
bool operator< (const error_code& lhs, const error_code& rhs) noexcept;
bool operator< (const error_condition& lhs, const error_condition& rhs) noexcept;
bool operator==(const error_code& lhs, const error_code& rhs) noexcept;
bool operator==(const error_code& lhs, const error_condition& rhs) noexcept;
bool operator==(const error_condition& lhs, const error_code& rhs) noexcept;
bool operator==(const error_condition& lhs, const error_condition& rhs) noexcept;
bool operator!=(const error_code& lhs, const error_code& rhs) noexcept;
bool operator!=(const error_code& lhs, const error_condition& rhs) noexcept;
bool operator!=(const error_condition& lhs, const error_code& rhs) noexcept;
bool operator!=(const error_condition& lhs, const error_condition& rhs) noexcept;

// 22.5.6, hash support
template <class T> struct hash;
template <> struct hash<error_code>;
template <> struct hash<error_condition>;

// 22.5, system error support
template <class T> inline constexpr bool is_error_code_enum_v
    = is_error_code_enum<T>::value;
template <class T> inline constexpr bool is_error_condition_enum_v
    = is_error_condition_enum<T>::value;
}

```

¹ The value of each `enum errc` constant shall be the same as the value of the `<cerrno>` macro shown in the above synopsis. Whether or not the `<system_error>` implementation exposes the `<cerrno>` macros is unspecified.

² The `is_error_code_enum` and `is_error_condition_enum` may be specialized for user-defined types to indicate that such types are eligible for `class error_code` and `class error_condition` automatic conversions,

respectively.

22.5.2 Class `error_category` [syserr.errcat]

22.5.2.1 Class `error_category` overview [syserr.errcat.overview]

- ¹ The class `error_category` serves as a base class for types used to identify the source and encoding of a particular category of error code. Classes may be derived from `error_category` to support categories of errors in addition to those defined in this International Standard. Such classes shall behave as specified in this subclause. [Note: `error_category` objects are passed by reference, and two such objects are equal if they have the same address. This means that applications using custom `error_category` types should create a single object of each such type. — end note]

```
namespace std {
    class error_category {
    public:
        constexpr error_category() noexcept;
        virtual ~error_category();
        error_category(const error_category&) = delete;
        error_category& operator=(const error_category&) = delete;
        virtual const char* name() const noexcept = 0;
        virtual error_condition default_error_condition(int ev) const noexcept;
        virtual bool equivalent(int code, const error_condition& condition) const noexcept;
        virtual bool equivalent(const error_code& code, int condition) const noexcept;
        virtual string message(int ev) const = 0;

        bool operator==(const error_category& rhs) const noexcept;
        bool operator!=(const error_category& rhs) const noexcept;
        bool operator<(const error_category& rhs) const noexcept;
    };

    const error_category& generic_category() noexcept;
    const error_category& system_category() noexcept;
}
```

22.5.2.2 Class `error_category` virtual members [syserr.errcat.virtuals]

```
virtual ~error_category();
```

- ¹ *Effects:* Destroys an object of class `error_category`.

```
virtual const char* name() const noexcept = 0;
```

- ² *Returns:* A string naming the error category.

```
virtual error_condition default_error_condition(int ev) const noexcept;
```

- ³ *Returns:* `error_condition(ev, *this)`.

```
virtual bool equivalent(int code, const error_condition& condition) const noexcept;
```

- ⁴ *Returns:* `default_error_condition(code) == condition`.

```
virtual bool equivalent(const error_code& code, int condition) const noexcept;
```

- ⁵ *Returns:* `*this == code.category() && code.value() == condition`.

```
virtual string message(int ev) const = 0;
```

- ⁶ *Returns:* A string that describes the error condition denoted by `ev`.

22.5.2.3 Class `error_category` non-virtual members [syserr.errcat.nonvirtuals]

```
constexpr error_category() noexcept;
```

1 *Effects:* Constructs an object of class `error_category`.

```
bool operator==(const error_category& rhs) const noexcept;
```

2 *Returns:* `this == &rhs`.

```
bool operator!=(const error_category& rhs) const noexcept;
```

3 *Returns:* `!(*this == rhs)`.

```
bool operator<(const error_category& rhs) const noexcept;
```

4 *Returns:* `less<const error_category*>()(this, &rhs)`.

[*Note:* `less` (23.14.7) provides a total ordering for pointers. — *end note*]

22.5.2.4 Program defined classes derived from `error_category` [syserr.errcat.derived]

```
virtual const char* name() const noexcept = 0;
```

1 *Returns:* A string naming the error category.

```
virtual error_condition default_error_condition(int ev) const noexcept;
```

2 *Returns:* An object of type `error_condition` that corresponds to `ev`.

```
virtual bool equivalent(int code, const error_condition& condition) const noexcept;
```

3 *Returns:* `true` if, for the category of error represented by `*this`, `code` is considered equivalent to `condition`; otherwise, `false`.

```
virtual bool equivalent(const error_code& code, int condition) const noexcept;
```

4 *Returns:* `true` if, for the category of error represented by `*this`, `code` is considered equivalent to `condition`; otherwise, `false`.

22.5.2.5 Error category objects [syserr.errcat.objects]

```
const error_category& generic_category() noexcept;
```

1 *Returns:* A reference to an object of a type derived from class `error_category`. All calls to this function shall return references to the same object.

2 *Remarks:* The object's `default_error_condition` and `equivalent` virtual functions shall behave as specified for the class `error_category`. The object's `name` virtual function shall return a pointer to the string "generic".

```
const error_category& system_category() noexcept;
```

3 *Returns:* A reference to an object of a type derived from class `error_category`. All calls to this function shall return references to the same object.

4 *Remarks:* The object's `equivalent` virtual functions shall behave as specified for class `error_category`. The object's `name` virtual function shall return a pointer to the string "system". The object's `default_error_condition` virtual function shall behave as follows:

If the argument `ev` corresponds to a POSIX `errno` value `posv`, the function shall return `error_condition(posv, generic_category())`. Otherwise, the function shall return `error_condition(ev, system_category())`. What constitutes correspondence for any given operating system is unspecified. [*Note:* The number of potential system error codes is large and unbounded, and some may not correspond to any POSIX `errno` value. Thus implementations are given latitude in determining correspondence. — *end note*]

22.5.3 Class error_code

[syserr.errcode]

22.5.3.1 Class error_code overview

[syserr.errcode.overview]

- ¹ The class `error_code` describes an object used to hold error code values, such as those originating from the operating system or other low-level application program interfaces. [*Note*: Class `error_code` is an adjunct to error reporting by exception. — *end note*]

```
namespace std {
    class error_code {
    public:
        // 22.5.3.2, constructors
        error_code() noexcept;
        error_code(int val, const error_category& cat) noexcept;
        template <class ErrorCodeEnum>
            error_code(ErrorCodeEnum e) noexcept;

        // 22.5.3.3, modifiers
        void assign(int val, const error_category& cat) noexcept;
        template <class ErrorCodeEnum>
            error_code& operator=(ErrorCodeEnum e) noexcept;
        void clear() noexcept;

        // 22.5.3.4, observers
        int value() const noexcept;
        const error_category& category() const noexcept;
        error_condition default_error_condition() const noexcept;
        string message() const;
        explicit operator bool() const noexcept;

    private:
        int val_; // exposition only
        const error_category* cat_; // exposition only
    };

    // 22.5.3.5, non-member functions
    error_code make_error_code(errc e) noexcept;

    template <class charT, class traits>
        basic_ostream<charT, traits>&
            operator<<(basic_ostream<charT, traits>& os, const error_code& ec);
}
```

22.5.3.2 Class error_code constructors

[syserr.errcode.constructors]

```
error_code() noexcept;
```

- ¹ *Effects*: Constructs an object of type `error_code`.
² *Postconditions*: `val_ == 0` and `cat_ == &system_category()`.

```
error_code(int val, const error_category& cat) noexcept;
```

- ³ *Effects*: Constructs an object of type `error_code`.
⁴ *Postconditions*: `val_ == val` and `cat_ == &cat`.

```
template <class ErrorCodeEnum>
    error_code(ErrorCodeEnum e) noexcept;
```

5 *Effects:* Constructs an object of type `error_code`.
 6 *Postconditions:* `*this == make_error_code(e)`.
 7 *Remarks:* This constructor shall not participate in overload resolution unless
 `is_error_code_enum_v<ErrorCodeEnum>` is true.

22.5.3.3 Class `error_code` modifiers [syserr.errcode.modifiers]

```
void assign(int val, const error_category& cat) noexcept;
```

1 *Postconditions:* `val_ == val` and `cat_ == &cat`.

```
template <class ErrorCodeEnum>
    error_code& operator=(ErrorCodeEnum e) noexcept;
```

2 *Postconditions:* `*this == make_error_code(e)`.
 3 *Returns:* `*this`.
 4 *Remarks:* This operator shall not participate in overload resolution unless
 `is_error_code_enum_v<ErrorCodeEnum>` is true.

```
void clear() noexcept;
```

5 *Postconditions:* `value() == 0` and `category() == system_category()`.

22.5.3.4 Class `error_code` observers [syserr.errcode.observers]

```
int value() const noexcept;
```

1 *Returns:* `val_`.

```
const error_category& category() const noexcept;
```

2 *Returns:* `*cat_`.

```
error_condition default_error_condition() const noexcept;
```

3 *Returns:* `category().default_error_condition(value())`.

```
string message() const;
```

4 *Returns:* `category().message(value())`.

```
explicit operator bool() const noexcept;
```

5 *Returns:* `value() != 0`.

22.5.3.5 Class `error_code` non-member functions [syserr.errcode.nonmembers]

```
error_code make_error_code(errc e) noexcept;
```

1 *Returns:* `error_code(static_cast<int>(e), generic_category())`.

```
template <class charT, class traits>
    basic_ostream<charT, traits>&
        operator<<(basic_ostream<charT, traits>& os, const error_code& ec);
```

2 *Effects:* As if by: `os << ec.category().name() << ':' << ec.value();`

22.5.4 Class `error_condition` [syserr.errcondition]

22.5.4.1 Class `error_condition` overview [syserr.errcondition.overview]

- ¹ The class `error_condition` describes an object used to hold values identifying error conditions. [*Note*: `error_condition` values are portable abstractions, while `error_code` values (22.5.3) are implementation specific. — *end note*]

```
namespace std {
    class error_condition {
    public:
        // 22.5.4.2, constructors
        error_condition() noexcept;
        error_condition(int val, const error_category& cat) noexcept;
        template <class ErrorConditionEnum>
            error_condition(ErrorConditionEnum e) noexcept;

        // 22.5.4.3, modifiers
        void assign(int val, const error_category& cat) noexcept;
        template <class ErrorConditionEnum>
            error_condition& operator=(ErrorConditionEnum e) noexcept;
        void clear() noexcept;

        // 22.5.4.4, observers
        int value() const noexcept;
        const error_category& category() const noexcept;
        string message() const;
        explicit operator bool() const noexcept;

    private:
        int val_; // exposition only
        const error_category* cat_; // exposition only
    };
}
```

22.5.4.2 Class `error_condition` constructors [syserr.errcondition.constructors]

```
error_condition() noexcept;
```

- ¹ *Effects*: Constructs an object of type `error_condition`.
² *Postconditions*: `val_ == 0` and `cat_ == &generic_category()`.

```
error_condition(int val, const error_category& cat) noexcept;
```

- ³ *Effects*: Constructs an object of type `error_condition`.
⁴ *Postconditions*: `val_ == val` and `cat_ == &cat`.

```
template <class ErrorConditionEnum>
    error_condition(ErrorConditionEnum e) noexcept;
```

- ⁵ *Effects*: Constructs an object of type `error_condition`.
⁶ *Postconditions*: `*this == make_error_condition(e)`.
⁷ *Remarks*: This constructor shall not participate in overload resolution unless `is_error_condition_enum_v<ErrorConditionEnum>` is true.

22.5.4.3 Class `error_condition` modifiers [syserr.errcondition.modifiers]

```
void assign(int val, const error_category& cat) noexcept;
```

```

1      Postconditions: val_ == val and cat_ == &cat.

template <class ErrorConditionEnum>
    error_condition& operator=(ErrorConditionEnum e) noexcept;
2      Postconditions: *this == make_error_condition(e).
3      Returns: *this.
4      Remarks: This operator shall not participate in overload resolution unless
    is_error_condition_enum_v<ErrorConditionEnum> is true.

void clear() noexcept;
5      Postconditions: value() == 0 and category() == generic_category().

```

22.5.4.4 Class error_condition observers [syserr.errcondition.observers]

```

int value() const noexcept;
1      Returns: val_.

const error_category& category() const noexcept;
2      Returns: *cat_.

string message() const;
3      Returns: category().message(value()).

explicit operator bool() const noexcept;
4      Returns: value() != 0.

```

22.5.4.5 Class error_condition non-member functions [syserr.errcondition.nonmembers]

```

error_condition make_error_condition(errc e) noexcept;
1      Returns: error_condition(static_cast<int>(e), generic_category()).

```

22.5.5 Comparison functions [syserr.compare]

```

bool operator<(const error_code& lhs, const error_code& rhs) noexcept;
1      Returns:
        lhs.category() < rhs.category() ||
        (lhs.category() == rhs.category() && lhs.value() < rhs.value());

bool operator<(const error_condition& lhs, const error_condition& rhs) noexcept;
2      Returns: lhs.category() < rhs.category() || lhs.category() == rhs.category() &&
        lhs.value() < rhs.value().

bool operator==(const error_code& lhs, const error_code& rhs) noexcept;
3      Returns: lhs.category() == rhs.category() && lhs.value() == rhs.value().

bool operator==(const error_code& lhs, const error_condition& rhs) noexcept;
4      Returns: lhs.category().equivalent(lhs.value(), rhs) || rhs.category().equivalent(lhs,
        rhs.value()).

bool operator==(const error_condition& lhs, const error_code& rhs) noexcept;

```

5 *Returns:* `rhs.category().equivalent(rhs.value(), lhs) || lhs.category().equivalent(rhs, lhs.value())`.

```
bool operator==(const error_condition& lhs, const error_condition& rhs) noexcept;
```

6 *Returns:* `lhs.category() == rhs.category() && lhs.value() == rhs.value()`.

```
bool operator!=(const error_code& lhs, const error_code& rhs) noexcept;
bool operator!=(const error_code& lhs, const error_condition& rhs) noexcept;
bool operator!=(const error_condition& lhs, const error_code& rhs) noexcept;
bool operator!=(const error_condition& lhs, const error_condition& rhs) noexcept;
```

7 *Returns:* `!(lhs == rhs)`.

22.5.6 System error hash support

[syserr.hash]

```
template <> struct hash<error_code>;
template <> struct hash<error_condition>;
```

1 The specializations are enabled (23.14.15).

22.5.7 Class `system_error`

[syserr.syserr]

22.5.7.1 Class `system_error` overview

[syserr.syserr.overview]

1 The class `system_error` describes an exception object used to report error conditions that have an associated error code. Such error conditions typically originate from the operating system or other low-level application program interfaces.

2 [*Note:* If an error represents an out-of-memory condition, implementations are encouraged to throw an exception object of type `bad_alloc` (21.6.3.1) rather than `system_error`. — *end note*]

```
namespace std {
    class system_error : public runtime_error {
    public:
        system_error(error_code ec, const string& what_arg);
        system_error(error_code ec, const char* what_arg);
        system_error(error_code ec);
        system_error(int ev, const error_category& ec, const string& what_arg);
        system_error(int ev, const error_category& ec, const char* what_arg);
        system_error(int ev, const error_category& ec);
        const error_code& code() const noexcept;
        const char* what() const noexcept override;
    };
}
```

22.5.7.2 Class `system_error` members

[syserr.syserr.members]

```
system_error(error_code ec, const string& what_arg);
```

1 *Effects:* Constructs an object of class `system_error`.

2 *Postconditions:* `code() == ec`.

```
string(what()).find(what_arg) != string::npos.
```

```
system_error(error_code ec, const char* what_arg);
```

3 *Effects:* Constructs an object of class `system_error`.

4 *Postconditions:* `code() == ec`.

```
string(what()).find(what_arg) != string::npos.
```

```
system_error(error_code ec);
```

5 *Effects:* Constructs an object of class `system_error`.

6 *Postconditions:* `code() == ec`.

```
system_error(int ev, const error_category& ecat, const string& what_arg);
```

7 *Effects:* Constructs an object of class `system_error`.

8 *Postconditions:* `code() == error_code(ev, ecat)`.

`string(what()).find(what_arg) != string::npos`.

```
system_error(int ev, const error_category& ecat, const char* what_arg);
```

9 *Effects:* Constructs an object of class `system_error`.

10 *Postconditions:* `code() == error_code(ev, ecat)`.

`string(what()).find(what_arg) != string::npos`.

```
system_error(int ev, const error_category& ecat);
```

11 *Effects:* Constructs an object of class `system_error`.

12 *Postconditions:* `code() == error_code(ev, ecat)`.

```
const error_code& code() const noexcept;
```

13 *Returns:* `ec` or `error_code(ev, ecat)`, from the constructor, as appropriate.

```
const char* what() const noexcept override;
```

14 *Returns:* An NTBS incorporating the arguments supplied in the constructor.

[*Note:* The returned NTBS might be the contents of `what_arg + ": " + code.message()`. — *end note*]

23 General utilities library [utilities]

23.1 General [utilities.general]

- ¹ This Clause describes utilities that are generally useful in C++ programs; some of these utilities are used by other elements of the C++ standard library. These utilities are summarized in Table 34.

Table 34 — General utilities library summary

Subclause	Header(s)
23.2 Utility components	<utility>
23.3 Compile-time integer sequences	<utility>
23.4 Pairs	<utility>
23.5 Tuples	<tuple>
23.6 Optional objects	<optional>
23.7 Variants	<variant>
23.8 Storage for any type	<any>
23.9 Fixed-size sequences of bits	<bitset>
23.10 Memory	<memory> <cstdlib>
23.11 Smart pointers	<memory>
23.12 Memory resources	<memory_resource>
23.13 Scoped allocators	<scoped_allocator>
23.14 Function objects	<functional>
23.15 Type traits	<type_traits>
23.16 Compile-time rational arithmetic	<ratio>
23.17 Time utilities	<chrono> <ctime>
23.18 Type indexes	<typeindex>
23.19 Execution policies	<execution>

23.2 Utility components [utility]

- ¹ This subclause contains some basic function and class templates that are used throughout the rest of the library.

23.2.1 Header <utility> synopsis [utility.syn]

```
#include <initializer_list>    // see 21.9.1

namespace std {
    // 23.2.2, operators
    namespace rel_ops {
        template<class T> bool operator!=(const T&, const T&);
        template<class T> bool operator> (const T&, const T&);
        template<class T> bool operator<=(const T&, const T&);
        template<class T> bool operator>=(const T&, const T&);
    }
}
```

```

// 23.2.3, swap
template <class T>
    void swap(T& a, T& b) noexcept(see below);
template <class T, size_t N>
    void swap(T (&a)[N], T (&b)[N]) noexcept(is_nothrow_swappable_v<T>);

// 23.2.4, exchange
template <class T, class U = T>
    T exchange(T& obj, U&& new_val);

// 23.2.5, forward/move
template <class T>
    constexpr T&& forward(remove_reference_t<T>& t) noexcept;
template <class T>
    constexpr T&& forward(remove_reference_t<T>&& t) noexcept;
template <class T>
    constexpr remove_reference_t<T>&& move(T&&) noexcept;
template <class T>
    constexpr conditional_t<
        !is_nothrow_move_constructible_v<T> && is_copy_constructible_v<T>, const T&, T&&>
        move_if_noexcept(T& x) noexcept;

// 23.2.6, as_const
template <class T>
    constexpr add_const_t<T>& as_const(T& t) noexcept;
template <class T>
    void as_const(const T&&) = delete;

// 23.2.7, declval
template <class T>
    add_rvalue_reference_t<T> declval() noexcept; // as unevaluated operand

// 23.3, Compile-time integer sequences
template<class T, T...>
    struct integer_sequence;
template<size_t... I>
    using index_sequence = integer_sequence<size_t, I...>;

template<class T, T N>
    using make_integer_sequence = integer_sequence<T, see below>;
template<size_t N>
    using make_index_sequence = make_integer_sequence<size_t, N>;

template<class... T>
    using index_sequence_for = make_index_sequence<sizeof...(T)>;

// 23.4, class template pair
template <class T1, class T2>
    struct pair;

// 23.4.3, pair specialized algorithms
template <class T1, class T2>
    constexpr bool operator==(const pair<T1, T2>&, const pair<T1, T2>&);
template <class T1, class T2>
    constexpr bool operator< (const pair<T1, T2>&, const pair<T1, T2>&);

```

```

template <class T1, class T2>
    constexpr bool operator!=(const pair<T1, T2>&, const pair<T1, T2>&);
template <class T1, class T2>
    constexpr bool operator> (const pair<T1, T2>&, const pair<T1, T2>&);
template <class T1, class T2>
    constexpr bool operator>=(const pair<T1, T2>&, const pair<T1, T2>&);
template <class T1, class T2>
    constexpr bool operator<=(const pair<T1, T2>&, const pair<T1, T2>&);

template <class T1, class T2>
    void swap(pair<T1, T2>& x, pair<T1, T2>& y) noexcept(noexcept(x.swap(y)));

template <class T1, class T2>
    constexpr see below make_pair(T1&&, T2&&);

// 23.4.4, tuple-like access to pair
template <class T> class tuple_size;
template <size_t I, class T> class tuple_element;

template <class T1, class T2> struct tuple_size<pair<T1, T2>>;
template <class T1, class T2> struct tuple_element<0, pair<T1, T2>>;
template <class T1, class T2> struct tuple_element<1, pair<T1, T2>>;

template<size_t I, class T1, class T2>
    constexpr tuple_element_t<I, pair<T1, T2>>& get(pair<T1, T2>&) noexcept;
template<size_t I, class T1, class T2>
    constexpr tuple_element_t<I, pair<T1, T2>>&& get(pair<T1, T2>&&) noexcept;
template<size_t I, class T1, class T2>
    constexpr const tuple_element_t<I, pair<T1, T2>>& get(const pair<T1, T2>&) noexcept;
template<size_t I, class T1, class T2>
    constexpr const tuple_element_t<I, pair<T1, T2>>&& get(const pair<T1, T2>&&) noexcept;
template <class T1, class T2>
    constexpr T1& get(pair<T1, T2>& p) noexcept;
template <class T1, class T2>
    constexpr const T1& get(const pair<T1, T2>& p) noexcept;
template <class T1, class T2>
    constexpr T1&& get(pair<T1, T2>&& p) noexcept;
template <class T1, class T2>
    constexpr const T1&& get(const pair<T1, T2>&& p) noexcept;
template <class T2, class T1>
    constexpr T2& get(pair<T1, T2>& p) noexcept;
template <class T2, class T1>
    constexpr const T2& get(const pair<T1, T2>& p) noexcept;
template <class T2, class T1>
    constexpr T2&& get(pair<T1, T2>&& p) noexcept;
template <class T2, class T1>
    constexpr const T2&& get(const pair<T1, T2>&& p) noexcept;

// 23.4.5, pair piecewise construction
struct piecewise_construct_t {
    explicit piecewise_construct_t() = default;
};
inline constexpr piecewise_construct_t piecewise_construct{};
template <class... Types> class tuple; // defined in <tuple> (23.5.2)

```

```

// in-place construction
struct in_place_t {
    explicit in_place_t() = default;
};
inline constexpr in_place_t in_place{};
template <class T>
    struct in_place_type_t {
        explicit in_place_type_t() = default;
    };
template <class T> inline constexpr in_place_type_t<T> in_place_type{};
template <size_t I>
    struct in_place_index_t {
        explicit in_place_index_t() = default;
    };
template <size_t I> inline constexpr in_place_index_t<I> in_place_index{};

// floating-point format for primitive numerical conversion
enum class chars_format {
    scientific = unspecified,
    fixed = unspecified,
    hex = unspecified,
    general = fixed | scientific
};

// 23.2.8, primitive numerical output conversion
struct to_chars_result {
    char* ptr;
    error_code ec;
};

to_chars_result to_chars(char* first, char* last, see below value, int base = 10);

to_chars_result to_chars(char* first, char* last, float value);
to_chars_result to_chars(char* first, char* last, double value);
to_chars_result to_chars(char* first, char* last, long double value);

to_chars_result to_chars(char* first, char* last, float value,
                        chars_format fmt);
to_chars_result to_chars(char* first, char* last, double value,
                        chars_format fmt);
to_chars_result to_chars(char* first, char* last, long double value,
                        chars_format fmt);

to_chars_result to_chars(char* first, char* last, float value,
                        chars_format fmt, int precision);
to_chars_result to_chars(char* first, char* last, double value,
                        chars_format fmt, int precision);
to_chars_result to_chars(char* first, char* last, long double value,
                        chars_format fmt, int precision);

// 23.2.9, primitive numerical input conversion
struct from_chars_result {
    const char* ptr;
    error_code ec;
};

```

```

from_chars_result from_chars(const char* first, const char* last,
                             see below& value, int base = 10);

from_chars_result from_chars(const char* first, const char* last, float& value,
                             chars_format fmt = chars_format::general);
from_chars_result from_chars(const char* first, const char* last, double& value,
                             chars_format fmt = chars_format::general);
from_chars_result from_chars(const char* first, const char* last, long double& value,
                             chars_format fmt = chars_format::general);
}

```

1 The header <utility> defines several types and function templates that are described in this Clause. It also defines the template `pair` and various function templates that operate on `pair` objects.

2 The type `chars_format` is a bitmask type (20.4.2.1.4) with elements `scientific`, `fixed`, and `hex`.

23.2.2 Operators

[operators]

1 To avoid redundant definitions of `operator!=` out of `operator==` and operators `>`, `<=`, and `>=` out of `operator<`, the library provides the following:

```
template <class T> bool operator!=(const T& x, const T& y);
```

2 *Requires:* Type `T` is `EqualityComparable` (Table 20).

3 *Returns:* `!(x == y)`.

```
template <class T> bool operator>(const T& x, const T& y);
```

4 *Requires:* Type `T` is `LessThanComparable` (Table 21).

5 *Returns:* `y < x`.

```
template <class T> bool operator<=(const T& x, const T& y);
```

6 *Requires:* Type `T` is `LessThanComparable` (Table 21).

7 *Returns:* `!(y < x)`.

```
template <class T> bool operator>=(const T& x, const T& y);
```

8 *Requires:* Type `T` is `LessThanComparable` (Table 21).

9 *Returns:* `!(x < y)`.

10 In this library, whenever a declaration is provided for an `operator!=`, `operator>`, `operator>=`, or `operator<=`, and requirements and semantics are not explicitly provided, the requirements and semantics are as specified in this Clause.

23.2.3 swap

[utility.swap]

```
template <class T>
void swap(T& a, T& b) noexcept(see below);
```

1 *Remarks:* This function shall not participate in overload resolution unless `is_move_constructible_v<T>` is true and `is_move_assignable_v<T>` is true. The expression inside `noexcept` is equivalent to:

```
is_nothrow_move_constructible_v<T> && is_nothrow_move_assignable_v<T>
```

2 *Requires:* Type `T` shall be `MoveConstructible` (Table 23) and `MoveAssignable` (Table 25).

3 *Effects:* Exchanges values stored in two locations.

```
template <class T, size_t N>
void swap(T (&a)[N], T (&b)[N]) noexcept(is_nothrow_swappable_v<T>);
```

- 4 *Remarks:* This function shall not participate in overload resolution unless `is_swappable_v<T>` is true.
- 5 *Requires:* `a[i]` shall be swappable with (20.5.3.2) `b[i]` for all `i` in the range `[0, N)`.
- 6 *Effects:* As if by `swap_ranges(a, a + N, b)`.

23.2.4 exchange

[utility.exchange]

```
template <class T, class U = T> T exchange(T& obj, U&& new_val);
```

- 1 *Effects:* Equivalent to:
- ```
 T old_val = std::move(obj);
 obj = std::forward<U>(new_val);
 return old_val;
```

### 23.2.5 Forward/move helpers

[forward]

- 1     The library provides templated helper functions to simplify applying move semantics to an lvalue and to simplify the implementation of forwarding functions. All functions specified in this subclause are signal-safe (21.10.3).

```
template <class T> constexpr T&& forward(remove_reference_t<T>& t) noexcept;
template <class T> constexpr T&& forward(remove_reference_t<T>&& t) noexcept;
```

- 2     *Returns:* `static_cast<T&&>(t)`.
- 3     *Remarks:* If the second form is instantiated with an lvalue reference type, the program is ill-formed.

4     [ *Example:*

```
template <class T, class A1, class A2>
shared_ptr<T> factory(A1&& a1, A2&& a2) {
 return shared_ptr<T>(new T(std::forward<A1>(a1), std::forward<A2>(a2)));
}
```

```
struct A {
 A(int&, const double&);
};
```

```
void g() {
 shared_ptr<A> sp1 = factory<A>(2, 1.414); // error: 2 will not bind to int&
 int i = 2;
 shared_ptr<A> sp2 = factory<A>(i, 1.414); // OK
}
```

In the first call to `factory`, `A1` is deduced as `int`, so `2` is forwarded to `A`'s constructor as an rvalue. In the second call to `factory`, `A1` is deduced as `int&`, so `i` is forwarded to `A`'s constructor as an lvalue. In both cases, `A2` is deduced as `double`, so `1.414` is forwarded to `A`'s constructor as an rvalue. — *end example*

```
template <class T> constexpr remove_reference_t<T>&& move(T&& t) noexcept;
```

- 5     *Returns:* `static_cast<remove_reference_t<T>&&>(t)`.

6     [ *Example:*

```
template <class T, class A1>
shared_ptr<T> factory(A1&& a1) {
 return shared_ptr<T>(new T(std::forward<A1>(a1)));
}
```

```

}

struct A {
 A();
 A(const A&); // copies from lvalues
 A(A&&); // moves from rvalues
};

void g() {
 A a;
 shared_ptr<A> sp1 = factory<A>(a); // "a" binds to A(const A&)
 shared_ptr<A> sp1 = factory<A>(std::move(a)); // "a" binds to A(A&&)
}

```

In the first call to `factory`, `A1` is deduced as `A&`, so `a` is forwarded as a non-const lvalue. This binds to the constructor `A(const A&)`, which copies the value from `a`. In the second call to `factory`, because of the call `std::move(a)`, `A1` is deduced as `A`, so `a` is forwarded as an rvalue. This binds to the constructor `A(A&&)`, which moves the value from `a`. — *end example*]

```

template <class T> constexpr conditional_t<
 !is_nothrow_move_constructible_v<T> && is_copy_constructible_v<T>, const T&, T&&>
 move_if_noexcept(T& x) noexcept;

```

7 *Returns:* `std::move(x)`.

### 23.2.6 Function template `as_const`

[utility.as\_const]

```

template <class T> constexpr add_const_t<T>& as_const(T& t) noexcept;

```

1 *Returns:* `t`.

### 23.2.7 Function template `declval`

[declval]

1 The library provides the function template `declval` to simplify the definition of expressions which occur as unevaluated operands (Clause 8).

```

template <class T> add_rvalue_reference_t<T> declval() noexcept; // as unevaluated operand

```

2 *Remarks:* If this function is odr-used (6.2), the program is ill-formed.

3 *Remarks:* The template parameter `T` of `declval` may be an incomplete type.

4 [Example:

```

 template <class To, class From> decltype(static_cast<To>(declval<From>())) convert(From&&);

```

declares a function template `convert` which only participates in overloading if the type `From` can be explicitly converted to type `To`. For another example see class template `common_type` (23.15.7.6). — *end example*]

### 23.2.8 Primitive numeric output conversion

[utility.to.chars]

1 All functions named `to_chars` convert `value` into a character string by successively filling the range `[first, last)`, where `[first, last)` is required to be a valid range. If the member `ec` of the return value is such that the value, when converted to `bool`, is `false`, the conversion was successful and the member `ptr` is the one-past-the-end pointer of the characters written. Otherwise, the member `ec` has the value `errc::value_too_large`, the member `ptr` has the value `last`, and the contents of the range `[first, last)` are unspecified.

2 The functions that take a floating-point `value` but not a `precision` parameter ensure that the string representation consists of the smallest number of characters such that there is at least one digit before the radix point (if present) and parsing the representation using the corresponding `from_chars` function recovers

value exactly. [ *Note:* This guarantee applies only if `to_chars` and `from_chars` are executed on the same implementation. — *end note* ]

- 3 The functions taking a `chars_format` parameter determine the conversion specifier for `printf` as follows: The conversion specifier is `f` if `fmt` is `chars_format::fixed`, `e` if `fmt` is `chars_format::scientific`, `a` (without leading "0x" in the result) if `fmt` is `chars_format::hex`, and `g` if `fmt` is `chars_format::general`.

```
to_chars_result to_chars(char* first, char* last, see below value, int base = 10);
```

- 4 *Requires:* `base` has a value between 2 and 36 (inclusive).
- 5 *Effects:* The value of `value` is converted to a string of digits in the given base (with no redundant leading zeroes). Digits in the range 10..35 (inclusive) are represented as lowercase characters `a..z`. If `value` is less than zero, the representation starts with a minus sign.
- 6 *Throws:* Nothing.
- 7 *Remarks:* The implementation shall provide overloads for all signed and unsigned integer types and `char` as the type of the parameter `value`.

```
to_chars_result to_chars(char* first, char* last, float value);
to_chars_result to_chars(char* first, char* last, double value);
to_chars_result to_chars(char* first, char* last, long double value);
```

- 8 *Effects:* `value` is converted to a string in the style of `printf` in the "C" locale. The conversion specifier is `f` or `e`, chosen according to the requirement for a shortest representation (see above); a tie is resolved in favor of `f`.
- 9 *Throws:* Nothing.

```
to_chars_result to_chars(char* first, char* last, float value, chars_format fmt);
to_chars_result to_chars(char* first, char* last, double value, chars_format fmt);
to_chars_result to_chars(char* first, char* last, long double value, chars_format fmt);
```

- 10 *Requires:* `fmt` has the value of one of the enumerators of `chars_format`.
- 11 *Effects:* `value` is converted to a string in the style of `printf` in the "C" locale.
- 12 *Throws:* Nothing.

```
to_chars_result to_chars(char* first, char* last, float value,
 chars_format fmt, int precision);
to_chars_result to_chars(char* first, char* last, double value,
 chars_format fmt, int precision);
to_chars_result to_chars(char* first, char* last, long double value,
 chars_format fmt, int precision);
```

- 13 *Requires:* `fmt` has the value of one of the enumerators of `chars_format`.
- 14 *Effects:* `value` is converted to a string in the style of `printf` in the "C" locale with the given precision.
- 15 *Throws:* Nothing.

SEE ALSO: ISO C 7.21.6.1.

### 23.2.9 Primitive numeric input conversion

[utility.from.chars]

- 1 All functions named `from_chars` analyze the string `[first, last)` for a pattern, where `[first, last)` is required to be a valid range. If no characters match the pattern, `value` is unmodified, the member `ptr` of the return value is `first` and the member `ec` is equal to `errc::invalid_argument`. Otherwise, the characters matching the pattern are interpreted as a representation of a value of the type of `value`. The member `ptr` of the return value points to the first character not matching the pattern, or has the value `last` if all characters match. If the parsed value is not in the range representable by the type of `value`, `value` is unmodified and



the member `ec` of the return value is equal to `errc::result_out_of_range`. Otherwise, `value` is set to the parsed value and the member `ec` is set such that the conversion to `bool` yields `false`.

```
from_chars_result from_chars(const char* first, const char* last,
 see below& value, int base = 10);
```

2 *Requires:* `base` has a value between 2 and 36 (inclusive).

3 *Effects:* The pattern is the expected form of the subject sequence in the "C" locale for the given nonzero `base`, as described for `strtoul`, except that no "0x" or "0X" prefix shall appear if the value of `base` is 16, and except that a minus sign is the only sign that may appear, and only if `value` has a signed type.

4 *Throws:* Nothing.

5 *Remarks:* The implementation shall provide overloads for all signed and unsigned integer types and `char` as the referenced type of the parameter `value`.

```
from_chars_result from_chars(const char* first, const char* last, float& value,
 chars_format fmt = chars_format::general);
from_chars_result from_chars(const char* first, const char* last, double& value,
 chars_format fmt = chars_format::general);
from_chars_result from_chars(const char* first, const char* last, long double& value,
 chars_format fmt = chars_format::general);
```

6 *Requires:* `fmt` has the value of one of the enumerators of `chars_format`.

7 *Effects:* The pattern is the expected form of the subject sequence in the "C" locale, as described for `strtod`, except that

- (7.1) — the only sign that may appear is a minus sign;
- (7.2) — if `fmt` has `chars_format::scientific` set but not `chars_format::fixed`, the otherwise optional exponent part shall appear;
- (7.3) — if `fmt` has `chars_format::fixed` set but not `chars_format::scientific`, the optional exponent part shall not appear; and
- (7.4) — if `fmt` is `chars_format::hex`, the prefix "0x" or "0X" is assumed. [*Example:* The string 0x123 is parsed to have the value 0 with remaining characters x123. — *end example*]

In any case, the resulting `value` is one of at most two floating-point values closest to the value of the string matching the pattern.

8 *Throws:* Nothing.

SEE ALSO: ISO C 7.22.1.3, ISO C 7.22.1.4.

## 23.3 Compile-time integer sequences [intseq]

### 23.3.1 In general [intseq.general]

- 1 The library provides a class template that can represent an integer sequence. When used as an argument to a function template the parameter pack defining the sequence can be deduced and used in a pack expansion. [*Note:* The `index_sequence` alias template is provided for the common case of an integer sequence of type `size_t`; see also 23.5.3.5. — *end note*]

### 23.3.2 Class template `integer_sequence` [intseq.intseq]

```
namespace std {
 template<class T, T... I>
 struct integer_sequence {
 using value_type = T;
 static constexpr size_t size() noexcept { return sizeof...(I); }
```

```
 };
}
```

- <sup>1</sup> T shall be an integer type.

### 23.3.3 Alias template `make_integer_sequence`

[intseq.make]

```
template<class T, T N>
using make_integer_sequence = integer_sequence<T, see below>;
```

- <sup>1</sup> If N is negative the program is ill-formed. The alias template `make_integer_sequence` denotes a specialization of `integer_sequence` with N template non-type arguments. The type `make_integer_sequence<T, N>` denotes the type `integer_sequence<T, 0, 1, ..., N-1>`. [Note: `make_integer_sequence<int, 0>` denotes the type `integer_sequence<int>` — end note]

## 23.4 Pairs

[pairs]

### 23.4.1 In general

[pairs.general]

- <sup>1</sup> The library provides a template for heterogeneous pairs of values. The library also provides a matching function template to simplify their construction and several templates that provide access to `pair` objects as if they were `tuple` objects (see 23.5.3.6 and 23.5.3.7).

### 23.4.2 Class template `pair`

[pairs.pair]

```
namespace std {
 template <class T1, class T2>
 struct pair {
 using first_type = T1;
 using second_type = T2;

 T1 first;
 T2 second;

 pair(const pair&) = default;
 pair(pair&&) = default;
 EXPLICIT constexpr pair();
 EXPLICIT constexpr pair(const T1& x, const T2& y);
 template<class U1, class U2> EXPLICIT constexpr pair(U1&& x, U2&& y);
 template<class U1, class U2> EXPLICIT constexpr pair(const pair<U1, U2>& p);
 template<class U1, class U2> EXPLICIT constexpr pair(pair<U1, U2>&& p);
 template <class... Args1, class... Args2>
 pair(piecewise_construct_t, tuple<Args1...> first_args, tuple<Args2...> second_args);

 pair& operator=(const pair& p);
 template<class U1, class U2> pair& operator=(const pair<U1, U2>& p);
 pair& operator=(pair&& p) noexcept(see below);
 template<class U1, class U2> pair& operator=(pair<U1, U2>&& p);

 void swap(pair& p) noexcept(see below);
 };

 template<class T1, class T2>
 pair(T1, T2) -> pair<T1, T2>;
}
```

- <sup>1</sup> Constructors and member functions of `pair` shall not throw exceptions unless one of the element-wise operations specified to be called for that operation throws an exception.

- 2 The defaulted move and copy constructor, respectively, of `pair` shall be a constexpr function if and only if all required element-wise initializations for copy and move, respectively, would satisfy the requirements for a constexpr function. The destructor of `pair` shall be a trivial destructor if `(is_trivially_destructible_v<T1> && is_trivially_destructible_v<T2>)` is true.

*EXPLICIT* constexpr pair();

- 3 *Effects:* Value-initializes `first` and `second`.

- 4 *Remarks:* This constructor shall not participate in overload resolution unless `is_default_constructible_v<first_type>` is true and `is_default_constructible_v<second_type>` is true. [ *Note:* This behavior can be implemented by a constructor template with default template arguments. — *end note* ] The constructor is explicit if and only if either `first_type` or `second_type` is not implicitly default-constructible. [ *Note:* This behavior can be implemented with a trait that checks whether a `const first_type&` or a `const second_type&` can be initialized with {}. — *end note* ]

*EXPLICIT* constexpr pair(const T1& x, const T2& y);

- 5 *Effects:* Initializes `first` with `x` and `second` with `y`.

- 6 *Remarks:* This constructor shall not participate in overload resolution unless `is_copy_constructible_v<first_type>` is true and `is_copy_constructible_v<second_type>` is true. The constructor is explicit if and only if `is_convertible_v<const first_type&, first_type>` is false or `is_convertible_v<const second_type&, second_type>` is false.

template<class U1, class U2> *EXPLICIT* constexpr pair(U1&& x, U2&& y);

- 7 *Effects:* Initializes `first` with `std::forward<U1>(x)` and `second` with `std::forward<U2>(y)`.

- 8 *Remarks:* This constructor shall not participate in overload resolution unless `is_constructible_v<first_type, U1&&>` is true and `is_constructible_v<second_type, U2&&>` is true. The constructor is explicit if and only if `is_convertible_v<U1&&, first_type>` is false or `is_convertible_v<U2&&, second_type>` is false.

template<class U1, class U2> *EXPLICIT* constexpr pair(const pair<U1, U2>& p);

- 9 *Effects:* Initializes members from the corresponding members of the argument.

- 10 *Remarks:* This constructor shall not participate in overload resolution unless `is_constructible_v<first_type, const U1&>` is true and `is_constructible_v<second_type, const U2&>` is true. The constructor is explicit if and only if `is_convertible_v<const U1&, first_type>` is false or `is_convertible_v<const U2&, second_type>` is false.

template<class U1, class U2> *EXPLICIT* constexpr pair(pair<U1, U2>&& p);

- 11 *Effects:* Initializes `first` with `std::forward<U1>(p.first)` and `second` with `std::forward<U2>(p.second)`.

- 12 *Remarks:* This constructor shall not participate in overload resolution unless `is_constructible_v<first_type, U1&&>` is true and `is_constructible_v<second_type, U2&&>` is true. The constructor is explicit if and only if `is_convertible_v<U1&&, first_type>` is false or `is_convertible_v<U2&&, second_type>` is false.

template<class... Args1, class... Args2>  
pair(piecewise\_construct\_t, tuple<Args1...> first\_args, tuple<Args2...> second\_args);

- 13 *Requires:* `is_constructible_v<first_type, Args1&&...>` is true and `is_constructible_v<second_type, Args2&&...>` is true.

- 14 *Effects:* Initializes `first` with arguments of types `Args1...` obtained by forwarding the elements of

`first_args` and initializes `second` with arguments of types `Args2...` obtained by forwarding the elements of `second_args`. (Here, forwarding an element `x` of type `U` within a `tuple` object means calling `std::forward<U>(x)`.) This form of construction, whereby constructor arguments for `first` and `second` are each provided in a separate `tuple` object, is called *piecewise construction*.

```
pair& operator=(const pair& p);
```

15 *Effects:* Assigns `p.first` to `first` and `p.second` to `second`.

16 *Remarks:* This operator shall be defined as deleted unless `is_copy_assignable_v<first_type>` is true and `is_copy_assignable_v<second_type>` is true.

17 *Returns:* `*this`.

```
template<class U1, class U2> pair& operator=(const pair<U1, U2>& p);
```

18 *Effects:* Assigns `p.first` to `first` and `p.second` to `second`.

19 *Remarks:* This operator shall not participate in overload resolution unless `is_assignable_v<first_type&, const U1&>` is true and `is_assignable_v<second_type&, const U2&>` is true.

20 *Returns:* `*this`.

```
pair& operator=(pair&& p) noexcept(see below);
```

21 *Effects:* Assigns to `first` with `std::forward<first_type>(p.first)` and to `second` with `std::forward<second_type>(p.second)`.

22 *Remarks:* This operator shall be defined as deleted unless `is_move_assignable_v<first_type>` is true and `is_move_assignable_v<second_type>` is true.

23 *Remarks:* The expression inside `noexcept` is equivalent to:

```
is_nothrow_move_assignable_v<T1> && is_nothrow_move_assignable_v<T2>
```

24 *Returns:* `*this`.

```
template<class U1, class U2> pair& operator=(pair<U1, U2>&& p);
```

25 *Effects:* Assigns to `first` with `std::forward<U>(p.first)` and to `second` with `std::forward<V>(p.second)`.

26 *Remarks:* This operator shall not participate in overload resolution unless `is_assignable_v<first_type&, U1&&>` is true and `is_assignable_v<second_type&, U2&&>` is true.

27 *Returns:* `*this`.

```
void swap(pair& p) noexcept(see below);
```

28 *Requires:* `first` shall be swappable with (20.5.3.2) `p.first` and `second` shall be swappable with `p.second`.

29 *Effects:* Swaps `first` with `p.first` and `second` with `p.second`.

30 *Remarks:* The expression inside `noexcept` is equivalent to:

```
is_nothrow_swappable_v<first_type> && is_nothrow_swappable_v<second_type>
```

### 23.4.3 Specialized algorithms

[pairs.spec]

```
template <class T1, class T2>
```

```
constexpr bool operator==(const pair<T1, T2>& x, const pair<T1, T2>& y);
```

1 *Returns:* `x.first == y.first && x.second == y.second`.

```
template <class T1, class T2>
```

```

constexpr bool operator<(const pair<T1, T2>& x, const pair<T1, T2>& y);
2 Returns: x.first < y.first || (!(y.first < x.first) && x.second < y.second).

template <class T1, class T2>
constexpr bool operator!=(const pair<T1, T2>& x, const pair<T1, T2>& y);
3 Returns: !(x == y).

template <class T1, class T2>
constexpr bool operator>(const pair<T1, T2>& x, const pair<T1, T2>& y);
4 Returns: y < x.

template <class T1, class T2>
constexpr bool operator>=(const pair<T1, T2>& x, const pair<T1, T2>& y);
5 Returns: !(x < y).

template <class T1, class T2>
constexpr bool operator<=(const pair<T1, T2>& x, const pair<T1, T2>& y);
6 Returns: !(y < x).

template<class T1, class T2> void swap(pair<T1, T2>& x, pair<T1, T2>& y)
noexcept(noexcept(x.swap(y)));
7 Effects: As if by x.swap(y).
8 Remarks: This function shall not participate in overload resolution unless is_swappable_v<T1> is
true and is_swappable_v<T2> is true.

template <class T1, class T2>
constexpr pair<V1, V2> make_pair(T1&& x, T2&& y);
9 Returns: pair<V1, V2>(std::forward<T1>(x), std::forward<T2>(y)), where V1 and V2 are deter-
mined as follows: Let Ui be decay_t<Ti> for each Ti. If Ui is a specialization of reference_wrapper,
then Vi is Ui::type&, otherwise Vi is Ui.
10 [Example: In place of:
 return pair<int, double>(5, 3.1415926); // explicit types
a C++ program may contain:
 return make_pair(5, 3.1415926); // types are deduced
— end example]
```

#### 23.4.4 Tuple-like access to pair

[pair.astuple]

```

template <class T1, class T2>
struct tuple_size<pair<T1, T2>> : integral_constant<size_t, 2> { };

tuple_element<0, pair<T1, T2>>::type
1 Value: The type T1.

tuple_element<1, pair<T1, T2>>::type
2 Value: The type T2.

template<size_t I, class T1, class T2>
constexpr tuple_element_t<I, pair<T1, T2>>& get(pair<T1, T2>& p) noexcept;
template<size_t I, class T1, class T2>
```

```
constexpr const tuple_element_t<I, pair<T1, T2>>& get(const pair<T1, T2>& p) noexcept;
template<size_t I, class T1, class T2>
constexpr tuple_element_t<I, pair<T1, T2>>&& get(pair<T1, T2>&& p) noexcept;
template<size_t I, class T1, class T2>
constexpr const tuple_element_t<I, pair<T1, T2>>&& get(const pair<T1, T2>&& p) noexcept;
```

- 3 *Returns:* If  $I == 0$  returns a reference to `p.first`; if  $I == 1$  returns a reference to `p.second`; otherwise the program is ill-formed.

```
template <class T1, class T2>
constexpr T1& get(pair<T1, T2>& p) noexcept;
template <class T1, class T2>
constexpr const T1& get(const pair<T1, T2>& p) noexcept;
template <class T1, class T2>
constexpr T1&& get(pair<T1, T2>&& p) noexcept;
template <class T1, class T2>
constexpr const T1&& get(const pair<T1, T2>&& p) noexcept;
```

- 4 *Requires:* `T1` and `T2` are distinct types. Otherwise, the program is ill-formed.

- 5 *Returns:* A reference to `p.first`.

```
template <class T2, class T1>
constexpr T2& get(pair<T1, T2>& p) noexcept;
template <class T2, class T1>
constexpr const T2& get(const pair<T1, T2>& p) noexcept;
template <class T2, class T1>
constexpr T2&& get(pair<T1, T2>&& p) noexcept;
template <class T2, class T1>
constexpr const T2&& get(const pair<T1, T2>&& p) noexcept;
```

- 6 *Requires:* `T1` and `T2` are distinct types. Otherwise, the program is ill-formed.

- 7 *Returns:* A reference to `p.second`.

### 23.4.5 Piecewise construction

[pair.piecewise]

```
struct piecewise_construct_t {
 explicit piecewise_construct_t() = default;
};
inline constexpr piecewise_construct_t piecewise_construct{};
```

- 1 The `struct piecewise_construct_t` is an empty structure type used as a unique type to disambiguate constructor and function overloading. Specifically, `pair` has a constructor with `piecewise_construct_t` as the first argument, immediately followed by two `tuple` (23.5) arguments used for piecewise construction of the elements of the `pair` object.

## 23.5 Tuples

[tuple]

### 23.5.1 In general

[tuple.general]

- 1 This subclause describes the tuple library that provides a tuple type as the class template `tuple` that can be instantiated with any number of arguments. Each template argument specifies the type of an element in the `tuple`. Consequently, tuples are heterogeneous, fixed-size collections of values. An instantiation of `tuple` with two arguments is similar to an instantiation of `pair` with the same two arguments. See 23.4.

### 23.5.2 Header `<tuple>` synopsis

[tuple.syn]

```
namespace std {
 // 23.5.3, class template tuple
 template <class... Types>
```

```

 class tuple;

 // 23.5.3.4, tuple creation functions
 inline constexpr unspecified ignore;

 template <class... TTypes>
 constexpr tuple<VTypes...> make_tuple(TTypes&&...);

 template <class... TTypes>
 constexpr tuple<TTypes&&...> forward_as_tuple(TTypes&&...) noexcept;

 template<class... TTypes>
 constexpr tuple<TTypes&...> tie(TTypes&...) noexcept;

 template <class... Tuples>
 constexpr tuple<CTypes...> tuple_cat(Tuples&&...);

 // 23.5.3.5, calling a function with a tuple of arguments
 template <class F, class Tuple>
 constexpr decltype(auto) apply(F&& f, Tuple&& t);

 template <class T, class Tuple>
 constexpr T make_from_tuple(Tuple&& t);

 // 23.5.3.6, tuple helper classes
 template <class T> class tuple_size; // not defined
 template <class T> class tuple_size<const T>;
 template <class T> class tuple_size<volatile T>;
 template <class T> class tuple_size<const volatile T>;

 template <class... Types> class tuple_size<tuple<Types...>>;

 template <size_t I, class T> class tuple_element; // not defined
 template <size_t I, class T> class tuple_element<I, const T>;
 template <size_t I, class T> class tuple_element<I, volatile T>;
 template <size_t I, class T> class tuple_element<I, const volatile T>;

 template <size_t I, class... Types>
 class tuple_element<I, tuple<Types...>>;

 template <size_t I, class T>
 using tuple_element_t = typename tuple_element<I, T>::type;

 // 23.5.3.7, element access
 template <size_t I, class... Types>
 constexpr tuple_element_t<I, tuple<Types...>>& get(tuple<Types...>&) noexcept;
 template <size_t I, class... Types>
 constexpr tuple_element_t<I, tuple<Types...>>&& get(tuple<Types...>&&) noexcept;
 template <size_t I, class... Types>
 constexpr const tuple_element_t<I, tuple<Types...>>& get(const tuple<Types...>&) noexcept;
 template <size_t I, class... Types>
 constexpr const tuple_element_t<I, tuple<Types...>>&& get(const tuple<Types...>&&) noexcept;
 template <class T, class... Types>
 constexpr T& get(tuple<Types...>& t) noexcept;
 template <class T, class... Types>

```

```

 constexpr T&& get(tuple<Types...>&& t) noexcept;
template <class T, class... Types>
 constexpr const T& get(const tuple<Types...>& t) noexcept;
template <class T, class... Types>
 constexpr const T&& get(const tuple<Types...>&& t) noexcept;

// 23.5.3.8, relational operators
template<class... TTypes, class... UTypes>
 constexpr bool operator==(const tuple<TTypes...>&, const tuple<UTypes...>&);
template<class... TTypes, class... UTypes>
 constexpr bool operator<(const tuple<TTypes...>&, const tuple<UTypes...>&);
template<class... TTypes, class... UTypes>
 constexpr bool operator!=(const tuple<TTypes...>&, const tuple<UTypes...>&);
template<class... TTypes, class... UTypes>
 constexpr bool operator>(const tuple<TTypes...>&, const tuple<UTypes...>&);
template<class... TTypes, class... UTypes>
 constexpr bool operator<=(const tuple<TTypes...>&, const tuple<UTypes...>&);
template<class... TTypes, class... UTypes>
 constexpr bool operator>=(const tuple<TTypes...>&, const tuple<UTypes...>&);

// 23.5.3.9, allocator-related traits
template <class... Types, class Alloc>
 struct uses_allocator<tuple<Types...>, Alloc>;

// 23.5.3.10, specialized algorithms
template <class... Types>
 void swap(tuple<Types...>& x, tuple<Types...>& y) noexcept(see below);

// 23.5.3.6, tuple helper classes
template <class T>
 inline constexpr size_t tuple_size_v = tuple_size<T>::value;
}

```

### 23.5.3 Class template tuple

[tuple.tuple]

```

namespace std {
 template <class... Types>
 class tuple {
 public:
 // 23.5.3.1, tuple construction
 EXPLICIT constexpr tuple();
 EXPLICIT constexpr tuple(const Types&...); // only if sizeof...(Types) >= 1
 template <class... UTypes>
 EXPLICIT constexpr tuple(UTypes&&...); // only if sizeof...(Types) >= 1

 tuple(const tuple&) = default;
 tuple(tuple&&) = default;

 template <class... UTypes>
 EXPLICIT constexpr tuple(const tuple<UTypes...>&);
 template <class... UTypes>
 EXPLICIT constexpr tuple(tuple<UTypes...>&&);

 template <class U1, class U2>
 EXPLICIT constexpr tuple(const pair<U1, U2>&); // only if sizeof...(Types) == 2
 template <class U1, class U2>

```



```

 EXPLICIT constexpr tuple(pair<U1, U2>&&); // only if sizeof...(Types) == 2

// allocator-extended constructors
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a);
template <class Alloc>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const Types&...);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, UTypes&&...);
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a, const tuple&);
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a, tuple&&);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const tuple<UTypes...>&);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, tuple<UTypes...>&&);
template <class Alloc, class U1, class U2>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const pair<U1, U2>&);
template <class Alloc, class U1, class U2>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, pair<U1, U2>&&);

// 23.5.3.2, tuple assignment
tuple& operator=(const tuple&);
tuple& operator=(tuple&&) noexcept(see below);

template <class... UTypes>
 tuple& operator=(const tuple<UTypes...>&);
template <class... UTypes>
 tuple& operator=(tuple<UTypes...>&&);

template <class U1, class U2>
 tuple& operator=(const pair<U1, U2>&); // only if sizeof...(Types) == 2
template <class U1, class U2>
 tuple& operator=(pair<U1, U2>&&); // only if sizeof...(Types) == 2

// 23.5.3.3, tuple swap
void swap(tuple&) noexcept(see below);
};

template<class... UTypes>
 tuple(UTypes...) -> tuple<UTypes...>;
template<class T1, class T2>
 tuple(pair<T1, T2>) -> tuple<T1, T2>;
template<class Alloc, class... UTypes>
 tuple(allocator_arg_t, Alloc, UTypes...) -> tuple<UTypes...>;
template<class Alloc, class T1, class T2>
 tuple(allocator_arg_t, Alloc, pair<T1, T2>) -> tuple<T1, T2>;
template<class Alloc, class... UTypes>
 tuple(allocator_arg_t, Alloc, tuple<UTypes...>) -> tuple<UTypes...>;
}

```

### 23.5.3.1 Construction

[tuple.cnstr]

- <sup>1</sup> For each tuple constructor, an exception is thrown only if the construction of one of the types in Types throws an exception.

- 2 The defaulted move and copy constructor, respectively, of `tuple` shall be a constexpr function if and only if all required element-wise initializations for copy and move, respectively, would satisfy the requirements for a constexpr function. The defaulted move and copy constructor of `tuple<>` shall be constexpr functions.
- 3 The destructor of `tuple` shall be a trivial destructor if `(is_trivially_destructible_v<Types> && ...)` is true.
- 4 In the constructor descriptions that follow, let  $i$  be in the range  $[0, \text{sizeof}...(Types))$  in order,  $T_i$  be the  $i^{\text{th}}$  type in `Types`, and  $U_i$  be the  $i^{\text{th}}$  type in a template parameter pack named `UTypes`, where indexing is zero-based.

*EXPLICIT* constexpr `tuple()`;

- 5 *Effects:* Value-initializes each element.

- 6 *Remarks:* This constructor shall not participate in overload resolution unless `is_default_constructible_v<Ti>` is true for all  $i$ . [ *Note:* This behavior can be implemented by a constructor template with default template arguments. — *end note* ] The constructor is explicit if and only if  $T_i$  is not implicitly default-constructible for at least one  $i$ . [ *Note:* This behavior can be implemented with a trait that checks whether a `const Ti&` can be initialized with `{}`. — *end note* ]

*EXPLICIT* constexpr `tuple(const Types&...)`;

- 7 *Effects:* Initializes each element with the value of the corresponding parameter.

- 8 *Remarks:* This constructor shall not participate in overload resolution unless `sizeof...(Types) >= 1` and `is_copy_constructible_v<Ti>` is true for all  $i$ . The constructor is explicit if and only if `is_convertible_v<const Ti&, Ti>` is false for at least one  $i$ .

template <class... UTypes> *EXPLICIT* constexpr `tuple(UTypes&&... u)`;

- 9 *Effects:* Initializes the elements in the tuple with the corresponding value in `std::forward<UTypes>(u)`.

- 10 *Remarks:* This constructor shall not participate in overload resolution unless `sizeof...(Types) == sizeof...(UTypes)` and `sizeof...(Types) >= 1` and `is_constructible_v<Ti, Ui&&>` is true for all  $i$ . The constructor is explicit if and only if `is_convertible_v<Ui&&, Ti>` is false for at least one  $i$ .

`tuple(const tuple& u) = default;`

- 11 *Requires:* `is_copy_constructible_v<Ti>` is true for all  $i$ .

- 12 *Effects:* Initializes each element of `*this` with the corresponding element of `u`.

`tuple(tuple&& u) = default;`

- 13 *Requires:* `is_move_constructible_v<Ti>` is true for all  $i$ .

- 14 *Effects:* For all  $i$ , initializes the  $i^{\text{th}}$  element of `*this` with `std::forward<Ti>(get<i.`

template <class... UTypes> *EXPLICIT* constexpr `tuple(const tuple<UTypes...>& u)`;

- 15 *Effects:* Initializes each element of `*this` with the corresponding element of `u`.

- 16 *Remarks:* This constructor shall not participate in overload resolution unless

- (16.1) — `sizeof...(Types) == sizeof...(UTypes)` and

- (16.2) — `is_constructible_v<Ti, const Ui&>` is true for all  $i$ , and

- (16.3) — `sizeof...(Types) != 1`, or (when `Types...` expands to `T` and `UTypes...` expands to `U`)  
`!is_convertible_v<const tuple<U>&, T> && !is_constructible_v<T, const tuple<U>&>`  
`&& !is_same_v<T, U>` is true.

The constructor is explicit if and only if `is_convertible_v<const Ui&, Ti>` is false for at least one

*i*.

```
template <class... UTypes> EXPLICIT constexpr tuple(tuple<UTypes...>&& u);
```

17 *Effects*: For all *i*, initializes the *i*<sup>th</sup> element of *\*this* with `std::forward<Ui>(get<i>(u))`.

18 *Remarks*: This constructor shall not participate in overload resolution unless

(18.1) — `sizeof...(Types) == sizeof...(UTypes)`, and

(18.2) — `is_constructible_v<Ti, Ui&&>` is true for all *i*, and

(18.3) — `sizeof...(Types) != 1`, or (when `Types...` expands to `T` and `UTypes...` expands to `U`)  
`!is_convertible_v<tuple<U>, T> && !is_constructible_v<T, tuple<U>> &&`  
`!is_same_v<T, U>` is true.

The constructor is explicit if and only if `is_convertible_v<Ui&&, Ti>` is false for at least one *i*.

```
template <class U1, class U2> EXPLICIT constexpr tuple(const pair<U1, U2>&& u);
```

19 *Effects*: Initializes the first element with `u.first` and the second element with `u.second`.

20 *Remarks*: This constructor shall not participate in overload resolution unless `sizeof...(Types) == 2`,  
`is_constructible_v<T0, const U1&>` is true and `is_constructible_v<T1, const U2&>` is true.

21 The constructor is explicit if and only if `is_convertible_v<const U1&, T0>` is false or `is_convertible_v<const U2&, T1>` is false.

```
template <class U1, class U2> EXPLICIT constexpr tuple(pair<U1, U2>&& u);
```

22 *Effects*: Initializes the first element with `std::forward<U1>(u.first)` and the second element with  
`std::forward<U2>(u.second)`.

23 *Remarks*: This constructor shall not participate in overload resolution unless `sizeof...(Types) == 2`,  
`is_constructible_v<T0, U1&&>` is true and `is_constructible_v<T1, U2&&>` is true.

24 The constructor is explicit if and only if `is_convertible_v<U1&&, T0>` is false or `is_convertible_v<U2&&, T1>` is false.

```
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a);
template <class Alloc>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const Types&...);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, UTypes&&...);
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a, const tuple&);
template <class Alloc>
 tuple(allocator_arg_t, const Alloc& a, tuple&&);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const tuple<UTypes...>&);
template <class Alloc, class... UTypes>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, tuple<UTypes...>&&);
template <class Alloc, class U1, class U2>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, const pair<U1, U2>&);
template <class Alloc, class U1, class U2>
 EXPLICIT tuple(allocator_arg_t, const Alloc& a, pair<U1, U2>&&);
```

25 *Requires*: `Alloc` shall meet the requirements for an `Allocator` (20.5.3.5).

26 *Effects*: Equivalent to the preceding constructors except that each element is constructed with `uses_allocator` construction (23.10.7.2).

**23.5.3.2 Assignment****[tuple.assign]**

- <sup>1</sup> For each **tuple** assignment operator, an exception is thrown only if the assignment of one of the types in **Types** throws an exception. In the function descriptions that follow, let  $i$  be in the range  $[0, \text{sizeof} \dots (\text{Types}))$  in order,  $T_i$  be the  $i^{\text{th}}$  type in **Types**, and  $U_i$  be the  $i^{\text{th}}$  type in a template parameter pack named **UTypes**, where indexing is zero-based.

```
tuple& operator=(const tuple& u);
```

- <sup>2</sup> *Effects:* Assigns each element of **u** to the corresponding element of **\*this**.  
<sup>3</sup> *Remarks:* This operator shall be defined as deleted unless **is\_copy\_assignable\_v<T<sub>i</sub>>** is **true** for all  $i$ .  
<sup>4</sup> *Returns:* **\*this**.

```
tuple& operator=(tuple&& u) noexcept(see below);
```

- <sup>5</sup> *Effects:* For all  $i$ , assigns **std::forward<T<sub>i</sub>>(get<i>(u))** to **get<i>(\*this)**.  
<sup>6</sup> *Remarks:* This operator shall be defined as deleted unless **is\_move\_assignable\_v<T<sub>i</sub>>** is **true** for all  $i$ .  
<sup>7</sup> *Remarks:* The expression inside **noexcept** is equivalent to the logical AND of the following expressions:  
     **is\_nothrow\_move\_assignable\_v<T<sub>i</sub>>**  
     where  $T_i$  is the  $i^{\text{th}}$  type in **Types**.  
<sup>8</sup> *Returns:* **\*this**.

```
template <class... UTypes> tuple& operator=(const tuple<UTypes...>& u);
```

- <sup>9</sup> *Effects:* Assigns each element of **u** to the corresponding element of **\*this**.  
<sup>10</sup> *Remarks:* This operator shall not participate in overload resolution unless **sizeof... (Types) == sizeof... (UTypes)** and **is\_assignable\_v<T<sub>i</sub>&, const U<sub>i</sub>&>** is **true** for all  $i$ .  
<sup>11</sup> *Returns:* **\*this**.

```
template <class... UTypes> tuple& operator=(tuple<UTypes...>&& u);
```

- <sup>12</sup> *Effects:* For all  $i$ , assigns **std::forward<U<sub>i</sub>>(get<i>(u))** to **get<i>(\*this)**.  
<sup>13</sup> *Remarks:* This operator shall not participate in overload resolution unless **is\_assignable\_v<T<sub>i</sub>&, U<sub>i</sub>&&> == true** for all  $i$  and **sizeof... (Types) == sizeof... (UTypes)**.  
<sup>14</sup> *Returns:* **\*this**.

```
template <class U1, class U2> tuple& operator=(const pair<U1, U2>& u);
```

- <sup>15</sup> *Effects:* Assigns **u.first** to the first element of **\*this** and **u.second** to the second element of **\*this**.  
<sup>16</sup> *Remarks:* This operator shall not participate in overload resolution unless **sizeof... (Types) == 2** and **is\_assignable\_v<T<sub>0</sub>&, const U1&>** is **true** for the first type  $T_0$  in **Types** and **is\_assignable\_v<T<sub>1</sub>&, const U2&>** is **true** for the second type  $T_1$  in **Types**.  
<sup>17</sup> *Returns:* **\*this**.

```
template <class U1, class U2> tuple& operator=(pair<U1, U2>&& u);
```

- <sup>18</sup> *Effects:* Assigns **std::forward<U1>(u.first)** to the first element of **\*this** and **std::forward<U2>(u.second)** to the second element of **\*this**.  
<sup>19</sup> *Remarks:* This operator shall not participate in overload resolution unless **sizeof... (Types) == 2** and **is\_assignable\_v<T<sub>0</sub>&, U1&&>** is **true** for the first type  $T_0$  in **Types** and **is\_assignable\_v<T<sub>1</sub>&, U2&&>** is **true** for the second type  $T_1$  in **Types**.  
<sup>20</sup> *Returns:* **\*this**.

**23.5.3.3 swap****[tuple.swap]**

```
void swap(tuple& rhs) noexcept(see below);
```

- 1 *Requires:* Each element in `*this` shall be swappable with (20.5.3.2) the corresponding element in `rhs`.
- 2 *Effects:* Calls `swap` for each element in `*this` and its corresponding element in `rhs`.
- 3 *Remarks:* The expression inside `noexcept` is equivalent to the logical AND of the following expressions:  
`is_nothrow_swappable_v<Ti>`  
 where  $T_i$  is the  $i^{\text{th}}$  type in `Types`.
- 4 *Throws:* Nothing unless one of the element-wise `swap` calls throws an exception.

**23.5.3.4 Tuple creation functions****[tuple.creation]**

- 1 In the function descriptions that follow, the members of a parameter pack `XTypes` are denoted by  $X_i$  for  $i$  in `[0, sizeof...(XTypes))` in order, where indexing is zero-based.

```
template<class... TTypes>
constexpr tuple<VTypes...> make_tuple(TTypes&&... t);
```

- 2 The pack `VTypes` is defined as follows. Let  $U_i$  be `decay_t<Ti>` for each  $T_i$  in `TTypes`. If  $U_i$  is a specialization of `reference_wrapper`, then  $V_i$  in `VTypes` is `Ui::type&`, otherwise  $V_i$  is  $U_i$ .
- 3 *Returns:* `tuple<VTypes...>(std::forward<TTypes>(t)...) .`
- 4 [ *Example:*  

```
int i; float j;
make_tuple(1, ref(i), cref(j))
```

 creates a tuple of type `tuple<int, int&, const float&>`. — *end example* ]

```
template<class... TTypes>
constexpr tuple<TTypes&&...> forward_as_tuple(TTypes&&... t) noexcept;
```

- 5 *Effects:* Constructs a tuple of references to the arguments in `t` suitable for forwarding as arguments to a function. Because the result may contain references to temporary variables, a program shall ensure that the return value of this function does not outlive any of its arguments (e.g., the program should typically not store the result in a named variable).
- 6 *Returns:* `tuple<TTypes&&...>(std::forward<TTypes>(t)...) .`

```
template<class... TTypes>
constexpr tuple<TTypes&...> tie(TTypes&... t) noexcept;
```

- 7 *Returns:* `tuple<TTypes&...>(t...) .` When an argument in `t` is `ignore`, assigning any value to the corresponding tuple element has no effect.
- 8 [ *Example:* `tie` functions allow one to create tuples that unpack tuples into variables. `ignore` can be used for elements that are not needed:  

```
int i; std::string s;
tie(i, ignore, s) = make_tuple(42, 3.14, "C++");
// i == 42, s == "C++"
```

 — *end example* ]

```
template <class... Tuples>
constexpr tuple<CTypes...> tuple_cat(Tuples&&... tpls);
```

- 9 In the following paragraphs, let  $T_i$  be the  $i^{\text{th}}$  type in `Tuples`,  $U_i$  be `remove_reference_t<Ti>`, and  $tp_i$  be the  $i^{\text{th}}$  parameter in the function parameter pack `tpls`, where all indexing is zero-based.

- 10 *Requires:* For all  $i$ ,  $U_i$  shall be the type  $cv_i$  `tuple<Argsi...>`, where  $cv_i$  is the (possibly empty)  $i^{\text{th}}$  *cv-qualifier-seq* and  $\text{Args}_i$  is the parameter pack representing the element types in  $U_i$ . Let  $A_{ik}$  be the  $k^{\text{th}}$  type in  $\text{Args}_i$ . For all  $A_{ik}$  the following requirements shall be satisfied:
- (10.1) — If  $T_i$  is deduced as an lvalue reference type, then `is_constructible_v<Aik, cvi Aik&&> == true`, otherwise
- (10.2) — `is_constructible_v<Aik, cvi Aik&&> == true`.
- 11 *Remarks:* The types in `CTypes` shall be equal to the ordered sequence of the extended types  $\text{Args}_0, \dots, \text{Args}_1, \dots, \dots, \text{Args}_{n-1}, \dots$ , where  $n$  is equal to `sizeof...(Tuples)`. Let  $e_i \dots$  be the  $i^{\text{th}}$  ordered sequence of tuple elements of the resulting tuple object corresponding to the type sequence  $\text{Args}_i$ .
- 12 *Returns:* A tuple object constructed by initializing the  $k_i^{\text{th}}$  type element  $e_{ik}$  in  $e_i \dots$  with  
`get<kiii))`  
for each valid  $k_i$  and each group  $e_i$  in order.
- 13 [ *Note:* An implementation may support additional types in the parameter pack `Tuples` that support the tuple-like protocol, such as `pair` and `array`. — *end note* ]

### 23.5.3.5 Calling a function with a tuple of arguments

[tuple.apply]

```
template <class F, class Tuple>
constexpr decltype(auto) apply(F&& f, Tuple&& t);
```

- 1 *Effects:* Given the exposition-only function:

```
template <class F, class Tuple, size_t... I>
constexpr decltype(auto)
 apply_impl(F&& f, Tuple&& t, index_sequence<I...>) { // exposition only
 return INVOKE(std::forward<F>(f), std::get<I>(std::forward<Tuple>(t))...);
}
```

Equivalent to:

```
return apply_impl(std::forward<F>(f), std::forward<Tuple>(t),
 make_index_sequence<tuple_size_v<decay_t<Tuple>>>{}>());
```

```
template <class T, class Tuple>
constexpr T make_from_tuple(Tuple&& t);
```

- 2 *Effects:* Given the exposition-only function:

```
template <class T, class Tuple, size_t... I>
constexpr T make_from_tuple_impl(Tuple&& t, index_sequence<I...>) { // exposition only
 return T(get<I>(std::forward<Tuple>(t))...);
}
```

Equivalent to:

```
return make_from_tuple_impl<T>(forward<Tuple>(t),
 make_index_sequence<tuple_size_v<decay_t<Tuple>>>{}>());
```

[ *Note:* The type of `T` must be supplied as an explicit template parameter, as it cannot be deduced from the argument list. — *end note* ]

### 23.5.3.6 Tuple helper classes

[tuple.helper]

```
template <class T> struct tuple_size;
```

- 1 *Remarks:* All specializations of `tuple_size` shall meet the `UnaryTypeTrait` requirements (23.15.1) with a base characteristic of `integral_constant<size_t, N>` for some `N`.

```
template <class... Types>
 class tuple_size<tuple<Types...>> : public integral_constant<size_t, sizeof...(Types)> { };
```

```
template <size_t I, class... Types>
 class tuple_element<I, tuple<Types...>> {
 public:
 using type = TI;
 };
```

2     *Requires:*  $I < \text{sizeof} \dots (\text{Types})$ . The program is ill-formed if  $I$  is out of bounds.

3     *Type:*  $\text{TI}$  is the type of the  $I$ th element of  $\text{Types}$ , where indexing is zero-based.

```
template <class T> class tuple_size<const T>;
template <class T> class tuple_size<volatile T>;
template <class T> class tuple_size<const volatile T>;
```

4     Let  $TS$  denote  $\text{tuple\_size}<T>$  of the *cv*-unqualified type  $T$ . If the expression  $TS::\text{value}$  is well-formed when treated as an unevaluated operand, then each of the three templates shall meet the `UnaryTypeTrait` requirements (23.15.1) with a base characteristic of

```
 integral_constant<size_t, TS::value>
```

Otherwise, they shall have no member `value`.

5     Access checking is performed as if in a context unrelated to  $TS$  and  $T$ . Only the validity of the immediate context of the expression is considered. [*Note:* The compilation of the expression can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — *end note*]

6     In addition to being available via inclusion of the `<tuple>` header, the three templates are available when either of the headers `<array>` or `<utility>` are included.

```
template <size_t I, class T> class tuple_element<I, const T>;
template <size_t I, class T> class tuple_element<I, volatile T>;
template <size_t I, class T> class tuple_element<I, const volatile T>;
```

7     Let  $TE$  denote  $\text{tuple\_element\_t}<I, T>$  of the *cv*-unqualified type  $T$ . Then each of the three templates shall meet the `TransformationTrait` requirements (23.15.1) with a member typedef `type` that names the following type:

(7.1)     — for the first specialization, `add_const_t<TE>`,

(7.2)     — for the second specialization, `add_volatile_t<TE>`, and

(7.3)     — for the third specialization, `add_cv_t<TE>`.

8     In addition to being available via inclusion of the `<tuple>` header, the three templates are available when either of the headers `<array>` or `<utility>` are included.

### 23.5.3.7 Element access

[`tuple.elem`]

```
template <size_t I, class... Types>
 constexpr tuple_element_t<I, tuple<Types...>>&
 get(tuple<Types...>& t) noexcept;
template <size_t I, class... Types>
 constexpr tuple_element_t<I, tuple<Types...>>&&
 get(tuple<Types...>&& t) noexcept; // Note A
template <size_t I, class... Types>
 constexpr const tuple_element_t<I, tuple<Types...>>&
 get(const tuple<Types...>& t) noexcept; // Note B
```

```
template <size_t I, class... Types>
constexpr const tuple_element_t<I, tuple<Types...>&& get(const tuple<Types...>&& t) noexcept;
```

1     *Requires:*  $I < \text{sizeof} \dots (\text{Types})$ . The program is ill-formed if  $I$  is out of bounds.

2     *Returns:* A reference to the  $I$ th element of  $t$ , where indexing is zero-based.

3     [ *Note A:* If a  $T$  in  $\text{Types}$  is some reference type  $X\&$ , the return type is  $X\&$ , not  $X\&\&$ . However, if the element type is a non-reference type  $T$ , the return type is  $T\&\&$ . — *end note* ]

4     [ *Note B:* Constness is shallow. If a  $T$  in  $\text{Types}$  is some reference type  $X\&$ , the return type is  $X\&$ , not  $\text{const } X\&$ . However, if the element type is a non-reference type  $T$ , the return type is  $\text{const } T\&\&$ . This is consistent with how constness is defined to work for member variables of reference type. — *end note* ]

```
template <class T, class... Types>
constexpr T& get(tuple<Types...>& t) noexcept;
template <class T, class... Types>
constexpr T&& get(tuple<Types...>&& t) noexcept;
template <class T, class... Types>
constexpr const T& get(const tuple<Types...>& t) noexcept;
template <class T, class... Types>
constexpr const T&& get(const tuple<Types...>&& t) noexcept;
```

5     *Requires:* The type  $T$  occurs exactly once in  $\text{Types} \dots$ . Otherwise, the program is ill-formed.

6     *Returns:* A reference to the element of  $t$  corresponding to the type  $T$  in  $\text{Types} \dots$ .

7     [ *Example:*

```
 const tuple<int, const int, double, double> t(1, 2, 3.4, 5.6);
 const int& i1 = get<int>(t); // OK. Not ambiguous. i1 == 1
 const int& i2 = get<const int>(t); // OK. Not ambiguous. i2 == 2
 const double& d = get<double>(t); // ERROR. ill-formed
```

— *end example* ]

8     [ *Note:* The reason `get` is a non-member function is that if this functionality had been provided as a member function, code where the type depended on a template parameter would have required using the `template` keyword. — *end note* ]

### 23.5.3.8 Relational operators

[tuple.rel]

```
template<class... TTypes, class... UTypes>
constexpr bool operator==(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

1     *Requires:* For all  $i$ , where  $0 \leq i$  and  $i < \text{sizeof} \dots (\text{TTypes})$ ,  $\text{get}<i>(t) == \text{get}<i>(u)$  is a valid expression returning a type that is convertible to `bool`.  $\text{sizeof} \dots (\text{TTypes}) == \text{sizeof} \dots (\text{UTypes})$ .

2     *Returns:* `true` if  $\text{get}<i>(t) == \text{get}<i>(u)$  for all  $i$ , otherwise `false`. For any two zero-length tuples  $e$  and  $f$ ,  $e == f$  returns `true`.

3     *Effects:* The elementary comparisons are performed in order from the zeroth index upwards. No comparisons or element accesses are performed after the first equality comparison that evaluates to `false`.

```
template<class... TTypes, class... UTypes>
constexpr bool operator<(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

4     *Requires:* For all  $i$ , where  $0 \leq i$  and  $i < \text{sizeof} \dots (\text{TTypes})$ , both  $\text{get}<i>(t) < \text{get}<i>(u)$  and  $\text{get}<i>(u) < \text{get}<i>(t)$  are valid expressions returning types that are convertible to `bool`.  $\text{sizeof} \dots (\text{TTypes}) == \text{sizeof} \dots (\text{UTypes})$ .

5     *Returns:* The result of a lexicographical comparison between  $t$  and  $u$ . The result is defined as:



$(\text{bool})(\text{get}<0>(t) < \text{get}<0>(u)) \ || \ (!(\text{bool})(\text{get}<0>(u) < \text{get}<0>(t)) \ \&\& \ t_{\text{tail}} < u_{\text{tail}})$ , where  $r_{\text{tail}}$  for some tuple  $r$  is a tuple containing all but the first element of  $r$ . For any two zero-length tuples  $e$  and  $f$ ,  $e < f$  returns false.

```
template<class... TTypes, class... UTypes>
constexpr bool operator!=(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

6 *Returns:*  $!(t == u)$ .

```
template<class... TTypes, class... UTypes>
constexpr bool operator>(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

7 *Returns:*  $u < t$ .

```
template<class... TTypes, class... UTypes>
constexpr bool operator<=(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

8 *Returns:*  $!(u < t)$ .

```
template<class... TTypes, class... UTypes>
constexpr bool operator>=(const tuple<TTypes...>& t, const tuple<UTypes...>& u);
```

9 *Returns:*  $!(t < u)$ .

10 [ *Note:* The above definitions for comparison functions do not require  $t_{\text{tail}}$  (or  $u_{\text{tail}}$ ) to be constructed. It may not even be possible, as  $t$  and  $u$  are not required to be copy constructible. Also, all comparison functions are short circuited; they do not perform element accesses beyond what is required to determine the result of the comparison. — *end note* ]

### 23.5.3.9 Tuple traits

[tuple.traits]

```
template <class... Types, class Alloc>
struct uses_allocator<tuple<Types...>, Alloc> : true_type { };
```

1 *Requires:* Alloc shall be an Allocator (20.5.3.5).

2 [ *Note:* Specialization of this trait informs other library components that `tuple` can be constructed with an allocator, even though it does not have a nested `allocator_type`. — *end note* ]

### 23.5.3.10 Tuple specialized algorithms

[tuple.special]

```
template <class... Types>
void swap(tuple<Types...>& x, tuple<Types...>& y) noexcept(see below);
```

1 *Remarks:* This function shall not participate in overload resolution unless `is_swappable_v<Ti>` is true for all  $i$ , where  $0 \leq i < \text{sizeof}...(Types)$ . The expression inside `noexcept` is equivalent to:

```
noexcept(x.swap(y))
```

2 *Effects:* As if by `x.swap(y)`.

## 23.6 Optional objects

[optional]

### 23.6.1 In general

[optional.general]

1 This subclause describes class template `optional` that represents optional objects. An *optional object* is an object that contains the storage for another object and manages the lifetime of this contained object, if any. The contained object may be initialized after the optional object has been initialized, and may be destroyed before the optional object has been destroyed. The initialization state of the contained object is tracked by the optional object.

### 23.6.2 Header <optional> synopsis

[optional.syn]

```

namespace std {
 // 23.6.3, class template optional
 template <class T>
 class optional;

 // 23.6.4, no-value state indicator
 struct nullopt_t{see below};
 inline constexpr nullopt_t nullopt(unspecified);

 // 23.6.5, class bad_optional_access
 class bad_optional_access;

 // 23.6.6, relational operators
 template <class T, class U>
 constexpr bool operator==(const optional<T>&, const optional<U>&);
 template <class T, class U>
 constexpr bool operator!=(const optional<T>&, const optional<U>&);
 template <class T, class U>
 constexpr bool operator<(const optional<T>&, const optional<U>&);
 template <class T, class U>
 constexpr bool operator>(const optional<T>&, const optional<U>&);
 template <class T, class U>
 constexpr bool operator<=(const optional<T>&, const optional<U>&);
 template <class T, class U>
 constexpr bool operator>=(const optional<T>&, const optional<U>&);

 // 23.6.7, comparison with nullopt
 template <class T> constexpr bool operator==(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator==(nullopt_t, const optional<T>&) noexcept;
 template <class T> constexpr bool operator!=(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator!=(nullopt_t, const optional<T>&) noexcept;
 template <class T> constexpr bool operator<(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator<(nullopt_t, const optional<T>&) noexcept;
 template <class T> constexpr bool operator<=(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator<=(nullopt_t, const optional<T>&) noexcept;
 template <class T> constexpr bool operator>(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator>(nullopt_t, const optional<T>&) noexcept;
 template <class T> constexpr bool operator>=(const optional<T>&, nullopt_t) noexcept;
 template <class T> constexpr bool operator>=(nullopt_t, const optional<T>&) noexcept;

 // 23.6.8, comparison with T
 template <class T, class U> constexpr bool operator==(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator==(const U&, const optional<T>&);
 template <class T, class U> constexpr bool operator!=(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator!=(const U&, const optional<T>&);
 template <class T, class U> constexpr bool operator<(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator<(const U&, const optional<T>&);
 template <class T, class U> constexpr bool operator<=(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator<=(const U&, const optional<T>&);
 template <class T, class U> constexpr bool operator>(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator>(const U&, const optional<T>&);
 template <class T, class U> constexpr bool operator>=(const optional<T>&, const U&);
 template <class T, class U> constexpr bool operator>=(const U&, const optional<T>&);

 // 23.6.9, specialized algorithms

```

```

template <class T>
 void swap(optional<T>&, optional<T>&) noexcept(see below);

template <class T>
 constexpr optional<see below> make_optional(T&&);
template <class T, class... Args>
 constexpr optional<T> make_optional(Args&&... args);
template <class T, class U, class... Args>
 constexpr optional<T> make_optional(initializer_list<U> il, Args&&... args);

// 23.6.10, hash support
template <class T> struct hash;
template <class T> struct hash<optional<T>>;
}

```

- <sup>1</sup> A program that necessitates the instantiation of template `optional` for a reference type, or for possibly cv-qualified types `in_place_t` or `nullopt_t` is ill-formed.

### 23.6.3 Class template `optional`

[optional.optional]

```

template <class T>
 class optional {
 public:
 using value_type = T;

// 23.6.3.1, constructors
 constexpr optional() noexcept;
 constexpr optional(nullopt_t) noexcept;
 constexpr optional(const optional&);
 constexpr optional(optional&&) noexcept(see below);
 template <class... Args>
 constexpr explicit optional(in_place_t, Args&&...);
 template <class U, class... Args>
 constexpr explicit optional(in_place_t, initializer_list<U>, Args&&...);
 template <class U = T>
 EXPLICIT constexpr optional(U&&);
 template <class U>
 EXPLICIT optional(const optional<U>&);
 template <class U>
 EXPLICIT optional(optional<U>&&);

// 23.6.3.2, destructor
 ~optional();

// 23.6.3.3, assignment
 optional& operator=(nullopt_t) noexcept;
 optional& operator=(const optional&);
 optional& operator=(optional&&) noexcept(see below);
 template <class U = T> optional& operator=(U&&);
 template <class U> optional& operator=(const optional<U>&);
 template <class U> optional& operator=(optional<U>&&);
 template <class... Args> T& emplace(Args&&...);
 template <class U, class... Args> T& emplace(initializer_list<U>, Args&&...);

// 23.6.3.4, swap
 void swap(optional&) noexcept(see below);

```

```

// 23.6.3.5, observers
constexpr const T* operator->() const;
constexpr T* operator->();
constexpr const T& operator*() const&;
constexpr T& operator*() &;
constexpr T&& operator*() &&;
constexpr const T&& operator*() const&&;
constexpr explicit operator bool() const noexcept;
constexpr bool has_value() const noexcept;
constexpr const T& value() const&;
constexpr T& value() &;
constexpr T&& value() &&;
constexpr const T&& value() const&&;
template <class U> constexpr T value_or(U&&) const&;
template <class U> constexpr T value_or(U&&) &&;

// 23.6.3.6, modifiers
void reset() noexcept;

private:
 T *val; // exposition only
};

```

```
template<class T> optional(T) -> optional<T>;
```

- <sup>1</sup> Any instance of `optional<T>` at any given time either contains a value or does not contain a value. When an instance of `optional<T>` *contains a value*, it means that an object of type `T`, referred to as the optional object's *contained value*, is allocated within the storage of the optional object. Implementations are not permitted to use additional storage, such as dynamic memory, to allocate its contained value. The contained value shall be allocated in a region of the `optional<T>` storage suitably aligned for the type `T`. When an object of type `optional<T>` is contextually converted to `bool`, the conversion returns `true` if the object contains a value; otherwise the conversion returns `false`.
- <sup>2</sup> Member `val` is provided for exposition only. When an `optional<T>` object contains a value, `val` points to the contained value.
- <sup>3</sup> `T` shall be an object type and shall satisfy the requirements of `Destructible` (Table 27).

### 23.6.3.1 Constructors

[optional.ctor]

```
constexpr optional() noexcept;
constexpr optional(nullopt_t) noexcept;
```

- <sup>1</sup> *Postconditions:* `*this` does not contain a value.
  - <sup>2</sup> *Remarks:* No contained value is initialized. For every object type `T` these constructors shall be `constexpr` constructors (10.1.5).
- ```
constexpr optional(const optional& rhs);
```
- ³ *Effects:* If `rhs` contains a value, initializes the contained value as if direct-non-list-initializing an object of type `T` with the expression `*rhs`.
 - ⁴ *Postconditions:* `bool(rhs) == bool(*this)`.
 - ⁵ *Throws:* Any exception thrown by the selected constructor of `T`.
 - ⁶ *Remarks:* This constructor shall be defined as `deleted` unless `is_copy_constructible_v<T>` is `true`. If `is_trivially_copy_constructible_v<T>` is `true`, this constructor shall be a `constexpr` constructor.

```
constexpr optional(optional&& rhs) noexcept(see below);
```

7 *Effects:* If `rhs` contains a value, initializes the contained value as if direct-non-list-initializing an object of type `T` with the expression `std::move(*rhs)`. `bool(rhs)` is unchanged.

8 *Postconditions:* `bool(rhs) == bool(*this)`.

9 *Throws:* Any exception thrown by the selected constructor of `T`.

10 *Remarks:* The expression inside `noexcept` is equivalent to `is_nothrow_move_constructible_v<T>`. This constructor shall not participate in overload resolution unless `is_move_constructible_v<T>` is `true`. If `is_trivially_move_constructible_v<T>` is `true`, this constructor shall be a `constexpr` constructor.

```
template <class... Args> constexpr explicit optional(in_place_t, Args&&... args);
```

11 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type `T` with the arguments `std::forward<Args>(args)...`

12 *Postconditions:* `*this` contains a value.

13 *Throws:* Any exception thrown by the selected constructor of `T`.

14 *Remarks:* If `T`'s constructor selected for the initialization is a `constexpr` constructor, this constructor shall be a `constexpr` constructor. This constructor shall not participate in overload resolution unless `is_constructible_v<T, Args...>` is `true`.

```
template <class U, class... Args>
constexpr explicit optional(in_place_t, initializer_list<U> il, Args&&... args);
```

15 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type `T` with the arguments `il, std::forward<Args>(args)...`

16 *Postconditions:* `*this` contains a value.

17 *Throws:* Any exception thrown by the selected constructor of `T`.

18 *Remarks:* This constructor shall not participate in overload resolution unless `is_constructible_v<T, initializer_list<U>&, Args&&...>` is `true`. If `T`'s constructor selected for the initialization is a `constexpr` constructor, this constructor shall be a `constexpr` constructor.

19 [*Note:* The following constructors are conditionally specified as explicit. This is typically implemented by declaring two such constructors, of which at most one participates in overload resolution. — *end note*]

```
template <class U = T> EXPLICIT constexpr optional(U&& v);
```

20 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type `T` with the expression `std::forward<U>(v)`.

21 *Postconditions:* `*this` contains a value.

22 *Throws:* Any exception thrown by the selected constructor of `T`.

23 *Remarks:* If `T`'s selected constructor is a `constexpr` constructor, this constructor shall be a `constexpr` constructor. This constructor shall not participate in overload resolution unless `is_constructible_v<T, U&&>` is `true`, `is_same_v<decay_t<U>, in_place_t>` is `false`, and `is_same_v<optional<T>, decay_t<U>>` is `false`. The constructor is explicit if and only if `is_convertible_v<U&&, T>` is `false`.

```
template <class U> EXPLICIT optional(const optional<U>& rhs);
```

24 *Effects:* If `rhs` contains a value, initializes the contained value as if direct-non-list-initializing an object of type `T` with the expression `*rhs`.

25 *Postconditions:* `bool(rhs) == bool(*this)`.

26 *Throws:* Any exception thrown by the selected constructor of T.

27 *Remarks:* This constructor shall not participate in overload resolution unless

- (27.1) — `is_constructible_v<T, const U&>` is true,
- (27.2) — `is_constructible_v<T, optional<U>&>` is false,
- (27.3) — `is_constructible_v<T, optional<U>&&>` is false,
- (27.4) — `is_constructible_v<T, const optional<U>&>` is false,
- (27.5) — `is_constructible_v<T, const optional<U>&&>` is false,
- (27.6) — `is_convertible_v<optional<U>&, T>` is false,
- (27.7) — `is_convertible_v<optional<U>&&, T>` is false,
- (27.8) — `is_convertible_v<const optional<U>&, T>` is false, and
- (27.9) — `is_convertible_v<const optional<U>&&, T>` is false.

The constructor is explicit if and only if `is_convertible_v<const U&, T>` is false.

```
template <class U> EXPLICIT optional(optional<U>&& rhs);
```

28 *Effects:* If `rhs` contains a value, initializes the contained value as if direct-non-list-initializing an object of type T with the expression `std::move(*rhs)`. `bool(rhs)` is unchanged.

29 *Postconditions:* `bool(rhs) == bool(*this)`.

30 *Throws:* Any exception thrown by the selected constructor of T.

31 *Remarks:* This constructor shall not participate in overload resolution unless

- (31.1) — `is_constructible_v<T, U&&>` is true,
- (31.2) — `is_constructible_v<T, optional<U>&>` is false,
- (31.3) — `is_constructible_v<T, optional<U>&&>` is false,
- (31.4) — `is_constructible_v<T, const optional<U>&>` is false,
- (31.5) — `is_constructible_v<T, const optional<U>&&>` is false,
- (31.6) — `is_convertible_v<optional<U>&, T>` is false,
- (31.7) — `is_convertible_v<optional<U>&&, T>` is false,
- (31.8) — `is_convertible_v<const optional<U>&, T>` is false, and
- (31.9) — `is_convertible_v<const optional<U>&&, T>` is false.

The constructor is explicit if and only if `is_convertible_v<U&&, T>` is false.

23.6.3.2 Destructor

[optional.dtor]

```
~optional();
```

1 *Effects:* If `is_trivially_destructible_v<T> != true` and `*this` contains a value, calls
`val->T::~~T()`

2 *Remarks:* If `is_trivially_destructible_v<T> == true` then this destructor shall be a trivial destructor.

23.6.3.3 Assignment

[optional.assign]

```
optional<T>& operator=(nullopt_t) noexcept;
```

1 *Effects:* If `*this` contains a value, calls `val->T::~~T()` to destroy the contained value; otherwise no effect.

2 *Returns:* `*this`.

3 *Postconditions:* `*this` does not contain a value.

`optional<T>& operator=(const optional& rhs);`

4 *Effects:* See Table 35.

Table 35 — `optional::operator=(const optional&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	assigns <code>*rhs</code> to the contained value	initializes the contained value as if direct-non-list-initializing an object of type T with <code>*rhs</code>
rhs does not contain a value	destroys the contained value by calling <code>val->T::~~T()</code>	no effect

5 *Returns:* `*this`.

6 *Postconditions:* `bool(rhs) == bool(*this)`.

7 *Remarks:* If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's copy constructor, no effect. If an exception is thrown during the call to T's copy assignment, the state of its contained value is as defined by the exception safety guarantee of T's copy assignment. This operator shall be defined as deleted unless `is_copy_constructible_v<T>` is true and `is_copy_assignable_v<T>` is true.

`optional<T>& operator=(optional&& rhs) noexcept(see below);`

8 *Effects:* See Table 36. The result of the expression `bool(rhs)` remains unchanged.

Table 36 — `optional::operator=(optional&&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	assigns <code>std::move(*rhs)</code> to the contained value	initializes the contained value as if direct-non-list-initializing an object of type T with <code>std::move(*rhs)</code>
rhs does not contain a value	destroys the contained value by calling <code>val->T::~~T()</code>	no effect

9 *Returns:* `*this`.

10 *Postconditions:* `bool(rhs) == bool(*this)`.

11 *Remarks:* The expression inside `noexcept` is equivalent to:

`is_nothrow_move_assignable_v<T> && is_nothrow_move_constructible_v<T>`

12 If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's move constructor, the state of `*rhs.val` is determined

by the exception safety guarantee of T's move constructor. If an exception is thrown during the call to T's move assignment, the state of **val* and **rhs.val* is determined by the exception safety guarantee of T's move assignment. This operator shall not participate in overload resolution unless `is_move_constructible_v<T>` is true and `is_move_assignable_v<T>` is true.

```
template <class U = T> optional<T>& operator=(U&& v);
```

13 *Effects:* If **this* contains a value, assigns `std::forward<U>(v)` to the contained value; otherwise initializes the contained value as if direct-non-list-initializing object of type T with `std::forward<U>(v)`.

14 *Returns:* **this*.

15 *Postconditions:* **this* contains a value.

16 *Remarks:* If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's constructor, the state of *v* is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of **val* and *v* is determined by the exception safety guarantee of T's assignment. This function shall not participate in overload resolution unless `is_same_v<optional<T>, decay_t<U>>` is false, `conjunction_v<is_scalar<T>, is_same<T, decay_t<U>>>` is false, `is_constructible_v<T, U>` is true, and `is_assignable_v<T&, U>` is true.

```
template <class U> optional<T>& operator=(const optional<U>& rhs);
```

17 *Effects:* See Table 37.

Table 37 — `optional::operator=(const optional<U>&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	assigns <i>*rhs</i> to the contained value	initializes the contained value as if direct-non-list-initializing an object of type T with <i>*rhs</i>
rhs does not contain a value	destroys the contained value by calling <code>val->T::~~T()</code>	no effect

18 *Returns:* **this*.

19 *Postconditions:* `bool(rhs) == bool(*this)`.

20 *Remarks:* If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's constructor, the state of **rhs.val* is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of **val* and **rhs.val* is determined by the exception safety guarantee of T's assignment. This function shall not participate in overload resolution unless

- (20.1) — `is_constructible_v<T, const U&>` is true,
- (20.2) — `is_assignable_v<T&, const U&>` is true,
- (20.3) — `is_constructible_v<T, optional<U>&>` is false,
- (20.4) — `is_constructible_v<T, optional<U>&&>` is false,
- (20.5) — `is_constructible_v<T, const optional<U>&>` is false,
- (20.6) — `is_constructible_v<T, const optional<U>&&>` is false,
- (20.7) — `is_convertible_v<optional<U>&, T>` is false,

- (20.8) — `is_convertible_v<optional<U>&&, T>` is false,
- (20.9) — `is_convertible_v<const optional<U>&, T>` is false,
- (20.10) — `is_convertible_v<const optional<U>&&, T>` is false,
- (20.11) — `is_assignable_v<T&, optional<U>&>` is false,
- (20.12) — `is_assignable_v<T&, optional<U>&&>` is false,
- (20.13) — `is_assignable_v<T&, const optional<U>&>` is false, and
- (20.14) — `is_assignable_v<T&, const optional<U>&&>` is false.

template <class U> optional<T>& operator=(optional<U>&& rhs);

21 *Effects:* See Table 38. The result of the expression `bool(rhs)` remains unchanged.

Table 38 — `optional::operator=(optional<U>&&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	assigns <code>std::move(*rhs)</code> to the contained value	initializes the contained value as if direct-non-list-initializing an object of type T with <code>std::move(*rhs)</code>
rhs does not contain a value	destroys the contained value by calling <code>val->T::~~T()</code>	no effect

22 *Returns:* `*this`.

23 *Postconditions:* `bool(rhs) == bool(*this)`.

24 *Remarks:* If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's constructor, the state of `*rhs.val` is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of T's assignment. This function shall not participate in overload resolution unless

- (24.1) — `is_constructible_v<T, U>` is true,
- (24.2) — `is_assignable_v<T&, U>` is true,
- (24.3) — `is_constructible_v<T, optional<U>&>` is false,
- (24.4) — `is_constructible_v<T, optional<U>&&>` is false,
- (24.5) — `is_constructible_v<T, const optional<U>&>` is false,
- (24.6) — `is_constructible_v<T, const optional<U>&&>` is false,
- (24.7) — `is_convertible_v<optional<U>&, T>` is false,
- (24.8) — `is_convertible_v<optional<U>&&, T>` is false,
- (24.9) — `is_convertible_v<const optional<U>&, T>` is false,
- (24.10) — `is_convertible_v<const optional<U>&&, T>` is false,
- (24.11) — `is_assignable_v<T&, optional<U>&>` is false,
- (24.12) — `is_assignable_v<T&, optional<U>&&>` is false,
- (24.13) — `is_assignable_v<T&, const optional<U>&>` is false, and

(24.14) — `is_assignable_v<T&, const optional<U>&&>` is false.

```
template <class... Args> T& emplace(Args&&... args);
```

25 *Requires:* `is_constructible_v<T, Args&&...>` is true.

26 *Effects:* Calls `*this = nullopt`. Then initializes the contained value as if direct-non-list-initializing an object of type `T` with the arguments `std::forward<Args>(args)...`

27 *Postconditions:* `*this` contains a value.

28 *Returns:* A reference to the new contained value.

29 *Throws:* Any exception thrown by the selected constructor of `T`.

30 *Remarks:* If an exception is thrown during the call to `T`'s constructor, `*this` does not contain a value, and the previous `*val` (if any) has been destroyed.

```
template <class U, class... Args> T& emplace(initializer_list<U> il, Args&&... args);
```

31 *Effects:* Calls `*this = nullopt`. Then initializes the contained value as if direct-non-list-initializing an object of type `T` with the arguments `il, std::forward<Args>(args)...`

32 *Postconditions:* `*this` contains a value.

33 *Returns:* A reference to the new contained value.

34 *Throws:* Any exception thrown by the selected constructor of `T`.

35 *Remarks:* If an exception is thrown during the call to `T`'s constructor, `*this` does not contain a value, and the previous `*val` (if any) has been destroyed. This function shall not participate in overload resolution unless `is_constructible_v<T, initializer_list<U>&, Args&&...>` is true.

23.6.3.4 Swap

[optional.swap]

```
void swap(optional& rhs) noexcept(see below);
```

1 *Requires:* Lvalues of type `T` shall be swappable and `is_move_constructible_v<T>` is true.

2 *Effects:* See Table 39.

3 *Throws:* Any exceptions thrown by the operations in the relevant part of Table 39.

4 *Remarks:* The expression inside `noexcept` is equivalent to:

```
is_nothrow_move_constructible_v<T> && is_nothrow_swappable_v<T>
```

If any exception is thrown, the results of the expressions `bool(*this)` and `bool(rhs)` remain unchanged. If an exception is thrown during the call to function `swap`, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of `swap` for lvalues of `T`. If an exception is thrown during the call to `T`'s move constructor, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of `T`'s move constructor.

23.6.3.5 Observers

[optional.observe]

```
constexpr const T* operator->() const;
constexpr T* operator->();
```

1 *Requires:* `*this` contains a value.

2 *Returns:* `val`.

3 *Throws:* Nothing.

4 *Remarks:* These functions shall be `constexpr` functions.

```
constexpr const T& operator*() const&;
```

Table 39 — `optional::swap(optional&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	calls <code>swap>(*this, rhs)</code>	initializes the contained value of <code>*this</code> as if direct-non-list-initializing an object of type <code>T</code> with the expression <code>std::move(rhs)</code> , followed by <code>rhs.val->T::~~T()</code> ; postcondition is that <code>*this</code> contains a value and <code>rhs</code> does not contain a value
rhs does not contain a value	initializes the contained value of <code>rhs</code> as if direct-non-list-initializing an object of type <code>T</code> with the expression <code>std::move(*this)</code> , followed by <code>val->T::~~T()</code> ; postcondition is that <code>*this</code> does not contain a value and <code>rhs</code> contains a value	no effect

```
constexpr T& operator*() &;
```

5 *Requires:* `*this` contains a value.

6 *Returns:* `*val`.

7 *Throws:* Nothing.

8 *Remarks:* These functions shall be constexpr functions.

```
constexpr T&& operator*() &&;
```

```
constexpr const T&& operator*() const&&;
```

9 *Requires:* `*this` contains a value.

10 *Effects:* Equivalent to: `return std::move(*val);`

```
constexpr explicit operator bool() const noexcept;
```

11 *Returns:* `true` if and only if `*this` contains a value.

12 *Remarks:* This function shall be a constexpr function.

```
constexpr bool has_value() const noexcept;
```

13 *Returns:* `true` if and only if `*this` contains a value.

14 *Remarks:* This function shall be a constexpr function.

```
constexpr const T& value() const&;
```

```
constexpr T& value() &;
```

15 *Effects:* Equivalent to:

```
return bool(*this) ? *val : throw bad_optional_access();
```

```
constexpr T&& value() &&;
constexpr const T&& value() const&&;
```

16 *Effects:* Equivalent to:

```
return bool(*this) ? std::move(*val) : throw bad_optional_access();
```

```
template <class U> constexpr T value_or(U&& v) const&&;
```

17 *Effects:* Equivalent to:

```
return bool(*this) ? **this : static_cast<T>(std::forward<U>(v));
```

18 *Remarks:* If `is_copy_constructible_v<T>` && `is_convertible_v<U&&, T>` is false, the program is ill-formed.

```
template <class U> constexpr T value_or(U&& v) &&;
```

19 *Effects:* Equivalent to:

```
return bool(*this) ? std::move(**this) : static_cast<T>(std::forward<U>(v));
```

20 *Remarks:* If `is_move_constructible_v<T>` && `is_convertible_v<U&&, T>` is false, the program is ill-formed.

23.6.3.6 Modifiers

[optional.mod]

```
void reset() noexcept;
```

1 *Effects:* If `*this` contains a value, calls `val->T::~~T()` to destroy the contained value; otherwise no effect.

2 *Postconditions:* `*this` does not contain a value.

23.6.4 No-value state indicator

[optional.nullopt]

```
struct nullopt_t{see below};
inline constexpr nullopt_t nullopt(unspecified);
```

1 The struct `nullopt_t` is an empty structure type used as a unique type to indicate the state of not containing a value for `optional` objects. In particular, `optional<T>` has a constructor with `nullopt_t` as a single argument; this indicates that an optional object not containing a value shall be constructed.

2 Type `nullopt_t` shall not have a default constructor or an initializer-list constructor, and shall not be an aggregate.

23.6.5 Class `bad_optional_access`

[optional.bad.access]

```
class bad_optional_access : public exception {
public:
    bad_optional_access();
};
```

1 The class `bad_optional_access` defines the type of objects thrown as exceptions to report the situation where an attempt is made to access the value of an optional object that does not contain a value.

```
bad_optional_access();
```

2 *Effects:* Constructs an object of class `bad_optional_access`.

3 *Postconditions:* `what()` returns an implementation-defined NTBS.

23.6.6 Relational operators

[optional.relops]

```
template <class T, class U> constexpr bool operator==(const optional<T>& x, const optional<U>& y);
```

Requires: The expression `*x == *y` shall be well-formed and its result shall be convertible to `bool`.
 [*Note:* `T` need not be `EqualityComparable`. — *end note*]

Returns: If `bool(x) != bool(y)`, `false`; otherwise if `bool(x) == false`, `true`; otherwise `*x == *y`.

Remarks: Specializations of this function template for which `*x == *y` is a core constant expression shall be `constexpr` functions.

```
template <class T, class U> constexpr bool operator!=(const optional<T>& x, const optional<U>& y);
```

Requires: The expression `*x != *y` shall be well-formed and its result shall be convertible to `bool`.

Returns: If `bool(x) != bool(y)`, `true`; otherwise, if `bool(x) == false`, `false`; otherwise `*x != *y`.

Remarks: Specializations of this function template for which `*x != *y` is a core constant expression shall be `constexpr` functions.

```
template <class T, class U> constexpr bool operator<(const optional<T>& x, const optional<U>& y);
```

Requires: `*x < *y` shall be well-formed and its result shall be convertible to `bool`.

Returns: If `!y`, `false`; otherwise, if `!x`, `true`; otherwise `*x < *y`.

Remarks: Specializations of this function template for which `*x < *y` is a core constant expression shall be `constexpr` functions.

```
template <class T, class U> constexpr bool operator>(const optional<T>& x, const optional<U>& y);
```

Requires: The expression `*x > *y` shall be well-formed and its result shall be convertible to `bool`.

Returns: If `!x`, `false`; otherwise, if `!y`, `true`; otherwise `*x > *y`.

Remarks: Specializations of this function template for which `*x > *y` is a core constant expression shall be `constexpr` functions.

```
template <class T, class U> constexpr bool operator<=(const optional<T>& x, const optional<U>& y);
```

Requires: The expression `*x <= *y` shall be well-formed and its result shall be convertible to `bool`.

Returns: If `!x`, `true`; otherwise, if `!y`, `false`; otherwise `*x <= *y`.

Remarks: Specializations of this function template for which `*x <= *y` is a core constant expression shall be `constexpr` functions.

```
template <class T, class U> constexpr bool operator>=(const optional<T>& x, const optional<U>& y);
```

Requires: The expression `*x >= *y` shall be well-formed and its result shall be convertible to `bool`.

Returns: If `!y`, `true`; otherwise, if `!x`, `false`; otherwise `*x >= *y`.

Remarks: Specializations of this function template for which `*x >= *y` is a core constant expression shall be `constexpr` functions.

23.6.7 Comparison with nullopt

[optional.nullopts]

```
template <class T> constexpr bool operator==(const optional<T>& x, nullopt_t) noexcept;
```

```
template <class T> constexpr bool operator==(nullopt_t, const optional<T>& x) noexcept;
```

Returns: `!x`.

```
template <class T> constexpr bool operator!=(const optional<T>& x, nullopt_t) noexcept;
```

```
template <class T> constexpr bool operator!=(nullopt_t, const optional<T>& x) noexcept;
```

Returns: `bool(x)`.

```
template <class T> constexpr bool operator<(const optional<T>& x, nullopt_t) noexcept;
```

Returns: false.

```
template <class T> constexpr bool operator<(nullopt_t, const optional<T>& x) noexcept;
```

Returns: bool(x).

```
template <class T> constexpr bool operator<=(const optional<T>& x, nullopt_t) noexcept;
```

Returns: !x.

```
template <class T> constexpr bool operator<=(nullopt_t, const optional<T>& x) noexcept;
```

Returns: true.

```
template <class T> constexpr bool operator>(const optional<T>& x, nullopt_t) noexcept;
```

Returns: bool(x).

```
template <class T> constexpr bool operator>(nullopt_t, const optional<T>& x) noexcept;
```

Returns: false.

```
template <class T> constexpr bool operator>=(const optional<T>& x, nullopt_t) noexcept;
```

Returns: true.

```
template <class T> constexpr bool operator>=(nullopt_t, const optional<T>& x) noexcept;
```

Returns: !x.

23.6.8 Comparison with T

[optional.comp_with_t]

```
template <class T, class U> constexpr bool operator==(const optional<T>& x, const U& v);
```

Requires: The expression `*x == v` shall be well-formed and its result shall be convertible to `bool`.
[Note: T need not be EqualityComparable. — end note]

Effects: Equivalent to: `return bool(x) ? *x == v : false;`

```
template <class T, class U> constexpr bool operator==(const U& v, const optional<T>& x);
```

Requires: The expression `v == *x` shall be well-formed and its result shall be convertible to `bool`.

Effects: Equivalent to: `return bool(x) ? v == *x : false;`

```
template <class T, class U> constexpr bool operator!=(const optional<T>& x, const U& v);
```

Requires: The expression `*x != v` shall be well-formed and its result shall be convertible to `bool`.

Effects: Equivalent to: `return bool(x) ? *x != v : true;`

```
template <class T, class U> constexpr bool operator!=(const U& v, const optional<T>& x);
```

Requires: The expression `v != *x` shall be well-formed and its result shall be convertible to `bool`.

Effects: Equivalent to: `return bool(x) ? v != *x : true;`

```
template <class T, class U> constexpr bool operator<(const optional<T>& x, const U& v);
```

Requires: The expression `*x < v` shall be well-formed and its result shall be convertible to `bool`.

Effects: Equivalent to: `return bool(x) ? *x < v : true;`

```
template <class T, class U> constexpr bool operator<(const U& v, const optional<T>& x);
```

Requires: The expression `v < *x` shall be well-formed and its result shall be convertible to `bool`.

Effects: Equivalent to: `return bool(x) ? v < *x : false;`

```
template <class T, class U> constexpr bool operator<=(const optional<T>& x, const U& v);
```

13 *Requires:* The expression `*x <= v` shall be well-formed and its result shall be convertible to `bool`.

14 *Effects:* Equivalent to: `return bool(x) ? *x <= v : true;`

```
template <class T, class U> constexpr bool operator<=(const U& v, const optional<T>& x);
```

15 *Requires:* The expression `v <= *x` shall be well-formed and its result shall be convertible to `bool`.

16 *Effects:* Equivalent to: `return bool(x) ? v <= *x : false;`

```
template <class T, class U> constexpr bool operator>(const optional<T>& x, const U& v);
```

17 *Requires:* The expression `*x > v` shall be well-formed and its result shall be convertible to `bool`.

18 *Effects:* Equivalent to: `return bool(x) ? *x > v : false;`

```
template <class T, class U> constexpr bool operator>(const U& v, const optional<T>& x);
```

19 *Requires:* The expression `v > *x` shall be well-formed and its result shall be convertible to `bool`.

20 *Effects:* Equivalent to: `return bool(x) ? v > *x : true;`

```
template <class T, class U> constexpr bool operator>=(const optional<T>& x, const U& v);
```

21 *Requires:* The expression `*x >= v` shall be well-formed and its result shall be convertible to `bool`.

22 *Effects:* Equivalent to: `return bool(x) ? *x >= v : false;`

```
template <class T, class U> constexpr bool operator>=(const U& v, const optional<T>& x);
```

23 *Requires:* The expression `v >= *x` shall be well-formed and its result shall be convertible to `bool`.

24 *Effects:* Equivalent to: `return bool(x) ? v >= *x : true;`

23.6.9 Specialized algorithms

[optional.specalg]

```
template <class T> void swap(optional<T>& x, optional<T>& y) noexcept(noexcept(x.swap(y)));
```

1 *Effects:* Calls `x.swap(y)`.

2 *Remarks:* This function shall not participate in overload resolution unless `is_move_constructible_v<T>` is true and `is_swappable_v<T>` is true.

```
template <class T> constexpr optional<decay_t<T>> make_optional(T&& v);
```

3 *Returns:* `optional<decay_t<T>>(std::forward<T>(v))`.

```
template <class T, class... Args>
constexpr optional<T> make_optional(Args&&... args);
```

4 *Effects:* Equivalent to: `return optional<T>(in_place, std::forward<Args>(args)...);`

```
template <class T, class U, class... Args>
constexpr optional<T> make_optional(initializer_list<U> il, Args&&... args);
```

5 *Effects:* Equivalent to: `return optional<T>(in_place, il, std::forward<Args>(args)...);`

23.6.10 Hash support

[optional.hash]

```
template <class T> struct hash<optional<T>>;
```

1 The specialization `hash<optional<T>>` is enabled (23.14.15) if and only if `hash<remove_const_t<T>>` is enabled. When enabled, for an object `o` of type `optional<T>`, if `bool(o) == true`, then `hash<optional<T>>()(o)` shall evaluate to the same value as `hash<remove_const_t<T>>()(*o)`; oth-

erwise it evaluates to an unspecified value. The member functions are not guaranteed to be `noexcept`.

23.7 Variants [variant]

23.7.1 In general [variant.general]

- ¹ A variant object holds and manages the lifetime of a value. If the `variant` holds a value, that value's type has to be one of the template argument types given to `variant`. These template arguments are called alternatives.

23.7.2 Header `<variant>` synopsis [variant.syn]

```
namespace std {
    // 23.7.3, class template variant
    template <class... Types>
        class variant;

    // 23.7.4, variant helper classes
    template <class T> struct variant_size; // not defined
    template <class T> struct variant_size<const T>;
    template <class T> struct variant_size<volatile T>;
    template <class T> struct variant_size<const volatile T>;
    template <class T>
        inline constexpr size_t variant_size_v = variant_size<T>::value;

    template <class... Types>
        struct variant_size<variant<Types...>>;

    template <size_t I, class T> struct variant_alternative; // not defined
    template <size_t I, class T> struct variant_alternative<I, const T>;
    template <size_t I, class T> struct variant_alternative<I, volatile T>;
    template <size_t I, class T> struct variant_alternative<I, const volatile T>;
    template <size_t I, class T>
        using variant_alternative_t = typename variant_alternative<I, T>::type;

    template <size_t I, class... Types>
        struct variant_alternative<I, variant<Types...>>;

    inline constexpr size_t variant_npos = -1;

    // 23.7.5, value access
    template <class T, class... Types>
        constexpr bool holds_alternative(const variant<Types...>&) noexcept;

    template <size_t I, class... Types>
        constexpr variant_alternative_t<I, variant<Types...>>& get(variant<Types...>&);
    template <size_t I, class... Types>
        constexpr variant_alternative_t<I, variant<Types...>>&& get(variant<Types...>&&);
    template <size_t I, class... Types>
        constexpr const variant_alternative_t<I, variant<Types...>>& get(const variant<Types...>&);
    template <size_t I, class... Types>
        constexpr const variant_alternative_t<I, variant<Types...>>&& get(const variant<Types...>&&);

    template <class T, class... Types>
        constexpr T& get(variant<Types...>&);
    template <class T, class... Types>
        constexpr T&& get(variant<Types...>&&);
    template <class T, class... Types>
```



```

    constexpr const T& get(const variant<Types...>&);
template <class T, class... Types>
    constexpr const T&& get(const variant<Types...>&&);

template <size_t I, class... Types>
    constexpr add_pointer_t<variant_alternative_t<I, variant<Types...>>>
        get_if(variant<Types...>*) noexcept;
template <size_t I, class... Types>
    constexpr add_pointer_t<const variant_alternative_t<I, variant<Types...>>>
        get_if(const variant<Types...>*) noexcept;

template <class T, class... Types>
    constexpr add_pointer_t<T>
        get_if(variant<Types...>*) noexcept;
template <class T, class... Types>
    constexpr add_pointer_t<const T>
        get_if(const variant<Types...>*) noexcept;

// 23.7.6, relational operators
template <class... Types>
    constexpr bool operator==(const variant<Types...>&, const variant<Types...>&);
template <class... Types>
    constexpr bool operator!=(const variant<Types...>&, const variant<Types...>&);
template <class... Types>
    constexpr bool operator<(const variant<Types...>&, const variant<Types...>&);
template <class... Types>
    constexpr bool operator>(const variant<Types...>&, const variant<Types...>&);
template <class... Types>
    constexpr bool operator<=(const variant<Types...>&, const variant<Types...>&);
template <class... Types>
    constexpr bool operator>=(const variant<Types...>&, const variant<Types...>&);

// 23.7.7, visitation
template <class Visitor, class... Variants>
    constexpr see below visit(Visitor&&, Variants&&...);

// 23.7.8, class monostate
struct monostate;

// 23.7.9, monostate relational operators
constexpr bool operator<(monostate, monostate) noexcept;
constexpr bool operator>(monostate, monostate) noexcept;
constexpr bool operator<=(monostate, monostate) noexcept;
constexpr bool operator>=(monostate, monostate) noexcept;
constexpr bool operator==(monostate, monostate) noexcept;
constexpr bool operator!=(monostate, monostate) noexcept;

// 23.7.10, specialized algorithms
template <class... Types>
    void swap(variant<Types...>&, variant<Types...>&) noexcept(see below);

// 23.7.11, class bad_variant_access
class bad_variant_access;

// 23.7.12, hash support

```

```

template <class T> struct hash;
template <class... Types> struct hash<variant<Types...>>;
template <> struct hash<monostate>;

// 23.7.13, allocator-related traits
template <class T, class Alloc> struct uses_allocator;
template <class... Types, class Alloc> struct uses_allocator<variant<Types...>, Alloc>;
}

```

23.7.3 Class template variant

[variant.variant]

```

namespace std {
    template <class... Types>
        class variant {
        public:
            // 23.7.3.1, constructors
            constexpr variant() noexcept(see below);
            variant(const variant&);
            variant(variant&&) noexcept(see below);

            template <class T>
                constexpr variant(T&&) noexcept(see below);

            template <class T, class... Args>
                constexpr explicit variant(in_place_type_t<T>, Args&&...);
            template <class T, class U, class... Args>
                constexpr explicit variant(in_place_type_t<T>, initializer_list<U>, Args&&...);

            template <size_t I, class... Args>
                constexpr explicit variant(in_place_index_t<I>, Args&&...);
            template <size_t I, class U, class... Args>
                constexpr explicit variant(in_place_index_t<I>, initializer_list<U>, Args&&...);

            // allocator-extended constructors
            template <class Alloc>
                variant(allocator_arg_t, const Alloc&);
            template <class Alloc>
                variant(allocator_arg_t, const Alloc&, const variant&);
            template <class Alloc>
                variant(allocator_arg_t, const Alloc&, variant&&);
            template <class Alloc, class T>
                variant(allocator_arg_t, const Alloc&, T&&);
            template <class Alloc, class T, class... Args>
                variant(allocator_arg_t, const Alloc&, in_place_type_t<T>, Args&&...);
            template <class Alloc, class T, class U, class... Args>
                variant(allocator_arg_t, const Alloc&, in_place_type_t<T>,
                    initializer_list<U>, Args&&...);
            template <class Alloc, size_t I, class... Args>
                variant(allocator_arg_t, const Alloc&, in_place_index_t<I>, Args&&...);
            template <class Alloc, size_t I, class U, class... Args>
                variant(allocator_arg_t, const Alloc&, in_place_index_t<I>,
                    initializer_list<U>, Args&&...);

            // 23.7.3.2, destructor
            ~variant();
        };
}

```

```

// 23.7.3.3, assignment
variant& operator=(const variant&);
variant& operator=(variant&&) noexcept(see below);

template <class T> variant& operator=(T&&) noexcept(see below);

// 23.7.3.4, modifiers
template <class T, class... Args>
    T& emplace(Args&&...);
template <class T, class U, class... Args>
    T& emplace(initializer_list<U>, Args&&...);
template <size_t I, class... Args>
    variant_alternative_t<I, variant<Types...>& emplace(Args&&...);
template <size_t I, class U, class... Args>
    variant_alternative_t<I, variant<Types...>& emplace(initializer_list<U>, Args&&...);

// 23.7.3.5, value status
constexpr bool valueless_by_exception() const noexcept;
constexpr size_t index() const noexcept;

// 23.7.3.6, swap
void swap(variant&&) noexcept(see below);
};
}

```

- 1 Any instance of **variant** at any given time either holds a value of one of its alternative types, or it holds no value. When an instance of **variant** holds a value of alternative type **T**, it means that a value of type **T**, referred to as the **variant** object's *contained value*, is allocated within the storage of the **variant** object. Implementations are not permitted to use additional storage, such as dynamic memory, to allocate the contained value. The contained value shall be allocated in a region of the **variant** storage suitably aligned for all types in **Types...** It is implementation-defined whether over-aligned types are supported.
- 2 All types in **Types...** shall be (possibly cv-qualified) object types that are not arrays.
- 3 A program that instantiates the definition of **variant** with no template arguments is ill-formed.

23.7.3.1 Constructors

[variant.ctor]

- 1 In the descriptions that follow, let i be in the range $[0, \text{sizeof}...(Types))$, and T_i be the i^{th} type in **Types...**

```
constexpr variant() noexcept(see below);
```

- 2 *Effects:* Constructs a **variant** holding a value-initialized value of type T_0 .
- 3 *Postconditions:* `valueless_by_exception()` is false and `index()` is 0.
- 4 *Throws:* Any exception thrown by the value-initialization of T_0 .
- 5 *Remarks:* This function shall be `constexpr` if and only if the value-initialization of the alternative type T_0 would satisfy the requirements for a `constexpr` function. The expression inside `noexcept` is equivalent to `is_nothrow_default_constructible_v<T0>`. This function shall not participate in overload resolution unless `is_default_constructible_v<T0>` is true. [Note: See also class `monostate`. — end note]

```
variant(const variant& w);
```

- 6 *Effects:* If **w** holds a value, initializes the **variant** to hold the same alternative as **w** and direct-initializes the contained value with `get<j>(w)`, where j is `w.index()`. Otherwise, initializes the **variant** to not hold a value.

- 7 *Throws:* Any exception thrown by direct-initializing any T_i for all i .
- 8 *Remarks:* This function shall not participate in overload resolution unless `is_copy_constructible_v< $T_i$ >` is true for all i .

```
variant(variant&& w) noexcept(see below);
```

- 9 *Effects:* If w holds a value, initializes the `variant` to hold the same alternative as w and direct-initializes the contained value with `get< $j$ >(std::move(w))`, where j is `w.index()`. Otherwise, initializes the `variant` to not hold a value.
- 10 *Throws:* Any exception thrown by move-constructing any T_i for all i .
- 11 *Remarks:* The expression inside `noexcept` is equivalent to the logical AND of `is_nothrow_move_constructible_v< $T_i$ >` for all i . This function shall not participate in overload resolution unless `is_move_constructible_v< $T_i$ >` is true for all i .

```
template <class T> constexpr variant(T&& t) noexcept(see below);
```

- 12 Let T_j be a type that is determined as follows: build an imaginary function $FUN(T_i)$ for each alternative type T_i . The overload $FUN(T_j)$ selected by overload resolution for the expression $FUN(std::forward<T>(t))$ defines the alternative T_j which is the type of the contained value after construction.
- 13 *Effects:* Initializes `*this` to hold the alternative type T_j and direct-initializes the contained value as if direct-non-list-initializing it with `std::forward<T>(t)`.
- 14 *Postconditions:* `holds_alternative< $T_j$ >(*this)` is true.
- 15 *Throws:* Any exception thrown by the initialization of the selected alternative T_j .
- 16 *Remarks:* This function shall not participate in overload resolution unless `is_same_v<decay_t<T>, variant>` is false, unless `decay_t<T>` is neither a specialization of `in_place_type_t` nor a specialization of `in_place_index_t`, unless `is_constructible_v< $T_j$ , T>` is true, and unless the expression $FUN(std::forward<T>(t))$ (with FUN being the above-mentioned set of imaginary functions) is well formed.
- 17 [*Note:*

```
variant<string, string> v("abc");
```

is ill-formed, as both alternative types have an equally viable constructor for the argument. — *end note*]
- 18 The expression inside `noexcept` is equivalent to `is_nothrow_constructible_v< $T_j$ , T>`. If T_j 's selected constructor is a constexpr constructor, this constructor shall be a constexpr constructor.

```
template <class T, class... Args> constexpr explicit variant(in_place_type_t<T>, Args&&... args);
```

- 19 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type T with the arguments `std::forward<Args>(args)...`.
- 20 *Postconditions:* `holds_alternative<T>(*this)` is true.
- 21 *Throws:* Any exception thrown by calling the selected constructor of T .
- 22 *Remarks:* This function shall not participate in overload resolution unless there is exactly one occurrence of T in `Types...` and `is_constructible_v<T, Args...>` is true. If T 's selected constructor is a constexpr constructor, this constructor shall be a constexpr constructor.

```
template <class T, class U, class... Args>
constexpr explicit variant(in_place_type_t<T>, initializer_list<U> il, Args&&... args);
```

- 23 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type T with the arguments `il, std::forward<Args>(args)...`.

24 *Postconditions:* holds_alternative<T>(*this) is true.

25 *Throws:* Any exception thrown by calling the selected constructor of T.

26 *Remarks:* This function shall not participate in overload resolution unless there is exactly one occurrence of T in Types... and is_constructible_v<T, initializer_list<U>&, Args...> is true. If T's selected constructor is a constexpr constructor, this constructor shall be a constexpr constructor.

```
template <size_t I, class... Args> constexpr explicit variant(in_place_index_t<I>, Args&&... args);
```

27 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type T_I with the arguments `std::forward<Args>(args)...`

28 *Postconditions:* index() is I.

29 *Throws:* Any exception thrown by calling the selected constructor of T_I .

30 *Remarks:* This function shall not participate in overload resolution unless

(30.1) — I is less than sizeof...(Types) and

(30.2) — is_constructible_v< T_I , Args...> is true.

If T_I 's selected constructor is a constexpr constructor, this constructor shall be a constexpr constructor.

```
template <size_t I, class U, class... Args>
constexpr explicit variant(in_place_index_t<I>, initializer_list<U> il, Args&&... args);
```

31 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type T_I with the arguments il, `std::forward<Args>(args)...`

32 *Postconditions:* index() is I.

33 *Remarks:* This function shall not participate in overload resolution unless

(33.1) — I is less than sizeof...(Types) and

(33.2) — is_constructible_v< T_I , initializer_list<U>&, Args...> is true.

If T_I 's selected constructor is a constexpr constructor, this constructor shall be a constexpr constructor.

// allocator-extended constructors

```
template <class Alloc>
    variant(allocator_arg_t, const Alloc& a);
template <class Alloc>
    variant(allocator_arg_t, const Alloc& a, const variant& v);
template <class Alloc>
    variant(allocator_arg_t, const Alloc& a, variant&& v);
template <class Alloc, class T>
    variant(allocator_arg_t, const Alloc& a, T&& t);
template <class Alloc, class T, class... Args>
    variant(allocator_arg_t, const Alloc& a, in_place_type_t<T>, Args&&... args);
template <class Alloc, class T, class U, class... Args>
    variant(allocator_arg_t, const Alloc& a, in_place_type_t<T>,
        initializer_list<U> il, Args&&... args);
template <class Alloc, size_t I, class... Args>
    variant(allocator_arg_t, const Alloc& a, in_place_index_t<I>, Args&&... args);
template <class Alloc, size_t I, class U, class... Args>
    variant(allocator_arg_t, const Alloc& a, in_place_index_t<I>,
        initializer_list<U> il, Args&&... args);
```

34 *Requires:* Alloc shall meet the requirements for an Allocator (20.5.3.5).

35 *Effects:* Equivalent to the preceding constructors except that the contained value is constructed with

uses-allocator construction (23.10.7.2).

23.7.3.2 Destructor

[variant.dtor]

`~variant();`

1 *Effects:* If `valueless_by_exception()` is false, destroys the currently contained value.

2 *Remarks:* If `is_trivially_destructible_v<Ti> == true` for all `Ti` then this destructor shall be a trivial destructor.

23.7.3.3 Assignment

[variant.assign]

`variant& operator=(const variant& rhs);`

1 Let `j` be `rhs.index()`.

2 *Effects:*

- (2.1) — If neither `*this` nor `rhs` holds a value, there is no effect. Otherwise,
- (2.2) — if `*this` holds a value but `rhs` does not, destroys the value contained in `*this` and sets `*this` to not hold a value. Otherwise,
- (2.3) — if `index() == j`, assigns the value contained in `rhs` to the value contained in `*this`. Otherwise,
- (2.4) — if either `is_nothrow_copy_constructible_v<Tj>` or `!is_nothrow_move_constructible_v<Tj>` is true, equivalent to `emplace<j>(get<j>(rhs))`. Otherwise,
- (2.5) — equivalent to `operator=(variant(rhs))`.

3 *Returns:* `*this`.

4 *Postconditions:* `index() == rhs.index()`.

5 *Remarks:* This function shall not participate in overload resolution unless `is_copy_constructible_v<Ti> && is_copy_assignable_v<Ti>` is true for all `i`.

`variant& operator=(variant&& rhs) noexcept(see below);`

6 Let `j` be `rhs.index()`.

7 *Effects:*

- (7.1) — If neither `*this` nor `rhs` holds a value, there is no effect. Otherwise,
- (7.2) — if `*this` holds a value but `rhs` does not, destroys the value contained in `*this` and sets `*this` to not hold a value. Otherwise,
- (7.3) — if `index() == j`, assigns `get<j>(std::move(rhs))` to the value contained in `*this`. Otherwise,
- (7.4) — equivalent to `emplace<j>(get<j>(std::move(rhs)))`.

8 *Returns:* `*this`.

9 *Remarks:* This function shall not participate in overload resolution unless `is_move_constructible_v<Ti> && is_move_assignable_v<Ti>` is true for all `i`. The expression inside `noexcept` is equivalent to: `is_nothrow_move_constructible_v<Ti> && is_nothrow_move_assignable_v<Ti>` for all `i`.

(9.1) — If an exception is thrown during the call to `Tj`'s move construction (with `j` being `rhs.index()`), the `variant` will hold no value.

(9.2) — If an exception is thrown during the call to `Tj`'s move assignment, the state of the contained value is as defined by the exception safety guarantee of `Tj`'s move assignment; `index()` will be `j`.

`template <class T> variant& operator=(T&& t) noexcept(see below);`

Let T_j be a type that is determined as follows: build an imaginary function $FUN(T_i)$ for each alternative type T_i . The overload $FUN(T_j)$ selected by overload resolution for the expression $FUN(std::forward<T>(t))$ defines the alternative T_j which is the type of the contained value after assignment.

Effects:

— If $*this$ holds a T_j , assigns $std::forward<T>(t)$ to the value contained in $*this$. Otherwise,

— if $is_nothrow_constructible_v<T_j, T> || !is_nothrow_move_constructible_v<T_j>$ is true, equivalent to $emplace<j>(std::forward<T>(t))$. Otherwise,

— equivalent to $operator=(variant(std::forward<T>(t)))$.

Postconditions: $holds_alternative<T_j>(*this)$ is true, with T_j selected by the imaginary function overload resolution described above.

Returns: $*this$.

Remarks: This function shall not participate in overload resolution unless $is_same_v<decay_t<T>, variant>$ is false, unless $is_assignable_v<T_j\&, T> \&\& is_constructible_v<T_j, T>$ is true, and unless the expression $FUN(std::forward<T>(t))$ (with FUN being the above-mentioned set of imaginary functions) is well formed.

[*Note:*

```
variant<string, string> v;
v = "abc";
```

is ill-formed, as both alternative types have an equally viable constructor for the argument. — *end note*]

The expression inside `noexcept` is equivalent to:

```
is_nothrow_assignable_v<T_j\&, T> \&\& is_nothrow_constructible_v<T_j, T>
```

— If an exception is thrown during the assignment of $std::forward<T>(t)$ to the value contained in $*this$, the state of the contained value and t are as defined by the exception safety guarantee of the assignment expression; `valueless_by_exception()` will be false.

— If an exception is thrown during the initialization of the contained value, the `variant` object might not hold a value.

23.7.3.4 Modifiers

[variant.mod]

```
template <class T, class... Args> T& emplace(Args&\&... args);
```

Let I be the zero-based index of T in `Types...`

Effects: Equivalent to: `return emplace<I>(std::forward<Args>(args)...);`

Remarks: This function shall not participate in overload resolution unless $is_constructible_v<T, Args...>$ is true, and T occurs exactly once in `Types...`

```
template <class T, class U, class... Args> T& emplace(initializer_list<U> il, Args&\&... args);
```

Let I be the zero-based index of T in `Types...`

Effects: Equivalent to: `return emplace<I>(il, std::forward<Args>(args)...);`

Remarks: This function shall not participate in overload resolution unless $is_constructible_v<T, initializer_list<U>\&, Args...>$ is true, and T occurs exactly once in `Types...`

```
template <size_t I, class... Args>
variant_alternative_t<I, variant<Types...>\&\& emplace(Args&\&... args);
```

Requires: $I < sizeof...(Types)$.

Effects: Destroys the currently contained value if `valueless_by_exception()` is false. Then initializes the contained value as if direct-non-list-initializing a value of type T_I with the arguments `std::forward<Args>(args)...`

Postconditions: `index()` is I .

Returns: A reference to the new contained value.

Throws: Any exception thrown during the initialization of the contained value.

Remarks: This function shall not participate in overload resolution unless `is_constructible_v< $T_I$ , Args...>` is true. If an exception is thrown during the initialization of the contained value, the `variant` might not hold a value.

```
template <size_t I, class U, class... Args>
    variant_alternative_t<I, variant<Types...>&& emplace(initializer_list<U> il, Args&&... args);
```

Requires: $I < \text{sizeof}...(Types)$.

Effects: Destroys the currently contained value if `valueless_by_exception()` is false. Then initializes the contained value as if direct-non-list-initializing a value of type T_I with the arguments `il, std::forward<Args>(args)...`

Postconditions: `index()` is I .

Returns: A reference to the new contained value.

Throws: Any exception thrown during the initialization of the contained value.

Remarks: This function shall not participate in overload resolution unless `is_constructible_v< $T_I$ , initializer_list<U>&, Args...>` is true. If an exception is thrown during the initialization of the contained value, the `variant` might not hold a value.

23.7.3.5 Value status

[`variant.status`]

```
constexpr bool valueless_by_exception() const noexcept;
```

Effects: Returns false if and only if the `variant` holds a value.

[*Note:* A `variant` might not hold a value if an exception is thrown during a type-changing assignment or emplacement. The latter means that even a `variant<float, int>` can become `valueless_by_exception()`, for instance by

```
struct S { operator int() { throw 42; } };
variant<float, int> v{12.f};
v.emplace<1>(S());
```

— *end note*]

```
constexpr size_t index() const noexcept;
```

Effects: If `valueless_by_exception()` is true, returns `variant_npos`. Otherwise, returns the zero-based index of the alternative of the contained value.

23.7.3.6 Swap

[`variant.swap`]

```
void swap(variant& rhs) noexcept(see below);
```

Requires: Lvalues of type T_i shall be swappable (20.5.3.2) and `is_move_constructible_v< $T_i$ >` shall be true for all i .

Effects:

(2.1) — if `valueless_by_exception() && rhs.valueless_by_exception()` no effect. Otherwise,

- (2.2) — if `index() == rhs.index()`, calls `swap(get<i>(*this), get<i>(rhs))` where *i* is `index()`. Otherwise,
- (2.3) — exchanges values of `rhs` and `*this`.
- 3 *Throws:* If `index() == rhs.index()`, any exception thrown by `swap(get<i>(*this), get<i>(rhs))` with *i* being `index()`. Otherwise, any exception thrown by the move constructor of T_i or T_j with *i* being `index()` and *j* being `rhs.index()`.
- 4 *Remarks:* If an exception is thrown during the call to function `swap(get<i>(*this), get<i>(rhs))`, the states of the contained values of `*this` and of `rhs` are determined by the exception safety guarantee of `swap` for lvalues of T_i with *i* being `index()`. If an exception is thrown during the exchange of the values of `*this` and `rhs`, the states of the values of `*this` and of `rhs` are determined by the exception safety guarantee of `variant`'s move constructor. The expression inside `noexcept` is equivalent to the logical AND of `is_nothrow_move_constructible_v<Ti> && is_nothrow_swappable_v<Ti>` for all *i*.

23.7.4 variant helper classes

[variant.helper]

```
template <class T> struct variant_size;
```

- 1 *Remarks:* All specializations of `variant_size` shall meet the `UnaryTypeTrait` requirements (23.15.1) with a base characteristic of `integral_constant<size_t, N>` for some *N*.

```
template <class T> class variant_size<const T>;
template <class T> class variant_size<volatile T>;
template <class T> class variant_size<const volatile T>;
```

- 2 Let *VS* denote `variant_size<T>` of the cv-unqualified type *T*. Then each of the three templates shall meet the `UnaryTypeTrait` requirements (23.15.1) with a base characteristic of `integral_constant<size_t, VS::value>`.

```
template <class... Types>
struct variant_size<variant<Types...>> : integral_constant<size_t, sizeof...(Types)> { };
```

```
template <size_t I, class T> class variant_alternative<I, const T>;
template <size_t I, class T> class variant_alternative<I, volatile T>;
template <size_t I, class T> class variant_alternative<I, const volatile T>;
```

- 3 Let *VA* denote `variant_alternative<I, T>` of the cv-unqualified type *T*. Then each of the three templates shall meet the `TransformationTrait` requirements (23.15.1) with a member typedef `type` that names the following type:

- (3.1) — for the first specialization, `add_const_t<VA::type>`,
- (3.2) — for the second specialization, `add_volatile_t<VA::type>`, and
- (3.3) — for the third specialization, `add_cv_t<VA::type>`.

```
variant_alternative<I, variant<Types...>>::type
```

- 4 *Requires:* `I < sizeof...(Types)`.
- 5 *Value:* The type T_I .

23.7.5 Value access

[variant.get]

```
template <class T, class... Types>
constexpr bool holds_alternative(const variant<Types...>& v) noexcept;
```

- 1 *Requires:* The type *T* occurs exactly once in `Types...`. Otherwise, the program is ill-formed.
- 2 *Returns:* `true` if `index()` is equal to the zero-based index of *T* in `Types...`.

```

template <size_t I, class... Types>
constexpr variant_alternative_t<I, variant<Types...>>& get(variant<Types...>& v);
template <size_t I, class... Types>
constexpr variant_alternative_t<I, variant<Types...>>&& get(variant<Types...>&& v);
template <size_t I, class... Types>
constexpr const variant_alternative_t<I, variant<Types...>>& get(const variant<Types...>& v);
template <size_t I, class... Types>
constexpr const variant_alternative_t<I, variant<Types...>>&& get(const variant<Types...>&& v);

```

3 *Requires:* $I < \text{sizeof} \dots (\text{Types})$. Otherwise the program is ill-formed.

4 *Effects:* If $v.\text{index}()$ is I , returns a reference to the object stored in the `variant`. Otherwise, throws an exception of type `bad_variant_access`.

```

template <class T, class... Types> constexpr T& get(variant<Types...>& v);
template <class T, class... Types> constexpr T&& get(variant<Types...>&& v);
template <class T, class... Types> constexpr const T& get(const variant<Types...>& v);
template <class T, class... Types> constexpr const T&& get(const variant<Types...>&& v);

```

5 *Requires:* The type T occurs exactly once in $\text{Types} \dots$. Otherwise, the program is ill-formed.

6 *Effects:* If v holds a value of type T , returns a reference to that value. Otherwise, throws an exception of type `bad_variant_access`.

```

template <size_t I, class... Types>
constexpr add_pointer_t<variant_alternative_t<I, variant<Types...>>>
get_if(variant<Types...>* v) noexcept;
template <size_t I, class... Types>
constexpr add_pointer_t<const variant_alternative_t<I, variant<Types...>>>
get_if(const variant<Types...>* v) noexcept;

```

7 *Requires:* $I < \text{sizeof} \dots (\text{Types})$. Otherwise the program is ill-formed.

8 *Returns:* A pointer to the value stored in the `variant`, if $v \neq \text{nullptr}$ and $v \rightarrow \text{index}() == I$. Otherwise, returns `nullptr`.

```

template <class T, class... Types>
constexpr add_pointer_t<T>
get_if(variant<Types...>* v) noexcept;
template <class T, class... Types>
constexpr add_pointer_t<const T>
get_if(const variant<Types...>* v) noexcept;

```

9 *Requires:* The type T occurs exactly once in $\text{Types} \dots$. Otherwise, the program is ill-formed.

10 *Effects:* Equivalent to: `return get_if<i>(v);` with i being the zero-based index of T in $\text{Types} \dots$.

23.7.6 Relational operators

[variant.relops]

```

template <class... Types>
constexpr bool operator==(const variant<Types...>& v, const variant<Types...>& w);

```

1 *Requires:* `get<i>(v) == get<i>(w)` is a valid expression returning a type that is convertible to `bool`, for all i .

2 *Returns:* If $v.\text{index}() \neq w.\text{index}()$, `false`; otherwise if $v.\text{valueless_by_exception}()$, `true`; otherwise `get<i>(v) == get<i>(w)` with i being $v.\text{index}()$.

```

template <class... Types>
constexpr bool operator!=(const variant<Types...>& v, const variant<Types...>& w);

```

3 *Requires:* `get<i>(v) != get<i>(w)` is a valid expression returning a type that is convertible to `bool`,

for all i .

- 4 *Returns:* If $v.index() \neq w.index()$, true; otherwise if $v.valueless_by_exception()$, false; otherwise $get<i>(v) \neq get<i>(w)$ with i being $v.index()$.

```
template <class... Types>
```

```
constexpr bool operator<(const variant<Types...>& v, const variant<Types...>& w);
```

- 5 *Requires:* $get<i>(v) < get<i>(w)$ is a valid expression returning a type that is convertible to bool, for all i .

- 6 *Returns:* If $w.valueless_by_exception()$, false; otherwise if $v.valueless_by_exception()$, true; otherwise, if $v.index() < w.index()$, true; otherwise if $v.index() > w.index()$, false; otherwise $get<i>(v) < get<i>(w)$ with i being $v.index()$.

```
template <class... Types>
```

```
constexpr bool operator>(const variant<Types...>& v, const variant<Types...>& w);
```

- 7 *Requires:* $get<i>(v) > get<i>(w)$ is a valid expression returning a type that is convertible to bool, for all i .

- 8 *Returns:* If $v.valueless_by_exception()$, false; otherwise if $w.valueless_by_exception()$, true; otherwise, if $v.index() > w.index()$, true; otherwise if $v.index() < w.index()$, false; otherwise $get<i>(v) > get<i>(w)$ with i being $v.index()$.

```
template <class... Types>
```

```
constexpr bool operator<=(const variant<Types...>& v, const variant<Types...>& w);
```

- 9 *Requires:* $get<i>(v) \leq get<i>(w)$ is a valid expression returning a type that is convertible to bool, for all i .

- 10 *Returns:* If $v.valueless_by_exception()$, true; otherwise if $w.valueless_by_exception()$, false; otherwise, if $v.index() < w.index()$, true; otherwise if $v.index() > w.index()$, false; otherwise $get<i>(v) \leq get<i>(w)$ with i being $v.index()$.

```
template <class... Types>
```

```
constexpr bool operator>=(const variant<Types...>& v, const variant<Types...>& w);
```

- 11 *Requires:* $get<i>(v) \geq get<i>(w)$ is a valid expression returning a type that is convertible to bool, for all i .

- 12 *Returns:* If $w.valueless_by_exception()$, true; otherwise if $v.valueless_by_exception()$, false; otherwise, if $v.index() > w.index()$, true; otherwise if $v.index() < w.index()$, false; otherwise $get<i>(v) \geq get<i>(w)$ with i being $v.index()$.

23.7.7 Visitation

[variant.visit]

```
template <class Visitor, class... Variants>
```

```
constexpr see below visit(Visitor&& vis, Variants&&... vars);
```

- 1 *Requires:* The expression in the *Effects:* element shall be a valid expression of the same type and value category, for all combinations of alternative types of all variants. Otherwise, the program is ill-formed.

- 2 *Effects:* Let $is...$ be $vars.index()...$. Returns $INVOKE(forward<Visitor>(vis), get<is>(forward<Variants>(vars))...)$.

- 3 *Remarks:* The return type is the common type of all possible *INVOKE* expressions of the *Effects:* element.

- 4 *Throws:* `bad_variant_access` if any variant in `vars` is `valueless_by_exception()`.

- 5 *Complexity:* For $\text{sizeof}...(Variants) \leq 1$, the invocation of the callable object is implemented in constant time, i.e. it does not depend on $\text{sizeof}...(Types)$. For $\text{sizeof}...(Variants) > 1$, the

invocation of the callable object has no complexity requirements.

23.7.8 Class monostate

[variant.monostate]

```
struct monostate{};
```

- ¹ The class `monostate` can serve as a first alternative type for a `variant` to make the `variant` type default constructible.

23.7.9 monostate relational operators

[variant.monostate.relops]

```
constexpr bool operator<(monostate, monostate) noexcept { return false; }
constexpr bool operator>(monostate, monostate) noexcept { return false; }
constexpr bool operator<=(monostate, monostate) noexcept { return true; }
constexpr bool operator>=(monostate, monostate) noexcept { return true; }
constexpr bool operator==(monostate, monostate) noexcept { return true; }
constexpr bool operator!=(monostate, monostate) noexcept { return false; }
```

- ¹ [Note: `monostate` objects have only a single state; they thus always compare equal. — end note]

23.7.10 Specialized algorithms

[variant.specalg]

```
template <class... Types>
void swap(variant<Types...& v, variant<Types...& w) noexcept(see below);
```

- ¹ *Effects:* Equivalent to `v.swap(w)`.
- ² *Remarks:* This function shall not participate in overload resolution unless `is_move_constructible_v<Ti>` && `is_swappable_v<Ti>` is true for all *i*. The expression inside `noexcept` is equivalent to `noexcept(v.swap(w))`.

23.7.11 Class bad_variant_access

[variant.bad.access]

```
class bad_variant_access : public exception {
public:
    bad_variant_access() noexcept;
    const char* what() const noexcept override;
};
```

- ¹ Objects of type `bad_variant_access` are thrown to report invalid accesses to the value of a `variant` object.

```
bad_variant_access() noexcept;
```

- ² Constructs a `bad_variant_access` object.

```
const char* what() const noexcept override;
```

- ³ *Returns:* An implementation-defined NTBS.

23.7.12 Hash support

[variant.hash]

```
template <class... Types> struct hash<variant<Types...>>;
```

- ¹ The specialization `hash<variant<Types...>>` is enabled (23.14.15) if and only if every specialization in `hash<remove_const_t<Types...>>...` is enabled. The member functions are not guaranteed to be `noexcept`.

```
template <> struct hash<monostate>;
```

- ² The specialization is enabled (23.14.15).

23.7.13 Allocator-related traits**[variant.traits]**

```
template <class... Types, class Alloc>
struct uses_allocator<variant<Types...>, Alloc> : true_type { };
```

¹ *Requires:* Alloc shall be an Allocator (20.5.3.5).

² [*Note:* Specialization of this trait informs other library components that variant can be constructed with an allocator, even though it does not have a nested `allocator_type`. — *end note*]

23.8 Storage for any type**[any]**

¹ This section describes components that C++ programs may use to perform operations on objects of a discriminated type.

² [*Note:* The discriminated type may contain values of different types but does not attempt conversion between them, i.e. 5 is held strictly as an `int` and is not implicitly convertible either to "5" or to 5.0. This indifference to interpretation but awareness of type effectively allows safe, generic containers of single values, with no scope for surprises from ambiguous conversions. — *end note*]

23.8.1 Header <any> synopsis**[any.synop]**

```
namespace std {
    // 23.8.2, class bad_any_cast
    class bad_any_cast;

    // 23.8.3, class any
    class any;

    // 23.8.4, non-member functions
    void swap(any& x, any& y) noexcept;

    template <class T, class... Args>
        any make_any(Args&& ...args);
    template <class T, class U, class... Args>
        any make_any(initializer_list<U> il, Args&& ...args);

    template<class T>
        T any_cast(const any& operand);
    template<class T>
        T any_cast(any& operand);
    template<class T>
        T any_cast(any&& operand);

    template<class T>
        const T* any_cast(const any* operand) noexcept;
    template<class T>
        T* any_cast(any* operand) noexcept;
}
```

23.8.2 Class bad_any_cast**[any.bad_any_cast]**

```
class bad_any_cast : public bad_cast {
public:
    const char* what() const noexcept override;
};
```

¹ Objects of type `bad_any_cast` are thrown by a failed `any_cast` (23.8.4).

```
const char* what() const noexcept override;
```

- 2 *Returns:* An implementation-defined NTBS.
- 3 *Remarks:* The message may be a null-terminated multibyte string (20.4.2.1.5.2), suitable for conversion and display as a wstring (24.3, 25.4.1.4).

23.8.3 Class **any**

[any.class]

```

class any {
public:
    // 23.8.3.1, construction and destruction
    constexpr any() noexcept;

    any(const any& other);
    any(any&& other) noexcept;

    template <class T> any(T&& value);

    template <class T, class... Args>
        explicit any(in_place_type_t<T>, Args&&...);
    template <class T, class U, class... Args>
        explicit any(in_place_type_t<T>, initializer_list<U>, Args&&...);

    ~any();

    // 23.8.3.2, assignments
    any& operator=(const any& rhs);
    any& operator=(any&& rhs) noexcept;

    template <class T> any& operator=(T&& rhs);

    // 23.8.3.3, modifiers
    template <class T, class... Args>
        decay_t<T>& emplace(Args&& ...);
    template <class T, class U, class... Args>
        decay_t<T>& emplace(initializer_list<U>, Args&&...);
    void reset() noexcept;
    void swap(any& rhs) noexcept;

    // 23.8.3.4, observers
    bool has_value() const noexcept;
    const type_info& type() const noexcept;
};

```

- 1 An object of class **any** stores an instance of any type that satisfies the constructor requirements or it has no value, and this is referred to as the *state* of the class **any** object. The stored instance is called the *contained value*. Two states are equivalent if either they both have no value, or both have a value and the contained values are equivalent.
- 2 The non-member **any_cast** functions provide type-safe access to the contained value.
- 3 Implementations should avoid the use of dynamically allocated memory for a small contained value. [*Example:* where the object constructed is holding only an `int`. — *end example*] Such small-object optimization shall only be applied to types `T` for which `is_nothrow_move_constructible_v<T>` is `true`.

23.8.3.1 Construction and destruction

[any.cons]

```
constexpr any() noexcept;
```

- 1 *Postconditions:* `has_value()` is `false`.

```
any(const any& other);
```

2 *Effects:* If `other.has_value()` is `false`, constructs an object that has no value. Otherwise, equivalent to `any(in_place<T>, any_cast<const T&>(other))` where `T` is the type of the contained object.

3 *Throws:* Any exceptions arising from calling the selected constructor for the contained value.

```
any(any&& other) noexcept;
```

4 *Effects:* If `other.has_value()` is `false`, constructs an object that has no value. Otherwise, constructs an object of type `any` that contains either the contained object of `other`, or contains an object of the same type constructed from the contained object of `other` considering that contained object as an rvalue.

5 *Postconditions:* `other` is left in a valid but otherwise unspecified state.

```
template<class T>
    any(T&& value);
```

6 Let `VT` be `decay_t<T>`.

7 *Requires:* `VT` shall satisfy the `CopyConstructible` requirements.

8 *Effects:* Constructs an object of type `any` that contains an object of type `VT` direct-initialized with `std::forward<T>(value)`.

9 *Remarks:* This constructor shall not participate in overload resolution unless `VT` is not the same type as `any`, `VT` is not a specialization of `in_place_type_t`, and `is_copy_constructible_v<VT>` is `true`.

10 *Throws:* Any exception thrown by the selected constructor of `VT`.

```
template <class T, class... Args>
    explicit any(in_place_type_t<T>, Args&&... args);
```

11 Let `VT` be `decay_t<T>`.

12 *Requires:* `VT` shall satisfy the `CopyConstructible` requirements.

13 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type `VT` with the arguments `std::forward<Args>(args)...`

14 *Postconditions:* `*this` contains a value of type `VT`.

15 *Throws:* Any exception thrown by the selected constructor of `VT`.

16 *Remarks:* This constructor shall not participate in overload resolution unless `is_copy_constructible_v<VT>` is `true` and `is_constructible_v<VT, Args...>` is `true`.

```
template <class T, class U, class... Args>
    explicit any(in_place_type_t<T>, initializer_list<U> il, Args&&... args);
```

17 Let `VT` be `decay_t<T>`.

18 *Requires:* `VT` shall satisfy the `CopyConstructible` requirements.

19 *Effects:* Initializes the contained value as if direct-non-list-initializing an object of type `VT` with the arguments `il, std::forward<Args>(args)...`

20 *Postconditions:* `*this` contains a value.

21 *Throws:* Any exception thrown by the selected constructor of `VT`.

22 *Remarks:* This constructor shall not participate in overload resolution unless `is_copy_constructible_v<VT>` is `true` and `is_constructible_v<VT, initializer_list<U>&, Args...>` is `true`.

```
~any();
```

23 *Effects:* As if by `reset()`.

23.8.3.2 Assignment

[any.assign]

`any& operator=(const any& rhs);`

1 *Effects:* As if by `any(rhs).swap(*this)`. No effects if an exception is thrown.

2 *Returns:* `*this`.

3 *Throws:* Any exceptions arising from the copy constructor for the contained value.

`any& operator=(any&& rhs) noexcept;`

4 *Effects:* As if by `any(std::move(rhs)).swap(*this)`.

5 *Returns:* `*this`.

6 *Postconditions:* The state of `*this` is equivalent to the original state of `rhs` and `rhs` is left in a valid but otherwise unspecified state.

`template<class T>`

`any& operator=(T&& rhs);`

7 Let VT be `decay_t<T>`.

8 *Requires:* VT shall satisfy the `CopyConstructible` requirements.

9 *Effects:* Constructs an object `tmp` of type `any` that contains an object of type VT direct-initialized with `std::forward<T>(rhs)`, and `tmp.swap(*this)`. No effects if an exception is thrown.

10 *Returns:* `*this`.

11 *Remarks:* This operator shall not participate in overload resolution unless VT is not the same type as `any` and `is_copy_constructible_v<VT>` is true.

12 *Throws:* Any exception thrown by the selected constructor of VT.

23.8.3.3 Modifiers

[any.modifiers]

`template <class T, class... Args>`

`decay_t<T>& emplace(Args&&... args);`

1 Let VT be `decay_t<T>`.

2 *Requires:* VT shall satisfy the `CopyConstructible` requirements.

3 *Effects:* Calls `reset()`. Then initializes the contained value as if direct-non-list-initializing an object of type VT with the arguments `std::forward<Args>(args)...`

4 *Postconditions:* `*this` contains a value.

5 *Returns:* A reference to the new contained value.

6 *Throws:* Any exception thrown by the selected constructor of VT.

7 *Remarks:* If an exception is thrown during the call to VT's constructor, `*this` does not contain a value, and any previously contained value has been destroyed. This function shall not participate in overload resolution unless `is_copy_constructible_v<VT>` is true and `is_constructible_v<VT, Args...>` is true.

`template <class T, class U, class... Args>`

`decay_t<T>& emplace(initializer_list<U> il, Args&&... args);`

8 Let VT be `decay_t<T>`.

9 *Requires:* VT shall satisfy the `CopyConstructible` requirements.

10 *Effects:* Calls `reset()`. Then initializes the contained value as if direct-non-list-initializing an object of type VT with the arguments `il, std::forward<Args>(args)...`

11 *Postconditions:* `*this` contains a value.

12 *Returns:* A reference to the new contained value.

13 *Throws:* Any exception thrown by the selected constructor of VT.

14 *Remarks:* If an exception is thrown during the call to VT's constructor, `*this` does not contain a value, and any previously contained value has been destroyed. The function shall not participate in overload resolution unless `is_copy_constructible_v<VT>` is true and `is_constructible_v<VT, initializer_list<U>&, Args...>` is true.

```
void reset() noexcept;
```

15 *Effects:* If `has_value()` is true, destroys the contained value.

16 *Postconditions:* `has_value()` is false.

```
void swap(any& rhs) noexcept;
```

17 *Effects:* Exchanges the states of `*this` and `rhs`.

23.8.3.4 Observers

[any.observers]

```
bool has_value() const noexcept;
```

1 *Returns:* true if `*this` contains an object, otherwise false.

```
const type_info& type() const noexcept;
```

2 *Returns:* `typeid(T)` if `*this` has a contained value of type T, otherwise `typeid(void)`.

3 [Note: Useful for querying against types known either at compile time or only at runtime. — end note]

23.8.4 Non-member functions

[any.nonmembers]

```
void swap(any& x, any& y) noexcept;
```

1 *Effects:* As if by `x.swap(y)`.

```
template <class T, class... Args>
    any make_any(Args&& ...args);
```

2 *Effects:* Equivalent to: `return any(in_place_type<T>, std::forward<Args>(args)...);`

```
template <class T, class U, class... Args>
    any make_any(initializer_list<U> il, Args&& ...args);
```

3 *Effects:* Equivalent to: `return any(in_place_type<T>, il, std::forward<Args>(args)...);`

```
template<class T>
    T any_cast(const any& operand);
template<class T>
    T any_cast(any& operand);
template<class T>
    T any_cast(any&& operand);
```

4 Let U be the type `remove_cv_t<remove_reference_t<ValueType>>`.

5 *Requires:* For the first overload, `is_constructible_v<ValueType, const U&>` is true. For the second overload, `is_constructible_v<ValueType, U&>` is true. For the third overload, `is_constructible_v<`

`v<ValueType, U>` is true. Otherwise the program is ill-formed.

6 *Returns:* For the first and second overload, `static_cast<ValueType>(*any_cast<U>(&operand))`.
For the third overload, `static_cast<ValueType>(std::move(*any_cast<U>(&operand)))`.

7 *Throws:* `bad_any_cast` if `operand.type() != typeid(remove_reference_t<T>)`.

8 [*Example:*

```

any x(5);                                // x holds int
assert(any_cast<int>(x) == 5);            // cast to value
any_cast<int&>(x) = 10;                    // cast to reference
assert(any_cast<int>(x) == 10);

x = "Meow";                               // x holds const char*
assert(strcmp(any_cast<const char*>(x), "Meow") == 0);
any_cast<const char*&>(x) = "Harry";
assert(strcmp(any_cast<const char*>(x), "Harry") == 0);

x = string("Meow");                       // x holds string
string s, s2("Jane");
s = move(any_cast<string&>(x));             // move from any
assert(s == "Meow");
any_cast<string&>(x) = move(s2);           // move to any
assert(any_cast<const string&>(x) == "Jane");

string cat("Meow");
const any y(cat);                         // const y holds string
assert(any_cast<const string&>(y) == cat);

any_cast<string&>(y);                      // error; cannot
                                           // any_cast away const

```

— end example]

```

template<class T>
    const T* any_cast(const any* operand) noexcept;
template<class T>
    T* any_cast(any* operand) noexcept;

```

9 *Returns:* If `operand != nullptr` && `operand->type() == typeid(T)`, a pointer to the object contained by `operand`; otherwise, `nullptr`.

10 [*Example:*

```

bool is_string(const any& operand) {
    return any_cast<string>(&operand) != nullptr;
}

```

— end example]

23.9 Bitsets

[bitset]

23.9.1 Header <bitset> synopsis

[bitset.syn]

```

#include <string>
#include <iosfwd>    // for istream (30.7.1), ostream (30.7.2), see 30.3.1

namespace std {
    template <size_t N> class bitset;

```

```

// 23.9.4, bitset operators
template <size_t N>
    bitset<N> operator&(const bitset<N>&, const bitset<N>&) noexcept;
template <size_t N>
    bitset<N> operator|(const bitset<N>&, const bitset<N>&) noexcept;
template <size_t N>
    bitset<N> operator^(const bitset<N>&, const bitset<N>&) noexcept;
template <class charT, class traits, size_t N>
    basic_istream<charT, traits>&
        operator>>(basic_istream<charT, traits>& is, bitset<N>& x);
template <class charT, class traits, size_t N>
    basic_ostream<charT, traits>&
        operator<<(basic_ostream<charT, traits>& os, const bitset<N>& x);
}

```

- ¹ The header <bitset> defines a class template and several related functions for representing and manipulating fixed-size sequences of bits.

23.9.2 Class template bitset

[template.bitset]

```

namespace std {
    template<size_t N> class bitset {
    public:
        // bit reference:
        class reference {
            friend class bitset;
            reference() noexcept;
        public:
            ~reference() noexcept;
            reference& operator=(bool x) noexcept;           // for b[i] = x;
            reference& operator=(const reference&) noexcept; // for b[i] = b[j];
            bool operator~() const noexcept;                 // flips the bit
            operator bool() const noexcept;                  // for x = b[i];
            reference& flip() noexcept;                       // for b[i].flip();
        };

        // 23.9.2.1, constructors
        constexpr bitset() noexcept;
        constexpr bitset(unsigned long long val) noexcept;
        template<class charT, class traits, class Allocator>
            explicit bitset(
                const basic_string<charT, traits, Allocator>& str,
                typename basic_string<charT, traits, Allocator>::size_type pos = 0,
                typename basic_string<charT, traits, Allocator>::size_type n =
                    basic_string<charT, traits, Allocator>::npos,
                charT zero = charT('0'),
                charT one = charT('1'));
        template <class charT>
            explicit bitset(
                const charT* str,
                typename basic_string<charT>::size_type n = basic_string<charT>::npos,
                charT zero = charT('0'),
                charT one = charT('1'));

        // 23.9.2.2, bitset operations
        bitset<N>& operator&=(const bitset<N>& rhs) noexcept;
        bitset<N>& operator|=(const bitset<N>& rhs) noexcept;
    };
}

```

```

bitset<N>& operator^=(const bitset<N>& rhs) noexcept;
bitset<N>& operator<=(size_t pos) noexcept;
bitset<N>& operator>=(size_t pos) noexcept;
bitset<N>& set() noexcept;
bitset<N>& set(size_t pos, bool val = true);
bitset<N>& reset() noexcept;
bitset<N>& reset(size_t pos);
bitset<N> operator~() const noexcept;
bitset<N>& flip() noexcept;
bitset<N>& flip(size_t pos);

// element access:
constexpr bool operator[](size_t pos) const;           // for b[i];
reference operator[](size_t pos);                       // for b[i];

unsigned long to_ulong() const;
unsigned long long to_ullong() const;
template <class charT = char,
          class traits = char_traits<charT>,
          class Allocator = allocator<charT>>
basic_string<charT, traits, Allocator>
to_string(charT zero = charT('0'), charT one = charT('1')) const;

size_t count() const noexcept;
constexpr size_t size() const noexcept;
bool operator==(const bitset<N>& rhs) const noexcept;
bool operator!=(const bitset<N>& rhs) const noexcept;
bool test(size_t pos) const;
bool all() const noexcept;
bool any() const noexcept;
bool none() const noexcept;
bitset<N> operator<<(size_t pos) const noexcept;
bitset<N> operator>>(size_t pos) const noexcept;
};

// 23.9.3, hash support
template <class T> struct hash;
template <size_t N> struct hash<bitset<N>>;
}

```

- 1 The class template `bitset<N>` describes an object that can store a sequence consisting of a fixed number of bits, `N`.
- 2 Each bit represents either the value zero (reset) or one (set). To *toggle* a bit is to change the value zero to one, or the value one to zero. Each bit has a non-negative position `pos`. When converting between an object of class `bitset<N>` and a value of some integral type, bit position `pos` corresponds to the *bit value* `1 << pos`. The integral value corresponding to two or more bits is the sum of their bit values.
- 3 The functions described in this subclause can report three kinds of errors, each associated with a distinct exception:
 - (3.1) — an *invalid-argument* error is associated with exceptions of type `invalid_argument` (22.2.4);
 - (3.2) — an *out-of-range* error is associated with exceptions of type `out_of_range` (22.2.6);
 - (3.3) — an *overflow* error is associated with exceptions of type `overflow_error` (22.2.9).

23.9.2.1 bitset constructors

[bitset.cons]

```
constexpr bitset() noexcept;
```

- 1 *Effects:* Constructs an object of class `bitset<N>`, initializing all bits to zero.

```
constexpr bitset(unsigned long long val) noexcept;
```

- 2 *Effects:* Constructs an object of class `bitset<N>`, initializing the first `M` bit positions to the corresponding bit values in `val`. `M` is the smaller of `N` and the number of bits in the value representation (6.9) of `unsigned long long`. If `M < N`, the remaining bit positions are initialized to zero.

```
template <class charT, class traits, class Allocator>
```

```
explicit
```

```
bitset(const basic_string<charT, traits, Allocator>& str,
        typename basic_string<charT, traits, Allocator>::size_type pos = 0,
        typename basic_string<charT, traits, Allocator>::size_type n =
            basic_string<charT, traits, Allocator>::npos,
        charT zero = charT('0'), charT one = charT('1'));
```

- 3 *Throws:* `out_of_range` if `pos > str.size()` or `invalid_argument` if an invalid character is found (see below).

- 4 *Effects:* Determines the effective length `rlen` of the initializing string as the smaller of `n` and `str.size() - pos`.

The function then throws `invalid_argument` if any of the `rlen` characters in `str` beginning at position `pos` is other than `zero` or `one`. The function uses `traits::eq()` to compare the character values.

Otherwise, the function constructs an object of class `bitset<N>`, initializing the first `M` bit positions to values determined from the corresponding characters in the string `str`. `M` is the smaller of `N` and `rlen`.

- 5 An element of the constructed object has value zero if the corresponding character in `str`, beginning at position `pos`, is `zero`. Otherwise, the element has the value one. Character position `pos + M - 1` corresponds to bit position zero. Subsequent decreasing character positions correspond to increasing bit positions.

- 6 If `M < N`, remaining bit positions are initialized to zero.

```
template <class charT>
```

```
explicit bitset(
```

```
    const charT* str,
    typename basic_string<charT>::size_type n = basic_string<charT>::npos,
    charT zero = charT('0'), charT one = charT('1'));
```

- 7 *Effects:* Constructs an object of class `bitset<N>` as if by:

```
    bitset(
        n == basic_string<charT>::npos
        ? basic_string<charT>(str)
        : basic_string<charT>(str, n),
        0, n, zero, one)
```

23.9.2.2 bitset members

[bitset.members]

```
bitset<N>& operator&=(const bitset<N>& rhs) noexcept;
```

- 1 *Effects:* Clears each bit in `*this` for which the corresponding bit in `rhs` is clear, and leaves all other bits unchanged.

- 2 *Returns:* `*this`.

```
bitset<N>& operator|=(const bitset<N>& rhs) noexcept;
```

3 *Effects:* Sets each bit in **this* for which the corresponding bit in *rhs* is set, and leaves all other bits unchanged.

4 *Returns:* **this*.

 bitset<N>& operator^=(const bitset<N>& rhs) noexcept;

5 *Effects:* Toggles each bit in **this* for which the corresponding bit in *rhs* is set, and leaves all other bits unchanged.

6 *Returns:* **this*.

 bitset<N>& operator<<=(size_t pos) noexcept;

7 *Effects:* Replaces each bit at position *I* in **this* with a value determined as follows:

(7.1) — If *I* < *pos*, the new value is zero;

(7.2) — If *I* >= *pos*, the new value is the previous value of the bit at position *I* - *pos*.

8 *Returns:* **this*.

 bitset<N>& operator>>=(size_t pos) noexcept;

9 *Effects:* Replaces each bit at position *I* in **this* with a value determined as follows:

(9.1) — If *pos* >= *N* - *I*, the new value is zero;

(9.2) — If *pos* < *N* - *I*, the new value is the previous value of the bit at position *I* + *pos*.

10 *Returns:* **this*.

 bitset<N>& set() noexcept;

11 *Effects:* Sets all bits in **this*.

12 *Returns:* **this*.

 bitset<N>& set(size_t pos, bool val = true);

13 *Throws:* *out_of_range* if *pos* does not correspond to a valid bit position.

14 *Effects:* Stores a new value in the bit at position *pos* in **this*. If *val* is nonzero, the stored value is one, otherwise it is zero.

15 *Returns:* **this*.

 bitset<N>& reset() noexcept;

16 *Effects:* Resets all bits in **this*.

17 *Returns:* **this*.

 bitset<N>& reset(size_t pos);

18 *Throws:* *out_of_range* if *pos* does not correspond to a valid bit position.

19 *Effects:* Resets the bit at position *pos* in **this*.

20 *Returns:* **this*.

 bitset<N> operator~() const noexcept;

21 *Effects:* Constructs an object *x* of class *bitset<N>* and initializes it with **this*.

22 *Returns:* *x.flip()*.

 bitset<N>& flip() noexcept;

23 *Effects:* Toggles all bits in **this*.

24 *Returns:* **this*.

```
bitset<N>& flip(size_t pos);
```

25 *Throws:* *out_of_range* if *pos* does not correspond to a valid bit position.

26 *Effects:* Toggles the bit at position *pos* in **this*.

27 *Returns:* **this*.

```
unsigned long to_ulong() const;
```

28 *Throws:* *overflow_error* if the integral value *x* corresponding to the bits in **this* cannot be represented as type *unsigned long*.

29 *Returns:* *x*.

```
unsigned long long to_ullong() const;
```

30 *Throws:* *overflow_error* if the integral value *x* corresponding to the bits in **this* cannot be represented as type *unsigned long long*.

31 *Returns:* *x*.

```
template <class charT = char,
         class traits = char_traits<charT>,
         class Allocator = allocator<charT>>
basic_string<charT, traits, Allocator>
to_string(charT zero = charT('0'), charT one = charT('1')) const;
```

32 *Effects:* Constructs a string object of the appropriate type and initializes it to a string of length *N* characters. Each character is determined by the value of its corresponding bit position in **this*. Character position *N* - 1 corresponds to bit position zero. Subsequent decreasing character positions correspond to increasing bit positions. Bit value zero becomes the character **zero**, bit value one becomes the character **one**.

33 *Returns:* The created object.

```
size_t count() const noexcept;
```

34 *Returns:* A count of the number of bits set in **this*.

```
constexpr size_t size() const noexcept;
```

35 *Returns:* *N*.

```
bool operator==(const bitset<N>& rhs) const noexcept;
```

36 *Returns:* *true* if the value of each bit in **this* equals the value of the corresponding bit in *rhs*.

```
bool operator!=(const bitset<N>& rhs) const noexcept;
```

37 *Returns:* *true* if *!(*this == rhs)*.

```
bool test(size_t pos) const;
```

38 *Throws:* *out_of_range* if *pos* does not correspond to a valid bit position.

39 *Returns:* *true* if the bit at position *pos* in **this* has the value one.

```
bool all() const noexcept;
```

40 *Returns:* *count() == size()*.

```

bool any() const noexcept;
41     Returns: count() != 0.

bool none() const noexcept;
42     Returns: count() == 0.

bitset<N> operator<<(size_t pos) const noexcept;
43     Returns: bitset<N>(*this) <<= pos.

bitset<N> operator>>(size_t pos) const noexcept;
44     Returns: bitset<N>(*this) >>= pos.

constexpr bool operator[](size_t pos) const;
45     Requires: pos shall be valid.
46     Returns: true if the bit at position pos in *this has the value one, otherwise false.
47     Throws: Nothing.

bitset<N>::reference operator[](size_t pos);
48     Requires: pos shall be valid.
49     Returns: An object of type bitset<N>::reference such that (*this)[pos] == this->test(pos),
and such that (*this)[pos] = val is equivalent to this->set(pos, val).
50     Throws: Nothing.
51     Remarks: For the purpose of determining the presence of a data race (4.7), any access or update through
the resulting reference potentially accesses or modifies, respectively, the entire underlying bitset.

```

23.9.3 bitset hash support

[bitset.hash]

```
template <size_t N> struct hash<bitset<N>>;
```

1 The specialization is enabled (23.14.15).

23.9.4 bitset operators

[bitset.operators]

```
bitset<N> operator&(const bitset<N>& lhs, const bitset<N>& rhs) noexcept;
```

1 *Returns:* bitset<N>(lhs) &= rhs.

```
bitset<N> operator|(const bitset<N>& lhs, const bitset<N>& rhs) noexcept;
```

2 *Returns:* bitset<N>(lhs) |= rhs.

```
bitset<N> operator^(const bitset<N>& lhs, const bitset<N>& rhs) noexcept;
```

3 *Returns:* bitset<N>(lhs) ^= rhs.

```
template <class charT, class traits, size_t N>
    basic_istream<charT, traits>&
    operator>>(basic_istream<charT, traits>& is, bitset<N>& x);
```

4 A formatted input function (30.7.4.2).

5 *Effects:* Extracts up to N characters from is. Stores these characters in a temporary object **str** of type `basic_string<charT, traits>`, then evaluates the expression `x = bitset<N>(str)`. Characters are extracted and stored until any of the following occurs:

- (5.1) — N characters have been extracted and stored;
- (5.2) — end-of-file occurs on the input sequence;
- (5.3) — the next input character is neither `is.widen('0')` nor `is.widen('1')` (in which case the input character is not extracted).

6 If no characters are stored in `str`, calls `is.setstate(ios_base::failbit)` (which may throw `ios_base::failure` (30.5.5.4)).

7 *Returns:* `is`.

```
template <class charT, class traits, size_t N>
    basic_ostream<charT, traits>&
    operator<<(basic_ostream<charT, traits>& os, const bitset<N>& x);
```

8 *Returns:*

```
    os << x.template to_string<charT, traits, allocator<charT>>(
        use_facet<ctype<charT>>(os.getloc()).widen('0'),
        use_facet<ctype<charT>>(os.getloc()).widen('1'))
    (see 30.7.5.2).
```

23.10 Memory

[memory]

23.10.1 In general

[memory.general]

- 1 This subclause describes the contents of the header `<memory>` (23.10.2) and some of the contents of the header `<cstdlib>` (21.2.2).

23.10.2 Header `<memory>` synopsis

[memory.syn]

- 1 The header `<memory>` defines several types and function templates that describe properties of pointers and pointer-like types, manage memory for containers and other template types, destroy objects, and construct multiple objects in uninitialized memory buffers (23.10.3–23.10.10). The header also defines the templates `unique_ptr`, `shared_ptr`, `weak_ptr`, and various function templates that operate on objects of these types (23.11).

```
namespace std {
    // 23.10.3, pointer traits
    template <class Ptr> struct pointer_traits;
    template <class T> struct pointer_traits<T*>;

    // 23.10.4, pointer safety
    enum class pointer_safety { relaxed, preferred, strict };
    void declare_reachable(void* p);
    template <class T> T* undeclare_reachable(T* p);
    void declare_no_pointers(char* p, size_t n);
    void undeclare_no_pointers(char* p, size_t n);
    pointer_safety get_pointer_safety() noexcept;

    // 23.10.5, pointer alignment function
    void* align(size_t alignment, size_t size, void*& ptr, size_t& space);

    // 23.10.6, allocator argument tag
    struct allocator_arg_t { explicit allocator_arg_t() = default; };
    inline constexpr allocator_arg_t allocator_arg{};

    // 23.10.7, uses_allocator
    template <class T, class Alloc> struct uses_allocator;
```

```

// 23.10.8, allocator traits
template <class Alloc> struct allocator_traits;

// 23.10.9, the default allocator
template <class T> class allocator;
template <class T, class U>
    bool operator==(const allocator<T>&, const allocator<U>&) noexcept;
template <class T, class U>
    bool operator!=(const allocator<T>&, const allocator<U>&) noexcept;

// 23.10.10, specialized algorithms
template <class T> constexpr T* addressof(T& r) noexcept;
template <class T> const T* addressof(const T&&) = delete;
template <class ForwardIterator>
    void uninitialized_default_construct(ForwardIterator first, ForwardIterator last);
template <class ExecutionPolicy, class ForwardIterator>
    void uninitialized_default_construct(ExecutionPolicy&& exec, // see 28.4.5
        ForwardIterator first, ForwardIterator last);
template <class ForwardIterator, class Size>
    ForwardIterator uninitialized_default_construct_n(ForwardIterator first, Size n);
template <class ExecutionPolicy, class ForwardIterator, class Size>
    ForwardIterator uninitialized_default_construct_n(ExecutionPolicy&& exec, // see 28.4.5
        ForwardIterator first, Size n);
template <class ForwardIterator>
    void uninitialized_value_construct(ForwardIterator first, ForwardIterator last);
template <class ExecutionPolicy, class ForwardIterator>
    void uninitialized_value_construct(ExecutionPolicy&& exec, // see 28.4.5
        ForwardIterator first, ForwardIterator last);
template <class ForwardIterator, class Size>
    ForwardIterator uninitialized_value_construct_n(ForwardIterator first, Size n);
template <class ExecutionPolicy, class ForwardIterator, class Size>
    ForwardIterator uninitialized_value_construct_n(ExecutionPolicy&& exec, // see 28.4.5
        ForwardIterator first, Size n);
template <class InputIterator, class ForwardIterator>
    ForwardIterator uninitialized_copy(InputIterator first, InputIterator last,
        ForwardIterator result);
template <class ExecutionPolicy, class InputIterator, class ForwardIterator>
    ForwardIterator uninitialized_copy(ExecutionPolicy&& exec, // see 28.4.5
        InputIterator first, InputIterator last,
        ForwardIterator result);
template <class InputIterator, class Size, class ForwardIterator>
    ForwardIterator uninitialized_copy_n(InputIterator first, Size n,
        ForwardIterator result);
template <class ExecutionPolicy, class InputIterator, class Size, class ForwardIterator>
    ForwardIterator uninitialized_copy_n(ExecutionPolicy&& exec, // see 28.4.5
        InputIterator first, Size n,
        ForwardIterator result);
template <class InputIterator, class ForwardIterator>
    ForwardIterator uninitialized_move(InputIterator first, InputIterator last,
        ForwardIterator result);
template <class ExecutionPolicy, class InputIterator, class ForwardIterator>
    ForwardIterator uninitialized_move(ExecutionPolicy&& exec, // see 28.4.5
        InputIterator first, InputIterator last,
        ForwardIterator result);

```

```

template <class InputIterator, class Size, class ForwardIterator>
    pair<InputIterator, ForwardIterator>
        uninitialized_move_n(InputIterator first, Size n, ForwardIterator result);
template <class ExecutionPolicy, class InputIterator, class Size, class ForwardIterator>
    pair<InputIterator, ForwardIterator>
        uninitialized_move_n(ExecutionPolicy&& exec, // see 28.4.5
                               InputIterator first, Size n, ForwardIterator result);
template <class ForwardIterator, class T>
    void uninitialized_fill(ForwardIterator first, ForwardIterator last,
                           const T& x);
template <class ExecutionPolicy, class ForwardIterator, class T>
    void uninitialized_fill(ExecutionPolicy&& exec, // see 28.4.5
                           ForwardIterator first, ForwardIterator last,
                           const T& x);
template <class ForwardIterator, class Size, class T>
    ForwardIterator uninitialized_fill_n(ForwardIterator first, Size n, const T& x);
template <class ExecutionPolicy, class ForwardIterator, class Size, class T>
    ForwardIterator uninitialized_fill_n(ExecutionPolicy&& exec, // see 28.4.5
                                         ForwardIterator first, Size n, const T& x);

template <class T>
    void destroy_at(T* location);
template <class ForwardIterator>
    void destroy(ForwardIterator first, ForwardIterator last);
template <class ExecutionPolicy, class ForwardIterator>
    void destroy(ExecutionPolicy&& exec, // see 28.4.5
                 ForwardIterator first, ForwardIterator last);
template <class ForwardIterator, class Size>
    ForwardIterator destroy_n(ForwardIterator first, Size n);
template <class ExecutionPolicy, class ForwardIterator, class Size>
    ForwardIterator destroy_n(ExecutionPolicy&& exec, // see 28.4.5
                              ForwardIterator first, Size n);

// 23.11.1, class template unique_ptr
template <class T> struct default_delete;
template <class T> struct default_delete<T[]>;
template <class T, class D = default_delete<T>> class unique_ptr;
template <class T, class D> class unique_ptr<T[], D>;

template <class T, class... Args> unique_ptr<T> make_unique(Args&&... args);
template <class T> unique_ptr<T> make_unique(size_t n);
template <class T, class... Args> unspecified make_unique(Args&&...) = delete;

template <class T, class D> void swap(unique_ptr<T, D>& x, unique_ptr<T, D>& y) noexcept;

template <class T1, class D1, class T2, class D2>
    bool operator==(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template <class T1, class D1, class T2, class D2>
    bool operator!=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template <class T1, class D1, class T2, class D2>
    bool operator<(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template <class T1, class D1, class T2, class D2>
    bool operator<=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template <class T1, class D1, class T2, class D2>
    bool operator>(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template <class T1, class D1, class T2, class D2>

```

```

    bool operator>=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);

template <class T, class D>
    bool operator==(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator==(nullptr_t, const unique_ptr<T, D>& y) noexcept;
template <class T, class D>
    bool operator!=(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator!=(nullptr_t, const unique_ptr<T, D>& y) noexcept;
template <class T, class D>
    bool operator<(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator<=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<=(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator>(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator>=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>=(nullptr_t, const unique_ptr<T, D>& y);

// 23.11.2.1, class bad_weak_ptr
class bad_weak_ptr;

// 23.11.2.2, class template shared_ptr
template<class T> class shared_ptr;

// 23.11.2.2.6, shared_ptr creation
template<class T, class... Args>
    shared_ptr<T> make_shared(Args&&... args);
template<class T, class A, class... Args>
    shared_ptr<T> allocate_shared(const A& a, Args&&... args);

// 23.11.2.2.7, shared_ptr comparisons
template<class T, class U>
    bool operator==(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator!=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator<(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator>(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator<=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator>=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;

template <class T>
    bool operator==(const shared_ptr<T>& x, nullptr_t) noexcept;

```

```

template <class T>
    bool operator==(nullptr_t, const shared_ptr<T>& y) noexcept;
template <class T>
    bool operator!=(const shared_ptr<T>& x, nullptr_t) noexcept;
template <class T>
    bool operator!=(nullptr_t, const shared_ptr<T>& y) noexcept;
template <class T>
    bool operator<(const shared_ptr<T>& x, nullptr_t) noexcept;
template <class T>
    bool operator<(nullptr_t, const shared_ptr<T>& y) noexcept;
template <class T>
    bool operator<=(const shared_ptr<T>& x, nullptr_t) noexcept;
template <class T>
    bool operator<=(nullptr_t, const shared_ptr<T>& y) noexcept;
template <class T>
    bool operator>(const shared_ptr<T>& x, nullptr_t) noexcept;
template <class T>
    bool operator>(nullptr_t, const shared_ptr<T>& y) noexcept;
template <class T>
    bool operator>=(const shared_ptr<T>& x, nullptr_t) noexcept;
template <class T>
    bool operator>=(nullptr_t, const shared_ptr<T>& y) noexcept;

// 23.11.2.2.8, shared_ptr specialized algorithms
template<class T>
    void swap(shared_ptr<T>& a, shared_ptr<T>& b) noexcept;

// 23.11.2.2.9, shared_ptr casts
template<class T, class U>
    shared_ptr<T> static_pointer_cast(const shared_ptr<U>& r) noexcept;
template<class T, class U>
    shared_ptr<T> dynamic_pointer_cast(const shared_ptr<U>& r) noexcept;
template<class T, class U>
    shared_ptr<T> const_pointer_cast(const shared_ptr<U>& r) noexcept;

// 23.11.2.2.10, shared_ptr get_deleter
template<class D, class T>
    D* get_deleter(const shared_ptr<T>& p) noexcept;

// 23.11.2.2.11, shared_ptr I/O
template<class E, class T, class Y>
    basic_ostream<E, T>& operator<< (basic_ostream<E, T>& os, const shared_ptr<Y>& p);

// 23.11.2.3, class template weak_ptr
template<class T> class weak_ptr;

// 23.11.2.3.6, weak_ptr specialized algorithms
template<class T> void swap(weak_ptr<T>& a, weak_ptr<T>& b) noexcept;

// 23.11.2.4, class template owner_less
template<class T = void> struct owner_less;

// 23.11.2.5, class template enable_shared_from_this
template<class T> class enable_shared_from_this;

```

```

// 23.11.2.6, shared_ptr atomic access
template<class T>
    bool atomic_is_lock_free(const shared_ptr<T>* p);

template<class T>
    shared_ptr<T> atomic_load(const shared_ptr<T>* p);
template<class T>
    shared_ptr<T> atomic_load_explicit(const shared_ptr<T>* p, memory_order mo);

template<class T>
    void atomic_store(shared_ptr<T>* p, shared_ptr<T> r);
template<class T>
    void atomic_store_explicit(shared_ptr<T>* p, shared_ptr<T> r, memory_order mo);

template<class T>
    shared_ptr<T> atomic_exchange(shared_ptr<T>* p, shared_ptr<T> r);
template<class T>
    shared_ptr<T> atomic_exchange_explicit(shared_ptr<T>* p, shared_ptr<T> r, memory_order mo);

template<class T>
    bool atomic_compare_exchange_weak(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w);
template<class T>
    bool atomic_compare_exchange_strong(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w);
template<class T>
    bool atomic_compare_exchange_weak_explicit(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w,
        memory_order success, memory_order failure);
template<class T>
    bool atomic_compare_exchange_strong_explicit(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w,
        memory_order success, memory_order failure);

// 23.11.2.7, hash support
template <class T> struct hash;
template <class T, class D> struct hash<unique_ptr<T, D>>;
template <class T> struct hash<shared_ptr<T>>;

// 23.10.7.1, uses_allocator
template <class T, class Alloc>
    inline constexpr bool uses_allocator_v = uses_allocator<T, Alloc>::value;
}

```

23.10.3 Pointer traits

[pointer.traits]

- ¹ The class template `pointer_traits` supplies a uniform interface to certain attributes of pointer-like types.

```

namespace std {
    template <class Ptr> struct pointer_traits {
        using pointer          = Ptr;
        using element_type     = see below;
        using difference_type  = see below;

        template <class U> using rebind = see below;
    };
}

```

```

    static pointer pointer_to(see below r);
};

template <class T> struct pointer_traits<T*> {
    using pointer          = T*;
    using element_type     = T;
    using difference_type  = ptrdiff_t;

    template <class U> using rebind = U*;

    static pointer pointer_to(see below r) noexcept;
};
}

```

23.10.3.1 Pointer traits member types

[pointer.traits.types]

using element_type = *see below*;

- ¹ *Type:* `Ptr::element_type` if the *qualified-id* `Ptr::element_type` is valid and denotes a type (17.8.2); otherwise, `T` if `Ptr` is a class template instantiation of the form `SomePointer<T, Args>`, where `Args` is zero or more type arguments; otherwise, the specialization is ill-formed.

using difference_type = *see below*;

- ² *Type:* `Ptr::difference_type` if the *qualified-id* `Ptr::difference_type` is valid and denotes a type (17.8.2); otherwise, `ptrdiff_t`.

template <class U> using rebind = *see below*;

- ³ *Alias template:* `Ptr::rebind<U>` if the *qualified-id* `Ptr::rebind<U>` is valid and denotes a type (17.8.2); otherwise, `SomePointer<U, Args>` if `Ptr` is a class template instantiation of the form `SomePointer<T, Args>`, where `Args` is zero or more type arguments; otherwise, the instantiation of `rebind` is ill-formed.

23.10.3.2 Pointer traits member functions

[pointer.traits.functions]

```

static pointer pointer_traits::pointer_to(see below r);
static pointer pointer_traits<T*>::pointer_to(see below r) noexcept;

```

- ¹ *Remarks:* If `element_type` is `cv void`, the type of `r` is unspecified; otherwise, it is `element_type&`.
- ² *Returns:* The first member function returns a pointer to `r` obtained by calling `Ptr::pointer_to(r)` through which indirection is valid; an instantiation of this function is ill-formed if `Ptr` does not have a matching `pointer_to` static member function. The second member function returns `addressof(r)`.

23.10.4 Pointer safety

[util.dynamic.safety]

- ¹ A complete object is *declared reachable* while the number of calls to `declare_reachable` with an argument referencing the object exceeds the number of calls to `undecare_reachable` with an argument referencing the object.

```
void declare_reachable(void* p);
```

- ² *Requires:* `p` shall be a safely-derived pointer (6.7.4.3) or a null pointer value.
- ³ *Effects:* If `p` is not null, the complete object referenced by `p` is subsequently declared reachable (6.7.4.3).
- ⁴ *Throws:* May throw `bad_alloc` if the system cannot allocate additional memory that may be required to track objects declared reachable.

```
template <class T> T* undecare_reachable(T* p);
```

5 *Requires:* If **p** is not null, the complete object referenced by **p** shall have been previously declared reachable, and shall be live (6.8) from the time of the call until the last **undecare_reachable(p)** call on the object.

6 *Returns:* A safely derived copy of **p** which shall compare equal to **p**.

7 *Throws:* Nothing.

8 [*Note:* It is expected that calls to **declare_reachable(p)** will consume a small amount of memory in addition to that occupied by the referenced object until the matching call to **undecare_reachable(p)** is encountered. Long running programs should arrange that calls are matched. — *end note*]

```
void declare_no_pointers(char* p, size_t n);
```

9 *Requires:* No bytes in the specified range are currently registered with **declare_no_pointers()**. If the specified range is in an allocated object, then it must be entirely within a single allocated object. The object must be live until the corresponding **undecare_no_pointers()** call. [*Note:* In a garbage-collecting implementation, the fact that a region in an object is registered with **declare_no_pointers()** should not prevent the object from being collected. — *end note*]

10 *Effects:* The **n** bytes starting at **p** no longer contain traceable pointer locations, independent of their type. Hence indirection through a pointer located there is undefined if the object it points to was created by global operator **new** and not previously declared reachable. [*Note:* This may be used to inform a garbage collector or leak detector that this region of memory need not be traced. — *end note*]

11 *Throws:* Nothing.

12 [*Note:* Under some conditions implementations may need to allocate memory. However, the request can be ignored if memory allocation fails. — *end note*]

```
void undecare_no_pointers(char* p, size_t n);
```

13 *Requires:* The same range must previously have been passed to **declare_no_pointers()**.

14 *Effects:* Unregisters a range registered with **declare_no_pointers()** for destruction. It must be called before the lifetime of the object ends.

15 *Throws:* Nothing.

```
pointer_safety get_pointer_safety() noexcept;
```

16 *Returns:* **pointer_safety::strict** if the implementation has strict pointer safety (6.7.4.3). It is implementation-defined whether **get_pointer_safety** returns **pointer_safety::relaxed** or **pointer_safety::preferred** if the implementation has relaxed pointer safety.²²¹

23.10.5 Align

[ptr.align]

```
void* align(size_t alignment, size_t size, void*& ptr, size_t& space);
```

1 *Effects:* If it is possible to fit **size** bytes of storage aligned by **alignment** into the buffer pointed to by **ptr** with length **space**, the function updates **ptr** to represent the first possible address of such storage and decreases **space** by the number of bytes used for alignment. Otherwise, the function does nothing.

2 *Requires:*

(2.1) — **alignment** shall be a power of two

(2.2) — **ptr** shall represent the address of contiguous storage of at least **space** bytes

²²¹) **pointer_safety::preferred** might be returned to indicate that a leak detector is running so that the program can avoid spurious leak reports.

3 *Returns:* A null pointer if the requested aligned buffer would not fit into the available space, otherwise the adjusted value of `ptr`.

4 [*Note:* The function updates its `ptr` and `space` arguments so that it can be called repeatedly with possibly different `alignment` and `size` arguments for the same buffer. — *end note*]

23.10.6 Allocator argument tag

[allocator.tag]

```
namespace std {
    struct allocator_arg_t { explicit allocator_arg_t() = default; };
    inline constexpr allocator_arg_t allocator_arg{};
}
```

1 The `allocator_arg_t` struct is an empty structure type used as a unique type to disambiguate constructor and function overloading. Specifically, several types (see [tuple 23.5](#)) have constructors with `allocator_arg_t` as the first argument, immediately followed by an argument of a type that satisfies the `Allocator` requirements ([20.5.3.5](#)).

23.10.7 uses_allocator

[allocator.uses]

23.10.7.1 uses_allocator trait

[allocator.uses.trait]

```
template <class T, class Alloc> struct uses_allocator;
```

1 *Remarks:* Automatically detects whether `T` has a nested `allocator_type` that is convertible from `Alloc`. Meets the `BinaryTypeTrait` requirements ([23.15.1](#)). The implementation shall provide a definition that is derived from `true_type` if the *qualified-id* `T::allocator_type` is valid and denotes a type ([17.8.2](#)) and `is_convertible_v<Alloc, T::allocator_type> != false`, otherwise it shall be derived from `false_type`. A program may specialize this template to derive from `true_type` for a user-defined type `T` that does not have a nested `allocator_type` but nonetheless can be constructed with an allocator where either:

(1.1) — the first argument of a constructor has type `allocator_arg_t` and the second argument has type `Alloc` or

(1.2) — the last argument of a constructor has type `Alloc`.

23.10.7.2 Uses-allocator construction

[allocator.uses.construction]

1 *Uses-allocator construction* with allocator `Alloc` refers to the construction of an object `obj` of type `T`, using constructor arguments `v1`, `v2`, ..., `vN` of types `V1`, `V2`, ..., `VN`, respectively, and an allocator `alloc` of type `Alloc`, according to the following rules:

(1.1) — if `uses_allocator_v<T, Alloc>` is false and `is_constructible_v<T, V1, V2, ..., VN>` is true, then `obj` is initialized as `obj(v1, v2, ..., vN)`;

(1.2) — otherwise, if `uses_allocator_v<T, Alloc>` is true and `is_constructible_v<T, allocator_arg_t, Alloc, V1, V2, ..., VN>` is true, then `obj` is initialized as `obj(allocator_arg, alloc, v1, v2, ..., vN)`;

(1.3) — otherwise, if `uses_allocator_v<T, Alloc>` is true and `is_constructible_v<T, V1, V2, ..., VN, Alloc>` is true, then `obj` is initialized as `obj(v1, v2, ..., vN, alloc)`;

(1.4) — otherwise, the request for uses-allocator construction is ill-formed. [*Note:* An error will result if `uses_allocator_v<T, Alloc>` is true but the specific constructor does not take an allocator. This definition prevents a silent failure to pass the allocator to an element. — *end note*]

23.10.8 Allocator traits

[allocator.traits]

1 The class template `allocator_traits` supplies a uniform interface to all allocator types. An allocator cannot be a non-class type, however, even if `allocator_traits` supplies the entire required interface. [*Note:* Thus,

it is always possible to create a derived class from an allocator. — *end note*]

```
namespace std {
    template <class Alloc> struct allocator_traits {
        using allocator_type      = Alloc;

        using value_type          = typename Alloc::value_type;

        using pointer              = see below;
        using const_pointer        = see below;
        using void_pointer         = see below;
        using const_void_pointer   = see below;

        using difference_type      = see below;
        using size_type            = see below;

        using propagate_on_container_copy_assignment = see below;
        using propagate_on_container_move_assignment = see below;
        using propagate_on_container_swap             = see below;
        using is_always_equal                         = see below;

        template <class T> using rebind_alloc = see below;
        template <class T> using rebind_traits = allocator_traits<rebind_alloc<T>>;

        static pointer allocate(Alloc& a, size_type n);
        static pointer allocate(Alloc& a, size_type n, const_void_pointer hint);

        static void deallocate(Alloc& a, pointer p, size_type n);

        template <class T, class... Args>
            static void construct(Alloc& a, T* p, Args&&... args);

        template <class T>
            static void destroy(Alloc& a, T* p);

        static size_type max_size(const Alloc& a) noexcept;

        static Alloc select_on_container_copy_construction(const Alloc& rhs);
    };
}
```

23.10.8.1 Allocator traits member types

[allocator.traits.types]

using pointer = *see below*;

- ¹ *Type:* Alloc::pointer if the *qualified-id* Alloc::pointer is valid and denotes a type (17.8.2); otherwise, value_type*.

using const_pointer = *see below*;

- ² *Type:* Alloc::const_pointer if the *qualified-id* Alloc::const_pointer is valid and denotes a type (17.8.2); otherwise, pointer_traits<pointer>::rebind<const value_type>.

using void_pointer = *see below*;

- ³ *Type:* Alloc::void_pointer if the *qualified-id* Alloc::void_pointer is valid and denotes a type (17.8.2); otherwise, pointer_traits<pointer>::rebind<void>.

```

using const_void_pointer = see below;
4   Type: Alloc::const_void_pointer if the qualified-id Alloc::const_void_pointer is valid and de-
    notes a type (17.8.2); otherwise, pointer_traits<pointer>::rebind<const void>.

using difference_type = see below;
5   Type: Alloc::difference_type if the qualified-id Alloc::difference_type is valid and denotes a
    type (17.8.2); otherwise, pointer_traits<pointer>::difference_type.

using size_type = see below;
6   Type: Alloc::size_type if the qualified-id Alloc::size_type is valid and denotes a type (17.8.2);
    otherwise, make_unsigned_t<difference_type>.

using propagate_on_container_copy_assignment = see below;
7   Type: Alloc::propagate_on_container_copy_assignment if the qualified-id Alloc::propagate_-
    on_container_copy_assignment is valid and denotes a type (17.8.2); otherwise false_type.

using propagate_on_container_move_assignment = see below;
8   Type: Alloc::propagate_on_container_move_assignment if the qualified-id Alloc::propagate_-
    on_container_move_assignment is valid and denotes a type (17.8.2); otherwise false_type.

using propagate_on_container_swap = see below;
9   Type: Alloc::propagate_on_container_swap if the qualified-id Alloc::propagate_on_container_-
    swap is valid and denotes a type (17.8.2); otherwise false_type.

using is_always_equal = see below;
10  Type: Alloc::is_always_equal if the qualified-id Alloc::is_always_equal is valid and denotes a
    type (17.8.2); otherwise is_empty<Alloc>::type.

template <class T> using rebind_alloc = see below;
11  Alias template: Alloc::rebind<T>::other if the qualified-id Alloc::rebind<T>::other is valid and
    denotes a type (17.8.2); otherwise, Alloc<T, Args> if Alloc is a class template instantiation of the
    form Alloc<U, Args>, where Args is zero or more type arguments; otherwise, the instantiation of
    rebind_alloc is ill-formed.

```

23.10.8.2 Allocator traits static member functions

[allocator.traits.members]

```

static pointer allocate(Alloc& a, size_type n);
1   Returns: a.allocate(n).

static pointer allocate(Alloc& a, size_type n, const_void_pointer hint);
2   Returns: a.allocate(n, hint) if that expression is well-formed; otherwise, a.allocate(n).

static void deallocate(Alloc& a, pointer p, size_type n);
3   Effects: Calls a.deallocate(p, n).
4   Throws: Nothing.

template <class T, class... Args>
    static void construct(Alloc& a, T* p, Args&&... args);
5   Effects: Calls a.construct(p, std::forward<Args>(args)...) if that call is well-formed; otherwise,
    invokes ::new (static_cast<void*>(p)) T(std::forward<Args>(args)...).

```

```

template <class T>
    static void destroy(Alloc& a, T* p);
6     Effects: Calls a.destroy(p) if that call is well-formed; otherwise, invokes p->~T().

    static size_type max_size(const Alloc& a) noexcept;
7     Returns: a.max_size() if that expression is well-formed; otherwise, numeric_limits<size_type>::max()/sizeof(value_type).

    static Alloc select_on_container_copy_construction(const Alloc& rhs);
8     Returns: rhs.select_on_container_copy_construction() if that expression is well-formed; otherwise, rhs.

```

23.10.9 The default allocator

[default.allocator]

- 1 All specializations of the default allocator satisfy the allocator completeness requirements (20.5.3.5.1).

```

namespace std {
    template <class T> class allocator {
    public:
        using value_type      = T;
        using propagate_on_container_move_assignment = true_type;
        using is_always_equal = true_type;

        allocator() noexcept;
        allocator(const allocator&) noexcept;
        template <class U> allocator(const allocator<U>&) noexcept;
        ~allocator();

        T* allocate(size_t n);
        void deallocate(T* p, size_t n);
    };
}

```

23.10.9.1 allocator members

[allocator.members]

- 1 Except for the destructor, member functions of the default allocator shall not introduce data races (4.7) as a result of concurrent calls to those member functions from different threads. Calls to these functions that allocate or deallocate a particular unit of storage shall occur in a single total order, and each such deallocation call shall happen before the next allocation (if any) in this order.

```
T* allocate(size_t n);
```

- 2 *Returns:* A pointer to the initial element of an array of storage of size `n * sizeof(T)`, aligned appropriately for objects of type `T`.
- 3 *Remarks:* the storage is obtained by calling `::operator new` (21.6.2), but it is unspecified when or how often this function is called.
- 4 *Throws:* `bad_alloc` if the storage cannot be obtained.

```
void deallocate(T* p, size_t n);
```

- 5 *Requires:* `p` shall be a pointer value obtained from `allocate()`. `n` shall equal the value passed as the first argument to the invocation of `allocate` which returned `p`.
- 6 *Effects:* Deallocates the storage referenced by `p`.
- 7 *Remarks:* Uses `::operator delete` (21.6.2), but it is unspecified when this function is called.

23.10.9.2 allocator globals**[allocator.globals]**

```
template <class T, class U>
    bool operator==(const allocator<T>&, const allocator<U>&) noexcept;
```

1 *Returns:* true.

```
template <class T, class U>
    bool operator!=(const allocator<T>&, const allocator<U>&) noexcept;
```

2 *Returns:* false.

23.10.10 Specialized algorithms**[specialized.algorithms]**

1 Throughout this subclause, the names of template parameters are used to express type requirements.

- (1.1) — If an algorithm's template parameter is named **InputIterator**, the template argument shall satisfy the requirements of an input iterator (27.2.3).
- (1.2) — If an algorithm's template parameter is named **ForwardIterator**, the template argument shall satisfy the requirements of a forward iterator (27.2.5), and is required to have the property that no exceptions are thrown from increment, assignment, comparison, or indirection through valid iterators.

Unless otherwise specified, if an exception is thrown in the following algorithms there are no effects.

23.10.10.1 addressof**[specialized.addressof]**

```
template <class T> constexpr T* addressof(T& r) noexcept;
```

1 *Returns:* The actual address of the object or function referenced by **r**, even in the presence of an overloaded **operator&**.

2 *Remarks:* An expression **addressof(E)** is a constant subexpression (20.3.6) if **E** is an lvalue constant subexpression.

23.10.10.2 uninitialized_default_construct**[uninitialized.construct.default]**

```
template <class ForwardIterator>
    void uninitialized_default_construct(ForwardIterator first, ForwardIterator last);
```

1 *Effects:* Equivalent to:

```
    for (; first != last; ++first)
        ::new (static_cast<void*>(addressof(*first)))
            typename iterator_traits<ForwardIterator>::value_type;
```

```
template <class ForwardIterator, class Size>
    ForwardIterator uninitialized_default_construct_n(ForwardIterator first, Size n);
```

2 *Effects:* Equivalent to:

```
    for (; n>0; (void)++first, --n)
        ::new (static_cast<void*>(addressof(*first)))
            typename iterator_traits<ForwardIterator>::value_type;
    return first;
```

23.10.10.3 uninitialized_value_construct**[uninitialized.construct.value]**

```
template <class ForwardIterator>
    void uninitialized_value_construct(ForwardIterator first, ForwardIterator last);
```

1 *Effects:* Equivalent to:

```
    for (; first != last; ++first)
```

```

::new (static_cast<void*>(addressof(*first)))
    typename iterator_traits<ForwardIterator>::value_type();

```

```

template <class ForwardIterator, class Size>
ForwardIterator uninitialized_value_construct_n(ForwardIterator first, Size n);

```

2 *Effects:* Equivalent to:

```

    for (; n>0; (void)++first, --n)
        ::new (static_cast<void*>(addressof(*first)))
            typename iterator_traits<ForwardIterator>::value_type();
    return first;

```

23.10.10.4 uninitialized_copy

[uninitialized.copy]

```

template <class InputIterator, class ForwardIterator>
ForwardIterator uninitialized_copy(InputIterator first, InputIterator last,
                                ForwardIterator result);

```

1 *Effects:* As if by:

```

    for (; first != last; ++result, (void) ++first)
        ::new (static_cast<void*>(addressof(*result)))
            typename iterator_traits<ForwardIterator>::value_type(*first);

```

2 *Returns:* result.

```

template <class InputIterator, class Size, class ForwardIterator>
ForwardIterator uninitialized_copy_n(InputIterator first, Size n,
                                   ForwardIterator result);

```

3 *Effects:* As if by:

```

    for ( ; n > 0; ++result, (void) ++first, --n) {
        ::new (static_cast<void*>(addressof(*result)))
            typename iterator_traits<ForwardIterator>::value_type(*first);
    }

```

4 *Returns:* result.

23.10.10.5 uninitialized_move

[uninitialized.move]

```

template <class InputIterator, class ForwardIterator>
ForwardIterator uninitialized_move(InputIterator first, InputIterator last,
                                 ForwardIterator result);

```

1 *Effects:* Equivalent to:

```

    for (; first != last; (void)++result, ++first)
        ::new (static_cast<void*>(addressof(*result)))
            typename iterator_traits<ForwardIterator>::value_type(std::move(*first));
    return result;

```

2 *Remarks:* If an exception is thrown, some objects in the range [first, last) are left in a valid but unspecified state.

```

template <class InputIterator, class Size, class ForwardIterator>
pair<InputIterator, ForwardIterator>
uninitialized_move_n(InputIterator first, Size n, ForwardIterator result);

```

3 *Effects:* Equivalent to:

```

    for (; n > 0; ++result, (void) ++first, --n)
        ::new (static_cast<void*>(addressof(*result)))

```

```

        typename iterator_traits<ForwardIterator>::value_type(std::move(*first));
    return {first,result};

```

- 4 *Remarks:* If an exception is thrown, some objects in the range `[first, std::next(first,n))` are left in a valid but unspecified state.

23.10.10.6 uninitialized_fill [uninitialized.fill]

```

template <class ForwardIterator, class T>
    void uninitialized_fill(ForwardIterator first, ForwardIterator last,
                           const T& x);

```

- 1 *Effects:* As if by:

```

    for (; first != last; ++first)
        ::new (static_cast<void*>(addressof(*first)))
            typename iterator_traits<ForwardIterator>::value_type(x);

```

```

template <class ForwardIterator, class Size, class T>
    ForwardIterator uninitialized_fill_n(ForwardIterator first, Size n, const T& x);

```

- 2 *Effects:* As if by:

```

    for (; n--; ++first)
        ::new (static_cast<void*>(addressof(*first)))
            typename iterator_traits<ForwardIterator>::value_type(x);
    return first;

```

23.10.10.7 destroy [specialized.destroy]

```

template <class T>
    void destroy_at(T* location);

```

- 1 *Effects:* Equivalent to:

```

    location->~T();

```

```

template <class ForwardIterator>
    void destroy(ForwardIterator first, ForwardIterator last);

```

- 2 *Effects:* Equivalent to:

```

    for (; first!=last; ++first)
        destroy_at(addressof(*first));

```

```

template <class ForwardIterator, class Size>
    ForwardIterator destroy_n(ForwardIterator first, Size n);

```

- 3 *Effects:* Equivalent to:

```

    for (; n > 0; (void)++first, --n)
        destroy_at(addressof(*first));
    return first;

```

23.10.11 C library memory allocation [c.malloc]

- 1 [*Note:* The header `<stdlib.h>` (21.2.2) declares the functions described in this subclause. — *end note*]

```

void* aligned_alloc(size_t alignment, size_t size);
void* calloc(size_t nmemb, size_t size);
void* malloc(size_t size);
void* realloc(void* ptr, size_t size);

```

- 2 *Effects:* These functions have the semantics specified in the C standard library.

- 3 *Remarks:* These functions do not attempt to allocate storage by calling `::operator new()` (21.6).
- 4 Storage allocated directly with these functions is implicitly declared reachable (see 6.7.4.3) on allocation, ceases to be declared reachable on deallocation, and need not cease to be declared reachable as the result of an `undecare_reachable()` call. [*Note:* This allows existing C libraries to remain unaffected by restrictions on pointers that are not safely derived, at the expense of providing far fewer garbage collection and leak detection options for `malloc()`-allocated objects. It also allows `malloc()` to be implemented with a separate allocation arena, bypassing the normal `declare_reachable()` implementation. The above functions should never intentionally be used as a replacement for `declare_reachable()`, and newly written code is strongly encouraged to treat memory allocated with these functions as though it were allocated with `operator new`. — *end note*]

```
void free(void* ptr);
```

- 5 *Effects:* This function has the semantics specified in the C standard library.
- 6 *Remarks:* This function does not attempt to deallocate storage by calling `::operator delete()`.
- SEE ALSO: ISO C 7.22.3.

23.11 Smart pointers

[smartptr]

23.11.1 Class template `unique_ptr`

[unique.ptr]

- 1 A *unique pointer* is an object that owns another object and manages that other object through a pointer. More precisely, a unique pointer is an object u that stores a pointer to a second object p and will dispose of p when u is itself destroyed (e.g., when leaving block scope (9.7)). In this context, u is said to *own* p .
- 2 The mechanism by which u disposes of p is known as p 's associated *deleter*, a function object whose correct invocation results in p 's appropriate disposition (typically its deletion).
- 3 Let the notation $u.p$ denote the pointer stored by u , and let $u.d$ denote the associated deleter. Upon request, u can *reset* (replace) $u.p$ and $u.d$ with another pointer and deleter, but must properly dispose of its owned object via the associated deleter before such replacement is considered completed.
- 4 Additionally, u can, upon request, *transfer ownership* to another unique pointer $u2$. Upon completion of such a transfer, the following postconditions hold:
- (4.1) — $u2.p$ is equal to the pre-transfer $u.p$,
- (4.2) — $u.p$ is equal to `nullptr`, and
- (4.3) — if the pre-transfer $u.d$ maintained state, such state has been transferred to $u2.d$.

As in the case of a reset, $u2$ must properly dispose of its pre-transfer owned object via the pre-transfer associated deleter before the ownership transfer is considered complete. [*Note:* A deleter's state need never be copied, only moved or swapped as ownership is transferred. — *end note*]

- 5 Each object of a type U instantiated from the `unique_ptr` template specified in this subclause has the strict ownership semantics, specified above, of a unique pointer. In partial satisfaction of these semantics, each such U is `MoveConstructible` and `MoveAssignable`, but is not `CopyConstructible` nor `CopyAssignable`. The template parameter T of `unique_ptr` may be an incomplete type.
- 6 [*Note:* The uses of `unique_ptr` include providing exception safety for dynamically allocated memory, passing ownership of dynamically allocated memory to a function, and returning dynamically allocated memory from a function. — *end note*]

```
namespace std {
    template<class T> struct default_delete;
    template<class T> struct default_delete<T[]>;

    template<class T, class D = default_delete<T>> class unique_ptr;
```



```

template<class T, class D> class unique_ptr<T[], D>;

template<class T, class... Args> unique_ptr<T> make_unique(Args&&... args);
template<class T> unique_ptr<T> make_unique(size_t n);
template<class T, class... Args> unspecified make_unique(Args&&...) = delete;

template<class T, class D> void swap(unique_ptr<T, D>& x, unique_ptr<T, D>& y) noexcept;

template<class T1, class D1, class T2, class D2>
    bool operator==(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template<class T1, class D1, class T2, class D2>
    bool operator!=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template<class T1, class D1, class T2, class D2>
    bool operator<(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template<class T1, class D1, class T2, class D2>
    bool operator<=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template<class T1, class D1, class T2, class D2>
    bool operator>(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
template<class T1, class D1, class T2, class D2>
    bool operator>=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);

template <class T, class D>
    bool operator==(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator==(nullptr_t, const unique_ptr<T, D>& y) noexcept;
template <class T, class D>
    bool operator!=(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator!=(nullptr_t, const unique_ptr<T, D>& y) noexcept;
template <class T, class D>
    bool operator<(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator<=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<=(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator>(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>(nullptr_t, const unique_ptr<T, D>& y);
template <class T, class D>
    bool operator>=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>=(nullptr_t, const unique_ptr<T, D>& y);
}

```

23.11.1.1 Default deleters

[unique.ptr.dltr]

23.11.1.1.1 In general

[unique.ptr.dltr.general]

- ¹ The class template `default_delete` serves as the default deleter (destruction policy) for the class template `unique_ptr`.
- ² The template parameter `T` of `default_delete` may be an incomplete type.

23.11.1.1.2 default_delete

[unique.ptr.dltr.dflt]

```

namespace std {
    template <class T> struct default_delete {
        constexpr default_delete() noexcept = default;
        template <class U> default_delete(const default_delete<U>&) noexcept;
        void operator()(T*) const;
    };
}

```

```

template <class U> default_delete(const default_delete<U>& other) noexcept;

```

- 1 *Effects:* Constructs a `default_delete` object from another `default_delete<U>` object.
- 2 *Remarks:* This constructor shall not participate in overload resolution unless `U*` is implicitly convertible to `T*`.

```

void operator()(T* ptr) const;

```

- 3 *Effects:* Calls `delete` on `ptr`.
- 4 *Remarks:* If `T` is an incomplete type, the program is ill-formed.

23.11.1.1.3 default_delete<T[]>

[unique.ptr.dltr.dflt1]

```

namespace std {
    template <class T> struct default_delete<T[]> {
        constexpr default_delete() noexcept = default;
        template <class U> default_delete(const default_delete<U[]>&) noexcept;
        template <class U> void operator()(U* ptr) const;
    };
}

```

```

template <class U> default_delete(const default_delete<U[]>& other) noexcept;

```

- 1 *Effects:* constructs a `default_delete` object from another `default_delete<U[]>` object.
- 2 *Remarks:* This constructor shall not participate in overload resolution unless `U(*) []` is convertible to `T(*) []`.

```

template <class U> void operator()(U* ptr) const;

```

- 3 *Effects:* Calls `delete[]` on `ptr`.
- 4 *Remarks:* If `U` is an incomplete type, the program is ill-formed. This function shall not participate in overload resolution unless `U(*) []` is convertible to `T(*) []`.

23.11.1.2 unique_ptr for single objects

[unique.ptr.single]

```

namespace std {
    template <class T, class D = default_delete<T>> class unique_ptr {
    public:
        using pointer      = see below;
        using element_type = T;
        using deleter_type = D;

        // 23.11.1.2.1, constructors
        constexpr unique_ptr() noexcept;
        explicit unique_ptr(pointer p) noexcept;
        unique_ptr(pointer p, see below d1) noexcept;
        unique_ptr(pointer p, see below d2) noexcept;
        unique_ptr(unique_ptr&& u) noexcept;
    };
}

```

```

constexpr unique_ptr(nullptr_t) noexcept;
template <class U, class E>
    unique_ptr(unique_ptr<U, E>&& u) noexcept;

// 23.11.1.2.2, destructor
~unique_ptr();

// 23.11.1.2.3, assignment
unique_ptr& operator=(unique_ptr&& u) noexcept;
template <class U, class E> unique_ptr& operator=(unique_ptr<U, E>&& u) noexcept;
unique_ptr& operator=(nullptr_t) noexcept;

// 23.11.1.2.4, observers
add_lvalue_reference_t<T> operator*() const;
pointer operator->() const noexcept;
pointer get() const noexcept;
deleter_type& get_deleter() noexcept;
const deleter_type& get_deleter() const noexcept;
explicit operator bool() const noexcept;

// 23.11.1.2.5, modifiers
pointer release() noexcept;
void reset(pointer p = pointer()) noexcept;
void swap(unique_ptr& u) noexcept;

// disable copy from lvalue
unique_ptr(const unique_ptr&) = delete;
unique_ptr& operator=(const unique_ptr&) = delete;
};
}

```

- 1 The default type for the template parameter D is `default_delete`. A client-supplied template argument D shall be a function object type (23.14), lvalue reference to function, or lvalue reference to function object type for which, given a value `d` of type D and a value `ptr` of type `unique_ptr<T, D>::pointer`, the expression `d(ptr)` is valid and has the effect of disposing of the pointer as appropriate for that deleter.
- 2 If the deleter's type D is not a reference type, D shall satisfy the requirements of `Destructible` (Table 27).
- 3 If the *qualified-id* `remove_reference_t<D>::pointer` is valid and denotes a type (17.8.2), then `unique_ptr<T, D>::pointer` shall be a synonym for `remove_reference_t<D>::pointer`. Otherwise `unique_ptr<T, D>::pointer` shall be a synonym for `element_type*`. The type `unique_ptr<T, D>::pointer` shall satisfy the requirements of `NullablePointer` (20.5.3.3).
- 4 [Example: Given an allocator type X (20.5.3.5) and letting A be a synonym for `allocator_traits<X>`, the types `A::pointer`, `A::const_pointer`, `A::void_pointer`, and `A::const_void_pointer` may be used as `unique_ptr<T, D>::pointer`. — end example]

23.11.1.2.1 `unique_ptr` constructors

[`unique_ptr.single.ctor`]

```

constexpr unique_ptr() noexcept;
constexpr unique_ptr(nullptr_t) noexcept;

```

- 1 *Requires:* D shall satisfy the requirements of `DefaultConstructible` (Table 22), and that construction shall not throw an exception.
- 2 *Effects:* Constructs a `unique_ptr` object that owns nothing, value-initializing the stored pointer and the stored deleter.
- 3 *Postconditions:* `get() == nullptr.get_deleter()` returns a reference to the stored deleter.

4 *Remarks:* If `is_pointer_v<deleter_type>` is true or `is_default_constructible_v<deleter_type>` is false, this constructor shall not participate in overload resolution.

```
explicit unique_ptr(pointer p) noexcept;
```

5 *Requires:* D shall satisfy the requirements of `DefaultConstructible` (Table 22), and that construction shall not throw an exception.

6 *Effects:* Constructs a `unique_ptr` which owns p, initializing the stored pointer with p and value-initializing the stored deleter.

7 *Postconditions:* `get() == p`. `get_deleter()` returns a reference to the stored deleter.

8 *Remarks:* If `is_pointer_v<deleter_type>` is true or `is_default_constructible_v<deleter_type>` is false, this constructor shall not participate in overload resolution. If class template argument deduction (16.3.1.8) would select the function template corresponding to this constructor, then the program is ill-formed.

```
unique_ptr(pointer p, see below d1) noexcept;
```

```
unique_ptr(pointer p, see below d2) noexcept;
```

9 The signature of these constructors depends upon whether D is a reference type. If D is a non-reference type A, then the signatures are:

```
unique_ptr(pointer p, const A& d) noexcept;
```

```
unique_ptr(pointer p, A&& d) noexcept;
```

10 If D is an lvalue reference type A&, then the signatures are:

```
unique_ptr(pointer p, A& d) noexcept;
```

```
unique_ptr(pointer p, A&& d) = delete;
```

11 If D is an lvalue reference type `const A&`, then the signatures are:

```
unique_ptr(pointer p, const A& d) noexcept;
```

```
unique_ptr(pointer p, const A&& d) = delete;
```

12 *Effects:* Constructs a `unique_ptr` object which owns p, initializing the stored pointer with p and initializing the deleter from `std::forward<decltype(d)>(d)`.

13 *Remarks:* These constructors shall not participate in overload resolution unless `is_constructible_v<D, decltype(d)>` is true.

14 *Postconditions:* `get() == p`. `get_deleter()` returns a reference to the stored deleter. If D is a reference type then `get_deleter()` returns a reference to the lvalue d.

15 *Remarks:* If class template argument deduction (16.3.1.8) would select a function template corresponding to either of these constructors, then the program is ill-formed.

16 [*Example:*

```
D d;
unique_ptr<int, D> p1(new int, D());           // D must be MoveConstructible
unique_ptr<int, D> p2(new int, d);             // D must be CopyConstructible
unique_ptr<int, D&> p3(new int, d);             // p3 holds a reference to d
unique_ptr<int, const D&> p4(new int, D());     // error: rvalue deleter object combined
                                              // with reference deleter type
```

— end example]

```
unique_ptr(unique_ptr&& u) noexcept;
```

17 *Requires:* If D is not a reference type, D shall satisfy the requirements of `MoveConstructible` (Table 23). Construction of the deleter from an rvalue of type D shall not throw an exception.

18 *Effects:* Constructs a `unique_ptr` by transferring ownership from `u` to `*this`. If `D` is a reference type, this deleter is copy constructed from `u`'s deleter; otherwise, this deleter is move constructed from `u`'s deleter. [*Note:* The deleter constructor can be implemented with `std::forward<D>`. — *end note*]

19 *Postconditions:* `get()` yields the value `u.get()` yielded before the construction. `get_deleter()` returns a reference to the stored deleter that was constructed from `u.get_deleter()`. If `D` is a reference type then `get_deleter()` and `u.get_deleter()` both reference the same lvalue deleter.

```
template <class U, class E> unique_ptr(unique_ptr<U, E>&& u) noexcept;
```

20 *Requires:* If `E` is not a reference type, construction of the deleter from an rvalue of type `E` shall be well formed and shall not throw an exception. Otherwise, `E` is a reference type and construction of the deleter from an lvalue of type `E` shall be well formed and shall not throw an exception.

21 *Remarks:* This constructor shall not participate in overload resolution unless:

- (21.1) — `unique_ptr<U, E>::pointer` is implicitly convertible to `pointer`,
- (21.2) — `U` is not an array type, and
- (21.3) — either `D` is a reference type and `E` is the same type as `D`, or `D` is not a reference type and `E` is implicitly convertible to `D`.

22 *Effects:* Constructs a `unique_ptr` by transferring ownership from `u` to `*this`. If `E` is a reference type, this deleter is copy constructed from `u`'s deleter; otherwise, this deleter is move constructed from `u`'s deleter. [*Note:* The deleter constructor can be implemented with `std::forward<E>`. — *end note*]

23 *Postconditions:* `get()` yields the value `u.get()` yielded before the construction. `get_deleter()` returns a reference to the stored deleter that was constructed from `u.get_deleter()`.

23.11.1.2.2 `unique_ptr` destructor [unique.ptr.single.dtor]

```
~unique_ptr();
```

1 *Requires:* The expression `get_deleter()(get())` shall be well formed, shall have well-defined behavior, and shall not throw exceptions. [*Note:* The use of `default_delete` requires `T` to be a complete type. — *end note*]

2 *Effects:* If `get() == nullptr` there are no effects. Otherwise `get_deleter()(get())`.

23.11.1.2.3 `unique_ptr` assignment [unique.ptr.single.asgn]

```
unique_ptr& operator=(unique_ptr&& u) noexcept;
```

1 *Requires:* If `D` is not a reference type, `D` shall satisfy the requirements of `MoveAssignable` (Table 25) and assignment of the deleter from an rvalue of type `D` shall not throw an exception. Otherwise, `D` is a reference type; `remove_reference_t<D>` shall satisfy the `CopyAssignable` requirements and assignment of the deleter from an lvalue of type `D` shall not throw an exception.

2 *Effects:* Transfers ownership from `u` to `*this` as if by calling `reset(u.release())` followed by `get_deleter() = std::forward<D>(u.get_deleter())`.

3 *Returns:* `*this`.

```
template <class U, class E> unique_ptr& operator=(unique_ptr<U, E>&& u) noexcept;
```

4 *Requires:* If `E` is not a reference type, assignment of the deleter from an rvalue of type `E` shall be well-formed and shall not throw an exception. Otherwise, `E` is a reference type and assignment of the deleter from an lvalue of type `E` shall be well-formed and shall not throw an exception.

5 *Remarks:* This operator shall not participate in overload resolution unless:

- (5.1) — `unique_ptr<U, E>::pointer` is implicitly convertible to `pointer`, and

- (5.2) — U is not an array type, and
 (5.3) — `is_assignable_v<D&, E&&>` is true.

6 *Effects:* Transfers ownership from `u` to `*this` as if by calling `reset(u.release())` followed by `get_deleter() = std::forward<E>(u.get_deleter())`.

7 *Returns:* `*this`.

`unique_ptr& operator=(nullptr_t) noexcept;`

8 *Effects:* As if by `reset()`.

9 *Postconditions:* `get() == nullptr`.

10 *Returns:* `*this`.

23.11.1.2.4 `unique_ptr` observers

[`unique_ptr.single.observers`]

`add_lvalue_reference_t<T> operator*() const;`

1 *Requires:* `get() != nullptr`.

2 *Returns:* `*get()`.

`pointer operator->() const noexcept;`

3 *Requires:* `get() != nullptr`.

4 *Returns:* `get()`.

5 [*Note:* The use of this function typically requires that `T` be a complete type. — *end note*]

`pointer get() const noexcept;`

6 *Returns:* The stored pointer.

`deleter_type& get_deleter() noexcept;`

`const deleter_type& get_deleter() const noexcept;`

7 *Returns:* A reference to the stored deleter.

`explicit operator bool() const noexcept;`

8 *Returns:* `get() != nullptr`.

23.11.1.2.5 `unique_ptr` modifiers

[`unique_ptr.single.modifiers`]

`pointer release() noexcept;`

1 *Postconditions:* `get() == nullptr`.

2 *Returns:* The value `get()` had at the start of the call to `release`.

`void reset(pointer p = pointer()) noexcept;`

3 *Requires:* The expression `get_deleter()(get())` shall be well formed, shall have well-defined behavior, and shall not throw exceptions.

4 *Effects:* Assigns `p` to the stored pointer, and then if and only if the old value of the stored pointer, `old_p`, was not equal to `nullptr`, calls `get_deleter()(old_p)`. [*Note:* The order of these operations is significant because the call to `get_deleter()` may destroy `*this`. — *end note*]

5 *Postconditions:* `get() == p`. [*Note:* The postcondition does not hold if the call to `get_deleter()` destroys `*this` since `this->get()` is no longer a valid expression. — *end note*]

`void swap(unique_ptr& u) noexcept;`

6 *Requires:* `get_deleter()` shall be swappable (20.5.3.2) and shall not throw an exception under `swap`.

7 *Effects:* Invokes `swap` on the stored pointers and on the stored deleters of `*this` and `u`.

23.11.1.3 `unique_ptr` for array objects with a runtime length [unique_ptr.runtime]

```
namespace std {
    template <class T, class D> class unique_ptr<T[], D> {
    public:
        using pointer          = see below;
        using element_type     = T;
        using deleter_type     = D;

        // 23.11.1.3.1, constructors
        constexpr unique_ptr() noexcept;
        template <class U> explicit unique_ptr(U p) noexcept;
        template <class U> unique_ptr(U p, see below d) noexcept;
        template <class U> unique_ptr(U p, see below d) noexcept;
        unique_ptr(unique_ptr&& u) noexcept;
        template <class U, class E>
            unique_ptr(unique_ptr<U, E>&& u) noexcept;
        constexpr unique_ptr(nullptr_t) noexcept;

        // destructor
        ~unique_ptr();

        // assignment
        unique_ptr& operator=(unique_ptr&& u) noexcept;
        template <class U, class E>
            unique_ptr& operator=(unique_ptr<U, E>&& u) noexcept;
        unique_ptr& operator=(nullptr_t) noexcept;

        // 23.11.1.3.3, observers
        T& operator[](size_t i) const;
        pointer get() const noexcept;
        deleter_type& get_deleter() noexcept;
        const deleter_type& get_deleter() const noexcept;
        explicit operator bool() const noexcept;

        // 23.11.1.3.4, modifiers
        pointer release() noexcept;
        template <class U> void reset(U p) noexcept;
        void reset(nullptr_t = nullptr) noexcept;
        void swap(unique_ptr& u) noexcept;

        // disable copy from lvalue
        unique_ptr(const unique_ptr&) = delete;
        unique_ptr& operator=(const unique_ptr&) = delete;
    };
}
```

¹ A specialization for array types is provided with a slightly altered interface.

- (1.1) — Conversions between different types of `unique_ptr<T[], D>` that would be disallowed for the corresponding pointer-to-array types, and conversions to or from the non-array forms of `unique_ptr`, produce an ill-formed program.
- (1.2) — Pointers to types derived from `T` are rejected by the constructors, and by `reset`.

(1.3) — The observers `operator*` and `operator->` are not provided.

(1.4) — The indexing observer `operator[]` is provided.

(1.5) — The default deleter will call `delete[]`.

2 Descriptions are provided below only for members that differ from the primary template.

3 The template argument `T` shall be a complete type.

23.11.1.3.1 `unique_ptr` constructors

[`unique_ptr.runtime.ctor`]

```
template <class U> explicit unique_ptr(U p) noexcept;
```

1 This constructor behaves the same as the constructor in the primary template that takes a single parameter of type `pointer` except that it additionally shall not participate in overload resolution unless

(1.1) — `U` is the same type as `pointer`, or

(1.2) — `pointer` is the same type as `element_type*`, `U` is a pointer type `V*`, and `V(*) []` is convertible to `element_type(*) []`.

```
template <class U> unique_ptr(U p, see below d) noexcept;
```

```
template <class U> unique_ptr(U p, see below d) noexcept;
```

2 These constructors behave the same as the constructors in the primary template that take a parameter of type `pointer` and a second parameter except that they shall not participate in overload resolution unless either

(2.1) — `U` is the same type as `pointer`,

(2.2) — `U` is `nullptr_t`, or

(2.3) — `pointer` is the same type as `element_type*`, `U` is a pointer type `V*`, and `V(*) []` is convertible to `element_type(*) []`.

```
template <class U, class E>
```

```
    unique_ptr(unique_ptr<U, E>&& u) noexcept;
```

3 This constructor behaves the same as in the primary template, except that it shall not participate in overload resolution unless all of the following conditions hold, where `UP` is `unique_ptr<U, E>`:

(3.1) — `U` is an array type, and

(3.2) — `pointer` is the same type as `element_type*`, and

(3.3) — `UP::pointer` is the same type as `UP::element_type*`, and

(3.4) — `UP::element_type(*) []` is convertible to `element_type(*) []`, and

(3.5) — either `D` is a reference type and `E` is the same type as `D`, or `D` is not a reference type and `E` is implicitly convertible to `D`.

[*Note:* This replaces the overload-resolution specification of the primary template — *end note*]

23.11.1.3.2 `unique_ptr` assignment

[`unique_ptr.runtime.asgn`]

```
template <class U, class E>
```

```
    unique_ptr& operator=(unique_ptr<U, E>&& u) noexcept;
```

1 This operator behaves the same as in the primary template, except that it shall not participate in overload resolution unless all of the following conditions hold, where `UP` is `unique_ptr<U, E>`:

(1.1) — `U` is an array type, and

(1.2) — `pointer` is the same type as `element_type*`, and

- (1.3) — `UP::pointer` is the same type as `UP::element_type*`, and
- (1.4) — `UP::element_type(*) []` is convertible to `element_type(*) []`, and
- (1.5) — `is_assignable_v<D&, E&&>` is true.

[*Note*: This replaces the overload-resolution specification of the primary template — *end note*]

23.11.1.3.3 `unique_ptr` observers

[`unique_ptr.runtime.observers`]

`T& operator[] (size_t i) const;`

1 *Requires*: `i` < the number of elements in the array to which the stored pointer points.

2 *Returns*: `get() [i]`.

23.11.1.3.4 `unique_ptr` modifiers

[`unique_ptr.runtime.modifiers`]

`void reset(nullptr_t p = nullptr) noexcept;`

1 *Effects*: Equivalent to `reset(pointer())`.

`template <class U> void reset(U p) noexcept;`

2 This function behaves the same as the `reset` member of the primary template, except that it shall not participate in overload resolution unless either

- (2.1) — `U` is the same type as `pointer`, or
- (2.2) — `pointer` is the same type as `element_type*`, `U` is a pointer type `V*`, and `V(*) []` is convertible to `element_type(*) []`.

23.11.1.4 `unique_ptr` creation

[`unique_ptr.create`]

`template <class T, class... Args> unique_ptr<T> make_unique(Args&&... args);`

1 *Remarks*: This function shall not participate in overload resolution unless `T` is not an array.

2 *Returns*: `unique_ptr<T>(new T(std::forward<Args>(args)...))`.

`template <class T> unique_ptr<T> make_unique(size_t n);`

3 *Remarks*: This function shall not participate in overload resolution unless `T` is an array of unknown bound.

4 *Returns*: `unique_ptr<T>(new remove_extent_t<T>[n]())`.

`template <class T, class... Args> unspecified make_unique(Args&&...) = delete;`

5 *Remarks*: This function shall not participate in overload resolution unless `T` is an array of known bound.

23.11.1.5 `unique_ptr` specialized algorithms

[`unique_ptr.special`]

`template <class T, class D> void swap(unique_ptr<T, D>& x, unique_ptr<T, D>& y) noexcept;`

1 *Remarks*: This function shall not participate in overload resolution unless `is_swappable_v<D>` is true.

2 *Effects*: Calls `x.swap(y)`.

`template <class T1, class D1, class T2, class D2>`

`bool operator==(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);`

3 *Returns*: `x.get() == y.get()`.

`template <class T1, class D1, class T2, class D2>`

`bool operator!=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);`

4 *Returns:* `x.get() != y.get()`.

```
template <class T1, class D1, class T2, class D2>
    bool operator<(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
```

5 *Requires:* Let *CT* denote

```
    common_type_t<typename unique_ptr<T1, D1>::pointer,
                  typename unique_ptr<T2, D2>::pointer>
```

Then the specialization `less<CT>` shall be a function object type (23.14) that induces a strict weak ordering (28.7) on the pointer values.

6 *Returns:* `less<CT>()(x.get(), y.get())`.

7 *Remarks:* If `unique_ptr<T1, D1>::pointer` is not implicitly convertible to *CT* or `unique_ptr<T2, D2>::pointer` is not implicitly convertible to *CT*, the program is ill-formed.

```
template <class T1, class D1, class T2, class D2>
    bool operator<=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
```

8 *Returns:* `!(y < x)`.

```
template <class T1, class D1, class T2, class D2>
    bool operator>(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
```

9 *Returns:* `y < x`.

```
template <class T1, class D1, class T2, class D2>
    bool operator>=(const unique_ptr<T1, D1>& x, const unique_ptr<T2, D2>& y);
```

10 *Returns:* `!(x < y)`.

```
template <class T, class D>
    bool operator==(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator==(nullptr_t, const unique_ptr<T, D>& x) noexcept;
```

11 *Returns:* `!x`.

```
template <class T, class D>
    bool operator!=(const unique_ptr<T, D>& x, nullptr_t) noexcept;
template <class T, class D>
    bool operator!=(nullptr_t, const unique_ptr<T, D>& x) noexcept;
```

12 *Returns:* `(bool)x`.

```
template <class T, class D>
    bool operator<(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<(nullptr_t, const unique_ptr<T, D>& x);
```

13 *Requires:* The specialization `less<unique_ptr<T, D>::pointer>` shall be a function object type (23.14) that induces a strict weak ordering (28.7) on the pointer values.

14 *Returns:* The first function template returns `less<unique_ptr<T, D>::pointer>()(x.get(), nullptr)`. The second function template returns `less<unique_ptr<T, D>::pointer>()(nullptr, x.get())`.

```
template <class T, class D>
    bool operator>(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>(nullptr_t, const unique_ptr<T, D>& x);
```

- 15 *Returns:* The first function template returns `nullptr < x`. The second function template returns `x < nullptr`.

```
template <class T, class D>
    bool operator<=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator<=(nullptr_t, const unique_ptr<T, D>& x);
```

- 16 *Returns:* The first function template returns `!(nullptr < x)`. The second function template returns `!(x < nullptr)`.

```
template <class T, class D>
    bool operator>=(const unique_ptr<T, D>& x, nullptr_t);
template <class T, class D>
    bool operator>=(nullptr_t, const unique_ptr<T, D>& x);
```

- 17 *Returns:* The first function template returns `!(x < nullptr)`. The second function template returns `!(nullptr < x)`.

23.11.2 Shared-ownership pointers

[util.smartptr]

23.11.2.1 Class `bad_weak_ptr`

[util.smartptr.weak.bad]

```
namespace std {
    class bad_weak_ptr : public exception {
    public:
        bad_weak_ptr() noexcept;
    };
}
```

- 1 An exception of type `bad_weak_ptr` is thrown by the `shared_ptr` constructor taking a `weak_ptr`.

```
bad_weak_ptr() noexcept;
```

- 2 *Postconditions:* `what()` returns an implementation-defined NTBS.

23.11.2.2 Class template `shared_ptr`

[util.smartptr.shared]

- 1 The `shared_ptr` class template stores a pointer, usually obtained via `new`. `shared_ptr` implements semantics of shared ownership; the last remaining owner of the pointer is responsible for destroying the object, or otherwise releasing the resources associated with the stored pointer. A `shared_ptr` is said to be empty if it does not own a pointer.

```
namespace std {
    template<class T> class shared_ptr {
    public:
        using element_type = remove_extent_t<T>;
        using weak_type     = weak_ptr<T>;

        // 23.11.2.2.1, constructors
        constexpr shared_ptr() noexcept;
        template<class Y> explicit shared_ptr(Y* p);
        template<class Y, class D> shared_ptr(Y* p, D d);
        template<class Y, class D, class A> shared_ptr(Y* p, D d, A a);
        template <class D> shared_ptr(nullptr_t p, D d);
        template <class D, class A> shared_ptr(nullptr_t p, D d, A a);
        template<class Y> shared_ptr(const shared_ptr<Y>& r, element_type* p) noexcept;
        shared_ptr(const shared_ptr& r) noexcept;
        template<class Y> shared_ptr(const shared_ptr<Y>& r) noexcept;
        shared_ptr(shared_ptr&& r) noexcept;
```

```

template<class Y> shared_ptr(shared_ptr<Y>&& r) noexcept;
template<class Y> explicit shared_ptr(const weak_ptr<Y>& r);
template <class Y, class D> shared_ptr(unique_ptr<Y, D>&& r);
constexpr shared_ptr(nullptr_t) noexcept : shared_ptr() { }

// 23.11.2.2.2, destructor
~shared_ptr();

// 23.11.2.2.3, assignment
shared_ptr& operator=(const shared_ptr& r) noexcept;
template<class Y> shared_ptr& operator=(const shared_ptr<Y>& r) noexcept;
shared_ptr& operator=(shared_ptr&& r) noexcept;
template<class Y> shared_ptr& operator=(shared_ptr<Y>&& r) noexcept;
template <class Y, class D> shared_ptr& operator=(unique_ptr<Y, D>&& r);

// 23.11.2.2.4, modifiers
void swap(shared_ptr& r) noexcept;
void reset() noexcept;
template<class Y> void reset(Y* p);
template<class Y, class D> void reset(Y* p, D d);
template<class Y, class D, class A> void reset(Y* p, D d, A a);

// 23.11.2.2.5, observers
element_type* get() const noexcept;
T& operator*() const noexcept;
T* operator->() const noexcept;
element_type& operator[](ptrdiff_t i) const;
long use_count() const noexcept;
explicit operator bool() const noexcept;
template<class U> bool owner_before(const shared_ptr<U>& b) const noexcept;
template<class U> bool owner_before(const weak_ptr<U>& b) const noexcept;
};

template<class T> shared_ptr(weak_ptr<T>) -> shared_ptr<T>;
template<class T, class D> shared_ptr(unique_ptr<T, D>) -> shared_ptr<T>;

// 23.11.2.2.6, shared_ptr creation
template<class T, class... Args>
    shared_ptr<T> make_shared(Args&&... args);
template<class T, class A, class... Args>
    shared_ptr<T> allocate_shared(const A& a, Args&&... args);

// 23.11.2.2.7, shared_ptr comparisons
template<class T, class U>
    bool operator==(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator!=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator<(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator>(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator<=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
template<class T, class U>
    bool operator>=(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;

```

```

template <class T>
    bool operator==(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator==(nullptr_t, const shared_ptr<T>& b) noexcept;
template <class T>
    bool operator!=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator!=(nullptr_t, const shared_ptr<T>& b) noexcept;
template <class T>
    bool operator<(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator<(nullptr_t, const shared_ptr<T>& b) noexcept;
template <class T>
    bool operator<=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator<=(nullptr_t, const shared_ptr<T>& b) noexcept;
template <class T>
    bool operator>(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator>(nullptr_t, const shared_ptr<T>& b) noexcept;
template <class T>
    bool operator>=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator>=(nullptr_t, const shared_ptr<T>& b) noexcept;

// 23.11.2.2.8, shared_ptr specialized algorithms
template<class T>
    void swap(shared_ptr<T>& a, shared_ptr<T>& b) noexcept;

// 23.11.2.2.9, shared_ptr casts
template<class T, class U>
    shared_ptr<T> static_pointer_cast(const shared_ptr<U>& r) noexcept;
template<class T, class U>
    shared_ptr<T> dynamic_pointer_cast(const shared_ptr<U>& r) noexcept;
template<class T, class U>
    shared_ptr<T> const_pointer_cast(const shared_ptr<U>& r) noexcept;
template<class T, class U>
    shared_ptr<T> reinterpret_pointer_cast(const shared_ptr<U>& r) noexcept;

// 23.11.2.2.10, shared_ptr get_deleter
template<class D, class T>
    D* get_deleter(const shared_ptr<T>& p) noexcept;

// 23.11.2.2.11, shared_ptr I/O
template<class E, class T, class Y>
    basic_ostream<E, T>& operator<< (basic_ostream<E, T>& os, const shared_ptr<Y>& p);
}

```

- ² Specializations of `shared_ptr` shall be `CopyConstructible`, `CopyAssignable`, and `LessThanComparable`, allowing their use in standard containers. Specializations of `shared_ptr` shall be contextually convertible to `bool`, allowing their use in boolean expressions and declarations in conditions. The template parameter `T` of `shared_ptr` may be an incomplete type.

- ³ [Example:

```

    if (shared_ptr<X> px = dynamic_pointer_cast<X>(py)) {
        // do something with px
    }

```

— end example]

- 4 For purposes of determining the presence of a data race, member functions shall access and modify only the `shared_ptr` and `weak_ptr` objects themselves and not objects they refer to. Changes in `use_count()` do not reflect modifications that can introduce data races.
- 5 For the purposes of subclause 23.11.2, a pointer type `Y*` is said to be *compatible with* a pointer type `T*` when either `Y*` is convertible to `T*` or `Y` is `U[N]` and `T` is *cv* `U[]`.

23.11.2.2.1 `shared_ptr` constructors

[`util.smartptr.shared.const`]

- 1 In the constructor definitions below, enables `shared_from_this` with `p`, for a pointer `p` of type `Y*`, means that if `Y` has an unambiguous and accessible base class that is a specialization of `enable_shared_from_this` (23.11.2.5), then `remove_cv_t<Y>*` shall be implicitly convertible to `T*` and the constructor evaluates the statement:

```

    if (p != nullptr && p->weak_this.expired())
        p->weak_this = shared_ptr<remove_cv_t<Y>>(*this, const_cast<remove_cv_t<Y>*>(p));

```

The assignment to the `weak_this` member is not atomic and conflicts with any potentially concurrent access to the same object (4.7).

```
constexpr shared_ptr() noexcept;
```

- 2 *Effects:* Constructs an empty `shared_ptr` object.
- 3 *Postconditions:* `use_count() == 0` && `get() == nullptr`.

```
template<class Y> explicit shared_ptr(Y* p);
```

- 4 *Requires:* `Y` shall be a complete type. The expression `delete[] p`, when `T` is an array type, or `delete p`, when `T` is not an array type, shall have well-defined behavior, and shall not throw exceptions.
- 5 *Effects:* When `T` is not an array type, constructs a `shared_ptr` object that owns the pointer `p`. Otherwise, constructs a `shared_ptr` that owns `p` and a deleter of an unspecified type that calls `delete[] p`. When `T` is not an array type, enables `shared_from_this` with `p`. If an exception is thrown, `delete p` is called when `T` is not an array type, `delete[] p` otherwise.
- 6 *Postconditions:* `use_count() == 1` && `get() == p`.
- 7 *Throws:* `bad_alloc`, or an implementation-defined exception when a resource other than memory could not be obtained.
- 8 *Remarks:* When `T` is an array type, this constructor shall not participate in overload resolution unless the expression `delete[] p` is well-formed and either `T` is `U[N]` and `Y(*)[N]` is convertible to `T*`, or `T` is `U[]` and `Y(*)[]` is convertible to `T*`. When `T` is not an array type, this constructor shall not participate in overload resolution unless the expression `delete p` is well-formed and `Y*` is convertible to `T*`.

```

template<class Y, class D> shared_ptr(Y* p, D d);
template<class Y, class D, class A> shared_ptr(Y* p, D d, A a);
template<class D> shared_ptr(nullptr_t p, D d);
template<class D, class A> shared_ptr(nullptr_t p, D d, A a);

```

- 9 *Requires:* Construction of `d` and a deleter of type `D` initialized with `std::move(d)` shall not throw exceptions. The expression `d(p)` shall have well-defined behavior and shall not throw exceptions. `A` shall be an allocator (20.5.3.5).
- 10 *Effects:* Constructs a `shared_ptr` object that owns the object `p` and the deleter `d`. When `T` is not an

array type, the first and second constructors enable `shared_from_this` with `p`. The second and fourth constructors shall use a copy of `a` to allocate memory for internal use. If an exception is thrown, `d(p)` is called.

11 *Postconditions:* `use_count() == 1 && get() == p`.

12 *Throws:* `bad_alloc`, or an implementation-defined exception when a resource other than memory could not be obtained.

13 *Remarks:* When `T` is an array type, this constructor shall not participate in overload resolution unless `is_move_constructible_v<D>` is `true`, the expression `d(p)` is well-formed, and either `T` is `U[N]` and `Y(*)[N]` is convertible to `T*`, or `T` is `U[]` and `Y(*)[]` is convertible to `T*`. When `T` is not an array type, this constructor shall not participate in overload resolution unless `is_move_constructible_v<D>` is `true`, the expression `d(p)` is well-formed, and `Y*` is convertible to `T*`.

```
template<class Y> shared_ptr(const shared_ptr<Y>& r, element_type* p) noexcept;
```

14 *Effects:* Constructs a `shared_ptr` instance that stores `p` and shares ownership with `r`.

15 *Postconditions:* `get() == p && use_count() == r.use_count()`.

16 [*Note:* To avoid the possibility of a dangling pointer, the user of this constructor must ensure that `p` remains valid at least until the ownership group of `r` is destroyed. — *end note*]

17 [*Note:* This constructor allows creation of an empty `shared_ptr` instance with a non-null stored pointer. — *end note*]

```
shared_ptr(const shared_ptr& r) noexcept;
```

```
template<class Y> shared_ptr(const shared_ptr<Y>& r) noexcept;
```

18 *Remarks:* The second constructor shall not participate in overload resolution unless `Y*` is compatible with `T*`.

19 *Effects:* If `r` is empty, constructs an empty `shared_ptr` object; otherwise, constructs a `shared_ptr` object that shares ownership with `r`.

20 *Postconditions:* `get() == r.get() && use_count() == r.use_count()`.

```
shared_ptr(shared_ptr&& r) noexcept;
```

```
template<class Y> shared_ptr(shared_ptr<Y>&& r) noexcept;
```

21 *Remarks:* The second constructor shall not participate in overload resolution unless `Y*` is compatible with `T*`.

22 *Effects:* Move constructs a `shared_ptr` instance from `r`.

23 *Postconditions:* `*this` shall contain the old value of `r`. `r` shall be empty. `r.get() == nullptr`.

```
template<class Y> explicit shared_ptr(const weak_ptr<Y>& r);
```

24 *Effects:* Constructs a `shared_ptr` object that shares ownership with `r` and stores a copy of the pointer stored in `r`. If an exception is thrown, the constructor has no effect.

25 *Postconditions:* `use_count() == r.use_count()`.

26 *Throws:* `bad_weak_ptr` when `r.expired()`.

27 *Remarks:* This constructor shall not participate in overload resolution unless `Y*` is compatible with `T*`.

```
template <class Y, class D> shared_ptr(unique_ptr<Y, D>&& r);
```

28 *Remarks:* This constructor shall not participate in overload resolution unless `Y*` is compatible with `T*` and `unique_ptr<Y, D>::pointer` is convertible to `element_type*`.

29 *Effects:* If `r.get() == nullptr`, equivalent to `shared_ptr()`. Otherwise, if `D` is not a reference

type, equivalent to `shared_ptr(r.release(), r.get_deleter())`. Otherwise, equivalent to `shared_ptr(r.release(), ref(r.get_deleter()))`. If an exception is thrown, the constructor has no effect.

23.11.2.2.2 `shared_ptr` destructor [util.smartptr.shared.dest]

```
~shared_ptr();
```

1 *Effects:*

- (1.1) — If `*this` is empty or shares ownership with another `shared_ptr` instance (`use_count() > 1`), there are no side effects.
- (1.2) — Otherwise, if `*this` owns an object `p` and a deleter `d`, `d(p)` is called.
- (1.3) — Otherwise, `*this` owns a pointer `p`, and `delete p` is called.

2 [*Note:* Since the destruction of `*this` decreases the number of instances that share ownership with `*this` by one, after `*this` has been destroyed all `shared_ptr` instances that shared ownership with `*this` will report a `use_count()` that is one less than its previous value. — *end note*]

23.11.2.2.3 `shared_ptr` assignment [util.smartptr.shared.assign]

```
shared_ptr& operator=(const shared_ptr& r) noexcept;
template<class Y> shared_ptr& operator=(const shared_ptr<Y>& r) noexcept;
```

1 *Effects:* Equivalent to `shared_ptr(r).swap(*this)`.

2 *Returns:* `*this`.

3 [*Note:* The use count updates caused by the temporary object construction and destruction are not observable side effects, so the implementation may meet the effects (and the implied guarantees) via different means, without creating a temporary. In particular, in the example:

```
shared_ptr<int> p(new int);
shared_ptr<void> q(p);
p = p;
q = p;
```

both assignments may be no-ops. — *end note*]

```
shared_ptr& operator=(shared_ptr&& r) noexcept;
template<class Y> shared_ptr& operator=(shared_ptr<Y>&& r) noexcept;
```

4 *Effects:* Equivalent to `shared_ptr(std::move(r)).swap(*this)`.

5 *Returns:* `*this`.

```
template <class Y, class D> shared_ptr& operator=(unique_ptr<Y, D>&& r);
```

6 *Effects:* Equivalent to `shared_ptr(std::move(r)).swap(*this)`.

7 *Returns:* `*this`.

23.11.2.2.4 `shared_ptr` modifiers [util.smartptr.shared.mod]

```
void swap(shared_ptr& r) noexcept;
```

1 *Effects:* Exchanges the contents of `*this` and `r`.

```
void reset() noexcept;
```

2 *Effects:* Equivalent to `shared_ptr().swap(*this)`.

```
template<class Y> void reset(Y* p);
```

3 *Effects:* Equivalent to `shared_ptr(p).swap(*this)`.


```
template<class Y, class D> void reset(Y* p, D d);
```

4 *Effects:* Equivalent to `shared_ptr(p, d).swap(*this)`.

```
template<class Y, class D, class A> void reset(Y* p, D d, A a);
```

5 *Effects:* Equivalent to `shared_ptr(p, d, a).swap(*this)`.

23.11.2.2.5 `shared_ptr` observers

[util.smartptr.shared.obs]

```
element_type* get() const noexcept;
```

1 *Returns:* The stored pointer.

```
T& operator*() const noexcept;
```

2 *Requires:* `get() != 0`.

3 *Returns:* `*get()`.

4 *Remarks:* When T is an array type or *cv* void, it is unspecified whether this member function is declared. If it is declared, it is unspecified what its return type is, except that the declaration (although not necessarily the definition) of the function shall be well formed.

```
T* operator->() const noexcept;
```

5 *Requires:* `get() != 0`.

6 *Returns:* `get()`.

7 *Remarks:* When T is an array type, it is unspecified whether this member function is declared. If it is declared, it is unspecified what its return type is, except that the declaration (although not necessarily the definition) of the function shall be well formed.

```
element_type& operator[](ptrdiff_t i) const;
```

8 *Requires:* `get() != 0 && i >= 0`. If T is U[N], `i < N`.

9 *Returns:* `get()[i]`.

10 *Remarks:* When T is not an array type, it is unspecified whether this member function is declared. If it is declared, it is unspecified what its return type is, except that the declaration (although not necessarily the definition) of the function shall be well formed.

11 *Throws:* Nothing.

```
long use_count() const noexcept;
```

12 *Returns:* The number of `shared_ptr` objects, `*this` included, that share ownership with `*this`, or 0 when `*this` is empty.

13 *Synchronization:* None.

14 [*Note:* `get() == nullptr` does not imply a specific return value of `use_count()`. — end note]

15 [*Note:* `weak_ptr<T>::lock()` can affect the return value of `use_count()`. — end note]

16 [*Note:* When multiple threads can affect the return value of `use_count()`, the result should be treated as approximate. In particular, `use_count() == 1` does not imply that accesses through a previously destroyed `shared_ptr` have in any sense completed. — end note]

```
explicit operator bool() const noexcept;
```

17 *Returns:* `get() != 0`.

```
template<class U> bool owner_before(const shared_ptr<U>& b) const noexcept;
```

```
template<class U> bool owner_before(const weak_ptr<U>& b) const noexcept;
```

- 18 *Returns:* An unspecified value such that
- (18.1) — `x.owner_before(y)` defines a strict weak ordering as defined in 28.7;
- (18.2) — under the equivalence relation defined by `owner_before`, `!a.owner_before(b) && !b.owner_before(a)`, two `shared_ptr` or `weak_ptr` instances are equivalent if and only if they share ownership or are both empty.

23.11.2.2.6 `shared_ptr` creation

[`util.smartptr.shared.create`]

```
template<class T, class... Args>
    shared_ptr<T> make_shared(Args&&... args);
template<class T, class A, class... Args>
    shared_ptr<T> allocate_shared(const A& a, Args&&... args);
```

- 1 *Requires:* The expression `::new (pv) T(std::forward<Args>(args)...)...`, where `pv` has type `void*` and points to storage suitable to hold an object of type `T`, shall be well formed. `A` shall be an allocator (20.5.3.5). The copy constructor and destructor of `A` shall not throw exceptions.
- 2 *Effects:* Allocates memory suitable for an object of type `T` and constructs an object in that memory via the placement *new-expression* `::new (pv) T(std::forward<Args>(args)...)...`. The template `allocate_shared` uses a copy of `a` to allocate memory. If an exception is thrown, the functions have no effect.
- 3 *Returns:* A `shared_ptr` instance that stores and owns the address of the newly constructed object of type `T`.
- 4 *Postconditions:* `get() != 0 && use_count() == 1`.
- 5 *Throws:* `bad_alloc`, or an exception thrown from `A::allocate` or from the constructor of `T`.
- 6 *Remarks:* The `shared_ptr` constructor called by this function enables `shared_from_this` with the address of the newly constructed object of type `T`. Implementations should perform no more than one memory allocation. [*Note:* This provides efficiency equivalent to an intrusive smart pointer. — *end note*]
- 7 [*Note:* These functions will typically allocate more memory than `sizeof(T)` to allow for internal bookkeeping structures such as the reference counts. — *end note*]

23.11.2.2.7 `shared_ptr` comparison

[`util.smartptr.shared.cmp`]

```
template<class T, class U>
    bool operator==(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
```

- 1 *Returns:* `a.get() == b.get()`.

```
template<class T, class U>
    bool operator<(const shared_ptr<T>& a, const shared_ptr<U>& b) noexcept;
```

- 2 *Returns:* `less<>()(a.get(), b.get())`.
- 3 [*Note:* Defining a comparison function allows `shared_ptr` objects to be used as keys in associative containers. — *end note*]

```
template <class T>
    bool operator==(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator==(nullptr_t, const shared_ptr<T>& a) noexcept;
```

- 4 *Returns:* `!a`.

```

template <class T>
    bool operator!=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator!=(nullptr_t, const shared_ptr<T>& a) noexcept;

```

5 *Returns:* (bool)a.

```

template <class T>
    bool operator<(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator<(nullptr_t, const shared_ptr<T>& a) noexcept;

```

6 *Returns:* The first function template returns `less<shared_ptr<T>::element_type*>()(a.get(), nullptr)`. The second function template returns `less<shared_ptr<T>::element_type*>()(nullptr, a.get())`.

```

template <class T>
    bool operator>(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator>(nullptr_t, const shared_ptr<T>& a) noexcept;

```

7 *Returns:* The first function template returns `nullptr < a`. The second function template returns `a < nullptr`.

```

template <class T>
    bool operator<=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator<=(nullptr_t, const shared_ptr<T>& a) noexcept;

```

8 *Returns:* The first function template returns `!(nullptr < a)`. The second function template returns `!(a < nullptr)`.

```

template <class T>
    bool operator>=(const shared_ptr<T>& a, nullptr_t) noexcept;
template <class T>
    bool operator>=(nullptr_t, const shared_ptr<T>& a) noexcept;

```

9 *Returns:* The first function template returns `!(a < nullptr)`. The second function template returns `!(nullptr < a)`.

23.11.2.2.8 shared_ptr specialized algorithms

[util.smartptr.shared.spec]

```

template<class T>
    void swap(shared_ptr<T>& a, shared_ptr<T>& b) noexcept;

```

1 *Effects:* Equivalent to `a.swap(b)`.

23.11.2.2.9 shared_ptr casts

[util.smartptr.shared.cast]

```

template<class T, class U>
    shared_ptr<T> static_pointer_cast(const shared_ptr<U>& r) noexcept;

```

1 *Requires:* The expression `static_cast<T*>((U*)0)` shall be well formed.

2 *Returns:*

```

    shared_ptr<T>(r, static_cast<typename shared_ptr<T>::element_type*>(r.get()))

```

3 [*Note:* The seemingly equivalent expression `shared_ptr<T>(static_cast<T*>(r.get()))` will eventually result in undefined behavior, attempting to delete the same object twice. — *end note*]

```

template<class T, class U>

```

```
shared_ptr<T> dynamic_pointer_cast(const shared_ptr<U>& r) noexcept;
```

4 *Requires:* The expression `dynamic_cast<T*>((U*)0)` shall be well formed and shall have well defined behavior.

5 *Returns:*

(5.1) — When `dynamic_cast<typename shared_ptr<T>::element_type*>(r.get())` returns a nonzero value `p`, `shared_ptr<T>(r, p)`.

(5.2) — Otherwise, `shared_ptr<T>()`.

6 [*Note:* The seemingly equivalent expression `shared_ptr<T>(dynamic_cast<T*>(r.get()))` will eventually result in undefined behavior, attempting to delete the same object twice. — *end note*]

```
template<class T, class U>
```

```
shared_ptr<T> const_pointer_cast(const shared_ptr<U>& r) noexcept;
```

7 *Requires:* The expression `const_cast<T*>((U*)0)` shall be well formed.

8 *Returns:*

```
shared_ptr<T>(r, const_cast<typename shared_ptr<T>::element_type*>(r.get()))
```

9 [*Note:* The seemingly equivalent expression `shared_ptr<T>(const_cast<T*>(r.get()))` will eventually result in undefined behavior, attempting to delete the same object twice. — *end note*]

```
template<class T, class U>
```

```
shared_ptr<T> reinterpret_pointer_cast(const shared_ptr<U>& r) noexcept;
```

10 *Requires:* The expression `reinterpret_cast<T*>((U*)0)` shall be well formed.

11 *Returns:*

```
shared_ptr<T>(r, reinterpret_cast<typename shared_ptr<T>::element_type*>(r.get()))
```

12 [*Note:* The seemingly equivalent expression `shared_ptr<T>(reinterpret_cast<T*>(r.get()))` will eventually result in undefined behavior, attempting to delete the same object twice. — *end note*]

23.11.2.2.10 get_deleter

[util.smartptr.getdeleter]

```
template<class D, class T>
```

```
D* get_deleter(const shared_ptr<T>& p) noexcept;
```

1 *Returns:* If `p` owns a deleter `d` of type cv-unqualified `D`, returns `addressof(d)`; otherwise returns `nullptr`. The returned pointer remains valid as long as there exists a `shared_ptr` instance that owns `d`. [*Note:* It is unspecified whether the pointer remains valid longer than that. This can happen if the implementation doesn't destroy the deleter until all `weak_ptr` instances that share ownership with `p` have been destroyed. — *end note*]

23.11.2.2.11 shared_ptr I/O

[util.smartptr.shared.io]

```
template<class E, class T, class Y>
```

```
basic_ostream<E, T>& operator<< (basic_ostream<E, T>& os, const shared_ptr<Y>& p);
```

1 *Effects:* As if by: `os << p.get();`

2 *Returns:* `os`.

23.11.2.3 Class template weak_ptr

[util.smartptr.weak]

1 The `weak_ptr` class template stores a weak reference to an object that is already managed by a `shared_ptr`. To access the object, a `weak_ptr` can be converted to a `shared_ptr` using the member function `lock`.

```
namespace std {
```

```

template<class T> class weak_ptr {
public:
    using element_type = T;

    // 23.11.2.3.1, constructors
    constexpr weak_ptr() noexcept;
    template<class Y> weak_ptr(const shared_ptr<Y>& r) noexcept;
    weak_ptr(const weak_ptr& r) noexcept;
    template<class Y> weak_ptr(const weak_ptr<Y>& r) noexcept;
    weak_ptr(weak_ptr&& r) noexcept;
    template<class Y> weak_ptr(weak_ptr<Y>&& r) noexcept;

    // 23.11.2.3.2, destructor
    ~weak_ptr();

    // 23.11.2.3.3, assignment
    weak_ptr& operator=(const weak_ptr& r) noexcept;
    template<class Y> weak_ptr& operator=(const weak_ptr<Y>& r) noexcept;
    template<class Y> weak_ptr& operator=(const shared_ptr<Y>& r) noexcept;
    weak_ptr& operator=(weak_ptr&& r) noexcept;
    template<class Y> weak_ptr& operator=(weak_ptr<Y>&& r) noexcept;

    // 23.11.2.3.4, modifiers
    void swap(weak_ptr& r) noexcept;
    void reset() noexcept;

    // 23.11.2.3.5, observers
    long use_count() const noexcept;
    bool expired() const noexcept;
    shared_ptr<T> lock() const noexcept;
    template<class U> bool owner_before(const shared_ptr<U>& b) const;
    template<class U> bool owner_before(const weak_ptr<U>& b) const;
};

template<class T> weak_ptr(shared_ptr<T>) -> weak_ptr<T>;

// 23.11.2.3.6, specialized algorithms
template<class T> void swap(weak_ptr<T>& a, weak_ptr<T>& b) noexcept;
}

```

- ² Specializations of `weak_ptr` shall be `CopyConstructible` and `CopyAssignable`, allowing their use in standard containers. The template parameter `T` of `weak_ptr` may be an incomplete type.

23.11.2.3.1 `weak_ptr` constructors [util.smartptr.weak.const]

```
constexpr weak_ptr() noexcept;
```

- ¹ *Effects:* Constructs an empty `weak_ptr` object.

- ² *Postconditions:* `use_count() == 0`.

```

weak_ptr(const weak_ptr& r) noexcept;
template<class Y> weak_ptr(const weak_ptr<Y>& r) noexcept;
template<class Y> weak_ptr(const shared_ptr<Y>& r) noexcept;

```

- ³ *Remarks:* The second and third constructors shall not participate in overload resolution unless `Y*` is compatible with `T*`.

4 *Effects:* If `r` is empty, constructs an empty `weak_ptr` object; otherwise, constructs a `weak_ptr` object that shares ownership with `r` and stores a copy of the pointer stored in `r`.

5 *Postconditions:* `use_count() == r.use_count()`.

```
weak_ptr(weak_ptr&& r) noexcept;
template<class Y> weak_ptr(weak_ptr<Y>&& r) noexcept;
```

6 *Remarks:* The second constructor shall not participate in overload resolution unless `Y*` is compatible with `T*`.

7 *Effects:* Move constructs a `weak_ptr` instance from `r`.

8 *Postconditions:* `*this` shall contain the old value of `r`. `r` shall be empty. `r.use_count() == 0`.

23.11.2.3.2 `weak_ptr` destructor [util.smartptr.weak.dest]

```
~weak_ptr();
```

1 *Effects:* Destroys this `weak_ptr` object but has no effect on the object its stored pointer points to.

23.11.2.3.3 `weak_ptr` assignment [util.smartptr.weak.assign]

```
weak_ptr& operator=(const weak_ptr& r) noexcept;
template<class Y> weak_ptr& operator=(const weak_ptr<Y>& r) noexcept;
template<class Y> weak_ptr& operator=(const shared_ptr<Y>& r) noexcept;
```

1 *Effects:* Equivalent to `weak_ptr(r).swap(*this)`.

2 *Remarks:* The implementation may meet the effects (and the implied guarantees) via different means, without creating a temporary.

3 *Returns:* `*this`.

```
weak_ptr& operator=(weak_ptr&& r) noexcept;
template<class Y> weak_ptr& operator=(weak_ptr<Y>&& r) noexcept;
```

4 *Effects:* Equivalent to `weak_ptr(std::move(r)).swap(*this)`.

5 *Returns:* `*this`.

23.11.2.3.4 `weak_ptr` modifiers [util.smartptr.weak.mod]

```
void swap(weak_ptr& r) noexcept;
```

1 *Effects:* Exchanges the contents of `*this` and `r`.

```
void reset() noexcept;
```

2 *Effects:* Equivalent to `weak_ptr().swap(*this)`.

23.11.2.3.5 `weak_ptr` observers [util.smartptr.weak.obs]

```
long use_count() const noexcept;
```

1 *Returns:* 0 if `*this` is empty; otherwise, the number of `shared_ptr` instances that share ownership with `*this`.

```
bool expired() const noexcept;
```

2 *Returns:* `use_count() == 0`.

```
shared_ptr<T> lock() const noexcept;
```

3 *Returns:* `expired() ? shared_ptr<T>() : shared_ptr<T>(*this)`, executed atomically.

```
template<class U> bool owner_before(const shared_ptr<U>& b) const;
template<class U> bool owner_before(const weak_ptr<U>& b) const;
```

4 *Returns:* An unspecified value such that

- (4.1) — `x.owner_before(y)` defines a strict weak ordering as defined in 28.7;
- (4.2) — under the equivalence relation defined by `owner_before`, `!a.owner_before(b) && !b.owner_before(a)`, two `shared_ptr` or `weak_ptr` instances are equivalent if and only if they share ownership or are both empty.

23.11.2.3.6 `weak_ptr` specialized algorithms

[util.smartptr.weak.spec]

```
template<class T>
void swap(weak_ptr<T>& a, weak_ptr<T>& b) noexcept;
```

1 *Effects:* Equivalent to `a.swap(b)`.

23.11.2.4 Class template `owner_less`

[util.smartptr.ownerless]

1 The class template `owner_less` allows ownership-based mixed comparisons of shared and weak pointers.

```
namespace std {
    template<class T = void> struct owner_less;

    template<class T> struct owner_less<shared_ptr<T>> {
        bool operator()(const shared_ptr<T>&, const shared_ptr<T>&) const noexcept;
        bool operator()(const shared_ptr<T>&, const weak_ptr<T>&) const noexcept;
        bool operator()(const weak_ptr<T>&, const shared_ptr<T>&) const noexcept;
    };

    template<class T> struct owner_less<weak_ptr<T>> {
        bool operator()(const weak_ptr<T>&, const weak_ptr<T>&) const noexcept;
        bool operator()(const shared_ptr<T>&, const weak_ptr<T>&) const noexcept;
        bool operator()(const weak_ptr<T>&, const shared_ptr<T>&) const noexcept;
    };

    template<> struct owner_less<void> {
        template<class T, class U>
            bool operator()(const shared_ptr<T>&, const shared_ptr<U>&) const noexcept;
        template<class T, class U>
            bool operator()(const shared_ptr<T>&, const weak_ptr<U>&) const noexcept;
        template<class T, class U>
            bool operator()(const weak_ptr<T>&, const shared_ptr<U>&) const noexcept;
        template<class T, class U>
            bool operator()(const weak_ptr<T>&, const weak_ptr<U>&) const noexcept;

        using is_transparent = unspecified;
    };
}
```

2 `operator()(x, y)` shall return `x.owner_before(y)`. [Note: Note that

- (2.1) — `operator()` defines a strict weak ordering as defined in 28.7;
 - (2.2) — under the equivalence relation defined by `operator()`, `!operator()(a, b) && !operator()(b, a)`, two `shared_ptr` or `weak_ptr` instances are equivalent if and only if they share ownership or are both empty.
- end note]

23.11.2.5 Class template `enable_shared_from_this` [util.smartptr.enab]

- ¹ A class `T` can inherit from `enable_shared_from_this<T>` to inherit the `shared_from_this` member functions that obtain a `shared_ptr` instance pointing to `*this`.

² [*Example:*

```
struct X: public enable_shared_from_this<X> { };

int main() {
    shared_ptr<X> p(new X);
    shared_ptr<X> q = p->shared_from_this();
    assert(p == q);
    assert(!p.owner_before(q) && !q.owner_before(p)); // p and q share ownership
}
```

— *end example*]

```
namespace std {
    template<class T> class enable_shared_from_this {
    protected:
        constexpr enable_shared_from_this() noexcept;
        enable_shared_from_this(const enable_shared_from_this&) noexcept;
        enable_shared_from_this& operator=(const enable_shared_from_this&) noexcept;
        ~enable_shared_from_this();
    public:
        shared_ptr<T> shared_from_this();
        shared_ptr<T const> shared_from_this() const;
        weak_ptr<T> weak_from_this() noexcept;
        weak_ptr<T const> weak_from_this() const noexcept;
    private:
        mutable weak_ptr<T> weak_this; // exposition only
    };
}
```

- ³ The template parameter `T` of `enable_shared_from_this` may be an incomplete type.

```
constexpr enable_shared_from_this() noexcept;
enable_shared_from_this(const enable_shared_from_this<T>&) noexcept;
```

- ⁴ *Effects:* Value-initializes `weak_this`.

```
enable_shared_from_this<T>& operator=(const enable_shared_from_this<T>&) noexcept;
```

- ⁵ *Returns:* `*this`.

- ⁶ [*Note:* `weak_this` is not changed. — *end note*]

```
shared_ptr<T> shared_from_this();
shared_ptr<T const> shared_from_this() const;
```

- ⁷ *Returns:* `shared_ptr<T>(weak_this)`.

```
weak_ptr<T> weak_from_this() noexcept;
weak_ptr<T const> weak_from_this() const noexcept;
```

- ⁸ *Returns:* `weak_this`.

23.11.2.6 `shared_ptr` atomic access [util.smartptr.shared.atomic]

- ¹ Concurrent access to a `shared_ptr` object from multiple threads does not introduce a data race if the access is done exclusively via the functions in this section and the instance is passed as their first argument.

2 The meaning of the arguments of type `memory_order` is explained in [32.4](#).

```
template<class T>
    bool atomic_is_lock_free(const shared_ptr<T>* p);
```

3 *Requires:* `p` shall not be null.

4 *Returns:* `true` if atomic access to `*p` is lock-free, `false` otherwise.

5 *Throws:* Nothing.

```
template<class T>
    shared_ptr<T> atomic_load(const shared_ptr<T>* p);
```

6 *Requires:* `p` shall not be null.

7 *Returns:* `atomic_load_explicit(p, memory_order_seq_cst)`.

8 *Throws:* Nothing.

```
template<class T>
    shared_ptr<T> atomic_load_explicit(const shared_ptr<T>* p, memory_order mo);
```

9 *Requires:* `p` shall not be null.

10 *Requires:* `mo` shall not be `memory_order_release` or `memory_order_acq_rel`.

11 *Returns:* `*p`.

12 *Throws:* Nothing.

```
template<class T>
    void atomic_store(shared_ptr<T>* p, shared_ptr<T> r);
```

13 *Requires:* `p` shall not be null.

14 *Effects:* As if by `atomic_store_explicit(p, r, memory_order_seq_cst)`.

15 *Throws:* Nothing.

```
template<class T>
    void atomic_store_explicit(shared_ptr<T>* p, shared_ptr<T> r, memory_order mo);
```

16 *Requires:* `p` shall not be null.

17 *Requires:* `mo` shall not be `memory_order_acquire` or `memory_order_acq_rel`.

18 *Effects:* As if by `p->swap(r)`.

19 *Throws:* Nothing.

```
template<class T>
    shared_ptr<T> atomic_exchange(shared_ptr<T>* p, shared_ptr<T> r);
```

20 *Requires:* `p` shall not be null.

21 *Returns:* `atomic_exchange_explicit(p, r, memory_order_seq_cst)`.

22 *Throws:* Nothing.

```
template<class T>
    shared_ptr<T> atomic_exchange_explicit(shared_ptr<T>* p, shared_ptr<T> r, memory_order mo);
```

23 *Requires:* `p` shall not be null.

24 *Effects:* As if by `p->swap(r)`.

25 *Returns:* The previous value of `*p`.

26 *Throws:* Nothing.

```
template<class T>
    bool atomic_compare_exchange_weak(shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w);
```

27 *Requires:* *p* shall not be null and *v* shall not be null.

28 *Returns:*

```
    atomic_compare_exchange_weak_explicit(p, v, w, memory_order_seq_cst, memory_order_seq_cst)
```

29 *Throws:* Nothing.

```
template<class T>
    bool atomic_compare_exchange_strong(shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w);
```

30 *Returns:*

```
    atomic_compare_exchange_strong_explicit(p, v, w, memory_order_seq_cst, memory_order_seq_cst)
```

```
template<class T>
    bool atomic_compare_exchange_weak_explicit(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w,
        memory_order success, memory_order failure);
```

```
template<class T>
    bool atomic_compare_exchange_strong_explicit(
        shared_ptr<T>* p, shared_ptr<T>* v, shared_ptr<T> w,
        memory_order success, memory_order failure);
```

31 *Requires:* *p* shall not be null and *v* shall not be null. The *failure* argument shall not be *memory_order_release* nor *memory_order_acq_rel*.

32 *Effects:* If **p* is equivalent to **v*, assigns *w* to **p* and has synchronization semantics corresponding to the value of *success*, otherwise assigns **p* to **v* and has synchronization semantics corresponding to the value of *failure*.

33 *Returns:* *true* if **p* was equivalent to **v*, *false* otherwise.

34 *Throws:* Nothing.

35 *Remarks:* Two *shared_ptr* objects are equivalent if they store the same pointer value and share ownership. The weak form may fail spuriously. See 32.6.1.

23.11.2.7 Smart pointer hash support

[util.smartptr.hash]

```
template <class T, class D> struct hash<unique_ptr<T, D>>;
```

1 Letting UP be *unique_ptr<T,D>*, the specialization *hash<UP>* is enabled (23.14.15) if and only if *hash<typename UP::pointer>* is enabled. When enabled, for an object *p* of type UP, *hash<UP>()* (*p*) shall evaluate to the same value as *hash<typename UP::pointer>()* (*p.get()*). The member functions are not guaranteed to be *noexcept*.

```
template <class T> struct hash<shared_ptr<T>>;
```

2 For an object *p* of type *shared_ptr<T>*, *hash<shared_ptr<T>>()* (*p*) shall evaluate to the same value as *hash<typename shared_ptr<T>::element_type*>()* (*p.get()*).

23.12 Memory resources

[mem.res]

23.12.1 Header <memory_resource> synopsis

[mem.res.syn]

```
namespace std::pmr {
    // 23.12.2, class memory_resource
    class memory_resource;
```

```

bool operator==(const memory_resource& a, const memory_resource& b) noexcept;
bool operator!=(const memory_resource& a, const memory_resource& b) noexcept;

// 23.12.3, class template polymorphic_allocator
template <class Tp> class polymorphic_allocator;

template <class T1, class T2>
    bool operator==(const polymorphic_allocator<T1>& a,
                    const polymorphic_allocator<T2>& b) noexcept;
template <class T1, class T2>
    bool operator!=(const polymorphic_allocator<T1>& a,
                    const polymorphic_allocator<T2>& b) noexcept;

// 23.12.4, global memory resources
memory_resource* new_delete_resource() noexcept;
memory_resource* null_memory_resource() noexcept;
memory_resource* set_default_resource(memory_resource* r) noexcept;
memory_resource* get_default_resource() noexcept;

// 23.12.5, pool resource classes
struct pool_options;
class synchronized_pool_resource;
class unsynchronized_pool_resource;
class monotonic_buffer_resource;
}

```

23.12.2 Class memory_resource

[mem.res.class]

- ¹ The memory_resource class is an abstract interface to an unbounded set of classes encapsulating memory resources.

```

class memory_resource {
    static constexpr size_t max_align = alignof(max_align_t); // exposition only

public:
    virtual ~memory_resource();

    void* allocate(size_t bytes, size_t alignment = max_align);
    void deallocate(void* p, size_t bytes, size_t alignment = max_align);

    bool is_equal(const memory_resource& other) const noexcept;

private:
    virtual void* do_allocate(size_t bytes, size_t alignment) = 0;
    virtual void do_deallocate(void* p, size_t bytes, size_t alignment) = 0;

    virtual bool do_is_equal(const memory_resource& other) const noexcept = 0;
};

```

23.12.2.1 memory_resource public member functions

[mem.res.public]

```
~memory_resource();
```

- ¹ *Effects:* Destroys this memory_resource.

```
void* allocate(size_t bytes, size_t alignment = max_align);
```

2 *Effects:* Equivalent to: `return do_allocate(bytes, alignment);`

`void deallocate(void* p, size_t bytes, size_t alignment = max_align);`

3 *Effects:* Equivalent to: `do_deallocate(p, bytes, alignment);`

`bool is_equal(const memory_resource& other) const noexcept;`

4 *Effects:* Equivalent to: `return do_is_equal(other);`

23.12.2.2 `memory_resource` private virtual member functions [mem.res.private]

`virtual void* do_allocate(size_t bytes, size_t alignment) = 0;`

1 *Requires:* `alignment` shall be a power of two.

2 *Returns:* A derived class shall implement this function to return a pointer to allocated storage (6.7.4.2) with a size of at least `bytes`. The returned storage is aligned to the specified alignment, if such alignment is supported (6.11); otherwise it is aligned to `max_align`.

3 *Throws:* A derived class implementation shall throw an appropriate exception if it is unable to allocate memory with the requested size and alignment.

`virtual void do_deallocate(void* p, size_t bytes, size_t alignment) = 0;`

4 *Requires:* `p` shall have been returned from a prior call to `allocate(bytes, alignment)` on a memory resource equal to `*this`, and the storage at `p` shall not yet have been deallocated.

5 *Effects:* A derived class shall implement this function to dispose of allocated storage.

6 *Throws:* Nothing.

`virtual bool do_is_equal(const memory_resource& other) const noexcept = 0;`

7 *Returns:* A derived class shall implement this function to return `true` if memory allocated from `this` can be deallocated from `other` and vice-versa, otherwise `false`. [*Note:* The most-derived type of `other` might not match the type of `this`. For a derived class `D`, a typical implementation of this function will immediately return `false` if `dynamic_cast<const D*>(&other) == nullptr`. — *end note*]

23.12.2.3 `memory_resource` equality [mem.res.eq]

`bool operator==(const memory_resource& a, const memory_resource& b) noexcept;`

1 *Returns:* `&a == &b || a.is_equal(b)`.

`bool operator!=(const memory_resource& a, const memory_resource& b) noexcept;`

2 *Returns:* `!(a == b)`.

23.12.3 Class template `polymorphic_allocator` [mem.poly.allocator.class]

1 A specialization of class template `pmr::polymorphic_allocator` conforms to the `Allocator` requirements (20.5.3.5). Constructed with different memory resources, different instances of the same specialization of `pmr::polymorphic_allocator` can exhibit entirely different allocation behavior. This runtime polymorphism allows objects that use `polymorphic_allocator` to behave as if they used different allocator types at run time even though they use the same static allocator type.

```
template <class Tp>
class polymorphic_allocator {
    memory_resource* memory_rsrc; // exposition only

public:
    using value_type = Tp;
```

```

// 23.12.3.1, constructors
polymorphic_allocator() noexcept;
polymorphic_allocator(memory_resource* r);

polymorphic_allocator(const polymorphic_allocator& other) = default;

template <class U>
    polymorphic_allocator(const polymorphic_allocator<U>& other) noexcept;

polymorphic_allocator&
    operator=(const polymorphic_allocator& rhs) = delete;

// 23.12.3.2, member functions
Tp* allocate(size_t n);
void deallocate(Tp* p, size_t n);

template <class T, class... Args>
void construct(T* p, Args&&... args);

template <class T1, class T2, class... Args1, class... Args2>
    void construct(pair<T1,T2>* p, piecewise_construct_t,
        tuple<Args1...> x, tuple<Args2...> y);
template <class T1, class T2>
    void construct(pair<T1,T2>* p);
template <class T1, class T2, class U, class V>
    void construct(pair<T1,T2>* p, U&& x, V&& y);
template <class T1, class T2, class U, class V>
    void construct(pair<T1,T2>* p, const pair<U, V>& pr);
template <class T1, class T2, class U, class V>
    void construct(pair<T1,T2>* p, pair<U, V>&& pr);

template <class T>
    void destroy(T* p);

polymorphic_allocator select_on_container_copy_construction() const;

memory_resource* resource() const;
};

```

23.12.3.1 polymorphic_allocator constructors

[mem.poly.allocator.ctor]

```
polymorphic_allocator() noexcept;
```

1 *Effects:* Sets `memory_rsrc` to `get_default_resource()`.

```
polymorphic_allocator(memory_resource* r);
```

2 *Requires:* `r` is non-null.

3 *Effects:* Sets `memory_rsrc` to `r`.

4 *Throws:* Nothing.

5 [*Note:* This constructor provides an implicit conversion from `memory_resource*`. — *end note*]

```

template <class U>
    polymorphic_allocator(const polymorphic_allocator<U>& other) noexcept;

```

6 *Effects:* Sets `memory_rsrc` to `other.resource()`.

23.12.3.2 polymorphic_allocator member functions [mem.poly.allocator.mem]

`Tp* allocate(size_t n);`

1 *Returns:* Equivalent to

```
return static_cast<Tp*>(memory_rsrc->allocate(n * sizeof(Tp), alignof(Tp)));
```

`void deallocate(Tp* p, size_t n);`

2 *Requires:* `p` was allocated from a memory resource `x`, equal to `*memory_rsrc`, using `x.allocate(n * sizeof(Tp), alignof(Tp))`.

3 *Effects:* Equivalent to `memory_rsrc->deallocate(p, n * sizeof(Tp), alignof(Tp))`.

4 *Throws:* Nothing.

```
template <class T, class... Args>
void construct(T* p, Args&&... args);
```

5 *Requires:* Uses-allocator construction of `T` with allocator `resource()` (see 23.10.7.2) and constructor arguments `std::forward<Args>(args)...` is well-formed. [*Note:* Uses-allocator construction is always well formed for types that do not use allocators. — *end note*]

6 *Effects:* Construct a `T` object in the storage whose address is represented by `p` by uses-allocator construction with allocator `resource()` and constructor arguments `std::forward<Args>(args)...`

7 *Throws:* Nothing unless the constructor for `T` throws.

```
template <class T1, class T2, class... Args1, class... Args2>
void construct(pair<T1,T2>* p, piecewise_construct_t,
              tuple<Args1...> x, tuple<Args2...> y);
```

8 [*Note:* This method and the `construct` methods that follow are overloads for piecewise construction of pairs (23.4.2). — *end note*]

9 *Effects:* Let `xprime` be a tuple constructed from `x` according to the appropriate rule from the following list. [*Note:* The following description can be summarized as constructing a `pair<T1, T2>` object in the storage whose address is represented by `p`, as if by separate uses-allocator construction with allocator `resource()` (23.10.7.2) of `p->first` using the elements of `x` and `p->second` using the elements of `y`. — *end note*]

(9.1) — If `uses_allocator_v<T1,memory_resource*>` is false
and `is_constructible_v<T1,Args1...>` is true,
then `xprime` is `x`.

(9.2) — Otherwise, if `uses_allocator_v<T1,memory_resource*>` is true
and `is_constructible_v<T1,allocator_arg_t,memory_resource*,Args1...>` is true,
then `xprime` is `tuple_cat(make_tuple(allocator_arg, resource()), std::move(x))`.

(9.3) — Otherwise, if `uses_allocator_v<T1,memory_resource*>` is true
and `is_constructible_v<T1,Args1...,memory_resource*>` is true,
then `xprime` is `tuple_cat(std::move(x), make_tuple(resource()))`.

(9.4) — Otherwise the program is ill formed.

Let `yprime` be a tuple constructed from `y` according to the appropriate rule from the following list:

(9.5) — If `uses_allocator_v<T2,memory_resource*>` is false
and `is_constructible_v<T2,Args2...>` is true,
then `yprime` is `y`.

- (9.6) — Otherwise, if `uses_allocator_v<T2,memory_resource*>` is true and `is_constructible_v<T2,allocator_arg_t,memory_resource*,Args2...>` is true, then `yprime` is `tuple_cat(make_tuple(allocator_arg, resource()), std::move(y))`.
- (9.7) — Otherwise, if `uses_allocator_v<T2,memory_resource*>` is true and `is_constructible_v<T2,Args2...,memory_resource*>` is true, then `yprime` is `tuple_cat(std::move(y), make_tuple(resource()))`.
- (9.8) — Otherwise the program is ill formed.

Then, using `piecewise_construct`, `xprime`, and `yprime` as the constructor arguments, this function constructs a `pair<T1, T2>` object in the storage whose address is represented by `p`.

```
template <class T1, class T2>
void construct(pair<T1,T2*> p);
```

10 *Effects:* Equivalent to:

```
construct(p, piecewise_construct, tuple<>(), tuple<>());
```

```
template <class T1, class T2, class U, class V>
void construct(pair<T1,T2*> p, U&& x, V&& y);
```

11 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(std::forward<U>(x)),
         forward_as_tuple(std::forward<V>(y)));
```

```
template <class T1, class T2, class U, class V>
void construct(pair<T1,T2*> p, const pair<U, V>& pr);
```

12 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(pr.first),
         forward_as_tuple(pr.second));
```

```
template <class T1, class T2, class U, class V>
void construct(pair<T1,T2*> p, pair<U, V>&& pr);
```

13 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(std::forward<U>(pr.first)),
         forward_as_tuple(std::forward<V>(pr.second)));
```

```
template <class T>
void destroy(T* p);
```

14 *Effects:* As if by `p->~T()`.

```
polymorphic_allocator select_on_container_copy_construction() const;
```

15 *Returns:* `polymorphic_allocator()`.

16 [*Note:* The memory resource is not propagated. — *end note*]

```
memory_resource* resource() const;
```

17 *Returns:* `memory_rsrc`.

23.12.3.3 polymorphic_allocator equality

[mem.poly.allocator.eq]

```
template <class T1, class T2>
```

```
bool operator==(const polymorphic_allocator<T1>& a,
                const polymorphic_allocator<T2>& b) noexcept;
```

1 *Returns:* `*a.resource() == *b.resource()`.

```
template <class T1, class T2>
bool operator!=(const polymorphic_allocator<T1>& a,
                const polymorphic_allocator<T2>& b) noexcept;
```

2 *Returns:* `!(a == b)`.

23.12.4 Access to program-wide memory_resource objects [mem.res.global]

```
memory_resource* new_delete_resource() noexcept;
```

1 *Returns:* A pointer to a static-duration object of a type derived from `memory_resource` that can serve as a resource for allocating memory using `::operator new` and `::operator delete`. The same value is returned every time this function is called. For a return value `p` and a memory resource `r`, `p->is_equal(r)` returns `&r == p`.

```
memory_resource* null_memory_resource() noexcept;
```

2 *Returns:* A pointer to a static-duration object of a type derived from `memory_resource` for which `allocate()` always throws `bad_alloc` and for which `deallocate()` has no effect. The same value is returned every time this function is called. For a return value `p` and a memory resource `r`, `p->is_equal(r)` returns `&r == p`.

3 The *default memory resource pointer* is a pointer to a memory resource that is used by certain facilities when an explicit memory resource is not supplied through the interface. Its initial value is the return value of `new_delete_resource()`.

```
memory_resource* set_default_resource(memory_resource* r) noexcept;
```

4 *Effects:* If `r` is non-null, sets the value of the default memory resource pointer to `r`, otherwise sets the default memory resource pointer to `new_delete_resource()`.

5 *Postconditions:* `get_default_resource() == r`.

6 *Returns:* The previous value of the default memory resource pointer.

7 *Remarks:* Calling the `set_default_resource` and `get_default_resource` functions shall not incur a data race. A call to the `set_default_resource` function shall synchronize with subsequent calls to the `set_default_resource` and `get_default_resource` functions.

```
memory_resource* get_default_resource() noexcept;
```

8 *Returns:* The current value of the default memory resource pointer.

23.12.5 Pool resource classes [mem.res.pool]

23.12.5.1 Classes `synchronized_pool_resource` and `unsynchronized_pool_resource` [mem.res.pool.overview]

1 The `synchronized_pool_resource` and `unsynchronized_pool_resource` classes (collectively called *pool resource classes*) are general-purpose memory resources having the following qualities:

- (1.1) — Each resource frees its allocated memory on destruction, even if `deallocate` has not been called for some of the allocated blocks.
- (1.2) — A pool resource consists of a collection of *pools*, serving requests for different block sizes. Each individual pool manages a collection of *chunks* that are in turn divided into blocks of uniform size, returned via

calls to `do_allocate`. Each call to `do_allocate(size, alignment)` is dispatched to the pool serving the smallest blocks accommodating at least `size` bytes.

- (1.3) — When a particular pool is exhausted, allocating a block from that pool results in the allocation of an additional chunk of memory from the *upstream allocator* (supplied at construction), thus replenishing the pool. With each successive replenishment, the chunk size obtained increases geometrically. [*Note*: By allocating memory in chunks, the pooling strategy increases the chance that consecutive allocations will be close together in memory. — *end note*]
- (1.4) — Allocation requests that exceed the largest block size of any pool are fulfilled directly from the upstream allocator.
- (1.5) — A `pool_options` struct may be passed to the pool resource constructors to tune the largest block size and the maximum chunk size.

² A `synchronized_pool_resource` may be accessed from multiple threads without external synchronization and may have thread-specific pools to reduce synchronization costs. An `unsynchronized_pool_resource` class may not be accessed from multiple threads simultaneously and thus avoids the cost of synchronization entirely in single-threaded applications.

```
struct pool_options {
    size_t max_blocks_per_chunk = 0;
    size_t largest_required_pool_block = 0;
};

class synchronized_pool_resource : public memory_resource {
public:
    synchronized_pool_resource(const pool_options& opts,
                               memory_resource* upstream);

    synchronized_pool_resource()
        : synchronized_pool_resource(pool_options(), get_default_resource()) {}
    explicit synchronized_pool_resource(memory_resource* upstream)
        : synchronized_pool_resource(pool_options(), upstream) {}
    explicit synchronized_pool_resource(const pool_options& opts)
        : synchronized_pool_resource(opts, get_default_resource()) {}

    synchronized_pool_resource(const synchronized_pool_resource&) = delete;
    virtual ~synchronized_pool_resource();

    synchronized_pool_resource&
        operator=(const synchronized_pool_resource&) = delete;

    void release();
    memory_resource* upstream_resource() const;
    pool_options options() const;

protected:
    void *do_allocate(size_t bytes, size_t alignment) override;
    void do_deallocate(void *p, size_t bytes, size_t alignment) override;

    bool do_is_equal(const memory_resource& other) const noexcept override;
};

class unsynchronized_pool_resource : public memory_resource {
public:
    unsynchronized_pool_resource(const pool_options& opts,
```

```

        memory_resource* upstream);

unsynchronized_pool_resource()
    : unsynchronized_pool_resource(pool_options(), get_default_resource()) {}
explicit unsynchronized_pool_resource(memory_resource* upstream)
    : unsynchronized_pool_resource(pool_options(), upstream) {}
explicit unsynchronized_pool_resource(const pool_options& opts)
    : unsynchronized_pool_resource(opts, get_default_resource()) {}

unsynchronized_pool_resource(const unsynchronized_pool_resource&) = delete;
virtual ~unsynchronized_pool_resource();

unsynchronized_pool_resource&
    operator=(const unsynchronized_pool_resource&) = delete;

void release();
memory_resource *upstream_resource() const;
pool_options options() const;

protected:
    void* do_allocate(size_t bytes, size_t alignment) override;
    void do_deallocate(void* p, size_t bytes, size_t alignment) override;

    bool do_is_equal(const memory_resource& other) const noexcept override;
};

```

23.12.5.2 pool_options data members

[mem.res.pool.options]

- ¹ The members of `pool_options` comprise a set of constructor options for pool resources. The effect of each option on the pool resource behavior is described below:

```
size_t max_blocks_per_chunk;
```

- ² The maximum number of blocks that will be allocated at once from the upstream memory resource (23.12.6) to replenish a pool. If the value of `max_blocks_per_chunk` is zero or is greater than an implementation-defined limit, that limit is used instead. The implementation may choose to use a smaller value than is specified in this field and may use different values for different pools.

```
size_t largest_required_pool_block;
```

- ³ The largest allocation size that is required to be fulfilled using the pooling mechanism. Attempts to allocate a single block larger than this threshold will be allocated directly from the upstream memory resource. If `largest_required_pool_block` is zero or is greater than an implementation-defined limit, that limit is used instead. The implementation may choose a pass-through threshold larger than specified in this field.

23.12.5.3 Pool resource constructors and destructors

[mem.res.pool.ctor]

```

synchronized_pool_resource(const pool_options& opts, memory_resource* upstream);
unsynchronized_pool_resource(const pool_options& opts, memory_resource* upstream);

```

- ¹ *Requires:* `upstream` is the address of a valid memory resource.
- ² *Effects:* Constructs a pool resource object that will obtain memory from `upstream` whenever the pool resource is unable to satisfy a memory request from its own internal data structures. The resulting object will hold a copy of `upstream`, but will not own the resource to which `upstream` points. [*Note:* The intention is that calls to `upstream->allocate()` will be substantially fewer than calls

to `this->allocate()` in most cases. — *end note*] The behavior of the pooling mechanism is tuned according to the value of the `opts` argument.

- 3 *Throws:* Nothing unless `upstream->allocate()` throws. It is unspecified if, or under what conditions, this constructor calls `upstream->allocate()`.

```
virtual ~synchronized_pool_resource();
virtual ~unsynchronized_pool_resource();
```

- 4 *Effects:* Calls `release()`.

23.12.5.4 Pool resource members [mem.res.pool.mem]

```
void release();
```

- 1 *Effects:* Calls `upstream_resource()->deallocate()` as necessary to release all allocated memory. [*Note:* The memory is released back to `upstream_resource()` even if `deallocate` has not been called for some of the allocated blocks. — *end note*]

```
memory_resource* upstream_resource() const;
```

- 2 *Returns:* The value of the `upstream` argument provided to the constructor of this object.

```
pool_options options() const;
```

- 3 *Returns:* The options that control the pooling behavior of this resource. The values in the returned struct may differ from those supplied to the pool resource constructor in that values of zero will be replaced with implementation-defined defaults, and sizes may be rounded to unspecified granularity.

```
void* do_allocate(size_t bytes, size_t alignment) override;
```

- 4 *Returns:* A pointer to allocated storage (6.7.4.2) with a size of at least `bytes`. The size and alignment of the allocated memory shall meet the requirements for a class derived from `memory_resource` (23.12).
- 5 *Effects:* If the pool selected for a block of size `bytes` is unable to satisfy the memory request from its own internal data structures, it will call `upstream_resource()->allocate()` to obtain more memory. If `bytes` is larger than that which the largest pool can handle, then memory will be allocated using `upstream_resource()->allocate()`.
- 6 *Throws:* Nothing unless `upstream_resource()->allocate()` throws.

```
void do_deallocate(void* p, size_t bytes, size_t alignment) override;
```

- 7 *Effects:* Returns the memory at `p` to the pool. It is unspecified if, or under what circumstances, this operation will result in a call to `upstream_resource()->deallocate()`.

- 8 *Throws:* Nothing.

```
bool synchronized_pool_resource::do_is_equal(
    const memory_resource& other) const noexcept override;
```

- 9 *Returns:* `this == dynamic_cast<const synchronized_pool_resource*>(&other)`.

```
bool unsynchronized_pool_resource::do_is_equal(
    const memory_resource& other) const noexcept override;
```

- 10 *Returns:* `this == dynamic_cast<const unsynchronized_pool_resource*>(&other)`.

23.12.6 Class `monotonic_buffer_resource` [mem.res.monotonic.buffer]

- 1 A `monotonic_buffer_resource` is a special-purpose memory resource intended for very fast memory allocations in situations where memory is used to build up a few objects and then is released all at once when the memory resource object is destroyed. It has the following qualities:

- (1.1) — A call to `deallocate` has no effect, thus the amount of memory consumed increases monotonically until the resource is destroyed.
- (1.2) — The program can supply an initial buffer, which the allocator uses to satisfy memory requests.
- (1.3) — When the initial buffer (if any) is exhausted, it obtains additional buffers from an *upstream* memory resource supplied at construction. Each additional buffer is larger than the previous one, following a geometric progression.
- (1.4) — It is intended for access from one thread of control at a time. Specifically, calls to `allocate` and `deallocate` do not synchronize with one another.
- (1.5) — It frees the allocated memory on destruction, even if `deallocate` has not been called for some of the allocated blocks.

```
class monotonic_buffer_resource : public memory_resource {
    memory_resource *upstream_rsrc; // exposition only
    void *current_buffer;           // exposition only
    size_t next_buffer_size;        // exposition only

public:
    explicit monotonic_buffer_resource(memory_resource *upstream);
    monotonic_buffer_resource(size_t initial_size, memory_resource *upstream);
    monotonic_buffer_resource(void *buffer, size_t buffer_size,
                              memory_resource *upstream);

    monotonic_buffer_resource()
        : monotonic_buffer_resource(get_default_resource()) {}
    explicit monotonic_buffer_resource(size_t initial_size)
        : monotonic_buffer_resource(initial_size, get_default_resource()) {}
    monotonic_buffer_resource(void *buffer, size_t buffer_size)
        : monotonic_buffer_resource(buffer, buffer_size, get_default_resource()) {}

    monotonic_buffer_resource(const monotonic_buffer_resource&) = delete;

    virtual ~monotonic_buffer_resource();

    monotonic_buffer_resource
        operator=(const monotonic_buffer_resource&) = delete;

    void release();
    memory_resource* upstream_resource() const;

protected:
    void* do_allocate(size_t bytes, size_t alignment) override;
    void do_deallocate(void* p, size_t bytes, size_t alignment) override;

    bool do_is_equal(const memory_resource& other) const noexcept override;
};
```

23.12.6.1 monotonic_buffer_resource constructor and destructor [mem.res.monotonic.buffer.ctor]

```
explicit monotonic_buffer_resource(memory_resource* upstream);
monotonic_buffer_resource(size_t initial_size, memory_resource* upstream);
```

- ¹ *Requires:* `upstream` shall be the address of a valid memory resource. `initial_size`, if specified, shall be greater than zero.

- 2 *Effects:* Sets `upstream_rsrc` to `upstream` and `current_buffer` to `nullptr`. If `initial_size` is specified, sets `next_buffer_size` to at least `initial_size`; otherwise sets `next_buffer_size` to an implementation-defined size.

```
monotonic_buffer_resource(void* buffer, size_t buffer_size, memory_resource* upstream);
```

- 3 *Requires:* `upstream` shall be the address of a valid memory resource. `buffer_size` shall be no larger than the number of bytes in `buffer`.

- 4 *Effects:* Sets `upstream_rsrc` to `upstream`, `current_buffer` to `buffer`, and `next_buffer_size` to `buffer_size` (but not less than 1), then increases `next_buffer_size` by an implementation-defined growth factor (which need not be integral).

```
~monotonic_buffer_resource();
```

- 5 *Effects:* Calls `release()`.

23.12.6.2 `monotonic_buffer_resource` members [mem.res.monotonic.buffer.mem]

```
void release();
```

- 1 *Effects:* Calls `upstream_rsrc->deallocate()` as necessary to release all allocated memory.

- 2 [*Note:* The memory is released back to `upstream_rsrc` even if some blocks that were allocated from `this` have not been deallocated from `this`. — *end note*]

```
memory_resource* upstream_resource() const;
```

- 3 *Returns:* The value of `upstream_rsrc`.

```
void* do_allocate(size_t bytes, size_t alignment) override;
```

- 4 *Returns:* A pointer to allocated storage (6.7.4.2) with a size of at least `bytes`. The size and alignment of the allocated memory shall meet the requirements for a class derived from `memory_resource` (23.12).

- 5 *Effects:* If the unused space in `current_buffer` can fit a block with the specified `bytes` and `alignment`, then allocate the return block from `current_buffer`; otherwise set `current_buffer` to `upstream_rsrc->allocate(n, m)`, where `n` is not less than `max(bytes, next_buffer_size)` and `m` is not less than `alignment`, and increase `next_buffer_size` by an implementation-defined growth factor (which need not be integral), then allocate the return block from the newly-allocated `current_buffer`.

- 6 *Throws:* Nothing unless `upstream_rsrc->allocate()` throws.

```
void do_deallocate(void* p, size_t bytes, size_t alignment) override;
```

- 7 *Effects:* None.

- 8 *Throws:* Nothing.

- 9 *Remarks:* Memory used by this resource increases monotonically until its destruction.

```
bool do_is_equal(const memory_resource& other) const noexcept override;
```

- 10 *Returns:* `this == dynamic_cast<const monotonic_buffer_resource*>(&other)`.

23.13 Class template `scoped_allocator_adaptor` [allocator.adaptor]

23.13.1 Header `<scoped_allocator>` synopsis [allocator.adaptor.syn]

```
// scoped allocator adaptor
template <class OuterAlloc, class... InnerAlloc>
    class scoped_allocator_adaptor;
template <class OuterA1, class OuterA2, class... InnerAllocs>
    bool operator==(const scoped_allocator_adaptor<OuterA1, InnerAllocs...>& a,
```

```

        const scoped_allocator_adaptor<OuterA2, InnerAllocs...& b) noexcept;
template <class OuterA1, class OuterA2, class... InnerAllocs>
    bool operator!=(const scoped_allocator_adaptor<OuterA1, InnerAllocs...& a,
        const scoped_allocator_adaptor<OuterA2, InnerAllocs...& b) noexcept;

```

- ¹ The class template `scoped_allocator_adaptor` is an allocator template that specifies the memory resource (the outer allocator) to be used by a container (as any other allocator does) and also specifies an inner allocator resource to be passed to the constructor of every element within the container. This adaptor is instantiated with one outer and zero or more inner allocator types. If instantiated with only one allocator type, the inner allocator becomes the `scoped_allocator_adaptor` itself, thus using the same allocator resource for the container and every element within the container and, if the elements themselves are containers, each of their elements recursively. If instantiated with more than one allocator, the first allocator is the outer allocator for use by the container, the second allocator is passed to the constructors of the container's elements, and, if the elements themselves are containers, the third allocator is passed to the elements' elements, and so on. If containers are nested to a depth greater than the number of allocators, the last allocator is used repeatedly, as in the single-allocator case, for any remaining recursions. [*Note:* The `scoped_allocator_adaptor` is derived from the outer allocator type so it can be substituted for the outer allocator type in most expressions. — *end note*]

```

namespace std {
    template <class OuterAlloc, class... InnerAllocs>
        class scoped_allocator_adaptor : public OuterAlloc {
    private:
        using OuterTraits = allocator_traits<OuterAlloc>; // exposition only
        scoped_allocator_adaptor<InnerAllocs...> inner; // exposition only
    public:
        using outer_allocator_type = OuterAlloc;
        using inner_allocator_type = see below;

        using value_type          = typename OuterTraits::value_type;
        using size_type           = typename OuterTraits::size_type;
        using difference_type     = typename OuterTraits::difference_type;
        using pointer             = typename OuterTraits::pointer;
        using const_pointer       = typename OuterTraits::const_pointer;
        using void_pointer        = typename OuterTraits::void_pointer;
        using const_void_pointer  = typename OuterTraits::const_void_pointer;

        using propagate_on_container_copy_assignment = see below;
        using propagate_on_container_move_assignment = see below;
        using propagate_on_container_swap            = see below;
        using is_always_equal                        = see below;

        template <class Tp>
            struct rebind {
                using other = scoped_allocator_adaptor<
                    OuterTraits::template rebind_alloc<Tp>, InnerAllocs...>;
            };

        scoped_allocator_adaptor();
        template <class OuterA2>
            scoped_allocator_adaptor(OuterA2&& outerAlloc,
                                    const InnerAllocs&... innerAllocs) noexcept;

        scoped_allocator_adaptor(const scoped_allocator_adaptor& other) noexcept;
        scoped_allocator_adaptor(scoped_allocator_adaptor&& other) noexcept;

```

```

template <class OuterA2>
    scoped_allocator_adaptor(
        const scoped_allocator_adaptor<OuterA2, InnerAllocs...>& other) noexcept;
template <class OuterA2>
    scoped_allocator_adaptor(
        scoped_allocator_adaptor<OuterA2, InnerAllocs...>&& other) noexcept;

scoped_allocator_adaptor& operator=(const scoped_allocator_adaptor&) = default;
scoped_allocator_adaptor& operator=(scoped_allocator_adaptor&&) = default;

~scoped_allocator_adaptor();

inner_allocator_type& inner_allocator() noexcept;
const inner_allocator_type& inner_allocator() const noexcept;
outer_allocator_type& outer_allocator() noexcept;
const outer_allocator_type& outer_allocator() const noexcept;

pointer allocate(size_type n);
pointer allocate(size_type n, const_void_pointer hint);
void deallocate(pointer p, size_type n);
size_type max_size() const;

template <class T, class... Args>
    void construct(T* p, Args&&... args);
template <class T1, class T2, class... Args1, class... Args2>
    void construct(pair<T1, T2>* p, piecewise_construct_t,
        tuple<Args1...> x, tuple<Args2...> y);
template <class T1, class T2>
    void construct(pair<T1, T2>* p);
template <class T1, class T2, class U, class V>
    void construct(pair<T1, T2>* p, U&& x, V&& y);
template <class T1, class T2, class U, class V>
    void construct(pair<T1, T2>* p, const pair<U, V>& x);
template <class T1, class T2, class U, class V>
    void construct(pair<T1, T2>* p, pair<U, V>&& x);

template <class T>
    void destroy(T* p);

scoped_allocator_adaptor select_on_container_copy_construction() const;
};

template<class OuterAlloc, class... InnerAllocs>
    scoped_allocator_adaptor(OuterAlloc, InnerAllocs...)
        -> scoped_allocator_adaptor<OuterAlloc, InnerAllocs...>;

template <class OuterA1, class OuterA2, class... InnerAllocs>
    bool operator==(const scoped_allocator_adaptor<OuterA1, InnerAllocs...>& a,
        const scoped_allocator_adaptor<OuterA2, InnerAllocs...>& b) noexcept;
template <class OuterA1, class OuterA2, class... InnerAllocs>
    bool operator!=(const scoped_allocator_adaptor<OuterA1, InnerAllocs...>& a,
        const scoped_allocator_adaptor<OuterA2, InnerAllocs...>& b) noexcept;
}

```

23.13.2 Scoped allocator adaptor member types [allocator.adaptor.types]

```
using inner_allocator_type = see below;

1      Type: scoped_allocator_adaptor<OuterAlloc> if sizeof...(InnerAllocs) is zero; otherwise,
      scoped_allocator_adaptor<InnerAllocs...>.

using propagate_on_container_copy_assignment = see below;

2      Type: true_type if allocator_traits<A>::propagate_on_container_copy_assignment::value is
      true for any A in the set of OuterAlloc and InnerAllocs...; otherwise, false_type.

using propagate_on_container_move_assignment = see below;

3      Type: true_type if allocator_traits<A>::propagate_on_container_move_assignment::value is
      true for any A in the set of OuterAlloc and InnerAllocs...; otherwise, false_type.

using propagate_on_container_swap = see below;

4      Type: true_type if allocator_traits<A>::propagate_on_container_swap::value is true for any
      A in the set of OuterAlloc and InnerAllocs...; otherwise, false_type.

using is_always_equal = see below;

5      Type: true_type if allocator_traits<A>::is_always_equal::value is true for every A in the set
      of OuterAlloc and InnerAllocs...; otherwise, false_type.
```

23.13.3 Scoped allocator adaptor constructors [allocator.adaptor.cnstr]

```
scoped_allocator_adaptor();

1      Effects: Value-initializes the OuterAlloc base class and the inner allocator object.

template <class OuterA2>
    scoped_allocator_adaptor(OuterA2&& outerAlloc,
                             const InnerAllocs&... innerAllocs) noexcept;

2      Effects: Initializes the OuterAlloc base class with std::forward<OuterA2>(outerAlloc) and inner
      with innerAllocs... (hence recursively initializing each allocator within the adaptor with the
      corresponding allocator from the argument list).

3      Remarks: This constructor shall not participate in overload resolution unless is_constructible_-
      v<OuterAlloc, OuterA2> is true.

scoped_allocator_adaptor(const scoped_allocator_adaptor& other) noexcept;

4      Effects: Initializes each allocator within the adaptor with the corresponding allocator from other.

scoped_allocator_adaptor(scoped_allocator_adaptor&& other) noexcept;

5      Effects: Move constructs each allocator within the adaptor with the corresponding allocator from
      other.

template <class OuterA2>
    scoped_allocator_adaptor(const scoped_allocator_adaptor<OuterA2,
                             InnerAllocs...>& other) noexcept;

6      Effects: Initializes each allocator within the adaptor with the corresponding allocator from other.

7      Remarks: This constructor shall not participate in overload resolution unless is_constructible_-
      v<OuterAlloc, const OuterA2&> is true.

template <class OuterA2>
```



```
scoped_allocator_adaptor(scoped_allocator_adaptor<OuterA2,
                          InnerAllocs...>&& other) noexcept;
```

8 *Effects:* Initializes each allocator within the adaptor with the corresponding allocator rvalue from *other*.

9 *Remarks:* This constructor shall not participate in overload resolution unless `is_constructible_v<OuterAlloc, OuterA2>` is true.

23.13.4 Scoped allocator adaptor members [allocator.adaptor.members]

1 In the `construct` member functions, `OUTERMOST(x)` is `x` if `x` does not have an `outer_allocator()` member function and `OUTERMOST(x.outer_allocator())` otherwise; `OUTERMOST_ALLOC_TRAITS(x)` is `allocator_traits<decltype(OUTERMOST(x))>`. [Note: `OUTERMOST(x)` and `OUTERMOST_ALLOC_TRAITS(x)` are recursive operations. It is incumbent upon the definition of `outer_allocator()` to ensure that the recursion terminates. It will terminate for all instantiations of `scoped_allocator_adaptor`. — end note]

```
inner_allocator_type& inner_allocator() noexcept;
const inner_allocator_type& inner_allocator() const noexcept;
```

2 *Returns:* `*this` if `sizeof...(InnerAllocs)` is zero; otherwise, `inner`.

```
outer_allocator_type& outer_allocator() noexcept;
```

3 *Returns:* `static_cast<OuterAlloc&>(*this)`.

```
const outer_allocator_type& outer_allocator() const noexcept;
```

4 *Returns:* `static_cast<const OuterAlloc&>(*this)`.

```
pointer allocate(size_type n);
```

5 *Returns:* `allocator_traits<OuterAlloc>::allocate(outer_allocator(), n)`.

```
pointer allocate(size_type n, const_void_pointer hint);
```

6 *Returns:* `allocator_traits<OuterAlloc>::allocate(outer_allocator(), n, hint)`.

```
void deallocate(pointer p, size_type n) noexcept;
```

7 *Effects:* As if by: `allocator_traits<OuterAlloc>::deallocate(outer_allocator(), p, n)`;

```
size_type max_size() const;
```

8 *Returns:* `allocator_traits<OuterAlloc>::max_size(outer_allocator())`.

```
template <class T, class... Args>
void construct(T* p, Args&&... args);
```

9 *Effects:*

(9.1) — If `uses_allocator_v<T, inner_allocator_type>` is false and `is_constructible_v<T, Args...>` is true, calls:

```
OUTERMOST_ALLOC_TRAITS(*this)::construct(
    OUTERMOST(*this), p, std::forward<Args>(args)...)

```

(9.2) — Otherwise, if `uses_allocator_v<T, inner_allocator_type>` is true and `is_constructible_v<T, allocator_arg_t, inner_allocator_type&, Args...>` is true, calls:

```
OUTERMOST_ALLOC_TRAITS(*this)::construct(
    OUTERMOST(*this), p, allocator_arg, inner_allocator(), std::forward<Args>(args)...)

```

(9.3) — Otherwise, if `uses_allocator_v<T, inner_allocator_type>` is true and `is_constructible_v<T, Args..., inner_allocator_type&>` is true, calls:

```

    OUTERMOST_ALLOC_TRAITS(*this)::construct(
        OUTERMOST(*this), p, std::forward<Args>(args)..., inner_allocator())

```

- (9.4) — Otherwise, the program is ill-formed. [*Note: An error will result if uses_allocator evaluates to true but the specific constructor does not take an allocator. This definition prevents a silent failure to pass an inner allocator to a contained element. — end note*]

```

template <class T1, class T2, class... Args1, class... Args2>
void construct(pair<T1, T2>* p, piecewise_construct_t,
    tuple<Args1...> x, tuple<Args2...> y);

```

10 *Requires:* all of the types in Args1 and Args2 shall be CopyConstructible (Table 24).

11 *Effects:* Constructs a tuple object xprime from x by the following rules:

- (11.1) — If uses_allocator_v<T1, inner_allocator_type> is false and is_constructible_v<T1, Args1...> is true, then xprime is x.
- (11.2) — Otherwise, if uses_allocator_v<T1, inner_allocator_type> is true and is_constructible_v<T1, allocator_arg_t, inner_allocator_type&, Args1...> is true, then xprime is:
- ```

 tuple_cat(
 tuple<allocator_arg_t, inner_allocator_type&>(allocator_arg, inner_allocator()),
 std::move(x))

```
- (11.3) — Otherwise, if uses\_allocator\_v<T1, inner\_allocator\_type> is true and is\_constructible\_v<T1, Args1..., inner\_allocator\_type&> is true, then xprime is:
- ```

    tuple_cat(std::move(x), tuple<inner_allocator_type&>(inner_allocator()))

```
- (11.4) — Otherwise, the program is ill-formed.

and constructs a tuple object yprime from y by the following rules:

- (11.5) — If uses_allocator_v<T2, inner_allocator_type> is false and is_constructible_v<T2, Args2...> is true, then yprime is y.
- (11.6) — Otherwise, if uses_allocator_v<T2, inner_allocator_type> is true and is_constructible_v<T2, allocator_arg_t, inner_allocator_type&, Args2...> is true, then yprime is:
- ```

 tuple_cat(
 tuple<allocator_arg_t, inner_allocator_type&>(allocator_arg, inner_allocator()),
 std::move(y))

```
- (11.7) — Otherwise, if uses\_allocator\_v<T2, inner\_allocator\_type> is true and is\_constructible\_v<T2, Args2..., inner\_allocator\_type&> is true, then yprime is:
- ```

    tuple_cat(std::move(y), tuple<inner_allocator_type&>(inner_allocator()))

```
- (11.8) — Otherwise, the program is ill-formed.

then calls:

```

    OUTERMOST_ALLOC_TRAITS(*this)::construct(
        OUTERMOST(*this), p, piecewise_construct, std::move(xprime), std::move(yprime))

```

```

template <class T1, class T2>
void construct(pair<T1, T2>* p);

```

12 *Effects:* Equivalent to:

```

    construct(p, piecewise_construct, tuple<>(), tuple<>());

```

```

template <class T1, class T2, class U, class V>
void construct(pair<T1, T2>* p, U&& x, V&& y);

```

13 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(std::forward<U>(x)),
         forward_as_tuple(std::forward<V>(y)));
```

```
template <class T1, class T2, class U, class V>
void construct(pair<T1, T2>* p, const pair<U, V>& x);
```

14 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(x.first),
         forward_as_tuple(x.second));
```

```
template <class T1, class T2, class U, class V>
void construct(pair<T1, T2>* p, pair<U, V>&& x);
```

15 *Effects:* Equivalent to:

```
construct(p, piecewise_construct,
         forward_as_tuple(std::forward<U>(x.first)),
         forward_as_tuple(std::forward<V>(x.second)));
```

```
template <class T>
void destroy(T* p);
```

16 *Effects:* Calls `OUTERMOST_ALLOC_TRAITS(*this)::destroy(OUTERMOST(*this), p)`.

```
scoped_allocator_adaptor select_on_container_copy_construction() const;
```

17 *Returns:* A new `scoped_allocator_adaptor` object where each allocator `A` in the adaptor is initialized from the result of calling `allocator_traits<A>::select_on_container_copy_construction()` on the corresponding allocator in `*this`.

23.13.5 Scoped allocator operators

[scoped.adaptor.operators]

```
template <class OuterA1, class OuterA2, class... InnerAllocs>
bool operator==(const scoped_allocator_adaptor<OuterA1, InnerAllocs...>& a,
               const scoped_allocator_adaptor<OuterA2, InnerAllocs...>& b) noexcept;
```

1 *Returns:* If `sizeof...(InnerAllocs)` is zero,

```
a.outer_allocator() == b.outer_allocator()
```

otherwise

```
a.outer_allocator() == b.outer_allocator() && a.inner_allocator() == b.inner_allocator()
```

```
template <class OuterA1, class OuterA2, class... InnerAllocs>
bool operator!=(const scoped_allocator_adaptor<OuterA1, InnerAllocs...>& a,
               const scoped_allocator_adaptor<OuterA2, InnerAllocs...>& b) noexcept;
```

2 *Returns:* `!(a == b)`.

23.14 Function objects

[function.objects]

1 A *function object type* is an object type (6.9) that can be the type of the *postfix-expression* in a function call (8.2.2, 16.3.1.1).²²² A *function object* is an object of a function object type. In the places where one would expect to pass a pointer to a function to an algorithmic template (Clause 28), the interface is specified to

²²² Such a type is a function pointer or a class type which has a member `operator()` or a class type which has a conversion to a pointer to function.

accept a function object. This not only makes algorithmic templates work with pointers to functions, but also enables them to work with arbitrary function objects.

23.14.1 Header <functional> synopsis

[functional.syn]

```
namespace std {
    // 23.14.4, invoke
    template <class F, class... Args>
        invoke_result_t<F, Args...> invoke(F&& f, Args&&... args)
            noexcept(is_nothrow_invocable_v<F, Args...>);

    // 23.14.5, reference_wrapper
    template <class T> class reference_wrapper;

    template <class T> reference_wrapper<T> ref(T&) noexcept;
    template <class T> reference_wrapper<const T> cref(const T&) noexcept;
    template <class T> void ref(const T&&) = delete;
    template <class T> void cref(const T&&) = delete;

    template <class T> reference_wrapper<T> ref(reference_wrapper<T>) noexcept;
    template <class T> reference_wrapper<const T> cref(reference_wrapper<T>) noexcept;

    // 23.14.6, arithmetic operations
    template <class T = void> struct plus;
    template <class T = void> struct minus;
    template <class T = void> struct multiplies;
    template <class T = void> struct divides;
    template <class T = void> struct modulus;
    template <class T = void> struct negate;
    template <> struct plus<void>;
    template <> struct minus<void>;
    template <> struct multiplies<void>;
    template <> struct divides<void>;
    template <> struct modulus<void>;
    template <> struct negate<void>;

    // 23.14.7, comparisons
    template <class T = void> struct equal_to;
    template <class T = void> struct not_equal_to;
    template <class T = void> struct greater;
    template <class T = void> struct less;
    template <class T = void> struct greater_equal;
    template <class T = void> struct less_equal;
    template <> struct equal_to<void>;
    template <> struct not_equal_to<void>;
    template <> struct greater<void>;
    template <> struct less<void>;
    template <> struct greater_equal<void>;
    template <> struct less_equal<void>;

    // 23.14.8, logical operations
    template <class T = void> struct logical_and;
    template <class T = void> struct logical_or;
    template <class T = void> struct logical_not;
    template <> struct logical_and<void>;
    template <> struct logical_or<void>;
```

```

template <> struct logical_not<void>;

// 23.14.9, bitwise operations
template <class T = void> struct bit_and;
template <class T = void> struct bit_or;
template <class T = void> struct bit_xor;
template <class T = void> struct bit_not;
template <> struct bit_and<void>;
template <> struct bit_or<void>;
template <> struct bit_xor<void>;
template <> struct bit_not<void>;

// 23.14.10, function template not_fn
template <class F>
    unspecified not_fn(F&& f);

// 23.14.11, bind
template<class T> struct is_bind_expression;
template<class T> struct is_placeholder;

template<class F, class... BoundArgs>
    unspecified bind(F&&, BoundArgs&&...);
template<class R, class F, class... BoundArgs>
    unspecified bind(F&&, BoundArgs&&...);

namespace placeholders {
    // M is the implementation-defined number of placeholders
    see below _1;
    see below _2;
    .
    .
    .
    see below _M;
}

// 23.14.12, member function adaptors
template<class R, class T>
    unspecified mem_fn(R T::*) noexcept;

// 23.14.13, polymorphic function wrappers
class bad_function_call;

template<class> class function; // not defined
template<class R, class... ArgTypes> class function<R(ArgTypes...)>;

template<class R, class... ArgTypes>
    void swap(function<R(ArgTypes...)>&, function<R(ArgTypes...)>&) noexcept;

template<class R, class... ArgTypes>
    bool operator==(const function<R(ArgTypes...)>&, nullptr_t) noexcept;
template<class R, class... ArgTypes>
    bool operator==(nullptr_t, const function<R(ArgTypes...)>&) noexcept;
template<class R, class... ArgTypes>
    bool operator!=(const function<R(ArgTypes...)>&, nullptr_t) noexcept;
template<class R, class... ArgTypes>

```

```

    bool operator!=(nullptr_t, const function<R(ArgTypes...)>&) noexcept;

// 23.14.14, searchers
template<class ForwardIterator, class BinaryPredicate = equal_to<>>
    class default_searcher;

template<class RandomAccessIterator,
        class Hash = hash<typename iterator_traits<RandomAccessIterator>::value_type>,
        class BinaryPredicate = equal_to<>>
    class boyer_moore_searcher;

template<class RandomAccessIterator,
        class Hash = hash<typename iterator_traits<RandomAccessIterator>::value_type>,
        class BinaryPredicate = equal_to<>>
    class boyer_moore_horspool_searcher;

// 23.14.15, hash function primary template
template <class T>
    struct hash;

// 23.14.11, function object binders
template <class T>
    inline constexpr bool is_bind_expression_v = is_bind_expression<T>::value;
template <class T>
    inline constexpr int is_placeholder_v = is_placeholder<T>::value;
}

```

- ¹ [Example: If a C++ program wants to have a by-element addition of two vectors **a** and **b** containing double and put the result into **a**, it can do:

```
transform(a.begin(), a.end(), b.begin(), a.begin(), plus<double>());
```

— end example]

- ² [Example: To negate every element of **a**:

```
transform(a.begin(), a.end(), a.begin(), negate<double>());
```

— end example]

23.14.2 Definitions

[func.def]

- ¹ The following definitions apply to this Clause:
- ² A *call signature* is the name of a return type followed by a parenthesized comma-separated list of zero or more argument types.
- ³ A *callable type* is a function object type (23.14) or a pointer to member.
- ⁴ A *callable object* is an object of a callable type.
- ⁵ A *call wrapper type* is a type that holds a callable object and supports a call operation that forwards to that object.
- ⁶ A *call wrapper* is an object of a call wrapper type.
- ⁷ A *target object* is the callable object held by a call wrapper.

23.14.3 Requirements

[func.require]

- ¹ Define *INVOKE*(**f**, **t1**, **t2**, ..., **tN**) as follows:
- (1.1) — (**t1**.***f**)(**t2**, ..., **tN**) when **f** is a pointer to a member function of a class **T** and *is_base_of_v*<**T**,

`decay_t<decltype(t1)>>` is true;

- (1.2) — `(t1.get().*f)(t2, ..., tN)` when `f` is a pointer to a member function of a class `T` and `decay_t<decltype(t1)>` is a specialization of `reference_wrapper`;
- (1.3) — `((*t1).*f)(t2, ..., tN)` when `f` is a pointer to a member function of a class `T` and `t1` does not satisfy the previous two items;
- (1.4) — `t1.*f` when `N == 1` and `f` is a pointer to data member of a class `T` and `is_base_of_v<T, decay_t<decltype(t1)>>` is true;
- (1.5) — `t1.get().*f` when `N == 1` and `f` is a pointer to data member of a class `T` and `decay_t<decltype(t1)>` is a specialization of `reference_wrapper`;
- (1.6) — `(*t1).*f` when `N == 1` and `f` is a pointer to data member of a class `T` and `t1` does not satisfy the previous two items;
- (1.7) — `f(t1, t2, ..., tN)` in all other cases.

² Define `INVOKE<R>(f, t1, t2, ..., tN)` as `static_cast<void>(INVOKE(f, t1, t2, ..., tN))` if `R` is *cv* void, otherwise `INVOKE(f, t1, t2, ..., tN)` implicitly converted to `R`.

³ Every call wrapper (23.14.2) shall be `MoveConstructible`. A *forwarding call wrapper* is a call wrapper that can be called with an arbitrary argument list and delivers the arguments to the wrapped callable object as references. This forwarding step shall ensure that rvalue arguments are delivered as rvalue references and lvalue arguments are delivered as lvalue references. A *simple call wrapper* is a forwarding call wrapper that is `CopyConstructible` and `CopyAssignable` and whose copy constructor, move constructor, and assignment operator do not throw exceptions. [Note: In a typical implementation forwarding call wrappers have an overloaded function call operator of the form

```
template<class... UnBoundArgs>
R operator()(UnBoundArgs&&... unbound_args) cv-qual;
```

— end note]

23.14.4 Function template invoke

[func.invoke]

```
template <class F, class... Args>
invoke_result_t<F, Args...> invoke(F&& f, Args&&... args)
noexcept(is_nothrow_invocable_v<F, Args...>);
```

¹ Returns: `INVOKE(std::forward<F>(f), std::forward<Args>(args)...) (23.14.3).`

23.14.5 Class template reference_wrapper

[refwrap]

```
namespace std {
    template <class T> class reference_wrapper {
    public:
        // types
        using type = T;

        // construct/copy/destroy
        reference_wrapper(T&) noexcept;
        reference_wrapper(T&&) = delete; // do not bind to temporary objects
        reference_wrapper(const reference_wrapper& x) noexcept;

        // assignment
        reference_wrapper& operator=(const reference_wrapper& x) noexcept;

        // access
        operator T& () const noexcept;
```

```

    T& get() const noexcept;

    // invocation
    template <class... ArgTypes>
        invoke_result_t<T&, ArgTypes...>
        operator() (ArgTypes&&...) const;
};

template<class T>
    reference_wrapper(reference_wrapper<T>) -> reference_wrapper<T>;
}

```

¹ `reference_wrapper<T>` is a CopyConstructible and CopyAssignable wrapper around a reference to an object or function of type T.

² `reference_wrapper<T>` shall be a trivially copyable type (6.9).

23.14.5.1 reference_wrapper construct/copy/destroy [refwrap.const]

```
reference_wrapper(T& t) noexcept;
```

¹ *Effects:* Constructs a `reference_wrapper` object that stores a reference to `t`.

```
reference_wrapper(const reference_wrapper& x) noexcept;
```

² *Effects:* Constructs a `reference_wrapper` object that stores a reference to `x.get()`.

23.14.5.2 reference_wrapper assignment [refwrap.assign]

```
reference_wrapper& operator=(const reference_wrapper& x) noexcept;
```

¹ *Postconditions:* `*this` stores a reference to `x.get()`.

23.14.5.3 reference_wrapper access [refwrap.access]

```
operator T& () const noexcept;
```

¹ *Returns:* The stored reference.

```
T& get() const noexcept;
```

² *Returns:* The stored reference.

23.14.5.4 reference_wrapper invocation [refwrap.invoke]

```

template <class... ArgTypes>
    invoke_result_t<T&, ArgTypes...>
    operator() (ArgTypes&&... args) const;

```

¹ *Returns:* `INVOKE(get(), std::forward<ArgTypes>(args)...) (23.14.3)`

23.14.5.5 reference_wrapper helper functions [refwrap.helpers]

```
template <class T> reference_wrapper<T> ref(T& t) noexcept;
```

¹ *Returns:* `reference_wrapper<T>(t)`.

```
template <class T> reference_wrapper<T> ref(reference_wrapper<T> t) noexcept;
```

² *Returns:* `ref(t.get())`.

```
template <class T> reference_wrapper<const T> cref(const T& t) noexcept;
```

³ *Returns:* `reference_wrapper <const T>(t)`.


```
template <class T> reference_wrapper<const T> cref(reference_wrapper<T> t) noexcept;
```

4 *Returns:* cref(t.get()).

23.14.6 Arithmetic operations [arithmetic.operations]

1 The library provides basic function object classes for all of the arithmetic operators in the language (8.6, 8.7).

23.14.6.1 Class template plus [arithmetic.operations.plus]

```
template <class T = void> struct plus {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* x + y.

```
template <> struct plus<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) + std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) + std::forward<U>(u));
```

2 *Returns:* std::forward<T>(t) + std::forward<U>(u).

23.14.6.2 Class template minus [arithmetic.operations.minus]

```
template <class T = void> struct minus {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* x - y.

```
template <> struct minus<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) - std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) - std::forward<U>(u));
```

2 *Returns:* std::forward<T>(t) - std::forward<U>(u).

23.14.6.3 Class template multiplies [arithmetic.operations.multiplies]

```
template <class T = void> struct multiplies {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* x * y.

```
template <> struct multiplies<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) * std::forward<U>(u));

    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) * std::forward<U>(u));
```

² *Returns:* std::forward<T>(t) * std::forward<U>(u).

23.14.6.4 Class template divides [arithmetic.operations.divides]

```
template <class T = void> struct divides {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

¹ *Returns:* x / y.

```
template <> struct divides<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) / std::forward<U>(u));

    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) / std::forward<U>(u));
```

² *Returns:* std::forward<T>(t) / std::forward<U>(u).

23.14.6.5 Class template modulus [arithmetic.operations.modulus]

```
template <class T = void> struct modulus {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

¹ *Returns:* x % y.

```
template <> struct modulus<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) % std::forward<U>(u));

    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) % std::forward<U>(u));
```

² *Returns:* std::forward<T>(t) % std::forward<U>(u).

23.14.6.6 Class template negate [arithmetic.operations.negate]

```
template <class T = void> struct negate {
    constexpr T operator()(const T& x) const;
};
```

```
constexpr T operator()(const T& x) const;
```

1 *Returns: -x.*

```
template <> struct negate<void> {
    template <class T> constexpr auto operator()(T&& t) const
        -> decltype(-std::forward<T>(t));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T> constexpr auto operator()(T&& t) const
    -> decltype(-std::forward<T>(t));
```

2 *Returns: -std::forward<T>(t).*

23.14.7 Comparisons

[comparisons]

1 The library provides basic function object classes for all of the comparison operators in the language (8.9, 8.10).

2 For templates `less`, `greater`, `less_equal`, and `greater_equal`, the specializations for any pointer type yield a strict total order that is consistent among those specializations and is also consistent with the partial order imposed by the built-in operators `<`, `>`, `<=`, `>=`. [Note: When `a < b` is well-defined for pointers `a` and `b` of type `P`, this implies `(a < b) == less<P>(a, b)`, `(a > b) == greater<P>(a, b)`, and so forth. —end note] For template specializations `less<void>`, `greater<void>`, `less_equal<void>`, and `greater_equal<void>`, if the call operator calls a built-in operator comparing pointers, the call operator yields a strict total order that is consistent among those specializations and is also consistent with the partial order imposed by those built-in operators.

23.14.7.1 Class template `equal_to`

[comparisons.equal_to]

```
template <class T = void> struct equal_to {
    constexpr bool operator()(const T& x, const T& y) const;
```

```
};

constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x == y.*

```
template <> struct equal_to<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) == std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) == std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) == std::forward<U>(u).*

23.14.7.2 Class template `not_equal_to`

[comparisons.not_equal_to]

```
template <class T = void> struct not_equal_to {
    constexpr bool operator()(const T& x, const T& y) const;
```

```
};

constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x != y.*

```
template <> struct not_equal_to<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) != std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) != std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) != std::forward<U>(u).*

23.14.7.3 Class template greater

[comparisons.greater]

```
template <class T = void> struct greater {
    constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x > y.*

```
template <> struct greater<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) > std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) > std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) > std::forward<U>(u).*

23.14.7.4 Class template less

[comparisons.less]

```
template <class T = void> struct less {
    constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x < y.*

```
template <> struct less<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) < std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) < std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) < std::forward<U>(u).*

23.14.7.5 Class template greater_equal

[comparisons.greater_equal]

```
template <class T = void> struct greater_equal {
```

```
constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x >= y.*

```
template <> struct greater_equal<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) >= std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) >= std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) >= std::forward<U>(u).*

23.14.7.6 Class template less_equal

[comparisons.less_equal]

```
template <class T = void> struct less_equal {
    constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x <= y.*

```
template <> struct less_equal<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) <= std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) <= std::forward<U>(u));
```

2 *Returns: std::forward<T>(t) <= std::forward<U>(u).*

23.14.8 Logical operations

[logical.operations]

1 The library provides basic function object classes for all of the logical operators in the language (8.14, 8.15, 8.3.1).

23.14.8.1 Class template logical_and

[logical.operations.and]

```
template <class T = void> struct logical_and {
    constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns: x && y.*

```
template <> struct logical_and<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) && std::forward<U>(u));
```

```
    using is_transparent = unspecified;
```

```
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
-> decltype(std::forward<T>(t) && std::forward<U>(u));
```

2 *Returns:* std::forward<T>(t) && std::forward<U>(u).

23.14.8.2 Class template logical_or

[logical.operations.or]

```
template <class T = void> struct logical_or {
    constexpr bool operator()(const T& x, const T& y) const;
};
```

```
constexpr bool operator()(const T& x, const T& y) const;
```

1 *Returns:* x || y.

```
template <> struct logical_or<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) || std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
-> decltype(std::forward<T>(t) || std::forward<U>(u));
```

2 *Returns:* std::forward<T>(t) || std::forward<U>(u).

23.14.8.3 Class template logical_not

[logical.operations.not]

```
template <class T = void> struct logical_not {
    constexpr bool operator()(const T& x) const;
};
```

```
constexpr bool operator()(const T& x) const;
```

1 *Returns:* !x.

```
template <> struct logical_not<void> {
    template <class T> constexpr auto operator()(T&& t) const
    -> decltype(!std::forward<T>(t));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T> constexpr auto operator()(T&& t) const
-> decltype(!std::forward<T>(t));
```

2 *Returns:* !std::forward<T>(t).

23.14.9 Bitwise operations

[bitwise.operations]

1 The library provides basic function object classes for all of the bitwise operators in the language (8.11, 8.13, 8.12, 8.3.1).

23.14.9.1 Class template bit_and

[bitwise.operations.and]

```
template <class T = void> struct bit_and {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* $x \& y$.

```
template <> struct bit_and<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) & std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) & std::forward<U>(u));
```

2 *Returns:* $\text{std::forward<T>(t)} \& \text{std::forward<U>(u)}$.

23.14.9.2 Class template bit_or

[bitwise.operations.or]

```
template <class T = void> struct bit_or {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* $x \mid y$.

```
template <> struct bit_or<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) \mid std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) \mid std::forward<U>(u));
```

2 *Returns:* $\text{std::forward<T>(t)} \mid \text{std::forward<U>(u)}$.

23.14.9.3 Class template bit_xor

[bitwise.operations.xor]

```
template <class T = void> struct bit_xor {
    constexpr T operator()(const T& x, const T& y) const;
};
```

```
constexpr T operator()(const T& x, const T& y) const;
```

1 *Returns:* $x \wedge y$.

```
template <> struct bit_xor<void> {
    template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
        -> decltype(std::forward<T>(t) ^ std::forward<U>(u));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T, class U> constexpr auto operator()(T&& t, U&& u) const
    -> decltype(std::forward<T>(t) ^ std::forward<U>(u));
```

2 *Returns:* $\text{std::forward<T>(t)} \wedge \text{std::forward<U>(u)}$.

23.14.9.4 Class template bit_not

[bitwise.operations.not]

```
template <class T = void> struct bit_not {
    constexpr T operator()(const T& x) const;
};
```

```
constexpr T operator()(const T& x) const;
```

1 *Returns: ~x.*

```
template <> struct bit_not<void> {
    template <class T> constexpr auto operator()(T&& t) const
        -> decltype(~std::forward<T>(t));
```

```
    using is_transparent = unspecified;
};
```

```
template <class T> constexpr auto operator()(T&&) const
    -> decltype(~std::forward<T>(t));
```

2 *Returns: ~std::forward<T>(t).*

23.14.10 Function template not_fn

[func.not_fn]

```
template <class F> unspecified not_fn(F&& f);
```

1 *Effects:* Equivalent to return *call_wrapper*(std::forward<F>(f)); where *call_wrapper* is an exposition only class defined as follows:

```
class call_wrapper {
    using FD = decay_t<F>;
    FD fd;

    explicit call_wrapper(F&& f);

public:
    call_wrapper(call_wrapper&&) = default;
    call_wrapper(const call_wrapper&) = default;

    template<class... Args>
        auto operator()(Args&&...) &
            -> decltype(!declval<invoke_result_t<FD&, Args...>>());

    template<class... Args>
        auto operator()(Args&&...) const&
            -> decltype(!declval<invoke_result_t<const FD&, Args...>>());

    template<class... Args>
        auto operator()(Args&&...) &&
            -> decltype(!declval<invoke_result_t<FD, Args...>>());

    template<class... Args>
        auto operator()(Args&&...) const&&
            -> decltype(!declval<invoke_result_t<const FD, Args...>>());
};
```

```
explicit call_wrapper(F&& f);
```

2 *Requires:* FD shall satisfy the requirements of MoveConstructible. is_constructible_v<FD, F> shall be true. fd shall be a callable object (23.14.2).

3 *Effects:* Initializes `fd` from `std::forward<F>(f)`.

4 *Throws:* Any exception thrown by construction of `fd`.

```
template<class... Args>
    auto operator()(Args&&... args) &
        -> decltype(!declval<invoke_result_t<FD&, Args...>>());
template<class... Args>
    auto operator()(Args&&... args) const&
        -> decltype(!declval<invoke_result_t<const FD&, Args...>>());
```

5 *Effects:* Equivalent to:

```
    return !INVOKE(fd, std::forward<Args>(args)...);           // see 23.14.3
```

```
template<class... Args>
    auto operator()(Args&&... args) &&
        -> decltype(!declval<invoke_result_t<FD, Args...>>());
template<class... Args>
    auto operator()(Args&&... args) const&&
        -> decltype(!declval<invoke_result_t<const FD, Args...>>());
```

6 *Effects:* Equivalent to:

```
    return !INVOKE(std::move(fd), std::forward<Args>(args)...); // see 23.14.3
```

23.14.11 Function object binders

[func.bind]

1 This subclause describes a uniform mechanism for binding arguments of callable objects.

23.14.11.1 Class template `is_bind_expression`

[func.bind.isbind]

```
namespace std {
    template<class T> struct is_bind_expression; // see below
}
```

1 The class template `is_bind_expression` can be used to detect function objects generated by `bind`. The function template `bind` uses `is_bind_expression` to detect subexpressions.

2 Instantiations of the `is_bind_expression` template shall meet the `UnaryTypeTrait` requirements (23.15.1). The implementation shall provide a definition that has a base characteristic of `true_type` if `T` is a type returned from `bind`, otherwise it shall have a base characteristic of `false_type`. A program may specialize this template for a user-defined type `T` to have a base characteristic of `true_type` to indicate that `T` should be treated as a subexpression in a `bind` call.

23.14.11.2 Class template `is_placeholder`

[func.bind.isplace]

```
namespace std {
    template<class T> struct is_placeholder; // see below
}
```

1 The class template `is_placeholder` can be used to detect the standard placeholders `_1`, `_2`, and so on. The function template `bind` uses `is_placeholder` to detect placeholders.

2 Instantiations of the `is_placeholder` template shall meet the `UnaryTypeTrait` requirements (23.15.1). The implementation shall provide a definition that has the base characteristic of `integral_constant<int, J>` if `T` is the type of `std::placeholders::_J`, otherwise it shall have a base characteristic of `integral_constant<int, 0>`. A program may specialize this template for a user-defined type `T` to have a base characteristic of `integral_constant<int, N>` with `N > 0` to indicate that `T` should be treated as a place-

holder type.

23.14.11.3 Function template bind

[func.bind.bind]

1 In the text that follows:

- (1.1) — `FD` is the type `decay_t<F>`,
- (1.2) — `fd` is an lvalue of type `FD` constructed from `std::forward<F>(f)`,
- (1.3) — T_i is the i^{th} type in the template parameter pack `BoundArgs`,
- (1.4) — `TDi` is the type `decay_t<Ti>`,
- (1.5) — `ti` is the i^{th} argument in the function parameter pack `bound_args`,
- (1.6) — `tdi` is an lvalue of type `TDi` constructed from `std::forward<Ti>(ti)`,
- (1.7) — U_j is the j^{th} deduced type of the `UnBoundArgs&&...` parameter of the forwarding call wrapper, and
- (1.8) — `uj` is the j^{th} argument associated with U_j .

```
template<class F, class... BoundArgs>
    unspecified bind(F&& f, BoundArgs&&... bound_args);
```

2 *Requires:* `is_constructible_v<FD, F>` shall be true. For each T_i in `BoundArgs`, `is_constructible_v<TDi, Ti>` shall be true. `INVOKE(fd, w1, w2, ..., wN)` (23.14.3) shall be a valid expression for some values `w1, w2, ..., wN`, where N has the value `sizeof...(bound_args)`. The cv-qualifiers *cv* of the call wrapper `g`, as specified below, shall be neither `volatile` nor `const volatile`.

3 *Returns:* A forwarding call wrapper `g` (23.14.3). The effect of `g(u1, u2, ..., uM)` shall be

```
INVOKE(fd, std::forward<V1>(v1), std::forward<V2>(v2), ..., std::forward<VN>(vN))
```

where the values and types of the bound arguments `v1, v2, ..., vN` are determined as specified below. The copy constructor and move constructor of the forwarding call wrapper shall throw an exception if and only if the corresponding constructor of `FD` or of any of the types `TDi` throws an exception.

4 *Throws:* Nothing unless the construction of `fd` or of one of the values `tdi` throws an exception.

5 *Remarks:* The return type shall satisfy the requirements of `MoveConstructible`. If all of `FD` and `TDi` satisfy the requirements of `CopyConstructible`, then the return type shall satisfy the requirements of `CopyConstructible`. [Note: This implies that all of `FD` and `TDi` are `MoveConstructible`. — end note]

```
template<class R, class F, class... BoundArgs>
    unspecified bind(F&& f, BoundArgs&&... bound_args);
```

6 *Requires:* `is_constructible_v<FD, F>` shall be true. For each T_i in `BoundArgs`, `is_constructible_v<TDi, Ti>` shall be true. `INVOKE(fd, w1, w2, ..., wN)` shall be a valid expression for some values `w1, w2, ..., wN`, where N has the value `sizeof...(bound_args)`. The cv-qualifiers *cv* of the call wrapper `g`, as specified below, shall be neither `volatile` nor `const volatile`.

7 *Returns:* A forwarding call wrapper `g` (23.14.3). The effect of `g(u1, u2, ..., uM)` shall be

```
INVOKE<R>(fd, std::forward<V1>(v1), std::forward<V2>(v2), ..., std::forward<VN>(vN))
```

where the values and types of the bound arguments `v1, v2, ..., vN` are determined as specified below. The copy constructor and move constructor of the forwarding call wrapper shall throw an exception if and only if the corresponding constructor of `FD` or of any of the types `TDi` throws an exception.

8 *Throws:* Nothing unless the construction of `fd` or of one of the values `tdi` throws an exception.

9 *Remarks:* The return type shall satisfy the requirements of `MoveConstructible`. If all of `FD` and `TDi` satisfy the requirements of `CopyConstructible`, then the return type shall satisfy the requirements of `CopyConstructible`. [Note: This implies that all of `FD` and `TDi` are `MoveConstructible`. — end note]

note]

- ¹⁰ The values of the *bound arguments* $v_1, v_2, \dots, v_N$ and their corresponding types $V_1, V_2, \dots, V_N$ depend on the types TD_i derived from the call to `bind` and the cv-qualifiers *cv* of the call wrapper *g* as follows:
- (10.1) — if TD_i is `reference_wrapper<T>`, the argument is `tdi.get()` and its type V_i is `T&`;
 - (10.2) — if the value of `is_bind_expression_v<TDi>` is `true`, the argument is `tdi(std::forward<Uj>(uj)...)` and its type V_i is `invoke_result_t<TDi cv &, Uj...>&&`;
 - (10.3) — if the value *j* of `is_placeholder_v<TDi>` is not zero, the argument is `std::forward<Uj>(uj)` and its type V_i is `Uj&&`;
 - (10.4) — otherwise, the value is `tdi` and its type V_i is `TDi cv &`.

23.14.11.4 Placeholders

[func.bind.place]

```
namespace std::placeholders {
    // M is the implementation-defined number of placeholders
    see below _1;
    see below _2;
    .
    .
    .
    see below _M;
}
```

- ¹ All placeholder types shall be `DefaultConstructible` and `CopyConstructible`, and their default constructors and copy/move constructors shall not throw exceptions. It is implementation-defined whether placeholder types are `CopyAssignable`. `CopyAssignable` placeholders' copy assignment operators shall not throw exceptions.
- ² Placeholders should be defined as:

```
inline constexpr unspecified _1{};
```

If they are not, they shall be declared as:

```
extern unspecified _1;
```

23.14.12 Function template `mem_fn`

[func.memfn]

```
template<class R, class T> unspecified mem_fn(R T::* pm) noexcept;
```

- ¹ *Returns:* A simple call wrapper (23.14.2) `fn` such that the expression `fn(t, a2, ..., aN)` is equivalent to `INVOKE(pm, t, a2, ..., aN)` (23.14.3).

23.14.13 Polymorphic function wrappers

[func.wrap]

- ¹ This subclause describes a polymorphic wrapper class that encapsulates arbitrary callable objects.

23.14.13.1 Class `bad_function_call`

[func.wrap.badcall]

- ¹ An exception of type `bad_function_call` is thrown by `function::operator()` (23.14.13.2.4) when the function wrapper object has no target.

```
namespace std {
    class bad_function_call : public exception {
    public:
        // 23.14.13.1.1, constructor
        bad_function_call() noexcept;
    };
}
```

23.14.13.1.1 bad_function_call constructor**[func.wrap.badcall.const]**

```
bad_function_call() noexcept;
```

1 *Effects:* Constructs a `bad_function_call` object.

2 *Postconditions:* `what()` returns an implementation-defined NTBS.

23.14.13.2 Class template function**[func.wrap.func]**

```
namespace std {
    template<class> class function; // not defined

    template<class R, class... ArgTypes>
    class function<R(ArgTypes...)> {
    public:
        using result_type = R;

        // 23.14.13.2.1, construct/copy/destroy
        function() noexcept;
        function(nullptr_t) noexcept;
        function(const function&);
        function(function&&);
        template<class F> function(F);

        function& operator=(const function&);
        function& operator=(function&&);
        function& operator=(nullptr_t) noexcept;
        template<class F> function& operator=(F&&);
        template<class F> function& operator=(reference_wrapper<F>) noexcept;

        ~function();

        // 23.14.13.2.2, function modifiers
        void swap(function&) noexcept;

        // 23.14.13.2.3, function capacity
        explicit operator bool() const noexcept;

        // 23.14.13.2.4, function invocation
        R operator()(ArgTypes...) const;

        // 23.14.13.2.5, function target access
        const type_info& target_type() const noexcept;
        template<class T> T* target() noexcept;
        template<class T> const T* target() const noexcept;
    };

    template<class R, class... ArgTypes>
        function(R*)(ArgTypes...) -> function<R(ArgTypes...)>;

    template<class F> function(F) -> function<see below>;

    // 23.14.13.2.6, Null pointer comparisons
    template <class R, class... ArgTypes>
        bool operator==(const function<R(ArgTypes...)>&, nullptr_t) noexcept;
```

```

template <class R, class... ArgTypes>
    bool operator==(nullptr_t, const function<R(ArgTypes...)>&) noexcept;

template <class R, class... ArgTypes>
    bool operator!=(const function<R(ArgTypes...)>&, nullptr_t) noexcept;

template <class R, class... ArgTypes>
    bool operator!=(nullptr_t, const function<R(ArgTypes...)>&) noexcept;

// 23.14.13.2.7, specialized algorithms
template <class R, class... ArgTypes>
    void swap(function<R(ArgTypes...)>&, function<R(ArgTypes...)>&) noexcept;
}

```

- 1 The **function** class template provides polymorphic wrappers that generalize the notion of a function pointer. Wrappers can store, copy, and call arbitrary callable objects (23.14.2), given a call signature (23.14.2), allowing functions to be first-class objects.
- 2 A callable type (23.14.2) **F** is *Lvalue-Callable* for argument types **ArgTypes** and return type **R** if the expression `INVOKE<R>(declval<F>(), declval<ArgTypes>()...)`, considered as an unevaluated operand (Clause 8), is well formed (23.14.3).
- 3 The **function** class template is a call wrapper (23.14.2) whose call signature (23.14.2) is `R(ArgTypes...)`.
- 4 [*Note*: The types deduced by the deduction guides for **function** may change in future versions of this International Standard. — *end note*]

23.14.13.2.1 function construct/copy/destroy [func.wrap.func.con]

- ```

function() noexcept;

```
- 1 *Postconditions*: `!*this`.
- ```

function(nullptr_t) noexcept;

```
- 2 *Postconditions*: `!*this`.
- ```

function(const function& f);

```
- 3 *Postconditions*: `!*this` if `!f`; otherwise, `*this` targets a copy of `f.target()`.
  - 4 *Throws*: shall not throw exceptions if `f`'s target is a specialization of `reference_wrapper` or a function pointer. Otherwise, may throw `bad_alloc` or any exception thrown by the copy constructor of the stored callable object. [ *Note*: Implementations are encouraged to avoid the use of dynamically allocated memory for small callable objects, for example, where `f`'s target is an object holding only a pointer or reference to an object and a member function pointer. — *end note* ]
- ```

function(function&& f);

```
- 5 *Postconditions*: If `!f`, `*this` has no target; otherwise, the target of `*this` is equivalent to the target of `f` before the construction, and `f` is in a valid state with an unspecified value.
 - 6 *Throws*: shall not throw exceptions if `f`'s target is a specialization of `reference_wrapper` or a function pointer. Otherwise, may throw `bad_alloc` or any exception thrown by the copy or move constructor of the stored callable object. [*Note*: Implementations are encouraged to avoid the use of dynamically allocated memory for small callable objects, for example, where `f`'s target is an object holding only a pointer or reference to an object and a member function pointer. — *end note*]
- ```

template<class F> function(F f);

```
- 7 *Requires*: `F` shall be `CopyConstructible`.

8 *Remarks:* This constructor template shall not participate in overload resolution unless `F` is Lvalue-Callable (23.14.13.2) for argument types `ArgTypes...` and return type `R`.

9 *Postconditions:* `!*this` if any of the following hold:

(9.1) — `f` is a null function pointer value.

(9.2) — `f` is a null member pointer value.

(9.3) — `F` is an instance of the function class template, and `!f`.

10 Otherwise, `*this` targets a copy of `f` initialized with `std::move(f)`. [*Note:* Implementations are encouraged to avoid the use of dynamically allocated memory for small callable objects, for example, where `f` is an object holding only a pointer or reference to an object and a member function pointer. — end note]

11 *Throws:* shall not throw exceptions when `f` is a function pointer or a `reference_wrapper<T>` for some `T`. Otherwise, may throw `bad_alloc` or any exception thrown by `F`'s copy or move constructor.

```
template<class F> function(F) -> function<see below>;
```

12 *Remarks:* This deduction guide participates in overload resolution only if `&F::operator()` is well-formed when treated as an unevaluated operand. In that case, if `decltype(&F::operator())` is of the form `R(G::*)(A...) cv &opt noexceptopt` for a class type `G`, then the deduced type is `function<R(A...)>`.

13 [*Example:*

```
void f() {
 int i{5};
 function g = [&](double) { return i; }; // deduces function<int(double)>
}
```

— end example]

```
function& operator=(const function& f);
```

14 *Effects:* As if by `function(f).swap(*this)`;

15 *Returns:* `*this`.

```
function& operator=(function&& f);
```

16 *Effects:* Replaces the target of `*this` with the target of `f`.

17 *Returns:* `*this`.

```
function& operator=(nullptr_t) noexcept;
```

18 *Effects:* If `*this != nullptr`, destroys the target of `this`.

19 *Postconditions:* `!(*this)`.

20 *Returns:* `*this`.

```
template<class F> function& operator=(F&& f);
```

21 *Effects:* As if by: `function(std::forward<F>(f)).swap(*this)`;

22 *Returns:* `*this`.

23 *Remarks:* This assignment operator shall not participate in overload resolution unless `decay_t<F>` is Lvalue-Callable (23.14.13.2) for argument types `ArgTypes...` and return type `R`.

```
template<class F> function& operator=(reference_wrapper<F> f) noexcept;
```

24 *Effects:* As if by: `function(f).swap(*this)`;

25 *Returns:* `*this`.

`~function();`

26 *Effects:* If `*this != nullptr`, destroys the target of `this`.

### 23.14.13.2.2 function modifiers [func.wrap.func.mod]

`void swap(function& other) noexcept;`

1 *Effects:* interchanges the targets of `*this` and `other`.

### 23.14.13.2.3 function capacity [func.wrap.func.cap]

`explicit operator bool() const noexcept;`

1 *Returns:* true if `*this` has a target, otherwise false.

### 23.14.13.2.4 function invocation [func.wrap.func.inv]

`R operator()(ArgTypes... args) const;`

1 *Returns:* `INVOKE<R>(f, std::forward<ArgTypes>(args)...) (23.14.3)`, where `f` is the target object (23.14.2) of `*this`.

2 *Throws:* `bad_function_call` if `!*this`; otherwise, any exception thrown by the wrapped callable object.

### 23.14.13.2.5 function target access [func.wrap.func.targ]

`const type_info& target_type() const noexcept;`

1 *Returns:* If `*this` has a target of type `T`, `typeid(T)`; otherwise, `typeid(void)`.

`template<class T> T* target() noexcept;`  
`template<class T> const T* target() const noexcept;`

2 *Returns:* If `target_type() == typeid(T)` a pointer to the stored function target; otherwise a null pointer.

### 23.14.13.2.6 null pointer comparison functions [func.wrap.func.nullptr]

`template <class R, class... ArgTypes>`  
`bool operator==(const function<R(ArgTypes...)>& f, nullptr_t) noexcept;`  
`template <class R, class... ArgTypes>`  
`bool operator==(nullptr_t, const function<R(ArgTypes...)>& f) noexcept;`

1 *Returns:* `!f`.

`template <class R, class... ArgTypes>`  
`bool operator!=(const function<R(ArgTypes...)>& f, nullptr_t) noexcept;`  
`template <class R, class... ArgTypes>`  
`bool operator!=(nullptr_t, const function<R(ArgTypes...)>& f) noexcept;`

2 *Returns:* `(bool)f`.

### 23.14.13.2.7 specialized algorithms [func.wrap.func.alg]

`template<class R, class... ArgTypes>`  
`void swap(function<R(ArgTypes...)>& f1, function<R(ArgTypes...)>& f2) noexcept;`

1 *Effects:* As if by: `f1.swap(f2);`

**23.14.14 Searchers****[func.search]**

<sup>1</sup> This subclause provides function object types (23.14) for operations that search for a sequence [pat\_first, pat\_last) in another sequence [first, last) that is provided to the object's function call operator. The first sequence (the pattern to be searched for) is provided to the object's constructor, and the second (the sequence to be searched) is provided to the function call operator.

<sup>2</sup> Each specialization of a class template specified in this subclause 23.14.14 shall meet the CopyConstructible and CopyAssignable requirements. Template parameters named

- (2.1) — ForwardIterator,
- (2.2) — ForwardIterator1,
- (2.3) — ForwardIterator2,
- (2.4) — RandomAccessIterator,
- (2.5) — RandomAccessIterator1,
- (2.6) — RandomAccessIterator2, and
- (2.7) — BinaryPredicate

of templates specified in this subclause 23.14.14 shall meet the same requirements and semantics as specified in 28.1. Template parameters named Hash shall meet the requirements as specified in 20.5.3.4.

<sup>3</sup> The Boyer-Moore searcher implements the Boyer-Moore search algorithm. The Boyer-Moore-Horspool searcher implements the Boyer-Moore-Horspool search algorithm. In general, the Boyer-Moore searcher will use more memory and give better runtime performance than Boyer-Moore-Horspool.

**23.14.14.1 Class template default\_searcher****[func.search.default]**

```
template <class ForwardIterator1, class BinaryPredicate = equal_to<>>
class default_searcher {
public:
 default_searcher(ForwardIterator1 pat_first, ForwardIterator1 pat_last,
 BinaryPredicate pred = BinaryPredicate());

 template <class ForwardIterator2>
 pair<ForwardIterator2, ForwardIterator2>
 operator()(ForwardIterator2 first, ForwardIterator2 last) const;

private:
 ForwardIterator1 pat_first_; // exposition only
 ForwardIterator1 pat_last_; // exposition only
 BinaryPredicate pred_; // exposition only
};
```

```
default_searcher(ForwardIterator pat_first, ForwardIterator pat_last,
 BinaryPredicate pred = BinaryPredicate());
```

<sup>1</sup> *Effects:* Constructs a default\_searcher object, initializing pat\_first\_ with pat\_first, pat\_last\_ with pat\_last, and pred\_ with pred.

<sup>2</sup> *Throws:* Any exception thrown by the copy constructor of BinaryPredicate or ForwardIterator1.

```
template<class ForwardIterator2>
pair<ForwardIterator2, ForwardIterator2>
operator()(ForwardIterator2 first, ForwardIterator2 last) const;
```

<sup>3</sup> *Effects:* Returns a pair of iterators i and j such that

- (3.1) — i == search(first, last, pat\_first\_, pat\_last\_, pred\_), and



- (3.2) — if  $i == \text{last}$ , then  $j == \text{last}$ , otherwise  $j == \text{next}(i, \text{distance}(\text{pat\_first\_}, \text{pat\_last\_}))$ .

#### 23.14.14.2 Class template `boyer_moore_searcher`

[func.search.bm]

```
template <class RandomAccessIterator1,
 class Hash = hash<typename iterator_traits<RandomAccessIterator1>::value_type>,
 class BinaryPredicate = equal_to<>>
class boyer_moore_searcher {
public:
 boyer_moore_searcher(RandomAccessIterator1 pat_first,
 RandomAccessIterator1 pat_last,
 Hash hf = Hash(),
 BinaryPredicate pred = BinaryPredicate());

 template <class RandomAccessIterator2>
 pair<RandomAccessIterator2, RandomAccessIterator2>
 operator()(RandomAccessIterator2 first, RandomAccessIterator2 last) const;

private:
 RandomAccessIterator1 pat_first_; // exposition only
 RandomAccessIterator1 pat_last_; // exposition only
 Hash hash_; // exposition only
 BinaryPredicate pred_; // exposition only
};

boyer_moore_searcher(RandomAccessIterator1 pat_first,
 RandomAccessIterator1 pat_last,
 Hash hf = Hash(),
 BinaryPredicate pred = BinaryPredicate());
```

1 *Requires:* The value type of `RandomAccessIterator1` shall meet the `DefaultConstructible` requirements, the `CopyConstructible` requirements, and the `CopyAssignable` requirements.

2 *Requires:* For any two values  $A$  and  $B$  of the type `iterator_traits<RandomAccessIterator1>::value_type`, if  $\text{pred}(A, B) == \text{true}$ , then  $\text{hf}(A) == \text{hf}(B)$  shall be true.

3 *Effects:* Constructs a `boyer_moore_searcher` object, initializing `pat_first_` with `pat_first`, `pat_last_` with `pat_last`, `hash_` with `hf`, and `pred_` with `pred`.

4 *Throws:* Any exception thrown by the copy constructor of `RandomAccessIterator1`, or by the default constructor, copy constructor, or the copy assignment operator of the value type of `RandomAccessIterator1`, or the copy constructor or `operator()` of `BinaryPredicate` or `Hash`. May throw `bad_alloc` if additional memory needed for internal data structures cannot be allocated.

```
template <class RandomAccessIterator2>
pair<RandomAccessIterator2, RandomAccessIterator2>
operator()(RandomAccessIterator2 first, RandomAccessIterator2 last) const;
```

5 *Requires:* `RandomAccessIterator1` and `RandomAccessIterator2` shall have the same value type.

6 *Effects:* Finds a subsequence of equal values in a sequence.

7 *Returns:* A pair of iterators  $i$  and  $j$  such that

- (7.1) —  $i$  is the first iterator in the range  $[\text{first}, \text{last} - (\text{pat\_last\_} - \text{pat\_first\_}))$  such that for every non-negative integer  $n$  less than  $\text{pat\_last\_} - \text{pat\_first\_}$  the following condition holds:  
 $\text{pred}(*(i + n), *(pat\_first\_ + n)) \neq \text{false}$ , and

- (7.2) —  $j == \text{next}(i, \text{distance}(\text{pat\_first\_}, \text{pat\_last\_}))$ .

Returns `make_pair(first, first)` if  $[\text{pat\_first\_}, \text{pat\_last\_})$  is empty, otherwise returns `make_`

pair(last, last) if no such iterator is found.

8 *Complexity:* At most  $(\text{last} - \text{first}) * (\text{pat\_last\_} - \text{pat\_first\_})$  applications of the predicate.

### 23.14.14.3 Class template boyer\_moore\_horspool\_searcher [func.search.bmh]

```
template <class RandomAccessIterator1,
 class Hash = hash<typename iterator_traits<RandomAccessIterator1>::value_type>,
 class BinaryPredicate = equal_to<>>
class boyer_moore_horspool_searcher {
public:
 boyer_moore_horspool_searcher(RandomAccessIterator1 pat_first,
 RandomAccessIterator1 pat_last,
 Hash hf = Hash(),
 BinaryPredicate pred = BinaryPredicate());

 template <class RandomAccessIterator2>
 pair<RandomAccessIterator2, RandomAccessIterator2>
 operator()(RandomAccessIterator2 first, RandomAccessIterator2 last) const;

private:
 RandomAccessIterator1 pat_first_; // exposition only
 RandomAccessIterator1 pat_last_; // exposition only
 Hash hash_; // exposition only
 BinaryPredicate pred_; // exposition only
};
```

```
boyer_moore_horspool_searcher(RandomAccessIterator1 pat_first,
 RandomAccessIterator1 pat_last,
 Hash hf = Hash(),
 BinaryPredicate pred = BinaryPredicate());
```

1 *Requires:* The value type of RandomAccessIterator1 shall meet the DefaultConstructible, CopyConstructible, and CopyAssignable requirements.

2 *Requires:* For any two values A and B of the type iterator\_traits<RandomAccessIterator1>::value\_type, if  $\text{pred}(A, B) == \text{true}$ , then  $\text{hf}(A) == \text{hf}(B)$  shall be true.

3 *Effects:* Constructs a boyer\_moore\_horspool\_searcher object, initializing pat\_first\_ with pat\_first, pat\_last\_ with pat\_last, hash\_ with hf, and pred\_ with pred.

4 *Throws:* Any exception thrown by the copy constructor of RandomAccessIterator1, or by the default constructor, copy constructor, or the copy assignment operator of the value type of RandomAccessIterator1 or the copy constructor or operator() of BinaryPredicate or Hash. May throw bad\_alloc if additional memory needed for internal data structures cannot be allocated.

```
template <class RandomAccessIterator2>
pair<RandomAccessIterator2, RandomAccessIterator2>
operator()(RandomAccessIterator2 first, RandomAccessIterator2 last) const;
```

5 *Requires:* RandomAccessIterator1 and RandomAccessIterator2 shall have the same value type.

6 *Effects:* Finds a subsequence of equal values in a sequence.

7 *Returns:* A pair of iterators i and j such that

(7.1) — i is the first iterator i in the range [first, last - (pat\_last\_ - pat\_first\_)) such that for every non-negative integer n less than pat\_last\_ - pat\_first\_ the following condition holds:  
 $\text{pred}(*(i + n), *(pat\_first\_ + n)) \neq \text{false}$ , and

(7.2) —  $j == \text{next}(i, \text{distance}(pat\_first_, pat\_last\_))$ .

Returns `make_pair(first, first)` if `[pat_first_, pat_last_)` is empty, otherwise returns `make_pair(last, last)` if no such iterator is found.

8 *Complexity:* At most  $(last - first) * (pat\_last\_ - pat\_first\_)$  applications of the predicate.

### 23.14.15 Class template `hash` [unord.hash]

- 1 The unordered associative containers defined in 26.5 use specializations of the class template `hash` (23.14.1) as the default hash function.
- 2 Each specialization of `hash` is either enabled or disabled, as described below. [ *Note:* Enabled specializations meet the requirements of `Hash`, and disabled specializations do not. — *end note* ] Each header that declares the template `hash` provides enabled specializations of `hash` for `nullptr_t` and all cv-unqualified arithmetic, enumeration, and pointer types. For any type `Key` for which neither the library nor the user provides an explicit or partial specialization of the class template `hash`, `hash<Key>` is disabled.
- 3 If the library provides an explicit or partial specialization of `hash<Key>`, that specialization is enabled except as noted otherwise, and its member functions are `noexcept` except as noted otherwise.
- 4 If `H` is a disabled specialization of `hash`, these values are `false`: `is_default_constructible_v<H>`, `is_copy_constructible_v<H>`, `is_move_constructible_v<H>`, `is_copy_assignable_v<H>`, and `is_move_assignable_v<H>`. Disabled specializations of `hash` are not function object types (23.14). [ *Note:* This means that the specialization of `hash` exists, but any attempts to use it as a `Hash` will be ill-formed. — *end note* ]
- 5 An enabled specialization `hash<Key>` will:
  - (5.1) — satisfy the `Hash` requirements (20.5.3.4), with `Key` as the function call argument type, the `DefaultConstructible` requirements (Table 22), the `CopyAssignable` requirements (Table 26),
  - (5.2) — be swappable (20.5.3.2) for lvalues,
  - (5.3) — satisfy the requirement that if `k1 == k2` is `true`, `h(k1) == h(k2)` is also `true`, where `h` is an object of type `hash<Key>` and `k1` and `k2` are objects of type `Key`;
  - (5.4) — satisfy the requirement that the expression `h(k)`, where `h` is an object of type `hash<Key>` and `k` is an object of type `Key`, shall not throw an exception unless `hash<Key>` is a user-defined specialization that depends on at least one user-defined type.

### 23.15 Metaprogramming and type traits [meta]

- 1 This subclause describes components used by C++ programs, particularly in templates, to support the widest possible range of types, optimise template code usage, detect type related user errors, and perform type inference and transformation at compile time. It includes type classification traits, type property inspection traits, and type transformations. The type classification traits describe a complete taxonomy of all possible C++ types, and state where in that taxonomy a given type belongs. The type property inspection traits allow important characteristics of types or of combinations of types to be inspected. The type transformations allow certain properties of types to be manipulated.
- 2 All functions specified in this subclause are signal-safe (21.10.3).

#### 23.15.1 Requirements [meta.rqmts]

- 1 A *UnaryTypeTrait* describes a property of a type. It shall be a class template that takes one template type argument and, optionally, additional arguments that help define the property being described. It shall be `DefaultConstructible`, `CopyConstructible`, and publicly and unambiguously derived, directly or indirectly, from its *base characteristic*, which is a specialization of the template `integral_constant` (23.15.3), with the arguments to the template `integral_constant` determined by the requirements for the particular property being described. The member names of the base characteristic shall not be hidden and shall be unambiguously available in the `UnaryTypeTrait`.

- <sup>2</sup> A *BinaryTypeTrait* describes a relationship between two types. It shall be a class template that takes two template type arguments and, optionally, additional arguments that help define the relationship being described. It shall be `DefaultConstructible`, `CopyConstructible`, and publicly and unambiguously derived, directly or indirectly, from its *base characteristic*, which is a specialization of the template `integral_constant` (23.15.3), with the arguments to the template `integral_constant` determined by the requirements for the particular relationship being described. The member names of the base characteristic shall not be hidden and shall be unambiguously available in the `BinaryTypeTrait`.
- <sup>3</sup> A *TransformationTrait* modifies a property of a type. It shall be a class template that takes one template type argument and, optionally, additional arguments that help define the modification. It shall define a publicly accessible nested type named `type`, which shall be a synonym for the modified type.

### 23.15.2 Header `<type_traits>` synopsis

[meta.type.synop]

```
namespace std {
 // 23.15.3, helper class
 template <class T, T v> struct integral_constant;

 template <bool B>
 using bool_constant = integral_constant<bool, B>;
 using true_type = bool_constant<true>;
 using false_type = bool_constant<false>;

 // 23.15.4.1, primary type categories
 template <class T> struct is_void;
 template <class T> struct is_null_pointer;
 template <class T> struct is_integral;
 template <class T> struct is_floating_point;
 template <class T> struct is_array;
 template <class T> struct is_pointer;
 template <class T> struct is_lvalue_reference;
 template <class T> struct is_rvalue_reference;
 template <class T> struct is_member_object_pointer;
 template <class T> struct is_member_function_pointer;
 template <class T> struct is_enum;
 template <class T> struct is_union;
 template <class T> struct is_class;
 template <class T> struct is_function;

 // 23.15.4.2, composite type categories
 template <class T> struct is_reference;
 template <class T> struct is_arithmetic;
 template <class T> struct is_fundamental;
 template <class T> struct is_object;
 template <class T> struct is_scalar;
 template <class T> struct is_compound;
 template <class T> struct is_member_pointer;

 // 23.15.4.3, type properties
 template <class T> struct is_const;
 template <class T> struct is_volatile;
 template <class T> struct is_trivial;
 template <class T> struct is_trivially_copyable;
 template <class T> struct is_standard_layout;
 template <class T> struct is_pod;
 template <class T> struct is_empty;
```

```

template <class T> struct is_polymorphic;
template <class T> struct is_abstract;
template <class T> struct is_final;
template <class T> struct is_aggregate;

template <class T> struct is_signed;
template <class T> struct is_unsigned;

template <class T, class... Args> struct is_constructible;
template <class T> struct is_default_constructible;
template <class T> struct is_copy_constructible;
template <class T> struct is_move_constructible;

template <class T, class U> struct is_assignable;
template <class T> struct is_copy_assignable;
template <class T> struct is_move_assignable;

template <class T, class U> struct is_swappable_with;
template <class T> struct is_swappable;

template <class T> struct is_destructible;

template <class T, class... Args> struct is_trivially_constructible;
template <class T> struct is_trivially_default_constructible;
template <class T> struct is_trivially_copy_constructible;
template <class T> struct is_trivially_move_constructible;

template <class T, class U> struct is_trivially_assignable;
template <class T> struct is_trivially_copy_assignable;
template <class T> struct is_trivially_move_assignable;
template <class T> struct is_trivially_destructible;

template <class T, class... Args> struct is_nothrow_constructible;
template <class T> struct is_nothrow_default_constructible;
template <class T> struct is_nothrow_copy_constructible;
template <class T> struct is_nothrow_move_constructible;

template <class T, class U> struct is_nothrow_assignable;
template <class T> struct is_nothrow_copy_assignable;
template <class T> struct is_nothrow_move_assignable;

template <class T, class U> struct is_nothrow_swappable_with;
template <class T> struct is_nothrow_swappable;

template <class T> struct is_nothrow_destructible;

template <class T> struct has_virtual_destructor;

template <class T> struct has_unique_object_representations;

// 23.15.5, type property queries
template <class T> struct alignment_of;
template <class T> struct rank;
template <class T, unsigned I = 0> struct extent;

```

```

// 23.15.6, type relations
template <class T, class U> struct is_same;
template <class Base, class Derived> struct is_base_of;
template <class From, class To> struct is_convertible;

template <class Fn, class... ArgTypes> struct is_invocable;
template <class R, class Fn, class... ArgTypes> struct is_invocable_r;

template <class Fn, class... ArgTypes> struct is_nothrow_invocable;
template <class R, class Fn, class... ArgTypes> struct is_nothrow_invocable_r;

// 23.15.7.1, const-volatile modifications
template <class T> struct remove_const;
template <class T> struct remove_volatile;
template <class T> struct remove_cv;
template <class T> struct add_const;
template <class T> struct add_volatile;
template <class T> struct add_cv;

template <class T>
 using remove_const_t = typename remove_const<T>::type;
template <class T>
 using remove_volatile_t = typename remove_volatile<T>::type;
template <class T>
 using remove_cv_t = typename remove_cv<T>::type;
template <class T>
 using add_const_t = typename add_const<T>::type;
template <class T>
 using add_volatile_t = typename add_volatile<T>::type;
template <class T>
 using add_cv_t = typename add_cv<T>::type;

// 23.15.7.2, reference modifications
template <class T> struct remove_reference;
template <class T> struct add_lvalue_reference;
template <class T> struct add_rvalue_reference;

template <class T>
 using remove_reference_t = typename remove_reference<T>::type;
template <class T>
 using add_lvalue_reference_t = typename add_lvalue_reference<T>::type;
template <class T>
 using add_rvalue_reference_t = typename add_rvalue_reference<T>::type;

// 23.15.7.3, sign modifications
template <class T> struct make_signed;
template <class T> struct make_unsigned;

template <class T>
 using make_signed_t = typename make_signed<T>::type;
template <class T>
 using make_unsigned_t = typename make_unsigned<T>::type;

// 23.15.7.4, array modifications
template <class T> struct remove_extent;

```

```

template <class T> struct remove_all_extents;

template <class T>
 using remove_extent_t = typename remove_extent<T>::type;
template <class T>
 using remove_all_extents_t = typename remove_all_extents<T>::type;

// 23.15.7.5, pointer modifications
template <class T> struct remove_pointer;
template <class T> struct add_pointer;

template <class T>
 using remove_pointer_t = typename remove_pointer<T>::type;
template <class T>
 using add_pointer_t = typename add_pointer<T>::type;

// 23.15.7.6, other transformations
template <size_t Len,
 size_t Align = default-alignment> // see 23.15.7.6
 struct aligned_storage;
template <size_t Len, class... Types> struct aligned_union;
template <class T> struct decay;
template <bool, class T = void> struct enable_if;
template <bool, class T, class F> struct conditional;
template <class... T> struct common_type;
template <class T> struct underlying_type;
template <class Fn, class... ArgTypes> struct invoke_result;

template <size_t Len,
 size_t Align = default-alignment> // see 23.15.7.6
 using aligned_storage_t = typename aligned_storage<Len, Align>::type;
template <size_t Len, class... Types>
 using aligned_union_t = typename aligned_union<Len, Types...>::type;
template <class T>
 using decay_t = typename decay<T>::type;
template <bool b, class T = void>
 using enable_if_t = typename enable_if<b, T>::type;
template <bool b, class T, class F>
 using conditional_t = typename conditional<b, T, F>::type;
template <class... T>
 using common_type_t = typename common_type<T...>::type;
template <class T>
 using underlying_type_t = typename underlying_type<T>::type;
template <class Fn, class... ArgTypes>
 using invoke_result_t = typename invoke_result<Fn, ArgTypes...>::type;
template <class...>
 using void_t = void;

// 23.15.8, logical operator traits
template<class... B> struct conjunction;
template<class... B> struct disjunction;
template<class B> struct negation;

// 23.15.4.1, primary type categories
template <class T> inline constexpr bool is_void_v

```

```

 = is_void<T>::value;
template <class T> inline constexpr bool is_null_pointer_v
 = is_null_pointer<T>::value;
template <class T> inline constexpr bool is_integral_v
 = is_integral<T>::value;
template <class T> inline constexpr bool is_floating_point_v
 = is_floating_point<T>::value;
template <class T> inline constexpr bool is_array_v
 = is_array<T>::value;
template <class T> inline constexpr bool is_pointer_v
 = is_pointer<T>::value;
template <class T> inline constexpr bool is_lvalue_reference_v
 = is_lvalue_reference<T>::value;
template <class T> inline constexpr bool is_rvalue_reference_v
 = is_rvalue_reference<T>::value;
template <class T> inline constexpr bool is_member_object_pointer_v
 = is_member_object_pointer<T>::value;
template <class T> inline constexpr bool is_member_function_pointer_v
 = is_member_function_pointer<T>::value;
template <class T> inline constexpr bool is_enum_v
 = is_enum<T>::value;
template <class T> inline constexpr bool is_union_v
 = is_union<T>::value;
template <class T> inline constexpr bool is_class_v
 = is_class<T>::value;
template <class T> inline constexpr bool is_function_v
 = is_function<T>::value;

// 23.15.4.2, composite type categories
template <class T> inline constexpr bool is_reference_v
 = is_reference<T>::value;
template <class T> inline constexpr bool is_arithmetic_v
 = is_arithmetic<T>::value;
template <class T> inline constexpr bool is_fundamental_v
 = is_fundamental<T>::value;
template <class T> inline constexpr bool is_object_v
 = is_object<T>::value;
template <class T> inline constexpr bool is_scalar_v
 = is_scalar<T>::value;
template <class T> inline constexpr bool is_compound_v
 = is_compound<T>::value;
template <class T> inline constexpr bool is_member_pointer_v
 = is_member_pointer<T>::value;

// 23.15.4.3, type properties
template <class T> inline constexpr bool is_const_v
 = is_const<T>::value;
template <class T> inline constexpr bool is_volatile_v
 = is_volatile<T>::value;
template <class T> inline constexpr bool is_trivial_v
 = is_trivial<T>::value;
template <class T> inline constexpr bool is_trivially_copyable_v
 = is_trivially_copyable<T>::value;
template <class T> inline constexpr bool is_standard_layout_v
 = is_standard_layout<T>::value;

```



```

template <class T> inline constexpr bool is_pod_v
 = is_pod<T>::value;
template <class T> inline constexpr bool is_empty_v
 = is_empty<T>::value;
template <class T> inline constexpr bool is_polymorphic_v
 = is_polymorphic<T>::value;
template <class T> inline constexpr bool is_abstract_v
 = is_abstract<T>::value;
template <class T> inline constexpr bool is_final_v
 = is_final<T>::value;
template <class T> inline constexpr bool is_aggregate_v
 = is_aggregate<T>::value;
template <class T> inline constexpr bool is_signed_v
 = is_signed<T>::value;
template <class T> inline constexpr bool is_unsigned_v
 = is_unsigned<T>::value;
template <class T, class... Args> inline constexpr bool is_constructible_v
 = is_constructible<T, Args...>::value;
template <class T> inline constexpr bool is_default_constructible_v
 = is_default_constructible<T>::value;
template <class T> inline constexpr bool is_copy_constructible_v
 = is_copy_constructible<T>::value;
template <class T> inline constexpr bool is_move_constructible_v
 = is_move_constructible<T>::value;
template <class T, class U> inline constexpr bool is_assignable_v
 = is_assignable<T, U>::value;
template <class T> inline constexpr bool is_copy_assignable_v
 = is_copy_assignable<T>::value;
template <class T> inline constexpr bool is_move_assignable_v
 = is_move_assignable<T>::value;
template <class T, class U> inline constexpr bool is_swappable_with_v
 = is_swappable_with<T, U>::value;
template <class T> inline constexpr bool is_swappable_v
 = is_swappable<T>::value;
template <class T> inline constexpr bool is_destructible_v
 = is_destructible<T>::value;
template <class T, class... Args> inline constexpr bool is_trivially_constructible_v
 = is_trivially_constructible<T, Args...>::value;
template <class T> inline constexpr bool is_trivially_default_constructible_v
 = is_trivially_default_constructible<T>::value;
template <class T> inline constexpr bool is_trivially_copy_constructible_v
 = is_trivially_copy_constructible<T>::value;
template <class T> inline constexpr bool is_trivially_move_constructible_v
 = is_trivially_move_constructible<T>::value;
template <class T, class U> inline constexpr bool is_trivially_assignable_v
 = is_trivially_assignable<T, U>::value;
template <class T> inline constexpr bool is_trivially_copy_assignable_v
 = is_trivially_copy_assignable<T>::value;
template <class T> inline constexpr bool is_trivially_move_assignable_v
 = is_trivially_move_assignable<T>::value;
template <class T> inline constexpr bool is_trivially_destructible_v
 = is_trivially_destructible<T>::value;
template <class T, class... Args> inline constexpr bool is_nothrow_constructible_v
 = is_nothrow_constructible<T, Args...>::value;
template <class T> inline constexpr bool is_nothrow_default_constructible_v

```

```

 = is_nothrow_default_constructible<T>::value;
template <class T> inline constexpr bool is_nothrow_copy_constructible_v
 = is_nothrow_copy_constructible<T>::value;
template <class T> inline constexpr bool is_nothrow_move_constructible_v
 = is_nothrow_move_constructible<T>::value;
template <class T, class U> inline constexpr bool is_nothrow_assignable_v
 = is_nothrow_assignable<T, U>::value;
template <class T> inline constexpr bool is_nothrow_copy_assignable_v
 = is_nothrow_copy_assignable<T>::value;
template <class T> inline constexpr bool is_nothrow_move_assignable_v
 = is_nothrow_move_assignable<T>::value;
template <class T, class U> inline constexpr bool is_nothrow_swappable_with_v
 = is_nothrow_swappable_with<T, U>::value;
template <class T> inline constexpr bool is_nothrow_swappable_v
 = is_nothrow_swappable<T>::value;
template <class T> inline constexpr bool is_nothrow_destructible_v
 = is_nothrow_destructible<T>::value;
template <class T> inline constexpr bool has_virtual_destructor_v
 = has_virtual_destructor<T>::value;
template <class T> inline constexpr bool has_unique_object_representations_v
 = has_unique_object_representations<T>::value;

// 23.15.5, type property queries
template <class T> inline constexpr size_t alignment_of_v
 = alignment_of<T>::value;
template <class T> inline constexpr size_t rank_v
 = rank<T>::value;
template <class T, unsigned I = 0> inline constexpr size_t extent_v
 = extent<T, I>::value;

// 23.15.6, type relations
template <class T, class U> inline constexpr bool is_same_v
 = is_same<T, U>::value;
template <class Base, class Derived> inline constexpr bool is_base_of_v
 = is_base_of<Base, Derived>::value;
template <class From, class To> inline constexpr bool is_convertible_v
 = is_convertible<From, To>::value;
template <class Fn, class... ArgTypes> inline constexpr bool is_invocable_v
 = is_invocable<Fn, ArgTypes...>::value;
template <class R, class Fn, class... ArgTypes> inline constexpr bool is_invocable_r_v
 = is_invocable_r<R, Fn, ArgTypes...>::value;
template <class Fn, class... ArgTypes> inline constexpr bool is_nothrow_invocable_v
 = is_nothrow_invocable<Fn, ArgTypes...>::value;
template <class R, class Fn, class... ArgTypes> inline constexpr bool is_nothrow_invocable_r_v
 = is_nothrow_invocable_r<R, Fn, ArgTypes...>::value;

// 23.15.8, logical operator traits
template<class... B> inline constexpr bool conjunction_v = conjunction<B...>::value;
template<class... B> inline constexpr bool disjunction_v = disjunction<B...>::value;
template<class B> inline constexpr bool negation_v = negation::value;
}

```

<sup>1</sup> The behavior of a program that adds specializations for any of the templates defined in this subclause is undefined unless otherwise specified.

- <sup>2</sup> Unless otherwise specified, an incomplete type may be used to instantiate a template in this subclause.

### 23.15.3 Helper classes

[meta.help]

```
namespace std {
 template <class T, T v>
 struct integral_constant {
 static constexpr T value = v;
 using value_type = T;
 using type = integral_constant<T, v>;
 constexpr operator value_type() const noexcept { return value; }
 constexpr value_type operator()() const noexcept { return value; }
 };
}
```

- <sup>1</sup> The class template `integral_constant`, alias template `bool_constant`, and its associated *typedef-names* `true_type` and `false_type` are used as base classes to define the interface for various type traits.

### 23.15.4 Unary type traits

[meta.unary]

- <sup>1</sup> This subclause contains templates that may be used to query the properties of a type at compile time.
- <sup>2</sup> Each of these templates shall be a `UnaryTypeTrait` (23.15.1) with a base characteristic of `true_type` if the corresponding condition is `true`, otherwise `false_type`.

#### 23.15.4.1 Primary type categories

[meta.unary.cat]

- <sup>1</sup> The primary type categories correspond to the descriptions given in section 6.9 of the C++ standard.
- <sup>2</sup> For any given type `T`, the result of applying one of these templates to `T` and to `cv T` shall yield the same result.
- <sup>3</sup> [Note: For any given type `T`, exactly one of the primary type categories has a `value` member that evaluates to `true`. — end note]

Table 40 — Primary type category predicates

| Template                                                                          | Condition                                                          | Comments                                                               |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------------------------|
| <code>template &lt;class T&gt;</code><br><code>struct is_void;</code>             | <code>T</code> is void                                             |                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_null_pointer;</code>     | <code>T</code> is <code>nullptr_t</code> (6.9.1)                   |                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_integral;</code>         | <code>T</code> is an integral type (6.9.1)                         |                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_floating_point;</code>   | <code>T</code> is a floating-point type (6.9.1)                    |                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_array;</code>            | <code>T</code> is an array type (6.9.2) of known or unknown extent | Class template <code>array</code> (26.3.7) is not an array type.       |
| <code>template &lt;class T&gt;</code><br><code>struct is_pointer;</code>          | <code>T</code> is a pointer type (6.9.2)                           | Includes pointers to functions but not pointers to non-static members. |
| <code>template &lt;class T&gt;</code><br><code>struct is_lvalue_reference;</code> | <code>T</code> is an lvalue reference type (11.3.2)                |                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_rvalue_reference;</code> | <code>T</code> is an rvalue reference type (11.3.2)                |                                                                        |

Table 40 — Primary type category predicates (continued)

| Template                                                                         | Condition                                    | Comments |
|----------------------------------------------------------------------------------|----------------------------------------------|----------|
| <code>template &lt;class T&gt;<br/>struct is_member_object_pointer;</code>       | T is a pointer to non-static data member     |          |
| <code>template &lt;class T&gt;<br/>struct<br/>is_member_function_pointer;</code> | T is a pointer to non-static member function |          |
| <code>template &lt;class T&gt;<br/>struct is_enum;</code>                        | T is an enumeration type (6.9.2)             |          |
| <code>template &lt;class T&gt;<br/>struct is_union;</code>                       | T is a union type (6.9.2)                    |          |
| <code>template &lt;class T&gt;<br/>struct is_class;</code>                       | T is a non-union class type (6.9.2)          |          |
| <code>template &lt;class T&gt;<br/>struct is_function;</code>                    | T is a function type (6.9.2)                 |          |

**23.15.4.2 Composite type traits****[meta.unary.comp]**

- These templates provide convenient compositions of the primary type categories, corresponding to the descriptions given in section 6.9.
- For any given type T, the result of applying one of these templates to T and to *cv* T shall yield the same result.

Table 41 — Composite type category predicates

| Template                                                            | Condition                                                              | Comments |
|---------------------------------------------------------------------|------------------------------------------------------------------------|----------|
| <code>template &lt;class T&gt;<br/>struct is_reference;</code>      | T is an lvalue reference or an rvalue reference                        |          |
| <code>template &lt;class T&gt;<br/>struct is_arithmetic;</code>     | T is an arithmetic type (6.9.1)                                        |          |
| <code>template &lt;class T&gt;<br/>struct is_fundamental;</code>    | T is a fundamental type (6.9.1)                                        |          |
| <code>template &lt;class T&gt;<br/>struct is_object;</code>         | T is an object type (6.9)                                              |          |
| <code>template &lt;class T&gt;<br/>struct is_scalar;</code>         | T is a scalar type (6.9)                                               |          |
| <code>template &lt;class T&gt;<br/>struct is_compound;</code>       | T is a compound type (6.9.2)                                           |          |
| <code>template &lt;class T&gt;<br/>struct is_member_pointer;</code> | T is a pointer to non-static data member or non-static member function |          |

**23.15.4.3 Type properties****[meta.unary.prop]**

- These templates provide access to some of the more important properties of types.
- It is unspecified whether the library defines any full or partial specializations of any of these templates.
- For all of the class templates X declared in this subclause, instantiating that template with a template-argument that is a class template specialization may result in the implicit instantiation of the template argument if and only if the semantics of X require that the argument must be a complete type.

- <sup>4</sup> For the purpose of defining the templates in this subclause, a function call expression `declval<T>()` for any type `T` is considered to be a trivial (6.9, 15) function call that is not an odr-use (6.2) of `declval` in the context of the corresponding definition notwithstanding the restrictions of 23.2.7.

Table 42 — Type property predicates

| Template                                                                            | Condition                                                                                                                                                                                                                                                            | Preconditions                                                                          |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <code>template &lt;class T&gt;</code><br><code>struct is_const;</code>              | <code>T</code> is const-qualified (6.9.3)                                                                                                                                                                                                                            |                                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_volatile;</code>           | <code>T</code> is volatile-qualified (6.9.3)                                                                                                                                                                                                                         |                                                                                        |
| <code>template &lt;class T&gt;</code><br><code>struct is_trivial;</code>            | <code>T</code> is a trivial type (6.9)                                                                                                                                                                                                                               | <code>remove_all_extents_t&lt;T&gt;</code> shall be a complete type or <i>cv</i> void. |
| <code>template &lt;class T&gt;</code><br><code>struct is_trivially_copyable;</code> | <code>T</code> is a trivially copyable type (6.9)                                                                                                                                                                                                                    | <code>remove_all_extents_t&lt;T&gt;</code> shall be a complete type or <i>cv</i> void. |
| <code>template &lt;class T&gt;</code><br><code>struct is_standard_layout;</code>    | <code>T</code> is a standard-layout type (6.9)                                                                                                                                                                                                                       | <code>remove_all_extents_t&lt;T&gt;</code> shall be a complete type or <i>cv</i> void. |
| <code>template &lt;class T&gt;</code><br><code>struct is_pod;</code>                | <code>T</code> is a POD type (6.9)                                                                                                                                                                                                                                   | <code>remove_all_extents_t&lt;T&gt;</code> shall be a complete type or <i>cv</i> void. |
| <code>template &lt;class T&gt;</code><br><code>struct is_empty;</code>              | <code>T</code> is a class type, but not a union type, with no non-static data members other than bit-fields of length 0, no virtual member functions, no virtual base classes, and no base class <code>B</code> for which <code>is_empty_v&lt;B&gt;</code> is false. | If <code>T</code> is a non-union class type, <code>T</code> shall be a complete type.  |
| <code>template &lt;class T&gt;</code><br><code>struct is_polymorphic;</code>        | <code>T</code> is a polymorphic class (13.3)                                                                                                                                                                                                                         | If <code>T</code> is a non-union class type, <code>T</code> shall be a complete type.  |
| <code>template &lt;class T&gt;</code><br><code>struct is_abstract;</code>           | <code>T</code> is an abstract class (13.4)                                                                                                                                                                                                                           | If <code>T</code> is a non-union class type, <code>T</code> shall be a complete type.  |
| <code>template &lt;class T&gt;</code><br><code>struct is_final;</code>              | <code>T</code> is a class type marked with the <i>class-virt-specifier</i> <code>final</code> (Clause 12). [ <i>Note:</i> A union is a class type that can be marked with <code>final</code> . — <i>end note</i> ]                                                   | If <code>T</code> is a class type, <code>T</code> shall be a complete type.            |
| <code>template &lt;class T&gt;</code><br><code>struct is_aggregate;</code>          | <code>T</code> is an aggregate type (11.6.1)                                                                                                                                                                                                                         | <code>remove_all_extents_t&lt;T&gt;</code> shall be a complete type or <i>cv</i> void. |

Table 42 — Type property predicates (continued)

| Template                                                      | Condition                                                                                                                                    | Preconditions                                                                                                                |
|---------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| template <class T><br>struct is_signed;                       | If <code>is_arithmetic_v&lt;T&gt;</code> is true, the same result as <code>T(-1) &lt; T(0)</code> ; otherwise, false                         |                                                                                                                              |
| template <class T><br>struct is_unsigned;                     | If <code>is_arithmetic_v&lt;T&gt;</code> is true, the same result as <code>T(0) &lt; T(-1)</code> ; otherwise, false                         |                                                                                                                              |
| template <class T, class... Args><br>struct is_constructible; | For a function type T or for a <i>cv</i> void type T, <code>is_constructible_v&lt;T, Args...&gt;</code> is false, otherwise <i>see below</i> | T and all types in the parameter pack <code>Args</code> shall be complete types, <i>cv</i> void, or arrays of unknown bound. |
| template <class T><br>struct is_default_constructible;        | <code>is_constructible_v&lt;T&gt;</code> is true.                                                                                            | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| template <class T><br>struct is_copy_constructible;           | For a referenceable type T (20.3.18), the same result as <code>is_constructible_v&lt;T, const T&amp;&gt;</code> , otherwise false.           | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| template <class T><br>struct is_move_constructible;           | For a referenceable type T, the same result as <code>is_constructible_v&lt;T, T&amp;&amp;&gt;</code> , otherwise false.                      | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |

Table 42 — Type property predicates (continued)

| Template                                                           | Condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Preconditions                                                                       |
|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <pre>template &lt;class T, class U&gt; struct is_assignable;</pre> | <p>The expression <code>declval&lt;T&gt;() = declval&lt;U&gt;()</code> is well-formed when treated as an unevaluated operand (Clause 8). Access checking is performed as if in a context unrelated to T and U. Only the validity of the immediate context of the assignment expression is considered. [ <i>Note</i>: The compilation of the expression can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — <i>end note</i> ]</p> | <p>T and U shall be complete types, <i>cv</i> void, or arrays of unknown bound.</p> |
| <pre>template &lt;class T&gt; struct is_copy_assignable;</pre>     | <p>For a referenceable type T, the same result as <code>is_assignable_v&lt;T&amp;, const T&amp;&gt;</code>, otherwise <code>false</code>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <p>T shall be a complete type, <i>cv</i> void, or an array of unknown bound.</p>    |
| <pre>template &lt;class T&gt; struct is_move_assignable;</pre>     | <p>For a referenceable type T, the same result as <code>is_assignable_v&lt;T&amp;, T&amp;&amp;&gt;</code>, otherwise <code>false</code>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <p>T shall be a complete type, <i>cv</i> void, or an array of unknown bound.</p>    |

Table 42 — Type property predicates (continued)

| Template                                                               | Condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Preconditions                                                                       |
|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <pre>template &lt;class T, class U&gt; struct is_swappable_with;</pre> | <p>The expressions <code>swap(declval&lt;T&gt;()), declval&lt;U&gt;())</code> and <code>swap(declval&lt;U&gt;(), declval&lt;T&gt;())</code> are each well-formed when treated as an unevaluated operand (Clause 8) in an overload-resolution context for swappable values (20.5.3.2). Access checking is performed as if in a context unrelated to T and U. Only the validity of the immediate context of the <code>swap</code> expressions is considered. [ <i>Note</i>: The compilation of the expressions can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — <i>end note</i> ]</p> | <p>T and U shall be complete types, <i>cv</i> void, or arrays of unknown bound.</p> |
| <pre>template &lt;class T&gt; struct is_swappable;</pre>               | <p>For a referenceable type T, the same result as <code>is_swappable_with_v&lt;T&amp;, T&amp;&gt;</code>, otherwise <code>false</code>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <p>T shall be a complete type, <i>cv</i> void, or an array of unknown bound.</p>    |
| <pre>template &lt;class T&gt; struct is_destructible;</pre>            | <p>Either T is a reference type, or T is a complete object type for which the expression <code>declval&lt;U&amp;&gt;().~U()</code> is well-formed when treated as an unevaluated operand (Clause 8), where U is <code>remove_all_extents&lt;T&gt;</code>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <p>T shall be a complete type, <i>cv</i> void, or an array of unknown bound.</p>    |



Table 42 — Type property predicates (continued)

| Template                                                                              | Condition                                                                                                                                                                                                | Preconditions                                                                                                                |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <pre>template &lt;class T, class... Args&gt; struct is_trivially_constructible;</pre> | <code>is_constructible_v&lt;T, Args...&gt;</code> is true and the variable definition for <code>is_constructible</code> , as defined below, is known to call no operation that is not trivial (6.9, 15). | T and all types in the parameter pack <code>Args</code> shall be complete types, <i>cv</i> void, or arrays of unknown bound. |
| <pre>template &lt;class T&gt; struct is_trivially_default_constructible;</pre>        | <code>is_trivially_constructible_v&lt;T&gt;</code> is true.                                                                                                                                              | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| <pre>template &lt;class T&gt; struct is_trivially_copy_constructible;</pre>           | For a referenceable type T, the same result as <code>is_trivially_constructible_v&lt;T, const T&amp;&gt;</code> , otherwise false.                                                                       | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| <pre>template &lt;class T&gt; struct is_trivially_move_constructible;</pre>           | For a referenceable type T, the same result as <code>is_trivially_constructible_v&lt;T, T&amp;&amp;&gt;</code> , otherwise false.                                                                        | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| <pre>template &lt;class T, class U&gt; struct is_trivially_assignable;</pre>          | <code>is_assignable_v&lt;T, U&gt;</code> is true and the assignment, as defined by <code>is_assignable</code> , is known to call no operation that is not trivial (6.9, 15).                             | T and U shall be complete types, <i>cv</i> void, or arrays of unknown bound.                                                 |
| <pre>template &lt;class T&gt; struct is_trivially_copy_assignable;</pre>              | For a referenceable type T, the same result as <code>is_trivially_assignable_v&lt;T&amp;, const T&amp;&gt;</code> , otherwise false.                                                                     | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| <pre>template &lt;class T&gt; struct is_trivially_move_assignable;</pre>              | For a referenceable type T, the same result as <code>is_trivially_assignable_v&lt;T&amp;, T&amp;&amp;&gt;</code> , otherwise false.                                                                      | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |
| <pre>template &lt;class T&gt; struct is_trivially_destructible;</pre>                 | <code>is_destructible_v&lt;T&gt;</code> is true and the indicated destructor is known to be trivial.                                                                                                     | T shall be a complete type, <i>cv</i> void, or an array of unknown bound.                                                    |

Table 42 — Type property predicates (continued)

| Template                                                              | Condition                                                                                                                                                | Preconditions                                                                                            |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| template <class T, class... Args><br>struct is_nothrow_constructible; | is_constructible_v<T, Args...> is true and the variable definition for is_constructible, as defined below, is known not to throw any exceptions (8.3.7). | T and all types in the parameter pack Args shall be complete types, cv void, or arrays of unknown bound. |
| template <class T><br>struct<br>is_nothrow_default_constructible;     | is_nothrow_constructible_v<T> is true.                                                                                                                   | T shall be a complete type, cv void, or an array of unknown bound.                                       |
| template <class T><br>struct<br>is_nothrow_copy_constructible;        | For a referenceable type T, the same result as is_nothrow_constructible_v<T, const T&>, otherwise false.                                                 | T shall be a complete type, cv void, or an array of unknown bound.                                       |
| template <class T><br>struct<br>is_nothrow_move_constructible;        | For a referenceable type T, the same result as is_nothrow_constructible_v<T, T&&>, otherwise false.                                                      | T shall be a complete type, cv void, or an array of unknown bound.                                       |
| template <class T, class U><br>struct is_nothrow_assignable;          | is_assignable_v<T, U> is true and the assignment is known not to throw any exceptions (8.3.7).                                                           | T and U shall be complete types, cv void, or arrays of unknown bound.                                    |
| template <class T><br>struct is_nothrow_copy_assignable;              | For a referenceable type T, the same result as is_nothrow_assignable_v<T&, const T&>, otherwise false.                                                   | T shall be a complete type, cv void, or an array of unknown bound.                                       |
| template <class T><br>struct is_nothrow_move_assignable;              | For a referenceable type T, the same result as is_nothrow_assignable_v<T&, T&&>, otherwise false.                                                        | T shall be a complete type, cv void, or an array of unknown bound.                                       |
| template <class T, class U><br>struct is_nothrow_swappable_with;      | is_swappable_with_v<T, U> is true and each swap expression of the definition of is_swappable_with<T, U> is known not to throw any exceptions (8.3.7).    | T and U shall be complete types, cv void, or arrays of unknown bound.                                    |
| template <class T><br>struct is_nothrow_swappable;                    | For a referenceable type T, the same result as is_nothrow_swappable_with_v<T&, T&>, otherwise false.                                                     | T shall be a complete type, cv void, or an array of unknown bound.                                       |

Table 42 — Type property predicates (continued)

| Template                                                                      | Condition                                                                                                                                                    | Preconditions                                                             |
|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <pre>template &lt;class T&gt; struct is_nothrow_destructible;</pre>           | <pre>is_destructible_v&lt;T&gt; is true and the indicated destructor is known not to throw any exceptions (8.3.7).</pre>                                     | T shall be a complete type, <i>cv</i> void, or an array of unknown bound. |
| <pre>template &lt;class T&gt; struct has_virtual_destructor;</pre>            | T has a virtual destructor (15.4)                                                                                                                            | If T is a non-union class type, T shall be a complete type.               |
| <pre>template &lt;class T&gt; struct has_unique_object_representations;</pre> | For an array type T, the same result as <code>has_unique_object_representations_v&lt;remove_all_extents_t&lt;T&gt;&gt;</code> , otherwise <i>see below</i> . | T shall be a complete type, <i>cv</i> void, or an array of unknown bound. |

5 [Example:

```
is_const_v<const volatile int> // true
is_const_v<const int*> // false
is_const_v<const int&> // false
is_const_v<int[3]> // false
is_const_v<const int[3]> // true
```

— end example]

6 [Example:

```
remove_const_t<const volatile int> // volatile int
remove_const_t<const int* const> // const int*
remove_const_t<const int&> // const int&
remove_const_t<const int[3]> // int[3]
```

— end example]

7 [Example:

```
// Given:
struct P final { };
union U1 { };
union U2 final { };

// the following assertions hold:
static_assert(!is_final_v<int>);
static_assert(is_final_v<P>);
static_assert(!is_final_v<U1>);
static_assert(is_final_v<U2>);
```

— end example]

8 The predicate condition for a template specialization `is_constructible<T, Args...>` shall be satisfied if and only if the following variable definition would be well-formed for some invented variable `t`:

```
T t(declval<Args>()...);
```

[Note: These tokens are never interpreted as a function declaration. — end note] Access checking is

performed as if in a context unrelated to **T** and any of the **Args**. Only the validity of the immediate context of the variable initialization is considered. [ *Note*: The evaluation of the initialization can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — *end note* ]

- 9 The predicate condition for a template specialization `has_unique_object_representations<T>` shall be satisfied if and only if:

- (9.1) — **T** is trivially copyable, and
- (9.2) — any two objects of type **T** with the same value have the same object representation, where two objects of array or non-union class type are considered to have the same value if their respective sequences of direct subobjects have the same values, and two objects of union type are considered to have the same value if they have the same active member and the corresponding members have the same value.

The set of scalar types for which this condition holds is implementation-defined. [ *Note*: If a type has padding bits, the condition does not hold; otherwise, the condition holds true for unsigned integral types. — *end note* ]

### 23.15.5 Type property queries

[**meta.unary.prop.query**]

- <sup>1</sup> This subclause contains templates that may be used to query properties of types at compile time.

Table 43 — Type property queries

| Template                                                                     | Value                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>template &lt;class T&gt;<br/>struct alignment_of;</code>               | <code>alignof(T)</code> .<br><i>Requires</i> : <code>alignof(T)</code> shall be a valid expression (8.3.6)                                                                                                                                                                                       |
| <code>template &lt;class T&gt;<br/>struct rank;</code>                       | If <b>T</b> names an array type, an integer value representing the number of dimensions of <b>T</b> ; otherwise, 0.                                                                                                                                                                              |
| <code>template &lt;class T,<br/>unsigned I = 0&gt;<br/>struct extent;</code> | If <b>T</b> is not an array type, or if it has rank less than or equal to <b>I</b> , or if <b>I</b> is 0 and <b>T</b> has type “array of unknown bound of <b>U</b> ”, then 0; otherwise, the bound (11.3.4) of the <b>I</b> ’th dimension of <b>T</b> , where indexing of <b>I</b> is zero-based |

- <sup>2</sup> Each of these templates shall be a `UnaryTypeTrait` (23.15.1) with a base characteristic of `integral_constant<size_t, Value>`.

- <sup>3</sup> [ *Example*:

```
// the following assertions hold:
assert(rank_v<int> == 0);
assert(rank_v<int[2]> == 1);
assert(rank_v<int[][4]> == 2);
```

— *end example* ]

- <sup>4</sup> [ *Example*:

```
// the following assertions hold:
assert(extent_v<int> == 0);
assert(extent_v<int[2]> == 2);
assert(extent_v<int[2][4]> == 2);
assert(extent_v<int[][4]> == 0);
assert((extent_v<int, 1>) == 0);
assert((extent_v<int[2], 1>) == 0);
assert((extent_v<int[2][4], 1>) == 4);
```

```
assert((extent_v<int[][4], 1>) == 4);
— end example]
```

### 23.15.6 Relationships between types

[meta.rel]

- <sup>1</sup> This subclause contains templates that may be used to query relationships between types at compile time.
- <sup>2</sup> Each of these templates shall be a `BinaryTypeTrait` (23.15.1) with a base characteristic of `true_type` if the corresponding condition is true, otherwise `false_type`.

Table 44 — Type relationship predicates

| Template                                                                          | Condition                                                                                                                                                                                               | Comments                                                                                                                                                                                                                                               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| template <class T, class U><br>struct is_same;                                    | T and U name the same type with the same cv-qualifications                                                                                                                                              |                                                                                                                                                                                                                                                        |
| template <class Base, class Derived><br>struct is_base_of;                        | Base is a base class of Derived (Clause 13) without regard to cv-qualifiers or Base and Derived are not unions and name the same class type without regard to cv-qualifiers                             | If Base and Derived are non-union class types and are not possibly cv-qualified versions of the same type, Derived shall be a complete type. [Note: Base classes that are private, protected, or ambiguous are, nonetheless, base classes. — end note] |
| template <class From, class To><br>struct is_convertible;                         | see below                                                                                                                                                                                               | From and To shall be complete types, arrays of unknown bound, or cv void types.                                                                                                                                                                        |
| template <class Fn, class... ArgTypes><br>struct is_invocable;                    | The expression <code>INVOKE(declval&lt;Fn&gt;(), declval&lt;ArgTypes&gt;()...)</code> is well formed when treated as an unevaluated operand                                                             | Fn and all types in the parameter pack ArgTypes shall be complete types, cv void, or arrays of unknown bound.                                                                                                                                          |
| template <class R, class Fn, class... ArgTypes><br>struct is_invocable_r;         | The expression <code>INVOKE&lt;R&gt;(declval&lt;Fn&gt;(), declval&lt;ArgTypes&gt;()...)</code> is well formed when treated as an unevaluated operand                                                    | Fn, R, and all types in the parameter pack ArgTypes shall be complete types, cv void, or arrays of unknown bound.                                                                                                                                      |
| template <class Fn, class... ArgTypes><br>struct is_nothrow_invocable;            | <code>is_invocable_v&lt;Fn, ArgTypes...&gt;</code> is true and the expression <code>INVOKE(declval&lt;Fn&gt;(), declval&lt;ArgTypes&gt;()...)</code> is known not to throw any exceptions               | Fn and all types in the parameter pack ArgTypes shall be complete types, cv void, or arrays of unknown bound.                                                                                                                                          |
| template <class R, class Fn, class... ArgTypes><br>struct is_nothrow_invocable_r; | <code>is_invocable_r_v&lt;R, Fn, ArgTypes...&gt;</code> is true and the expression <code>INVOKE&lt;R&gt;(declval&lt;Fn&gt;(), declval&lt;ArgTypes&gt;()...)</code> is known not to throw any exceptions | Fn, R, and all types in the parameter pack ArgTypes shall be complete types, cv void, or arrays of unknown bound.                                                                                                                                      |

- <sup>3</sup> For the purpose of defining the templates in this subclause, a function call expression `declval<T>()` for any type `T` is considered to be a trivial (6.9, 15) function call that is not an odr-use (6.2) of `declval` in the context of the corresponding definition notwithstanding the restrictions of 23.2.7.

<sup>4</sup> [Example:

```
struct B {};
struct B1 : B {};
struct B2 : B {};
struct D : private B1, private B2 {};
```

```
is_base_of_v<B, D> // true
is_base_of_v<const B, D> // true
is_base_of_v<B, const D> // true
is_base_of_v<B, const B> // true
is_base_of_v<D, B> // false
is_base_of_v<B&, D&> // false
is_base_of_v<B[3], D[3]> // false
is_base_of_v<int, int> // false
```

— end example]

- <sup>5</sup> The predicate condition for a template specialization `is_convertible<From, To>` shall be satisfied if and only if the return expression in the following code would be well-formed, including any implicit conversions to the return type of the function:

```
To test() {
 return declval<From>();
}
```

[Note: This requirement gives well defined results for reference types, void types, array types, and function types. — end note] Access checking is performed in a context unrelated to `To` and `From`. Only the validity of the immediate context of the *expression* of the `return` statement (including initialization of the returned object or reference) is considered. [Note: The initialization can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — end note]

### 23.15.7 Transformations between types

[meta.trans]

- <sup>1</sup> This subclause contains templates that may be used to transform one type to another following some predefined rule.
- <sup>2</sup> Each of the templates in this subclause shall be a `TransformationTrait` (23.15.1).

#### 23.15.7.1 Const-volatile modifications

[meta.trans.cv]

Table 45 — Const-volatile modifications

| Template                                                 | Comments                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>template &lt;class T&gt; struct remove_const;</pre> | <p>The member typedef <code>type</code> names the same type as <code>T</code> except that any top-level const-qualifier has been removed. [Example: <code>remove_const_t&lt;const volatile int&gt;</code> evaluates to <code>volatile int</code>, whereas <code>remove_const_t&lt;const int*&gt;</code> evaluates to <code>const int*</code>. — end example]</p> |

Table 45 — Const-volatile modifications (continued)

| Template                                      | Comments                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| template <class T><br>struct remove_volatile; | The member typedef <b>type</b> names the same type as T except that any top-level volatile-qualifier has been removed. [ <i>Example:</i> <code>remove_volatile_t&lt;const volatile int&gt;</code> evaluates to <code>const int</code> , whereas <code>remove_volatile_t&lt;volatile int*&gt;</code> evaluates to <code>volatile int*</code> . — <i>end example</i> ] |
| template <class T><br>struct remove_cv;       | The member typedef <b>type</b> shall be the same as T except that any top-level cv-qualifier has been removed. [ <i>Example:</i> <code>remove_cv_t&lt;const volatile int&gt;</code> evaluates to <code>int</code> , whereas <code>remove_cv_t&lt;const volatile int*&gt;</code> evaluates to <code>const volatile int*</code> . — <i>end example</i> ]               |
| template <class T><br>struct add_const;       | If T is a reference, function, or top-level const-qualified type, then <b>type</b> names the same type as T, otherwise T <code>const</code> .                                                                                                                                                                                                                        |
| template <class T><br>struct add_volatile;    | If T is a reference, function, or top-level volatile-qualified type, then <b>type</b> names the same type as T, otherwise T <code>volatile</code> .                                                                                                                                                                                                                  |
| template <class T><br>struct add_cv;          | The member typedef <b>type</b> names the same type as <code>add_const_t&lt;add_volatile_t&lt;T&gt;&gt;</code> .                                                                                                                                                                                                                                                      |

## 23.15.7.2 Reference modifications

[meta.trans.ref]

Table 46 — Reference modifications

| Template                                              | Comments                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| template <class T><br>struct remove_reference;        | If T has type “reference to T1” then the member typedef <b>type</b> names T1; otherwise, <b>type</b> names T.                                                                                                                                                                                                                                       |
| template <class T><br>struct<br>add_lvalue_reference; | If T names a referenceable type (20.3.18) then the member typedef <b>type</b> names T&; otherwise, <b>type</b> names T. [ <i>Note:</i> This rule reflects the semantics of reference collapsing (11.3.2). — <i>end note</i> ]                                                                                                                       |
| template <class T><br>struct<br>add_rvalue_reference; | If T names a referenceable type then the member typedef <b>type</b> names T&&; otherwise, <b>type</b> names T. [ <i>Note:</i> This rule reflects the semantics of reference collapsing (11.3.2). For example, when a type T names a type T1&, the type <code>add_rvalue_reference_t&lt;T&gt;</code> is not an rvalue reference. — <i>end note</i> ] |

## 23.15.7.3 Sign modifications

[meta.trans.sign]

Table 47 — Sign modifications

| Template                                                  | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>template &lt;class T&gt; struct make_signed;</pre>   | <p>If T names a (possibly cv-qualified) signed integer type (6.9.1) then the member typedef <b>type</b> names the type T; otherwise, if T names a (possibly cv-qualified) unsigned integer type then <b>type</b> names the corresponding signed integer type, with the same cv-qualifiers as T; otherwise, <b>type</b> names the signed integer type with smallest rank (7.15) for which <code>sizeof(T) == sizeof(type)</code>, with the same cv-qualifiers as T.</p> <p><i>Requires:</i> T shall be a (possibly cv-qualified) integral type or enumeration but not a <code>bool</code> type.</p>     |
| <pre>template &lt;class T&gt; struct make_unsigned;</pre> | <p>If T names a (possibly cv-qualified) unsigned integer type (6.9.1) then the member typedef <b>type</b> names the type T; otherwise, if T names a (possibly cv-qualified) signed integer type then <b>type</b> names the corresponding unsigned integer type, with the same cv-qualifiers as T; otherwise, <b>type</b> names the unsigned integer type with smallest rank (7.15) for which <code>sizeof(T) == sizeof(type)</code>, with the same cv-qualifiers as T.</p> <p><i>Requires:</i> T shall be a (possibly cv-qualified) integral type or enumeration but not a <code>bool</code> type.</p> |



## 23.15.7.4 Array modifications

[meta.trans.arr]

Table 48 — Array modifications

| Template                                         | Comments                                                                                                                                                                                                                                                                        |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| template <class T><br>struct remove_extent;      | If T names a type “array of U”, the member typedef <b>type</b> shall be U, otherwise T. [ <i>Note</i> : For multidimensional arrays, only the first array dimension is removed. For a type “array of <b>const</b> U”, the resulting type is <b>const</b> U. — <i>end note</i> ] |
| template <class T><br>struct remove_all_extents; | If T is “multi-dimensional array of U”, the resulting member typedef <b>type</b> is U, otherwise T.                                                                                                                                                                             |

<sup>1</sup> [ *Example*:*// the following assertions hold:*

```
assert((is_same_v<remove_extent_t<int>, int>));
assert((is_same_v<remove_extent_t<int[2]>, int>));
assert((is_same_v<remove_extent_t<int[2][3]>, int[3]>));
assert((is_same_v<remove_extent_t<int[][3]>, int[3]>));
```

— *end example*]<sup>2</sup> [ *Example*:*// the following assertions hold:*

```
assert((is_same_v<remove_all_extents_t<int>, int>));
assert((is_same_v<remove_all_extents_t<int[2]>, int>));
assert((is_same_v<remove_all_extents_t<int[2][3]>, int>));
assert((is_same_v<remove_all_extents_t<int[][3]>, int>));
```

— *end example*]

## 23.15.7.5 Pointer modifications

[meta.trans.ptr]

Table 49 — Pointer modifications

| Template                                     | Comments                                                                                                                                                                                            |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| template <class T><br>struct remove_pointer; | If T has type “(possibly cv-qualified) pointer to T1” then the member typedef <b>type</b> names T1; otherwise, it names T.                                                                          |
| template <class T><br>struct add_pointer;    | If T names a referenceable type (20.3.18) or a <i>cv</i> void type then the member typedef <b>type</b> names the same type as <b>remove_reference_t&lt;T&gt;*</b> ; otherwise, <b>type</b> names T. |

## 23.15.7.6 Other transformations

[meta.trans.other]

Table 50 — Other transformations

| Template                                                                                                | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>template &lt;size_t Len, size_t Align = <i>default-alignment</i>&gt; struct aligned_storage;</pre> | <p>The value of <i>default-alignment</i> shall be the most stringent alignment requirement for any C++ object type whose size is no greater than <b>Len</b> (6.9). The member typedef <b>type</b> shall be a POD type suitable for use as uninitialized storage for any object whose size is at most <i>Len</i> and whose alignment is a divisor of <i>Align</i>.</p> <p><i>Requires:</i> <b>Len</b> shall not be zero. <b>Align</b> shall be equal to <code>alignof(T)</code> for some type <b>T</b> or to <i>default-alignment</i>.</p>                                                                                                                                                                                                                              |
| <pre>template &lt;size_t Len, class... Types&gt; struct aligned_union;</pre>                            | <p>The member typedef <b>type</b> shall be a POD type suitable for use as uninitialized storage for any object whose type is listed in <b>Types</b>; its size shall be at least <b>Len</b>. The static member <b>alignment_value</b> shall be an integral constant of type <code>size_t</code> whose value is the strictest alignment of all types listed in <b>Types</b>.</p> <p><i>Requires:</i> At least one type is provided.</p>                                                                                                                                                                                                                                                                                                                                  |
| <pre>template &lt;class T&gt; struct decay;</pre>                                                       | <p>Let <b>U</b> be <code>remove_reference_t&lt;T&gt;</code>. If <code>is_array_v&lt;U&gt;</code> is <b>true</b>, the member typedef <b>type</b> shall equal <code>remove_extent_t&lt;U&gt;*</code>. If <code>is_function_v&lt;U&gt;</code> is <b>true</b>, the member typedef <b>type</b> shall equal <code>add_pointer_t&lt;U&gt;</code>. Otherwise the member typedef <b>type</b> equals <code>remove_cv_t&lt;U&gt;</code>. [ <i>Note:</i> This behavior is similar to the lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) conversions applied when an lvalue expression is used as an rvalue, but also strips <i>cv</i>-qualifiers from class types in order to more closely model by-value argument passing. — <i>end note</i> ]</p> |
| <pre>template &lt;bool B, class T = void&gt; struct enable_if;</pre>                                    | <p>If <b>B</b> is <b>true</b>, the member typedef <b>type</b> shall equal <b>T</b>; otherwise, there shall be no member <b>type</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <pre>template &lt;bool B, class T, class F&gt; struct conditional;</pre>                                | <p>If <b>B</b> is <b>true</b>, the member typedef <b>type</b> shall equal <b>T</b>. If <b>B</b> is <b>false</b>, the member typedef <b>type</b> shall equal <b>F</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <pre>template &lt;class... T&gt; struct common_type;</pre>                                              | <p>Unless this trait is specialized (as specified in Note B, below), the member <b>type</b> shall be defined or omitted as specified in Note A, below. If it is omitted, there shall be no member <b>type</b>. Each type in the parameter pack <b>T</b> shall be complete, <i>cv void</i>, or an array of unknown bound.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <pre>template &lt;class T&gt; struct underlying_type;</pre>                                             | <p>The member typedef <b>type</b> names the underlying type of <b>T</b>.</p> <p><i>Requires:</i> <b>T</b> shall be a complete enumeration type (10.2)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

Table 50 — Other transformations (continued)

| Template                                                                      | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>template &lt;class Fn, class... ArgTypes&gt; struct invoke_result;</pre> | <p>If the expression <i>INVOKE</i>(<i>declval</i>&lt;Fn&gt;(), <i>declval</i>&lt;ArgTypes&gt;()...) is well formed when treated as an unevaluated operand (Clause 8), the member typedef <i>type</i> names the type <i>decltype</i>(<i>INVOKE</i>(<i>declval</i>&lt;Fn&gt;(), <i>declval</i>&lt;ArgTypes&gt;()...)); otherwise, there shall be no member <i>type</i>. Access checking is performed as if in a context unrelated to <i>Fn</i> and <i>ArgTypes</i>. Only the validity of the immediate context of the expression is considered. [ <i>Note</i>: The compilation of the expression can result in side effects such as the instantiation of class template specializations and function template specializations, the generation of implicitly-defined functions, and so on. Such side effects are not in the “immediate context” and can result in the program being ill-formed. — <i>end note</i> ]</p> <p><i>Requires</i>: <i>Fn</i> and all types in the parameter pack <i>ArgTypes</i> shall be complete types, <i>cv</i> void, or arrays of unknown bound.</p> |

<sup>1</sup> [ *Note*: A typical implementation would define *aligned\_storage* as:

```
template <size_t Len, size_t Alignment>
struct aligned_storage {
 typedef struct {
 alignas(Alignment) unsigned char __data[Len];
 } type;
};
```

— *end note* ]

<sup>2</sup> It is implementation-defined whether any extended alignment is supported (6.11).

<sup>3</sup> Note A: For the *common\_type* trait applied to a parameter pack *T* of types, the member *type* shall be either defined or not present as follows:

(3.1) — If *sizeof...(T)* is zero, there shall be no member *type*.

(3.2) — If *sizeof...(T)* is one, let *T0* denote the sole type constituting the pack *T*. The member *typedef-name type* shall denote the same type, if any, as *common\_type\_t*<*T0*, *T0*>; otherwise there shall be no member *type*.

(3.3) — If *sizeof...(T)* is two, let the first and second types constituting *T* be denoted by *T1* and *T2*, respectively, and let *D1* and *D2* denote the same types as *decay\_t*<*T1*> and *decay\_t*<*T2*>, respectively.

(3.3.1) — If *is\_same\_v*<*T1*, *D1*> is false or *is\_same\_v*<*T2*, *D2*> is false, let *C* denote the same type, if any, as *common\_type\_t*<*D1*, *D2*>.

(3.3.2) — Otherwise, let *C* denote the same type, if any, as

```
decay_t<decltype(false ? declval<D1>() : declval<D2>())>
```

[ *Note*: This will not apply if there is a specialization *common\_type*<*D1*, *D2*>. — *end note* ]

In either case, the member *typedef-name type* shall denote the same type, if any, as *C*. Otherwise, there shall be no member *type*.

(3.4) — If *sizeof...(T)* is greater than two, let *T1*, *T2*, and *R*, respectively, denote the first, second, and (pack of) remaining types constituting *T*. Let *C* denote the same type, if any, as *common\_type\_t*<*T1*, *T2*>. If there is such a type *C*, the member *typedef-name type* shall denote the same type, if any, as

`common_type_t<C, R...>`. Otherwise, there shall be no member `type`.

- <sup>4</sup> Note B: Notwithstanding the provisions of 23.15.2, and pursuant to 20.5.4.2.1, a program may specialize `common_type_t<T1, T2>` for types `T1` and `T2` such that `is_same_v<T1, decay_t<T1>>` and `is_same_v<T2, decay_t<T2>>` are each `true`. [Note: Such specializations are needed when only explicit conversions are desired between the template arguments. — end note] Such a specialization need not have a member named `type`, but if it does, that member shall be a *typedef-name* for an accessible and unambiguous cv-unqualified non-reference type `C` to which each of the types `T1` and `T2` is explicitly convertible. Moreover, `common_type_t<T1, T2>` shall denote the same type, if any, as does `common_type_t<T2, T1>`. No diagnostic is required for a violation of this Note's rules.

- <sup>5</sup> [Example: Given these definitions:

```
using PF1 = bool (&)();
using PF2 = short (*)(long);

struct S {
 operator PF2() const;
 double operator()(char, int&);
 void fn(long) const;
 char data;
};

using PMF = void (S::*)(long) const;
using PMD = char S::*;
```

the following assertions will hold:

```
static_assert(is_same_v<invoke_result_t<S, int>, short>);
static_assert(is_same_v<invoke_result_t<S&, unsigned char, int&>, double>);
static_assert(is_same_v<invoke_result_t<PF1>, bool>);
static_assert(is_same_v<invoke_result_t<PMF, unique_ptr<S>, int>, void>);
static_assert(is_same_v<invoke_result_t<PMD, S>, char&&>);
static_assert(is_same_v<invoke_result_t<PMD, const S*>, const char&>);
```

— end example]

### 23.15.8 Logical operator traits

[meta.logical]

- <sup>1</sup> This subclause describes type traits for applying logical operators to other type traits.

```
template<class... B> struct conjunction : see below { };
```

- <sup>2</sup> The class template `conjunction` forms the logical conjunction of its template type arguments.

- <sup>3</sup> For a specialization `conjunction<B1, ..., BN>`, if there is a template type argument `Bi` for which `bool(Bi::value)` is `false`, then instantiating `conjunction<B1, ..., BN>::value` does not require the instantiation of `Bj::value` for `j > i`. [Note: This is analogous to the short-circuiting behavior of the built-in operator `&&`. — end note]

- <sup>4</sup> Every template type argument for which `Bi::value` is instantiated shall be usable as a base class and shall have a member `value` which is convertible to `bool`, is not hidden, and is unambiguously available in the type.

- <sup>5</sup> The specialization `conjunction<B1, ..., BN>` has a public and unambiguous base that is either

- (5.1) — the first type `Bi` in the list `true_type`, `B1, ..., BN` for which `bool(Bi::value)` is `false`, or
- (5.2) — if there is no such `Bi`, the last type in the list.

[Note: This means a specialization of `conjunction` does not necessarily inherit from either `true_type` or `false_type`. — end note]

- 6 The member names of the base class, other than `conjunction` and `operator=`, shall not be hidden and shall be unambiguously available in `conjunction`.

```
template<class... B> struct disjunction : see below { };
```

- 7 The class template `disjunction` forms the logical disjunction of its template type arguments.
- 8 For a specialization `disjunction<B1, ..., BN>`, if there is a template type argument `Bi` for which `bool(Bi::value)` is `true`, then instantiating `disjunction<B1, ..., BN>::value` does not require the instantiation of `Bj::value` for `j > i`. [*Note: This is analogous to the short-circuiting behavior of the built-in operator `||`. — end note*]
- 9 Every template type argument for which `Bi::value` is instantiated shall be usable as a base class and shall have a member `value` which is convertible to `bool`, is not hidden, and is unambiguously available in the type.

- 10 The specialization `disjunction<B1, ..., BN>` has a public and unambiguous base that is either
- (10.1) — the first type `Bi` in the list `false_type, B1, ..., BN` for which `bool(Bi::value)` is `true`, or
- (10.2) — if there is no such `Bi`, the last type in the list.

[*Note: This means a specialization of `disjunction` does not necessarily inherit from either `true_type` or `false_type`. — end note*]

- 11 The member names of the base class, other than `disjunction` and `operator=`, shall not be hidden and shall be unambiguously available in `disjunction`.

```
template<class B> struct negation : see below { };
```

- 12 The class template `negation` forms the logical negation of its template type argument. The type `negation<B>` is a `UnaryTypeTrait` with a base characteristic of `bool_constant<!bool(B::value)>`.

## 23.16 Compile-time rational arithmetic [ratio]

### 23.16.1 In general [ratio.general]

- 1 This subclause describes the ratio library. It provides a class template `ratio` which exactly represents any finite rational number with a numerator and denominator representable by compile-time constants of type `intmax_t`.
- 2 Throughout this subclause, the names of template parameters are used to express type requirements. If a template parameter is named `R1` or `R2`, and the template argument is not a specialization of the `ratio` template, the program is ill-formed.

### 23.16.2 Header `<ratio>` synopsis [ratio.syn]

```
namespace std {
 // 23.16.3, class template ratio
 template <intmax_t N, intmax_t D = 1> class ratio;

 // 23.16.4, ratio arithmetic
 template <class R1, class R2> using ratio_add = see below;
 template <class R1, class R2> using ratio_subtract = see below;
 template <class R1, class R2> using ratio_multiply = see below;
 template <class R1, class R2> using ratio_divide = see below;

 // 23.16.5, ratio comparison
 template <class R1, class R2> struct ratio_equal;
 template <class R1, class R2> struct ratio_not_equal;
 template <class R1, class R2> struct ratio_less;
```



- <sup>2</sup> The static data members `num` and `den` shall have the following values, where `gcd` represents the greatest common divisor of the absolute values of `N` and `D`:

- (2.1) — `num` shall have the value `sign(N) * sign(D) * abs(N) / gcd`.
- (2.2) — `den` shall have the value `abs(D) / gcd`.

### 23.16.4 Arithmetic on ratios

[ratio.arithmetic]

- <sup>1</sup> Each of the alias templates `ratio_add`, `ratio_subtract`, `ratio_multiply`, and `ratio_divide` denotes the result of an arithmetic computation on two ratios `R1` and `R2`. With `X` and `Y` computed (in the absence of arithmetic overflow) as specified by Table 51, each alias denotes a `ratio<U, V>` such that `U` is the same as `ratio<X, Y>::num` and `V` is the same as `ratio<X, Y>::den`.
- <sup>2</sup> If it is not possible to represent `U` or `V` with `intmax_t`, the program is ill-formed. Otherwise, an implementation should yield correct values of `U` and `V`. If it is not possible to represent `X` or `Y` with `intmax_t`, the program is ill-formed unless the implementation yields correct values of `U` and `V`.

Table 51 — Expressions used to perform ratio arithmetic

| Type                                      | Value of X                                         | Value of Y                     |
|-------------------------------------------|----------------------------------------------------|--------------------------------|
| <code>ratio_add&lt;R1, R2&gt;</code>      | <code>R1::num * R2::den + R2::num * R1::den</code> | <code>R1::den * R2::den</code> |
| <code>ratio_subtract&lt;R1, R2&gt;</code> | <code>R1::num * R2::den - R2::num * R1::den</code> | <code>R1::den * R2::den</code> |
| <code>ratio_multiply&lt;R1, R2&gt;</code> | <code>R1::num * R2::num</code>                     | <code>R1::den * R2::den</code> |
| <code>ratio_divide&lt;R1, R2&gt;</code>   | <code>R1::num * R2::den</code>                     | <code>R1::den * R2::num</code> |

- <sup>3</sup> [Example:

```
static_assert(ratio_add<ratio<1, 3>, ratio<1, 6>>::num == 1, "1/3+1/6 == 1/2");
static_assert(ratio_add<ratio<1, 3>, ratio<1, 6>>::den == 2, "1/3+1/6 == 1/2");
static_assert(ratio_multiply<ratio<1, 3>, ratio<3, 2>>::num == 1, "1/3*3/2 == 1/2");
static_assert(ratio_multiply<ratio<1, 3>, ratio<3, 2>>::den == 2, "1/3*3/2 == 1/2");
```

*// The following cases may cause the program to be ill-formed under some implementations*

```
static_assert(ratio_add<ratio<1, INT_MAX>, ratio<1, INT_MAX>>::num == 2,
 "1/MAX+1/MAX == 2/MAX");
static_assert(ratio_add<ratio<1, INT_MAX>, ratio<1, INT_MAX>>::den == INT_MAX,
 "1/MAX+1/MAX == 2/MAX");
static_assert(ratio_multiply<ratio<1, INT_MAX>, ratio<INT_MAX, 2>>::num == 1,
 "1/MAX * MAX/2 == 1/2");
static_assert(ratio_multiply<ratio<1, INT_MAX>, ratio<INT_MAX, 2>>::den == 2,
 "1/MAX * MAX/2 == 1/2");
```

— end example]

### 23.16.5 Comparison of ratios

[ratio.comparison]

```
template <class R1, class R2>
 struct ratio_equal : bool_constant<R1::num == R2::num && R1::den == R2::den> { };

template <class R1, class R2>
 struct ratio_not_equal : bool_constant<!ratio_equal_v<R1, R2>> { };

template <class R1, class R2>
 struct ratio_less : bool_constant<see below> { };
```

- <sup>1</sup> If  $R1::\text{num} \times R2::\text{den}$  is less than  $R2::\text{num} \times R1::\text{den}$ , `ratio_less<R1, R2>` shall be derived from `bool_constant<true>`; otherwise it shall be derived from `bool_constant<false>`. Implementations may use other algorithms to compute this relationship to avoid overflow. If overflow occurs, the program is ill-formed.

```
template <class R1, class R2>
 struct ratio_less_equal : bool_constant<!ratio_less_v<R2, R1>> { };

template <class R1, class R2>
 struct ratio_greater : bool_constant<ratio_less_v<R2, R1>> { };

template <class R1, class R2>
 struct ratio_greater_equal : bool_constant<!ratio_less_v<R1, R2>> { };
```

### 23.16.6 SI types for ratio

[ratio.si]

- <sup>1</sup> For each of the *typedef-names* `yocto`, `zepto`, `zetta`, and `yotta`, if both of the constants used in its specification are representable by `intmax_t`, the typedef shall be defined; if either of the constants is not representable by `intmax_t`, the typedef shall not be defined.

## 23.17 Time utilities

[time]

### 23.17.1 In general

[time.general]

- <sup>1</sup> This subclause describes the chrono library (23.17.2) and various C functions (23.17.8) that provide generally useful time utilities.

### 23.17.2 Header <chrono> synopsis

[time.syn]

```
namespace std {
 namespace chrono {
 // 23.17.5, class template duration
 template <class Rep, class Period = ratio<1>> class duration;

 // 23.17.6, class template time_point
 template <class Clock, class Duration = typename Clock::duration> class time_point;
 }

 // 23.17.4.3, common_type specializations
 template <class Rep1, class Period1, class Rep2, class Period2>
 struct common_type<chrono::duration<Rep1, Period1>,
 chrono::duration<Rep2, Period2>>;

 template <class Clock, class Duration1, class Duration2>
 struct common_type<chrono::time_point<Clock, Duration1>,
 chrono::time_point<Clock, Duration2>>;

 namespace chrono {
 // 23.17.4, customization traits
 template <class Rep> struct treat_as_floating_point;
 template <class Rep> struct duration_values;
 template <class Rep> inline constexpr bool treat_as_floating_point_v
 = treat_as_floating_point<Rep>::value;

 // 23.17.5.5, duration arithmetic
 template <class Rep1, class Period1, class Rep2, class Period2>
 common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
 constexpr operator+(const duration<Rep1, Period1>& lhs,
```



```

 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
 constexpr operator-(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period, class Rep2>
 duration<common_type_t<Rep1, Rep2>, Period>
 constexpr operator*(const duration<Rep1, Period>& d, const Rep2& s);
template <class Rep1, class Rep2, class Period>
 duration<common_type_t<Rep1, Rep2>, Period>
 constexpr operator*(const Rep1& s, const duration<Rep2, Period>& d);
template <class Rep1, class Period, class Rep2>
 duration<common_type_t<Rep1, Rep2>, Period>
 constexpr operator/(const duration<Rep1, Period>& d, const Rep2& s);
template <class Rep1, class Period1, class Rep2, class Period2>
 common_type_t<Rep1, Rep2>
 constexpr operator/(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period, class Rep2>
 duration<common_type_t<Rep1, Rep2>, Period>
 constexpr operator%(const duration<Rep1, Period>& d, const Rep2& s);
template <class Rep1, class Period1, class Rep2, class Period2>
 common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
 constexpr operator%(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);

// 23.17.5.6, duration comparisons
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator==(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator!=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator< (const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator<=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator> (const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
 constexpr bool operator>=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);

// 23.17.5.7, duration_cast
template <class ToDuration, class Rep, class Period>
 constexpr ToDuration duration_cast(const duration<Rep, Period>& d);
template <class ToDuration, class Rep, class Period>
 constexpr ToDuration floor(const duration<Rep, Period>& d);
template <class ToDuration, class Rep, class Period>
 constexpr ToDuration ceil(const duration<Rep, Period>& d);
template <class ToDuration, class Rep, class Period>
 constexpr ToDuration round(const duration<Rep, Period>& d);

```

```

// convenience typedefs
using nanoseconds = duration<signed integer type of at least 64 bits, nano>;
using microseconds = duration<signed integer type of at least 55 bits, micro>;
using milliseconds = duration<signed integer type of at least 45 bits, milli>;
using seconds = duration<signed integer type of at least 35 bits>;
using minutes = duration<signed integer type of at least 29 bits, ratio< 60>>;
using hours = duration<signed integer type of at least 23 bits, ratio<3600>>;

// 23.17.6.5, time_point arithmetic
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr time_point<Clock, common_type_t<Duration1, duration<Rep2, Period2>>>
operator+(const time_point<Clock, Duration1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Clock, class Duration2>
constexpr time_point<Clock, common_type_t<duration<Rep1, Period1>, Duration2>>
operator+(const duration<Rep1, Period1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr time_point<Clock, common_type_t<Duration1, duration<Rep2, Period2>>>
operator-(const time_point<Clock, Duration1>& lhs,
 const duration<Rep2, Period2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr common_type_t<Duration1, Duration2>
operator-(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);

// 23.17.6.6, time_point comparisons
template <class Clock, class Duration1, class Duration2>
constexpr bool operator==(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr bool operator!=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr bool operator< (const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr bool operator<=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr bool operator> (const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
template <class Clock, class Duration1, class Duration2>
constexpr bool operator>=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);

// 23.17.6.7, time_point_cast
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
time_point_cast(const time_point<Clock, Duration>& t);
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
floor(const time_point<Clock, Duration>& tp);
template <class ToDuration, class Clock, class Duration>

```

```

 constexpr time_point<Clock, ToDuration>
 ceil(const time_point<Clock, Duration>& tp);
template <class ToDuration, class Clock, class Duration>
 constexpr time_point<Clock, ToDuration>
 round(const time_point<Clock, Duration>& tp);

// 23.17.5.9, specialized algorithms
template <class Rep, class Period>
 constexpr duration<Rep, Period> abs(duration<Rep, Period> d);

// 23.17.7, clocks
class system_clock;
class steady_clock;
class high_resolution_clock;
}

inline namespace literals {
 inline namespace chrono_literals {
 // 23.17.5.8, suffixes for duration literals
 constexpr chrono::hours operator""h(unsigned long long);
 constexpr chrono::duration<unspecified, ratio<3600,1>> operator""h(long double);
 constexpr chrono::minutes operator""min(unsigned long long);
 constexpr chrono::duration<unspecified, ratio<60,1>> operator""min(long double);
 constexpr chrono::seconds operator""s(unsigned long long);
 constexpr chrono::duration<unspecified> operator""s(long double);
 constexpr chrono::milliseconds operator""ms(unsigned long long);
 constexpr chrono::duration<unspecified, milli> operator""ms(long double);
 constexpr chrono::microseconds operator""us(unsigned long long);
 constexpr chrono::duration<unspecified, micro> operator""us(long double);
 constexpr chrono::nanoseconds operator""ns(unsigned long long);
 constexpr chrono::duration<unspecified, nano> operator""ns(long double);
 }
}

namespace chrono {
 using namespace literals::chrono_literals;
}
}

```

### 23.17.3 Clock requirements

[time.clock.req]

- <sup>1</sup> A clock is a bundle consisting of a `duration`, a `time_point`, and a function `now()` to get the current `time_point`. The origin of the clock's `time_point` is referred to as the clock's *epoch*. A clock shall meet the requirements in Table 52.
- <sup>2</sup> In Table 52 C1 and C2 denote clock types. `t1` and `t2` are values returned by `C1::now()` where the call returning `t1` happens before (4.7) the call returning `t2` and both of these calls occur before `C1::time_point::max()`. [Note: This means C1 did not wrap around between `t1` and `t2`. — end note]

Table 52 — Clock requirements

| Expression           | Return type                                                | Operational semantics                                  |
|----------------------|------------------------------------------------------------|--------------------------------------------------------|
| <code>C1::rep</code> | An arithmetic type or a class emulating an arithmetic type | The representation type of <code>C1::duration</code> . |

Table 52 — Clock requirements (continued)

| Expression                  | Return type                                                                                          | Operational semantics                                                                                                                                  |
|-----------------------------|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>C1::period</code>     | a specialization of <code>ratio</code>                                                               | The tick period of the clock in seconds.                                                                                                               |
| <code>C1::duration</code>   | <code>chrono::duration&lt;C1::rep, C1::period&gt;</code>                                             | The <code>duration</code> type of the clock.                                                                                                           |
| <code>C1::time_point</code> | <code>chrono::time_point&lt;C1&gt;</code> or <code>chrono::time_point&lt;C2, C1::duration&gt;</code> | The <code>time_point</code> type of the clock. <code>C1</code> and <code>C2</code> shall refer to the same epoch.                                      |
| <code>C1::is_steady</code>  | <code>const bool</code>                                                                              | <code>true</code> if <code>t1 &lt;= t2</code> is always <code>true</code> and the time between clock ticks is constant, otherwise <code>false</code> . |
| <code>C1::now()</code>      | <code>C1::time_point</code>                                                                          | Returns a <code>time_point</code> object representing the current point in time.                                                                       |

<sup>3</sup> [ *Note*: The relative difference in durations between those reported by a given clock and the SI definition is a measure of the quality of implementation. — *end note* ]

<sup>4</sup> A type `TC` meets the `TrivialClock` requirements if:

- (4.1) — `TC` satisfies the `Clock` requirements (23.17.3),
- (4.2) — the types `TC::rep`, `TC::duration`, and `TC::time_point` satisfy the requirements of `EqualityComparable` (Table 20), `LessThanComparable` (Table 21), `DefaultConstructible` (Table 22), `CopyConstructible` (Table 24), `CopyAssignable` (Table 26), `Destructible` (Table 27), and the requirements of numeric types (29.3). [ *Note*: This means, in particular, that operations on these types will not throw exceptions. — *end note* ]
- (4.3) — lvalues of the types `TC::rep`, `TC::duration`, and `TC::time_point` are swappable (20.5.3.2),
- (4.4) — the function `TC::now()` does not throw exceptions, and
- (4.5) — the type `TC::time_point::clock` meets the `TrivialClock` requirements, recursively.

## 23.17.4 Time-related traits

[time.traits]

### 23.17.4.1 `treat_as_floating_point`

[time.traits.is\_fp]

```
template <class Rep> struct treat_as_floating_point
: is_floating_point<Rep> { };
```

- <sup>1</sup> The `duration` template uses the `treat_as_floating_point` trait to help determine if a `duration` object can be converted to another `duration` with a different tick period. If `treat_as_floating_point_v<Rep>` is `true`, then implicit conversions are allowed among `durations`. Otherwise, the implicit convertibility depends on the tick periods of the `durations`. [ *Note*: The intention of this trait is to indicate whether a given class behaves like a floating-point type, and thus allows division of one value by another with acceptable loss of precision. If `treat_as_floating_point_v<Rep>` is `false`, `Rep` will be treated as if it behaved like an integral type for the purpose of these conversions. — *end note* ]

### 23.17.4.2 `duration_values`

[time.traits.duration\_values]

```
template <class Rep>
struct duration_values {
public:
```

```

 static constexpr Rep zero();
 static constexpr Rep min();
 static constexpr Rep max();
};

```

- <sup>1</sup> The `duration` template uses the `duration_values` trait to construct special values of the durations representation (`Rep`). This is done because the representation might be a class type with behavior which requires some other implementation to return these special values. In that case, the author of that class type should specialize `duration_values` to return the indicated values.

```
static constexpr Rep zero();
```

- <sup>2</sup> *Returns:* `Rep(0)`. [*Note:* `Rep(0)` is specified instead of `Rep()` because `Rep()` may have some other meaning, such as an uninitialized value. — *end note*]

- <sup>3</sup> *Remarks:* The value returned shall be the additive identity.

```
static constexpr Rep min();
```

- <sup>4</sup> *Returns:* `numeric_limits<Rep>::lowest()`.

- <sup>5</sup> *Remarks:* The value returned shall compare less than or equal to `zero()`.

```
static constexpr Rep max();
```

- <sup>6</sup> *Returns:* `numeric_limits<Rep>::max()`.

- <sup>7</sup> *Remarks:* The value returned shall compare greater than `zero()`.

#### 23.17.4.3 Specializations of `common_type`

[`time.traits.specializations`]

```

template <class Rep1, class Period1, class Rep2, class Period2>
struct common_type<chrono::duration<Rep1, Period1>, chrono::duration<Rep2, Period2>> {
 using type = chrono::duration<common_type_t<Rep1, Rep2>, see below>;
};

```

- <sup>1</sup> The period of the duration indicated by this specialization of `common_type` shall be the greatest common divisor of `Period1` and `Period2`. [*Note:* This can be computed by forming a ratio of the greatest common divisor of `Period1::num` and `Period2::num` and the least common multiple of `Period1::den` and `Period2::den`. — *end note*]

- <sup>2</sup> [*Note:* The typedef name `type` is a synonym for the `duration` with the largest tick period possible where both `duration` arguments will convert to it without requiring a division operation. The representation of this type is intended to be able to hold any value resulting from this conversion with no truncation error, although floating-point durations may have round-off errors. — *end note*]

```

template <class Clock, class Duration1, class Duration2>
struct common_type<chrono::time_point<Clock, Duration1>, chrono::time_point<Clock, Duration2>> {
 using type = chrono::time_point<Clock, common_type_t<Duration1, Duration2>>;
};

```

- <sup>3</sup> The common type of two `time_point` types is a `time_point` with the same clock as the two types and the common type of their two durations.

#### 23.17.5 Class template `duration`

[`time.duration`]

- <sup>1</sup> A `duration` type measures time between two points in time (`time_points`). A `duration` has a representation which holds a count of ticks and a tick period. The tick period is the amount of time which occurs from one tick to the next, in units of seconds. It is expressed as a rational constant using the template `ratio`.

```

template <class Rep, class Period = ratio<1>>
class duration {

```

```

public:
 using rep = Rep;
 using period = typename Period::type;
private:
 rep rep_; // exposition only
public:
 // 23.17.5.1, construct/copy/destroy
 constexpr duration() = default;
 template <class Rep2>
 constexpr explicit duration(const Rep2& r);
 template <class Rep2, class Period2>
 constexpr duration(const duration<Rep2, Period2>& d);
 ~duration() = default;
 duration(const duration&) = default;
 duration& operator=(const duration&) = default;

 // 23.17.5.2, observer
 constexpr rep count() const;

 // 23.17.5.3, arithmetic
 constexpr common_type_t<duration> operator+() const;
 constexpr common_type_t<duration> operator-() const;
 constexpr duration& operator++();
 constexpr duration operator++(int);
 constexpr duration& operator--();
 constexpr duration operator--(int);

 constexpr duration& operator+=(const duration& d);
 constexpr duration& operator-=(const duration& d);

 constexpr duration& operator*=(const rep& rhs);
 constexpr duration& operator/=(const rep& rhs);
 constexpr duration& operator%=(const rep& rhs);
 constexpr duration& operator%=(const duration& rhs);

 // 23.17.5.4, special values
 static constexpr duration zero();
 static constexpr duration min();
 static constexpr duration max();
};

```

- 2 Rep shall be an arithmetic type or a class emulating an arithmetic type. If `duration` is instantiated with a `duration` type as the argument for the template parameter `Rep`, the program is ill-formed.
- 3 If `Period` is not a specialization of `ratio`, the program is ill-formed. If `Period::num` is not positive, the program is ill-formed.
- 4 Members of `duration` shall not throw exceptions other than those thrown by the indicated operations on their representations.
- 5 The defaulted copy constructor of `duration` shall be a `constexpr` function if and only if the required initialization of the member `rep_` for copy and move, respectively, would satisfy the requirements for a `constexpr` function.
- 6 [Example:

```

duration<long, ratio<60>> d0; // holds a count of minutes using a long
duration<long long, milli> d1; // holds a count of milliseconds using a long long
duration<double, ratio<1, 30>> d2; // holds a count with a tick period of $\frac{1}{30}$ of a second

```

*// (30 Hz) using a double*

*— end example]*

### 23.17.5.1 duration constructors

[time.duration.cons]

```
template <class Rep2>
```

```
constexpr explicit duration(const Rep2& r);
```

1 *Remarks:* This constructor shall not participate in overload resolution unless `Rep2` is implicitly convertible to `rep` and

(1.1) *—* `treat_as_floating_point_v<rep>` is true or

(1.2) *—* `treat_as_floating_point_v<Rep2>` is false.

[ *Example:*

```
duration<int, milli> d(3); // OK
```

```
duration<int, milli> d(3.5); // error
```

*— end example]*

2 *Effects:* Constructs an object of type `duration`.

3 *Postconditions:* `count() == static_cast<rep>(r)`.

```
template <class Rep2, class Period2>
```

```
constexpr duration(const duration<Rep2, Period2>& d);
```

4 *Remarks:* This constructor shall not participate in overload resolution unless no overflow is induced in the conversion and `treat_as_floating_point_v<rep>` is true or both `ratio_divide<Period2, period>::den` is 1 and `treat_as_floating_point_v<Rep2>` is false. [ *Note:* This requirement prevents implicit truncation error when converting between integral-based `duration` types. Such a construction could easily lead to confusion about the value of the `duration`. *— end note* ] [ *Example:*

```
duration<int, milli> ms(3);
```

```
duration<int, micro> us = ms; // OK
```

```
duration<int, milli> ms2 = us; // error
```

*— end example]*

5 *Effects:* Constructs an object of type `duration`, constructing `rep_` from `duration_cast<duration>(d).count()`.

### 23.17.5.2 duration observer

[time.duration.observer]

```
constexpr rep count() const;
```

1 *Returns:* `rep_`.

### 23.17.5.3 duration arithmetic

[time.duration.arithmetic]

```
constexpr common_type_t<duration> operator+() const;
```

1 *Returns:* `common_type_t<duration>(*this)`.

```
constexpr common_type_t<duration> operator-() const;
```

2 *Returns:* `common_type_t<duration>(-rep_)`.

```
constexpr duration& operator++();
```

3 *Effects:* As if by `++rep_`.

4 *Returns:* `*this`.

```

constexpr duration operator++(int);
5 Returns: duration(rep_++).

constexpr duration& operator--();
6 Effects: As if by --rep_.
7 Returns: *this.

constexpr duration operator--(int);
8 Returns: duration(rep_--).

constexpr duration& operator+=(const duration& d);
9 Effects: As if by: rep_ += d.count();
10 Returns: *this.

constexpr duration& operator-=(const duration& d);
11 Effects: As if by: rep_ -= d.count();
12 Returns: *this.

constexpr duration& operator*=(const rep& rhs);
13 Effects: As if by: rep_ *= rhs;
14 Returns: *this.

constexpr duration& operator/=(const rep& rhs);
15 Effects: As if by: rep_ /= rhs;
16 Returns: *this.

constexpr duration& operator%=(const rep& rhs);
17 Effects: As if by: rep_ %= rhs;
18 Returns: *this.

constexpr duration& operator%=(const duration& rhs);
19 Effects: As if by: rep_ %= rhs.count();
20 Returns: *this.

```

#### 23.17.5.4 duration special values

[time.duration.special]

```

static constexpr duration zero();
1 Returns: duration(duration_values<rep>::zero()).

static constexpr duration min();
2 Returns: duration(duration_values<rep>::min()).

static constexpr duration max();
3 Returns: duration(duration_values<rep>::max()).

```

#### 23.17.5.5 duration non-member arithmetic

[time.duration.nonmember]

1 In the function descriptions that follow, CD represents the return type of the function. CR(A, B) represents common\_type\_t<A, B>.



```

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
operator+(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
2 Returns: CD(CD(lhs).count() + CD(rhs).count()).

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
operator-(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
3 Returns: CD(CD(lhs).count() - CD(rhs).count()).

template <class Rep1, class Period, class Rep2>
constexpr duration<common_type_t<Rep1, Rep2>, Period>
operator*(const duration<Rep1, Period>& d, const Rep2& s);
4 Remarks: This operator shall not participate in overload resolution unless Rep2 is implicitly convertible
to CR(Rep1, Rep2).
5 Returns: CD(CD(d).count() * s).

template <class Rep1, class Rep2, class Period>
constexpr duration<common_type_t<Rep1, Rep2>, Period>
operator*(const Rep1& s, const duration<Rep2, Period>& d);
6 Remarks: This operator shall not participate in overload resolution unless Rep1 is implicitly convertible
to CR(Rep1, Rep2).
7 Returns: d * s.

template <class Rep1, class Period, class Rep2>
constexpr duration<common_type_t<Rep1, Rep2>, Period>
operator/(const duration<Rep1, Period>& d, const Rep2& s);
8 Remarks: This operator shall not participate in overload resolution unless Rep2 is implicitly convertible
to CR(Rep1, Rep2) and Rep2 is not a specialization of duration.
9 Returns: CD(CD(d).count() / s).

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr common_type_t<Rep1, Rep2>
operator/(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
10 Returns: CD(lhs).count() / CD(rhs).count().

template <class Rep1, class Period, class Rep2>
constexpr duration<common_type_t<Rep1, Rep2>, Period>
operator%(const duration<Rep1, Period>& d, const Rep2& s);
11 Remarks: This operator shall not participate in overload resolution unless Rep2 is implicitly convertible
to CR(Rep1, Rep2) and Rep2 is not a specialization of duration.
12 Returns: CD(CD(d).count() % s).

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr common_type_t<duration<Rep1, Period1>, duration<Rep2, Period2>>
operator%(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
13 Returns: CD(CD(lhs).count() % CD(rhs).count()).

```

**23.17.5.6 duration comparisons****[time.duration.comparisons]**

- <sup>1</sup> In the function descriptions that follow, *CT* represents `common_type_t<A, B>`, where A and B are the types of the two arguments to the function.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator==(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>2</sup> *Returns:* `CT(lhs).count() == CT(rhs).count()`.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator!=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>3</sup> *Returns:* `!(lhs == rhs)`.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator<(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>4</sup> *Returns:* `CT(lhs).count() < CT(rhs).count()`.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator<=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>5</sup> *Returns:* `!(rhs < lhs)`.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator>(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>6</sup> *Returns:* `rhs < lhs`.

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator>=(const duration<Rep1, Period1>& lhs,
 const duration<Rep2, Period2>& rhs);
```

- <sup>7</sup> *Returns:* `!(lhs < rhs)`.

**23.17.5.7 duration\_cast****[time.duration.cast]**

```
template <class ToDuration, class Rep, class Period>
constexpr ToDuration duration_cast(const duration<Rep, Period>& d);
```

- <sup>1</sup> *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

- <sup>2</sup> *Returns:* Let CF be `ratio_divide<Period, typename ToDuration::period>`, and CR be `common_type<typename ToDuration::rep, Rep, intmax_t>::type`.

- (2.1) — If `CF::num == 1` and `CF::den == 1`, returns  
`ToDuration(static_cast<typename ToDuration::rep>(d.count()))`
- (2.2) — otherwise, if `CF::num != 1` and `CF::den == 1`, returns  
`ToDuration(static_cast<typename ToDuration::rep>(
 static_cast<CR>(d.count()) * static_cast<CR>(CF::num)))`
- (2.3) — otherwise, if `CF::num == 1` and `CF::den != 1`, returns  
`ToDuration(static_cast<typename ToDuration::rep>(
 static_cast<CR>(d.count()) / static_cast<CR>(CF::den)))`

(2.4) — otherwise, returns

```
ToDuration(static_cast<typename ToDuration::rep>(
 static_cast<CR>(d.count()) * static_cast<CR>(CF::num) / static_cast<CR>(CF::den)))
```

3 [ *Note:* This function does not use any implicit conversions; all conversions are done with `static_cast`. It avoids multiplications and divisions when it is known at compile time that one or more arguments is 1. Intermediate computations are carried out in the widest representation and only converted to the destination representation at the final step. — *end note* ]

```
template <class ToDuration, class Rep, class Period>
constexpr ToDuration floor(const duration<Rep, Period>& d);
```

4 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

5 *Returns:* The greatest result `t` representable in `ToDuration` for which `t <= d`.

```
template <class ToDuration, class Rep, class Period>
constexpr ToDuration ceil(const duration<Rep, Period>& d);
```

6 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

7 *Returns:* The least result `t` representable in `ToDuration` for which `t >= d`.

```
template <class ToDuration, class Rep, class Period>
constexpr ToDuration round(const duration<Rep, Period>& d);
```

8 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`, and `treat_as_floating_point_v<typename ToDuration::rep>` is `false`.

9 *Returns:* The value of `ToDuration` that is closest to `d`. If there are two closest values, then return the value `t` for which `t % 2 == 0`.

### 23.17.5.8 Suffixes for duration literals

[time.duration.literals]

1 This section describes literal suffixes for constructing duration literals. The suffixes `h`, `min`, `s`, `ms`, `us`, `ns` denote duration values of the corresponding types `hours`, `minutes`, `seconds`, `milliseconds`, `microseconds`, and `nanoseconds` respectively if they are applied to integral literals.

2 If any of these suffixes are applied to a floating-point literal the result is a `chrono::duration` literal with an unspecified floating-point representation.

3 If any of these suffixes are applied to an integer literal and the resulting `chrono::duration` value cannot be represented in the result type because of overflow, the program is ill-formed.

4 [ *Example:* The following code shows some duration literals.

```
using namespace std::chrono_literals;
auto constexpr aday=24h;
auto constexpr lesson=45min;
auto constexpr halfanhour=0.5h;
```

— *end example* ]

```
constexpr chrono::hours operator""h(unsigned long long hours);
constexpr chrono::duration<unspecified, ratio<3600, 1>> operator""h(long double hours);
```

5 *Returns:* A duration literal representing hours hours.

```
constexpr chrono::minutes operator""min(unsigned long long minutes);
constexpr chrono::duration<unspecified, ratio<60, 1>> operator""min(long double minutes);
```

6 *Returns:* A duration literal representing minutes minutes.

```
constexpr chrono::seconds operator"s(unsigned long long sec);
constexpr chrono::duration<unspecified> operator"s(long double sec);
```

7 *Returns:* A duration literal representing sec seconds.

8 [ *Note:* The same suffix s is used for basic\_string but there is no conflict, since duration suffixes apply to numbers and string literal suffixes apply to character array literals. — end note ]

```
constexpr chrono::milliseconds operator"ms(unsigned long long msec);
constexpr chrono::duration<unspecified, milli> operator"ms(long double msec);
```

9 *Returns:* A duration literal representing msec milliseconds.

```
constexpr chrono::microseconds operator"us(unsigned long long usec);
constexpr chrono::duration<unspecified, micro> operator"us(long double usec);
```

10 *Returns:* A duration literal representing usec microseconds.

```
constexpr chrono::nanoseconds operator"ns(unsigned long long nsec);
constexpr chrono::duration<unspecified, nano> operator"ns(long double nsec);
```

11 *Returns:* A duration literal representing nsec nanoseconds.

### 23.17.5.9 duration algorithms

[time.duration.alg]

```
template <class Rep, class Period>
constexpr duration<Rep, Period> abs(duration<Rep, Period> d);
```

1 *Remarks:* This function shall not participate in overload resolution unless numeric\_limits<Rep>::is\_signed is true.

2 *Returns:* If d >= d.zero(), return d, otherwise return -d.

### 23.17.6 Class template time\_point

[time.point]

```
template <class Clock, class Duration = typename Clock::duration>
class time_point {
public:
 using clock = Clock;
 using duration = Duration;
 using rep = typename duration::rep;
 using period = typename duration::period;
private:
 duration d_; // exposition only

public:
 // 23.17.6.1, construct
 constexpr time_point(); // has value epoch
 constexpr explicit time_point(const duration& d); // same as time_point() + d
 template <class Duration2>
 constexpr time_point(const time_point<clock, Duration2>& t);

 // 23.17.6.2, observer
 constexpr duration time_since_epoch() const;

 // 23.17.6.3, arithmetic
 constexpr time_point& operator+=(const duration& d);
 constexpr time_point& operator-=(const duration& d);
```

```

 // 23.17.6.4, special values
 static constexpr time_point min();
 static constexpr time_point max();
};

```

1 Clock shall meet the Clock requirements (23.17.3).

2 If Duration is not an instance of duration, the program is ill-formed.

#### 23.17.6.1 time\_point constructors [time.point.cons]

```
constexpr time_point();
```

1 *Effects:* Constructs an object of type time\_point, initializing d\_ with duration::zero(). Such a time\_point object represents the epoch.

```
constexpr explicit time_point(const duration& d);
```

2 *Effects:* Constructs an object of type time\_point, initializing d\_ with d. Such a time\_point object represents the epoch + d.

```
template <class Duration2>
constexpr time_point(const time_point<clock, Duration2>& t);
```

3 *Remarks:* This constructor shall not participate in overload resolution unless Duration2 is implicitly convertible to duration.

4 *Effects:* Constructs an object of type time\_point, initializing d\_ with t.time\_since\_epoch().

#### 23.17.6.2 time\_point observer [time.point.observer]

```
constexpr duration time_since_epoch() const;
```

1 *Returns:* d\_.

#### 23.17.6.3 time\_point arithmetic [time.point.arithmetic]

```
constexpr time_point& operator+=(const duration& d);
```

1 *Effects:* As if by: d\_ += d;

2 *Returns:* \*this.

```
constexpr time_point& operator-=(const duration& d);
```

3 *Effects:* As if by: d\_ -= d;

4 *Returns:* \*this.

#### 23.17.6.4 time\_point special values [time.point.special]

```
static constexpr time_point min();
```

1 *Returns:* time\_point(duration::min()).

```
static constexpr time_point max();
```

2 *Returns:* time\_point(duration::max()).

#### 23.17.6.5 time\_point non-member arithmetic [time.point.nonmember]

```
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr time_point<Clock, common_type_t<Duration1, duration<Rep2, Period2>>>
operator+(const time_point<Clock, Duration1>& lhs, const duration<Rep2, Period2>& rhs);
```

1 *Returns:* CT(lhs.time\_since\_epoch() + rhs), where CT is the type of the return value.

```
template <class Rep1, class Period1, class Clock, class Duration2>
constexpr time_point<Clock, common_type_t<duration<Rep1, Period1>, Duration2>>
operator+(const duration<Rep1, Period1>& lhs, const time_point<Clock, Duration2>& rhs);
```

2     *Returns:* rhs + lhs.

```
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr time_point<Clock, common_type_t<Duration1, duration<Rep2, Period2>>>
operator-(const time_point<Clock, Duration1>& lhs, const duration<Rep2, Period2>& rhs);
```

3     *Returns:* CT(lhs.time\_since\_epoch() - rhs), where CT is the type of the return value.

```
template <class Clock, class Duration1, class Duration2>
constexpr common_type_t<Duration1, Duration2>
operator-(const time_point<Clock, Duration1>& lhs, const time_point<Clock, Duration2>& rhs);
```

4     *Returns:* lhs.time\_since\_epoch() - rhs.time\_since\_epoch().

### 23.17.6.6 time\_point comparisons

[time.point.comparisons]

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator==(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

1     *Returns:* lhs.time\_since\_epoch() == rhs.time\_since\_epoch().

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator!=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

2     *Returns:* !(lhs == rhs).

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator<(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

3     *Returns:* lhs.time\_since\_epoch() < rhs.time\_since\_epoch().

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator<=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

4     *Returns:* !(rhs < lhs).

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator>(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

5     *Returns:* rhs < lhs.

```
template <class Clock, class Duration1, class Duration2>
constexpr bool operator>=(const time_point<Clock, Duration1>& lhs,
 const time_point<Clock, Duration2>& rhs);
```

6     *Returns:* !(lhs < rhs).

### 23.17.6.7 time\_point\_cast

[time.point.cast]

```
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
time_point_cast(const time_point<Clock, Duration>& t);
```

1 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

2 *Returns:*

```
time_point<Clock, ToDuration>(duration_cast<ToDuration>(t.time_since_epoch()))
```

```
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
floor(const time_point<Clock, Duration>& tp);
```

3 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

4 *Returns:* `time_point<Clock, ToDuration>(floor<ToDuration>(tp.time_since_epoch()))`.

```
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
ceil(const time_point<Clock, Duration>& tp);
```

5 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`.

6 *Returns:* `time_point<Clock, ToDuration>(ceil<ToDuration>(tp.time_since_epoch()))`.

```
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
round(const time_point<Clock, Duration>& tp);
```

7 *Remarks:* This function shall not participate in overload resolution unless `ToDuration` is a specialization of `duration`, and `treat_as_floating_point_v<typename ToDuration::rep>` is `false`.

8 *Returns:* `time_point<Clock, ToDuration>(round<ToDuration>(tp.time_since_epoch()))`.

### 23.17.7 Clocks

[time.clock]

1 The types defined in this subclause shall satisfy the `TrivialClock` requirements (23.17.3).

#### 23.17.7.1 Class `system_clock`

[time.clock.system]

1 Objects of class `system_clock` represent wall clock time from the system-wide realtime clock.

```
class system_clock {
public:
 using rep = see below;
 using period = ratio<unspecified, unspecified>;
 using duration = chrono::duration<rep, period>;
 using time_point = chrono::time_point<system_clock>;
 static constexpr bool is_steady = unspecified;

 static time_point now() noexcept;

 // Map to C API
 static time_t to_time_t (const time_point& t) noexcept;
 static time_point from_time_t(time_t t) noexcept;
};
```

```
using system_clock::rep = unspecified;
```

2 *Requires:* `system_clock::duration::min() < system_clock::duration::zero()` shall be `true`.  
[Note: This implies that `rep` is a signed type. — end note]

```
static time_t to_time_t(const time_point& t) noexcept;
```

- <sup>3</sup> *Returns:* A `time_t` object that represents the same point in time as `t` when both values are restricted to the coarser of the precisions of `time_t` and `time_point`. It is implementation-defined whether values are rounded or truncated to the required precision.

```
static time_point from_time_t(time_t t) noexcept;
```

- <sup>4</sup> *Returns:* A `time_point` object that represents the same point in time as `t` when both values are restricted to the coarser of the precisions of `time_t` and `time_point`. It is implementation-defined whether values are rounded or truncated to the required precision.

### 23.17.7.2 Class `steady_clock` [time.clock.steady]

- <sup>1</sup> Objects of class `steady_clock` represent clocks for which values of `time_point` never decrease as physical time advances and for which values of `time_point` advance at a steady rate relative to real time. That is, the clock may not be adjusted.

```
class steady_clock {
public:
 using rep = unspecified;
 using period = ratio<unspecified, unspecified>;
 using duration = chrono::duration<rep, period>;
 using time_point = chrono::time_point<unspecified, duration>;
 static constexpr bool is_steady = true;

 static time_point now() noexcept;
};
```

### 23.17.7.3 Class `high_resolution_clock` [time.clock.hires]

- <sup>1</sup> Objects of class `high_resolution_clock` represent clocks with the shortest tick period. `high_resolution_clock` may be a synonym for `system_clock` or `steady_clock`.

```
class high_resolution_clock {
public:
 using rep = unspecified;
 using period = ratio<unspecified, unspecified>;
 using duration = chrono::duration<rep, period>;
 using time_point = chrono::time_point<unspecified, duration>;
 static constexpr bool is_steady = unspecified;

 static time_point now() noexcept;
};
```

## 23.17.8 Header `<ctime>` synopsis [ctime.syn]

```
#define NULL see 21.2.3
#define CLOCKS_PER_SEC see below
#define TIME_UTC see below

namespace std {
 using size_t = see 21.2.4;
 using clock_t = see below;
 using time_t = see below;

 struct timespec;
 struct tm;

 clock_t clock();
 double difftime(time_t time1, time_t time0);
```



```

time_t mktime(struct tm* timeptr);
time_t time(time_t* timer);
int timespec_get(timespec* ts, int base);
char* asctime(const struct tm* timeptr);
char* ctime(const time_t* timer);
struct tm* gmtime(const time_t* timer);
struct tm* localtime(const time_t* timer);
size_t strftime(char* s, size_t maxsize, const char* format, const struct tm* timeptr);
}

```

<sup>1</sup> The contents of the header <ctime> are the same as the C standard library header <time.h>. <sup>223</sup>

<sup>2</sup> The functions asctime, ctime, gmtime, and localtime are not required to avoid data races (20.5.5.9).

SEE ALSO: ISO C 7.27.

## 23.18 Class type\_index

[type.index]

### 23.18.1 Header <typeindex> synopsis

[type.index.synopsis]

```

namespace std {
 class type_index;
 template <class T> struct hash;
 template<> struct hash<type_index>;
}

```

### 23.18.2 type\_index overview

[type.index.overview]

```

namespace std {
 class type_index {
 public:
 type_index(const type_info& rhs) noexcept;
 bool operator==(const type_index& rhs) const noexcept;
 bool operator!=(const type_index& rhs) const noexcept;
 bool operator< (const type_index& rhs) const noexcept;
 bool operator<= (const type_index& rhs) const noexcept;
 bool operator> (const type_index& rhs) const noexcept;
 bool operator>= (const type_index& rhs) const noexcept;
 size_t hash_code() const noexcept;
 const char* name() const noexcept;
 private:
 const type_info* target; // exposition only
 // Note that the use of a pointer here, rather than a reference,
 // means that the default copy/move constructor and assignment
 // operators will be provided and work as expected.
 };
}

```

<sup>1</sup> The class type\_index provides a simple wrapper for type\_info which can be used as an index type in associative containers (26.4) and in unordered associative containers (26.5).

### 23.18.3 type\_index members

[type.index.members]

```
type_index(const type_info& rhs) noexcept;
```

<sup>1</sup> *Effects:* Constructs a type\_index object, the equivalent of `target = &rhs`.

```
bool operator==(const type_index& rhs) const noexcept;
```

<sup>2</sup> *Returns:* `*target == *rhs.target`.

---

223) strftime supports the C conversion specifiers C, D, e, F, g, G, h, r, R, t, T, u, V, and z, and the modifiers E and O.

```

bool operator!=(const type_index& rhs) const noexcept;
3 Returns: *target != *rhs.target.

bool operator<(const type_index& rhs) const noexcept;
4 Returns: target->before(*rhs.target).

bool operator<=(const type_index& rhs) const noexcept;
5 Returns: !rhs.target->before(*target).

bool operator>(const type_index& rhs) const noexcept;
6 Returns: rhs.target->before(*target).

bool operator>=(const type_index& rhs) const noexcept;
7 Returns: !target->before(*rhs.target).

size_t hash_code() const noexcept;
8 Returns: target->hash_code().

const char* name() const noexcept;
9 Returns: target->name().

```

#### 23.18.4 Hash support

[type.index.hash]

```

template <> struct hash<type_index>;
1 For an object index of type type_index, hash<type_index>()(index) shall evaluate to the same
 result as index.hash_code().

```

### 23.19 Execution policies

[execpol]

#### 23.19.1 In general

[execpol.general]

1 This subclause describes classes that are *execution policy* types. An object of an execution policy type indicates the kinds of parallelism allowed in the execution of an algorithm and expresses the consequent requirements on the element access functions. [Example:

```

using namespace std;
vector<int> v = /* ... */;

// standard sequential sort
sort(v.begin(), v.end());

// explicitly sequential sort
sort(execution::seq, v.begin(), v.end());

// permitting parallel execution
sort(execution::par, v.begin(), v.end());

// permitting vectorization as well
sort(execution::par_unseq, v.begin(), v.end());

```

— end example] [Note: Because different parallel architectures may require idiosyncratic parameters for efficient execution, implementations may provide additional execution policies to those described in this standard as extensions. — end note]

#### 23.19.2 Header <execution> synopsis

[execution.syn]

```

namespace std {
 // 23.19.3, execution policy type trait
 template<class T> struct is_execution_policy;
 template<class T> inline constexpr bool is_execution_policy_v = is_execution_policy<T>::value;
}

namespace std::execution {
 // 23.19.4, sequenced execution policy
 class sequenced_policy;

 // 23.19.5, parallel execution policy
 class parallel_policy;

 // 23.19.6, parallel and unsequenced execution policy
 class parallel_unsequenced_policy;

 // 23.19.7, execution policy objects
 inline constexpr sequenced_policy seq{ unspecified };
 inline constexpr parallel_policy par{ unspecified };
 inline constexpr parallel_unsequenced_policy par_unseq{ unspecified };
}

```

### 23.19.3 Execution policy type trait

[execpol.type]

template<class T> struct is\_execution\_policy { *see below* };

- 1 is\_execution\_policy can be used to detect execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- 2 is\_execution\_policy<T> shall be a `UnaryTypeTrait` with a base characteristic of `true_type` if T is the type of a standard or implementation-defined execution policy, otherwise `false_type`.  
[ *Note*: This provision reserves the privilege of creating non-standard execution policies to the library implementation. — *end note*]
- 3 The behavior of a program that adds specializations for `is_execution_policy` is undefined.

### 23.19.4 Sequenced execution policy

[execpol.seq]

class execution::sequenced\_policy { *unspecified* };

- 1 The class `execution::sequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and require that a parallel algorithm's execution may not be parallelized.
- 2 During the execution of a parallel algorithm with the `execution::sequenced_policy` policy, if the invocation of an element access function exits via an uncaught exception, `terminate()` shall be called.

### 23.19.5 Parallel execution policy

[execpol.par]

class execution::parallel\_policy { *unspecified* };

- 1 The class `execution::parallel_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized.
- 2 During the execution of a parallel algorithm with the `execution::parallel_policy` policy, if the invocation of an element access function exits via an uncaught exception, `terminate()` shall be called.

### 23.19.6 Parallel and unsequenced execution policy

[execpol.parunseq]

```
class execution::parallel_unsequenced_policy { unspecified };
```

- 1 The class `execution::parallel_unsequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized and vectorized.
- 2 During the execution of a parallel algorithm with the `execution::parallel_unsequenced_policy` policy, if the invocation of an element access function exits via an uncaught exception, `terminate()` shall be called.

### 23.19.7 Execution policy objects

[execpol.objects]

```
inline constexpr execution::sequenced_policy execution::seq{ unspecified };
inline constexpr execution::parallel_policy execution::par{ unspecified };
inline constexpr execution::parallel_unsequenced_policy execution::par_unseq{ unspecified };
```

- 1 The header `<execution>` declares global objects associated with each type of execution policy.

## 24 Strings library

[strings]

### 24.1 General

[strings.general]

- <sup>1</sup> This Clause describes components for manipulating sequences of any non-array POD (6.9) type. Such types are called *char-like types*, and objects of char-like types are called *char-like objects* or simply *characters*.
- <sup>2</sup> The following subclauses describe a character traits class, a string class, and null-terminated sequence utilities, as summarized in Table 53.

Table 53 — Strings library summary

| Subclause                               | Header(s)     |
|-----------------------------------------|---------------|
| 24.2 Character traits                   | <string>      |
| 24.3 String classes                     | <string>      |
| 24.4 String view classes                | <string_view> |
| 24.5 Null-terminated sequence utilities | <cctype>      |
|                                         | <cwctype>     |
|                                         | <cstring>     |
|                                         | <wchar>       |
|                                         | <cstdlib>     |
|                                         | <cuchar>      |

### 24.2 Character traits

[char.traits]

- <sup>1</sup> This subclause defines requirements on classes representing *character traits*, and defines a class template `char_traits<CharT>`, along with four specializations, `char_traits<char>`, `char_traits<char16_t>`, `char_traits<char32_t>`, and `char_traits<wchar_t>`, that satisfy those requirements.
- <sup>2</sup> Most classes specified in Clauses 24.3 and 30 need a set of related types and functions to complete the definition of their semantics. These types and functions are provided as a set of member *typedef-names* and functions in the template parameter `traits` used by each such template. This subclause defines the semantics of these members.
- <sup>3</sup> To specialize those templates to generate a string or iostream class to handle a particular character container type `CharT`, that and its related character traits class `Traits` are passed as a pair of parameters to the string or iostream template as parameters `charT` and `traits`. `Traits::char_type` shall be the same as `CharT`.
- <sup>4</sup> This subclause specifies a class template, `char_traits<CharT>`, and four explicit specializations of it, `char_traits<char>`, `char_traits<char16_t>`, `char_traits<char32_t>`, and `char_traits<wchar_t>`, all of which appear in the header `<string>` and satisfy the requirements below.

#### 24.2.1 Character traits requirements

[char.traits.require]

- <sup>1</sup> In Table 54, `X` denotes a Traits class defining types and functions for the character container type `CharT`; `c` and `d` denote values of type `CharT`; `p` and `q` denote values of type `const CharT*`; `s` denotes a value of type `CharT*`; `n`, `i` and `j` denote values of type `size_t`; `e` and `f` denote values of type `X::int_type`; `pos` denotes a value of type `X::pos_type`; `state` denotes a value of type `X::state_type`; and `r` denotes an lvalue of type `CharT`. Operations on Traits shall not throw exceptions.

Table 54 — Character traits requirements

| Expression                      | Return type                      | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                 | Complexity   |
|---------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <code>X::char_type</code>       | <code>charT</code>               | (described in 24.2.2)                                                                                                                                                                                                                                                                                                                                                                 | compile-time |
| <code>X::int_type</code>        |                                  | (described in 24.2.2)                                                                                                                                                                                                                                                                                                                                                                 | compile-time |
| <code>X::off_type</code>        |                                  | (described in 24.2.2)                                                                                                                                                                                                                                                                                                                                                                 | compile-time |
| <code>X::pos_type</code>        |                                  | (described in 24.2.2)                                                                                                                                                                                                                                                                                                                                                                 | compile-time |
| <code>X::state_type</code>      |                                  | (described in 24.2.2)                                                                                                                                                                                                                                                                                                                                                                 | compile-time |
| <code>X::eq(c,d)</code>         | <code>bool</code>                | <i>Returns:</i> whether <code>c</code> is to be treated as equal to <code>d</code> .                                                                                                                                                                                                                                                                                                  | constant     |
| <code>X::lt(c,d)</code>         | <code>bool</code>                | <i>Returns:</i> whether <code>c</code> is to be treated as less than <code>d</code> .                                                                                                                                                                                                                                                                                                 | constant     |
| <code>X::compare(p,q,n)</code>  | <code>int</code>                 | <i>Returns:</i> 0 if for each <code>i</code> in <code>[0,n)</code> , <code>X::eq(p[i],q[i])</code> is <code>true</code> ; else, a negative value if, for some <code>j</code> in <code>[0,n)</code> , <code>X::lt(p[j],q[j])</code> is <code>true</code> and for each <code>i</code> in <code>[0,j)</code> <code>X::eq(p[i],q[i])</code> is <code>true</code> ; else a positive value. | linear       |
| <code>X::length(p)</code>       | <code>size_t</code>              | <i>Returns:</i> the smallest <code>i</code> such that <code>X::eq(p[i],charT())</code> is <code>true</code> .                                                                                                                                                                                                                                                                         | linear       |
| <code>X::find(p,n,c)</code>     | <code>const X::char_type*</code> | <i>Returns:</i> the smallest <code>q</code> in <code>[p,p+n)</code> such that <code>X::eq(*q,c)</code> is <code>true</code> , zero otherwise.                                                                                                                                                                                                                                         | linear       |
| <code>X::move(s,p,n)</code>     | <code>X::char_type*</code>       | for each <code>i</code> in <code>[0,n)</code> , performs <code>X::assign(s[i],p[i])</code> . Copies correctly even where the ranges <code>[p,p+n)</code> and <code>[s,s+n)</code> overlap.<br><i>Returns:</i> <code>s</code> .                                                                                                                                                        | linear       |
| <code>X::copy(s,p,n)</code>     | <code>X::char_type*</code>       | <i>Requires:</i> <code>p</code> not in <code>[s,s+n)</code> .<br><i>Returns:</i> <code>s</code> .<br>for each <code>i</code> in <code>[0,n)</code> , performs <code>X::assign(s[i],p[i])</code> .                                                                                                                                                                                     | linear       |
| <code>X::assign(r,d)</code>     | (not used)                       | assigns <code>r=d</code> .                                                                                                                                                                                                                                                                                                                                                            | constant     |
| <code>X::assign(s,n,c)</code>   | <code>X::char_type*</code>       | for each <code>i</code> in <code>[0,n)</code> , performs <code>X::assign(s[i],c)</code> .<br><i>Returns:</i> <code>s</code> .                                                                                                                                                                                                                                                         | linear       |
| <code>X::not_eof(e)</code>      | <code>int_type</code>            | <i>Returns:</i> <code>e</code> if <code>X::eq_int_type(e,X::eof())</code> is <code>false</code> , otherwise a value <code>f</code> such that <code>X::eq_int_type(f,X::eof())</code> is <code>false</code> .                                                                                                                                                                          | constant     |
| <code>X::to_char_type(e)</code> | <code>X::char_type</code>        | <i>Returns:</i> if for some <code>c</code> , <code>X::eq_int_type(e,X::to_int_type(c))</code> is <code>true</code> , <code>c</code> ; else some unspecified value.                                                                                                                                                                                                                    | constant     |

Table 54 — Character traits requirements (continued)

| Expression                       | Return type              | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                 | Complexity |
|----------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>X::to_int_type(c)</code>   | <code>X::int_type</code> | <i>Returns:</i> some value <code>e</code> , constrained by the definitions of <code>to_char_type</code> and <code>eq_int_type</code> .                                                                                                                                                                                                                                                                                                                                | constant   |
| <code>X::eq_int_type(e,f)</code> | <code>bool</code>        | <i>Returns:</i> for all <code>c</code> and <code>d</code> , <code>X::eq(c,d)</code> is equal to <code>X::eq_int_type(X::to_int_type(c), X::to_int_type(d))</code> ; otherwise, yields <code>true</code> if <code>e</code> and <code>f</code> are both copies of <code>X::eof()</code> ; otherwise, yields <code>false</code> if one of <code>e</code> and <code>f</code> is a copy of <code>X::eof()</code> and the other is not; otherwise the value is unspecified. | constant   |
| <code>X::eof()</code>            | <code>X::int_type</code> | <i>Returns:</i> a value <code>e</code> such that <code>X::eq_int_type(e,X::to_int_type(c))</code> is false for all values <code>c</code> .                                                                                                                                                                                                                                                                                                                            | constant   |

<sup>2</sup> The class template

```
template<class charT> struct char_traits;
```

shall be provided in the header `<string>` as a basis for explicit specializations.

### 24.2.2 Traits typedefs

[char.traits.typedefs]

```
using char_type = CHAR_T;
```

<sup>1</sup> The type `char_type` is used to refer to the character container type in the implementation of the library classes defined in 24.3 and Clause 30.

```
using int_type = INT_T;
```

<sup>2</sup> *Requires:* For a certain character container type `char_type`, a related container type `INT_T` shall be a type or class which can represent all of the valid characters converted from the corresponding `char_type` values, as well as an end-of-file value, `eof()`. The type `int_type` represents a character container type which can hold end-of-file to be used as a return type of the `istream` class member functions.<sup>224</sup>

```
using off_type = implementation-defined;
```

```
using pos_type = implementation-defined;
```

<sup>3</sup> *Requires:* Requirements for `off_type` and `pos_type` are described in 30.2.2 and 30.3.

```
using state_type = STATE_T;
```

<sup>4</sup> *Requires:* `state_type` shall meet the requirements of `CopyAssignable` (Table 26), `CopyConstructible` (Table 24), and `DefaultConstructible` (Table 22) types.

### 24.2.3 char\_traits specializations

[char.traits.specializations]

<sup>224</sup> If `eof()` can be held in `char_type` then some `istream`s operations may give surprising results.

```

namespace std {
 template<> struct char_traits<char>;
 template<> struct char_traits<char16_t>;
 template<> struct char_traits<char32_t>;
 template<> struct char_traits<wchar_t>;
}

```

- <sup>1</sup> The header <string> shall define four specializations of the class template char\_traits: char\_traits<char>, char\_traits<char16\_t>, char\_traits<char32\_t>, and char\_traits<wchar\_t>.
- <sup>2</sup> The requirements for the members of these specializations are given in Clause 24.2.1.

#### 24.2.3.1 struct char\_traits<char> [char.traits.specializations.char]

```

namespace std {
 template<> struct char_traits<char> {
 using char_type = char;
 using int_type = int;
 using off_type = streamoff;
 using pos_type = streampos;
 using state_type = mbstate_t;

 static constexpr void assign(char_type& c1, const char_type& c2) noexcept;
 static constexpr bool eq(char_type c1, char_type c2) noexcept;
 static constexpr bool lt(char_type c1, char_type c2) noexcept;

 static constexpr int compare(const char_type* s1, const char_type* s2, size_t n);
 static constexpr size_t length(const char_type* s);
 static constexpr const char_type* find(const char_type* s, size_t n,
 const char_type& a);
 static char_type* move(char_type* s1, const char_type* s2, size_t n);
 static char_type* copy(char_type* s1, const char_type* s2, size_t n);
 static char_type* assign(char_type* s, size_t n, char_type a);

 static constexpr int_type not_eof(int_type c) noexcept;
 static constexpr char_type to_char_type(int_type c) noexcept;
 static constexpr int_type to_int_type(char_type c) noexcept;
 static constexpr bool eq_int_type(int_type c1, int_type c2) noexcept;
 static constexpr int_type eof() noexcept;
 };
}

```

- <sup>1</sup> The defined types for int\_type, pos\_type, off\_type, and state\_type shall be int, streampos, streamoff, and mbstate\_t respectively.
- <sup>2</sup> The type streampos shall be an implementation-defined type that satisfies the requirements for pos\_type in 30.2.2 and 30.3.
- <sup>3</sup> The type streamoff shall be an implementation-defined type that satisfies the requirements for off\_type in 30.2.2 and 30.3.
- <sup>4</sup> The type mbstate\_t is defined in <wchar> and can represent any of the conversion states that can occur in an implementation-defined set of supported multibyte character encoding rules.
- <sup>5</sup> The two-argument member assign shall be defined identically to the built-in operator =. The two-argument members eq and lt shall be defined identically to the built-in operators == and < for type unsigned char.
- <sup>6</sup> The member eof() shall return EOF.

#### 24.2.3.2 struct char\_traits<char16\_t> [char.traits.specializations.char16\_t]



```

namespace std {
 template<> struct char_traits<char16_t> {
 using char_type = char16_t;
 using int_type = uint_least16_t;
 using off_type = streamoff;
 using pos_type = u16streampos;
 using state_type = mbstate_t;

 static constexpr void assign(char_type& c1, const char_type& c2) noexcept;
 static constexpr bool eq(char_type c1, char_type c2) noexcept;
 static constexpr bool lt(char_type c1, char_type c2) noexcept;

 static constexpr int compare(const char_type* s1, const char_type* s2, size_t n);
 static constexpr size_t length(const char_type* s);
 static constexpr const char_type* find(const char_type* s, size_t n,
 const char_type& a);
 static char_type* move(char_type* s1, const char_type* s2, size_t n);
 static char_type* copy(char_type* s1, const char_type* s2, size_t n);
 static char_type* assign(char_type* s, size_t n, char_type a);

 static constexpr int_type not_eof(int_type c) noexcept;
 static constexpr char_type to_char_type(int_type c) noexcept;
 static constexpr int_type to_int_type(char_type c) noexcept;
 static constexpr bool eq_int_type(int_type c1, int_type c2) noexcept;
 static constexpr int_type eof() noexcept;
 };
}

```

- <sup>1</sup> The type `u16streampos` shall be an implementation-defined type that satisfies the requirements for `pos_type` in 30.2.2 and 30.3.
- <sup>2</sup> The two-argument members `assign`, `eq`, and `lt` shall be defined identically to the built-in operators `=`, `==`, and `<` respectively.
- <sup>3</sup> The member `eof()` shall return an implementation-defined constant that cannot appear as a valid UTF-16 code unit.

#### 24.2.3.3 struct `char_traits<char32_t>`

[`char.traits.specializations.char32_t`]

```

namespace std {
 template<> struct char_traits<char32_t> {
 using char_type = char32_t;
 using int_type = uint_least32_t;
 using off_type = streamoff;
 using pos_type = u32streampos;
 using state_type = mbstate_t;

 static constexpr void assign(char_type& c1, const char_type& c2) noexcept;
 static constexpr bool eq(char_type c1, char_type c2) noexcept;
 static constexpr bool lt(char_type c1, char_type c2) noexcept;

 static constexpr int compare(const char_type* s1, const char_type* s2, size_t n);
 static constexpr size_t length(const char_type* s);
 static constexpr const char_type* find(const char_type* s, size_t n,
 const char_type& a);
 static char_type* move(char_type* s1, const char_type* s2, size_t n);
 static char_type* copy(char_type* s1, const char_type* s2, size_t n);
 static char_type* assign(char_type* s, size_t n, char_type a);
 };
}

```

```

 static constexpr int_type not_eof(int_type c) noexcept;
 static constexpr char_type to_char_type(int_type c) noexcept;
 static constexpr int_type to_int_type(char_type c) noexcept;
 static constexpr bool eq_int_type(int_type c1, int_type c2) noexcept;
 static constexpr int_type eof() noexcept;
};
}

```

- <sup>1</sup> The type `u32streampos` shall be an implementation-defined type that satisfies the requirements for `pos_type` in 30.2.2 and 30.3.
- <sup>2</sup> The two-argument members `assign`, `eq`, and `lt` shall be defined identically to the built-in operators `=`, `==`, and `<` respectively.
- <sup>3</sup> The member `eof()` shall return an implementation-defined constant that cannot appear as a Unicode code point.

#### 24.2.3.4 struct `char_traits<wchar_t>`

[`char.traits.specializations.wchar.t`]

```

namespace std {
 template<> struct char_traits<wchar_t> {
 using char_type = wchar_t;
 using int_type = wint_t;
 using off_type = streamoff;
 using pos_type = wstreampos;
 using state_type = mbstate_t;

 static constexpr void assign(char_type& c1, const char_type& c2) noexcept;
 static constexpr bool eq(char_type c1, char_type c2) noexcept;
 static constexpr bool lt(char_type c1, char_type c2) noexcept;

 static constexpr int compare(const char_type* s1, const char_type* s2, size_t n);
 static constexpr size_t length(const char_type* s);
 static constexpr const char_type* find(const char_type* s, size_t n,
 const char_type& a);
 static char_type* move(char_type* s1, const char_type* s2, size_t n);
 static char_type* copy(char_type* s1, const char_type* s2, size_t n);
 static char_type* assign(char_type* s, size_t n, char_type a);

 static constexpr int_type not_eof(int_type c) noexcept;
 static constexpr char_type to_char_type(int_type c) noexcept;
 static constexpr int_type to_int_type(char_type c) noexcept;
 static constexpr bool eq_int_type(int_type c1, int_type c2) noexcept;
 static constexpr int_type eof() noexcept;
 };
}

```

- <sup>1</sup> The defined types for `int_type`, `pos_type`, and `state_type` shall be `wint_t`, `wstreampos`, and `mbstate_t` respectively.
- <sup>2</sup> The type `wstreampos` shall be an implementation-defined type that satisfies the requirements for `pos_type` in 30.2.2 and 30.3.
- <sup>3</sup> The type `mbstate_t` is defined in `<cwchar>` and can represent any of the conversion states that can occur in an implementation-defined set of supported multibyte character encoding rules.
- <sup>4</sup> The two-argument members `assign`, `eq`, and `lt` shall be defined identically to the built-in operators `=`, `==`, and `<` respectively.

- <sup>5</sup> The member `eof()` shall return `WEOF`.

## 24.3 String classes

[string.classes]

- <sup>1</sup> The header `<string>` defines the `basic_string` class template for manipulating varying-length sequences of char-like objects and four *typedef-names*, `string`, `u16string`, `u32string`, and `wstring`, that name the specializations `basic_string<char>`, `basic_string<char16_t>`, `basic_string<char32_t>`, and `basic_string<wchar_t>`, respectively.

### 24.3.1 Header `<string>` synopsis

[string.syn]

```
#include <initializer_list>

namespace std {
 // 24.2, character traits
 template<class charT> struct char_traits;
 template<> struct char_traits<char>;
 template<> struct char_traits<char16_t>;
 template<> struct char_traits<char32_t>;
 template<> struct char_traits<wchar_t>;

 // 24.3.2, basic_string
 template<class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_string;

 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(basic_string<charT, traits, Allocator>&& lhs,
 const basic_string<charT, traits, Allocator>& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs,
 basic_string<charT, traits, Allocator>&& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(basic_string<charT, traits, Allocator>&& lhs,
 basic_string<charT, traits, Allocator>&& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const charT* lhs,
 basic_string<charT, traits, Allocator>&& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(charT lhs, const basic_string<charT, traits, Allocator>& rhs);
 template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(charT lhs, basic_string<charT, traits, Allocator>&& rhs);
 template<class charT, class traits, class Allocator>
```

```

 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(basic_string<charT, traits, Allocator>&& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs, charT rhs);
template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(basic_string<charT, traits, Allocator>&& lhs, charT rhs);

template<class charT, class traits, class Allocator>
 bool operator==(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
template<class charT, class traits, class Allocator>
 bool operator==(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
template<class charT, class traits, class Allocator>
 bool operator==(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 bool operator!=(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
template<class charT, class traits, class Allocator>
 bool operator!=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
template<class charT, class traits, class Allocator>
 bool operator!=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);

template<class charT, class traits, class Allocator>
 bool operator< (const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
template<class charT, class traits, class Allocator>
 bool operator< (const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 bool operator< (const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
template<class charT, class traits, class Allocator>
 bool operator> (const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
template<class charT, class traits, class Allocator>
 bool operator> (const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
template<class charT, class traits, class Allocator>
 bool operator> (const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);

template<class charT, class traits, class Allocator>
 bool operator<= (const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;

```

```

template<class charT, class traits, class Allocator>
 bool operator<=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 bool operator<=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
template<class charT, class traits, class Allocator>
 bool operator>=(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
template<class charT, class traits, class Allocator>
 bool operator>=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
template<class charT, class traits, class Allocator>
 bool operator>=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);

// 24.3.3.8, swap
template<class charT, class traits, class Allocator>
 void swap(basic_string<charT, traits, Allocator>& lhs,
 basic_string<charT, traits, Allocator>& rhs)
 noexcept(noexcept(lhs.swap(rhs)));

// 24.3.3.9, inserters and extractors
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 operator>>(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str);
template<class charT, class traits, class Allocator>
 basic_ostream<charT, traits>&
 operator<<(basic_ostream<charT, traits>& os,
 const basic_string<charT, traits, Allocator>& str);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str,
 charT delim);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>&& is,
 basic_string<charT, traits, Allocator>& str,
 charT delim);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>&& is,
 basic_string<charT, traits, Allocator>& str);

// basic_string typedef names
using string = basic_string<char>;
using u16string = basic_string<char16_t>;
using u32string = basic_string<char32_t>;
using wstring = basic_string<wchar_t>;

```

```

// 24.3.4, numeric conversions
int stoi(const string& str, size_t* idx = 0, int base = 10);
long stol(const string& str, size_t* idx = 0, int base = 10);
unsigned long stoul(const string& str, size_t* idx = 0, int base = 10);
long long stoll(const string& str, size_t* idx = 0, int base = 10);
unsigned long long stoull(const string& str, size_t* idx = 0, int base = 10);
float stof(const string& str, size_t* idx = 0);
double stod(const string& str, size_t* idx = 0);
long double stold(const string& str, size_t* idx = 0);
string to_string(int val);
string to_string(unsigned val);
string to_string(long val);
string to_string(unsigned long val);
string to_string(long long val);
string to_string(unsigned long long val);
string to_string(float val);
string to_string(double val);
string to_string(long double val);

int stoi(const wstring& str, size_t* idx = 0, int base = 10);
long stol(const wstring& str, size_t* idx = 0, int base = 10);
unsigned long stoul(const wstring& str, size_t* idx = 0, int base = 10);
long long stoll(const wstring& str, size_t* idx = 0, int base = 10);
unsigned long long stoull(const wstring& str, size_t* idx = 0, int base = 10);
float stof(const wstring& str, size_t* idx = 0);
double stod(const wstring& str, size_t* idx = 0);
long double stold(const wstring& str, size_t* idx = 0);
wstring to_wstring(int val);
wstring to_wstring(unsigned val);
wstring to_wstring(long val);
wstring to_wstring(unsigned long val);
wstring to_wstring(long long val);
wstring to_wstring(unsigned long long val);
wstring to_wstring(float val);
wstring to_wstring(double val);
wstring to_wstring(long double val);

// 24.3.5, hash support
template<class T> struct hash;
template<> struct hash<string>;
template<> struct hash<u16string>;
template<> struct hash<u32string>;
template<> struct hash<wstring>;

namespace pmr {
 template <class charT, class traits = char_traits<charT>>
 using basic_string =
 std::basic_string<charT, traits, polymorphic_allocator<charT>>;

 using string = basic_string<char>;
 using u16string = basic_string<char16_t>;
 using u32string = basic_string<char32_t>;
 using wstring = basic_string<wchar_t>;
}

```

```

inline namespace literals {
inline namespace string_literals {
 // 24.3.6, suffix for basic_string literals
 string operator""s(const char* str, size_t len);
 u16string operator""s(const char16_t* str, size_t len);
 u32string operator""s(const char32_t* str, size_t len);
 wstring operator""s(const wchar_t* str, size_t len);
}
}
}

```

### 24.3.2 Class template `basic_string` [basic.string]

- <sup>1</sup> The class template `basic_string` describes objects that can store a sequence consisting of a varying number of arbitrary char-like objects with the first element of the sequence at position zero. Such a sequence is also called a “string” if the type of the char-like objects that it holds is clear from context. In the rest of this Clause, the type of the char-like objects held in a `basic_string` object is designated by `charT`.
- <sup>2</sup> The member functions of `basic_string` use an object of the `Allocator` class passed as a template parameter to allocate and free storage for the contained char-like objects.<sup>225</sup>
- <sup>3</sup> A `basic_string` is a contiguous container (26.2.1).
- <sup>4</sup> In all cases, `size() <= capacity()`.
- <sup>5</sup> The functions described in this Clause can report two kinds of errors, each associated with an exception type:
  - (5.1) — a *length* error is associated with exceptions of type `length_error` (22.2.5);
  - (5.2) — an *out-of-range* error is associated with exceptions of type `out_of_range` (22.2.6).

```

namespace std {
 template<class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_string {
 public:
 // types:
 using traits_type = traits;
 using value_type = charT;
 using allocator_type = Allocator;
 using size_type = typename allocator_traits<Allocator>::size_type;
 using difference_type = typename allocator_traits<Allocator>::difference_type;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;

 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;
 static const size_type npos = -1;

 // 24.3.2.2, construct/copy/destroy
 basic_string() noexcept(noexcept(Allocator())) : basic_string(Allocator()) { }
 explicit basic_string(const Allocator& a) noexcept;
 basic_string(const basic_string& str);
 };
}

```

<sup>225</sup>) `Allocator::value_type` must name the same type as `charT` (24.3.2.1).

```

basic_string(basic_string&& str) noexcept;
basic_string(const basic_string& str, size_type pos,
 const Allocator& a = Allocator());
basic_string(const basic_string& str, size_type pos, size_type n,
 const Allocator& a = Allocator());
template<class T>
 basic_string(const T& t, size_type pos, size_type n,
 const Allocator& a = Allocator());
explicit basic_string(basic_string_view<charT, traits> sv,
 const Allocator& a = Allocator());
basic_string(const charT* s,
 size_type n, const Allocator& a = Allocator());
basic_string(const charT* s, const Allocator& a = Allocator());
basic_string(size_type n, charT c, const Allocator& a = Allocator());
template<class InputIterator>
 basic_string(InputIterator begin, InputIterator end,
 const Allocator& a = Allocator());
basic_string(initializer_list<charT>, const Allocator& = Allocator());
basic_string(const basic_string&, const Allocator&);
basic_string(basic_string&&, const Allocator&);

~basic_string();
basic_string& operator=(const basic_string& str);
basic_string& operator=(basic_string&& str)
 noexcept(allocator_traits<Allocator>::propagate_on_container_move_assignment::value ||
 allocator_traits<Allocator>::is_always_equal::value);
basic_string& operator=(basic_string_view<charT, traits> sv);
basic_string& operator=(const charT* s);
basic_string& operator=(charT c);
basic_string& operator=(initializer_list<charT>);

// 24.3.2.3, iterators
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;

reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// 24.3.2.4, capacity
size_type size() const noexcept;
size_type length() const noexcept;
size_type max_size() const noexcept;
void resize(size_type n, charT c);
void resize(size_type n);
size_type capacity() const noexcept;
void reserve(size_type res_arg = 0);

```



```

void shrink_to_fit();
void clear() noexcept;
bool empty() const noexcept;

// 24.3.2.5, element access
const_reference operator[](size_type pos) const;
reference operator[](size_type pos);
const_reference at(size_type n) const;
reference at(size_type n);

const charT& front() const;
charT& front();
const charT& back() const;
charT& back();

// 24.3.2.6, modifiers
basic_string& operator+=(const basic_string& str);
basic_string& operator+=(basic_string_view<charT, traits> sv);
basic_string& operator+=(const charT* s);
basic_string& operator+=(charT c);
basic_string& operator+=(initializer_list<charT>);
basic_string& append(const basic_string& str);
basic_string& append(const basic_string& str, size_type pos,
 size_type n = npos);
basic_string& append(basic_string_view<charT, traits> sv);
template<class T>
 basic_string& append(const T& t, size_type pos, size_type n = npos);
basic_string& append(const charT* s, size_type n);
basic_string& append(const charT* s);
basic_string& append(size_type n, charT c);
template<class InputIterator>
 basic_string& append(InputIterator first, InputIterator last);
basic_string& append(initializer_list<charT>);
void push_back(charT c);

basic_string& assign(const basic_string& str);
basic_string& assign(basic_string&& str)
 noexcept(allocator_traits<Allocator>::propagate_on_container_move_assignment::value ||
 allocator_traits<Allocator>::is_always_equal::value);
basic_string& assign(const basic_string& str, size_type pos,
 size_type n = npos);
basic_string& assign(basic_string_view<charT, traits> sv);
template<class T>
 basic_string& assign(const T& t, size_type pos, size_type n = npos);
basic_string& assign(const charT* s, size_type n);
basic_string& assign(const charT* s);
basic_string& assign(size_type n, charT c);
template<class InputIterator>
 basic_string& assign(InputIterator first, InputIterator last);
basic_string& assign(initializer_list<charT>);

basic_string& insert(size_type pos, const basic_string& str);
basic_string& insert(size_type pos1, const basic_string& str,
 size_type pos2, size_type n = npos);
basic_string& insert(size_type pos, basic_string_view<charT, traits> sv);

```

```

template<class T>
 basic_string& insert(size_type pos1, const T& t,
 size_type pos2, size_type n = npos);
basic_string& insert(size_type pos, const charT* s, size_type n);
basic_string& insert(size_type pos, const charT* s);
basic_string& insert(size_type pos, size_type n, charT c);
iterator insert(const_iterator p, charT c);
iterator insert(const_iterator p, size_type n, charT c);
template<class InputIterator>
 iterator insert(const_iterator p, InputIterator first, InputIterator last);
iterator insert(const_iterator p, initializer_list<charT>);

basic_string& erase(size_type pos = 0, size_type n = npos);
iterator erase(const_iterator p);
iterator erase(const_iterator first, const_iterator last);

void pop_back();

basic_string& replace(size_type pos1, size_type n1,
 const basic_string& str);
basic_string& replace(size_type pos1, size_type n1,
 const basic_string& str,
 size_type pos2, size_type n2 = npos);
basic_string& replace(size_type pos1, size_type n1,
 basic_string_view<charT, traits> sv);
template<class T>
 basic_string& replace(size_type pos1, size_type n1, const T& t,
 size_type pos2, size_type n2 = npos);
basic_string& replace(size_type pos, size_type n1, const charT* s,
 size_type n2);
basic_string& replace(size_type pos, size_type n1, const charT* s);
basic_string& replace(size_type pos, size_type n1, size_type n2,
 charT c);

basic_string& replace(const_iterator i1, const_iterator i2,
 const basic_string& str);
basic_string& replace(const_iterator i1, const_iterator i2,
 basic_string_view<charT, traits> sv);
basic_string& replace(const_iterator i1, const_iterator i2, const charT* s,
 size_type n);
basic_string& replace(const_iterator i1, const_iterator i2, const charT* s);
basic_string& replace(const_iterator i1, const_iterator i2,
 size_type n, charT c);
template<class InputIterator>
 basic_string& replace(const_iterator i1, const_iterator i2,
 InputIterator j1, InputIterator j2);
basic_string& replace(const_iterator, const_iterator, initializer_list<charT>);

size_type copy(charT* s, size_type n, size_type pos = 0) const;
void swap(basic_string& str)
 noexcept(allocator_traits<Allocator>::propagate_on_container_swap::value ||
 allocator_traits<Allocator>::is_always_equal::value);

// 24.3.2.7, string operations
const charT* c_str() const noexcept;

```

```

const charT* data() const noexcept;
charT* data() noexcept;
operator basic_string_view<charT, traits>() const noexcept;
allocator_type get_allocator() const noexcept;

size_type find (basic_string_view<charT, traits> sv,
 size_type pos = 0) const noexcept;
size_type find (const basic_string& str, size_type pos = 0) const noexcept;
size_type find (const charT* s, size_type pos, size_type n) const;
size_type find (const charT* s, size_type pos = 0) const;
size_type find (charT c, size_type pos = 0) const;
size_type rfind(basic_string_view<charT, traits> sv,
 size_type pos = npos) const noexcept;
size_type rfind(const basic_string& str, size_type pos = npos) const noexcept;
size_type rfind(const charT* s, size_type pos, size_type n) const;
size_type rfind(const charT* s, size_type pos = npos) const;
size_type rfind(charT c, size_type pos = npos) const;

size_type find_first_of(basic_string_view<charT, traits> sv,
 size_type pos = 0) const noexcept;
size_type find_first_of(const basic_string& str,
 size_type pos = 0) const noexcept;
size_type find_first_of(const charT* s,
 size_type pos, size_type n) const;
size_type find_first_of(const charT* s, size_type pos = 0) const;
size_type find_first_of(charT c, size_type pos = 0) const;
size_type find_last_of (basic_string_view<charT, traits> sv,
 size_type pos = npos) const noexcept;
size_type find_last_of (const basic_string& str,
 size_type pos = npos) const noexcept;
size_type find_last_of (const charT* s,
 size_type pos, size_type n) const;
size_type find_last_of (const charT* s, size_type pos = npos) const;
size_type find_last_of (charT c, size_type pos = npos) const;

size_type find_first_not_of(basic_string_view<charT, traits> sv,
 size_type pos = 0) const noexcept;
size_type find_first_not_of(const basic_string& str,
 size_type pos = 0) const noexcept;
size_type find_first_not_of(const charT* s, size_type pos,
 size_type n) const;
size_type find_first_not_of(const charT* s, size_type pos = 0) const;
size_type find_first_not_of(charT c, size_type pos = 0) const;
size_type find_last_not_of (basic_string_view<charT, traits> sv,
 size_type pos = npos) const noexcept;
size_type find_last_not_of (const basic_string& str,
 size_type pos = npos) const noexcept;
size_type find_last_not_of (const charT* s, size_type pos,
 size_type n) const;
size_type find_last_not_of (const charT* s,
 size_type pos = npos) const;
size_type find_last_not_of (charT c, size_type pos = npos) const;

basic_string substr(size_type pos = 0, size_type n = npos) const;
int compare(basic_string_view<charT, traits> sv) const noexcept;

```

```

 int compare(size_type pos1, size_type n1,
 basic_string_view<charT, traits> sv) const;
 template<class T>
 int compare(size_type pos1, size_type n1, const T& t,
 size_type pos2, size_type n2 = npos) const;
 int compare(const basic_string& str) const noexcept;
 int compare(size_type pos1, size_type n1,
 const basic_string& str) const;
 int compare(size_type pos1, size_type n1,
 const basic_string& str,
 size_type pos2, size_type n2 = npos) const;
 int compare(const charT* s) const;
 int compare(size_type pos1, size_type n1,
 const charT* s) const;
 int compare(size_type pos1, size_type n1,
 const charT* s, size_type n2) const;
};

template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
 basic_string(InputIterator, InputIterator, Allocator = Allocator())
 -> basic_string<typename iterator_traits<InputIterator>::value_type,
 char_traits<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;
}

```

#### 24.3.2.1 `basic_string` general requirements [string.require]

- <sup>1</sup> If any operation would cause `size()` to exceed `max_size()`, that operation shall throw an exception object of type `length_error`.
- <sup>2</sup> If any member function or operator of `basic_string` throws an exception, that function or operator shall have no other effect.
- <sup>3</sup> In every specialization `basic_string<charT, traits, Allocator>`, the type `allocator_traits<Allocator>::value_type` shall name the same type as `charT`. Every object of type `basic_string<charT, traits, Allocator>` shall use an object of type `Allocator` to allocate and free storage for the contained `charT` objects as needed. The `Allocator` object used shall be obtained as described in 26.2.1. In every specialization `basic_string<charT, traits, Allocator>`, the type `traits` shall satisfy the character traits requirements (24.2), and the type `traits::char_type` shall name the same type as `charT`.
- <sup>4</sup> References, pointers, and iterators referring to the elements of a `basic_string` sequence may be invalidated by the following uses of that `basic_string` object:
  - (4.1) — as an argument to any standard library function taking a reference to non-const `basic_string` as an argument.<sup>226</sup>
  - (4.2) — Calling non-const member functions, except `operator[]`, `at`, `data`, `front`, `back`, `begin`, `rbegin`, `end`, and `rend`.

#### 24.3.2.2 `basic_string` constructors and assignment operators [string.cons]

`explicit basic_string(const Allocator& a) noexcept;`

- <sup>1</sup> *Effects:* Constructs an object of class `basic_string`. The postconditions of this function are indicated in Table 55.

<sup>226</sup> For example, as an argument to non-member functions `swap()` (24.3.3.8), `operator>>()` (24.3.3.9), and `getline()` (24.3.3.9), or as an argument to `basic_string::swap()`.

Table 55 — `basic_string(const Allocator&)` effects

| Element                 | Value                                                          |
|-------------------------|----------------------------------------------------------------|
| <code>data()</code>     | a non-null pointer that is copyable and can have 0 added to it |
| <code>size()</code>     | 0                                                              |
| <code>capacity()</code> | an unspecified value                                           |

```
basic_string(const basic_string& str);
basic_string(basic_string&& str) noexcept;
```

- <sup>2</sup> *Effects:* Constructs an object of class `basic_string` as indicated in Table 56. In the second form, `str` is left in a valid state with an unspecified value.

Table 56 — `basic_string(const basic_string&)` effects

| Element                 | Value                                                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated copy of the array whose first element is pointed at by <code>str.data()</code> |
| <code>size()</code>     | <code>str.size()</code>                                                                                                    |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                           |

```
basic_string(const basic_string& str, size_type pos,
 const Allocator& a = Allocator());
```

- <sup>3</sup> *Throws:* `out_of_range` if `pos > str.size()`.
- <sup>4</sup> *Effects:* Constructs an object of class `basic_string` and determines the effective length `rlen` of the initial string value as `str.size() - pos`, as indicated in Table 57.

```
basic_string(const basic_string& str, size_type pos, size_type n,
 const Allocator& a = Allocator());
```

- <sup>5</sup> *Throws:* `out_of_range` if `pos > str.size()`.
- <sup>6</sup> *Effects:* Constructs an object of class `basic_string` and determines the effective length `rlen` of the initial string value as the smaller of `n` and `str.size() - pos`, as indicated in Table 57.

Table 57 — `basic_string(const basic_string&, size_type, const Allocator&)` and `basic_string(const basic_string&, size_type, size_type, const Allocator&)` effects

| Element                 | Value                                                                                                                                                                          |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated copy of <code>rlen</code> consecutive elements of the string controlled by <code>str</code> beginning at position <code>pos</code> |
| <code>size()</code>     | <code>rlen</code>                                                                                                                                                              |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                                                                               |

```
template<class T>
basic_string(const T& t, size_type pos, size_type n,
 const Allocator& a = Allocator());
```

7 *Effects:* Creates a variable, `sv`, as if by `basic_string_view<charT, traits> sv = t;` and then behaves the same as:

```
 basic_string(sv.substr(pos, n), a);
```

8 *Remarks:* This constructor shall not participate in overload resolution unless `is_convertible_v<const T&, basic_string_view<charT, traits>>` is true.

```
explicit basic_string(basic_string_view<charT, traits> sv,
 const Allocator& a = Allocator());
```

9 *Effects:* Same as `basic_string(sv.data(), sv.size(), a)`.

```
basic_string(const charT* s, size_type n,
 const Allocator& a = Allocator());
```

10 *Requires:* `s` points to an array of at least `n` elements of `charT`.

11 *Effects:* Constructs an object of class `basic_string` and determines its initial string value from the array of `charT` of length `n` whose first element is designated by `s`, as indicated in Table 58.

Table 58 — `basic_string(const charT*, size_type, const Allocator&)` effects

| Element                 | Value                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated copy of the array whose first element is pointed at by <code>s</code> |
| <code>size()</code>     | <code>n</code>                                                                                                    |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                  |

```
basic_string(const charT* s, const Allocator& a = Allocator());
```

12 *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

13 *Effects:* Constructs an object of class `basic_string` and determines its initial string value from the array of `charT` of length `traits::length(s)` whose first element is designated by `s`, as indicated in Table 59.

Table 59 — `basic_string(const charT*, const Allocator&)` effects

| Element                 | Value                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated copy of the array whose first element is pointed at by <code>s</code> |
| <code>size()</code>     | <code>traits::length(s)</code>                                                                                    |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                  |

```
basic_string(size_type n, charT c, const Allocator& a = Allocator());
```

14 *Requires:* `n < npos`.

15 *Effects:* Constructs an object of class `basic_string` and determines its initial string value by repeating the char-like object `c` for all `n` elements, as indicated in Table 60.

```
template<class InputIterator>
 basic_string(InputIterator begin, InputIterator end,
 const Allocator& a = Allocator());
```

16 *Effects:* If `InputIterator` is an integral type, equivalent to:

Table 60 — `basic_string(size_t, charT, const Allocator&)` effects

| Element                 | Value                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated array of <code>n</code> elements, each storing the initial value <code>c</code> |
| <code>size()</code>     | <code>n</code>                                                                                                              |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                            |

```
basic_string(static_cast<size_type>(begin), static_cast<value_type>(end), a);
```

Otherwise constructs a string from the values in the range `[begin, end)`, as indicated in the Sequence Requirements table (see 26.2.3).

```
basic_string(initializer_list<charT> il, const Allocator& a = Allocator());
```

17 *Effects:* Same as `basic_string(il.begin(), il.end(), a)`.

```
basic_string(const basic_string& str, const Allocator& alloc);
```

```
basic_string(basic_string&& str, const Allocator& alloc);
```

18 *Effects:* Constructs an object of class `basic_string` as indicated in Table 61. The stored allocator is constructed from `alloc`. In the second form, `str` is left in a valid state with an unspecified value.

Table 61 — `basic_string(const basic_string&, const Allocator&)` and `basic_string(basic_string&&, const Allocator&)` effects

| Element                      | Value                                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>          | points at the first element of an allocated copy of the array whose first element is pointed at by the original value of <code>str.data()</code> . |
| <code>size()</code>          | the original value of <code>str.size()</code>                                                                                                      |
| <code>capacity()</code>      | a value at least as large as <code>size()</code>                                                                                                   |
| <code>get_allocator()</code> | <code>alloc</code>                                                                                                                                 |

19 *Throws:* The second form throws nothing if `alloc == str.get_allocator()`.

```
template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
basic_string(InputIterator, InputIterator, Allocator = Allocator())
-> basic_string<typename iterator_traits<InputIterator>::value_type,
 char_traits<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;
```

20 *Remarks:* Shall not participate in overload resolution if `InputIterator` is a type that does not qualify as an input iterator, or if `Allocator` is a type that does not qualify as an allocator (26.2.1).

```
basic_string& operator=(const basic_string& str);
```

21 *Effects:* If `*this` and `str` are not the same object, modifies `*this` as shown in Table 62.

22 If `*this` and `str` are the same object, the member has no effect.

23 *Returns:* `*this`.

```
basic_string& operator=(basic_string&& str)
noexcept(allocator_traits<Allocator>::propagate_on_container_move_assignment::value ||
```

Table 62 — `operator=(const basic_string&)` effects

| Element                 | Value                                                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <code>data()</code>     | points at the first element of an allocated copy of the array whose first element is pointed at by <code>str.data()</code> |
| <code>size()</code>     | <code>str.size()</code>                                                                                                    |
| <code>capacity()</code> | a value at least as large as <code>size()</code>                                                                           |

`allocator_traits<Allocator>::is_always_equal::value);`

24 *Effects:* Move assigns as a sequence container (26.2), except that iterators, pointers and references may be invalidated.

25 *Returns:* `*this`.

`basic_string& operator=(basic_string_view<charT, traits> sv);`

26 *Effects:* Equivalent to: `return assign(sv);`

`basic_string& operator=(const charT* s);`

27 *Returns:* `*this = basic_string(s)`.

28 *Remarks:* Uses `traits::length()`.

`basic_string& operator=(charT c);`

29 *Returns:* `*this = basic_string(1, c)`.

`basic_string& operator=(initializer_list<charT> il);`

30 *Effects:* As if by: `*this = basic_string(il);`

31 *Returns:* `*this`.

### 24.3.2.3 `basic_string` iterator support

[string.iterators]

`iterator begin() noexcept;`  
`const_iterator begin() const noexcept;`  
`const_iterator cbegin() const noexcept;`

1 *Returns:* An iterator referring to the first character in the string.

`iterator end() noexcept;`  
`const_iterator end() const noexcept;`  
`const_iterator cend() const noexcept;`

2 *Returns:* An iterator which is the past-the-end value.

`reverse_iterator rbegin() noexcept;`  
`const_reverse_iterator rbegin() const noexcept;`  
`const_reverse_iterator crbegin() const noexcept;`

3 *Returns:* An iterator which is semantically equivalent to `reverse_iterator(end())`.

`reverse_iterator rend() noexcept;`  
`const_reverse_iterator rend() const noexcept;`  
`const_reverse_iterator crend() const noexcept;`

4 *Returns:* An iterator which is semantically equivalent to `reverse_iterator(begin())`.



**24.3.2.4 basic\_string capacity****[string.capacity]****size\_type size() const noexcept;**

1       *Returns:* A count of the number of char-like objects currently in the string.

2       *Complexity:* Constant time.

**size\_type length() const noexcept;**

3       *Returns:* **size()**.

**size\_type max\_size() const noexcept;**

4       *Returns:* The largest possible number of char-like objects that can be stored in a **basic\_string**.

5       *Complexity:* Constant time.

**void resize(size\_type n, charT c);**

6       *Throws:* **length\_error** if **n > max\_size()**.

7       *Effects:* Alters the length of the string designated by **\*this** as follows:

(7.1)       — If **n <= size()**, the function replaces the string designated by **\*this** with a string of length **n** whose elements are a copy of the initial elements of the original string designated by **\*this**.

(7.2)       — If **n > size()**, the function replaces the string designated by **\*this** with a string of length **n** whose first **size()** elements are a copy of the original string designated by **\*this**, and whose remaining elements are all initialized to **c**.

**void resize(size\_type n);**

8       *Effects:* As if by **resize(n, charT())**.

**size\_type capacity() const noexcept;**

9       *Returns:* The size of the allocated storage in the string.

**void reserve(size\_type res\_arg=0);**

10       The member function **reserve()** is a directive that informs a **basic\_string** object of a planned change in size, so that it can manage the storage allocation accordingly.

11       *Effects:* After **reserve()**, **capacity()** is greater or equal to the argument of **reserve**. [ *Note:* Calling **reserve()** with a **res\_arg** argument less than **capacity()** is in effect a non-binding shrink request. A call with **res\_arg <= size()** is in effect a non-binding shrink-to-fit request. — *end note* ]

12       *Throws:* **length\_error** if **res\_arg > max\_size()**.<sup>227</sup>

**void shrink\_to\_fit();**

13       *Effects:* **shrink\_to\_fit** is a non-binding request to reduce **capacity()** to **size()**. [ *Note:* The request is non-binding to allow latitude for implementation-specific optimizations. — *end note* ] It does not increase **capacity()**, but may reduce **capacity()** by causing reallocation.

14       *Complexity:* Linear in the size of the sequence.

15       *Remarks:* Reallocation invalidates all the references, pointers, and iterators referring to the elements in the sequence as well as the past-the-end iterator. If no reallocation happens, they remain valid.

**void clear() noexcept;**

16       *Effects:* Behaves as if the function calls:

227) **reserve()** uses **allocator\_traits<Allocator>::allocate()** which may throw an appropriate exception.

```
erase(begin(), end());
```

```
bool empty() const noexcept;
```

17 *Returns:* `size() == 0`.

### 24.3.2.5 basic\_string element access

[string.access]

```
const_reference operator[](size_type pos) const;
```

```
reference operator[](size_type pos);
```

1 *Requires:* `pos <= size()`.

2 *Returns:* `*(begin() + pos)` if `pos < size()`. Otherwise, returns a reference to an object of type `charT` with value `charT()`, where modifying the object to any value other than `charT()` leads to undefined behavior.

3 *Throws:* Nothing.

4 *Complexity:* Constant time.

```
const_reference at(size_type pos) const;
```

```
reference at(size_type pos);
```

5 *Throws:* `out_of_range` if `pos >= size()`.

6 *Returns:* `operator[] (pos)`.

```
const charT& front() const;
```

```
charT& front();
```

7 *Requires:* `!empty()`.

8 *Effects:* Equivalent to: `return operator[] (0);`

```
const charT& back() const;
```

```
charT& back();
```

9 *Requires:* `!empty()`.

10 *Effects:* Equivalent to: `return operator[] (size() - 1);`

### 24.3.2.6 basic\_string modifiers

[string.modifiers]

#### 24.3.2.6.1 basic\_string::operator+=

[string.op+=]

```
basic_string&
```

```
operator+=(const basic_string& str);
```

1 *Effects:* Calls `append(str)`.

2 *Returns:* `*this`.

```
basic_string& operator+=(basic_string_view<charT, traits> sv);
```

3 *Effects:* Calls `append(sv)`.

4 *Returns:* `*this`.

```
basic_string& operator+=(const charT* s);
```

5 *Effects:* Calls `append(s)`.

6 *Returns:* `*this`.

```
basic_string& operator+=(charT c);
```

7       *Effects:* Calls `push_back(c)`;

8       *Returns:* `*this`.

`basic_string& operator+=(initializer_list<charT> il);`

9       *Effects:* Calls `append(il)`.

10      *Returns:* `*this`.

#### 24.3.2.6.2 `basic_string::append`

[string.append]

`basic_string&`

`append(const basic_string& str);`

1       *Effects:* Calls `append(str.data(), str.size())`.

2       *Returns:* `*this`.

`basic_string&`

`append(const basic_string& str, size_type pos, size_type n = npos);`

3       *Throws:* `out_of_range` if `pos > str.size()`.

4       *Effects:* Determines the effective length `rlen` of the string to append as the smaller of `n` and `str.size() - pos` and calls `append(str.data() + pos, rlen)`.

5       *Returns:* `*this`.

`basic_string& append(basic_string_view<charT, traits> sv);`

6       *Effects:* Equivalent to: `return append(sv.data(), sv.size());`

`template<class T>`

`basic_string& append(const T& t, size_type pos, size_type n = npos);`

7       *Throws:* `out_of_range` if `pos > sv.size()`.

8       *Effects:* Creates a variable, `sv`, as if by `basic_string_view<charT, traits> sv = t`. Determines the effective length `rlen` of the string to append as the smaller of `n` and `sv.size() - pos` and calls `append(sv.data() + pos, rlen)`.

9       *Remarks:* This function shall not participate in overload resolution unless `is_convertible_v<const T&, basic_string_view<charT, traits>>` is true and `is_convertible_v<const T&, const charT*>` is false.

10      *Returns:* `*this`.

`basic_string&`

`append(const charT* s, size_type n);`

11      *Requires:* `s` points to an array of at least `n` elements of `charT`.

12      *Throws:* `length_error` if `size() + n > max_size()`.

13      *Effects:* The function replaces the string controlled by `*this` with a string of length `size() + n` whose first `size()` elements are a copy of the original string controlled by `*this` and whose remaining elements are a copy of the initial `n` elements of `s`.

14      *Returns:* `*this`.

`basic_string& append(const charT* s);`

15      *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

16      *Effects:* Calls `append(s, traits::length(s))`.

17 *Returns:* `*this`.

`basic_string& append(size_type n, charT c);`

18 *Effects:* Equivalent to `append(basic_string(n, c))`.

19 *Returns:* `*this`.

`template<class InputIterator>`

`basic_string& append(InputIterator first, InputIterator last);`

20 *Requires:* `[first, last)` is a valid range.

21 *Effects:* Equivalent to `append(basic_string(first, last, get_allocator()))`.

22 *Returns:* `*this`.

`basic_string& append(initializer_list<charT> il);`

23 *Effects:* Calls `append(il.begin(), il.size())`.

24 *Returns:* `*this`.

`void push_back(charT c);`

25 *Effects:* Equivalent to `append(static_cast<size_type>(1), c)`.

#### 24.3.2.6.3 `basic_string::assign`

[string.assign]

`basic_string& assign(const basic_string& str);`

1 *Effects:* Equivalent to `*this = str`.

2 *Returns:* `*this`.

`basic_string& assign(basic_string&& str)`

`noexcept(allocator_traits<Allocator>::propagate_on_container_move_assignment::value ||  
allocator_traits<Allocator>::is_always_equal::value);`

3 *Effects:* Equivalent to `*this = std::move(str)`.

4 *Returns:* `*this`.

`basic_string&`

`assign(const basic_string& str, size_type pos,  
size_type n = npos);`

5 *Throws:* `out_of_range` if `pos > str.size()`.

6 *Effects:* Determines the effective length `rlen` of the string to assign as the smaller of `n` and `str.size() - pos` and calls `assign(str.data() + pos, rlen)`.

7 *Returns:* `*this`.

`basic_string& assign(basic_string_view<charT, traits> sv);`

8 *Effects:* Equivalent to: `return assign(sv.data(), sv.size());`

`template<class T>`

`basic_string& assign(const T& t, size_type pos, size_type n = npos);`

9 *Throws:* `out_of_range` if `pos > sv.size()`.

10 *Effects:* Creates a variable, `sv`, as if by `basic_string_view<charT, traits> sv = t`. Determines the effective length `rlen` of the string to assign as the smaller of `n` and `sv.size() - pos` and calls `assign(sv.data() + pos, rlen)`.

11 *Remarks:* This function shall not participate in overload resolution unless `is_convertible_v<const T&, basic_string_view<charT, traits>>` is true and `is_convertible_v<const T&, const charT*>` is false.

12 *Returns:* `*this`.

```
basic_string& assign(const charT* s, size_type n);
```

13 *Requires:* `s` points to an array of at least `n` elements of `charT`.

14 *Throws:* `length_error` if `n > max_size()`.

15 *Effects:* Replaces the string controlled by `*this` with a string of length `n` whose elements are a copy of those pointed to by `s`.

16 *Returns:* `*this`.

```
basic_string& assign(const charT* s);
```

17 *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

18 *Effects:* Calls `assign(s, traits::length(s))`.

19 *Returns:* `*this`.

```
basic_string& assign(initializer_list<charT> il);
```

20 *Effects:* Calls `assign(il.begin(), il.size())`.

21 *Returns:* `*this`.

```
basic_string& assign(size_type n, charT c);
```

22 *Effects:* Equivalent to `assign(basic_string(n, c))`.

23 *Returns:* `*this`.

```
template<class InputIterator>
```

```
basic_string& assign(InputIterator first, InputIterator last);
```

24 *Effects:* Equivalent to `assign(basic_string(first, last, get_allocator()))`.

25 *Returns:* `*this`.

#### 24.3.2.6.4 `basic_string::insert`

[string.insert]

```
basic_string&
```

```
insert(size_type pos,
 const basic_string& str);
```

1 *Effects:* Equivalent to: `return insert(pos, str.data(), str.size());`

```
basic_string&
```

```
insert(size_type pos1,
 const basic_string& str,
 size_type pos2, size_type n = npos);
```

2 *Throws:* `out_of_range` if `pos1 > size()` or `pos2 > str.size()`.

3 *Effects:* Determines the effective length `rlen` of the string to insert as the smaller of `n` and `str.size() - pos2` and calls `insert(pos1, str.data() + pos2, rlen)`.

4 *Returns:* `*this`.

```
basic_string& insert(size_type pos, basic_string_view<charT, traits> sv);
```

5 *Effects:* Equivalent to: `return insert(pos, sv.data(), sv.size());`

```

template<class T>
 basic_string& insert(size_type pos1, const T& t,
 size_type pos2, size_type n = npos);
6 Throws: out_of_range if pos1 > size() or pos2 > sv.size().
7 Effects: Creates a variable, sv, as if by basic_string_view<charT, traits> sv = t. Determines
 the effective length rlen of the string to assign as the smaller of n and sv.size() - pos2 and calls
 insert(pos1, sv.data() + pos2, rlen).
8 Remarks: This function shall not participate in overload resolution unless is_convertible_v<const T&,
 basic_string_view<charT, traits>> is true and is_convertible_v<const T&, const charT*>
 is false.
9 Returns: *this.

basic_string&
 insert(size_type pos, const charT* s, size_type n);
10 Requires: s points to an array of at least n elements of charT.
11 Throws: out_of_range if pos > size() or length_error if size() + n > max_size().
12 Effects: Replaces the string controlled by *this with a string of length size() + n whose first pos
 elements are a copy of the initial elements of the original string controlled by *this and whose next n
 elements are a copy of the elements in s and whose remaining elements are a copy of the remaining
 elements of the original string controlled by *this.
13 Returns: *this.

basic_string&
 insert(size_type pos, const charT* s);
14 Requires: s points to an array of at least traits::length(s) + 1 elements of charT.
15 Effects: Equivalent to: return insert(pos, s, traits::length(s));

basic_string&
 insert(size_type pos, size_type n, charT c);
16 Effects: Equivalent to insert(pos, basic_string(n, c)).
17 Returns: *this.

iterator insert(const_iterator p, charT c);
18 Requires: p is a valid iterator on *this.
19 Effects: Inserts a copy of c before the character referred to by p.
20 Returns: An iterator which refers to the copy of the inserted character.

iterator insert(const_iterator p, size_type n, charT c);
21 Requires: p is a valid iterator on *this.
22 Effects: Inserts n copies of c before the character referred to by p.
23 Returns: An iterator which refers to the copy of the first inserted character, or p if n == 0.

template<class InputIterator>
 iterator insert(const_iterator p, InputIterator first, InputIterator last);
24 Requires: p is a valid iterator on *this. [first, last) is a valid range.
25 Effects: Equivalent to insert(p - begin(), basic_string(first, last, get_allocator())).

```

26 *Returns:* An iterator which refers to the copy of the first inserted character, or `p` if `first == last`.

```
iterator insert(const_iterator p, initializer_list<charT> il);
```

27 *Effects:* As if by `insert(p, il.begin(), il.end())`.

28 *Returns:* An iterator which refers to the copy of the first inserted character, or `p` if `il` is empty.

#### 24.3.2.6.5 `basic_string::erase` [string.erase]

```
basic_string& erase(size_type pos = 0, size_type n = npos);
```

1 *Throws:* `out_of_range` if `pos > size()`.

2 *Effects:* Determines the effective length `xlen` of the string to be removed as the smaller of `n` and `size() - pos`.

3 The function then replaces the string controlled by `*this` with a string of length `size() - xlen` whose first `pos` elements are a copy of the initial elements of the original string controlled by `*this`, and whose remaining elements are a copy of the elements of the original string controlled by `*this` beginning at position `pos + xlen`.

4 *Returns:* `*this`.

```
iterator erase(const_iterator p);
```

5 *Throws:* Nothing.

6 *Effects:* Removes the character referred to by `p`.

7 *Returns:* An iterator which points to the element immediately following `p` prior to the element being erased. If no such element exists, `end()` is returned.

```
iterator erase(const_iterator first, const_iterator last);
```

8 *Requires:* `first` and `last` are valid iterators on `*this`, defining a range `[first, last)`.

9 *Throws:* Nothing.

10 *Effects:* Removes the characters in the range `[first, last)`.

11 *Returns:* An iterator which points to the element pointed to by `last` prior to the other elements being erased. If no such element exists, `end()` is returned.

```
void pop_back();
```

12 *Requires:* `!empty()`.

13 *Throws:* Nothing.

14 *Effects:* Equivalent to `erase(size() - 1, 1)`.

#### 24.3.2.6.6 `basic_string::replace` [string.replace]

```
basic_string&
 replace(size_type pos1, size_type n1,
 const basic_string& str);
```

1 *Effects:* Equivalent to: `return replace(pos1, n1, str.data(), str.size());`

```
basic_string&
 replace(size_type pos1, size_type n1,
 const basic_string& str,
 size_type pos2, size_type n2 = npos);
```

2 *Throws:* `out_of_range` if `pos1 > size()` or `pos2 > str.size()`.

3       *Effects:* Determines the effective length `rlen` of the string to be inserted as the smaller of `n2` and `str.size() - pos2` and calls `replace(pos1, n1, str.data() + pos2, rlen)`.

4       *Returns:* `*this`.

```
basic_string& replace(size_type pos1, size_type n1,
 basic_string_view<charT, traits> sv);
```

5       *Effects:* Equivalent to: `return replace(pos1, n1, sv.data(), sv.size());`

```
template<class T>
 basic_string& replace(size_type pos1, size_type n1, const T& t,
 size_type pos2, size_type n2 = npos);
```

6       *Throws:* `out_of_range` if `pos1 > size()` or `pos2 > sv.size()`.

7       *Effects:* Creates a variable, `sv`, as if by `basic_string_view<charT, traits> sv = t`. Determines the effective length `rlen` of the string to be inserted as the smaller of `n2` and `sv.size() - pos2` and calls `replace(pos1, n1, sv.data() + pos2, rlen)`.

8       *Remarks:* This function shall not participate in overload resolution unless `is_convertible_v<const T&, basic_string_view<charT, traits>>` is true and `is_convertible_v<const T&, const charT*>` is false.

9       *Returns:* `*this`.

```
basic_string&
 replace(size_type pos1, size_type n1, const charT* s, size_type n2);
```

10       *Requires:* `s` points to an array of at least `n2` elements of `charT`.

11       *Throws:* `out_of_range` if `pos1 > size()` or `length_error` if the length of the resulting string would exceed `max_size()` (see below).

12       *Effects:* Determines the effective length `xlen` of the string to be removed as the smaller of `n1` and `size() - pos1`. If `size() - xlen >= max_size() - n2` throws `length_error`. Otherwise, the function replaces the string controlled by `*this` with a string of length `size() - xlen + n2` whose first `pos1` elements are a copy of the initial elements of the original string controlled by `*this`, whose next `n2` elements are a copy of the initial `n2` elements of `s`, and whose remaining elements are a copy of the elements of the original string controlled by `*this` beginning at position `pos + xlen`.

13       *Returns:* `*this`.

```
basic_string&
 replace(size_type pos, size_type n, const charT* s);
```

14       *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

15       *Effects:* Equivalent to: `return replace(pos, n, s, traits::length(s));`

```
basic_string&
 replace(size_type pos1, size_type n1,
 size_type n2, charT c);
```

16       *Effects:* Equivalent to `replace(pos1, n1, basic_string(n2, c))`.

17       *Returns:* `*this`.

```
basic_string& replace(const_iterator i1, const_iterator i2, const basic_string& str);
```

18       *Requires:* `[begin(), i1)` and `[i1, i2)` are valid ranges.

19       *Effects:* Calls `replace(i1 - begin(), i2 - i1, str)`.



20       *Returns:* *\*this*.

```
basic_string& replace(const_iterator i1, const_iterator i2,
 basic_string_view<charT, traits> sv);
```

21       *Requires:* *[begin(), i1)* and *[i1, i2)* are valid ranges.

22       *Effects:* Calls *replace(i1 - begin(), i2 - i1, sv)*.

23       *Returns:* *\*this*.

```
basic_string&
replace(const_iterator i1, const_iterator i2, const charT* s, size_type n);
```

24       *Requires:* *[begin(), i1)* and *[i1, i2)* are valid ranges and *s* points to an array of at least *n* elements of *charT*.

25       *Effects:* Calls *replace(i1 - begin(), i2 - i1, s, n)*.

26       *Returns:* *\*this*.

```
basic_string& replace(const_iterator i1, const_iterator i2, const charT* s);
```

27       *Requires:* *[begin(), i1)* and *[i1, i2)* are valid ranges and *s* points to an array of at least *traits::length(s) + 1* elements of *charT*.

28       *Effects:* Calls *replace(i1 - begin(), i2 - i1, s, traits::length(s))*.

29       *Returns:* *\*this*.

```
basic_string& replace(const_iterator i1, const_iterator i2, size_type n,
 charT c);
```

30       *Requires:* *[begin(), i1)* and *[i1, i2)* are valid ranges.

31       *Effects:* Calls *replace(i1 - begin(), i2 - i1, basic\_string(n, c))*.

32       *Returns:* *\*this*.

```
template<class InputIterator>
basic_string& replace(const_iterator i1, const_iterator i2,
 InputIterator j1, InputIterator j2);
```

33       *Requires:* *[begin(), i1)*, *[i1, i2)* and *[j1, j2)* are valid ranges.

34       *Effects:* Calls *replace(i1 - begin(), i2 - i1, basic\_string(j1, j2, get\_allocator()))*.

35       *Returns:* *\*this*.

```
basic_string& replace(const_iterator i1, const_iterator i2,
 initializer_list<charT> il);
```

36       *Requires:* *[begin(), i1)* and *[i1, i2)* are valid ranges.

37       *Effects:* Calls *replace(i1 - begin(), i2 - i1, il.begin(), il.size())*.

38       *Returns:* *\*this*.

#### 24.3.2.6.7 `basic_string::copy`

[string.copy]

```
size_type copy(charT* s, size_type n, size_type pos = 0) const;
```

1       Let *rlen* be the smaller of *n* and *size() - pos*.

2       *Throws:* *out\_of\_range* if *pos > size()*.

3       *Requires:* *[s, s + rlen)* is a valid range.

4 *Effects:* Equivalent to: `traits::copy(s, data() + pos, rlen)`. [ *Note:* This does not terminate `s` with a null object. — *end note* ]

5 *Returns:* `rlen`.

#### 24.3.2.6.8 `basic_string::swap` [string.swap]

```
void swap(basic_string& s)
 noexcept(allocator_traits<Allocator>::propagate_on_container_swap::value ||
 allocator_traits<Allocator>::is_always_equal::value);
```

1 *Postconditions:* `*this` contains the same sequence of characters that was in `s`, `s` contains the same sequence of characters that was in `*this`.

2 *Throws:* Nothing.

3 *Complexity:* Constant time.

### 24.3.2.7 `basic_string` string operations [string.ops]

#### 24.3.2.7.1 `basic_string` accessors [string.accessors]

```
const charT* c_str() const noexcept;
const charT* data() const noexcept;
```

1 *Returns:* A pointer `p` such that `p + i == &operator[](i)` for each `i` in `[0, size())`.

2 *Complexity:* Constant time.

3 *Requires:* The program shall not alter any of the values stored in the character array.

```
charT* data() noexcept;
```

4 *Returns:* A pointer `p` such that `p + i == &operator[](i)` for each `i` in `[0, size())`.

5 *Complexity:* Constant time.

6 *Requires:* The program shall not alter the value stored at `p + size()`.

```
operator basic_string_view<charT, traits>() const noexcept;
```

7 *Effects:* Equivalent to: `return basic_string_view<charT, traits>(data(), size());`

```
allocator_type get_allocator() const noexcept;
```

8 *Returns:* A copy of the `Allocator` object used to construct the string or, if that allocator has been replaced, a copy of the most recent replacement.

#### 24.3.2.7.2 `basic_string::find` [string.find]

```
size_type find(basic_string_view<charT, traits> sv, size_type pos = 0) const noexcept;
```

1 *Effects:* Determines the lowest position `xpos`, if possible, such that both of the following conditions hold:

(1.1) — `pos <= xpos` and `xpos + sv.size() <= size()`;

(1.2) — `traits::eq(at(xpos + I), sv.at(I))` for all elements `I` of the data referenced by `sv`.

2 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

```
size_type find(const basic_string& str, size_type pos = 0) const noexcept;
```

3 *Effects:* Equivalent to: `return find(basic_string_view<charT, traits>(str), pos);`

```
size_type find(const charT* s, size_type pos, size_type n) const;
```

4 *Returns:* find(basic\_string\_view<charT, traits>(s, n), pos).

size\_type find(const charT\* s, size\_type pos = 0) const;

5 *Requires:* s points to an array of at least traits::length(s) + 1 elements of charT.

6 *Returns:* find(basic\_string\_view<charT, traits>(s), pos).

size\_type find(charT c, size\_type pos = 0) const;

7 *Returns:* find(basic\_string(1, c), pos).

#### 24.3.2.7.3 basic\_string::rfind [string.rfind]

size\_type rfind(basic\_string\_view<charT, traits> sv, size\_type pos = npos) const noexcept;

1 *Effects:* Determines the highest position xpos, if possible, such that both of the following conditions hold:

(1.1) — xpos <= pos and xpos + sv.size() <= size();

(1.2) — traits::eq(at(xpos + I), sv.at(I)) for all elements I of the data referenced by sv.

2 *Returns:* xpos if the function can determine such a value for xpos. Otherwise, returns npos.

size\_type rfind(const basic\_string& str, size\_type pos = npos) const noexcept;

3 *Effects:* Equivalent to: return rfind(basic\_string\_view<charT, traits>(str), pos);

size\_type rfind(const charT\* s, size\_type pos, size\_type n) const;

4 *Returns:* rfind(basic\_string\_view<charT, traits>(s, n), pos).

size\_type rfind(const charT\* s, size\_type pos = npos) const;

5 *Requires:* s points to an array of at least traits::length(s) + 1 elements of charT.

6 *Returns:* rfind(basic\_string\_view<charT, traits>(s), pos).

size\_type rfind(charT c, size\_type pos = npos) const;

7 *Returns:* rfind(basic\_string(1, c), pos).

#### 24.3.2.7.4 basic\_string::find\_first\_of [string.find.first.of]

size\_type find\_first\_of(basic\_string\_view<charT, traits> sv, size\_type pos = 0) const noexcept;

1 *Effects:* Determines the lowest position xpos, if possible, such that both of the following conditions hold:

(1.1) — pos <= xpos and xpos < size();

(1.2) — traits::eq(at(xpos), sv.at(I)) for some element I of the data referenced by sv.

2 *Returns:* xpos if the function can determine such a value for xpos. Otherwise, returns npos.

size\_type find\_first\_of(const basic\_string& str, size\_type pos = 0) const noexcept;

3 *Effects:* Equivalent to: return find\_first\_of(basic\_string\_view<charT, traits>(str), pos);

size\_type find\_first\_of(const charT\* s, size\_type pos, size\_type n) const;

4 *Returns:* find\_first\_of(basic\_string\_view<charT, traits>(s, n), pos).

size\_type find\_first\_of(const charT\* s, size\_type pos = 0) const;

5 *Requires:* s points to an array of at least traits::length(s) + 1 elements of charT.

6 *Returns:* `find_first_of(basic_string_view<charT, traits>(s), pos)`.

`size_type find_first_of(charT c, size_type pos = 0) const;`

7 *Returns:* `find_first_of(basic_string(1, c), pos)`.

#### 24.3.2.7.5 `basic_string::find_last_of` [string.find.last.of]

`size_type find_last_of(basic_string_view<charT, traits> sv, size_type pos = npos) const noexcept;`

1 *Effects:* Determines the highest position `xpos`, if possible, such that both of the following conditions hold:

(1.1) — `xpos <= pos` and `xpos < size()`;

(1.2) — `traits::eq(at(xpos), sv.at(I))` for some element `I` of the data referenced by `sv`.

2 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`size_type find_last_of(const basic_string& str, size_type pos = npos) const noexcept;`

3 *Effects:* Equivalent to: `return find_last_of(basic_string_view<charT, traits>(str), pos);`

`size_type find_last_of(const charT* s, size_type pos, size_type n) const;`

4 *Returns:* `find_last_of(basic_string_view<charT, traits>(s, n), pos)`.

`size_type find_last_of(const charT* s, size_type pos = npos) const;`

5 *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

6 *Returns:* `find_last_of(basic_string_view<charT, traits>(s), pos)`.

`size_type find_last_of(charT c, size_type pos = npos) const;`

7 *Returns:* `find_last_of(basic_string(1, c), pos)`.

#### 24.3.2.7.6 `basic_string::find_first_not_of` [string.find.first.not.of]

`size_type find_first_not_of(basic_string_view<charT, traits> sv,  
size_type pos = 0) const noexcept;`

1 *Effects:* Determines the lowest position `xpos`, if possible, such that both of the following conditions hold:

(1.1) — `pos <= xpos` and `xpos < size()`;

(1.2) — `traits::eq(at(xpos), sv.at(I))` for no element `I` of the data referenced by `sv`.

2 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`size_type find_first_not_of(const basic_string& str, size_type pos = 0) const noexcept;`

3 *Effects:* Equivalent to:

`return find_first_not_of(basic_string_view<charT, traits>(str), pos);`

`size_type find_first_not_of(const charT* s, size_type pos, size_type n) const;`

4 *Returns:* `find_first_not_of(basic_string_view<charT, traits>(s, n), pos)`.

`size_type find_first_not_of(const charT* s, size_type pos = 0) const;`

5 *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

6 *Returns:* `find_first_not_of(basic_string_view<charT, traits>(s), pos)`.

`size_type find_first_not_of(charT c, size_type pos = 0) const;`

7 *Returns:* `find_first_not_of(basic_string(1, c), pos)`.

#### 24.3.2.7.7 `basic_string::find_last_not_of` [string.find.last.not.of]

```
size_type find_last_not_of(basic_string_view<charT, traits> sv,
 size_type pos = npos) const noexcept;
```

1 *Effects:* Determines the highest position `xpos`, if possible, such that both of the following conditions hold:

(1.1) — `xpos <= pos` and `xpos < size()`;

(1.2) — `traits::eq(at(xpos), sv.at(I))` for no element `I` of the data referenced by `sv`.

2 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

```
size_type find_last_not_of(const basic_string& str, size_type pos = npos) const noexcept;
```

3 *Effects:* Equivalent to:

```
return find_last_not_of(basic_string_view<charT, traits>(str), pos);
```

```
size_type find_last_not_of(const charT* s, size_type pos, size_type n) const;
```

4 *Returns:* `find_last_not_of(basic_string_view<charT, traits>(s, n), pos)`.

```
size_type find_last_not_of(const charT* s, size_type pos = npos) const;
```

5 *Requires:* `s` points to an array of at least `traits::length(s) + 1` elements of `charT`.

6 *Returns:* `find_last_not_of(basic_string_view<charT, traits>(s), pos)`.

```
size_type find_last_not_of(charT c, size_type pos = npos) const;
```

7 *Returns:* `find_last_not_of(basic_string(1, c), pos)`.

#### 24.3.2.7.8 `basic_string::substr` [string.substr]

```
basic_string substr(size_type pos = 0, size_type n = npos) const;
```

1 *Throws:* `out_of_range` if `pos > size()`.

2 *Effects:* Determines the effective length `rlen` of the string to copy as the smaller of `n` and `size() - pos`.

3 *Returns:* `basic_string(data()+pos, rlen)`.

#### 24.3.2.7.9 `basic_string::compare` [string.compare]

```
int compare(basic_string_view<charT, traits> sv) const noexcept;
```

1 *Effects:* Determines the effective length `rlen` of the strings to compare as the smaller of `size()` and `sv.size()`. The function then compares the two strings by calling `traits::compare(data(), sv.data(), rlen)`.

2 *Returns:* The nonzero result if the result of the comparison is nonzero. Otherwise, returns a value as indicated in Table 63.

```
int compare(size_type pos1, size_type n1, basic_string_view<charT, traits> sv) const;
```

3 *Effects:* Equivalent to:

```
return basic_string_view<charT, traits>(data(), size()).substr(pos1, n1).compare(sv);
```

```
template<class T>
```

```
int compare(size_type pos1, size_type n1, const T& t,
```

Table 63 — compare() results

| Condition           | Return Value |
|---------------------|--------------|
| size() < sv.size()  | < 0          |
| size() == sv.size() | 0            |
| size() > sv.size()  | > 0          |

```
size_type pos2, size_type n2 = npos) const;
```

4 *Effects:* Equivalent to:

```
basic_string_view<charT, traits> sv = t;
return basic_string_view<charT, traits>(
 data(), size()).substr(pos1, n1).compare(sv.substr(pos2, n2));
```

5 *Remarks:* This function shall not participate in overload resolution unless `is_convertible_v<const T&, basic_string_view<charT, traits>>` is true and `is_convertible_v<const T&, const charT*>` is false.

```
int compare(const basic_string& str) const noexcept;
```

6 *Effects:* Equivalent to: `return compare(basic_string_view<charT, traits>(str));`

```
int compare(size_type pos1, size_type n1, const basic_string& str) const;
```

7 *Effects:* Equivalent to: `return compare(pos1, n1, basic_string_view<charT, traits>(str));`

```
int compare(size_type pos1, size_type n1,
 const basic_string& str,
 size_type pos2, size_type n2 = npos) const;
```

8 *Effects:* Equivalent to:

```
return compare(pos1, n1, basic_string_view<charT, traits>(str), pos2, n2);
```

```
int compare(const charT* s) const;
```

9 *Returns:* `compare(basic_string(s)).`

```
int compare(size_type pos, size_type n1, const charT* s) const;
```

10 *Returns:* `basic_string(*this, pos, n1).compare(basic_string(s)).`

```
int compare(size_type pos, size_type n1, const charT* s, size_type n2) const;
```

11 *Returns:* `basic_string(*this, pos, n1).compare(basic_string(s, n2)).`

### 24.3.3 basic\_string non-member functions

[string.nonmembers]

#### 24.3.3.1 operator+

[string.op+]

```
template<class charT, class traits, class Allocator>
basic_string<charT, traits, Allocator>
operator+(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

1 *Returns:* `basic_string<charT, traits, Allocator>(lhs).append(rhs).`

```
template<class charT, class traits, class Allocator>
basic_string<charT, traits, Allocator>
operator+(basic_string<charT, traits, Allocator>&& lhs,
```

```

 const basic_string<charT, traits, Allocator>& rhs);
2 Returns: std::move(lhs.append(rhs)).

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs,
 basic_string<charT, traits, Allocator>&& rhs);
3 Returns: std::move(rhs.insert(0, lhs)).

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(basic_string<charT, traits, Allocator>&& lhs,
 basic_string<charT, traits, Allocator>&& rhs);
4 Returns: std::move(lhs.append(rhs)). [Note: Or equivalently, std::move(rhs.insert(0, lhs)).
 — end note]

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
5 Returns: basic_string<charT, traits, Allocator>(lhs) + rhs.
6 Remarks: Uses traits::length().

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const charT* lhs,
 basic_string<charT, traits, Allocator>&& rhs);
7 Returns: std::move(rhs.insert(0, lhs)).
8 Remarks: Uses traits::length().

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(charT lhs,
 const basic_string<charT, traits, Allocator>& rhs);
9 Returns: basic_string<charT, traits, Allocator>(1, lhs) + rhs.

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(charT lhs,
 basic_string<charT, traits, Allocator>&& rhs);
10 Returns: std::move(rhs.insert(0, 1, lhs)).

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>
 operator+(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
11 Returns: lhs + basic_string<charT, traits, Allocator>(rhs).
12 Remarks: Uses traits::length().

template<class charT, class traits, class Allocator>
 basic_string<charT, traits, Allocator>

```

```
operator+(basic_string<charT, traits, Allocator>&& lhs,
 const charT* rhs);
```

13 *Returns:* `std::move(lhs.append(rhs))`.

14 *Remarks:* Uses `traits::length()`.

```
template<class charT, class traits, class Allocator>
basic_string<charT, traits, Allocator>
operator+(const basic_string<charT, traits, Allocator>& lhs,
 charT rhs);
```

15 *Returns:* `lhs + basic_string<charT, traits, Allocator>(1, rhs)`.

```
template<class charT, class traits, class Allocator>
basic_string<charT, traits, Allocator>
operator+(basic_string<charT, traits, Allocator>&& lhs,
 charT rhs);
```

16 *Returns:* `std::move(lhs.append(1, rhs))`.

### 24.3.3.2 operator==

[string.operator==]

```
template<class charT, class traits, class Allocator>
bool operator==(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1 *Returns:* `lhs.compare(rhs) == 0`.

```
template<class charT, class traits, class Allocator>
bool operator==(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2 *Returns:* `rhs == lhs`.

```
template<class charT, class traits, class Allocator>
bool operator==(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3 *Requires:* `rhs` points to an array of at least `traits::length(rhs) + 1` elements of `charT`.

4 *Returns:* `lhs.compare(rhs) == 0`.

### 24.3.3.3 operator!=

[string.op!=]

```
template<class charT, class traits, class Allocator>
bool operator!=(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1 *Returns:* `!(lhs == rhs)`.

```
template<class charT, class traits, class Allocator>
bool operator!=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2 *Returns:* `rhs != lhs`.

```
template<class charT, class traits, class Allocator>
bool operator!=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3 *Requires:* `rhs` points to an array of at least `traits::length(rhs) + 1` elements of `charT`.

4 *Returns:* `lhs.compare(rhs) != 0`.



**24.3.3.4 operator<****[string.op<]**

```
template<class charT, class traits, class Allocator>
 bool operator< (const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1     *Returns:* lhs.compare(rhs) < 0.

```
template<class charT, class traits, class Allocator>
 bool operator< (const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2     *Returns:* rhs.compare(lhs) > 0.

```
template<class charT, class traits, class Allocator>
 bool operator< (const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3     *Returns:* lhs.compare(rhs) < 0.

**24.3.3.5 operator>****[string.op>]**

```
template<class charT, class traits, class Allocator>
 bool operator> (const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1     *Returns:* lhs.compare(rhs) > 0.

```
template<class charT, class traits, class Allocator>
 bool operator> (const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2     *Returns:* rhs.compare(lhs) < 0.

```
template<class charT, class traits, class Allocator>
 bool operator> (const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3     *Returns:* lhs.compare(rhs) > 0.

**24.3.3.6 operator<=****[string.op<=]**

```
template<class charT, class traits, class Allocator>
 bool operator<=(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1     *Returns:* lhs.compare(rhs) <= 0.

```
template<class charT, class traits, class Allocator>
 bool operator<=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2     *Returns:* rhs.compare(lhs) >= 0.

```
template<class charT, class traits, class Allocator>
 bool operator<=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3     *Returns:* lhs.compare(rhs) <= 0.

**24.3.3.7 operator>=****[string.op>=]**

```
template<class charT, class traits, class Allocator>
```

```
bool operator>=(const basic_string<charT, traits, Allocator>& lhs,
 const basic_string<charT, traits, Allocator>& rhs) noexcept;
```

1 *Returns:* lhs.compare(rhs) >= 0.

```
template<class charT, class traits, class Allocator>
bool operator>=(const charT* lhs,
 const basic_string<charT, traits, Allocator>& rhs);
```

2 *Returns:* rhs.compare(lhs) <= 0.

```
template<class charT, class traits, class Allocator>
bool operator>=(const basic_string<charT, traits, Allocator>& lhs,
 const charT* rhs);
```

3 *Returns:* lhs.compare(rhs) >= 0.

#### 24.3.3.8 swap

[string.special]

```
template<class charT, class traits, class Allocator>
void swap(basic_string<charT, traits, Allocator>& lhs,
 basic_string<charT, traits, Allocator>& rhs)
noexcept(noexcept(lhs.swap(rhs)));
```

1 *Effects:* Equivalent to: lhs.swap(rhs);

#### 24.3.3.9 Inserters and extractors

[string.io]

```
template<class charT, class traits, class Allocator>
basic_istream<charT, traits>&
operator>>(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str);
```

1 *Effects:* Behaves as a formatted input function (30.7.4.2.1). After constructing a `sentry` object, if the `sentry` converts to `true`, calls `str.erase()` and then extracts characters from `is` and appends them to `str` as if by calling `str.append(1, c)`. If `is.width()` is greater than zero, the maximum number `n` of characters appended is `is.width()`; otherwise `n` is `str.max_size()`. Characters are extracted and appended until any of the following occurs:

- (1.1) — `n` characters are stored;
- (1.2) — end-of-file occurs on the input sequence;
- (1.3) — `isspace(c, is.getloc())` is `true` for the next available input character `c`.

2 After the last character (if any) is extracted, `is.width(0)` is called and the `sentry` object is destroyed.

3 If the function extracts no characters, it calls `is.setstate(ios::failbit)`, which may throw `ios_base::failure` (30.5.5.4).

4 *Returns:* `is`.

```
template<class charT, class traits, class Allocator>
basic_ostream<charT, traits>&
operator<<(basic_ostream<charT, traits>& os,
 const basic_string<charT, traits, Allocator>& str);
```

5 *Effects:* Equivalent to: `return os << basic_string_view<charT, traits>(str);`

```
template<class charT, class traits, class Allocator>
basic_istream<charT, traits>&
getline(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str,
```

```

 charT delim);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>&& is,
 basic_string<charT, traits, Allocator>& str,
 charT delim);

```

6 *Effects:* Behaves as an unformatted input function (30.7.4.3), except that it does not affect the value returned by subsequent calls to `basic_istream<>::gcount()`. After constructing a `sentry` object, if the sentry converts to `true`, calls `str.erase()` and then extracts characters from `is` and appends them to `str` as if by calling `str.append(1, c)` until any of the following occurs:

- (6.1) — end-of-file occurs on the input sequence (in which case, the `getline` function calls `is.setstate(ios_base::eofbit)`).
- (6.2) — `traits::eq(c, delim)` for the next available input character `c` (in which case, `c` is extracted but not appended) (30.5.5.4)
- (6.3) — `str.max_size()` characters are stored (in which case, the function calls `is.setstate(ios_base::failbit)`) (30.5.5.4)

7 The conditions are tested in the order shown. In any case, after the last character is extracted, the `sentry` object is destroyed.

8 If the function extracts no characters, it calls `is.setstate(ios_base::failbit)` which may throw `ios_base::failure` (30.5.5.4).

9 *Returns:* `is`.

```

template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>& is,
 basic_string<charT, traits, Allocator>& str);
template<class charT, class traits, class Allocator>
 basic_istream<charT, traits>&
 getline(basic_istream<charT, traits>&& is,
 basic_string<charT, traits, Allocator>& str);

```

10 *Returns:* `getline(is, str, is.widen('\n'))`.

#### 24.3.4 Numeric conversions

[string.conversions]

```

int stoi(const string& str, size_t* idx = 0, int base = 10);
long stol(const string& str, size_t* idx = 0, int base = 10);
unsigned long stoul(const string& str, size_t* idx = 0, int base = 10);
long long stoll(const string& str, size_t* idx = 0, int base = 10);
unsigned long long stoull(const string& str, size_t* idx = 0, int base = 10);

```

1 *Effects:* the first two functions call `strtoul(str.c_str(), ptr, base)`, and the last three functions call `strtoul(str.c_str(), ptr, base)`, `strtoll(str.c_str(), ptr, base)`, and `strtoull(str.c_str(), ptr, base)`, respectively. Each function returns the converted result, if any. The argument `ptr` designates a pointer to an object internal to the function that is used to determine what to store at `*idx`. If the function does not throw an exception and `idx != 0`, the function stores in `*idx` the index of the first unconverted element of `str`.

2 *Returns:* The converted result.

3 *Throws:* `invalid_argument` if `strtoul`, `strtoll`, or `strtoull` reports that no conversion could be performed. Throws `out_of_range` if `strtoul`, `strtoll` or `strtoull` sets `errno` to `ERANGE`, or if the converted value is outside the range of representable values for the return type.

```
float stof(const string& str, size_t* idx = 0);
double stod(const string& str, size_t* idx = 0);
long double stold(const string& str, size_t* idx = 0);
```

- 4 *Effects:* These functions call `strtod(str.c_str(), ptr)`, `strtod(str.c_str(), ptr)`, and `strtold(str.c_str(), ptr)`, respectively. Each function returns the converted result, if any. The argument `ptr` designates a pointer to an object internal to the function that is used to determine what to store at `*idx`. If the function does not throw an exception and `idx != 0`, the function stores in `*idx` the index of the first unconverted element of `str`.

- 5 *Returns:* The converted result.

- 6 *Throws:* `invalid_argument` if `stof`, `stod`, or `stold` reports that no conversion could be performed. Throws `out_of_range` if `stof`, `stod`, or `stold` sets `errno` to `ERANGE` or if the converted value is outside the range of representable values for the return type.

```
string to_string(int val);
string to_string(unsigned val);
string to_string(long val);
string to_string(unsigned long val);
string to_string(long long val);
string to_string(unsigned long long val);
string to_string(float val);
string to_string(double val);
string to_string(long double val);
```

- 7 *Returns:* Each function returns a `string` object holding the character representation of the value of its argument that would be generated by calling `sprintf(buf, fmt, val)` with a format specifier of `"%d"`, `"%u"`, `"%ld"`, `"%lu"`, `"%lld"`, `"%llu"`, `"%f"`, `"%f"`, or `"%Lf"`, respectively, where `buf` designates an internal character buffer of sufficient size.

```
int stoi(const wstring& str, size_t* idx = 0, int base = 10);
long stol(const wstring& str, size_t* idx = 0, int base = 10);
unsigned long stoul(const wstring& str, size_t* idx = 0, int base = 10);
long long stoll(const wstring& str, size_t* idx = 0, int base = 10);
unsigned long long stoull(const wstring& str, size_t* idx = 0, int base = 10);
```

- 8 *Effects:* the first two functions call `wcstol(str.c_str(), ptr, base)`, and the last three functions call `wcstoul(str.c_str(), ptr, base)`, `wcstoll(str.c_str(), ptr, base)`, and `wcstoull(str.c_str(), ptr, base)`, respectively. Each function returns the converted result, if any. The argument `ptr` designates a pointer to an object internal to the function that is used to determine what to store at `*idx`. If the function does not throw an exception and `idx != 0`, the function stores in `*idx` the index of the first unconverted element of `str`.

- 9 *Returns:* The converted result.

- 10 *Throws:* `invalid_argument` if `wcstol`, `wcstoul`, `wcstoll`, or `wcstoull` reports that no conversion could be performed. Throws `out_of_range` if the converted value is outside the range of representable values for the return type.

```
float stof(const wstring& str, size_t* idx = 0);
double stod(const wstring& str, size_t* idx = 0);
long double stold(const wstring& str, size_t* idx = 0);
```

- 11 *Effects:* These functions call `wcstof(str.c_str(), ptr)`, `wcstod(str.c_str(), ptr)`, and `wcstold(str.c_str(), ptr)`, respectively. Each function returns the converted result, if any. The argument `ptr` designates a pointer to an object internal to the function that is used to determine what to store at `*idx`. If the function does not throw an exception and `idx != 0`, the function stores in `*idx` the

index of the first unconverted element of `str`.

12 *Returns:* The converted result.

13 *Throws:* `invalid_argument` if `wcstof`, `wcstod`, or `wcstold` reports that no conversion could be performed. Throws `out_of_range` if `wcstof`, `wcstod`, or `wcstold` sets `errno` to `ERANGE`.

```
wstring to_wstring(int val);
wstring to_wstring(unsigned val);
wstring to_wstring(long val);
wstring to_wstring(unsigned long val);
wstring to_wstring(long long val);
wstring to_wstring(unsigned long long val);
wstring to_wstring(float val);
wstring to_wstring(double val);
wstring to_wstring(long double val);
```

14 *Returns:* Each function returns a `wstring` object holding the character representation of the value of its argument that would be generated by calling `swprintf(buf, buffsz, fmt, val)` with a format specifier of `L"%d"`, `L"%u"`, `L"%ld"`, `L"%lu"`, `L"%lld"`, `L"%llu"`, `L"%f"`, `L"%F"`, or `L"%Lf"`, respectively, where `buf` designates an internal character buffer of sufficient size `buffersz`.

### 24.3.5 Hash support

[basic.string.hash]

```
template<> struct hash<string>;
template<> struct hash<u16string>;
template<> struct hash<u32string>;
template<> struct hash<wstring>;
```

1 If `S` is one of these string types, `SV` is the corresponding string view type, and `s` is an object of type `S`, then `hash<S>()(s) == hash<SV>()(SV(s))`.

### 24.3.6 Suffix for `basic_string` literals

[basic.string.literals]

```
string operator""s(const char* str, size_t len);
```

1 *Returns:* `string{str, len}`.

```
u16string operator""s(const char16_t* str, size_t len);
```

2 *Returns:* `u16string{str, len}`.

```
u32string operator""s(const char32_t* str, size_t len);
```

3 *Returns:* `u32string{str, len}`.

```
wstring operator""s(const wchar_t* str, size_t len);
```

4 *Returns:* `wstring{str, len}`.

5 [Note: The same suffix `s` is used for `chrono::duration` literals denoting seconds but there is no conflict, since duration suffixes apply to numbers and string literal suffixes apply to character array literals. — end note]

## 24.4 String view classes

[string.view]

1 The class template `basic_string_view` describes an object that can refer to a constant contiguous sequence of char-like (24.1) objects with the first element of the sequence at position zero. In the rest of this section, the type of the char-like objects held in a `basic_string_view` object is designated by `charT`.

2 [Note: The library provides implicit conversions from `const charT*` and `std::basic_string<charT, ...>` to `std::basic_string_view<charT, ...>` so that user code can accept just `std::basic_string_`

`view<charT>` as a non-templated parameter wherever a sequence of characters is expected. User-defined types should define their own implicit conversions to `std::basic_string_view` in order to interoperate with these functions. — *end note*

- <sup>3</sup> The complexity of `basic_string_view` member functions is  $\mathcal{O}(1)$  unless otherwise specified.

#### 24.4.1 Header `<string_view>` synopsis

[string.view.synop]

```
namespace std {
 // 24.4.2, class template basic_string_view
 template<class charT, class traits = char_traits<charT>>
 class basic_string_view;

 // 24.4.3, non-member comparison functions
 template<class charT, class traits>
 constexpr bool operator==(basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 template<class charT, class traits>
 constexpr bool operator!=(basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 template<class charT, class traits>
 constexpr bool operator< (basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 template<class charT, class traits>
 constexpr bool operator> (basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 template<class charT, class traits>
 constexpr bool operator<= (basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 template<class charT, class traits>
 constexpr bool operator>= (basic_string_view<charT, traits> x,
 basic_string_view<charT, traits> y) noexcept;
 // see 24.4.3, sufficient additional overloads of comparison functions

 // 24.4.4, inserters and extractors
 template<class charT, class traits>
 basic_ostream<charT, traits>&
 operator<< (basic_ostream<charT, traits>& os,
 basic_string_view<charT, traits> str);

 // basic_string_view typedef names
 using string_view = basic_string_view<char>;
 using u16string_view = basic_string_view<char16_t>;
 using u32string_view = basic_string_view<char32_t>;
 using wstring_view = basic_string_view<wchar_t>;

 // 24.4.5, hash support
 template<class T> struct hash;
 template<> struct hash<string_view>;
 template<> struct hash<u16string_view>;
 template<> struct hash<u32string_view>;
 template<> struct hash<wstring_view>;

 inline namespace literals {
 inline namespace string_view_literals {
 // 24.4.6, suffix for basic_string_view literals
```

```

constexpr string_view operator""sv(const char* str, size_t len) noexcept;
constexpr u16string_view operator""sv(const char16_t* str, size_t len) noexcept;
constexpr u32string_view operator""sv(const char32_t* str, size_t len) noexcept;
constexpr wstring_view operator""sv(const wchar_t* str, size_t len) noexcept;
}
}
}

```

- <sup>1</sup> The function templates defined in 23.2.3 and 27.7 are available when `<string_view>` is included.

#### 24.4.2 Class template `basic_string_view`

[string.view.template]

```

template<class charT, class traits = char_traits<charT>>
class basic_string_view {
public:
 // types
 using traits_type = traits;
 using value_type = charT;
 using pointer = value_type*;
 using const_pointer = const value_type*;
 using reference = value_type&;
 using const_reference = const value_type&;
 using const_iterator = implementation-defined; // see 24.4.2.2
 using iterator = const_iterator;228
 using const_reverse_iterator = reverse_iterator<const_iterator>;
 using reverse_iterator = const_reverse_iterator;
 using size_type = size_t;
 using difference_type = ptrdiff_t;
 static constexpr size_type npos = size_type(-1);

 // 24.4.2.1, construction and assignment
 constexpr basic_string_view() noexcept;
 constexpr basic_string_view(const basic_string_view&) noexcept = default;
 constexpr basic_string_view& operator=(const basic_string_view&) noexcept = default;
 constexpr basic_string_view(const charT* str);
 constexpr basic_string_view(const charT* str, size_type len);

 // 24.4.2.2, iterator support
 constexpr const_iterator begin() const noexcept;
 constexpr const_iterator end() const noexcept;
 constexpr const_iterator cbegin() const noexcept;
 constexpr const_iterator cend() const noexcept;
 constexpr const_reverse_iterator rbegin() const noexcept;
 constexpr const_reverse_iterator rend() const noexcept;
 constexpr const_reverse_iterator crbegin() const noexcept;
 constexpr const_reverse_iterator crend() const noexcept;

 // 24.4.2.3, capacity
 constexpr size_type size() const noexcept;
 constexpr size_type length() const noexcept;
 constexpr size_type max_size() const noexcept;
 constexpr bool empty() const noexcept;

 // 24.4.2.4, element access
 constexpr const_reference operator[](size_type pos) const;

```

228) Because `basic_string_view` refers to a constant sequence, `iterator` and `const_iterator` are the same type.

```

constexpr const_reference at(size_type pos) const;
constexpr const_reference front() const;
constexpr const_reference back() const;
constexpr const_pointer data() const noexcept;

// 24.4.2.5, modifiers
constexpr void remove_prefix(size_type n);
constexpr void remove_suffix(size_type n);
constexpr void swap(basic_string_view& s) noexcept;

// 24.4.2.6, string operations
size_type copy(charT* s, size_type n, size_type pos = 0) const;

constexpr basic_string_view substr(size_type pos = 0, size_type n = npos) const;
constexpr int compare(basic_string_view s) const noexcept;
constexpr int compare(size_type pos1, size_type n1, basic_string_view s) const;
constexpr int compare(size_type pos1, size_type n1, basic_string_view s,
 size_type pos2, size_type n2) const;
constexpr int compare(const charT* s) const;
constexpr int compare(size_type pos1, size_type n1, const charT* s) const;
constexpr int compare(size_type pos1, size_type n1, const charT* s,
 size_type n2) const;
constexpr size_type find(basic_string_view s, size_type pos = 0) const noexcept;
constexpr size_type find(charT c, size_type pos = 0) const noexcept;
constexpr size_type find(const charT* s, size_type pos, size_type n) const;
constexpr size_type find(const charT* s, size_type pos = 0) const;
constexpr size_type rfind(basic_string_view s, size_type pos = npos) const noexcept;
constexpr size_type rfind(charT c, size_type pos = npos) const noexcept;
constexpr size_type rfind(const charT* s, size_type pos, size_type n) const;
constexpr size_type rfind(const charT* s, size_type pos = npos) const;
constexpr size_type find_first_of(basic_string_view s, size_type pos = 0) const noexcept;
constexpr size_type find_first_of(charT c, size_type pos = 0) const noexcept;
constexpr size_type find_first_of(const charT* s, size_type pos, size_type n) const;
constexpr size_type find_first_of(const charT* s, size_type pos = 0) const;
constexpr size_type find_last_of(basic_string_view s, size_type pos = npos) const noexcept;
constexpr size_type find_last_of(charT c, size_type pos = npos) const noexcept;
constexpr size_type find_last_of(const charT* s, size_type pos, size_type n) const;
constexpr size_type find_last_of(const charT* s, size_type pos = npos) const;
constexpr size_type find_first_not_of(basic_string_view s, size_type pos = 0) const noexcept;
constexpr size_type find_first_not_of(charT c, size_type pos = 0) const noexcept;
constexpr size_type find_first_not_of(const charT* s, size_type pos,
 size_type n) const;
constexpr size_type find_first_not_of(const charT* s, size_type pos = 0) const;
constexpr size_type find_last_not_of(basic_string_view s,
 size_type pos = npos) const noexcept;
constexpr size_type find_last_not_of(charT c, size_type pos = npos) const noexcept;
constexpr size_type find_last_not_of(const charT* s, size_type pos,
 size_type n) const;
constexpr size_type find_last_not_of(const charT* s, size_type pos = npos) const;

private:
 const_pointer data_; // exposition only
 size_type size_; // exposition only
};

```

<sup>1</sup> In every specialization `basic_string_view<charT, traits>`, the type `traits` shall satisfy the character



traits requirements (24.2), and the type `traits::char_type` shall name the same type as `charT`.

#### 24.4.2.1 Construction and assignment

[string.view.cons]

```
constexpr basic_string_view() noexcept;
```

1 *Effects:* Constructs an empty `basic_string_view`.

2 *Postconditions:* `size_ == 0` and `data_ == nullptr`.

```
constexpr basic_string_view(const charT* str);
```

3 *Requires:* `[str, str + traits::length(str))` is a valid range.

4 *Effects:* Constructs a `basic_string_view`, with the postconditions in Table 64.

Table 64 — `basic_string_view(const charT*)` effects

| Element            | Value                            |
|--------------------|----------------------------------|
| <code>data_</code> | <code>str</code>                 |
| <code>size_</code> | <code>traits::length(str)</code> |

5 *Complexity:*  $\mathcal{O}(\text{traits::length(str)})$ .

```
constexpr basic_string_view(const charT* str, size_type len);
```

6 *Requires:* `[str, str + len)` is a valid range.

7 *Effects:* Constructs a `basic_string_view`, with the postconditions in Table 65.

Table 65 — `basic_string_view(const charT*, size_type)` effects

| Element            | Value            |
|--------------------|------------------|
| <code>data_</code> | <code>str</code> |
| <code>size_</code> | <code>len</code> |

#### 24.4.2.2 Iterator support

[string.view.iterators]

```
using const_iterator = implementation-defined;
```

1 A type that meets the requirements of a constant random access iterator (27.2.7) and of a contiguous iterator (27.2.1) whose `value_type` is the template parameter `charT`.

2 For a `basic_string_view` `str`, any operation that invalidates a pointer in the range `[str.data(), str.data() + str.size())` invalidates pointers, iterators, and references returned from `str`'s methods.

3 All requirements on container iterators (26.2) apply to `basic_string_view::const_iterator` as well.

```
constexpr const_iterator begin() const noexcept;
```

```
constexpr const_iterator cbegin() const noexcept;
```

4 *Returns:* An iterator such that

(4.1) — if `!empty()`, `&*begin() == data_`,

(4.2) — otherwise, an unspecified value such that `[begin(), end())` is a valid range.

```
constexpr const_iterator end() const noexcept;
```

```
constexpr const_iterator cend() const noexcept;
```

5 *Returns:* `begin() + size()`.

```
constexpr const_reverse_iterator rbegin() const noexcept;
constexpr const_reverse_iterator crbegin() const noexcept;
```

6       *Returns:* `const_reverse_iterator(end())`.

```
constexpr const_reverse_iterator rend() const noexcept;
constexpr const_reverse_iterator crend() const noexcept;
```

7       *Returns:* `const_reverse_iterator(begin())`.

#### 24.4.2.3 Capacity

[string.view.capacity]

```
constexpr size_type size() const noexcept;
```

1       *Returns:* `size_`.

```
constexpr size_type length() const noexcept;
```

2       *Returns:* `size_`.

```
constexpr size_type max_size() const noexcept;
```

3       *Returns:* The largest possible number of char-like objects that can be referred to by a `basic_string_view`.

```
constexpr bool empty() const noexcept;
```

4       *Returns:* `size_ == 0`.

#### 24.4.2.4 Element access

[string.view.access]

```
constexpr const_reference operator[](size_type pos) const;
```

1       *Requires:* `pos < size()`.

2       *Returns:* `data_[pos]`.

3       *Throws:* Nothing.

4       [ *Note:* Unlike `basic_string::operator[]`, `basic_string_view::operator[](size())` has undefined behavior instead of returning `charT()`. — *end note* ]

```
constexpr const_reference at(size_type pos) const;
```

5       *Throws:* `out_of_range` if `pos >= size()`.

6       *Returns:* `data_[pos]`.

```
constexpr const_reference front() const;
```

7       *Requires:* `!empty()`.

8       *Returns:* `data_[0]`.

9       *Throws:* Nothing.

```
constexpr const_reference back() const;
```

10      *Requires:* `!empty()`.

11      *Returns:* `data_[size() - 1]`.

12      *Throws:* Nothing.

```
constexpr const_pointer data() const noexcept;
```

13      *Returns:* `data_`.

- 14 [ *Note:* Unlike `basic_string::data()` and string literals, `data()` may return a pointer to a buffer that is not null-terminated. Therefore it is typically a mistake to pass `data()` to a function that takes just a `const charT*` and expects a null-terminated string. — *end note*]

#### 24.4.2.5 Modifiers

[string.view.modifiers]

`constexpr void remove_prefix(size_type n);`

1 *Requires:* `n <= size()`.

2 *Effects:* Equivalent to: `data_ += n; size_ -= n;`

`constexpr void remove_suffix(size_type n);`

3 *Requires:* `n <= size()`.

4 *Effects:* Equivalent to: `size_ -= n;`

`constexpr void swap(basic_string_view& s) noexcept;`

5 *Effects:* Exchanges the values of `*this` and `s`.

#### 24.4.2.6 String operations

[string.view.ops]

`size_type copy(charT* s, size_type n, size_type pos = 0) const;`

1 Let `rlen` be the smaller of `n` and `size() - pos`.

2 *Throws:* `out_of_range` if `pos > size()`.

3 *Requires:* `[s, s + rlen)` is a valid range.

4 *Effects:* Equivalent to `traits::copy(s, data() + pos, rlen)`.

5 *Returns:* `rlen`.

6 *Complexity:*  $\mathcal{O}(\text{rlen})$ .

`constexpr basic_string_view substr(size_type pos = 0, size_type n = npos) const;`

7 Let `rlen` be the smaller of `n` and `size() - pos`.

8 *Throws:* `out_of_range` if `pos > size()`.

9 *Effects:* Determines `rlen`, the effective length of the string to reference.

10 *Returns:* `basic_string_view(data() + pos, rlen)`.

`constexpr int compare(basic_string_view str) const noexcept;`

11 Let `rlen` be the smaller of `size()` and `str.size()`.

12 *Effects:* Determines `rlen`, the effective length of the strings to compare. The function then compares the two strings by calling `traits::compare(data(), str.data(), rlen)`.

13 *Complexity:*  $\mathcal{O}(\text{rlen})$ .

14 *Returns:* The nonzero result if the result of the comparison is nonzero. Otherwise, returns a value as indicated in Table 66.

`constexpr int compare(size_type pos1, size_type n1, basic_string_view str) const;`

15 *Effects:* Equivalent to: `return substr(pos1, n1).compare(str);`

`constexpr int compare(size_type pos1, size_type n1, basic_string_view str,  
size_type pos2, size_type n2) const;`

16 *Effects:* Equivalent to: `return substr(pos1, n1).compare(str.substr(pos2, n2));`

Table 66 — `compare()` results

| Condition                           | Return Value        |
|-------------------------------------|---------------------|
| <code>size() &lt; str.size()</code> | <code>&lt; 0</code> |
| <code>size() == str.size()</code>   | <code>0</code>      |
| <code>size() &gt; str.size()</code> | <code>&gt; 0</code> |

```
constexpr int compare(const charT* s) const;
```

17 *Effects:* Equivalent to: `return compare(basic_string_view(s));`

```
constexpr int compare(size_type pos1, size_type n1, const charT* s) const;
```

18 *Effects:* Equivalent to: `return substr(pos1, n1).compare(basic_string_view(s));`

```
constexpr int compare(size_type pos1, size_type n1,
 const charT* s, size_type n2) const;
```

19 *Effects:* Equivalent to: `return substr(pos1, n1).compare(basic_string_view(s, n2));`

#### 24.4.2.7 Searching

[string.view.find]

1 This section specifies the `basic_string_view` member functions named `find`, `rfind`, `find_first_of`, `find_last_of`, `find_first_not_of`, and `find_last_not_of`.

2 Member functions in this section have complexity  $\mathcal{O}(\text{size()} * \text{str.size}())$  at worst, although implementations are encouraged to do better.

3 Each member function of the form

```
constexpr return-type F(const charT* s, size_type pos);
```

is equivalent to `return F(basic_string_view(s), pos);`

4 Each member function of the form

```
constexpr return-type F(const charT* s, size_type pos, size_type n);
```

is equivalent to `return F(basic_string_view(s, n), pos);`

5 Each member function of the form

```
constexpr return-type F(charT c, size_type pos);
```

is equivalent to `return F(basic_string_view(&c, 1), pos);`

```
constexpr size_type find(basic_string_view str, size_type pos = 0) const noexcept;
```

6 Let `xpos` be the lowest position, if possible, such that the following conditions hold:

(6.1) — `pos <= xpos`

(6.2) — `xpos + str.size() <= size()`

(6.3) — `traits::eq(at(xpos + I), str.at(I))` for all elements `I` of the string referenced by `str`.

7 *Effects:* Determines `xpos`.

8 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

```
constexpr size_type rfind(basic_string_view str, size_type pos = npo) const noexcept;
```

9 Let `xpos` be the highest position, if possible, such that the following conditions hold:

(9.1) — `xpos <= pos`

- (9.2) — `xpos + str.size() <= size()`  
 (9.3) — `traits::eq(at(xpos + I), str.at(I))` for all elements `I` of the string referenced by `str`.  
 10 *Effects:* Determines `xpos`.  
 11 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`constexpr size_type find_first_of(basic_string_view str, size_type pos = 0) const noexcept;`

- 12 Let `xpos` be the lowest position, if possible, such that the following conditions hold:  
 (12.1) — `pos <= xpos`  
 (12.2) — `xpos < size()`  
 (12.3) — `traits::eq(at(xpos), str.at(I))` for some element `I` of the string referenced by `str`.  
 13 *Effects:* Determines `xpos`.  
 14 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`constexpr size_type find_last_of(basic_string_view str, size_type pos = npow) const noexcept;`

- 15 Let `xpos` be the highest position, if possible, such that the following conditions hold:  
 (15.1) — `xpos <= pos`  
 (15.2) — `xpos < size()`  
 (15.3) — `traits::eq(at(xpos), str.at(I))` for some element `I` of the string referenced by `str`.  
 16 *Effects:* Determines `xpos`.  
 17 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`constexpr size_type find_first_not_of(basic_string_view str, size_type pos = 0) const noexcept;`

- 18 Let `xpos` be the lowest position, if possible, such that the following conditions hold:  
 (18.1) — `pos <= xpos`  
 (18.2) — `xpos < size()`  
 (18.3) — `traits::eq(at(xpos), str.at(I))` for no element `I` of the string referenced by `str`.  
 19 *Effects:* Determines `xpos`.  
 20 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

`constexpr size_type find_last_not_of(basic_string_view str, size_type pos = npow) const noexcept;`

- 21 Let `xpos` be the highest position, if possible, such that the following conditions hold:  
 (21.1) — `xpos <= pos`  
 (21.2) — `xpos < size()`  
 (21.3) — `traits::eq(at(xpos), str.at(I))` for no element `I` of the string referenced by `str`.  
 22 *Effects:* Determines `xpos`.  
 23 *Returns:* `xpos` if the function can determine such a value for `xpos`. Otherwise, returns `npos`.

### 24.4.3 Non-member comparison functions [string.view.comparison]

- <sup>1</sup> Let `S` be `basic_string_view<charT, traits>`, and `sv` be an instance of `S`. Implementations shall provide sufficient additional overloads marked `constexpr` and `noexcept` so that an object `t` with an implicit conversion to `S` can be compared according to Table 67.

[*Example:* A sample conforming implementation for `operator==` would be:

Table 67 — Additional `basic_string_view` comparison overloads

| Expression              | Equivalent to              |
|-------------------------|----------------------------|
| <code>t == sv</code>    | <code>S(t) == sv</code>    |
| <code>sv == t</code>    | <code>sv == S(t)</code>    |
| <code>t != sv</code>    | <code>S(t) != sv</code>    |
| <code>sv != t</code>    | <code>sv != S(t)</code>    |
| <code>t &lt; sv</code>  | <code>S(t) &lt; sv</code>  |
| <code>sv &lt; t</code>  | <code>sv &lt; S(t)</code>  |
| <code>t &gt; sv</code>  | <code>S(t) &gt; sv</code>  |
| <code>sv &gt; t</code>  | <code>sv &gt; S(t)</code>  |
| <code>t &lt;= sv</code> | <code>S(t) &lt;= sv</code> |
| <code>sv &lt;= t</code> | <code>sv &lt;= S(t)</code> |
| <code>t &gt;= sv</code> | <code>S(t) &gt;= sv</code> |
| <code>sv &gt;= t</code> | <code>sv &gt;= S(t)</code> |

```

template<class T> using __identity = decay_t<T>;
template<class charT, class traits>
 constexpr bool operator==(basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept {
 return lhs.compare(rhs) == 0;
}
template<class charT, class traits>
 constexpr bool operator==(basic_string_view<charT, traits> lhs,
 __identity<basic_string_view<charT, traits>> rhs) noexcept {
 return lhs.compare(rhs) == 0;
}
template<class charT, class traits>
 constexpr bool operator==(__identity<basic_string_view<charT, traits>> lhs,
 basic_string_view<charT, traits> rhs) noexcept {
 return lhs.compare(rhs) == 0;
}

```

— *end example*]

```

template<class charT, class traits>
 constexpr bool operator==(basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept;

```

<sup>2</sup>     *Returns:* `lhs.compare(rhs) == 0`.

```

template<class charT, class traits>
 constexpr bool operator!=(basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept;

```

<sup>3</sup>     *Returns:* `lhs.compare(rhs) != 0`.

```

template<class charT, class traits>
 constexpr bool operator< (basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept;

```

<sup>4</sup>     *Returns:* `lhs.compare(rhs) < 0`.

```

template<class charT, class traits>
 constexpr bool operator> (basic_string_view<charT, traits> lhs,

```

```
basic_string_view<charT, traits> rhs) noexcept;
```

5 *Returns:* lhs.compare(rhs) > 0.

```
template<class charT, class traits>
constexpr bool operator<=(basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept;
```

6 *Returns:* lhs.compare(rhs) <= 0.

```
template<class charT, class traits>
constexpr bool operator>=(basic_string_view<charT, traits> lhs,
 basic_string_view<charT, traits> rhs) noexcept;
```

7 *Returns:* lhs.compare(rhs) >= 0.

#### 24.4.4 Inserters and extractors

[string.view.io]

```
template<class charT, class traits>
basic_ostream<charT, traits>&
operator<<(basic_ostream<charT, traits>& os,
 basic_string_view<charT, traits> str);
```

1 *Effects:* Behaves as a formatted output function (30.7.5.2.1) of os. Forms a character sequence seq, initially consisting of the elements defined by the range [str.begin(), str.end()). Determines padding for seq as described in 30.7.5.2.1. Then inserts seq as if by calling os.rdbuf()->sputn(seq, n), where n is the larger of os.width() and str.size(); then calls os.width(0).

2 *Returns:* os

#### 24.4.5 Hash support

[string.view.hash]

```
template<> struct hash<string_view>;
template<> struct hash<u16string_view>;
template<> struct hash<u32string_view>;
template<> struct hash<wstring_view>;
```

1 The specialization is enabled (23.14.15). [ *Note:* The hash value of a string view object is equal to the hash value of the corresponding string object (24.3.5). — *end note* ]

#### 24.4.6 Suffix for basic\_string\_view literals

[string.view.literals]

```
constexpr string_view operator""sv(const char* str, size_t len) noexcept;
```

1 *Returns:* string\_view{str, len}.

```
constexpr u16string_view operator""sv(const char16_t* str, size_t len) noexcept;
```

2 *Returns:* u16string\_view{str, len}.

```
constexpr u32string_view operator""sv(const char32_t* str, size_t len) noexcept;
```

3 *Returns:* u32string\_view{str, len}.

```
constexpr wstring_view operator""sv(const wchar_t* str, size_t len) noexcept;
```

4 *Returns:* wstring\_view{str, len}.

### 24.5 Null-terminated sequence utilities

[c.strings]

#### 24.5.1 Header <cctype> synopsis

[cctype.syn]

```
namespace std {
```

```

 int isalnum(int c);
 int isalpha(int c);
 int isblank(int c);
 int iscntrl(int c);
 int isdigit(int c);
 int isgraph(int c);
 int islower(int c);
 int isprint(int c);
 int ispunct(int c);
 int isspace(int c);
 int isupper(int c);
 int isxdigit(int c);
 int tolower(int c);
 int toupper(int c);
}

```

- <sup>1</sup> The contents and meaning of the header <cctype> are the same as the C standard library header <ctype.h>.

SEE ALSO: ISO C 7.4

### 24.5.2 Header <cwctype> synopsis

[cwctype.syn]

```

namespace std {
 using wint_t = see below;
 using wctrans_t = see below;
 using wctype_t = see below;

 int iswalnum(wint_t wc);
 int iswalpha(wint_t wc);
 int iswblank(wint_t wc);
 int iswcntrl(wint_t wc);
 int iswdigit(wint_t wc);
 int iswgraph(wint_t wc);
 int iswlower(wint_t wc);
 int iswprint(wint_t wc);
 int iswpunct(wint_t wc);
 int iswspace(wint_t wc);
 int iswupper(wint_t wc);
 int iswxdigit(wint_t wc);
 int iswctype(wint_t wc, wctype_t desc);
 wctype_t wctype(const char* property);
 wint_t towlower(wint_t wc);
 wint_t towupper(wint_t wc);
 wint_t towctrans(wint_t wc, wctrans_t desc);
 wctrans_t wctrans(const char* property);
}

#define WEOF see below

```

- <sup>1</sup> The contents and meaning of the header <cwctype> are the same as the C standard library header <wctype.h>.

SEE ALSO: ISO C 7.30

### 24.5.3 Header <cstring> synopsis

[cstring.syn]

```

namespace std {
 using size_t = see 21.2.4;

 void* memcpy(void* s1, const void* s2, size_t n);

```



```

void* memmove(void* s1, const void* s2, size_t n);
char* strcpy(char* s1, const char* s2);
char* strncpy(char* s1, const char* s2, size_t n);
char* strcat(char* s1, const char* s2);
char* strncat(char* s1, const char* s2, size_t n);
int memcmp(const void* s1, const void* s2, size_t n);
int strcmp(const char* s1, const char* s2);
int strcoll(const char* s1, const char* s2);
int strncmp(const char* s1, const char* s2, size_t n);
size_t strxfrm(char* s1, const char* s2, size_t n);
const void* memchr(const void* s, int c, size_t n); // see 20.2
void* memchr(void* s, int c, size_t n) // see 20.2
const char* strchr(const char* s, int c) // see 20.2
char* strchr(char* s, int c) // see 20.2
size_t strcspn(const char* s1, const char* s2);
const char* strpbrk(const char* s1, const char* s2) // see 20.2
char* strpbrk(char* s1, const char* s2) // see 20.2
const char* strrchr(const char* s, int c) // see 20.2
char* strrchr(char* s, int c) // see 20.2
size_t strspn(const char* s1, const char* s2);
const char* strstr(const char* s1, const char* s2) // see 20.2
char* strstr(char* s1, const char* s2) // see 20.2
char* strtok(char* s1, const char* s2);
void* memset(void* s, int c, size_t n);
char* strerror(int errnum);
size_t strlen(const char* s);
}

```

#define NULL see 21.2.3

- 1 The contents and meaning of the header <cstring> are the same as the C standard library header <string.h>.
- 2 The functions `strerror` and `strtok` are not required to avoid data races (20.5.5.9).
- 3 The functions `memcpy` and `memmove` are signal-safe (21.10.3).
- 4 [Note: The functions `strchr`, `strpbrk`, `strrchr`, `strstr`, and `memchr`, have different signatures in this International Standard, but they have the same behavior as in the C standard library (20.2). — end note]

SEE ALSO: ISO C 7.24.

#### 24.5.4 Header <wchar> synopsis

[`wchar.syn`]

```

namespace std {
 using size_t = see 21.2.4;
 using mbstate_t = see below;
 using wint_t = see below;

 struct tm;

 int fwprintf(FILE* stream, const wchar_t* format, ...);
 int fwscanf(FILE* stream, const wchar_t* format, ...);
 int swprintf(wchar_t* s, size_t n, const wchar_t* format, ...);
 int swscanf(const wchar_t* s, const wchar_t* format, ...);
 int vfwprintf(FILE* stream, const wchar_t* format, va_list arg);
 int vfwscanf(FILE* stream, const wchar_t* format, va_list arg);
 int vswprintf(wchar_t* s, size_t n, const wchar_t* format, va_list arg);
 int vswscanf(const wchar_t* s, const wchar_t* format, va_list arg);
 int vwprintf(const wchar_t* format, va_list arg);
}

```

```

int vwscanf(const wchar_t* format, va_list arg);
int wprintf(const wchar_t* format, ...);
int wscanf(const wchar_t* format, ...);
wint_t fgetwc(FILE* stream);
wchar_t* fgetws(wchar_t* s, int n, FILE* stream);
wint_t fputwc(wchar_t c, FILE* stream);
int fputws(const wchar_t* s, FILE* stream);
int fwide(FILE* stream, int mode);
wint_t getwc(FILE* stream);
wint_t getwchar();
wint_t putwc(wchar_t c, FILE* stream);
wint_t putwchar(wchar_t c);
wint_t ungetwc(wint_t c, FILE* stream);
double wcstod(const wchar_t* nptr, wchar_t** endptr);
float wcstof(const wchar_t* nptr, wchar_t** endptr);
long double wcstold(const wchar_t* nptr, wchar_t** endptr);
long int wcstol(const wchar_t* nptr, wchar_t** endptr, int base);
long long int wcstoll(const wchar_t* nptr, wchar_t** endptr, int base);
unsigned long int wcstoul(const wchar_t* nptr, wchar_t** endptr, int base);
unsigned long long int wcstoull(const wchar_t* nptr, wchar_t** endptr, int base);
wchar_t* wcsncpy(wchar_t* s1, const wchar_t* s2, size_t n);
wchar_t* wcsncpy(wchar_t* s1, const wchar_t* s2, size_t n);
wchar_t* wmemcpy(wchar_t* s1, const wchar_t* s2, size_t n);
wchar_t* wmemmove(wchar_t* s1, const wchar_t* s2, size_t n);
wchar_t* wscat(wchar_t* s1, const wchar_t* s2);
wchar_t* wcsncat(wchar_t* s1, const wchar_t* s2, size_t n);
int wscmp(const wchar_t* s1, const wchar_t* s2);
int wscoll(const wchar_t* s1, const wchar_t* s2);
int wcsncmp(const wchar_t* s1, const wchar_t* s2, size_t n);
size_t wcsxfrm(wchar_t* s1, const wchar_t* s2, size_t n);
int wmemcmp(const wchar_t* s1, const wchar_t* s2, size_t n);
const wchar_t* wcschr(const wchar_t* s, wchar_t c) // see 20.2
wchar_t* wcschr(wchar_t* s, wchar_t c) // see 20.2
size_t wcslen(const wchar_t* s, const wchar_t* s2);
const wchar_t* wcsrchr(const wchar_t* s1, const wchar_t* s2) // see 20.2
wchar_t* wcsrchr(wchar_t* s1, const wchar_t* s2) // see 20.2
const wchar_t* wcsrchr(const wchar_t* s, wchar_t c) // see 20.2
wchar_t* wcsrchr(wchar_t* s, wchar_t c) // see 20.2
size_t wcsnlen(const wchar_t* s1, const wchar_t* s2);
const wchar_t* wcsstr(const wchar_t* s1, const wchar_t* s2) // see 20.2
wchar_t* wcsstr(wchar_t* s1, const wchar_t* s2) // see 20.2
wchar_t* wcstok(wchar_t* s1, const wchar_t* s2, wchar_t** ptr);
const wchar_t* wmemchr(const wchar_t* s, wchar_t c, size_t n) // see 20.2
wchar_t* wmemchr(wchar_t* s, wchar_t c, size_t n) // see 20.2
size_t wcslen(const wchar_t* s);
wchar_t* wmemset(wchar_t* s, wchar_t c, size_t n);
size_t wcsftime(wchar_t* s, size_t maxsize, const wchar_t* format, const struct tm* timeptr);
wint_t btowc(int c);
int wctob(wint_t c);

// 24.5.6, multibyte / wide string and character conversion functions
int mbsinit(const mbstate_t* ps);
size_t mbrlen(const char* s, size_t n, mbstate_t* ps);
size_t mbrtowc(wchar_t* pwc, const char* s, size_t n, mbstate_t* ps);
size_t wctomb(char* s, wchar_t wc, mbstate_t* ps);

```

```

 size_t mbsrtowcs(wchar_t* dst, const char** src, size_t len, mbstate_t* ps);
 size_t wcsrtombs(char* dst, const wchar_t** src, size_t len, mbstate_t* ps);
}

```

```

#define NULL see 21.2.3
#define WCHAR_MAX see below
#define WCHAR_MIN see below
#define WEOF see below

```

- <sup>1</sup> The contents and meaning of the header <wchar> are the same as the C standard library header <wchar.h>, except that it does not declare a type wchar\_t.
- <sup>2</sup> [*Note:* The functions wcschr, wcpbrk, wcsrchr, wcsstr, and wmemchr have different signatures in this International Standard, but they have the same behavior as in the C standard library (20.2). — end note]

SEE ALSO: ISO C 7.29

### 24.5.5 Header <cuchar> synopsis

[cuchar.syn]

```

namespace std {
 using mbstate_t = see below;
 using size_t = see 21.2.4;

 size_t mbrtoc16(char16_t* pc16, const char* s, size_t n, mbstate_t* ps);
 size_t c16rtomb(char* s, char16_t c16, mbstate_t* ps);
 size_t mbrtoc32(char32_t* pc32, const char* s, size_t n, mbstate_t* ps);
 size_t c32rtomb(char* s, char32_t c32, mbstate_t* ps);
}

```

- <sup>1</sup> The contents and meaning of the header <cuchar> are the same as the C standard library header <uchar.h>, except that it does not declare types char16\_t nor char32\_t.

SEE ALSO: ISO C 7.28

### 24.5.6 Multibyte / wide string and character conversion functions

[c.mb.wcs]

- <sup>1</sup> [*Note:* The headers <stdlib> (21.2.2) and <wchar> (24.5.4) declare the functions described in this subclause. — end note]

```

int mbsinit(const mbstate_t* ps);
int mblen(const char* s, size_t n);
size_t mbstowcs(wchar_t* pwcs, const char* s, size_t n);
size_t wcstombs(char* s, const wchar_t* pwcs, size_t n);

```

- <sup>2</sup> *Effects:* These functions have the semantics specified in the C standard library.

SEE ALSO: ISO C 7.22.7.1, 7.22.8, 7.29.6.2.1

```

int mbtowc(wchar_t* pwc, const char* s, size_t n);
int wctomb(char* s, wchar_t wchar);

```

- <sup>3</sup> *Effects:* These functions have the semantics specified in the C standard library.

- <sup>4</sup> *Remarks:* Calls to these functions may introduce a data race (20.5.5.9) with other calls to the same function.

SEE ALSO: ISO C 7.22.7

```

size_t mbrlen(const char* s, size_t n, mbstate_t* ps);
size_t mbrtowc(wchar_t* pwc, const char* s, size_t n, mbstate_t* ps);
size_t wctomb(char* s, wchar_t wc, mbstate_t* ps);
size_t mbsrtowcs(wchar_t* dst, const char** src, size_t len, mbstate_t* ps);
size_t wcsrtombs(char* dst, const wchar_t** src, size_t len, mbstate_t* ps);

```

- 5     *Effects:* These functions have the semantics specified in the C standard library.
- 6     *Remarks:* Calling these functions with an `mbstate_t*` argument that is a null pointer value may introduce a data race (20.5.5.9) with other calls to the same function with an `mbstate_t*` argument that is a null pointer value.

SEE ALSO: ISO C 7.29.6.3

## 25 Localization library

[localization]

### 25.1 General

[localization.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to encapsulate (and therefore be more portable when confronting) cultural differences. The locale facility includes internationalization support for character classification and string collation, numeric, monetary, and date/time formatting and parsing, and message retrieval.
- <sup>2</sup> The following subclauses describe components for locales themselves, the standard facets, and facilities from the ISO C library, as summarized in Table 68.

Table 68 — Localization library summary

|                      | Subclause                  | Header(s) |
|----------------------|----------------------------|-----------|
| <a href="#">25.3</a> | Locales                    | <locale>  |
| <a href="#">25.4</a> | Standard locale Categories |           |
| <a href="#">25.5</a> | C library locales          | <clocale> |

### 25.2 Header <locale> synopsis

[locale.syn]

```

namespace std {
 // 25.3.1, locale
 class locale;
 template <class Facet> const Facet& use_facet(const locale&);
 template <class Facet> bool has_facet(const locale&) noexcept;

 // 25.3.3, convenience interfaces
 template <class charT> bool isspace (charT c, const locale& loc);
 template <class charT> bool isprint (charT c, const locale& loc);
 template <class charT> bool iscntrl (charT c, const locale& loc);
 template <class charT> bool isupper (charT c, const locale& loc);
 template <class charT> bool islower (charT c, const locale& loc);
 template <class charT> bool isalpha (charT c, const locale& loc);
 template <class charT> bool isdigit (charT c, const locale& loc);
 template <class charT> bool ispunct (charT c, const locale& loc);
 template <class charT> bool isxdigit(charT c, const locale& loc);
 template <class charT> bool isalnum (charT c, const locale& loc);
 template <class charT> bool isgraph (charT c, const locale& loc);
 template <class charT> bool isblank (charT c, const locale& loc);
 template <class charT> charT toupper(charT c, const locale& loc);
 template <class charT> charT tolower(charT c, const locale& loc);

 // 25.4.1, ctype
 class ctype_base;
 template <class charT> class ctype;
 template <> class ctype<char>; // specialization
 template <class charT> class ctype_byname;
 class codecvt_base;
 template <class internT, class externT, class stateT> class codecvt;
 template <class internT, class externT, class stateT> class codecvt_byname;

```

```

// 25.4.2, numeric
template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class num_get;
template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class num_put;
template <class charT>
 class numpunct;
template <class charT>
 class numpunct_byname;

// 25.4.4, collation
template <class charT> class collate;
template <class charT> class collate_byname;

// 25.4.5, date and time
class time_base;
template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class time_get;
template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class time_get_byname;
template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class time_put;
template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class time_put_byname;

// 25.4.6, money
class money_base;
template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class money_get;
template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class money_put;
template <class charT, bool Intl = false>
 class moneypunct;
template <class charT, bool Intl = false>
 class moneypunct_byname;

// 25.4.7, message retrieval
class messages_base;
template <class charT> class messages;
template <class charT> class messages_byname;
}

```

<sup>1</sup> The header `<locale>` defines classes and declares functions that encapsulate and manipulate the information peculiar to a locale.<sup>229</sup>

<sup>229</sup>) In this subclause, the type name `struct tm` is an incomplete type that is defined in `<ctime>`.

## 25.3 Locales

[locales]

### 25.3.1 Class locale

[locale]

```

namespace std {
 class locale {
 public:
 // types:
 class facet;
 class id;
 using category = int;
 static const category // values assigned here are for exposition only
 none = 0,
 collate = 0x010, ctype = 0x020,
 monetary = 0x040, numeric = 0x080,
 time = 0x100, messages = 0x200,
 all = collate | ctype | monetary | numeric | time | messages;

 // construct/copy/destroy:
 locale() noexcept;
 locale(const locale& other) noexcept;
 explicit locale(const char* std_name);
 explicit locale(const string& std_name);
 locale(const locale& other, const char* std_name, category);
 locale(const locale& other, const string& std_name, category);
 template <class Facet> locale(const locale& other, Facet* f);
 locale(const locale& other, const locale& one, category);
 ~locale(); // not virtual
 const locale& operator=(const locale& other) noexcept;
 template <class Facet> locale combine(const locale& other) const;

 // locale operations:
 basic_string<char> name() const;

 bool operator==(const locale& other) const;
 bool operator!=(const locale& other) const;

 template <class charT, class traits, class Allocator>
 bool operator()(const basic_string<charT, traits, Allocator>& s1,
 const basic_string<charT, traits, Allocator>& s2) const;

 // global locale objects:
 static locale global(const locale&);
 static const locale& classic();
 };
}

```

<sup>1</sup> Class `locale` implements a type-safe polymorphic set of facets, indexed by facet *type*. In other words, a facet has a dual role: in one sense, it's just a class interface; at the same time, it's an index into a locale's set of facets.

<sup>2</sup> Access to the facets of a `locale` is via two function templates, `use_facet<>` and `has_facet<>`.

<sup>3</sup> [Example: An `ostream operator<<` might be implemented as:<sup>230</sup>

```

template <class charT, class traits>
basic_ostream<charT, traits>&

```

230) Note that in the call to `put` the stream is implicitly converted to an `ostreambuf_iterator<charT, traits>`.

```

operator<< (basic_ostream<charT, traits>& s, Date d) {
 typename basic_ostream<charT, traits>::sentry cerberos(s);
 if (cerberos) {
 ios_base::iostate err = ios_base::iostate::goodbit;
 tm tmbuf; d.extract(tmbuf);
 use_facet<time_put<charT, ostreambuf_iterator<charT, traits>>> >(>
 s.getloc()).put(s, s, s.fill(), err, &tmbuf, 'x');
 s.setstate(err); // might throw
 }
 return s;
}

```

— *end example*]

- 4 In the call to `use_facet<Facet>(loc)`, the type argument chooses a facet, making available all members of the named type. If `Facet` is not present in a locale, it throws the standard exception `bad_cast`. A C++ program can check if a locale implements a particular facet with the function template `has_facet<Facet>()`. User-defined facets may be installed in a locale, and used identically as may standard facets (25.4.8).
- 5 [ *Note*: All locale semantics are accessed via `use_facet<>` and `has_facet<>`, except that:
  - (5.1) — A member operator template `operator()(const basic_string<C, T, A>&, const basic_string<C, T, A>&)` is provided so that a locale may be used as a predicate argument to the standard collections, to collate strings.
  - (5.2) — Convenient global interfaces are provided for traditional `ctype` functions such as `isdigit()` and `isspace()`, so that given a locale object `loc` a C++ program can call `isspace(c, loc)`. (This eases upgrading existing extractors (30.7.4.2).)
- *end note*]
- 6 Once a facet reference is obtained from a locale object by calling `use_facet<>`, that reference remains usable, and the results from member functions of it may be cached and re-used, as long as some locale object refers to that facet.
- 7 In successive calls to a locale facet member function on a facet object installed in the same locale, the returned result shall be identical.
- 8 A `locale` constructed from a name string (such as "POSIX"), or from parts of two named locales, has a name; all others do not. Named locales may be compared for equality; an unnamed locale is equal only to (copies of) itself. For an unnamed locale, `locale::name()` returns the string "\*".
- 9 Whether there is one global locale object for the entire program or one global locale object per thread is implementation-defined. Implementations should provide one global locale object per thread. If there is a single global locale object for the entire program, implementations are not required to avoid data races on it (20.5.5.9).

### 25.3.1.1 locale types

[`locale.types`]

#### 25.3.1.1.1 Type `locale::category`

[`locale.category`]

```
using category = int;
```

- 1 *Valid* category values include the `locale` member bitmask elements `collate`, `ctype`, `monetary`, `numeric`, `time`, and `messages`, each of which represents a single locale category. In addition, `locale` member bitmask constant `none` is defined as zero and represents no category. And `locale` member bitmask constant `all` is defined such that the expression

```
(collate | ctype | monetary | numeric | time | messages | all) == all
```

is `true`, and represents the union of all categories. Further, the expression `(X | Y)`, where `X` and `Y` each



represent a single category, represents the union of the two categories.

- <sup>2</sup> **locale** member functions expecting a **category** argument require one of the **category** values defined above, or the union of two or more such values. Such a **category** value identifies a set of locale categories. Each locale category, in turn, identifies a set of locale facets, including at least those shown in Table 69.

Table 69 — Locale category facets

| Category | Includes facets                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| collate  | collate<char>, collate<wchar_t>                                                                                                                                                |
| ctype    | ctype<char>, ctype<wchar_t><br>codecvt<char, char, mbstate_t><br>codecvt<char16_t, char, mbstate_t><br>codecvt<char32_t, char, mbstate_t><br>codecvt<wchar_t, char, mbstate_t> |
| monetary | moneypunct<char>, moneypunct<wchar_t><br>moneypunct<char, true>, moneypunct<wchar_t, true><br>money_get<char>, money_get<wchar_t><br>money_put<char>, money_put<wchar_t>       |
| numeric  | numput<char>, numput<wchar_t><br>num_get<char>, num_get<wchar_t><br>num_put<char>, num_put<wchar_t>                                                                            |
| time     | time_get<char>, time_get<wchar_t><br>time_put<char>, time_put<wchar_t>                                                                                                         |
| messages | messages<char>, messages<wchar_t>                                                                                                                                              |

- <sup>3</sup> For any locale **loc** either constructed, or returned by **locale::classic()**, and any facet **Facet** shown in Table 69, **has\_facet<Facet>(loc)** is **true**. Each locale member function which takes a **locale::category** argument operates on the corresponding set of facets.
- <sup>4</sup> An implementation is required to provide those specializations for facet templates identified as members of a category, and for those shown in Table 70.
- <sup>5</sup> The provided implementation of members of facets **num\_get<charT>** and **num\_put<charT>** calls **use\_facet<F>(1)** only for facet **F** of types **numput<charT>** and **ctype<charT>**, and for locale **l** the value obtained by calling member **getloc()** on the **ios\_base&** argument to these functions.
- <sup>6</sup> In declarations of facets, a template parameter with name **InputIterator** or **OutputIterator** indicates the set of all possible specializations on parameters that satisfy the requirements of an Input Iterator or an Output Iterator, respectively (27.2). A template parameter with name **C** represents the set of types containing **char**, **wchar\_t**, and any other implementation-defined character types that satisfy the requirements for a character on which any of the iostream components can be instantiated. A template parameter with name **International** represents the set of all possible specializations on a **bool** parameter.

#### 25.3.1.1.2 Class **locale::facet**

[locale.facet]

```
namespace std {
 class locale::facet {
 protected:
 explicit facet(size_t refs = 0);
 virtual ~facet();
 facet(const facet&) = delete;
 void operator=(const facet&) = delete;
 };
}
```

Table 70 — Required specializations

| Category | Includes facets                                                                                                                                                                                                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| collate  | collate_byname<char>, collate_byname<wchar_t>                                                                                                                                                                                                                                                                    |
| ctype    | ctype_byname<char>, ctype_byname<wchar_t><br>codecvt_byname<char, char, mbstate_t><br>codecvt_byname<char16_t, char, mbstate_t><br>codecvt_byname<char32_t, char, mbstate_t><br>codecvt_byname<wchar_t, char, mbstate_t>                                                                                         |
| monetary | moneypunct_byname<char, International><br>moneypunct_byname<wchar_t, International><br>money_get<C, InputIterator><br>money_put<C, OutputIterator>                                                                                                                                                               |
| numeric  | numpunct_byname<char>, numpunct_byname<wchar_t><br>num_get<C, InputIterator>, num_put<C, OutputIterator>                                                                                                                                                                                                         |
| time     | time_get<char, InputIterator><br>time_get_byname<char, InputIterator><br>time_get<wchar_t, InputIterator><br>time_get_byname<wchar_t, InputIterator><br>time_put<char, OutputIterator><br>time_put_byname<char, OutputIterator><br>time_put<wchar_t, OutputIterator><br>time_put_byname<wchar_t, OutputIterator> |
| messages | messages_byname<char>, messages_byname<wchar_t>                                                                                                                                                                                                                                                                  |

```

}

```

- <sup>1</sup> Class **facet** is the base class for locale feature sets. A class is a *facet* if it is publicly derived from another facet, or if it is a class derived from `locale::facet` and contains a publicly accessible declaration as follows:<sup>231</sup>

```

static ::std::locale::id id;

```

- <sup>2</sup> Template parameters in this Clause which are required to be facets are those named **Facet** in declarations. A program that passes a type that is *not* a facet, or a type that refers to a volatile-qualified facet, as an (explicit or deduced) template parameter to a locale function expecting a facet, is ill-formed. A const-qualified facet is a valid template argument to any locale function that expects a **Facet** template parameter.
- <sup>3</sup> The **refs** argument to the constructor is used for lifetime management. For **refs** == 0, the implementation performs `delete static_cast<locale::facet*>(f)` (where **f** is a pointer to the facet) when the last **locale** object containing the facet is destroyed; for **refs** == 1, the implementation never destroys the facet.
- <sup>4</sup> Constructors of all facets defined in this Clause take such an argument and pass it along to their **facet** base class constructor. All one-argument constructors defined in this Clause are *explicit*, preventing their participation in automatic conversions.
- <sup>5</sup> For some standard facets a standard “...\_byname” class, derived from it, implements the virtual function semantics equivalent to that facet of the locale constructed by `locale(const char*)` with the same name. Each such facet provides a constructor that takes a `const char*` argument, which names the locale, and a **refs** argument, which is passed to the base class constructor. Each such facet also provides a constructor that takes a **string** argument **str** and a **refs** argument, which has the same effect as calling the first constructor with the two arguments `str.c_str()` and **refs**. If there is no “...\_byname” version of a facet, the base class

231) This is a complete list of requirements; there are no other requirements. Thus, a facet class need not have a public copy constructor, assignment, default constructor, destructor, etc.

implements named locale semantics itself by reference to other facets.

#### 25.3.1.1.3 Class `locale::id`

[`locale.id`]

```
namespace std {
 class locale::id {
 public:
 id();
 void operator=(const id&) = delete;
 id(const id&) = delete;
 };
}
```

<sup>1</sup> The class `locale::id` provides identification of a locale facet interface, used as an index for lookup and to encapsulate initialization.

<sup>2</sup> [*Note:* Because facets are used by iostreams, potentially while static constructors are running, their initialization cannot depend on programmed static initialization. One initialization strategy is for `locale` to initialize each facet's `id` member the first time an instance of the facet is installed into a locale. This depends only on static storage being zero before constructors run (6.6.2). — *end note*]

#### 25.3.1.2 `locale` constructors and destructor

[`locale.cons`]

```
locale() noexcept;
```

<sup>1</sup> Default constructor: a snapshot of the current global locale.

<sup>2</sup> *Effects:* Constructs a copy of the argument last passed to `locale::global(locale&)`, if it has been called; else, the resulting facets have virtual function semantics identical to those of `locale::classic()`. [*Note:* This constructor is commonly used as the default value for arguments of functions that take a `const locale&` argument. — *end note*]

```
locale(const locale& other) noexcept;
```

<sup>3</sup> *Effects:* Constructs a locale which is a copy of `other`.

```
explicit locale(const char* std_name);
```

<sup>4</sup> *Effects:* Constructs a locale using standard C locale names, e.g., "POSIX". The resulting locale implements semantics defined to be associated with that name.

<sup>5</sup> *Throws:* `runtime_error` if the argument is not valid, or is null.

<sup>6</sup> *Remarks:* The set of valid string argument values is "C", "", and any implementation-defined values.

```
explicit locale(const string& std_name);
```

<sup>7</sup> *Effects:* The same as `locale(std_name.c_str())`.

```
locale(const locale& other, const char* std_name, category);
```

<sup>8</sup> *Effects:* Constructs a locale as a copy of `other` except for the facets identified by the `category` argument, which instead implement the same semantics as `locale(std_name)`.

<sup>9</sup> *Throws:* `runtime_error` if the argument is not valid, or is null.

<sup>10</sup> *Remarks:* The locale has a name if and only if `other` has a name.

```
locale(const locale& other, const string& std_name, category cat);
```

<sup>11</sup> *Effects:* The same as `locale(other, std_name.c_str(), cat)`.

```
template <class Facet> locale(const locale& other, Facet* f);
```

<sup>12</sup> *Effects:* Constructs a locale incorporating all facets from the first argument except that of type `Facet`,

and installs the second argument as the remaining facet. If `f` is null, the resulting object is a copy of `other`.

13 *Remarks:* The resulting locale has no name.

```
locale(const locale& other, const locale& one, category cats);
```

14 *Effects:* Constructs a locale incorporating all facets from the first argument except those that implement `cats`, which are instead incorporated from the second argument.

15 *Remarks:* The resulting locale has a name if and only if the first two arguments have names.

```
const locale& operator=(const locale& other) noexcept;
```

16 *Effects:* Creates a copy of `other`, replacing the current value.

17 *Returns:* `*this`.

```
~locale();
```

18 A non-virtual destructor that throws no exceptions.

### 25.3.1.3 locale members

[locale.members]

```
template <class Facet> locale combine(const locale& other) const;
```

1 *Effects:* Constructs a locale incorporating all facets from `*this` except for that one facet of `other` that is identified by `Facet`.

2 *Returns:* The newly created locale.

3 *Throws:* `runtime_error` if `has_facet<Facet>(other)` is false.

4 *Remarks:* The resulting locale has no name.

```
basic_string<char> name() const;
```

5 *Returns:* The name of `*this`, if it has one; otherwise, the string `" "`.

### 25.3.1.4 locale operators

[locale.operators]

```
bool operator==(const locale& other) const;
```

1 *Returns:* `true` if both arguments are the same locale, or one is a copy of the other, or each has a name and the names are identical; `false` otherwise.

```
bool operator!=(const locale& other) const;
```

2 *Returns:* `!(*this == other)`.

```
template <class charT, class traits, class Allocator>
bool operator()(const basic_string<charT, traits, Allocator>& s1,
 const basic_string<charT, traits, Allocator>& s2) const;
```

3 *Effects:* Compares two strings according to the `collate<charT>` facet.

4 *Remarks:* This member operator template (and therefore `locale` itself) satisfies requirements for a comparator predicate template argument (Clause 28) applied to strings.

5 *Returns:*

```
use_facet<collate<charT>>(*this).compare(s1.data(), s1.data() + s1.size(),
 s2.data(), s2.data() + s2.size()) < 0
```

6 [ *Example:* A vector of strings `v` can be collated according to collation rules in locale `loc` simply by (28.7.1, 26.3.11):

```
std::sort(v.begin(), v.end(), loc);
— end example]
```

### 25.3.1.5 locale static members

[locale.statics]

```
static locale global(const locale& loc);
```

1 Sets the global locale to its argument.

2 *Effects:* Causes future calls to the constructor `locale()` to return a copy of the argument. If the argument has a name, does

```
setlocale(LC_ALL, loc.name().c_str());
```

otherwise, the effect on the C locale, if any, is implementation-defined. No library function other than `locale::global()` shall affect the value returned by `locale()`. [Note: See 25.5 for data race considerations when `setlocale` is invoked. — end note]

3 *Returns:* The previous value of `locale()`.

```
static const locale& classic();
```

4 The "C" locale.

5 *Returns:* A locale that implements the classic "C" locale semantics, equivalent to the value `locale("C")`.

6 *Remarks:* This locale, its facets, and their member functions, do not change with time.

### 25.3.2 locale globals

[locale.global.templates]

```
template <class Facet> const Facet& use_facet(const locale& loc);
```

1 *Requires:* `Facet` is a facet class whose definition contains the public static member `id` as defined in 25.3.1.1.2.

2 *Returns:* A reference to the corresponding facet of `loc`, if present.

3 *Throws:* `bad_cast` if `has_facet<Facet>(loc)` is false.

4 *Remarks:* The reference returned remains valid at least as long as any copy of `loc` exists.

```
template <class Facet> bool has_facet(const locale& loc) noexcept;
```

5 *Returns:* true if the facet requested is present in `loc`; otherwise false.

### 25.3.3 Convenience interfaces

[locale.convenience]

#### 25.3.3.1 Character classification

[classification]

```
template <class charT> bool isspace (charT c, const locale& loc);
template <class charT> bool isprint (charT c, const locale& loc);
template <class charT> bool iscntrl (charT c, const locale& loc);
template <class charT> bool isupper (charT c, const locale& loc);
template <class charT> bool islower (charT c, const locale& loc);
template <class charT> bool isalpha (charT c, const locale& loc);
template <class charT> bool isdigit (charT c, const locale& loc);
template <class charT> bool ispunct (charT c, const locale& loc);
template <class charT> bool isxdigit(charT c, const locale& loc);
template <class charT> bool isalnum (charT c, const locale& loc);
template <class charT> bool isgraph (charT c, const locale& loc);
template <class charT> bool isblank (charT c, const locale& loc);
```

1 Each of these functions `isF` returns the result of the expression:

```
use_facet<ctype<charT>>(loc).is(ctype_base::F, c)
```

where *F* is the `ctype_base::mask` value corresponding to that function (25.4.1).<sup>232</sup>

### 25.3.3.2 Conversions

[conversions]

#### 25.3.3.2.1 Character conversions

[conversions.character]

```
template <class charT> charT toupper(charT c, const locale& loc);
```

<sup>1</sup> *Returns:* `use_facet<ctype<charT>>(loc).toupper(c)`.

```
template <class charT> charT tolower(charT c, const locale& loc);
```

<sup>2</sup> *Returns:* `use_facet<ctype<charT>>(loc).tolower(c)`.

## 25.4 Standard locale categories

[locale.categories]

- <sup>1</sup> Each of the standard categories includes a family of facets. Some of these implement formatting or parsing of a datum, for use by standard or users' iostream operators << and >>, as members `put()` and `get()`, respectively. Each such member function takes an `ios_base&` argument whose members `flags()`, `precision()`, and `width()`, specify the format of the corresponding datum (30.5.3). Those functions which need to use other facets call its member `getloc()` to retrieve the locale imbued there. Formatting facets use the character argument `fill` to fill out the specified width where necessary.
- <sup>2</sup> The `put()` members make no provision for error reporting. (Any failures of the `OutputIterator` argument must be extracted from the returned iterator.) The `get()` members take an `ios_base::iostate&` argument whose value they ignore, but set to `ios_base::failbit` in case of a parse error.
- <sup>3</sup> Within this clause it is unspecified whether one virtual function calls another virtual function.

### 25.4.1 The ctype category

[category.ctype]

```
namespace std {
 class ctype_base {
 public:
 using mask = T;

 // numeric values are for exposition only.
 static const mask space = 1 << 0;
 static const mask print = 1 << 1;
 static const mask cntrl = 1 << 2;
 static const mask upper = 1 << 3;
 static const mask lower = 1 << 4;
 static const mask alpha = 1 << 5;
 static const mask digit = 1 << 6;
 static const mask punct = 1 << 7;
 static const mask xdigit = 1 << 8;
 static const mask blank = 1 << 9;
 static const mask alnum = alpha | digit;
 static const mask graph = alnum | punct;
 };
}
```

- <sup>1</sup> The type `mask` is a bitmask type (20.4.2.1.4).

#### 25.4.1.1 Class template ctype

[locale.ctype]

```
namespace std {
 template <class charT>
```

<sup>232</sup>) When used in a loop, it is faster to cache the `ctype<>` facet and use it directly, or use the vector form of `ctype<>::is`.

```

class ctype : public locale::facet, public ctype_base {
public:
 using char_type = charT;

 explicit ctype(size_t refs = 0);

 bool is(mask m, charT c) const;
 const charT* is(const charT* low, const charT* high, mask* vec) const;
 const charT* scan_is(mask m, const charT* low, const charT* high) const;
 const charT* scan_not(mask m, const charT* low, const charT* high) const;
 charT toupper(charT c) const;
 const charT* toupper(charT* low, const charT* high) const;
 charT tolower(charT c) const;
 const charT* tolower(charT* low, const charT* high) const;

 charT widen(char c) const;
 const char* widen(const char* low, const char* high, charT* to) const;
 char narrow(charT c, char dfault) const;
 const charT* narrow(const charT* low, const charT* high, char dfault, char* to) const;

 static locale::id id;

protected:
 ~ctype();
 virtual bool do_is(mask m, charT c) const;
 virtual const charT* do_is(const charT* low, const charT* high, mask* vec) const;
 virtual const charT* do_scan_is(mask m, const charT* low, const charT* high) const;
 virtual const charT* do_scan_not(mask m, const charT* low, const charT* high) const;
 virtual charT do_toupper(charT) const;
 virtual const charT* do_toupper(charT* low, const charT* high) const;
 virtual charT do_tolower(charT) const;
 virtual const charT* do_tolower(charT* low, const charT* high) const;
 virtual charT do_widen(char) const;
 virtual const char* do_widen(const char* low, const char* high, charT* dest) const;
 virtual char do_narrow(charT, char dfault) const;
 virtual const charT* do_narrow(const charT* low, const charT* high,
 char dfault, char* dest) const;
};

```

<sup>1</sup> Class `ctype` encapsulates the C library `<cctype>` features. `istream` members are required to use `ctype<>` for character classing during input parsing.

<sup>2</sup> The specializations required in Table 69 (25.3.1.1.1), namely `ctype<char>` and `ctype<wchar_t>`, implement character classing appropriate to the implementation's native character set.

#### 25.4.1.1.1 `ctype` members

[`locale.ctype.members`]

```

bool is(mask m, charT c) const;
const charT* is(const charT* low, const charT* high,
 mask* vec) const;

```

<sup>1</sup> *Returns:* `do_is(m, c)` or `do_is(low, high, vec)`.

```

const charT* scan_is(mask m,
 const charT* low, const charT* high) const;

```

<sup>2</sup> *Returns:* `do_scan_is(m, low, high)`.

```
const charT* scan_not(mask m,
 const charT* low, const charT* high) const;
```

3     *Returns:* do\_scan\_not(m, low, high).

```
charT toupper(charT c) const;
const charT* toupper(charT* low, const charT* high) const;
```

4     *Returns:* do\_toupper(c) or do\_toupper(low, high).

```
charT tolower(charT c) const;
const charT* tolower(charT* low, const charT* high) const;
```

5     *Returns:* do\_tolower(c) or do\_tolower(low, high).

```
charT widen(char c) const;
const char* widen(const char* low, const char* high, charT* to) const;
```

6     *Returns:* do\_widen(c) or do\_widen(low, high, to).

```
char narrow(charT c, char dfault) const;
const charT* narrow(const charT* low, const charT* high, char dfault,
 char* to) const;
```

7     *Returns:* do\_narrow(c, dfault) or do\_narrow(low, high, dfault, to).

#### 25.4.1.1.2 ctype virtual functions [locale.ctype.virtuals]

```
bool do_is(mask m, charT c) const;
const charT* do_is(const charT* low, const charT* high,
 mask* vec) const;
```

1     *Effects:* Classifies a character or sequence of characters. For each argument character, identifies a value M of type `ctype_base::mask`. The second form identifies a value M of type `ctype_base::mask` for each \*p where (low <= p && p < high), and places it into vec[p - low].

2     *Returns:* The first form returns the result of the expression (M & m) != 0; i.e., true if the character has the characteristics specified. The second form returns high.

```
const charT* do_scan_is(mask m, const charT* low, const charT* high) const;
```

3     *Effects:* Locates a character in a buffer that conforms to a classification m.

4     *Returns:* The smallest pointer p in the range [low, high) such that is(m, \*p) would return true; otherwise, returns high.

```
const charT* do_scan_not(mask m, const charT* low, const charT* high) const;
```

5     *Effects:* Locates a character in a buffer that fails to conform to a classification m.

6     *Returns:* The smallest pointer p, if any, in the range [low, high) such that is(m, \*p) would return false; otherwise, returns high.

```
charT do_toupper(charT c) const;
const charT* do_toupper(charT* low, const charT* high) const;
```

7     *Effects:* Converts a character or characters to upper case. The second form replaces each character \*p in the range [low, high) for which a corresponding upper-case character exists, with that character.

8     *Returns:* The first form returns the corresponding upper-case character if it is known to exist, or its argument if not. The second form returns high.

```
charT do_tolower(charT c) const;
```



```
const charT* do_tolower(charT* low, const charT* high) const;
```

9 *Effects:* Converts a character or characters to lower case. The second form replaces each character *\*p* in the range `[low, high)` and for which a corresponding lower-case character exists, with that character.

10 *Returns:* The first form returns the corresponding lower-case character if it is known to exist, or its argument if not. The second form returns `high`.

```
charT do_widen(char c) const;
const char* do_widen(const char* low, const char* high,
 charT* dest) const;
```

11 *Effects:* Applies the simplest reasonable transformation from a `char` value or sequence of `char` values to the corresponding `charT` value or values.<sup>233</sup> The only characters for which unique transformations are required are those in the basic source character set (5.3).

For any named `ctype` category with a `ctype<charT>` facet `ctc` and valid `ctype_base::mask` value `M`, `(ctc.is(M, c) || !is(M, do_widen(c)) )` is true.<sup>234</sup>

The second form transforms each character *\*p* in the range `[low, high)`, placing the result in `dest[p - low]`.

12 *Returns:* The first form returns the transformed value. The second form returns `high`.

```
char do_narrow(charT c, char ddefault) const;
const charT* do_narrow(const charT* low, const charT* high,
 char ddefault, char* dest) const;
```

13 *Effects:* Applies the simplest reasonable transformation from a `charT` value or sequence of `charT` values to the corresponding `char` value or values.

For any character `c` in the basic source character set (5.3) the transformation is such that

```
do_widen(do_narrow(c, 0)) == c
```

For any named `ctype` category with a `ctype<char>` facet `ctc` however, and `ctype_base::mask` value `M`,

```
(is(M, c) || !ctc.is(M, do_narrow(c, ddefault)))
```

is true (unless `do_narrow` returns `ddefault`). In addition, for any digit character `c`, the expression `(do_narrow(c, ddefault) - '0')` evaluates to the digit value of the character. The second form transforms each character *\*p* in the range `[low, high)`, placing the result (or `ddefault` if no simple transformation is readily available) in `dest[p - low]`.

14 *Returns:* The first form returns the transformed value; or `ddefault` if no mapping is readily available. The second form returns `high`.

#### 25.4.1.2 Class template `ctype_byname`

[`locale.ctype.byname`]

```
namespace std {
 template <class charT>
 class ctype_byname : public ctype<charT> {
 public:
 using mask = typename ctype<charT>::mask;
 explicit ctype_byname(const char*, size_t refs = 0);
 explicit ctype_byname(const string&, size_t refs = 0);
 protected:
 ~ctype_byname();
 };
```

233) The `char` argument of `do_widen` is intended to accept values derived from character literals for conversion to the locale's encoding.

234) In other words, the transformed character is not a member of any character classification that `c` is not also a member of.

```
};
}
```

### 25.4.1.3 ctype specializations

[facet.ctype.special]

```
namespace std {
 template <>
 class ctype<char> : public locale::facet, public ctype_base {
 public:
 using char_type = char;

 explicit ctype(const mask* tab = 0, bool del = false,
 size_t refs = 0);

 bool is(mask m, char c) const;
 const char* is(const char* low, const char* high, mask* vec) const;
 const char* scan_is (mask m,
 const char* low, const char* high) const;
 const char* scan_not(mask m,
 const char* low, const char* high) const;

 char toupper(char c) const;
 const char* toupper(char* low, const char* high) const;
 char tolower(char c) const;
 const char* tolower(char* low, const char* high) const;

 char widen(char c) const;
 const char* widen(const char* low, const char* high, char* to) const;
 char narrow(char c, char dfault) const;
 const char* narrow(const char* low, const char* high, char dfault,
 char* to) const;

 static locale::id id;
 static const size_t table_size = implementation-defined;

 const mask* table() const noexcept;
 static const mask* classic_table() noexcept;

 protected:
 ~ctype();
 virtual char do_toupper(char c) const;
 virtual const char* do_toupper(char* low, const char* high) const;
 virtual char do_tolower(char c) const;
 virtual const char* do_tolower(char* low, const char* high) const;

 virtual char do_widen(char c) const;
 virtual const char* do_widen(const char* low,
 const char* high,
 char* to) const;
 virtual char do_narrow(char c, char dfault) const;
 virtual const char* do_narrow(const char* low,
 const char* high,
 char dfault, char* to) const;
 };
}
```

<sup>1</sup> A specialization `ctype<char>` is provided so that the member functions on type `char` can be implemented

inline.<sup>235</sup> The implementation-defined value of member `table_size` is at least 256.

#### 25.4.1.3.1 `ctype<char>` destructor [facet.ctype.char.dtor]

```
~ctype();
```

- <sup>1</sup> *Effects:* If the constructor's first argument was nonzero, and its second argument was `true`, does `delete [] table()`.

#### 25.4.1.3.2 `ctype<char>` members [facet.ctype.char.members]

- <sup>1</sup> In the following member descriptions, for `unsigned char` values `v` where `v >= table_size`, `table()[v]` is assumed to have an implementation-specific value (possibly different for each such value `v`) without performing the array lookup.

```
explicit ctype(const mask* tbl = 0, bool del = false,
 size_t refs = 0);
```

- <sup>2</sup> *Requires:* `tbl` either 0 or an array of at least `table_size` elements.

- <sup>3</sup> *Effects:* Passes its `refs` argument to its base class constructor.

```
bool is(mask m, char c) const;
const char* is(const char* low, const char* high,
 mask* vec) const;
```

- <sup>4</sup> *Effects:* The second form, for all `*p` in the range `[low, high)`, assigns into `vec[p - low]` the value `table()[ (unsigned char)*p]`.

- <sup>5</sup> *Returns:* The first form returns `table()[ (unsigned char)c] & m`; the second form returns `high`.

```
const char* scan_is(mask m,
 const char* low, const char* high) const;
```

- <sup>6</sup> *Returns:* The smallest `p` in the range `[low, high)` such that `table()[ (unsigned char) *p] & m` is `true`.

```
const char* scan_not(mask m,
 const char* low, const char* high) const;
```

- <sup>7</sup> *Returns:* The smallest `p` in the range `[low, high)` such that `table()[ (unsigned char) *p] & m` is `false`.

```
char toupper(char c) const;
const char* toupper(char* low, const char* high) const;
```

- <sup>8</sup> *Returns:* `do_toupper(c)` or `do_toupper(low, high)`, respectively.

```
char tolower(char c) const;
const char* tolower(char* low, const char* high) const;
```

- <sup>9</sup> *Returns:* `do_tolower(c)` or `do_tolower(low, high)`, respectively.

```
char widen(char c) const;
const char* widen(const char* low, const char* high,
 char* to) const;
```

---

<sup>235</sup> Only the `char` (not `unsigned char` and `signed char`) form is provided. The specialization is specified in the standard, and not left as an implementation detail, because it affects the derivation interface for `ctype<char>`.

10 *Returns:* `do_widen(c)` or `do_widen(low, high, to)`, respectively.

```
char narrow(char c, char dfaul) const;
const char* narrow(const char* low, const char* high,
 char dfaul, char* to) const;
```

11 *Returns:* `do_narrow(c, dfaul)` or `do_narrow(low, high, dfaul, to)`, respectively.

```
const mask* table() const noexcept;
```

12 *Returns:* The first constructor argument, if it was nonzero, otherwise `classic_table()`.

### 25.4.1.3.3 `ctype<char>` static members [facet.ctype.char.statics]

```
static const mask* classic_table() noexcept;
```

1 *Returns:* A pointer to the initial element of an array of size `table_size` which represents the classifications of characters in the "C" locale.

### 25.4.1.3.4 `ctype<char>` virtual functions [facet.ctype.char.virtuals]

```
char do_toupper(char) const;
const char* do_toupper(char* low, const char* high) const;
char do_tolower(char) const;
const char* do_tolower(char* low, const char* high) const;

virtual char do_widen(char c) const;
virtual const char* do_widen(const char* low,
 const char* high,
 char* to) const;
virtual char do_narrow(char c, char dfaul) const;
virtual const char* do_narrow(const char* low,
 const char* high,
 char dfaul, char* to) const;
```

These functions are described identically as those members of the same name in the `ctype` class template (25.4.1.1.1).

### 25.4.1.4 Class template `codecvt` [locale.codecvt]

```
namespace std {
 class codecvt_base {
 public:
 enum result { ok, partial, error, noconv };
 };

 template <class internT, class externT, class stateT>
 class codecvt : public locale::facet, public codecvt_base {
 public:
 using intern_type = internT;
 using extern_type = externT;
 using state_type = stateT;

 explicit codecvt(size_t refs = 0);

 result out(
 stateT& state,
 const internT* from, const internT* from_end, const internT*& from_next,
 externT* to, externT* to_end, externT*& to_next) const;
```

```

 result unshift(
 stateT& state,
 externT* to, externT* to_end, externT*& to_next) const;

 result in(
 stateT& state,
 const externT* from, const externT* from_end, const externT*& from_next,
 internT* to, internT* to_end, internT*& to_next) const;

 int encoding() const noexcept;
 bool always_noconv() const noexcept;
 int length(stateT&, const externT* from, const externT* end, size_t max) const;
 int max_length() const noexcept;

 static locale::id id;

protected:
 ~codecvt();
 virtual result do_out(
 stateT& state,
 const internT* from, const internT* from_end, const internT*& from_next,
 externT* to, externT* to_end, externT*& to_next) const;
 virtual result do_in(
 stateT& state,
 const externT* from, const externT* from_end, const externT*& from_next,
 internT* to, internT* to_end, internT*& to_next) const;
 virtual result do_unshift(
 stateT& state,
 externT* to, externT* to_end, externT*& to_next) const;

 virtual int do_encoding() const noexcept;
 virtual bool do_always_noconv() const noexcept;
 virtual int do_length(stateT&, const externT* from, const externT* end, size_t max) const;
 virtual int do_max_length() const noexcept;
};
}

```

- <sup>1</sup> The class `codecvt<internT, externT, stateT>` is for use when converting from one character encoding to another, such as from wide characters to multibyte characters or between wide character encodings such as Unicode and EUC.
- <sup>2</sup> The `stateT` argument selects the pair of character encodings being mapped between.
- <sup>3</sup> The specializations required in Table 69 (25.3.1.1.1) convert the implementation-defined native character set. `codecvt<char, char, mbstate_t>` implements a degenerate conversion; it does not convert at all. The specialization `codecvt<char16_t, char, mbstate_t>` converts between the UTF-16 and UTF-8 encoding forms, and the specialization `codecvt<char32_t, char, mbstate_t>` converts between the UTF-32 and UTF-8 encoding forms. `codecvt<wchar_t, char, mbstate_t>` converts between the native character sets for narrow and wide characters. Specializations on `mbstate_t` perform conversion between encodings known to the library implementer. Other encodings can be converted by specializing on a user-defined `stateT` type. Objects of type `stateT` can contain any state that is useful to communicate to or from the specialized `do_in` or `do_out` members.

#### 25.4.1.4.1 `codecvt` members

[`locale.codecvt.members`]

```

result out(
 stateT& state,

```

```
const internT* from, const internT* from_end, const internT*& from_next,
externT* to, externT* to_end, externT*& to_next) const;
```

1     *Returns:* do\_out(state, from, from\_end, from\_next, to, to\_end, to\_next).

```
result unshift(stateT& state, externT* to, externT* to_end, externT*& to_next) const;
```

2     *Returns:* do\_unshift(state, to, to\_end, to\_next).

```
result in(
 stateT& state,
 const externT* from, const externT* from_end, const externT*& from_next,
 internT* to, internT* to_end, internT*& to_next) const;
```

3     *Returns:* do\_in(state, from, from\_end, from\_next, to, to\_end, to\_next).

```
int encoding() const noexcept;
```

4     *Returns:* do\_encoding().

```
bool always_noconv() const noexcept;
```

5     *Returns:* do\_always\_noconv().

```
int length(stateT& state, const externT* from, const externT* from_end, size_t max) const;
```

6     *Returns:* do\_length(state, from, from\_end, max).

```
int max_length() const noexcept;
```

7     *Returns:* do\_max\_length().

#### 25.4.1.4.2 codecvt virtual functions

[locale.codecvt.virtuals]

```
result do_out(
 stateT& state,
 const internT* from, const internT* from_end, const internT*& from_next,
 externT* to, externT* to_end, externT*& to_next) const;
```

```
result do_in(
 stateT& state,
 const externT* from, const externT* from_end, const externT*& from_next,
 internT* to, internT* to_end, internT*& to_next) const;
```

1     *Requires:* (from <= from\_end && to <= to\_end) well-defined and true; state initialized, if at the beginning of a sequence, or else equal to the result of converting the preceding characters in the sequence.

2     *Effects:* Translates characters in the source range [from, from\_end), placing the results in sequential positions starting at destination to. Converts no more than (from\_end - from) source elements, and stores no more than (to\_end - to) destination elements.

Stops if it encounters a character it cannot convert. It always leaves the from\_next and to\_next pointers pointing one beyond the last element successfully converted. If returns noconv, internT and externT are the same type and the converted sequence is identical to the input sequence [from, from\_next). to\_next is set equal to to, the value of state is unchanged, and there are no changes to the values in [to, to\_end).

3     A codecvt facet that is used by basic\_filebuf (30.9) shall have the property that if

```
do_out(state, from, from_end, from_next, to, to_end, to_next)
would return ok, where from != from_end, then
```

```
do_out(state, from, from + 1, from_next, to, to_end, to_next)
```

shall also return `ok`, and that if

```
do_in(state, from, from_end, from_next, to, to_end, to_next)
```

would return `ok`, where `to != to_end`, then

```
do_in(state, from, from_end, from_next, to, to + 1, to_next)
```

shall also return `ok`.<sup>236</sup> [ *Note:* As a result of operations on `state`, it can return `ok` or `partial` and set `from_next == from` and `to_next != to`. — *end note* ]

4 *Remarks:* Its operations on `state` are unspecified. [ *Note:* This argument can be used, for example, to maintain shift state, to specify conversion options (such as count only), or to identify a cache of seek offsets. — *end note* ]

5 *Returns:* An enumeration value, as summarized in Table 71.

Table 71 — `do_in/do_out` result values

| Value                | Meaning                                                                                                                |
|----------------------|------------------------------------------------------------------------------------------------------------------------|
| <code>ok</code>      | completed the conversion                                                                                               |
| <code>partial</code> | not all source characters converted                                                                                    |
| <code>error</code>   | encountered a character in <code>[from, from_end)</code> that it could not convert                                     |
| <code>noconv</code>  | <code>internT</code> and <code>externT</code> are the same type, and input sequence is identical to converted sequence |

A return value of `partial`, if `(from_next == from_end)`, indicates that either the destination sequence has not absorbed all the available destination elements, or that additional source elements are needed before another destination element can be produced.

```
result do_unshift(stateT& state, externT* to, externT* to_end, externT*& to_next) const;
```

6 *Requires:* `(to <= to_end)` well defined and `true`; state initialized, if at the beginning of a sequence, or else equal to the result of converting the preceding characters in the sequence.

7 *Effects:* Places characters starting at `to` that should be appended to terminate a sequence when the current `stateT` is given by `state`.<sup>237</sup> Stores no more than `(to_end - to)` destination elements, and leaves the `to_next` pointer pointing one beyond the last element successfully stored.

8 *Returns:* An enumeration value, as summarized in Table 72.

Table 72 — `do_unshift` result values

| Value                | Meaning                                                                                                                                    |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <code>ok</code>      | completed the sequence                                                                                                                     |
| <code>partial</code> | space for more than <code>to_end - to</code> destination elements was needed to terminate a sequence given the value of <code>state</code> |
| <code>error</code>   | an unspecified error has occurred                                                                                                          |
| <code>noconv</code>  | no termination is needed for this <code>state_type</code>                                                                                  |

236) Informally, this means that `basic_filebuf` assumes that the mappings from internal to external characters is 1 to N: a `codecvt` facet that is used by `basic_filebuf` must be able to translate characters one internal character at a time.

237) Typically these will be characters to return the state to `stateT()`.

```
int do_encoding() const noexcept;
```

- 9 *Returns:* -1 if the encoding of the `externT` sequence is state-dependent; else the constant number of `externT` characters needed to produce an internal character; or 0 if this number is not a constant.<sup>238</sup>

```
bool do_always_noconv() const noexcept;
```

- 10 *Returns:* true if `do_in()` and `do_out()` return `noconv` for all valid argument values. `codecvt<char, char, mbstate_t>` returns true.

```
int do_length(stateT& state, const externT* from, const externT* from_end, size_t max) const;
```

- 11 *Requires:* (`from <= from_end`) well-defined and true; `state` initialized, if at the beginning of a sequence, or else equal to the result of converting the preceding characters in the sequence.

- 12 *Effects:* The effect on the `state` argument is “as if” it called `do_in(state, from, from_end, from, to, to+max, to)` for `to` pointing to a buffer of at least `max` elements.

- 13 *Returns:* (`from_next-from`) where `from_next` is the largest value in the range [`from`, `from_end`] such that the sequence of values in the range [`from`, `from_next`) represents `max` or fewer valid complete characters of type `internT`. The specialization `codecvt<char, char, mbstate_t>`, returns the lesser of `max` and (`from_end-from`).

```
int do_max_length() const noexcept;
```

- 14 *Returns:* The maximum value that `do_length(state, from, from_end, 1)` can return for any valid range [`from`, `from_end`) and `stateT` value `state`. The specialization `codecvt<char, char, mbstate_t>::do_max_length()` returns 1.

#### 25.4.1.5 Class template `codecvt_byname`

[locale.codecvt.byname]

```
namespace std {
 template <class internT, class externT, class stateT>
 class codecvt_byname : public codecvt<internT, externT, stateT> {
 public:
 explicit codecvt_byname(const char*, size_t refs = 0);
 explicit codecvt_byname(const string&, size_t refs = 0);
 protected:
 ~codecvt_byname();
 };
}
```

#### 25.4.2 The numeric category

[category.numeric]

- 1 The classes `num_get<>` and `num_put<>` handle numeric formatting and parsing. Virtual functions are provided for several numeric types. Implementations may (but are not required to) delegate extraction of smaller types to extractors for larger types.<sup>239</sup>
- 2 All specifications of member functions for `num_put` and `num_get` in the subclauses of 25.4.2 only apply to the specializations required in Tables 69 and 70 (25.3.1.1.1), namely `num_get<char>`, `num_get<wchar_t>`, `num_get<C, InputIterator>`, `num_put<char>`, `num_put<wchar_t>`, and `num_put<C, OutputIterator>`. These specializations refer to the `ios_base&` argument for formatting specifications (25.4), and to its imbued locale for the `num_punct<>` facet to identify all numeric punctuation preferences, and also for the `ctype<>` facet to perform character classification.

<sup>238</sup>) If `encoding()` yields -1, then more than `max_length()` `externT` elements may be consumed when producing a single `internT` character, and additional `externT` elements may appear at the end of a sequence after those that yield the final `internT` character.

<sup>239</sup>) Parsing “-1” correctly into, e.g., an `unsigned short` requires that the corresponding member `get()` at least extract the sign before delegating.



- <sup>3</sup> Extractor and inserter members of the standard iostreams use `num_get<>` and `num_put<>` member functions for formatting and parsing numeric values (30.7.4.2.1, 30.7.5.2.1).

#### 25.4.2.1 Class template `num_get`

[`locale.num.get`]

```
namespace std {
 template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class num_get : public locale::facet {
 public:
 using char_type = charT;
 using iter_type = InputIterator;

 explicit num_get(size_t refs = 0);

 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, bool& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, long& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, long long& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, unsigned short& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, unsigned int& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, unsigned long& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, unsigned long long& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, float& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, double& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, long double& v) const;
 iter_type get(iter_type in, iter_type end, ios_base&,
 ios_base::iostate& err, void*& v) const;

 static locale::id id;

 protected:
 ~num_get();
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, bool& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, long& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, long long& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, unsigned short& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, unsigned int& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, unsigned long& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, unsigned long long& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, void*& v) const;
 };
}
```

```

 ios_base::iostate& err, float& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, double& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, long double& v) const;
 virtual iter_type do_get(iter_type, iter_type, ios_base&,
 ios_base::iostate& err, void*& v) const;
};
}

```

<sup>1</sup> The facet `num_get` is used to parse numeric values from an input sequence such as an istream.

#### 25.4.2.1.1 `num_get` members

[facet.num.get.members]

```

iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, bool& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long long& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned short& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned int& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned long& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned long long& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, float& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, double& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long double& val) const;
iter_type get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, void*& val) const;

```

<sup>1</sup> *Returns:* `do_get(in, end, str, err, val)`.

#### 25.4.2.1.2 `num_get` virtual functions

[facet.num.get.virtuals]

```

iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long long& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned short& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned int& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned long& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, unsigned long long& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, float& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, double& val) const;

```

```

iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, long double& val) const;
iter_type do_get(iter_type in, iter_type end, ios_base& str,
 ios_base::iostate& err, void*& val) const;

```

<sup>1</sup> *Effects:* Reads characters from `in`, interpreting them according to `str.flags()`, `use_facet<ctype<charT>>(loc)`, and `use_facet<num_punct<charT>>(loc)`, where `loc` is `str.getloc()`.

<sup>2</sup> The details of this operation occur in three stages

(2.1) — Stage 1: Determine a conversion specifier

(2.2) — Stage 2: Extract characters from `in` and determine a corresponding `char` value for the format expected by the conversion specification determined in stage 1.

(2.3) — Stage 3: Store results

<sup>3</sup> The details of the stages are presented below.

**Stage 1:** The function initializes local variables via

```

fmtflags flags = str.flags();
fmtflags basefield = (flags & ios_base::basefield);
fmtflags uppercase = (flags & ios_base::uppercase);
fmtflags boolalpha = (flags & ios_base::boolalpha);

```

For conversion to an integral type, the function determines the integral conversion specifier as indicated in Table 73. The table is ordered. That is, the first line whose condition is true applies.

Table 73 — Integer conversions

| State                         | stdio equivalent |
|-------------------------------|------------------|
| <code>basefield == oct</code> | <code>%o</code>  |
| <code>basefield == hex</code> | <code>%X</code>  |
| <code>basefield == 0</code>   | <code>%i</code>  |
| signed integral type          | <code>%d</code>  |
| unsigned integral type        | <code>%u</code>  |

For conversions to a floating type the specifier is `%g`.

For conversions to `void*` the specifier is `%p`.

A length modifier is added to the conversion specification, if needed, as indicated in Table 74.

Table 74 — Length modifier

| Type                            | Length modifier |
|---------------------------------|-----------------|
| <code>short</code>              | <code>h</code>  |
| <code>unsigned short</code>     | <code>h</code>  |
| <code>long</code>               | <code>l</code>  |
| <code>unsigned long</code>      | <code>l</code>  |
| <code>long long</code>          | <code>ll</code> |
| <code>unsigned long long</code> | <code>ll</code> |
| <code>double</code>             | <code>l</code>  |
| <code>long double</code>        | <code>L</code>  |

**Stage 2:** If `in == end` then stage 2 terminates. Otherwise a `charT` is taken from `in` and local variables are initialized as if by

```

char_type ct = *in;
char c = src[find(atoms, atoms + sizeof(src) - 1, ct) - atoms];
if (ct == use_facet<num_punct<charT>>(loc).decimal_point())
 c = '.';
bool discard =
 ct == use_facet<num_punct<charT>>(loc).thousands_sep()
 && use_facet<num_punct<charT>>(loc).grouping().length() != 0;
where the values src and atoms are defined as if by:
static const char src[] = "0123456789abcdefxABCDEFX+--";
char_type atoms[sizeof(src)];
use_facet<ctype<charT>>(loc).widen(src, src + sizeof(src), atoms);

```

for this value of `loc`.

If `discard` is `true`, then if `'.'` has not yet been accumulated, then the position of the character is remembered, but the character is otherwise ignored. Otherwise, if `'.'` has already been accumulated, the character is discarded and Stage 2 terminates. If it is not discarded, then a check is made to determine if `c` is allowed as the next character of an input field of the conversion specifier returned by Stage 1. If so, it is accumulated.

If the character is either discarded or accumulated then `in` is advanced by `++in` and processing returns to the beginning of stage 2.

**Stage 3:** The sequence of `chars` accumulated in stage 2 (the field) is converted to a numeric value by the rules of one of the functions declared in the header `<cstdlib>`:

- (3.1) — For a signed integer value, the function `strtoll`.
- (3.2) — For an unsigned integer value, the function `strtoull`.
- (3.3) — For a `float` value, the function `strtof`.
- (3.4) — For a `double` value, the function `strtod`.
- (3.5) — For a long double value, the function `strtold`.

The numeric value to be stored can be one of:

- (3.6) — zero, if the conversion function does not convert the entire field.
- (3.7) — the most positive (or negative) representable value, if the field to be converted to a signed integer type represents a value too large positive (or negative) to be represented in `val`.
- (3.8) — the most positive representable value, if the field to be converted to an unsigned integer type represents a value that cannot be represented in `val`.
- (3.9) — the converted value, otherwise.

The resultant numeric value is stored in `val`. If the conversion function does not convert the entire field, or if the field represents a value outside the range of representable values, `ios_base::failbit` is assigned to `err`.

4 Digit grouping is checked. That is, the positions of discarded separators is examined for consistency with `use_facet<num_punct<charT>>(loc).grouping()`. If they are not consistent then `ios_base::failbit` is assigned to `err`.

5 In any case, if stage 2 processing was terminated by the test for `in == end` then `err |= ios_base::eofbit` is performed.

```

iter_type do_get(iter_type in, iter_type end, ios_base& str,
ios_base::iostate& err, bool& val) const;

```

6 *Effects:* If `(str.flags() & ios_base::boolalpha) == 0` then input proceeds as it would for a `long` except that if a value is being stored into `val`, the value is determined according to the following: If the value to be stored is 0 then `false` is stored. If the value is 1 then `true` is stored. Otherwise `true` is stored and `ios_base::failbit` is assigned to `err`.

- 7 Otherwise target sequences are determined “as if” by calling the members `falsename()` and `truename()` of the facet obtained by `use_facet<num_punct<charT>>(str.getloc())`. Successive characters in the range `[in, end)` (see 26.2.3) are obtained and matched against corresponding positions in the target sequences only as necessary to identify a unique match. The input iterator `in` is compared to `end` only when necessary to obtain a character. If a target sequence is uniquely matched, `val` is set to the corresponding value. Otherwise `false` is stored and `ios_base::failbit` is assigned to `err`.
- 8 The `in` iterator is always left pointing one position beyond the last character successfully matched. If `val` is set, then `err` is set to `str.goodbit`; or to `str.eofbit` if, when seeking another character to match, it is found that `(in == end)`. If `val` is not set, then `err` is set to `str.failbit`; or to `(str.failbit|str.eofbit)` if the reason for the failure was that `(in == end)`. [Example: For targets `true: "a"` and `false: "abb"`, the input sequence `"a"` yields `val == true` and `err == str.eofbit`; the input sequence `"abc"` yields `err = str.failbit`, with `in` ending at the `'c'` element. For targets `true: "1"` and `false: "0"`, the input sequence `"1"` yields `val == true` and `err == str.goodbit`. For empty targets `( "")`, any input sequence yields `err == str.failbit`. — end example]
- 9 *Returns:* `in`.

#### 25.4.2.2 Class template `num_put`

[locale.nm.put]

```
namespace std {
 template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class num_put : public locale::facet {
 public:
 using char_type = charT;
 using iter_type = OutputIterator;

 explicit num_put(size_t refs = 0);

 iter_type put(iter_type s, ios_base& f, char_type fill, bool v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, long v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, long long v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, unsigned long v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, unsigned long long v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, double v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, long double v) const;
 iter_type put(iter_type s, ios_base& f, char_type fill, const void* v) const;

 static locale::id id;

 protected:
 ~num_put();
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, bool v) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, long v) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, long long v) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, unsigned long) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, unsigned long long) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, double v) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, long double v) const;
 virtual iter_type do_put(iter_type, ios_base&, char_type fill, const void* v) const;
 };
 };
```

- 1 The facet `num_put` is used to format numeric values to a character sequence such as an ostream.

##### 25.4.2.2.1 `num_put` members

[facet.num.put.members]

```

iter_type put(iter_type out, ios_base& str, char_type fill, bool val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, long val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, long long val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, unsigned long val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, unsigned long long val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, double val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, long double val) const;
iter_type put(iter_type out, ios_base& str, char_type fill, const void* val) const;

```

1 *Returns:* do\_put(out, str, fill, val).

#### 25.4.2.2.2 num\_put virtual functions

[facet.num.put.virtuals]

```

iter_type do_put(iter_type out, ios_base& str, char_type fill, long val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, long long val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, unsigned long val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, unsigned long long val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, double val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, long double val) const;
iter_type do_put(iter_type out, ios_base& str, char_type fill, const void* val) const;

```

1 *Effects:* Writes characters to the sequence out, formatting val as desired. In the following description, a local variable initialized with:

```
locale loc = str.getloc();
```

2 The details of this operation occur in several stages:

(2.1) — Stage 1: Determine a printf conversion specifier **spec** and determine the characters that would be printed by **printf** (30.11) given this conversion specifier for

```
printf(spec, val)
```

assuming that the current locale is the "C" locale.

(2.2) — Stage 2: Adjust the representation by converting each **char** determined by stage 1 to a **charT** using a conversion and values returned by members of **use\_facet<num\_punct<charT>>(str.getloc())**

(2.3) — Stage 3: Determine where padding is required.

(2.4) — Stage 4: Insert the sequence into the out.

3 Detailed descriptions of each stage follow.

4 *Returns:* out.

5

**Stage 1:** The first action of stage 1 is to determine a conversion specifier. The tables that describe this determination use the following local variables

```

fmtflags flags = str.flags();
fmtflags basefield = (flags & (ios_base::basefield));
fmtflags uppercase = (flags & (ios_base::uppercase));
fmtflags floatfield = (flags & (ios_base::floatfield));
fmtflags showpos = (flags & (ios_base::showpos));
fmtflags showbase = (flags & (ios_base::showbase));
fmtflags showpoint = (flags & (ios_base::showpoint));

```

All tables used in describing stage 1 are ordered. That is, the first line whose condition is true applies. A line without a condition is the default behavior when none of the earlier lines apply.

For conversion from an integral type other than a character type, the function determines the integral conversion specifier as indicated in Table 75.

Table 75 — Integer conversions

| State                                                           | stdio equivalent |
|-----------------------------------------------------------------|------------------|
| <code>basefield == ios_base::oct</code>                         | <code>%o</code>  |
| <code>(basefield == ios_base::hex) &amp;&amp; !uppercase</code> | <code>%x</code>  |
| <code>(basefield == ios_base::hex)</code>                       | <code>%X</code>  |
| for a <b>signed</b> integral type                               | <code>%d</code>  |
| for an <b>unsigned</b> integral type                            | <code>%u</code>  |

For conversion from a floating-point type, the function determines the floating-point conversion specifier as indicated in Table 76.

Table 76 — Floating-point conversions

| State                                                                                     | stdio equivalent |
|-------------------------------------------------------------------------------------------|------------------|
| <code>floatfield == ios_base::fixed</code>                                                | <code>%f</code>  |
| <code>floatfield == ios_base::scientific &amp;&amp; !uppercase</code>                     | <code>%e</code>  |
| <code>floatfield == ios_base::scientific</code>                                           | <code>%E</code>  |
| <code>floatfield == (ios_base::fixed   ios_base::scientific) &amp;&amp; !uppercase</code> | <code>%a</code>  |
| <code>floatfield == (ios_base::fixed   ios_base::scientific)</code>                       | <code>%A</code>  |
| <code>!uppercase</code>                                                                   | <code>%g</code>  |
| <i>otherwise</i>                                                                          | <code>%G</code>  |

For conversions from an integral or floating-point type a length modifier is added to the conversion specifier as indicated in Table 77.

Table 77 — Length modifier

| Type                            | Length modifier |
|---------------------------------|-----------------|
| <code>long</code>               | <code>l</code>  |
| <code>long long</code>          | <code>ll</code> |
| <code>unsigned long</code>      | <code>l</code>  |
| <code>unsigned long long</code> | <code>ll</code> |
| <code>long double</code>        | <code>L</code>  |
| <i>otherwise</i>                | <i>none</i>     |

The conversion specifier has the following optional additional qualifiers prepended as indicated in Table 78.

Table 78 — Numeric conversions

| Type(s)               | State                  | stdio equivalent |
|-----------------------|------------------------|------------------|
| an integral type      | <code>showpos</code>   | <code>+</code>   |
|                       | <code>showbase</code>  | <code>#</code>   |
| a floating-point type | <code>showpos</code>   | <code>+</code>   |
|                       | <code>showpoint</code> | <code>#</code>   |

For conversion from a floating-point type, if `floatfield != (ios_base::fixed | ios_base::scientific)`, `str.precision()` is specified as precision in the conversion specification. Otherwise, no precision is specified.

For conversion from `void*` the specifier is `%p`.

The representations at the end of stage 1 consists of the `char`'s that would be printed by a call of `printf(s, val)` where `s` is the conversion specifier determined above.

**Stage 2:** Any character `c` other than a decimal point(`.`) is converted to a `charT` via `use_facet<ctype<charT>>(loc).widen( c )`

A local variable `punct` is initialized via

```
const numpunct<charT>& punct = use_facet<numpunct<charT>>(str.getloc());
```

For arithmetic types, `punct.thousands_sep()` characters are inserted into the sequence as determined by the value returned by `punct.do_grouping()` using the method described in 25.4.3.1.2

Decimal point characters(`.`) are replaced by `punct.decimal_point()`

**Stage 3:** A local variable is initialized as

```
fmtflags adjustfield = (flags & (ios_base::adjustfield));
```

The location of any padding<sup>240</sup> is determined according to Table 79.

Table 79 — Fill padding

| State                                                                                                               | Location                                   |
|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| <code>adjustfield == ios_base::left</code>                                                                          | pad after                                  |
| <code>adjustfield == ios_base::right</code>                                                                         | pad before                                 |
| <code>adjustfield == internal</code> and a sign occurs in the representation                                        | pad after the sign                         |
| <code>adjustfield == internal</code> and representation after stage 1 began with <code>0x</code> or <code>0X</code> | pad after <code>x</code> or <code>X</code> |
| <i>otherwise</i>                                                                                                    | pad before                                 |

If `str.width()` is nonzero and the number of `charT`'s in the sequence after stage 2 is less than `str.width()`, then enough fill characters are added to the sequence at the position indicated for padding to bring the length of the sequence to `str.width()`.

`str.width(0)` is called.

**Stage 4:** The sequence of `charT`'s at the end of stage 3 are output via

```
*out++ = c
```

```
iter_type do_put(iter_type out, ios_base& str, char_type fill, bool val) const;
```

<sup>6</sup> *Returns:* If `(str.flags() & ios_base::boolalpha) == 0` returns `do_put(out, str, fill, (int)val)`, otherwise obtains a string `s` as if by

```
string_type s =
 val ? use_facet<numpunct<charT>>(loc).truename()
 : use_facet<numpunct<charT>>(loc).falsename();
```

and then inserts each character `c` of `s` into `out` via `*out++ = c` and returns `out`.

## 25.4.3 The numeric punctuation facet

[facet.numpunct]

### 25.4.3.1 Class template numpunct

[locale.numpunct]

```
namespace std {
 template <class charT>
 class numpunct : public locale::facet {
 public:
```

<sup>240</sup>) The conversion specification `#0` generates a leading `0` which is *not* a padding character.



```

using char_type = charT;
using string_type = basic_string<charT>;

explicit numpunct(size_t refs = 0);

char_type decimal_point() const;
char_type thousands_sep() const;
string grouping() const;
string_type truename() const;
string_type falsename() const;

static locale::id id;

protected:
 ~numpunct(); // virtual
 virtual char_type do_decimal_point() const;
 virtual char_type do_thousands_sep() const;
 virtual string do_grouping() const;
 virtual string_type do_truename() const; // for bool
 virtual string_type do_falsename() const; // for bool
};

```

- <sup>1</sup> `numpunct<>` specifies numeric punctuation. The specializations required in Table 69 (25.3.1.1.1), namely `numpunct<wchar_t>` and `numpunct<char>`, provide classic "C" numeric formats, i.e., they contain information equivalent to that contained in the "C" locale or their wide character counterparts as if obtained by a call to `widen`.
- <sup>2</sup> The syntax for number formats is as follows, where `digit` represents the radix set specified by the `fmtflags` argument value, and `thousands_sep` and `decimal_point` are the results of corresponding `numpunct<charT>` members. Integer values have the format:

```

integer ::= [sign] units
sign ::= plusminus
plusminus ::= '+' | '-'
units ::= digits [thousands_sep units]
digits ::= digit [digits]

```

and floating-point values have:

```

floatval ::= [sign] units [decimal-point [digits]] [e [sign] digits] |
 [sign] decimal-point digits [e [sign] digits]
e ::= 'e' | 'E'

```

where the number of digits between `thousands-seps` is as specified by `do_grouping()`. For parsing, if the digits portion contains no thousands-separators, no grouping constraint is applied.

#### 25.4.3.1.1 `numpunct` members [facet.numpunct.members]

```
char_type decimal_point() const;
```

- <sup>1</sup> *Returns:* `do_decimal_point()`.

```
char_type thousands_sep() const;
```

- <sup>2</sup> *Returns:* `do_thousands_sep()`.

```
string grouping() const;
```

- <sup>3</sup> *Returns:* `do_grouping()`.

```
string_type truename() const;
string_type falsename() const;
```

4 *Returns:* `do_truename()` or `do_falsename()`, respectively.

### 25.4.3.1.2 `num_punct` virtual functions

[`facet.num_punct.virtuals`]

```
char_type do_decimal_point() const;
```

1 *Returns:* A character for use as the decimal radix separator. The required specializations return `'.'` or `L'.'`.

```
char_type do_thousands_sep() const;
```

2 *Returns:* A character for use as the digit group separator. The required specializations return `'.'` or `L'.'`.

```
string do_grouping() const;
```

3 *Returns:* A `basic_string<char>` `vec` used as a vector of integer values, in which each element `vec[i]` represents the number of digits<sup>241</sup> in the group at position `i`, starting with position 0 as the rightmost group. If `vec.size() <= i`, the number is the same as group `(i - 1)`; if `(i < 0 || vec[i] <= 0 || vec[i] == CHAR_MAX)`, the size of the digit group is unlimited.

4 The required specializations return the empty string, indicating no grouping.

```
string_type do_truename() const;
string_type do_falsename() const;
```

5 *Returns:* A string representing the name of the boolean value `true` or `false`, respectively.

6 In the base class implementation these names are `"true"` and `"false"`, or `L"true"` and `L"false"`.

### 25.4.3.2 Class template `num_punct_byname`

[`locale.num_punct.byname`]

```
namespace std {
 template <class charT>
 class num_punct_byname : public num_punct<charT> {
 // this class is specialized for char and wchar_t.
 public:
 using char_type = charT;
 using string_type = basic_string<charT>;

 explicit num_punct_byname(const char*, size_t refs = 0);
 explicit num_punct_byname(const string&, size_t refs = 0);
 protected:
 ~num_punct_byname();
 };
}
```

## 25.4.4 The collate category

[`category.collate`]

### 25.4.4.1 Class template `collate`

[`locale.collate`]

```
namespace std {
 template <class charT>
 class collate : public locale::facet {
 public:
 using char_type = charT;
```

241) Thus, the string `"\003"` specifies groups of 3 digits each, and `"3"` probably indicates groups of 51 (!) digits each, because 51 is the ASCII value of `"3"`.

```

using string_type = basic_string<charT>;

explicit collate(size_t refs = 0);

int compare(const charT* low1, const charT* high1,
 const charT* low2, const charT* high2) const;
string_type transform(const charT* low, const charT* high) const;
long hash(const charT* low, const charT* high) const;

static locale::id id;

protected:
 ~collate();
 virtual int do_compare(const charT* low1, const charT* high1,
 const charT* low2, const charT* high2) const;
 virtual string_type do_transform(const charT* low, const charT* high) const;
 virtual long do_hash(const charT* low, const charT* high) const;
};
}

```

- <sup>1</sup> The class `collate<charT>` provides features for use in the collation (comparison) and hashing of strings. A locale member function template, `operator()`, uses the collate facet to allow a locale to act directly as the predicate argument for standard algorithms (Clause 28) and containers operating on strings. The specializations required in Table 69 (25.3.1.1.1), namely `collate<char>` and `collate<wchar_t>`, apply lexicographic ordering (28.7.10).

- <sup>2</sup> Each function compares a string of characters `*p` in the range `[low, high)`.

#### 25.4.4.1.1 collate members

[locale.collate.members]

```

int compare(const charT* low1, const charT* high1,
 const charT* low2, const charT* high2) const;

```

- <sup>1</sup> *Returns:* `do_compare(low1, high1, low2, high2)`.

```

string_type transform(const charT* low, const charT* high) const;

```

- <sup>2</sup> *Returns:* `do_transform(low, high)`.

```

long hash(const charT* low, const charT* high) const;

```

- <sup>3</sup> *Returns:* `do_hash(low, high)`.

#### 25.4.4.1.2 collate virtual functions

[locale.collate.virtuals]

```

int do_compare(const charT* low1, const charT* high1,
 const charT* low2, const charT* high2) const;

```

- <sup>1</sup> *Returns:* 1 if the first string is greater than the second, -1 if less, zero otherwise. The specializations required in Table 69 (25.3.1.1.1), namely `collate<char>` and `collate<wchar_t>`, implement a lexicographical comparison (28.7.10).

```

string_type do_transform(const charT* low, const charT* high) const;

```

- <sup>2</sup> *Returns:* A `basic_string<charT>` value that, compared lexicographically with the result of calling `transform()` on another string, yields the same result as calling `do_compare()` on the same two strings.<sup>242</sup>

```

long do_hash(const charT* low, const charT* high) const;

```

<sup>242</sup>) This function is useful when one string is being compared to many other strings.

- <sup>3</sup> *Returns:* An integer value equal to the result of calling `hash()` on any other string for which `do_compare()` returns 0 (equal) when passed the two strings. [ *Note:* The probability that the result equals that for another string which does not compare equal should be very small, approaching  $(1.0/\text{numeric\_limits}<\text{unsigned long}>::\text{max}())$ . — *end note* ]

#### 25.4.4.2 Class template `collate_byname`

[`locale.collate.byname`]

```
namespace std {
 template <class charT>
 class collate_byname : public collate<charT> {
 public:
 using string_type = basic_string<charT>;

 explicit collate_byname(const char*, size_t refs = 0);
 explicit collate_byname(const string&, size_t refs = 0);
 protected:
 ~collate_byname();
 };
}
```

#### 25.4.5 The time category

[`category.time`]

- <sup>1</sup> Templates `time_get<charT, InputIterator>` and `time_put<charT, OutputIterator>` provide date and time formatting and parsing. All specifications of member functions for `time_put` and `time_get` in the subclauses of 25.4.5 only apply to the specializations required in Tables 69 and 70 (25.3.1.1.1). Their members use their `ios_base&`, `ios_base::iostate&`, and fill arguments as described in 25.4, and the `ctype<>` facet, to determine formatting details.

##### 25.4.5.1 Class template `time_get`

[`locale.time.get`]

```
namespace std {
 class time_base {
 public:
 enum dateorder { no_order, dmy, mdy, ymd, ydm };
 };

 template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class time_get : public locale::facet, public time_base {
 public:
 using char_type = charT;
 using iter_type = InputIterator;

 explicit time_get(size_t refs = 0);

 dateorder date_order() const { return do_date_order(); }
 iter_type get_time(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 iter_type get_date(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 iter_type get_weekday(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 iter_type get_monthname(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 iter_type get_year(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 iter_type get(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t, char format, char modifier = 0) const;
 };
}
```

```

 iter_type get(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t, const char_type* fmt,
 const char_type* fmtend) const;

 static locale::id id;

protected:
 ~time_get();
 virtual dateorder do_date_order() const;
 virtual iter_type do_get_time(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 virtual iter_type do_get_date(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 virtual iter_type do_get_weekday(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 virtual iter_type do_get_monthname(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 virtual iter_type do_get_year(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t) const;
 virtual iter_type do_get(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t, char format, char modifier) const;
};
}

```

<sup>1</sup> `time_get` is used to parse a character sequence, extracting components of a time or date into a `struct tm` object. Each `get` member parses a format as produced by a corresponding format specifier to `time_put<>::put`. If the sequence being parsed matches the correct format, the corresponding members of the `struct tm` argument are set to the values used to produce the sequence; otherwise either an error is reported or unspecified values are assigned.<sup>243</sup>

<sup>2</sup> If the end iterator is reached during parsing by any of the `get()` member functions, the member sets `ios_base::eofbit` in `err`.

#### 25.4.5.1.1 `time_get` members

[`locale.time.get.members`]

```
dateorder date_order() const;
```

<sup>1</sup> *Returns:* `do_date_order()`.

```
iter_type get_time(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

<sup>2</sup> *Returns:* `do_get_time(s, end, str, err, t)`.

```
iter_type get_date(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

<sup>3</sup> *Returns:* `do_get_date(s, end, str, err, t)`.

```
iter_type get_weekday(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
iter_type get_monthname(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

<sup>4</sup> *Returns:* `do_get_weekday(s, end, str, err, t)` or `do_get_monthname(s, end, str, err, t)`.

```
iter_type get_year(iter_type s, iter_type end, ios_base& str,
```

<sup>243</sup>) In other words, user confirmation is required for reliable parsing of user-entered dates and times, but machine-generated formats can be parsed reliably. This allows parsers to be aggressive about interpreting user variations on standard formats.

```
ios_base::iostate& err, tm* t) const;
```

5 *Returns:* `do_get_year(s, end, str, err, t)`.

```
iter_type get(iter_type s, iter_type end, ios_base& f, ios_base::iostate& err,
 tm* t, char format, char modifier = 0) const;
```

6 *Returns:* `do_get(s, end, f, err, t, format, modifier)`.

```
iter_type get(iter_type s, iter_type end, ios_base& f, ios_base::iostate& err,
 tm* t, const char_type* fmt, const char_type* fmtend) const;
```

7 *Requires:* `[fmt, fmtend)` shall be a valid range.

8 *Effects:* The function starts by evaluating `err = ios_base::goodbit`. It then enters a loop, reading zero or more characters from `s` at each iteration. Unless otherwise specified below, the loop terminates when the first of the following conditions holds:

- (8.1) — The expression `fmt == fmtend` evaluates to `true`.
- (8.2) — The expression `err == ios_base::goodbit` evaluates to `false`.
- (8.3) — The expression `s == end` evaluates to `true`, in which case the function evaluates `err = ios_base::eofbit | ios_base::failbit`.
- (8.4) — The next element of `fmt` is equal to `'%'`, optionally followed by a modifier character, followed by a conversion specifier character, `format`, together forming a conversion specification valid for the ISO/IEC 9945 function `strptime`. If the number of elements in the range `[fmt, fmtend)` is not sufficient to unambiguously determine whether the conversion specification is complete and valid, the function evaluates `err = ios_base::failbit`. Otherwise, the function evaluates `s = do_get(s, end, f, err, t, format, modifier)`, where the value of `modifier` is `'\0'` when the optional modifier is absent from the conversion specification. If `err == ios_base::goodbit` holds after the evaluation of the expression, the function increments `fmt` to point just past the end of the conversion specification and continues looping.
- (8.5) — The expression `isspace(*fmt, f.getloc())` evaluates to `true`, in which case the function first increments `fmt` until `fmt == fmtend || !isspace(*fmt, f.getloc())` evaluates to `true`, then advances `s` until `s == end || !isspace(*s, f.getloc())` is `true`, and finally resumes looping.
- (8.6) — The next character read from `s` matches the element pointed to by `fmt` in a case-insensitive comparison, in which case the function evaluates `++fmt, ++s` and continues looping. Otherwise, the function evaluates `err = ios_base::failbit`.

9 [ *Note:* The function uses the `ctype<charT>` facet installed in `f`'s locale to determine valid whitespace characters. It is unspecified by what means the function performs case-insensitive comparison or whether multi-character sequences are considered while doing so. — *end note* ]

10 *Returns:* `s`.

#### 25.4.5.1.2 time\_get virtual functions

[`locale.time.get.virtuals`]

```
dateorder do_date_order() const;
```

1 *Returns:* An enumeration value indicating the preferred order of components for those date formats that are composed of day, month, and year.<sup>244</sup> Returns `no_order` if the date format specified by `'x'` contains other variable components (e.g., Julian day, week number, week day).

```
iter_type do_get_time(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

244) This function is intended as a convenience only, for common formats, and may return `no_order` in valid locales.

2 *Effects:* Reads characters starting at `s` until it has extracted those `struct tm` members, and remaining format characters, used by `time_put<>::put` to produce the format specified by `"%H:%M:%S"`, or until it encounters an error or end of sequence.

3 *Returns:* An iterator pointing immediately beyond the last character recognized as possibly part of a valid time.

```
iter_type do_get_date(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

4 *Effects:* Reads characters starting at `s` until it has extracted those `struct tm` members and remaining format characters used by `time_put<>::put` to produce one of the following formats, or until it encounters an error. The format depends on the value returned by `date_order()` as shown in Table 80.

Table 80 — `do_get_date` effects

| <code>date_order()</code> | Format                |
|---------------------------|-----------------------|
| <code>no_order</code>     | <code>"%m%d%y"</code> |
| <code>dmy</code>          | <code>"%d%m%y"</code> |
| <code>mdy</code>          | <code>"%m%d%y"</code> |
| <code>ymd</code>          | <code>"%y%m%d"</code> |
| <code>ydm</code>          | <code>"%y%d%m"</code> |

5 An implementation may also accept additional implementation-defined formats.

6 *Returns:* An iterator pointing immediately beyond the last character recognized as possibly part of a valid date.

```
iter_type do_get_weekday(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
iter_type do_get_monthname(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

7 *Effects:* Reads characters starting at `s` until it has extracted the (perhaps abbreviated) name of a weekday or month. If it finds an abbreviation that is followed by characters that could match a full name, it continues reading until it matches the full name or fails. It sets the appropriate `struct tm` member accordingly.

8 *Returns:* An iterator pointing immediately beyond the last character recognized as part of a valid name.

```
iter_type do_get_year(iter_type s, iter_type end, ios_base& str,
 ios_base::iostate& err, tm* t) const;
```

9 *Effects:* Reads characters starting at `s` until it has extracted an unambiguous year identifier. It is implementation-defined whether two-digit year numbers are accepted, and (if so) what century they are assumed to lie in. Sets the `t->tm_year` member accordingly.

10 *Returns:* An iterator pointing immediately beyond the last character recognized as part of a valid year identifier.

```
iter_type do_get(iter_type s, iter_type end, ios_base& f,
 ios_base::iostate& err, tm* t, char format, char modifier) const;
```

11 *Requires:* `t` shall point to an object.

12 *Effects:* The function starts by evaluating `err = ios_base::goodbit`. It then reads characters starting at `s` until it encounters an error, or until it has extracted and assigned those `struct tm` members, and any remaining format characters, corresponding to a conversion directive appropriate for the ISO/IEC

9945 function `strptime`, formed by concatenating `'%'`, the modifier character, when non-NUL, and the format character. When the concatenation fails to yield a complete valid directive the function leaves the object pointed to by `t` unchanged and evaluates `err |= ios_base::failbit`. When `s == end` evaluates to `true` after reading a character the function evaluates `err |= ios_base::eofbit`.

13 For complex conversion directives such as `%c`, `%x`, or `%X`, or directives that involve the optional modifiers `E` or `O`, when the function is unable to unambiguously determine some or all `struct tm` members from the input sequence `[s, end)`, it evaluates `err |= ios_base::eofbit`. In such cases the values of those `struct tm` members are unspecified and may be outside their valid range.

14 *Remarks:* It is unspecified whether multiple calls to `do_get()` with the address of the same `struct tm` object will update the current contents of the object or simply overwrite its members. Portable programs must zero out the object before invoking the function.

15 *Returns:* An iterator pointing immediately beyond the last character recognized as possibly part of a valid input sequence for the given format and modifier.

#### 25.4.5.2 Class template `time_get_byname` [locale.time.get.byname]

```
namespace std {
 template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class time_get_byname : public time_get<charT, InputIterator> {
 public:
 using dateorder = time_base::dateorder;
 using iter_type = InputIterator;

 explicit time_get_byname(const char*, size_t refs = 0);
 explicit time_get_byname(const string&, size_t refs = 0);
 protected:
 ~time_get_byname();
 };
}
```

#### 25.4.5.3 Class template `time_put` [locale.time.put]

```
namespace std {
 template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class time_put : public locale::facet {
 public:
 using char_type = charT;
 using iter_type = OutputIterator;

 explicit time_put(size_t refs = 0);

 // the following is implemented in terms of other member functions.
 iter_type put(iter_type s, ios_base& f, char_type fill, const tm* tmb,
 const charT* pattern, const charT* pat_end) const;
 iter_type put(iter_type s, ios_base& f, char_type fill,
 const tm* tmb, char format, char modifier = 0) const;

 static locale::id id;

 protected:
 ~time_put();
 virtual iter_type do_put(iter_type s, ios_base&, char_type, const tm* t,
 char format, char modifier) const;
 };
}
```



25.4.5.3.1 `time_put` members[`locale.time.put.members`]

```

iter_type put(iter_type s, ios_base& str, char_type fill, const tm* t,
 const charT* pattern, const charT* pat_end) const;
iter_type put(iter_type s, ios_base& str, char_type fill, const tm* t,
 char format, char modifier = 0) const;

```

- 1 *Effects:* The first form steps through the sequence from `pattern` to `pat_end`, identifying characters that are part of a format sequence. Each character that is not part of a format sequence is written to `s` immediately, and each format sequence, as it is identified, results in a call to `do_put`; thus, format elements and other characters are interleaved in the output in the order in which they appear in the pattern. Format sequences are identified by converting each character `c` to a `char` value as if by `ct.narrow(c, 0)`, where `ct` is a reference to `ctype<charT>` obtained from `str.getloc()`. The first character of each sequence is equal to `'%'`, followed by an optional modifier character `mod`<sup>245</sup> and a format specifier character `spec` as defined for the function `strftime`. If no modifier character is present, `mod` is zero. For each valid format sequence identified, calls `do_put(s, str, fill, t, spec, mod)`.
- 2 The second form calls `do_put(s, str, fill, t, format, modifier)`.
- 3 [*Note:* The `fill` argument may be used in the implementation-defined formats or by derivations. A space character is a reasonable default for this argument. — *end note*]
- 4 *Returns:* An iterator pointing immediately after the last character produced.

25.4.5.3.2 `time_put` virtual functions[`locale.time.put.virtuals`]

```

iter_type do_put(iter_type s, ios_base&, char_type fill, const tm* t,
 char format, char modifier) const;

```

- 1 *Effects:* Formats the contents of the parameter `t` into characters placed on the output sequence `s`. Formatting is controlled by the parameters `format` and `modifier`, interpreted identically as the format specifiers in the string argument to the standard library function `strftime()`<sup>246</sup>, except that the sequence of characters produced for those specifiers that are described as depending on the C locale are instead implementation-defined.<sup>247</sup>
- 2 *Returns:* An iterator pointing immediately after the last character produced. [*Note:* The `fill` argument may be used in the implementation-defined formats or by derivations. A space character is a reasonable default for this argument. — *end note*]

25.4.5.4 Class template `time_put_byname`[`locale.time.put.byname`]

```

namespace std {
 template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
 class time_put_byname : public time_put<charT, OutputIterator>
 {
 public:
 using char_type = charT;
 using iter_type = OutputIterator;

 explicit time_put_byname(const char*, size_t refs = 0);
 explicit time_put_byname(const string&, size_t refs = 0);
 protected:
 ~time_put_byname();
 };
}

```

245) Although the C programming language defines no modifiers, most vendors do.

246) Interpretation of the `modifier` argument is implementation-defined, but should follow POSIX conventions.

247) Implementations are encouraged to refer to other standards such as POSIX for these definitions.

### 25.4.6 The monetary category [category.monetary]

- <sup>1</sup> These templates handle monetary formats. A template parameter indicates whether local or international monetary formats are to be used.
- <sup>2</sup> All specifications of member functions for `money_put` and `money_get` in the subclauses of 25.4.6 only apply to the specializations required in Tables 69 and 70 (25.3.1.1.1). Their members use their `ios_base&`, `ios_base::iostate&`, and fill arguments as described in 25.4, and the `moneypunct<>` and `ctype<>` facets, to determine formatting details.

#### 25.4.6.1 Class template `money_get` [locale.money.get]

```
namespace std {
 template <class charT, class InputIterator = istreambuf_iterator<charT>>
 class money_get : public locale::facet {
 public:
 using char_type = charT;
 using iter_type = InputIterator;
 using string_type = basic_string<charT>;

 explicit money_get(size_t refs = 0);

 iter_type get(iter_type s, iter_type end, bool intl,
 ios_base& f, ios_base::iostate& err,
 long double& units) const;
 iter_type get(iter_type s, iter_type end, bool intl,
 ios_base& f, ios_base::iostate& err,
 string_type& digits) const;

 static locale::id id;

 protected:
 ~money_get();
 virtual iter_type do_get(iter_type, iter_type, bool, ios_base&,
 ios_base::iostate& err, long double& units) const;
 virtual iter_type do_get(iter_type, iter_type, bool, ios_base&,
 ios_base::iostate& err, string_type& digits) const;
 };
 }
```

##### 25.4.6.1.1 `money_get` members [locale.money.get.members]

```
iter_type get(iter_type s, iter_type end, bool intl,
 ios_base& f, ios_base::iostate& err,
 long double& quant) const;
iter_type get(s, iter_type end, bool intl, ios_base&f,
 ios_base::iostate& err, string_type& quant) const;
```

- <sup>1</sup> *Returns:* `do_get(s, end, intl, f, err, quant)`.

##### 25.4.6.1.2 `money_get` virtual functions [locale.money.get.virtuals]

```
iter_type do_get(iter_type s, iter_type end, bool intl,
 ios_base& str, ios_base::iostate& err,
 long double& units) const;
iter_type do_get(iter_type s, iter_type end, bool intl,
 ios_base& str, ios_base::iostate& err,
 string_type& digits) const;
```

- <sup>1</sup> *Effects:* Reads characters from `s` to parse and construct a monetary value according to the format specified by a `money_punct<charT, Int1>` facet reference `mp` and the character mapping specified by a `ctype<charT>` facet reference `ct` obtained from the locale returned by `str.getloc()`, and `str.flags()`. If a valid sequence is recognized, does not change `err`; otherwise, sets `err` to `(err|str.failbit)`, or `(err|str.failbit|str.eofbit)` if no more characters are available, and does not change `units` or `digits`. Uses the pattern returned by `mp.neg_format()` to parse all values. The result is returned as an integral value stored in `units` or as a sequence of digits possibly preceded by a minus sign (as produced by `ct.widen(c)` where `c` is '-' or in the range from '0' through '9', inclusive) stored in `digits`. [*Example:* The sequence \$1,056.23 in a common United States locale would yield, for `units`, 105623, or, for `digits`, "105623". — *end example*] If `mp.grouping()` indicates that no thousands separators are permitted, any such characters are not read, and parsing is terminated at the point where they first appear. Otherwise, thousands separators are optional; if present, they are checked for correct placement only after all format components have been read.
- <sup>2</sup> Where `money_base::space` or `money_base::none` appears as the last element in the format pattern, no white space is consumed. Otherwise, where `money_base::space` appears in any of the initial elements of the format pattern, at least one white space character is required. Where `money_base::none` appears in any of the initial elements of the format pattern, white space is allowed but not required. If `(str.flags() & str.showbase)` is false, the currency symbol is optional and is consumed only if other characters are needed to complete the format; otherwise, the currency symbol is required.
- <sup>3</sup> If the first character (if any) in the string `pos` returned by `mp.positive_sign()` or the string `neg` returned by `mp.negative_sign()` is recognized in the position indicated by `sign` in the format pattern, it is consumed and any remaining characters in the string are required after all the other format components. [*Example:* If `showbase` is off, then for a `neg` value of "(" and a currency symbol of "L", in "(100 L)" the "L" is consumed; but if `neg` is "-", the "L" in "-100 L" is not consumed. — *end example*] If `pos` or `neg` is empty, the sign component is optional, and if no sign is detected, the result is given the sign that corresponds to the source of the empty string. Otherwise, the character in the indicated position must match the first character of `pos` or `neg`, and the result is given the corresponding sign. If the first character of `pos` is equal to the first character of `neg`, or if both strings are empty, the result is given a positive sign.
- <sup>4</sup> Digits in the numeric monetary component are extracted and placed in `digits`, or into a character buffer `buf1` for conversion to produce a value for `units`, in the order in which they appear, preceded by a minus sign if and only if the result is negative. The value `units` is produced as if by<sup>248</sup>
- ```
for (int i = 0; i < n; ++i)
    buf2[i] = src[find(atoms, atoms+sizeof(src), buf1[i]) - atoms];
buf2[n] = 0;
sscanf(buf2, "%Lf", &units);
```
- where `n` is the number of characters placed in `buf1`, `buf2` is a character buffer, and the values `src` and `atoms` are defined as if by
- ```
static const char src[] = "0123456789-";
charT atoms[sizeof(src)];
ct.widen(src, src + sizeof(src) - 1, atoms);
```
- <sup>5</sup> *Returns:* An iterator pointing immediately beyond the last character recognized as part of a valid monetary quantity.

#### 25.4.6.2 Class template `money_put`

[`locale.money.put`]

```
namespace std {
 template <class charT, class OutputIterator = ostreambuf_iterator<charT>>
```

248) The semantics here are different from `ct.narrow`.

```

class money_put : public locale::facet {
public:
 using char_type = charT;
 using iter_type = OutputIterator;
 using string_type = basic_string<charT>;

 explicit money_put(size_t refs = 0);

 iter_type put(iter_type s, bool intl, ios_base& f,
 char_type fill, long double units) const;
 iter_type put(iter_type s, bool intl, ios_base& f,
 char_type fill, const string_type& digits) const;

 static locale::id id;

protected:
 ~money_put();
 virtual iter_type do_put(iter_type, bool, ios_base&, char_type fill,
 long double units) const;
 virtual iter_type do_put(iter_type, bool, ios_base&, char_type fill,
 const string_type& digits) const;
};

```

#### 25.4.6.2.1 money\_put members

[locale.money.put.members]

```

iter_type put(iter_type s, bool intl, ios_base& f, char_type fill,
 long double quant) const;
iter_type put(iter_type s, bool intl, ios_base& f, char_type fill,
 const string_type& quant) const;

```

<sup>1</sup> *Returns:* do\_put(s, intl, f, loc, quant).

#### 25.4.6.2.2 money\_put virtual functions

[locale.money.put.virtuals]

```

iter_type do_put(iter_type s, bool intl, ios_base& str,
 char_type fill, long double units) const;
iter_type do_put(iter_type s, bool intl, ios_base& str,
 char_type fill, const string_type& digits) const;

```

<sup>1</sup> *Effects:* Writes characters to *s* according to the format specified by a `money_punct<charT, Intl>` facet reference *mp* and the character mapping specified by a `ctype<charT>` facet reference *ct* obtained from the locale returned by *str.getloc()*, and *str.flags()*. The argument *units* is transformed into a sequence of wide characters as if by

```
ct.widen(buf1, buf1 + sprintf(buf1, "%.0Lf", units), buf2)
```

for character buffers *buf1* and *buf2*. If the first character in *digits* or *buf2* is equal to `ct.widen('')`, then the pattern used for formatting is the result of *mp.neg\_format()*; otherwise the pattern is the result of *mp.pos\_format()*. Digit characters are written, interspersed with any thousands separators and decimal point specified by the format, in the order they appear (after the optional leading minus sign) in *digits* or *buf2*. In *digits*, only the optional leading minus sign and the immediately subsequent digit characters (as classified according to *ct*) are used; any trailing characters (including digits appearing after a non-digit character) are ignored. Calls *str.width(0)*.

<sup>2</sup> *Remarks:* The currency symbol is generated if and only if `(str.flags() & str.showbase)` is nonzero. If the number of characters generated for the specified format is less than the value returned by *str.width()* on entry to the function, then copies of *fill* are inserted as necessary to pad to the speci-

fied width. For the value `af` equal to `(str.flags() & str.adjustfield)`, if `(af == str.internal)` is `true`, the fill characters are placed where `none` or `space` appears in the formatting pattern; otherwise if `(af == str.left)` is `true`, they are placed after the other characters; otherwise, they are placed before the other characters. [ *Note*: It is possible, with some combinations of format patterns and flag values, to produce output that cannot be parsed using `num_get<>::get`. — *end note* ]

<sup>3</sup> *Returns*: An iterator pointing immediately after the last character produced.

### 25.4.6.3 Class template `moneypunct`

[`locale.moneypunct`]

```
namespace std {
 class money_base {
 public:
 enum part { none, space, symbol, sign, value };
 struct pattern { char field[4]; };
 };

 template <class charT, bool International = false>
 class moneypunct : public locale::facet, public money_base {
 public:
 using char_type = charT;
 using string_type = basic_string<charT>;

 explicit moneypunct(size_t refs = 0);

 charT decimal_point() const;
 charT thousands_sep() const;
 string grouping() const;
 string_type curr_symbol() const;
 string_type positive_sign() const;
 string_type negative_sign() const;
 int frac_digits() const;
 pattern pos_format() const;
 pattern neg_format() const;

 static locale::id id;
 static const bool intl = International;

 protected:
 ~moneypunct();
 virtual charT do_decimal_point() const;
 virtual charT do_thousands_sep() const;
 virtual string do_grouping() const;
 virtual string_type do_curr_symbol() const;
 virtual string_type do_positive_sign() const;
 virtual string_type do_negative_sign() const;
 virtual int do_frac_digits() const;
 virtual pattern do_pos_format() const;
 virtual pattern do_neg_format() const;
 };
}
```

<sup>1</sup> The `moneypunct<>` facet defines monetary formatting parameters used by `money_get<>` and `money_put<>`. A monetary format is a sequence of four components, specified by a `pattern` value `p`, such that the `part` value `static_cast<part>(p.field[i])` determines the *i*th component of the format<sup>249</sup> In the `field` member

<sup>249</sup>) An array of `char`, rather than an array of `part`, is specified for `pattern::field` purely for efficiency.

of a `pattern` object, each value `symbol`, `sign`, `value`, and either `space` or `none` appears exactly once. The value `none`, if present, is not first; the value `space`, if present, is neither first nor last.

- <sup>2</sup> Where `none` or `space` appears, white space is permitted in the format, except where `none` appears at the end, in which case no white space is permitted. The value `space` indicates that at least one space is required at that position. Where `symbol` appears, the sequence of characters returned by `curr_symbol()` is permitted, and can be required. Where `sign` appears, the first (if any) of the sequence of characters returned by `positive_sign()` or `negative_sign()` (respectively as the monetary value is non-negative or negative) is required. Any remaining characters of the sign sequence are required after all other format components. Where `value` appears, the absolute numeric monetary value is required.
- <sup>3</sup> The format of the numeric monetary value is a decimal number:

```
value ::= units [decimal-point [digits]] |
 decimal-point digits
```

if `frac_digits()` returns a positive value, or

```
value ::= units
```

otherwise. The symbol `decimal-point` indicates the character returned by `decimal_point()`. The other symbols are defined as follows:

```
units ::= digits [thousands-sep units]
digits ::= adigit [digits]
```

In the syntax specification, the symbol `adigit` is any of the values `ct.widen(c)` for `c` in the range '0' through '9', inclusive, and `ct` is a reference of type `const ctype<charT>&` obtained as described in the definitions of `money_get<>` and `money_put<>`. The symbol `thousands-sep` is the character returned by `thousands_sep()`. The space character used is the value `ct.widen(' ')`. White space characters are those characters `c` for which `ci.is(space, c)` returns `true`. The number of digits required after the decimal point (if any) is exactly the value returned by `frac_digits()`.

- <sup>4</sup> The placement of thousands-separator characters (if any) is determined by the value returned by `grouping()`, defined identically as the member `num_punct<>::do_grouping()`.

#### 25.4.6.3.1 money\_punct members

[`locale.money_punct.members`]

```
charT decimal_point() const;
charT thousands_sep() const;
string grouping() const;
string_type curr_symbol() const;
string_type positive_sign() const;
string_type negative_sign() const;
int frac_digits() const;
pattern pos_format() const;
pattern neg_format() const;
```

- <sup>1</sup> Each of these functions *F* returns the result of calling the corresponding virtual member function `do_F()`.

#### 25.4.6.3.2 money\_punct virtual functions

[`locale.money_punct.virtuals`]

```
charT do_decimal_point() const;
```

- <sup>1</sup> *Returns:* The radix separator to use in case `do_frac_digits()` is greater than zero.<sup>250</sup>

```
charT do_thousands_sep() const;
```

- <sup>2</sup> *Returns:* The digit group separator to use in case `do_grouping()` specifies a digit grouping pattern.<sup>251</sup>

<sup>250</sup>) In common U.S. locales this is '.'.

<sup>251</sup>) In common U.S. locales this is ',', '.

```
string do_grouping() const;
```

- 3 *Returns:* A pattern defined identically as, but not necessarily equal to, the result of `num_punct<charT>::do_grouping()`.<sup>252</sup>

```
string_type do_curr_symbol() const;
```

- 4 *Returns:* A string to use as the currency identifier symbol.<sup>253</sup>

```
string_type do_positive_sign() const;
```

```
string_type do_negative_sign() const;
```

- 5 *Returns:* `do_positive_sign()` returns the string to use to indicate a positive monetary value;<sup>254</sup> `do_negative_sign()` returns the string to use to indicate a negative value.

```
int do_frac_digits() const;
```

- 6 *Returns:* The number of digits after the decimal radix separator, if any.<sup>255</sup>

```
pattern do_pos_format() const;
```

```
pattern do_neg_format() const;
```

- 7 *Returns:* The specializations required in Table 70 (25.3.1.1.1), namely `money_punct<char>`, `money_punct<wchar_t>`, `money_punct<char, true>`, and `money_punct<wchar_t, true>`, return an object of type `pattern` initialized to { symbol, sign, none, value }.<sup>256</sup>

#### 25.4.6.4 Class template `money_punct_byname`

[`locale.money_punct.byname`]

```
namespace std {
 template <class charT, bool Intl = false>
 class money_punct_byname : public money_punct<charT, Intl> {
 public:
 using pattern = money_base::pattern;
 using string_type = basic_string<charT>;

 explicit money_punct_byname(const char*, size_t refs = 0);
 explicit money_punct_byname(const string&, size_t refs = 0);
 protected:
 ~money_punct_byname();
 };
}
```

#### 25.4.7 The message retrieval category

[`category.messages`]

- 1 Class `messages<charT>` implements retrieval of strings from message catalogs.

##### 25.4.7.1 Class template `messages`

[`locale.messages`]

```
namespace std {
 class messages_base {
 public:
 using catalog = unspecified signed integer type;
 };

 template <class charT>
```

252) To specify grouping by 3s, the value is "`\003`" *not* "`3`".

253) For international specializations (second template parameter `true`) this is typically four characters long, usually three letters and a space.

254) This is usually the empty string.

255) In common U.S. locales, this is 2.

256) Note that the international symbol returned by `do_curr_sym()` usually contains a space, itself; for example, "`USD` ".

```

class messages : public locale::facet, public messages_base {
public:
 using char_type = charT;
 using string_type = basic_string<charT>;

 explicit messages(size_t refs = 0);

 catalog open(const basic_string<char>& fn, const locale&) const;
 string_type get(catalog c, int set, int msgid,
 const string_type& default) const;
 void close(catalog c) const;

 static locale::id id;

protected:
 ~messages();
 virtual catalog do_open(const basic_string<char>&, const locale&) const;
 virtual string_type do_get(catalog, int set, int msgid,
 const string_type& default) const;
 virtual void do_close(catalog) const;
};

```

- <sup>1</sup> Values of type `messages_base::catalog` usable as arguments to members `get` and `close` can be obtained only by calling member `open`.

#### 25.4.7.1.1 messages members [locale.messages.members]

```
catalog open(const basic_string<char>& name, const locale& loc) const;
```

- <sup>1</sup> *Returns:* `do_open(name, loc)`.

```
string_type get(catalog cat, int set, int msgid, const string_type& default) const;
```

- <sup>2</sup> *Returns:* `do_get(cat, set, msgid, default)`.

```
void close(catalog cat) const;
```

- <sup>3</sup> *Effects:* Calls `do_close(cat)`.

#### 25.4.7.1.2 messages virtual functions [locale.messages.virtuals]

```
catalog do_open(const basic_string<char>& name, const locale& loc) const;
```

- <sup>1</sup> *Returns:* A value that may be passed to `get()` to retrieve a message from the message catalog identified by the string `name` according to an implementation-defined mapping. The result can be used until it is passed to `close()`.

- <sup>2</sup> Returns a value less than 0 if no such catalog can be opened.

- <sup>3</sup> *Remarks:* The locale argument `loc` is used for character set code conversion when retrieving messages, if needed.

```
string_type do_get(catalog cat, int set, int msgid, const string_type& default) const;
```

- <sup>4</sup> *Requires:* `cat` shall be a catalog obtained from `open()` and not yet closed.

- <sup>5</sup> *Returns:* A message identified by arguments `set`, `msgid`, and `default`, according to an implementation-defined mapping. If no such message can be found, returns `default`.

```
void do_close(catalog cat) const;
```



- 6 *Requires:* `cat` shall be a catalog obtained from `open()` and not yet closed.
- 7 *Effects:* Releases unspecified resources associated with `cat`.
- 8 *Remarks:* The limit on such resources, if any, is implementation-defined.

#### 25.4.7.2 Class template `messages_byname`

[`locale.messages.byname`]

```
namespace std {
 template <class charT>
 class messages_byname : public messages<charT> {
 public:
 using catalog = messages_base::catalog;
 using string_type = basic_string<charT>;

 explicit messages_byname(const char*, size_t refs = 0);
 explicit messages_byname(const string&, size_t refs = 0);
 protected:
 ~messages_byname();
 };
}
```

#### 25.4.8 Program-defined facets

[`facets.examples`]

- 1 A C++ program may define facets to be added to a locale and used identically as the built-in facets. To create a new facet interface, C++ programs simply derive from `locale::facet` a class containing a static member: `static locale::id id`.
- 2 [ *Note:* The locale member function templates verify its type and storage class. — *end note* ]
- 3 [ *Example:* Traditional global localization is still easy:

```
#include <iostream>
#include <locale>
int main(int argc, char** argv) {
 using namespace std;
 locale::global(locale("")); // set the global locale
 // imbue it on all the std streams

 cin.imbue(locale());
 cout.imbue(locale());
 cerr.imbue(locale());
 wcin.imbue(locale());
 wcout.imbue(locale());
 wcerr.imbue(locale());

 return MyObject(argc, argv).doit();
}
```

— *end example*]

- 4 [ *Example:* Greater flexibility is possible:

```
#include <iostream>
#include <locale>
int main() {
 using namespace std;
 cin.imbue(locale("")); // the user's preferred locale
 cout.imbue(locale::classic());
 double f;
 while (cin >> f) cout << f << endl;
 return (cin.fail() != 0);
}
```

```
}

```

In a European locale, with input 3.456,78, output is 3456.78. — *end example*]

- 5 This can be important even for simple programs, which may need to write a data file in a fixed format, regardless of a user's preference.

- 6 [*Example:* Here is an example of the use of locales in a library interface.

```
// file: Date.h
#include <iosfwd>
#include <string>
#include <locale>

class Date {
public:
 Date(unsigned day, unsigned month, unsigned year);
 std::string asString(const std::locale& = std::locale());
};

std::istream& operator>>(std::istream& s, Date& d);
std::ostream& operator<<(std::ostream& s, Date d);

```

- 7 This example illustrates two architectural uses of class `locale`.

- 8 The first is as a default argument in `Date::asString()`, where the default is the global (presumably user-preferred) locale.

- 9 The second is in the operators `<<` and `>>`, where a locale “hitchhikes” on another object, in this case a stream, to the point where it is needed.

```
// file: Date.C
#include "Date" // includes <ctime>
#include <sstream>
std::string Date::asString(const std::locale& l) {
 using namespace std;
 ostringstream s; s.imbue(l);
 s << *this; return s.str();
}

std::istream& operator>>(std::istream& s, Date& d) {
 using namespace std;
 istream::sentry cerberos(s);
 if (cerberos) {
 ios_base::iostate err = goodbit;
 struct tm t;
 use_facet<time_get<char>>(s.getloc()).get_date(s, 0, s, err, &t);
 if (!err) d = Date(t.tm_day, t.tm_mon + 1, t.tm_year + 1900);
 s.setstate(err);
 }
 return s;
}

```

— *end example*]

- 10 A locale object may be extended with a new facet simply by constructing it with an instance of a class derived from `locale::facet`. The only member a C++ program must define is the static member `id`, which identifies your class interface as a new facet.

- 11 [*Example:* Classifying Japanese characters:

```

// file: <jctype>
#include <locale>
namespace My {
 using namespace std;
 class JType : public locale::facet {
 public:
 static locale::id id; // required for use as a new locale facet
 bool is_kanji (wchar_t c) const;
 JType() { }
 protected:
 ~JType() { }
 };
}

// file: filt.C
#include <iostream>
#include <locale>
#include "jctype" // above
std::locale::id My::JType::id; // the static JType member declared above.

int main() {
 using namespace std;
 using wctype = ctype<wchar_t>;
 locale loc(locale(""), // the user's preferred locale ...
 new My::JType); // and a new feature ...
 wchar_t c = use_facet<wctype>(loc).widen('!');
 if (!use_facet<My::JType>(loc).is_kanji(c))
 cout << "no it isn't!" << endl;
}

```

<sup>12</sup> The new facet is used exactly like the built-in facets. — *end example*]

<sup>13</sup> [*Example*: Replacing an existing facet is even easier. The code does not define a member `id` because it is reusing the `numpunct<charT>` facet interface:

```

// file: my_bool.C
#include <iostream>
#include <locale>
#include <string>
namespace My {
 using namespace std;
 using cnumpunct = numpunct_byname<char>;
 class BoolNames : public cnumpunct {
 protected:
 string do_truename() const { return "Oui Oui!"; }
 string do_falsename() const { return "Mais Non!"; }
 ~BoolNames() { }
 public:
 BoolNames(const char* name) : cnumpunct(name) { }
 };
}

int main(int argc, char** argv) {
 using namespace std;
 // make the user's preferred locale, except for...
 locale loc(locale(""), new My::BoolNames(""));
 cout.imbue(loc);
}

```

```
 cout << boolalpha << "Any arguments today? " << (argc > 1) << endl;
}
```

— *end example*]

## 25.5 C library locales

[c.locales]

### 25.5.1 Header <locale> synopsis

[clocale.syn]

```
namespace std {
 struct lconv;

 char* setlocale(int category, const char* locale);
 lconv* localeconv();
}
```

```
#define NULL see 21.2.3
#define LC_ALL see below
#define LC_COLLATE see below
#define LC_CTYPE see below
#define LC_MONETARY see below
#define LC_NUMERIC see below
#define LC_TIME see below
```

- <sup>1</sup> The contents and meaning of the header <locale> are the same as the C standard library header <locale.h>.
- <sup>2</sup> Calls to the function `setlocale` may introduce a data race (20.5.5.9) with other calls to `setlocale` or with calls to the functions listed in Table 81.

SEE ALSO: ISO C 7.11.

Table 81 — Potential `setlocale` data races

|                      |                       |                        |                         |                       |
|----------------------|-----------------------|------------------------|-------------------------|-----------------------|
| <code>fprintf</code> | <code>isprint</code>  | <code>iswdigit</code>  | <code>localeconv</code> | <code>tolower</code>  |
| <code>fscanf</code>  | <code>ispunct</code>  | <code>iswgraph</code>  | <code>mblen</code>      | <code>toupper</code>  |
| <code>isalnum</code> | <code>isspace</code>  | <code>iswlower</code>  | <code>mbstowcs</code>   | <code>towlower</code> |
| <code>isalpha</code> | <code>isupper</code>  | <code>iswprint</code>  | <code>mbtowc</code>     | <code>towupper</code> |
| <code>isblank</code> | <code>iswalnum</code> | <code>iswpunct</code>  | <code>setlocale</code>  | <code>wcscoll</code>  |
| <code>iscntrl</code> | <code>iswalpha</code> | <code>iswspace</code>  | <code>strcoll</code>    | <code>wcstod</code>   |
| <code>isdigit</code> | <code>iswblank</code> | <code>iswupper</code>  | <code>strerror</code>   | <code>wcstombs</code> |
| <code>isgraph</code> | <code>iswcntrl</code> | <code>iswxdigit</code> | <code>strtod</code>     | <code>wcsxfrm</code>  |
| <code>islower</code> | <code>iswctype</code> | <code>isxdigit</code>  | <code>strxfrm</code>    | <code>wctomb</code>   |

## 26 Containers library [containers]

### 26.1 General [containers.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to organize collections of information.
- <sup>2</sup> The following subclauses describe container requirements, and components for sequence containers and associative containers, as summarized in Table 82.

Table 82 — Containers library summary

| Subclause                                             | Header(s)                                                                                                                                                 |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">26.2</a> Requirements                     |                                                                                                                                                           |
| <a href="#">26.3</a> Sequence containers              | <code>&lt;array&gt;</code><br><code>&lt;deque&gt;</code><br><code>&lt;forward_list&gt;</code><br><code>&lt;list&gt;</code><br><code>&lt;vector&gt;</code> |
| <a href="#">26.4</a> Associative containers           | <code>&lt;map&gt;</code><br><code>&lt;set&gt;</code>                                                                                                      |
| <a href="#">26.5</a> Unordered associative containers | <code>&lt;unordered_map&gt;</code><br><code>&lt;unordered_set&gt;</code>                                                                                  |
| <a href="#">26.6</a> Container adaptors               | <code>&lt;queue&gt;</code><br><code>&lt;stack&gt;</code>                                                                                                  |

### 26.2 Container requirements [container.requirements]

#### 26.2.1 General container requirements [container.requirements.general]

- <sup>1</sup> Containers are objects that store other objects. They control allocation and deallocation of these objects through constructors, destructors, insert and erase operations.
- <sup>2</sup> All of the complexity requirements in this Clause are stated solely in terms of the number of operations on the contained objects. [*Example:* The copy constructor of type `vector<vector<int>>` has linear complexity, even though the complexity of copying each contained `vector<int>` is itself linear. — *end example*]
- <sup>3</sup> For the components affected by this subclause that declare an `allocator_type`, objects stored in these components shall be constructed using the function `allocator_traits<allocator_type>::rebind_traits<U>::construct` and destroyed using the function `allocator_traits<allocator_type>::rebind_traits<U>::destroy` (23.10.8.2), where `U` is either `allocator_type::value_type` or an internal type used by the container. These functions are called only for the container's element type, not for internal types used by the container. [*Note:* This means, for example, that a node-based container might need to construct nodes containing aligned buffers and call `construct` to place the element into the buffer. — *end note*]
- <sup>4</sup> In Tables 83, 84, and 85 `X` denotes a container class containing objects of type `T`, `a` and `b` denote values of type `X`, `u` denotes an identifier, `r` denotes a non-const value of type `X`, and `rv` denotes a non-const rvalue of type `X`.

Table 83 — Container requirements

| Expression                                      | Return type                                  | Operational semantics | Assertion/note pre-/post-condition                                                                                  | Complexity   |
|-------------------------------------------------|----------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------|--------------|
| <code>X::value_type</code>                      | T                                            |                       | <i>Requires:</i> T is <b>Erasable</b> from X (see 26.2.1, below)                                                    | compile time |
| <code>X::reference</code>                       | T&                                           |                       |                                                                                                                     | compile time |
| <code>X::const_reference</code>                 | const T&                                     |                       |                                                                                                                     | compile time |
| <code>X::iterator</code>                        | iterator type whose value type is T          |                       | any iterator category that meets the forward iterator requirements. convertible to <code>X::const_iterator</code> . | compile time |
| <code>X::const_iterator</code>                  | constant iterator type whose value type is T |                       | any iterator category that meets the forward iterator requirements.                                                 | compile time |
| <code>X::difference_type</code>                 | signed integer type                          |                       | is identical to the difference type of <code>X::iterator</code> and <code>X::const_iterator</code>                  | compile time |
| <code>X::size_type</code>                       | unsigned integer type                        |                       | <code>size_type</code> can represent any non-negative value of <code>difference_type</code>                         | compile time |
| <code>X u;</code>                               |                                              |                       | <i>Postconditions:</i> <code>u.empty()</code>                                                                       | constant     |
| <code>X()</code>                                |                                              |                       | <i>Postconditions:</i> <code>X().empty()</code>                                                                     | constant     |
| <code>X(a)</code>                               |                                              |                       | <i>Requires:</i> T is <b>CopyInsertable</b> into X (see below).<br><i>Postconditions:</i> <code>a == X(a)</code> .  | linear       |
| <code>X u(a);</code><br><code>X u = a;</code>   |                                              |                       | <i>Requires:</i> T is <b>CopyInsertable</b> into X (see below).<br><i>Postconditions:</i> <code>u == a</code>       | linear       |
| <code>X u(rv);</code><br><code>X u = rv;</code> |                                              |                       | <i>Postconditions:</i> <code>u</code> shall be equal to the value that <code>rv</code> had before this construction | (Note B)     |

Table 83 — Container requirements (continued)

| Expression                     | Return type                                                                                           | Operational semantics                                                                                                                                     | Assertion/note pre-/post-condition                                                                 | Complexity                                                                                |
|--------------------------------|-------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| <code>a = rv</code>            | <code>X&amp;</code>                                                                                   | All existing elements of <code>a</code> are either move assigned to or destroyed                                                                          | <code>a</code> shall be equal to the value that <code>rv</code> had before this assignment         | linear                                                                                    |
| <code>(&amp;a)-&gt;~X()</code> | <code>void</code>                                                                                     |                                                                                                                                                           | the destructor is applied to every element of <code>a</code> ; any memory obtained is deallocated. | linear                                                                                    |
| <code>a.begin()</code>         | <code>iterator;</code><br><code>const_</code><br><code>iterator</code> for<br>constant <code>a</code> |                                                                                                                                                           |                                                                                                    | constant                                                                                  |
| <code>a.end()</code>           | <code>iterator;</code><br><code>const_</code><br><code>iterator</code> for<br>constant <code>a</code> |                                                                                                                                                           |                                                                                                    | constant                                                                                  |
| <code>a.cbegin()</code>        | <code>const_</code><br><code>iterator</code>                                                          | <code>const_cast&lt;X</code><br><code>const&amp;&gt;(a)</code><br><code>.begin();</code>                                                                  |                                                                                                    | constant                                                                                  |
| <code>a.cend()</code>          | <code>const_</code><br><code>iterator</code>                                                          | <code>const_cast&lt;X</code><br><code>const&amp;&gt;(a).end();</code>                                                                                     |                                                                                                    | constant                                                                                  |
| <code>a == b</code>            | convertible to<br><code>bool</code>                                                                   | <code>==</code> is an equivalence relation.<br><code>equal(a.begin(),</code><br><code>a.end(),</code><br><code>b.begin(),</code><br><code>b.end())</code> | <i>Requires:</i> <code>T</code> is<br><code>EqualityComparable</code>                              | Constant if<br><code>a.size() !=</code><br><code>b.size()</code> ,<br>linear<br>otherwise |
| <code>a != b</code>            | convertible to<br><code>bool</code>                                                                   | Equivalent to <code>!(a == b)</code>                                                                                                                      |                                                                                                    | linear                                                                                    |
| <code>a.swap(b)</code>         | <code>void</code>                                                                                     |                                                                                                                                                           | exchanges the contents of <code>a</code> and <code>b</code>                                        | (Note A)                                                                                  |
| <code>swap(a, b)</code>        | <code>void</code>                                                                                     | <code>a.swap(b)</code>                                                                                                                                    |                                                                                                    | (Note A)                                                                                  |
| <code>r = a</code>             | <code>X&amp;</code>                                                                                   |                                                                                                                                                           | <i>Postconditions:</i> <code>r == a</code> .                                                       | linear                                                                                    |
| <code>a.size()</code>          | <code>size_type</code>                                                                                | <code>distance(a.begin(),</code><br><code>a.end())</code>                                                                                                 |                                                                                                    | constant                                                                                  |
| <code>a.max_size()</code>      | <code>size_type</code>                                                                                | <code>distance(begin(),</code><br><code>end())</code> for the largest possible container                                                                  |                                                                                                    | constant                                                                                  |
| <code>a.empty()</code>         | convertible to<br><code>bool</code>                                                                   | <code>a.begin() ==</code><br><code>a.end()</code>                                                                                                         |                                                                                                    | constant                                                                                  |

Those entries marked “(Note A)” or “(Note B)” have linear complexity for `array` and have constant complexity for all other standard containers. [ *Note:* The algorithm `equal()` is defined in Clause 28. — *end note* ]

- 5 The member function `size()` returns the number of elements in the container. The number of elements is defined by the rules of constructors, inserts, and erases.
- 6 `begin()` returns an iterator referring to the first element in the container. `end()` returns an iterator which is the past-the-end value for the container. If the container is empty, then `begin() == end()`.
- 7 In the expressions

```

i == j
i != j
i < j
i <= j
i >= j
i > j
i - j

```

where `i` and `j` denote objects of a container's `iterator` type, either or both may be replaced by an object of the container's `const_iterator` type referring to the same element with no change in semantics.

- 8 Unless otherwise specified, all containers defined in this clause obtain memory using an allocator (see 20.5.3.5). [Note: In particular, containers and iterators do not store references to allocated elements other than through the allocator's pointer type, i.e., as objects of type `P` or `pointer_traits<P>::template rebind<unspecified>`, where `P` is `allocator_traits<allocator_type>::pointer`. — end note] Copy constructors for these container types obtain an allocator by calling `allocator_traits<allocator_type>::select_on_container_copy_construction` on the allocator belonging to the container being copied. Move constructors obtain an allocator by move construction from the allocator belonging to the container being moved. Such move construction of the allocator shall not exit via an exception. All other constructors for these container types take a `const allocator_type&` argument. [Note: If an invocation of a constructor uses the default value of an optional allocator argument, then the `Allocator` type must support value-initialization. — end note] A copy of this allocator is used for any memory allocation and element construction performed, by these constructors and by all member functions, during the lifetime of each container object or until the allocator is replaced. The allocator may be replaced only via assignment or `swap()`. Allocator replacement is performed by copy assignment, move assignment, or swapping of the allocator only if `allocator_traits<allocator_type>::propagate_on_container_copy_assignment::value`, `allocator_traits<allocator_type>::propagate_on_container_move_assignment::value`, or `allocator_traits<allocator_type>::propagate_on_container_swap::value` is `true` within the implementation of the corresponding container operation. In all container types defined in this Clause, the member `get_allocator()` returns a copy of the allocator used to construct the container or, if that allocator has been replaced, a copy of the most recent replacement.
- 9 The expression `a.swap(b)`, for containers `a` and `b` of a standard container type other than `array`, shall exchange the values of `a` and `b` without invoking any move, copy, or swap operations on the individual container elements. Lvalues of any `Compare`, `Pred`, or `Hash` types belonging to `a` and `b` shall be swappable and shall be exchanged by calling `swap` as described in 20.5.3.2. If `allocator_traits<allocator_type>::propagate_on_container_swap::value` is `true`, then lvalues of type `allocator_type` shall be swappable and the allocators of `a` and `b` shall also be exchanged by calling `swap` as described in 20.5.3.2. Otherwise, the allocators shall not be swapped, and the behavior is undefined unless `a.get_allocator() == b.get_allocator()`. Every iterator referring to an element in one container before the swap shall refer to the same element in the other container after the swap. It is unspecified whether an iterator with value `a.end()` before the swap will have value `b.end()` after the swap.
- 10 If the iterator type of a container belongs to the bidirectional or random access iterator categories (27.2), the container is called *reversible* and satisfies the additional requirements in Table 84.



Table 84 — Reversible container requirements

| Expression                             | Return type                                                                           | Assertion/note<br>pre-/post-condition                   | Complexity   |
|----------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------|--------------|
| <code>X::reverse_iterator</code>       | iterator type whose value type is T                                                   | <code>reverse_iterator&lt;iterator&gt;</code>           | compile time |
| <code>X::const_reverse_iterator</code> | constant iterator type whose value type is T                                          | <code>reverse_iterator&lt;const_iterator&gt;</code>     | compile time |
| <code>a.rbegin()</code>                | <code>reverse_iterator</code> ;<br><code>const_reverse_iterator</code> for constant a | <code>reverse_iterator(end())</code>                    | constant     |
| <code>a.rend()</code>                  | <code>reverse_iterator</code> ;<br><code>const_reverse_iterator</code> for constant a | <code>reverse_iterator(begin())</code>                  | constant     |
| <code>a.crbegin()</code>               | <code>const_reverse_iterator</code>                                                   | <code>const_cast&lt;X const&amp;&gt;(a).rbegin()</code> | constant     |
| <code>a.crend()</code>                 | <code>const_reverse_iterator</code>                                                   | <code>const_cast&lt;X const&amp;&gt;(a).rend()</code>   | constant     |

<sup>11</sup> Unless otherwise specified (see 26.2.6.1, 26.2.7.1, 26.3.8.4, and 26.3.11.5) all container types defined in this Clause meet the following additional requirements:

- (11.1) — if an exception is thrown by an `insert()` or `emplace()` function while inserting a single element, that function has no effects.
- (11.2) — if an exception is thrown by a `push_back()`, `push_front()`, `emplace_back()`, or `emplace_front()` function, that function has no effects.
- (11.3) — no `erase()`, `clear()`, `pop_back()` or `pop_front()` function throws an exception.
- (11.4) — no copy constructor or assignment operator of a returned iterator throws an exception.
- (11.5) — no `swap()` function throws an exception.
- (11.6) — no `swap()` function invalidates any references, pointers, or iterators referring to the elements of the containers being swapped. [Note: The `end()` iterator does not refer to any element, so it may be invalidated. — end note]

<sup>12</sup> Unless otherwise specified (either explicitly or by defining a function in terms of other functions), invoking a container member function or passing a container as an argument to a library function shall not invalidate iterators to, or change the values of, objects within that container.

<sup>13</sup> A *contiguous container* is a container that supports random access iterators (27.2.7) and whose member types `iterator` and `const_iterator` are contiguous iterators (27.2.1).

<sup>14</sup> Table 85 lists operations that are provided for some types of containers but not others. Those containers for which the listed operations are provided shall implement the semantics described in Table 85 unless otherwise stated.

Table 85 — Optional container operations

| Expression             | Return type                      | Operational semantics                                                        | Assertion/note pre-/post-condition                                                                                               | Complexity |
|------------------------|----------------------------------|------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>a &lt; b</code>  | convertible to <code>bool</code> | <code>lexicographical_compare(a.begin(), a.end(), b.begin(), b.end())</code> | <i>Requires:</i> <code>&lt;</code> is defined for values of <code>T</code> . <code>&lt;</code> is a total ordering relationship. | linear     |
| <code>a &gt; b</code>  | convertible to <code>bool</code> | <code>b &lt; a</code>                                                        |                                                                                                                                  | linear     |
| <code>a &lt;= b</code> | convertible to <code>bool</code> | <code>!(a &gt; b)</code>                                                     |                                                                                                                                  | linear     |
| <code>a &gt;= b</code> | convertible to <code>bool</code> | <code>!(a &lt; b)</code>                                                     |                                                                                                                                  | linear     |

[ *Note:* The algorithm `lexicographical_compare()` is defined in Clause 28. — *end note* ]

- 15 All of the containers defined in this Clause and in 24.3.2 except `array` meet the additional requirements of an allocator-aware container, as described in Table 86.

Given an allocator type `A` and given a container type `X` having a `value_type` identical to `T` and an `allocator_type` identical to `allocator_traits<A>::rebind_alloc<T>` and given an lvalue `m` of type `A`, a pointer `p` of type `T*`, an expression `v` of type (possibly `const`) `T`, and an rvalue `rv` of type `T`, the following terms are defined. If `X` is not allocator-aware, the terms below are defined as if `A` were `allocator<T>` — no allocator object needs to be created and user specializations of `allocator<T>` are not instantiated:

- (15.1) — `T` is *DefaultInsertable* into `X` means that the following expression is well-formed:
- ```
allocator_traits<A>::construct(m, p)
```
- (15.2) — An element of `X` is *default-inserted* if it is initialized by evaluation of the expression
- ```
allocator_traits<A>::construct(m, p)
```
- where `p` is the address of the uninitialized storage for the element allocated within `X`.
- (15.3) — `T` is *MoveInsertable* into `X` means that the following expression is well-formed:
- ```
allocator_traits<A>::construct(m, p, rv)
```
- and its evaluation causes the following postcondition to hold: The value of `*p` is equivalent to the value of `rv` before the evaluation. [*Note:* `rv` remains a valid object. Its state is unspecified — *end note*]
- (15.4) — `T` is *CopyInsertable* into `X` means that, in addition to `T` being *MoveInsertable* into `X`, the following expression is well-formed:
- ```
allocator_traits<A>::construct(m, p, v)
```
- and its evaluation causes the following postcondition to hold: The value of `v` is unchanged and is equivalent to `*p`.
- (15.5) — `T` is *EmplaceConstructible* into `X` from `args`, for zero or more arguments `args`, means that the following expression is well-formed:
- ```
allocator_traits<A>::construct(m, p, args)
```
- (15.6) — `T` is *Erasable* from `X` means that the following expression is well-formed:
- ```
allocator_traits<A>::destroy(m, p)
```

[*Note:* A container calls `allocator_traits<A>::construct(m, p, args)` to construct an element at `p` using `args`, with `m == get_allocator()`. The default `construct` in `allocator` will call `::new((void*)p) T(args)`, but specialized allocators may choose a different definition. — *end note*]

- <sup>16</sup> In Table 86, `X` denotes an allocator-aware container class with a `value_type` of `T` using allocator of type `A`, `u` denotes a variable, `a` and `b` denote non-const lvalues of type `X`, `t` denotes an lvalue or a const rvalue of type `X`, `rv` denotes a non-const rvalue of type `X`, and `m` is a value of type `A`.

Table 86 — Allocator-aware container requirements

| Expression                                        | Return type         | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                        | Complexity                                                                |
|---------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <code>allocator_-type</code>                      | <code>A</code>      | <i>Requires:</i><br><code>allocator_type::value_type</code><br>is the same as <code>X::value_type</code> .                                                                                                                                                                                   | compile time                                                              |
| <code>get_allocator()</code>                      | <code>A</code>      |                                                                                                                                                                                                                                                                                              | constant                                                                  |
| <code>X()</code><br><code>X u;</code>             |                     | <i>Requires:</i> <code>A</code> is<br><code>DefaultConstructible</code> .<br><i>Postconditions:</i> <code>u.empty()</code><br>returns <code>true</code> ,<br><code>u.get_allocator() == A()</code>                                                                                           | constant                                                                  |
| <code>X(m)</code><br><code>X u(m);</code>         |                     | <i>Postconditions:</i> <code>u.empty()</code><br>returns <code>true</code> ,<br><code>u.get_allocator() == m</code>                                                                                                                                                                          | constant                                                                  |
| <code>X(t, m)</code><br><code>X u(t, m);</code>   |                     | <i>Requires:</i> <code>T</code> is <code>CopyInsertable</code><br>into <code>X</code> .<br><i>Postconditions:</i> <code>u == t</code> ,<br><code>u.get_allocator() == m</code>                                                                                                               | linear                                                                    |
| <code>X(rv)</code><br><code>X u(rv);</code>       |                     | <i>Postconditions:</i> <code>u</code> shall have the<br>same elements as <code>rv</code> had before<br>this construction; the value of<br><code>u.get_allocator()</code> shall be<br>the same as the value of<br><code>rv.get_allocator()</code> before<br>this construction.                | constant                                                                  |
| <code>X(rv, m)</code><br><code>X u(rv, m);</code> |                     | <i>Requires:</i> <code>T</code> is <code>MoveInsertable</code><br>into <code>X</code> .<br><i>Postconditions:</i> <code>u</code> shall have the<br>same elements, or copies of the<br>elements, that <code>rv</code> had before<br>this construction,<br><code>u.get_allocator() == m</code> | constant if <code>m == rv.get_allocator()</code> ,<br>otherwise<br>linear |
| <code>a = t</code>                                | <code>X&amp;</code> | <i>Requires:</i> <code>T</code> is <code>CopyInsertable</code><br>into <code>X</code> and <code>CopyAssignable</code> .<br><i>Postconditions:</i> <code>a == t</code>                                                                                                                        | linear                                                                    |

Table 86 — Allocator-aware container requirements (continued)

| Expression             | Return type         | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                      | Complexity |
|------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>a = rv</code>    | <code>X&amp;</code> | <i>Requires:</i> If <code>allocator_traits&lt;allocator_type&gt;::propagate_on_container_move_assignment::value</code> is <code>false</code> , <code>T</code> is <code>MoveInsertable</code> into <code>X</code> and <code>MoveAssignable</code> . All existing elements of <code>a</code> are either move assigned to or destroyed.<br><i>Postconditions:</i> <code>a</code> shall be equal to the value that <code>rv</code> had before this assignment. | linear     |
| <code>a.swap(b)</code> | <code>void</code>   | exchanges the contents of <code>a</code> and <code>b</code>                                                                                                                                                                                                                                                                                                                                                                                                | constant   |

- <sup>17</sup> The behavior of certain container member functions and deduction guides depends on whether types qualify as input iterators or allocators. The extent to which an implementation determines that a type cannot be an input iterator is unspecified, except that as a minimum integral types shall not qualify as input iterators. Likewise, the extent to which an implementation determines that a type cannot be an allocator is unspecified, except that as a minimum a type `A` shall not qualify as an allocator unless it satisfies both of the following conditions:

- (17.1) — The *qualified-id* `A::value_type` is valid and denotes a type (17.8.2).
- (17.2) — The expression `declval<A&>().allocate(size_t{})` is well-formed when treated as an unevaluated operand.

### 26.2.2 Container data races

[container.requirements.dataraces]

- <sup>1</sup> For purposes of avoiding data races (20.5.5.9), implementations shall consider the following functions to be `const`: `begin`, `end`, `rbegin`, `rend`, `front`, `back`, `data`, `find`, `lower_bound`, `upper_bound`, `equal_range`, `at` and, except in associative or unordered associative containers, `operator[]`.
- <sup>2</sup> Notwithstanding 20.5.5.9, implementations are required to avoid data races when the contents of the contained object in different elements in the same container, excepting `vector<bool>`, are modified concurrently.
- <sup>3</sup> [Note: For a `vector<int> x` with a size greater than one, `x[1] = 5` and `*x.begin() = 10` can be executed concurrently without a data race, but `x[0] = 5` and `*x.begin() = 10` executed concurrently may result in a data race. As an exception to the general rule, for a `vector<bool> y`, `y[0] = true` may race with `y[1] = true`. — end note]

### 26.2.3 Sequence containers

[sequence.reqmts]

- <sup>1</sup> A sequence container organizes a finite set of objects, all of the same type, into a strictly linear arrangement. The library provides four basic kinds of sequence containers: `vector`, `forward_list`, `list`, and `deque`. In addition, `array` is provided as a sequence container which provides limited sequence operations because it has a fixed number of elements. The library also provides container adaptors that make it easy to construct abstract data types, such as `stacks` or `queues`, out of the basic sequence container kinds (or out of other kinds of sequence containers that the user might define).
- <sup>2</sup> The sequence containers offer the programmer different complexity trade-offs and should be used accordingly. `vector` or `array` is the type of sequence container that should be used by default. `list` or `forward_list`

should be used when there are frequent insertions and deletions from the middle of the sequence. `deque` is the data structure of choice when most insertions and deletions take place at the beginning or at the end of the sequence.

- <sup>3</sup> In Tables 87 and 88, `X` denotes a sequence container class, `a` denotes a value of type `X` containing elements of type `T`, `u` denotes the name of a variable being declared, `A` denotes `X::allocator_type` if the *qualified-id* `X::allocator_type` is valid and denotes a type (17.8.2) and `allocator<T>` if it doesn't, `i` and `j` denote iterators satisfying input iterator requirements and refer to elements implicitly convertible to `value_type`, `[i, j)` denotes a valid range, `il` designates an object of type `initializer_list<value_type>`, `n` denotes a value of type `X::size_type`, `p` denotes a valid constant iterator to `a`, `q` denotes a valid dereferenceable constant iterator to `a`, `[q1, q2)` denotes a valid range of constant iterators in `a`, `t` denotes an lvalue or a const rvalue of `X::value_type`, and `rv` denotes a non-const rvalue of `X::value_type`. `Args` denotes a template parameter pack; `args` denotes a function parameter pack with the pattern `Args&&`.
- <sup>4</sup> The complexities of the expressions are sequence dependent.

Table 87 — Sequence container requirements (in addition to container)

| Expression                                      | Return type           | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>X(n, t)</code><br><code>X u(n, t);</code> |                       | <i>Requires:</i> <code>T</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Postconditions:</i> <code>distance(begin(), end()) == n</code><br>Constructs a sequence container with <code>n</code> copies of <code>t</code>                                                                                                                                                                                                                                                                                                         |
| <code>X(i, j)</code><br><code>X u(i, j);</code> |                       | <i>Requires:</i> <code>T</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>*i</code> . For <code>vector</code> , if the iterator does not meet the forward iterator requirements (27.2.5), <code>T</code> shall also be <code>MoveInsertable</code> into <code>X</code> . Each iterator in the range <code>[i, j)</code> shall be dereferenced exactly once.<br><i>Postconditions:</i> <code>distance(begin(), end()) == distance(i, j)</code><br>Constructs a sequence container equal to the range <code>[i, j)</code> |
| <code>X(il)</code>                              |                       | Equivalent to <code>X(il.begin(), il.end())</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>a = il</code>                             | <code>X&amp;</code>   | <i>Requires:</i> <code>T</code> is <code>CopyInsertable</code> into <code>X</code> and <code>CopyAssignable</code> . Assigns the range <code>[il.begin(), il.end())</code> into <code>a</code> . All existing elements of <code>a</code> are either assigned to or destroyed.<br><i>Returns:</i> <code>*this</code> .                                                                                                                                                                                                                                   |
| <code>a.emplace(p, args)</code>                 | <code>iterator</code> | <i>Requires:</i> <code>T</code> is <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> . For <code>vector</code> and <code>deque</code> , <code>T</code> is also <code>MoveInsertable</code> into <code>X</code> and <code>MoveAssignable</code> .<br><i>Effects:</i> Inserts an object of type <code>T</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> before <code>p</code> .                                                                                                                         |

Table 87 — Sequence container requirements (in addition to container) (continued)

| Expression                   | Return type | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                   |
|------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a.insert(p,t)</code>   | iterator    | <i>Requires:</i> T shall be CopyInsertable into X. For vector and deque, T shall also be CopyAssignable.<br><i>Effects:</i> Inserts a copy of t before p.                                                                                                                                                                                                               |
| <code>a.insert(p,rv)</code>  | iterator    | <i>Requires:</i> T shall be MoveInsertable into X. For vector and deque, T shall also be MoveAssignable.<br><i>Effects:</i> Inserts a copy of rv before p.                                                                                                                                                                                                              |
| <code>a.insert(p,n,t)</code> | iterator    | <i>Requires:</i> T shall be CopyInsertable into X and CopyAssignable.<br>Inserts n copies of t before p.                                                                                                                                                                                                                                                                |
| <code>a.insert(p,i,j)</code> | iterator    | <i>Requires:</i> T shall be EmplaceConstructible into X from *i. For vector and deque, T shall also be MoveInsertable into X, MoveConstructible, MoveAssignable, and swappable (20.5.3.2). Each iterator in the range [i, j) shall be dereferenced exactly once.<br><i>Requires:</i> i and j are not iterators into a.<br>Inserts copies of elements in [i, j) before p |
| <code>a.insert(p, il)</code> | iterator    | <code>a.insert(p, il.begin(), il.end())</code> .                                                                                                                                                                                                                                                                                                                        |
| <code>a.erase(q)</code>      | iterator    | <i>Requires:</i> For vector and deque, T shall be MoveAssignable.<br><i>Effects:</i> Erases the element pointed to by q.                                                                                                                                                                                                                                                |
| <code>a.erase(q1,q2)</code>  | iterator    | <i>Requires:</i> For vector and deque, T shall be MoveAssignable.<br><i>Effects:</i> Erases the elements in the range [q1, q2).                                                                                                                                                                                                                                         |
| <code>a.clear()</code>       | void        | Destroys all elements in a. Invalidates all references, pointers, and iterators referring to the elements of a and may invalidate the past-the-end iterator.<br><i>Postconditions:</i> <code>a.empty()</code> returns true.<br><i>Complexity:</i> Linear.                                                                                                               |

Table 87 — Sequence container requirements (in addition to container) (continued)

| Expression                  | Return type       | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a.assign(i, j)</code> | <code>void</code> | <i>Requires:</i> T shall be <code>EmplaceConstructible</code> into X from <code>*i</code> and assignable from <code>*i</code> . For <code>vector</code> , if the iterator does not meet the forward iterator requirements (27.2.5), T shall also be <code>MoveInsertable</code> into X.<br>Each iterator in the range <code>[i, j)</code> shall be dereferenced exactly once.<br><i>Requires:</i> <code>i, j</code> are not iterators into <code>a</code> .<br>Replaces elements in <code>a</code> with a copy of <code>[i, j)</code> .<br>Invalidates all references, pointers and iterators referring to the elements of <code>a</code> . For <code>vector</code> and <code>deque</code> , also invalidates the past-the-end iterator. |
| <code>a.assign(il)</code>   | <code>void</code> | <code>a.assign(il.begin(), il.end())</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>a.assign(n, t)</code> | <code>void</code> | <i>Requires:</i> T shall be <code>CopyInsertable</code> into X and <code>CopyAssignable</code> .<br><i>Requires:</i> <code>t</code> is not a reference into <code>a</code> .<br>Replaces elements in <code>a</code> with <code>n</code> copies of <code>t</code> .<br>Invalidates all references, pointers and iterators referring to the elements of <code>a</code> . For <code>vector</code> and <code>deque</code> , also invalidates the past-the-end iterator.                                                                                                                                                                                                                                                                      |

- <sup>5</sup> The iterator returned from `a.insert(p, t)` points to the copy of `t` inserted into `a`.
- <sup>6</sup> The iterator returned from `a.insert(p, rv)` points to the copy of `rv` inserted into `a`.
- <sup>7</sup> The iterator returned from `a.insert(p, n, t)` points to the copy of the first element inserted into `a`, or `p` if `n == 0`.
- <sup>8</sup> The iterator returned from `a.insert(p, i, j)` points to the copy of the first element inserted into `a`, or `p` if `i == j`.
- <sup>9</sup> The iterator returned from `a.insert(p, il)` points to the copy of the first element inserted into `a`, or `p` if `il` is empty.
- <sup>10</sup> The iterator returned from `a.emplace(p, args)` points to the new element constructed from `args` into `a`.
- <sup>11</sup> The iterator returned from `a.erase(q)` points to the element immediately following `q` prior to the element being erased. If no such element exists, `a.end()` is returned.
- <sup>12</sup> The iterator returned by `a.erase(q1, q2)` points to the element pointed to by `q2` prior to any elements being erased. If no such element exists, `a.end()` is returned.
- <sup>13</sup> For every sequence container defined in this Clause and in Clause 24:
- (13.1) — If the constructor

```
template <class InputIterator>
X(InputIterator first, InputIterator last,
 const allocator_type& alloc = allocator_type());
```

is called with a type `InputIterator` that does not qualify as an input iterator, then the constructor shall not participate in overload resolution.

- (13.2) — If the member functions of the forms:

```
template <class InputIterator>
 return-type F(const_iterator p,
 InputIterator first, InputIterator last); // such as insert

template <class InputIterator>
 return-type F(InputIterator first, InputIterator last); // such as append, assign

template <class InputIterator>
 return-type F(const_iterator i1, const_iterator i2,
 InputIterator first, InputIterator last); // such as replace
```

are called with a type `InputIterator` that does not qualify as an input iterator, then these functions shall not participate in overload resolution.

- (13.3) — A deduction guide for a sequence container shall not participate in overload resolution if it has an `InputIterator` template parameter and a type that does not qualify as an input iterator is deduced for that parameter, or if it has an `Allocator` template parameter and a type that does not qualify as an allocator is deduced for that parameter.

- <sup>14</sup> Table 88 lists operations that are provided for some types of sequence containers but not others. An implementation shall provide these operations for all container types shown in the “container” column, and shall implement them so as to take amortized constant time.

Table 88 — Optional sequence container operations

| Expression                         | Return type                                                            | Operational semantics                                                                                                                                                                                                                                                                        | Container                                                                                                                                          |
|------------------------------------|------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a.front()</code>             | reference; <code>const_reference</code><br>for constant <code>a</code> | <code>*a.begin()</code>                                                                                                                                                                                                                                                                      | <code>basic_string</code> ,<br><code>array</code> , <code>deque</code> ,<br><code>forward_list</code> ,<br><code>list</code> , <code>vector</code> |
| <code>a.back()</code>              | reference; <code>const_reference</code><br>for constant <code>a</code> | { <code>auto tmp = a.end();</code><br><code>--tmp;</code><br><code>return *tmp;</code> }                                                                                                                                                                                                     | <code>basic_string</code> ,<br><code>array</code> , <code>deque</code> ,<br><code>list</code> , <code>vector</code>                                |
| <code>a.emplace_front(args)</code> | reference                                                              | Prepends an object of type <code>T</code><br>constructed with<br><code>std::forward&lt;Args&gt;(args)...</code><br><i>Requires:</i> <code>T</code> shall be<br><code>EmplaceConstructible</code> into <code>X</code><br>from <code>args</code> .<br><i>Returns:</i> <code>a.front()</code> . | <code>deque</code> ,<br><code>forward_list</code> ,<br><code>list</code>                                                                           |



Table 88 — Optional sequence container operations (continued)

| Expression                        | Return type                                               | Operational semantics                                                                                                                                                                                                                                                                                                                                                                     | Container                          |
|-----------------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| <code>a.emplace_back(args)</code> | reference                                                 | Appends an object of type <code>T</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> .<br><i>Requires:</i> <code>T</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> . For <code>vector</code> , <code>T</code> shall also be <code>MoveInsertable</code> into <code>X</code> .<br><i>Returns:</i> <code>a.back()</code> . | deque, list, vector                |
| <code>a.push_front(t)</code>      | void                                                      | Prepends a copy of <code>t</code> .<br><i>Requires:</i> <code>T</code> shall be <code>CopyInsertable</code> into <code>X</code> .                                                                                                                                                                                                                                                         | deque, forward_list, list          |
| <code>a.push_front(rv)</code>     | void                                                      | Prepends a copy of <code>rv</code> .<br><i>Requires:</i> <code>T</code> shall be <code>MoveInsertable</code> into <code>X</code> .                                                                                                                                                                                                                                                        | deque, forward_list, list          |
| <code>a.push_back(t)</code>       | void                                                      | Appends a copy of <code>t</code> .<br><i>Requires:</i> <code>T</code> shall be <code>CopyInsertable</code> into <code>X</code> .                                                                                                                                                                                                                                                          | basic_string, deque, list, vector  |
| <code>a.push_back(rv)</code>      | void                                                      | Appends a copy of <code>rv</code> .<br><i>Requires:</i> <code>T</code> shall be <code>MoveInsertable</code> into <code>X</code> .                                                                                                                                                                                                                                                         | basic_string, deque, list, vector  |
| <code>a.pop_front()</code>        | void                                                      | Destroys the first element.<br><i>Requires:</i> <code>a.empty()</code> shall be <code>false</code> .                                                                                                                                                                                                                                                                                      | deque, forward_list, list          |
| <code>a.pop_back()</code>         | void                                                      | Destroys the last element.<br><i>Requires:</i> <code>a.empty()</code> shall be <code>false</code> .                                                                                                                                                                                                                                                                                       | basic_string, deque, list, vector  |
| <code>a[n]</code>                 | reference; const_reference<br>for constant <code>a</code> | <code>*(a.begin() + n)</code>                                                                                                                                                                                                                                                                                                                                                             | basic_string, array, deque, vector |
| <code>a.at(n)</code>              | reference; const_reference<br>for constant <code>a</code> | <code>*(a.begin() + n)</code>                                                                                                                                                                                                                                                                                                                                                             | basic_string, array, deque, vector |

- <sup>15</sup> The member function `at()` provides bounds-checked access to container elements. `at()` throws `out_of_range` if `n >= a.size()`.

## 26.2.4 Node handles

[container.node]

### 26.2.4.1 node\_handle overview

[container.node.overview]

- <sup>1</sup> A *node handle* is an object that accepts ownership of a single element from an associative container (26.2.6) or an unordered associative container (26.2.7). It may be used to transfer that ownership to another container with compatible nodes. Containers with compatible nodes have the same node handle type. Elements may be transferred in either direction between container types in the same row of Table 89.
- <sup>2</sup> If a node handle is not empty, then it contains an allocator that is equal to the allocator of the container when the element was extracted. If a node handle is empty, it contains no allocator.

Table 89 — Container types with compatible nodes

|                                                   |                                                        |
|---------------------------------------------------|--------------------------------------------------------|
| <code>map&lt;K, T, C1, A&gt;</code>               | <code>map&lt;K, T, C2, A&gt;</code>                    |
| <code>map&lt;K, T, C1, A&gt;</code>               | <code>multimap&lt;K, T, C2, A&gt;</code>               |
| <code>set&lt;K, C1, A&gt;</code>                  | <code>set&lt;K, C2, A&gt;</code>                       |
| <code>set&lt;K, C1, A&gt;</code>                  | <code>multiset&lt;K, C2, A&gt;</code>                  |
| <code>unordered_map&lt;K, T, H1, E1, A&gt;</code> | <code>unordered_map&lt;K, T, H2, E2, A&gt;</code>      |
| <code>unordered_map&lt;K, T, H1, E1, A&gt;</code> | <code>unordered_multimap&lt;K, T, H2, E2, A&gt;</code> |
| <code>unordered_set&lt;K, H1, E1, A&gt;</code>    | <code>unordered_set&lt;K, H2, E2, A&gt;</code>         |
| <code>unordered_set&lt;K, H1, E1, A&gt;</code>    | <code>unordered_multiset&lt;K, H2, E2, A&gt;</code>    |

- <sup>3</sup> Class `node_handle` is for exposition only. An implementation is permitted to provide equivalent functionality without providing a class with this name.
- <sup>4</sup> If a user-defined specialization of `pair` exists for `pair<const Key, T>` or `pair<Key, T>`, where `Key` is the container's `key_type` and `T` is the container's `mapped_type`, the behavior of operations involving node handles is undefined.

```
template<unspecified>
class node_handle {
public:
 // These type declarations are described in Tables 90 and 91.
 using value_type = see below; // not present for map containers
 using key_type = see below; // not present for set containers
 using mapped_type = see below; // not present for set containers
 using allocator_type = see below;

private:
 using container_node_type = unspecified;
 using ator_traits = allocator_traits<allocator_type>;

 typename ator_traits::rebind_traits<container_node_type>::pointer ptr_;
 optional<allocator_type> alloc_;

public:
 constexpr node_handle() noexcept : ptr_(), alloc_() {}
 ~node_handle();
 node_handle(node_handle&&) noexcept;
 node_handle& operator=(node_handle&&);

 value_type& value() const; // not present for map containers
 key_type& key() const; // not present for set containers
 mapped_type& mapped() const; // not present for set containers

 allocator_type get_allocator() const;
 explicit operator bool() const noexcept;
 bool empty() const noexcept;

 void swap(node_handle&)
 noexcept(ator_traits::propagate_on_container_swap::value ||
 ator_traits::is_always_equal::value);

 friend void swap(node_handle& x, node_handle& y) noexcept(noexcept(x.swap(y))) {
```

```

 x.swap(y);
 }
};

```

#### 26.2.4.2 *node\_handle* constructors, copy, and assignment

[container.node.cons]

```
node_handle(node_handle&& nh) noexcept;
```

- 1 *Effects:* Constructs a *node\_handle* object initializing *ptr\_* with *nh.ptr\_*. Move constructs *alloc\_* with *nh.alloc\_*. Assigns *nullptr* to *nh.ptr\_* and assigns *nullopt* to *nh.alloc\_*.

```
node_handle& operator=(node_handle&& nh);
```

- 2 *Requires:* Either *!alloc\_*, or *ator\_traits::propagate\_on\_container\_move\_assignment* is *true*, or *alloc\_ == nh.alloc\_*.

- 3 *Effects:*

- (3.1) — If *ptr\_ != nullptr*, destroys the *value\_type* subobject in the *container\_node\_type* object pointed to by *ptr\_* by calling *ator\_traits::destroy*, then deallocates *ptr\_* by calling *ator\_traits::rebind\_traits<container\_node\_type>::deallocate*.
- (3.2) — Assigns *nh.ptr\_* to *ptr\_*.
- (3.3) — If *!alloc\_* or *ator\_traits::propagate\_on\_container\_move\_assignment* is *true*, move assigns *nh.alloc\_* to *alloc\_*.
- (3.4) — Assigns *nullptr* to *nh.ptr\_* and assigns *nullopt* to *nh.alloc\_*.

- 4 *Returns:* *\*this*.

- 5 *Throws:* Nothing.

#### 26.2.4.3 *node\_handle* destructor

[container.node.dtor]

```
~node_handle();
```

- 1 *Effects:* If *ptr\_ != nullptr*, destroys the *value\_type* subobject in the *container\_node\_type* object pointed to by *ptr\_* by calling *ator\_traits::destroy*, then deallocates *ptr\_* by calling *ator\_traits::rebind\_traits<container\_node\_type>::deallocate*.

#### 26.2.4.4 *node\_handle* observers

[container.node.observers]

```
value_type& value() const;
```

- 1 *Requires:* *empty() == false*.

- 2 *Returns:* A reference to the *value\_type* subobject in the *container\_node\_type* object pointed to by *ptr\_*.

- 3 *Throws:* Nothing.

```
key_type& key() const;
```

- 4 *Requires:* *empty() == false*.

- 5 *Returns:* A non-const reference to the *key\_type* member of the *value\_type* subobject in the *container\_node\_type* object pointed to by *ptr\_*.

- 6 *Throws:* Nothing.

- 7 *Remarks:* Modifying the key through the returned reference is permitted.

```
mapped_type& mapped() const;
```

- 8 *Requires:* *empty() == false*.

9 *Returns:* A reference to the `mapped_type` member of the `value_type` subobject in the `container_node_type` object pointed to by `ptr_`.

10 *Throws:* Nothing.

```
allocator_type get_allocator() const;
```

11 *Requires:* `empty() == false`.

12 *Returns:* `*alloc_`.

13 *Throws:* Nothing.

```
explicit operator bool() const noexcept;
```

14 *Returns:* `ptr_ != nullptr`.

```
bool empty() const noexcept;
```

15 *Returns:* `ptr_ == nullptr`.

#### 26.2.4.5 `node_handle` modifiers [container.node.modifiers]

```
void swap(node_handle& nh)
 noexcept(ator_traits::propagate_on_container_swap::value ||
 ator_traits::is_always_equal::value);
```

1 *Requires:* `!alloc_`, or `!nh.alloc_`, or `ator_traits::propagate_on_container_swap` is true, or `alloc_ == nh.alloc_`.

2 *Effects:* Calls `swap(ptr_, nh.ptr_)`. If `!alloc_`, or `!nh.alloc_`, or `ator_traits::propagate_on_container_swap` is true calls `swap(alloc_, nh.alloc_)`.

#### 26.2.5 Insert return type [container.insert.return]

1 The associative containers with unique keys and the unordered containers with unique keys have a member function `insert` that returns a nested type `insert_return_type`. That return type is a specialization of the type specified in this subclause.

```
template <class Iterator, class NodeType>
struct INSERT_RETURN_TYPE
{
 Iterator position;
 bool inserted;
 NodeType node;
};
```

2 The name `INSERT_RETURN_TYPE` is exposition only. `INSERT_RETURN_TYPE` has the template parameters, data members, and special members specified above. It has no base classes or members other than those specified.

#### 26.2.6 Associative containers [associative.reqmts]

1 Associative containers provide fast retrieval of data based on keys. The library provides four basic kinds of associative containers: `set`, `multiset`, `map` and `multimap`.

2 Each associative container is parameterized on `Key` and an ordering relation `Compare` that induces a strict weak ordering (28.7) on elements of `Key`. In addition, `map` and `multimap` associate an arbitrary *mapped type* `T` with the `Key`. The object of type `Compare` is called the *comparison object* of a container.

3 The phrase “equivalence of keys” means the equivalence relation imposed by the comparison and *not* the `operator==` on keys. That is, two keys `k1` and `k2` are considered to be equivalent if for the comparison

object `comp`, `comp(k1, k2) == false && comp(k2, k1) == false`. For any two keys `k1` and `k2` in the same container, calling `comp(k1, k2)` shall always return the same value.

- <sup>4</sup> An associative container supports *unique keys* if it may contain at most one element for each key. Otherwise, it supports *equivalent keys*. The `set` and `map` classes support unique keys; the `multiset` and `multimap` classes support equivalent keys. For `multiset` and `multimap`, `insert`, `emplace`, and `erase` preserve the relative ordering of equivalent elements.
- <sup>5</sup> For `set` and `multiset` the value type is the same as the key type. For `map` and `multimap` it is equal to `pair<const Key, T>`.
- <sup>6</sup> `iterator` of an associative container is of the bidirectional iterator category. For associative containers where the value type is the same as the key type, both `iterator` and `const_iterator` are constant iterators. It is unspecified whether or not `iterator` and `const_iterator` are the same type. [ *Note:* `iterator` and `const_iterator` have identical semantics in this case, and `iterator` is convertible to `const_iterator`. Users can avoid violating the one-definition rule by always using `const_iterator` in their function parameter lists. — *end note* ]
- <sup>7</sup> The associative containers meet all the requirements of Allocator-aware containers (26.2.1), except that for `map` and `multimap`, the requirements placed on `value_type` in Table 83 apply instead to `key_type` and `mapped_type`. [ *Note:* For example, in some cases `key_type` and `mapped_type` are required to be `CopyAssignable` even though the associated `value_type`, `pair<const key_type, mapped_type>`, is not `CopyAssignable`. — *end note* ]
- <sup>8</sup> In Table 90, `X` denotes an associative container class, `a` denotes a value of type `X`, `a2` denotes a value of a type with nodes compatible with type `X` (Table 89), `b` denotes a possibly `const` value of type `X`, `u` denotes the name of a variable being declared, `a_uniq` denotes a value of type `X` when `X` supports unique keys, `a_eq` denotes a value of type `X` when `X` supports multiple keys, `a_tran` denotes a possibly `const` value of type `X` when the *qualified-id* `X::key_compare::is_transparent` is valid and denotes a type (17.8.2), `i` and `j` satisfy input iterator requirements and refer to elements implicitly convertible to `value_type`, `[i, j)` denotes a valid range, `p` denotes a valid constant iterator to `a`, `q` denotes a valid dereferenceable constant iterator to `a`, `r` denotes a valid dereferenceable iterator to `a`, `[q1, q2)` denotes a valid range of constant iterators in `a`, `il` designates an object of type `initializer_list<value_type>`, `t` denotes a value of type `X::value_type`, `k` denotes a value of type `X::key_type` and `c` denotes a possibly `const` value of type `X::key_compare`; `kl` is a value such that `a` is partitioned (28.7) with respect to `c(r, kl)`, with `r` the key value of `e` and `e` in `a`; `ku` is a value such that `a` is partitioned with respect to `!c(ku, r)`; `ke` is a value such that `a` is partitioned with respect to `c(r, ke)` and `!c(ke, r)`, with `c(r, ke)` implying `!c(ke, r)`. `A` denotes the storage allocator used by `X`, if any, or `allocator<X::value_type>` otherwise, `m` denotes an allocator of a type convertible to `A`, and `nh` denotes a non-const rvalue of type `X::node_type`.

Table 90 — Associative container requirements (in addition to container)

| Expression                                          | Return type | Assertion/note<br>pre-/post-condition                                    | Complexity   |
|-----------------------------------------------------|-------------|--------------------------------------------------------------------------|--------------|
| <code>X::key_type</code>                            | Key         |                                                                          | compile time |
| <code>X::mapped_type</code> (map and multimap only) | T           |                                                                          | compile time |
| <code>X::value_type</code> (set and multiset only)  | Key         | <i>Requires:</i> <code>value_type</code> is Erasable from <code>X</code> | compile time |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                                         | Return type                                                                                                                                    | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                     | Complexity                                                                                                                                          |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>X::value_type</code> (map and multimap only) | <code>pair&lt;const Key, T&gt;</code>                                                                                                          | <i>Requires:</i> <code>value_type</code> is Erasable from X                                                                                                                                                                                                               | compile time                                                                                                                                        |
| <code>X::key_compare</code>                        | <code>Compare</code>                                                                                                                           | <i>Requires:</i> <code>key_compare</code> is <code>CopyConstructible</code> .                                                                                                                                                                                             | compile time                                                                                                                                        |
| <code>X::value_compare</code>                      | a binary predicate type                                                                                                                        | is the same as <code>key_compare</code> for <code>set</code> and <code>multiset</code> ; is an ordering relation on pairs induced by the first component (i.e., <code>Key</code> ) for <code>map</code> and <code>multimap</code> .                                       | compile time                                                                                                                                        |
| <code>X::node_type</code>                          | a specialization of a <i>node_handle</i> class template, such that the public nested types are the same types as the corresponding types in X. | see 26.2.4                                                                                                                                                                                                                                                                | compile time                                                                                                                                        |
| <code>X(c)</code><br><code>X u(c);</code>          |                                                                                                                                                | <i>Effects:</i> Constructs an empty container. Uses a copy of <code>c</code> as a comparison object.                                                                                                                                                                      | constant                                                                                                                                            |
| <code>X()</code><br><code>X u;</code>              |                                                                                                                                                | <i>Requires:</i> <code>key_compare</code> is <code>DefaultConstructible</code> .<br><i>Effects:</i> Constructs an empty container. Uses <code>Compare()</code> as a comparison object                                                                                     | constant                                                                                                                                            |
| <code>X(i,j,c)</code><br><code>X u(i,j,c);</code>  |                                                                                                                                                | <i>Requires:</i> <code>value_type</code> is <code>EmplaceConstructible</code> into X from <code>*i</code> .<br><i>Effects:</i> Constructs an empty container and inserts elements from the range <code>[i, j)</code> into it; uses <code>c</code> as a comparison object. | $N \log N$ in general, where $N$ has the value <code>distance(i, j)</code> ; linear if <code>[i, j)</code> is sorted with <code>value_comp()</code> |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                                    | Return type                             | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Complexity                                                                                                                                                                |
|-----------------------------------------------|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>X(i,j)</code><br><code>X u(i,j);</code> |                                         | <i>Requires:</i> <code>key_compare</code> is <code>DefaultConstructible</code> .<br><code>value_type</code> is <code>EmplaceConstructible</code> into <code>X</code> from <code>*i</code> .<br><i>Effects:</i> Same as above, but uses <code>Compare()</code> as a comparison object.                                                                                                                                                                                                                                                                                                                                  | same as above                                                                                                                                                             |
| <code>X(il)</code>                            |                                         | same as <code>X(il.begin(), il.end())</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | same as <code>X(il.begin(), il.end())</code>                                                                                                                              |
| <code>X(il,c)</code>                          |                                         | same as <code>X(il.begin(), il.end(), c)</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | same as <code>X(il.begin(), il.end(), c)</code>                                                                                                                           |
| <code>a = il</code>                           | <code>X&amp;</code>                     | <i>Requires:</i> <code>value_type</code> is <code>CopyInsertable</code> into <code>X</code> and <code>CopyAssignable</code> .<br><i>Effects:</i> Assigns the range <code>[il.begin(), il.end())</code> into <code>a</code> . All existing elements of <code>a</code> are either assigned to or destroyed.                                                                                                                                                                                                                                                                                                              | $N \log N$ in general, where $N$ has the value <code>il.size() + a.size()</code> ; linear if <code>[il.begin(), il.end())</code> is sorted with <code>value_comp()</code> |
| <code>b.key_comp()</code>                     | <code>X::key_compare</code>             | returns the comparison object out of which <code>b</code> was constructed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | constant                                                                                                                                                                  |
| <code>b.value_comp()</code>                   | <code>X::value_compare</code>           | returns an object of <code>value_compare</code> constructed out of the comparison object                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | constant                                                                                                                                                                  |
| <code>a_uniq.emplace(args)</code>             | <code>pair&lt;iterator, bool&gt;</code> | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> .<br><i>Effects:</i> Inserts a <code>value_type</code> object <code>t</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> if and only if there is no element in the container with key equivalent to the key of <code>t</code> . The <code>bool</code> component of the returned pair is <code>true</code> if and only if the insertion takes place, and the iterator component of the pair points to the element with key equivalent to the key of <code>t</code> . | logarithmic                                                                                                                                                               |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                           | Return type                             | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Complexity                                                                                            |
|--------------------------------------|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| <code>a_eq.emplace(args)</code>      | <code>iterator</code>                   | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> .<br><i>Effects:</i> Inserts a <code>value_type</code> object <code>t</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> and returns the iterator pointing to the newly inserted element. If a range containing elements equivalent to <code>t</code> exists in <code>a_eq</code> , <code>t</code> is inserted at the end of that range.                                                                                                                                                             | logarithmic                                                                                           |
| <code>a.emplace_hint(p, args)</code> | <code>iterator</code>                   | equivalent to <code>a.emplace(std::forward&lt;Args&gt;(args)...) .</code> Return value is an iterator pointing to the element with the key equivalent to the newly inserted element. The element is inserted as close as possible to the position just prior to <code>p</code> .                                                                                                                                                                                                                                                                                                                                                                        | logarithmic in general, but amortized constant if the element is inserted right before <code>p</code> |
| <code>a_uniq.insert(t)</code>        | <code>pair&lt;iterator, bool&gt;</code> | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Inserts <code>t</code> if and only if there is no element in the container with key equivalent to the key of <code>t</code> . The <code>bool</code> component of the returned pair is <code>true</code> if and only if the insertion takes place, and the <code>iterator</code> component of the pair points to the element with key equivalent to the key of <code>t</code> . | logarithmic                                                                                           |



Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                       | Return type | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Complexity                                                                                                 |
|----------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| <code>a_eq.<br/>insert(t)</code> | iterator    | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Inserts <code>t</code> and returns the iterator pointing to the newly inserted element. If a range containing elements equivalent to <code>t</code> exists in <code>a_eq</code> , <code>t</code> is inserted at the end of that range.                                                                                                                                                                             | logarithmic                                                                                                |
| <code>a.insert(p,<br/>t)</code>  | iterator    | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Inserts <code>t</code> if and only if there is no element with key equivalent to the key of <code>t</code> in containers with unique keys; always inserts <code>t</code> in containers with equivalent keys. Always returns the iterator pointing to the element with key equivalent to the key of <code>t</code> . <code>t</code> is inserted as close as possible to the position just prior to <code>p</code> . | logarithmic in general, but amortized constant if <code>t</code> is inserted right before <code>p</code> . |
| <code>a.insert(i,<br/>j)</code>  | void        | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>*i</code> .<br><i>Requires:</i> <code>i</code> , <code>j</code> are not iterators into <code>a</code> . inserts each element from the range <code>[i, j)</code> if and only if there is no element with key equivalent to the key of that element in containers with unique keys; always inserts that element in containers with equivalent keys.                                                                                                                                                                                                                        | $N \log(a.size() + N)$ , where $N$ has the value <code>distance(i, j)</code>                               |
| <code>a.insert(<br/>il)</code>   | void        | equivalent to<br><code>a.insert(il.begin(),<br/>il.end())</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                            |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                          | Return type                          | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Complexity  |
|-------------------------------------|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| <code>a_uniq.<br/>insert(nh)</code> | <code>insert_<br/>return_type</code> | <p><i>Requires:</i> <code>nh</code> is empty or <code>a_uniq.get_allocator() == nh.get_allocator()</code>.</p> <p><i>Effects:</i> If <code>nh</code> is empty, has no effect. Otherwise, inserts the element owned by <code>nh</code> if and only if there is no element in the container with a key equivalent to <code>nh.key()</code>.</p> <p><i>Postconditions:</i> If <code>nh</code> is empty, <code>inserted</code> is <code>false</code>, <code>position</code> is <code>end()</code>, and <code>node</code> is empty. Otherwise if the insertion took place, <code>inserted</code> is <code>true</code>, <code>position</code> points to the inserted element, and <code>node</code> is empty; if the insertion failed, <code>inserted</code> is <code>false</code>, <code>node</code> has the previous value of <code>nh</code>, and <code>position</code> points to an element with a key equivalent to <code>nh.key()</code>.</p> | logarithmic |
| <code>a_eq.<br/>insert(nh)</code>   | <code>iterator</code>                | <p><i>Requires:</i> <code>nh</code> is empty or <code>a_eq.get_allocator() == nh.get_allocator()</code>.</p> <p><i>Effects:</i> If <code>nh</code> is empty, has no effect and returns <code>a_eq.end()</code>. Otherwise, inserts the element owned by <code>nh</code> and returns an iterator pointing to the newly inserted element. If a range containing elements with keys equivalent to <code>nh.key()</code> exists in <code>a_eq</code>, the element is inserted at the end of that range.</p> <p><i>Postconditions:</i> <code>nh</code> is empty.</p>                                                                                                                                                                                                                                                                                                                                                                               | logarithmic |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression             | Return type | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Complexity                                                                                        |
|------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| <b>a.insert(p, nh)</b> | iterator    | <p><i>Requires:</i> <b>nh</b> is empty or <b>a.get_allocator() == nh.get_allocator()</b>.</p> <p><i>Effects:</i> If <b>nh</b> is empty, has no effect and returns <b>a.end()</b>. Otherwise, inserts the element owned by <b>nh</b> if and only if there is no element with key equivalent to <b>nh.key()</b> in containers with unique keys; always inserts the element owned by <b>nh</b> in containers with equivalent keys. Always returns the iterator pointing to the element with key equivalent to <b>nh.key()</b>. The element is inserted as close as possible to the position just prior to <b>p</b>.</p> <p><i>Postconditions:</i> <b>nh</b> is empty if insertion succeeds, unchanged if insertion fails.</p> | logarithmic in general, but amortized constant if the element is inserted right before <b>p</b> . |
| <b>a.extract(k)</b>    | node_type   | removes the first element in the container with key equivalent to <b>k</b> . Returns a <b>node_type</b> owning the element if found, otherwise an empty <b>node_type</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | $\log(a.size())$                                                                                  |
| <b>a.extract(q)</b>    | node_type   | removes the element pointed to by <b>q</b> . Returns a <b>node_type</b> owning that element.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | amortized constant                                                                                |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression               | Return type            | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Complexity                                                                |
|--------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <code>a.merge(a2)</code> | <code>void</code>      | <p><i>Requires:</i> <code>a.get_allocator() == a2.get_allocator()</code>. Attempts to extract each element in <code>a2</code> and insert it into <code>a</code> using the comparison object of <code>a</code>. In containers with unique keys, if there is an element in <code>a</code> with key equivalent to the key of an element from <code>a2</code>, then that element is not extracted from <code>a2</code>.</p> <p><i>Postconditions:</i> Pointers and references to the transferred elements of <code>a2</code> refer to those same elements but as members of <code>a</code>. Iterators referring to the transferred elements will continue to refer to their elements, but they now behave as iterators into <code>a</code>, not into <code>a2</code>.</p> <p><i>Throws:</i> Nothing unless the comparison object throws.</p> | $N \log(a.size() + N)$ , where $N$ has the value <code>a2.size()</code> . |
| <code>a.erase(k)</code>  | <code>size_type</code> | erases all elements in the container with key equivalent to <code>k</code> . returns the number of erased elements.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | $\log(a.size()) + a.count(k)$                                             |
| <code>a.erase(q)</code>  | <code>iterator</code>  | erases the element pointed to by <code>q</code> . Returns an iterator pointing to the element immediately following <code>q</code> prior to the element being erased. If no such element exists, returns <code>a.end()</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | amortized constant                                                        |
| <code>a.erase(r)</code>  | <code>iterator</code>  | erases the element pointed to by <code>r</code> . Returns an iterator pointing to the element immediately following <code>r</code> prior to the element being erased. If no such element exists, returns <code>a.end()</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | amortized constant                                                        |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                          | Return type                                      | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                   | Complexity                                                                     |
|-------------------------------------|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| <code>a.erase(q1, q2)</code>        | iterator                                         | erases all the elements in the range <code>[q1, q2)</code> . Returns an iterator pointing to the element pointed to by <code>q2</code> prior to any elements being erased. If no such element exists, <code>a.end()</code> is returned. | $\log(a.size()) + N$ , where $N$ has the value <code>distance(q1, q2)</code> . |
| <code>a.clear()</code>              | void                                             | <code>a.erase(a.begin(), a.end())</code><br><br><i>Postconditions:</i> <code>a.empty()</code> returns true.                                                                                                                             | linear in <code>a.size()</code> .                                              |
| <code>b.find(k)</code>              | iterator;<br>const_iterator for constant b.      | returns an iterator pointing to an element with the key equivalent to <code>k</code> , or <code>b.end()</code> if such an element is not found                                                                                          | logarithmic                                                                    |
| <code>a_tran.find(ke)</code>        | iterator;<br>const_iterator for constant a_tran. | returns an iterator pointing to an element with key <code>r</code> such that <code>!c(r, ke) &amp;&amp; !c(ke, r)</code> , or <code>a_tran.end()</code> if such an element is not found                                                 | logarithmic                                                                    |
| <code>b.count(k)</code>             | size_type                                        | returns the number of elements with key equivalent to <code>k</code>                                                                                                                                                                    | $\log(b.size()) + b.count(k)$                                                  |
| <code>a_tran.count(ke)</code>       | size_type                                        | returns the number of elements with key <code>r</code> such that <code>!c(r, ke) &amp;&amp; !c(ke, r)</code>                                                                                                                            | $\log(a\_tran.size()) + a\_tran.count(ke)$                                     |
| <code>b.lower_bound(k)</code>       | iterator;<br>const_iterator for constant b.      | returns an iterator pointing to the first element with key not less than <code>k</code> , or <code>b.end()</code> if such an element is not found.                                                                                      | logarithmic                                                                    |
| <code>a_tran.lower_bound(k1)</code> | iterator;<br>const_iterator for constant a_tran. | returns an iterator pointing to the first element with key <code>r</code> such that <code>!c(r, k1)</code> , or <code>a_tran.end()</code> if such an element is not found.                                                              | logarithmic                                                                    |
| <code>b.upper_bound(k)</code>       | iterator;<br>const_iterator for constant b.      | returns an iterator pointing to the first element with key greater than <code>k</code> , or <code>b.end()</code> if such an element is not found.                                                                                       | logarithmic                                                                    |
| <code>a_tran.upper_bound(ku)</code> | iterator;<br>const_iterator for constant a_tran. | returns an iterator pointing to the first element with key <code>r</code> such that <code>c(ku, r)</code> , or <code>a_tran.end()</code> if such an element is not found.                                                               | logarithmic                                                                    |

Table 90 — Associative container requirements (in addition to container) (continued)

| Expression                          | Return type                                                                                                                                | Assertion/note<br>pre-/post-condition                                                  | Complexity  |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------------|
| <code>b.equal_range(k)</code>       | <code>pair&lt;iterator, iterator&gt;;</code><br><code>pair&lt;const_iterator, const_iterator&gt;</code> for constant <code>b</code> .      | equivalent to <code>make_pair(b.lower_bound(k), b.upper_bound(k))</code> .             | logarithmic |
| <code>a_tran.equal_range(ke)</code> | <code>pair&lt;iterator, iterator&gt;;</code><br><code>pair&lt;const_iterator, const_iterator&gt;</code> for constant <code>a_tran</code> . | equivalent to <code>make_pair(a_tran.lower_bound(ke), a_tran.upper_bound(ke))</code> . | logarithmic |

- <sup>9</sup> The **insert** and **emplace** members shall not affect the validity of iterators and references to the container, and the **erase** members shall invalidate only iterators and references to the erased elements.
- <sup>10</sup> The **extract** members invalidate only iterators to the removed element; pointers and references to the removed element remain valid. However, accessing the element through such pointers and references while the element is owned by a **node\_type** is undefined behavior. References and pointers to an element obtained while it is owned by a **node\_type** are invalidated if the element is successfully inserted.
- <sup>11</sup> The fundamental property of iterators of associative containers is that they iterate through the containers in the non-descending order of keys where non-descending is defined by the comparison that was used to construct them. For any two dereferenceable iterators *i* and *j* such that distance from *i* to *j* is positive, the following condition holds:
- ```
value_comp(*j, *i) == false
```
- ¹² For associative containers with unique keys the stronger condition holds:
- ```
value_comp(*i, *j) != false
```
- <sup>13</sup> When an associative container is constructed by passing a comparison object the container shall not store a pointer or reference to the passed object, even if that object is passed by reference. When an associative container is copied, either through a copy constructor or an assignment operator, the target container shall then use the comparison object from the container being copied, as if that comparison object had been passed to the target container in its constructor.
- <sup>14</sup> The member function templates **find**, **count**, **lower\_bound**, **upper\_bound**, and **equal\_range** shall not participate in overload resolution unless the *qualified-id* `Compare::is_transparent` is valid and denotes a type (17.8.2).
- <sup>15</sup> A deduction guide for an associative container shall not participate in overload resolution if any of the following are true:
- (15.1) — It has an **InputIterator** template parameter and a type that does not qualify as an input iterator is

deduced for that parameter.

- (15.2) — It has an `Allocator` template parameter and a type that does not qualify as an allocator is deduced for that parameter.
- (15.3) — It has a `Compare` template parameter and a type that qualifies as an allocator is deduced for that parameter.

### 26.2.6.1 Exception safety guarantees

[associative.reqmts.except]

- 1 For associative containers, no `clear()` function throws an exception. `erase(k)` does not throw an exception unless that exception is thrown by the container's `Compare` object (if any).
- 2 For associative containers, if an exception is thrown by any operation from within an `insert` or `emplace` function inserting a single element, the insertion has no effect.
- 3 For associative containers, no `swap` function throws an exception unless that exception is thrown by the swap of the container's `Compare` object (if any).

### 26.2.7 Unordered associative containers

[unord.req]

- 1 Unordered associative containers provide an ability for fast retrieval of data based on keys. The worst-case complexity for most operations is linear, but the average case is much faster. The library provides four unordered associative containers: `unordered_set`, `unordered_map`, `unordered_multiset`, and `unordered_multimap`.
- 2 Unordered associative containers conform to the requirements for Containers (26.2), except that the expressions `a == b` and `a != b` have different semantics than for the other container types.
- 3 Each unordered associative container is parameterized by `Key`, by a function object type `Hash` that meets the `Hash` requirements (20.5.3.4) and acts as a hash function for argument values of type `Key`, and by a binary predicate `Pred` that induces an equivalence relation on values of type `Key`. Additionally, `unordered_map` and `unordered_multimap` associate an arbitrary *mapped type* `T` with the `Key`.
- 4 The container's object of type `Hash` — denoted by `hash` — is called the *hash function* of the container. The container's object of type `Pred` — denoted by `pred` — is called the *key equality predicate* of the container.
- 5 Two values `k1` and `k2` of type `Key` are considered equivalent if the container's key equality predicate returns `true` when passed those values. If `k1` and `k2` are equivalent, the container's hash function shall return the same value for both. [ *Note:* Thus, when an unordered associative container is instantiated with a non-default `Pred` parameter it usually needs a non-default `Hash` parameter as well. — *end note* ] For any two keys `k1` and `k2` in the same container, calling `pred(k1, k2)` shall always return the same value. For any key `k` in a container, calling `hash(k)` shall always return the same value.
- 6 An unordered associative container supports *unique keys* if it may contain at most one element for each key. Otherwise, it supports *equivalent keys*. `unordered_set` and `unordered_map` support unique keys. `unordered_multiset` and `unordered_multimap` support equivalent keys. In containers that support equivalent keys, elements with equivalent keys are adjacent to each other in the iteration order of the container. Thus, although the absolute order of elements in an unordered container is not specified, its elements are grouped into *equivalent-key groups* such that all elements of each group have equivalent keys. Mutating operations on unordered containers shall preserve the relative order of elements within each equivalent-key group unless otherwise specified.
- 7 For `unordered_set` and `unordered_multiset` the value type is the same as the key type. For `unordered_map` and `unordered_multimap` it is `pair<const Key, T>`.
- 8 For unordered containers where the value type is the same as the key type, both `iterator` and `const_iterator` are constant iterators. It is unspecified whether or not `iterator` and `const_iterator` are the same type. [ *Note:* `iterator` and `const_iterator` have identical semantics in this case, and `iterator` is convertible

to `const_iterator`. Users can avoid violating the one-definition rule by always using `const_iterator` in their function parameter lists. — *end note*]

- <sup>9</sup> The elements of an unordered associative container are organized into *buckets*. Keys with the same hash code appear in the same bucket. The number of buckets is automatically increased as elements are added to an unordered associative container, so that the average number of elements per bucket is kept below a bound. Rehashing invalidates iterators, changes ordering between elements, and changes which buckets elements appear in, but does not invalidate pointers or references to elements. For `unordered_multiset` and `unordered_multimap`, rehashing preserves the relative ordering of equivalent elements.
- <sup>10</sup> The unordered associative containers meet all the requirements of Allocator-aware containers (26.2.1), except that for `unordered_map` and `unordered_multimap`, the requirements placed on `value_type` in Table 83 apply instead to `key_type` and `mapped_type`. [Note: For example, `key_type` and `mapped_type` are sometimes required to be `CopyAssignable` even though the associated `value_type`, `pair<const key_type, mapped_type>`, is not `CopyAssignable`. — *end note*]
- <sup>11</sup> In Table 91: `X` denotes an unordered associative container class, `a` denotes a value of type `X`, `a2` denotes a value of a type with nodes compatible with type `X` (Table 89), `b` denotes a possibly const value of type `X`, `a_uniq` denotes a value of type `X` when `X` supports unique keys, `a_eq` denotes a value of type `X` when `X` supports equivalent keys, `i` and `j` denote input iterators that refer to `value_type`, `[i, j)` denotes a valid range, `p` and `q2` denote valid constant iterators to `a`, `q` and `q1` denote valid dereferenceable constant iterators to `a`, `r` denotes a valid dereferenceable iterator to `a`, `[q1, q2)` denotes a valid range in `a`, `il` denotes a value of type `initializer_list<value_type>`, `t` denotes a value of type `X::value_type`, `k` denotes a value of type `key_type`, `hf` denotes a possibly const value of type `hasher`, `eq` denotes a possibly const value of type `key_equal`, `n` denotes a value of type `size_type`, `z` denotes a value of type `float`, and `nh` denotes a non-const rvalue of type `X::node_type`.

Table 91 — Unordered associative container requirements (in addition to container)

| Expression                                                                                                  | Return type                           | Assertion/note<br>pre-/post-condition                                                                                          | Complexity   |
|-------------------------------------------------------------------------------------------------------------|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|--------------|
| <code>X::key_type</code>                                                                                    | Key                                   |                                                                                                                                | compile time |
| <code>X::mapped_type</code><br>( <code>unordered_map</code> and<br><code>unordered_multimap</code><br>only) | T                                     |                                                                                                                                | compile time |
| <code>X::value_type</code><br>( <code>unordered_set</code> and<br><code>unordered_multiset</code><br>only)  | Key                                   | <i>Requires:</i> <code>value_type</code> is<br>Erasable from <code>X</code>                                                    | compile time |
| <code>X::value_type</code><br>( <code>unordered_map</code> and<br><code>unordered_multimap</code><br>only)  | <code>pair&lt;const Key, T&gt;</code> | <i>Requires:</i> <code>value_type</code> is<br>Erasable from <code>X</code>                                                    | compile time |
| <code>X::hasher</code>                                                                                      | Hash                                  | Hash shall be a unary function<br>object type such that the<br>expression <code>hf(k)</code> has type<br><code>size_t</code> . | compile time |



Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                                                | Return type                                                                                                                                                        | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                       | Complexity       |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <code>X::key_equal</code>                                 | <code>Pred</code>                                                                                                                                                  | <i>Requires:</i> <code>Pred</code> is <code>CopyConstructible</code> .<br><code>Pred</code> shall be a binary predicate that takes two arguments of type <code>Key</code> . <code>Pred</code> is an equivalence relation.                                                                                   | compile time     |
| <code>X::local_iterator</code>                            | An iterator type whose category, value type, difference type, and pointer and reference types are the same as <code>X::iterator</code> 's.                         | A <code>local_iterator</code> object may be used to iterate through a single bucket, but may not be used to iterate across buckets.                                                                                                                                                                         | compile time     |
| <code>X::const_local_iterator</code>                      | An iterator type whose category, value type, difference type, and pointer and reference types are the same as <code>X::const_iterator</code> 's.                   | A <code>const_local_iterator</code> object may be used to iterate through a single bucket, but may not be used to iterate across buckets.                                                                                                                                                                   | compile time     |
| <code>X::node_type</code>                                 | a specialization of a <code>node_handle</code> class template, such that the public nested types are the same types as the corresponding types in <code>X</code> . | see 26.2.4                                                                                                                                                                                                                                                                                                  | compile time     |
| <code>X(n, hf, eq)</code><br><code>X a(n, hf, eq);</code> | <code>X</code>                                                                                                                                                     | <i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hf</code> as the hash function and <code>eq</code> as the key equality predicate.                                                                                                                           | $\mathcal{O}(n)$ |
| <code>X(n, hf)</code><br><code>X a(n, hf);</code>         | <code>X</code>                                                                                                                                                     | <i>Requires:</i> <code>key_equal</code> is <code>DefaultConstructible</code> .<br><i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hf</code> as the hash function and <code>key_equal()</code> as the key equality predicate.                                | $\mathcal{O}(n)$ |
| <code>X(n)</code><br><code>X a(n);</code>                 | <code>X</code>                                                                                                                                                     | <i>Requires:</i> <code>hasher</code> and <code>key_equal</code> are <code>DefaultConstructible</code> .<br><i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hasher()</code> as the hash function and <code>key_equal()</code> as the key equality predicate. | $\mathcal{O}(n)$ |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                                                            | Return type | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                            | Complexity                                                                                          |
|-----------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <code>X()</code><br><code>X a;</code>                                 | X           | <i>Requires:</i> <code>hasher</code> and <code>key_equal</code> are <code>DefaultConstructible</code> .<br><i>Effects:</i> Constructs an empty container with an unspecified number of buckets, using <code>hasher()</code> as the hash function and <code>key_equal()</code> as the key equality predicate.                                                                                                                                                     | constant                                                                                            |
| <code>X(i, j, n, hf, eq)</code><br><code>X a(i, j, n, hf, eq);</code> | X           | <i>Requires:</i> <code>value_type</code> is <code>EmplaceConstructible</code> into X from <code>*i</code> .<br><i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hf</code> as the hash function and <code>eq</code> as the key equality predicate, and inserts elements from <code>[i, j)</code> into it.                                                                                                          | Average case $\mathcal{O}(N)$ ( $N$ is <code>distance(i, j)</code> ), worst case $\mathcal{O}(N^2)$ |
| <code>X(i, j, n, hf)</code><br><code>X a(i, j, n, hf);</code>         | X           | <i>Requires:</i> <code>key_equal</code> is <code>DefaultConstructible</code> .<br><code>value_type</code> is <code>EmplaceConstructible</code> into X from <code>*i</code> .<br><i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hf</code> as the hash function and <code>key_equal()</code> as the key equality predicate, and inserts elements from <code>[i, j)</code> into it.                                | Average case $\mathcal{O}(N)$ ( $N$ is <code>distance(i, j)</code> ), worst case $\mathcal{O}(N^2)$ |
| <code>X(i, j, n)</code><br><code>X a(i, j, n);</code>                 | X           | <i>Requires:</i> <code>hasher</code> and <code>key_equal</code> are <code>DefaultConstructible</code> .<br><code>value_type</code> is <code>EmplaceConstructible</code> into X from <code>*i</code> .<br><i>Effects:</i> Constructs an empty container with at least <code>n</code> buckets, using <code>hasher()</code> as the hash function and <code>key_equal()</code> as the key equality predicate, and inserts elements from <code>[i, j)</code> into it. | Average case $\mathcal{O}(N)$ ( $N$ is <code>distance(i, j)</code> ), worst case $\mathcal{O}(N^2)$ |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                                      | Return type         | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                          | Complexity                                                                                          |
|-------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <code>X(i, j)</code><br><code>X a(i, j);</code> | X                   | <i>Requires:</i> <code>hasher</code> and <code>key_equal</code> are <code>DefaultConstructible</code> . <code>value_type</code> is <code>EmplaceConstructible</code> into X from <code>*i</code> .<br><i>Effects:</i> Constructs an empty container with an unspecified number of buckets, using <code>hasher()</code> as the hash function and <code>key_equal()</code> as the key equality predicate, and inserts elements from <code>[i, j)</code> into it. | Average case $\mathcal{O}(N)$ ( $N$ is <code>distance(i, j)</code> ), worst case $\mathcal{O}(N^2)$ |
| <code>X(il)</code>                              | X                   | Same as <code>X(il.begin(), il.end())</code> .                                                                                                                                                                                                                                                                                                                                                                                                                 | Same as <code>X(il.begin(), il.end())</code> .                                                      |
| <code>X(il, n)</code>                           | X                   | Same as <code>X(il.begin(), il.end(), n)</code> .                                                                                                                                                                                                                                                                                                                                                                                                              | Same as <code>X(il.begin(), il.end(), n)</code> .                                                   |
| <code>X(il, n, hf)</code>                       | X                   | Same as <code>X(il.begin(), il.end(), n, hf)</code> .                                                                                                                                                                                                                                                                                                                                                                                                          | Same as <code>X(il.begin(), il.end(), n, hf)</code> .                                               |
| <code>X(il, n, hf, eq)</code>                   | X                   | Same as <code>X(il.begin(), il.end(), n, hf, eq)</code> .                                                                                                                                                                                                                                                                                                                                                                                                      | Same as <code>X(il.begin(), il.end(), n, hf, eq)</code> .                                           |
| <code>X(b)</code><br><code>X a(b);</code>       | X                   | Copy constructor. In addition to the requirements of Table 83, copies the hash function, predicate, and maximum load factor.                                                                                                                                                                                                                                                                                                                                   | Average case linear in <code>b.size()</code> , worst case quadratic.                                |
| <code>a = b</code>                              | X&                  | Copy assignment operator. In addition to the requirements of Table 83, copies the hash function, predicate, and maximum load factor.                                                                                                                                                                                                                                                                                                                           | Average case linear in <code>b.size()</code> , worst case quadratic.                                |
| <code>a = il</code>                             | X&                  | <i>Requires:</i> <code>value_type</code> is <code>CopyInsertable</code> into X and <code>CopyAssignable</code> .<br><i>Effects:</i> Assigns the range <code>[il.begin(), il.end())</code> into a. All existing elements of a are either assigned to or destroyed.                                                                                                                                                                                              | Same as <code>a = X(il)</code> .                                                                    |
| <code>b.hash_function()</code>                  | <code>hasher</code> | Returns b's hash function.                                                                                                                                                                                                                                                                                                                                                                                                                                     | constant                                                                                            |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                               | Return type                             | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Complexity                                                                 |
|------------------------------------------|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <code>b.key_eq()</code>                  | <code>key_equal</code>                  | Returns <code>b</code> 's key equality predicate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | constant                                                                   |
| <code>a_uniq.<br/>emplace(args)</code>   | <code>pair&lt;iterator, bool&gt;</code> | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> .<br><i>Effects:</i> Inserts a <code>value_type</code> object <code>t</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> if and only if there is no element in the container with key equivalent to the key of <code>t</code> . The <code>bool</code> component of the returned pair is <code>true</code> if and only if the insertion takes place, and the iterator component of the pair points to the element with key equivalent to the key of <code>t</code> . | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(a\_uniq.size())$ . |
| <code>a_eq.emplace(args)</code>          | <code>iterator</code>                   | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> .<br><i>Effects:</i> Inserts a <code>value_type</code> object <code>t</code> constructed with <code>std::forward&lt;Args&gt;(args)...</code> and returns the iterator pointing to the newly inserted element.                                                                                                                                                                                                                                                                           | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(a\_eq.size())$ .   |
| <code>a.emplace_hint(p,<br/>args)</code> | <code>iterator</code>                   | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>args</code> .<br><i>Effects:</i> Equivalent to <code>a.emplace( std::forward&lt;Args&gt;(args)...) .</code> Return value is an iterator pointing to the element with the key equivalent to the newly inserted element. The <code>const_iterator</code> <code>p</code> is a hint pointing to where the search should start. Implementations are permitted to ignore the hint.                                                                                                                        | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(a.size())$ .       |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                    | Return type                                 | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Complexity                                                                                                                    |
|-------------------------------|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <code>a_uniq.insert(t)</code> | <code>pair&lt;iterator,<br/>bool&gt;</code> | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Inserts <code>t</code> if and only if there is no element in the container with key equivalent to the key of <code>t</code> . The <code>bool</code> component of the returned pair indicates whether the insertion takes place, and the <code>iterator</code> component points to the element with key equivalent to the key of <code>t</code> . | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(\text{a\_uniq.size}())$ .                                             |
| <code>a_eq.insert(t)</code>   | <code>iterator</code>                       | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Inserts <code>t</code> , and returns an iterator pointing to the newly inserted element.                                                                                                                                                                                                                                                         | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(\text{a\_eq.size}())$ .                                               |
| <code>a.insert(p, t)</code>   | <code>iterator</code>                       | <i>Requires:</i> If <code>t</code> is a non-const rvalue expression, <code>value_type</code> shall be <code>MoveInsertable</code> into <code>X</code> ; otherwise, <code>value_type</code> shall be <code>CopyInsertable</code> into <code>X</code> .<br><i>Effects:</i> Equivalent to <code>a.insert(t)</code> . Return value is an iterator pointing to the element with the key equivalent to that of <code>t</code> . The iterator <code>p</code> is a hint pointing to where the search should start. Implementations are permitted to ignore the hint.                                                              | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(\text{a.size}())$ .                                                   |
| <code>a.insert(i, j)</code>   | <code>void</code>                           | <i>Requires:</i> <code>value_type</code> shall be <code>EmplaceConstructible</code> into <code>X</code> from <code>*i</code> .<br><i>Requires:</i> <code>i</code> and <code>j</code> are not iterators in <code>a</code> . Equivalent to <code>a.insert(t)</code> for each element in <code>[i, j)</code> .                                                                                                                                                                                                                                                                                                               | Average case $\mathcal{O}(N)$ , where $N$ is <code>distance(i, j)</code> . Worst case $\mathcal{O}(N(\text{a.size}() + 1))$ . |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                          | Return type                     | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Complexity                                                                 |
|-------------------------------------|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <code>a.insert(il)</code>           | <code>void</code>               | Same as <code>a.insert(il.begin(), il.end())</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Same as <code>a.insert(il.begin(), il.end())</code> .                      |
| <code>a_uniq.<br/>insert(nh)</code> | <code>insert_return_type</code> | <p><i>Requires:</i> <code>nh</code> is empty or <code>a_uniq.get_allocator() == nh.get_allocator()</code>.</p> <p><i>Effects:</i> If <code>nh</code> is empty, has no effect. Otherwise, inserts the element owned by <code>nh</code> if and only if there is no element in the container with a key equivalent to <code>nh.key()</code>.</p> <p><i>Postconditions:</i> If <code>nh</code> is empty, <code>inserted</code> is <code>false</code>, <code>position</code> is <code>end()</code>, and <code>node</code> is empty. Otherwise if the insertion took place, <code>inserted</code> is <code>true</code>, <code>position</code> points to the inserted element, and <code>node</code> is empty; if the insertion failed, <code>inserted</code> is <code>false</code>, <code>node</code> has the previous value of <code>nh</code>, and <code>position</code> points to an element with a key equivalent to <code>nh.key()</code>.</p> | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(a\_uniq.size())$ . |
| <code>a_eq.<br/>insert(nh)</code>   | <code>iterator</code>           | <p><i>Requires:</i> <code>nh</code> is empty or <code>a_eq.get_allocator() == nh.get_allocator()</code>.</p> <p><i>Effects:</i> If <code>nh</code> is empty, has no effect and returns <code>a_eq.end()</code>. Otherwise, inserts the element owned by <code>nh</code> and returns an iterator pointing to the newly inserted element.</p> <p><i>Postconditions:</i> <code>nh</code> is empty.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Average case $\mathcal{O}(1)$ , worst case $\mathcal{O}(a\_eq.size())$ .   |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                   | Return type | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Complexity                                                                                      |
|------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <code>a.insert(q, nh)</code> | iterator    | <p><i>Requires:</i> <code>nh</code> is empty or <code>a.get_allocator() == nh.get_allocator()</code>.</p> <p><i>Effects:</i> If <code>nh</code> is empty, has no effect and returns <code>a.end()</code>. Otherwise, inserts the element owned by <code>nh</code> if and only if there is no element with key equivalent to <code>nh.key()</code> in containers with unique keys; always inserts the element owned by <code>nh</code> in containers with equivalent keys. Always returns the iterator pointing to the element with key equivalent to <code>nh.key()</code>. The iterator <code>q</code> is a hint pointing to where the search should start. Implementations are permitted to ignore the hint.</p> <p><i>Postconditions:</i> <code>nh</code> is empty if insertion succeeds, unchanged if insertion fails.</p> | <p>Average case <math>\mathcal{O}(1)</math>, worst case <math>\mathcal{O}(a.size())</math>.</p> |
| <code>a.extract(k)</code>    | node_type   | Removes an element in the container with key equivalent to <code>k</code> . Returns a <code>node_type</code> owning the element if found, otherwise an empty <code>node_type</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>Average case <math>\mathcal{O}(1)</math>, worst case <math>\mathcal{O}(a.size())</math>.</p> |
| <code>a.extract(q)</code>    | node_type   | Removes the element pointed to by <code>q</code> . Returns a <code>node_type</code> owning that element.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <p>Average case <math>\mathcal{O}(1)</math>, worst case <math>\mathcal{O}(a.size())</math>.</p> |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                   | Return type            | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Complexity                                                                                                                                                  |
|------------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a.merge(a2)</code>     | <code>void</code>      | <p><i>Requires:</i> <code>a.get_allocator() == a2.get_allocator()</code>. Attempts to extract each element in <code>a2</code> and insert it into <code>a</code> using the hash function and key equality predicate of <code>a</code>. In containers with unique keys, if there is an element in <code>a</code> with key equivalent to the key of an element from <code>a2</code>, then that element is not extracted from <code>a2</code>.</p> <p><i>Postconditions:</i> Pointers and references to the transferred elements of <code>a2</code> refer to those same elements but as members of <code>a</code>. Iterators referring to the transferred elements and all iterators referring to <code>a</code> will be invalidated, but iterators to elements remaining in <code>a2</code> will remain valid.</p> <p><i>Throws:</i> Nothing unless the hash function or key equality predicate throws.</p> | <p>Average case <math>\mathcal{O}(N)</math>, where <math>N</math> is <code>a2.size()</code>.<br/>Worst case <math>\mathcal{O}(N * a.size() + N)</math>.</p> |
| <code>a.erase(k)</code>      | <code>size_type</code> | Erases all elements with key equivalent to <code>k</code> . Returns the number of elements erased.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <p>Average case <math>\mathcal{O}(a.count(k))</math>.<br/>Worst case <math>\mathcal{O}(a.size())</math>.</p>                                                |
| <code>a.erase(q)</code>      | <code>iterator</code>  | Erases the element pointed to by <code>q</code> . Returns the iterator immediately following <code>q</code> prior to the erasure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <p>Average case <math>\mathcal{O}(1)</math>, worst case <math>\mathcal{O}(a.size())</math>.</p>                                                             |
| <code>a.erase(r)</code>      | <code>iterator</code>  | Erases the element pointed to by <code>r</code> . Returns the iterator immediately following <code>r</code> prior to the erasure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <p>Average case <math>\mathcal{O}(1)</math>, worst case <math>\mathcal{O}(a.size())</math>.</p>                                                             |
| <code>a.erase(q1, q2)</code> | <code>iterator</code>  | Erases all elements in the range <code>[q1, q2)</code> . Returns the iterator immediately following the erased elements prior to the erasure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>Average case linear in <code>distance(q1, q2)</code>, worst case <math>\mathcal{O}(a.size())</math>.</p>                                                 |
| <code>a.clear()</code>       | <code>void</code>      | Erases all elements in the container. <i>Postconditions:</i> <code>a.empty()</code> returns <code>true</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>Linear in <code>a.size()</code>.</p>                                                                                                                     |



Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                        | Return type                                                                             | Assertion/note<br>pre-/post-condition                                                                                                                                                                                                                                                        | Complexity                                                                             |
|-----------------------------------|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <code>b.find(k)</code>            | iterator;<br>const_iterator for<br>const b.                                             | Returns an iterator pointing to an element with key equivalent to <code>k</code> , or <code>b.end()</code> if no such element exists.                                                                                                                                                        | Average case<br>$\mathcal{O}(1)$ , worst case<br>$\mathcal{O}(b.size())$ .             |
| <code>b.count(k)</code>           | size_type                                                                               | Returns the number of elements with key equivalent to <code>k</code> .                                                                                                                                                                                                                       | Average case<br>$\mathcal{O}(b.count(k))$ ,<br>worst case<br>$\mathcal{O}(b.size())$ . |
| <code>b.equal_range(k)</code>     | pair<iterator,<br>iterator>;<br>pair<const_iterator,<br>const_iterator> for<br>const b. | Returns a range containing all elements with keys equivalent to <code>k</code> . Returns <code>make_pair(b.end(), b.end())</code> if no such elements exist.                                                                                                                                 | Average case<br>$\mathcal{O}(b.count(k))$ .<br>Worst case<br>$\mathcal{O}(b.size())$ . |
| <code>b.bucket_count()</code>     | size_type                                                                               | Returns the number of buckets that <code>b</code> contains.                                                                                                                                                                                                                                  | Constant                                                                               |
| <code>b.max_bucket_count()</code> | size_type                                                                               | Returns an upper bound on the number of buckets that <code>b</code> might ever contain.                                                                                                                                                                                                      | Constant                                                                               |
| <code>b.bucket(k)</code>          | size_type                                                                               | <i>Requires:</i> <code>b.bucket_count() &gt; 0</code> .<br>Returns the index of the bucket in which elements with keys equivalent to <code>k</code> would be found, if any such element existed.<br><i>Postconditions:</i> the return value shall be in the range $[0, b.bucket\_count())$ . | Constant                                                                               |
| <code>b.bucket_size(n)</code>     | size_type                                                                               | <i>Requires:</i> <code>n</code> shall be in the range $[0, b.bucket\_count())$ .<br>Returns the number of elements in the $n^{\text{th}}$ bucket.                                                                                                                                            | $\mathcal{O}(b.bucket\_size(n))$                                                       |
| <code>b.begin(n)</code>           | local_iterator;<br>const_local_iterator for const<br>b.                                 | <i>Requires:</i> <code>n</code> shall be in the range $[0, b.bucket\_count())$ .<br><code>b.begin(n)</code> returns an iterator referring to the first element in the bucket. If the bucket is empty, then <code>b.begin(n) == b.end(n)</code> .                                             | Constant                                                                               |
| <code>b.end(n)</code>             | local_iterator;<br>const_local_iterator for const<br>b.                                 | <i>Requires:</i> <code>n</code> shall be in the range $[0, b.bucket\_count())$ .<br><code>b.end(n)</code> returns an iterator which is the past-the-end value for the bucket.                                                                                                                | Constant                                                                               |

Table 91 — Unordered associative container requirements (in addition to container) (continued)

| Expression                        | Return type                       | Assertion/note<br>pre-/post-condition                                                                                                                                                                                    | Complexity                                                           |
|-----------------------------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| <code>b.cbegin(n)</code>          | <code>const_local_iterator</code> | <i>Requires:</i> <code>n</code> shall be in the range <code>[0, b.bucket_count())</code> . Note: <code>[b.cbegin(n), b.cend(n))</code> is a valid range containing all of the elements in the $n^{\text{th}}$ bucket.    | Constant                                                             |
| <code>b.cend(n)</code>            | <code>const_local_iterator</code> | <i>Requires:</i> <code>n</code> shall be in the range <code>[0, b.bucket_count())</code> .                                                                                                                               | Constant                                                             |
| <code>b.load_factor()</code>      | <code>float</code>                | Returns the average number of elements per bucket.                                                                                                                                                                       | Constant                                                             |
| <code>b.max_load_factor()</code>  | <code>float</code>                | Returns a positive number that the container attempts to keep the load factor less than or equal to. The container automatically increases the number of buckets as necessary to keep the load factor below this number. | Constant                                                             |
| <code>a.max_load_factor(z)</code> | <code>void</code>                 | <i>Requires:</i> <code>z</code> shall be positive. May change the container's maximum load factor, using <code>z</code> as a hint.                                                                                       | Constant                                                             |
| <code>a.rehash(n)</code>          | <code>void</code>                 | <i>Postconditions:</i><br><code>a.bucket_count() &gt;= a.size() / a.max_load_factor()</code> and <code>a.bucket_count() &gt;= n</code> .                                                                                 | Average case linear in <code>a.size()</code> , worst case quadratic. |
| <code>a.reserve(n)</code>         | <code>void</code>                 | Same as <code>a.rehash(ceil(n / a.max_load_factor()))</code> .                                                                                                                                                           | Average case linear in <code>a.size()</code> , worst case quadratic. |

<sup>12</sup> Two unordered containers `a` and `b` compare equal if `a.size() == b.size()` and, for every equivalent-key group `[Ea1, Ea2)` obtained from `a.equal_range(Ea1)`, there exists an equivalent-key group `[Eb1, Eb2)` obtained from `b.equal_range(Ea1)`, such that `is_permutation(Ea1, Ea2, Eb1, Eb2)` returns `true`. For `unordered_set` and `unordered_map`, the complexity of `operator==` (i.e., the number of calls to the `==` operator of the `value_type`, to the predicate returned by `key_eq()`, and to the hasher returned by `hash_function()`) is proportional to  $N$  in the average case and to  $N^2$  in the worst case, where  $N$  is `a.size()`. For `unordered_multiset` and `unordered_multimap`, the complexity of `operator==` is proportional to  $\sum E_i^2$  in the average case and to  $N^2$  in the worst case, where  $N$  is `a.size()`, and  $E_i$  is the size of the  $i^{\text{th}}$  equivalent-key group in `a`. However, if the respective elements of each corresponding pair of equivalent-key groups `Eai` and `Ebi` are arranged in the same order (as is commonly the case, e.g., if `a` and `b` are unmodified copies of the same container), then the average-case complexity for `unordered_multiset` and `unordered_multimap` becomes proportional to  $N$  (but worst-case complexity remains  $\mathcal{O}(N^2)$ , e.g., for a pathologically bad hash function). The behavior of a program that uses `operator==` or `operator!=` on unordered containers is undefined unless the `Hash` and `Pred` function objects respectively have the same behavior for both containers and the equality

comparison function for `Key` is a refinement<sup>257</sup> of the partition into equivalent-key groups produced by `Pred`.

- 13 The iterator types `iterator` and `const_iterator` of an unordered associative container are of at least the forward iterator category. For unordered associative containers where the key type and value type are the same, both `iterator` and `const_iterator` are constant iterators.
- 14 The `insert` and `emplace` members shall not affect the validity of references to container elements, but may invalidate all iterators to the container. The `erase` members shall invalidate only iterators and references to the erased elements, and preserve the relative order of the elements that are not erased.
- 15 The `insert` and `emplace` members shall not affect the validity of iterators if  $(N+n) \leq z * B$ , where  $N$  is the number of elements in the container prior to the insert operation,  $n$  is the number of elements inserted,  $B$  is the container's bucket count, and  $z$  is the container's maximum load factor.
- 16 The `extract` members invalidate only iterators to the removed element, and preserve the relative order of the elements that are not erased; pointers and references to the removed element remain valid. However, accessing the element through such pointers and references while the element is owned by a `node_type` is undefined behavior. References and pointers to an element obtained while it is owned by a `node_type` are invalidated if the element is successfully inserted.
- 17 A deduction guide for an unordered associative container shall not participate in overload resolution if any of the following are true:
  - (17.1) — It has an `InputIterator` template parameter and a type that does not qualify as an input iterator is deduced for that parameter.
  - (17.2) — It has an `Allocator` template parameter and a type that does not qualify as an allocator is deduced for that parameter.
  - (17.3) — It has a `Hash` template parameter and an integral type or a type that qualifies as an allocator is deduced for that parameter.
  - (17.4) — It has a `Pred` template parameter and a type that qualifies as an allocator is deduced for that parameter.

#### 26.2.7.1 Exception safety guarantees

[unord.req.except]

- 1 For unordered associative containers, no `clear()` function throws an exception. `erase(k)` does not throw an exception unless that exception is thrown by the container's `Hash` or `Pred` object (if any).
- 2 For unordered associative containers, if an exception is thrown by any operation other than the container's hash function from within an `insert` or `emplace` function inserting a single element, the insertion has no effect.
- 3 For unordered associative containers, no `swap` function throws an exception unless that exception is thrown by the swap of the container's `Hash` or `Pred` object (if any).
- 4 For unordered associative containers, if an exception is thrown from within a `rehash()` function other than by the container's hash function or comparison function, the `rehash()` function has no effect.

### 26.3 Sequence containers

[sequences]

#### 26.3.1 In general

[sequences.general]

- 1 The headers `<array>`, `<deque>`, `<forward_list>`, `<list>`, and `<vector>` define class templates that meet the requirements for sequence containers.

#### 26.3.2 Header `<array>` synopsis

[array.syn]

```
#include <initializer_list>
```

<sup>257</sup>) Equality comparison is a refinement of partitioning if no two objects that compare equal fall into different partitions.

```

namespace std {
 // 26.3.7, class template array
 template <class T, size_t N> struct array;
 template <class T, size_t N>
 bool operator==(const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 bool operator!=(const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 bool operator< (const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 bool operator> (const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 bool operator<= (const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 bool operator>= (const array<T, N>& x, const array<T, N>& y);
 template <class T, size_t N>
 void swap(array<T, N>& x, array<T, N>& y) noexcept(noexcept(x.swap(y)));

 template <class T> class tuple_size;
 template <size_t I, class T> class tuple_element;
 template <class T, size_t N>
 struct tuple_size<array<T, N>>;
 template <size_t I, class T, size_t N>
 struct tuple_element<I, array<T, N>>;
 template <size_t I, class T, size_t N>
 constexpr T& get(array<T, N>&) noexcept;
 template <size_t I, class T, size_t N>
 constexpr T&& get(array<T, N>&&) noexcept;
 template <size_t I, class T, size_t N>
 constexpr const T& get(const array<T, N>&) noexcept;
 template <size_t I, class T, size_t N>
 constexpr const T&& get(const array<T, N>&&) noexcept;
}

```

### 26.3.3 Header <deque> synopsis

[deque.syn]

```
#include <initializer_list>
```

```

namespace std {
 // 26.3.8, class template deque
 template <class T, class Allocator = allocator<T>> class deque;
 template <class T, class Allocator>
 bool operator==(const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator< (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator!=(const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator> (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator>= (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator<= (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
 template <class T, class Allocator>
 void swap(deque<T, Allocator>& x, deque<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

```

namespace pmr {
 template <class T>
 using deque = std::deque<T, polymorphic_allocator<T>>;
}
}

```

### 26.3.4 Header <forward\_list> synopsis

[forward\_list.syn]

```

#include <initializer_list>

namespace std {
 // 26.3.9, class template forward_list
 template <class T, class Allocator = allocator<T>> class forward_list;
 template <class T, class Allocator>
 bool operator==(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator< (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator!=(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator> (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator>= (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator<= (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
 template <class T, class Allocator>
 void swap(forward_list<T, Allocator>& x, forward_list<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

 namespace pmr {
 template <class T>
 using forward_list = std::forward_list<T, polymorphic_allocator<T>>;
 }
}

```

### 26.3.5 Header <list> synopsis

[list.syn]

```

#include <initializer_list>

namespace std {
 // 26.3.10, class template list
 template <class T, class Allocator = allocator<T>> class list;
 template <class T, class Allocator>
 bool operator==(const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator< (const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator!=(const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator> (const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator>= (const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator<= (const list<T, Allocator>& x, const list<T, Allocator>& y);
 template <class T, class Allocator>
 void swap(list<T, Allocator>& x, list<T, Allocator>& y)

```

```

 noexcept(noexcept(x.swap(y)));

 namespace pmr {
 template <class T>
 using list = std::list<T, polymorphic_allocator<T>>;
 }
}

```

### 26.3.6 Header <vector> synopsis

[vector.syn]

```

#include <initializer_list>

namespace std {
 // 26.3.11, class template vector
 template <class T, class Allocator = allocator<T>> class vector;
 template <class T, class Allocator>
 bool operator==(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator< (const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator!=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator> (const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator>=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 bool operator<=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
 template <class T, class Allocator>
 void swap(vector<T, Allocator>& x, vector<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

 // 26.3.12, class vector<bool>
 template <class Allocator> class vector<bool, Allocator>;

 // hash support
 template <class T> struct hash;
 template <class Allocator> struct hash<vector<bool, Allocator>>;

 namespace pmr {
 template <class T>
 using vector = std::vector<T, polymorphic_allocator<T>>;
 }
}

```

### 26.3.7 Class template array

[array]

#### 26.3.7.1 Class template array overview

[array.overview]

- <sup>1</sup> The header <array> defines a class template for storing fixed-size sequences of objects. An **array** is a contiguous container (26.2.1). An instance of **array**<T, N> stores N elements of type T, so that **size()** == N is an invariant.
- <sup>2</sup> An **array** is an aggregate (11.6.1) that can be list-initialized with up to N elements whose types are convertible to T.
- <sup>3</sup> An **array** satisfies all of the requirements of a container and of a reversible container (26.2), except that a default constructed **array** object is not empty and that **swap** does not have constant complexity. An **array** satisfies some of the requirements of a sequence container (26.2.3). Descriptions are provided here only for

operations on array that are not described in one of these tables and for operations where there is additional semantic information.

```

namespace std {
 template <class T, size_t N>
 struct array {
 // types:
 using value_type = T;
 using pointer = T*;
 using const_pointer = const T*;
 using reference = T&;
 using const_reference = const T&;
 using size_type = size_t;
 using difference_type = ptrdiff_t;
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;

 // no explicit construct/copy/destroy for aggregate type

 void fill(const T& u);
 void swap(array&) noexcept(is_nothrow_swappable_v<T>);

 // iterators:
 constexpr iterator begin() noexcept;
 constexpr const_iterator begin() const noexcept;
 constexpr iterator end() noexcept;
 constexpr const_iterator end() const noexcept;

 constexpr reverse_iterator rbegin() noexcept;
 constexpr const_reverse_iterator rbegin() const noexcept;
 constexpr reverse_iterator rend() noexcept;
 constexpr const_reverse_iterator rend() const noexcept;

 constexpr const_iterator cbegin() const noexcept;
 constexpr const_iterator cend() const noexcept;
 constexpr const_reverse_iterator crbegin() const noexcept;
 constexpr const_reverse_iterator crend() const noexcept;

 // capacity:
 constexpr bool empty() const noexcept;
 constexpr size_type size() const noexcept;
 constexpr size_type max_size() const noexcept;

 // element access:
 constexpr reference operator[](size_type n);
 constexpr const_reference operator[](size_type n) const;
 constexpr reference at(size_type n);
 constexpr const_reference at(size_type n) const;
 constexpr reference front();
 constexpr const_reference front() const;
 constexpr reference back();
 constexpr const_reference back() const;

 constexpr T * data() noexcept;
 };

```

```

 constexpr const T * data() const noexcept;
};

template<class T, class... U>
 array(T, U...) -> array<T, 1 + sizeof...(U)>;
}

```

### 26.3.7.2 array constructors, copy, and assignment [array.cons]

- <sup>1</sup> The conditions for an aggregate (11.6.1) shall be met. Class `array` relies on the implicitly-declared special member functions (15.1, 15.4, and 15.8) to conform to the container requirements table in 26.2. In addition to the requirements specified in the container requirements table, the implicit move constructor and move assignment operator for `array` require that `T` be `MoveConstructible` or `MoveAssignable`, respectively.

```

template<class T, class... U>
 array(T, U...) -> array<T, 1 + sizeof...(U)>;

```

- <sup>2</sup> *Requires:* `(is_same_v<T, U> && ...)` is true. Otherwise the program is ill-formed.

### 26.3.7.3 array specialized algorithms [array.special]

```

template <class T, size_t N>
 void swap(array<T, N>& x, array<T, N>& y) noexcept(noexcept(x.swap(y)));

```

- <sup>1</sup> *Remarks:* This function shall not participate in overload resolution unless `N == 0` or `is_swappable_v<T>` is true.
- <sup>2</sup> *Effects:* As if by `x.swap(y)`.
- <sup>3</sup> *Complexity:* Linear in `N`.

### 26.3.7.4 array::size [array.size]

```

template <class T, size_t N> constexpr size_type array<T, N>::size() const noexcept;

```

- <sup>1</sup> *Returns:* `N`.

### 26.3.7.5 array::data [array.data]

```

constexpr T* data() noexcept;
constexpr const T* data() const noexcept;

```

- <sup>1</sup> *Returns:* A pointer such that `data() == addressof(front())`, and `[data(), data() + size())` is a valid range.

### 26.3.7.6 array::fill [array.fill]

```

void fill(const T& u);

```

- <sup>1</sup> *Effects:* As if by `fill_n(begin(), N, u)`.

### 26.3.7.7 array::swap [array.swap]

```

void swap(array& y) noexcept(is_nothrow_swappable_v<T>);

```

- <sup>1</sup> *Effects:* Equivalent to `swap_ranges(begin(), end(), y.begin())`.
- <sup>2</sup> [ *Note:* Unlike the `swap` function for other containers, `array::swap` takes linear time, may exit via an exception, and does not cause iterators to become associated with the other container. — *end note* ]

### 26.3.7.8 Zero sized arrays [array.zero]

- <sup>1</sup> `array` shall provide support for the special case `N == 0`.



- 2 In the case that `N == 0`, `begin()` == `end()` == unique value. The return value of `data()` is unspecified.
- 3 The effect of calling `front()` or `back()` for a zero-sized array is undefined.
- 4 Member function `swap()` shall have a non-throwing exception specification.

### 26.3.7.9 Tuple interface to class template array

[array.tuple]

```
template <class T, size_t N>
 struct tuple_size<array<T, N>> : integral_constant<size_t, N> { };

tuple_element<I, array<T, N>>::type
```

- 1 *Requires:* `I < N`. The program is ill-formed if `I` is out of bounds.
- 2 *Value:* The type `T`.

```
template <size_t I, class T, size_t N>
 constexpr T& get(array<T, N>& a) noexcept;
template <size_t I, class T, size_t N>
 constexpr T&& get(array<T, N>&& a) noexcept;
template <size_t I, class T, size_t N>
 constexpr const T& get(const array<T, N>& a) noexcept;
template <size_t I, class T, size_t N>
 constexpr const T&& get(const array<T, N>&& a) noexcept;
```

- 3 *Requires:* `I < N`. The program is ill-formed if `I` is out of bounds.
- 4 *Returns:* A reference to the `I`th element of `a`, where indexing is zero-based.

### 26.3.8 Class template deque

[deque]

#### 26.3.8.1 Class template deque overview

[deque.overview]

- 1 A `deque` is a sequence container that supports random access iterators (27.2.7). In addition, it supports constant time insert and erase operations at the beginning or the end; insert and erase in the middle take linear time. That is, a `deque` is especially optimized for pushing and popping elements at the beginning and end. Storage management is handled automatically.
- 2 A `deque` satisfies all of the requirements of a container, of a reversible container (given in tables in 26.2), of a sequence container, including the optional sequence container requirements (26.2.3), and of an allocator-aware container (Table 86). Descriptions are provided here only for operations on `deque` that are not described in one of these tables or for operations where there is additional semantic information.

```
namespace std {
 template <class T, class Allocator = allocator<T>>
 class deque {
 public:
 // types:
 using value_type = T;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;
```

```

// 26.3.8.2, construct/copy/destroy
deque() : deque(Allocator()) { }
explicit deque(const Allocator&);
explicit deque(size_type n, const Allocator& = Allocator());
deque(size_type n, const T& value, const Allocator& = Allocator());
template <class InputIterator>
 deque(InputIterator first, InputIterator last, const Allocator& = Allocator());
deque(const deque& x);
deque(deque&&);
deque(const deque&, const Allocator&);
deque(deque&&, const Allocator&);
deque(initializer_list<T>, const Allocator& = Allocator());

~deque();
deque& operator=(const deque& x);
deque& operator=(deque&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value);
deque& operator=(initializer_list<T>);
template <class InputIterator>
 void assign(InputIterator first, InputIterator last);
void assign(size_type n, const T& t);
void assign(initializer_list<T>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// 26.3.8.3, capacity
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;
void resize(size_type sz);
void resize(size_type sz, const T& c);
void shrink_to_fit();

// element access:
reference operator[](size_type n);
const_reference operator[](size_type n) const;
reference at(size_type n);
const_reference at(size_type n) const;
reference front();
const_reference front() const;

```

```

 reference back();
 const_reference back() const;

 // 26.3.8.4, modifiers
 template <class... Args> reference emplace_front(Args&&... args);
 template <class... Args> reference emplace_back(Args&&... args);
 template <class... Args> iterator emplace(const_iterator position, Args&&... args);

 void push_front(const T& x);
 void push_front(T&& x);
 void push_back(const T& x);
 void push_back(T&& x);

 iterator insert(const_iterator position, const T& x);
 iterator insert(const_iterator position, T&& x);
 iterator insert(const_iterator position, size_type n, const T& x);
 template <class InputIterator>
 iterator insert(const_iterator position, InputIterator first, InputIterator last);
 iterator insert(const_iterator position, initializer_list<T>);

 void pop_front();
 void pop_back();

 iterator erase(const_iterator position);
 iterator erase(const_iterator first, const_iterator last);
 void swap(deque&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value);
 void clear() noexcept;
};

template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
 deque(InputIterator, InputIterator, Allocator = Allocator())
 -> deque<typename iterator_traits<InputIterator>::value_type, Allocator>;

template <class T, class Allocator>
 bool operator==(const deque<T, Allocator>& x, const deque<T, Allocator>& y);
template <class T, class Allocator>
 bool operator< (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
template <class T, class Allocator>
 bool operator!=(const deque<T, Allocator>& x, const deque<T, Allocator>& y);
template <class T, class Allocator>
 bool operator> (const deque<T, Allocator>& x, const deque<T, Allocator>& y);
template <class T, class Allocator>
 bool operator>=(const deque<T, Allocator>& x, const deque<T, Allocator>& y);
template <class T, class Allocator>
 bool operator<=(const deque<T, Allocator>& x, const deque<T, Allocator>& y);

 // 26.3.8.5, specialized algorithms
 template <class T, class Allocator>
 void swap(deque<T, Allocator>& x, deque<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

## 26.3.8.2 deque constructors, copy, and assignment

[deque.cons]

```
explicit deque(const Allocator&);
```

1     *Effects:* Constructs an empty deque, using the specified allocator.

2     *Complexity:* Constant.

```
explicit deque(size_type n, const Allocator& = Allocator());
```

3     *Effects:* Constructs a deque with *n* default-inserted elements using the specified allocator.

4     *Requires:* T shall be DefaultInsertable into \*this.

5     *Complexity:* Linear in *n*.

```
deque(size_type n, const T& value, const Allocator& = Allocator());
```

6     *Effects:* Constructs a deque with *n* copies of *value*, using the specified allocator.

7     *Requires:* T shall be CopyInsertable into \*this.

8     *Complexity:* Linear in *n*.

```
template <class InputIterator>
```

```
 deque(InputIterator first, InputIterator last, const Allocator& = Allocator());
```

9     *Effects:* Constructs a deque equal to the range [*first*, *last*), using the specified allocator.

10    *Complexity:* Linear in *distance(first, last)*.

### 26.3.8.3 deque capacity

[deque.capacity]

```
void resize(size_type sz);
```

1     *Effects:* If *sz* < *size()*, erases the last *size()* - *sz* elements from the sequence. Otherwise, appends *sz* - *size()* default-inserted elements to the sequence.

2     *Requires:* T shall be MoveInsertable and DefaultInsertable into \*this.

```
void resize(size_type sz, const T& c);
```

3     *Effects:* If *sz* < *size()*, erases the last *size()* - *sz* elements from the sequence. Otherwise, appends *sz* - *size()* copies of *c* to the sequence.

4     *Requires:* T shall be CopyInsertable into \*this.

```
void shrink_to_fit();
```

5     *Requires:* T shall be MoveInsertable into \*this.

6     *Effects:* *shrink\_to\_fit* is a non-binding request to reduce memory use but does not change the size of the sequence. [ *Note:* The request is non-binding to allow latitude for implementation-specific optimizations. — *end note* ] If an exception is thrown other than by the move constructor of a non-CopyInsertable T there are no effects.

7     *Complexity:* Linear in the size of the sequence.

8     *Remarks:* *shrink\_to\_fit* invalidates all the references, pointers, and iterators referring to the elements in the sequence as well as the past-the-end iterator.

### 26.3.8.4 deque modifiers

[deque.modifiers]

```
iterator insert(const_iterator position, const T& x);
```

```
iterator insert(const_iterator position, T&& x);
```

```
iterator insert(const_iterator position, size_type n, const T& x);
```

```
template <class InputIterator>
```

```
 iterator insert(const_iterator position,
```

```

 InputIterator first, InputIterator last);
iterator insert(const_iterator position, initializer_list<T>);

template <class... Args> reference emplace_front(Args&&... args);
template <class... Args> reference emplace_back(Args&&... args);
template <class... Args> iterator emplace(const_iterator position, Args&&... args);
void push_front(const T& x);
void push_front(T&& x);
void push_back(const T& x);
void push_back(T&& x);

```

1 *Effects:* An insertion in the middle of the deque invalidates all the iterators and references to elements of the deque. An insertion at either end of the deque invalidates all the iterators to the deque, but has no effect on the validity of references to elements of the deque.

2 *Remarks:* If an exception is thrown other than by the copy constructor, move constructor, assignment operator, or move assignment operator of **T** there are no effects. If an exception is thrown while inserting a single element at either end, there are no effects. Otherwise, if an exception is thrown by the move constructor of a non-CopyInsertable **T**, the effects are unspecified.

3 *Complexity:* The complexity is linear in the number of elements inserted plus the lesser of the distances to the beginning and end of the deque. Inserting a single element either at the beginning or end of a deque always takes constant time and causes a single call to a constructor of **T**.

```

iterator erase(const_iterator position);
iterator erase(const_iterator first, const_iterator last);
void pop_front();
void pop_back();

```

4 *Effects:* An erase operation that erases the last element of a deque invalidates only the past-the-end iterator and all iterators and references to the erased elements. An erase operation that erases the first element of a deque but not the last element invalidates only iterators and references to the erased elements. An erase operation that erases neither the first element nor the last element of a deque invalidates the past-the-end iterator and all iterators and references to all the elements of the deque. [ *Note:* `pop_front` and `pop_back` are erase operations. — *end note* ]

5 *Complexity:* The number of calls to the destructor of **T** is the same as the number of elements erased, but the number of calls to the assignment operator of **T** is no more than the lesser of the number of elements before the erased elements and the number of elements after the erased elements.

6 *Throws:* Nothing unless an exception is thrown by the copy constructor, move constructor, assignment operator, or move assignment operator of **T**.

### 26.3.8.5 deque specialized algorithms

[deque.special]

```

template <class T, class Allocator>
void swap(deque<T, Allocator>& x, deque<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

```

1 *Effects:* As if by `x.swap(y)`.

### 26.3.9 Class template forward\_list

[forwardlist]

#### 26.3.9.1 Class template forward\_list overview

[forwardlist.overview]

1 A `forward_list` is a container that supports forward iterators and allows constant time insert and erase operations anywhere within the sequence, with storage management handled automatically. Fast random access to list elements is not supported. [ *Note:* It is intended that `forward_list` have zero space or time

overhead relative to a hand-written C-style singly linked list. Features that would conflict with that goal have been omitted. — *end note*]

- <sup>2</sup> A `forward_list` satisfies all of the requirements of a container (Table 83), except that the `size()` member function is not provided and `operator==` has linear complexity. A `forward_list` also satisfies all of the requirements for an allocator-aware container (Table 86). In addition, a `forward_list` provides the `assign` member functions (Table 87) and several of the optional container requirements (Table 88). Descriptions are provided here only for operations on `forward_list` that are not described in that table or for operations where there is additional semantic information.
- <sup>3</sup> [*Note:* Modifying any list requires access to the element preceding the first element of interest, but in a `forward_list` there is no constant-time way to access a preceding element. For this reason, ranges that are modified, such as those supplied to `erase` and `splice`, must be open at the beginning. — *end note*]

```
namespace std {
 template <class T, class Allocator = allocator<T>>
 class forward_list {
 public:
 // types:
 using value_type = T;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2

 // 26.3.9.2, construct/copy/destroy
 forward_list() : forward_list(Allocator()) { }
 explicit forward_list(const Allocator&);
 explicit forward_list(size_type n, const Allocator& = Allocator());
 forward_list(size_type n, const T& value,
 const Allocator& = Allocator());
 template <class InputIterator>
 forward_list(InputIterator first, InputIterator last,
 const Allocator& = Allocator());
 forward_list(const forward_list& x);
 forward_list(forward_list&& x);
 forward_list(const forward_list& x, const Allocator&);
 forward_list(forward_list&& x, const Allocator&);
 forward_list(initializer_list<T>, const Allocator& = Allocator());
 ~forward_list();
 forward_list& operator=(const forward_list& x);
 forward_list& operator=(forward_list&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value);
 forward_list& operator=(initializer_list<T>);
 template <class InputIterator>
 void assign(InputIterator first, InputIterator last);
 void assign(size_type n, const T& t);
 void assign(initializer_list<T>);
 allocator_type get_allocator() const noexcept;

 // 26.3.9.3, iterators
```

```

iterator before_begin() noexcept;
const_iterator before_begin() const noexcept;
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cbefore_begin() const noexcept;
const_iterator cend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type max_size() const noexcept;

// 26.3.9.4, element access
reference front();
const_reference front() const;

// 26.3.9.5, modifiers
template <class... Args> reference emplace_front(Args&&... args);
void push_front(const T& x);
void push_front(T&& x);
void pop_front();

template <class... Args> iterator emplace_after(const_iterator position, Args&&... args);
iterator insert_after(const_iterator position, const T& x);
iterator insert_after(const_iterator position, T&& x);

iterator insert_after(const_iterator position, size_type n, const T& x);
template <class InputIterator>
 iterator insert_after(const_iterator position, InputIterator first, InputIterator last);
iterator insert_after(const_iterator position, initializer_list<T> il);

iterator erase_after(const_iterator position);
iterator erase_after(const_iterator position, const_iterator last);
void swap(forward_list&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value);

void resize(size_type sz);
void resize(size_type sz, const value_type& c);
void clear() noexcept;

// 26.3.9.6, forward_list operations
void splice_after(const_iterator position, forward_list& x);
void splice_after(const_iterator position, forward_list&& x);
void splice_after(const_iterator position, forward_list& x,
 const_iterator i);
void splice_after(const_iterator position, forward_list&& x,
 const_iterator i);
void splice_after(const_iterator position, forward_list& x,
 const_iterator first, const_iterator last);
void splice_after(const_iterator position, forward_list&& x,
 const_iterator first, const_iterator last);

```

```

void remove(const T& value);
template <class Predicate> void remove_if(Predicate pred);

void unique();
template <class BinaryPredicate> void unique(BinaryPredicate binary_pred);

void merge(forward_list& x);
void merge(forward_list&& x);
template <class Compare> void merge(forward_list& x, Compare comp);
template <class Compare> void merge(forward_list&& x, Compare comp);

void sort();
template <class Compare> void sort(Compare comp);

void reverse() noexcept;
};

template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
forward_list(InputIterator, InputIterator, Allocator = Allocator())
-> forward_list<typename iterator_traits<InputIterator>::value_type, Allocator>;

template <class T, class Allocator>
bool operator==(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
template <class T, class Allocator>
bool operator< (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
template <class T, class Allocator>
bool operator!=(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
template <class T, class Allocator>
bool operator> (const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
template <class T, class Allocator>
bool operator>=(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);
template <class T, class Allocator>
bool operator<=(const forward_list<T, Allocator>& x, const forward_list<T, Allocator>& y);

// 26.3.9.7, specialized algorithms
template <class T, class Allocator>
void swap(forward_list<T, Allocator>& x, forward_list<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

- <sup>4</sup> An incomplete type T may be used when instantiating `forward_list` if the allocator satisfies the allocator completeness requirements (20.5.3.5.1). T shall be complete before any member of the resulting specialization of `forward_list` is referenced.

### 26.3.9.2 `forward_list` constructors, copy, assignment

[forwardlist.cons]

```
explicit forward_list(const Allocator&);
```

- <sup>1</sup> *Effects:* Constructs an empty `forward_list` object using the specified allocator.
- <sup>2</sup> *Complexity:* Constant.

```
explicit forward_list(size_type n, const Allocator& = Allocator());
```

- <sup>3</sup> *Effects:* Constructs a `forward_list` object with n default-inserted elements using the specified allocator.
- <sup>4</sup> *Requires:* T shall be `DefaultInsertable` into `*this`.



5 *Complexity:* Linear in *n*.

`forward_list(size_type n, const T& value, const Allocator& = Allocator());`

6 *Effects:* Constructs a `forward_list` object with *n* copies of *value* using the specified allocator.

7 *Requires:* *T* shall be CopyInsertable into *\*this*.

8 *Complexity:* Linear in *n*.

`template <class InputIterator>`

`forward_list(InputIterator first, InputIterator last, const Allocator& = Allocator());`

9 *Effects:* Constructs a `forward_list` object equal to the range `[first, last)`.

10 *Complexity:* Linear in `distance(first, last)`.

### 26.3.9.3 `forward_list` iterators

[forwardlist.iter]

`iterator before_begin() noexcept;`

`const_iterator before_begin() const noexcept;`

`const_iterator cbefore_begin() const noexcept;`

1 *Returns:* A non-dereferenceable iterator that, when incremented, is equal to the iterator returned by `begin()`.

2 *Effects:* `cbefore_begin()` is equivalent to `const_cast<forward_list const*>(*this).before_begin()`.

3 *Remarks:* `before_begin() == end()` shall equal false.

### 26.3.9.4 `forward_list` element access

[forwardlist.access]

`reference front();`

`const_reference front() const;`

1 *Returns:* `*begin()`

### 26.3.9.5 `forward_list` modifiers

[forwardlist.modifiers]

1 None of the overloads of `insert_after` shall affect the validity of iterators and references, and `erase_after` shall invalidate only iterators and references to the erased elements. If an exception is thrown during `insert_after` there shall be no effect. Inserting *n* elements into a `forward_list` is linear in *n*, and the number of calls to the copy or move constructor of *T* is exactly equal to *n*. Erasing *n* elements from a `forward_list` is linear in *n* and the number of calls to the destructor of type *T* is exactly equal to *n*.

`template <class... Args> reference emplace_front(Args&&... args);`

2 *Effects:* Inserts an object of type `value_type` constructed with `value_type(std::forward<Args>(args)...) at the beginning of the list.`

`void push_front(const T& x);`

`void push_front(T&& x);`

3 *Effects:* Inserts a copy of *x* at the beginning of the list.

`void pop_front();`

4 *Effects:* As if by `erase_after(before_begin())`.

`iterator insert_after(const_iterator position, const T& x);`

`iterator insert_after(const_iterator position, T&& x);`

5 *Requires:* *position* is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`.

6       *Effects:* Inserts a copy of `x` after `position`.

7       *Returns:* An iterator pointing to the copy of `x`.

```
iterator insert_after(const_iterator position, size_type n, const T& x);
```

8       *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`.

9       *Effects:* Inserts `n` copies of `x` after `position`.

10      *Returns:* An iterator pointing to the last inserted copy of `x` or `position` if `n == 0`.

```
template <class InputIterator>
 iterator insert_after(const_iterator position, InputIterator first, InputIterator last);
```

11      *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`.  
`first` and `last` are not iterators in `*this`.

12      *Effects:* Inserts copies of elements in `[first, last)` after `position`.

13      *Returns:* An iterator pointing to the last inserted element or `position` if `first == last`.

```
iterator insert_after(const_iterator position, initializer_list<T> il);
```

14      *Effects:* `insert_after(p, il.begin(), il.end())`.

15      *Returns:* An iterator pointing to the last inserted element or `position` if `il` is empty.

```
template <class... Args>
 iterator emplace_after(const_iterator position, Args&&... args);
```

16      *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`.

17      *Effects:* Inserts an object of type `value_type` constructed with `value_type(std::forward<Args>(args)...) after position`.

18      *Returns:* An iterator pointing to the new object.

```
iterator erase_after(const_iterator position);
```

19      *Requires:* The iterator following `position` is dereferenceable.

20      *Effects:* Erases the element pointed to by the iterator following `position`.

21      *Returns:* An iterator pointing to the element following the one that was erased, or `end()` if no such element exists.

22      *Throws:* Nothing.

```
iterator erase_after(const_iterator position, const_iterator last);
```

23      *Requires:* All iterators in the range `(position, last)` are dereferenceable.

24      *Effects:* Erases the elements in the range `(position, last)`.

25      *Returns:* `last`.

26      *Throws:* Nothing.

```
void resize(size_type sz);
```

27      *Effects:* If `sz < distance(begin(), end())`, erases the last `distance(begin(), end()) - sz` elements from the list. Otherwise, inserts `sz - distance(begin(), end())` default-inserted elements at the end of the list.

28      *Requires:* `T` shall be `DefaultInsertable` into `*this`.

```
void resize(size_type sz, const value_type& c);
```

29 *Effects:* If `sz < distance(begin(), end())`, erases the last `distance(begin(), end()) - sz` elements from the list. Otherwise, inserts `sz - distance(begin(), end())` copies of `c` at the end of the list.

30 *Requires:* `T` shall be CopyInsertable into `*this`.

`void clear() noexcept;`

31 *Effects:* Erases all elements in the range `[begin(), end())`.

32 *Remarks:* Does not invalidate past-the-end iterators.

### 26.3.9.6 forward\_list operations

[forwardlist.ops]

`void splice_after(const_iterator position, forward_list& x);`

`void splice_after(const_iterator position, forward_list&& x);`

1 *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`. `get_allocator() == x.get_allocator(). &x != this`.

2 *Effects:* Inserts the contents of `x` after `position`, and `x` becomes empty. Pointers and references to the moved elements of `x` now refer to those same elements but as members of `*this`. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into `*this`, not into `x`.

3 *Throws:* Nothing.

4 *Complexity:*  $\mathcal{O}(\text{distance}(x.\text{begin}(), x.\text{end}()))$

`void splice_after(const_iterator position, forward_list& x, const_iterator i);`

`void splice_after(const_iterator position, forward_list&& x, const_iterator i);`

5 *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`. The iterator following `i` is a dereferenceable iterator in `x`. `get_allocator() == x.get_allocator()`.

6 *Effects:* Inserts the element following `i` into `*this`, following `position`, and removes it from `x`. The result is unchanged if `position == i` or `position == ++i`. Pointers and references to `*++i` continue to refer to the same element but as a member of `*this`. Iterators to `*++i` continue to refer to the same element, but now behave as iterators into `*this`, not into `x`.

7 *Throws:* Nothing.

8 *Complexity:*  $\mathcal{O}(1)$

`void splice_after(const_iterator position, forward_list& x,  
                  const_iterator first, const_iterator last);`

`void splice_after(const_iterator position, forward_list&& x,  
                  const_iterator first, const_iterator last);`

9 *Requires:* `position` is `before_begin()` or is a dereferenceable iterator in the range `[begin(), end())`. `(first, last)` is a valid range in `x`, and all iterators in the range `(first, last)` are dereferenceable. `position` is not an iterator in the range `(first, last)`. `get_allocator() == x.get_allocator()`.

10 *Effects:* Inserts elements in the range `(first, last)` after `position` and removes the elements from `x`. Pointers and references to the moved elements of `x` now refer to those same elements but as members of `*this`. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into `*this`, not into `x`.

11 *Complexity:*  $\mathcal{O}(\text{distance}(\text{first}, \text{last}))$

`void remove(const T& value);`

`template <class Predicate> void remove_if(Predicate pred);`

12 *Effects:* Erases all the elements in the list referred by a list iterator `i` for which the following conditions hold: `*i == value` (for `remove()`), `pred(*i)` is `true` (for `remove_if()`). Invalidates only the iterators and references to the erased elements.

13 *Throws:* Nothing unless an exception is thrown by the equality comparison or the predicate.

14 *Remarks:* Stable (20.5.5.7).

15 *Complexity:* Exactly `distance(begin(), end())` applications of the corresponding predicate.

```
void unique();
template <class BinaryPredicate> void unique(BinaryPredicate pred);
```

16 *Effects:* Erases all but the first element from every consecutive group of equal elements referred to by the iterator `i` in the range `[first + 1, last)` for which `*i == *(i-1)` (for the version with no arguments) or `pred(*i, *(i - 1))` (for the version with a predicate argument) holds. Invalidates only the iterators and references to the erased elements.

17 *Throws:* Nothing unless an exception is thrown by the equality comparison or the predicate.

18 *Complexity:* If the range `[first, last)` is not empty, exactly `(last - first) - 1` applications of the corresponding predicate, otherwise no applications of the predicate.

```
void merge(forward_list& x);
void merge(forward_list&& x);
template <class Compare> void merge(forward_list& x, Compare comp);
template <class Compare> void merge(forward_list&& x, Compare comp);
```

19 *Requires:* `comp` defines a strict weak ordering (28.7), and `*this` and `x` are both sorted according to this ordering. `get_allocator() == x.get_allocator()`.

20 *Effects:* Merges the two sorted ranges `[begin(), end())` and `[x.begin(), x.end())`. `x` is empty after the merge. If an exception is thrown other than by a comparison there are no effects. Pointers and references to the moved elements of `x` now refer to those same elements but as members of `*this`. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into `*this`, not into `x`.

21 *Remarks:* Stable (20.5.5.7). The behavior is undefined if `get_allocator() != x.get_allocator()`.

22 *Complexity:* At most `distance(begin(), end()) + distance(x.begin(), x.end()) - 1` comparisons.

```
void sort();
template <class Compare> void sort(Compare comp);
```

23 *Requires:* `operator<` (for the version with no arguments) or `comp` (for the version with a comparison argument) defines a strict weak ordering (28.7).

24 *Effects:* Sorts the list according to the `operator<` or the `comp` function object. If an exception is thrown, the order of the elements in `*this` is unspecified. Does not affect the validity of iterators and references.

25 *Remarks:* Stable (20.5.5.7).

26 *Complexity:* Approximately  $N \log N$  comparisons, where  $N$  is `distance(begin(), end())`.

```
void reverse() noexcept;
```

27 *Effects:* Reverses the order of the elements in the list. Does not affect the validity of iterators and references.

28 *Complexity:* Linear time.

**26.3.9.7 forward\_list specialized algorithms**

[forwardlist.spec]

```
template <class T, class Allocator>
void swap(forward_list<T, Allocator>& x, forward_list<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
```

<sup>1</sup> *Effects:* As if by `x.swap(y)`.

**26.3.10 Class template list**

[list]

**26.3.10.1 Class template list overview**

[list.overview]

- <sup>1</sup> A `list` is a sequence container that supports bidirectional iterators and allows constant time insert and erase operations anywhere within the sequence, with storage management handled automatically. Unlike vectors (26.3.11) and deques (26.3.8), fast random access to list elements is not supported, but many algorithms only need sequential access anyway.
- <sup>2</sup> A `list` satisfies all of the requirements of a container, of a reversible container (given in two tables in 26.2), of a sequence container, including most of the optional sequence container requirements (26.2.3), and of an allocator-aware container (Table 86). The exceptions are the `operator[]` and `at` member functions, which are not provided.<sup>258</sup> Descriptions are provided here only for operations on `list` that are not described in one of these tables or for operations where there is additional semantic information.

```
namespace std {
 template <class T, class Allocator = allocator<T>>
 class list {
 public:
 // types:
 using value_type = T;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;

 // 26.3.10.2, construct/copy/destroy
 list() : list(Allocator()) { }
 explicit list(const Allocator&);
 explicit list(size_type n, const Allocator& = Allocator());
 list(size_type n, const T& value, const Allocator& = Allocator());
 template <class InputIterator>
 list(InputIterator first, InputIterator last, const Allocator& = Allocator());
 list(const list& x);
 list(list&& x);
 list(const list&, const Allocator&);
 list(list&&, const Allocator&);
 list(initializer_list<T>, const Allocator& = Allocator());
 ~list();
 list& operator=(const list& x);
 list& operator=(list&& x)
```

<sup>258</sup>) These member functions are only provided by containers whose iterators are random access iterators.

```

 noexcept(allocator_traits<Allocator>::is_always_equal::value);
list& operator=(initializer_list<T>);
template <class InputIterator>
 void assign(InputIterator first, InputIterator last);
void assign(size_type n, const T& t);
void assign(initializer_list<T>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// 26.3.10.3, capacity
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;
void resize(size_type sz);
void resize(size_type sz, const T& c);

// element access:
reference front();
const_reference front() const;
reference back();
const_reference back() const;

// 26.3.10.4, modifiers
template <class... Args> reference emplace_front(Args&&... args);
template <class... Args> reference emplace_back(Args&&... args);
void push_front(const T& x);
void push_front(T&& x);
void pop_front();
void push_back(const T& x);
void push_back(T&& x);
void pop_back();

template <class... Args> iterator emplace(const_iterator position, Args&&... args);
iterator insert(const_iterator position, const T& x);
iterator insert(const_iterator position, T&& x);
iterator insert(const_iterator position, size_type n, const T& x);
template <class InputIterator>
 iterator insert(const_iterator position, InputIterator first,
 InputIterator last);
iterator insert(const_iterator position, initializer_list<T> il);

```

```

 iterator erase(const_iterator position);
 iterator erase(const_iterator position, const_iterator last);
 void swap(list&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value);
 void clear() noexcept;

 // 26.3.10.5, list operations
 void splice(const_iterator position, list& x);
 void splice(const_iterator position, list&& x);
 void splice(const_iterator position, list& x, const_iterator i);
 void splice(const_iterator position, list&& x, const_iterator i);
 void splice(const_iterator position, list& x,
 const_iterator first, const_iterator last);
 void splice(const_iterator position, list&& x,
 const_iterator first, const_iterator last);

 void remove(const T& value);
 template <class Predicate> void remove_if(Predicate pred);

 void unique();
 template <class BinaryPredicate>
 void unique(BinaryPredicate binary_pred);

 void merge(list& x);
 void merge(list&& x);
 template <class Compare> void merge(list& x, Compare comp);
 template <class Compare> void merge(list&& x, Compare comp);

 void sort();
 template <class Compare> void sort(Compare comp);

 void reverse() noexcept;
};

template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
list(InputIterator, InputIterator, Allocator = Allocator())
 -> list<typename iterator_traits<InputIterator>::value_type, Allocator>;

template <class T, class Allocator>
 bool operator==(const list<T, Allocator>& x, const list<T, Allocator>& y);
template <class T, class Allocator>
 bool operator< (const list<T, Allocator>& x, const list<T, Allocator>& y);
template <class T, class Allocator>
 bool operator!=(const list<T, Allocator>& x, const list<T, Allocator>& y);
template <class T, class Allocator>
 bool operator> (const list<T, Allocator>& x, const list<T, Allocator>& y);
template <class T, class Allocator>
 bool operator>=(const list<T, Allocator>& x, const list<T, Allocator>& y);
template <class T, class Allocator>
 bool operator<=(const list<T, Allocator>& x, const list<T, Allocator>& y);

 // 26.3.10.6, specialized algorithms
 template <class T, class Allocator>
 void swap(list<T, Allocator>& x, list<T, Allocator>& y)

```

```

 noexcept(noexcept(x.swap(y)));
 }

```

- 3 An incomplete type `T` may be used when instantiating `list` if the allocator satisfies the allocator completeness requirements (20.5.3.5.1). `T` shall be complete before any member of the resulting specialization of `list` is referenced.

### 26.3.10.2 `list` constructors, copy, and assignment

[list.cons]

```
explicit list(const Allocator&);
```

- 1 *Effects:* Constructs an empty list, using the specified allocator.

- 2 *Complexity:* Constant.

```
explicit list(size_type n, const Allocator& = Allocator());
```

- 3 *Effects:* Constructs a `list` with `n` default-inserted elements using the specified allocator.

- 4 *Requires:* `T` shall be `DefaultInsertable` into `*this`.

- 5 *Complexity:* Linear in `n`.

```
list(size_type n, const T& value, const Allocator& = Allocator());
```

- 6 *Effects:* Constructs a `list` with `n` copies of `value`, using the specified allocator.

- 7 *Requires:* `T` shall be `CopyInsertable` into `*this`.

- 8 *Complexity:* Linear in `n`.

```
template <class InputIterator>
```

```
list(InputIterator first, InputIterator last, const Allocator& = Allocator());
```

- 9 *Effects:* Constructs a `list` equal to the range `[first, last)`.

- 10 *Complexity:* Linear in `distance(first, last)`.

### 26.3.10.3 `list` capacity

[list.capacity]

```
void resize(size_type sz);
```

- 1 *Effects:* If `size() < sz`, appends `sz - size()` default-inserted elements to the sequence. If `sz <= size()`, equivalent to:

```

 list<T>::iterator it = begin();
 advance(it, sz);
 erase(it, end());

```

- 2 *Requires:* `T` shall be `DefaultInsertable` into `*this`.

```
void resize(size_type sz, const T& c);
```

- 3 *Effects:* As if by:

```

 if (sz > size())
 insert(end(), sz-size(), c);
 else if (sz < size()) {
 iterator i = begin();
 advance(i, sz);
 erase(i, end());
 }
 else
 ; // do nothing

```

- 4 *Requires:* `T` shall be `CopyInsertable` into `*this`.



**26.3.10.4 list modifiers****[list.modifiers]**

```

iterator insert(const_iterator position, const T& x);
iterator insert(const_iterator position, T&& x);
iterator insert(const_iterator position, size_type n, const T& x);
template <class InputIterator>
 iterator insert(const_iterator position, InputIterator first,
 InputIterator last);
iterator insert(const_iterator position, initializer_list<T>);

template <class... Args> reference emplace_front(Args&&... args);
template <class... Args> reference emplace_back(Args&&... args);
template <class... Args> iterator emplace(const_iterator position, Args&&... args);
void push_front(const T& x);
void push_front(T&& x);
void push_back(const T& x);
void push_back(T&& x);

```

1 *Remarks:* Does not affect the validity of iterators and references. If an exception is thrown there are no effects.

2 *Complexity:* Insertion of a single element into a list takes constant time and exactly one call to a constructor of T. Insertion of multiple elements into a list is linear in the number of elements inserted, and the number of calls to the copy constructor or move constructor of T is exactly equal to the number of elements inserted.

```

iterator erase(const_iterator position);
iterator erase(const_iterator first, const_iterator last);

```

```

void pop_front();
void pop_back();
void clear() noexcept;

```

3 *Effects:* Invalidates only the iterators and references to the erased elements.

4 *Throws:* Nothing.

5 *Complexity:* Erasing a single element is a constant time operation with a single call to the destructor of T. Erasing a range in a list is linear time in the size of the range and the number of calls to the destructor of type T is exactly equal to the size of the range.

**26.3.10.5 list operations****[list.ops]**

1 Since lists allow fast insertion and erasing from the middle of a list, certain operations are provided specifically for them.<sup>259</sup>

2 `list` provides three splice operations that destructively move elements from one list to another. The behavior of splice operations is undefined if `get_allocator() != x.get_allocator()`.

```

void splice(const_iterator position, list& x);
void splice(const_iterator position, list&& x);

```

3 *Requires:* `&x != this`.

4 *Effects:* Inserts the contents of `x` before `position` and `x` becomes empty. Pointers and references to the moved elements of `x` now refer to those same elements but as members of `*this`. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into `*this`, not into `x`.

259) As specified in 20.5.3.5, the requirements in this Clause apply only to lists whose allocators compare equal.

5 *Throws:* Nothing.

6 *Complexity:* Constant time.

```
void splice(const_iterator position, list& x, const_iterator i);
void splice(const_iterator position, list&& x, const_iterator i);
```

7 *Requires:* *i* is a valid dereferenceable iterator of *x*.

8 *Effects:* Inserts an element pointed to by *i* from list *x* before *position* and removes the element from *x*. The result is unchanged if *position* == *i* or *position* == ++*i*. Pointers and references to \**i* continue to refer to this same element but as a member of \**this*. Iterators to \**i* (including *i* itself) continue to refer to the same element, but now behave as iterators into \**this*, not into *x*.

9 *Throws:* Nothing.

10 *Complexity:* Constant time.

```
void splice(const_iterator position, list& x, const_iterator first,
 const_iterator last);
void splice(const_iterator position, list&& x, const_iterator first,
 const_iterator last);
```

11 *Requires:* [*first*, *last*) is a valid range in *x*. The program has undefined behavior if *position* is an iterator in the range [*first*, *last*).

12 *Effects:* Inserts elements in the range [*first*, *last*) before *position* and removes the elements from *x*. Pointers and references to the moved elements of *x* now refer to those same elements but as members of \**this*. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into \**this*, not into *x*.

13 *Throws:* Nothing.

14 *Complexity:* Constant time if &*x* == *this*; otherwise, linear time.

```
void remove(const T& value);
template <class Predicate> void remove_if(Predicate pred);
```

15 *Effects:* Erases all the elements in the list referred by a list iterator *i* for which the following conditions hold: \**i* == *value*, *pred*(\**i*) != *false*. Invalidates only the iterators and references to the erased elements.

16 *Throws:* Nothing unless an exception is thrown by \**i* == *value* or *pred*(\**i*) != *false*.

17 *Remarks:* Stable (20.5.5.7).

18 *Complexity:* Exactly *size()* applications of the corresponding predicate.

```
void unique();
template <class BinaryPredicate> void unique(BinaryPredicate binary_pred);
```

19 *Effects:* Erases all but the first element from every consecutive group of equal elements referred to by the iterator *i* in the range [*first* + 1, *last*) for which \**i* == \*(*i*-1) (for the version of *unique* with no arguments) or *pred*(\**i*, \*(*i* - 1)) (for the version of *unique* with a predicate argument) holds. Invalidates only the iterators and references to the erased elements.

20 *Throws:* Nothing unless an exception is thrown by \**i* == \*(*i*-1) or *pred*(\**i*, \*(*i* - 1))

21 *Complexity:* If the range [*first*, *last*) is not empty, exactly (*last* - *first*) - 1 applications of the corresponding predicate, otherwise no applications of the predicate.

```
void merge(list& x);
void merge(list&& x);
```

```
template <class Compare> void merge(list& x, Compare comp);
template <class Compare> void merge(list&& x, Compare comp);
```

22 *Requires:* `comp` shall define a strict weak ordering (28.7), and both the list and the argument list shall be sorted according to this ordering.

23 *Effects:* If `(&x == this)` does nothing; otherwise, merges the two sorted ranges `[begin(), end())` and `[x.begin(), x.end())`. The result is a range in which the elements will be sorted in non-decreasing order according to the ordering defined by `comp`; that is, for every iterator `i`, in the range other than the first, the condition `comp(*i, *(i - 1))` will be `false`. Pointers and references to the moved elements of `x` now refer to those same elements but as members of `*this`. Iterators referring to the moved elements will continue to refer to their elements, but they now behave as iterators into `*this`, not into `x`.

24 *Remarks:* Stable (20.5.5.7). If `(&x != this)` the range `[x.begin(), x.end())` is empty after the merge. No elements are copied by this operation. The behavior is undefined if `get_allocator() != x.get_allocator()`.

25 *Complexity:* At most `size() + x.size() - 1` applications of `comp` if `(&x != this)`; otherwise, no applications of `comp` are performed. If an exception is thrown other than by a comparison there are no effects.

```
void reverse() noexcept;
```

26 *Effects:* Reverses the order of the elements in the list. Does not affect the validity of iterators and references.

27 *Complexity:* Linear time.

```
void sort();
template <class Compare> void sort(Compare comp);
```

28 *Requires:* `operator<` (for the first version) or `comp` (for the second version) shall define a strict weak ordering (28.7).

29 *Effects:* Sorts the list according to the `operator<` or a `Compare` function object. If an exception is thrown, the order of the elements in `*this` is unspecified. Does not affect the validity of iterators and references.

30 *Remarks:* Stable (20.5.5.7).

31 *Complexity:* Approximately  $N \log N$  comparisons, where  $N == \text{size}()$ .

### 26.3.10.6 list specialized algorithms

[list.special]

```
template <class T, class Allocator>
void swap(list<T, Allocator>& x, list<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
```

1 *Effects:* As if by `x.swap(y)`.

### 26.3.11 Class template vector

[vector]

#### 26.3.11.1 Class template vector overview

[vector.overview]

1 A **vector** is a sequence container that supports (amortized) constant time insert and erase operations at the end; insert and erase in the middle take linear time. Storage management is handled automatically, though hints can be given to improve efficiency.

2 A **vector** satisfies all of the requirements of a container and of a reversible container (given in two tables in 26.2), of a sequence container, including most of the optional sequence container requirements (26.2.3), of an allocator-aware container (Table 86), and, for an element type other than `bool`, of a contiguous

container (26.2.1). The exceptions are the `push_front`, `pop_front`, and `emplace_front` member functions, which are not provided. Descriptions are provided here only for operations on `vector` that are not described in one of these tables or for operations where there is additional semantic information.

```
namespace std {
 template <class T, class Allocator = allocator<T>>
 class vector {
 public:
 // types:
 using value_type = T;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;

 // 26.3.11.2, construct/copy/destroy
 vector() noexcept(noexcept(Allocator())) : vector(Allocator()) { }
 explicit vector(const Allocator&) noexcept;
 explicit vector(size_type n, const Allocator& = Allocator());
 vector(size_type n, const T& value, const Allocator& = Allocator());
 template <class InputIterator>
 vector(InputIterator first, InputIterator last, const Allocator& = Allocator());
 vector(const vector& x);
 vector(vector&&) noexcept;
 vector(const vector&, const Allocator&);
 vector(vector&&, const Allocator&);
 vector(initializer_list<T>, const Allocator& = Allocator());
 ~vector();
 vector& operator=(const vector& x);
 vector& operator=(vector&& x)
 noexcept(allocator_traits<Allocator>::propagate_on_container_move_assignment::value ||
 allocator_traits<Allocator>::is_always_equal::value);
 vector& operator=(initializer_list<T>);
 template <class InputIterator>
 void assign(InputIterator first, InputIterator last);
 void assign(size_type n, const T& u);
 void assign(initializer_list<T>);
 allocator_type get_allocator() const noexcept;

 // iterators:
 iterator begin() noexcept;
 const_iterator begin() const noexcept;
 iterator end() noexcept;
 const_iterator end() const noexcept;
 reverse_iterator rbegin() noexcept;
 const_reverse_iterator rbegin() const noexcept;
 reverse_iterator rend() noexcept;
 const_reverse_iterator rend() const noexcept;
```

```

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// 26.3.11.3, capacity
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;
size_type capacity() const noexcept;
void resize(size_type sz);
void resize(size_type sz, const T& c);
void reserve(size_type n);
void shrink_to_fit();

// element access:
reference operator[](size_type n);
const_reference operator[](size_type n) const;
const_reference at(size_type n) const;
reference at(size_type n);
reference front();
const_reference front() const;
reference back();
const_reference back() const;

// 26.3.11.4, data access
T* data() noexcept;
const T* data() const noexcept;

// 26.3.11.5, modifiers
template <class... Args> reference emplace_back(Args&&... args);
void push_back(const T& x);
void push_back(T&& x);
void pop_back();

template <class... Args> iterator emplace(const_iterator position, Args&&... args);
iterator insert(const_iterator position, const T& x);
iterator insert(const_iterator position, T&& x);
iterator insert(const_iterator position, size_type n, const T& x);
template <class InputIterator>
 iterator insert(const_iterator position, InputIterator first, InputIterator last);
iterator insert(const_iterator position, initializer_list<T> il);
iterator erase(const_iterator position);
iterator erase(const_iterator first, const_iterator last);
void swap(vector&)
 noexcept(allocator_traits<Allocator>::propagate_on_container_swap::value ||
 allocator_traits<Allocator>::is_always_equal::value);
void clear() noexcept;
};

template<class InputIterator,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
vector(InputIterator, InputIterator, Allocator = Allocator())
 -> vector<typename iterator_traits<InputIterator>::value_type, Allocator>;

```

```

template <class T, class Allocator>
 bool operator==(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
template <class T, class Allocator>
 bool operator< (const vector<T, Allocator>& x, const vector<T, Allocator>& y);
template <class T, class Allocator>
 bool operator!=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
template <class T, class Allocator>
 bool operator> (const vector<T, Allocator>& x, const vector<T, Allocator>& y);
template <class T, class Allocator>
 bool operator>=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);
template <class T, class Allocator>
 bool operator<=(const vector<T, Allocator>& x, const vector<T, Allocator>& y);

// 26.3.11.6, specialized algorithms
template <class T, class Allocator>
 void swap(vector<T, Allocator>& x, vector<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

- 3 An incomplete type *T* may be used when instantiating `vector` if the allocator satisfies the allocator completeness requirements (20.5.3.5.1). *T* shall be complete before any member of the resulting specialization of `vector` is referenced.

### 26.3.11.2 vector constructors, copy, and assignment

[vector.cons]

```
explicit vector(const Allocator&);
```

- 1 *Effects*: Constructs an empty `vector`, using the specified allocator.  
 2 *Complexity*: Constant.

```
explicit vector(size_type n, const Allocator& = Allocator());
```

- 3 *Effects*: Constructs a `vector` with *n* default-inserted elements using the specified allocator.  
 4 *Requires*: *T* shall be `DefaultInsertable` into *\*this*.  
 5 *Complexity*: Linear in *n*.

```
vector(size_type n, const T& value,
 const Allocator& = Allocator());
```

- 6 *Effects*: Constructs a `vector` with *n* copies of *value*, using the specified allocator.  
 7 *Requires*: *T* shall be `CopyInsertable` into *\*this*.  
 8 *Complexity*: Linear in *n*.

```
template <class InputIterator>
 vector(InputIterator first, InputIterator last,
 const Allocator& = Allocator());
```

- 9 *Effects*: Constructs a `vector` equal to the range [*first*, *last*), using the specified allocator.  
 10 *Complexity*: Makes only *N* calls to the copy constructor of *T* (where *N* is the distance between *first* and *last*) and no reallocations if iterators *first* and *last* are of forward, bidirectional, or random access categories. It makes order *N* calls to the copy constructor of *T* and order  $\log N$  reallocations if they are just input iterators.

### 26.3.11.3 vector capacity

[vector.capacity]

```
size_type capacity() const noexcept;
```

1     *Returns:* The total number of elements that the vector can hold without requiring reallocation.

```
void reserve(size_type n);
```

2     *Requires:* T shall be `MoveInsertable` into `*this`.

3     *Effects:* A directive that informs a `vector` of a planned change in size, so that it can manage the storage allocation accordingly. After `reserve()`, `capacity()` is greater or equal to the argument of `reserve` if reallocation happens; and equal to the previous value of `capacity()` otherwise. Reallocation happens at this point if and only if the current capacity is less than the argument of `reserve()`. If an exception is thrown other than by the move constructor of a non-`CopyInsertable` type, there are no effects.

4     *Complexity:* It does not change the size of the sequence and takes at most linear time in the size of the sequence.

5     *Throws:* `length_error` if `n > max_size()`.<sup>260</sup>

6     *Remarks:* Reallocation invalidates all the references, pointers, and iterators referring to the elements in the sequence. No reallocation shall take place during insertions that happen after a call to `reserve()` until the time when an insertion would make the size of the vector greater than the value of `capacity()`.

```
void shrink_to_fit();
```

7     *Requires:* T shall be `MoveInsertable` into `*this`.

8     *Effects:* `shrink_to_fit` is a non-binding request to reduce `capacity()` to `size()`. [ *Note:* The request is non-binding to allow latitude for implementation-specific optimizations. — *end note* ] It does not increase `capacity()`, but may reduce `capacity()` by causing reallocation. If an exception is thrown other than by the move constructor of a non-`CopyInsertable` T there are no effects.

9     *Complexity:* Linear in the size of the sequence.

10    *Remarks:* Reallocation invalidates all the references, pointers, and iterators referring to the elements in the sequence as well as the past-the-end iterator. If no reallocation happens, they remain valid.

```
void swap(vector& x)
 noexcept(allocator_traits<Allocator>::propagate_on_container_swap::value ||
 allocator_traits<Allocator>::is_always_equal::value);
```

11    *Effects:* Exchanges the contents and `capacity()` of `*this` with that of `x`.

12    *Complexity:* Constant time.

```
void resize(size_type sz);
```

13    *Effects:* If `sz < size()`, erases the last `size() - sz` elements from the sequence. Otherwise, appends `sz - size()` default-inserted elements to the sequence.

14    *Requires:* T shall be `MoveInsertable` and `DefaultInsertable` into `*this`.

15    *Remarks:* If an exception is thrown other than by the move constructor of a non-`CopyInsertable` T there are no effects.

```
void resize(size_type sz, const T& c);
```

16    *Effects:* If `sz < size()`, erases the last `size() - sz` elements from the sequence. Otherwise, appends `sz - size()` copies of `c` to the sequence.

17    *Requires:* T shall be `CopyInsertable` into `*this`.

18    *Remarks:* If an exception is thrown there are no effects.

---

260) `reserve()` uses `Allocator::allocate()` which may throw an appropriate exception.

**26.3.11.4 vector data****[vector.data]**

```
T* data() noexcept;
const T* data() const noexcept;
```

1 *Returns:* A pointer such that `[data(), data() + size())` is a valid range. For a non-empty vector, `data() == addressof(front())`.

2 *Complexity:* Constant time.

**26.3.11.5 vector modifiers****[vector.modifiers]**

```
iterator insert(const_iterator position, const T& x);
iterator insert(const_iterator position, T&& x);
iterator insert(const_iterator position, size_type n, const T& x);
template <class InputIterator>
 iterator insert(const_iterator position, InputIterator first, InputIterator last);
iterator insert(const_iterator position, initializer_list<T>);
```

```
template <class... Args> reference emplace_back(Args&&... args);
template <class... Args> iterator emplace(const_iterator position, Args&&... args);
void push_back(const T& x);
void push_back(T&& x);
```

1 *Remarks:* Causes reallocation if the new size is greater than the old capacity. Reallocation invalidates all the references, pointers, and iterators referring to the elements in the sequence. If no reallocation happens, all the iterators and references before the insertion point remain valid. If an exception is thrown other than by the copy constructor, move constructor, assignment operator, or move assignment operator of `T` or by any `InputIterator` operation there are no effects. If an exception is thrown while inserting a single element at the end and `T` is `CopyInsertable` or `is_nothrow_move_constructible_v<T>` is `true`, there are no effects. Otherwise, if an exception is thrown by the move constructor of a non-`CopyInsertable` `T`, the effects are unspecified.

2 *Complexity:* The complexity is linear in the number of elements inserted plus the distance to the end of the vector.

```
iterator erase(const_iterator position);
iterator erase(const_iterator first, const_iterator last);
void pop_back();
```

3 *Effects:* Invalidates iterators and references at or after the point of the erase.

4 *Complexity:* The destructor of `T` is called the number of times equal to the number of the elements erased, but the assignment operator of `T` is called the number of times equal to the number of elements in the vector after the erased elements.

5 *Throws:* Nothing unless an exception is thrown by the assignment operator or move assignment operator of `T`.

**26.3.11.6 vector specialized algorithms****[vector.special]**

```
template <class T, class Allocator>
 void swap(vector<T, Allocator>& x, vector<T, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
```

1 *Effects:* As if by `x.swap(y)`.

**26.3.12 Class vector<bool>****[vector.bool]**

1 To optimize space allocation, a specialization of vector for `bool` elements is provided:



```

namespace std {
 template <class Allocator>
 class vector<bool, Allocator> {
 public:
 // types:
 using value_type = bool;
 using allocator_type = Allocator;
 using pointer = implementation-defined;
 using const_pointer = implementation-defined;
 using const_reference = bool;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;

 // bit reference:
 class reference {
 friend class vector;
 reference() noexcept;
 public:
 ~reference();
 operator bool() const noexcept;
 reference& operator=(const bool x) noexcept;
 reference& operator=(const reference& x) noexcept;
 void flip() noexcept; // flips the bit
 };

 // construct/copy/destroy:
 vector() : vector(Allocator()) { }
 explicit vector(const Allocator&);
 explicit vector(size_type n, const Allocator& = Allocator());
 vector(size_type n, const bool& value,
 const Allocator& = Allocator());
 template <class InputIterator>
 vector(InputIterator first, InputIterator last,
 const Allocator& = Allocator());
 vector(const vector<bool, Allocator>& x);
 vector(vector<bool, Allocator>&& x);
 vector(const vector&, const Allocator&);
 vector(vector&&, const Allocator&);
 vector(initializer_list<bool>, const Allocator& = Allocator());
 ~vector();
 vector<bool, Allocator>& operator=(const vector<bool, Allocator>& x);
 vector<bool, Allocator>& operator=(vector<bool, Allocator>&& x);
 vector& operator=(initializer_list<bool>);
 template <class InputIterator>
 void assign(InputIterator first, InputIterator last);
 void assign(size_type n, const bool& t);
 void assign(initializer_list<bool>);
 allocator_type get_allocator() const noexcept;

 // iterators:
 iterator begin() noexcept;

```

```

const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;
size_type capacity() const noexcept;
void resize(size_type sz, bool c = false);
void reserve(size_type n);
void shrink_to_fit();

// element access:
reference operator[](size_type n);
const_reference operator[](size_type n) const;
const_reference at(size_type n) const;
reference at(size_type n);
reference front();
const_reference front() const;
reference back();
const_reference back() const;

// modifiers:
template <class... Args> reference emplace_back(Args&&... args);
void push_back(const bool& x);
void pop_back();
template <class... Args> iterator emplace(const_iterator position, Args&&... args);
iterator insert(const_iterator position, const bool& x);
iterator insert(const_iterator position, size_type n, const bool& x);
template <class InputIterator>
 iterator insert(const_iterator position,
 InputIterator first, InputIterator last);
iterator insert(const_iterator position, initializer_list<bool> il);

iterator erase(const_iterator position);
iterator erase(const_iterator first, const_iterator last);
void swap(vector<bool, Allocator>&);
static void swap(reference x, reference y) noexcept;
void flip() noexcept; // flips all bits
void clear() noexcept;
};
}

```

- <sup>2</sup> Unless described below, all operations have the same requirements and semantics as the primary **vector** template, except that operations dealing with the **bool** value type map to bit values in the container storage

and `allocator_traits::construct` (23.10.8.2) is not used to construct these values.

- 3 There is no requirement that the data be stored as a contiguous allocation of `bool` values. A space-optimized representation of bits is recommended instead.

- 4 `reference` is a class that simulates the behavior of references of a single bit in `vector<bool>`. The conversion function returns `true` when the bit is set, and `false` otherwise. The assignment operator sets the bit when the argument is (convertible to) `true` and clears it otherwise. `flip` reverses the state of the bit.

```
void flip() noexcept;
```

- 5 *Effects:* Replaces each element in the container with its complement.

```
static void swap(reference x, reference y) noexcept;
```

- 6 *Effects:* Exchanges the contents of `x` and `y` as if by:

```
bool b = x;
x = y;
y = b;
```

```
template <class Allocator> struct hash<vector<bool, Allocator>>;
```

- 7 The specialization is enabled (23.14.15).

## 26.4 Associative containers

[associative]

### 26.4.1 In general

[associative.general]

- 1 The header `<map>` defines the class templates `map` and `multimap`; the header `<set>` defines the class templates `set` and `multiset`.
- 2 The following exposition-only alias templates may appear in deduction guides for associative containers:

```
template<class InputIterator>
using iter_key_t = remove_const_t<
 typename iterator_traits<InputIterator>::value_type::first_type>; // exposition only
template<class InputIterator>
using iter_val_t
 = typename iterator_traits<InputIterator>::value_type::second_type; // exposition only
template<class InputIterator>
using iter_to_alloc_t
 = pair<add_const_t<typename iterator_traits<InputIterator>::value_type::first_type>,
 typename iterator_traits<InputIterator>::value_type::second_type>; // exposition only
```

### 26.4.2 Header `<map>` synopsis

[associative.map.syn]

```
#include <initializer_list>
```

```
namespace std {
 // 26.4.4, class template map
 template <class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class map;
 template <class Key, class T, class Compare, class Allocator>
 bool operator==(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
 template <class Key, class T, class Compare, class Allocator>
 bool operator< (const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
 template <class Key, class T, class Compare, class Allocator>
 bool operator!=(const map<Key, T, Compare, Allocator>& x,
```

```

 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator> (const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator>=(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator<=(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 void swap(map<Key, T, Compare, Allocator>& x,
 map<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

// 26.4.5, class template multimap
template <class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class multimap;
template <class Key, class T, class Compare, class Allocator>
 bool operator==(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator< (const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator!=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator> (const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator>=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator<=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 void swap(multimap<Key, T, Compare, Allocator>& x,
 multimap<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

namespace pmr {
 template <class Key, class T, class Compare = less<Key>>
 using map = std::map<Key, T, Compare,
 polymorphic_allocator<pair<const Key, T>>>;

 template <class Key, class T, class Compare = less<Key>>
 using multimap = std::multimap<Key, T, Compare,
 polymorphic_allocator<pair<const Key, T>>>;
 }
}

```

### 26.4.3 Header <set> synopsis

[associative.set.syn]

```
#include <initializer_list>
```

```

namespace std {
 // 26.4.6, class template set
 template <class Key, class Compare = less<Key>,
 class Allocator = allocator<Key>>
 class set;
 template <class Key, class Compare, class Allocator>
 bool operator==(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator< (const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator!=(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator> (const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator>=(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator<=(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 void swap(set<Key, Compare, Allocator>& x,
 set<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

 // 26.4.7, class template multiset
 template <class Key, class Compare = less<Key>,
 class Allocator = allocator<Key>>
 class multiset;
 template <class Key, class Compare, class Allocator>
 bool operator==(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator< (const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator!=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator> (const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator>=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 bool operator<=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
 template <class Key, class Compare, class Allocator>
 void swap(multiset<Key, Compare, Allocator>& x,
 multiset<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

```

```

namespace pmr {
 template <class Key, class Compare = less<Key>>
 using set = std::set<Key, Compare,
 polymorphic_allocator<Key>>;

 template <class Key, class Compare = less<Key>>
 using multiset = std::multiset<Key, Compare,
 polymorphic_allocator<Key>>;
}
}

```

## 26.4.4 Class template map [map]

### 26.4.4.1 Class template map overview [map.overview]

- <sup>1</sup> A `map` is an associative container that supports unique keys (contains at most one of each key value) and provides for fast retrieval of values of another type `T` based on the keys. The `map` class supports bidirectional iterators.
- <sup>2</sup> A `map` satisfies all of the requirements of a container, of a reversible container (26.2), of an associative container (26.2.6), and of an allocator-aware container (Table 86). A `map` also provides most operations described in 26.2.6 for unique keys. This means that a `map` supports the `a_uniq` operations in 26.2.6 but not the `a_eq` operations. For a `map<Key,T>` the `key_type` is `Key` and the `value_type` is `pair<const Key,T>`. Descriptions are provided here only for operations on `map` that are not described in one of those tables or for operations where there is additional semantic information.

```

namespace std {
 template <class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class map {
 public:
 // types:
 using key_type = Key;
 using mapped_type = T;
 using value_type = pair<const Key, T>;
 using key_compare = Compare;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;
 using node_type = unspecified;
 using insert_return_type = INSERT_RETURN_TYPE<iterator, node_type>;

 class value_compare {
 friend class map;
 protected:
 Compare comp;
 value_compare(Compare c) : comp(c) {}
 public:

```

```

 bool operator()(const value_type& x, const value_type& y) const {
 return comp(x.first, y.first);
 }
};

// 26.4.4.2, construct/copy/destroy
map() : map(Compare()) { }
explicit map(const Compare& comp, const Allocator& = Allocator());
template <class InputIterator>
 map(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());
map(const map& x);
map(map&& x);
explicit map(const Allocator&);
map(const map&, const Allocator&);
map(map&&, const Allocator&);
map(initializer_list<value_type>,
 const Compare& = Compare(),
 const Allocator& = Allocator());
template <class InputIterator>
 map(InputIterator first, InputIterator last, const Allocator& a)
 : map(first, last, Compare(), a) { }
map(initializer_list<value_type> il, const Allocator& a)
 : map(il, Compare(), a) { }
~map();
map& operator=(const map& x);
map& operator=(map&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Compare>);
map& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;

reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// 26.4.4.3, element access
T& operator[](const key_type& x);

```

```

T& operator[](key_type&& x);
T& at(const key_type& x);
const T& at(const key_type& x) const;

// 26.4.4.4, modifiers
template <class... Args> pair<iterator, bool> emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
pair<iterator, bool> insert(const value_type& x);
pair<iterator, bool> insert(value_type&& x);
template <class P> pair<iterator, bool> insert(P&& x);
iterator insert(const_iterator position, const value_type& x);
iterator insert(const_iterator position, value_type&& x);
template <class P>
 iterator insert(const_iterator position, P&&);
template <class InputIterator>
 void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
insert_return_type insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

template <class... Args>
 pair<iterator, bool> try_emplace(const key_type& k, Args&&... args);
template <class... Args>
 pair<iterator, bool> try_emplace(key_type&& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, const key_type& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, key_type&& k, Args&&... args);
template <class M>
 pair<iterator, bool> insert_or_assign(const key_type& k, M&& obj);
template <class M>
 pair<iterator, bool> insert_or_assign(key_type&& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, const key_type& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, key_type&& k, M&& obj);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& x);
iterator erase(const_iterator first, const_iterator last);
void swap(map&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Compare>);
void clear() noexcept;

template<class C2>
 void merge(map<Key, T, C2, Allocator>& source);
template<class C2>
 void merge(map<Key, T, C2, Allocator>&& source);
template<class C2>
 void merge(multimap<Key, T, C2, Allocator>& source);

```



```

template<class C2>
 void merge(multimap<Key, T, C2, Allocator>&& source);

// observers:
key_compare key_comp() const;
value_compare value_comp() const;

// map operations:
iterator find(const key_type& x);
const_iterator find(const key_type& x) const;
template <class K> iterator find(const K& x);
template <class K> const_iterator find(const K& x) const;

size_type count(const key_type& x) const;
template <class K> size_type count(const K& x) const;

iterator lower_bound(const key_type& x);
const_iterator lower_bound(const key_type& x) const;
template <class K> iterator lower_bound(const K& x);
template <class K> const_iterator lower_bound(const K& x) const;

iterator upper_bound(const key_type& x);
const_iterator upper_bound(const key_type& x) const;
template <class K> iterator upper_bound(const K& x);
template <class K> const_iterator upper_bound(const K& x) const;

pair<iterator, iterator> equal_range(const key_type& x);
pair<const_iterator, const_iterator> equal_range(const key_type& x) const;
template <class K>
 pair<iterator, iterator> equal_range(const K& x);
template <class K>
 pair<const_iterator, const_iterator> equal_range(const K& x) const;
};

template<class InputIterator, class Compare = less<iter_key_t<InputIterator>>,
 class Allocator = allocator<iter_to_alloc_t<InputIterator>>>
 map(InputIterator, InputIterator, Compare = Compare(), Allocator = Allocator())
 -> map<iter_key_t<InputIterator>, iter_val_t<InputIterator>, Compare, Allocator>;

template<class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 map(initializer_list<pair<const Key, T>>, Compare = Compare(), Allocator = Allocator())
 -> map<Key, T, Compare, Allocator>;

template <class InputIterator, class Allocator>
 map(InputIterator, InputIterator, Allocator)
 -> map<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 less<iter_key_t<InputIterator>>, Allocator>;

template<class Key, class T, class Allocator>
 map(initializer_list<pair<const Key, T>>, Allocator) -> map<Key, T, less<Key>, Allocator>;

template <class Key, class T, class Compare, class Allocator>
 bool operator==(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);

```

```

template <class Key, class T, class Compare, class Allocator>
 bool operator< (const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator!=(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator> (const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator>=(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator<=(const map<Key, T, Compare, Allocator>& x,
 const map<Key, T, Compare, Allocator>& y);

// 26.4.4.5, specialized algorithms
template <class Key, class T, class Compare, class Allocator>
 void swap(map<Key, T, Compare, Allocator>& x,
 map<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

#### 26.4.4.2 map constructors, copy, and assignment

[map.cons]

explicit map(const Compare& comp, const Allocator& = Allocator());

1 *Effects:* Constructs an empty map using the specified comparison object and allocator.

2 *Complexity:* Constant.

```

template <class InputIterator>
 map(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());

```

3 *Effects:* Constructs an empty map using the specified comparison object and allocator, and inserts elements from the range [first, last).

4 *Complexity:* Linear in  $N$  if the range [first, last) is already sorted using comp and otherwise  $N \log N$ , where  $N$  is last - first.

#### 26.4.4.3 map element access

[map.access]

T& operator[] (const key\_type& x);

1 *Effects:* Equivalent to: return try\_emplace(x).first->second;

T& operator[] (key\_type&& x);

2 *Effects:* Equivalent to: return try\_emplace(move(x)).first->second;

```

T& at(const key_type& x);
const T& at(const key_type& x) const;

```

3 *Returns:* A reference to the mapped\_type corresponding to x in \*this.

4 *Throws:* An exception object of type out\_of\_range if no such element is present.

5 *Complexity:* Logarithmic.

#### 26.4.4.4 map modifiers

[map.modifiers]

```

template <class P>
 pair<iterator, bool> insert(P&& x);
template <class P>
 iterator insert(const_iterator position, P&& x);

```

1     *Effects:* The first form is equivalent to return `emplace(std::forward<P>(x))`. The second form is equivalent to return `emplace_hint(position, std::forward<P>(x))`.

2     *Remarks:* These signatures shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

```

template <class... Args>
 pair<iterator, bool> try_emplace(const key_type& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, const key_type& k, Args&&... args);

```

3     *Requires:* `value_type` shall be `EmplaceConstructible` into map from `piecewise_construct`, `forward_as_tuple(k)`, `forward_as_tuple(std::forward<Args>(args)...)...`.

4     *Effects:* If the map already contains an element whose key is equivalent to `k`, there is no effect. Otherwise inserts an object of type `value_type` constructed with `piecewise_construct`, `forward_as_tuple(k)`, `forward_as_tuple(std::forward<Args>(args)...)...`.

5     *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

6     *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```

template <class... Args>
 pair<iterator, bool> try_emplace(key_type&& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, key_type&& k, Args&&... args);

```

7     *Requires:* `value_type` shall be `EmplaceConstructible` into map from `piecewise_construct`, `forward_as_tuple(std::move(k))`, `forward_as_tuple(std::forward<Args>(args)...)...`.

8     *Effects:* If the map already contains an element whose key is equivalent to `k`, there is no effect. Otherwise inserts an object of type `value_type` constructed with `piecewise_construct`, `forward_as_tuple(std::move(k))`, `forward_as_tuple(std::forward<Args>(args)...)...`.

9     *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

10    *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```

template <class M>
 pair<iterator, bool> insert_or_assign(const key_type& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, const key_type& k, M&& obj);

```

11    *Requires:* `is_assignable_v<mapped_type&, M&&>` shall be true. `value_type` shall be `EmplaceConstructible` into map from `k`, `forward<M>(obj)`.

12    *Effects:* If the map already contains an element `e` whose key is equivalent to `k`, assigns `std::forward<M>(obj)` to `e.second`. Otherwise inserts an object of type `value_type` constructed with `k`, `std::forward<M>(obj)`.

13    *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

14    *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```

template <class M>
 pair<iterator, bool> insert_or_assign(key_type&& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, key_type&& k, M&& obj);

```

- 15 *Requires:* `is_assignable_v<mapped_type&, M&&>` shall be true. `value_type` shall be `Emplace-Constructible` into map from `move(k)`, `forward<M>(obj)`.
- 16 *Effects:* If the map already contains an element `e` whose key is equivalent to `k`, assigns `std::forward<M>(obj)` to `e.second`. Otherwise inserts an object of type `value_type` constructed with `std::move(k)`, `std::forward<M>(obj)`.
- 17 *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.
- 18 *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

#### 26.4.4.5 map specialized algorithms

[map.special]

```

template <class Key, class T, class Compare, class Allocator>
 void swap(map<Key, T, Compare, Allocator>& x,
 map<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

```

- 1 *Effects:* As if by `x.swap(y)`.

### 26.4.5 Class template multimap

[multimap]

#### 26.4.5.1 Class template multimap overview

[multimap.overview]

- 1 A `multimap` is an associative container that supports equivalent keys (possibly containing multiple copies of the same key value) and provides for fast retrieval of values of another type `T` based on the keys. The `multimap` class supports bidirectional iterators.
- 2 A `multimap` satisfies all of the requirements of a container and of a reversible container (26.2), of an associative container (26.2.6), and of an allocator-aware container (Table 86). A `multimap` also provides most operations described in 26.2.6 for equal keys. This means that a `multimap` supports the `a_eq` operations in 26.2.6 but not the `a_uniq` operations. For a `multimap<Key,T>` the `key_type` is `Key` and the `value_type` is `pair<const Key,T>`. Descriptions are provided here only for operations on `multimap` that are not described in one of those tables or for operations where there is additional semantic information.

```

namespace std {
 template <class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class multimap {
 public:
 // types:
 using key_type = Key;
 using mapped_type = T;
 using value_type = pair<const Key, T>;
 using key_compare = Compare;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2

```

```

using reverse_iterator = std::reverse_iterator<iterator>;
using const_reverse_iterator = std::reverse_iterator<const_iterator>;
using node_type = unspecified;

class value_compare {
 friend class multimap;
protected:
 Compare comp;
 value_compare(Compare c) : comp(c) { }
public:
 bool operator()(const value_type& x, const value_type& y) const {
 return comp(x.first, y.first);
 }
};

// 26.4.5.2, construct/copy/destroy
multimap() : multimap(Compare()) { }
explicit multimap(const Compare& comp, const Allocator& = Allocator());
template <class InputIterator>
 multimap(InputIterator first, InputIterator last,
 const Compare& comp = Compare(),
 const Allocator& = Allocator());
multimap(const multimap& x);
multimap(multimap&& x);
explicit multimap(const Allocator&);
multimap(const multimap&, const Allocator&);
multimap(multimap&&, const Allocator&);
multimap(initializer_list<value_type>,
 const Compare& = Compare(),
 const Allocator& = Allocator());
template <class InputIterator>
 multimap(InputIterator first, InputIterator last, const Allocator& a)
 : multimap(first, last, Compare(), a) { }
multimap(initializer_list<value_type> il, const Allocator& a)
 : multimap(il, Compare(), a) { }
~multimap();
multimap& operator=(const multimap& x);
multimap& operator=(multimap&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Compare>);
multimap& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;

reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;

```

```

const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// 26.4.5.3, modifiers
template <class... Args> iterator emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
iterator insert(const value_type& x);
iterator insert(value_type&& x);
template <class P> iterator insert(P&& x);
iterator insert(const_iterator position, const value_type& x);
iterator insert(const_iterator position, value_type&& x);
template <class P> iterator insert(const_iterator position, P&& x);
template <class InputIterator>
 void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
iterator insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& x);
iterator erase(const_iterator first, const_iterator last);
void swap(multimap&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Compare>);
void clear() noexcept;

template<class C2>
 void merge(multimap<Key, T, C2, Allocator>& source);
template<class C2>
 void merge(multimap<Key, T, C2, Allocator>&& source);
template<class C2>
 void merge(map<Key, T, C2, Allocator>& source);
template<class C2>
 void merge(map<Key, T, C2, Allocator>&& source);

// observers:
key_compare key_comp() const;
value_compare value_comp() const;

// map operations:
iterator find(const key_type& x);
const_iterator find(const key_type& x) const;
template <class K> iterator find(const K& x);
template <class K> const_iterator find(const K& x) const;

```

```

size_type count(const key_type& x) const;
template <class K> size_type count(const K& x) const;

iterator lower_bound(const key_type& x);
const_iterator lower_bound(const key_type& x) const;
template <class K> iterator lower_bound(const K& x);
template <class K> const_iterator lower_bound(const K& x) const;

iterator upper_bound(const key_type& x);
const_iterator upper_bound(const key_type& x) const;
template <class K> iterator upper_bound(const K& x);
template <class K> const_iterator upper_bound(const K& x) const;

pair<iterator, iterator> equal_range(const key_type& x);
pair<const_iterator, const_iterator> equal_range(const key_type& x) const;
template <class K>
 pair<iterator, iterator> equal_range(const K& x);
template <class K>
 pair<const_iterator, const_iterator> equal_range(const K& x) const;
};

template<class InputIterator, class Compare = less<iter_key_t<InputIterator>>,
 class Allocator = allocator<iter_to_alloc_t<InputIterator>>>
 multimap(InputIterator, InputIterator, Compare = Compare(), Allocator = Allocator())
 -> multimap<iter_key_t<InputIterator>, iter_val_t<InputIterator>, Compare, Allocator>;

template<class Key, class T, class Compare = less<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 multimap(initializer_list<pair<const Key, T>>, Compare = Compare(), Allocator = Allocator())
 -> multimap<Key, T, Compare, Allocator>;

template<class InputIterator, class Allocator>
 multimap(InputIterator, InputIterator, Allocator)
 -> multimap<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 less<iter_key_t<InputIterator>>, Allocator>;

template<class Key, class T, class Allocator>
 multimap(initializer_list<pair<const Key, T>>, Allocator)
 -> multimap<Key, T, less<Key>, Allocator>;

template <class Key, class T, class Compare, class Allocator>
 bool operator==(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator< (const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator!=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator> (const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
template <class Key, class T, class Compare, class Allocator>
 bool operator>=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);

```

```
template <class Key, class T, class Compare, class Allocator>
 bool operator<=(const multimap<Key, T, Compare, Allocator>& x,
 const multimap<Key, T, Compare, Allocator>& y);
```

// 26.4.5.4, specialized algorithms

```
template <class Key, class T, class Compare, class Allocator>
 void swap(multimap<Key, T, Compare, Allocator>& x,
 multimap<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}
```

#### 26.4.5.2 multimap constructors

[multimap.cons]

```
explicit multimap(const Compare& comp, const Allocator& = Allocator());
```

1 *Effects:* Constructs an empty multimap using the specified comparison object and allocator.

2 *Complexity:* Constant.

```
template <class InputIterator>
 multimap(InputIterator first, InputIterator last,
 const Compare& comp = Compare(),
 const Allocator& = Allocator());
```

3 *Effects:* Constructs an empty multimap using the specified comparison object and allocator, and inserts elements from the range [first, last).

4 *Complexity:* Linear in  $N$  if the range [first, last) is already sorted using comp and otherwise  $N \log N$ , where  $N$  is last - first.

#### 26.4.5.3 multimap modifiers

[multimap.modifiers]

```
template <class P> iterator insert(P&& x);
template <class P> iterator insert(const_iterator position, P&& x);
```

1 *Effects:* The first form is equivalent to return `emplace(std::forward<P>(x))`. The second form is equivalent to return `emplace_hint(position, std::forward<P>(x))`.

2 *Remarks:* These signatures shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

#### 26.4.5.4 multimap specialized algorithms

[multimap.special]

```
template <class Key, class T, class Compare, class Allocator>
 void swap(multimap<Key, T, Compare, Allocator>& x,
 multimap<Key, T, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
```

1 *Effects:* As if by `x.swap(y)`.

### 26.4.6 Class template set

[set]

#### 26.4.6.1 Class template set overview

[set.overview]

1 A **set** is an associative container that supports unique keys (contains at most one of each key value) and provides for fast retrieval of the keys themselves. The **set** class supports bidirectional iterators.

2 A **set** satisfies all of the requirements of a container, of a reversible container (26.2), of an associative container (26.2.6), and of an allocator-aware container (Table 86). A **set** also provides most operations described in 26.2.6 for unique keys. This means that a **set** supports the `a_uniq` operations in 26.2.6 but not the `a_eq` operations. For a `set<Key>` both the `key_type` and `value_type` are `Key`. Descriptions are



provided here only for operations on `set` that are not described in one of these tables and for operations where there is additional semantic information.

```

namespace std {
 template <class Key, class Compare = less<Key>,
 class Allocator = allocator<Key>>
 class set {
 public:
 // types:
 using key_type = Key;
 using key_compare = Compare;
 using value_type = Key;
 using value_compare = Compare;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;
 using node_type = unspecified;
 using insert_return_type = INSERT_RETURN_TYPE<iterator, node_type>;

 // 26.4.6.2, construct/copy/destroy
 set() : set(Compare()) { }
 explicit set(const Compare& comp, const Allocator& = Allocator());
 template <class InputIterator>
 set(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());
 set(const set&& x);
 set(set&& x);
 explicit set(const Allocator&);
 set(const set&, const Allocator&);
 set(set&&, const Allocator&);
 set(initializer_list<value_type>, const Compare& = Compare(),
 const Allocator& = Allocator());
 template <class InputIterator>
 set(InputIterator first, InputIterator last, const Allocator& a)
 : set(first, last, Compare(), a) { }
 set(initializer_list<value_type> il, const Allocator& a)
 : set(il, Compare(), a) { }
 ~set();
 set& operator=(const set& x);
 set& operator=(set&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Compare>);
 set& operator=(initializer_list<value_type>);
 allocator_type get_allocator() const noexcept;

 // iterators:
 iterator begin() noexcept;
 const_iterator begin() const noexcept;

```

```

iterator end() noexcept;
const_iterator end() const noexcept;

reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// modifiers:
template <class... Args> pair<iterator, bool> emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
pair<iterator, bool> insert(const value_type& x);
pair<iterator, bool> insert(value_type&& x);
iterator insert(const_iterator position, const value_type& x);
iterator insert(const_iterator position, value_type&& x);
template <class InputIterator>
 void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
insert_return_type insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& x);
iterator erase(const_iterator first, const_iterator last);
void swap(set&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Compare>);
void clear() noexcept;

template<class C2>
 void merge(set<Key, C2, Allocator>& source);
template<class C2>
 void merge(set<Key, C2, Allocator>&& source);
template<class C2>
 void merge(multiset<Key, C2, Allocator>& source);
template<class C2>
 void merge(multiset<Key, C2, Allocator>&& source);

// observers:
key_compare key_comp() const;
value_compare value_comp() const;

```

```

// set operations:
iterator find(const key_type& x);
const_iterator find(const key_type& x) const;
template <class K> iterator find(const K& x);
template <class K> const_iterator find(const K& x) const;

size_type count(const key_type& x) const;
template <class K> size_type count(const K& x) const;

iterator lower_bound(const key_type& x);
const_iterator lower_bound(const key_type& x) const;
template <class K> iterator lower_bound(const K& x);
template <class K> const_iterator lower_bound(const K& x) const;

iterator upper_bound(const key_type& x);
const_iterator upper_bound(const key_type& x) const;
template <class K> iterator upper_bound(const K& x);
template <class K> const_iterator upper_bound(const K& x) const;

pair<iterator, iterator> equal_range(const key_type& x);
pair<const_iterator, const_iterator> equal_range(const key_type& x) const;
template <class K>
 pair<iterator, iterator> equal_range(const K& x);
template <class K>
 pair<const_iterator, const_iterator> equal_range(const K& x) const;
};

template<class InputIterator,
 class Compare = less<typename iterator_traits<InputIterator>::value_type>,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
set(InputIterator, InputIterator,
 Compare = Compare(), Allocator = Allocator())
-> set<typename iterator_traits<InputIterator>::value_type, Compare, Allocator>;

template<class Key, class Compare = less<Key>, class Allocator = allocator<Key>>
set(initializer_list<Key>, Compare = Compare(), Allocator = Allocator())
-> set<Key, Compare, Allocator>;

template<class InputIterator, class Allocator>
set(InputIterator, InputIterator, Allocator)
-> set<typename iterator_traits<InputIterator>::value_type,
 less<typename iterator_traits<InputIterator>::value_type>, Allocator>;

template<class Key, class Allocator>
set(initializer_list<Key>, Allocator) -> set<Key, less<Key>, Allocator>;

template <class Key, class Compare, class Allocator>
bool operator==(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
bool operator< (const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
bool operator!=(const set<Key, Compare, Allocator>& x,

```

```

 const set<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
 bool operator> (const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
 bool operator>=(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
 bool operator<=(const set<Key, Compare, Allocator>& x,
 const set<Key, Compare, Allocator>& y);

// 26.4.6.3, specialized algorithms
template <class Key, class Compare, class Allocator>
 void swap(set<Key, Compare, Allocator>& x,
 set<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

### 26.4.6.2 set constructors, copy, and assignment

[set.cons]

```
explicit set(const Compare& comp, const Allocator& = Allocator());
```

<sup>1</sup> *Effects:* Constructs an empty `set` using the specified comparison objects and allocator.

<sup>2</sup> *Complexity:* Constant.

```

template <class InputIterator>
 set(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());

```

<sup>3</sup> *Effects:* Constructs an empty `set` using the specified comparison object and allocator, and inserts elements from the range `[first, last)`.

<sup>4</sup> *Complexity:* Linear in  $N$  if the range `[first, last)` is already sorted using `comp` and otherwise  $N \log N$ , where  $N$  is `last - first`.

### 26.4.6.3 set specialized algorithms

[set.special]

```

template <class Key, class Compare, class Allocator>
 void swap(set<Key, Compare, Allocator>& x,
 set<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

```

<sup>1</sup> *Effects:* As if by `x.swap(y)`.

## 26.4.7 Class template multiset

[multiset]

### 26.4.7.1 Class template multiset overview

[multiset.overview]

<sup>1</sup> A `multiset` is an associative container that supports equivalent keys (possibly contains multiple copies of the same key value) and provides for fast retrieval of the keys themselves. The `multiset` class supports bidirectional iterators.

<sup>2</sup> A `multiset` satisfies all of the requirements of a container, of a reversible container (26.2), of an associative container (26.2.6), and of an allocator-aware container (Table 86). `multiset` also provides most operations described in 26.2.6 for duplicate keys. This means that a `multiset` supports the `a_eq` operations in 26.2.6 but not the `a_uniq` operations. For a `multiset<Key>` both the `key_type` and `value_type` are `Key`. Descriptions are provided here only for operations on `multiset` that are not described in one of these tables and for operations where there is additional semantic information.

```

namespace std {
 template <class Key, class Compare = less<Key>,
 class Allocator = allocator<Key>>
 class multiset {
 public:
 // types:
 using key_type = Key;
 using key_compare = Compare;
 using value_type = Key;
 using value_compare = Compare;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2
 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using reverse_iterator = std::reverse_iterator<iterator>;
 using const_reverse_iterator = std::reverse_iterator<const_iterator>;
 using node_type = unspecified;

 // 26.4.7.2, construct/copy/destroy
 multiset() : multiset(Compare()) { }
 explicit multiset(const Compare& comp, const Allocator& = Allocator());
 template <class InputIterator>
 multiset(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());
 multiset(const multiset& x);
 multiset(multiset&& x);
 explicit multiset(const Allocator&);
 multiset(const multiset&, const Allocator&);
 multiset(multiset&&, const Allocator&);
 multiset(initializer_list<value_type>, const Compare& = Compare(),
 const Allocator& = Allocator());
 template <class InputIterator>
 multiset(InputIterator first, InputIterator last, const Allocator& a)
 : multiset(first, last, Compare(), a) { }
 multiset(initializer_list<value_type> il, const Allocator& a)
 : multiset(il, Compare(), a) { }
 ~multiset();
 multiset& operator=(const multiset& x);
 multiset& operator=(multiset&& x)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Compare>);
 multiset& operator=(initializer_list<value_type>);
 allocator_type get_allocator() const noexcept;

 // iterators:
 iterator begin() noexcept;
 const_iterator begin() const noexcept;
 iterator end() noexcept;
 const_iterator end() const noexcept;

```

```

reverse_iterator rbegin() noexcept;
const_reverse_iterator rbegin() const noexcept;
reverse_iterator rend() noexcept;
const_reverse_iterator rend() const noexcept;

const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;
const_reverse_iterator crbegin() const noexcept;
const_reverse_iterator crend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// modifiers:
template <class... Args> iterator emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
iterator insert(const value_type& x);
iterator insert(value_type&& x);
iterator insert(const_iterator position, const value_type& x);
iterator insert(const_iterator position, value_type&& x);
template <class InputIterator>
 void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
iterator insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& x);
iterator erase(const_iterator first, const_iterator last);
void swap(multiset&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Compare>);
void clear() noexcept;

template<class C2>
 void merge(multiset<Key, C2, Allocator>& source);
template<class C2>
 void merge(multiset<Key, C2, Allocator>&& source);
template<class C2>
 void merge(set<Key, C2, Allocator>& source);
template<class C2>
 void merge(set<Key, C2, Allocator>&& source);

// observers:
key_compare key_comp() const;
value_compare value_comp() const;

// set operations:
iterator find(const key_type& x);

```

```

const_iterator find(const key_type& x) const;
template <class K> iterator find(const K& x);
template <class K> const_iterator find(const K& x) const;

size_type count(const key_type& x) const;
template <class K> size_type count(const K& x) const;

iterator lower_bound(const key_type& x);
const_iterator lower_bound(const key_type& x) const;
template <class K> iterator lower_bound(const K& x);
template <class K> const_iterator lower_bound(const K& x) const;

iterator upper_bound(const key_type& x);
const_iterator upper_bound(const key_type& x) const;
template <class K> iterator upper_bound(const K& x);
template <class K> const_iterator upper_bound(const K& x) const;

pair<iterator, iterator> equal_range(const key_type& x);
pair<const_iterator, const_iterator> equal_range(const key_type& x) const;
template <class K>
pair<iterator, iterator> equal_range(const K& x);
template <class K>
pair<const_iterator, const_iterator> equal_range(const K& x) const;
};

template<class InputIterator,
 class Compare = less<typename iterator_traits<InputIterator>::value_type>,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
multiset(InputIterator, InputIterator,
 Compare = Compare(), Allocator = Allocator())
-> multiset<typename iterator_traits<InputIterator>::value_type, Compare, Allocator>;

template<class Key, class Compare = less<Key>, class Allocator = allocator<Key>>
multiset(initializer_list<Key>, Compare = Compare(), Allocator = Allocator())
-> multiset<Key, Compare, Allocator>;

template<class InputIterator, class Allocator>
multiset(InputIterator, InputIterator, Allocator)
-> multiset<typename iterator_traits<InputIterator>::value_type,
 less<typename iterator_traits<InputIterator>::value_type>, Allocator>;

template<class Key, class Allocator>
multiset(initializer_list<Key>, Allocator) -> multiset<Key, less<Key>, Allocator>;

template <class Key, class Compare, class Allocator>
bool operator==(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
bool operator< (const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
bool operator!=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
bool operator> (const multiset<Key, Compare, Allocator>& x,

```

```

 const multiset<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
 bool operator>=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);
template <class Key, class Compare, class Allocator>
 bool operator<=(const multiset<Key, Compare, Allocator>& x,
 const multiset<Key, Compare, Allocator>& y);

// 26.4.7.3, specialized algorithms
template <class Key, class Compare, class Allocator>
 void swap(multiset<Key, Compare, Allocator>& x,
 multiset<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));
}

```

### 26.4.7.2 multiset constructors

[multiset.cons]

```
explicit multiset(const Compare& comp, const Allocator& = Allocator());
```

<sup>1</sup> *Effects:* Constructs an empty multiset using the specified comparison object and allocator.

<sup>2</sup> *Complexity:* Constant.

```

template <class InputIterator>
 multiset(InputIterator first, InputIterator last,
 const Compare& comp = Compare(), const Allocator& = Allocator());

```

<sup>3</sup> *Effects:* Constructs an empty multiset using the specified comparison object and allocator, and inserts elements from the range [first, last).

<sup>4</sup> *Complexity:* Linear in  $N$  if the range [first, last) is already sorted using comp and otherwise  $N \log N$ , where  $N$  is last - first.

### 26.4.7.3 multiset specialized algorithms

[multiset.special]

```

template <class Key, class Compare, class Allocator>
 void swap(multiset<Key, Compare, Allocator>& x,
 multiset<Key, Compare, Allocator>& y)
 noexcept(noexcept(x.swap(y)));

```

<sup>1</sup> *Effects:* As if by x.swap(y).

## 26.5 Unordered associative containers

[unord]

### 26.5.1 In general

[unord.general]

<sup>1</sup> The header <unordered\_map> defines the class templates unordered\_map and unordered\_multimap; the header <unordered\_set> defines the class templates unordered\_set and unordered\_multiset.

<sup>2</sup> The exposition-only alias templates iter\_key\_t, iter\_val\_t, and iter\_to\_alloc\_t defined in 26.4.1 may appear in deduction guides for unordered containers.

### 26.5.2 Header <unordered\_map> synopsis

[unord.map.syn]

```

#include <initializer_list>

namespace std {
 // 26.5.4, class template unordered_map
 template <class Key,
 class T,
 class Hash = hash<Key>,

```



```

 class Pred = equal_to<Key>,
 class Alloc = allocator<pair<const Key, T>>>
class unordered_map;

// 26.5.5, class template unordered_multimap
template <class Key,
 class T,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Alloc = allocator<pair<const Key, T>>>
class unordered_multimap;

template <class Key, class T, class Hash, class Pred, class Alloc>
void swap(unordered_map<Key, T, Hash, Pred, Alloc>& x,
 unordered_map<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));

template <class Key, class T, class Hash, class Pred, class Alloc>
void swap(unordered_multimap<Key, T, Hash, Pred, Alloc>& x,
 unordered_multimap<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));

template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator==(const unordered_map<Key, T, Hash, Pred, Alloc>& a,
 const unordered_map<Key, T, Hash, Pred, Alloc>& b);
template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator!=(const unordered_map<Key, T, Hash, Pred, Alloc>& a,
 const unordered_map<Key, T, Hash, Pred, Alloc>& b);
template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator==(const unordered_multimap<Key, T, Hash, Pred, Alloc>& a,
 const unordered_multimap<Key, T, Hash, Pred, Alloc>& b);
template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator!=(const unordered_multimap<Key, T, Hash, Pred, Alloc>& a,
 const unordered_multimap<Key, T, Hash, Pred, Alloc>& b);

namespace pmr {
 template <class Key,
 class T,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>>
 using unordered_map =
 std::unordered_map<Key, T, Hash, Pred,
 polymorphic_allocator<pair<const Key, T>>>;
 template <class Key,
 class T,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>>
 using unordered_multimap =
 std::unordered_multimap<Key, T, Hash, Pred,
 polymorphic_allocator<pair<const Key, T>>>;
 }
}

```

### 26.5.3 Header <unordered\_set> synopsis

[unord.set.syn]

```

#include <initializer_list>

namespace std {
 // 26.5.6, class template unordered_set
 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Alloc = allocator<Key>>
 class unordered_set;

 // 26.5.7, class template unordered_multiset
 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Alloc = allocator<Key>>
 class unordered_multiset;

 template <class Key, class Hash, class Pred, class Alloc>
 void swap(unordered_set<Key, Hash, Pred, Alloc>& x,
 unordered_set<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));

 template <class Key, class Hash, class Pred, class Alloc>
 void swap(unordered_multiset<Key, Hash, Pred, Alloc>& x,
 unordered_multiset<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));

 template <class Key, class Hash, class Pred, class Alloc>
 bool operator==(const unordered_set<Key, Hash, Pred, Alloc>& a,
 const unordered_set<Key, Hash, Pred, Alloc>& b);
 template <class Key, class Hash, class Pred, class Alloc>
 bool operator!=(const unordered_set<Key, Hash, Pred, Alloc>& a,
 const unordered_set<Key, Hash, Pred, Alloc>& b);
 template <class Key, class Hash, class Pred, class Alloc>
 bool operator==(const unordered_multiset<Key, Hash, Pred, Alloc>& a,
 const unordered_multiset<Key, Hash, Pred, Alloc>& b);
 template <class Key, class Hash, class Pred, class Alloc>
 bool operator!=(const unordered_multiset<Key, Hash, Pred, Alloc>& a,
 const unordered_multiset<Key, Hash, Pred, Alloc>& b);

 namespace pmr {
 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>>
 using unordered_set = std::unordered_set<Key, Hash, Pred,
 polymorphic_allocator<Key>>;

 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>>
 using unordered_multiset = std::unordered_multiset<Key, Hash, Pred,
 polymorphic_allocator<Key>>;
 }
}

```

## 26.5.4 Class template `unordered_map` [unord.map]

### 26.5.4.1 Class template `unordered_map` overview [unord.map.overview]

- <sup>1</sup> An `unordered_map` is an unordered associative container that supports unique keys (an `unordered_map` contains at most one of each key value) and that associates values of another type `mapped_type` with the keys. The `unordered_map` class supports forward iterators.
- <sup>2</sup> An `unordered_map` satisfies all of the requirements of a container, of an unordered associative container, and of an allocator-aware container (Table 86). It provides the operations described in the preceding requirements table for unique keys; that is, an `unordered_map` supports the `a_uniq` operations in that table, not the `a_eq` operations. For an `unordered_map<Key, T>` the `key_type` is `Key`, the mapped type is `T`, and the value type is `pair<const Key, T>`.
- <sup>3</sup> This section only describes operations on `unordered_map` that are not described in one of the requirement tables, or for which there is additional semantic information.

```
namespace std {
 template <class Key,
 class T,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class unordered_map {
 public:
 // types:
 using key_type = Key;
 using mapped_type = T;
 using value_type = pair<const Key, T>;
 using hasher = Hash;
 using key_equal = Pred;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2

 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using local_iterator = implementation-defined; // see 26.2
 using const_local_iterator = implementation-defined; // see 26.2
 using node_type = unspecified;
 using insert_return_type = INSERT_RETURN_TYPE<iterator, node_type>;

 // 26.5.4.2, construct/copy/destroy
 unordered_map();
 explicit unordered_map(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

 template <class InputIterator>
 unordered_map(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
```

```

 const allocator_type& a = allocator_type();
unordered_map(const unordered_map&);
unordered_map(unordered_map&&);
explicit unordered_map(const Allocator&);
unordered_map(const unordered_map&, const Allocator&);
unordered_map(unordered_map&&, const Allocator&);
unordered_map(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_map(size_type n, const allocator_type& a)
 : unordered_map(n, hasher(), key_equal(), a) { }
unordered_map(size_type n, const hasher& hf, const allocator_type& a)
 : unordered_map(n, hf, key_equal(), a) { }
template <class InputIterator>
 unordered_map(InputIterator f, InputIterator l, size_type n, const allocator_type& a)
 : unordered_map(f, l, n, hasher(), key_equal(), a) { }
template <class InputIterator>
 unordered_map(InputIterator f, InputIterator l, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_map(f, l, n, hf, key_equal(), a) { }
unordered_map(initializer_list<value_type> il, size_type n, const allocator_type& a)
 : unordered_map(il, n, hasher(), key_equal(), a) { }
unordered_map(initializer_list<value_type> il, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_map(il, n, hf, key_equal(), a) { }
~unordered_map();
unordered_map& operator=(const unordered_map&);
unordered_map& operator=(unordered_map&&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Hash> &&
 is_nothrow_move_assignable_v<Pred>);
unordered_map& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// 26.5.4.4, modifiers
template <class... Args> pair<iterator, bool> emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
pair<iterator, bool> insert(const value_type& obj);
pair<iterator, bool> insert(value_type&& obj);
template <class P> pair<iterator, bool> insert(P&& obj);

```

```

iterator insert(const_iterator hint, const value_type& obj);
iterator insert(const_iterator hint, value_type&& obj);
template <class P> iterator insert(const_iterator hint, P&& obj);
template <class InputIterator> void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
insert_return_type insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

template <class... Args>
 pair<iterator, bool> try_emplace(const key_type& k, Args&&... args);
template <class... Args>
 pair<iterator, bool> try_emplace(key_type&& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, const key_type& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, key_type&& k, Args&&... args);
template <class M>
 pair<iterator, bool> insert_or_assign(const key_type& k, M&& obj);
template <class M>
 pair<iterator, bool> insert_or_assign(key_type&& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, const key_type& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, key_type&& k, M&& obj);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& k);
iterator erase(const_iterator first, const_iterator last);
void swap(unordered_map&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Hash> &&
 is_nothrow_swappable_v<Pred>);
void clear() noexcept;

template<class H2, class P2>
 void merge(unordered_map<Key, T, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_map<Key, T, H2, P2, Allocator>&& source);
template<class H2, class P2>
 void merge(unordered_multimap<Key, T, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_multimap<Key, T, H2, P2, Allocator>&& source);

// observers:
hasher hash_function() const;
key_equal key_eq() const;

// map operations:
iterator find(const key_type& k);
const_iterator find(const key_type& k) const;
size_type count(const key_type& k) const;

```

```

pair<iterator, iterator> equal_range(const key_type& k);
pair<const_iterator, const_iterator> equal_range(const key_type& k) const;

// 26.5.4.3, element access
mapped_type& operator[] (const key_type& k);
mapped_type& operator[] (key_type&& k);
mapped_type& at(const key_type& k);
const mapped_type& at(const key_type& k) const;

// bucket interface:
size_type bucket_count() const noexcept;
size_type max_bucket_count() const noexcept;
size_type bucket_size(size_type n) const;
size_type bucket(const key_type& k) const;
local_iterator begin(size_type n);
const_local_iterator begin(size_type n) const;
local_iterator end(size_type n);
const_local_iterator end(size_type n) const;
const_local_iterator cbegin(size_type n) const;
const_local_iterator cend(size_type n) const;

// hash policy:
float load_factor() const noexcept;
float max_load_factor() const noexcept;
void max_load_factor(float z);
void rehash(size_type n);
void reserve(size_type n);
};

template<class InputIterator,
 class Hash = hash<iter_key_t<InputIterator>>,
 class Pred = equal_to<iter_key_t<InputIterator>>,
 class Allocator = allocator<iter_to_alloc_t<InputIterator>>>
unordered_map(InputIterator, InputIterator, typename see_below::size_type = see_below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
-> unordered_map<iter_key_t<InputIterator>, iter_value_t<InputIterator>, Hash, Pred,
 Allocator>;

template<class Key, class T, class Hash = hash<Key>,
 class Pred = equal_to<Key>, class Allocator = allocator<pair<const Key, T>>>
unordered_map(initializer_list<pair<const Key, T>>,
 typename see_below::size_type = see_below, Hash = Hash(),
 Pred = Pred(), Allocator = Allocator())
-> unordered_map<Key, T, Hash, Pred, Allocator>;

template<class InputIterator, class Allocator>
unordered_map(InputIterator, InputIterator, typename see_below::size_type, Allocator)
-> unordered_map<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 hash<iter_key_t<InputIterator>>, equal_to<iter_key_t<InputIterator>>,
 Allocator>;

template<class InputIterator, class Allocator>
unordered_map(InputIterator, InputIterator, Allocator)
-> unordered_map<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 hash<iter_key_t<InputIterator>>, equal_to<iter_key_t<InputIterator>>,
 Allocator>;

```

```

 Allocator>;

template<class InputIterator, class Hash, class Allocator>
unordered_map(InputIterator, InputIterator, typename see below::size_type, Hash, Allocator)
-> unordered_map<iter_key_t<InputIterator>, iter_val_t<InputIterator>, Hash,
 equal_to<iter_key_t<InputIterator>>, Allocator>;

template<class Key, class T, typename Allocator>
unordered_map(initializer_list<pair<const Key, T>>, typename see below::size_type,
 Allocator)
-> unordered_map<Key, T, hash<Key>, equal_to<Key>, Allocator>;

template<class Key, class T, typename Allocator>
unordered_map(initializer_list<pair<const Key, T>>, Allocator)
-> unordered_map<Key, T, hash<Key>, equal_to<Key>, Allocator>;

template<class Key, class T, class Hash, class Allocator>
unordered_map(initializer_list<pair<const Key, T>>, typename see below::size_type, Hash,
 Allocator)
-> unordered_map<Key, T, Hash, equal_to<Key>, Allocator>;

template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator==(const unordered_map<Key, T, Hash, Pred, Alloc>& a,
 const unordered_map<Key, T, Hash, Pred, Alloc>& b);
template <class Key, class T, class Hash, class Pred, class Alloc>
bool operator!=(const unordered_map<Key, T, Hash, Pred, Alloc>& a,
 const unordered_map<Key, T, Hash, Pred, Alloc>& b);

// 26.5.4.5, swap
template <class Key, class T, class Hash, class Pred, class Alloc>
void swap(unordered_map<Key, T, Hash, Pred, Alloc>& x,
 unordered_map<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
}

```

- <sup>4</sup> A `size_type` parameter type in an `unordered_map` deduction guide refers to the `size_type` member type of the type deduced by the deduction guide.

#### 26.5.4.2 unordered\_map constructors

[unord.map.cnstr]

```

unordered_map() : unordered_map(size_type(see below)) { }
explicit unordered_map(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

- <sup>1</sup> *Effects:* Constructs an empty `unordered_map` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. For the default constructor, the number of buckets is implementation-defined. `max_load_factor()` returns 1.0.
- <sup>2</sup> *Complexity:* Constant.

```

template <class InputIterator>
unordered_map(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),

```

```

 const allocator_type& a = allocator_type();
unordered_map(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

3 *Effects:* Constructs an empty `unordered_map` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. If `n` is not provided, the number of buckets is implementation-defined. Then inserts elements from the range `[f, 1)` for the first form, or from the range `[il.begin(), il.end())` for the second form. `max_load_factor()` returns 1.0.

4 *Complexity:* Average case linear, worst case quadratic.

#### 26.5.4.3 `unordered_map` element access

[unord.map.elem]

```
mapped_type& operator[](const key_type& k);
```

1 *Effects:* Equivalent to: `return try_emplace(k).first->second;`

```
mapped_type& operator[](key_type&& k);
```

2 *Effects:* Equivalent to: `return try_emplace(move(k)).first->second;`

```
mapped_type& at(const key_type& k);
const mapped_type& at(const key_type& k) const;
```

3 *Returns:* A reference to `x.second`, where `x` is the (unique) element whose key is equivalent to `k`.

4 *Throws:* An exception object of type `out_of_range` if no such element is present.

#### 26.5.4.4 `unordered_map` modifiers

[unord.map.modifiers]

```
template <class P>
pair<iterator, bool> insert(P&& obj);
```

1 *Effects:* Equivalent to: `return emplace(std::forward<P>(obj));`

2 *Remarks:* This signature shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

```
template <class P>
iterator insert(const_iterator hint, P&& obj);
```

3 *Effects:* Equivalent to: `return emplace_hint(hint, std::forward<P>(obj));`

4 *Remarks:* This signature shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

```
template <class... Args>
pair<iterator, bool> try_emplace(const key_type& k, Args&&... args);
template <class... Args>
iterator try_emplace(const_iterator hint, const key_type& k, Args&&... args);
```

5 *Requires:* `value_type` shall be `EmplaceConstructible` into `unordered_map` from `piecewise_construct`, `forward_as_tuple(k)`, `forward_as_tuple(std::forward<Args>(args)...) .`

6 *Effects:* If the map already contains an element whose key is equivalent to `k`, there is no effect. Otherwise inserts an object of type `value_type` constructed with `piecewise_construct`, `forward_as_tuple(k)`, `forward_as_tuple(std::forward<Args>(args)...) .`

7 *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.



8 *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```
template <class... Args>
 pair<iterator, bool> try_emplace(key_type&& k, Args&&... args);
template <class... Args>
 iterator try_emplace(const_iterator hint, key_type&& k, Args&&... args);
```

9 *Requires:* `value_type` shall be `EmplaceConstructible` into `unordered_map` from `piecewise_construct`, `forward_as_tuple(std::move(k))`, `forward_as_tuple(std::forward<Args>(args)...)...`.

10 *Effects:* If the map already contains an element whose key is equivalent to `k`, there is no effect. Otherwise inserts an object of type `value_type` constructed with `piecewise_construct`, `forward_as_tuple(std::move(k))`, `forward_as_tuple(std::forward<Args>(args)...)...`.

11 *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

12 *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```
template <class M>
 pair<iterator, bool> insert_or_assign(const key_type& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, const key_type& k, M&& obj);
```

13 *Requires:* `is_assignable_v<mapped_type&, M&&>` shall be `true`. `value_type` shall be `EmplaceConstructible` into `unordered_map` from `k`, `std::forward<M>(obj)`.

14 *Effects:* If the map already contains an element `e` whose key is equivalent to `k`, assigns `std::forward<M>(obj)` to `e.second`. Otherwise inserts an object of type `value_type` constructed with `k`, `std::forward<M>(obj)`.

15 *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

16 *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

```
template <class M>
 pair<iterator, bool> insert_or_assign(key_type&& k, M&& obj);
template <class M>
 iterator insert_or_assign(const_iterator hint, key_type&& k, M&& obj);
```

17 *Requires:* `is_assignable_v<mapped_type&, M&&>` shall be `true`. `value_type` shall be `EmplaceConstructible` into `unordered_map` from `std::move(k)`, `std::forward<M>(obj)`.

18 *Effects:* If the map already contains an element `e` whose key is equivalent to `k`, assigns `std::forward<M>(obj)` to `e.second`. Otherwise inserts an object of type `value_type` constructed with `std::move(k)`, `std::forward<M>(obj)`.

19 *Returns:* In the first overload, the `bool` component of the returned pair is `true` if and only if the insertion took place. The returned iterator points to the map element whose key is equivalent to `k`.

20 *Complexity:* The same as `emplace` and `emplace_hint`, respectively.

#### 26.5.4.5 unordered\_map swap

[unord.map.swap]

```
template <class Key, class T, class Hash, class Pred, class Alloc>
 void swap(unordered_map<Key, T, Hash, Pred, Alloc>& x,
 unordered_map<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
```

1 *Effects:* As if by `x.swap(y)`.

## 26.5.5 Class template unordered\_multimap [unord.multimap]

### 26.5.5.1 Class template unordered\_multimap overview [unord.multimap.overview]

- <sup>1</sup> An `unordered_multimap` is an unordered associative container that supports equivalent keys (an instance of `unordered_multimap` may contain multiple copies of each key value) and that associates values of another type `mapped_type` with the keys. The `unordered_multimap` class supports forward iterators.
- <sup>2</sup> An `unordered_multimap` satisfies all of the requirements of a container, of an unordered associative container, and of an allocator-aware container (Table 86). It provides the operations described in the preceding requirements table for equivalent keys; that is, an `unordered_multimap` supports the `a_eq` operations in that table, not the `a_uniq` operations. For an `unordered_multimap<Key, T>` the key type is `Key`, the mapped type is `T`, and the value type is `pair<const Key, T>`.
- <sup>3</sup> This section only describes operations on `unordered_multimap` that are not described in one of the requirement tables, or for which there is additional semantic information.

```
namespace std {
 template <class Key,
 class T,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Allocator = allocator<pair<const Key, T>>>
 class unordered_multimap {
 public:
 // types:
 using key_type = Key;
 using mapped_type = T;
 using value_type = pair<const Key, T>;
 using hasher = Hash;
 using key_equal = Pred;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2

 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using local_iterator = implementation-defined; // see 26.2
 using const_local_iterator = implementation-defined; // see 26.2
 using node_type = unspecified;

 // 26.5.5.2, construct/copy/destroy
 unordered_multimap();
 explicit unordered_multimap(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

 template <class InputIterator>
 unordered_multimap(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
```

```

unordered_multimap(const unordered_multimap&);
unordered_multimap(unordered_multimap&&);
explicit unordered_multimap(const Allocator&);
unordered_multimap(const unordered_multimap&, const Allocator&);
unordered_multimap(unordered_multimap&&, const Allocator&);
unordered_multimap(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_multimap(size_type n, const allocator_type& a)
 : unordered_multimap(n, hasher(), key_equal(), a) { }
unordered_multimap(size_type n, const hasher& hf, const allocator_type& a)
 : unordered_multimap(n, hf, key_equal(), a) { }
template <class InputIterator>
 unordered_multimap(InputIterator f, InputIterator l, size_type n, const allocator_type& a)
 : unordered_multimap(f, l, n, hasher(), key_equal(), a) { }
template <class InputIterator>
 unordered_multimap(InputIterator f, InputIterator l, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_multimap(f, l, n, hf, key_equal(), a) { }
unordered_multimap(initializer_list<value_type> il, size_type n, const allocator_type& a)
 : unordered_multimap(il, n, hasher(), key_equal(), a) { }
unordered_multimap(initializer_list<value_type> il, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_multimap(il, n, hf, key_equal(), a) { }
~unordered_multimap();
unordered_multimap& operator=(const unordered_multimap&);
unordered_multimap& operator=(unordered_multimap&&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Hash> &&
 is_nothrow_move_assignable_v<Pred>);
unordered_multimap& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// 26.5.5.3, modifiers
template <class... Args> iterator emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
iterator insert(const value_type& obj);
iterator insert(value_type&& obj);
template <class P> iterator insert(P&& obj);
iterator insert(const_iterator hint, const value_type& obj);

```

```

iterator insert(const_iterator hint, value_type&& obj);
template <class P> iterator insert(const_iterator hint, P&& obj);
template <class InputIterator> void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
iterator insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& k);
iterator erase(const_iterator first, const_iterator last);
void swap(unordered_multimap&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Hash> &&
 is_nothrow_swappable_v<Pred>);
void clear() noexcept;

template<class H2, class P2>
 void merge(unordered_multimap<Key, T, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_multimap<Key, T, H2, P2, Allocator>&& source);
template<class H2, class P2>
 void merge(unordered_map<Key, T, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_map<Key, T, H2, P2, Allocator>&& source);

// observers:
hasher hash_function() const;
key_equal key_eq() const;

// map operations:
iterator find(const key_type& k);
const_iterator find(const key_type& k) const;
size_type count(const key_type& k) const;
pair<iterator, iterator> equal_range(const key_type& k);
pair<const_iterator, const_iterator> equal_range(const key_type& k) const;

// bucket interface:
size_type bucket_count() const noexcept;
size_type max_bucket_count() const noexcept;
size_type bucket_size(size_type n) const;
size_type bucket(const key_type& k) const;
local_iterator begin(size_type n);
const_local_iterator begin(size_type n) const;
local_iterator end(size_type n);
const_local_iterator end(size_type n) const;
const_local_iterator cbegin(size_type n) const;
const_local_iterator cend(size_type n) const;

// hash policy
float load_factor() const noexcept;
float max_load_factor() const noexcept;

```

```

 void max_load_factor(float z);
 void rehash(size_type n);
 void reserve(size_type n);
};

template<class InputIterator,
 class Hash = hash<iter_key_t<InputIterator>>,
 class Pred = equal_to<iter_key_t<InputIterator>>,
 class Allocator = allocator<iter_to_alloc_t<InputIterator>>>
 unordered_multimap(InputIterator, InputIterator,
 typename see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
 -> unordered_multimap<iter_key_t<InputIterator>, iter_value_t<InputIterator>, Hash, Pred,
 Allocator>;

template<class Key, class T, class Hash = hash<Key>,
 class Pred = equal_to<Key>, class Allocator = allocator<pair<const Key, T>>>
 unordered_multimap(initializer_list<pair<const Key, T>>,
 typename see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
 -> unordered_multimap<Key, T, Hash, Pred, Allocator>;

template<class InputIterator, class Allocator>
 unordered_multimap(InputIterator, InputIterator, typename see below::size_type, Allocator)
 -> unordered_multimap<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 hash<iter_key_t<InputIterator>>,
 equal_to<iter_key_t<InputIterator>>, Allocator>;

template<class InputIterator, class Allocator>
 unordered_multimap(InputIterator, InputIterator, Allocator)
 -> unordered_multimap<iter_key_t<InputIterator>, iter_val_t<InputIterator>,
 hash<iter_key_t<InputIterator>>,
 equal_to<iter_key_t<InputIterator>>, Allocator>;

template<class InputIterator, class Hash, class Allocator>
 unordered_multimap(InputIterator, InputIterator, typename see below::size_type, Hash,
 Allocator)
 -> unordered_multimap<iter_key_t<InputIterator>, iter_val_t<InputIterator>, Hash,
 equal_to<iter_key_t<InputIterator>>, Allocator>;

template<class Key, class T, typename Allocator>
 unordered_multimap(initializer_list<pair<const Key, T>>, typename see below::size_type,
 Allocator)
 -> unordered_multimap<Key, T, hash<Key>, equal_to<Key>, Allocator>;

template<class Key, class T, typename Allocator>
 unordered_multimap(initializer_list<pair<const Key, T>>, Allocator)
 -> unordered_multimap<Key, T, hash<Key>, equal_to<Key>, Allocator>;

template<class Key, class T, class Hash, class Allocator>
 unordered_multimap(initializer_list<pair<const Key, T>>, typename see below::size_type,
 Hash, Allocator)
 -> unordered_multimap<Key, T, Hash, equal_to<Key>, Allocator>;

template <class Key, class T, class Hash, class Pred, class Alloc>

```

```

 bool operator==(const unordered_multimap<Key, T, Hash, Pred, Alloc>& a,
 const unordered_multimap<Key, T, Hash, Pred, Alloc>& b);
template <class Key, class T, class Hash, class Pred, class Alloc>
 bool operator!=(const unordered_multimap<Key, T, Hash, Pred, Alloc>& a,
 const unordered_multimap<Key, T, Hash, Pred, Alloc>& b);

// 26.5.5.4, swap
template <class Key, class T, class Hash, class Pred, class Alloc>
 void swap(unordered_multimap<Key, T, Hash, Pred, Alloc>& x,
 unordered_multimap<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
}

```

- 4 A `size_type` parameter type in an `unordered_multimap` deduction guide refers to the `size_type` member type of the type deduced by the deduction guide.

### 26.5.5.2 `unordered_multimap` constructors

[unord.multimap.cnstr]

```

unordered_multimap() : unordered_multimap(size_type(see below)) { }
explicit unordered_multimap(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

- 1 *Effects:* Constructs an empty `unordered_multimap` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. For the default constructor, the number of buckets is implementation-defined. `max_load_factor()` returns 1.0.
- 2 *Complexity:* Constant.

```

template <class InputIterator>
 unordered_multimap(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_multimap(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

- 3 *Effects:* Constructs an empty `unordered_multimap` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. If `n` is not provided, the number of buckets is implementation-defined. Then inserts elements from the range `[f, l)` for the first form, or from the range `[il.begin(), il.end())` for the second form. `max_load_factor()` returns 1.0.
- 4 *Complexity:* Average case linear, worst case quadratic.

### 26.5.5.3 `unordered_multimap` modifiers

[unord.multimap.modifiers]

```

template <class P>
 iterator insert(P&& obj);

```

- 1 *Effects:* Equivalent to: `return.emplace(std::forward<P>(obj));`
- 2 *Remarks:* This signature shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

```
template <class P>
 iterator insert(const_iterator hint, P&& obj);
```

3     *Effects:* Equivalent to: `return emplace_hint(hint, std::forward<P>(obj));`

4     *Remarks:* This signature shall not participate in overload resolution unless `is_constructible_v<value_type, P&&>` is true.

#### 26.5.5.4 unordered\_multimap swap

[unord.multimap.swap]

```
template <class Key, class T, class Hash, class Pred, class Alloc>
 void swap(unordered_multimap<Key, T, Hash, Pred, Alloc>& x,
 unordered_multimap<Key, T, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
```

1     *Effects:* As if by `x.swap(y)`.

### 26.5.6 Class template unordered\_set

[unord.set]

#### 26.5.6.1 Class template unordered\_set overview

[unord.set.overview]

1 An `unordered_set` is an unordered associative container that supports unique keys (an `unordered_set` contains at most one of each key value) and in which the elements' keys are the elements themselves. The `unordered_set` class supports forward iterators.

2 An `unordered_set` satisfies all of the requirements of a container, of an unordered associative container, and of an allocator-aware container (Table 86). It provides the operations described in the preceding requirements table for unique keys; that is, an `unordered_set` supports the `a_uniq` operations in that table, not the `a_eq` operations. For an `unordered_set<Key>` the `key` type and the value type are both `Key`. The `iterator` and `const_iterator` types are both constant iterator types. It is unspecified whether they are the same type.

3 This section only describes operations on `unordered_set` that are not described in one of the requirement tables, or for which there is additional semantic information.

```
namespace std {
 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Allocator = allocator<Key>>
 class unordered_set {
 public:
 // types:
 using key_type = Key;
 using value_type = Key;
 using hasher = Hash;
 using key_equal = Pred;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2

 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using local_iterator = implementation-defined; // see 26.2
 using const_local_iterator = implementation-defined; // see 26.2
 using node_type = unspecified;
```

```

using insert_return_type = INSERT_RETURN_TYPE<iterator, node_type>;

// 26.5.6.2, construct/copy/destroy
unordered_set();
explicit unordered_set(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
template <class InputIterator>
 unordered_set(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_set(const unordered_set&);
unordered_set(unordered_set&&);
explicit unordered_set(const Allocator&);
unordered_set(const unordered_set&, const Allocator&);
unordered_set(unordered_set&&, const Allocator&);
unordered_set(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_set(size_type n, const allocator_type& a)
 : unordered_set(n, hasher(), key_equal(), a) { }
unordered_set(size_type n, const hasher& hf, const allocator_type& a)
 : unordered_set(n, hf, key_equal(), a) { }
template <class InputIterator>
 unordered_set(InputIterator f, InputIterator l, size_type n, const allocator_type& a)
 : unordered_set(f, l, n, hasher(), key_equal(), a) { }
template <class InputIterator>
 unordered_set(InputIterator f, InputIterator l, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_set(f, l, n, hf, key_equal(), a) { }
unordered_set(initializer_list<value_type> il, size_type n, const allocator_type& a)
 : unordered_set(il, n, hasher(), key_equal(), a) { }
unordered_set(initializer_list<value_type> il, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_set(il, n, hf, key_equal(), a) { }
~unordered_set();
unordered_set& operator=(const unordered_set&);
unordered_set& operator=(unordered_set&&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Hash> &&
 is_nothrow_move_assignable_v<Pred>);
unordered_set& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
const_iterator cbegin() const noexcept;

```



```

const_iterator cend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// modifiers:
template <class... Args> pair<iterator, bool> emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
pair<iterator, bool> insert(const value_type& obj);
pair<iterator, bool> insert(value_type&& obj);
iterator insert(const_iterator hint, const value_type& obj);
iterator insert(const_iterator hint, value_type&& obj);
template <class InputIterator> void insert(InputIterator first, InputIterator last);
void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
insert_return_type insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& k);
iterator erase(const_iterator first, const_iterator last);
void swap(unordered_set&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Hash> &&
 is_nothrow_swappable_v<Pred>);
void clear() noexcept;

template<class H2, class P2>
 void merge(unordered_set<Key, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_set<Key, H2, P2, Allocator>&& source);
template<class H2, class P2>
 void merge(unordered_multiset<Key, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_multiset<Key, H2, P2, Allocator>&& source);

// observers:
hasher hash_function() const;
key_equal key_eq() const;

// set operations:
iterator find(const key_type& k);
const_iterator find(const key_type& k) const;
size_type count(const key_type& k) const;
pair<iterator, iterator> equal_range(const key_type& k);
pair<const_iterator, const_iterator> equal_range(const key_type& k) const;

// bucket interface:
size_type bucket_count() const noexcept;
size_type max_bucket_count() const noexcept;

```

```

size_type bucket_size(size_type n) const;
size_type bucket(const key_type& k) const;
local_iterator begin(size_type n);
const_local_iterator begin(size_type n) const;
local_iterator end(size_type n);
const_local_iterator end(size_type n) const;
const_local_iterator cbegin(size_type n) const;
const_local_iterator cend(size_type n) const;

// hash policy:
float load_factor() const noexcept;
float max_load_factor() const noexcept;
void max_load_factor(float z);
void rehash(size_type n);
void reserve(size_type n);
};

template<class InputIterator,
 class Hash = hash<typename iterator_traits<InputIterator>::value_type>,
 class Pred = equal_to<typename iterator_traits<InputIterator>::value_type>,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
unordered_set(InputIterator, InputIterator, typename see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
-> unordered_set<typename iterator_traits<InputIterator>::value_type,
 Hash, Pred, Allocator>;

template<class T, class Hash = hash<T>,
 class Pred = equal_to<T>, class Allocator = allocator<T>>
unordered_set(initializer_list<T>, typename see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
-> unordered_set<T, Hash, Pred, Allocator>;

template<class InputIterator, class Allocator>
unordered_set(InputIterator, InputIterator, typename see below::size_type, Allocator)
-> unordered_set<typename iterator_traits<InputIterator>::value_type,
 hash<typename iterator_traits<InputIterator>::value_type>,
 equal_to<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;

template<class InputIterator, class Hash, class Allocator>
unordered_set(InputIterator, InputIterator, typename see below::size_type,
 Hash, Allocator)
-> unordered_set<typename iterator_traits<InputIterator>::value_type, Hash,
 equal_to<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;

template<class T, class Allocator>
unordered_set(initializer_list<T>, typename see below::size_type, Allocator)
-> unordered_set<T, hash<T>, equal_to<T>, Allocator>;

template<class T, class Hash, class Allocator>
unordered_set(initializer_list<T>, typename see below::size_type, Hash, Allocator)
-> unordered_set<T, Hash, equal_to<T>, Allocator>;

template <class Key, class Hash, class Pred, class Alloc>

```

```

 bool operator==(const unordered_set<Key, Hash, Pred, Alloc>& a,
 const unordered_set<Key, Hash, Pred, Alloc>& b);
template <class Key, class Hash, class Pred, class Alloc>
 bool operator!=(const unordered_set<Key, Hash, Pred, Alloc>& a,
 const unordered_set<Key, Hash, Pred, Alloc>& b);

// 26.5.6.3, swap
template <class Key, class Hash, class Pred, class Alloc>
 void swap(unordered_set<Key, Hash, Pred, Alloc>& x,
 unordered_set<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
}

```

- 4 A `size_type` parameter type in an `unordered_set` deduction guide refers to the `size_type` member type of the primary `unordered_set` template.

### 26.5.6.2 unordered\_set constructors

[unord.set.cnstr]

```

unordered_set() : unordered_set(size_type(see below)) { }
explicit unordered_set(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

- 1 *Effects:* Constructs an empty `unordered_set` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. For the default constructor, the number of buckets is implementation-defined. `max_load_factor()` returns 1.0.
- 2 *Complexity:* Constant.

```

template <class InputIterator>
 unordered_set(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_set(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

```

- 3 *Effects:* Constructs an empty `unordered_set` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. If `n` is not provided, the number of buckets is implementation-defined. Then inserts elements from the range `[f, l)` for the first form, or from the range `[il.begin(), il.end())` for the second form. `max_load_factor()` returns 1.0.
- 4 *Complexity:* Average case linear, worst case quadratic.

### 26.5.6.3 unordered\_set swap

[unord.set.swap]

```

template <class Key, class Hash, class Pred, class Alloc>
 void swap(unordered_set<Key, Hash, Pred, Alloc>& x,
 unordered_set<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));

```

- 1 *Effects:* As if by `x.swap(y)`.

## 26.5.7 Class template `unordered_multiset` [unord.multiset]

### 26.5.7.1 Class template `unordered_multiset` overview [unord.multiset.overview]

- <sup>1</sup> An `unordered_multiset` is an unordered associative container that supports equivalent keys (an instance of `unordered_multiset` may contain multiple copies of the same key value) and in which each element's key is the element itself. The `unordered_multiset` class supports forward iterators.
- <sup>2</sup> An `unordered_multiset` satisfies all of the requirements of a container, of an unordered associative container, and of an allocator-aware container (Table 86). It provides the operations described in the preceding requirements table for equivalent keys; that is, an `unordered_multiset` supports the `a_eq` operations in that table, not the `a_uniq` operations. For an `unordered_multiset<Key>` the `key` type and the value type are both `Key`. The `iterator` and `const_iterator` types are both constant iterator types. It is unspecified whether they are the same type.
- <sup>3</sup> This section only describes operations on `unordered_multiset` that are not described in one of the requirement tables, or for which there is additional semantic information.

```
namespace std {
 template <class Key,
 class Hash = hash<Key>,
 class Pred = equal_to<Key>,
 class Allocator = allocator<Key>>
 class unordered_multiset {
 public:
 // types:
 using key_type = Key;
 using value_type = Key;
 using hasher = Hash;
 using key_equal = Pred;
 using allocator_type = Allocator;
 using pointer = typename allocator_traits<Allocator>::pointer;
 using const_pointer = typename allocator_traits<Allocator>::const_pointer;
 using reference = value_type&;
 using const_reference = const value_type&;
 using size_type = implementation-defined; // see 26.2
 using difference_type = implementation-defined; // see 26.2

 using iterator = implementation-defined; // see 26.2
 using const_iterator = implementation-defined; // see 26.2
 using local_iterator = implementation-defined; // see 26.2
 using const_local_iterator = implementation-defined; // see 26.2
 using node_type = unspecified;

 // 26.5.7.2, construct/copy/destroy
 unordered_multiset();
 explicit unordered_multiset(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());

 template <class InputIterator>
 unordered_multiset(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
 unordered_multiset(const unordered_multiset&);
 };
};
```

```

unordered_multiset(unordered_multiset&&);
explicit unordered_multiset(const Allocator&);
unordered_multiset(const unordered_multiset&, const Allocator&);
unordered_multiset(unordered_multiset&&, const Allocator&);
unordered_multiset(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_multiset(size_type n, const allocator_type& a)
 : unordered_multiset(n, hasher(), key_equal(), a) { }
unordered_multiset(size_type n, const hasher& hf, const allocator_type& a)
 : unordered_multiset(n, hf, key_equal(), a) { }
template <class InputIterator>
 unordered_multiset(InputIterator f, InputIterator l, size_type n, const allocator_type& a)
 : unordered_multiset(f, l, n, hasher(), key_equal(), a) { }
template <class InputIterator>
 unordered_multiset(InputIterator f, InputIterator l, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_multiset(f, l, n, hf, key_equal(), a) { }
unordered_multiset(initializer_list<value_type> il, size_type n, const allocator_type& a)
 : unordered_multiset(il, n, hasher(), key_equal(), a) { }
unordered_multiset(initializer_list<value_type> il, size_type n, const hasher& hf,
 const allocator_type& a)
 : unordered_multiset(il, n, hf, key_equal(), a) { }
~unordered_multiset();
unordered_multiset& operator=(const unordered_multiset&);
unordered_multiset& operator=(unordered_multiset&&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_move_assignable_v<Hash> &&
 is_nothrow_move_assignable_v<Pred>);
unordered_multiset& operator=(initializer_list<value_type>);
allocator_type get_allocator() const noexcept;

// iterators:
iterator begin() noexcept;
const_iterator begin() const noexcept;
iterator end() noexcept;
const_iterator end() const noexcept;
const_iterator cbegin() const noexcept;
const_iterator cend() const noexcept;

// capacity:
bool empty() const noexcept;
size_type size() const noexcept;
size_type max_size() const noexcept;

// modifiers:
template <class... Args> iterator emplace(Args&&... args);
template <class... Args> iterator emplace_hint(const_iterator position, Args&&... args);
iterator insert(const value_type& obj);
iterator insert(value_type&& obj);
iterator insert(const_iterator hint, const value_type& obj);
iterator insert(const_iterator hint, value_type&& obj);
template <class InputIterator> void insert(InputIterator first, InputIterator last);

```

```

void insert(initializer_list<value_type>);

node_type extract(const_iterator position);
node_type extract(const key_type& x);
iterator insert(node_type&& nh);
iterator insert(const_iterator hint, node_type&& nh);

iterator erase(iterator position);
iterator erase(const_iterator position);
size_type erase(const key_type& k);
iterator erase(const_iterator first, const_iterator last);
void swap(unordered_multiset&)
 noexcept(allocator_traits<Allocator>::is_always_equal::value &&
 is_nothrow_swappable_v<Hash> &&
 is_nothrow_swappable_v<Pred>);
void clear() noexcept;

template<class H2, class P2>
 void merge(unordered_multiset<Key, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_multiset<Key, H2, P2, Allocator>&& source);
template<class H2, class P2>
 void merge(unordered_set<Key, H2, P2, Allocator>& source);
template<class H2, class P2>
 void merge(unordered_set<Key, H2, P2, Allocator>&& source);

// observers:
hasher hash_function() const;
key_equal key_eq() const;

// set operations:
iterator find(const key_type& k);
const_iterator find(const key_type& k) const;
size_type count(const key_type& k) const;
pair<iterator, iterator> equal_range(const key_type& k);
pair<const_iterator, const_iterator> equal_range(const key_type& k) const;

// bucket interface:
size_type bucket_count() const noexcept;
size_type max_bucket_count() const noexcept;
size_type bucket_size(size_type n) const;
size_type bucket(const key_type& k) const;
local_iterator begin(size_type n);
const_local_iterator begin(size_type n) const;
local_iterator end(size_type n);
const_local_iterator end(size_type n) const;
const_local_iterator cbegin(size_type n) const;
const_local_iterator cend(size_type n) const;

// hash policy:
float load_factor() const noexcept;
float max_load_factor() const noexcept;
void max_load_factor(float z);
void rehash(size_type n);
void reserve(size_type n);

```

```

};

template<class InputIterator,
 class Hash = hash<typename iterator_traits<InputIterator>::value_type>,
 class Pred = equal_to<typename iterator_traits<InputIterator>::value_type>,
 class Allocator = allocator<typename iterator_traits<InputIterator>::value_type>>
unordered_multiset(InputIterator, InputIterator, see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
-> unordered_multiset<typename iterator_traits<InputIterator>::value_type,
 Hash, Pred, Allocator>;

template<class T, class Hash = hash<T>,
 class Pred = equal_to<T>, class Allocator = allocator<T>>
unordered_multiset(initializer_list<T>, typename see below::size_type = see below,
 Hash = Hash(), Pred = Pred(), Allocator = Allocator())
-> unordered_multiset<T, Hash, Pred, Allocator>;

template<class InputIterator, class Allocator>
unordered_multiset(InputIterator, InputIterator, typename see below::size_type, Allocator)
-> unordered_multiset<typename iterator_traits<InputIterator>::value_type,
 hash<typename iterator_traits<InputIterator>::value_type>,
 equal_to<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;

template<class InputIterator, class Hash, class Allocator>
unordered_multiset(InputIterator, InputIterator, typename see below::size_type,
 Hash, Allocator)
-> unordered_multiset<typename iterator_traits<InputIterator>::value_type, Hash,
 equal_to<typename iterator_traits<InputIterator>::value_type>,
 Allocator>;

template<class T, class Allocator>
unordered_multiset(initializer_list<T>, typename see below::size_type, Allocator)
-> unordered_multiset<T, hash<T>, equal_to<T>, Allocator>;

template<class T, class Hash, class Allocator>
unordered_multiset(initializer_list<T>, typename see below::size_type, Hash, Allocator)
-> unordered_multiset<T, Hash, equal_to<T>, Allocator>;

template <class Key, class Hash, class Pred, class Alloc>
bool operator==(const unordered_multiset<Key, Hash, Pred, Alloc>& a,
 const unordered_multiset<Key, Hash, Pred, Alloc>& b);
template <class Key, class Hash, class Pred, class Alloc>
bool operator!=(const unordered_multiset<Key, Hash, Pred, Alloc>& a,
 const unordered_multiset<Key, Hash, Pred, Alloc>& b);

// 26.5.7.3, swap
template <class Key, class Hash, class Pred, class Alloc>
void swap(unordered_multiset<Key, Hash, Pred, Alloc>& x,
 unordered_multiset<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
}

```

<sup>4</sup> A `size_type` parameter type in an `unordered_multiset` deduction guide refers to the `size_type` member type of the primary `unordered_multiset` template.

**26.5.7.2 unordered\_multiset constructors****[unord.multiset.cnstr]**

```
unordered_multiset() : unordered_multiset(size_type(see below)) { }
explicit unordered_multiset(size_type n,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
```

- <sup>1</sup> *Effects:* Constructs an empty `unordered_multiset` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. For the default constructor, the number of buckets is implementation-defined. `max_load_factor()` returns 1.0.

- <sup>2</sup> *Complexity:* Constant.

```
template <class InputIterator>
 unordered_multiset(InputIterator f, InputIterator l,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
unordered_multiset(initializer_list<value_type> il,
 size_type n = see below,
 const hasher& hf = hasher(),
 const key_equal& eql = key_equal(),
 const allocator_type& a = allocator_type());
```

- <sup>3</sup> *Effects:* Constructs an empty `unordered_multiset` using the specified hash function, key equality predicate, and allocator, and using at least `n` buckets. If `n` is not provided, the number of buckets is implementation-defined. Then inserts elements from the range `[f, l)` for the first form, or from the range `[il.begin(), il.end())` for the second form. `max_load_factor()` returns 1.0.

- <sup>4</sup> *Complexity:* Average case linear, worst case quadratic.

**26.5.7.3 unordered\_multiset swap****[unord.multiset.swap]**

```
template <class Key, class Hash, class Pred, class Alloc>
 void swap(unordered_multiset<Key, Hash, Pred, Alloc>& x,
 unordered_multiset<Key, Hash, Pred, Alloc>& y)
 noexcept(noexcept(x.swap(y)));
```

- <sup>1</sup> *Effects:* As if by `x.swap(y)`.

**26.6 Container adaptors****[container.adaptors]****26.6.1 In general****[container.adaptors.general]**

- <sup>1</sup> The headers `<queue>` and `<stack>` define the container adaptors `queue`, `priority_queue`, and `stack`.
- <sup>2</sup> The container adaptors each take a `Container` template parameter, and each constructor takes a `Container` reference argument. This container is copied into the `Container` member of each adaptor. If the container takes an allocator, then a compatible allocator may be passed in to the adaptor's constructor. Otherwise, normal copy or move construction is used for the container argument. The first template parameter `T` of the container adaptors shall denote the same type as `Container::value_type`.
- <sup>3</sup> For container adaptors, no `swap` function throws an exception unless that exception is thrown by the swap of the adaptor's `Container` or `Compare` object (if any).
- <sup>4</sup> A deduction guide for a container adaptor shall not participate in overload resolution if any of the following are true:



- (4.1) — It has an `InputIterator` template parameter and a type that does not qualify as an input iterator is deduced for that parameter.
- (4.2) — It has a `Compare` template parameter and a type that qualifies as an allocator is deduced for that parameter.
- (4.3) — It has a `Container` template parameter and a type that qualifies as an allocator is deduced for that parameter.
- (4.4) — It has an `Allocator` template parameter and a type that does not qualify as an allocator is deduced for that parameter.
- (4.5) — It has both `Container` and `Allocator` template parameters, and `uses_allocator_v<Container, Allocator>` is false.

### 26.6.2 Header `<queue>` synopsis

[queue.syn]

```
#include <initializer_list>

namespace std {
 template <class T, class Container = deque<T>> class queue;
 template <class T, class Container = vector<T>,
 class Compare = less<typename Container::value_type>>
 class priority_queue;

 template <class T, class Container>
 bool operator==(const queue<T, Container>& x, const queue<T, Container>& y);
 template <class T, class Container>
 bool operator< (const queue<T, Container>& x, const queue<T, Container>& y);
 template <class T, class Container>
 bool operator!=(const queue<T, Container>& x, const queue<T, Container>& y);
 template <class T, class Container>
 bool operator> (const queue<T, Container>& x, const queue<T, Container>& y);
 template <class T, class Container>
 bool operator>= (const queue<T, Container>& x, const queue<T, Container>& y);
 template <class T, class Container>
 bool operator<= (const queue<T, Container>& x, const queue<T, Container>& y);

 template <class T, class Container>
 void swap(queue<T, Container>& x, queue<T, Container>& y) noexcept(noexcept(x.swap(y)));
 template <class T, class Container, class Compare>
 void swap(priority_queue<T, Container, Compare>& x,
 priority_queue<T, Container, Compare>& y) noexcept(noexcept(x.swap(y)));
}
```

### 26.6.3 Header `<stack>` synopsis

[stack.syn]

```
#include <initializer_list>

namespace std {
 template <class T, class Container = deque<T>> class stack;
 template <class T, class Container>
 bool operator==(const stack<T, Container>& x, const stack<T, Container>& y);
 template <class T, class Container>
 bool operator< (const stack<T, Container>& x, const stack<T, Container>& y);
 template <class T, class Container>
 bool operator!=(const stack<T, Container>& x, const stack<T, Container>& y);
 template <class T, class Container>
 bool operator> (const stack<T, Container>& x, const stack<T, Container>& y);
}
```

```

template <class T, class Container>
 bool operator>=(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator<=(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 void swap(stack<T, Container>& x, stack<T, Container>& y) noexcept(noexcept(x.swap(y)));
}

```

## 26.6.4 Class template queue

[queue]

### 26.6.4.1 queue definition

[queue.defn]

- <sup>1</sup> Any sequence container supporting operations `front()`, `back()`, `push_back()` and `pop_front()` can be used to instantiate `queue`. In particular, `list` (26.3.10) and `deque` (26.3.8) can be used.

```

namespace std {
 template <class T, class Container = deque<T>>
 class queue {
 public:
 using value_type = typename Container::value_type;
 using reference = typename Container::reference;
 using const_reference = typename Container::const_reference;
 using size_type = typename Container::size_type;
 using container_type = Container;

 protected:
 Container c;

 public:
 explicit queue(const Container&);
 explicit queue(Container&& = Container());
 template <class Alloc> explicit queue(const Alloc&);
 template <class Alloc> queue(const Container&, const Alloc&);
 template <class Alloc> queue(Container&&, const Alloc&);
 template <class Alloc> queue(const queue&, const Alloc&);
 template <class Alloc> queue(queue&&, const Alloc&);

 bool empty() const { return c.empty(); }
 size_type size() const { return c.size(); }
 reference front() { return c.front(); }
 const_reference front() const { return c.front(); }
 reference back() { return c.back(); }
 const_reference back() const { return c.back(); }
 void push(const value_type& x) { c.push_back(x); }
 void push(value_type&& x) { c.push_back(std::move(x)); }
 template <class... Args>
 reference emplace(Args&&... args) { return c.emplace_back(std::forward<Args>(args)...); }
 void pop() { c.pop_front(); }
 void swap(queue& q) noexcept(is_nothrow_swappable_v<Container>)
 { using std::swap; swap(c, q.c); }
 };

 template<class Container>
 queue(Container) -> queue<typename Container::value_type, Container>;

 template<class Container, class Allocator>
 queue(Container, Allocator) -> queue<typename Container::value_type, Container>;

```

```

template <class T, class Container>
 bool operator==(const queue<T, Container>& x, const queue<T, Container>& y);
template <class T, class Container>
 bool operator< (const queue<T, Container>& x, const queue<T, Container>& y);
template <class T, class Container>
 bool operator!=(const queue<T, Container>& x, const queue<T, Container>& y);
template <class T, class Container>
 bool operator> (const queue<T, Container>& x, const queue<T, Container>& y);
template <class T, class Container>
 bool operator>=(const queue<T, Container>& x, const queue<T, Container>& y);
template <class T, class Container>
 bool operator<=(const queue<T, Container>& x, const queue<T, Container>& y);

template <class T, class Container>
 void swap(queue<T, Container>& x, queue<T, Container>& y) noexcept(noexcept(x.swap(y)));

template <class T, class Container, class Alloc>
 struct uses_allocator<queue<T, Container>, Alloc>
 : uses_allocator<Container, Alloc>::type { };
}

```

#### 26.6.4.2 queue constructors

[queue.cons]

```
explicit queue(const Container& cont);
```

- 1 *Effects:* Initializes *c* with *cont*.

```
explicit queue(Container&& cont = Container());
```

- 2 *Effects:* Initializes *c* with `std::move(cont)`.

#### 26.6.4.3 queue constructors with allocators

[queue.cons.alloc]

- 1 If `uses_allocator_v<container_type, Alloc>` is false the constructors in this subclause shall not participate in overload resolution.

```
template <class Alloc> explicit queue(const Alloc& a);
```

- 2 *Effects:* Initializes *c* with *a*.

```
template <class Alloc> queue(const container_type& cont, const Alloc& a);
```

- 3 *Effects:* Initializes *c* with *cont* as the first argument and *a* as the second argument.

```
template <class Alloc> queue(container_type&& cont, const Alloc& a);
```

- 4 *Effects:* Initializes *c* with `std::move(cont)` as the first argument and *a* as the second argument.

```
template <class Alloc> queue(const queue& q, const Alloc& a);
```

- 5 *Effects:* Initializes *c* with *q.c* as the first argument and *a* as the second argument.

```
template <class Alloc> queue(queue&& q, const Alloc& a);
```

- 6 *Effects:* Initializes *c* with `std::move(q.c)` as the first argument and *a* as the second argument.

#### 26.6.4.4 queue operators

[queue.ops]

```

template <class T, class Container>
 bool operator==(const queue<T, Container>& x, const queue<T, Container>& y);

```

1       *Returns:* `x.c == y.c.`

```
template <class T, class Container>
 bool operator!=(const queue<T, Container>& x, const queue<T, Container>& y);
```

2       *Returns:* `x.c != y.c.`

```
template <class T, class Container>
 bool operator< (const queue<T, Container>& x, const queue<T, Container>& y);
```

3       *Returns:* `x.c < y.c.`

```
template <class T, class Container>
 bool operator<=(const queue<T, Container>& x, const queue<T, Container>& y);
```

4       *Returns:* `x.c <= y.c.`

```
template <class T, class Container>
 bool operator> (const queue<T, Container>& x, const queue<T, Container>& y);
```

5       *Returns:* `x.c > y.c.`

```
template <class T, class Container>
 bool operator>=(const queue<T, Container>& x,
 const queue<T, Container>& y);
```

6       *Returns:* `x.c >= y.c.`

#### 26.6.4.5 queue specialized algorithms

[queue.special]

```
template <class T, class Container>
 void swap(queue<T, Container>& x, queue<T, Container>& y) noexcept(noexcept(x.swap(y)));
```

1       *Remarks:* This function shall not participate in overload resolution unless `is_swappable_v<Container>` is true.

2       *Effects:* As if by `x.swap(y)`.

#### 26.6.5 Class template `priority_queue`

[priority.queue]

1 Any sequence container with random access iterator and supporting operations `front()`, `push_back()` and `pop_back()` can be used to instantiate `priority_queue`. In particular, `vector` (26.3.11) and `deque` (26.3.8) can be used. Instantiating `priority_queue` also involves supplying a function or function object for making priority comparisons; the library assumes that the function or function object defines a strict weak ordering (28.7).

```
namespace std {
 template <class T, class Container = vector<T>,
 class Compare = less<typename Container::value_type>>
 class priority_queue {
 public:
 using value_type = typename Container::value_type;
 using reference = typename Container::reference;
 using const_reference = typename Container::const_reference;
 using size_type = typename Container::size_type;
 using container_type = Container;
 using value_compare = Compare;

 protected:
 Container c;
 Compare comp;
```

```

public:
 priority_queue(const Compare& x, const Container&);
 explicit priority_queue(const Compare& x = Compare(), Container&& = Container());
 template <class InputIterator>
 priority_queue(InputIterator first, InputIterator last,
 const Compare& x, const Container&);
 template <class InputIterator>
 priority_queue(InputIterator first, InputIterator last,
 const Compare& x = Compare(), Container&& = Container());
 template <class Alloc> explicit priority_queue(const Alloc&);
 template <class Alloc> priority_queue(const Compare&, const Alloc&);
 template <class Alloc> priority_queue(const Compare&, const Container&, const Alloc&);
 template <class Alloc> priority_queue(const Compare&, Container&&, const Alloc&);
 template <class Alloc> priority_queue(const priority_queue&, const Alloc&);
 template <class Alloc> priority_queue(priority_queue&&, const Alloc&);

 bool empty() const { return c.empty(); }
 size_type size() const { return c.size(); }
 const_reference top() const { return c.front(); }
 void push(const value_type& x);
 void push(value_type&& x);
 template <class... Args> void emplace(Args&&... args);
 void pop();
 void swap(priority_queue& q) noexcept(is_nothrow_swappable_v<Container> &&
 is_nothrow_swappable_v<Compare>)
 { using std::swap; swap(c, q.c); swap(comp, q.comp); }
};

template<class Compare, class Container>
 priority_queue(Compare, Container)
 -> priority_queue<typename Container::value_type, Container, Compare>;

template<class InputIterator,
 class Compare = less<typename iterator_traits<InputIterator>::value_type>,
 class Container = vector<typename iterator_traits<InputIterator>::value_type>>
 priority_queue(InputIterator, InputIterator, Compare = Compare(), Container = Container())
 -> priority_queue<typename iterator_traits<InputIterator>::value_type, Container, Compare>;

template<class Compare, class Container, class Allocator>
 priority_queue(Compare, Container, Allocator)
 -> priority_queue<typename Container::value_type, Container, Compare>;

// no equality is provided

template <class T, class Container, class Compare>
 void swap(priority_queue<T, Container, Compare>& x,
 priority_queue<T, Container, Compare>& y) noexcept(noexcept(x.swap(y)));

template <class T, class Container, class Compare, class Alloc>
 struct uses_allocator<priority_queue<T, Container, Compare>, Alloc>
 : uses_allocator<Container, Alloc>::type { };
}

```

### 26.6.5.1 priority\_queue constructors

[priqueue.cons]

```
priority_queue(const Compare& x, const Container& y);
explicit priority_queue(const Compare& x = Compare(), Container&& y = Container());
```

1 *Requires:* x shall define a strict weak ordering (28.7).

2 *Effects:* Initializes comp with x and c with y (copy constructing or move constructing as appropriate); calls make\_heap(c.begin(), c.end(), comp).

```
template <class InputIterator>
 priority_queue(InputIterator first, InputIterator last,
 const Compare& x,
 const Container& y);
template <class InputIterator>
 priority_queue(InputIterator first, InputIterator last,
 const Compare& x = Compare(),
 Container&& y = Container());
```

3 *Requires:* x shall define a strict weak ordering (28.7).

4 *Effects:* Initializes comp with x and c with y (copy constructing or move constructing as appropriate); calls c.insert(c.end(), first, last); and finally calls make\_heap(c.begin(), c.end(), comp).

### 26.6.5.2 priority\_queue constructors with allocators [priqueue.cons.alloc]

1 If uses\_allocator\_v<container\_type, Alloc> is false the constructors in this subclause shall not participate in overload resolution.

```
template <class Alloc> explicit priority_queue(const Alloc& a);
```

2 *Effects:* Initializes c with a and value-initializes comp.

```
template <class Alloc> priority_queue(const Compare& compare, const Alloc& a);
```

3 *Effects:* Initializes c with a and initializes comp with compare.

```
template <class Alloc>
 priority_queue(const Compare& compare, const Container& cont, const Alloc& a);
```

4 *Effects:* Initializes c with cont as the first argument and a as the second argument, and initializes comp with compare; calls make\_heap(c.begin(), c.end(), comp).

```
template <class Alloc>
 priority_queue(const Compare& compare, Container&& cont, const Alloc& a);
```

5 *Effects:* Initializes c with std::move(cont) as the first argument and a as the second argument, and initializes comp with compare; calls make\_heap(c.begin(), c.end(), comp).

```
template <class Alloc> priority_queue(const priority_queue& q, const Alloc& a);
```

6 *Effects:* Initializes c with q.c as the first argument and a as the second argument, and initializes comp with q.comp.

```
template <class Alloc> priority_queue(priority_queue&& q, const Alloc& a);
```

7 *Effects:* Initializes c with std::move(q.c) as the first argument and a as the second argument, and initializes comp with std::move(q.comp).

### 26.6.5.3 priority\_queue members [priqueue.members]

```
void push(const value_type& x);
```

1 *Effects:* As if by:

```
 c.push_back(x);
```

```

 push_heap(c.begin(), c.end(), comp);

void push(value_type&& x);
2 Effects: As if by:
 c.push_back(std::move(x));
 push_heap(c.begin(), c.end(), comp);

template <class... Args> void emplace(Args&&... args)
3 Effects: As if by:
 c.emplace_back(std::forward<Args>(args)...);
 push_heap(c.begin(), c.end(), comp);

void pop();
4 Effects: As if by:
 pop_heap(c.begin(), c.end(), comp);
 c.pop_back();

```

#### 26.6.5.4 priority\_queue specialized algorithms

[priority\_queue.special]

```

template <class T, class Container, class Compare>
void swap(priority_queue<T, Container, Compare>& x,
 priority_queue<T, Container, Compare>& y) noexcept(noexcept(x.swap(y)));
1 Remarks: This function shall not participate in overload resolution unless is_swappable_v<Container>
 is true and is_swappable_v<Compare> is true.
2 Effects: As if by x.swap(y).

```

#### 26.6.6 Class template stack

[stack]

- 1 Any sequence container supporting operations `back()`, `push_back()` and `pop_back()` can be used to instantiate `stack`. In particular, `vector` (26.3.11), `list` (26.3.10) and `deque` (26.3.8) can be used.

##### 26.6.6.1 stack definition

[stack.defn]

```

namespace std {
 template <class T, class Container = deque<T>>
 class stack {
 public:
 using value_type = typename Container::value_type;
 using reference = typename Container::reference;
 using const_reference = typename Container::const_reference;
 using size_type = typename Container::size_type;
 using container_type = Container;

 protected:
 Container c;

 public:
 explicit stack(const Container&);
 explicit stack(Container&& = Container());
 template <class Alloc> explicit stack(const Alloc&);
 template <class Alloc> stack(const Container&, const Alloc&);
 template <class Alloc> stack(Container&&, const Alloc&);
 template <class Alloc> stack(const stack&, const Alloc&);
 template <class Alloc> stack(stack&&, const Alloc&);

```

```

 bool empty() const { return c.empty(); }
 size_type size() const { return c.size(); }
 reference top() const { return c.back(); }
 const_reference top() const { return c.back(); }
 void push(const value_type& x) { c.push_back(x); }
 void push(value_type&& x) { c.push_back(std::move(x)); }
 template <class... Args>
 reference emplace(Args&&... args) { return c.emplace_back(std::forward<Args>(args)...); }
 void pop() { c.pop_back(); }
 void swap(stack& s) noexcept(is_nothrow_swappable_v<Container>)
 { using std::swap; swap(c, s.c); }
};

template<class Container>
 stack(Container) -> stack<typename Container::value_type, Container>;

template<class Container, class Allocator>
 stack(Container, Allocator) -> stack<typename Container::value_type, Container>;

template <class T, class Container>
 bool operator==(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator< (const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator!=(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator> (const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator>=(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 bool operator<=(const stack<T, Container>& x, const stack<T, Container>& y);
template <class T, class Container>
 void swap(stack<T, Container>& x, stack<T, Container>& y) noexcept(noexcept(x.swap(y)));

template <class T, class Container, class Alloc>
 struct uses_allocator<stack<T, Container>, Alloc>
 : uses_allocator<Container, Alloc>::type { };
}

```

### 26.6.6.2 stack constructors

[stack.cons]

```
explicit stack(const Container& cont);
```

<sup>1</sup> *Effects:* Initializes c with cont.

```
explicit stack(Container&& cont = Container());
```

<sup>2</sup> *Effects:* Initializes c with std::move(cont).

### 26.6.6.3 stack constructors with allocators

[stack.cons.alloc]

<sup>1</sup> If uses\_allocator\_v<container\_type, Alloc> is false the constructors in this subclause shall not participate in overload resolution.

```
template <class Alloc> explicit stack(const Alloc& a);
```

<sup>2</sup> *Effects:* Initializes c with a.



```
template <class Alloc> stack(const container_type& cont, const Alloc& a);
```

3     *Effects:* Initializes `c` with `cont` as the first argument and `a` as the second argument.

```
template <class Alloc> stack(container_type&& cont, const Alloc& a);
```

4     *Effects:* Initializes `c` with `std::move(cont)` as the first argument and `a` as the second argument.

```
template <class Alloc> stack(const stack& s, const Alloc& a);
```

5     *Effects:* Initializes `c` with `s.c` as the first argument and `a` as the second argument.

```
template <class Alloc> stack(stack&& s, const Alloc& a);
```

6     *Effects:* Initializes `c` with `std::move(s.c)` as the first argument and `a` as the second argument.

#### 26.6.6.4 stack operators

[stack.ops]

```
template <class T, class Container>
bool operator==(const stack<T, Container>& x, const stack<T, Container>& y);
```

1     *Returns:* `x.c == y.c`.

```
template <class T, class Container>
bool operator!=(const stack<T, Container>& x, const stack<T, Container>& y);
```

2     *Returns:* `x.c != y.c`.

```
template <class T, class Container>
bool operator<(const stack<T, Container>& x, const stack<T, Container>& y);
```

3     *Returns:* `x.c < y.c`.

```
template <class T, class Container>
bool operator<=(const stack<T, Container>& x, const stack<T, Container>& y);
```

4     *Returns:* `x.c <= y.c`.

```
template <class T, class Container>
bool operator>(const stack<T, Container>& x, const stack<T, Container>& y);
```

5     *Returns:* `x.c > y.c`.

```
template <class T, class Container>
bool operator>=(const stack<T, Container>& x, const stack<T, Container>& y);
```

6     *Returns:* `x.c >= y.c`.

#### 26.6.6.5 stack specialized algorithms

[stack.special]

```
template <class T, class Container>
void swap(stack<T, Container>& x, stack<T, Container>& y) noexcept(noexcept(x.swap(y)));
```

1     *Remarks:* This function shall not participate in overload resolution unless `is_swappable_v<Container>` is true.

2     *Effects:* As if by `x.swap(y)`.

## 27 Iterators library

[iterators]

### 27.1 General

[iterators.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to perform iterations over containers (Clause 26), streams (30.7), and stream buffers (30.6).
- <sup>2</sup> The following subclauses describe iterator requirements, and components for iterator primitives, predefined iterators, and stream iterators, as summarized in Table 92.

Table 92 — Iterators library summary

| Subclause                 | Header(s)  |
|---------------------------|------------|
| 27.2 Requirements         |            |
| 27.4 Iterator primitives  | <iterator> |
| 27.5 Predefined iterators |            |
| 27.6 Stream iterators     |            |

### 27.2 Iterator requirements

[iterator.requirements]

#### 27.2.1 In general

[iterator.requirements.general]

- <sup>1</sup> Iterators are a generalization of pointers that allow a C++ program to work with different data structures (containers) in a uniform manner. To be able to construct template algorithms that work correctly and efficiently on different types of data structures, the library formalizes not just the interfaces but also the semantics and complexity assumptions of iterators. An input iterator *i* supports the expression *\*i*, resulting in a value of some object type *T*, called the *value type* of the iterator. An output iterator *i* has a non-empty set of types that are *writable* to the iterator; for each such type *T*, the expression *\*i = o* is valid where *o* is a value of type *T*. An iterator *i* for which the expression *(\*i).m* is well-defined supports the expression *i->m* with the same semantics as *(\*i).m*. For every iterator type *X* for which equality is defined, there is a corresponding signed integer type called the *difference type* of the iterator.
- <sup>2</sup> Since iterators are an abstraction of pointers, their semantics is a generalization of most of the semantics of pointers in C++. This ensures that every function template that takes iterators works as well with regular pointers. This International Standard defines five categories of iterators, according to the operations defined on them: *input iterators*, *output iterators*, *forward iterators*, *bidirectional iterators* and *random access iterators*, as shown in Table 93.

Table 93 — Relations among iterator categories

|                      |   |                      |   |                |   |               |
|----------------------|---|----------------------|---|----------------|---|---------------|
| <b>Random Access</b> | → | <b>Bidirectional</b> | → | <b>Forward</b> | → | <b>Input</b>  |
|                      |   |                      |   |                | → | <b>Output</b> |

- <sup>3</sup> Forward iterators satisfy all the requirements of input iterators and can be used whenever an input iterator is specified; Bidirectional iterators also satisfy all the requirements of forward iterators and can be used whenever a forward iterator is specified; Random access iterators also satisfy all the requirements of bidirectional iterators and can be used whenever a bidirectional iterator is specified.
- <sup>4</sup> Iterators that further satisfy the requirements of output iterators are called *mutable iterators*. Nonmutable iterators are referred to as *constant iterators*.

- 5 In addition to the requirements in this subclause, the nested *typedef-names* specified in 27.4.1 shall be provided for the iterator type. [Note: Either the iterator type must provide the *typedef-names* directly (in which case `iterator_traits` pick them up automatically), or an `iterator_traits` specialization must provide them. — end note]
- 6 Iterators that further satisfy the requirement that, for integral values `n` and dereferenceable iterator values `a` and `(a + n)`, `*(a + n)` is equivalent to `*(addressof(*a) + n)`, are called *contiguous iterators*. [Note: For example, the type “pointer to `int`” is a contiguous iterator, but `reverse_iterator<int*>` is not. For a valid iterator range `[a,b)` with dereferenceable `a`, the corresponding range denoted by pointers is `[addressof(*a),addressof(*a) + (b - a))`; `b` might not be dereferenceable. — end note]
- 7 Just as a regular pointer to an array guarantees that there is a pointer value pointing past the last element of the array, so for any iterator type there is an iterator value that points past the last element of a corresponding sequence. These values are called *past-the-end* values. Values of an iterator `i` for which the expression `*i` is defined are called *dereferenceable*. The library never assumes that past-the-end values are dereferenceable. Iterators can also have singular values that are not associated with any sequence. [Example: After the declaration of an uninitialized pointer `x` (as with `int* x;`), `x` must always be assumed to have a singular value of a pointer. — end example] Results of most expressions are undefined for singular values; the only exceptions are destroying an iterator that holds a singular value, the assignment of a non-singular value to an iterator that holds a singular value, and, for iterators that satisfy the `DefaultConstructible` requirements, using a value-initialized iterator as the source of a copy or move operation. [Note: This guarantee is not offered for default-initialization, although the distinction only matters for types with trivial default constructors such as pointers or aggregates holding pointers. — end note] In these cases the singular value is overwritten the same way as any other value. Dereferenceable values are always non-singular.
- 8 An iterator `j` is called *reachable* from an iterator `i` if and only if there is a finite sequence of applications of the expression `++i` that makes `i == j`. If `j` is reachable from `i`, they refer to elements of the same sequence.
- 9 Most of the library’s algorithmic templates that operate on data structures have interfaces that use ranges. A *range* is a pair of iterators that designate the beginning and end of the computation. A range `[i, i)` is an empty range; in general, a range `[i, j)` refers to the elements in the data structure starting with the element pointed to by `i` and up to but not including the element pointed to by `j`. Range `[i, j)` is valid if and only if `j` is reachable from `i`. The result of the application of functions in the library to invalid ranges is undefined.
- 10 All the categories of iterators require only those functions that are realizable for a given category in constant time (amortized). Therefore, requirement tables for the iterators do not have a complexity column.
- 11 Destruction of an iterator may invalidate pointers and references previously obtained from that iterator.
- 12 An *invalid* iterator is an iterator that may be singular.<sup>261</sup>
- 13 In the following sections, `a` and `b` denote values of type `X` or `const X`, `difference_type` and `reference` refer to the types `iterator_traits<X>::difference_type` and `iterator_traits<X>::reference`, respectively, `n` denotes a value of `difference_type`, `u`, `tmp`, and `m` denote identifiers, `r` denotes a value of `X&`, `t` denotes a value of value type `T`, `o` denotes a value of some type that is writable to the output iterator. [Note: For an iterator type `X` there must be an instantiation of `iterator_traits<X>` (27.4.1). — end note]

## 27.2.2 Iterator

[iterator.iterators]

- 1 The **Iterator** requirements form the basis of the iterator concept taxonomy; every iterator satisfies the **Iterator** requirements. This set of requirements specifies operations for dereferencing and incrementing an iterator. Most algorithms will require additional operations to read (27.2.3) or write (27.2.4) values, or to provide a richer set of iterator movements (27.2.5, 27.2.6, 27.2.7).
- 2 A type `X` satisfies the **Iterator** requirements if:

<sup>261</sup>) This definition applies to pointers, since pointers are iterators. The effect of dereferencing an iterator that has been invalidated is undefined.

- (2.1) — **X** satisfies the `CopyConstructible`, `CopyAssignable`, and `Destructible` requirements (20.5.3.1) and lvalues of type **X** are swappable (20.5.3.2), and
- (2.2) — the expressions in Table 94 are valid and have the indicated semantics.

Table 94 — Iterator requirements

| Expression       | Return type         | Operational semantics | Assertion/note pre-/post-condition                  |
|------------------|---------------------|-----------------------|-----------------------------------------------------|
| <code>*r</code>  | unspecified         |                       | <i>Requires:</i> <code>r</code> is dereferenceable. |
| <code>++r</code> | <code>X&amp;</code> |                       |                                                     |

### 27.2.3 Input iterators

[input.iterators]

- <sup>1</sup> A class or pointer type **X** satisfies the requirements of an input iterator for the value type **T** if **X** satisfies the `Iterator` (27.2.2) and `EqualityComparable` (Table 20) requirements and the expressions in Table 95 are valid and have the indicated semantics.
- <sup>2</sup> In Table 95, the term *the domain of ==* is used in the ordinary mathematical sense to denote the set of values over which == is (required to be) defined. This set can change over time. Each algorithm places additional requirements on the domain of == for the iterator values it uses. These requirements can be inferred from the uses that algorithm makes of == and !=. [ *Example:* The call `find(a,b,x)` is defined only if the value of `a` has the property *p* defined as follows: `b` has property *p* and a value `i` has property *p* if `(*i==x)` or if `(*i!=x` and `++i` has property *p*). — *end example* ]

Table 95 — Input iterator requirements (in addition to `Iterator`)

| Expression           | Return type                                   | Operational semantics  | Assertion/note pre-/post-condition                                                                                                                                                                                                                                                |
|----------------------|-----------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>a != b</code>  | contextually convertible to <code>bool</code> | <code>!(a == b)</code> | <i>Requires:</i> <code>(a, b)</code> is in the domain of ==.                                                                                                                                                                                                                      |
| <code>*a</code>      | reference, convertible to <b>T</b>            |                        | <i>Requires:</i> <code>a</code> is dereferenceable.<br>The expression <code>(void)*a</code> , <code>*a</code> is equivalent to <code>*a</code> .<br>If <code>a == b</code> and <code>(a, b)</code> is in the domain of == then <code>*a</code> is equivalent to <code>*b</code> . |
| <code>a-&gt;m</code> |                                               | <code>(*a).m</code>    | <i>Requires:</i> <code>a</code> is dereferenceable.                                                                                                                                                                                                                               |

Table 95 — Input iterator requirements (in addition to `Iterator`)  
(continued)

| Expression             | Return type                   | Operational semantics                           | Assertion/note pre-/post-condition                                                                                                                                                                                                                                                                       |
|------------------------|-------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>++r</code>       | <code>X&amp;</code>           |                                                 | <i>Requires:</i> <code>r</code> is dereferenceable.<br><i>Postconditions:</i> <code>r</code> is dereferenceable or <code>r</code> is past-the-end;<br>any copies of the previous value of <code>r</code> are no longer required either to be dereferenceable or to be in the domain of <code>==</code> . |
| <code>(void)r++</code> |                               |                                                 | equivalent to <code>(void)++r</code>                                                                                                                                                                                                                                                                     |
| <code>*r++</code>      | convertible to <code>T</code> | <pre>{ T tmp = *r;   ++r;   return tmp; }</pre> |                                                                                                                                                                                                                                                                                                          |

<sup>3</sup> [ *Note:* For input iterators, `a == b` does not imply `++a == ++b`. (Equality does not guarantee the substitution property or referential transparency.) Algorithms on input iterators should never attempt to pass through the same iterator twice. They should be *single pass* algorithms. Value type `T` is not required to be a `CopyAssignable` type (Table 26). These algorithms can be used with `istream` as the source of the input data through the `istream_iterator` class template. — *end note* ]

## 27.2.4 Output iterators

[output.iterators]

<sup>1</sup> A class or pointer type `X` satisfies the requirements of an output iterator if `X` satisfies the `Iterator` requirements (27.2.2) and the expressions in Table 96 are valid and have the indicated semantics.

Table 96 — Output iterator requirements (in addition to `Iterator`)

| Expression          | Return type                              | Operational semantics                          | Assertion/note pre-/post-condition                                                                                                                                                         |
|---------------------|------------------------------------------|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>*r = o</code> | result is not used                       |                                                | <i>Remarks:</i> After this operation <code>r</code> is not required to be dereferenceable.<br><i>Postconditions:</i> <code>r</code> is incrementable.                                      |
| <code>++r</code>    | <code>X&amp;</code>                      |                                                | <code>&amp;r == &amp;++r</code> .<br><i>Remarks:</i> After this operation <code>r</code> is not required to be dereferenceable.<br><i>Postconditions:</i> <code>r</code> is incrementable. |
| <code>r++</code>    | convertible to <code>const X&amp;</code> | <pre>{ X tmp = r;   ++r;   return tmp; }</pre> | <i>Remarks:</i> After this operation <code>r</code> is not required to be dereferenceable.<br><i>Postconditions:</i> <code>r</code> is incrementable.                                      |

Table 96 — Output iterator requirements (in addition to Iterator)  
(continued)

| Expression      | Return type        | Operational semantics | Assertion/note pre-/post-condition                                                                                                        |
|-----------------|--------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>*r++ = o</b> | result is not used |                       | <i>Remarks:</i> After this operation <b>r</b> is not required to be dereferenceable.<br><i>Postconditions:</i> <b>r</b> is incrementable. |

<sup>2</sup> [ *Note:* The only valid use of an operator **\*** is on the left side of the assignment statement. *Assignment through the same value of the iterator happens only once.* Algorithms on output iterators should never attempt to pass through the same iterator twice. They should be *single pass* algorithms. Equality and inequality might not be defined. Algorithms that take output iterators can be used with ostream as the destination for placing data through the `ostream_iterator` class as well as with insert iterators and insert pointers. — *end note* ]

### 27.2.5 Forward iterators

[forward.iterators]

<sup>1</sup> A class or pointer type **X** satisfies the requirements of a forward iterator if

- (1.1) — **X** satisfies the requirements of an input iterator (27.2.3),
- (1.2) — **X** satisfies the `DefaultConstructible` requirements (20.5.3.1),
- (1.3) — if **X** is a mutable iterator, **reference** is a reference to **T**; if **X** is a constant iterator, **reference** is a reference to `const T`,
- (1.4) — the expressions in Table 97 are valid and have the indicated semantics, and
- (1.5) — objects of type **X** offer the multi-pass guarantee, described below.

<sup>2</sup> The domain of `==` for forward iterators is that of iterators over the same underlying sequence. However, value-initialized iterators may be compared and shall compare equal to other value-initialized iterators of the same type. [ *Note:* Value-initialized iterators behave as if they refer past the end of the same empty sequence. — *end note* ]

<sup>3</sup> Two dereferenceable iterators **a** and **b** of type **X** offer the *multi-pass guarantee* if:

- (3.1) — **a == b** implies `++a == ++b` and
- (3.2) — **X** is a pointer type or the expression `(void)++X(a)`, `*a` is equivalent to the expression `*a`.

<sup>4</sup> [ *Note:* The requirement that **a == b** implies `++a == ++b` (which is not true for input and output iterators) and the removal of the restrictions on the number of the assignments through a mutable iterator (which applies to output iterators) allows the use of multi-pass one-directional algorithms with forward iterators. — *end note* ]

Table 97 — Forward iterator requirements (in addition to input iterator)

| Expression | Return type                              | Operational semantics                                                        | Assertion/note pre-/post-condition |
|------------|------------------------------------------|------------------------------------------------------------------------------|------------------------------------|
| <b>r++</b> | convertible to <code>const X&amp;</code> | { <code>X tmp = r;</code><br><code>++r;</code><br><code>return tmp;</code> } |                                    |

Table 97 — Forward iterator requirements (in addition to input iterator) (continued)

| Expression  | Return type | Operational semantics | Assertion/note pre-/post-condition |
|-------------|-------------|-----------------------|------------------------------------|
| <b>*r++</b> | reference   |                       |                                    |

<sup>5</sup> If **a** and **b** are equal, then either **a** and **b** are both dereferenceable or else neither is dereferenceable.

<sup>6</sup> If **a** and **b** are both dereferenceable, then **a == b** if and only if **\*a** and **\*b** are bound to the same object.

### 27.2.6 Bidirectional iterators

[bidirectional.iterators]

<sup>1</sup> A class or pointer type **X** satisfies the requirements of a bidirectional iterator if, in addition to satisfying the requirements for forward iterators, the following expressions are valid as shown in Table 98.

Table 98 — Bidirectional iterator requirements (in addition to forward iterator)

| Expression  | Return type                        | Operational semantics                                         | Assertion/note pre-/post-condition                                                                                                                                                                                             |
|-------------|------------------------------------|---------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>--r</b>  | <b>X&amp;</b>                      |                                                               | <i>Requires:</i> there exists <b>s</b> such that <b>r == ++s</b> .<br><i>Postconditions:</i> <b>r</b> is dereferenceable.<br><b>--(++r) == r</b> .<br><b>--r == --s</b> implies <b>r == s</b> .<br><b>&amp;r == &amp;--r</b> . |
| <b>r--</b>  | convertible to <b>const X&amp;</b> | { <b>X tmp = r</b> ;<br><b>--r</b> ;<br><b>return tmp</b> ; } |                                                                                                                                                                                                                                |
| <b>*r--</b> | reference                          |                                                               |                                                                                                                                                                                                                                |

<sup>2</sup> [ *Note:* Bidirectional iterators allow algorithms to move iterators backward as well as forward. — *end note* ]

### 27.2.7 Random access iterators

[random.access.iterators]

<sup>1</sup> A class or pointer type **X** satisfies the requirements of a random access iterator if, in addition to satisfying the requirements for bidirectional iterators, the following expressions are valid as shown in Table 99.

Table 99 — Random access iterator requirements (in addition to bidirectional iterator)

| Expression                               | Return type                                     | Operational semantics                                                                                                           | Assertion/note pre-/post-condition                                                                                                                              |
|------------------------------------------|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>r += n</code>                      | <code>X&amp;</code>                             | <pre>{ difference_type m = n;   if (m &gt;= 0)     while (m--)       ++r;   else     while (m++)       --r;   return r; }</pre> |                                                                                                                                                                 |
| <code>a + n</code><br><code>n + a</code> | <code>X</code>                                  | <pre>{ X tmp = a;   return tmp += n; }</pre>                                                                                    | <code>a + n == n + a.</code>                                                                                                                                    |
| <code>r -= n</code>                      | <code>X&amp;</code>                             | <code>return r += -n;</code>                                                                                                    | <i>Requires:</i> the absolute value of <code>n</code> is in the range of representable values of <code>difference_type</code> .                                 |
| <code>a - n</code>                       | <code>X</code>                                  | <pre>{ X tmp = a;   return tmp -= n; }</pre>                                                                                    |                                                                                                                                                                 |
| <code>b - a</code>                       | <code>difference_type</code>                    | <code>return n</code>                                                                                                           | <i>Requires:</i> there exists a value <code>n</code> of type <code>difference_type</code> such that <code>a + n == b</code> .<br><code>b == a + (b - a).</code> |
| <code>a[n]</code>                        | convertible to reference                        | <code>*(a + n)</code>                                                                                                           |                                                                                                                                                                 |
| <code>a &lt; b</code>                    | contextually convertible to <code>bool</code>   | <code>b - a &gt; 0</code>                                                                                                       | <code>&lt;</code> is a total ordering relation                                                                                                                  |
| <code>a &gt; b</code>                    | contextually convertible to <code>bool</code>   | <code>b &lt; a</code>                                                                                                           | <code>&gt;</code> is a total ordering relation opposite to <code>&lt;</code> .                                                                                  |
| <code>a &gt;= b</code>                   | contextually convertible to <code>bool</code>   | <code>!(a &lt; b)</code>                                                                                                        |                                                                                                                                                                 |
| <code>a &lt;= b</code>                   | contextually convertible to <code>bool</code> . | <code>!(a &gt; b)</code>                                                                                                        |                                                                                                                                                                 |

## 27.3 Header `<iterator>` synopsis

[iterator.synopsis]

```
namespace std {
 // 27.4, primitives
 template<class Iterator> struct iterator_traits;
 template<class T> struct iterator_traits<T*>;
 template<class T> struct iterator_traits<const T*>;

 struct input_iterator_tag { };
 struct output_iterator_tag { };
 struct forward_iterator_tag: public input_iterator_tag { };
 struct bidirectional_iterator_tag: public forward_iterator_tag { };
}
```



```

struct random_access_iterator_tag: public bidirectional_iterator_tag { };

// 27.4.3, iterator operations
template <class InputIterator, class Distance>
constexpr void advance(InputIterator& i, Distance n);
template <class InputIterator>
constexpr typename iterator_traits<InputIterator>::difference_type
distance(InputIterator first, InputIterator last);
template <class InputIterator>
constexpr InputIterator next(InputIterator x,
 typename iterator_traits<InputIterator>::difference_type n = 1);
template <class BidirectionalIterator>
constexpr BidirectionalIterator prev(BidirectionalIterator x,
 typename iterator_traits<BidirectionalIterator>::difference_type n = 1);

// 27.5, predefined iterators
template <class Iterator> class reverse_iterator;

template <class Iterator1, class Iterator2>
constexpr bool operator==(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator<(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator!=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator>(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator>=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator<=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);

template <class Iterator1, class Iterator2>
constexpr auto operator-(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y) ->decltype(y.base() - x.base());
template <class Iterator>
constexpr reverse_iterator<Iterator>
operator+(
 typename reverse_iterator<Iterator>::difference_type n,
 const reverse_iterator<Iterator>& x);

template <class Iterator>
constexpr reverse_iterator<Iterator> make_reverse_iterator(Iterator i);

```

```

template <class Container> class back_insert_iterator;
template <class Container>
 back_insert_iterator<Container> back_inserter(Container& x);

template <class Container> class front_insert_iterator;
template <class Container>
 front_insert_iterator<Container> front_inserter(Container& x);

template <class Container> class insert_iterator;
template <class Container>
 insert_iterator<Container> inserter(Container& x, typename Container::iterator i);

template <class Iterator> class move_iterator;
template <class Iterator1, class Iterator2>
 constexpr bool operator==(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator!=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator<(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator<=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator>(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator>=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);

template <class Iterator1, class Iterator2>
 constexpr auto operator-(
 const move_iterator<Iterator1>& x,
 const move_iterator<Iterator2>& y) -> decltype(x.base() - y.base());
template <class Iterator>
 constexpr move_iterator<Iterator> operator+(
 typename move_iterator<Iterator>::difference_type n, const move_iterator<Iterator>& x);
template <class Iterator>
 constexpr move_iterator<Iterator> make_move_iterator(Iterator i);

// 27.6, stream iterators
template <class T, class charT = char, class traits = char_traits<charT>,
 class Distance = ptrdiff_t>
class istream_iterator;
template <class T, class charT, class traits, class Distance>
 bool operator==(const istream_iterator<T, charT, traits, Distance>& x,
 const istream_iterator<T, charT, traits, Distance>& y);
template <class T, class charT, class traits, class Distance>
 bool operator!=(const istream_iterator<T, charT, traits, Distance>& x,
 const istream_iterator<T, charT, traits, Distance>& y);

template <class T, class charT = char, class traits = char_traits<charT>>

```

```

 class ostream_iterator;

template<class charT, class traits = char_traits<charT>>
 class istreambuf_iterator;
template <class charT, class traits>
 bool operator==(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);
template <class charT, class traits>
 bool operator!=(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);

template <class charT, class traits = char_traits<charT>>
 class ostreambuf_iterator;

// 27.7, range access
template <class C> constexpr auto begin(C& c) -> decltype(c.begin());
template <class C> constexpr auto begin(const C& c) -> decltype(c.begin());
template <class C> constexpr auto end(C& c) -> decltype(c.end());
template <class C> constexpr auto end(const C& c) -> decltype(c.end());
template <class T, size_t N> constexpr T* begin(T (&array)[N]) noexcept;
template <class T, size_t N> constexpr T* end(T (&array)[N]) noexcept;
template <class C> constexpr auto cbegin(const C& c) noexcept(noexcept(std::begin(c)))
 -> decltype(std::begin(c));
template <class C> constexpr auto cend(const C& c) noexcept(noexcept(std::end(c)))
 -> decltype(std::end(c));
template <class C> constexpr auto rbegin(C& c) -> decltype(c.rbegin());
template <class C> constexpr auto rbegin(const C& c) -> decltype(c.rbegin());
template <class C> constexpr auto rend(C& c) -> decltype(c.rend());
template <class C> constexpr auto rend(const C& c) -> decltype(c.rend());
template <class T, size_t N> constexpr reverse_iterator<T*> rbegin(T (&array)[N]);
template <class T, size_t N> constexpr reverse_iterator<T*> rend(T (&array)[N]);
template <class E> constexpr reverse_iterator<const E*> rbegin(initializer_list<E> il);
template <class E> constexpr reverse_iterator<const E*> rend(initializer_list<E> il);
template <class C> constexpr auto crbegin(const C& c) -> decltype(std::rbegin(c));
template <class C> constexpr auto crend(const C& c) -> decltype(std::rend(c));

// 27.8, container access
template <class C> constexpr auto size(const C& c) -> decltype(c.size());
template <class T, size_t N> constexpr size_t size(const T (&array)[N]) noexcept;
template <class C> constexpr auto empty(const C& c) -> decltype(c.empty());
template <class T, size_t N> constexpr bool empty(const T (&array)[N]) noexcept;
template <class E> constexpr bool empty(initializer_list<E> il) noexcept;
template <class C> constexpr auto data(C& c) -> decltype(c.data());
template <class C> constexpr auto data(const C& c) -> decltype(c.data());
template <class T, size_t N> constexpr T* data(T (&array)[N]) noexcept;
template <class E> constexpr const E* data(initializer_list<E> il) noexcept;
}

```

## 27.4 Iterator primitives

[iterator.primitives]

- <sup>1</sup> To simplify the task of defining iterators, the library provides several classes and functions:

### 27.4.1 Iterator traits

[iterator.traits]

- <sup>1</sup> To implement algorithms only in terms of iterators, it is often necessary to determine the value and difference types that correspond to a particular iterator type. Accordingly, it is required that if `Iterator` is the type of an iterator, the types

```

iterator_traits<Iterator>::difference_type
iterator_traits<Iterator>::value_type
iterator_traits<Iterator>::iterator_category

```

be defined as the iterator's difference type, value type and iterator category, respectively. In addition, the types

```

iterator_traits<Iterator>::reference
iterator_traits<Iterator>::pointer

```

shall be defined as the iterator's reference and pointer types, that is, for an iterator object *a*, the same type as the type of *\*a* and *a->*, respectively. In the case of an output iterator, the types

```

iterator_traits<Iterator>::difference_type
iterator_traits<Iterator>::value_type
iterator_traits<Iterator>::reference
iterator_traits<Iterator>::pointer

```

may be defined as void.

- <sup>2</sup> If *Iterator* has valid (17.8.2) member types *difference\_type*, *value\_type*, *pointer*, *reference*, and *iterator\_category*, *iterator\_traits<Iterator>* shall have the following as publicly accessible members:

```

using difference_type = typename Iterator::difference_type;
using value_type = typename Iterator::value_type;
using pointer = typename Iterator::pointer;
using reference = typename Iterator::reference;
using iterator_category = typename Iterator::iterator_category;

```

Otherwise, *iterator\_traits<Iterator>* shall have no members by any of the above names.

- <sup>3</sup> It is specialized for pointers as

```

namespace std {
 template<class T> struct iterator_traits<T*> {
 using difference_type = ptrdiff_t;
 using value_type = T;
 using pointer = T*;
 using reference = T&;
 using iterator_category = random_access_iterator_tag;
 };
}

```

and for pointers to const as

```

namespace std {
 template<class T> struct iterator_traits<const T*> {
 using difference_type = ptrdiff_t;
 using value_type = T;
 using pointer = const T*;
 using reference = const T&;
 using iterator_category = random_access_iterator_tag;
 };
}

```

- <sup>4</sup> [Example: To implement a generic *reverse* function, a C++ program can do the following:

```

template <class BidirectionalIterator>
void reverse(BidirectionalIterator first, BidirectionalIterator last) {
 typename iterator_traits<BidirectionalIterator>::difference_type n =
 distance(first, last);

```

```

--n;
while(n > 0) {
 typename iterator_traits<BidirectionalIterator>::value_type
 tmp = *first;
 *first++ = *--last;
 *last = tmp;
 n -= 2;
}
}

```

— *end example*]

## 27.4.2 Standard iterator tags

[std.iterator.tags]

- <sup>1</sup> It is often desirable for a function template specialization to find out what is the most specific category of its iterator argument, so that the function can select the most efficient algorithm at compile time. To facilitate this, the library introduces *category tag* classes which are used as compile time tags for algorithm selection. They are: `input_iterator_tag`, `output_iterator_tag`, `forward_iterator_tag`, `bidirectional_iterator_tag` and `random_access_iterator_tag`. For every iterator of type `Iterator`, `iterator_traits<Iterator>::iterator_category` shall be defined to be the most specific category tag that describes the iterator's behavior.

```

namespace std {
 struct input_iterator_tag { };
 struct output_iterator_tag { };
 struct forward_iterator_tag: public input_iterator_tag { };
 struct bidirectional_iterator_tag: public forward_iterator_tag { };
 struct random_access_iterator_tag: public bidirectional_iterator_tag { };
}

```

- <sup>2</sup> [*Example*: For a program-defined iterator `BinaryTreeIterator`, it could be included into the bidirectional iterator category by specializing the `iterator_traits` template:

```

template<class T> struct iterator_traits<BinaryTreeIterator<T>> {
 using iterator_category = bidirectional_iterator_tag;
 using difference_type = ptrdiff_t;
 using value_type = T;
 using pointer = T*;
 using reference = T&;
};

```

— *end example*]

- <sup>3</sup> [*Example*: If `evolve()` is well defined for bidirectional iterators, but can be implemented more efficiently for random access iterators, then the implementation is as follows:

```

template <class BidirectionalIterator>
inline void
evolve(BidirectionalIterator first, BidirectionalIterator last) {
 evolve(first, last,
 typename iterator_traits<BidirectionalIterator>::iterator_category());
}

template <class BidirectionalIterator>
void evolve(BidirectionalIterator first, BidirectionalIterator last,
 bidirectional_iterator_tag) {
 // more generic, but less efficient algorithm
}

```

```

template <class RandomAccessIterator>
void evolve(RandomAccessIterator first, RandomAccessIterator last,
 random_access_iterator_tag) {
 // more efficient, but less generic algorithm
}

```

— end example]

### 27.4.3 Iterator operations

[iterator.operations]

- <sup>1</sup> Since only random access iterators provide + and - operators, the library provides two function templates `advance` and `distance`. These function templates use + and - for random access iterators (and are, therefore, constant time for them); for input, forward and bidirectional iterators they use ++ to provide linear time implementations.

```

template <class InputIterator, class Distance>
constexpr void advance(InputIterator& i, Distance n);

```

- <sup>2</sup> *Requires:* n shall be negative only for bidirectional and random access iterators.

- <sup>3</sup> *Effects:* Increments (or decrements for negative n) iterator reference i by n.

```

template <class InputIterator>
constexpr typename iterator_traits<InputIterator>::difference_type
distance(InputIterator first, InputIterator last);

```

- <sup>4</sup> *Effects:* If `InputIterator` meets the requirements of random access iterator, returns (last - first); otherwise, returns the number of increments needed to get from first to last.

- <sup>5</sup> *Requires:* If `InputIterator` meets the requirements of random access iterator, last shall be reachable from first or first shall be reachable from last; otherwise, last shall be reachable from first.

```

template <class InputIterator>
constexpr InputIterator next(InputIterator x,
 typename iterator_traits<InputIterator>::difference_type n = 1);

```

- <sup>6</sup> *Effects:* Equivalent to: advance(x, n); return x;

```

template <class BidirectionalIterator>
constexpr BidirectionalIterator prev(BidirectionalIterator x,
 typename iterator_traits<BidirectionalIterator>::difference_type n = 1);

```

- <sup>7</sup> *Effects:* Equivalent to: advance(x, -n); return x;

## 27.5 Iterator adaptors

[predef.iterators]

### 27.5.1 Reverse iterators

[reverse.iterators]

- <sup>1</sup> Class template `reverse_iterator` is an iterator adaptor that iterates from the end of the sequence defined by its underlying iterator to the beginning of that sequence. The fundamental relation between a reverse iterator and its corresponding iterator i is established by the identity: `&*(reverse_iterator(i)) == &(i - 1)`.

#### 27.5.1.1 Class template reverse\_iterator

[reverse.iterator]

```

namespace std {
 template <class Iterator>
 class reverse_iterator {
 public:
 using iterator_type = Iterator;
 using iterator_category = typename iterator_traits<Iterator>::iterator_category;
 };
}

```

```

using value_type = typename iterator_traits<Iterator>::value_type;
using difference_type = typename iterator_traits<Iterator>::difference_type;
using pointer = typename iterator_traits<Iterator>::pointer;
using reference = typename iterator_traits<Iterator>::reference;

constexpr reverse_iterator();
constexpr explicit reverse_iterator(Iterator x);
template <class U> constexpr reverse_iterator(const reverse_iterator<U>& u);
template <class U> constexpr reverse_iterator& operator=(const reverse_iterator<U>& u);

constexpr Iterator base() const; // explicit
constexpr reference operator*() const;
constexpr pointer operator->() const;

constexpr reverse_iterator& operator++();
constexpr reverse_iterator operator++(int);
constexpr reverse_iterator& operator--();
constexpr reverse_iterator operator--(int);

constexpr reverse_iterator operator+ (difference_type n) const;
constexpr reverse_iterator& operator+=(difference_type n);
constexpr reverse_iterator operator- (difference_type n) const;
constexpr reverse_iterator& operator-=(difference_type n);
constexpr unspecified operator[] (difference_type n) const;
protected:
 Iterator current;
};

template <class Iterator1, class Iterator2>
constexpr bool operator==(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator<(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator!=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator>(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator>=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr bool operator<=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
constexpr auto operator-(
 const reverse_iterator<Iterator1>& x,

```

```

 const reverse_iterator<Iterator2>& y) -> decltype(y.base() - x.base());
template <class Iterator>
constexpr reverse_iterator<Iterator> operator+(
 typename reverse_iterator<Iterator>::difference_type n,
 const reverse_iterator<Iterator>& x);

template <class Iterator>
constexpr reverse_iterator<Iterator> make_reverse_iterator(Iterator i);
}

```

### 27.5.1.2 reverse\_iterator requirements [reverse.iter.requirements]

- <sup>1</sup> The template parameter `Iterator` shall meet all the requirements of a Bidirectional Iterator (27.2.6).
- <sup>2</sup> Additionally, `Iterator` shall meet the requirements of a random access iterator (27.2.7) if any of the members `operator+` (27.5.1.3.8), `operator-` (27.5.1.3.10), `operator+=` (27.5.1.3.9), `operator-=` (27.5.1.3.11), `operator[]` (27.5.1.3.12), or the non-member operators `operator<` (27.5.1.3.14), `operator>` (27.5.1.3.16), `operator<=` (27.5.1.3.18), `operator>=` (27.5.1.3.17), `operator-` (27.5.1.3.19) or `operator+` (27.5.1.3.20) are referenced in a way that requires instantiation (17.7.1).

### 27.5.1.3 reverse\_iterator operations [reverse.iter.ops]

#### 27.5.1.3.1 reverse\_iterator constructor [reverse.iter.cons]

```
constexpr reverse_iterator();
```

- <sup>1</sup> *Effects:* Value-initializes `current`. Iterator operations applied to the resulting iterator have defined behavior if and only if the corresponding operations are defined on a value-initialized iterator of type `Iterator`.

```
constexpr explicit reverse_iterator(Iterator x);
```

- <sup>2</sup> *Effects:* Initializes `current` with `x`.

```
template <class U> constexpr reverse_iterator(const reverse_iterator<U>& u);
```

- <sup>3</sup> *Effects:* Initializes `current` with `u.current`.

#### 27.5.1.3.2 reverse\_iterator::operator= [reverse.iter.op=]

```
template <class U>
constexpr reverse_iterator&
operator=(const reverse_iterator<U>& u);
```

- <sup>1</sup> *Effects:* Assigns `u.base()` to `current`.
- <sup>2</sup> *Returns:* `*this`.

#### 27.5.1.3.3 Conversion [reverse.iter.conv]

```
constexpr Iterator base() const; // explicit
```

- <sup>1</sup> *Returns:* `current`.

#### 27.5.1.3.4 operator\* [reverse.iter.op.star]

```
constexpr reference operator*() const;
```

- <sup>1</sup> *Effects:* As if by:

```

 Iterator tmp = current;
 return *--tmp;
```



**27.5.1.3.5 operator->** [reverse.iter.opref]

```
constexpr pointer operator->() const;
```

1 *Returns:* addressof(operator\*()).

**27.5.1.3.6 operator++** [reverse.iter.op++]

```
constexpr reverse_iterator& operator++();
```

1 *Effects:* As if by: --current;

2 *Returns:* \*this.

```
constexpr reverse_iterator operator++(int);
```

3 *Effects:* As if by:

```
reverse_iterator tmp = *this;
--current;
return tmp;
```

**27.5.1.3.7 operator--** [reverse.iter.op--]

```
constexpr reverse_iterator& operator--();
```

1 *Effects:* As if by ++current.

2 *Returns:* \*this.

```
constexpr reverse_iterator operator--(int);
```

3 *Effects:* As if by:

```
reverse_iterator tmp = *this;
++current;
return tmp;
```

**27.5.1.3.8 operator+** [reverse.iter.op+]

```
constexpr reverse_iterator operator+(difference_type n) const;
```

1 *Returns:* reverse\_iterator(current-n).

**27.5.1.3.9 operator+=** [reverse.iter.op+=]

```
constexpr reverse_iterator& operator+=(difference_type n);
```

1 *Effects:* As if by: current -= n;

2 *Returns:* \*this.

**27.5.1.3.10 operator-** [reverse.iter.op-]

```
constexpr reverse_iterator operator-(difference_type n) const;
```

1 *Returns:* reverse\_iterator(current+n).

**27.5.1.3.11 operator-=** [reverse.iter.op-=]

```
constexpr reverse_iterator& operator-=(difference_type n);
```

1 *Effects:* As if by: current += n;

2 *Returns:* \*this.

**27.5.1.3.12 operator[]**

[reverse.iter.opindex]

```
constexpr unspecified operator[](difference_type n) const;
```

<sup>1</sup> *Returns:* current[-n-1].

**27.5.1.3.13 operator==**

[reverse.iter.op==]

```
template <class Iterator1, class Iterator2>
constexpr bool operator==(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current == y.current.

**27.5.1.3.14 operator<**

[reverse.iter.op&lt;]

```
template <class Iterator1, class Iterator2>
constexpr bool operator<(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current > y.current.

**27.5.1.3.15 operator!=**

[reverse.iter.op!=]

```
template <class Iterator1, class Iterator2>
constexpr bool operator!=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current != y.current.

**27.5.1.3.16 operator>**

[reverse.iter.op&gt;]

```
template <class Iterator1, class Iterator2>
constexpr bool operator>(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current < y.current.

**27.5.1.3.17 operator>=**

[reverse.iter.op&gt;=]

```
template <class Iterator1, class Iterator2>
constexpr bool operator>=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current <= y.current.

**27.5.1.3.18 operator<=**

[reverse.iter.op&lt;=]

```
template <class Iterator1, class Iterator2>
constexpr bool operator<=(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y);
```

<sup>1</sup> *Returns:* x.current >= y.current.

**27.5.1.3.19 operator-**

[reverse.iter.opdiff]

```
template <class Iterator1, class Iterator2>
constexpr auto operator-(
 const reverse_iterator<Iterator1>& x,
 const reverse_iterator<Iterator2>& y) -> decltype(y.base() - x.base());
```

<sup>1</sup> *Returns:* y.current - x.current.

**27.5.1.3.20 operator+**

[reverse.iter.opsum]

```
template <class Iterator>
constexpr reverse_iterator<Iterator> operator+(
 typename reverse_iterator<Iterator>::difference_type n,
 const reverse_iterator<Iterator>& x);
```

<sup>1</sup> *Returns:* reverse\_iterator<Iterator> (x.current - n).

**27.5.1.3.21 Non-member function make\_reverse\_iterator()**

[reverse.iter.make]

```
template <class Iterator>
constexpr reverse_iterator<Iterator> make_reverse_iterator(Iterator i);
```

<sup>1</sup> *Returns:* reverse\_iterator<Iterator>(i).

**27.5.2 Insert iterators**

[insert.iterators]

<sup>1</sup> To make it possible to deal with insertion in the same way as writing into an array, a special kind of iterator adaptors, called *insert iterators*, are provided in the library. With regular iterator classes,

```
while (first != last) *result++ = *first++;
```

causes a range [first, last) to be copied into a range starting with result. The same code with **result** being an insert iterator will insert corresponding elements into the container. This device allows all of the copying algorithms in the library to work in the *insert mode* instead of the *regular overwrite mode*.

<sup>2</sup> An insert iterator is constructed from a container and possibly one of its iterators pointing to where insertion takes place if it is neither at the beginning nor at the end of the container. Insert iterators satisfy the requirements of output iterators. **operator\*** returns the insert iterator itself. The assignment **operator=(const T& x)** is defined on insert iterators to allow writing into them, it inserts x right before where the insert iterator is pointing. In other words, an insert iterator is like a cursor pointing into the container where the insertion takes place. **back\_insert\_iterator** inserts elements at the end of a container, **front\_insert\_iterator** inserts elements at the beginning of a container, and **insert\_iterator** inserts elements where the iterator points to in a container. **back\_inserter**, **front\_inserter**, and **inserter** are three functions making the insert iterators out of a container.

**27.5.2.1 Class template back\_insert\_iterator**

[back.insert.iterator]

```
namespace std {
 template <class Container>
 class back_insert_iterator {
 protected:
 Container* container;

 public:
 using iterator_category = output_iterator_tag;
 using value_type = void;
 using difference_type = void;
 using pointer = void;
 using reference = void;
```

```

using container_type = Container;

explicit back_insert_iterator(Container& x);
back_insert_iterator& operator=(const typename Container::value_type& value);
back_insert_iterator& operator=(typename Container::value_type&& value);

back_insert_iterator& operator*();
back_insert_iterator& operator++();
back_insert_iterator operator++(int);
};

template <class Container>
 back_insert_iterator<Container> back_inserter(Container& x);
}

```

## 27.5.2.2 back\_insert\_iterator operations [back.insert.iter.ops]

### 27.5.2.2.1 back\_insert\_iterator constructor [back.insert.iter.cons]

```
explicit back_insert_iterator(Container& x);
```

1 *Effects:* Initializes container with addressof(x).

### 27.5.2.2.2 back\_insert\_iterator::operator= [back.insert.iter.op=]

```
back_insert_iterator& operator=(const typename Container::value_type& value);
```

1 *Effects:* As if by: container->push\_back(value);

2 *Returns:* \*this.

```
back_insert_iterator& operator=(typename Container::value_type&& value);
```

3 *Effects:* As if by: container->push\_back(std::move(value));

4 *Returns:* \*this.

### 27.5.2.2.3 back\_insert\_iterator::operator\* [back.insert.iter.op\*]

```
back_insert_iterator& operator*();
```

1 *Returns:* \*this.

### 27.5.2.2.4 back\_insert\_iterator::operator++ [back.insert.iter.op++]

```
back_insert_iterator& operator++();
```

```
back_insert_iterator operator++(int);
```

1 *Returns:* \*this.

### 27.5.2.2.5 back\_inserter [back.inserter]

```
template <class Container>
 back_insert_iterator<Container> back_inserter(Container& x);
```

1 *Returns:* back\_insert\_iterator<Container>(x).

## 27.5.2.3 Class template front\_insert\_iterator [front.insert.iterator]

```

namespace std {
 template <class Container>
 class front_insert_iterator {
 protected:
 Container* container;

```

```

public:
 using iterator_category = output_iterator_tag;
 using value_type = void;
 using difference_type = void;
 using pointer = void;
 using reference = void;
 using container_type = Container;

 explicit front_insert_iterator(Container& x);
 front_insert_iterator& operator=(const typename Container::value_type& value);
 front_insert_iterator& operator=(typename Container::value_type&& value);

 front_insert_iterator& operator*();
 front_insert_iterator& operator++();
 front_insert_iterator operator++(int);
};

template <class Container>
 front_insert_iterator<Container> front_inserter(Container& x);
}

```

**27.5.2.4 front\_insert\_iterator operations** [front.insert.iter.ops]

**27.5.2.4.1 front\_insert\_iterator constructor** [front.insert.iter.cons]

```
explicit front_insert_iterator(Container& x);
```

1 *Effects:* Initializes container with `addressof(x)`.

**27.5.2.4.2 front\_insert\_iterator::operator=** [front.insert.iter.op=]

```
front_insert_iterator& operator=(const typename Container::value_type& value);
```

1 *Effects:* As if by: `container->push_front(value)`;

2 *Returns:* `*this`.

```
front_insert_iterator& operator=(typename Container::value_type&& value);
```

3 *Effects:* As if by: `container->push_front(std::move(value))`;

4 *Returns:* `*this`.

**27.5.2.4.3 front\_insert\_iterator::operator\*** [front.insert.iter.op\*]

```
front_insert_iterator& operator*();
```

1 *Returns:* `*this`.

**27.5.2.4.4 front\_insert\_iterator::operator++** [front.insert.iter.op++]

```
front_insert_iterator& operator++();
```

```
front_insert_iterator operator++(int);
```

1 *Returns:* `*this`.

**27.5.2.4.5 front\_inserter** [front.inserter]

```
template <class Container>
```

```
 front_insert_iterator<Container> front_inserter(Container& x);
```

1 *Returns:* `front_insert_iterator<Container>(x)`.

**27.5.2.5 Class template insert\_iterator**

[insert.iterator]

```

namespace std {
 template <class Container>
 class insert_iterator {
 protected:
 Container* container;
 typename Container::iterator iter;

 public:
 using iterator_category = output_iterator_tag;
 using value_type = void;
 using difference_type = void;
 using pointer = void;
 using reference = void;
 using container_type = Container;

 insert_iterator(Container& x, typename Container::iterator i);
 insert_iterator& operator=(const typename Container::value_type& value);
 insert_iterator& operator=(typename Container::value_type&& value);

 insert_iterator& operator*();
 insert_iterator& operator++();
 insert_iterator& operator++(int);
 };

 template <class Container>
 insert_iterator<Container> inserter(Container& x, typename Container::iterator i);
}

```

**27.5.2.6 insert\_iterator operations**

[insert.iter.ops]

**27.5.2.6.1 insert\_iterator constructor**

[insert.iter.cons]

```
insert_iterator(Container& x, typename Container::iterator i);
```

1 *Effects:* Initializes container with addressof(x) and iter with i.

**27.5.2.6.2 insert\_iterator::operator=**

[insert.iter.op=]

```
insert_iterator& operator=(const typename Container::value_type& value);
```

1 *Effects:* As if by:

```
 iter = container->insert(iter, value);
 ++iter;
```

2 *Returns:* \*this.

```
insert_iterator& operator=(typename Container::value_type&& value);
```

3 *Effects:* As if by:

```
 iter = container->insert(iter, std::move(value));
 ++iter;
```

4 *Returns:* \*this.

**27.5.2.6.3 insert\_iterator::operator\***

[insert.iter.op\*]

```
insert_iterator& operator*();
```

1 *Returns:* \*this.

**27.5.2.6.4 insert\_iterator::operator++****[insert.iter.op++]**

```
insert_iterator& operator++();
insert_iterator& operator++(int);
```

<sup>1</sup> *Returns: \*this.*

**27.5.2.6.5 inserter****[inserter]**

```
template <class Container>
 insert_iterator<Container> inserter(Container& x, typename Container::iterator i);
```

<sup>1</sup> *Returns: insert\_iterator<Container>(x, i).*

**27.5.3 Move iterators****[move.iterators]**

<sup>1</sup> Class template `move_iterator` is an iterator adaptor with the same behavior as the underlying iterator except that its indirection operator implicitly converts the value returned by the underlying iterator's indirection operator to an rvalue. Some generic algorithms can be called with move iterators to replace copying with moving.

<sup>2</sup> [Example:

```
list<string> s;
// populate the list s
vector<string> v1(s.begin(), s.end()); // copies strings into v1
vector<string> v2(make_move_iterator(s.begin()),
 make_move_iterator(s.end())); // moves strings into v2
```

— end example]

**27.5.3.1 Class template move\_iterator****[move.iterator]**

```
namespace std {
 template <class Iterator>
 class move_iterator {
 public:
 using iterator_type = Iterator;
 using iterator_category = typename iterator_traits<Iterator>::iterator_category;
 using value_type = typename iterator_traits<Iterator>::value_type;
 using difference_type = typename iterator_traits<Iterator>::difference_type;
 using pointer = Iterator;
 using reference = see below;

 constexpr move_iterator();
 constexpr explicit move_iterator(Iterator i);
 template <class U> constexpr move_iterator(const move_iterator<U>& u);
 template <class U> constexpr move_iterator& operator=(const move_iterator<U>& u);

 constexpr iterator_type base() const;
 constexpr reference operator*() const;
 constexpr pointer operator->() const;

 constexpr move_iterator& operator++();
 constexpr move_iterator operator++(int);
 constexpr move_iterator& operator--();
 constexpr move_iterator operator--(int);

 constexpr move_iterator operator+(difference_type n) const;
 constexpr move_iterator& operator+=(difference_type n);
```

```

 constexpr move_iterator operator-(difference_type n) const;
 constexpr move_iterator& operator--(difference_type n);
 constexpr unspecified operator[](difference_type n) const;

private:
 Iterator current; // exposition only
};

template <class Iterator1, class Iterator2>
 constexpr bool operator==(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator!=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator<(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator<=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator>(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
template <class Iterator1, class Iterator2>
 constexpr bool operator>=(
 const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);

template <class Iterator1, class Iterator2>
 constexpr auto operator-(
 const move_iterator<Iterator1>& x,
 const move_iterator<Iterator2>& y) -> decltype(x.base() - y.base());
template <class Iterator>
 constexpr move_iterator<Iterator> operator+(
 typename move_iterator<Iterator>::difference_type n, const move_iterator<Iterator>& x);
template <class Iterator>
 constexpr move_iterator<Iterator> make_move_iterator(Iterator i);
}

```

- <sup>1</sup> Let  $R$  denote `iterator_traits<Iterator>::reference`. If `is_reference_v<R>` is true, the template specialization `move_iterator<Iterator>` shall define the nested type named `reference` as a synonym for `remove_reference_t<R>&&`, otherwise as a synonym for  $R$ .

### 27.5.3.2 `move_iterator` requirements

[move.iter.requirements]

- <sup>1</sup> The template parameter `Iterator` shall meet the requirements of an input iterator (27.2.3). Additionally, if any of the bidirectional or random access traversal functions are instantiated, the template parameter shall meet the requirements for a Bidirectional Iterator (27.2.6) or a Random Access Iterator (27.2.7), respectively.

### 27.5.3.3 `move_iterator` operations

[move.iter.ops]

#### 27.5.3.3.1 `move_iterator` constructors

[move.iter.op.const]

```
constexpr move_iterator();
```

- <sup>1</sup> *Effects:* Constructs a `move_iterator`, value-initializing `current`. Iterator operations applied to the resulting iterator have defined behavior if and only if the corresponding operations are defined on a value-initialized iterator of type `Iterator`.



```
constexpr explicit move_iterator(Iterator i);
```

2     *Effects:* Constructs a `move_iterator`, initializing `current` with `i`.

```
template <class U> constexpr move_iterator(const move_iterator<U>& u);
```

3     *Effects:* Constructs a `move_iterator`, initializing `current` with `u.base()`.

4     *Requires:* `U` shall be convertible to `Iterator`.

**27.5.3.3.2**   `move_iterator::operator=` [move.iter.op=]

```
template <class U> constexpr move_iterator& operator=(const move_iterator<U>& u);
```

1     *Effects:* Assigns `u.base()` to `current`.

2     *Requires:* `U` shall be convertible to `Iterator`.

**27.5.3.3.3**   `move_iterator` conversion [move.iter.op.conv]

```
constexpr Iterator base() const;
```

1     *Returns:* `current`.

**27.5.3.3.4**   `move_iterator::operator*` [move.iter.op.star]

```
constexpr reference operator*() const;
```

1     *Returns:* `static_cast<reference>(*current)`.

**27.5.3.3.5**   `move_iterator::operator->` [move.iter.op.ref]

```
constexpr pointer operator->() const;
```

1     *Returns:* `current`.

**27.5.3.3.6**   `move_iterator::operator++` [move.iter.op.incr]

```
constexpr move_iterator& operator++();
```

1     *Effects:* As if by `++current`.

2     *Returns:* `*this`.

```
constexpr move_iterator operator++(int);
```

3     *Effects:* As if by:

```
 move_iterator tmp = *this;
 ++current;
 return tmp;
```

**27.5.3.3.7**   `move_iterator::operator--` [move.iter.op.decr]

```
constexpr move_iterator& operator--();
```

1     *Effects:* As if by `--current`.

2     *Returns:* `*this`.

```
constexpr move_iterator operator--(int);
```

3     *Effects:* As if by:

```
 move_iterator tmp = *this;
 --current;
 return tmp;
```

**27.5.3.3.8 move\_iterator::operator+ [move.iter.op.+]**

```
constexpr move_iterator operator+(difference_type n) const;
```

1 *Returns:* move\_iterator(current + n).

**27.5.3.3.9 move\_iterator::operator+= [move.iter.op.+=]**

```
constexpr move_iterator& operator+=(difference_type n);
```

1 *Effects:* As if by: current += n;

2 *Returns:* \*this.

**27.5.3.3.10 move\_iterator::operator- [move.iter.op.-]**

```
constexpr move_iterator operator-(difference_type n) const;
```

1 *Returns:* move\_iterator(current - n).

**27.5.3.3.11 move\_iterator::operator-= [move.iter.op.-=]**

```
constexpr move_iterator& operator-=(difference_type n);
```

1 *Effects:* As if by: current -= n;

2 *Returns:* \*this.

**27.5.3.3.12 move\_iterator::operator[] [move.iter.op.index]**

```
constexpr unspecified operator[](difference_type n) const;
```

1 *Returns:* std::move(current[n]).

**27.5.3.3.13 move\_iterator comparisons [move.iter.op.comp]**

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator==(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

1 *Returns:* x.base() == y.base().

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator!=(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

2 *Returns:* !(x == y).

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator<(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

3 *Returns:* x.base() < y.base().

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator<=(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

4 *Returns:* !(y < x).

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator>(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

5 *Returns:* y < x.

```
template <class Iterator1, class Iterator2>
```

```
constexpr bool operator>=(const move_iterator<Iterator1>& x, const move_iterator<Iterator2>& y);
```

6 *Returns:* !(x < y).

**27.5.3.3.14 move\_iterator non-member functions****[move.iter.nonmember]**

```
template <class Iterator1, class Iterator2>
constexpr auto operator-(
 const move_iterator<Iterator1>& x,
 const move_iterator<Iterator2>& y) -> decltype(x.base() - y.base());
```

1 *Returns:* x.base() - y.base().

```
template <class Iterator>
constexpr move_iterator<Iterator> operator+(
 typename move_iterator<Iterator>::difference_type n, const move_iterator<Iterator>& x);
```

2 *Returns:* x + n.

```
template <class Iterator>
constexpr move_iterator<Iterator> make_move_iterator(Iterator i);
```

3 *Returns:* move\_iterator<Iterator>(i).

**27.6 Stream iterators****[stream.iterators]**

- 1 To make it possible for algorithmic templates to work directly with input/output streams, appropriate iterator-like class templates are provided.

[ *Example:*

```
partial_sum(istream_iterator<double, char>(cin),
 istream_iterator<double, char>(),
 ostream_iterator<double, char>(cout, "\n"));
```

reads a file containing floating-point numbers from cin, and prints the partial sums onto cout. — *end example*]

**27.6.1 Class template istream\_iterator****[istream.iterator]**

- 1 The class template `istream_iterator` is an input iterator (27.2.3) that reads (using `operator>>`) successive elements from the input stream for which it was constructed. After it is constructed, and every time `++` is used, the iterator reads and stores a value of `T`. If the iterator fails to read and store a value of `T` (`fail()` on the stream returns `true`), the iterator becomes equal to the *end-of-stream* iterator value. The constructor with no arguments `istream_iterator()` always constructs an end-of-stream input iterator object, which is the only legitimate iterator to be used for the end condition. The result of `operator*` on an end-of-stream iterator is not defined. For any other iterator value a `const T&` is returned. The result of `operator->` on an end-of-stream iterator is not defined. For any other iterator value a `const T*` is returned. The behavior of a program that applies `operator++()` to an end-of-stream iterator is undefined. It is impossible to store things into istream iterators. The type `T` shall meet the `DefaultConstructible`, `CopyConstructible`, and `CopyAssignable` requirements.
- 2 Two end-of-stream iterators are always equal. An end-of-stream iterator is not equal to a non-end-of-stream iterator. Two non-end-of-stream iterators are equal when they are constructed from the same stream.

```
namespace std {
 template <class T, class charT = char, class traits = char_traits<charT>,
 class Distance = ptrdiff_t>
 class istream_iterator {
 public:
 using iterator_category = input_iterator_tag;
 using value_type = T;
 using difference_type = Distance;
 using pointer = const T*;
```

```

using reference = const T&;
using char_type = charT;
using traits_type = traits;
using istream_type = basic_istream<charT,traits>;

constexpr istream_iterator();
istream_iterator(istream_type& s);
istream_iterator(const istream_iterator& x) = default;
~istream_iterator() = default;

const T& operator*() const;
const T* operator->() const;
istream_iterator& operator++();
istream_iterator operator++(int);
private:
 basic_istream<charT,traits>* in_stream; // exposition only
 T value; // exposition only
};

template <class T, class charT, class traits, class Distance>
 bool operator==(const istream_iterator<T,charT,traits,Distance>& x,
 const istream_iterator<T,charT,traits,Distance>& y);
template <class T, class charT, class traits, class Distance>
 bool operator!=(const istream_iterator<T,charT,traits,Distance>& x,
 const istream_iterator<T,charT,traits,Distance>& y);
}

```

#### 27.6.1.1 istream\_iterator constructors and destructor

[istream.iterator.cons]

```
constexpr istream_iterator();
```

1 *Effects:* Constructs the end-of-stream iterator. If `is_trivially_default_constructible_v<T>` is `true`, then this constructor is a constexpr constructor.

2 *Postconditions:* `in_stream == 0`.

```
istream_iterator(istream_type& s);
```

3 *Effects:* Initializes `in_stream` with `addressof(s)`. `value` may be initialized during construction or the first time it is referenced.

4 *Postconditions:* `in_stream == addressof(s)`.

```
istream_iterator(const istream_iterator& x) = default;
```

5 *Effects:* Constructs a copy of `x`. If `is_trivially_copy_constructible_v<T>` is `true`, then this constructor is a trivial copy constructor.

6 *Postconditions:* `in_stream == x.in_stream`.

```
~istream_iterator() = default;
```

7 *Effects:* The iterator is destroyed. If `is_trivially_destructible_v<T>` is `true`, then this destructor is a trivial destructor.

#### 27.6.1.2 istream\_iterator operations

[istream.iterator.ops]

```
const T& operator*() const;
```

1 *Returns:* `value`.

```

const T* operator->() const;
2 Returns: addressof(operator*()).

istream_iterator& operator++();
3 Requires: in_stream != 0.
4 Effects: As if by: *in_stream >> value;
5 Returns: *this.

istream_iterator operator++(int);
6 Requires: in_stream != 0.
7 Effects: As if by:
 istream_iterator tmp = *this;
 *in_stream >> value;
 return (tmp);

template <class T, class charT, class traits, class Distance>
 bool operator==(const istream_iterator<T,charT,traits,Distance>& x,
 const istream_iterator<T,charT,traits,Distance>& y);
8 Returns: x.in_stream == y.in_stream.

template <class T, class charT, class traits, class Distance>
 bool operator!=(const istream_iterator<T,charT,traits,Distance>& x,
 const istream_iterator<T,charT,traits,Distance>& y);
9 Returns: !(x == y)

```

## 27.6.2 Class template ostream\_iterator

[ostream.iterator]

1 ostream\_iterator writes (using operator<<) successive elements onto the output stream from which it was constructed. If it was constructed with charT\* as a constructor argument, this string, called a *delimiter string*, is written to the stream after every T is written. It is not possible to get a value out of the output iterator. Its only use is as an output iterator in situations like

```

while (first != last)
 *result++ = *first++;

```

2 ostream\_iterator is defined as:

```

namespace std {
 template <class T, class charT = char, class traits = char_traits<charT>>
 class ostream_iterator {
 public:
 using iterator_category = output_iterator_tag;
 using value_type = void;
 using difference_type = void;
 using pointer = void;
 using reference = void;
 using char_type = charT;
 using traits_type = traits;
 using ostream_type = basic_ostream<charT,traits>;

 ostream_iterator(ostream_type& s);
 ostream_iterator(ostream_type& s, const charT* delimiter);
 ostream_iterator(const ostream_iterator& x);
 ~ostream_iterator();
 };

```

```

 ostream_iterator& operator=(const T& value);

 ostream_iterator& operator*();
 ostream_iterator& operator++();
 ostream_iterator& operator++(int);
private:
 basic_ostream<charT,traits>* out_stream; // exposition only
 const charT* delim; // exposition only
};
}

```

### 27.6.2.1 ostream\_iterator constructors and destructor [ostream.iterator.cons.des]

```
ostream_iterator(ostream_type& s);
```

- 1 *Effects:* Initializes `out_stream` with `addressof(s)` and `delim` with `null`.

```
ostream_iterator(ostream_type& s, const charT* delimiter);
```

- 2 *Effects:* Initializes `out_stream` with `addressof(s)` and `delim` with `delimiter`.

```
ostream_iterator(const ostream_iterator& x);
```

- 3 *Effects:* Constructs a copy of `x`.

```
~ostream_iterator();
```

- 4 *Effects:* The iterator is destroyed.

### 27.6.2.2 ostream\_iterator operations [ostream.iterator.ops]

```
ostream_iterator& operator=(const T& value);
```

- 1 *Effects:* As if by:

```

 *out_stream << value;
 if (delim != 0)
 *out_stream << delim;
 return *this;

```

```
ostream_iterator& operator*();
```

- 2 *Returns:* `*this`.

```

ostream_iterator& operator++();
ostream_iterator& operator++(int);

```

- 3 *Returns:* `*this`.

### 27.6.3 Class template istreambuf\_iterator [istreambuf.iterator]

- 1 The class template `istreambuf_iterator` defines an input iterator (27.2.3) that reads successive *characters* from the streambuf for which it was constructed. `operator*` provides access to the current input character, if any. Each time `operator++` is evaluated, the iterator advances to the next input character. If the end of stream is reached (`streambuf_type::sgetc()` returns `traits::eof()`), the iterator becomes equal to the *end-of-stream* iterator value. The default constructor `istreambuf_iterator()` and the constructor `istreambuf_iterator(0)` both construct an end-of-stream iterator object suitable for use as an end-of-range. All specializations of `istreambuf_iterator` shall have a trivial copy constructor, a `constexpr` default constructor, and a trivial destructor.
- 2 The result of `operator*()` on an end-of-stream iterator is undefined. For any other iterator value a `char_type` value is returned. It is impossible to assign a character via an input iterator.

```

namespace std {
 template<class charT, class traits = char_traits<charT>>
 class istreambuf_iterator {
 public:
 using iterator_category = input_iterator_tag;
 using value_type = charT;
 using difference_type = typename traits::off_type;
 using pointer = unspecified;
 using reference = charT;
 using char_type = charT;
 using traits_type = traits;
 using int_type = typename traits::int_type;
 using streambuf_type = basic_streambuf<charT,traits>;
 using istream_type = basic_istream<charT,traits>;

 class proxy; // exposition only

 constexpr istreambuf_iterator() noexcept;
 istreambuf_iterator(const istreambuf_iterator&) noexcept = default;
 ~istreambuf_iterator() = default;
 istreambuf_iterator(istream_type& s) noexcept;
 istreambuf_iterator(streambuf_type* s) noexcept;
 istreambuf_iterator(const proxy& p) noexcept;
 charT operator*() const;
 istreambuf_iterator& operator++();
 proxy operator++(int);
 bool equal(const istreambuf_iterator& b) const;
 private:
 streambuf_type* sbuf_; // exposition only
 };

 template <class charT, class traits>
 bool operator==(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);
 template <class charT, class traits>
 bool operator!=(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);
}

```

### 27.6.3.1 Class template `istreambuf_iterator::proxy`

[istreambuf.iterator.proxy]

```

namespace std {
 template <class charT, class traits = char_traits<charT>>
 class istreambuf_iterator<charT, traits>::proxy { // exposition only
 charT keep_;
 basic_streambuf<charT,traits>* sbuf_;
 proxy(charT c, basic_streambuf<charT,traits>* sbuf)
 : keep_(c), sbuf_(sbuf) { }
 public:
 charT operator*() { return keep_; }
 };
}

```

- <sup>1</sup> Class `istreambuf_iterator<charT,traits>::proxy` is for exposition only. An implementation is permitted to provide equivalent functionality without providing a class with this name. Class `istreambuf_iterator<charT, traits>::proxy` provides a temporary placeholder as the return value of the post-

increment operator (`operator++`). It keeps the character pointed to by the previous value of the iterator for some possible future access to get the character.

### 27.6.3.2 `istreambuf_iterator` constructors [istreambuf.iterator.cons]

- 1 For each `istreambuf_iterator` constructor in this section, an end-of-stream iterator is constructed if and only if the exposition-only member `sbuf_` is initialized with a null pointer value.

```
constexpr istreambuf_iterator() noexcept;
```

- 2 *Effects:* Initializes `sbuf_` with `nullptr`.

```
istreambuf_iterator(istream_type& s) noexcept;
```

- 3 *Effects:* Initializes `sbuf_` with `s.rdbuf()`.

```
istreambuf_iterator(streambuf_type* s) noexcept;
```

- 4 *Effects:* Initializes `sbuf_` with `s`.

```
istreambuf_iterator(const proxy& p) noexcept;
```

- 5 *Effects:* Initializes `sbuf_` with `p.sbuf_`.

### 27.6.3.3 `istreambuf_iterator` operations [istreambuf.iterator.ops]

```
charT operator*() const
```

- 1 *Returns:* The character obtained via the `streambuf` member `sbuf_` `->sgetc()`.

```
istreambuf_iterator& operator++();
```

- 2 *Effects:* As if by `sbuf_` `->sbumpc()`.

- 3 *Returns:* `*this`.

```
proxy operator++(int);
```

- 4 *Returns:* `proxy(sbuf_` `->sbumpc(), sbuf_)`.

```
bool equal(const istreambuf_iterator& b) const;
```

- 5 *Returns:* `true` if and only if both iterators are at end-of-stream, or neither is at end-of-stream, regardless of what `streambuf` object they use.

```
template <class charT, class traits>
 bool operator==(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);
```

- 6 *Returns:* `a.equal(b)`.

```
template <class charT, class traits>
 bool operator!=(const istreambuf_iterator<charT,traits>& a,
 const istreambuf_iterator<charT,traits>& b);
```

- 7 *Returns:* `!a.equal(b)`.

### 27.6.4 Class template `ostreambuf_iterator` [ostreambuf.iterator]

```
namespace std {
 template <class charT, class traits = char_traits<charT>>
 class ostreambuf_iterator {
 public:
 using iterator_category = output_iterator_tag;
 using value_type = void;
```



```

 using difference_type = void;
 using pointer = void;
 using reference = void;
 using char_type = charT;
 using traits_type = traits;
 using streambuf_type = basic_streambuf<charT,traits>;
 using ostream_type = basic_ostream<charT,traits>;

 ostreambuf_iterator(ostream_type& s) noexcept;
 ostreambuf_iterator(streambuf_type* s) noexcept;
 ostreambuf_iterator& operator=(charT c);

 ostreambuf_iterator& operator*();
 ostreambuf_iterator& operator++();
 ostreambuf_iterator& operator++(int);
 bool failed() const noexcept;

 private:
 streambuf_type* sbuf_; // exposition only
 };
}

```

- <sup>1</sup> The class template `ostreambuf_iterator` writes successive *characters* onto the output stream from which it was constructed. It is not possible to get a character value out of the output iterator.

#### 27.6.4.1 ostreambuf\_iterator constructors

[ostreambuf.iter.cons]

```
ostreambuf_iterator(ostream_type& s) noexcept;
```

- <sup>1</sup> *Requires:* `s.rdbuf()` shall not be a null pointer.

- <sup>2</sup> *Effects:* Initializes `sbuf_` with `s.rdbuf()`.

```
ostreambuf_iterator(streambuf_type* s) noexcept;
```

- <sup>3</sup> *Requires:* `s` shall not be a null pointer.

- <sup>4</sup> *Effects:* Initializes `sbuf_` with `s`.

#### 27.6.4.2 ostreambuf\_iterator operations

[ostreambuf.iter.ops]

```
ostreambuf_iterator& operator=(charT c);
```

- <sup>1</sup> *Effects:* If `failed()` yields false, calls `sbuf_>sputc(c)`; otherwise has no effect.

- <sup>2</sup> *Returns:* `*this`.

```
ostreambuf_iterator& operator*();
```

- <sup>3</sup> *Returns:* `*this`.

```
ostreambuf_iterator& operator++();
```

```
ostreambuf_iterator& operator++(int);
```

- <sup>4</sup> *Returns:* `*this`.

```
bool failed() const noexcept;
```

- <sup>5</sup> *Returns:* true if in any prior use of member `operator=`, the call to `sbuf_>sputc()` returned `traits::eof()`; or false otherwise.

## 27.7 Range access

[iterator.range]

- <sup>1</sup> In addition to being available via inclusion of the `<iterator>` header, the function templates in 27.7 are available when any of the following headers are included: `<array>`, `<deque>`, `<forward_list>`, `<list>`, `<map>`, `<regex>`, `<set>`, `<string>`, `<string_view>`, `<unordered_map>`, `<unordered_set>`, and `<vector>`.

```
template <class C> constexpr auto begin(C& c) -> decltype(c.begin());
template <class C> constexpr auto begin(const C& c) -> decltype(c.begin());
```

- <sup>2</sup> *Returns:* `c.begin()`.

```
template <class C> constexpr auto end(C& c) -> decltype(c.end());
template <class C> constexpr auto end(const C& c) -> decltype(c.end());
```

- <sup>3</sup> *Returns:* `c.end()`.

```
template <class T, size_t N> constexpr T* begin(T (&array)[N]) noexcept;
```

- <sup>4</sup> *Returns:* `array`.

```
template <class T, size_t N> constexpr T* end(T (&array)[N]) noexcept;
```

- <sup>5</sup> *Returns:* `array + N`.

```
template <class C> constexpr auto cbegin(const C& c) noexcept(noexcept(std::begin(c)))
-> decltype(std::begin(c));
```

- <sup>6</sup> *Returns:* `std::begin(c)`.

```
template <class C> constexpr auto cend(const C& c) noexcept(noexcept(std::end(c)))
-> decltype(std::end(c));
```

- <sup>7</sup> *Returns:* `std::end(c)`.

```
template <class C> constexpr auto rbegin(C& c) -> decltype(c.rbegin());
template <class C> constexpr auto rbegin(const C& c) -> decltype(c.rbegin());
```

- <sup>8</sup> *Returns:* `c.rbegin()`.

```
template <class C> constexpr auto rend(C& c) -> decltype(c.rend());
template <class C> constexpr auto rend(const C& c) -> decltype(c.rend());
```

- <sup>9</sup> *Returns:* `c.rend()`.

```
template <class T, size_t N> constexpr reverse_iterator<T*> rbegin(T (&array)[N]);
```

- <sup>10</sup> *Returns:* `reverse_iterator<T*>(array + N)`.

```
template <class T, size_t N> constexpr reverse_iterator<T*> rend(T (&array)[N]);
```

- <sup>11</sup> *Returns:* `reverse_iterator<T*>(array)`.

```
template <class E> constexpr reverse_iterator<const E*> rbegin(initializer_list<E> il);
```

- <sup>12</sup> *Returns:* `reverse_iterator<const E*>(il.end())`.

```
template <class E> constexpr reverse_iterator<const E*> rend(initializer_list<E> il);
```

- <sup>13</sup> *Returns:* `reverse_iterator<const E*>(il.begin())`.

```
template <class C> constexpr auto crbegin(const C& c) -> decltype(std::rbegin(c));
```

- <sup>14</sup> *Returns:* `std::rbegin(c)`.

```
template <class C> constexpr auto crend(const C& c) -> decltype(std::rend(c));
```

15 *Returns:* `std::rend(c)`.

## 27.8 Container access [iterator.container]

1 In addition to being available via inclusion of the `<iterator>` header, the function templates in 27.8 are available when any of the following headers are included: `<array>`, `<deque>`, `<forward_list>`, `<list>`, `<map>`, `<regex>`, `<set>`, `<string>`, `<unordered_map>`, `<unordered_set>`, and `<vector>`.

```
template <class C> constexpr auto size(const C& c) -> decltype(c.size());
```

2 *Returns:* `c.size()`.

```
template <class T, size_t N> constexpr size_t size(const T (&array)[N]) noexcept;
```

3 *Returns:* `N`.

```
template <class C> constexpr auto empty(const C& c) -> decltype(c.empty());
```

4 *Returns:* `c.empty()`.

```
template <class T, size_t N> constexpr bool empty(const T (&array)[N]) noexcept;
```

5 *Returns:* `false`.

```
template <class E> constexpr bool empty(initializer_list<E> il) noexcept;
```

6 *Returns:* `il.size() == 0`.

```
template <class C> constexpr auto data(C& c) -> decltype(c.data());
```

```
template <class C> constexpr auto data(const C& c) -> decltype(c.data());
```

7 *Returns:* `c.data()`.

```
template <class T, size_t N> constexpr T* data(T (&array)[N]) noexcept;
```

8 *Returns:* `array`.

```
template <class E> constexpr const E* data(initializer_list<E> il) noexcept;
```

9 *Returns:* `il.begin()`.

## 28 Algorithms library [algorithms]

### 28.1 General [algorithms.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to perform algorithmic operations on containers (Clause 26) and other sequences.
- <sup>2</sup> The following subclauses describe components for non-modifying sequence operations, modifying sequence operations, sorting and related operations, and algorithms from the ISO C library, as summarized in Table 100.

Table 100 — Algorithms library summary

| Subclause                                              | Header(s)                      |
|--------------------------------------------------------|--------------------------------|
| <a href="#">28.5</a> Non-modifying sequence operations |                                |
| <a href="#">28.6</a> Mutating sequence operations      | <code>&lt;algorithm&gt;</code> |
| <a href="#">28.7</a> Sorting and related operations    |                                |
| <a href="#">28.8</a> C library algorithms              | <code>&lt;cstdlib&gt;</code>   |

### 28.2 Header `<algorithm>` synopsis [algorithm.syn]

```
#include <initializer_list>

namespace std {
 // 28.5, non-modifying sequence operations
 // 28.5.1, all of
 template <class InputIterator, class Predicate>
 bool all_of(InputIterator first, InputIterator last, Predicate pred);
 template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool all_of(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Predicate pred);

 // 28.5.2, any of
 template <class InputIterator, class Predicate>
 bool any_of(InputIterator first, InputIterator last, Predicate pred);
 template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool any_of(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Predicate pred);

 // 28.5.3, none of
 template <class InputIterator, class Predicate>
 bool none_of(InputIterator first, InputIterator last, Predicate pred);
 template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool none_of(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Predicate pred);

 // 28.5.4, for each
 template<class InputIterator, class Function>
 Function for_each(InputIterator first, InputIterator last, Function f);
 template<class ExecutionPolicy, class ForwardIterator, class Function>
 void for_each(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Function f);
```

```

template<class InputIterator, class Size, class Function>
 InputIterator for_each_n(InputIterator first, Size n, Function f);
template<class ExecutionPolicy, class ForwardIterator, class Size, class Function>
 ForwardIterator for_each_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, Size n, Function f);

// 28.5.5, find
template<class InputIterator, class T>
 InputIterator find(InputIterator first, InputIterator last,
 const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 ForwardIterator find(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 const T& value);
template<class InputIterator, class Predicate>
 InputIterator find_if(InputIterator first, InputIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator find_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Predicate pred);
template<class InputIterator, class Predicate>
 InputIterator find_if_not(InputIterator first, InputIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator find_if_not(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Predicate pred);

// 28.5.6, find end
template<class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 find_end(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ForwardIterator1, class ForwardIterator2, class BinaryPredicate>
 ForwardIterator1
 find_end(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 find_end(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1,
 class ForwardIterator2, class BinaryPredicate>
 ForwardIterator1
 find_end(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

// 28.5.7, find first
template<class InputIterator, class ForwardIterator>
 InputIterator

```

```

 find_first_of(InputIterator first1, InputIterator last1,
 ForwardIterator first2, ForwardIterator last2);
template<class InputIterator, class ForwardIterator, class BinaryPredicate>
InputIterator
 find_first_of(InputIterator first1, InputIterator last1,
 ForwardIterator first2, ForwardIterator last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
ForwardIterator1
 find_first_of(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1,
 class ForwardIterator2, class BinaryPredicate>
ForwardIterator1
 find_first_of(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

// 28.5.8, adjacent find
template<class ForwardIterator>
ForwardIterator adjacent_find(ForwardIterator first,
 ForwardIterator last);
template<class ForwardIterator, class BinaryPredicate>
ForwardIterator adjacent_find(ForwardIterator first,
 ForwardIterator last,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator>
ForwardIterator adjacent_find(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first,
 ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class BinaryPredicate>
ForwardIterator adjacent_find(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first,
 ForwardIterator last,
 BinaryPredicate pred);

// 28.5.9, count
template<class InputIterator, class T>
typename iterator_traits<InputIterator>::difference_type
 count(InputIterator first, InputIterator last, const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
typename iterator_traits<ForwardIterator>::difference_type
 count(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, const T& value);
template<class InputIterator, class Predicate>
typename iterator_traits<InputIterator>::difference_type
 count_if(InputIterator first, InputIterator last, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
typename iterator_traits<ForwardIterator>::difference_type
 count_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Predicate pred);

// 28.5.10, mismatch

```

```

template<class InputIterator1, class InputIterator2>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2);
template<class InputIterator1, class InputIterator2, class BinaryPredicate>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, BinaryPredicate pred);
template<class InputIterator1, class InputIterator2>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class InputIterator1, class InputIterator2, class BinaryPredicate>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

// 28.5.11, equal
template<class InputIterator1, class InputIterator2>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2);
template<class InputIterator1, class InputIterator2, class BinaryPredicate>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, BinaryPredicate pred);
template<class InputIterator1, class InputIterator2>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class InputIterator1, class InputIterator2, class BinaryPredicate>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 BinaryPredicate pred);

```

```

template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool equal(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 bool equal(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool equal(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 bool equal(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

// 28.5.12, is_permutation
template<class ForwardIterator1, class ForwardIterator2>
 bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ForwardIterator1, class ForwardIterator2, class BinaryPredicate>
 bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);

template<class ForwardIterator1, class ForwardIterator2>
 bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class ForwardIterator1, class ForwardIterator2, class BinaryPredicate>
 bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

// 28.5.13, search
template<class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1 search(
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ForwardIterator1, class ForwardIterator2, class BinaryPredicate>
 ForwardIterator1 search(
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1 search(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1 search(

```



```

 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
template<class ForwardIterator, class Size, class T>
 ForwardIterator search_n(ForwardIterator first, ForwardIterator last,
 Size count, const T& value);
template<class ForwardIterator, class Size, class T, class BinaryPredicate>
 ForwardIterator search_n(ForwardIterator first, ForwardIterator last,
 Size count, const T& value,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Size, class T>
 ForwardIterator search_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Size count, const T& value);
template<class ExecutionPolicy, class ForwardIterator, class Size, class T,
 class BinaryPredicate>
 ForwardIterator search_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Size count, const T& value,
 BinaryPredicate pred);

template <class ForwardIterator, class Searcher>
 ForwardIterator search(ForwardIterator first, ForwardIterator last,
 const Searcher& searcher);

// 28.6, modifying sequence operations
// 28.6.1, copy
template<class InputIterator, class OutputIterator>
 OutputIterator copy(InputIterator first, InputIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);
template<class InputIterator, class Size, class OutputIterator>
 OutputIterator copy_n(InputIterator first, Size n,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class Size,
 class ForwardIterator2>
 ForwardIterator2 copy_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, Size n,
 ForwardIterator2 result);
template<class InputIterator, class OutputIterator, class Predicate>
 OutputIterator copy_if(InputIterator first, InputIterator last,
 OutputIterator result, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Predicate>
 ForwardIterator2 copy_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, Predicate pred);
template<class BidirectionalIterator1, class BidirectionalIterator2>
 BidirectionalIterator2 copy_backward(
 BidirectionalIterator1 first, BidirectionalIterator1 last,
 BidirectionalIterator2 result);

```

```

// 28.6.2, move
template<class InputIterator, class OutputIterator>
 OutputIterator move(InputIterator first, InputIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1,
 class ForwardIterator2>
 ForwardIterator2 move(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);
template<class BidirectionalIterator1, class BidirectionalIterator2>
 BidirectionalIterator2 move_backward(
 BidirectionalIterator1 first, BidirectionalIterator1 last,
 BidirectionalIterator2 result);

// 28.6.3, swap
template<class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 swap_ranges(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 swap_ranges(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ForwardIterator1, class ForwardIterator2>
 void iter_swap(ForwardIterator1 a, ForwardIterator2 b);

// 28.6.4, transform
template<class InputIterator, class OutputIterator, class UnaryOperation>
 OutputIterator transform(InputIterator first, InputIterator last,
 OutputIterator result, UnaryOperation op);
template<class InputIterator1, class InputIterator2, class OutputIterator,
 class BinaryOperation>
 OutputIterator transform(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, OutputIterator result,
 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class UnaryOperation>
 ForwardIterator2 transform(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, UnaryOperation op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class BinaryOperation>
 ForwardIterator transform(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator result,
 BinaryOperation binary_op);

// 28.6.5, replace
template<class ForwardIterator, class T>
 void replace(ForwardIterator first, ForwardIterator last,
 const T& old_value, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 void replace(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 const T& old_value, const T& new_value);

```

```

template<class ForwardIterator, class Predicate, class T>
 void replace_if(ForwardIterator first, ForwardIterator last,
 Predicate pred, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator, class Predicate, class T>
 void replace_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Predicate pred, const T& new_value);
template<class InputIterator, class OutputIterator, class T>
 OutputIterator replace_copy(InputIterator first, InputIterator last,
 OutputIterator result,
 const T& old_value, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T>
 ForwardIterator2 replace_copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 const T& old_value, const T& new_value);
template<class InputIterator, class OutputIterator, class Predicate, class T>
 OutputIterator replace_copy_if(InputIterator first, InputIterator last,
 OutputIterator result,
 Predicate pred, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Predicate, class T>
 ForwardIterator2 replace_copy_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 Predicate pred, const T& new_value);

// 28.6.6, fill
template<class ForwardIterator, class T>
 void fill(ForwardIterator first, ForwardIterator last, const T& value);
template<class ExecutionPolicy, class ForwardIterator,
 class T>
 void fill(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, const T& value);
template<class OutputIterator, class Size, class T>
 OutputIterator fill_n(OutputIterator first, Size n, const T& value);
template<class ExecutionPolicy, class ForwardIterator,
 class Size, class T>
 ForwardIterator fill_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, Size n, const T& value);

// 28.6.7, generate
template<class ForwardIterator, class Generator>
 void generate(ForwardIterator first, ForwardIterator last,
 Generator gen);
template<class ExecutionPolicy, class ForwardIterator, class Generator>
 void generate(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Generator gen);
template<class OutputIterator, class Size, class Generator>
 OutputIterator generate_n(OutputIterator first, Size n, Generator gen);
template<class ExecutionPolicy, class ForwardIterator, class Size, class Generator>
 ForwardIterator generate_n(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, Size n, Generator gen);

```

```

// 28.6.8, remove
template<class ForwardIterator, class T>
 ForwardIterator remove(ForwardIterator first, ForwardIterator last,
 const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 ForwardIterator remove(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 const T& value);
template<class ForwardIterator, class Predicate>
 ForwardIterator remove_if(ForwardIterator first, ForwardIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator remove_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Predicate pred);
template<class InputIterator, class OutputIterator, class T>
 OutputIterator remove_copy(InputIterator first, InputIterator last,
 OutputIterator result, const T& value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class T>
 ForwardIterator2 remove_copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, const T& value);
template<class InputIterator, class OutputIterator, class Predicate>
 OutputIterator remove_copy_if(InputIterator first, InputIterator last,
 OutputIterator result, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Predicate>
 ForwardIterator2 remove_copy_if(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, Predicate pred);

// 28.6.9, unique
template<class ForwardIterator>
 ForwardIterator unique(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class BinaryPredicate>
 ForwardIterator unique(ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator unique(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class BinaryPredicate>
 ForwardIterator unique(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
template<class InputIterator, class OutputIterator>
 OutputIterator unique_copy(InputIterator first, InputIterator last,
 OutputIterator result);
template<class InputIterator, class OutputIterator, class BinaryPredicate>
 OutputIterator unique_copy(InputIterator first, InputIterator last,
 OutputIterator result, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 unique_copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);

```

```

template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator2 unique_copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, BinaryPredicate pred);

// 28.6.10, reverse
template<class BidirectionalIterator>
 void reverse(BidirectionalIterator first, BidirectionalIterator last);
template<class ExecutionPolicy, class BidirectionalIterator>
 void reverse(ExecutionPolicy&& exec, // see 28.4.5
 BidirectionalIterator first, BidirectionalIterator last);
template<class BidirectionalIterator, class OutputIterator>
 OutputIterator reverse_copy(BidirectionalIterator first,
 BidirectionalIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class BidirectionalIterator, class ForwardIterator>
 ForwardIterator reverse_copy(ExecutionPolicy&& exec, // see 28.4.5
 BidirectionalIterator first,
 BidirectionalIterator last,
 ForwardIterator result);

// 28.6.11, rotate
template<class ForwardIterator>
 ForwardIterator rotate(ForwardIterator first,
 ForwardIterator middle,
 ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator rotate(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first,
 ForwardIterator middle,
 ForwardIterator last);
template<class ForwardIterator, class OutputIterator>
 OutputIterator rotate_copy(
 ForwardIterator first, ForwardIterator middle,
 ForwardIterator last, OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 rotate_copy(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 middle,
 ForwardIterator1 last, ForwardIterator2 result);

// 28.6.12, sample
template<class PopulationIterator, class SampleIterator,
 class Distance, class UniformRandomBitGenerator>
 SampleIterator sample(PopulationIterator first, PopulationIterator last,
 SampleIterator out, Distance n,
 UniformRandomBitGenerator&& g);

// 28.6.13, shuffle
template<class RandomAccessIterator, class UniformRandomBitGenerator>
 void shuffle(RandomAccessIterator first,
 RandomAccessIterator last,
 UniformRandomBitGenerator&& g);

```

```

// 28.7.4, partitions
template <class InputIterator, class Predicate>
 bool is_partitioned(InputIterator first, InputIterator last, Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool is_partitioned(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Predicate pred);

template<class ForwardIterator, class Predicate>
 ForwardIterator partition(ForwardIterator first,
 ForwardIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator partition(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first,
 ForwardIterator last,
 Predicate pred);
template<class BidirectionalIterator, class Predicate>
 BidirectionalIterator stable_partition(BidirectionalIterator first,
 BidirectionalIterator last,
 Predicate pred);
template<class ExecutionPolicy, class BidirectionalIterator, class Predicate>
 BidirectionalIterator stable_partition(ExecutionPolicy&& exec, // see 28.4.5
 BidirectionalIterator first,
 BidirectionalIterator last,
 Predicate pred);
template <class InputIterator, class OutputIterator1,
 class OutputIterator2, class Predicate>
 pair<OutputIterator1, OutputIterator2>
 partition_copy(InputIterator first, InputIterator last,
 OutputIterator1 out_true, OutputIterator2 out_false,
 Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class ForwardIterator1,
 class ForwardIterator2, class Predicate>
 pair<ForwardIterator1, ForwardIterator2>
 partition_copy(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 ForwardIterator1 out_true, ForwardIterator2 out_false,
 Predicate pred);
template<class ForwardIterator, class Predicate>
 ForwardIterator partition_point(ForwardIterator first,
 ForwardIterator last,
 Predicate pred);

// 28.7, sorting and related operations
// 28.7.1, sorting
template<class RandomAccessIterator>
 void sort(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
 void sort(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
 void sort(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void sort(ExecutionPolicy&& exec, // see 28.4.5

```

```

 RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
 void stable_sort(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
 void stable_sort(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
 void stable_sort(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void stable_sort(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
 void partial_sort(RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
 void partial_sort(RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last, Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
 void partial_sort(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void partial_sort(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last, Compare comp);
template<class InputIterator, class RandomAccessIterator>
 RandomAccessIterator partial_sort_copy(
 InputIterator first, InputIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last);
template<class InputIterator, class RandomAccessIterator, class Compare>
 RandomAccessIterator partial_sort_copy(
 InputIterator first, InputIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator, class RandomAccessIterator>
 RandomAccessIterator partial_sort_copy(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last);
template<class ExecutionPolicy, class ForwardIterator, class RandomAccessIterator,
 class Compare>
 RandomAccessIterator partial_sort_copy(
 ExecutionPolicy&& exec, // see 28.4.5

```

```

 ForwardIterator first, ForwardIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last,
 Compare comp);
template<class ForwardIterator>
 bool is_sorted(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class Compare>
 bool is_sorted(ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator>
 bool is_sorted(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 bool is_sorted(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ForwardIterator>
 ForwardIterator is_sorted_until(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class Compare>
 ForwardIterator is_sorted_until(ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator is_sorted_until(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 ForwardIterator is_sorted_until(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Compare comp);

// 28.7.2, Nth element
template<class RandomAccessIterator>
 void nth_element(RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
 void nth_element(RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last, Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
 void nth_element(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void nth_element(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last, Compare comp);

// 28.7.3, binary search
template<class ForwardIterator, class T>
 ForwardIterator lower_bound(ForwardIterator first, ForwardIterator last,
 const T& value);
template<class ForwardIterator, class T, class Compare>
 ForwardIterator lower_bound(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);

template<class ForwardIterator, class T>
 ForwardIterator upper_bound(ForwardIterator first, ForwardIterator last,

```



```

 const T& value);
template<class ForwardIterator, class T, class Compare>
 ForwardIterator upper_bound(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);

template<class ForwardIterator, class T>
 pair<ForwardIterator, ForwardIterator>
 equal_range(ForwardIterator first, ForwardIterator last,
 const T& value);
template<class ForwardIterator, class T, class Compare>
 pair<ForwardIterator, ForwardIterator>
 equal_range(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);

template<class ForwardIterator, class T>
 bool binary_search(ForwardIterator first, ForwardIterator last,
 const T& value);
template<class ForwardIterator, class T, class Compare>
 bool binary_search(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);

// 28.7.5, merge
template<class InputIterator1, class InputIterator2, class OutputIterator>
 OutputIterator merge(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class InputIterator1, class InputIterator2, class OutputIterator,
 class Compare>
 OutputIterator merge(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
 ForwardIterator merge(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
 ForwardIterator merge(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

template<class BidirectionalIterator>
 void inplace_merge(BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last);
template<class BidirectionalIterator, class Compare>
 void inplace_merge(BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last, Compare comp);
template<class ExecutionPolicy, class BidirectionalIterator>
 void inplace_merge(ExecutionPolicy&& exec, // see 28.4.5
 BidirectionalIterator first,

```

```

 BidirectionalIterator middle,
 BidirectionalIterator last);
template<class ExecutionPolicy, class BidirectionalIterator, class Compare>
 void inplace_merge(ExecutionPolicy&& exec, // see 28.4.5
 BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last, Compare comp);

// 28.7.6, set operations
template<class InputIterator1, class InputIterator2>
 bool includes(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class InputIterator1, class InputIterator2, class Compare>
 bool includes(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool includes(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Compare>
 bool includes(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2, Compare comp);

template<class InputIterator1, class InputIterator2, class OutputIterator>
 OutputIterator set_union(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class InputIterator1, class InputIterator2, class OutputIterator, class Compare>
 OutputIterator set_union(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
 ForwardIterator set_union(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
 ForwardIterator set_union(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

template<class InputIterator1, class InputIterator2, class OutputIterator>
 OutputIterator set_intersection(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class InputIterator1, class InputIterator2, class OutputIterator, class Compare>
 OutputIterator set_intersection(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,

```

```

 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator set_intersection(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator set_intersection(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

template<class InputIterator1, class InputIterator2, class OutputIterator>
OutputIterator set_difference(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class InputIterator1, class InputIterator2, class OutputIterator, class Compare>
OutputIterator set_difference(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator set_difference(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator set_difference(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

template<class InputIterator1, class InputIterator2, class OutputIterator>
OutputIterator set_symmetric_difference(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class InputIterator1, class InputIterator2, class OutputIterator, class Compare>
OutputIterator set_symmetric_difference(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator set_symmetric_difference(
 ExecutionPolicy&& exec, // see 28.4.5

```

```

 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator set_symmetric_difference(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

// 28.7.7, heap operations
template<class RandomAccessIterator>
void push_heap(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
void push_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
void pop_heap(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
void pop_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
void make_heap(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
void make_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
void sort_heap(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
void sort_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

template<class RandomAccessIterator>
bool is_heap(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
bool is_heap(RandomAccessIterator first, RandomAccessIterator last, Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
bool is_heap(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
bool is_heap(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last, Compare comp);
template<class RandomAccessIterator>
RandomAccessIterator is_heap_until(RandomAccessIterator first, RandomAccessIterator last);
template<class RandomAccessIterator, class Compare>
RandomAccessIterator is_heap_until(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator>
RandomAccessIterator is_heap_until(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>

```

```

 RandomAccessIterator is_heap_until(ExecutionPolicy&& exec, // see 28.4.5
 RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

// 28.7.8, minimum and maximum
template<class T> constexpr const T& min(const T& a, const T& b);
template<class T, class Compare>
 constexpr const T& min(const T& a, const T& b, Compare comp);
template<class T>
 constexpr T min(initializer_list<T> t);
template<class T, class Compare>
 constexpr T min(initializer_list<T> t, Compare comp);

template<class T> constexpr const T& max(const T& a, const T& b);
template<class T, class Compare>
 constexpr const T& max(const T& a, const T& b, Compare comp);
template<class T>
 constexpr T max(initializer_list<T> t);
template<class T, class Compare>
 constexpr T max(initializer_list<T> t, Compare comp);

template<class T> constexpr pair<const T&, const T&> minmax(const T& a, const T& b);
template<class T, class Compare>
 constexpr pair<const T&, const T&> minmax(const T& a, const T& b, Compare comp);
template<class T>
 constexpr pair<T, T> minmax(initializer_list<T> t);
template<class T, class Compare>
 constexpr pair<T, T> minmax(initializer_list<T> t, Compare comp);

template<class ForwardIterator>
 constexpr ForwardIterator min_element(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class Compare>
 constexpr ForwardIterator min_element(ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator min_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 ForwardIterator min_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ForwardIterator>
 constexpr ForwardIterator max_element(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class Compare>
 constexpr ForwardIterator max_element(ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator max_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 ForwardIterator max_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ForwardIterator>
 constexpr pair<ForwardIterator, ForwardIterator>

```

```

 minmax_element(ForwardIterator first, ForwardIterator last);
template<class ForwardIterator, class Compare>
 constexpr pair<ForwardIterator, ForwardIterator>
 minmax_element(ForwardIterator first, ForwardIterator last, Compare comp);
template<class ExecutionPolicy, class ForwardIterator>
 pair<ForwardIterator, ForwardIterator>
 minmax_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 pair<ForwardIterator, ForwardIterator>
 minmax_element(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, Compare comp);

// 28.7.9, bounded value
template<class T>
 constexpr const T& clamp(const T& v, const T& lo, const T& hi);
template<class T, class Compare>
 constexpr const T& clamp(const T& v, const T& lo, const T& hi, Compare comp);

// 28.7.10, lexicographical comparison
template<class InputIterator1, class InputIterator2>
 bool lexicographical_compare(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class InputIterator1, class InputIterator2, class Compare>
 bool lexicographical_compare(
 InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool lexicographical_compare(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Compare>
 bool lexicographical_compare(
 ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 Compare comp);

// 28.7.11, permutations
template<class BidirectionalIterator>
 bool next_permutation(BidirectionalIterator first,
 BidirectionalIterator last);
template<class BidirectionalIterator, class Compare>
 bool next_permutation(BidirectionalIterator first,
 BidirectionalIterator last, Compare comp);
template<class BidirectionalIterator>
 bool prev_permutation(BidirectionalIterator first,
 BidirectionalIterator last);
template<class BidirectionalIterator, class Compare>
 bool prev_permutation(BidirectionalIterator first,
 BidirectionalIterator last, Compare comp);

```

}

### 28.3 Algorithms requirements [algorithms.requirements]

- <sup>1</sup> All of the algorithms are separated from the particular implementations of data structures and are parameterized by iterator types. Because of this, they can work with program-defined data structures, as long as these data structures have iterator types satisfying the assumptions on the algorithms.
- <sup>2</sup> For purposes of determining the existence of data races, algorithms shall not modify objects referenced through an iterator argument unless the specification requires such modification.
- <sup>3</sup> Throughout this Clause, the names of template parameters are used to express type requirements.
  - (3.1) — If an algorithm's template parameter is named `InputIterator`, `InputIterator1`, or `InputIterator2`, the template argument shall satisfy the requirements of an input iterator (27.2.3).
  - (3.2) — If an algorithm's template parameter is named `OutputIterator`, `OutputIterator1`, or `OutputIterator2`, the template argument shall satisfy the requirements of an output iterator (27.2.4).
  - (3.3) — If an algorithm's template parameter is named `ForwardIterator`, `ForwardIterator1`, or `ForwardIterator2`, the template argument shall satisfy the requirements of a forward iterator (27.2.5).
  - (3.4) — If an algorithm's template parameter is named `BidirectionalIterator`, `BidirectionalIterator1`, or `BidirectionalIterator2`, the template argument shall satisfy the requirements of a bidirectional iterator (27.2.6).
  - (3.5) — If an algorithm's template parameter is named `RandomAccessIterator`, `RandomAccessIterator1`, or `RandomAccessIterator2`, the template argument shall satisfy the requirements of a random-access iterator (27.2.7).
- <sup>4</sup> If an algorithm's *Effects*: section says that a value pointed to by any iterator passed as an argument is modified, then that algorithm has an additional type requirement: The type of that argument shall satisfy the requirements of a mutable iterator (27.2). [ *Note*: This requirement does not affect arguments that are named `OutputIterator`, `OutputIterator1`, or `OutputIterator2`, because output iterators must always be mutable. — *end note* ]
- <sup>5</sup> Both in-place and copying versions are provided for certain algorithms.<sup>262</sup> When such a version is provided for *algorithm* it is called *algorithm\_copy*. Algorithms that take predicates end with the suffix `_if` (which follows the suffix `_copy`).
- <sup>6</sup> The `Predicate` parameter is used whenever an algorithm expects a function object (23.14) that, when applied to the result of dereferencing the corresponding iterator, returns a value testable as `true`. In other words, if an algorithm takes `Predicate pred` as its argument and `first` as its iterator argument, it should work correctly in the construct `pred(*first)` contextually converted to `bool` (Clause 7). The function object `pred` shall not apply any non-constant function through the dereferenced iterator.
- <sup>7</sup> The `BinaryPredicate` parameter is used whenever an algorithm expects a function object that when applied to the result of dereferencing two corresponding iterators or to dereferencing an iterator and type `T` when `T` is part of the signature returns a value testable as `true`. In other words, if an algorithm takes `BinaryPredicate binary_pred` as its argument and `first1` and `first2` as its iterator arguments, it should work correctly in the construct `binary_pred(*first1, *first2)` contextually converted to `bool` (Clause 7). `BinaryPredicate` always takes the first iterator's `value_type` as its first argument, that is, in those cases when `T value` is part of the signature, it should work correctly in the construct `binary_pred(*first1, value)` contextually converted to `bool` (Clause 7). `binary_pred` shall not apply any non-constant function through the dereferenced iterators.

<sup>262</sup> The decision whether to include a copying version was usually based on complexity considerations. When the cost of doing the operation dominates the cost of copy, the copying version is not included. For example, `sort_copy` is not included because the cost of sorting is much more significant, and users might as well do `copy` followed by `sort`.



- <sup>8</sup> [ *Note*: Unless otherwise specified, algorithms that take function objects as arguments are permitted to copy those function objects freely. Programmers for whom object identity is important should consider using a wrapper class that points to a noncopied implementation object such as `reference_wrapper<T>` (23.14.5), or some equivalent solution. — *end note* ]
- <sup>9</sup> When the description of an algorithm gives an expression such as `*first == value` for a condition, the expression shall evaluate to either `true` or `false` in boolean contexts.
- <sup>10</sup> In the description of the algorithms operators `+` and `-` are used for some of the iterator categories for which they do not have to be defined. In these cases the semantics of `a+n` is the same as that of

```
X tmp = a;
advance(tmp, n);
return tmp;
```

and that of `b-a` is the same as of

```
return distance(a, b);
```

## 28.4 Parallel algorithms

[algorithms.parallel]

- <sup>1</sup> This section describes components that C++ programs may use to perform operations on containers and other sequences in parallel.

### 28.4.1 Terms and definitions

[algorithms.parallel.defns]

- <sup>1</sup> A *parallel algorithm* is a function template listed in this International Standard with a template parameter named `ExecutionPolicy`.
- <sup>2</sup> Parallel algorithms access objects indirectly accessible via their arguments by invoking the following functions:
- (2.1) — All operations of the categories of the iterators that the algorithm is instantiated with.
  - (2.2) — Operations on those sequence elements that are required by its specification.
  - (2.3) — User-provided function objects to be applied during the execution of the algorithm, if required by the specification.
  - (2.4) — Operations on those function objects required by the specification. [ *Note*: See 28.1. — *end note* ]

These functions are herein called *element access functions*. [ *Example*: The `sort` function may invoke the following element access functions:

- (2.5) — Operations of the random-access iterator of the actual template argument (as per 27.2.7), as implied by the name of the template parameter `RandomAccessIterator`.
  - (2.6) — The `swap` function on the elements of the sequence (as per the preconditions specified in 28.7.1.1).
  - (2.7) — The user-provided `Compare` function object.
- *end example* ]

### 28.4.2 Requirements on user-provided function objects

[algorithms.parallel.user]

- <sup>1</sup> Unless otherwise specified, function objects passed into parallel algorithms as objects of type `Predicate`, `BinaryPredicate`, `Compare`, `UnaryOperation`, `BinaryOperation`, `BinaryOperation1`, `BinaryOperation2`, and the operators used by the analogous overloads to these parallel algorithms that could be formed by the invocation with the specified default predicate or operation (where applicable) shall not directly or indirectly modify objects via their arguments, nor shall they rely on the identity of the provided objects..

### 28.4.3 Effect of execution policies on algorithm execution

[algorithms.parallel.exec]

- <sup>1</sup> Parallel algorithms have template parameters named `ExecutionPolicy` (23.19) which describe the manner in which the execution of these algorithms may be parallelized and the manner in which they apply the element



access functions.

- <sup>2</sup> Unless otherwise stated, implementations may make arbitrary copies of elements (with type `T`) from sequences where `is_trivially_copy_constructible_v<T>` and `is_trivially_destructible_v<T>` are `true`. [ *Note:* This implies that user-supplied function objects should not rely on object identity of arguments for such input sequences. Users for whom the object identity of the arguments to these function objects is important should consider using a wrapping iterator that returns a non-copied implementation object such as `reference_wrapper<T>` (23.14.5) or some equivalent solution. — *end note* ]
- <sup>3</sup> The invocations of element access functions in parallel algorithms invoked with an execution policy object of type `execution::sequenced_policy` all occur in the calling thread of execution. [ *Note:* The invocations are not interleaved; see 4.6. — *end note* ]
- <sup>4</sup> The invocations of element access functions in parallel algorithms invoked with an execution policy object of type `execution::parallel_policy` are permitted to execute in either the invoking thread of execution or in a thread of execution implicitly created by the library to support parallel algorithm execution. If the threads of execution created by `thread` (33.3.2) provide concurrent forward progress guarantees (4.7.2), then a thread of execution implicitly created by the library will provide parallel forward progress guarantees; otherwise, the provided forward progress guarantee is implementation-defined. Any such invocations executing in the same thread of execution are indeterminately sequenced with respect to each other. [ *Note:* It is the caller's responsibility to ensure that the invocation does not introduce data races or deadlocks. — *end note* ]  
[ *Example:*

```
int a[] = {0,1};
std::vector<int> v;
std::for_each(std::execution::par, std::begin(a), std::end(a), [&](int i) {
 v.push_back(i*2+1); // incorrect: data race
});
```

The program above has a data race because of the unsynchronized access to the container `v`. — *end example* ]  
[ *Example:*

```
std::atomic<int> x{0};
int a[] = {1,2};
std::for_each(std::execution::par, std::begin(a), std::end(a), [&](int) {
 x.fetch_add(1, std::memory_order_relaxed);
 // spin wait for another iteration to change the value of x
 while (x.load(std::memory_order_relaxed) == 1) { } // incorrect: assumes execution order
});
```

The above example depends on the order of execution of the iterations, and will not terminate if both iterations are executed sequentially on the same thread of execution. — *end example* ] [ *Example:*

```
int x = 0;
std::mutex m;
int a[] = {1,2};
std::for_each(std::execution::par, std::begin(a), std::end(a), [&](int) {
 std::lock_guard<mutex> guard(m);
 ++x;
});
```

The above example synchronizes access to object `x` ensuring that it is incremented correctly. — *end example* ]

- <sup>5</sup> The invocations of element access functions in parallel algorithms invoked with an execution policy of type `execution::parallel_unsequenced_policy` are permitted to execute in an unordered fashion in unspecified threads of execution, and unsequenced with respect to one another within each thread of execution. These threads of execution are either the invoking thread of execution or threads of execution implicitly created by the library; the latter will provide weakly parallel forward progress guarantees. [ *Note:* This means that

multiple function object invocations may be interleaved on a single thread of execution, which overrides the usual guarantee from 4.6 that function executions do not interleave with one another. — *end note*] Since `execution::parallel_unsequenced_policy` allows the execution of element access functions to be interleaved on a single thread of execution, blocking synchronization, including the use of mutexes, risks deadlock. Thus, the synchronization with `execution::parallel_unsequenced_policy` is restricted as follows: A standard library function is *vectorization-unsafe* if it is specified to synchronize with another function invocation, or another function invocation is specified to synchronize with it, and if it is not a memory allocation or deallocation function. Vectorization-unsafe standard library functions may not be invoked by user code called from `execution::parallel_unsequenced_policy` algorithms. [ *Note*: Implementations must ensure that internal synchronization inside standard library functions does not prevent forward progress when those functions are executed by threads of execution with weakly parallel forward progress guarantees. — *end note*] [ *Example*:

```
int x = 0;
std::mutex m;
int a[] = {1,2};
std::for_each(std::execution::par_unseq, std::begin(a), std::end(a), [&](int) {
 std::lock_guard<mutex> guard(m); // incorrect: lock_guard constructor calls m.lock()
 ++x;
});
```

The above program may result in two consecutive calls to `m.lock()` on the same thread of execution (which may deadlock), because the applications of the function object are not guaranteed to run on different threads of execution. — *end example*] [ *Note*: The semantics of the `execution::parallel_policy` or the `execution::parallel_unsequenced_policy` invocation allow the implementation to fall back to sequential execution if the system cannot parallelize an algorithm invocation due to lack of resources. — *end note*]

- 6 If an invocation of a parallel algorithm uses threads of execution implicitly created by the library, then the invoking thread of execution will either
  - (6.1) — temporarily block with forward progress guarantee delegation (4.7.2) on the completion of these library-managed threads of execution, or
  - (6.2) — eventually execute an element access function;

the thread of execution will continue to do so until the algorithm is finished. [ *Note*: In blocking with forward progress guarantee delegation in this context, a thread of execution created by the library is considered to have finished execution as soon as it has finished the execution of the particular element access function that the invoking thread of execution logically depends on. — *end note*]

- 7 The semantics of parallel algorithms invoked with an execution policy object of implementation-defined type are implementation-defined.

#### 28.4.4 Parallel algorithm exceptions

[`algorithms.parallel.exceptions`]

- 1 During the execution of a parallel algorithm, if temporary memory resources are required for parallelization and none are available, the algorithm throws a `bad_alloc` exception.
- 2 During the execution of a parallel algorithm, if the invocation of an element access function exits via an uncaught exception, the behavior is determined by the `ExecutionPolicy`.

#### 28.4.5 ExecutionPolicy algorithm overloads

[`algorithms.parallel.overloads`]

- 1 Parallel algorithms are algorithm overloads. Each parallel algorithm overload has an additional template type parameter named `ExecutionPolicy`, which is the first template parameter. Additionally, each parallel algorithm overload has an additional function parameter of type `ExecutionPolicy&&`, which is the first function parameter. [ *Note*: Not all algorithms have parallel algorithm overloads. — *end note*]

- <sup>2</sup> Unless otherwise specified, the semantics of `ExecutionPolicy` algorithm overloads are identical to their overloads without.
- <sup>3</sup> Unless otherwise specified, the complexity requirements of `ExecutionPolicy` algorithm overloads are relaxed from the complexity requirements of the overloads without as follows: when the guarantee says “at most *expr*” or “exactly *expr*” and does not specify the number of assignments or swaps, and *expr* is not already expressed with  $\mathcal{O}()$  notation, the complexity of the algorithm shall be  $\mathcal{O}(\textit{expr})$ .
- <sup>4</sup> Parallel algorithms shall not participate in overload resolution unless `is_execution_policy_v<decay_t<ExecutionPolicy>>` is true.

## 28.5 Non-modifying sequence operations

[alg.nonmodifying]

### 28.5.1 All of

[alg.all\_of]

```
template <class InputIterator, class Predicate>
 bool all_of(InputIterator first, InputIterator last, Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool all_of(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 Predicate pred);
```

- <sup>1</sup> *Returns:* true if `[first, last)` is empty or if `pred(*i)` is true for every iterator *i* in the range `[first, last)`, and false otherwise.
- <sup>2</sup> *Complexity:* At most `last - first` applications of the predicate.

### 28.5.2 Any of

[alg.any\_of]

```
template <class InputIterator, class Predicate>
 bool any_of(InputIterator first, InputIterator last, Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool any_of(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 Predicate pred);
```

- <sup>1</sup> *Returns:* false if `[first, last)` is empty or if there is no iterator *i* in the range `[first, last)` such that `pred(*i)` is true, and true otherwise.
- <sup>2</sup> *Complexity:* At most `last - first` applications of the predicate.

### 28.5.3 None of

[alg.none\_of]

```
template <class InputIterator, class Predicate>
 bool none_of(InputIterator first, InputIterator last, Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool none_of(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 Predicate pred);
```

- <sup>1</sup> *Returns:* true if `[first, last)` is empty or if `pred(*i)` is false for every iterator *i* in the range `[first, last)`, and false otherwise.
- <sup>2</sup> *Complexity:* At most `last - first` applications of the predicate.

### 28.5.4 For each

[alg.foreach]

```
template<class InputIterator, class Function>
 Function for_each(InputIterator first, InputIterator last, Function f);
```

- <sup>1</sup> *Requires:* Function shall meet the requirements of `MoveConstructible` (Table 23). [Note: Function need not meet the requirements of `CopyConstructible` (Table 24). — end note]

*Effects:* Applies **f** to the result of dereferencing every iterator in the range [**first**, **last**), starting from **first** and proceeding to **last** - 1. [ *Note:* If the type of **first** satisfies the requirements of a mutable iterator, **f** may apply non-constant functions through the dereferenced iterator. — *end note* ]

*Returns:* **f**.

*Complexity:* Applies **f** exactly **last** - **first** times.

*Remarks:* If **f** returns a result, the result is ignored.

```
template<class ExecutionPolicy, class ForwardIterator, class Function>
void for_each(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Function f);
```

*Requires:* **Function** shall meet the requirements of **CopyConstructible**.

*Effects:* Applies **f** to the result of dereferencing every iterator in the range [**first**, **last**). [ *Note:* If the type of **first** satisfies the requirements of a mutable iterator, **f** may apply non-constant functions through the dereferenced iterator. — *end note* ]

*Complexity:* Applies **f** exactly **last** - **first** times.

*Remarks:* If **f** returns a result, the result is ignored. Implementations do not have the freedom granted under 28.4.3 to make arbitrary copies of elements from the input sequence.

[ *Note:* Does not return a copy of its **Function** parameter, since parallelization may not permit efficient state accumulation. — *end note* ]

```
template<class InputIterator, class Size, class Function>
InputIterator for_each_n(InputIterator first, Size n, Function f);
```

*Requires:* **Function** shall meet the requirements of **MoveConstructible** [ *Note:* **Function** need not meet the requirements of **CopyConstructible**. — *end note* ]

*Requires:* **n** >= 0.

*Effects:* Applies **f** to the result of dereferencing every iterator in the range [**first**, **first** + **n**) in order. [ *Note:* If the type of **first** satisfies the requirements of a mutable iterator, **f** may apply non-constant functions through the dereferenced iterator. — *end note* ]

*Returns:* **first** + **n**.

*Remarks:* If **f** returns a result, the result is ignored.

```
template<class ExecutionPolicy, class ForwardIterator, class Size, class Function>
ForwardIterator for_each_n(ExecutionPolicy&& exec, ForwardIterator first, Size n,
 Function f);
```

*Requires:* **Function** shall meet the requirements of **CopyConstructible**.

*Requires:* **n** >= 0.

*Effects:* Applies **f** to the result of dereferencing every iterator in the range [**first**, **first** + **n**). [ *Note:* If the type of **first** satisfies the requirements of a mutable iterator, **f** may apply non-constant functions through the dereferenced iterator. — *end note* ]

*Returns:* **first** + **n**.

*Remarks:* If **f** returns a result, the result is ignored. Implementations do not have the freedom granted under 28.4.3 to make arbitrary copies of elements from the input sequence.

## 28.5.5 Find

[**alg.find**]

```

template<class InputIterator, class T>
 InputIterator find(InputIterator first, InputIterator last,
 const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 ForwardIterator find(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 const T& value);

template<class InputIterator, class Predicate>
 InputIterator find_if(InputIterator first, InputIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator find_if(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 Predicate pred);

template<class InputIterator, class Predicate>
 InputIterator find_if_not(InputIterator first, InputIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator find_if_not(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last,
 Predicate pred);

```

- 1     *Returns:* The first iterator *i* in the range  $[first, last)$  for which the following corresponding conditions hold:  $*i == value$ ,  $pred(*i) != false$ ,  $pred(*i) == false$ . Returns *last* if no such iterator is found.
- 2     *Complexity:* At most  $last - first$  applications of the corresponding predicate.

### 28.5.6 Find end

[alg.find.end]

```

template<class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 find_end(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 find_end(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1
 find_end(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1
 find_end(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

```

- 1     *Effects:* Finds a subsequence of equal values in a sequence.
- 2     *Returns:* The last iterator *i* in the range  $[first1, last1 - (last2 - first2))$  such that for every non-negative integer  $n < (last2 - first2)$ , the following corresponding conditions hold:  $*(i +$

$n) == *(first2 + n)$ ,  $pred(*(i + n), *(first2 + n)) != false$ . Returns `last1` if  $[first2, last2)$  is empty or if no such iterator is found.

- 3 *Complexity:* At most  $(last2 - first2) * (last1 - first1 - (last2 - first2) + 1)$  applications of the corresponding predicate.

### 28.5.7 Find first

[alg.find.first.of]

```
template<class InputIterator, class ForwardIterator>
 InputIterator
 find_first_of(InputIterator first1, InputIterator last1,
 ForwardIterator first2, ForwardIterator last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 find_first_of(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class InputIterator, class ForwardIterator,
 class BinaryPredicate>
 InputIterator
 find_first_of(InputIterator first1, InputIterator last1,
 ForwardIterator first2, ForwardIterator last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1
 find_first_of(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
```

- 1 *Effects:* Finds an element that matches one of a set of values.
- 2 *Returns:* The first iterator  $i$  in the range  $[first1, last1)$  such that for some iterator  $j$  in the range  $[first2, last2)$  the following conditions hold:  $*i == *j$ ,  $pred(*i, *j) != false$ . Returns `last1` if  $[first2, last2)$  is empty or if no such iterator is found.
- 3 *Complexity:* At most  $(last1 - first1) * (last2 - first2)$  applications of the corresponding predicate.

### 28.5.8 Adjacent find

[alg.adjacent.find]

```
template<class ForwardIterator>
 ForwardIterator adjacent_find(ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator adjacent_find(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

template<class ForwardIterator, class BinaryPredicate>
 ForwardIterator adjacent_find(ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator, class BinaryPredicate>
 ForwardIterator adjacent_find(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
```

- 1 *Returns:* The first iterator  $i$  such that both  $i$  and  $i + 1$  are in the range  $[first, last)$  for which the following corresponding conditions hold:  $*i == *(i + 1)$ ,  $pred(*i, *(i + 1)) != false$ . Returns

last if no such iterator is found.

- <sup>2</sup> *Complexity:* For the overloads with no `ExecutionPolicy`, exactly  $\min((i - \text{first}) + 1, (\text{last} - \text{first}) - 1)$  applications of the corresponding predicate, where  $i$  is `adjacent_find`'s return value. For the overloads with an `ExecutionPolicy`,  $\mathcal{O}(\text{last} - \text{first})$  applications of the corresponding predicate.

### 28.5.9 Count

[alg.count]

```
template<class InputIterator, class T>
 typename iterator_traits<InputIterator>::difference_type
 count(InputIterator first, InputIterator last, const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 typename iterator_traits<ForwardIterator>::difference_type
 count(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last, const T& value);

template<class InputIterator, class Predicate>
 typename iterator_traits<InputIterator>::difference_type
 count_if(InputIterator first, InputIterator last, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 typename iterator_traits<ForwardIterator>::difference_type
 count_if(ExecutionPolicy&& exec, ForwardIterator first, ForwardIterator last, Predicate pred);
```

- <sup>1</sup> *Effects:* Returns the number of iterators  $i$  in the range  $[\text{first}, \text{last})$  for which the following corresponding conditions hold:  $*i == \text{value}$ ,  $\text{pred}(*i) != \text{false}$ .
- <sup>2</sup> *Complexity:* Exactly  $\text{last} - \text{first}$  applications of the corresponding predicate.

### 28.5.10 Mismatch

[mismatch]

```
template<class InputIterator1, class InputIterator2>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);

template<class InputIterator1, class InputIterator2,
 class BinaryPredicate>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);

template<class InputIterator1, class InputIterator2>
 pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
```

```

pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class InputIterator1, class InputIterator2,
 class BinaryPredicate>
pair<InputIterator1, InputIterator2>
 mismatch(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
pair<ForwardIterator1, ForwardIterator2>
 mismatch(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);

```

1     *Remarks:* If `last2` was not given in the argument list, it denotes `first2 + (last1 - first1)` below.

2     *Returns:* A pair of iterators `first1 + n` and `first2 + n`, where `n` is the smallest integer such that, respectively,

(2.1)     — `!(*(first1 + n) == *(first2 + n))` or

(2.2)     — `pred(*(first1 + n), *(first2 + n)) == false`,

or `min(last1 - first1, last2 - first2)` if no such integer exists.

3     *Complexity:* At most `min(last1 - first1, last2 - first2)` applications of the corresponding predicate.

### 28.5.11 Equal

[alg.equal]

```

template<class InputIterator1, class InputIterator2>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool equal(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);

template<class InputIterator1, class InputIterator2,
 class BinaryPredicate>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 bool equal(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);

template<class InputIterator1, class InputIterator2>
 bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool equal(ExecutionPolicy&& exec,

```



```
ForwardIterator1 first1, ForwardIterator1 last1,
ForwardIterator2 first2, ForwardIterator2 last2);
```

```
template<class InputIterator1, class InputIterator2,
 class BinaryPredicate>
bool equal(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
bool equal(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
```

1 *Remarks:* If last2 was not given in the argument list, it denotes first2 + (last1 - first1) below.

2 *Returns:* If last1 - first1 != last2 - first2, return false. Otherwise return true if for every iterator i in the range [first1, last1) the following corresponding conditions hold: \*i == \*(first2 + (i - first1)), pred(\*i, \*(first2 + (i - first1))) != false. Otherwise, returns false.

3 *Complexity:*

- (3.1) — For the overloads with no ExecutionPolicy,
  - (3.1.1) — if InputIterator1 and InputIterator2 meet the requirements of random access iterators (27.2.7) and last1 - first1 != last2 - first2, then no applications of the corresponding predicate; otherwise,
  - (3.1.2) — at most min(last1 - first1, last2 - first2) applications of the corresponding predicate.
- (3.2) — For the overloads with no ExecutionPolicy,
  - (3.2.1) — if ForwardIterator1 and ForwardIterator2 meet the requirements of random access iterators and last1 - first1 != last2 - first2, then no applications of the corresponding predicate; otherwise,
  - (3.2.2) —  $\mathcal{O}(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$  applications of the corresponding predicate.

### 28.5.12 Is permutation

[alg.is\_permutation]

```
template<class ForwardIterator1, class ForwardIterator2>
bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
template<class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, BinaryPredicate pred);
template<class ForwardIterator1, class ForwardIterator2>
bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
bool is_permutation(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
```

1 *Requires:* ForwardIterator1 and ForwardIterator2 shall have the same value type. The comparison function shall be an equivalence relation.

- 2 *Remarks:* If `last2` was not given in the argument list, it denotes `first2 + (last1 - first1)` below.
- 3 *Returns:* If `last1 - first1 != last2 - first2`, return `false`. Otherwise return `true` if there exists a permutation of the elements in the range `[first2, first2 + (last1 - first1))`, beginning with `ForwardIterator2 begin`, such that `equal(first1, last1, begin)` returns `true` or `equal(first1, last1, begin, pred)` returns `true`; otherwise, returns `false`.
- 4 *Complexity:* No applications of the corresponding predicate if `ForwardIterator1` and `ForwardIterator2` meet the requirements of random access iterators and `last1 - first1 != last2 - first2`. Otherwise, exactly `last1 - first1` applications of the corresponding predicate if `equal(first1, last1, first2, last2)` would return `true` if `pred` was not given in the argument list or `equal(first1, last1, first2, last2, pred)` would return `true` if `pred` was given in the argument list; otherwise, at worst  $\mathcal{O}(N^2)$ , where  $N$  has the value `last1 - first1`.

### 28.5.13 Search

[alg.search]

```
template<class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 search(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator1
 search(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1
 search(ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator1
 search(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 BinaryPredicate pred);
```

- 1 *Effects:* Finds a subsequence of equal values in a sequence.
- 2 *Returns:* The first iterator `i` in the range `[first1, last1 - (last2 - first2))` such that for every non-negative integer `n` less than `last2 - first2` the following corresponding conditions hold: `*(i + n) == *(first2 + n)`, `pred(*(i + n), *(first2 + n)) != false`. Returns `first1` if `[first2, last2)` is empty, otherwise returns `last1` if no such iterator is found.
- 3 *Complexity:* At most `(last1 - first1) * (last2 - first2)` applications of the corresponding predicate.

```
template<class ForwardIterator, class Size, class T>
 ForwardIterator
 search_n(ForwardIterator first, ForwardIterator last, Size count,
 const T& value);

template<class ForwardIterator, class Size, class T,
 class BinaryPredicate>
```

```
ForwardIterator
search_n(ForwardIterator first, ForwardIterator last, Size count,
 const T& value, BinaryPredicate pred);
```

```
template<class ExecutionPolicy, class ForwardIterator, class Size, class T>
```

```
ForwardIterator
search_n(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Size count, const T& value);
```

```
template<class ExecutionPolicy, class ForwardIterator, class Size, class T,
 class BinaryPredicate>
```

```
ForwardIterator
search_n(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Size count, const T& value,
 BinaryPredicate pred);
```

4     *Requires:* The type `Size` shall be convertible to integral type (7.8, 15.3).

5     *Effects:* Finds a subsequence of equal values in a sequence.

6     *Returns:* The first iterator `i` in the range `[first, last-count)` such that for every non-negative integer `n` less than `count` the following corresponding conditions hold: `*(i + n) == value`, `pred(*(i + n), value) != false`. Returns `last` if no such iterator is found.

7     *Complexity:* At most `last - first` applications of the corresponding predicate.

```
template<class ForwardIterator, class Searcher>
ForwardIterator search(ForwardIterator first, ForwardIterator last,
 const Searcher& searcher);
```

8     *Effects:* Equivalent to: `return searcher(first, last).first;`

9     *Remarks:* `Searcher` need not meet the `CopyConstructible` requirements.

## 28.6 Mutating sequence operations

[alg.modifying.operations]

### 28.6.1 Copy

[alg.copy]

```
template<class InputIterator, class OutputIterator>
OutputIterator copy(InputIterator first, InputIterator last,
 OutputIterator result);
```

1     *Requires:* `result` shall not be in the range `[first, last)`.

2     *Effects:* Copies elements in the range `[first, last)` into the range `[result, result + (last - first))` starting from `first` and proceeding to `last`. For each non-negative integer `n < (last - first)`, performs `*(result + n) = *(first + n)`.

3     *Returns:* `result + (last - first)`.

4     *Complexity:* Exactly `last - first` assignments.

```
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
ForwardIterator2 copy(ExecutionPolicy&& policy,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);
```

5     *Requires:* The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

6     *Effects:* Copies elements in the range `[first, last)` into the range `[result, result + (last - first))`. For each non-negative integer `n < (last - first)`, performs `*(result + n) = *(first`

+ n).

7 *Returns:* result + (last - first).

8 *Complexity:* Exactly last - first assignments.

```
template<class InputIterator, class Size, class OutputIterator>
 OutputIterator copy_n(InputIterator first, Size n,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class Size, class ForwardIterator2>
 ForwardIterator2 copy_n(ExecutionPolicy&& exec,
 ForwardIterator1 first, Size n,
 ForwardIterator2 result);
```

9 *Effects:* For each non-negative integer  $i < n$ , performs  $*(result + i) = *(first + i)$ .

10 *Returns:* result + n.

11 *Complexity:* Exactly n assignments.

```
template<class InputIterator, class OutputIterator, class Predicate>
 OutputIterator copy_if(InputIterator first, InputIterator last,
 OutputIterator result, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class Predicate>
 ForwardIterator2 copy_if(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, Predicate pred);
```

12 *Requires:* The ranges [first, last) and [result, result + (last - first)) shall not overlap.  
 [Note: For the overload with an ExecutionPolicy, there may be a performance cost if `iterator_traits<ForwardIterator1>::value_type` is not MoveConstructible (Table 23). — end note]

13 *Effects:* Copies all of the elements referred to by the iterator i in the range [first, last) for which `pred(*i)` is true.

14 *Returns:* The end of the resulting range.

15 *Complexity:* Exactly last - first applications of the corresponding predicate.

16 *Remarks:* Stable (20.5.5.7).

```
template<class BidirectionalIterator1, class BidirectionalIterator2>
 BidirectionalIterator2
 copy_backward(BidirectionalIterator1 first,
 BidirectionalIterator1 last,
 BidirectionalIterator2 result);
```

17 *Requires:* result shall not be in the range (first, last].

18 *Effects:* Copies elements in the range [first, last) into the range [result - (last-first), result) starting from last - 1 and proceeding to first.<sup>263</sup> For each positive integer  $n \leq (last - first)$ , performs  $*(result - n) = *(last - n)$ .

19 *Returns:* result - (last - first).

20 *Complexity:* Exactly last - first assignments.

## 28.6.2 Move

[alg.move]

```
template<class InputIterator, class OutputIterator>
 OutputIterator move(InputIterator first, InputIterator last, OutputIterator result);
```

<sup>263</sup>) `copy_backward` should be used instead of `copy` when last is in the range [result - (last - first), result).

- 1 *Requires:* result shall not be in the range [first, last).
- 2 *Effects:* Moves elements in the range [first, last) into the range [result, result + (last - first)) starting from first and proceeding to last. For each non-negative integer  $n < (last - first)$ , performs  $*(result + n) = std::move(*(first + n))$ .
- 3 *Returns:* result + (last - first).
- 4 *Complexity:* Exactly last - first move assignments.
- ```
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
    ForwardIterator2 move(ExecutionPolicy&& policy,
                          ForwardIterator1 first, ForwardIterator1 last,
                          ForwardIterator2 result);
```
- 5 *Requires:* The ranges [first, last) and [result, result + (last - first)) shall not overlap.
- 6 *Effects:* Moves elements in the range [first, last) into the range [result, result + (last - first)). For each non-negative integer $n < (last - first)$, performs $*(result + n) = std::move(*(first + n))$.
- 7 *Returns:* result + (last - first).
- 8 *Complexity:* Exactly last - first assignments.
- ```
template<class BidirectionalIterator1, class BidirectionalIterator2>
 BidirectionalIterator2
 move_backward(BidirectionalIterator1 first,
 BidirectionalIterator1 last,
 BidirectionalIterator2 result);
```
- 9 *Requires:* result shall not be in the range (first, last].
- 10 *Effects:* Moves elements in the range [first, last) into the range [result - (last - first), result) starting from last - 1 and proceeding to first.<sup>264</sup> For each positive integer  $n \leq (last - first)$ , performs  $*(result - n) = std::move(*(last - n))$ .
- 11 *Returns:* result - (last - first).
- 12 *Complexity:* Exactly last - first assignments.

### 28.6.3 Swap

[alg.swap]

- ```
template<class ForwardIterator1, class ForwardIterator2>
    ForwardIterator2
    swap_ranges(ForwardIterator1 first1, ForwardIterator1 last1,
                ForwardIterator2 first2);
```
- ```
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2
 swap_ranges(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2);
```
- 1 *Requires:* The two ranges [first1, last1) and [first2, first2 + (last1 - first1)) shall not overlap.  $*(first1 + n)$  shall be swappable with  $(20.5.3.2) *(first2 + n)$ .
- 2 *Effects:* For each non-negative integer  $n < (last1 - first1)$  performs:  $swap(*(first1 + n), *(first2 + n))$ .
- 3 *Returns:* first2 + (last1 - first1).

<sup>264</sup>) move\_backward should be used instead of move when last is in the range [result - (last - first), result).

4 *Complexity:* Exactly `last1 - first1` swaps.

```
template<class ForwardIterator1, class ForwardIterator2>
void iter_swap(ForwardIterator1 a, ForwardIterator2 b);
```

5 *Requires:* `a` and `b` shall be dereferenceable. `*a` shall be swappable with (20.5.3.2) `*b`.

6 *Effects:* As if by `swap(*a, *b)`.

## 28.6.4 Transform

[alg.transform]

```
template<class InputIterator, class OutputIterator,
 class UnaryOperation>
OutputIterator
transform(InputIterator first, InputIterator last,
 OutputIterator result, UnaryOperation op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class UnaryOperation>
ForwardIterator2
transform(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, UnaryOperation op);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class BinaryOperation>
OutputIterator
transform(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, OutputIterator result,
 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class BinaryOperation>
ForwardIterator
transform(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator result,
 BinaryOperation binary_op);
```

1 *Requires:* `op` and `binary_op` shall not invalidate iterators or subranges, or modify elements in the ranges

(1.1) — `[first1, last1]`,

(1.2) — `[first2, first2 + (last1 - first1)]`, and

(1.3) — `[result, result + (last1 - first1)]`.<sup>265</sup>

2 *Effects:* Assigns through every iterator `i` in the range `[result, result + (last1 - first1))` a new corresponding value equal to `op(*(first1 + (i - result)))` or `binary_op(*(first1 + (i - result)), *(first2 + (i - result)))`.

3 *Returns:* `result + (last1 - first1)`.

4 *Complexity:* Exactly `last1 - first1` applications of `op` or `binary_op`. This requirement also applies to the overload with an `ExecutionPolicy`.

5 *Remarks:* `result` may be equal to `first` in case of unary transform, or to `first1` or `first2` in case of binary transform.

## 28.6.5 Replace

[alg.replace]

---

<sup>265</sup>) The use of fully closed ranges is intentional.

```

template<class ForwardIterator, class T>
 void replace(ForwardIterator first, ForwardIterator last,
 const T& old_value, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 void replace(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 const T& old_value, const T& new_value);

template<class ForwardIterator, class Predicate, class T>
 void replace_if(ForwardIterator first, ForwardIterator last,
 Predicate pred, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator, class Predicate, class T>
 void replace_if(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Predicate pred, const T& new_value);

```

- 1     *Requires:* The expression `*first = new_value` shall be valid.
- 2     *Effects:* Substitutes elements referred by the iterator `i` in the range `[first, last)` with `new_value`, when the following corresponding conditions hold: `*i == old_value`, `pred(*i) != false`.
- 3     *Complexity:* Exactly `last - first` applications of the corresponding predicate.

```

template<class InputIterator, class OutputIterator, class T>
 OutputIterator
 replace_copy(InputIterator first, InputIterator last,
 OutputIterator result,
 const T& old_value, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T>
 ForwardIterator2
 replace_copy(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 const T& old_value, const T& new_value);

template<class InputIterator, class OutputIterator, class Predicate, class T>
 OutputIterator
 replace_copy_if(InputIterator first, InputIterator last,
 OutputIterator result,
 Predicate pred, const T& new_value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class Predicate, class T>
 ForwardIterator2
 replace_copy_if(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 Predicate pred, const T& new_value);

```

- 4     *Requires:* The results of the expressions `*first` and `new_value` shall be writable (27.2.1) to the `result` output iterator. The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.
- 5     *Effects:* Assigns to every iterator `i` in the range `[result, result + (last - first))` either `new_value` or `*(first + (i - result))` depending on whether the following corresponding conditions hold:
 

```

 *(first + (i - result)) == old_value
 pred(*(first + (i - result))) != false

```

6 *Returns:* result + (last - first).

7 *Complexity:* Exactly last - first applications of the corresponding predicate.

### 28.6.6 Fill

[alg.fill]

```
template<class ForwardIterator, class T>
 void fill(ForwardIterator first, ForwardIterator last, const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 void fill(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, const T& value);

template<class OutputIterator, class Size, class T>
 OutputIterator fill_n(OutputIterator first, Size n, const T& value);
template<class ExecutionPolicy, class ForwardIterator, class Size, class T>
 ForwardIterator fill_n(ExecutionPolicy&& exec,
 ForwardIterator first, Size n, const T& value);
```

1 *Requires:* The expression value shall be writable (27.2.1) to the output iterator. The type Size shall be convertible to an integral type (7.8, 15.3).

2 *Effects:* The fill algorithms assign value through all the iterators in the range [first, last). The fill\_n algorithms assign value through all the iterators in the range [first, first + n) if n is positive, otherwise they do nothing.

3 *Returns:* fill\_n returns first + n for non-negative values of n and first for negative values.

4 *Complexity:* Exactly last - first, n, or 0 assignments, respectively.

### 28.6.7 Generate

[alg.generate]

```
template<class ForwardIterator, class Generator>
 void generate(ForwardIterator first, ForwardIterator last,
 Generator gen);
template<class ExecutionPolicy, class ForwardIterator, class Generator>
 void generate(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Generator gen);

template<class OutputIterator, class Size, class Generator>
 OutputIterator generate_n(OutputIterator first, Size n, Generator gen);
template<class ExecutionPolicy, class ForwardIterator, class Size, class Generator>
 ForwardIterator generate_n(ExecutionPolicy&& exec,
 ForwardIterator first, Size n, Generator gen);
```

1 *Requires:* gen takes no arguments, Size shall be convertible to an integral type (7.8, 15.3).

2 *Effects:* The generate algorithms invoke the function object gen and assign the return value of gen through all the iterators in the range [first, last). The generate\_n algorithms invoke the function object gen and assign the return value of gen through all the iterators in the range [first, first + n) if n is positive, otherwise they do nothing.

3 *Returns:* generate\_n returns first + n for non-negative values of n and first for negative values.

4 *Complexity:* Exactly last - first, n, or 0 invocations of gen and assignments, respectively.

### 28.6.8 Remove

[alg.remove]

```
template<class ForwardIterator, class T>
 ForwardIterator remove(ForwardIterator first, ForwardIterator last,
```



```

 const T& value);
template<class ExecutionPolicy, class ForwardIterator, class T>
 ForwardIterator remove(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 const T& value);

template<class ForwardIterator, class Predicate>
 ForwardIterator remove_if(ForwardIterator first, ForwardIterator last,
 Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator remove_if(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Predicate pred);

```

1     *Requires:* The type of *\*first* shall satisfy the `MoveAssignable` requirements (Table 25).

2     *Effects:* Eliminates all the elements referred to by iterator *i* in the range `[first, last)` for which the following corresponding conditions hold: *\*i* == *value*, *pred(\*i)* != *false*.

3     *Returns:* The end of the resulting range.

4     *Remarks:* Stable (20.5.5.7).

5     *Complexity:* Exactly *last* - *first* applications of the corresponding predicate.

6     [ *Note:* Each element in the range `[ret, last)`, where *ret* is the returned value, has a valid but unspecified state, because the algorithms can eliminate elements by moving from elements that were originally in that range. — *end note* ]

```

template<class InputIterator, class OutputIterator, class T>
 OutputIterator
 remove_copy(InputIterator first, InputIterator last,
 OutputIterator result, const T& value);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T>
 ForwardIterator2
 remove_copy(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, const T& value);

```

```

template<class InputIterator, class OutputIterator, class Predicate>
 OutputIterator
 remove_copy_if(InputIterator first, InputIterator last,
 OutputIterator result, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class Predicate>
 ForwardIterator2
 remove_copy_if(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, Predicate pred);

```

7     *Requires:* The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap. The expression *\*result* = *\*first* shall be valid. [ *Note:* For the overloads with an `ExecutionPolicy`, there may be a performance cost if `iterator_traits<ForwardIterator1>::value_type` is not `MoveConstructible` (Table 23). — *end note* ]

8     *Effects:* Copies all the elements referred to by the iterator *i* in the range `[first, last)` for which the following corresponding conditions do not hold: *\*i* == *value*, *pred(\*i)* != *false*.

9     *Returns:* The end of the resulting range.

10    *Complexity:* Exactly *last* - *first* applications of the corresponding predicate.

11 *Remarks:* Stable (20.5.5.7).

## 28.6.9 Unique

[alg.unique]

```
template<class ForwardIterator>
 ForwardIterator unique(ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator unique(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

template<class ForwardIterator, class BinaryPredicate>
 ForwardIterator unique(ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator, class BinaryPredicate>
 ForwardIterator unique(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 BinaryPredicate pred);
```

1 *Requires:* The comparison function shall be an equivalence relation. The type of `*first` shall satisfy the `MoveAssignable` requirements (Table 25).

2 *Effects:* For a nonempty range, eliminates all but the first element from every consecutive group of equivalent elements referred to by the iterator `i` in the range `[first + 1, last)` for which the following conditions hold: `*(i - 1) == *i` or `pred(*(i - 1), *i) != false`.

3 *Returns:* The end of the resulting range.

4 *Complexity:* For nonempty ranges, exactly  $(last - first) - 1$  applications of the corresponding predicate.

```
template<class InputIterator, class OutputIterator>
 OutputIterator
 unique_copy(InputIterator first, InputIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2
 unique_copy(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);

template<class InputIterator, class OutputIterator,
 class BinaryPredicate>
 OutputIterator
 unique_copy(InputIterator first, InputIterator last,
 OutputIterator result, BinaryPredicate pred);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryPredicate>
 ForwardIterator2
 unique_copy(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result, BinaryPredicate pred);
```

5 *Requires:*

- (5.1) — The comparison function shall be an equivalence relation.
- (5.2) — The ranges `[first, last)` and `[result, result+(last-first))` shall not overlap.
- (5.3) — The expression `*result = *first` shall be valid.

- (5.4) — For the overloads with no `ExecutionPolicy`, let `T` be the value type of `InputIterator`. If `InputIterator` meets the forward iterator requirements, then there are no additional requirements for `T`. Otherwise, if `OutputIterator` meets the forward iterator requirements and its value type is the same as `T`, then `T` shall be `CopyAssignable` (Table 26). Otherwise, `T` shall be both `CopyConstructible` (Table 24) and `CopyAssignable`. [Note: For the overloads with an `ExecutionPolicy`, there may be a performance cost if the value type of `ForwardIterator1` is not both `CopyConstructible` and `CopyAssignable`. — end note]
- 6 *Effects*: Copies only the first element from every consecutive group of equal elements referred to by the iterator `i` in the range `[first, last)` for which the following corresponding conditions hold: `*i == *(i - 1)` or `pred(*i, *(i - 1)) != false`.
- 7 *Returns*: The end of the resulting range.
- 8 *Complexity*: For nonempty ranges, exactly `last - first - 1` applications of the corresponding predicate.

### 28.6.10 Reverse

[alg.reverse]

```
template<class BidirectionalIterator>
 void reverse(BidirectionalIterator first, BidirectionalIterator last);
template<class ExecutionPolicy, class BidirectionalIterator>
 void reverse(ExecutionPolicy&& exec,
 BidirectionalIterator first, BidirectionalIterator last);
```

- 1 *Requires*: `*first` shall be swappable (20.5.3.2).
- 2 *Effects*: For each non-negative integer `i < (last - first) / 2`, applies `iter_swap` to all pairs of iterators `first + i`, `(last - i) - 1`.
- 3 *Requires*: `BidirectionalIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2).
- 4 *Complexity*: Exactly `(last - first)/2` swaps.

```
template<class BidirectionalIterator, class OutputIterator>
 OutputIterator
 reverse_copy(BidirectionalIterator first, BidirectionalIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class BidirectionalIterator, class ForwardIterator>
 ForwardIterator
 reverse_copy(ExecutionPolicy&& exec,
 BidirectionalIterator first, BidirectionalIterator last,
 ForwardIterator result);
```

- 5 *Requires*: The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.
- 6 *Effects*: Copies the range `[first, last)` to the range `[result, result + (last - first))` such that for every non-negative integer `i < (last - first)` the following assignment takes place: `*(result + (last - first) - 1 - i) = *(first + i)`.
- 7 *Returns*: `result + (last - first)`.
- 8 *Complexity*: Exactly `last - first` assignments.

### 28.6.11 Rotate

[alg.rotate]

```
template<class ForwardIterator>
 ForwardIterator
 rotate(ForwardIterator first, ForwardIterator middle, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator
```

```
rotate(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator middle, ForwardIterator last);
```

1 *Requires:* [first, middle) and [middle, last) shall be valid ranges. ForwardIterator shall satisfy the requirements of ValueSwappable (20.5.3.2). The type of \*first shall satisfy the requirements of MoveConstructible (Table 23) and the requirements of MoveAssignable (Table 25).

2 *Effects:* For each non-negative integer  $i < (\text{last} - \text{first})$ , places the element from the position  $\text{first} + i$  into position  $\text{first} + (i + (\text{last} - \text{middle})) \% (\text{last} - \text{first})$ .

3 *Returns:*  $\text{first} + (\text{last} - \text{middle})$ .

4 *Remarks:* This is a left rotate.

5 *Complexity:* At most  $\text{last} - \text{first}$  swaps.

```
template<class ForwardIterator, class OutputIterator>
OutputIterator
rotate_copy(ForwardIterator first, ForwardIterator middle, ForwardIterator last,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
ForwardIterator2
rotate_copy(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 middle, ForwardIterator1 last,
 ForwardIterator2 result);
```

6 *Requires:* The ranges [first, last) and [result, result + (last - first)) shall not overlap.

7 *Effects:* Copies the range [first, last) to the range [result, result + (last - first)) such that for each non-negative integer  $i < (\text{last} - \text{first})$  the following assignment takes place:  $\text{*(result} + i) = \text{*(first} + (i + (\text{middle} - \text{first})) \% (\text{last} - \text{first}))$ .

8 *Returns:*  $\text{result} + (\text{last} - \text{first})$ .

9 *Complexity:* Exactly  $\text{last} - \text{first}$  assignments.

## 28.6.12 Sample

[alg.random.sample]

```
template<class PopulationIterator, class SampleIterator,
 class Distance, class UniformRandomBitGenerator>
SampleIterator sample(PopulationIterator first, PopulationIterator last,
 SampleIterator out, Distance n,
 UniformRandomBitGenerator&& g);
```

1 *Requires:*

- (1.1) — PopulationIterator shall satisfy the requirements of an input iterator (27.2.3).
- (1.2) — SampleIterator shall satisfy the requirements of an output iterator (27.2.4).
- (1.3) — SampleIterator shall satisfy the additional requirements of a random access iterator (27.2.7) unless PopulationIterator satisfies the additional requirements of a forward iterator (27.2.5).
- (1.4) — PopulationIterator's value type shall be writable (27.2.1) to out.
- (1.5) — Distance shall be an integer type.
- (1.6) — remove\_reference\_t<UniformRandomBitGenerator> shall meet the requirements of a uniform random bit generator type (29.6.1.3) whose return type is convertible to Distance.
- (1.7) — out shall not be in the range [first, last).

2 *Effects:* Copies  $\min(\text{last} - \text{first}, n)$  elements (the *sample*) from [first, last) (the *population*) to out such that each possible sample has equal probability of appearance. [ *Note:* Algorithms that

obtain such effects include *selection sampling* and *reservoir sampling*. — end note]

3 *Returns:* The end of the resulting sample range.

4 *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$ .

5 *Remarks:*

(5.1) — Stable if and only if `PopulationIterator` satisfies the requirements of a forward iterator.

(5.2) — To the extent that the implementation of this function makes use of random numbers, the object `g` shall serve as the implementation's source of randomness.

### 28.6.13 Shuffle

[alg.random.shuffle]

```
template<class RandomAccessIterator, class UniformRandomBitGenerator>
void shuffle(RandomAccessIterator first,
 RandomAccessIterator last,
 UniformRandomBitGenerator&& g);
```

1 *Requires:* `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type `remove_reference_t<UniformRandomBitGenerator>` shall meet the requirements of a uniform random bit generator (29.6.1.3) type whose return type is convertible to `iterator_traits<RandomAccessIterator>::difference_type`.

2 *Effects:* Permutes the elements in the range `[first, last)` such that each possible permutation of those elements has equal probability of appearance.

3 *Complexity:* Exactly `(last - first) - 1` swaps.

4 *Remarks:* To the extent that the implementation of this function makes use of random numbers, the object `g` shall serve as the implementation's source of randomness.

## 28.7 Sorting and related operations

[alg.sorting]

1 All the operations in 28.7 have two versions: one that takes a function object of type `Compare` and one that uses an `operator<`.

2 `Compare` is a function object type (23.14). The return value of the function call operation applied to an object of type `Compare`, when contextually converted to `bool` (Clause 7), yields `true` if the first argument of the call is less than the second, and `false` otherwise. `Compare comp` is used throughout for algorithms assuming an ordering relation. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

3 For all algorithms that take `Compare`, there is a version that uses `operator<` instead. That is, `comp(*i, *j) != false` defaults to `*i < *j != false`. For algorithms other than those described in 28.7.3, `comp` shall induce a strict weak ordering on the values.

4 The term *strict* refers to the requirement of an irreflexive relation (`!comp(x, x)` for all `x`), and the term *weak* to requirements that are not as strong as those for a total ordering, but stronger than those for a partial ordering. If we define `equiv(a, b)` as `!comp(a, b) && !comp(b, a)`, then the requirements are that `comp` and `equiv` both be transitive relations:

(4.1) — `comp(a, b) && comp(b, c)` implies `comp(a, c)`

(4.2) — `equiv(a, b) && equiv(b, c)` implies `equiv(a, c)`

[Note: Under these conditions, it can be shown that

(4.3) — `equiv` is an equivalence relation

(4.4) — `comp` induces a well-defined relation on the equivalence classes determined by `equiv`

(4.5) — The induced relation is a strict total ordering.

— end note]

- <sup>5</sup> A sequence is *sorted with respect to a comparator comp* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, `comp(*(i + n), *i) == false`.
- <sup>6</sup> A sequence [*start*, *finish*) is *partitioned with respect to an expression f(e)* if there exists an integer *n* such that for all  $0 \leq i < (\text{finish} - \text{start})$ , `f(*(start + i))` is true if and only if  $i < n$ .
- <sup>7</sup> In the descriptions of the functions that deal with ordering relationships we frequently use a notion of equivalence to describe concepts such as stability. The equivalence to which we refer is not necessarily an `operator==`, but an equivalence relation induced by the strict weak ordering. That is, two elements *a* and *b* are considered equivalent if and only if `!(a < b) && !(b < a)`.

## 28.7.1 Sorting

[alg.sort]

### 28.7.1.1 sort

[sort]

```
template<class RandomAccessIterator>
 void sort(RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator>
 void sort(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void sort(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void sort(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
```

- <sup>1</sup> *Requires:* `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).
- <sup>2</sup> *Effects:* Sorts the elements in the range [*first*, *last*).
- <sup>3</sup> *Complexity:*  $\mathcal{O}(N \log N)$  comparisons, where  $N = \text{last} - \text{first}$ .

### 28.7.1.2 stable\_sort

[stable.sort]

```
template<class RandomAccessIterator>
 void stable_sort(RandomAccessIterator first, RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator>
 void stable_sort(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void stable_sort(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void stable_sort(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
```

- <sup>1</sup> *Requires:* `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).

- 2 *Effects:* Sorts the elements in the range `[first, last)`.
- 3 *Complexity:* At most  $N \log^2(N)$  comparisons, where  $N = \text{last} - \text{first}$ , but only  $N \log N$  comparisons if there is enough extra memory.
- 4 *Remarks:* Stable (20.5.5.7).

### 28.7.1.3 `partial_sort`

[partial.sort]

```
template<class RandomAccessIterator>
 void partial_sort(RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator>
 void partial_sort(ExecutionPolicy&& exec,
 RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void partial_sort(RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last,
 Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void partial_sort(ExecutionPolicy&& exec,
 RandomAccessIterator first,
 RandomAccessIterator middle,
 RandomAccessIterator last,
 Compare comp);
```

- 1 *Requires:* `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).
- 2 *Effects:* Places the first `middle - first` sorted elements from the range `[first, last)` into the range `[first, middle)`. The rest of the elements in the range `[middle, last)` are placed in an unspecified order.
- 3 *Complexity:* Approximately  $(\text{last} - \text{first}) * \log(\text{middle} - \text{first})$  comparisons.

### 28.7.1.4 `partial_sort_copy`

[partial.sort.copy]

```
template<class InputIterator, class RandomAccessIterator>
 RandomAccessIterator
 partial_sort_copy(InputIterator first, InputIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last);
template<class ExecutionPolicy, class ForwardIterator, class RandomAccessIterator>
 RandomAccessIterator
 partial_sort_copy(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last);

template<class InputIterator, class RandomAccessIterator,
 class Compare>
 RandomAccessIterator
```

```

 partial_sort_copy(InputIterator first, InputIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator, class RandomAccessIterator,
 class Compare>
RandomAccessIterator
partial_sort_copy(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 RandomAccessIterator result_first,
 RandomAccessIterator result_last,
 Compare comp);

```

1 *Requires:* RandomAccessIterator shall satisfy the requirements of ValueSwappable (20.5.3.2). The type of \*result\_first shall satisfy the requirements of MoveConstructible (Table 23) and of MoveAssignable (Table 25).

2 *Effects:* Places the first min(last - first, result\_last - result\_first) sorted elements into the range [result\_first, result\_first + min(last - first, result\_last - result\_first)).

3 *Returns:* The smaller of: result\_last or result\_first + (last - first).

4 *Complexity:* Approximately (last - first) \* log(min(last - first, result\_last - result\_first)) comparisons.

#### 28.7.1.5 is\_sorted

[is.sorted]

```

template<class ForwardIterator>
bool is_sorted(ForwardIterator first, ForwardIterator last);

```

1 *Returns:* is\_sorted\_until(first, last) == last

```

template<class ExecutionPolicy, class ForwardIterator>
bool is_sorted(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

```

2 *Returns:* is\_sorted\_until(std::forward<ExecutionPolicy>(exec), first, last) == last

```

template<class ForwardIterator, class Compare>
bool is_sorted(ForwardIterator first, ForwardIterator last,
 Compare comp);

```

3 *Returns:* is\_sorted\_until(first, last, comp) == last

```

template<class ExecutionPolicy, class ForwardIterator, class Compare>
bool is_sorted(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Compare comp);

```

4 *Returns:*

```

 is_sorted_until(std::forward<ExecutionPolicy>(exec), first, last, comp) == last

```

```

template<class ForwardIterator>
ForwardIterator is_sorted_until(ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
ForwardIterator is_sorted_until(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

```

```

template<class ForwardIterator, class Compare>
ForwardIterator is_sorted_until(ForwardIterator first, ForwardIterator last,
 Compare comp);

```



```

 Compare comp);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 ForwardIterator is_sorted_until(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Compare comp);

```

5     *Returns:* If  $(last - first) < 2$ , returns last. Otherwise, returns the last iterator  $i$  in  $[first, last]$  for which the range  $[first, i)$  is sorted.

6     *Complexity:* Linear.

## 28.7.2 Nth element

[alg.nth.element]

```

template<class RandomAccessIterator>
 void nth_element(RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last);
template<class ExecutionPolicy, class RandomAccessIterator>
 void nth_element(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void nth_element(RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last, Compare comp);
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 void nth_element(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator nth,
 RandomAccessIterator last, Compare comp);

```

1     *Requires:* RandomAccessIterator shall satisfy the requirements of ValueSwappable (20.5.3.2). The type of  $*first$  shall satisfy the requirements of MoveConstructible (Table 23) and of MoveAssignable (Table 25).

2     *Effects:* After nth\_element the element in the position pointed to by nth is the element that would be in that position if the whole range were sorted, unless  $nth == last$ . Also for every iterator  $i$  in the range  $[first, nth)$  and every iterator  $j$  in the range  $[nth, last)$  it holds that:  $!(*j < *i)$  or  $comp(*j, *i) == false$ .

3     *Complexity:* For the overloads with no ExecutionPolicy, linear on average. For the overloads with an ExecutionPolicy,  $\mathcal{O}(N)$  applications of the predicate, and  $\mathcal{O}(N \log N)$  swaps, where  $N = last - first$ .

## 28.7.3 Binary search

[alg.binary.search]

1 All of the algorithms in this section are versions of binary search and assume that the sequence being searched is partitioned with respect to an expression formed by binding the search key to an argument of the implied or explicit comparison function. They work on non-random access iterators minimizing the number of comparisons, which will be logarithmic for all types of iterators. They are especially appropriate for random access iterators, because these algorithms do a logarithmic number of steps through the data structure. For non-random access iterators they execute a linear number of steps.

### 28.7.3.1 lower\_bound

[lower.bound]

```

template<class ForwardIterator, class T>
 ForwardIterator
 lower_bound(ForwardIterator first, ForwardIterator last,
 const T& value);

```

```
template<class ForwardIterator, class T, class Compare>
ForwardIterator
lower_bound(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);
```

- 1     *Requires:* The elements *e* of  $[first, last)$  shall be partitioned with respect to the expression  $e < value$  or  $comp(e, value)$ .
- 2     *Returns:* The furthestmost iterator *i* in the range  $[first, last]$  such that for every iterator *j* in the range  $[first, i)$  the following corresponding conditions hold:  $*j < value$  or  $comp(*j, value) != false$ .
- 3     *Complexity:* At most  $\log_2(last - first) + \mathcal{O}(1)$  comparisons.

### 28.7.3.2 upper\_bound

[upper.bound]

```
template<class ForwardIterator, class T>
ForwardIterator
upper_bound(ForwardIterator first, ForwardIterator last,
 const T& value);
```

```
template<class ForwardIterator, class T, class Compare>
ForwardIterator
upper_bound(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);
```

- 1     *Requires:* The elements *e* of  $[first, last)$  shall be partitioned with respect to the expression  $!(value < e)$  or  $!comp(value, e)$ .
- 2     *Returns:* The furthestmost iterator *i* in the range  $[first, last]$  such that for every iterator *j* in the range  $[first, i)$  the following corresponding conditions hold:  $!(value < *j)$  or  $comp(value, *j) == false$ .
- 3     *Complexity:* At most  $\log_2(last - first) + \mathcal{O}(1)$  comparisons.

### 28.7.3.3 equal\_range

[equal.range]

```
template<class ForwardIterator, class T>
pair<ForwardIterator, ForwardIterator>
equal_range(ForwardIterator first,
 ForwardIterator last, const T& value);
```

```
template<class ForwardIterator, class T, class Compare>
pair<ForwardIterator, ForwardIterator>
equal_range(ForwardIterator first,
 ForwardIterator last, const T& value,
 Compare comp);
```

- 1     *Requires:* The elements *e* of  $[first, last)$  shall be partitioned with respect to the expressions  $e < value$  and  $!(value < e)$  or  $comp(e, value)$  and  $!comp(value, e)$ . Also, for all elements *e* of  $[first, last)$ ,  $e < value$  shall imply  $!(value < e)$  or  $comp(e, value)$  shall imply  $!comp(value, e)$ .
- 2     *Returns:*
- make\_pair(lower\_bound(first, last, value),  
          upper\_bound(first, last, value))
- or
- make\_pair(lower\_bound(first, last, value, comp),

upper\_bound(first, last, value, comp))

3 *Complexity:* At most  $2 * \log_2(\text{last} - \text{first}) + \mathcal{O}(1)$  comparisons.

#### 28.7.3.4 binary\_search

[binary.search]

```
template<class ForwardIterator, class T>
 bool binary_search(ForwardIterator first, ForwardIterator last,
 const T& value);
```

```
template<class ForwardIterator, class T, class Compare>
 bool binary_search(ForwardIterator first, ForwardIterator last,
 const T& value, Compare comp);
```

1 *Requires:* The elements  $e$  of  $[\text{first}, \text{last})$  are partitioned with respect to the expressions  $e < \text{value}$  and  $!(\text{value} < e)$  or  $\text{comp}(e, \text{value})$  and  $!\text{comp}(\text{value}, e)$ . Also, for all elements  $e$  of  $[\text{first}, \text{last})$ ,  $e < \text{value}$  implies  $!(\text{value} < e)$  or  $\text{comp}(e, \text{value})$  implies  $!\text{comp}(\text{value}, e)$ .

2 *Returns:* true if there is an iterator  $i$  in the range  $[\text{first}, \text{last})$  that satisfies the corresponding conditions:  $!(\ast i < \text{value}) \ \&\& \ !(\text{value} < \ast i)$  or  $\text{comp}(\ast i, \text{value}) == \text{false} \ \&\& \ \text{comp}(\text{value}, \ast i) == \text{false}$ .

3 *Complexity:* At most  $\log_2(\text{last} - \text{first}) + \mathcal{O}(1)$  comparisons.

#### 28.7.4 Partitions

[alg.partitions]

```
template <class InputIterator, class Predicate>
 bool is_partitioned(InputIterator first, InputIterator last, Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class Predicate>
 bool is_partitioned(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, Predicate pred);
```

1 *Requires:* For the overload with no ExecutionPolicy, InputIterator's value type shall be convertible to Predicate's argument type. For the overload with an ExecutionPolicy, ForwardIterator's value type shall be convertible to Predicate's argument type.

2 *Returns:* true if  $[\text{first}, \text{last})$  is empty or if  $[\text{first}, \text{last})$  is partitioned by  $\text{pred}$ , i.e. if all elements that satisfy  $\text{pred}$  appear before those that do not.

3 *Complexity:* Linear. At most  $\text{last} - \text{first}$  applications of  $\text{pred}$ .

```
template<class ForwardIterator, class Predicate>
 ForwardIterator
 partition(ForwardIterator first, ForwardIterator last, Predicate pred);
template<class ExecutionPolicy, class ForwardIterator, class Predicate>
 ForwardIterator
 partition(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, Predicate pred);
```

4 *Requires:* ForwardIterator shall satisfy the requirements of ValueSwappable (20.5.3.2).

5 *Effects:* Places all the elements in the range  $[\text{first}, \text{last})$  that satisfy  $\text{pred}$  before all the elements that do not satisfy it.

6 *Returns:* An iterator  $i$  such that for every iterator  $j$  in the range  $[\text{first}, i)$   $\text{pred}(\ast j) \neq \text{false}$ , and for every iterator  $k$  in the range  $[i, \text{last})$ ,  $\text{pred}(\ast k) == \text{false}$ .

7 *Complexity:* Let  $N = \text{last} - \text{first}$ :

(7.1) — For the overload with no ExecutionPolicy, exactly  $N$  applications of the predicate. At most  $N/2$  swaps if ForwardIterator meets the BidirectionalIterator requirements and at most  $N$

swaps otherwise.

- (7.2) — For the overload with an `ExecutionPolicy`,  $\mathcal{O}(N \log N)$  swaps and  $\mathcal{O}(N)$  applications of the predicate.

```
template<class BidirectionalIterator, class Predicate>
 BidirectionalIterator
 stable_partition(BidirectionalIterator first, BidirectionalIterator last,
 Predicate pred);
template<class ExecutionPolicy, class BidirectionalIterator, class Predicate>
 BidirectionalIterator
 stable_partition(ExecutionPolicy&& exec,
 BidirectionalIterator first, BidirectionalIterator last,
 Predicate pred);
```

8 *Requires:* `BidirectionalIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).

9 *Effects:* Places all the elements in the range `[first, last)` that satisfy `pred` before all the elements that do not satisfy it.

10 *Returns:* An iterator `i` such that for every iterator `j` in the range `[first, i)`, `pred(*j) != false`, and for every iterator `k` in the range `[i, last)`, `pred(*k) == false`. The relative order of the elements in both groups is preserved.

11 *Complexity:* Let  $N = \text{last} - \text{first}$ :

- (11.1) — For the overload with no `ExecutionPolicy`, at most  $N \log N$  swaps, but only  $\mathcal{O}(N)$  swaps if there is enough extra memory. Exactly  $N$  applications of the predicate.
- (11.2) — For the overload with an `ExecutionPolicy`,  $\mathcal{O}(N \log N)$  swaps and  $\mathcal{O}(N)$  applications of the predicate.

```
template <class InputIterator, class OutputIterator1,
 class OutputIterator2, class Predicate>
 pair<OutputIterator1, OutputIterator2>
 partition_copy(InputIterator first, InputIterator last,
 OutputIterator1 out_true, OutputIterator2 out_false,
 Predicate pred);
template <class ExecutionPolicy, class ForwardIterator, class ForwardIterator1,
 class ForwardIterator2, class Predicate>
 pair<ForwardIterator1, ForwardIterator2>
 partition_copy(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 ForwardIterator1 out_true, ForwardIterator2 out_false,
 Predicate pred);
```

12 *Requires:*

- (12.1) — For the overload with no `ExecutionPolicy`, `InputIterator`'s value type shall be `CopyAssignable` (Table 26), and shall be writable (27.2.1) to the `out_true` and `out_false` `OutputIterators`, and shall be convertible to `Predicate`'s argument type.
- (12.2) — For the overload with an `ExecutionPolicy`, `ForwardIterator`'s value type shall be `CopyAssignable`, and shall be writable to the `out_true` and `out_false` `ForwardIterators`, and shall be convertible to `Predicate`'s argument type. [Note: There may be a performance cost if `ForwardIterator`'s value type is not `CopyConstructible`. — end note]
- (12.3) — For both overloads, the input range shall not overlap with either of the output ranges.

- 13 *Effects:* For each iterator *i* in `[first, last)`, copies `*i` to the output range beginning with `out_true` if `pred(*i)` is `true`, or to the output range beginning with `out_false` otherwise.
- 14 *Returns:* A pair `p` such that `p.first` is the end of the output range beginning at `out_true` and `p.second` is the end of the output range beginning at `out_false`.
- 15 *Complexity:* Exactly `last - first` applications of `pred`.

```
template<class ForwardIterator, class Predicate>
 ForwardIterator partition_point(ForwardIterator first,
 ForwardIterator last,
 Predicate pred);
```

- 16 *Requires:* `ForwardIterator`'s value type shall be convertible to `Predicate`'s argument type. `[first, last)` shall be partitioned by `pred`, i.e. all elements that satisfy `pred` shall appear before those that do not.
- 17 *Returns:* An iterator `mid` such that `all_of(first, mid, pred)` and `none_of(mid, last, pred)` are both `true`.
- 18 *Complexity:*  $\mathcal{O}(\log(\text{last} - \text{first}))$  applications of `pred`.

## 28.7.5 Merge

[alg.merge]

```
template<class InputIterator1, class InputIterator2,
 class OutputIterator>
 OutputIterator
 merge(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
 ForwardIterator
 merge(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class Compare>
 OutputIterator
 merge(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
 ForwardIterator
 merge(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);
```

- 1 *Requires:* The ranges `[first1, last1)` and `[first2, last2)` shall be sorted with respect to `operator<` or `comp`. The resulting range shall not overlap with either of the original ranges.
- 2 *Effects:* Copies all the elements of the two ranges `[first1, last1)` and `[first2, last2)` into the range `[result, result_last)`, where `result_last` is `result + (last1 - first1) + (last2 - first2)`, such that the resulting range satisfies `is_sorted(result, result_last)` or `is_sorted(result,`

result\_last, comp), respectively.

3 *Returns:* result + (last1 - first1) + (last2 - first2).

4 *Complexity:* Let  $N = (\text{last1} - \text{first1}) + (\text{last2} - \text{first2})$ :

(4.1) — For the overloads with no `ExecutionPolicy`, at most  $N - 1$  comparisons.

(4.2) — For the overloads with an `ExecutionPolicy`,  $\mathcal{O}(N)$  comparisons.

5 *Remarks:* Stable (20.5.5.7).

```
template<class BidirectionalIterator>
 void inplace_merge(BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last);
template<class ExecutionPolicy, class BidirectionalIterator>
 void inplace_merge(ExecutionPolicy&& exec,
 BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last);

template<class BidirectionalIterator, class Compare>
 void inplace_merge(BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last, Compare comp);
template<class ExecutionPolicy, class BidirectionalIterator, class Compare>
 void inplace_merge(ExecutionPolicy&& exec,
 BidirectionalIterator first,
 BidirectionalIterator middle,
 BidirectionalIterator last, Compare comp);
```

6 *Requires:* The ranges `[first, middle)` and `[middle, last)` shall be sorted with respect to `operator<` or `comp`. `BidirectionalIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).

7 *Effects:* Merges two sorted consecutive ranges `[first, middle)` and `[middle, last)`, putting the result of the merge into the range `[first, last)`. The resulting range will be in non-decreasing order; that is, for every iterator `i` in `[first, last)` other than `first`, the condition `*i < *(i - 1)` or, respectively, `comp(*i, *(i - 1))` will be false.

8 *Complexity:* Let  $N = \text{last} - \text{first}$ :

(8.1) — For the overloads with no `ExecutionPolicy`, if enough additional memory is available, exactly  $N - 1$  comparisons.

(8.2) — For the overloads with no `ExecutionPolicy` if no additional memory is available,  $\mathcal{O}(N \log N)$  comparisons.

(8.3) — For the overloads with an `ExecutionPolicy`,  $\mathcal{O}(N \log N)$  comparisons.

9 *Remarks:* Stable (20.5.5.7).

## 28.7.6 Set operations on sorted structures

[alg.set.operations]

1 This section defines all the basic set operations on sorted structures. They also work with `multisets` (26.4.7) containing multiple copies of equivalent elements. The semantics of the set operations are generalized to `multisets` in a standard way by defining `set_union()` to contain the maximum number of occurrences of every element, `set_intersection()` to contain the minimum, and so on.

## 28.7.6.1 includes

[includes]

```

template<class InputIterator1, class InputIterator2>
 bool includes(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool includes(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class InputIterator1, class InputIterator2, class Compare>
 bool includes(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class Compare>
 bool includes(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 Compare comp);

```

<sup>1</sup> *Returns:* true if [first2, last2) is empty or if every element in the range [first2, last2) is contained in the range [first1, last1). Returns false otherwise.

<sup>2</sup> *Complexity:* At most  $2 * ((last1 - first1) + (last2 - first2)) - 1$  comparisons.

## 28.7.6.2 set\_union

[set.union]

```

template<class InputIterator1, class InputIterator2,
 class OutputIterator>
 OutputIterator
 set_union(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
 ForwardIterator
 set_union(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class Compare>
 OutputIterator
 set_union(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
 ForwardIterator
 set_union(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

```

<sup>1</sup> *Requires:* The resulting range shall not overlap with either of the original ranges.

<sup>2</sup> *Effects:* Constructs a sorted union of the elements from the two ranges; that is, the set of elements that

are present in one or both of the ranges.

3 *Returns:* The end of the constructed range.

4 *Complexity:* At most  $2 * ((\text{last1} - \text{first1}) + (\text{last2} - \text{first2})) - 1$  comparisons.

5 *Remarks:* If  $[\text{first1}, \text{last1})$  contains  $m$  elements that are equivalent to each other and  $[\text{first2}, \text{last2})$  contains  $n$  elements that are equivalent to them, then all  $m$  elements from the first range shall be copied to the output range, in order, and then  $\max(n - m, 0)$  elements from the second range shall be copied to the output range, in order.

### 28.7.6.3 set\_intersection

[set.intersection]

```
template<class InputIterator1, class InputIterator2,
 class OutputIterator>
OutputIterator
set_intersection(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator
set_intersection(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class Compare>
OutputIterator
set_intersection(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator
set_intersection(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);
```

1 *Requires:* The resulting range shall not overlap with either of the original ranges.

2 *Effects:* Constructs a sorted intersection of the elements from the two ranges; that is, the set of elements that are present in both of the ranges.

3 *Returns:* The end of the constructed range.

4 *Complexity:* At most  $2 * ((\text{last1} - \text{first1}) + (\text{last2} - \text{first2})) - 1$  comparisons.

5 *Remarks:* If  $[\text{first1}, \text{last1})$  contains  $m$  elements that are equivalent to each other and  $[\text{first2}, \text{last2})$  contains  $n$  elements that are equivalent to them, the first  $\min(m, n)$  elements shall be copied from the first range to the output range, in order.

### 28.7.6.4 set\_difference

[set.difference]

```
template<class InputIterator1, class InputIterator2,
 class OutputIterator>
OutputIterator
set_difference(InputIterator1 first1, InputIterator1 last1,
```



```

 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator
 set_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class Compare>
OutputIterator
 set_difference(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator
 set_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

```

- 1     *Requires:* The resulting range shall not overlap with either of the original ranges.
- 2     *Effects:* Copies the elements of the range `[first1, last1)` which are not present in the range `[first2, last2)` to the range beginning at `result`. The elements in the constructed range are sorted.
- 3     *Returns:* The end of the constructed range.
- 4     *Complexity:* At most  $2 * ((last1 - first1) + (last2 - first2)) - 1$  comparisons.
- 5     *Remarks:* If `[first1, last1)` contains  $m$  elements that are equivalent to each other and `[first2, last2)` contains  $n$  elements that are equivalent to them, the last  $\max(m - n, 0)$  elements from `[first1, last1)` shall be copied to the output range.

#### 28.7.6.5    set\_symmetric\_difference [set.symmetric.difference]

```

template<class InputIterator1, class InputIterator2,
 class OutputIterator>
OutputIterator
 set_symmetric_difference(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 OutputIterator result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator>
ForwardIterator
 set_symmetric_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result);

template<class InputIterator1, class InputIterator2,
 class OutputIterator, class Compare>
OutputIterator
 set_symmetric_difference(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,

```

```

 OutputIterator result, Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class ForwardIterator, class Compare>
ForwardIterator
set_symmetric_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 ForwardIterator result, Compare comp);

```

- 1 *Requires:* The resulting range shall not overlap with either of the original ranges.
- 2 *Effects:* Copies the elements of the range `[first1, last1)` that are not present in the range `[first2, last2)`, and the elements of the range `[first2, last2)` that are not present in the range `[first1, last1)` to the range beginning at `result`. The elements in the constructed range are sorted.
- 3 *Returns:* The end of the constructed range.
- 4 *Complexity:* At most  $2 * ((last1 - first1) + (last2 - first2)) - 1$  comparisons.
- 5 *Remarks:* If `[first1, last1)` contains  $m$  elements that are equivalent to each other and `[first2, last2)` contains  $n$  elements that are equivalent to them, then  $|m - n|$  of those elements shall be copied to the output range: the last  $m - n$  of these elements from `[first1, last1)` if  $m > n$ , and the last  $n - m$  of these elements from `[first2, last2)` if  $m < n$ .

## 28.7.7 Heap operations

[alg.heap.operations]

- 1 A *heap* is a particular organization of elements in a range between two random access iterators `[a, b)` such that:
- (1.1) — With  $N = b - a$ , for all  $i$ ,  $0 < i < N$ , `comp(a[ $\lfloor \frac{i-1}{2} \rfloor$ ], a[i])` is false.
- (1.2) — `*a` may be removed by `pop_heap()`, or a new element added by `push_heap()`, in  $\mathcal{O}(\log N)$  time.
- 2 These properties make heaps useful as priority queues.
- 3 `make_heap()` converts a range into a heap and `sort_heap()` turns a heap into a sorted sequence.

### 28.7.7.1 push\_heap

[push.heap]

```

template<class RandomAccessIterator>
void push_heap(RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
void push_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

```

- 1 *Requires:* The range `[first, last - 1)` shall be a valid heap. The type of `*first` shall satisfy the `MoveConstructible` requirements (Table 23) and the `MoveAssignable` requirements (Table 25).
- 2 *Effects:* Places the value in the location `last - 1` into the resulting heap `[first, last)`.
- 3 *Complexity:* At most  $\log(last - first)$  comparisons.

### 28.7.7.2 pop\_heap

[pop.heap]

```

template<class RandomAccessIterator>
void pop_heap(RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
void pop_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);

```

- 1 *Requires:* The range `[first, last)` shall be a valid non-empty heap. `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).
- 2 *Effects:* Swaps the value in the location `first` with the value in the location `last - 1` and makes `[first, last - 1)` into a heap.
- 3 *Complexity:* At most  $2\log(\text{last} - \text{first})$  comparisons.

**28.7.7.3 make\_heap****[make.heap]**

```
template<class RandomAccessIterator>
 void make_heap(RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void make_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
```

- 1 *Requires:* The type of `*first` shall satisfy the `MoveConstructible` requirements (Table 23) and the `MoveAssignable` requirements (Table 25).
- 2 *Effects:* Constructs a heap out of the range `[first, last)`.
- 3 *Complexity:* At most  $3(\text{last} - \text{first})$  comparisons.

**28.7.7.4 sort\_heap****[sort.heap]**

```
template<class RandomAccessIterator>
 void sort_heap(RandomAccessIterator first, RandomAccessIterator last);

template<class RandomAccessIterator, class Compare>
 void sort_heap(RandomAccessIterator first, RandomAccessIterator last,
 Compare comp);
```

- 1 *Requires:* The range `[first, last)` shall be a valid heap. `RandomAccessIterator` shall satisfy the requirements of `ValueSwappable` (20.5.3.2). The type of `*first` shall satisfy the requirements of `MoveConstructible` (Table 23) and of `MoveAssignable` (Table 25).
- 2 *Effects:* Sorts elements in the heap `[first, last)`.
- 3 *Complexity:* At most  $N \log N$  comparisons, where  $N = \text{last} - \text{first}$ .

**28.7.7.5 is\_heap****[is.heap]**

```
template<class RandomAccessIterator>
 bool is_heap(RandomAccessIterator first, RandomAccessIterator last);
```

- 1 *Returns:* `is_heap_until(first, last) == last`

```
template<class ExecutionPolicy, class RandomAccessIterator>
 bool is_heap(ExecutionPolicy&& exec,
 RandomAccessIterator first, RandomAccessIterator last);
```

- 2 *Returns:* `is_heap_until(std::forward<ExecutionPolicy>(exec), first, last) == last`

```
template<class RandomAccessIterator, class Compare>
 bool is_heap(RandomAccessIterator first, RandomAccessIterator last, Compare comp);
```

- 3 *Returns:* `is_heap_until(first, last, comp) == last`

```
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
 bool is_heap(ExecutionPolicy&& exec,
```

```
RandomAccessIterator first, RandomAccessIterator last, Compare comp);
```

4 *Returns:*

```
is_heap_until(std::forward<ExecutionPolicy>(exec), first, last, comp) == last
```

```
template<class RandomAccessIterator>
```

```
RandomAccessIterator is_heap_until(RandomAccessIterator first, RandomAccessIterator last);
```

```
template<class ExecutionPolicy, class RandomAccessIterator>
```

```
RandomAccessIterator is_heap_until(ExecutionPolicy&& exec,
```

```
RandomAccessIterator first, RandomAccessIterator last);
```

```
template<class RandomAccessIterator, class Compare>
```

```
RandomAccessIterator is_heap_until(RandomAccessIterator first, RandomAccessIterator last,
```

```
Compare comp);
```

```
template<class ExecutionPolicy, class RandomAccessIterator, class Compare>
```

```
RandomAccessIterator is_heap_until(ExecutionPolicy&& exec,
```

```
RandomAccessIterator first, RandomAccessIterator last,
```

```
Compare comp);
```

5 *Returns:* If  $(last - first) < 2$ , returns last. Otherwise, returns the last iterator  $i$  in  $[first, last]$  for which the range  $[first, i)$  is a heap.

6 *Complexity:* Linear.

## 28.7.8 Minimum and maximum

[alg.min.max]

```
template<class T> constexpr const T& min(const T& a, const T& b);
```

```
template<class T, class Compare>
```

```
constexpr const T& min(const T& a, const T& b, Compare comp);
```

1 *Requires:* For the first form, type  $T$  shall be `LessThanComparable` (Table 21).

2 *Returns:* The smaller value.

3 *Remarks:* Returns the first argument when the arguments are equivalent.

4 *Complexity:* Exactly one comparison.

```
template<class T>
```

```
constexpr T min(initializer_list<T> t);
```

```
template<class T, class Compare>
```

```
constexpr T min(initializer_list<T> t, Compare comp);
```

5 *Requires:*  $T$  shall be `CopyConstructible` and  $t.size() > 0$ . For the first form, type  $T$  shall be `LessThanComparable`.

6 *Returns:* The smallest value in the `initializer_list`.

7 *Remarks:* Returns a copy of the leftmost argument when several arguments are equivalent to the smallest.

8 *Complexity:* Exactly  $t.size() - 1$  comparisons.

```
template<class T> constexpr const T& max(const T& a, const T& b);
```

```
template<class T, class Compare>
```

```
constexpr const T& max(const T& a, const T& b, Compare comp);
```

9 *Requires:* For the first form, type  $T$  shall be `LessThanComparable` (Table 21).

10 *Returns:* The larger value.

11 *Remarks:* Returns the first argument when the arguments are equivalent.

12 *Complexity:* Exactly one comparison.

```
template<class T>
constexpr T max(initializer_list<T> t);
template<class T, class Compare>
constexpr T max(initializer_list<T> t, Compare comp);
```

13 *Requires:* T shall be CopyConstructible and `t.size() > 0`. For the first form, type T shall be LessThanComparable.

14 *Returns:* The largest value in the `initializer_list`.

15 *Remarks:* Returns a copy of the leftmost argument when several arguments are equivalent to the largest.

16 *Complexity:* Exactly `t.size() - 1` comparisons.

```
template<class T> constexpr pair<const T&, const T&> minmax(const T& a, const T& b);
template<class T, class Compare>
constexpr pair<const T&, const T&> minmax(const T& a, const T& b, Compare comp);
```

17 *Requires:* For the first form, type T shall be LessThanComparable (Table 21).

18 *Returns:* `pair<const T&, const T&>(b, a)` if b is smaller than a, and `pair<const T&, const T&>(a, b)` otherwise.

19 *Remarks:* Returns `pair<const T&, const T&>(a, b)` when the arguments are equivalent.

20 *Complexity:* Exactly one comparison.

```
template<class T>
constexpr pair<T, T> minmax(initializer_list<T> t);
template<class T, class Compare>
constexpr pair<T, T> minmax(initializer_list<T> t, Compare comp);
```

21 *Requires:* T shall be CopyConstructible and `t.size() > 0`. For the first form, type T shall be LessThanComparable.

22 *Returns:* `pair<T, T>(x, y)`, where x has the smallest and y has the largest value in the initializer list.

23 *Remarks:* x is a copy of the leftmost argument when several arguments are equivalent to the smallest. y is a copy of the rightmost argument when several arguments are equivalent to the largest.

24 *Complexity:* At most  $(3/2)t.size()$  applications of the corresponding predicate.

```
template<class ForwardIterator>
constexpr ForwardIterator min_element(ForwardIterator first, ForwardIterator last);
```

```
template<class ExecutionPolicy, class ForwardIterator>
ForwardIterator min_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);
```

```
template<class ForwardIterator, class Compare>
constexpr ForwardIterator min_element(ForwardIterator first, ForwardIterator last,
 Compare comp);
```

```
template<class ExecutionPolicy, class ForwardIterator, class Compare>
ForwardIterator min_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Compare comp);
```

25 *Returns:* The first iterator i in the range `[first, last)` such that for every iterator j in the range `[first, last)` the following corresponding conditions hold: `!(*j < *i)` or `comp(*j, *i) == false`. Returns last if `first == last`.

26 *Complexity:* Exactly  $\max(\text{last} - \text{first} - 1, 0)$  applications of the corresponding comparisons.

```
template<class ForwardIterator>
 constexpr ForwardIterator max_element(ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 ForwardIterator max_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

template<class ForwardIterator, class Compare>
 constexpr ForwardIterator max_element(ForwardIterator first, ForwardIterator last,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 ForwardIterator max_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 Compare comp);
```

27 *Returns:* The first iterator  $i$  in the range  $[\text{first}, \text{last})$  such that for every iterator  $j$  in the range  $[\text{first}, \text{last})$  the following corresponding conditions hold:  $!(i < *j)$  or  $\text{comp}(*i, *j) == \text{false}$ . Returns  $\text{last}$  if  $\text{first} == \text{last}$ .

28 *Complexity:* Exactly  $\max(\text{last} - \text{first} - 1, 0)$  applications of the corresponding comparisons.

```
template<class ForwardIterator>
 constexpr pair<ForwardIterator, ForwardIterator>
 minmax_element(ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator>
 pair<ForwardIterator, ForwardIterator>
 minmax_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);

template<class ForwardIterator, class Compare>
 constexpr pair<ForwardIterator, ForwardIterator>
 minmax_element(ForwardIterator first, ForwardIterator last, Compare comp);
template<class ExecutionPolicy, class ForwardIterator, class Compare>
 pair<ForwardIterator, ForwardIterator>
 minmax_element(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, Compare comp);
```

29 *Returns:*  $\text{make\_pair}(\text{first}, \text{first})$  if  $[\text{first}, \text{last})$  is empty, otherwise  $\text{make\_pair}(m, M)$ , where  $m$  is the first iterator in  $[\text{first}, \text{last})$  such that no iterator in the range refers to a smaller element, and where  $M$  is the last iterator<sup>266</sup> in  $[\text{first}, \text{last})$  such that no iterator in the range refers to a larger element.

30 *Complexity:* At most  $\max(\lfloor \frac{3}{2}(N - 1) \rfloor, 0)$  applications of the corresponding predicate, where  $N$  is  $\text{last} - \text{first}$ .

### 28.7.9 Bounded value

[alg.clamp]

```
template<class T>
 constexpr const T& clamp(const T& v, const T& lo, const T& hi);
template<class T, class Compare>
 constexpr const T& clamp(const T& v, const T& lo, const T& hi, Compare comp);
```

1 *Requires:* The value of  $\text{lo}$  shall be no greater than  $\text{hi}$ . For the first form, type  $T$  shall be `LessThanComparable` (Table 21).

2 *Returns:*  $\text{lo}$  if  $v$  is less than  $\text{lo}$ ,  $\text{hi}$  if  $\text{hi}$  is less than  $v$ , otherwise  $v$ .

<sup>266</sup>) This behavior intentionally differs from `max_element()`.

[ *Note*: If NaN is avoided, T can be a floating-point type. — *end note* ]

*Complexity*: At most two comparisons.

### 28.7.10 Lexicographical comparison

[alg.lex.comparison]

```
template<class InputIterator1, class InputIterator2>
 bool
 lexicographical_compare(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 bool
 lexicographical_compare(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2);

template<class InputIterator1, class InputIterator2, class Compare>
 bool
 lexicographical_compare(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, InputIterator2 last2,
 Compare comp);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class Compare>
 bool
 lexicographical_compare(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2, ForwardIterator2 last2,
 Compare comp);
```

*Returns*: **true** if the sequence of elements defined by the range [first1, last1) is lexicographically less than the sequence of elements defined by the range [first2, last2) and **false** otherwise.

*Complexity*: At most 2min(last1 - first1, last2 - first2) applications of the corresponding comparison.

*Remarks*: If two sequences have the same number of elements and their corresponding elements (if any) are equivalent, then neither sequence is lexicographically less than the other. If one sequence is a prefix of the other, then the shorter sequence is lexicographically less than the longer sequence. Otherwise, the lexicographical comparison of the sequences yields the same result as the comparison of the first corresponding pair of elements that are not equivalent.

[ *Example*: The following sample implementation satisfies these requirements:

```
for (; first1 != last1 && first2 != last2 ; ++first1, (void) ++first2) {
 if (*first1 < *first2) return true;
 if (*first2 < *first1) return false;
}
return first1 == last1 && first2 != last2;
```

— *end example* ]

[ *Note*: An empty sequence is lexicographically less than any non-empty sequence, but not less than any empty sequence. — *end note* ]

### 28.7.11 Permutation generators

[alg.permutation.generators]

```
template<class BidirectionalIterator>
 bool next_permutation(BidirectionalIterator first,
 BidirectionalIterator last);
```

```
template<class BidirectionalIterator, class Compare>
 bool next_permutation(BidirectionalIterator first,
 BidirectionalIterator last, Compare comp);
```

- 1     *Requires:* BidirectionalIterator shall satisfy the requirements of ValueSwappable (20.5.3.2).
- 2     *Effects:* Takes a sequence defined by the range [first, last) and transforms it into the next permutation. The next permutation is found by assuming that the set of all permutations is lexicographically sorted with respect to operator< or comp.
- 3     *Returns:* true if such a permutation exists. Otherwise, it transforms the sequence into the smallest permutation, that is, the ascendingly sorted one, and returns false.
- 4     *Complexity:* At most (last - first) / 2 swaps.

```
template<class BidirectionalIterator>
 bool prev_permutation(BidirectionalIterator first,
 BidirectionalIterator last);
```

```
template<class BidirectionalIterator, class Compare>
 bool prev_permutation(BidirectionalIterator first,
 BidirectionalIterator last, Compare comp);
```

- 5     *Requires:* BidirectionalIterator shall satisfy the requirements of ValueSwappable (20.5.3.2).
- 6     *Effects:* Takes a sequence defined by the range [first, last) and transforms it into the previous permutation. The previous permutation is found by assuming that the set of all permutations is lexicographically sorted with respect to operator< or comp.
- 7     *Returns:* true if such a permutation exists. Otherwise, it transforms the sequence into the largest permutation, that is, the descendingly sorted one, and returns false.
- 8     *Complexity:* At most (last - first) / 2 swaps.

## 28.8 C library algorithms

[alg.c.library]

- 1     [ *Note:* The header <cstdlib> (21.2.2) declares the functions described in this subclause. — end note ]

```
void* bsearch(const void* key, const void* base, size_t nmemb, size_t size,
 c-compare-pred* compar);
void* bsearch(const void* key, const void* base, size_t nmemb, size_t size,
 compare-pred* compar);
void qsort(void* base, size_t nmemb, size_t size, c-compare-pred* compar);
void qsort(void* base, size_t nmemb, size_t size, compare-pred* compar);
```

- 2     *Effects:* These functions have the semantics specified in the C standard library.
- 3     *Remarks:* The behavior is undefined unless the objects in the array pointed to by base are of trivial type.
- 4     *Throws:* Any exception thrown by compar() (20.5.5.12).

SEE ALSO: ISO C 7.22.5.



## 29 Numerics library

[numerics]

### 29.1 General

[numerics.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to perform seminumerical operations.
- <sup>2</sup> The following subclauses describe components for complex number types, random number generation, numeric ( $n$ -at-a-time) arrays, generalized numeric algorithms, and mathematical functions for floating-point types, as summarized in Table 101.

Table 101 — Numerics library summary

| Subclause                                                            | Header(s)            |
|----------------------------------------------------------------------|----------------------|
| <a href="#">29.2</a> Definitions                                     |                      |
| <a href="#">29.3</a> Requirements                                    |                      |
| <a href="#">29.4</a> Floating-point environment                      | <cfenv>              |
| <a href="#">29.5</a> Complex numbers                                 | <complex>            |
| <a href="#">29.6</a> Random number generation                        | <random>             |
| <a href="#">29.7</a> Numeric arrays                                  | <valarray>           |
| <a href="#">29.8</a> Generalized numeric operations                  | <numeric>            |
| <a href="#">29.9</a> Mathematical functions for floating-point types | <cmath><br><cstdlib> |

### 29.2 Definitions

[numerics.defns]

- <sup>1</sup> Define *GENERALIZED\_NONCOMMUTATIVE\_SUM*(*op*, *a1*, ..., *aN*) as follows:
  - (1.1) — *a1* when *N* is 1, otherwise
  - (1.2) — *op*(*GENERALIZED\_NONCOMMUTATIVE\_SUM*(*op*, *a1*, ..., *aK*),  
*GENERALIZED\_NONCOMMUTATIVE\_SUM*(*op*, *aM*, ..., *aN*)) for any *K* where  $1 < K + 1 = M \leq N$ .
- <sup>2</sup> Define *GENERALIZED\_SUM*(*op*, *a1*, ..., *aN*) as *GENERALIZED\_NONCOMMUTATIVE\_SUM*(*op*, *b1*, ..., *bN*), where *b1*, ..., *bN* may be any permutation of *a1*, ..., *aN*.

### 29.3 Numeric type requirements

[numeric.requirements]

- <sup>1</sup> The **complex** and **valarray** components are parameterized by the type of information they contain and manipulate. A C++ program shall instantiate these components only with a type *T* that satisfies the following requirements:<sup>267</sup>
  - (1.1) — *T* is not an abstract class (it has no pure virtual member functions);
  - (1.2) — *T* is not a reference type;
  - (1.3) — *T* is not cv-qualified;
  - (1.4) — If *T* is a class, it has a public default constructor;
  - (1.5) — If *T* is a class, it has a public copy constructor with the signature *T::T*(const *T*&);
  - (1.6) — If *T* is a class, it has a public destructor;

<sup>267</sup>) In other words, value types. These include arithmetic types, pointers, the library class **complex**, and instantiations of **valarray** for value types.

- (1.7) — If **T** is a class, it has a public assignment operator whose signature is either **T& T::operator=(const T&)** or **T& T::operator=(T)**
- (1.8) — If **T** is a class, its assignment operator, copy and default constructors, and destructor shall correspond to each other in the following sense:
  - (1.8.1) — Initialization of raw storage using the copy constructor on the value of **T()**, however obtained, is semantically equivalent to value-initialization of the same raw storage.
  - (1.8.2) — Initialization of raw storage using the default constructor, followed by assignment, is semantically equivalent to initialization of raw storage using the copy constructor.
  - (1.8.3) — Destruction of an object, followed by initialization of its raw storage using the copy constructor, is semantically equivalent to assignment to the original object.

[*Note:* This rule states, in part, that there shall not be any subtle differences in the semantics of initialization versus assignment. This gives an implementation considerable flexibility in how arrays are initialized.

[*Example:* An implementation is allowed to initialize a **valarray** by allocating storage using the **new** operator (which implies a call to the default constructor for each element) and then assigning each element its value. Or the implementation can allocate raw storage and use the copy constructor to initialize each element. — *end example*]

If the distinction between initialization and assignment is important for a class, or if it fails to satisfy any of the other conditions listed above, the programmer should use **vector** (26.3.11) instead of **valarray** for that class. — *end note*]

- (1.9) — If **T** is a class, it does not overload unary **operator&**.
  - 2 If any operation on **T** throws an exception the effects are undefined.
  - 3 In addition, many member and related functions of **valarray<T>** can be successfully instantiated and will exhibit well-defined behavior if and only if **T** satisfies additional requirements specified for each such member or related function.
  - 4 [*Example:* It is valid to instantiate **valarray<complex>**, but **operator>()** will not be successfully instantiated for **valarray<complex>** operands, since **complex** does not have any ordering operators. — *end example*]

## 29.4 The floating-point environment

[cfenv]

### 29.4.1 Header <cfenv> synopsis

[cfenv.syn]

```
#define FE_ALL_EXCEPT see below
#define FE_DIVBYZERO see below
#define FE_INEXACT see below
#define FE_INVALID see below
#define FE_OVERFLOW see below
#define FE_UNDERFLOW see below

#define FE_DOWNWARD see below
#define FE_TONEAREST see below
#define FE_TOWARDZERO see below
#define FE_UPWARD see below

#define FE_DFL_ENV see below

namespace std {
 // types
 using fenv_t = object type;
 using fexcept_t = integer type;
```

```

// functions
int feclearexcept(int except);
int fegetexceptflag(fexcept_t* pflag, int except);
int feraiseexcept(int except);
int fesetexceptflag(const fexcept_t* pflag, int except);
int fetestexcept(int except);

int fegetround();
int fesetround(int mode);

int fegetenv(fenv_t* penv);
int feholdexcept(fenv_t* penv);
int fesetenv(const fenv_t* penv);
int feupdateenv(const fenv_t* penv);
}

```

- <sup>1</sup> The contents and meaning of the header `<cfenv>` are the same as the C standard library header `<fenv.h>`. [ *Note:* This International Standard does not require an implementation to support the `FENV_ACCESS` pragma; it is implementation-defined (19.6) whether the pragma is supported. As a consequence, it is implementation-defined whether these functions can be used to test floating-point status flags, set floating-point control modes, or run under non-default mode settings. If the pragma is used to enable control over the floating-point environment, this International Standard does not specify the effect on floating-point evaluation in constant expressions. — *end note* ]
- <sup>2</sup> The floating-point environment has thread storage duration (6.7.2). The initial state for a thread's floating-point environment is the state of the floating-point environment of the thread that constructs the corresponding **thread** object (33.3.2) at the time it constructed the object. [ *Note:* That is, the child thread gets the floating-point state of the parent thread at the time of the child's creation. — *end note* ]
- <sup>3</sup> A separate floating-point environment shall be maintained for each thread. Each function accesses the environment corresponding to its calling thread.

SEE ALSO: ISO C 7.6

## 29.5 Complex numbers

[complex.numbers]

- <sup>1</sup> The header `<complex>` defines a class template, and numerous functions for representing and manipulating complex numbers.
- <sup>2</sup> The effect of instantiating the template `complex` for any type other than `float`, `double`, or `long double` is unspecified. The specializations `complex<float>`, `complex<double>`, and `complex<long double>` are literal types (6.9).
- <sup>3</sup> If the result of a function is not mathematically defined or not in the range of representable values for its type, the behavior is undefined.
- <sup>4</sup> If **z** is an lvalue expression of type `cv complex<T>` then:
  - (4.1) — the expression `reinterpret_cast<cv T(&)[2]>(z)` shall be well-formed,
  - (4.2) — `reinterpret_cast<cv T(&)[2]>(z)[0]` shall designate the real part of **z**, and
  - (4.3) — `reinterpret_cast<cv T(&)[2]>(z)[1]` shall designate the imaginary part of **z**.

Moreover, if **a** is an expression of type `cv complex<T>*` and the expression **a**[**i**] is well-defined for an integer expression **i**, then:

- (4.4) — `reinterpret_cast<cv T*>(a)[2*i]` shall designate the real part of **a**[**i**], and
- (4.5) — `reinterpret_cast<cv T*>(a)[2*i + 1]` shall designate the imaginary part of **a**[**i**].

## 29.5.1 Header &lt;complex&gt; synopsis

[complex.syn]

```

namespace std {
 template<class T> class complex;
 template<> class complex<float>;
 template<> class complex<double>;
 template<> class complex<long double>;

 // 29.5.6, operators
 template<class T>
 complex<T> operator+(const complex<T>&, const complex<T>&);
 template<class T> complex<T> operator+(const complex<T>&, const T&);
 template<class T> complex<T> operator+(const T&, const complex<T>&);

 template<class T> complex<T> operator-(
 const complex<T>&, const complex<T>&);
 template<class T> complex<T> operator-(const complex<T>&, const T&);
 template<class T> complex<T> operator-(const T&, const complex<T>&);

 template<class T> complex<T> operator*(
 const complex<T>&, const complex<T>&);
 template<class T> complex<T> operator*(const complex<T>&, const T&);
 template<class T> complex<T> operator*(const T&, const complex<T>&);

 template<class T> complex<T> operator/(
 const complex<T>&, const complex<T>&);
 template<class T> complex<T> operator/(const complex<T>&, const T&);
 template<class T> complex<T> operator/(const T&, const complex<T>&);

 template<class T> complex<T> operator+(const complex<T>&);
 template<class T> complex<T> operator-(const complex<T>&);

 template<class T> constexpr bool operator==(
 const complex<T>&, const complex<T>&);
 template<class T> constexpr bool operator==(const complex<T>&, const T&);
 template<class T> constexpr bool operator==(const T&, const complex<T>&);

 template<class T> constexpr bool operator!=(const complex<T>&, const complex<T>&);
 template<class T> constexpr bool operator!=(const complex<T>&, const T&);
 template<class T> constexpr bool operator!=(const T&, const complex<T>&);

 template<class T, class charT, class traits>
 basic_istream<charT, traits>&
 operator>>(basic_istream<charT, traits>&, complex<T>&);

 template<class T, class charT, class traits>
 basic_ostream<charT, traits>&
 operator<<(basic_ostream<charT, traits>&, const complex<T>&);

 // 29.5.7, values
 template<class T> constexpr T real(const complex<T>&);
 template<class T> constexpr T imag(const complex<T>&);

 template<class T> T abs(const complex<T>&);
 template<class T> T arg(const complex<T>&);
 template<class T> T norm(const complex<T>&);

```

```

template<class T> complex<T> conj(const complex<T>&);
template<class T> complex<T> proj(const complex<T>&);
template<class T> complex<T> polar(const T&, const T& = 0);

// 29.5.8, transcendentals
template<class T> complex<T> acos(const complex<T>&);
template<class T> complex<T> asin(const complex<T>&);
template<class T> complex<T> atan(const complex<T>&);

template<class T> complex<T> acosh(const complex<T>&);
template<class T> complex<T> asinh(const complex<T>&);
template<class T> complex<T> atanh(const complex<T>&);

template<class T> complex<T> cos (const complex<T>&);
template<class T> complex<T> cosh (const complex<T>&);
template<class T> complex<T> exp (const complex<T>&);
template<class T> complex<T> log (const complex<T>&);
template<class T> complex<T> log10(const complex<T>&);

template<class T> complex<T> pow (const complex<T>&, const T&);
template<class T> complex<T> pow (const complex<T>&, const complex<T>&);
template<class T> complex<T> pow (const T&, const complex<T>&);

template<class T> complex<T> sin (const complex<T>&);
template<class T> complex<T> sinh (const complex<T>&);
template<class T> complex<T> sqrt (const complex<T>&);
template<class T> complex<T> tan (const complex<T>&);
template<class T> complex<T> tanh (const complex<T>&);

// 29.5.10, complex literals
inline namespace literals {
 inline namespace complex_literals {
 constexpr complex<long double> operator""il(long double);
 constexpr complex<long double> operator""il(unsigned long long);
 constexpr complex<double> operator""i(long double);
 constexpr complex<double> operator""i(unsigned long long);
 constexpr complex<float> operator""if(long double);
 constexpr complex<float> operator""if(unsigned long long);
 }
}
}

```

## 29.5.2 Class template complex

[complex]

```

namespace std {
 template<class T>
 class complex {
 public:
 using value_type = T;

 constexpr complex(const T& re = T(), const T& im = T());
 constexpr complex(const complex&);
 template<class X> constexpr complex(const complex<X>&);

 constexpr T real() const;

```

```

void real(T);
constexpr T imag() const;
void imag(T);

complex<T>& operator= (const T&);
complex<T>& operator+=(const T&);
complex<T>& operator-=(const T&);
complex<T>& operator*=(const T&);
complex<T>& operator/=(const T&);

complex& operator=(const complex&);
template<class X> complex<T>& operator= (const complex<X>&);
template<class X> complex<T>& operator+=(const complex<X>&);
template<class X> complex<T>& operator-=(const complex<X>&);
template<class X> complex<T>& operator*=(const complex<X>&);
template<class X> complex<T>& operator/=(const complex<X>&);
};
}

```

- <sup>1</sup> The class `complex` describes an object that can store the Cartesian components, `real()` and `imag()`, of a complex number.

### 29.5.3 complex specializations

[complex.special]

```

namespace std {
 template<> class complex<float> {
 public:
 using value_type = float;

 constexpr complex(float re = 0.0f, float im = 0.0f);
 constexpr explicit complex(const complex<double>&);
 constexpr explicit complex(const complex<long double>&);

 constexpr float real() const;
 void real(float);
 constexpr float imag() const;
 void imag(float);

 complex<float>& operator= (float);
 complex<float>& operator+=(float);
 complex<float>& operator-=(float);
 complex<float>& operator*=(float);
 complex<float>& operator/=(float);

 complex<float>& operator=(const complex<float>&);
 template<class X> complex<float>& operator= (const complex<X>&);
 template<class X> complex<float>& operator+=(const complex<X>&);
 template<class X> complex<float>& operator-=(const complex<X>&);
 template<class X> complex<float>& operator*=(const complex<X>&);
 template<class X> complex<float>& operator/=(const complex<X>&);
 };

 template<> class complex<double> {
 public:
 using value_type = double;

 constexpr complex(double re = 0.0, double im = 0.0);

```

```

constexpr complex(const complex<float>&);
constexpr explicit complex(const complex<long double>&);

constexpr double real() const;
void real(double);
constexpr double imag() const;
void imag(double);

complex<double>& operator= (double);
complex<double>& operator+=(double);
complex<double>& operator-=(double);
complex<double>& operator*=(double);
complex<double>& operator/=(double);

complex<double>& operator=(const complex<double>&);
template<class X> complex<double>& operator= (const complex<X>&);
template<class X> complex<double>& operator+=(const complex<X>&);
template<class X> complex<double>& operator-=(const complex<X>&);
template<class X> complex<double>& operator*=(const complex<X>&);
template<class X> complex<double>& operator/=(const complex<X>&);
};

template<> class complex<long double> {
public:
 using value_type = long double;

 constexpr complex(long double re = 0.0L, long double im = 0.0L);
 constexpr complex(const complex<float>&);
 constexpr complex(const complex<double>&);

 constexpr long double real() const;
 void real(long double);
 constexpr long double imag() const;
 void imag(long double);

 complex<long double>& operator=(const complex<long double>&);
 complex<long double>& operator= (long double);
 complex<long double>& operator+=(long double);
 complex<long double>& operator-=(long double);
 complex<long double>& operator*=(long double);
 complex<long double>& operator/=(long double);

 template<class X> complex<long double>& operator= (const complex<X>&);
 template<class X> complex<long double>& operator+=(const complex<X>&);
 template<class X> complex<long double>& operator-=(const complex<X>&);
 template<class X> complex<long double>& operator*=(const complex<X>&);
 template<class X> complex<long double>& operator/=(const complex<X>&);
};
}

```

#### 29.5.4 complex member functions

[complex.members]

```
template<class T> constexpr complex(const T& re = T(), const T& im = T());
```

- 1 *Effects:* Constructs an object of class `complex`.
- 2 *Postconditions:* `real() == re` && `imag() == im`.

```
constexpr T real() const;
```

3       *Returns:* The value of the real component.

```
void real(T val);
```

4       *Effects:* Assigns `val` to the real component.

```
constexpr T imag() const;
```

5       *Returns:* The value of the imaginary component.

```
void imag(T val);
```

6       *Effects:* Assigns `val` to the imaginary component.

## 29.5.5 complex member operators

[complex.member.ops]

```
complex<T>& operator+=(const T& rhs);
```

1       *Effects:* Adds the scalar value `rhs` to the real part of the complex value `*this` and stores the result in the real part of `*this`, leaving the imaginary part unchanged.

2       *Returns:* `*this`.

```
complex<T>& operator-=(const T& rhs);
```

3       *Effects:* Subtracts the scalar value `rhs` from the real part of the complex value `*this` and stores the result in the real part of `*this`, leaving the imaginary part unchanged.

4       *Returns:* `*this`.

```
complex<T>& operator*=(const T& rhs);
```

5       *Effects:* Multiplies the scalar value `rhs` by the complex value `*this` and stores the result in `*this`.

6       *Returns:* `*this`.

```
complex<T>& operator/=(const T& rhs);
```

7       *Effects:* Divides the scalar value `rhs` into the complex value `*this` and stores the result in `*this`.

8       *Returns:* `*this`.

```
template<class X> complex<T>& operator+=(const complex<X>& rhs);
```

9       *Effects:* Adds the complex value `rhs` to the complex value `*this` and stores the sum in `*this`.

10      *Returns:* `*this`.

```
template<class X> complex<T>& operator-=(const complex<X>& rhs);
```

11      *Effects:* Subtracts the complex value `rhs` from the complex value `*this` and stores the difference in `*this`.

12      *Returns:* `*this`.

```
template<class X> complex<T>& operator*=(const complex<X>& rhs);
```

13      *Effects:* Multiplies the complex value `rhs` by the complex value `*this` and stores the product in `*this`.

14      *Returns:* `*this`.

```
template<class X> complex<T>& operator/=(const complex<X>& rhs);
```

15      *Effects:* Divides the complex value `rhs` into the complex value `*this` and stores the quotient in `*this`.

16      *Returns:* `*this`.



## 29.5.6 complex non-member operations

[complex.ops]

```
template<class T> complex<T> operator+(const complex<T>& lhs);
```

1 *Returns:* complex<T>(lhs).

2 *Remarks:* unary operator.

```
template<class T> complex<T> operator+(const complex<T>& lhs, const complex<T>& rhs);
template<class T> complex<T> operator+(const complex<T>& lhs, const T& rhs);
template<class T> complex<T> operator+(const T& lhs, const complex<T>& rhs);
```

3 *Returns:* complex<T>(lhs) += rhs.

```
template<class T> complex<T> operator-(const complex<T>& lhs);
```

4 *Returns:* complex<T>(-lhs.real(), -lhs.imag()).

5 *Remarks:* unary operator.

```
template<class T> complex<T> operator-(const complex<T>& lhs, const complex<T>& rhs);
template<class T> complex<T> operator-(const complex<T>& lhs, const T& rhs);
template<class T> complex<T> operator-(const T& lhs, const complex<T>& rhs);
```

6 *Returns:* complex<T>(lhs) -= rhs.

```
template<class T> complex<T> operator*(const complex<T>& lhs, const complex<T>& rhs);
template<class T> complex<T> operator*(const complex<T>& lhs, const T& rhs);
template<class T> complex<T> operator*(const T& lhs, const complex<T>& rhs);
```

7 *Returns:* complex<T>(lhs) \*= rhs.

```
template<class T> complex<T> operator/(const complex<T>& lhs, const complex<T>& rhs);
template<class T> complex<T> operator/(const complex<T>& lhs, const T& rhs);
template<class T> complex<T> operator/(const T& lhs, const complex<T>& rhs);
```

8 *Returns:* complex<T>(lhs) /= rhs.

```
template<class T> constexpr bool operator==(const complex<T>& lhs, const complex<T>& rhs);
template<class T> constexpr bool operator==(const complex<T>& lhs, const T& rhs);
template<class T> constexpr bool operator==(const T& lhs, const complex<T>& rhs);
```

9 *Returns:* lhs.real() == rhs.real() && lhs.imag() == rhs.imag().

10 *Remarks:* The imaginary part is assumed to be T(), or 0.0, for the T arguments.

```
template<class T> constexpr bool operator!=(const complex<T>& lhs, const complex<T>& rhs);
template<class T> constexpr bool operator!=(const complex<T>& lhs, const T& rhs);
template<class T> constexpr bool operator!=(const T& lhs, const complex<T>& rhs);
```

11 *Returns:* rhs.real() != lhs.real() || rhs.imag() != lhs.imag().

```
template<class T, class charT, class traits>
basic_istream<charT, traits>&
operator>>(basic_istream<charT, traits>& is, complex<T>& x);
```

12 *Requires:* The input values shall be convertible to T.

13 *Effects:* Extracts a complex number x of the form: u, (u), or (u,v), where u is the real part and v is the imaginary part (30.7.4.2).

14 If bad input is encountered, calls is.setstate(ios\_base::failbit) (which may throw ios::failure (30.5.5.4)).

15 *Returns:* is.

- 16 *Remarks:* This extraction is performed as a series of simpler extractions. Therefore, the skipping of whitespace is specified to be the same for each of the simpler extractions.

```
template<class T, class charT, class traits>
basic_ostream<charT, traits>&
operator<<(basic_ostream<charT, traits>& o, const complex<T>& x);
```

- 17 *Effects:* Inserts the complex number `x` onto the stream `o` as if it were implemented as follows:

```
 basic_ostringstream<charT, traits> s;
 s.flags(o.flags());
 s.imbue(o.getloc());
 s.precision(o.precision());
 s << '(' << x.real() << "," << x.imag() << ')';
 return o << s.str();
```

- 18 [ *Note:* In a locale in which comma is used as a decimal point character, the use of comma as a field separator can be ambiguous. Inserting `showpoint` into the output stream forces all outputs to show an explicit decimal point character; as a result, all inserted sequences of complex numbers can be extracted unambiguously. — *end note* ]

### 29.5.7 complex value operations

[complex.value.ops]

```
template<class T> constexpr T real(const complex<T>& x);
```

- 1 *Returns:* `x.real()`.

```
template<class T> constexpr T imag(const complex<T>& x);
```

- 2 *Returns:* `x.imag()`.

```
template<class T> T abs(const complex<T>& x);
```

- 3 *Returns:* The magnitude of `x`.

```
template<class T> T arg(const complex<T>& x);
```

- 4 *Returns:* The phase angle of `x`, or `atan2(imag(x), real(x))`.

```
template<class T> T norm(const complex<T>& x);
```

- 5 *Returns:* The squared magnitude of `x`.

```
template<class T> complex<T> conj(const complex<T>& x);
```

- 6 *Returns:* The complex conjugate of `x`.

```
template<class T> complex<T> proj(const complex<T>& x);
```

- 7 *Returns:* The projection of `x` onto the Riemann sphere.

- 8 *Remarks:* Behaves the same as the C function `cproj`, defined in 7.3.9.4.

```
template<class T> complex<T> polar(const T& rho, const T& theta = 0);
```

- 9 *Requires:* `rho` shall be non-negative and non-NaN. `theta` shall be finite.

- 10 *Returns:* The complex value corresponding to a complex number whose magnitude is `rho` and whose phase angle is `theta`.

### 29.5.8 complex transcendentals

[complex.transcendentals]

```
template<class T> complex<T> acos(const complex<T>& x);
```

1       *Returns:* The complex arc cosine of  $x$ .

2       *Remarks:* Behaves the same as C function `cacos`, defined in 7.3.5.1.

```
template<class T> complex<T> asin(const complex<T>& x);
```

3       *Returns:* The complex arc sine of  $x$ .

4       *Remarks:* Behaves the same as C function `casin`, defined in 7.3.5.2.

```
template<class T> complex<T> atan(const complex<T>& x);
```

5       *Returns:* The complex arc tangent of  $x$ .

6       *Remarks:* Behaves the same as C function `catan`, defined in 7.3.5.3.

```
template<class T> complex<T> acosh(const complex<T>& x);
```

7       *Returns:* The complex arc hyperbolic cosine of  $x$ .

8       *Remarks:* Behaves the same as C function `cacosh`, defined in 7.3.6.1.

```
template<class T> complex<T> asinh(const complex<T>& x);
```

9       *Returns:* The complex arc hyperbolic sine of  $x$ .

10      *Remarks:* Behaves the same as C function `casinh`, defined in 7.3.6.2.

```
template<class T> complex<T> atanh(const complex<T>& x);
```

11      *Returns:* The complex arc hyperbolic tangent of  $x$ .

12      *Remarks:* Behaves the same as C function `catanh`, defined in 7.3.6.3.

```
template<class T> complex<T> cos(const complex<T>& x);
```

13      *Returns:* The complex cosine of  $x$ .

```
template<class T> complex<T> cosh(const complex<T>& x);
```

14      *Returns:* The complex hyperbolic cosine of  $x$ .

```
template<class T> complex<T> exp(const complex<T>& x);
```

15      *Returns:* The complex base- $e$  exponential of  $x$ .

```
template<class T> complex<T> log(const complex<T>& x);
```

16      *Returns:* The complex natural (base- $e$ ) logarithm of  $x$ . For all  $x$ , `imag(log(x))` lies in the interval  $[-\pi, \pi]$ , and when  $x$  is a negative real number, `imag(log(x))` is  $\pi$ .

17      *Remarks:* The branch cuts are along the negative real axis.

```
template<class T> complex<T> log10(const complex<T>& x);
```

18      *Returns:* The complex common (base-10) logarithm of  $x$ , defined as  $\log(x) / \log(10)$ .

19      *Remarks:* The branch cuts are along the negative real axis.

```
template<class T> complex<T> pow(const complex<T>& x, const complex<T>& y);
template<class T> complex<T> pow(const complex<T>& x, const T& y);
template<class T> complex<T> pow(const T& x, const complex<T>& y);
```

20      *Returns:* The complex power of base  $x$  raised to the  $y^{\text{th}}$  power, defined as  $\exp(y * \log(x))$ . The value returned for `pow(0, 0)` is implementation-defined.

21      *Remarks:* The branch cuts are along the negative real axis.

```
template<class T> complex<T> sin(const complex<T>& x);
```

22 *Returns:* The complex sine of *x*.

```
template<class T> complex<T> sinh(const complex<T>& x);
```

23 *Returns:* The complex hyperbolic sine of *x*.

```
template<class T> complex<T> sqrt(const complex<T>& x);
```

24 *Returns:* The complex square root of *x*, in the range of the right half-plane. If the argument is a negative real number, the value returned lies on the positive imaginary axis.

25 *Remarks:* The branch cuts are along the negative real axis.

```
template<class T> complex<T> tan(const complex<T>& x);
```

26 *Returns:* The complex tangent of *x*.

```
template<class T> complex<T> tanh(const complex<T>& x);
```

27 *Returns:* The complex hyperbolic tangent of *x*.

### 29.5.9 Additional overloads

[**cmplx.over**]

1 The following function templates shall have additional overloads:

|             |             |
|-------------|-------------|
| <b>arg</b>  | <b>norm</b> |
| <b>conj</b> | <b>proj</b> |
| <b>imag</b> | <b>real</b> |

2 The additional overloads shall be sufficient to ensure:

1. If the argument has type **long double**, then it is effectively cast to **complex<long double>**.
2. Otherwise, if the argument has type **double** or an integer type, then it is effectively cast to **complex<double>**.
3. Otherwise, if the argument has type **float**, then it is effectively cast to **complex<float>**.

3 Function template **pow** shall have additional overloads sufficient to ensure, for a call with at least one argument of type **complex<T>**:

1. If either argument has type **complex<long double>** or type **long double**, then both arguments are effectively cast to **complex<long double>**.
2. Otherwise, if either argument has type **complex<double>**, **double**, or an integer type, then both arguments are effectively cast to **complex<double>**.
3. Otherwise, if either argument has type **complex<float>** or **float**, then both arguments are effectively cast to **complex<float>**.

### 29.5.10 Suffixes for complex number literals

[**complex.literals**]

1 This section describes literal suffixes for constructing complex number literals. The suffixes **i**, **il**, and **if** create complex numbers of the types **complex<double>**, **complex<long double>**, and **complex<float>** respectively, with their imaginary part denoted by the given literal number and the real part being zero.

```
constexpr complex<long double> operator""il(long double d);
constexpr complex<long double> operator""il(unsigned long long d);
```

2 *Returns:* **complex<long double>{0.0L, static\_cast<long double>(d)}**.

```
constexpr complex<double> operator""i(long double d);
constexpr complex<double> operator""i(unsigned long long d);
```

3 *Returns:* `complex<double>{0.0, static_cast<double>(d)}`.

```
constexpr complex<float> operator""if(long double d);
constexpr complex<float> operator""if(unsigned long long d);
```

4 *Returns:* `complex<float>{0.0f, static_cast<float>(d)}`.

## 29.6 Random number generation

[rand]

1 This subclause defines a facility for generating (pseudo-)random numbers.

2 In addition to a few utilities, four categories of entities are described: *uniform random bit generators*, *random number engines*, *random number engine adaptors*, and *random number distributions*. These categorizations are applicable to types that satisfy the corresponding requirements, to objects instantiated from such types, and to templates producing such types when instantiated. [ *Note:* These entities are specified in such a way as to permit the binding of any uniform random bit generator object *e* as the argument to any random number distribution object *d*, thus producing a zero-argument function object such as given by `bind(d,e)`. — *end note* ]

3 Each of the entities specified via this subclause has an associated arithmetic type (6.9.1) identified as **result\_type**. With *T* as the **result\_type** thus associated with such an entity, that entity is characterized:

- a) as *boolean* or equivalently as *boolean-valued*, if *T* is `bool`;
- b) otherwise as *integral* or equivalently as *integer-valued*, if `numeric_limits<T>::is_integer` is `true`;
- c) otherwise as *floating* or equivalently as *real-valued*.

If integer-valued, an entity may optionally be further characterized as *signed* or *unsigned*, according to `numeric_limits<T>::is_signed`.

4 Unless otherwise specified, all descriptions of calculations in this subclause use mathematical real numbers.

5 Throughout this subclause, the operators `bitand`, `bitor`, and `xor` denote the respective conventional bitwise operations. Further:

- a) the operator `rshift` denotes a bitwise right shift with zero-valued bits appearing in the high bits of the result, and
- b) the operator `lshiftw` denotes a bitwise left shift with zero-valued bits appearing in the low bits of the result, and whose result is always taken modulo  $2^w$ .

### 29.6.1 Requirements

[rand.req]

#### 29.6.1.1 General requirements

[rand.req.genl]

1 Throughout this subclause 29.6, the effect of instantiating a template:

- a) that has a template type parameter named **Sseq** is undefined unless the corresponding template argument is cv-unqualified and satisfies the requirements of seed sequence (29.6.1.2).
- b) that has a template type parameter named **URBG** is undefined unless the corresponding template argument is cv-unqualified and satisfies the requirements of uniform random bit generator (29.6.1.3).
- c) that has a template type parameter named **Engine** is undefined unless the corresponding template argument is cv-unqualified and satisfies the requirements of random number engine (29.6.1.4).
- d) that has a template type parameter named **RealType** is undefined unless the corresponding template argument is cv-unqualified and is one of `float`, `double`, or `long double`.
- e) that has a template type parameter named **IntType** is undefined unless the corresponding template argument is cv-unqualified and is one of `short`, `int`, `long`, `long long`, `unsigned short`, `unsigned int`, `unsigned long`, or `unsigned long long`.

- f) that has a template type parameter named `UIntType` is undefined unless the corresponding template argument is cv-unqualified and is one of `unsigned short`, `unsigned int`, `unsigned long`, or `unsigned long long`.
- <sup>2</sup> Throughout this subclause 29.6, phrases of the form “`x` is an iterator of a specific kind” shall be interpreted as equivalent to the more formal requirement that “`x` is a value of a type satisfying the requirements of the specified iterator type”.
- <sup>3</sup> Throughout this subclause 29.6, any constructor that can be called with a single argument and that satisfies a requirement specified in this subclause shall be declared **explicit**.

### 29.6.1.2 Seed sequence requirements

[rand.req.seedseq]

- <sup>1</sup> A *seed sequence* is an object that consumes a sequence of integer-valued data and produces a requested number of unsigned integer values  $i$ ,  $0 \leq i < 2^{32}$ , based on the consumed data. [Note: Such an object provides a mechanism to avoid replication of streams of random variates. This can be useful, for example, in applications requiring large numbers of random number engines. — end note]
- <sup>2</sup> A class `S` satisfies the requirements of a seed sequence if the expressions shown in Table 102 are valid and have the indicated semantics, and if `S` also satisfies all other requirements of this section 29.6.1.2. In that Table and throughout this section:
- a) `T` is the type named by `S`’s associated `result_type`;
  - b) `q` is a value of `S` and `r` is a possibly const value of `S`;
  - c) `ib` and `ie` are input iterators with an unsigned integer `value_type` of at least 32 bits;
  - d) `rb` and `re` are mutable random access iterators with an unsigned integer `value_type` of at least 32 bits;
  - e) `ob` is an output iterator; and
  - f) `il` is a value of `initializer_list<T>`.

Table 102 — Seed sequence requirements

| Expression                  | Return type    | Pre/post-condition                                                                                                                     | Complexity                                   |
|-----------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| <code>S::result_type</code> | <code>T</code> | <code>T</code> is an unsigned integer type (6.9.1) of at least 32 bits.                                                                | compile-time                                 |
| <code>S()</code>            |                | Creates a seed sequence with the same initial state as all other default-constructed seed sequences of type <code>S</code> .           | constant                                     |
| <code>S(ib, ie)</code>      |                | Creates a seed sequence having internal state that depends on some or all of the bits of the supplied sequence <code>[ib, ie)</code> . | $\mathcal{O}(ie - ib)$                       |
| <code>S(il)</code>          |                | Same as <code>S(il.begin(), il.end())</code> .                                                                                         | same as <code>S(il.begin(), il.end())</code> |

Table 102 — Seed sequence requirements (continued)

| Expression                      | Return type         | Pre/post-condition                                                                                                                                                                                                                                                               | Complexity                           |
|---------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| <code>q.generate(rb, re)</code> | <code>void</code>   | Does nothing if <code>rb == re</code> .<br>Otherwise, fills the supplied sequence <code>[rb, re)</code> with 32-bit quantities that depend on the sequence supplied to the constructor and possibly also depend on the history of <code>generate</code> 's previous invocations. | $\mathcal{O}(\text{re} - \text{rb})$ |
| <code>r.size()</code>           | <code>size_t</code> | The number of 32-bit units that would be copied by a call to <code>r.param</code> .                                                                                                                                                                                              | constant                             |
| <code>r.param(ob)</code>        | <code>void</code>   | Copies to the given destination a sequence of 32-bit units that can be provided to the constructor of a second object of type <code>S</code> , and that would reproduce in that second object a state indistinguishable from the state of the first object.                      | $\mathcal{O}(\text{r.size}())$       |

**29.6.1.3 Uniform random bit generator requirements****[rand.req.urng]**

- <sup>1</sup> A *uniform random bit generator* `g` of type `G` is a function object returning unsigned integer values such that each value in the range of possible results has (ideally) equal probability of being returned. [ *Note*: The degree to which `g`'s results approximate the ideal is often determined statistically. — *end note* ]
- <sup>2</sup> A class `G` satisfies the requirements of a *uniform random bit generator* if the expressions shown in Table 103 are valid and have the indicated semantics, and if `G` also satisfies all other requirements of this section 29.6.1.3. In that Table and throughout this section:
- a) `T` is the type named by `G`'s associated `result_type`, and
  - b) `g` is a value of `G`.

Table 103 — Uniform random bit generator requirements

| Expression                  | Return type    | Pre/post-condition                                                           | Complexity            |
|-----------------------------|----------------|------------------------------------------------------------------------------|-----------------------|
| <code>G::result_type</code> | <code>T</code> | <code>T</code> is an unsigned integer type (6.9.1).                          | compile-time          |
| <code>g()</code>            | <code>T</code> | Returns a value in the closed interval <code>[G::min(), G::max())</code> .   | amortized<br>constant |
| <code>G::min()</code>       | <code>T</code> | Denotes the least value potentially returned by <code>operator()</code> .    | compile-time          |
| <code>G::max()</code>       | <code>T</code> | Denotes the greatest value potentially returned by <code>operator()</code> . | compile-time          |

<sup>3</sup> The following relation shall hold: `G::min() < G::max()`.

#### 29.6.1.4 Random number engine requirements

[rand.req.eng]

- <sup>1</sup> A *random number engine* (commonly shortened to *engine*) `e` of type `E` is a uniform random bit generator that additionally meets the requirements (e.g., for seeding and for input/output) specified in this section.
- <sup>2</sup> At any given time, `e` has a state `ei` for some integer  $i \geq 0$ . Upon construction, `e` has an initial state `e0`. An engine's state may be established via a constructor, a `seed` function, assignment, or a suitable `operator>>`.
- <sup>3</sup> `E`'s specification shall define:
- a) the size of `E`'s state in multiples of the size of `result_type`, given as an integral constant expression;
  - b) the *transition algorithm* `TA` by which `e`'s state `ei` is advanced to its *successor state* `ei+1`; and
  - c) the *generation algorithm* `GA` by which an engine's state is mapped to a value of type `result_type`.
- <sup>4</sup> A class `E` that satisfies the requirements of a uniform random bit generator (29.6.1.3) also satisfies the requirements of a *random number engine* if the expressions shown in Table 104 are valid and have the indicated semantics, and if `E` also satisfies all other requirements of this section 29.6.1.4. In that Table and throughout this section:
- a) `T` is the type named by `E`'s associated `result_type`;
  - b) `e` is a value of `E`, `v` is an lvalue of `E`, `x` and `y` are (possibly `const`) values of `E`;
  - c) `s` is a value of `T`;
  - d) `q` is an lvalue satisfying the requirements of a seed sequence (29.6.1.2);
  - e) `z` is a value of type `unsigned long long`;
  - f) `os` is an lvalue of the type of some class template specialization `basic_ostream<charT, traits>`; and
  - g) `is` is an lvalue of the type of some class template specialization `basic_istream<charT, traits>`;
- where `charT` and `traits` are constrained according to Clause 24 and Clause 30.

Table 104 — Random number engine requirements

| Expression                       | Return type       | Pre/post-condition                                                                                                   | Complexity                                                                                       |
|----------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <code>E()</code>                 |                   | Creates an engine with the same initial state as all other default-constructed engines of type <code>E</code> .      | $\mathcal{O}(\text{size of state})$                                                              |
| <code>E(x)</code>                |                   | Creates an engine that compares equal to <code>x</code> .                                                            | $\mathcal{O}(\text{size of state})$                                                              |
| <code>E(s)</code>                |                   | Creates an engine with initial state determined by <code>s</code> .                                                  | $\mathcal{O}(\text{size of state})$                                                              |
| <code>E(q)</code> <sup>268</sup> |                   | Creates an engine with an initial state that depends on a sequence produced by one call to <code>q.generate</code> . | same as complexity of <code>q.generate</code> called on a sequence whose length is size of state |
| <code>e.seed()</code>            | <code>void</code> | <i>Postconditions:</i> <code>e == E()</code> .                                                                       | same as <code>E()</code>                                                                         |

<sup>268</sup> This constructor (as well as the subsequent corresponding `seed()` function) may be particularly useful to applications requiring a large number of independent random sequences.



| Expression                               | Return type                              | Pre/post-condition                                                                                                                                                                                                                                                                                                                                                                                   | Complexity                                                                        |
|------------------------------------------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| <code>e.seed(s)</code>                   | <code>void</code>                        | <i>Postconditions:</i> <code>e == E(s)</code> .                                                                                                                                                                                                                                                                                                                                                      | same as <code>E(s)</code>                                                         |
| <code>e.seed(q)</code>                   | <code>void</code>                        | <i>Postconditions:</i> <code>e == E(q)</code> .                                                                                                                                                                                                                                                                                                                                                      | same as <code>E(q)</code>                                                         |
| <code>e()</code>                         | <code>T</code>                           | Advances <code>e</code> 's state <code>e<sub>i</sub></code> to <code>e<sub>i+1</sub></code> = <code>TA(e<sub>i</sub>)</code> and returns <code>GA(e<sub>i</sub>)</code> .                                                                                                                                                                                                                            | per Table 103                                                                     |
| <code>e.discard(z)</code> <sup>269</sup> | <code>void</code>                        | Advances <code>e</code> 's state <code>e<sub>i</sub></code> to <code>e<sub>i+z</sub></code> by any means equivalent to <code>z</code> consecutive calls <code>e()</code> .                                                                                                                                                                                                                           | no worse than the complexity of <code>z</code> consecutive calls <code>e()</code> |
| <code>x == y</code>                      | <code>bool</code>                        | This operator is an equivalence relation. With $S_x$ and $S_y$ as the infinite sequences of values that would be generated by repeated future calls to <code>x()</code> and <code>y()</code> , respectively, returns <code>true</code> if $S_x = S_y$ ; else returns <code>false</code> .                                                                                                            | $\mathcal{O}(\text{size of state})$                                               |
| <code>x != y</code>                      | <code>bool</code>                        | <code>!(x == y)</code> .                                                                                                                                                                                                                                                                                                                                                                             | $\mathcal{O}(\text{size of state})$                                               |
| <code>os &lt;&lt; x</code>               | reference to the type of <code>os</code> | With <code>os.fmtflags</code> set to <code>ios_base::dec   ios_base::left</code> and the fill character set to the space character, writes to <code>os</code> the textual representation of <code>x</code> 's current state. In the output, adjacent numbers are separated by one or more space characters.<br><i>Postconditions:</i> The <code>os.fmtflags</code> and fill character are unchanged. | $\mathcal{O}(\text{size of state})$                                               |

<sup>269</sup>) This operation is common in user code, and can often be implemented in an engine-specific manner so as to provide significant performance improvements over an equivalent naive loop that makes `z` consecutive calls `e()`.

| Expression                 | Return type                                 | Pre/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Complexity                          |
|----------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <code>is &gt;&gt; v</code> | reference to the type of<br><code>is</code> | With <code>is.fmtflags</code> set to<br><code>ios_base::dec</code> , sets <code>v</code> 's state<br>as determined by reading its<br>textual representation from <code>is</code> .<br>If bad input is encountered,<br>ensures that <code>v</code> 's state is<br>unchanged by the operation and<br>calls<br><code>is.setstate(ios::failbit)</code><br>(which may throw<br><code>ios::failure (30.5.5.4)</code> ). If a<br>textual representation written<br>via <code>os &lt;&lt; x</code> was subsequently<br>read via <code>is &gt;&gt; v</code> , then <code>x == v</code><br>provided that there have been<br>no intervening invocations of <code>x</code><br>or of <code>v</code> .<br><i>Requires:</i> <code>is</code> provides a textual<br>representation that was<br>previously written using an<br>output stream whose imbued<br>locale was the same as that of<br><code>is</code> , and whose type's template<br>specialization arguments <code>charT</code><br>and <code>traits</code> were respectively<br>the same as those of <code>is</code> .<br><i>Postconditions:</i> The <code>is.fmtflags</code><br>are unchanged. | $\mathcal{O}(\text{size of state})$ |

- <sup>5</sup> `E` shall meet the requirements of `CopyConstructible` (Table 24) and `CopyAssignable` (Table 26) types. These operations shall each be of complexity no worse than  $\mathcal{O}(\text{size of state})$ .

#### 29.6.1.5 Random number engine adaptor requirements

[rand.req.adapt]

- <sup>1</sup> A *random number engine adaptor* (commonly shortened to *adaptor*) `a` of type `A` is a random number engine that takes values produced by some other random number engine, and applies an algorithm to those values in order to deliver a sequence of values with different randomness properties. An engine `b` of type `B` adapted in this way is termed a *base engine* in this context. The expression `a.base()` shall be valid and shall return a const reference to `a`'s base engine.
- <sup>2</sup> The requirements of a random number engine type shall be interpreted as follows with respect to a random number engine adaptor type.

`A::A();`

- <sup>3</sup> *Effects:* The base engine is initialized as if by its default constructor.

`bool operator==(const A& a1, const A& a2);`

- <sup>4</sup> *Returns:* `true` if `a1`'s base engine is equal to `a2`'s base engine. Otherwise returns `false`.

`A::A(result_type s);`

- <sup>5</sup> *Effects:* The base engine is initialized with `s`.

```
template<class Sseq> A::A(Sseq& q);
```

6 *Effects:* The base engine is initialized with **q**.

```
void seed();
```

7 *Effects:* With **b** as the base engine, invokes **b.seed()**.

```
void seed(result_type s);
```

8 *Effects:* With **b** as the base engine, invokes **b.seed(s)**.

```
template<class Sseq> void seed(Sseq& q);
```

9 *Effects:* With **b** as the base engine, invokes **b.seed(q)**.

10 **A** shall also satisfy the following additional requirements:

- a) The complexity of each function shall not exceed the complexity of the corresponding function applied to the base engine.
- b) The state of **A** shall include the state of its base engine. The size of **A**'s state shall be no less than the size of the base engine.
- c) Copying **A**'s state (e.g., during copy construction or copy assignment) shall include copying the state of the base engine of **A**.
- d) The textual representation of **A** shall include the textual representation of its base engine.

#### 29.6.1.6 Random number distribution requirements

[rand.req.dist]

- 1 A *random number distribution* (commonly shortened to *distribution*) **d** of type **D** is a function object returning values that are distributed according to an associated mathematical *probability density function*  $p(z)$  or according to an associated *discrete probability function*  $P(z_i)$ . A distribution's specification identifies its associated probability function  $p(z)$  or  $P(z_i)$ .
- 2 An associated probability function is typically expressed using certain externally-supplied quantities known as the *parameters of the distribution*. Such distribution parameters are identified in this context by writing, for example,  $p(z | a, b)$  or  $P(z_i | a, b)$ , to name specific parameters, or by writing, for example,  $p(z | \{p\})$  or  $P(z_i | \{p\})$ , to denote a distribution's parameters **p** taken as a whole.
- 3 A class **D** satisfies the requirements of a *random number distribution* if the expressions shown in Table 105 are valid and have the indicated semantics, and if **D** and its associated types also satisfy all other requirements of this section 29.6.1.6. In that Table and throughout this section,
  - a) **T** is the type named by **D**'s associated **result\_type**;
  - b) **P** is the type named by **D**'s associated **param\_type**;
  - c) **d** is a value of **D**, and **x** and **y** are (possibly **const**) values of **D**;
  - d) **glb** and **lub** are values of **T** respectively corresponding to the greatest lower bound and the least upper bound on the values potentially returned by **d**'s **operator()**, as determined by the current values of **d**'s parameters;
  - e) **p** is a (possibly **const**) value of **P**;
  - f) **g**, **g1**, and **g2** are lvalues of a type satisfying the requirements of a uniform random bit generator (29.6.1.3);
  - g) **os** is an lvalue of the type of some class template specialization **basic\_ostream<charT, traits>**; and
  - h) **is** is an lvalue of the type of some class template specialization **basic\_istream<charT, traits>**;

where **charT** and **traits** are constrained according to Clauses 24 and 30.

Table 105 — Random number distribution requirements

| Expression                  | Return type | Pre/post-condition                                                                                                                                                                                                   | Complexity                                    |
|-----------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <code>D::result_type</code> | T           | T is an arithmetic type (6.9.1).                                                                                                                                                                                     | compile-time                                  |
| <code>D::param_type</code>  | P           |                                                                                                                                                                                                                      | compile-time                                  |
| <code>D()</code>            |             | Creates a distribution whose behavior is indistinguishable from that of any other newly default-constructed distribution of type D.                                                                                  | constant                                      |
| <code>D(p)</code>           |             | Creates a distribution whose behavior is indistinguishable from that of a distribution newly constructed directly from the values used to construct p.                                                               | same as p's construction                      |
| <code>d.reset()</code>      | void        | Subsequent uses of d do not depend on values produced by any engine prior to invoking <code>reset</code> .                                                                                                           | constant                                      |
| <code>x.param()</code>      | P           | Returns a value p such that <code>D(p).param() == p</code> .                                                                                                                                                         | no worse than the complexity of D(p)          |
| <code>d.param(p)</code>     | void        | <i>Postconditions:</i> <code>d.param() == p</code> .                                                                                                                                                                 | no worse than the complexity of D(p)          |
| <code>d(g)</code>           | T           | With <code>p = d.param()</code> , the sequence of numbers returned by successive invocations with the same object g is randomly distributed according to the associated $p(z   \{p\})$ or $P(z_i   \{p\})$ function. | amortized constant number of invocations of g |
| <code>d(g,p)</code>         | T           | The sequence of numbers returned by successive invocations with the same objects g and p is randomly distributed according to the associated $p(z   \{p\})$ or $P(z_i   \{p\})$ function.                            | amortized constant number of invocations of g |
| <code>x.min()</code>        | T           | Returns <code>glb</code> .                                                                                                                                                                                           | constant                                      |
| <code>x.max()</code>        | T           | Returns <code>lub</code> .                                                                                                                                                                                           | constant                                      |

| Expression                 | Return type                              | Pre/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Complexity                    |
|----------------------------|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| <code>x == y</code>        | <code>bool</code>                        | This operator is an equivalence relation. Returns <code>true</code> if <code>x.param() == y.param()</code> and $S_1 = S_2$ , where $S_1$ and $S_2$ are the infinite sequences of values that would be generated, respectively, by repeated future calls to <code>x(g1)</code> and <code>y(g2)</code> whenever <code>g1 == g2</code> . Otherwise returns <code>false</code> .                                                                                                                                                                                                                                                                                                  | constant                      |
| <code>x != y</code>        | <code>bool</code>                        | <code>!(x == y)</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | same as <code>x == y</code> . |
| <code>os &lt;&lt; x</code> | reference to the type of <code>os</code> | Writes to <code>os</code> a textual representation for the parameters and the additional internal data of <code>x</code> .<br><i>Postconditions:</i> The <code>os.fmtflags</code> and fill character are unchanged.                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                               |
| <code>is &gt;&gt; d</code> | reference to the type of <code>is</code> | Restores from <code>is</code> the parameters and additional internal data of the lvalue <code>d</code> . If bad input is encountered, ensures that <code>d</code> is unchanged by the operation and calls<br><code>is.setstate(ios::failbit)</code><br>(which may throw <code>ios::failure</code> (30.5.5.4)).<br><i>Requires:</i> <code>is</code> provides a textual representation that was previously written using an <code>os</code> whose imbued locale and whose type's template specialization arguments <code>charT</code> and <code>traits</code> were the same as those of <code>is</code> .<br><i>Postconditions:</i> The <code>is.fmtflags</code> are unchanged. |                               |

- <sup>4</sup> D shall satisfy the requirements of `CopyConstructible` (Table 24) and `CopyAssignable` (Table 26) types.
- <sup>5</sup> The sequence of numbers produced by repeated invocations of `d(g)` shall be independent of any invocation of `os << d` or of any `const` member function of D between any of the invocations `d(g)`.
- <sup>6</sup> If a textual representation is written using `os << x` and that representation is restored into the same or a different object `y` of the same type using `is >> y`, repeated invocations of `y(g)` shall produce the same sequence of numbers as would repeated invocations of `x(g)`.
- <sup>7</sup> It is unspecified whether `D::param_type` is declared as a (nested) `class` or via a `typedef`. In this subclause 29.6, declarations of `D::param_type` are in the form of `typedefs` for convenience of exposition only.
- <sup>8</sup> P shall satisfy the requirements of `CopyConstructible` (Table 24), `CopyAssignable` (Table 26), and `EqualityComparable` (Table 20) types.
- <sup>9</sup> For each of the constructors of D taking arguments corresponding to parameters of the distribution, P shall

have a corresponding constructor subject to the same requirements and taking arguments identical in number, type, and default values. Moreover, for each of the member functions of D that return values corresponding to parameters of the distribution, P shall have a corresponding member function with the identical name, type, and semantics.

- <sup>10</sup> P shall have a declaration of the form

```
using distribution_type = D;
```

## 29.6.2 Header <random> synopsis

[rand.synopsis]

```
#include <initializer_list>

namespace std {
 // 29.6.3.1, class template linear_congruential_engine
 template<class UIntType, UIntType a, UIntType c, UIntType m>
 class linear_congruential_engine;

 // 29.6.3.2, class template mersenne_twister_engine
 template<class UIntType, size_t w, size_t n, size_t m, size_t r,
 UIntType a, size_t u, UIntType d, size_t s,
 UIntType b, size_t t,
 UIntType c, size_t l, UIntType f>
 class mersenne_twister_engine;

 // 29.6.3.3, class template subtract_with_carry_engine
 template<class UIntType, size_t w, size_t s, size_t r>
 class subtract_with_carry_engine;

 // 29.6.4.2, class template discard_block_engine
 template<class Engine, size_t p, size_t r>
 class discard_block_engine;

 // 29.6.4.3, class template independent_bits_engine
 template<class Engine, size_t w, class UIntType>
 class independent_bits_engine;

 // 29.6.4.4, class template shuffle_order_engine
 template<class Engine, size_t k>
 class shuffle_order_engine;

 // 29.6.5, engines and engine adaptors with predefined parameters
 using minstd_rand0 = see below;
 using minstd_rand = see below;
 using mt19937 = see below;
 using mt19937_64 = see below;
 using ranlux24_base = see below;
 using ranlux48_base = see below;
 using ranlux24 = see below;
 using ranlux48 = see below;
 using knuth_b = see below;

 using default_random_engine = see below;

 // 29.6.6, class random_device
 class random_device;
```

```
// 29.6.7.1, class seed_seq
class seed_seq;

// 29.6.7.2, function template generate_canonical
template<class RealType, size_t bits, class URBG>
 RealType generate_canonical(URBG& g);

// 29.6.8.2.1, class template uniform_int_distribution
template<class IntType = int>
 class uniform_int_distribution;

// 29.6.8.2.2, class template uniform_real_distribution
template<class RealType = double>
 class uniform_real_distribution;

// 29.6.8.3.1, class bernoulli_distribution
class bernoulli_distribution;

// 29.6.8.3.2, class template binomial_distribution
template<class IntType = int>
 class binomial_distribution;

// 29.6.8.3.3, class template geometric_distribution
template<class IntType = int>
 class geometric_distribution;

// 29.6.8.3.4, class template negative_binomial_distribution
template<class IntType = int>
 class negative_binomial_distribution;

// 29.6.8.4.1, class template poisson_distribution
template<class IntType = int>
 class poisson_distribution;

// 29.6.8.4.2, class template exponential_distribution
template<class RealType = double>
 class exponential_distribution;

// 29.6.8.4.3, class template gamma_distribution
template<class RealType = double>
 class gamma_distribution;

// 29.6.8.4.4, class template weibull_distribution
template<class RealType = double>
 class weibull_distribution;

// 29.6.8.4.5, class template extreme_value_distribution
template<class RealType = double>
 class extreme_value_distribution;

// 29.6.8.5.1, class template normal_distribution
template<class RealType = double>
 class normal_distribution;

// 29.6.8.5.2, class template lognormal_distribution
```

```

template<class RealType = double>
 class lognormal_distribution;

// 29.6.8.5.3, class template chi_squared_distribution
template<class RealType = double>
 class chi_squared_distribution;

// 29.6.8.5.4, class template cauchy_distribution
template<class RealType = double>
 class cauchy_distribution;

// 29.6.8.5.5, class template fisher_f_distribution
template<class RealType = double>
 class fisher_f_distribution;

// 29.6.8.5.6, class template student_t_distribution
template<class RealType = double>
 class student_t_distribution;

// 29.6.8.6.1, class template discrete_distribution
template<class IntType = int>
 class discrete_distribution;

// 29.6.8.6.2, class template piecewise_constant_distribution
template<class RealType = double>
 class piecewise_constant_distribution;

// 29.6.8.6.3, class template piecewise_linear_distribution
template<class RealType = double>
 class piecewise_linear_distribution;
}

```

### 29.6.3 Random number engine class templates

[rand.eng]

- <sup>1</sup> Each type instantiated from a class template specified in this section 29.6.3 satisfies the requirements of a random number engine (29.6.1.4) type.
- <sup>2</sup> Except where specified otherwise, the complexity of each function specified in this section 29.6.3 is constant.
- <sup>3</sup> Except where specified otherwise, no function described in this section 29.6.3 throws an exception.
- <sup>4</sup> Every function described in this section 29.6.3 that has a function parameter `q` of type `Sseq&` for a template type parameter named `Sseq` that is different from type `seed_seq` throws what and when the invocation of `q.generate` throws.
- <sup>5</sup> Descriptions are provided in this section 29.6.3 only for engine operations that are not described in 29.6.1.4 or for operations where there is additional semantic information. In particular, declarations for copy constructors, for copy assignment operators, for streaming operators, and for equality and inequality operators are not shown in the synopses.
- <sup>6</sup> Each template specified in this section 29.6.3 requires one or more relationships, involving the value(s) of its non-type template parameter(s), to hold. A program instantiating any of these templates is ill-formed if any such required relationship fails to hold.
- <sup>7</sup> For every random number engine and for every random number engine adaptor `X` defined in this subclause (29.6.3) and in subclause 29.6.4:
  - (7.1) — if the constructor



```
template <class Sseq> explicit X(Sseq& q);
```

is called with a type `Sseq` that does not qualify as a seed sequence, then this constructor shall not participate in overload resolution;

- (7.2) — if the member function

```
template <class Sseq> void seed(Sseq& q);
```

is called with a type `Sseq` that does not qualify as a seed sequence, then this function shall not participate in overload resolution.

The extent to which an implementation determines that a type cannot be a seed sequence is unspecified, except that as a minimum a type shall not qualify as a seed sequence if it is implicitly convertible to `X::result_type`.

### 29.6.3.1 Class template `linear_congruential_engine`

[rand.eng.lcong]

- <sup>1</sup> A `linear_congruential_engine` random number engine produces unsigned integer random numbers. The state  $x_i$  of a `linear_congruential_engine` object `x` is of size 1 and consists of a single integer. The transition algorithm is a modular linear function of the form  $TA(x_i) = (a \cdot x_i + c) \bmod m$ ; the generation algorithm is  $GA(x_i) = x_{i+1}$ .

```
template<class UIntType, UIntType a, UIntType c, UIntType m>
class linear_congruential_engine {
public:
 // types
 using result_type = UIntType;

 // engine characteristics
 static constexpr result_type multiplier = a;
 static constexpr result_type increment = c;
 static constexpr result_type modulus = m;
 static constexpr result_type min() { return c == 0u ? 1u: 0u; }
 static constexpr result_type max() { return m - 1u; }
 static constexpr result_type default_seed = 1u;

 // constructors and seeding functions
 explicit linear_congruential_engine(result_type s = default_seed);
 template<class Sseq> explicit linear_congruential_engine(Sseq& q);
 void seed(result_type s = default_seed);
 template<class Sseq> void seed(Sseq& q);

 // generating functions
 result_type operator()();
 void discard(unsigned long long z);
};
```

- <sup>2</sup> If the template parameter `m` is 0, the modulus  $m$  used throughout this section 29.6.3.1 is `numeric_limits<result_type>::max()` plus 1. [Note:  $m$  need not be representable as a value of type `result_type`. — end note]
- <sup>3</sup> If the template parameter `m` is not 0, the following relations shall hold:  $a < m$  and  $c < m$ .
- <sup>4</sup> The textual representation consists of the value of  $x_i$ .

```
explicit linear_congruential_engine(result_type s = default_seed);
```

- <sup>5</sup> *Effects:* Constructs a `linear_congruential_engine` object. If  $c \bmod m$  is 0 and  $s \bmod m$  is 0, sets the engine's state to 1, otherwise sets the engine's state to  $s \bmod m$ .

```
template<class Sseq> explicit linear_congruential_engine(Sseq& q);
```

- <sup>6</sup> *Effects:* Constructs a `linear_congruential_engine` object. With  $k = \left\lceil \frac{\log_2 m}{32} \right\rceil$  and  $a$  an array (or equivalent) of length  $k + 3$ , invokes `q.generate(a + 0, a + k + 3)` and then computes  $S = \left( \sum_{j=0}^{k-1} a_{j+3} \cdot 2^{32j} \right) \bmod m$ . If  $c \bmod m$  is 0 and  $S$  is 0, sets the engine's state to 1, else sets the engine's state to  $S$ .

### 29.6.3.2 Class template `mersenne_twister_engine` [rand.eng.mers]

- <sup>1</sup> A `mersenne_twister_engine` random number engine<sup>270</sup> produces unsigned integer random numbers in the closed interval  $[0, 2^w - 1]$ . The state  $x_i$  of a `mersenne_twister_engine` object  $x$  is of size  $n$  and consists of a sequence  $X$  of  $n$  values of the type delivered by  $x$ ; all subscripts applied to  $X$  are to be taken modulo  $n$ .
- <sup>2</sup> The transition algorithm employs a twisted generalized feedback shift register defined by shift values  $n$  and  $m$ , a twist value  $r$ , and a conditional xor-mask  $a$ . To improve the uniformity of the result, the bits of the raw shift register are additionally *tempered* (i.e., scrambled) according to a bit-scrambling matrix defined by values  $u, d, s, b, t, c$ , and  $\ell$ .

The state transition is performed as follows:

- a) Concatenate the upper  $w - r$  bits of  $X_{i-n}$  with the lower  $r$  bits of  $X_{i+1-n}$  to obtain an unsigned integer value  $Y$ .
- b) With  $\alpha = a \cdot (Y \text{ bitand } 1)$ , set  $X_i$  to  $X_{i+m-n} \text{ xor } (Y \text{ rshift } 1) \text{ xor } \alpha$ .

The sequence  $X$  is initialized with the help of an initialization multiplier  $f$ .

- <sup>3</sup> The generation algorithm determines the unsigned integer values  $z_1, z_2, z_3, z_4$  as follows, then delivers  $z_4$  as its result:
- a) Let  $z_1 = X_i \text{ xor } ((X_i \text{ rshift } u) \text{ bitand } d)$ .
  - b) Let  $z_2 = z_1 \text{ xor } ((z_1 \text{ lshift}_w s) \text{ bitand } b)$ .
  - c) Let  $z_3 = z_2 \text{ xor } ((z_2 \text{ lshift}_w t) \text{ bitand } c)$ .
  - d) Let  $z_4 = z_3 \text{ xor } (z_3 \text{ rshift } \ell)$ .

```
template<class UIntType, size_t w, size_t n, size_t m, size_t r,
 UIntType a, size_t u, UIntType d, size_t s,
 UIntType b, size_t t,
 UIntType c, size_t l, UIntType f>
class mersenne_twister_engine {
public:
 // types
 using result_type = UIntType;

 // engine characteristics
 static constexpr size_t word_size = w;
 static constexpr size_t state_size = n;
 static constexpr size_t shift_size = m;
 static constexpr size_t mask_bits = r;
 static constexpr UIntType xor_mask = a;
 static constexpr size_t tempering_u = u;
 static constexpr UIntType tempering_d = d;
 static constexpr size_t tempering_s = s;
 static constexpr UIntType tempering_b = b;
```

<sup>270</sup>) The name of this engine refers, in part, to a property of its period: For properly-selected values of the parameters, the period is closely related to a large Mersenne prime number.

```

static constexpr size_t tempering_t = t;
static constexpr UIntType tempering_c = c;
static constexpr size_t tempering_l = l;
static constexpr UIntType initialization_multiplier = f;
static constexpr result_type min() { return 0; }
static constexpr result_type max() { return 2w - 1; }
static constexpr result_type default_seed = 5489u;

// constructors and seeding functions
explicit mersenne_twister_engine(result_type value = default_seed);
template<class Sseq> explicit mersenne_twister_engine(Sseq& q);
void seed(result_type value = default_seed);
template<class Sseq> void seed(Sseq& q);

// generating functions
result_type operator()();
void discard(unsigned long long z);
};

```

- 4 The following relations shall hold:  $0 < m, m \leq n, 2u < w, r \leq w, u \leq w, s \leq w, t \leq w, l \leq w, w \leq \text{numeric\_limits}<\text{UIntType}>::\text{digits}, a \leq (1u < w) - 1u, b \leq (1u < w) - 1u, c \leq (1u < w) - 1u, d \leq (1u < w) - 1u$ , and  $f \leq (1u < w) - 1u$ .

- 5 The textual representation of  $\mathbf{x}_i$  consists of the values of  $X_{i-n}, \dots, X_{i-1}$ , in that order.

```
explicit mersenne_twister_engine(result_type value = default_seed);
```

- 6 *Effects:* Constructs a `mersenne_twister_engine` object. Sets  $X_{-n}$  to value mod  $2^w$ . Then, iteratively for  $i = 1-n, \dots, -1$ , sets  $X_i$  to

$$[f \cdot (X_{i-1} \text{ xor } (X_{i-1} \text{ rshift } (w - 2))) + i \bmod n] \bmod 2^w.$$

- 7 *Complexity:*  $\mathcal{O}(n)$ .

```
template<class Sseq> explicit mersenne_twister_engine(Sseq& q);
```

- 8 *Effects:* Constructs a `mersenne_twister_engine` object. With  $k = \lceil w/32 \rceil$  and  $a$  an array (or equivalent) of length  $n \cdot k$ , invokes `q.generate(a+0, a+n·k)` and then, iteratively for  $i = -n, \dots, -1$ , sets  $X_i$  to  $(\sum_{j=0}^{k-1} a_{k(i+n)+j} \cdot 2^{32j}) \bmod 2^w$ . Finally, if the most significant  $w - r$  bits of  $X_{-n}$  are zero, and if each of the other resulting  $X_i$  is 0, changes  $X_{-n}$  to  $2^{w-1}$ .

### 29.6.3.3 Class template `subtract_with_carry_engine`

[rand.eng.sub]

- 1 A `subtract_with_carry_engine` random number engine produces unsigned integer random numbers.

- 2 The state  $\mathbf{x}_i$  of a `subtract_with_carry_engine` object  $\mathbf{x}$  is of size  $\mathcal{O}(r)$ , and consists of a sequence  $X$  of  $r$  integer values  $0 \leq X_i < m = 2^w$ ; all subscripts applied to  $X$  are to be taken modulo  $r$ . The state  $\mathbf{x}_i$  additionally consists of an integer  $c$  (known as the *carry*) whose value is either 0 or 1.

- 3 The state transition is performed as follows:

a) Let  $Y = X_{i-s} - X_{i-r} - c$ .

b) Set  $X_i$  to  $y = Y \bmod m$ . Set  $c$  to 1 if  $Y < 0$ , otherwise set  $c$  to 0.

[Note: This algorithm corresponds to a modular linear function of the form  $\text{TA}(\mathbf{x}_i) = (a \cdot \mathbf{x}_i) \bmod b$ , where  $b$  is of the form  $m^r - m^s + 1$  and  $a = b - (b - 1)/m$ . — end note]

- 4 The generation algorithm is given by  $\text{GA}(\mathbf{x}_i) = y$ , where  $y$  is the value produced as a result of advancing the engine's state as described above.

```

template<class UIntType, size_t w, size_t s, size_t r>
class subtract_with_carry_engine {
public:
 // types
 using result_type = UIntType;

 // engine characteristics
 static constexpr size_t word_size = w;
 static constexpr size_t short_lag = s;
 static constexpr size_t long_lag = r;
 static constexpr result_type min() { return 0; }
 static constexpr result_type max() { return m - 1; }
 static constexpr result_type default_seed = 19780503u;

 // constructors and seeding functions
 explicit subtract_with_carry_engine(result_type value = default_seed);
 template<class Sseq> explicit subtract_with_carry_engine(Sseq& q);
 void seed(result_type value = default_seed);
 template<class Sseq> void seed(Sseq& q);

 // generating functions
 result_type operator()();
 void discard(unsigned long long z);
};

```

5 The following relations shall hold:  $0u < s$ ,  $s < r$ ,  $0 < w$ , and  $w \leq \text{numeric\_limits}<\text{UIntType}>::\text{digits}$ .

6 The textual representation consists of the values of  $X_{i-r}, \dots, X_{i-1}$ , in that order, followed by  $c$ .

```
explicit subtract_with_carry_engine(result_type value = default_seed);
```

7 *Effects:* Constructs a `subtract_with_carry_engine` object. Sets the values of  $X_{-r}, \dots, X_{-1}$ , in that order, as specified below. If  $X_{-1}$  is then 0, sets  $c$  to 1; otherwise sets  $c$  to 0.

To set the values  $X_k$ , first construct `e`, a `linear_congruential_engine` object, as if by the following definition:

```

linear_congruential_engine<result_type,
 40014u, 0u, 2147483563u> e(value == 0u ? default_seed : value);

```

Then, to set each  $X_k$ , obtain new values  $z_0, \dots, z_{n-1}$  from  $n = \lceil w/32 \rceil$  successive invocations of `e` taken modulo  $2^{32}$ . Set  $X_k$  to  $\left(\sum_{j=0}^{n-1} z_j \cdot 2^{32j}\right) \bmod m$ .

8 *Complexity:* Exactly  $n \cdot r$  invocations of `e`.

```
template<class Sseq> explicit subtract_with_carry_engine(Sseq& q);
```

9 *Effects:* Constructs a `subtract_with_carry_engine` object. With  $k = \lceil w/32 \rceil$  and  $a$  an array (or equivalent) of length  $r \cdot k$ , invokes `q.generate(a+0, a+r \cdot k)` and then, iteratively for  $i = -r, \dots, -1$ , sets  $X_i$  to  $\left(\sum_{j=0}^{k-1} a_{k(i+r)+j} \cdot 2^{32j}\right) \bmod m$ . If  $X_{-1}$  is then 0, sets  $c$  to 1; otherwise sets  $c$  to 0.

## 29.6.4 Random number engine adaptor class templates

[rand.adapt]

### 29.6.4.1 In general

[rand.adapt.general]

1 Each type instantiated from a class template specified in this section 29.6.4 satisfies the requirements of a random number engine adaptor (29.6.1.5) type.

2 Except where specified otherwise, the complexity of each function specified in this section 29.6.4 is constant.

3 Except where specified otherwise, no function described in this section 29.6.4 throws an exception.

- <sup>4</sup> Every function described in this section 29.6.4 that has a function parameter `q` of type `Sseq&` for a template type parameter named `Sseq` that is different from type `seed_seq` throws what and when the invocation of `q.generate` throws.
- <sup>5</sup> Descriptions are provided in this section 29.6.4 only for adaptor operations that are not described in section 29.6.1.5 or for operations where there is additional semantic information. In particular, declarations for copy constructors, for copy assignment operators, for streaming operators, and for equality and inequality operators are not shown in the synopses.
- <sup>6</sup> Each template specified in this section 29.6.4 requires one or more relationships, involving the value(s) of its non-type template parameter(s), to hold. A program instantiating any of these templates is ill-formed if any such required relationship fails to hold.

#### 29.6.4.2 Class template `discard_block_engine`

[rand.adapt.disc]

- <sup>1</sup> A `discard_block_engine` random number engine adaptor produces random numbers selected from those produced by some base engine  $e$ . The state  $x_i$  of a `discard_block_engine` engine adaptor object  $x$  consists of the state  $e_i$  of its base engine  $e$  and an additional integer  $n$ . The size of the state is the size of  $e$ 's state plus 1.
- <sup>2</sup> The transition algorithm discards all but  $r > 0$  values from each block of  $p \geq r$  values delivered by  $e$ . The state transition is performed as follows: If  $n \geq r$ , advance the state of  $e$  from  $e_i$  to  $e_{i+p-r}$  and set  $n$  to 0. In any case, then increment  $n$  and advance  $e$ 's then-current state  $e_j$  to  $e_{j+1}$ .
- <sup>3</sup> The generation algorithm yields the value returned by the last invocation of `e()` while advancing  $e$ 's state as described above.

```
template<class Engine, size_t p, size_t r>
class discard_block_engine {
public:
 // types
 using result_type = typename Engine::result_type;

 // engine characteristics
 static constexpr size_t block_size = p;
 static constexpr size_t used_block = r;
 static constexpr result_type min() { return Engine::min(); }
 static constexpr result_type max() { return Engine::max(); }

 // constructors and seeding functions
 discard_block_engine();
 explicit discard_block_engine(const Engine& e);
 explicit discard_block_engine(Engine&& e);
 explicit discard_block_engine(result_type s);
 template<class Sseq> explicit discard_block_engine(Sseq& q);
 void seed();
 void seed(result_type s);
 template<class Sseq> void seed(Sseq& q);

 // generating functions
 result_type operator()();
 void discard(unsigned long long z);

 // property functions
 const Engine& base() const noexcept { return e; };

private:
```

```

 Engine e; // exposition only
 int n; // exposition only
};

```

- 4 The following relations shall hold:  $0 < r$  and  $r \leq p$ .
- 5 The textual representation consists of the textual representation of **e** followed by the value of **n**.
- 6 In addition to its behavior pursuant to section 29.6.1.5, each constructor that is not a copy constructor sets **n** to 0.

#### 29.6.4.3 Class template `independent_bits_engine` [rand.adapt.ibits]

- 1 An `independent_bits_engine` random number engine adaptor combines random numbers that are produced by some base engine *e*, so as to produce random numbers with a specified number of bits *w*. The state  $x_i$  of an `independent_bits_engine` engine adaptor object **x** consists of the state  $e_i$  of its base engine **e**; the size of the state is the size of *e*'s state.
- 2 The transition and generation algorithms are described in terms of the following integral constants:
  - a) Let  $R = e.max() - e.min() + 1$  and  $m = \lfloor \log_2 R \rfloor$ .
  - b) With *n* as determined below, let  $w_0 = \lfloor w/n \rfloor$ ,  $n_0 = n - w \bmod n$ ,  $y_0 = 2^{w_0} \lfloor R/2^{w_0} \rfloor$ , and  $y_1 = 2^{w_0+1} \lfloor R/2^{w_0+1} \rfloor$ .
  - c) Let  $n = \lceil w/m \rceil$  if and only if the relation  $R - y_0 \leq \lfloor y_0/n \rfloor$  holds as a result. Otherwise let  $n = 1 + \lceil w/m \rceil$ .

[Note: The relation  $w = n_0 w_0 + (n - n_0)(w_0 + 1)$  always holds. — end note]
- 3 The transition algorithm is carried out by invoking `e()` as often as needed to obtain  $n_0$  values less than  $y_0 + e.min()$  and  $n - n_0$  values less than  $y_1 + e.min()$ .
- 4 The generation algorithm uses the values produced while advancing the state as described above to yield a quantity *S* obtained as if by the following algorithm:

```

S = 0;
for (k = 0; k ≠ n0; k += 1) {
 do u = e() - e.min(); while (u ≥ y0);
 S = 2w0 · S + u mod 2w0;
}
for (k = n0; k ≠ n; k += 1) {
 do u = e() - e.min(); while (u ≥ y1);
 S = 2w0+1 · S + u mod 2w0+1;
}

template<class Engine, size_t w, class UIntType>
class independent_bits_engine {
public:
 // types
 using result_type = UIntType;

 // engine characteristics
 static constexpr result_type min() { return 0; }
 static constexpr result_type max() { return 2w - 1; }

 // constructors and seeding functions
 independent_bits_engine();
 explicit independent_bits_engine(const Engine& e);
 explicit independent_bits_engine(Engine&& e);
 explicit independent_bits_engine(result_type s);
 template<class Sseq> explicit independent_bits_engine(Sseq& q);
 void seed();

```

```

void seed(result_type s);
template<class Sseq> void seed(Sseq& q);

// generating functions
result_type operator()();
void discard(unsigned long long z);

// property functions
const Engine& base() const noexcept { return e; };

private:
 Engine e; // exposition only
};

```

5 The following relations shall hold:  $0 < w$  and  $w \leq \text{numeric\_limits}<\text{result\_type}>::\text{digits}$ .

6 The textual representation consists of the textual representation of  $e$ .

#### 29.6.4.4 Class template `shuffle_order_engine` [rand.adapt.shuf]

1 A `shuffle_order_engine` random number engine adaptor produces the same random numbers that are produced by some base engine  $e$ , but delivers them in a different sequence. The state  $x_i$  of a `shuffle_order_engine` engine adaptor object  $x$  consists of the state  $e_i$  of its base engine  $e$ , an additional value  $Y$  of the type delivered by  $e$ , and an additional sequence  $V$  of  $k$  values also of the type delivered by  $e$ . The size of the state is the size of  $e$ 's state plus  $k + 1$ .

2 The transition algorithm permutes the values produced by  $e$ . The state transition is performed as follows:

- a) Calculate an integer  $j = \left\lfloor \frac{k \cdot (Y - e_{\min})}{e_{\max} - e_{\min} + 1} \right\rfloor$ .
- b) Set  $Y$  to  $V_j$  and then set  $V_j$  to  $e()$ .

3 The generation algorithm yields the last value of  $Y$  produced while advancing  $e$ 's state as described above.

```

template<class Engine, size_t k>
class shuffle_order_engine {
public:
 // types
 using result_type = typename Engine::result_type;

 // engine characteristics
 static constexpr size_t table_size = k;
 static constexpr result_type min() { return Engine::min(); }
 static constexpr result_type max() { return Engine::max(); }

 // constructors and seeding functions
 shuffle_order_engine();
 explicit shuffle_order_engine(const Engine& e);
 explicit shuffle_order_engine(Engine&& e);
 explicit shuffle_order_engine(result_type s);
 template<class Sseq> explicit shuffle_order_engine(Sseq& q);
 void seed();
 void seed(result_type s);
 template<class Sseq> void seed(Sseq& q);

 // generating functions
 result_type operator()();
 void discard(unsigned long long z);

```

```

// property functions
const Engine& base() const noexcept { return e; };

private:
 Engine e; // exposition only
 result_type V[k]; // exposition only
 result_type Y; // exposition only
};

```

- 4 The following relation shall hold:  $0 < k$ .
- 5 The textual representation consists of the textual representation of **e**, followed by the **k** values of **V**, followed by the value of **Y**.
- 6 In addition to its behavior pursuant to section 29.6.1.5, each constructor that is not a copy constructor initializes **V**[0], ..., **V**[**k**-1] and **Y**, in that order, with values returned by successive invocations of **e**().

### 29.6.5 Engines and engine adaptors with predefined parameters [rand.predef]

```

using minstd_rand0 =
 linear_congruential_engine<uint_fast32_t, 16807, 0, 2147483647>;

```

- 1 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **minstd\_rand0** shall produce the value 1043618065.

```

using minstd_rand =
 linear_congruential_engine<uint_fast32_t, 48271, 0, 2147483647>;

```

- 2 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **minstd\_rand** shall produce the value 399268537.

```

using mt19937 =
 merzenne_twister_engine<uint_fast32_t,
 32,624,397,31,0x9908b0df,11,0xffffffff,7,0x9d2c5680,15,0xefc60000,18,1812433253>;

```

- 3 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **mt19937** shall produce the value 4123659995.

```

using mt19937_64 =
 merzenne_twister_engine<uint_fast64_t,
 64,312,156,31,0xb5026f5aa96619e9,29,
 0x5555555555555555,17,
 0x71d67ffeda60000,37,
 0xfff7eee000000000,43,
 6364136223846793005>;

```

- 4 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **mt19937\_64** shall produce the value 9981545732273789042.

```

using ranlux24_base =
 subtract_with_carry_engine<uint_fast32_t, 24, 10, 24>;

```

- 5 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **ranlux24\_base** shall produce the value 7937952.

```

using ranlux48_base =
 subtract_with_carry_engine<uint_fast64_t, 48, 5, 12>;

```

- 6 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type **ranlux48\_base** shall produce the value 61839128582725.



```
using ranlux24 = discard_block_engine<ranlux24_base, 223, 23>;
```

- 7 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type `ranlux24` shall produce the value 9901578.

```
using ranlux48 = discard_block_engine<ranlux48_base, 389, 11>;
```

- 8 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type `ranlux48` shall produce the value 249142670248501.

```
using knuth_b = shuffle_order_engine<minstd_rand0, 256>;
```

- 9 *Required behavior:* The 10000<sup>th</sup> consecutive invocation of a default-constructed object of type `knuth_b` shall produce the value 1112339016.

```
using default_random_engine = implementation-defined;
```

- 10 *Remarks:* The choice of engine type named by this `typedef` is implementation-defined. [ *Note:* The implementation may select this type on the basis of performance, size, quality, or any combination of such factors, so as to provide at least acceptable engine behavior for relatively casual, inexperienced, and/or lightweight use. Because different implementations may select different underlying engine types, code that uses this `typedef` need not generate identical sequences across implementations. — *end note* ]

### 29.6.6 Class `random_device`

[`rand.device`]

- 1 A `random_device` uniform random bit generator produces nondeterministic random numbers.
- 2 If implementation limitations prevent generating nondeterministic random numbers, the implementation may employ a random number engine.

```
class random_device {
public:
 // types
 using result_type = unsigned int;

 // generator characteristics
 static constexpr result_type min() { return numeric_limits<result_type>::min(); }
 static constexpr result_type max() { return numeric_limits<result_type>::max(); }

 // constructors
 explicit random_device(const string& token = implementation-defined);

 // generating functions
 result_type operator()();

 // property functions
 double entropy() const noexcept;

 // no copy functions
 random_device(const random_device&) = delete;
 void operator=(const random_device&) = delete;
};
```

```
explicit random_device(const string& token = implementation-defined);
```

- 3 *Effects:* Constructs a `random_device` nondeterministic uniform random bit generator object. The semantics and default value of the `token` parameter are implementation-defined.<sup>271</sup>

271) The parameter is intended to allow an implementation to differentiate between different sources of randomness.

- 4 *Throws:* A value of an implementation-defined type derived from `exception` if the `random_device` could not be initialized.

```
double entropy() const noexcept;
```

- 5 *Returns:* If the implementation employs a random number engine, returns 0.0. Otherwise, returns an entropy estimate<sup>272</sup> for the random numbers returned by `operator()`, in the range `min()` to  $\log_2(\text{max}() + 1)$ .

```
result_type operator()();
```

- 6 *Returns:* A nondeterministic random value, uniformly distributed between `min()` and `max()`, inclusive. It is implementation-defined how these values are generated.

- 7 *Throws:* A value of an implementation-defined type derived from `exception` if a random number could not be obtained.

## 29.6.7 Utilities

[rand.util]

### 29.6.7.1 Class `seed_seq`

[rand.util.seedseq]

```
class seed_seq {
public:
 // types
 using result_type = uint_least32_t;

 // constructors
 seed_seq();
 template<class T>
 seed_seq(initializer_list<T> il);
 template<class InputIterator>
 seed_seq(InputIterator begin, InputIterator end);

 // generating functions
 template<class RandomAccessIterator>
 void generate(RandomAccessIterator begin, RandomAccessIterator end);

 // property functions
 size_t size() const noexcept;
 template<class OutputIterator>
 void param(OutputIterator dest) const;

 // no copy functions
 seed_seq(const seed_seq&) = delete;
 void operator=(const seed_seq&) = delete;

private:
 vector<result_type> v; // exposition only
};
```

```
seed_seq();
```

- 1 *Effects:* Constructs a `seed_seq` object as if by default-constructing its member `v`.

- 2 *Throws:* Nothing.

```
template<class T>
```

---

272) If a device has  $n$  states whose respective probabilities are  $P_0, \dots, P_{n-1}$ , the device entropy  $S$  is defined as  $S = -\sum_{i=0}^{n-1} P_i \cdot \log P_i$ .

```
seed_seq(initializer_list<T> il);
```

3 *Requires:* T shall be an integer type.

4 *Effects:* Same as `seed_seq(il.begin(), il.end())`.

```
template<class InputIterator>
```

```
seed_seq(InputIterator begin, InputIterator end);
```

5 *Requires:* InputIterator shall satisfy the requirements of an input iterator (Table 95) type. Moreover, `iterator_traits<InputIterator>::value_type` shall denote an integer type.

6 *Effects:* Constructs a `seed_seq` object by the following algorithm:

```
for(InputIterator s = begin; s != end; ++s)
 v.push_back((*s) mod 232);
```

```
template<class RandomAccessIterator>
```

```
void generate(RandomAccessIterator begin, RandomAccessIterator end);
```

7 *Requires:* RandomAccessIterator shall meet the requirements of a mutable random access iterator (27.2.7). Moreover, `iterator_traits<RandomAccessIterator>::value_type` shall denote an unsigned integer type capable of accommodating 32-bit quantities.

8 *Effects:* Does nothing if `begin == end`. Otherwise, with  $s = v.size()$  and  $n = end - begin$ , fills the supplied range `[begin, end)` according to the following algorithm in which each operation is to be carried out modulo  $2^{32}$ , each indexing operator applied to `begin` is to be taken modulo  $n$ , and  $T(x)$  is defined as  $x \text{ xor } (x \text{ rshift } 27)$ :

a) By way of initialization, set each element of the range to the value `0x8b8b8b8b`. Additionally, for use in subsequent steps, let  $p = (n - t)/2$  and let  $q = p + t$ , where

$$t = (n \geq 623) ? 11 : (n \geq 68) ? 7 : (n \geq 39) ? 5 : (n \geq 7) ? 3 : (n - 1)/2;$$

b) With  $m$  as the larger of  $s + 1$  and  $n$ , transform the elements of the range: iteratively for  $k = 0, \dots, m - 1$ , calculate values

$$\begin{aligned} r_1 &= 1664525 \cdot T(\text{begin}[k] \text{ xor } \text{begin}[k + p] \text{ xor } \text{begin}[k - 1]) \\ r_2 &= r_1 + \begin{cases} s & , k = 0 \\ k \bmod n + v[k - 1] & , 0 < k \leq s \\ k \bmod n & , s < k \end{cases} \end{aligned}$$

and, in order, increment `begin[k + p]` by  $r_1$ , increment `begin[k + q]` by  $r_2$ , and set `begin[k]` to  $r_2$ .

c) Transform the elements of the range again, beginning where the previous step ended: iteratively for  $k = m, \dots, m + n - 1$ , calculate values

$$\begin{aligned} r_3 &= 1566083941 \cdot T(\text{begin}[k] + \text{begin}[k + p] + \text{begin}[k - 1]) \\ r_4 &= r_3 - (k \bmod n) \end{aligned}$$

and, in order, update `begin[k + p]` by xoring it with  $r_3$ , update `begin[k + q]` by xoring it with  $r_4$ , and set `begin[k]` to  $r_4$ .

9 *Throws:* What and when RandomAccessIterator operations of `begin` and `end` throw.

```
size_t size() const noexcept;
```

10 *Returns:* The number of 32-bit units that would be returned by a call to `param()`.

11 *Complexity:* Constant time.

```
template<class OutputIterator>
```

```
void param(OutputIterator dest) const;
```

12 *Requires:* `OutputIterator` shall satisfy the requirements of an output iterator (27.2.4). Moreover, the expression `*dest = rt` shall be valid for a value `rt` of type `result_type`.

13 *Effects:* Copies the sequence of prepared 32-bit units to the given destination, as if by executing the following statement:

```
copy(v.begin(), v.end(), dest);
```

14 *Throws:* What and when `OutputIterator` operations of `dest` throw.

### 29.6.7.2 Function template `generate_canonical`

[rand.util.canonical]

1 Each function instantiated from the template described in this section 29.6.7.2 maps the result of one or more invocations of a supplied uniform random bit generator `g` to one member of the specified `RealType` such that, if the values  $g_i$  produced by `g` are uniformly distributed, the instantiation's results  $t_j$ ,  $0 \leq t_j < 1$ , are distributed as uniformly as possible as specified below.

2 [ *Note:* Obtaining a value in this way can be a useful step in the process of transforming a value generated by a uniform random bit generator into a value that can be delivered by a random number distribution. — *end note* ]

```
template<class RealType, size_t bits, class URBG>
```

```
RealType generate_canonical(URBG& g);
```

3 *Complexity:* Exactly  $k = \max(1, \lceil b/\log_2 R \rceil)$  invocations of `g`, where  $b^{273}$  is the lesser of `numeric_limits<RealType>::digits` and `bits`, and  $R$  is the value of `g.max() - g.min() + 1`.

4 *Effects:* Invokes `g()`  $k$  times to obtain values  $g_0, \dots, g_{k-1}$ , respectively. Calculates a quantity

$$S = \sum_{i=0}^{k-1} (g_i - g.\text{min}()) \cdot R^i$$

using arithmetic of type `RealType`.

5 *Returns:*  $S/R^k$ .

6 *Throws:* What and when `g` throws.

## 29.6.8 Random number distribution class templates

[rand.dist]

### 29.6.8.1 In general

[rand.dist.general]

1 Each type instantiated from a class template specified in this section 29.6.8 satisfies the requirements of a random number distribution (29.6.1.6) type.

2 Descriptions are provided in this section 29.6.8 only for distribution operations that are not described in 29.6.1.6 or for operations where there is additional semantic information. In particular, declarations for copy constructors, for copy assignment operators, for streaming operators, and for equality and inequality operators are not shown in the synopses.

3 The algorithms for producing each of the specified distributions are implementation-defined.

4 The value of each probability density function  $p(z)$  and of each discrete probability function  $P(z_i)$  specified in this section is 0 everywhere outside its stated domain.

---

273)  $b$  is introduced to avoid any attempt to produce more bits of randomness than can be held in `RealType`.

**29.6.8.2 Uniform distributions****[rand.dist.uni]****29.6.8.2.1 Class template uniform\_int\_distribution****[rand.dist.uni.int]**

- <sup>1</sup> A `uniform_int_distribution` random number distribution produces random integers  $i$ ,  $a \leq i \leq b$ , distributed according to the constant discrete probability function

$$P(i | a, b) = 1 / (b - a + 1) .$$

```
template<class IntType = int>
class uniform_int_distribution {
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit uniform_int_distribution(IntType a = 0, IntType b = numeric_limits<IntType>::max());
 explicit uniform_int_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 result_type a() const;
 result_type b() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit uniform_int_distribution(IntType a = 0, IntType b = numeric_limits<IntType>::max());
```

- <sup>2</sup> *Requires:*  $a \leq b$ .
- <sup>3</sup> *Effects:* Constructs a `uniform_int_distribution` object;  $a$  and  $b$  correspond to the respective parameters of the distribution.

```
result_type a() const;
```

- <sup>4</sup> *Returns:* The value of the  $a$  parameter with which the object was constructed.

```
result_type b() const;
```

- <sup>5</sup> *Returns:* The value of the  $b$  parameter with which the object was constructed.

**29.6.8.2.2 Class template uniform\_real\_distribution****[rand.dist.uni.real]**

- <sup>1</sup> A `uniform_real_distribution` random number distribution produces random numbers  $x$ ,  $a \leq x < b$ , distributed according to the constant probability density function

$$p(x | a, b) = 1 / (b - a) .$$

[ *Note:* This implies that  $p(x | a, b)$  is undefined when  $a == b$ . — end note ]

```

template<class RealType = double>
class uniform_real_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit uniform_real_distribution(RealType a = 0.0, RealType b = 1.0);
 explicit uniform_real_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 result_type a() const;
 result_type b() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit uniform_real_distribution(RealType a = 0.0, RealType b = 1.0);
```

<sup>2</sup> *Requires:*  $a \leq b$  and  $b - a \leq \text{numeric\_limits}<\text{RealType}>::\text{max}()$ .

<sup>3</sup> *Effects:* Constructs a `uniform_real_distribution` object; `a` and `b` correspond to the respective parameters of the distribution.

```
result_type a() const;
```

<sup>4</sup> *Returns:* The value of the `a` parameter with which the object was constructed.

```
result_type b() const;
```

<sup>5</sup> *Returns:* The value of the `b` parameter with which the object was constructed.

### 29.6.8.3 Bernoulli distributions

[rand.dist.bern]

#### 29.6.8.3.1 Class `bernoulli_distribution`

[rand.dist.bern.bernoulli]

<sup>1</sup> A `bernoulli_distribution` random number distribution produces `bool` values `b` distributed according to the discrete probability function

$$P(b|p) = \begin{cases} p & \text{if } b = \text{true} \\ 1 - p & \text{if } b = \text{false} \end{cases}.$$

```

class bernoulli_distribution {
public:
 // types
 using result_type = bool;
 using param_type = unspecified;

 // constructors and reset functions

```

```

explicit bernoulli_distribution(double p = 0.5);
explicit bernoulli_distribution(const param_type& parm);
void reset();

// generating functions
template<class URBG>
 result_type operator()(URBG& g);
template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

// property functions
double p() const;
param_type param() const;
void param(const param_type& parm);
result_type min() const;
result_type max() const;
};

```

```
explicit bernoulli_distribution(double p = 0.5);
```

2     *Requires:*  $0 \leq p \leq 1$ .

3     *Effects:* Constructs a `bernoulli_distribution` object; `p` corresponds to the parameter of the distribution.

```
double p() const;
```

4     *Returns:* The value of the `p` parameter with which the object was constructed.

#### 29.6.8.3.2 Class template `binomial_distribution` [rand.dist.bern.bin]

1 A `binomial_distribution` random number distribution produces integer values  $i \geq 0$  distributed according to the discrete probability function

$$P(i|t, p) = \binom{t}{i} \cdot p^i \cdot (1 - p)^{t-i}.$$

```

template<class IntType = int>
class binomial_distribution {
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit binomial_distribution(IntType t = 1, double p = 0.5);
 explicit binomial_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 IntType t() const;
 double p() const;
};

```

```

 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit binomial_distribution(IntType t = 1, double p = 0.5);
```

2     *Requires:*  $0 \leq p \leq 1$  and  $0 \leq t$ .

3     *Effects:* Constructs a `binomial_distribution` object; `t` and `p` correspond to the respective parameters of the distribution.

```
IntType t() const;
```

4     *Returns:* The value of the `t` parameter with which the object was constructed.

```
double p() const;
```

5     *Returns:* The value of the `p` parameter with which the object was constructed.

### 29.6.8.3.3 Class template `geometric_distribution` [rand.dist.bern.geo]

1 A `geometric_distribution` random number distribution produces integer values  $i \geq 0$  distributed according to the discrete probability function

$$P(i|p) = p \cdot (1 - p)^i.$$

```

template<class IntType = int>
class geometric_distribution {
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit geometric_distribution(double p = 0.5);
 explicit geometric_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 double p() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit geometric_distribution(double p = 0.5);
```

2     *Requires:*  $0 < p < 1$ .

3     *Effects:* Constructs a `geometric_distribution` object; `p` corresponds to the parameter of the distribution.



double p() const;

<sup>4</sup> *Returns:* The value of the p parameter with which the object was constructed.

#### 29.6.8.3.4 Class template negative\_binomial\_distribution [rand.dist.bern.negbin]

<sup>1</sup> A `negative_binomial_distribution` random number distribution produces random integers  $i \geq 0$  distributed according to the discrete probability function

$$P(i|k,p) = \binom{k+i-1}{i} \cdot p^k \cdot (1-p)^i.$$

[*Note:* This implies that  $P(i|k,p)$  is undefined when  $p == 1$ . — *end note*]

```
template<class IntType = int>
class negative_binomial_distribution {
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit negative_binomial_distribution(IntType k = 1, double p = 0.5);
 explicit negative_binomial_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 IntType k() const;
 double p() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit negative_binomial_distribution(IntType k = 1, double p = 0.5);
```

<sup>2</sup> *Requires:*  $0 < p \leq 1$  and  $0 < k$ .

<sup>3</sup> *Effects:* Constructs a `negative_binomial_distribution` object; k and p correspond to the respective parameters of the distribution.

IntType k() const;

<sup>4</sup> *Returns:* The value of the k parameter with which the object was constructed.

double p() const;

<sup>5</sup> *Returns:* The value of the p parameter with which the object was constructed.

**29.6.8.4 Poisson distributions****[rand.dist.pois]****29.6.8.4.1 Class template poisson\_distribution****[rand.dist.pois.poisson]**

- <sup>1</sup> A `poisson_distribution` random number distribution produces integer values  $i \geq 0$  distributed according to the discrete probability function

$$P(i | \mu) = \frac{e^{-\mu} \mu^i}{i!} .$$

The distribution parameter  $\mu$  is also known as this distribution's *mean* .

```
template<class IntType = int>
class poisson_distribution
{
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit poisson_distribution(double mean = 1.0);
 explicit poisson_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 double mean() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit poisson_distribution(double mean = 1.0);
```

- <sup>2</sup> *Requires:*  $0 < \text{mean}$ .
- <sup>3</sup> *Effects:* Constructs a `poisson_distribution` object; `mean` corresponds to the parameter of the distribution.

```
double mean() const;
```

- <sup>4</sup> *Returns:* The value of the `mean` parameter with which the object was constructed.

**29.6.8.4.2 Class template exponential\_distribution****[rand.dist.pois.exp]**

- <sup>1</sup> An `exponential_distribution` random number distribution produces random numbers  $x > 0$  distributed according to the probability density function

$$p(x | \lambda) = \lambda e^{-\lambda x} .$$

```
template<class RealType = double>
class exponential_distribution {
public:
 // types
```

```

using result_type = RealType;
using param_type = unspecified;

// constructors and reset functions
explicit exponential_distribution(RealType lambda = 1.0);
explicit exponential_distribution(const param_type& parm);
void reset();

// generating functions
template<class URBG>
 result_type operator()(URBG& g);
template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

// property functions
RealType lambda() const;
param_type param() const;
void param(const param_type& parm);
result_type min() const;
result_type max() const;
};

```

```
explicit exponential_distribution(RealType lambda = 1.0);
```

2     *Requires:*  $0 < \text{lambda}$ .

3     *Effects:* Constructs an `exponential_distribution` object; `lambda` corresponds to the parameter of the distribution.

```
RealType lambda() const;
```

4     *Returns:* The value of the `lambda` parameter with which the object was constructed.

#### 29.6.8.4.3 Class template `gamma_distribution` [rand.dist.pois.gamma]

1     A `gamma_distribution` random number distribution produces random numbers  $x > 0$  distributed according to the probability density function

$$p(x | \alpha, \beta) = \frac{e^{-x/\beta}}{\beta^\alpha \cdot \Gamma(\alpha)} \cdot x^{\alpha-1}.$$

```

template<class RealType = double>
class gamma_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit gamma_distribution(RealType alpha = 1.0, RealType beta = 1.0);
 explicit gamma_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

```

```

 // property functions
 RealType alpha() const;
 RealType beta() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit gamma_distribution(RealType alpha = 1.0, RealType beta = 1.0);
```

<sup>2</sup> *Requires:*  $0 < \text{alpha}$  and  $0 < \text{beta}$ .

<sup>3</sup> *Effects:* Constructs a `gamma_distribution` object; `alpha` and `beta` correspond to the parameters of the distribution.

```
RealType alpha() const;
```

<sup>4</sup> *Returns:* The value of the `alpha` parameter with which the object was constructed.

```
RealType beta() const;
```

<sup>5</sup> *Returns:* The value of the `beta` parameter with which the object was constructed.

#### 29.6.8.4.4 Class template `weibull_distribution` [rand.dist.pois.weibull]

<sup>1</sup> A `weibull_distribution` random number distribution produces random numbers  $x \geq 0$  distributed according to the probability density function

$$p(x|a,b) = \frac{a}{b} \cdot \left(\frac{x}{b}\right)^{a-1} \cdot \exp\left(-\left(\frac{x}{b}\right)^a\right).$$

```

template<class RealType = double>
class weibull_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit weibull_distribution(RealType a = 1.0, RealType b = 1.0);
 explicit weibull_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType a() const;
 RealType b() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit weibull_distribution(RealType a = 1.0, RealType b = 1.0);
```

<sup>2</sup> *Requires:*  $0 < a$  and  $0 < b$ .

<sup>3</sup> *Effects:* Constructs a `weibull_distribution` object; `a` and `b` correspond to the respective parameters of the distribution.

```
RealType a() const;
```

<sup>4</sup> *Returns:* The value of the `a` parameter with which the object was constructed.

```
RealType b() const;
```

<sup>5</sup> *Returns:* The value of the `b` parameter with which the object was constructed.

#### 29.6.8.4.5 Class template `extreme_value_distribution` [rand.dist.pois.extreme]

<sup>1</sup> An `extreme_value_distribution` random number distribution produces random numbers  $x$  distributed according to the probability density function<sup>274</sup>

$$p(x|a,b) = \frac{1}{b} \cdot \exp\left(\frac{a-x}{b} - \exp\left(\frac{a-x}{b}\right)\right).$$

```
template<class RealType = double>
class extreme_value_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit extreme_value_distribution(RealType a = 0.0, RealType b = 1.0);
 explicit extreme_value_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType a() const;
 RealType b() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit extreme_value_distribution(RealType a = 0.0, RealType b = 1.0);
```

<sup>2</sup> *Requires:*  $0 < b$ .

<sup>3</sup> *Effects:* Constructs an `extreme_value_distribution` object; `a` and `b` correspond to the respective parameters of the distribution.

<sup>274</sup>) The distribution corresponding to this probability density function is also known (with a possible change of variable) as the Gumbel Type I, the log-Weibull, or the Fisher-Tippett Type I distribution.

RealType a() const;

4 *Returns:* The value of the `a` parameter with which the object was constructed.

RealType b() const;

5 *Returns:* The value of the `b` parameter with which the object was constructed.

### 29.6.8.5 Normal distributions

[rand.dist.norm]

#### 29.6.8.5.1 Class template `normal_distribution`

[rand.dist.norm.normal]

1 A `normal_distribution` random number distribution produces random numbers  $x$  distributed according to the probability density function

$$p(x|\mu, \sigma) = \frac{1}{\sigma\sqrt{2\pi}} \cdot \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right).$$

The distribution parameters  $\mu$  and  $\sigma$  are also known as this distribution's *mean* and *standard deviation*.

```
template<class RealType = double>
class normal_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructors and reset functions
 explicit normal_distribution(RealType mean = 0.0, RealType stddev = 1.0);
 explicit normal_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType mean() const;
 RealType stddev() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit normal_distribution(RealType mean = 0.0, RealType stddev = 1.0);
```

2 *Requires:*  $0 < \text{stddev}$ .

3 *Effects:* Constructs a `normal_distribution` object; `mean` and `stddev` correspond to the respective parameters of the distribution.

RealType mean() const;

4 *Returns:* The value of the `mean` parameter with which the object was constructed.

RealType stddev() const;

5 *Returns:* The value of the `stddev` parameter with which the object was constructed.

**29.6.8.5.2 Class template lognormal\_distribution****[rand.dist.norm.lognormal]**

- <sup>1</sup> A `lognormal_distribution` random number distribution produces random numbers  $x > 0$  distributed according to the probability density function

$$p(x|m,s) = \frac{1}{sx\sqrt{2\pi}} \cdot \exp\left(-\frac{(\ln x - m)^2}{2s^2}\right).$$

```
template<class RealType = double>
class lognormal_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit lognormal_distribution(RealType m = 0.0, RealType s = 1.0);
 explicit lognormal_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType m() const;
 RealType s() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

```
explicit lognormal_distribution(RealType m = 0.0, RealType s = 1.0);
```

- <sup>2</sup> *Requires:*  $0 < s$ .
- <sup>3</sup> *Effects:* Constructs a `lognormal_distribution` object; `m` and `s` correspond to the respective parameters of the distribution.

```
RealType m() const;
```

- <sup>4</sup> *Returns:* The value of the `m` parameter with which the object was constructed.

```
RealType s() const;
```

- <sup>5</sup> *Returns:* The value of the `s` parameter with which the object was constructed.

**29.6.8.5.3 Class template chi\_squared\_distribution****[rand.dist.norm.chisq]**

- <sup>1</sup> A `chi_squared_distribution` random number distribution produces random numbers  $x > 0$  distributed according to the probability density function

$$p(x|n) = \frac{x^{(n/2)-1} \cdot e^{-x/2}}{\Gamma(n/2) \cdot 2^{n/2}}.$$

```

template<class RealType = double>
class chi_squared_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit chi_squared_distribution(RealType n = 1);
 explicit chi_squared_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType n() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit chi_squared_distribution(RealType n = 1);
```

2     *Requires:*  $0 < n$ .

3     *Effects:* Constructs a `chi_squared_distribution` object; `n` corresponds to the parameter of the distribution.

```
RealType n() const;
```

4     *Returns:* The value of the `n` parameter with which the object was constructed.

#### 29.6.8.5.4 Class template `cauchy_distribution` [rand.dist.norm.cauchy]

1 A `cauchy_distribution` random number distribution produces random numbers  $x$  distributed according to the probability density function

$$p(x | a, b) = \left( \pi b \left( 1 + \left( \frac{x - a}{b} \right)^2 \right) \right)^{-1}.$$

```

template<class RealType = double>
class cauchy_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit cauchy_distribution(RealType a = 0.0, RealType b = 1.0);
 explicit cauchy_distribution(const param_type& parm);
 void reset();

```



```

// generating functions
template<class URBG>
 result_type operator()(URBG& g);
template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

// property functions
RealType a() const;
RealType b() const;
param_type param() const;
void param(const param_type& parm);
result_type min() const;
result_type max() const;
};

```

```
explicit cauchy_distribution(RealType a = 0.0, RealType b = 1.0);
```

2     *Requires:*  $0 < b$ .

3     *Effects:* Constructs a `cauchy_distribution` object; `a` and `b` correspond to the respective parameters of the distribution.

```
RealType a() const;
```

4     *Returns:* The value of the `a` parameter with which the object was constructed.

```
RealType b() const;
```

5     *Returns:* The value of the `b` parameter with which the object was constructed.

#### 29.6.8.5.5 Class template `fisher_f_distribution` [rand.dist.norm.f]

1 A `fisher_f_distribution` random number distribution produces random numbers  $x \geq 0$  distributed according to the probability density function

$$p(x | m, n) = \frac{\Gamma((m+n)/2)}{\Gamma(m/2) \Gamma(n/2)} \cdot \left(\frac{m}{n}\right)^{m/2} \cdot x^{(m/2)-1} \cdot \left(1 + \frac{mx}{n}\right)^{-(m+n)/2}.$$

```

template<class RealType = double>
class fisher_f_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit fisher_f_distribution(RealType m = 1, RealType n = 1);
 explicit fisher_f_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType m() const;

```

```

 RealType n() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit fisher_f_distribution(RealType m = 1, RealType n = 1);
```

2     *Requires:*  $0 < m$  and  $0 < n$ .

3     *Effects:* Constructs a `fisher_f_distribution` object; `m` and `n` correspond to the respective parameters of the distribution.

```
RealType m() const;
```

4     *Returns:* The value of the `m` parameter with which the object was constructed.

```
RealType n() const;
```

5     *Returns:* The value of the `n` parameter with which the object was constructed.

#### 29.6.8.5.6 Class template `student_t_distribution` [rand.dist.norm.t]

1 A `student_t_distribution` random number distribution produces random numbers  $x$  distributed according to the probability density function

$$p(x|n) = \frac{1}{\sqrt{n\pi}} \cdot \frac{\Gamma((n+1)/2)}{\Gamma(n/2)} \cdot \left(1 + \frac{x^2}{n}\right)^{-(n+1)/2}.$$

```

template<class RealType = double>
class student_t_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 explicit student_t_distribution(RealType n = 1);
 explicit student_t_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 RealType n() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```
explicit student_t_distribution(RealType n = 1);
```

2     *Requires:*  $0 < n$ .

- <sup>3</sup> *Effects:* Constructs a `student_t_distribution` object; `n` corresponds to the parameter of the distribution.

RealType n() const;

- <sup>4</sup> *Returns:* The value of the `n` parameter with which the object was constructed.

### 29.6.8.6 Sampling distributions [rand.dist.samp]

#### 29.6.8.6.1 Class template `discrete_distribution` [rand.dist.samp.discrete]

- <sup>1</sup> A `discrete_distribution` random number distribution produces random integers  $i$ ,  $0 \leq i < n$ , distributed according to the discrete probability function

$$P(i | p_0, \dots, p_{n-1}) = p_i.$$

- <sup>2</sup> Unless specified otherwise, the distribution parameters are calculated as:  $p_k = w_k / S$  for  $k = 0, \dots, n-1$ , in which the values  $w_k$ , commonly known as the *weights*, shall be non-negative, non-NaN, and non-infinity. Moreover, the following relation shall hold:  $0 < S = w_0 + \dots + w_{n-1}$ .

```
template<class IntType = int>
class discrete_distribution {
public:
 // types
 using result_type = IntType;
 using param_type = unspecified;

 // constructor and reset functions
 discrete_distribution();
 template<class InputIterator>
 discrete_distribution(InputIterator firstW, InputIterator lastW);
 discrete_distribution(initializer_list<double> wl);
 template<class UnaryOperation>
 discrete_distribution(size_t nw, double xmin, double xmax, UnaryOperation fw);
 explicit discrete_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

 // property functions
 vector<double> probabilities() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};
```

`discrete_distribution();`

- <sup>3</sup> *Effects:* Constructs a `discrete_distribution` object with  $n = 1$  and  $p_0 = 1$ . [Note: Such an object will always deliver the value 0. — end note]

```
template<class InputIterator>
 discrete_distribution(InputIterator firstW, InputIterator lastW);
```

4 *Requires:* `InputIterator` shall satisfy the requirements of an input iterator (27.2.3). Moreover, `iterator_traits<InputIterator>::value_type` shall denote a type that is convertible to `double`. If `firstW == lastW`, let  $n = 1$  and  $w_0 = 1$ . Otherwise,  $[firstW, lastW)$  shall form a sequence  $w$  of length  $n > 0$ .

5 *Effects:* Constructs a `discrete_distribution` object with probabilities given by the formula above.

```
discrete_distribution(initializer_list<double> wl);
```

6 *Effects:* Same as `discrete_distribution(wl.begin(), wl.end())`.

```
template<class UnaryOperation>
discrete_distribution(size_t nw, double xmin, double xmax, UnaryOperation fw);
```

7 *Requires:* Each instance of type `UnaryOperation` shall be a function object (23.14) whose return type shall be convertible to `double`. Moreover, `double` shall be convertible to the type of `UnaryOperation`'s sole parameter. If `nw = 0`, let  $n = 1$ , otherwise let  $n = nw$ . The relation  $0 < \delta = (xmax - xmin)/n$  shall hold.

8 *Effects:* Constructs a `discrete_distribution` object with probabilities given by the formula above, using the following values: If `nw = 0`, let  $w_0 = 1$ . Otherwise, let  $w_k = fw(xmin + k \cdot \delta + \delta/2)$  for  $k = 0, \dots, n-1$ .

9 *Complexity:* The number of invocations of `fw` shall not exceed  $n$ .

```
vector<double> probabilities() const;
```

10 *Returns:* A `vector<double>` whose `size` member returns  $n$  and whose `operator[]` member returns  $p_k$  when invoked with argument  $k$  for  $k = 0, \dots, n-1$ .

#### 29.6.8.6.2 Class template `piecewise_constant_distribution` [rand.dist.samp.pconst]

1 A `piecewise_constant_distribution` random number distribution produces random numbers  $x$ ,  $b_0 \leq x < b_n$ , uniformly distributed over each subinterval  $[b_i, b_{i+1})$  according to the probability density function

$$p(x | b_0, \dots, b_n, \rho_0, \dots, \rho_{n-1}) = \rho_i, \text{ for } b_i \leq x < b_{i+1}.$$

2 The  $n + 1$  distribution parameters  $b_i$ , also known as this distribution's *interval boundaries*, shall satisfy the relation  $b_i < b_{i+1}$  for  $i = 0, \dots, n-1$ . Unless specified otherwise, the remaining  $n$  distribution parameters are calculated as:

$$\rho_k = \frac{w_k}{S \cdot (b_{k+1} - b_k)} \text{ for } k = 0, \dots, n-1,$$

in which the values  $w_k$ , commonly known as the *weights*, shall be non-negative, non-NaN, and non-infinity. Moreover, the following relation shall hold:  $0 < S = w_0 + \dots + w_{n-1}$ .

```
template<class RealType = double>
class piecewise_constant_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 piecewise_constant_distribution();
 template<class InputIteratorB, class InputIteratorW>
 piecewise_constant_distribution(InputIteratorB firstB, InputIteratorB lastB,
 InputIteratorW firstW);
 template<class UnaryOperation>
 piecewise_constant_distribution(initializer_list<RealType> bl, UnaryOperation fw);
```

```

template<class UnaryOperation>
 piecewise_constant_distribution(size_t nw, RealType xmin, RealType xmax,
 UnaryOperation fw);
explicit piecewise_constant_distribution(const param_type& parm);
void reset();

// generating functions
template<class URBG>
 result_type operator()(URBG& g);
template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);

// property functions
vector<result_type> intervals() const;
vector<result_type> densities() const;
param_type param() const;
void param(const param_type& parm);
result_type min() const;
result_type max() const;
};

```

```
piecewise_constant_distribution();
```

- 3     *Effects:* Constructs a `piecewise_constant_distribution` object with  $n = 1$ ,  $\rho_0 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ .

```

template<class InputIteratorB, class InputIteratorW>
 piecewise_constant_distribution(InputIteratorB firstB, InputIteratorB lastB,
 InputIteratorW firstW);

```

- 4     *Requires:* `InputIteratorB` and `InputIteratorW` shall each satisfy the requirements of an input iterator (Table 95) type. Moreover, `iterator_traits<InputIteratorB>::value_type` and `iterator_traits<InputIteratorW>::value_type` shall each denote a type that is convertible to `double`. If `firstB == lastB` or `++firstB == lastB`, let  $n = 1$ ,  $w_0 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ . Otherwise, `[firstB, lastB)` shall form a sequence  $b$  of length  $n + 1$ , the length of the sequence  $w$  starting from `firstW` shall be at least  $n$ , and any  $w_k$  for  $k \geq n$  shall be ignored by the distribution.

- 5     *Effects:* Constructs a `piecewise_constant_distribution` object with parameters as specified above.

```

template<class UnaryOperation>
 piecewise_constant_distribution(initializer_list<RealType> bl, UnaryOperation fw);

```

- 6     *Requires:* Each instance of type `UnaryOperation` shall be a function object (23.14) whose return type shall be convertible to `double`. Moreover, `double` shall be convertible to the type of `UnaryOperation`'s sole parameter.

- 7     *Effects:* Constructs a `piecewise_constant_distribution` object with parameters taken or calculated from the following values: If `bl.size() < 2`, let  $n = 1$ ,  $w_0 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ . Otherwise, let `[bl.begin(), bl.end())` form a sequence  $b_0, \dots, b_n$ , and let  $w_k = fw((b_{k+1} + b_k)/2)$  for  $k = 0, \dots, n-1$ .

- 8     *Complexity:* The number of invocations of `fw` shall not exceed  $n$ .

```

template<class UnaryOperation>
 piecewise_constant_distribution(size_t nw, RealType xmin, RealType xmax, UnaryOperation fw);

```

- 9     *Requires:* Each instance of type `UnaryOperation` shall be a function object (23.14) whose return type shall be convertible to `double`. Moreover, `double` shall be convertible to the type of `UnaryOperation`'s sole parameter. If `nw = 0`, let  $n = 1$ , otherwise let  $n = nw$ . The relation  $0 < \delta = (xmax - xmin)/n$  shall

hold.

<sup>10</sup> *Effects:* Constructs a `piecewise_constant_distribution` object with parameters taken or calculated from the following values: Let  $b_k = \text{xmin} + k \cdot \delta$  for  $k = 0, \dots, n$ , and  $w_k = \text{fw}(b_k + \delta/2)$  for  $k = 0, \dots, n-1$ .

<sup>11</sup> *Complexity:* The number of invocations of `fw` shall not exceed  $n$ .

```
vector<result_type> intervals() const;
```

<sup>12</sup> *Returns:* A `vector<result_type>` whose `size` member returns  $n + 1$  and whose `operator[]` member returns  $b_k$  when invoked with argument  $k$  for  $k = 0, \dots, n$ .

```
vector<result_type> densities() const;
```

<sup>13</sup> *Returns:* A `vector<result_type>` whose `size` member returns  $n$  and whose `operator[]` member returns  $\rho_k$  when invoked with argument  $k$  for  $k = 0, \dots, n-1$ .

### 29.6.8.6.3 Class template `piecewise_linear_distribution` [rand.dist.samp.plinear]

<sup>1</sup> A `piecewise_linear_distribution` random number distribution produces random numbers  $x$ ,  $b_0 \leq x < b_n$ , distributed over each subinterval  $[b_i, b_{i+1})$  according to the probability density function

$$p(x | b_0, \dots, b_n, \rho_0, \dots, \rho_n) = \rho_i \cdot \frac{b_{i+1} - x}{b_{i+1} - b_i} + \rho_{i+1} \cdot \frac{x - b_i}{b_{i+1} - b_i}, \text{ for } b_i \leq x < b_{i+1}.$$

<sup>2</sup> The  $n + 1$  distribution parameters  $b_i$ , also known as this distribution's *interval boundaries*, shall satisfy the relation  $b_i < b_{i+1}$  for  $i = 0, \dots, n-1$ . Unless specified otherwise, the remaining  $n + 1$  distribution parameters are calculated as  $\rho_k = w_k/S$  for  $k = 0, \dots, n$ , in which the values  $w_k$ , commonly known as the *weights at boundaries*, shall be non-negative, non-NaN, and non-infinity. Moreover, the following relation shall hold:

$$0 < S = \frac{1}{2} \cdot \sum_{k=0}^{n-1} (w_k + w_{k+1}) \cdot (b_{k+1} - b_k).$$

```
template<class RealType = double>
class piecewise_linear_distribution {
public:
 // types
 using result_type = RealType;
 using param_type = unspecified;

 // constructor and reset functions
 piecewise_linear_distribution();
 template<class InputIteratorB, class InputIteratorW>
 piecewise_linear_distribution(InputIteratorB firstB, InputIteratorB lastB,
 InputIteratorW firstW);
 template<class UnaryOperation>
 piecewise_linear_distribution(initializer_list<RealType> bl, UnaryOperation fw);
 template<class UnaryOperation>
 piecewise_linear_distribution(size_t nw, RealType xmin, RealType xmax, UnaryOperation fw);
 explicit piecewise_linear_distribution(const param_type& parm);
 void reset();

 // generating functions
 template<class URBG>
 result_type operator()(URBG& g);
 template<class URBG>
 result_type operator()(URBG& g, const param_type& parm);
```

```

 // property functions
 vector<result_type> intervals() const;
 vector<result_type> densities() const;
 param_type param() const;
 void param(const param_type& parm);
 result_type min() const;
 result_type max() const;
};

```

```

piecewise_linear_distribution();

```

- 3     *Effects:* Constructs a `piecewise_linear_distribution` object with  $n = 1$ ,  $\rho_0 = \rho_1 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ .

```

template<class InputIteratorB, class InputIteratorW>
piecewise_linear_distribution(InputIteratorB firstB, InputIteratorB lastB,
 InputIteratorW firstW);

```

- 4     *Requires:* `InputIteratorB` and `InputIteratorW` shall each satisfy the requirements of an input iterator (Table 95) type. Moreover, `iterator_traits<InputIteratorB>::value_type` and `iterator_traits<InputIteratorW>::value_type` shall each denote a type that is convertible to `double`. If `firstB == lastB` or `++firstB == lastB`, let  $n = 1$ ,  $\rho_0 = \rho_1 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ . Otherwise, `[firstB, lastB)` shall form a sequence  $b$  of length  $n + 1$ , the length of the sequence  $w$  starting from `firstW` shall be at least  $n + 1$ , and any  $w_k$  for  $k \geq n + 1$  shall be ignored by the distribution.

- 5     *Effects:* Constructs a `piecewise_linear_distribution` object with parameters as specified above.

```

template<class UnaryOperation>
piecewise_linear_distribution(initializer_list<RealType> bl, UnaryOperation fw);

```

- 6     *Requires:* Each instance of type `UnaryOperation` shall be a function object (23.14) whose return type shall be convertible to `double`. Moreover, `double` shall be convertible to the type of `UnaryOperation`'s sole parameter.

- 7     *Effects:* Constructs a `piecewise_linear_distribution` object with parameters taken or calculated from the following values: If `bl.size() < 2`, let  $n = 1$ ,  $\rho_0 = \rho_1 = 1$ ,  $b_0 = 0$ , and  $b_1 = 1$ . Otherwise, let `[bl.begin(), bl.end())` form a sequence  $b_0, \dots, b_n$ , and let  $w_k = fw(b_k)$  for  $k = 0, \dots, n$ .

- 8     *Complexity:* The number of invocations of `fw` shall not exceed  $n + 1$ .

```

template<class UnaryOperation>
piecewise_linear_distribution(size_t nw, RealType xmin, RealType xmax, UnaryOperation fw);

```

- 9     *Requires:* Each instance of type `UnaryOperation` shall be a function object (23.14) whose return type shall be convertible to `double`. Moreover, `double` shall be convertible to the type of `UnaryOperation`'s sole parameter. If `nw = 0`, let  $n = 1$ , otherwise let  $n = nw$ . The relation  $0 < \delta = (xmax - xmin)/n$  shall hold.

- 10    *Effects:* Constructs a `piecewise_linear_distribution` object with parameters taken or calculated from the following values: Let  $b_k = xmin + k \cdot \delta$  for  $k = 0, \dots, n$ , and  $w_k = fw(b_k)$  for  $k = 0, \dots, n$ .

- 11    *Complexity:* The number of invocations of `fw` shall not exceed  $n + 1$ .

```

vector<result_type> intervals() const;

```

- 12    *Returns:* A `vector<result_type>` whose `size` member returns  $n + 1$  and whose `operator[]` member returns  $b_k$  when invoked with argument  $k$  for  $k = 0, \dots, n$ .

```

vector<result_type> densities() const;

```

- 13 *Returns:* A `vector<result_type>` whose `size` member returns  $n$  and whose `operator[]` member returns  $\rho_k$  when invoked with argument  $k$  for  $k = 0, \dots, n$ .

## 29.6.9 Low-quality random number generation [c.math.rand]

- 1 [Note: The header `<cstdlib>` (21.2.2) declares the functions described in this subclause. — end note]

```
int rand();
void srand(unsigned int seed);
```

- 2 *Effects:* The `rand` and `srand` functions have the semantics specified in the C standard library.

- 3 *Remarks:* The implementation may specify that particular library functions may call `rand`. It is implementation-defined whether the `rand` function may introduce data races (20.5.5.9). [Note: The other random number generation facilities in this International Standard (29.6) are often preferable to `rand`, because `rand`'s underlying algorithm is unspecified. Use of `rand` therefore continues to be non-portable, with unpredictable and oft-questionable quality and performance. — end note]

SEE ALSO: ISO C 7.22.2

## 29.7 Numeric arrays [numarray]

### 29.7.1 Header `<valarray>` synopsis [valarray.syn]

```
#include <initializer_list>

namespace std {
 template<class T> class valarray; // An array of type T
 class slice; // a BLAS-like slice out of an array
 template<class T> class slice_array;
 class gslice; // a generalized slice out of an array
 template<class T> class gslice_array;
 template<class T> class mask_array; // a masked array
 template<class T> class indirect_array; // an indirected array

 template<class T> void swap(valarray<T>&, valarray<T>&) noexcept;

 template<class T> valarray<T> operator* (const valarray<T>&, const valarray<T>&);
 template<class T> valarray<T> operator* (const valarray<T>&, const T&);
 template<class T> valarray<T> operator* (const T&, const valarray<T>&);

 template<class T> valarray<T> operator/ (const valarray<T>&, const valarray<T>&);
 template<class T> valarray<T> operator/ (const valarray<T>&, const T&);
 template<class T> valarray<T> operator/ (const T&, const valarray<T>&);

 template<class T> valarray<T> operator% (const valarray<T>&, const valarray<T>&);
 template<class T> valarray<T> operator% (const valarray<T>&, const T&);
 template<class T> valarray<T> operator% (const T&, const valarray<T>&);

 template<class T> valarray<T> operator+ (const valarray<T>&, const valarray<T>&);
 template<class T> valarray<T> operator+ (const valarray<T>&, const T&);
 template<class T> valarray<T> operator+ (const T&, const valarray<T>&);

 template<class T> valarray<T> operator- (const valarray<T>&, const valarray<T>&);
 template<class T> valarray<T> operator- (const valarray<T>&, const T&);
 template<class T> valarray<T> operator- (const T&, const valarray<T>&);

 template<class T> valarray<T> operator^ (const valarray<T>&, const valarray<T>&);
```



[illegible]

```

template<class T> valarray<T> asin (const valarray<T>&);
template<class T> valarray<T> atan (const valarray<T>&);

template<class T> valarray<T> atan2(const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> atan2(const valarray<T>&, const T&);
template<class T> valarray<T> atan2(const T&, const valarray<T>&);

template<class T> valarray<T> cos (const valarray<T>&);
template<class T> valarray<T> cosh (const valarray<T>&);
template<class T> valarray<T> exp (const valarray<T>&);
template<class T> valarray<T> log (const valarray<T>&);
template<class T> valarray<T> log10(const valarray<T>&);

template<class T> valarray<T> pow(const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> pow(const valarray<T>&, const T&);
template<class T> valarray<T> pow(const T&, const valarray<T>&);

template<class T> valarray<T> sin (const valarray<T>&);
template<class T> valarray<T> sinh (const valarray<T>&);
template<class T> valarray<T> sqrt (const valarray<T>&);
template<class T> valarray<T> tan (const valarray<T>&);
template<class T> valarray<T> tanh (const valarray<T>&);

template <class T> unspecified1 begin(valarray<T>& v);
template <class T> unspecified2 begin(const valarray<T>& v);
template <class T> unspecified1 end(valarray<T>& v);
template <class T> unspecified2 end(const valarray<T>& v);
}

```

- <sup>1</sup> The header `<valarray>` defines five class templates (`valarray`, `slice_array`, `gslice_array`, `mask_array`, and `indirect_array`), two classes (`slice` and `gslice`), and a series of related function templates for representing and manipulating arrays of values.
- <sup>2</sup> The `valarray` array classes are defined to be free of certain forms of aliasing, thus allowing operations on these classes to be optimized.
- <sup>3</sup> Any function returning a `valarray<T>` is permitted to return an object of another type, provided all the `const` member functions of `valarray<T>` are also applicable to this type. This return type shall not add more than two levels of template nesting over the most deeply nested argument type.<sup>275</sup>
- <sup>4</sup> Implementations introducing such replacement types shall provide additional functions and operators as follows:
  - (4.1) — for every function taking a `const valarray<T>&` other than `begin` and `end` (29.7.10), identical functions taking the replacement types shall be added;
  - (4.2) — for every function taking two `const valarray<T>&` arguments, identical functions taking every combination of `const valarray<T>&` and replacement types shall be added.
- <sup>5</sup> In particular, an implementation shall allow a `valarray<T>` to be constructed from such replacement types and shall allow assignments and compound assignments of such types to `valarray<T>`, `slice_array<T>`, `gslice_array<T>`, `mask_array<T>` and `indirect_array<T>` objects.
- <sup>6</sup> These library functions are permitted to throw a `bad_alloc` (21.6.3.1) exception if there are not sufficient resources available to carry out the operation. Note that the exception is not mandated.

<sup>275</sup>) Annex B recommends a minimum number of recursively nested template instantiations. This requirement thus indirectly suggests a minimum allowable complexity for `valarray` expressions.

## 29.7.2 Class template valarray

[template.valarray]

### 29.7.2.1 Class template valarray overview

[template.valarray.overview]

```

namespace std {
 template<class T> class valarray {
 public:
 using value_type = T;

 // 29.7.2.2, construct/destroy
 valarray();
 explicit valarray(size_t);
 valarray(const T&, size_t);
 valarray(const T*, size_t);
 valarray(const valarray&);
 valarray(valarray&&) noexcept;
 valarray(const slice_array<T>&);
 valarray(const gslice_array<T>&);
 valarray(const mask_array<T>&);
 valarray(const indirect_array<T>&);
 valarray(initializer_list<T>);
 ~valarray();

 // 29.7.2.3, assignment
 valarray& operator=(const valarray&);
 valarray& operator=(valarray&&) noexcept;
 valarray& operator=(initializer_list<T>);
 valarray& operator=(const T&);
 valarray& operator=(const slice_array<T>&);
 valarray& operator=(const gslice_array<T>&);
 valarray& operator=(const mask_array<T>&);
 valarray& operator=(const indirect_array<T>&);

 // 29.7.2.4, element access
 const T& operator[] (size_t) const;
 T& operator[] (size_t);

 // 29.7.2.5, subset operations
 valarray operator[] (slice) const;
 slice_array<T> operator[] (slice);
 valarray operator[] (const gslice&) const;
 gslice_array<T> operator[] (const gslice&);
 valarray operator[] (const valarray<bool>&) const;
 mask_array<T> operator[] (const valarray<bool>&);
 valarray operator[] (const valarray<size_t>&) const;
 indirect_array<T> operator[] (const valarray<size_t>&);

 // 29.7.2.6, unary operators
 valarray operator+() const;
 valarray operator-() const;
 valarray operator~() const;
 valarray<bool> operator!() const;

 // 29.7.2.7, compound assignment
 valarray& operator*=(const T&);
 valarray& operator/=(const T&);

```

```

 valarray& operator%= (const T&);
 valarray& operator+= (const T&);
 valarray& operator-= (const T&);
 valarray& operator^= (const T&);
 valarray& operator&= (const T&);
 valarray& operator|= (const T&);
 valarray& operator<<=(const T&);
 valarray& operator>>=(const T&);

 valarray& operator*= (const valarray&);
 valarray& operator/= (const valarray&);
 valarray& operator%= (const valarray&);
 valarray& operator+= (const valarray&);
 valarray& operator-= (const valarray&);
 valarray& operator^= (const valarray&);
 valarray& operator|= (const valarray&);
 valarray& operator&= (const valarray&);
 valarray& operator<<=(const valarray&);
 valarray& operator>>=(const valarray&);

 // 29.7.2.8, member functions
 void swap(valarray&) noexcept;

 size_t size() const;

 T sum() const;
 T min() const;
 T max() const;

 valarray shift (int) const;
 valarray cshift(int) const;
 valarray apply(T func(T)) const;
 valarray apply(T func(const T&)) const;
 void resize(size_t sz, T c = T());
};

template<class T, size_t cnt> valarray(const T(&)[cnt], size_t) -> valarray<T>;
}

```

- <sup>1</sup> The class template `valarray<T>` is a one-dimensional smart array, with elements numbered sequentially from zero. It is a representation of the mathematical concept of an ordered set of values. For convenience, an object of type `valarray<T>` is referred to as an “array” throughout the remainder of 29.7. The illusion of higher dimensionality may be produced by the familiar idiom of computed indices, together with the powerful subsetting capabilities provided by the generalized subscript operators.<sup>276</sup>
- <sup>2</sup> An implementation is permitted to qualify any of the functions declared in `<valarray>` as `inline`.

### 29.7.2.2 `valarray` constructors

[`valarray.cons`]

```
valarray();
```

- <sup>1</sup> *Effects:* Constructs a `valarray` that has zero length.<sup>277</sup>

<sup>276</sup>) The intent is to specify an array template that has the minimum functionality necessary to address aliasing ambiguities and the proliferation of temporaries. Thus, the `valarray` template is neither a matrix class nor a field class. However, it is a very useful building block for designing such classes.

<sup>277</sup>) This default constructor is essential, since arrays of `valarray` may be useful. After initialization, the length of an empty array can be increased with the `resize` member function.

```
explicit valarray(size_t n);
```

2     *Effects:* Constructs a **valarray** that has length **n**. Each element of the array is value-initialized (11.6).

```
valarray(const T& v, size_t n);
```

3     *Effects:* Constructs a **valarray** that has length **n**. Each element of the array is initialized with **v**.

```
valarray(const T* p, size_t n);
```

4     *Requires:* **p** points to an array (11.3.4) of at least **n** elements.

*Effects:* Constructs a **valarray** that has length **n**. The values of the elements of the array are initialized with the first **n** values pointed to by the first argument.<sup>278</sup>

```
valarray(const valarray& v);
```

5     *Effects:* Constructs a **valarray** that has the same length as **v**. The elements are initialized with the values of the corresponding elements of **v**.<sup>279</sup>

```
valarray(valarray&& v) noexcept;
```

6     *Effects:* Constructs a **valarray** that has the same length as **v**. The elements are initialized with the values of the corresponding elements of **v**.

7     *Complexity:* Constant.

```
valarray(initializer_list<T> il);
```

8     *Effects:* Equivalent to `valarray(il.begin(), il.size())`.

```
valarray(const slice_array<T>&);
```

```
valarray(const gslice_array<T>&);
```

```
valarray(const mask_array<T>&);
```

```
valarray(const indirect_array<T>&);
```

9     These conversion constructors convert one of the four reference templates to a **valarray**.

```
~valarray();
```

10    *Effects:* The destructor is applied to every element of **\*this**; an implementation may return all allocated memory.

### 29.7.2.3 valarray assignment

[**valarray.assign**]

```
valarray& operator=(const valarray& v);
```

1     *Effects:* Each element of the **\*this** array is assigned the value of the corresponding element of **v**. If the length of **v** is not equal to the length of **\*this**, resizes **\*this** to make the two arrays the same length, as if by calling `resize(v.size())`, before performing the assignment.

2     *Postconditions:* `size() == v.size()`.

3     *Returns:* **\*this**.

```
valarray& operator=(valarray&& v) noexcept;
```

4     *Effects:* **\*this** obtains the value of **v**. The value of **v** after the assignment is not specified.

5     *Returns:* **\*this**.

6     *Complexity:* Linear.

---

<sup>278</sup>) This constructor is the preferred method for converting a C array to a **valarray** object.

<sup>279</sup>) This copy constructor creates a distinct array rather than an alias. Implementations in which arrays share storage are permitted, but they shall implement a copy-on-reference mechanism to ensure that arrays are conceptually distinct.

```
valarray& operator=(initializer_list<T> il);
```

7     *Effects:* Equivalent to: `return *this = valarray(il);`

```
valarray& operator=(const T& v);
```

8     *Effects:* Assigns `v` to each element of `*this`.

9     *Returns:* `*this`.

```
valarray& operator=(const slice_array<T>&);
```

```
valarray& operator=(const gslice_array<T>&);
```

```
valarray& operator=(const mask_array<T>&);
```

```
valarray& operator=(const indirect_array<T>&);
```

10     *Requires:* The length of the array to which the argument refers equals `size()`. The value of an element in the left-hand side of a `valarray` assignment operator does not depend on the value of another element in that left-hand side.

11     These operators allow the results of a generalized subscripting operation to be assigned directly to a `valarray`.

#### 29.7.2.4 `valarray` element access

[`valarray.access`]

```
const T& operator[](size_t n) const;
```

```
T& operator[](size_t n);
```

1     *Requires:* `n < size()`.

2     *Returns:* A reference to the corresponding element of the array. [ *Note:* The expression `(a[i] = q, a[i]) == q` evaluates to `true` for any non-constant `valarray<T>` `a`, any `T` `q`, and for any `size_t i` such that the value of `i` is less than the length of `a`. — *end note* ]

3     *Remarks:* The expression `&a[i+j] == &a[i] + j` evaluates to `true` for all `size_t i` and `size_t j` such that `i+j < a.size()`.

4     The expression `&a[i] != &b[j]` evaluates to `true` for any two arrays `a` and `b` and for any `size_t i` and `size_t j` such that `i < a.size()` and `j < b.size()`. [ *Note:* This property indicates an absence of aliasing and may be used to advantage by optimizing compilers. Compilers may take advantage of inlining, constant propagation, loop fusion, tracking of pointers obtained from `operator new`, and other techniques to generate efficient `valarrays`. — *end note* ]

5     The reference returned by the subscript operator for an array shall be valid until the member function `resize(size_t, T)` (29.7.2.8) is called for that array or until the lifetime of that array ends, whichever happens first.

#### 29.7.2.5 `valarray` subset operations

[`valarray.sub`]

1     The member `operator[]` is overloaded to provide several ways to select sequences of elements from among those controlled by `*this`. Each of these operations returns a subset of the array. The const-qualified versions return this subset as a new `valarray` object. The non-const versions return a class template object which has reference semantics to the original array, working in conjunction with various overloads of `operator=` and other assigning operators to allow selective replacement (slicing) of the controlled sequence. In each case the selected element(s) must exist.

```
valarray operator[](slice slicearr) const;
```

2     *Returns:* A `valarray` containing those elements of the controlled sequence designated by `slicearr`.  
[ *Example:*

```
const valarray<char> v0("abcdefghijklmnop", 16);
// v0[slice(2, 5, 3)] returns valarray<char>("cfilo", 5)
```

— end example]

```
slice_array<T> operator[](slice slicearr);
```

- 3 *Returns:* An object that holds references to elements of the controlled sequence selected by `slicearr`.  
[ *Example:*

```
valarray<char> v0("abcdefghijklmnop", 16);
valarray<char> v1("ABCDE", 5);
v0[slice(2, 5, 3)] = v1;
// v0 == valarray<char>("abAdeBghCjkDmnEp", 16);
```

— end example]

```
valarray operator[](const gslice& gslicearr) const;
```

- 4 *Returns:* A `valarray` containing those elements of the controlled sequence designated by `gslicearr`.  
[ *Example:*

```
const valarray<char> v0("abcdefghijklmnop", 16);
const size_t lv[] = { 2, 3 };
const size_t dv[] = { 7, 2 };
const valarray<size_t> len(lv, 2), str(dv, 2);
// v0[gslice(3, len, str)] returns
// valarray<char>("dfhkmo", 6)
```

— end example]

```
gslice_array<T> operator[](const gslice& gslicearr);
```

- 5 *Returns:* An object that holds references to elements of the controlled sequence selected by `gslicearr`.  
[ *Example:*

```
valarray<char> v0("abcdefghijklmnop", 16);
valarray<char> v1("ABCDEF", 6);
const size_t lv[] = { 2, 3 };
const size_t dv[] = { 7, 2 };
const valarray<size_t> len(lv, 2), str(dv, 2);
v0[gslice(3, len, str)] = v1;
// v0 == valarray<char>("abcAeBgCijDlEnFp", 16)
```

— end example]

```
valarray operator[](const valarray<bool>& boolarr) const;
```

- 6 *Returns:* A `valarray` containing those elements of the controlled sequence designated by `boolarr`.  
[ *Example:*

```
const valarray<char> v0("abcdefghijklmnop", 16);
const bool vb[] = { false, false, true, true, false, true };
// v0[valarray<bool>(vb, 6)] returns
// valarray<char>("cdf", 3)
```

— end example]

```
mask_array<T> operator[](const valarray<bool>& boolarr);
```

- 7 *Returns:* An object that holds references to elements of the controlled sequence selected by `boolarr`.  
[ *Example:*

```
valarray<char> v0("abcdefghijklmnop", 16);
valarray<char> v1("ABC", 3);
const bool vb[] = { false, false, true, true, false, true };
```

```

v0[valarray<bool>(vb, 6)] = v1;
// v0 == valarray<char>("abABeCghijklmnop", 16)
— end example]

```

```
valarray operator[](const valarray<size_t>& indarr) const;
```

- 8 *Returns:* A `valarray` containing those elements of the controlled sequence designated by `indarr`.  
*[Example:*

```

const valarray<char> v0("abcdefghijklnop", 16);
const size_t vi[] = { 7, 5, 2, 3, 8 };
// v0[valarray<size_t>(vi, 5)] returns
// valarray<char>("hfcdi", 5)
— end example]

```

```
indirect_array<T> operator[](const valarray<size_t>& indarr);
```

- 9 *Returns:* An object that holds references to elements of the controlled sequence selected by `indarr`.  
*[Example:*

```

valarray<char> v0("abcdefghijklnop", 16);
valarray<char> v1("ABCDE", 5);
const size_t vi[] = { 7, 5, 2, 3, 8 };
v0[valarray<size_t>(vi, 5)] = v1;
// v0 == valarray<char>("abCDeBgAEjklmnop", 16)
— end example]

```

### 29.7.2.6 valarray unary operators

[`valarray.unary`]

```

valarray operator+() const;
valarray operator-() const;
valarray operator~() const;
valarray<bool> operator!() const;

```

- 1 *Requires:* Each of these operators may only be instantiated for a type `T` to which the indicated operator can be applied and for which the indicated operator returns a value which is of type `T` (`bool` for `operator!`) or which may be unambiguously implicitly converted to type `T` (`bool` for `operator!`).  
2 *Returns:* A `valarray` whose length is `size()`. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array.

### 29.7.2.7 valarray compound assignment

[`valarray.cassign`]

```

valarray& operator*= (const valarray& v);
valarray& operator/= (const valarray& v);
valarray& operator%= (const valarray& v);
valarray& operator+= (const valarray& v);
valarray& operator-= (const valarray& v);
valarray& operator^= (const valarray& v);
valarray& operator&= (const valarray& v);
valarray& operator|= (const valarray& v);
valarray& operator<<= (const valarray& v);
valarray& operator>>= (const valarray& v);

```

- 1 *Requires:* `size() == v.size()`. Each of these operators may only be instantiated for a type `T` if the indicated operator can be applied to two operands of type `T`. The value of an element in the left-hand side of a `valarray` compound assignment operator does not depend on the value of another element in that left hand side.



2 *Effects:* Each of these operators performs the indicated operation on each of the elements of **\*this** and the corresponding element of **v**.

3 *Returns:* **\*this**.

4 *Remarks:* The appearance of an array on the left-hand side of a compound assignment does not invalidate references or pointers.

```
valarray& operator*=(const T& v);
valarray& operator/=(const T& v);
valarray& operator%=(const T& v);
valarray& operator+=(const T& v);
valarray& operator-=(const T& v);
valarray& operator^=(const T& v);
valarray& operator&=(const T& v);
valarray& operator|=(const T& v);
valarray& operator<<=(const T& v);
valarray& operator>>=(const T& v);
```

5 *Requires:* Each of these operators may only be instantiated for a type **T** if the indicated operator can be applied to two operands of type **T**.

6 *Effects:* Each of these operators applies the indicated operation to each element of **\*this** and **v**.

7 *Returns:* **\*this**

8 *Remarks:* The appearance of an array on the left-hand side of a compound assignment does not invalidate references or pointers to the elements of the array.

### 29.7.2.8 valarray member functions

[valarray.members]

```
void swap(valarray& v) noexcept;
```

1 *Effects:* **\*this** obtains the value of **v**. **v** obtains the value of **\*this**.

2 *Complexity:* Constant.

```
size_t size() const;
```

3 *Returns:* The number of elements in the array.

4 *Complexity:* Constant time.

```
T sum() const;
```

5 *Requires:* **size()** > 0. This function may only be instantiated for a type **T** to which **operator+=** can be applied.

6 *Returns:* The sum of all the elements of the array. If the array has length 1, returns the value of element 0. Otherwise, the returned value is calculated by applying **operator+=** to a copy of an element of the array and all other elements of the array in an unspecified order.

```
T min() const;
```

7 *Requires:* **size()** > 0

8 *Returns:* The minimum value contained in **\*this**. For an array of length 1, the value of element 0 is returned. For all other array lengths, the determination is made using **operator<**.

```
T max() const;
```

9 *Requires:* **size()** > 0.

10 *Returns:* The maximum value contained in **\*this**. For an array of length 1, the value of element 0 is

returned. For all other array lengths, the determination is made using `operator<`.

`valarray shift(int n) const;`

11 *Returns:* A `valarray` of length `size()`, each of whose elements  $I$  is `(*this)[I + n]` if  $I + n$  is non-negative and less than `size()`, otherwise `T()`. [ *Note:* If element zero is taken as the leftmost element, a positive value of  $n$  shifts the elements left  $n$  places, with zero fill. — *end note* ]

12 [ *Example:* If the argument has the value -2, the first two elements of the result will be value-initialized (11.6); the third element of the result will be assigned the value of the first element of the argument; etc. — *end example* ]

`valarray cshift(int n) const;`

13 *Returns:* A `valarray` of length `size()` that is a circular shift of `*this`. If element zero is taken as the leftmost element, a non-negative value of  $n$  shifts the elements circularly left  $n$  places and a negative value of  $n$  shifts the elements circularly right  $-n$  places.

`valarray apply(T func(T)) const;`

`valarray apply(T func(const T&)) const;`

14 *Returns:* A `valarray` whose length is `size()`. Each element of the returned array is assigned the value returned by applying the argument function to the corresponding element of `*this`.

`void resize(size_t sz, T c = T());`

15 *Effects:* Changes the length of the `*this` array to `sz` and then assigns to each element the value of the second argument. Resizing invalidates all pointers and references to elements in the array.

### 29.7.3 `valarray` non-member operations

[`valarray.nonmembers`]

#### 29.7.3.1 `valarray` binary operators

[`valarray.binary`]

```
template<class T> valarray<T> operator*
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator/
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator%
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator+
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator-
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator^
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator&
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator|
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator<<
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> operator>>
 (const valarray<T>&, const valarray<T>&);
```

1 *Requires:* Each of these operators may only be instantiated for a type `T` to which the indicated operator can be applied and for which the indicated operator returns a value which is of type `T` or which can be unambiguously implicitly converted to type `T`. The argument arrays have the same length.

2 *Returns:* A `valarray` whose length is equal to the lengths of the argument arrays. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding

elements of the argument arrays.

```
template<class T> valarray<T> operator* (const valarray<T>&, const T&);
template<class T> valarray<T> operator* (const T&, const valarray<T>&);
template<class T> valarray<T> operator/ (const valarray<T>&, const T&);
template<class T> valarray<T> operator/ (const T&, const valarray<T>&);
template<class T> valarray<T> operator% (const valarray<T>&, const T&);
template<class T> valarray<T> operator% (const T&, const valarray<T>&);
template<class T> valarray<T> operator+ (const valarray<T>&, const T&);
template<class T> valarray<T> operator+ (const T&, const valarray<T>&);
template<class T> valarray<T> operator- (const valarray<T>&, const T&);
template<class T> valarray<T> operator- (const T&, const valarray<T>&);
template<class T> valarray<T> operator^ (const valarray<T>&, const T&);
template<class T> valarray<T> operator^ (const T&, const valarray<T>&);
template<class T> valarray<T> operator& (const valarray<T>&, const T&);
template<class T> valarray<T> operator& (const T&, const valarray<T>&);
template<class T> valarray<T> operator| (const valarray<T>&, const T&);
template<class T> valarray<T> operator| (const T&, const valarray<T>&);
template<class T> valarray<T> operator<< (const valarray<T>&, const T&);
template<class T> valarray<T> operator<< (const T&, const valarray<T>&);
template<class T> valarray<T> operator>> (const valarray<T>&, const T&);
template<class T> valarray<T> operator>> (const T&, const valarray<T>&);
```

- 3 *Requires:* Each of these operators may only be instantiated for a type T to which the indicated operator can be applied and for which the indicated operator returns a value which is of type T or which can be unambiguously implicitly converted to type T.
- 4 *Returns:* A `valarray` whose length is equal to the length of the array argument. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array argument and the non-array argument.

### 29.7.3.2 valarray logical operators

[valarray.comparison]

```
template<class T> valarray<bool> operator==
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator!=
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator<
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator>
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator<=
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator>=
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator&&
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<bool> operator||
 (const valarray<T>&, const valarray<T>&);
```

- 1 *Requires:* Each of these operators may only be instantiated for a type T to which the indicated operator can be applied and for which the indicated operator returns a value which is of type `bool` or which can be unambiguously implicitly converted to type `bool`. The two array arguments have the same length.
- 2 *Returns:* A `valarray<bool>` whose length is equal to the length of the array arguments. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding elements of the argument arrays.

```

template<class T> valarray<bool> operator==(const valarray<T>&, const T&);
template<class T> valarray<bool> operator==(const T&, const valarray<T>&);
template<class T> valarray<bool> operator!=(const valarray<T>&, const T&);
template<class T> valarray<bool> operator!=(const T&, const valarray<T>&);
template<class T> valarray<bool> operator< (const valarray<T>&, const T&);
template<class T> valarray<bool> operator< (const T&, const valarray<T>&);
template<class T> valarray<bool> operator> (const valarray<T>&, const T&);
template<class T> valarray<bool> operator> (const T&, const valarray<T>&);
template<class T> valarray<bool> operator<=(const valarray<T>&, const T&);
template<class T> valarray<bool> operator<=(const T&, const valarray<T>&);
template<class T> valarray<bool> operator>=(const valarray<T>&, const T&);
template<class T> valarray<bool> operator>=(const T&, const valarray<T>&);
template<class T> valarray<bool> operator&&(const valarray<T>&, const T&);
template<class T> valarray<bool> operator&&(const T&, const valarray<T>&);
template<class T> valarray<bool> operator||(const valarray<T>&, const T&);
template<class T> valarray<bool> operator||(const T&, const valarray<T>&);

```

- 3 *Requires:* Each of these operators may only be instantiated for a type T to which the indicated operator can be applied and for which the indicated operator returns a value which is of type bool or which can be unambiguously implicitly converted to type bool.
- 4 *Returns:* A `valarray<bool>` whose length is equal to the length of the array argument. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array and the non-array argument.

### 29.7.3.3 valarray transcendentals

[valarray.transcend]

```

template<class T> valarray<T> abs (const valarray<T>&);
template<class T> valarray<T> acos (const valarray<T>&);
template<class T> valarray<T> asin (const valarray<T>&);
template<class T> valarray<T> atan (const valarray<T>&);
template<class T> valarray<T> atan2
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> atan2(const valarray<T>&, const T&);
template<class T> valarray<T> atan2(const T&, const valarray<T>&);
template<class T> valarray<T> cos (const valarray<T>&);
template<class T> valarray<T> cosh (const valarray<T>&);
template<class T> valarray<T> exp (const valarray<T>&);
template<class T> valarray<T> log (const valarray<T>&);
template<class T> valarray<T> log10(const valarray<T>&);
template<class T> valarray<T> pow
 (const valarray<T>&, const valarray<T>&);
template<class T> valarray<T> pow (const valarray<T>&, const T&);
template<class T> valarray<T> pow (const T&, const valarray<T>&);
template<class T> valarray<T> sin (const valarray<T>&);
template<class T> valarray<T> sinh (const valarray<T>&);
template<class T> valarray<T> sqrt (const valarray<T>&);
template<class T> valarray<T> tan (const valarray<T>&);
template<class T> valarray<T> tanh (const valarray<T>&);

```

- 1 *Requires:* Each of these functions may only be instantiated for a type T to which a unique function with the indicated name can be applied (unqualified). This function shall return a value which is of type T or which can be unambiguously implicitly converted to type T.

### 29.7.3.4 valarray specialized algorithms

[valarray.special]

```

template <class T> void swap(valarray<T>& x, valarray<T>& y) noexcept;

```

<sup>1</sup> *Effects:* Equivalent to `x.swap(y)`.

## 29.7.4 Class slice

[class.slice]

### 29.7.4.1 Class slice overview

[class.slice.overview]

```
namespace std {
 class slice {
 public:
 slice();
 slice(size_t, size_t, size_t);

 size_t start() const;
 size_t size() const;
 size_t stride() const;
 };
}
```

<sup>1</sup> The `slice` class represents a BLAS-like slice from an array. Such a slice is specified by a starting index, a length, and a stride.<sup>280</sup>

### 29.7.4.2 slice constructors

[cons.slice]

```
slice();
slice(size_t start, size_t length, size_t stride);
slice(const slice&);
```

<sup>1</sup> The default constructor is equivalent to `slice(0, 0, 0)`. A default constructor is provided only to permit the declaration of arrays of slices. The constructor with arguments for a slice takes a start, length, and stride parameter.

<sup>2</sup> [*Example:* `slice(3, 8, 2)` constructs a slice which selects elements 3, 5, 7, ... 17 from an array. — *end example*]

### 29.7.4.3 slice access functions

[slice.access]

```
size_t start() const;
size_t size() const;
size_t stride() const;
```

<sup>1</sup> *Returns:* The start, length, or stride specified by a `slice` object.

<sup>2</sup> *Complexity:* Constant time.

## 29.7.5 Class template slice\_array

[template.slice.array]

### 29.7.5.1 Class template slice\_array overview

[template.slice.array.overview]

```
namespace std {
 template <class T> class slice_array {
 public:
 using value_type = T;

 void operator= (const valarray<T>&) const;
 void operator*= (const valarray<T>&) const;
 void operator/= (const valarray<T>&) const;
 void operator%=(const valarray<T>&) const;
 void operator+=(const valarray<T>&) const;
```

<sup>280</sup>) BLAS stands for *Basic Linear Algebra Subprograms*. C++ programs may instantiate this class. See, for example, Dongarra, Du Croz, Duff, and Hammerling: *A set of Level 3 Basic Linear Algebra Subprograms*; Technical Report MCS-P1-0888, Argonne National Laboratory (USA), Mathematics and Computer Science Division, August, 1988.

```

void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<<= (const valarray<T>&) const;
void operator>>= (const valarray<T>&) const;

slice_array(const slice_array&);
~slice_array();
const slice_array& operator=(const slice_array&) const;
void operator=(const T&) const;

slice_array() = delete; // as implied by declaring copy constructor above
};
}

```

- <sup>1</sup> The `slice_array` template is a helper template used by the `slice` subscript operator

```
slice_array<T> valarray<T>::operator[] (slice);
```

It has reference semantics to a subset of an array specified by a `slice` object.

- <sup>2</sup> [*Example:* The expression `a[slice(1, 5, 3)] = b;` has the effect of assigning the elements of `b` to a slice of the elements in `a`. For the slice shown, the elements selected from `a` are 1, 4, ..., 13. — *end example*]

### 29.7.5.2 `slice_array` assignment [slice.arr.assign]

```

void operator=(const valarray<T>&) const;
const slice_array& operator=(const slice_array&) const;

```

- <sup>1</sup> These assignment operators have reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which the `slice_array` object refers.

### 29.7.5.3 `slice_array` compound assignment [slice.arr.comp.assign]

```

void operator*= (const valarray<T>&) const;
void operator/= (const valarray<T>&) const;
void operator%= (const valarray<T>&) const;
void operator+= (const valarray<T>&) const;
void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<<= (const valarray<T>&) const;
void operator>>= (const valarray<T>&) const;

```

- <sup>1</sup> These compound assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the `slice_array` object refers.

### 29.7.5.4 `slice_array` fill function [slice.arr.fill]

```
void operator=(const T&) const;
```

- <sup>1</sup> This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `slice_array` object refers.

## 29.7.6 The `gslice` class [class.gslice]

### 29.7.6.1 The `gslice` class overview [class.gslice.overview]

```

namespace std {
 class gslice {
 public:
 gslice();
 gslice(size_t s, const valarray<size_t>& l, const valarray<size_t>& d);

 size_t start() const;
 valarray<size_t> size() const;
 valarray<size_t> stride() const;
 };
}

```

- <sup>1</sup> This class represents a generalized slice out of an array. A **gslice** is defined by a starting offset ( $s$ ), a set of lengths ( $l_j$ ), and a set of strides ( $d_j$ ). The number of lengths shall equal the number of strides.
- <sup>2</sup> A **gslice** represents a mapping from a set of indices ( $i_j$ ), equal in number to the number of strides, to a single index  $k$ . It is useful for building multidimensional array classes using the **valarray** template, which is one-dimensional. The set of one-dimensional index values specified by a **gslice** are

$$k = s + \sum_j i_j d_j$$

where the multidimensional indices  $i_j$  range in value from 0 to  $l_{ij} - 1$ .

- <sup>3</sup> [*Example:* The **gslice** specification

```

start = 3
length = {2, 4, 3}
stride = {19, 4, 1}

```

yields the sequence of one-dimensional indices

$$k = 3 + (0, 1) \times 19 + (0, 1, 2, 3) \times 4 + (0, 1, 2) \times 1$$

which are ordered as shown in the following table:

| $(i_0,$ | $i_1,$ | $i_2,$ | $k)$ | = |
|---------|--------|--------|------|---|
| (0,     | 0,     | 0,     | 3),  |   |
| (0,     | 0,     | 1,     | 4),  |   |
| (0,     | 0,     | 2,     | 5),  |   |
| (0,     | 1,     | 0,     | 7),  |   |
| (0,     | 1,     | 1,     | 8),  |   |
| (0,     | 1,     | 2,     | 9),  |   |
| (0,     | 2,     | 0,     | 11), |   |
| (0,     | 2,     | 1,     | 12), |   |
| (0,     | 2,     | 2,     | 13), |   |
| (0,     | 3,     | 0,     | 15), |   |
| (0,     | 3,     | 1,     | 16), |   |
| (0,     | 3,     | 2,     | 17), |   |
| (1,     | 0,     | 0,     | 22), |   |
| (1,     | 0,     | 1,     | 23), |   |
| ...     |        |        |      |   |
| (1,     | 3,     | 2,     | 36)  |   |

That is, the highest-ordered index turns fastest. — *end example*]

- <sup>4</sup> It is possible to have degenerate generalized slices in which an address is repeated.

- <sup>5</sup> [*Example*: If the stride parameters in the previous example are changed to {1, 1, 1}, the first few elements of the resulting sequence of indices will be

```
(0, 0, 0, 3),
(0, 0, 1, 4),
(0, 0, 2, 5),
(0, 1, 0, 4),
(0, 1, 1, 5),
(0, 1, 2, 6),
...
```

— *end example*]

- <sup>6</sup> If a degenerate slice is used as the argument to the non-const version of `operator[]` (`const gslice&`), the behavior is undefined.

### 29.7.6.2 gslice constructors

[gslice.cons]

```
gslice();
gslice(size_t start, const valarray<size_t>& lengths,
 const valarray<size_t>& strides);
gslice(const gslice&);
```

- <sup>1</sup> The default constructor is equivalent to `gslice(0, valarray<size_t>(), valarray<size_t>())`. The constructor with arguments builds a `gslice` based on a specification of start, lengths, and strides, as explained in the previous section.

### 29.7.6.3 gslice access functions

[gslice.access]

```
size_t start() const;
valarray<size_t> size() const;
valarray<size_t> stride() const;
```

- <sup>1</sup> *Returns*: The representation of the start, lengths, or strides specified for the `gslice`.
- <sup>2</sup> *Complexity*: `start()` is constant time. `size()` and `stride()` are linear in the number of strides.

## 29.7.7 Class template gslice\_array

[template.gslice.array]

### 29.7.7.1 Class template gslice\_array overview

[template.gslice.array.overview]

```
namespace std {
 template <class T> class gslice_array {
 public:
 using value_type = T;

 void operator= (const valarray<T>&) const;
 void operator*= (const valarray<T>&) const;
 void operator/= (const valarray<T>&) const;
 void operator%=(const valarray<T>&) const;
 void operator+=(const valarray<T>&) const;
 void operator-=(const valarray<T>&) const;
 void operator^=(const valarray<T>&) const;
 void operator&=(const valarray<T>&) const;
 void operator|=(const valarray<T>&) const;
 void operator<<=(const valarray<T>&) const;
 void operator>>=(const valarray<T>&) const;
```



```

 gslice_array(const gslice_array&);
 ~gslice_array();
 const gslice_array& operator=(const gslice_array&) const;
 void operator=(const T&) const;

 gslice_array() = delete; // as implied by declaring copy constructor above
};
}

```

<sup>1</sup> This template is a helper template used by the `slice` subscript operator

```
gslice_array<T> valarray<T>::operator[](const gslice&);
```

<sup>2</sup> It has reference semantics to a subset of an array specified by a `gslice` object.

<sup>3</sup> Thus, the expression `a[gslice(1, length, stride)] = b` has the effect of assigning the elements of `b` to a generalized slice of the elements in `a`.

### 29.7.7.2 `gslice_array` assignment

[`gslice.array.assign`]

```

void operator=(const valarray<T>&) const;
const gslice_array& operator=(const gslice_array&) const;

```

<sup>1</sup> These assignment operators have reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which the `gslice_array` refers.

### 29.7.7.3 `gslice_array` compound assignment

[`gslice.array.comp.assign`]

```

void operator*= (const valarray<T>&) const;
void operator/= (const valarray<T>&) const;
void operator%= (const valarray<T>&) const;
void operator+= (const valarray<T>&) const;
void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<<= (const valarray<T>&) const;
void operator>>= (const valarray<T>&) const;

```

<sup>1</sup> These compound assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the `gslice_array` object refers.

### 29.7.7.4 `gslice_array` fill function

[`gslice.array.fill`]

```
void operator=(const T&) const;
```

<sup>1</sup> This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `gslice_array` object refers.

## 29.7.8 Class template `mask_array`

[`template.mask.array`]

### 29.7.8.1 Class template `mask_array` overview

[`template.mask.array.overview`]

```

namespace std {
 template <class T> class mask_array {
 public:
 using value_type = T;

 void operator= (const valarray<T>&) const;
 void operator*= (const valarray<T>&) const;
 };
}

```

```

void operator/= (const valarray<T>&) const;
void operator%= (const valarray<T>&) const;
void operator+= (const valarray<T>&) const;
void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<<= (const valarray<T>&) const;
void operator>>= (const valarray<T>&) const;

mask_array(const mask_array&);
~mask_array();
const mask_array& operator=(const mask_array&) const;
void operator=(const T&) const;

mask_array() = delete; // as implied by declaring copy constructor above
};
}

```

- <sup>1</sup> This template is a helper template used by the mask subscript operator:

```
mask_array<T> valarray<T>::operator[] (const valarray<bool>&).
```

- <sup>2</sup> It has reference semantics to a subset of an array specified by a boolean mask. Thus, the expression `a[mask] = b;` has the effect of assigning the elements of `b` to the masked elements in `a` (those for which the corresponding element in `mask` is `true`.)

#### 29.7.8.2 mask\_array assignment

[mask.array.assign]

```

void operator=(const valarray<T>&) const;
const mask_array& operator=(const mask_array&) const;

```

- <sup>1</sup> These assignment operators have reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which it refers.

#### 29.7.8.3 mask\_array compound assignment

[mask.array.comp.assign]

```

void operator*= (const valarray<T>&) const;
void operator/= (const valarray<T>&) const;
void operator%= (const valarray<T>&) const;
void operator+= (const valarray<T>&) const;
void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<<= (const valarray<T>&) const;
void operator>>= (const valarray<T>&) const;

```

- <sup>1</sup> These compound assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the mask object refers.

#### 29.7.8.4 mask\_array fill function

[mask.array.fill]

```
void operator=(const T&) const;
```

- <sup>1</sup> This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `mask_array` object refers.

**29.7.9 Class template indirect\_array****[template.indirect.array]****29.7.9.1 Class template indirect\_array overview****[template.indirect.array.overview]**

```

namespace std {
 template <class T> class indirect_array {
 public:
 using value_type = T;

 void operator= (const valarray<T>&) const;
 void operator*= (const valarray<T>&) const;
 void operator/= (const valarray<T>&) const;
 void operator%= (const valarray<T>&) const;
 void operator+= (const valarray<T>&) const;
 void operator-= (const valarray<T>&) const;
 void operator^= (const valarray<T>&) const;
 void operator&= (const valarray<T>&) const;
 void operator|= (const valarray<T>&) const;
 void operator<<= (const valarray<T>&) const;
 void operator>>= (const valarray<T>&) const;

 indirect_array(const indirect_array&);
 ~indirect_array();
 const indirect_array& operator=(const indirect_array&) const;
 void operator=(const T&) const;

 indirect_array() = delete; // as implied by declaring copy constructor above
 };
}

```

- 1 This template is a helper template used by the indirect subscript operator

```
indirect_array<T> valarray<T>::operator[](const valarray<size_t>&).
```

- 2 It has reference semantics to a subset of an array specified by an `indirect_array`. Thus the expression `a[indirect] = b;` has the effect of assigning the elements of `b` to the elements in `a` whose indices appear in `indirect`.

**29.7.9.2 indirect\_array assignment****[indirect.array.assign]**

```

void operator=(const valarray<T>&) const;
const indirect_array& operator=(const indirect_array&) const;

```

- 1 These assignment operators have reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which it refers.
- 2 If the `indirect_array` specifies an element in the `valarray<T>` object to which it refers more than once, the behavior is undefined.

- 3 [Example:

```

 int addr[] = {2, 3, 1, 4, 4};
 valarray<size_t> indirect(addr, 5);
 valarray<double> a(0., 10), b(1., 5);
 a[indirect] = b;

```

results in undefined behavior since element 4 is specified twice in the indirection. — end example]

**29.7.9.3 indirect\_array compound assignment****[indirect.array.comp.assign]**

```
void operator*= (const valarray<T>&) const;
```

```

void operator/= (const valarray<T>&) const;
void operator%= (const valarray<T>&) const;
void operator+= (const valarray<T>&) const;
void operator-= (const valarray<T>&) const;
void operator^= (const valarray<T>&) const;
void operator&= (const valarray<T>&) const;
void operator|= (const valarray<T>&) const;
void operator<= (const valarray<T>&) const;
void operator>= (const valarray<T>&) const;

```

- 1 These compound assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the `indirect_array` object refers.
- 2 If the `indirect_array` specifies an element in the `valarray<T>` object to which it refers more than once, the behavior is undefined.

#### 29.7.9.4 `indirect_array` fill function

[`indirect.array.fill`]

```
void operator=(const T&) const;
```

- 1 This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `indirect_array` object refers.

#### 29.7.10 `valarray` range access

[`valarray.range`]

- 1 In the `begin` and `end` function templates that follow, *unspecified1* is a type that meets the requirements of a mutable random access iterator (27.2.7) and of a contiguous iterator (27.2.1) whose `value_type` is the template parameter `T` and whose `reference` type is `T&`. *unspecified2* is a type that meets the requirements of a constant random access iterator (27.2.7) and of a contiguous iterator (27.2.1) whose `value_type` is the template parameter `T` and whose `reference` type is `const T&`.
- 2 The iterators returned by `begin` and `end` for an array are guaranteed to be valid until the member function `resize(size_t, T)` (29.7.2.8) is called for that array or until the lifetime of that array ends, whichever happens first.

```

template <class T> unspecified1 begin(valarray<T>& v);
template <class T> unspecified2 begin(const valarray<T>& v);

```

- 3 *Returns:* An iterator referencing the first value in the array.

```

template <class T> unspecified1 end(valarray<T>& v);
template <class T> unspecified2 end(const valarray<T>& v);

```

- 4 *Returns:* An iterator referencing one past the last value in the array.

### 29.8 Generalized numeric operations

[`numeric.ops`]

#### 29.8.1 Header `<numeric>` synopsis

[`numeric.ops.overview`]

```

namespace std {
 // 29.8.2, accumulate
 template <class InputIterator, class T>
 T accumulate(InputIterator first, InputIterator last, T init);
 template <class InputIterator, class T, class BinaryOperation>
 T accumulate(InputIterator first, InputIterator last, T init,
 BinaryOperation binary_op);

 // 29.8.3, reduce
 template<class InputIterator>

```

```

 typename iterator_traits<InputIterator>::value_type
 reduce(InputIterator first, InputIterator last);
template<class InputIterator, class T>
 T reduce(InputIterator first, InputIterator last, T init);
template<class InputIterator, class T, class BinaryOperation>
 T reduce(InputIterator first, InputIterator last, T init,
 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator>
 typename iterator_traits<ForwardIterator>::value_type
 reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last);
template<class ExecutionPolicy, class ForwardIterator, class T>
 T reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, T init);
template<class ExecutionPolicy, class ForwardIterator, class T, class BinaryOperation>
 T reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last, T init,
 BinaryOperation binary_op);

// 29.8.4, inner product
template <class InputIterator1, class InputIterator2, class T>
 T inner_product(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, T init);
template <class InputIterator1, class InputIterator2, class T,
 class BinaryOperation1, class BinaryOperation2>
 T inner_product(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);

// 29.8.5, transform reduce
template<class InputIterator1, class InputIterator2, class T>
 T transform_reduce(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2,
 T init);
template<class InputIterator1, class InputIterator2, class T,
 class BinaryOperation1, class BinaryOperation2>
 T transform_reduce(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2,
 T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);
template<class InputIterator, class T,
 class BinaryOperation, class UnaryOperation>
 T transform_reduce(InputIterator first, InputIterator last,
 T init,
 BinaryOperation binary_op, UnaryOperation unary_op);
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T>
 T transform_reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2,
 T init);
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T,

```

```

 class BinaryOperation1, class BinaryOperation2>
 T transform_reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2,
 T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);
template<class ExecutionPolicy,
 class ForwardIterator, class T,
 class BinaryOperation, class UnaryOperation>
 T transform_reduce(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator first, ForwardIterator last,
 T init,
 BinaryOperation binary_op, UnaryOperation unary_op);

// 29.8.6, partial sum
template <class InputIterator, class OutputIterator>
 OutputIterator partial_sum(InputIterator first,
 InputIterator last,
 OutputIterator result);
template <class InputIterator, class OutputIterator, class BinaryOperation>
 OutputIterator partial_sum(InputIterator first,
 InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op);

// 29.8.7, exclusive scan
template<class InputIterator, class OutputIterator, class T>
 OutputIterator exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 T init);
template<class InputIterator, class OutputIterator, class T, class BinaryOperation>
 OutputIterator exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 T init, BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T>
 ForwardIterator2 exclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T,
 class BinaryOperation>
 ForwardIterator2 exclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init, BinaryOperation binary_op);

// 29.8.8, inclusive scan
template<class InputIterator, class OutputIterator>
 OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result);
template<class InputIterator, class OutputIterator, class BinaryOperation>
 OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op);

```

```

template<class InputIterator, class OutputIterator, class BinaryOperation, class T>
 OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op, T init);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation>
 ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation, class T>
 ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op, T init);

// 29.8.9, transform exclusive scan
template<class InputIterator, class OutputIterator, class T,
 class BinaryOperation, class UnaryOperation>
 OutputIterator transform_exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 T init,
 BinaryOperation binary_op,
 UnaryOperation unary_op);
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T,
 class BinaryOperation, class UnaryOperation>
 ForwardIterator2 transform_exclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init,
 BinaryOperation binary_op,
 UnaryOperation unary_op);

// 29.8.10, transform inclusive scan
template<class InputIterator, class OutputIterator,
 class BinaryOperation, class UnaryOperation>
 OutputIterator transform_inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op,
 UnaryOperation unary_op);
template<class InputIterator, class OutputIterator,
 class BinaryOperation, class UnaryOperation, class T>
 OutputIterator transform_inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op,
 UnaryOperation unary_op,
 T init);
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2,

```

```

 class BinaryOperation, class UnaryOperation>
 ForwardIterator2 transform_inclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op,
 UnaryOperation unary_op);

template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation, class UnaryOperation, class T>
 ForwardIterator2 transform_inclusive_scan(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op,
 UnaryOperation unary_op,
 T init);

// 29.8.11, adjacent difference
template <class InputIterator, class OutputIterator>
 OutputIterator adjacent_difference(InputIterator first,
 InputIterator last,
 OutputIterator result);

template <class InputIterator, class OutputIterator, class BinaryOperation>
 OutputIterator adjacent_difference(InputIterator first,
 InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op);

template <class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2 adjacent_difference(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first,
 ForwardIterator1 last,
 ForwardIterator2 result);

template <class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation>
 ForwardIterator2 adjacent_difference(ExecutionPolicy&& exec, // see 28.4.5
 ForwardIterator1 first,
 ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op);

// 29.8.12, iota
template <class ForwardIterator, class T>
 void iota(ForwardIterator first, ForwardIterator last, T value);

// 29.8.13, greatest common divisor
template <class M, class N>
 constexpr common_type_t<M,N> gcd(M m, N n);

// 29.8.14, least common multiple
template <class M, class N>
 constexpr common_type_t<M,N> lcm(M m, N n);
}

```

<sup>1</sup> The requirements on the types of algorithms' arguments that are described in the introduction to Clause 28 also apply to the following algorithms.

<sup>2</sup> Throughout this subclause, the parameters UnaryOperation, BinaryOperation, BinaryOperation1, and



BinaryOperation2 are used whenever an algorithm expects a function object (23.14).

- <sup>3</sup> [Note: The use of closed ranges as well as semi-open ranges to specify requirements throughout this subclause is intentional. — end note]

### 29.8.2 Accumulate

[accumulate]

```
template <class InputIterator, class T>
 T accumulate(InputIterator first, InputIterator last, T init);
template <class InputIterator, class T, class BinaryOperation>
 T accumulate(InputIterator first, InputIterator last, T init,
 BinaryOperation binary_op);
```

- <sup>1</sup> *Requires:* T shall meet the requirements of CopyConstructible (Table 24) and CopyAssignable (Table 26) types. In the range [first, last], binary\_op shall neither modify elements nor invalidate iterators or subranges.<sup>281</sup>
- <sup>2</sup> *Effects:* Computes its result by initializing the accumulator acc with the initial value init and then modifies it with acc = acc + \*i or acc = binary\_op(acc, \*i) for every iterator i in the range [first, last) in order.<sup>282</sup>

### 29.8.3 Reduce

[reduce]

```
template<class InputIterator>
 typename iterator_traits<InputIterator>::value_type
 reduce(InputIterator first, InputIterator last);
```

<sup>1</sup> *Effects:* Equivalent to:

```
 return reduce(first, last,
 typename iterator_traits<InputIterator>::value_type{});
```

```
template<class ExecutionPolicy, class ForwardIterator>
 typename iterator_traits<ForwardIterator>::value_type
 reduce(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last);
```

<sup>2</sup> *Effects:* Equivalent to:

```
 return reduce(std::forward<ExecutionPolicy>(exec), first, last,
 typename iterator_traits<ForwardIterator>::value_type{});
```

```
template<class InputIterator, class T>
 T reduce(InputIterator first, InputIterator last, T init);
```

<sup>3</sup> *Effects:* Equivalent to:

```
 return reduce(first, last, init, plus<>());
```

```
template<class ExecutionPolicy, class ForwardIterator, class T>
 T reduce(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, T init);
```

<sup>4</sup> *Effects:* Equivalent to:

```
 return reduce(std::forward<ExecutionPolicy>(exec), first, last, init, plus<>());
```

```
template<class InputIterator, class T, class BinaryOperation>
 T reduce(InputIterator first, InputIterator last, T init,
```

<sup>281</sup>) The use of fully closed ranges is intentional.

<sup>282</sup>) accumulate is similar to the APL reduction operator and Common Lisp reduce function, but it avoids the difficulty of defining the result of reduction on an empty sequence by always requiring an initial value.

```

 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator, class T, class BinaryOperation>
 T reduce(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last, T init,
 BinaryOperation binary_op);

```

5     *Requires:*

- (5.1)     — T shall be MoveConstructible (Table 23).
  - (5.2)     — All of `binary_op(init, *first)`, `binary_op(*first, init)`, `binary_op(init, init)`, and `binary_op(*first, *first)` shall be convertible to T.
  - (5.3)     — `binary_op` shall neither invalidate iterators or subranges, nor modify elements in the range `[first, last]`.
- 6     *Returns:* `GENERALIZED_SUM(binary_op, init, *i, ...)` for every i in `[first, last]`.
- 7     *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications of `binary_op`.
- 8     [*Note:* The difference between `reduce` and `accumulate` is that `reduce` applies `binary_op` in an unspecified order, which yields a nondeterministic result for non-associative or non-commutative `binary_op` such as floating-point addition. — *end note*]

#### 29.8.4 Inner product

[inner.product]

```

template <class InputIterator1, class InputIterator2, class T>
 T inner_product(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, T init);
template <class InputIterator1, class InputIterator2, class T,
 class BinaryOperation1, class BinaryOperation2>
 T inner_product(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2, T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);

```

- 1     *Requires:* T shall meet the requirements of CopyConstructible (Table 24) and CopyAssignable (Table 26) types. In the ranges `[first1, last1]` and `[first2, first2 + (last1 - first1)]` `binary_op1` and `binary_op2` shall neither modify elements nor invalidate iterators or subranges.<sup>283</sup>
- 2     *Effects:* Computes its result by initializing the accumulator `acc` with the initial value `init` and then modifying it with `acc = acc + (*i1) * (*i2)` or `acc = binary_op1(acc, binary_op2(*i1, *i2))` for every iterator `i1` in the range `[first1, last1)` and iterator `i2` in the range `[first2, first2 + (last1 - first1))` in order.

#### 29.8.5 Transform reduce

[transform.reduce]

```

template <class InputIterator1, class InputIterator2, class T>
 T transform_reduce(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2,
 T init);
template <class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T>
 T transform_reduce(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2,
 T init);

```

<sup>283</sup>) The use of fully closed ranges is intentional.

1 *Effects:* Equivalent to:

```

 return transform_reduce(first1, last1, first2, init, plus<>(), multiplies<>());

template <class InputIterator1, class InputIterator2, class T,
 class BinaryOperation1, class BinaryOperation2>
 T transform_reduce(InputIterator1 first1, InputIterator1 last1,
 InputIterator2 first2,
 T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);

template <class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T,
 class BinaryOperation1, class BinaryOperation2>
 T transform_reduce(ExecutionPolicy&& exec,
 ForwardIterator1 first1, ForwardIterator1 last1,
 ForwardIterator2 first2,
 T init,
 BinaryOperation1 binary_op1,
 BinaryOperation2 binary_op2);

```

2 *Requires:*

- (2.1) — T shall be MoveConstructible (Table 23).
- (2.2) — All of
  - (2.2.1) — binary\_op1(init, init),
  - (2.2.2) — binary\_op1(init, binary\_op2(\*first1, \*first2)),
  - (2.2.3) — binary\_op1(binary\_op2(\*first1, \*first2), init), and
  - (2.2.4) — binary\_op1(binary\_op2(\*first1, \*first2), binary\_op2(\*first1, \*first2))
 shall be convertible to T.
- (2.3) — Neither binary\_op1 nor binary\_op2 shall invalidate subranges, or modify elements in the ranges [first1, last1] and [first2, first2 + (last1 - first1)].

3 *Returns:*

*GENERALIZED\_SUM*(binary\_op1, init, binary\_op2(\*i, \*(first2 + (i - first1))), ...) for every iterator i in [first1, last1).

4 *Complexity:*  $\mathcal{O}(\text{last1} - \text{first1})$  applications each of binary\_op1 and binary\_op2.

```

template<class InputIterator, class T,
 class BinaryOperation, class UnaryOperation>
 T transform_reduce(InputIterator first, InputIterator last, T init,
 BinaryOperation binary_op, UnaryOperation unary_op);

template<class ExecutionPolicy,
 class ForwardIterator, class T,
 class BinaryOperation, class UnaryOperation>
 T transform_reduce(ExecutionPolicy&& exec,
 ForwardIterator first, ForwardIterator last,
 T init, BinaryOperation binary_op, UnaryOperation unary_op);

```

5 *Requires:*

- (5.1) — T shall be MoveConstructible (Table 23).
- (5.2) — All of

- (5.2.1) — `binary_op(init, init)`,
  - (5.2.2) — `binary_op(init, unary_op(*first))`,
  - (5.2.3) — `binary_op(unary_op(*first), init)`, and
  - (5.2.4) — `binary_op(unary_op(*first), unary_op(*first))`
- shall be convertible to `T`.
- (5.3) — Neither `unary_op` nor `binary_op` shall invalidate subranges, or modify elements in the range `[first, last]`.

6 *Returns:*

`GENERALIZED_SUM(binary_op, init, unary_op(*i), ...)`

for every iterator `i` in `[first, last]`.

7 *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications each of `unary_op` and `binary_op`.

8 [*Note:* `transform_reduce` does not apply `unary_op` to `init`. — end note]

## 29.8.6 Partial sum

[partial.sum]

```
template <class InputIterator, class OutputIterator>
OutputIterator partial_sum(
 InputIterator first, InputIterator last,
 OutputIterator result);
template <class InputIterator, class OutputIterator, class BinaryOperation>
OutputIterator partial_sum(
 InputIterator first, InputIterator last,
 OutputIterator result, BinaryOperation binary_op);
```

1 *Requires:* `InputIterator`'s value type shall be constructible from the type of `*first`. The result of the expression `acc + *i` or `binary_op(acc, *i)` shall be implicitly convertible to `InputIterator`'s value type. `acc` shall be writable (27.2.1) to the `result` output iterator. In the ranges `[first, last]` and `[result, result + (last - first)]` `binary_op` shall neither modify elements nor invalidate iterators or subranges.<sup>284</sup>

2 *Effects:* For a non-empty range, the function creates an accumulator `acc` whose type is `InputIterator`'s value type, initializes it with `*first`, and assigns the result to `*result`. For every iterator `i` in `[first + 1, last)` in order, `acc` is then modified by `acc = acc + *i` or `acc = binary_op(acc, *i)` and the result is assigned to `*(result + (i - first))`.

3 *Returns:* `result + (last - first)`.

4 *Complexity:* Exactly  $(\text{last} - \text{first}) - 1$  applications of the binary operation.

5 *Remarks:* `result` may be equal to `first`.

## 29.8.7 Exclusive scan

[exclusive.scan]

```
template<class InputIterator, class OutputIterator, class T>
OutputIterator exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 T init);
```

1 *Effects:* Equivalent to:

```
return exclusive_scan(first, last, result, init, plus<>());
```

```
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2, class T>
```

<sup>284</sup>) The use of fully closed ranges is intentional.

```
ForwardIterator2 exclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init);
```

2 *Effects:* Equivalent to:

```
return exclusive_scan(std::forward<ExecutionPolicy>(exec),
 first, last, result, init, plus<>());
```

```
template<class InputIterator, class OutputIterator, class T, class BinaryOperation>
OutputIterator exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 T init, BinaryOperation binary_op);
```

```
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T, class BinaryOperation>
ForwardIterator2 exclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init, BinaryOperation binary_op);
```

3 *Requires:*

- (3.1) — T shall be MoveConstructible (Table 23).
- (3.2) — All of `binary_op(init, init)`, `binary_op(init, *first)`, and `binary_op(*first, *first)` shall be convertible to T.
- (3.3) — `binary_op` shall neither invalidate iterators or subranges, nor modify elements in the ranges `[first, last]` or `[result, result + (last - first)]`.

4 *Effects:* For each integer K in `[0, last - first)` assigns through `result + K` the value of:

```
GENERALIZED_NONCOMMUTATIVE_SUM(
 binary_op, init, *(first + 0), *(first + 1), ..., *(first + K - 1))
```

5 *Returns:* The end of the resulting range beginning at `result`.

6 *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications of `binary_op`.

7 *Remarks:* `result` may be equal to `first`.

8 [ *Note:* The difference between `exclusive_scan` and `inclusive_scan` is that `exclusive_scan` excludes the *i*th input element from the *i*th sum. If `binary_op` is not mathematically associative, the behavior of `exclusive_scan` may be nondeterministic. — end note ]

## 29.8.8 Inclusive scan

[inclusive.scan]

```
template<class InputIterator, class OutputIterator>
OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result);
```

1 *Effects:* Equivalent to:

```
return inclusive_scan(first, last, result, plus<>());
```

```
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);
```

2 *Effects:* Equivalent to:

```
return inclusive_scan(std::forward<ExecutionPolicy>(exec), first, last, result, plus<>());
```

```

template<class InputIterator, class OutputIterator, class BinaryOperation>
 OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op);
template<class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation>
 ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op);

template<class InputIterator, class OutputIterator, class BinaryOperation, class T>
 OutputIterator inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op, T init);
template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class BinaryOperation, class T>
 ForwardIterator2 inclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op, T init);

```

3     *Requires:*

- (3.1)     — If `init` is provided, `T` shall be `MoveConstructible` (Table 23); otherwise, `ForwardIterator1`'s value type shall be `MoveConstructible`.
- (3.2)     — If `init` is provided, all of `binary_op(init, init)`, `binary_op(init, *first)`, and `binary_op(*first, *first)` shall be convertible to `T`; otherwise, `binary_op(*first, *first)` shall be convertible to `ForwardIterator1`'s value type.
- (3.3)     — `binary_op` shall neither invalidate iterators or subranges, nor modify elements in the ranges `[first, last]` or `[result, result + (last - first)]`.

4     *Effects:* For each integer `K` in `[0, last - first)` assigns through `result + K` the value of

- (4.1)     — *GENERALIZED\_NONCOMMUTATIVE\_SUM*(  
         `binary_op, init, *(first + 0), *(first + 1), ..., *(first + K)`)  
         if `init` is provided, or
- (4.2)     — *GENERALIZED\_NONCOMMUTATIVE\_SUM*(  
         `binary_op, *(first + 0), *(first + 1), ..., *(first + K)`)  
         otherwise.

5     *Returns:* The end of the resulting range beginning at `result`.

6     *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications of `binary_op`.

7     *Remarks:* `result` may be equal to `first`.

8     [ *Note:* The difference between `exclusive_scan` and `inclusive_scan` is that `inclusive_scan` includes the *i*th input element in the *i*th sum. If `binary_op` is not mathematically associative, the behavior of `inclusive_scan` may be nondeterministic. — end note ]

## 29.8.9 Transform exclusive scan

[transform.exclusive.scan]

```

template<class InputIterator, class OutputIterator, class T,
 class BinaryOperation, class UnaryOperation>
 OutputIterator transform_exclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,

```

```

 T init,
 BinaryOperation binary_op,
 UnaryOperation unary_op);

template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2, class T,
 class BinaryOperation, class UnaryOperation>
ForwardIterator2 transform_exclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 T init,
 BinaryOperation binary_op,
 UnaryOperation unary_op);

```

1 *Requires:*

- (1.1) — T shall be MoveConstructible (Table 23).
- (1.2) — All of
  - (1.2.1) — binary\_op(init, init),
  - (1.2.2) — binary\_op(init, unary\_op(\*first)), and
  - (1.2.3) — binary\_op(unary\_op(\*first), unary\_op(\*first))
 shall be convertible to T.
- (1.3) — Neither unary\_op nor binary\_op shall invalidate iterators or subranges, or modify elements in the ranges [first, last] or [result, result + (last - first)].

2 *Effects:* For each integer K in [0, last - first) assigns through result + K the value of:

```

GENERALIZED_NONCOMMUTATIVE_SUM(
 binary_op, init,
 unary_op(*(first + 0)), unary_op(*(first + 1)), ..., unary_op(*(first + K - 1)))

```

3 *Returns:* The end of the resulting range beginning at result.

4 *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications each of unary\_op and binary\_op.

5 *Remarks:* result may be equal to first.

6 [Note: The difference between transform\_exclusive\_scan and transform\_inclusive\_scan is that transform\_exclusive\_scan excludes the  $i^{\text{th}}$  input element from the  $i^{\text{th}}$  sum. If binary\_op is not mathematically associative, the behavior of transform\_exclusive\_scan may be nondeterministic. transform\_exclusive\_scan does not apply unary\_op to init. — end note]

## 29.8.10 Transform inclusive scan

[transform.inclusive.scan]

```

template<class InputIterator, class OutputIterator,
 class BinaryOperation, class UnaryOperation>
OutputIterator transform_inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op,
 UnaryOperation unary_op);

template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation, class UnaryOperation>
ForwardIterator2 transform_inclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op,

```

```

 UnaryOperation unary_op);
template<class InputIterator, class OutputIterator,
 class BinaryOperation, class UnaryOperation, class T>
 OutputIterator transform_inclusive_scan(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op,
 UnaryOperation unary_op,
 T init);

template<class ExecutionPolicy,
 class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation, class UnaryOperation, class T>
 ForwardIterator2 transform_inclusive_scan(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op,
 UnaryOperation unary_op,
 T init);

```

1 *Requires:*

- (1.1) — If `init` is provided, `T` shall be `MoveConstructible` (Table 23); otherwise, `ForwardIterator1`'s value type shall be `MoveConstructible`.
- (1.2) — If `init` is provided, all of
  - (1.2.1) — `binary_op(init, init)`,
  - (1.2.2) — `binary_op(init, unary_op(*first))`, and
  - (1.2.3) — `binary_op(unary_op(*first), unary_op(*first))`
 shall be convertible to `T`; otherwise, `binary_op(unary_op(*first), unary_op(*first))` shall be convertible to `ForwardIterator1`'s value type.
- (1.3) — Neither `unary_op` nor `binary_op` shall invalidate iterators or subranges, nor modify elements in the ranges `[first, last]` or `[result, result + (last - first)]`.

2 *Effects:* For each integer `K` in `[0, last - first)` assigns through `result + K` the value of

- (2.1) — `GENERALIZED_NONCOMMUTATIVE_SUM(`  
     `binary_op, init,`  
     `unary_op(*(first + 0)), unary_op(*(first + 1)), ..., unary_op(*(first + K))`  
     if `init` is provided, or
- (2.2) — `GENERALIZED_NONCOMMUTATIVE_SUM(`  
     `binary_op,`  
     `unary_op(*(first + 0)), unary_op(*(first + 1)), ..., unary_op(*(first + K))`  
     otherwise.

3 *Returns:* The end of the resulting range beginning at `result`.

4 *Complexity:*  $\mathcal{O}(\text{last} - \text{first})$  applications each of `unary_op` and `binary_op`.

5 *Remarks:* `result` may be equal to `first`.

6 [ *Note:* The difference between `transform_exclusive_scan` and `transform_inclusive_scan` is that `transform_inclusive_scan` includes the  $i^{\text{th}}$  input element in the  $i^{\text{th}}$  sum. If `binary_op` is not mathematically associative, the behavior of `transform_inclusive_scan` may be nondeterministic. `transform_inclusive_scan` does not apply `unary_op` to `init`. — end note ]

## 29.8.11 Adjacent difference

[adjacent.difference]



```

template <class InputIterator, class OutputIterator>
 OutputIterator
 adjacent_difference(InputIterator first, InputIterator last,
 OutputIterator result);
template <class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2>
 ForwardIterator2
 adjacent_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result);

template <class InputIterator, class OutputIterator, class BinaryOperation>
 OutputIterator
 adjacent_difference(InputIterator first, InputIterator last,
 OutputIterator result,
 BinaryOperation binary_op);
template <class ExecutionPolicy, class ForwardIterator1, class ForwardIterator2,
 class BinaryOperation>
 ForwardIterator2
 adjacent_difference(ExecutionPolicy&& exec,
 ForwardIterator1 first, ForwardIterator1 last,
 ForwardIterator2 result,
 BinaryOperation binary_op);

```

1 *Requires:*

- (1.1) — For the overloads with no `ExecutionPolicy`, `InputIterator`'s value type shall be `MoveAssignable` (Table 25) and shall be constructible from the type of `*first`. `acc` (defined below) shall be writable (27.2.1) to the `result` output iterator. The result of the expression `val - acc` or `binary_op(val, acc)` shall be writable to the `result` output iterator.
- (1.2) — For the overloads with an `ExecutionPolicy`, the value type of `ForwardIterator1` shall be `CopyConstructible` (Table 24), constructible from the expression `*first - *first` or `binary_op(*first, *first)`, and assignable to the value type of `ForwardIterator2`.
- (1.3) — For all overloads, in the ranges `[first, last]` and `[result, result + (last - first)]`, `binary_op` shall neither modify elements nor invalidate iterators or subranges.<sup>285</sup>

2 *Effects:* For the overloads with no `ExecutionPolicy` and a non-empty range, the function creates an accumulator `acc` whose type is `InputIterator`'s value type, initializes it with `*first`, and assigns the result to `*result`. For every iterator `i` in `[first + 1, last)` in order, creates an object `val` whose type is `InputIterator`'s value type, initializes it with `*i`, computes `val - acc` or `binary_op(val, acc)`, assigns the result to `*(result + (i - first))`, and move assigns from `val` to `acc`.

3 For the overloads with an `ExecutionPolicy` and a non-empty range, first the function creates an object whose type is `ForwardIterator1`'s value type, initializes it with `*first`, and assigns the result to `*result`. Then for every `d` in `[1, last - first - 1]`, creates an object `val` whose type is `ForwardIterator1`'s value type, initializes it with `*(first + d) - *(first + d - 1)` or `binary_op(*(first + d), *(first + d - 1))`, and assigns the result to `*(result + d)`.

4 *Returns:* `result + (last - first)`.

5 *Complexity:* Exactly `(last - first) - 1` applications of the binary operation.

6 *Remarks:* For the overloads with no `ExecutionPolicy`, `result` may be equal to `first`. For the overloads with an `ExecutionPolicy`, the ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

285) The use of fully closed ranges is intentional.

**29.8.12 Iota****[numeric.iota]**

```
template <class ForwardIterator, class T>
void iota(ForwardIterator first, ForwardIterator last, T value);
```

- 1 *Requires:* T shall be convertible to ForwardIterator's value type. The expression ++val, where val has type T, shall be well formed.
- 2 *Effects:* For each element referred to by the iterator i in the range [first, last), assigns \*i = value and increments value as if by ++value.
- 3 *Complexity:* Exactly last - first increments and assignments.

**29.8.13 Greatest common divisor****[numeric.ops.gcd]**

```
template <class M, class N>
constexpr common_type_t<M,N> gcd(M m, N n);
```

- 1 *Requires:* |m| and |n| shall be representable as a value of common\_type\_t<M, N>. [Note: These requirements ensure, for example, that gcd(m, m) = |m| is representable as a value of type M. — end note]
- 2 *Remarks:* If either M or N is not an integer type, or if either is cv bool, the program is ill-formed.
- 3 *Returns:* Zero when m and n are both zero. Otherwise, returns the greatest common divisor of |m| and |n|.
- 4 *Throws:* Nothing.

**29.8.14 Least common multiple****[numeric.ops.lcm]**

```
template <class M, class N>
constexpr common_type_t<M,N> lcm(M m, N n);
```

- 1 *Requires:* |m| and |n| shall be representable as a value of common\_type\_t<M, N>. The least common multiple of |m| and |n| shall be representable as a value of type common\_type\_t<M,N>.
- 2 *Remarks:* If either M or N is not an integer type, or if either is cv bool the program is ill-formed.
- 3 *Returns:* Zero when either m or n is zero. Otherwise, returns the least common multiple of |m| and |n|.
- 4 *Throws:* Nothing.

**29.9 Mathematical functions for floating-point types****[c.math]****29.9.1 Header <cmath> synopsis****[cmath.syn]**

```
namespace std {
 using float_t = see below;
 using double_t = see below;
}

#define HUGE_VAL see below
#define HUGE_VALF see below
#define HUGE_VALL see below
#define INFINITY see below
#define NAN see below
#define FP_INFINITE see below
#define FP_NAN see below
#define FP_NORMAL see below
#define FP_SUBNORMAL see below
#define FP_ZERO see below
```

```

#define FP_FAST_FMA see below
#define FP_FAST_FMAF see below
#define FP_FAST_FMAL see below
#define FP_ILOGB0 see below
#define FP_ILOGBNAN see below
#define MATH_ERRNO see below
#define MATH_ERREXCEPT see below

#define math_errhandling see below

namespace std {
 float acos(float x); // see 20.2
 double acos(double x);
 long double acos(long double x); // see 20.2
 float acosf(float x);
 long double acosl(long double x);

 float asin(float x); // see 20.2
 double asin(double x);
 long double asin(long double x); // see 20.2
 float asinf(float x);
 long double asinl(long double x);

 float atan(float x); // see 20.2
 double atan(double x);
 long double atan(long double x); // see 20.2
 float atanf(float x);
 long double atanl(long double x);

 float atan2(float y, float x); // see 20.2
 double atan2(double y, double x);
 long double atan2(long double y, long double x); // see 20.2
 float atan2f(float y, float x);
 long double atan2l(long double y, long double x);

 float cos(float x); // see 20.2
 double cos(double x);
 long double cos(long double x); // see 20.2
 float cosf(float x);
 long double cosl(long double x);

 float sin(float x); // see 20.2
 double sin(double x);
 long double sin(long double x); // see 20.2
 float sinf(float x);
 long double sinl(long double x);

 float tan(float x); // see 20.2
 double tan(double x);
 long double tan(long double x); // see 20.2
 float tanf(float x);
 long double tanl(long double x);

 float acosh(float x); // see 20.2
 double acosh(double x);

```

```
long double acosh(long double x); // see 20.2
float acoshf(float x);
long double acoshl(long double x);

float asinh(float x); // see 20.2
double asinh(double x);
long double asinh(long double x); // see 20.2
float asinhf(float x);
long double asinhl(long double x);

float atanh(float x); // see 20.2
double atanh(double x);
long double atanh(long double x); // see 20.2
float atanhf(float x);
long double atanhhl(long double x);

float cosh(float x); // see 20.2
double cosh(double x);
long double cosh(long double x); // see 20.2
float coshf(float x);
long double coshl(long double x);

float sinh(float x); // see 20.2
double sinh(double x);
long double sinh(long double x); // see 20.2
float sinhlf(float x);
long double sinhl(long double x);

float tanh(float x); // see 20.2
double tanh(double x);
long double tanh(long double x); // see 20.2
float tanhf(float x);
long double tanhl(long double x);

float exp(float x); // see 20.2
double exp(double x);
long double exp(long double x); // see 20.2
float expf(float x);
long double expl(long double x);

float exp2(float x); // see 20.2
double exp2(double x);
long double exp2(long double x); // see 20.2
float exp2f(float x);
long double exp2l(long double x);

float expm1(float x); // see 20.2
double expm1(double x);
long double expm1(long double x); // see 20.2
float expm1f(float x);
long double expm1l(long double x);

float frexp(float value, int* exp); // see 20.2
double frexp(double value, int* exp);
long double frexp(long double value, int* exp); // see 20.2
```

```

float frexpf(float value, int* exp);
long double frexpl(long double value, int* exp);

int ilogb(float x); // see 20.2
int ilogb(double x);
int ilogb(long double x); // see 20.2
int ilogbf(float x);
int ilogbl(long double x);

float ldexp(float x, int exp); // see 20.2
double ldexp(double x, int exp);
long double ldexp(long double x, int exp); // see 20.2
float ldexpf(float x, int exp);
long double ldexpl(long double x, int exp);

float log(float x); // see 20.2
double log(double x);
long double log(long double x); // see 20.2
float logf(float x);
long double logl(long double x);

float log10(float x); // see 20.2
double log10(double x);
long double log10(long double x); // see 20.2
float log10f(float x);
long double log10l(long double x);

float log1p(float x); // see 20.2
double log1p(double x);
long double log1p(long double x); // see 20.2
float log1pf(float x);
long double log1pl(long double x);

float log2(float x); // see 20.2
double log2(double x);
long double log2(long double x); // see 20.2
float log2f(float x);
long double log2l(long double x);

float logb(float x); // see 20.2
double logb(double x);
long double logb(long double x); // see 20.2
float logbf(float x);
long double logbl(long double x);

float modf(float value, float* iptr); // see 20.2
double modf(double value, double* iptr);
long double modf(long double value, long double* iptr); // see 20.2
float modff(float value, float* iptr);
long double modfl(long double value, long double* iptr);

float scalbn(float x, int n); // see 20.2
double scalbn(double x, int n);
long double scalbn(long double x, int n); // see 20.2
float scalbnf(float x, int n);

```

```

long double scalbnl(long double x, int n);

float scalbln(float x, long int n); // see 20.2
double scalbln(double x, long int n);
long double scalbln(long double x, long int n); // see 20.2
float scalblnf(float x, long int n);
long double scalblnl(long double x, long int n);

float cbrt(float x); // see 20.2
double cbrt(double x);
long double cbrt(long double x); // see 20.2
float cbrtf(float x);
long double cbrtl(long double x);

// 29.9.2, absolute values
int abs(int j);
long int abs(long int j);
long long int abs(long long int j);
float abs(float j);
double abs(double j);
long double abs(long double j);

float fabs(float x); // see 20.2
double fabs(double x);
long double fabs(long double x); // see 20.2
float fabsf(float x);
long double fabsl(long double x);

float hypot(float x, float y); // see 20.2
double hypot(double x, double y);
long double hypot(double x, double y); // see 20.2
float hypotf(float x, float y);
long double hypotl(long double x, long double y);

// 29.9.3, three-dimensional hypotenuse
float hypot(float x, float y, float z);
double hypot(double x, double y, double z);
long double hypot(long double x, long double y, long double z);

float pow(float x, float y); // see 20.2
double pow(double x, double y);
long double pow(long double x, long double y); // see 20.2
float powf(float x, float y);
long double powl(long double x, long double y);

float sqrt(float x); // see 20.2
double sqrt(double x);
long double sqrt(long double x); // see 20.2
float sqrtf(float x);
long double sqrtl(long double x);

float erf(float x); // see 20.2
double erf(double x);
long double erf(long double x); // see 20.2
float erff(float x);

```

```
long double erfl(long double x);

float erfc(float x); // see 20.2
double erfc(double x);
long double erfc(long double x); // see 20.2
float erfcf(float x);
long double erfcl(long double x);

float lgamma(float x); // see 20.2
double lgamma(double x);
long double lgamma(long double x); // see 20.2
float lgammaf(float x);
long double lgammal(long double x);

float tgamma(float x); // see 20.2
double tgamma(double x);
long double tgamma(long double x); // see 20.2
float tgammaf(float x);
long double tgamma_l(long double x);

float ceil(float x); // see 20.2
double ceil(double x);
long double ceil(long double x); // see 20.2
float ceilf(float x);
long double ceill(long double x);

float floor(float x); // see 20.2
double floor(double x);
long double floor(long double x); // see 20.2
float floorf(float x);
long double floorl(long double x);

float nearbyint(float x); // see 20.2
double nearbyint(double x);
long double nearbyint(long double x); // see 20.2
float nearbyintf(float x);
long double nearbyintl(long double x);

float rint(float x); // see 20.2
double rint(double x);
long double rint(long double x); // see 20.2
float rintf(float x);
long double rintl(long double x);

long int lrint(float x); // see 20.2
long int lrint(double x);
long int lrint(long double x); // see 20.2
long int lrintf(float x);
long int lrintl(long double x);

long long int llrint(float x); // see 20.2
long long int llrint(double x);
long long int llrint(long double x); // see 20.2
long long int llrintf(float x);
long long int llrintl(long double x);
```

```

float round(float x); // see 20.2
double round(double x);
long double round(long double x); // see 20.2
float roundf(float x);
long double roundl(long double x);

long int lround(float x); // see 20.2
long int lround(double x);
long int lround(long double x); // see 20.2
long int lroundf(float x);
long int lroundl(long double x);

long long int llround(float x); // see 20.2
long long int llround(double x);
long long int llround(long double x); // see 20.2
long long int llroundf(float x);
long long int llroundl(long double x);

float trunc(float x); // see 20.2
double trunc(double x);
long double trunc(long double x); // see 20.2
float truncf(float x);
long double truncf(long double x);

float fmod(float x, float y); // see 20.2
double fmod(double x, double y);
long double fmod(long double x, long double y); // see 20.2
float fmodf(float x, float y);
long double fmodl(long double x, long double y);

float remainder(float x, float y); // see 20.2
double remainder(double x, double y);
long double remainder(long double x, long double y); // see 20.2
float remainderf(float x, float y);
long double remainderl(long double x, long double y);

float remquo(float x, float y, int* quo); // see 20.2
double remquo(double x, double y, int* quo);
long double remquo(long double x, long double y, int* quo); // see 20.2
float remquof(float x, float y, int* quo);
long double remquol(long double x, long double y, int* quo);

float copysign(float x, float y); // see 20.2
double copysign(double x, double y);
long double copysign(long double x, long double y); // see 20.2
float copysignf(float x, float y);
long double copysignl(long double x, long double y);

double nan(const char* tagp);
float nanf(const char* tagp);
long double nanl(const char* tagp);

float nextafter(float x, float y); // see 20.2
double nextafter(double x, double y);

```



```

long double nextafter(long double x, long double y); // see 20.2
float nextafterf(float x, float y);
long double nextafterl(long double x, long double y);

float nexttoward(float x, long double y); // see 20.2
double nexttoward(double x, long double y);
long double nexttoward(long double x, long double y); // see 20.2
float nexttowardf(float x, long double y);
long double nexttowardl(long double x, long double y);

float fdim(float x, float y); // see 20.2
double fdim(double x, double y);
long double fdim(long double x, long double y); // see 20.2
float fdimf(float x, float y);
long double fdiml(long double x, long double y);

float fmax(float x, float y); // see 20.2
double fmax(double x, double y);
long double fmax(long double x, long double y); // see 20.2
float fmaxf(float x, float y);
long double fmaxl(long double x, long double y);

float fmin(float x, float y); // see 20.2
double fmin(double x, double y);
long double fmin(long double x, long double y); // see 20.2
float fminf(float x, float y);
long double fminl(long double x, long double y);

float fma(float x, float y, float z); // see 20.2
double fma(double x, double y, double z);
long double fma(long double x, long double y, long double z); // see 20.2
float fmaf(float x, float y, float z);
long double fmal(long double x, long double y, long double z);

// 29.9.4, classification / comparison functions
int fpclassify(float x);
int fpclassify(double x);
int fpclassify(long double x);

int isfinite(float x);
int isfinite(double x);
int isfinite(long double x);

int isinf(float x);
int isinf(double x);
int isinf(long double x);

int isnan(float x);
int isnan(double x);
int isnan(long double x);

int isnormal(float x);
int isnormal(double x);
int isnormal(long double x);

```

```

int signbit(float x);
int signbit(double x);
int signbit(long double x);

int isgreater(float x, float y);
int isgreater(double x, double y);
int isgreater(long double x, long double y);

int isgreaterequal(float x, float y);
int isgreaterequal(double x, double y);
int isgreaterequal(long double x, long double y);

int isless(float x, float y);
int isless(double x, double y);
int isless(long double x, long double y);

int islessequal(float x, float y);
int islessequal(double x, double y);
int islessequal(long double x, long double y);

int islessgreater(float x, float y);
int islessgreater(double x, double y);
int islessgreater(long double x, long double y);

int isunordered(float x, float y);
int isunordered(double x, double y);
int isunordered(long double x, long double y);

// 29.9.5, mathematical special functions

// 29.9.5.1, associated Laguerre polynomials
double assoc_laguerre(unsigned n, unsigned m, double x);
float assoc_laguerref(unsigned n, unsigned m, float x);
long double assoc_laguerrel(unsigned n, unsigned m, long double x);

// 29.9.5.2, associated Legendre functions
double assoc_legendre(unsigned l, unsigned m, double x);
float assoc_legendref(unsigned l, unsigned m, float x);
long double assoc_legendrel(unsigned l, unsigned m, long double x);

// 29.9.5.3, beta function
double beta(double x, double y);
float betaf(float x, float y);
long double betal(long double x, long double y);

// 29.9.5.4, complete elliptic integral of the first kind
double comp_ellint_1(double k);
float comp_ellint_1f(float k);
long double comp_ellint_1l(long double k);

// 29.9.5.5, complete elliptic integral of the second kind
double comp_ellint_2(double k);
float comp_ellint_2f(float k);
long double comp_ellint_2l(long double k);

```

```

// 29.9.5.6, complete elliptic integral of the third kind
double comp_ellint_3(double k, double nu);
float comp_ellint_3f(float k, float nu);
long double comp_ellint_3l(long double k, long double nu);

// 29.9.5.7, regular modified cylindrical Bessel functions
double cyl_bessel_i(double nu, double x);
float cyl_bessel_if(float nu, float x);
long double cyl_bessel_il(long double nu, long double x);

// 29.9.5.8, cylindrical Bessel functions of the first kind
double cyl_bessel_j(double nu, double x);
float cyl_bessel_jf(float nu, float x);
long double cyl_bessel_jl(long double nu, long double x);

// 29.9.5.9, irregular modified cylindrical Bessel functions
double cyl_bessel_k(double nu, double x);
float cyl_bessel_kf(float nu, float x);
long double cyl_bessel_kl(long double nu, long double x);

// 29.9.5.10, cylindrical Neumann functions;
// cylindrical Bessel functions of the second kind
double cyl_neumann(double nu, double x);
float cyl_neumannf(float nu, float x);
long double cyl_neumannl(long double nu, long double x);

// 29.9.5.11, incomplete elliptic integral of the first kind
double ellint_1(double k, double phi);
float ellint_1f(float k, float phi);
long double ellint_1l(long double k, long double phi);

// 29.9.5.12, incomplete elliptic integral of the second kind
double ellint_2(double k, double phi);
float ellint_2f(float k, float phi);
long double ellint_2l(long double k, long double phi);

// 29.9.5.13, incomplete elliptic integral of the third kind
double ellint_3(double k, double nu, double phi);
float ellint_3f(float k, float nu, float phi);
long double ellint_3l(long double k, long double nu, long double phi);

// 29.9.5.14, exponential integral
double expint(double x);
float expintf(float x);
long double expintl(long double x);

// 29.9.5.15, Hermite polynomials
double hermite(unsigned n, double x);
float hermitef(unsigned n, float x);
long double hermitel(unsigned n, long double x);

// 29.9.5.16, Laguerre polynomials
double laguerre(unsigned n, double x);
float laguerref(unsigned n, float x);
long double laguerrel(unsigned n, long double x);

```

```

// 29.9.5.17, Legendre polynomials
double legendre(unsigned l, double x);
float legendref(unsigned l, float x);
long double legendrel(unsigned l, long double x);

// 29.9.5.18, Riemann zeta function
double riemann_zeta(double x);
float riemann_zetaf(float x);
long double riemann_zetal(long double x);

// 29.9.5.19, spherical Bessel functions of the first kind
double sph_bessel(unsigned n, double x);
float sph_besself(unsigned n, float x);
long double sph_bessell(unsigned n, long double x);

// 29.9.5.20, spherical associated Legendre functions
double sph_legendre(unsigned l, unsigned m, double theta);
float sph_legendref(unsigned l, unsigned m, float theta);
long double sph_legendrel(unsigned l, unsigned m, long double theta);

// 29.9.5.21, spherical Neumann functions;
// spherical Bessel functions of the second kind:
double sph_neumann(unsigned n, double x);
float sph_neumannf(unsigned n, float x);
long double sph_neumannl(unsigned n, long double x);
}

```

<sup>1</sup> The contents and meaning of the header `<cmath>` are the same as the C standard library header `<math.h>`, with the addition of a three-dimensional hypotenuse function (29.9.3) and the mathematical special functions described in 29.9.5. [Note: Several functions have additional overloads in this International Standard, but they have the same behavior as in the C standard library (20.2). — end note]

<sup>2</sup> For each set of overloaded functions within `<cmath>`, with the exception of `abs`, there shall be additional overloads sufficient to ensure:

1. If any argument of arithmetic type corresponding to a `double` parameter has type `long double`, then all arguments of arithmetic type (6.9.1) corresponding to `double` parameters are effectively cast to `long double`.
2. Otherwise, if any argument of arithmetic type corresponding to a `double` parameter has type `double` or an integer type, then all arguments of arithmetic type corresponding to `double` parameters are effectively cast to `double`.
3. Otherwise, all arguments of arithmetic type corresponding to `double` parameters have type `float`.

[Note: `abs` is exempted from these rules in order to stay compatible with C. — end note]

SEE ALSO: ISO C 7.12

## 29.9.2 Absolute values

[c.math.abs]

<sup>1</sup> [Note: The headers `<cstdlib>` (21.2.2) and `<cmath>` (29.9.1) declare the functions described in this subclause. — end note]

```

int abs(int j);
long int abs(long int j);
long long int abs(long long int j);
float abs(float j);

```

```
double abs(double j);
long double abs(long double j);
```

2 *Effects:* The `abs` functions have the semantics specified in the C standard library for the functions `abs`, `labs`, `llabs`, `fabsf`, `fabs`, and `fabsl`.

3 *Remarks:* If `abs()` is called with an argument of type `X` for which `is_unsigned_v<X>` is `true` and if `X` cannot be converted to `int` by integral promotion (7.6), the program is ill-formed. [ *Note:* Arguments that can be promoted to `int` are permitted for compatibility with C. — *end note* ]

SEE ALSO: ISO C 7.12.7.2, 7.22.6.1

### 29.9.3 Three-dimensional hypotenuse

[**c.math.hypot3**]

```
float hypot(float x, float y, float z);
double hypot(double x, double y, double z);
long double hypot(long double x, long double y, long double z);
```

1 *Returns:*  $\sqrt{x^2 + y^2 + z^2}$ .

### 29.9.4 Classification / comparison functions

[**c.math.fpclass**]

1 The classification / comparison functions behave the same as the C macros with the corresponding names defined in the C standard library. Each function is overloaded for the three floating-point types.

SEE ALSO: ISO C 7.12.3, 7.12.4

### 29.9.5 Mathematical special functions

[**sf.cmath**]

1 If any argument value to any of the functions specified in this subclause is a NaN (Not a Number), the function shall return a NaN but it shall not report a domain error. Otherwise, the function shall report a domain error for just those argument values for which:

- (1.1) — the function description's *Returns:* clause explicitly specifies a domain and those argument values fall outside the specified domain, or
- (1.2) — the corresponding mathematical function value has a nonzero imaginary component, or
- (1.3) — the corresponding mathematical function is not mathematically defined.<sup>286</sup>

2 Unless otherwise specified, each function is defined for all finite values, for negative infinity, and for positive infinity.

#### 29.9.5.1 Associated Laguerre polynomials

[**sf.cmath.assoc\_laguerre**]

```
double assoc_laguerre(unsigned n, unsigned m, double x);
float assoc_laguerref(unsigned n, unsigned m, float x);
long double assoc_laguerrel(unsigned n, unsigned m, long double x);
```

1 *Effects:* These functions compute the associated Laguerre polynomials of their respective arguments `n`, `m`, and `x`.

2 *Returns:*

$$L_n^m(x) = (-1)^m \frac{d^m}{dx^m} L_{n+m}(x), \quad \text{for } x \geq 0$$

where `n` is `n`, `m` is `m`, and `x` is `x`.

3 *Remarks:* The effect of calling each of these functions is implementation-defined if `n`  $\geq$  128 or if `m`  $\geq$  128.

<sup>286</sup>) A mathematical function is mathematically defined for a given set of argument values (a) if it is explicitly defined for that set of argument values, or (b) if its limiting value exists and does not depend on the direction of approach.

**29.9.5.2 Associated Legendre functions****[sf.cmath.assoc\_legendre]**

```
double assoc_legendre(unsigned l, unsigned m, double x);
float assoc_legendref(unsigned l, unsigned m, float x);
long double assoc_legendrel(unsigned l, unsigned m, long double x);
```

<sup>1</sup> *Effects:* These functions compute the associated Legendre functions of their respective arguments *l*, *m*, and *x*.

<sup>2</sup> *Returns:*

$$P_\ell^m(x) = (1 - x^2)^{m/2} \frac{d^m}{dx^m} P_\ell(x), \quad \text{for } |x| \leq 1$$

where *l* is *l*, *m* is *m*, and *x* is *x*.

<sup>3</sup> *Remarks:* The effect of calling each of these functions is implementation-defined if *l* >= 128.

**29.9.5.3 Beta function****[sf.cmath.beta]**

```
double beta(double x, double y);
float betaf(float x, float y);
long double betal(long double x, long double y);
```

<sup>1</sup> *Effects:* These functions compute the beta function of their respective arguments *x* and *y*.

<sup>2</sup> *Returns:*

$$B(x, y) = \frac{\Gamma(x) \Gamma(y)}{\Gamma(x + y)}, \quad \text{for } x > 0, y > 0$$

where *x* is *x* and *y* is *y*.

**29.9.5.4 Complete elliptic integral of the first kind****[sf.cmath.comp\_ellint\_1]**

```
double comp_ellint_1(double k);
float comp_ellint_1f(float k);
long double comp_ellint_1l(long double k);
```

<sup>1</sup> *Effects:* These functions compute the complete elliptic integral of the first kind of their respective arguments *k*.

<sup>2</sup> *Returns:*

$$K(k) = F(k, \pi/2), \quad \text{for } |k| \leq 1$$

where *k* is *k*.

<sup>3</sup> See also [29.9.5.11](#).

**29.9.5.5 Complete elliptic integral of the second kind****[sf.cmath.comp\_ellint\_2]**

```
double comp_ellint_2(double k);
float comp_ellint_2f(float k);
long double comp_ellint_2l(long double k);
```

<sup>1</sup> *Effects:* These functions compute the complete elliptic integral of the second kind of their respective arguments *k*.

<sup>2</sup> *Returns:*

$$E(k) = E(k, \pi/2), \quad \text{for } |k| \leq 1$$

where *k* is *k*.

<sup>3</sup> See also [29.9.5.12](#).

**29.9.5.6 Complete elliptic integral of the third kind**

[sf.cmath.comp\_ellint\_3]

```
double comp_ellint_3(double k, double nu);
float comp_ellint_3f(float k, float nu);
long double comp_ellint_3l(long double k, long double nu);
```

1 *Effects:* These functions compute the complete elliptic integral of the third kind of their respective arguments *k* and *nu*.

2 *Returns:*

$$\Pi(\nu, k) = \Pi(\nu, k, \pi/2), \quad \text{for } |k| \leq 1$$

where *k* is *k* and *ν* is *nu*.

3 See also [29.9.5.13](#).

**29.9.5.7 Regular modified cylindrical Bessel functions**

[sf.cmath.cyl\_bessel\_i]

```
double cyl_bessel_i(double nu, double x);
float cyl_bessel_if(float nu, float x);
long double cyl_bessel_il(long double nu, long double x);
```

1 *Effects:* These functions compute the regular modified cylindrical Bessel functions of their respective arguments *nu* and *x*.

2 *Returns:*

$$I_\nu(x) = i^{-\nu} J_\nu(ix) = \sum_{k=0}^{\infty} \frac{(x/2)^{\nu+2k}}{k! \Gamma(\nu + k + 1)}, \quad \text{for } x \geq 0$$

where *ν* is *nu* and *x* is *x*.

3 *Remarks:* The effect of calling each of these functions is implementation-defined if *nu* >= 128.

4 See also [29.9.5.8](#).

**29.9.5.8 Cylindrical Bessel functions of the first kind**

[sf.cmath.cyl\_bessel\_j]

```
double cyl_bessel_j(double nu, double x);
float cyl_bessel_jf(float nu, float x);
long double cyl_bessel_jl(long double nu, long double x);
```

1 *Effects:* These functions compute the cylindrical Bessel functions of the first kind of their respective arguments *nu* and *x*.

2 *Returns:*

$$J_\nu(x) = \sum_{k=0}^{\infty} \frac{(-1)^k (x/2)^{\nu+2k}}{k! \Gamma(\nu + k + 1)}, \quad \text{for } x \geq 0$$

where *ν* is *nu* and *x* is *x*.

3 *Remarks:* The effect of calling each of these functions is implementation-defined if *nu* >= 128.

**29.9.5.9 Irregular modified cylindrical Bessel functions**

[sf.cmath.cyl\_bessel\_k]

```
double cyl_bessel_k(double nu, double x);
float cyl_bessel_kf(float nu, float x);
long double cyl_bessel_kl(long double nu, long double x);
```

1 *Effects:* These functions compute the irregular modified cylindrical Bessel functions of their respective arguments *nu* and *x*.

*Returns:*

$$K_\nu(x) = (\pi/2)i^{\nu+1}(J_\nu(ix) + iN_\nu(ix)) = \begin{cases} \frac{\pi}{2} \frac{I_{-\nu}(x) - I_\nu(x)}{\sin \nu\pi}, & \text{for } x \geq 0 \text{ and non-integral } \nu \\ \frac{\pi}{2} \lim_{\mu \rightarrow \nu} \frac{I_{-\mu}(x) - I_\mu(x)}{\sin \mu\pi}, & \text{for } x \geq 0 \text{ and integral } \nu \end{cases}$$

where  $\nu$  is `nu` and  $x$  is `x`.

*Remarks:* The effect of calling each of these functions is implementation-defined if `nu`  $\geq$  128.

See also [29.9.5.7](#), [29.9.5.8](#), [29.9.5.10](#).

#### 29.9.5.10 Cylindrical Neumann functions

[`sf.cmath.cyl_neumann`]

```
double cyl_neumann(double nu, double x);
float cyl_neumannf(float nu, float x);
long double cyl_neumannl(long double nu, long double x);
```

*Effects:* These functions compute the cylindrical Neumann functions, also known as the cylindrical Bessel functions of the second kind, of their respective arguments `nu` and `x`.

*Returns:*

$$N_\nu(x) = \begin{cases} \frac{J_\nu(x) \cos \nu\pi - J_{-\nu}(x)}{\sin \nu\pi}, & \text{for } x \geq 0 \text{ and non-integral } \nu \\ \lim_{\mu \rightarrow \nu} \frac{J_\mu(x) \cos \mu\pi - J_{-\mu}(x)}{\sin \mu\pi}, & \text{for } x \geq 0 \text{ and integral } \nu \end{cases}$$

where  $\nu$  is `nu` and  $x$  is `x`.

*Remarks:* The effect of calling each of these functions is implementation-defined if `nu`  $\geq$  128.

See also [29.9.5.8](#).

#### 29.9.5.11 Incomplete elliptic integral of the first kind

[`sf.cmath.ellint_1`]

```
double ellint_1(double k, double phi);
float ellint_1f(float k, float phi);
long double ellint_1l(long double k, long double phi);
```

*Effects:* These functions compute the incomplete elliptic integral of the first kind of their respective arguments `k` and `phi` (`phi` measured in radians).

*Returns:*

$$F(k, \phi) = \int_0^\phi \frac{d\theta}{\sqrt{1 - k^2 \sin^2 \theta}}, \quad \text{for } |k| \leq 1$$

where  $k$  is `k` and  $\phi$  is `phi`.

#### 29.9.5.12 Incomplete elliptic integral of the second kind

[`sf.cmath.ellint_2`]

```
double ellint_2(double k, double phi);
float ellint_2f(float k, float phi);
long double ellint_2l(long double k, long double phi);
```

*Effects:* These functions compute the incomplete elliptic integral of the second kind of their respective arguments `k` and `phi` (`phi` measured in radians).

*Returns:*

$$E(k, \phi) = \int_0^\phi \sqrt{1 - k^2 \sin^2 \theta} d\theta, \quad \text{for } |k| \leq 1$$



where  $k$  is `k` and  $\phi$  is `phi`.

### 29.9.5.13 Incomplete elliptic integral of the third kind

[sf.cmath.ellint\_3]

```
double ellint_3(double k, double nu, double phi);
float ellint_3f(float k, float nu, float phi);
long double ellint_3l(long double k, long double nu, long double phi);
```

<sup>1</sup> *Effects:* These functions compute the incomplete elliptic integral of the third kind of their respective arguments `k`, `nu`, and `phi` (`phi` measured in radians).

<sup>2</sup> *Returns:*

$$\Pi(\nu, k, \phi) = \int_0^\phi \frac{d\theta}{(1 - \nu \sin^2 \theta) \sqrt{1 - k^2 \sin^2 \theta}}, \quad \text{for } |k| \leq 1$$

where  $\nu$  is `nu`,  $k$  is `k`, and  $\phi$  is `phi`.

### 29.9.5.14 Exponential integral

[sf.cmath.expint]

```
double expint(double x);
float expintf(float x);
long double expintl(long double x);
```

<sup>1</sup> *Effects:* These functions compute the exponential integral of their respective arguments `x`.

<sup>2</sup> *Returns:*

$$\text{Ei}(x) = - \int_{-x}^{\infty} \frac{e^{-t}}{t} dt$$

where  $x$  is `x`.

### 29.9.5.15 Hermite polynomials

[sf.cmath.hermite]

```
double hermite(unsigned n, double x);
float hermitef(unsigned n, float x);
long double hermitel(unsigned n, long double x);
```

<sup>1</sup> *Effects:* These functions compute the Hermite polynomials of their respective arguments `n` and `x`.

<sup>2</sup> *Returns:*

$$H_n(x) = (-1)^n e^{x^2} \frac{d^n}{dx^n} e^{-x^2}$$

where  $n$  is `n` and  $x$  is `x`.

<sup>3</sup> *Remarks:* The effect of calling each of these functions is implementation-defined if `n`  $\geq$  128.

### 29.9.5.16 Laguerre polynomials

[sf.cmath.laguerre]

```
double laguerre(unsigned n, double x);
float laguerref(unsigned n, float x);
long double laguerrel(unsigned n, long double x);
```

<sup>1</sup> *Effects:* These functions compute the Laguerre polynomials of their respective arguments `n` and `x`.

<sup>2</sup> *Returns:*

$$L_n(x) = \frac{e^x}{n!} \frac{d^n}{dx^n} (x^n e^{-x}), \quad \text{for } x \geq 0$$

where  $n$  is `n` and  $x$  is `x`.

<sup>3</sup> *Remarks:* The effect of calling each of these functions is implementation-defined if `n`  $\geq$  128.

**29.9.5.17 Legendre polynomials****[sf.cmath.legendre]**

```
double legendre(unsigned l, double x);
float legendref(unsigned l, float x);
long double legendrel(unsigned l, long double x);
```

*Effects:* These functions compute the Legendre polynomials of their respective arguments `l` and `x`.

*Returns:*

$$P_\ell(x) = \frac{1}{2^\ell \ell!} \frac{d^\ell}{dx^\ell} (x^2 - 1)^\ell, \quad \text{for } |x| \leq 1$$

where  $l$  is `l` and  $x$  is `x`.

*Remarks:* The effect of calling each of these functions is implementation-defined if `l`  $\geq$  128.

**29.9.5.18 Riemann zeta function****[sf.cmath.riemann\_zeta]**

```
double riemann_zeta(double x);
float riemann_zetaf(float x);
long double riemann_zetal(long double x);
```

*Effects:* These functions compute the Riemann zeta function of their respective arguments `x`.

*Returns:*

$$\zeta(x) = \begin{cases} \sum_{k=1}^{\infty} k^{-x}, & \text{for } x > 1 \\ \frac{1}{1-2^{1-x}} \sum_{k=1}^{\infty} (-1)^{k-1} k^{-x}, & \text{for } 0 \leq x \leq 1 \\ 2^x \pi^{x-1} \sin\left(\frac{\pi x}{2}\right) \Gamma(1-x) \zeta(1-x), & \text{for } x < 0 \end{cases}$$

where  $x$  is `x`.

**29.9.5.19 Spherical Bessel functions of the first kind****[sf.cmath.sph\_bessel]**

```
double sph_bessel(unsigned n, double x);
float sph_besself(unsigned n, float x);
long double sph_bessell(unsigned n, long double x);
```

*Effects:* These functions compute the spherical Bessel functions of the first kind of their respective arguments `n` and `x`.

*Returns:*

$$j_n(x) = (\pi/2x)^{1/2} J_{n+1/2}(x), \quad \text{for } x \geq 0$$

where  $n$  is `n` and  $x$  is `x`.

*Remarks:* The effect of calling each of these functions is implementation-defined if `n`  $\geq$  128.

See also [29.9.5.8](#).

**29.9.5.20 Spherical associated Legendre functions****[sf.cmath.sph\_legendre]**

```
double sph_legendre(unsigned l, unsigned m, double theta);
float sph_legendref(unsigned l, unsigned m, float theta);
long double sph_legendrel(unsigned l, unsigned m, long double theta);
```

*Effects:* These functions compute the spherical associated Legendre functions of their respective arguments `l`, `m`, and `theta` (`theta` measured in radians).

2 *Returns:*

$$Y_{\ell}^m(\theta, 0)$$

where

$$Y_{\ell}^m(\theta, \phi) = (-1)^m \left[ \frac{(2\ell+1)}{4\pi} \frac{(\ell-m)!}{(\ell+m)!} \right]^{1/2} P_{\ell}^m(\cos \theta) e^{im\phi}, \quad \text{for } |m| \leq \ell$$

and  $\ell$  is `l`,  $m$  is `m`, and  $\theta$  is `theta`.

3 *Remarks:* The effect of calling each of these functions is implementation-defined if `l >= 128`.

4 See also [29.9.5.2](#).

### 29.9.5.21 Spherical Neumann functions

[sf.cmath.sph\_neumann]

```
double sph_neumann(unsigned n, double x);
float sph_neumannf(unsigned n, float x);
long double sph_neumannl(unsigned n, long double x);
```

1 *Effects:* These functions compute the spherical Neumann functions, also known as the spherical Bessel functions of the second kind, of their respective arguments `n` and `x`.

2 *Returns:*

$$y_n(x) = (\pi/2x)^{1/2} N_{n+1/2}(x), \quad \text{for } x \geq 0$$

where  $n$  is `n` and  $x$  is `x`.

3 *Remarks:* The effect of calling each of these functions is implementation-defined if `n >= 128`.

4 See also [29.9.5.10](#).

## 30 Input/output library [input.output]

### 30.1 General [input.output.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to perform input/output operations.
- <sup>2</sup> The following subclauses describe requirements for stream parameters, and components for forward declarations of iostreams, predefined iostreams objects, base iostreams classes, stream buffering, stream formatting and manipulators, string streams, and file streams, as summarized in Table 106.

Table 106 — Input/output library summary

| Subclause                                        | Header(s)                                                                                    |
|--------------------------------------------------|----------------------------------------------------------------------------------------------|
| <a href="#">30.2</a> Requirements                |                                                                                              |
| <a href="#">30.3</a> Forward declarations        | <code>&lt;iosfwd&gt;</code>                                                                  |
| <a href="#">30.4</a> Standard iostream objects   | <code>&lt;iostream&gt;</code>                                                                |
| <a href="#">30.5</a> Iostreams base classes      | <code>&lt;ios&gt;</code>                                                                     |
| <a href="#">30.6</a> Stream buffers              | <code>&lt;streambuf&gt;</code>                                                               |
| <a href="#">30.7</a> Formatting and manipulators | <code>&lt;istream&gt;</code><br><code>&lt;ostream&gt;</code><br><code>&lt;iomanip&gt;</code> |
| <a href="#">30.8</a> String streams              | <code>&lt;sstream&gt;</code>                                                                 |
| <a href="#">30.9</a> File streams                | <code>&lt;fstream&gt;</code>                                                                 |
| <a href="#">30.10</a> File systems               | <code>&lt;filesystem&gt;</code>                                                              |
| <a href="#">30.11</a> C library files            | <code>&lt;cstdio&gt;</code><br><code>&lt;ctype&gt;</code>                                    |

- <sup>3</sup> Figure 7 illustrates relationships among various types described in this clause. A line from **A** to **B** indicates that **A** is an alias (e.g. a typedef) for **B** or that **A** is defined in terms of **B**.




Figure 7 — Stream position, offset, and size types [non-normative]

## 30.2 Iostreams requirements

[iostreams.requirements]

### 30.2.1 Imbue limitations

[iostream.limits.imbue]

- 1 No function described in Clause 30 except for `ios_base::imbue` and `basic_filebuf::pubimbue` causes any instance of `basic_ios::imbue` or `basic_streambuf::imbue` to be called. If any user function called from a function declared in Clause 30 or as an overriding virtual function of any class declared in Clause 30 calls `imbue`, the behavior is undefined.

### 30.2.2 Positioning type limitations

[iostreams.limits.pos]

- 1 The classes of Clause 30 with template arguments `charT` and `traits` behave as described if `traits::pos_type` and `traits::off_type` are `streampos` and `streamoff` respectively. Except as noted explicitly below, their behavior when `traits::pos_type` and `traits::off_type` are other types is implementation-defined.
- 2 In the classes of Clause 30, a template parameter with name `charT` represents a member of the set of types containing `char`, `wchar_t`, and any other implementation-defined character types that satisfy the requirements for a character on which any of the istream components can be instantiated.

### 30.2.3 Thread safety

[iostreams.threadafety]

- 1 Concurrent access to a stream object (30.8, 30.9), stream buffer object (30.6), or C Library stream (30.11) by multiple threads may result in a data race (4.7) unless otherwise specified (30.4). [ *Note*: Data races result in undefined behavior (4.7). — *end note* ]
- 2 If one thread makes a library call *a* that writes a value to a stream and, as a result, another thread reads this value from the stream through a library call *b* such that this does not result in a data race, then *a*'s write synchronizes with *b*'s read.

## 30.3 Forward declarations

[iostream.forward]

### 30.3.1 Header <iosfwd> synopsis

[iosfwd.syn]

```

namespace std {
 template<class charT> class char_traits;
 template<> class char_traits<char>;
 template<> class char_traits<char16_t>;
 template<> class char_traits<char32_t>;
 template<> class char_traits<wchar_t>;

 template<class T> class allocator;

 template <class charT, class traits = char_traits<charT>>
 class basic_ios;
 template <class charT, class traits = char_traits<charT>>
 class basic_streambuf;
 template <class charT, class traits = char_traits<charT>>
 class basic_istream;
 template <class charT, class traits = char_traits<charT>>
 class basic_ostream;
 template <class charT, class traits = char_traits<charT>>
 class basic_iostream;

 template <class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_stringbuf;
 template <class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_istreamstream;

```

```

template <class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_ostringstream;
template <class charT, class traits = char_traits<charT>,
 class Allocator = allocator<charT>>
 class basic_stringstream;

template <class charT, class traits = char_traits<charT>>
 class basic_filebuf;
template <class charT, class traits = char_traits<charT>>
 class basic_ifstream;
template <class charT, class traits = char_traits<charT>>
 class basic_ofstream;
template <class charT, class traits = char_traits<charT>>
 class basic_fstream;

template <class charT, class traits = char_traits<charT>>
 class istreambuf_iterator;
template <class charT, class traits = char_traits<charT>>
 class ostreambuf_iterator;

using ios = basic_ios<char>;
using wios = basic_ios<wchar_t>;

using streambuf = basic_streambuf<char>;
using istream = basic_istream<char>;
using ostream = basic_ostream<char>;
using iostream = basic_iostream<char>;

using stringbuf = basic_stringbuf<char>;
using istringstream = basic_istream<char>;
using ostreamstream = basic_ostream<char>;
using stringstream = basic_stringstream<char>;

using filebuf = basic_filebuf<char>;
using ifstream = basic_ifstream<char>;
using ofstream = basic_ofstream<char>;
using fstream = basic_fstream<char>;

using wstreambuf = basic_streambuf<wchar_t>;
using wistream = basic_istream<wchar_t>;
using wostream = basic_ostream<wchar_t>;
using wiostream = basic_iostream<wchar_t>;

using wstringbuf = basic_stringbuf<wchar_t>;
using wistringstream = basic_istream<wchar_t>;
using wostringstream = basic_ostream<wchar_t>;
using wstringstream = basic_stringstream<wchar_t>;

using wfilebuf = basic_filebuf<wchar_t>;
using wifstream = basic_ifstream<wchar_t>;
using wofstream = basic_ofstream<wchar_t>;
using wfstream = basic_fstream<wchar_t>;

template <class state> class fpos;

```

```

 using streampos = fpos<char_traits<char>::state_type>;
 using wstreampos = fpos<char_traits<wchar_t>::state_type>;
}

```

- <sup>1</sup> Default template arguments are described as appearing both in `<iosfwd>` and in the synopsis of other headers but it is well-formed to include both `<iosfwd>` and one or more of the other headers.<sup>287</sup>

### 30.3.2 Overview

[[iostream.forward.overview](#)]

- <sup>1</sup> The class template specialization `basic_ios<charT, traits>` serves as a virtual base class for the class templates `basic_istream`, `basic_ostream`, and class templates derived from them. `basic_iostream` is a class template derived from both `basic_istream<charT, traits>` and `basic_ostream<charT, traits>`.
- <sup>2</sup> The class template specialization `basic_streambuf<charT, traits>` serves as a base class for class templates `basic_stringbuf` and `basic_filebuf`.
- <sup>3</sup> The class template specialization `basic_istream<charT, traits>` serves as a base class for class templates `basic_istreamstream` and `basic_ifstream`.
- <sup>4</sup> The class template specialization `basic_ostream<charT, traits>` serves as a base class for class templates `basic_ostreamstream` and `basic_ofstream`.
- <sup>5</sup> The class template specialization `basic_iostream<charT, traits>` serves as a base class for class templates `basic_stringstream` and `basic_fstream`.
- <sup>6</sup> Other *typedef-names* define instances of class templates specialized for `char` or `wchar_t` types.
- <sup>7</sup> Specializations of the class template `fpos` are used for specifying file position information.
- <sup>8</sup> The types `streampos` and `wstreampos` are used for positioning streams specialized on `char` and `wchar_t` respectively.
- <sup>9</sup> [*Note:* This synopsis suggests a circularity between `streampos` and `char_traits<char>`. An implementation can avoid this circularity by substituting equivalent types. One way to do this might be

```

template<class stateT> class fpos { ... }; // depends on nothing
using _STATE = ... ; // implementation private declaration of stateT

using streampos = fpos<_STATE>;

template<> struct char_traits<char> {
 using pos_type = streampos;
}

```

— end note]

## 30.4 Standard iostream objects

[[iostream.objects](#)]

### 30.4.1 Header `<iostream>` synopsis

[[iostream.syn](#)]

```

#include <ios> // see 30.5.1
#include <streambuf> // see 30.6.1
#include <istream> // see 30.7.1
#include <ostream> // see 30.7.2

namespace std {
 extern istream cin;
 extern ostream cout;
 extern ostream cerr;
 extern ostream clog;
}

```

<sup>287</sup>) It is the implementation's responsibility to implement headers so that including `<iosfwd>` and other headers does not violate the rules about multiple occurrences of default arguments.

```

extern wistream wcin;
extern wostream wcout;
extern wostream wcerr;
extern wostream wclog;
}

```

### 30.4.2 Overview

[[iostream.objects.overview](#)]

- <sup>1</sup> In this Clause, the type name `FILE` refers to the type `FILE` declared in `<stdio>` ([30.11.1](#)).
- <sup>2</sup> The header `<iostream>` declares objects that associate objects with the standard C streams provided for by the functions declared in `<stdio>` ([30.11](#)), and includes all the headers necessary to use these objects.
- <sup>3</sup> The objects are constructed and the associations are established at some time prior to or during the first time an object of class `ios_base::Init` is constructed, and in any case before the body of `main` ([6.6.1](#)) begins execution.<sup>288</sup> The objects are not destroyed during program execution.<sup>289</sup> The results of including `<iostream>` in a translation unit shall be as if `<iostream>` defined an instance of `ios_base::Init` with static storage duration.
- <sup>4</sup> Mixing operations on corresponding wide- and narrow-character streams follows the same semantics as mixing such operations on `FILE`s, as specified in the C standard library.
- <sup>5</sup> Concurrent access to a synchronized ([30.5.3.4](#)) standard `iostream` object's formatted and unformatted input ([30.7.4.1](#)) and output ([30.7.5.1](#)) functions or a standard C stream by multiple threads shall not result in a data race ([4.7](#)). [*Note: Users must still synchronize concurrent use of these objects and streams by multiple threads if they wish to avoid interleaved characters. — end note*]

SEE ALSO: ISO C 7.21.2.

### 30.4.3 Narrow stream objects

[[narrow.stream.objects](#)]

```
istream cin;
```

- <sup>1</sup> The object `cin` controls input from a stream buffer associated with the object `stdin`, declared in `<stdio>` ([30.11.1](#)).
- <sup>2</sup> After the object `cin` is initialized, `cin.tie()` returns `&cout`. Its state is otherwise the same as required for `basic_ios<char>::init` ([30.5.5.2](#)).

```
ostream cout;
```

- <sup>3</sup> The object `cout` controls output to a stream buffer associated with the object `stdout`, declared in `<stdio>` ([30.11.1](#)).

```
ostream cerr;
```

- <sup>4</sup> The object `cerr` controls output to a stream buffer associated with the object `stderr`, declared in `<stdio>` ([30.11.1](#)).
- <sup>5</sup> After the object `cerr` is initialized, `cerr.flags() & unitbuf` is nonzero and `cerr.tie()` returns `&cout`. Its state is otherwise the same as required for `basic_ios<char>::init` ([30.5.5.2](#)).

```
ostream clog;
```

- <sup>6</sup> The object `clog` controls output to a stream buffer associated with the object `stderr`, declared in `<stdio>` ([30.11.1](#)).

<sup>288</sup>) If it is possible for them to do so, implementations are encouraged to initialize the objects earlier than required.

<sup>289</sup>) Constructors and destructors for static objects can access these objects to read input from `stdin` or write output to `stdout` or `stderr`.



### 30.4.4 Wide stream objects

[wide.stream.objects]

```
wistream wcin;
```

- 1 The object `wcin` controls input from a stream buffer associated with the object `stdin`, declared in `<cstdio>` (30.11.1).

- 2 After the object `wcin` is initialized, `wcin.tie()` returns `&wcout`. Its state is otherwise the same as required for `basic_ios<wchar_t>::init` (30.5.5.2).

```
wostream wcout;
```

- 3 The object `wcout` controls output to a stream buffer associated with the object `stdout`, declared in `<cstdio>` (30.11.1).

```
wostream wcerr;
```

- 4 The object `wcerr` controls output to a stream buffer associated with the object `stderr`, declared in `<cstdio>` (30.11.1).

- 5 After the object `wcerr` is initialized, `wcerr.flags() & unitbuf` is nonzero and `wcerr.tie()` returns `&wcout`. Its state is otherwise the same as required for `basic_ios<wchar_t>::init` (30.5.5.2).

```
wostream wlog;
```

- 6 The object `wlog` controls output to a stream buffer associated with the object `stderr`, declared in `<cstdio>` (30.11.1).

## 30.5 Iostreams base classes

[iostreams.base]

### 30.5.1 Header `<ios>` synopsis

[ios.syn]

```
#include <iosfwd> // see 30.3.1
```

```
namespace std {
 using streamoff = implementation-defined;
 using streamsize = implementation-defined;
 template <class stateT> class fpos;

 class ios_base;
 template <class charT, class traits = char_traits<charT>>
 class basic_ios;

 // 30.5.6, manipulators
 ios_base& boolalpha (ios_base& str);
 ios_base& noboolalpha (ios_base& str);

 ios_base& showbase (ios_base& str);
 ios_base& noshowbase (ios_base& str);

 ios_base& showpoint (ios_base& str);
 ios_base& noshowpoint (ios_base& str);

 ios_base& showpos (ios_base& str);
 ios_base& noshowpos (ios_base& str);

 ios_base& skipws (ios_base& str);
 ios_base& noskipws (ios_base& str);

 ios_base& uppercase (ios_base& str);
```

```

ios_base& nouppercase(ios_base& str);

ios_base& unitbuf (ios_base& str);
ios_base& nounitbuf (ios_base& str);

// 30.5.6.2, adjustfield
ios_base& internal (ios_base& str);
ios_base& left (ios_base& str);
ios_base& right (ios_base& str);

// 30.5.6.3, basefield
ios_base& dec (ios_base& str);
ios_base& hex (ios_base& str);
ios_base& oct (ios_base& str);

// 30.5.6.4, floatfield
ios_base& fixed (ios_base& str);
ios_base& scientific (ios_base& str);
ios_base& hexfloat (ios_base& str);
ios_base& defaultfloat (ios_base& str);

// 30.5.6.5, error reporting
enum class io_errc {
 stream = 1
};

template <> struct is_error_code_enum<io_errc> : public true_type { };
error_code make_error_code(io_errc e) noexcept;
error_condition make_error_condition(io_errc e) noexcept;
const error_category& iostream_category() noexcept;
}

```

### 30.5.2 Types

[stream.types]

using streamoff = *implementation-defined*;

- <sup>1</sup> The type `streamoff` is a synonym for one of the signed basic integral types of sufficient size to represent the maximum possible file size for the operating system.<sup>290</sup>

using streamsize = *implementation-defined*;

- <sup>2</sup> The type `streamsize` is a synonym for one of the signed basic integral types. It is used to represent the number of characters transferred in an I/O operation, or the size of I/O buffers.<sup>291</sup>

### 30.5.3 Class `ios_base`

[ios.base]

```

namespace std {
 class ios_base {
 public:
 class failure; // see below

 // 30.5.3.1.2, fmtflags
 using fmtflags = T1;
 };
}

```

<sup>290</sup>) Typically long long.

<sup>291</sup>) `streamsize` is used in most places where ISO C would use `size_t`. Most of the uses of `streamsize` could use `size_t`, except for the `strstreambuf` constructors, which require negative values. It should probably be the signed type corresponding to `size_t` (which is what Posix.2 calls `ssize_t`).

```

static constexpr fmtflags boolalpha = unspecified;
static constexpr fmtflags dec = unspecified;
static constexpr fmtflags fixed = unspecified;
static constexpr fmtflags hex = unspecified;
static constexpr fmtflags internal = unspecified;
static constexpr fmtflags left = unspecified;
static constexpr fmtflags oct = unspecified;
static constexpr fmtflags right = unspecified;
static constexpr fmtflags scientific = unspecified;
static constexpr fmtflags showbase = unspecified;
static constexpr fmtflags showpoint = unspecified;
static constexpr fmtflags showpos = unspecified;
static constexpr fmtflags skipws = unspecified;
static constexpr fmtflags unitbuf = unspecified;
static constexpr fmtflags uppercase = unspecified;
static constexpr fmtflags adjustfield = see below;
static constexpr fmtflags basefield = see below;
static constexpr fmtflags floatfield = see below;

```

```

// 30.5.3.1.3, iostate

```

```

using iostate = T2;
static constexpr iostate badbit = unspecified;
static constexpr iostate eofbit = unspecified;
static constexpr iostate failbit = unspecified;
static constexpr iostate goodbit = see below;

```

```

// 30.5.3.1.4, openmode

```

```

using openmode = T3;
static constexpr openmode app = unspecified;
static constexpr openmode ate = unspecified;
static constexpr openmode binary = unspecified;
static constexpr openmode in = unspecified;
static constexpr openmode out = unspecified;
static constexpr openmode trunc = unspecified;

```

```

// 30.5.3.1.5, seekdir

```

```

using seekdir = T4;
static constexpr seekdir beg = unspecified;
static constexpr seekdir cur = unspecified;
static constexpr seekdir end = unspecified;

```

```

class Init;

```

```

// 30.5.3.2, fmtflags state

```

```

fmtflags flags() const;
fmtflags flags(fmtflags fmtfl);
fmtflags setf(fmtflags fmtfl);
fmtflags setf(fmtflags fmtfl, fmtflags mask);
void unsetf(fmtflags mask);

```

```

streamsize precision() const;
streamsize precision(streamsize prec);
streamsize width() const;
streamsize width(streamsize wide);

```

```

// 30.5.3.3, locales
locale imbue(const locale& loc);
locale getloc() const;

// 30.5.3.5, storage
static int xalloc();
long& iword(int index);
void*& pword(int index);

// destructor:
virtual ~ios_base();

// 30.5.3.6, callbacks;
enum event { erase_event, imbue_event, copyfmt_event };
using event_callback = void (*)(event, ios_base&, int index);
void register_callback(event_callback fn, int index);

ios_base(const ios_base&) = delete;
ios_base& operator=(const ios_base&) = delete;

static bool sync_with_stdio(bool sync = true);

protected:
 ios_base();

private:
 static int index; // exposition only
 long* iarray; // exposition only
 void** parray; // exposition only
};
}

```

<sup>1</sup> `ios_base` defines several member types:

- (1.1) — a type `failure`, defined as either a class derived from `system_error` or a synonym for a class derived from `system_error`;
- (1.2) — a class `Init`;
- (1.3) — three bitmask types, `fmtflags`, `iostate`, and `openmode`;
- (1.4) — an enumerated type, `seekdir`.

<sup>2</sup> It maintains several kinds of data:

- (2.1) — state information that reflects the integrity of the stream buffer;
- (2.2) — control information that influences how to interpret (format) input sequences and how to generate (format) output sequences;
- (2.3) — additional information that is stored by the program for its private use.

<sup>3</sup> [ *Note:* For the sake of exposition, the maintained data is presented here as:

- (3.1) — `static int index`, specifies the next available unique index for the integer or pointer arrays maintained for the private use of the program, initialized to an unspecified value;
- (3.2) — `long* iarray`, points to the first element of an arbitrary-length `long` array maintained for the private use of the program;
- (3.3) — `void** parray`, points to the first element of an arbitrary-length pointer array maintained for the

private use of the program.

— *end note*]

### 30.5.3.1 Types

[ios.types]

#### 30.5.3.1.1 Class `ios_base::failure`

[ios::failure]

```
namespace std {
 class ios_base::failure : public system_error {
 public:
 explicit failure(const string& msg, const error_code& ec = io_errc::stream);
 explicit failure(const char* msg, const error_code& ec = io_errc::stream);
 };
}
```

<sup>1</sup> An implementation is permitted to define `ios_base::failure` as a synonym for a class with equivalent functionality to class `ios_base::failure` shown in this subclause. [ *Note:* When `ios_base::failure` is a synonym for another type it shall provide a nested type `failure`, to emulate the injected class name. — *end note* ] The class `failure` defines the base class for the types of all objects thrown as exceptions, by functions in the `iostreams` library, to report errors detected during stream buffer operations.

<sup>2</sup> When throwing `ios_base::failure` exceptions, implementations should provide values of `ec` that identify the specific reason for the failure. [ *Note:* Errors arising from the operating system would typically be reported as `system_category()` errors with an error value of the error number reported by the operating system. Errors arising from within the stream library would typically be reported as `error_code(io_errc::stream, iostream_category())`. — *end note* ]

```
explicit failure(const string& msg, const error_code& ec = io_errc::stream);
```

<sup>3</sup> *Effects:* Constructs an object of class `failure` by constructing the base class with `msg` and `ec`.

```
explicit failure(const char* msg, const error_code& ec = io_errc::stream);
```

<sup>4</sup> *Effects:* Constructs an object of class `failure` by constructing the base class with `msg` and `ec`.

#### 30.5.3.1.2 Type `ios_base::fmtflags`

[ios::fmtflags]

```
using fmtflags = T1;
```

<sup>1</sup> The type `fmtflags` is a bitmask type (20.4.2.1.4). Setting its elements has the effects indicated in Table 107.

<sup>2</sup> Type `fmtflags` also defines the constants indicated in Table 108.

#### 30.5.3.1.3 Type `ios_base::iostate`

[ios::iostate]

```
using iostate = T2;
```

<sup>1</sup> The type `iostate` is a bitmask type (20.4.2.1.4) that contains the elements indicated in Table 109.

<sup>2</sup> Type `iostate` also defines the constant:

(2.1) — `goodbit`, the value zero.

#### 30.5.3.1.4 Type `ios_base::openmode`

[ios::openmode]

```
using openmode = T3;
```

<sup>1</sup> The type `openmode` is a bitmask type (20.4.2.1.4). It contains the elements indicated in Table 110.

#### 30.5.3.1.5 Type `ios_base::seekdir`

[ios::seekdir]

```
using seekdir = T4;
```

Table 107 — `fmtflags` effects

| Element                 | Effect(s) if set                                                                                                                                   |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>boolalpha</code>  | insert and extract <code>bool</code> type in alphabetic format                                                                                     |
| <code>dec</code>        | converts integer input or generates integer output in decimal base                                                                                 |
| <code>fixed</code>      | generate floating-point output in fixed-point notation                                                                                             |
| <code>hex</code>        | converts integer input or generates integer output in hexadecimal base                                                                             |
| <code>internal</code>   | adds fill characters at a designated internal point in certain generated output, or identical to <code>right</code> if no such point is designated |
| <code>left</code>       | adds fill characters on the right (final positions) of certain generated output                                                                    |
| <code>oct</code>        | converts integer input or generates integer output in octal base                                                                                   |
| <code>right</code>      | adds fill characters on the left (initial positions) of certain generated output                                                                   |
| <code>scientific</code> | generates floating-point output in scientific notation                                                                                             |
| <code>showbase</code>   | generates a prefix indicating the numeric base of generated integer output                                                                         |
| <code>showpoint</code>  | generates a decimal-point character unconditionally in generated floating-point output                                                             |
| <code>showpos</code>    | generates a <code>+</code> sign in non-negative generated numeric output                                                                           |
| <code>skipws</code>     | skips leading whitespace before certain input operations                                                                                           |
| <code>unitbuf</code>    | flushes output after each output operation                                                                                                         |
| <code>uppercase</code>  | replaces certain lowercase letters with their uppercase equivalents in generated output                                                            |

Table 108 — `fmtflags` constants

| Constant                 | Allowable values                                               |
|--------------------------|----------------------------------------------------------------|
| <code>adjustfield</code> | <code>left</code>   <code>right</code>   <code>internal</code> |
| <code>basefield</code>   | <code>dec</code>   <code>oct</code>   <code>hex</code>         |
| <code>floatfield</code>  | <code>scientific</code>   <code>fixed</code>                   |

Table 109 — `iostate` effects

| Element              | Effect(s) if set                                                                                                                                 |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>badbit</code>  | indicates a loss of integrity in an input or output sequence (such as an irrecoverable read error from a file);                                  |
| <code>eofbit</code>  | indicates that an input operation reached the end of an input sequence;                                                                          |
| <code>failbit</code> | indicates that an input operation failed to read the expected characters, or that an output operation failed to generate the desired characters. |

Table 110 — `openmode` effects

| Element             | Effect(s) if set                                                  |
|---------------------|-------------------------------------------------------------------|
| <code>app</code>    | seek to end before each write                                     |
| <code>ate</code>    | open and seek to end immediately after opening                    |
| <code>binary</code> | perform input and output in binary mode (as opposed to text mode) |
| <code>in</code>     | open for input                                                    |
| <code>out</code>    | open for output                                                   |
| <code>trunc</code>  | truncate an existing stream when opening                          |

<sup>1</sup> The type `seekdir` is an enumerated type (20.4.2.1.3) that contains the elements indicated in Table 111.

Table 111 — `seekdir` effects

| Element          | Meaning                                                                                 |
|------------------|-----------------------------------------------------------------------------------------|
| <code>beg</code> | request a seek (for subsequent input or output) relative to the beginning of the stream |
| <code>cur</code> | request a seek relative to the current position within the sequence                     |
| <code>end</code> | request a seek relative to the current end of the sequence                              |

### 30.5.3.1.6 Class `ios_base::Init`

[`ios::Init`]

```
namespace std {
 class ios_base::Init {
 public:
 Init();
 ~Init();
 private:
 static int init_cnt; // exposition only
 };
}
```

<sup>1</sup> The class `Init` describes an object whose construction ensures the construction of the eight objects declared in `<iostream>` (30.4) that associate file stream buffers with the standard C streams provided for by the functions declared in `<cstdio>` (30.11.1).

<sup>2</sup> For the sake of exposition, the maintained data is presented here as:

(2.1) — `static int init_cnt`, counts the number of constructor and destructor calls for class `Init`, initialized to zero.

```
Init();
```

<sup>3</sup> *Effects:* Constructs an object of class `Init`. Constructs and initializes the objects `cin`, `cout`, `cerr`, `clog`, `wcin`, `wcout`, `wcerr`, and `wclog` if they have not already been constructed and initialized.

```
~Init();
```

<sup>4</sup> *Effects:* Destroys an object of class `Init`. If there are no other instances of the class still in existence, calls `cout.flush()`, `cerr.flush()`, `clog.flush()`, `wcout.flush()`, `wcerr.flush()`, `wclog.flush()`.

### 30.5.3.2 `ios_base` state functions

[`fmtflags.state`]

```
fmtflags flags() const;
```

<sup>1</sup> *Returns:* The format control information for both input and output.

```
fmtflags flags(fmtflags fmtfl);
```

<sup>2</sup> *Postconditions:* `fmtfl == flags()`.

<sup>3</sup> *Returns:* The previous value of `flags()`.

```
fmtflags setf(fmtflags fmtfl);
```

<sup>4</sup> *Effects:* Sets `fmtfl` in `flags()`.

<sup>5</sup> *Returns:* The previous value of `flags()`.

```
fmtflags setf(fmtflags fmtfl, fmtflags mask);
```

6 *Effects:* Clears mask in `flags()`, sets `fmtfl` & mask in `flags()`.

7 *Returns:* The previous value of `flags()`.

```
void unsetf(fmtflags mask);
```

8 *Effects:* Clears mask in `flags()`.

```
streamsize precision() const;
```

9 *Returns:* The precision to generate on certain output conversions.

```
streamsize precision(streamsize prec);
```

10 *Postconditions:* `prec == precision()`.

11 *Returns:* The previous value of `precision()`.

```
streamsize width() const;
```

12 *Returns:* The minimum field width (number of characters) to generate on certain output conversions.

```
streamsize width(streamsize wide);
```

13 *Postconditions:* `wide == width()`.

14 *Returns:* The previous value of `width()`.

### 30.5.3.3 `ios_base` functions

[`ios.base.locales`]

```
locale imbue(const locale& loc);
```

1 *Effects:* Calls each registered callback pair `(fn, index)` (30.5.3.6) as `(*fn)(imbue_event, *this, index)` at such a time that a call to `ios_base::getloc()` from within `fn` returns the new locale value `loc`.

2 *Returns:* The previous value of `getloc()`.

3 *Postconditions:* `loc == getloc()`.

```
locale getloc() const;
```

4 *Returns:* If no locale has been imbued, a copy of the global C++ locale, `locale()`, in effect at the time of construction. Otherwise, returns the imbued locale, to be used to perform locale-dependent input and output operations.

### 30.5.3.4 `ios_base` static members

[`ios.members.static`]

```
bool sync_with_stdio(bool sync = true);
```

1 *Returns:* `true` if the previous state of the standard iostream objects (30.4) was synchronized and otherwise returns `false`. The first time it is called, the function returns `true`.

2 *Effects:* If any input or output operation has occurred using the standard streams prior to the call, the effect is implementation-defined. Otherwise, called with a `false` argument, it allows the standard streams to operate independently of the standard C streams.

3 When a standard iostream object `str` is *synchronized* with a standard stdio stream `f`, the effect of inserting a character `c` by

```
fputc(f, c);
```

is the same as the effect of

```
str.rdbuf()->sputc(c);
```

for any sequences of characters; the effect of extracting a character `c` by



```

 c = fgetc(f);
is the same as the effect of
 c = str.rdbuf()->sgetc();
for any sequences of characters; and the effect of pushing back a character c by
 ungetc(c, f);
is the same as the effect of
 str.rdbuf()->sputbackc(c);
for any sequence of characters.292

```

### 30.5.3.5 ios\_base storage functions

[ios.base.storage]

```
static int xalloc();
```

1 *Returns:* index ++.

2 *Remarks:* Concurrent access to this function by multiple threads shall not result in a data race (4.7).

```
long& iword(int idx);
```

3 *Effects:* If `iarray` is a null pointer, allocates an array of `long` of unspecified size and stores a pointer to its first element in `iarray`. The function then extends the array pointed at by `iarray` as necessary to include the element `iarray[idx]`. Each newly allocated element of the array is initialized to zero. The reference returned is invalid after any other operations on the object.<sup>293</sup> However, the value of the storage referred to is retained, so that until the next call to `copyfmt`, calling `iword` with the same index yields another reference to the same value. If the function fails<sup>294</sup> and `*this` is a base class subobject of a `basic_ios<>` object or subobject, the effect is equivalent to calling `basic_ios<>::setstate(badbit)` on the derived object (which may throw `failure`).

4 *Returns:* On success `iarray[idx]`. On failure, a valid `long&` initialized to 0.

```
void*& pword(int idx);
```

5 *Effects:* If `parray` is a null pointer, allocates an array of pointers to `void` of unspecified size and stores a pointer to its first element in `parray`. The function then extends the array pointed at by `parray` as necessary to include the element `parray[idx]`. Each newly allocated element of the array is initialized to a null pointer. The reference returned is invalid after any other operations on the object. However, the value of the storage referred to is retained, so that until the next call to `copyfmt`, calling `pword` with the same index yields another reference to the same value. If the function fails<sup>295</sup> and `*this` is a base class subobject of a `basic_ios<>` object or subobject, the effect is equivalent to calling `basic_ios<>::setstate(badbit)` on the derived object (which may throw `failure`).

6 *Returns:* On success `parray[idx]`. On failure a valid `void*&` initialized to 0.

7 *Remarks:* After a subsequent call to `pword(int)` for the same object, the earlier return value may no longer be valid.

### 30.5.3.6 ios\_base callbacks

[ios.base.callback]

```
void register_callback(event_callback fn, int index);
```

292) This implies that operations on a standard iostream object can be mixed arbitrarily with operations on the corresponding stdio stream. In practical terms, synchronization usually means that a standard iostream object and a standard stdio object share a buffer.

293) An implementation is free to implement both the integer array pointed at by `iarray` and the pointer array pointed at by `parray` as sparse data structures, possibly with a one-element cache for each.

294) for example, because it cannot allocate space.

295) for example, because it cannot allocate space.

1 *Effects:* Registers the pair (fn, index) such that during calls to imbue() (30.5.3.3), copyfmt(), or ~ios\_base() (30.5.3.7), the function fn is called with argument index. Functions registered are called when an event occurs, in opposite order of registration. Functions registered while a callback function is active are not called until the next event.

2 *Requires:* The function fn shall not throw exceptions.

3 *Remarks:* Identical pairs are not merged. A function registered twice will be called twice.

### 30.5.3.7 ios\_base constructors/destructor

[ios.base.cons]

ios\_base();

1 *Effects:* Each ios\_base member has an indeterminate value after construction. The object's members shall be initialized by calling basic\_ios::init before the object's first use or before it is destroyed, whichever comes first; otherwise the behavior is undefined.

~ios\_base();

2 *Effects:* Destroys an object of class ios\_base. Calls each registered callback pair (fn, index) (30.5.3.6) as (\*fn)(erase\_event, \*this, index) at such time that any ios\_base member function called from within fn has well defined results.

### 30.5.4 Class template fpos

[fpos]

```
namespace std {
 template <class stateT> class fpos {
 public:
 // 30.5.4.1, members
 stateT state() const;
 void state(stateT);
 private:
 stateT st; // exposition only
 };
}
```

#### 30.5.4.1 fpos members

[fpos.members]

void state(stateT s);

1 *Effects:* Assigns s to st.

stateT state() const;

2 *Returns:* Current value of st.

#### 30.5.4.2 fpos requirements

[fpos.operations]

1 Operations specified in Table 112 are permitted. In that table,

- (1.1) — P refers to an instance of fpos,
- (1.2) — p and q refer to values of type P,
- (1.3) — 0 refers to type streamoff,
- (1.4) — o refers to a value of type streamoff,
- (1.5) — sz refers to a value of type streamsize and
- (1.6) — i refers to a value of type int.

Table 112 — Position type requirements

| Expression          | Return type         | Operational semantics | Assertion/note pre-/post-condition          |
|---------------------|---------------------|-----------------------|---------------------------------------------|
| P(i)                |                     |                       | p == P(i)<br>note: a destructor is assumed. |
| P p(i);<br>P p = i; |                     |                       | <i>Postconditions:</i> p == P(i).           |
| P(o)                | fpos                | converts from offset  |                                             |
| O(p)                | streamoff           | converts to offset    | P(O(p)) == p                                |
| p == q              | convertible to bool |                       | == is an equivalence relation               |
| p != q              | convertible to bool | !(p == q)             |                                             |
| q = p + o<br>p += o | fpos                | + offset              | q - o == p                                  |
| q = p - o<br>p -= o | fpos                | - offset              | q + o == p                                  |
| o = p - q           | streamoff           | distance              | q + o == p                                  |
| streamsize(o)       | streamsize          | converts              | streamsize(O(sz)) == sz                     |
| O(sz)               | streamoff           | converts              | streamsize(O(sz)) == sz                     |

<sup>2</sup> [Note: Every implementation is required to supply overloaded operators on fpos objects to satisfy the requirements of 30.5.4.2. It is unspecified whether these operators are members of fpos, global operators, or provided in some other way. — end note]

<sup>3</sup> Stream operations that return a value of type traits::pos\_type return P(O(-1)) as an invalid value to signal an error. If this value is used as an argument to any istream, ostream, or streambuf member that accepts a value of type traits::pos\_type then the behavior of that function is undefined.

### 30.5.5 Class template basic\_ios

[ios]

#### 30.5.5.1 Overview

[ios.overview]

```

namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_ios : public ios_base {
 public:
 using char_type = charT;
 using int_type = typename traits::int_type;
 using pos_type = typename traits::pos_type;
 using off_type = typename traits::off_type;
 using traits_type = traits;

 // 30.5.5.4, flags functions
 explicit operator bool() const;
 bool operator!() const;
 iostate rdstate() const;
 void clear(iostate state = goodbit);
 void setstate(iostate state);
 bool good() const;
 bool eof() const;
 bool fail() const;
 bool bad() const;

 iostate exceptions() const;
 };

```

```

void exceptions(iostate except);

// 30.5.5.2, constructor/destructor
explicit basic_ios(basic_streambuf<charT, traits>* sb);
virtual ~basic_ios();

// 30.5.5.3, members
basic_ostream<charT, traits>* tie() const;
basic_ostream<charT, traits>* tie(basic_ostream<charT, traits>* tiestr);

basic_streambuf<charT, traits>* rdbuf() const;
basic_streambuf<charT, traits>* rdbuf(basic_streambuf<charT, traits>* sb);

basic_ios& copyfmt(const basic_ios& rhs);

char_type fill() const;
char_type fill(char_type ch);

locale imbue(const locale& loc);

char narrow(char_type c, char dfault) const;
char_type widen(char c) const;

basic_ios(const basic_ios&) = delete;
basic_ios& operator=(const basic_ios&) = delete;

protected:
 basic_ios();
 void init(basic_streambuf<charT, traits>* sb);
 void move(basic_ios& rhs);
 void move(basic_ios&& rhs);
 void swap(basic_ios& rhs) noexcept;
 void set_rdbuf(basic_streambuf<charT, traits>* sb);

};
}

```

### 30.5.5.2 basic\_ios constructors

[basic.ios.cons]

```
explicit basic_ios(basic_streambuf<charT, traits>* sb);
```

- 1 *Effects:* Constructs an object of class `basic_ios`, assigning initial values to its member objects by calling `init(sb)`.

```
basic_ios();
```

- 2 *Effects:* Constructs an object of class `basic_ios` (30.5.3.7) leaving its member objects uninitialized. The object shall be initialized by calling `basic_ios::init` before its first use or before it is destroyed, whichever comes first; otherwise the behavior is undefined.

```
~basic_ios();
```

- 3 *Remarks:* The destructor does not destroy `rdbuf()`.

```
void init(basic_streambuf<charT, traits>* sb);
```

- 4 *Postconditions:* The postconditions of this function are indicated in Table 113.

Table 113 — `basic_ios::init()` effects

| Element                   | Value                                                               |
|---------------------------|---------------------------------------------------------------------|
| <code>rdbuf()</code>      | <code>sb</code>                                                     |
| <code>tie()</code>        | <code>0</code>                                                      |
| <code>rdstate()</code>    | goodbit if <code>sb</code> is not a null pointer, otherwise badbit. |
| <code>exceptions()</code> | goodbit                                                             |
| <code>flags()</code>      | <code>skipws</code>   <code>dec</code>                              |
| <code>width()</code>      | <code>0</code>                                                      |
| <code>precision()</code>  | <code>6</code>                                                      |
| <code>fill()</code>       | <code>widen(' ')</code>                                             |
| <code>getloc()</code>     | a copy of the value returned by <code>locale()</code>               |
| <i>iarray</i>             | a null pointer                                                      |
| <i>parray</i>             | a null pointer                                                      |

### 30.5.5.3 Member functions

[`basic.ios.members`]

```
basic_ostream<charT, traits>* tie() const;
```

1 *Returns:* An output sequence that is *tied* to (synchronized with) the sequence controlled by the stream buffer.

```
basic_ostream<charT, traits>* tie(basic_ostream<charT, traits>* tiestr);
```

2 *Requires:* If `tiestr` is not null, `tiestr` must not be reachable by traversing the linked list of tied stream objects starting from `tiestr->tie()`.

3 *Postconditions:* `tiestr == tie()`.

4 *Returns:* The previous value of `tie()`.

```
basic_streambuf<charT, traits>* rdbuf() const;
```

5 *Returns:* A pointer to the `streambuf` associated with the stream.

```
basic_streambuf<charT, traits>* rdbuf(basic_streambuf<charT, traits>* sb);
```

6 *Postconditions:* `sb == rdbuf()`.

7 *Effects:* Calls `clear()`.

8 *Returns:* The previous value of `rdbuf()`.

```
locale imbue(const locale& loc);
```

9 *Effects:* Calls `ios_base::imbue(loc)` (30.5.3.3) and if `rdbuf() != 0` then `rdbuf()->pubimbue(loc)` (30.6.3.2.1).

10 *Returns:* The prior value of `ios_base::imbue()`.

```
char narrow(char_type c, char dfault) const;
```

11 *Returns:* `use_facet<ctype<char_type>>(getloc()).narrow(c, dfault)`

```
char_type widen(char c) const;
```

12 *Returns:* `use_facet<ctype<char_type>>(getloc()).widen(c)`

```
char_type fill() const;
```

13 *Returns:* The character used to pad (fill) an output conversion to the specified field width.

```
char_type fill(char_type fillch);
```

14 *Postconditions:* `traits::eq(fillch, fill())`.

15 *Returns:* The previous value of `fill()`.

```
basic_ios& copyfmt(const basic_ios& rhs);
```

16 *Effects:* If `(this == &rhs)` does nothing. Otherwise assigns to the member objects of `*this` the corresponding member objects of `rhs` as follows:

1. calls each registered callback pair `(fn, index)` as `(*fn)(erase_event, *this, index)`;
2. assigns to the member objects of `*this` the corresponding member objects of `rhs`, except that
  - (16.1) — `rdstate()`, `rdbuf()`, and `exceptions()` are left unchanged;
  - (16.2) — the contents of arrays pointed at by `pword` and `iword` are copied, not the pointers themselves;<sup>296</sup> and
  - (16.3) — if any newly stored pointer values in `*this` point at objects stored outside the object `rhs` and those objects are destroyed when `rhs` is destroyed, the newly stored pointer values are altered to point at newly constructed copies of the objects;
3. calls each callback pair that was copied from `rhs` as `(*fn)(copyfmt_event, *this, index)`;
4. calls `exceptions(rhs.exceptions())`.

17 [ *Note:* The second pass through the callback pairs permits a copied `pword` value to be zeroed, or to have its referent deep copied or reference counted, or to have other special action taken. — *end note* ]

18 *Postconditions:* The postconditions of this function are indicated in Table 114.

Table 114 — `basic_ios::copyfmt()` effects

| Element                   | Value                         |
|---------------------------|-------------------------------|
| <code>rdbuf()</code>      | <i>unchanged</i>              |
| <code>tie()</code>        | <code>rhs.tie()</code>        |
| <code>rdstate()</code>    | <i>unchanged</i>              |
| <code>exceptions()</code> | <code>rhs.exceptions()</code> |
| <code>flags()</code>      | <code>rhs.flags()</code>      |
| <code>width()</code>      | <code>rhs.width()</code>      |
| <code>precision()</code>  | <code>rhs.precision()</code>  |
| <code>fill()</code>       | <code>rhs.fill()</code>       |
| <code>getloc()</code>     | <code>rhs.getloc()</code>     |

19 *Returns:* `*this`.

```
void move(basic_ios& rhs);
void move(basic_ios&& rhs);
```

20 *Postconditions:* `*this` shall have the state that `rhs` had before the function call, except that `rdbuf()` shall return 0. `rhs` shall be in a valid but unspecified state, except that `rhs.rdbuf()` shall return the same value as it returned before the function call, and `rhs.tie()` shall return 0.

```
void swap(basic_ios& rhs) noexcept;
```

<sup>296</sup>) This suggests an infinite amount of copying, but the implementation can keep track of the maximum element of the arrays that is nonzero.

21 *Effects:* The states of `*this` and `rhs` shall be exchanged, except that `rdbuf()` shall return the same value as it returned before the function call, and `rhs.rdbuf()` shall return the same value as it returned before the function call.

`void set_rdbuf(basic_streambuf<charT, traits>* sb);`

22 *Requires:* `sb != nullptr`.

23 *Effects:* Associates the `basic_streambuf` object pointed to by `sb` with this stream without calling `clear()`.

24 *Postconditions:* `rdbuf() == sb`.

25 *Throws:* Nothing.

#### 30.5.5.4 `basic_ios` flags functions [`iostate.flags`]

`explicit operator bool() const;`

1 *Returns:* `!fail()`.

`bool operator!() const;`

2 *Returns:* `fail()`.

`iostate rdstate() const;`

3 *Returns:* The error state of the stream buffer.

`void clear(iostate state = goodbit);`

4 *Postconditions:* If `rdbuf() != 0` then `state == rdstate()`; otherwise `rdstate() == (state | ios_base::badbit)`.

5 *Effects:* If `((state | (rdbuf() ? goodbit : badbit)) & exceptions()) == 0`, returns. Otherwise, the function throws an object of class `basic_ios::failure` (30.5.3.1.1), constructed with implementation-defined argument values.

`void setstate(iostate state);`

6 *Effects:* Calls `clear(rdstate() | state)` (which may throw `basic_ios::failure` (30.5.3.1.1)).

`bool good() const;`

7 *Returns:* `rdstate() == 0`

`bool eof() const;`

8 *Returns:* `true` if `eofbit` is set in `rdstate()`.

`bool fail() const;`

9 *Returns:* `true` if `failbit` or `badbit` is set in `rdstate()`.<sup>297</sup>

`bool bad() const;`

10 *Returns:* `true` if `badbit` is set in `rdstate()`.

`iostate exceptions() const;`

11 *Returns:* A mask that determines what elements set in `rdstate()` cause exceptions to be thrown.

`void exceptions(iostate except);`

---

<sup>297</sup>) Checking `badbit` also for `fail()` is historical practice.

12       *Postconditions:* `except == exceptions()`.

13       *Effects:* Calls `clear(rdstate())`.

### 30.5.6 ios\_base manipulators

[std.ios.manip]

#### 30.5.6.1 fmtflags manipulators

[fmtflags.manip]

`ios_base& boolalpha(ios_base& str);`

1       *Effects:* Calls `str.setf(ios_base::boolalpha)`.

2       *Returns:* `str`.

`ios_base& noboolalpha(ios_base& str);`

3       *Effects:* Calls `str.unsetf(ios_base::boolalpha)`.

4       *Returns:* `str`.

`ios_base& showbase(ios_base& str);`

5       *Effects:* Calls `str.setf(ios_base::showbase)`.

6       *Returns:* `str`.

`ios_base& noshowbase(ios_base& str);`

7       *Effects:* Calls `str.unsetf(ios_base::showbase)`.

8       *Returns:* `str`.

`ios_base& showpoint(ios_base& str);`

9       *Effects:* Calls `str.setf(ios_base::showpoint)`.

10       *Returns:* `str`.

`ios_base& noshowpoint(ios_base& str);`

11       *Effects:* Calls `str.unsetf(ios_base::showpoint)`.

12       *Returns:* `str`.

`ios_base& showpos(ios_base& str);`

13       *Effects:* Calls `str.setf(ios_base::showpos)`.

14       *Returns:* `str`.

`ios_base& noshowpos(ios_base& str);`

15       *Effects:* Calls `str.unsetf(ios_base::showpos)`.

16       *Returns:* `str`.

`ios_base& skipws(ios_base& str);`

17       *Effects:* Calls `str.setf(ios_base::skipws)`.

18       *Returns:* `str`.

`ios_base& noskipws(ios_base& str);`

19       *Effects:* Calls `str.unsetf(ios_base::skipws)`.

20       *Returns:* `str`.

`ios_base& uppercase(ios_base& str);`



21 *Effects:* Calls `str.setf(ios_base::uppercase)`.

22 *Returns:* `str`.

`ios_base& nouppercase(ios_base& str);`

23 *Effects:* Calls `str.unsetf(ios_base::uppercase)`.

24 *Returns:* `str`.

`ios_base& unitbuf(ios_base& str);`

25 *Effects:* Calls `str.setf(ios_base::unitbuf)`.

26 *Returns:* `str`.

`ios_base& nounitbuf(ios_base& str);`

27 *Effects:* Calls `str.unsetf(ios_base::unitbuf)`.

28 *Returns:* `str`.

### 30.5.6.2 adjustfield manipulators

[adjustfield.manip]

`ios_base& internal(ios_base& str);`

1 *Effects:* Calls `str.setf(ios_base::internal, ios_base::adjustfield)`.

2 *Returns:* `str`.

`ios_base& left(ios_base& str);`

3 *Effects:* Calls `str.setf(ios_base::left, ios_base::adjustfield)`.

4 *Returns:* `str`.

`ios_base& right(ios_base& str);`

5 *Effects:* Calls `str.setf(ios_base::right, ios_base::adjustfield)`.

6 *Returns:* `str`.

### 30.5.6.3 basefield manipulators

[basefield.manip]

`ios_base& dec(ios_base& str);`

1 *Effects:* Calls `str.setf(ios_base::dec, ios_base::basefield)`.

2 *Returns:* `str`<sup>298</sup>.

`ios_base& hex(ios_base& str);`

3 *Effects:* Calls `str.setf(ios_base::hex, ios_base::basefield)`.

4 *Returns:* `str`.

`ios_base& oct(ios_base& str);`

5 *Effects:* Calls `str.setf(ios_base::oct, ios_base::basefield)`.

6 *Returns:* `str`.

### 30.5.6.4 floatfield manipulators

[floatfield.manip]

`ios_base& fixed(ios_base& str);`

---

298) The function signature `dec(ios_base&)` can be called by the function signature `basic_ostream& stream::operator<<(ios_base& (*)(ios_base&))` to permit expressions of the form `cout << dec` to change the format flags stored in `cout`.

1       *Effects:* Calls `str.setf(ios_base::fixed, ios_base::floatfield)`.  
 2       *Returns:* `str`.

`ios_base& scientific(ios_base& str);`

3       *Effects:* Calls `str.setf(ios_base::scientific, ios_base::floatfield)`.  
 4       *Returns:* `str`.

`ios_base& hexfloat(ios_base& str);`

5       *Effects:* Calls `str.setf(ios_base::fixed | ios_base::scientific, ios_base::floatfield)`.  
 6       *Returns:* `str`.

7   [ *Note:* The more obvious use of `ios_base::hex` to specify hexadecimal floating-point format would change the meaning of existing well defined programs. C++ 2003 gives no meaning to the combination of `fixed` and `scientific`. — *end note* ]

`ios_base& defaultfloat(ios_base& str);`

8       *Effects:* Calls `str.unsetf(ios_base::floatfield)`.  
 9       *Returns:* `str`.

### 30.5.6.5 Error reporting

[error.reporting]

`error_code make_error_code(io_errc e) noexcept;`

1       *Returns:* `error_code(static_cast<int>(e), iostream_category())`.

`error_condition make_error_condition(io_errc e) noexcept;`

2       *Returns:* `error_condition(static_cast<int>(e), iostream_category())`.

`const error_category& iostream_category() noexcept;`

3       *Returns:* A reference to an object of a type derived from class `error_category`.

4       The object's `default_error_condition` and `equivalent` virtual functions shall behave as specified for the class `error_category`. The object's `name` virtual function shall return a pointer to the string "iostream".

## 30.6 Stream buffers

[stream.buffers]

### 30.6.1 Header <streambuf> synopsis

[streambuf.syn]

```
namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_streambuf;
 using streambuf = basic_streambuf<char>;
 using wstreambuf = basic_streambuf<wchar_t>;
}
```

1 The header <streambuf> defines types that control input from and output to *character* sequences.

### 30.6.2 Stream buffer requirements

[streambuf.reqts]

1 Stream buffers can impose various constraints on the sequences they control. Some constraints are:

- (1.1) — The controlled input sequence can be not readable.
- (1.2) — The controlled output sequence can be not writable.
- (1.3) — The controlled sequences can be associated with the contents of other representations for character sequences, such as external files.

- (1.4) — The controlled sequences can support operations *directly* to or from associated sequences.
  - (1.5) — The controlled sequences can impose limitations on how the program can read characters from a sequence, write characters to a sequence, put characters back into an input sequence, or alter the stream position.
- <sup>2</sup> Each sequence is characterized by three pointers which, if non-null, all point into the same `charT` array object. The array object represents, at any moment, a (sub)sequence of characters from the sequence. Operations performed on a sequence alter the values stored in these pointers, perform reads and writes directly to or from associated sequences, and alter “the stream position” and conversion state as needed to maintain this subsequence relationship. The three pointers are:
- (2.1) — the *beginning pointer*, or lowest element address in the array (called `xbeg` here);
  - (2.2) — the *next pointer*, or next element address that is a current candidate for reading or writing (called `xnext` here);
  - (2.3) — the *end pointer*, or first element address beyond the end of the array (called `xend` here).
- <sup>3</sup> The following semantic constraints shall always apply for any set of three pointers for a sequence, using the pointer names given immediately above:
- (3.1) — If `xnext` is not a null pointer, then `xbeg` and `xend` shall also be non-null pointers into the same `charT` array, as described above; otherwise, `xbeg` and `xend` shall also be null.
  - (3.2) — If `xnext` is not a null pointer and `xnext < xend` for an output sequence, then a *write position* is available. In this case, `*xnext` shall be assignable as the next element to write (to put, or to store a character value, into the sequence).
  - (3.3) — If `xnext` is not a null pointer and `xbeg < xnext` for an input sequence, then a *putback position* is available. In this case, `xnext[-1]` shall have a defined value and is the next (preceding) element to store a character that is put back into the input sequence.
  - (3.4) — If `xnext` is not a null pointer and `xnext < xend` for an input sequence, then a *read position* is available. In this case, `*xnext` shall have a defined value and is the next element to read (to get, or to obtain a character value, from the sequence).

### 30.6.3 Class template `basic_streambuf`

[streambuf]

```

namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_streambuf {
 public:
 using char_type = charT;
 using int_type = typename traits::int_type;
 using pos_type = typename traits::pos_type;
 using off_type = typename traits::off_type;
 using traits_type = traits;

 virtual ~basic_streambuf();

 // 30.6.3.2.1, locales
 locale pubimbue(const locale& loc);
 locale getloc() const;

 // 30.6.3.2.2, buffer and positioning
 basic_streambuf* pubsetbuf(char_type* s, streamsize n);
 pos_type pubseekoff(off_type off, ios_base::seekdir way,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
 };
}

```

```

pos_type pubseekpos(pos_type sp,
 ios_base::openmode which
 = ios_base::in | ios_base::out);

int pubsync();

// Get and put areas
// 30.6.3.2.3, get area
streamsize in_avail();
int_type snextc();
int_type sbumpc();
int_type sgetc();
streamsize sgetn(char_type* s, streamsize n);

// 30.6.3.2.4, putback
int_type sputbackc(char_type c);
int_type sungetc();

// 30.6.3.2.5, put area
int_type sputc(char_type c);
streamsize sputn(const char_type* s, streamsize n);

protected:
 basic_streambuf();
 basic_streambuf(const basic_streambuf& rhs);
 basic_streambuf& operator=(const basic_streambuf& rhs);

 void swap(basic_streambuf& rhs);

// 30.6.3.3.2, get area access
char_type* eback() const;
char_type* gptr() const;
char_type* egptr() const;
void gbump(int n);
void setg(char_type* gbeg, char_type* gnext, char_type* gend);

// 30.6.3.3.3, put area access
char_type* pbase() const;
char_type* pptr() const;
char_type* ep_ptr() const;
void pbump(int n);
void setp(char_type* pbeg, char_type* pend);

// 30.6.3.4, virtual functions
// 30.6.3.4.1, locales
virtual void imbue(const locale& loc);

// 30.6.3.4.2, buffer management and positioning
virtual basic_streambuf* setbuf(char_type* s, streamsize n);
virtual pos_type seekoff(off_type off, ios_base::seekdir way,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
virtual pos_type seekpos(pos_type sp,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
virtual int sync();

```

```

// 30.6.3.4.3, get area
virtual streamsize showmanyc();
virtual streamsize xsgetn(char_type* s, streamsize n);
virtual int_type underflow();
virtual int_type uflow();

// 30.6.3.4.4, putback
virtual int_type pbackfail(int_type c = traits::eof());

// 30.6.3.4.5, put area
virtual streamsize xspn(const char_type* s, streamsize n);
virtual int_type overflow(int_type c = traits::eof());
};
}

```

<sup>1</sup> The class template `basic_streambuf` serves as an abstract base class for deriving various *stream buffers* whose objects each control two *character sequences*:

- (1.1) — a character *input sequence*;
- (1.2) — a character *output sequence*.

### 30.6.3.1 `basic_streambuf` constructors

[streambuf.cons]

```
basic_streambuf();
```

<sup>1</sup> *Effects:* Constructs an object of class `basic_streambuf<charT, traits>` and initializes:<sup>299</sup>

- (1.1) — all its pointer member objects to null pointers,
- (1.2) — the `getloc()` member to a copy the global locale, `locale()`, at the time of construction.

<sup>2</sup> *Remarks:* Once the `getloc()` member is initialized, results of calling locale member functions, and of members of facets so obtained, can safely be cached until the next time the member `imbue` is called.

```
basic_streambuf(const basic_streambuf& rhs);
```

<sup>3</sup> *Effects:* Constructs a copy of `rhs`.

<sup>4</sup> *Postconditions:*

- (4.1) — `eback() == rhs.eback()`
- (4.2) — `gptr() == rhs.gptr()`
- (4.3) — `egptr() == rhs.egptr()`
- (4.4) — `pbase() == rhs.pbase()`
- (4.5) — `pptr() == rhs.pptr()`
- (4.6) — `epptr() == rhs.epptr()`
- (4.7) — `getloc() == rhs.getloc()`

```
~basic_streambuf();
```

<sup>5</sup> *Effects:* None.

### 30.6.3.2 `basic_streambuf` public member functions

[streambuf.members]

#### 30.6.3.2.1 Locales

[streambuf.locales]

---

<sup>299</sup>) The default constructor is protected for class `basic_streambuf` to assure that only objects for classes derived from this class may be constructed.

```
locale pubimbue(const locale& loc);
```

1     *Postconditions:* `loc == getloc()`.

2     *Effects:* Calls `imbue(loc)`.

3     *Returns:* Previous value of `getloc()`.

```
locale getloc() const;
```

4     *Returns:* If `pubimbue()` has ever been called, then the last value of `loc` supplied, otherwise the current global locale, `locale()`, in effect at the time of construction. If called after `pubimbue()` has been called but before `pubimbue` has returned (i.e., from within the call of `imbue()`) then it returns the previous value.

### 30.6.3.2.2 Buffer management and positioning

[streambuf.buffer]

```
basic_streambuf* pubsetbuf(char_type* s, streamsize n);
```

1     *Returns:* `setbuf(s, n)`.

```
pos_type pubseekoff(off_type off, ios_base::seekdir way,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
```

2     *Returns:* `seekoff(off, way, which)`.

```
pos_type pubseekpos(pos_type sp,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
```

3     *Returns:* `seekpos(sp, which)`.

```
int pubsync();
```

4     *Returns:* `sync()`.

### 30.6.3.2.3 Get area

[streambuf.pub.get]

```
streamsize in_avail();
```

1     *Returns:* If a read position is available, returns `egptr() - gptr()`. Otherwise returns `showmanyc()` (30.6.3.4.3).

```
int_type snextc();
```

2     *Effects:* Calls `sbumpc()`.

3     *Returns:* If that function returns `traits::eof()`, returns `traits::eof()`. Otherwise, returns `sgetc()`.

```
int_type sbumpc();
```

4     *Returns:* If the input sequence read position is not available, returns `uflow()`. Otherwise, returns `traits::to_int_type(*gptr())` and increments the next pointer for the input sequence.

```
int_type sgetc();
```

5     *Returns:* If the input sequence read position is not available, returns `underflow()`. Otherwise, returns `traits::to_int_type(*gptr())`.

```
streamsize sgetn(char_type* s, streamsize n);
```

6     *Returns:* `xsgetn(s, n)`.

### 30.6.3.2.4 Putback

[streambuf.pub.putback]

`int_type sputbackc(char_type c);`

- 1 *Returns:* If the input sequence putback position is not available, or if `traits::eq(c, gptr()[-1])` is `false`, returns `pbackfail(traits::to_int_type(c))`. Otherwise, decrements the next pointer for the input sequence and returns `traits::to_int_type(*gptr())`.

`int_type sungetc();`

- 2 *Returns:* If the input sequence putback position is not available, returns `pbackfail()`. Otherwise, decrements the next pointer for the input sequence and returns `traits::to_int_type(*gptr())`.

### 30.6.3.2.5 Put area

[streambuf.pub.put]

`int_type sputc(char_type c);`

- 1 *Returns:* If the output sequence write position is not available, returns `overflow(traits::to_int_type(c))`. Otherwise, stores `c` at the next pointer for the output sequence, increments the pointer, and returns `traits::to_int_type(c)`.

`streamsize sputn(const char_type* s, streamsize n);`

- 2 *Returns:* `xputn(s, n)`.

### 30.6.3.3 basic\_streambuf protected member functions

[streambuf.protected]

#### 30.6.3.3.1 Assignment

[streambuf.assign]

`basic_streambuf& operator=(const basic_streambuf& rhs);`

- 1 *Effects:* Assigns the data members of `rhs` to `*this`.
- 2 *Postconditions:*
- (2.1) — `eback() == rhs.eback()`
  - (2.2) — `gptr() == rhs.gptr()`
  - (2.3) — `egptr() == rhs.egptr()`
  - (2.4) — `pbase() == rhs.pbase()`
  - (2.5) — `pptr() == rhs.pptr()`
  - (2.6) — `epptr() == rhs.epptr()`
  - (2.7) — `getloc() == rhs.getloc()`
- 3 *Returns:* `*this`.

`void swap(basic_streambuf& rhs);`

- 4 *Effects:* Swaps the data members of `rhs` and `*this`.

#### 30.6.3.3.2 Get area access

[streambuf.get.area]

`char_type* eback() const;`

- 1 *Returns:* The beginning pointer for the input sequence.

`char_type* gptr() const;`

- 2 *Returns:* The next pointer for the input sequence.

`char_type* egptr() const;`

- 3 *Returns:* The end pointer for the input sequence.

```
void gbump(int n);
```

4     *Effects:* Adds `n` to the next pointer for the input sequence.

```
void setg(char_type* gbeg, char_type* gnext, char_type* gend);
```

5     *Postconditions:* `gbeg == eback()`, `gnext == gptr()`, and `gend == egptr()`.

### 30.6.3.3.3 Put area access

[streambuf.put.area]

```
char_type* pbase() const;
```

1     *Returns:* The beginning pointer for the output sequence.

```
char_type* pptr() const;
```

2     *Returns:* The next pointer for the output sequence.

```
char_type* epptr() const;
```

3     *Returns:* The end pointer for the output sequence.

```
void pbump(int n);
```

4     *Effects:* Adds `n` to the next pointer for the output sequence.

```
void setp(char_type* pbeg, char_type* pend);
```

5     *Postconditions:* `pbeg == pbase()`, `pbeg == pptr()`, and `pend == epptr()`.

### 30.6.3.4 basic\_streambuf virtual functions

[streambuf.virtuals]

#### 30.6.3.4.1 Locales

[streambuf.virt.locales]

```
void imbue(const locale&);
```

1     *Effects:* Change any translations based on locale.

2     *Remarks:* Allows the derived class to be informed of changes in locale at the time they occur. Between invocations of this function a class derived from `streambuf` can safely cache results of calls to locale functions and to members of facets so obtained.

3     *Default behavior:* Does nothing.

#### 30.6.3.4.2 Buffer management and positioning

[streambuf.virt.buffer]

```
basic_streambuf* setbuf(char_type* s, streamsize n);
```

1     *Effects:* Influences stream buffering in a way that is defined separately for each class derived from `basic_streambuf` in this Clause (30.8.2.4, 30.9.2.4).

2     *Default behavior:* Does nothing. Returns `this`.

```
pos_type seekoff(off_type off, ios_base::seekdir way,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
```

3     *Effects:* Alters the stream positions within one or more of the controlled sequences in a way that is defined separately for each class derived from `basic_streambuf` in this Clause (30.8.2.4, 30.9.2.4).

4     *Default behavior:* Returns `pos_type(off_type(-1))`.

```
pos_type seekpos(pos_type sp,
 ios_base::openmode which
 = ios_base::in | ios_base::out);
```



5 *Effects:* Alters the stream positions within one or more of the controlled sequences in a way that is defined separately for each class derived from `basic_streambuf` in this Clause (30.8.2, 30.9.2).

6 *Default behavior:* Returns `pos_type(off_type(-1))`.

`int sync();`

7 *Effects:* Synchronizes the controlled sequences with the arrays. That is, if `pbase()` is non-null the characters between `pbase()` and `pptr()` are written to the controlled sequence. The pointers may then be reset as appropriate.

8 *Returns:* `-1` on failure. What constitutes failure is determined by each derived class (30.9.2.4).

9 *Default behavior:* Returns zero.

### 30.6.3.4.3 Get area

[`streambuf.virt.get`]

`streamsize showmanyc();`<sup>300</sup>

1 *Returns:* An estimate of the number of characters available in the sequence, or `-1`. If it returns a positive value, then successive calls to `underflow()` will not return `traits::eof()` until at least that number of characters have been extracted from the stream. If `showmanyc()` returns `-1`, then calls to `underflow()` or `uflow()` will fail.<sup>301</sup>

2 *Default behavior:* Returns zero.

3 *Remarks:* Uses `traits::eof()`.

`streamsize xsgetn(char_type* s, streamsize n);`

4 *Effects:* Assigns up to `n` characters to successive elements of the array whose first element is designated by `s`. The characters assigned are read from the input sequence as if by repeated calls to `sbumpc()`. Assigning stops when either `n` characters have been assigned or a call to `sbumpc()` would return `traits::eof()`.

5 *Returns:* The number of characters assigned.<sup>302</sup>

6 *Remarks:* Uses `traits::eof()`.

`int_type underflow();`

7 *Remarks:* The public members of `basic_streambuf` call this virtual function only if `gptr()` is null or `gptr() >= egptr()`

8 *Returns:* `traits::to_int_type(c)`, where `c` is the first *character* of the *pending sequence*, without moving the input sequence position past it. If the pending sequence is null then the function returns `traits::eof()` to indicate failure.

9 The *pending sequence* of characters is defined as the concatenation of

(9.1) — the empty sequence if `gptr()` is null, otherwise the characters in `[gptr(), egptr())`, followed by

(9.2) — some (possibly empty) sequence of characters read from the input sequence.

10 The *result character* is the first character of the pending sequence if it is non-empty, otherwise the next character that would be read from the input sequence.

11 The *backup sequence* is the empty sequence if `eback()` is null, otherwise the characters in `[eback(), gptr())`.

300) The morphemes of `showmanyc` are “es-how-many-see”, not “show-manic”.

301) `underflow` or `uflow` might fail by throwing an exception prematurely. The intention is not only that the calls will not return `eof()` but that they will return “immediately”.

302) Classes derived from `basic_streambuf` can provide more efficient ways to implement `xsgetn()` and `xspn()` by overriding these definitions from the base class.

- 12 *Effects:* The function sets up the `gptr()` and `egptr()` such that if the pending sequence is non-empty, then `egptr()` is non-null and the characters in `[gptr(), egptr())` are the characters in the pending sequence, otherwise either `gptr()` is null or `gptr() == egptr()`.
- 13 If `eback()` and `gptr()` are non-null then the function is not constrained as to their contents, but the “usual backup condition” is that either
- (13.1) — the backup sequence contains at least `gptr() - eback()` characters, in which case the characters in `[eback(), gptr())` agree with the last `gptr() - eback()` characters of the backup sequence, or
- (13.2) — the characters in `[gptr() - n, gptr())` agree with the backup sequence (where `n` is the length of the backup sequence).
- 14 *Default behavior:* Returns `traits::eof()`.
- `int_type uflow();`
- 15 *Requires:* The constraints are the same as for `underflow()`, except that the result character shall be transferred from the pending sequence to the backup sequence, and the pending sequence shall not be empty before the transfer.
- 16 *Default behavior:* Calls `underflow()`. If `underflow()` returns `traits::eof()`, returns `traits::eof()`. Otherwise, returns the value of `traits::to_int_type(*gptr())` and increment the value of the next pointer for the input sequence.
- 17 *Returns:* `traits::eof()` to indicate failure.

#### 30.6.3.4.4 Putback

[`streambuf.virt.pback`]

`int_type pbackfail(int_type c = traits::eof());`

- 1 *Remarks:* The public functions of `basic_streambuf` call this virtual function only when `gptr()` is null, `gptr() == eback()`, or `traits::eq(traits::to_char_type(c), gptr()[-1])` returns `false`. Other calls shall also satisfy that constraint.
- The *pending sequence* is defined as for `underflow()`, with the modifications that
- (1.1) — If `traits::eq_int_type(c, traits::eof())` returns `true`, then the input sequence is backed up one character before the pending sequence is determined.
- (1.2) — If `traits::eq_int_type(c, traits::eof())` returns `false`, then `c` is prepended. Whether the input sequence is backed up or modified in any other way is unspecified.
- 2 *Postconditions:* On return, the constraints of `gptr()`, `eback()`, and `pptr()` are the same as for `underflow()`.
- 3 *Returns:* `traits::eof()` to indicate failure. Failure may occur because the input sequence could not be backed up, or if for some other reason the pointers could not be set consistent with the constraints. `pbackfail()` is called only when put back has really failed.
- 4 Returns some value other than `traits::eof()` to indicate success.
- 5 *Default behavior:* Returns `traits::eof()`.

#### 30.6.3.4.5 Put area

[`streambuf.virt.put`]

`streamsize xsputn(const char_type* s, streamsize n);`

- 1 *Effects:* Writes up to `n` characters to the output sequence as if by repeated calls to `sputc(c)`. The characters written are obtained from successive elements of the array whose first element is designated by `s`. Writing stops when either `n` characters have been written or a call to `sputc(c)` would return

`traits::eof()`. It is unspecified whether the function calls `overflow()` when `pptr() == eptr()` becomes `true` or whether it achieves the same effects by other means.

2 *Returns:* The number of characters written.

`int_type overflow(int_type c = traits::eof());`

3 *Effects:* Consumes some initial subsequence of the characters of the *pending sequence*. The pending sequence is defined as the concatenation of

(3.1) — the empty sequence if `pbase()` is not null, otherwise the `pptr() - pbase()` characters beginning at `pbase()`, followed by

(3.2) — the empty sequence if `traits::eq_int_type(c, traits::eof())` returns `true`, otherwise the sequence consisting of `c`.

4 *Remarks:* The member functions `sputc()` and `sputn()` call this function in case that no room can be found in the put buffer enough to accommodate the argument character sequence.

5 *Requires:* Every overriding definition of this virtual function shall obey the following constraints:

1. The effect of consuming a character on the associated output sequence is specified<sup>303</sup>
2. Let `r` be the number of characters in the pending sequence not consumed. If `r` is nonzero then `pbase()` and `pptr()` shall be set so that: `pptr() - pbase() == r` and the `r` characters starting at `pbase()` are the associated output stream. In case `r` is zero (all characters of the pending sequence have been consumed) then either `pbase()` is set to `nullptr`, or `pbase()` and `pptr()` are both set to the same non-null value.
3. The function may fail if either appending some character to the associated output stream fails or if it is unable to establish `pbase()` and `pptr()` according to the above rules.

6 *Returns:* `traits::eof()` or throws an exception if the function fails.

Otherwise, returns some value other than `traits::eof()` to indicate success.<sup>304</sup>

7 *Default behavior:* Returns `traits::eof()`.

## 30.7 Formatting and manipulators

[*iostream.format*]

### 30.7.1 Header `<istream>` synopsis

[*istream.syn*]

```
namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_istream;

 using istream = basic_istream<char>;
 using wistream = basic_istream<wchar_t>;

 template <class charT, class traits = char_traits<charT>>
 class basic_iostream;

 using iostream = basic_iostream<char>;
 using wiostream = basic_iostream<wchar_t>;

 template <class charT, class traits>
 basic_istream<charT, traits>& ws(basic_istream<charT, traits>& is);
```

303) That is, for each class derived from an instance of `basic_streambuf` in this Clause (30.8.2, 30.9.2), a specification of how consuming a character effects the associated output sequence is given. There is no requirement on a program-defined class.

304) Typically, `overflow` returns `c` to indicate success, except when `traits::eq_int_type(c, traits::eof())` returns `true`, in which case it returns `traits::not_eof(c)`.

```

 template <class charT, class traits, class T>
 basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>&& is, T&& x);
}

```

### 30.7.2 Header <ostream> synopsis

[ostream.syn]

```

namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_ostream;

 using ostream = basic_ostream<char>;
 using wostream = basic_ostream<wchar_t>;

 template <class charT, class traits>
 basic_ostream<charT, traits>& endl(basic_ostream<charT, traits>& os);
 template <class charT, class traits>
 basic_ostream<charT, traits>& ends(basic_ostream<charT, traits>& os);
 template <class charT, class traits>
 basic_ostream<charT, traits>& flush(basic_ostream<charT, traits>& os);

 template <class charT, class traits, class T>
 basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&& os, const T& x);
}

```

### 30.7.3 Header <iomanip> synopsis

[iomanip.syn]

```

namespace std {
 // types T1, T2, ... are unspecified implementation types
 T1 resetiosflags(ios_base::fmtflags mask);
 T2 setiosflags (ios_base::fmtflags mask);
 T3 setbase(int base);
 template<charT> T4 setfill(charT c);
 T5 setprecision(int n);
 T6 setw(int n);
 template <class moneyT> T7 get_money(moneyT& mon, bool intl = false);
 template <class moneyT> T8 put_money(const moneyT& mon, bool intl = false);
 template <class charT> T9 get_time(struct tm* tmb, const charT* fmt);
 template <class charT> T10 put_time(const struct tm* tmb, const charT* fmt);

 template <class charT>
 T11 quoted(const charT* s, charT delim = charT('"'), charT escape = charT('\\'));

 template <class charT, class traits, class Allocator>
 T12 quoted(const basic_string<charT, traits, Allocator>& s,
 charT delim = charT('"'), charT escape = charT('\\'));

 template <class charT, class traits, class Allocator>
 T13 quoted(basic_string<charT, traits, Allocator>& s,
 charT delim = charT('"'), charT escape = charT('\\'));

 template <class charT, class traits>
 T14 quoted(basic_string_view<charT, traits> s,
 charT delim = charT('"'), charT escape = charT('\\'));
}

```

### 30.7.4 Input streams

[input.streams]

- <sup>1</sup> The header <istream> defines two types and a function signature that control input from a stream buffer along with a function template that extracts from stream rvalues.

#### 30.7.4.1 Class template basic\_istream

[istream]

```

namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_istream : virtual public basic_ios<charT, traits> {
 public:
 // types (inherited from basic_ios (30.5.5)):
 using char_type = charT;
 using int_type = typename traits::int_type;
 using pos_type = typename traits::pos_type;
 using off_type = typename traits::off_type;
 using traits_type = traits;

 // 30.7.4.1.1, constructor/destructor
 explicit basic_istream(basic_streambuf<charT, traits>* sb);
 virtual ~basic_istream();

 // 30.7.4.1.3, prefix/suffix
 class sentry;

 // 30.7.4.2, formatted input
 basic_istream<charT, traits>&
 operator>>(basic_istream<charT, traits>& (*pf)(basic_istream<charT, traits>&));
 basic_istream<charT, traits>&
 operator>>(basic_ios<charT, traits>& (*pf)(basic_ios<charT, traits>&));
 basic_istream<charT, traits>&
 operator>>(ios_base& (*pf)(ios_base&));

 basic_istream<charT, traits>& operator>>(bool& n);
 basic_istream<charT, traits>& operator>>(short& n);
 basic_istream<charT, traits>& operator>>(unsigned short& n);
 basic_istream<charT, traits>& operator>>(int& n);
 basic_istream<charT, traits>& operator>>(unsigned int& n);
 basic_istream<charT, traits>& operator>>(long& n);
 basic_istream<charT, traits>& operator>>(unsigned long& n);
 basic_istream<charT, traits>& operator>>(long long& n);
 basic_istream<charT, traits>& operator>>(unsigned long long& n);
 basic_istream<charT, traits>& operator>>(float& f);
 basic_istream<charT, traits>& operator>>(double& f);
 basic_istream<charT, traits>& operator>>(long double& f);

 basic_istream<charT, traits>& operator>>(void*& p);
 basic_istream<charT, traits>& operator>>(basic_streambuf<char_type, traits>* sb);

 // 30.7.4.3, unformatted input
 streamsize gcount() const;
 int_type get();
 basic_istream<charT, traits>& get(char_type& c);
 basic_istream<charT, traits>& get(char_type* s, streamsize n);
 basic_istream<charT, traits>& get(char_type* s, streamsize n, char_type delim);
 basic_istream<charT, traits>& get(basic_streambuf<char_type, traits>& sb);
 basic_istream<charT, traits>& get(basic_streambuf<char_type, traits>& sb, char_type delim);
 };
}

```

```

 basic_istream<charT, traits>& getline(char_type* s, streamsize n);
 basic_istream<charT, traits>& getline(char_type* s, streamsize n, char_type delim);

 basic_istream<charT, traits>& ignore(streamsize n = 1, int_type delim = traits::eof());
 int_type peek();
 basic_istream<charT, traits>& read (char_type* s, streamsize n);
 streamsize readsome(char_type* s, streamsize n);

 basic_istream<charT, traits>& putback(char_type c);
 basic_istream<charT, traits>& unget();
 int sync();

 pos_type tellg();
 basic_istream<charT, traits>& seekg(pos_type);
 basic_istream<charT, traits>& seekg(off_type, ios_base::seekdir);

protected:
 // 30.7.4.1.1, copy/move constructor
 basic_istream(const basic_istream& rhs) = delete;
 basic_istream(basic_istream&& rhs);

 // 30.7.4.1.2, assign and swap
 basic_istream& operator=(const basic_istream& rhs) = delete;
 basic_istream& operator=(basic_istream&& rhs);
 void swap(basic_istream& rhs);
};

// 30.7.4.2.3, character extraction templates
template<class charT, class traits>
 basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>&, charT&);
template<class traits>
 basic_istream<char, traits>& operator>>(basic_istream<char, traits>&, unsigned char&);
template<class traits>
 basic_istream<char, traits>& operator>>(basic_istream<char, traits>&, signed char&);

template<class charT, class traits>
 basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>&, charT*);
template<class traits>
 basic_istream<char, traits>& operator>>(basic_istream<char, traits>&, unsigned char*);
template<class traits>
 basic_istream<char, traits>& operator>>(basic_istream<char, traits>&, signed char*);
}

```

- <sup>1</sup> The class template `basic_istream` defines a number of member function signatures that assist in reading and interpreting input from sequences controlled by a stream buffer.
- <sup>2</sup> Two groups of member function signatures share common properties: the *formatted input functions* (or *extractors*) and the *unformatted input functions*. Both groups of input functions are described as if they obtain (or *extract*) input *characters* by calling `rdbuf()->sbumpc()` or `rdbuf()->sgetc()`. They may use other public members of `istream`.
- <sup>3</sup> If `rdbuf()->sbumpc()` or `rdbuf()->sgetc()` returns `traits::eof()`, then the input function, except as explicitly noted otherwise, completes its actions and does `setstate(eofbit)`, which may throw `ios_base::failure` (30.5.5.4), before returning.

- <sup>4</sup> If one of these called functions throws an exception, then unless explicitly noted otherwise, the input function sets `badbit` in error state. If `badbit` is on in `exceptions()`, the input function rethrows the exception without completing its actions, otherwise it does not throw anything and proceeds as if the called function had returned a failure indication.

#### 30.7.4.1.1 `basic_istream` constructors

[istream.cons]

```
explicit basic_istream(basic_streambuf<charT, traits>* sb);
```

- <sup>1</sup> *Effects:* Constructs an object of class `basic_istream`, initializing the base class subobject with `basic_ios::init(sb)` (30.5.5.2).
- <sup>2</sup> *Postconditions:* `gcount() == 0`.

```
basic_istream(basic_istream&& rhs);
```

- <sup>3</sup> *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by default constructing the base class, copying the `gcount()` from `rhs`, calling `basic_ios<charT, traits>::move(rhs)` to initialize the base class, and setting the `gcount()` for `rhs` to 0.

```
virtual ~basic_istream();
```

- <sup>4</sup> *Effects:* Destroys an object of class `basic_istream`.
- <sup>5</sup> *Remarks:* Does not perform any operations of `rdbuf()`.

#### 30.7.4.1.2 Class `basic_istream` assign and swap

[istream.assign]

```
basic_istream& operator=(basic_istream&& rhs);
```

- <sup>1</sup> *Effects:* As if by `swap(rhs)`.
- <sup>2</sup> *Returns:* `*this`.

```
void swap(basic_istream& rhs);
```

- <sup>3</sup> *Effects:* Calls `basic_ios<charT, traits>::swap(rhs)`. Exchanges the values returned by `gcount()` and `rhs.gcount()`.

#### 30.7.4.1.3 Class `basic_istream::sentry`

[istream::sentry]

```
namespace std {
 template <class charT, class traits = char_traits<charT>>
 class basic_istream<charT, traits>::sentry {
 using traits_type = traits;
 bool ok_; // exposition only
 public:
 explicit sentry(basic_istream<charT, traits>& is, bool noskipws = false);
 ~sentry();
 explicit operator bool() const { return ok_; }
 sentry(const sentry&) = delete;
 sentry& operator=(const sentry&) = delete;
 };
}
```

- <sup>1</sup> The class `sentry` defines a class that is responsible for doing exception safe prefix and suffix operations.

```
explicit sentry(basic_istream<charT, traits>& is, bool noskipws = false);
```

- <sup>2</sup> *Effects:* If `is.good()` is false, calls `is.setstate(failbit)`. Otherwise, prepares for formatted or unformatted input. First, if `is.tie()` is not a null pointer, the function calls `is.tie()->flush()` to synchronize the output sequence with any associated external C stream. Except that this call

can be suppressed if the put area of `is.tie()` is empty. Further an implementation is allowed to defer the call to `flush` until a call of `is.rdbuf()->underflow()` occurs. If no such call occurs before the `sentry` object is destroyed, the call to `flush` may be eliminated entirely.<sup>305</sup> If `noskipws` is zero and `is.flags() & ios_base::skipws` is nonzero, the function extracts and discards each character as long as the next available input character `c` is a whitespace character. If `is.rdbuf()->sbumpc()` or `is.rdbuf()->sgetc()` returns `traits::eof()`, the function calls `setstate(failbit | eofbit)` (which may throw `ios_base::failure`).

3 *Remarks:* The constructor

```
explicit sentry(basic_istream<charT, traits>& is, bool noskipws = false)
```

uses the currently imbued locale in `is`, to determine whether the next input character is whitespace or not.

4 To decide if the character `c` is a whitespace character, the constructor performs as if it executes the following code fragment:

```
const ctype<charT>& ctype = use_facet<ctype<charT>>(is.getloc());
if (ctype.is(ctype.space, c) != 0)
 // c is a whitespace character.
```

5 If, after any preparation is completed, `is.good()` is `true`, `ok_ != false` otherwise, `ok_ == false`. During preparation, the constructor may call `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4))<sup>306</sup>

```
~sentry();
```

6 *Effects:* None.

```
explicit operator bool() const;
```

7 *Effects:* Returns `ok_`.

### 30.7.4.2 Formatted input functions

[istream.formatted]

#### 30.7.4.2.1 Common requirements

[istream.formatted.reqmts]

1 Each formatted input function begins execution by constructing an object of class `sentry` with the `noskipws` (second) argument `false`. If the `sentry` object returns `true`, when converted to a value of type `bool`, the function endeavors to obtain the requested input. If an exception is thrown during input then `ios::badbit` is turned on<sup>307</sup> in `*this`'s error state. If `(exceptions()&badbit) != 0` then the exception is rethrown. In any case, the formatted input function destroys the `sentry` object. If no exception has been thrown, it returns `*this`.

#### 30.7.4.2.2 Arithmetic extractors

[istream.formatted.arithmetic]

```
operator>>(unsigned short& val);
operator>>(unsigned int& val);
operator>>(long& val);
operator>>(unsigned long& val);
operator>>(long long& val);
operator>>(unsigned long long& val);
operator>>(float& val);
operator>>(double& val);
operator>>(long double& val);
```

305) This will be possible only in functions that are part of the library. The semantics of the constructor used in user code is as specified.

306) The `sentry` constructor and destructor can also perform additional implementation-dependent operations.

307) This is done without causing an `ios::failure` to be thrown.



```
operator>>(bool& val);
operator>>(void*& val);
```

- 1 As in the case of the inserters, these extractors depend on the locale's `num_get<>` (25.4.2.1) object to perform parsing the input stream data. These extractors behave as formatted input functions (as described in 30.7.4.2.1). After a sentry object is constructed, the conversion occurs as if performed by the following code fragment:

```
using numget = num_get<charT, istreambuf_iterator<charT, traits>>;
iostate err = iostate::goodbit;
use_facet<numget>(loc).get(*this, 0, *this, err, val);
setstate(err);
```

In the above fragment, `loc` stands for the private member of the `basic_ios` class. [Note: The first argument provides an object of the `istreambuf_iterator` class which is an iterator pointed to an input stream. It bypasses istreams and uses streambufs directly. — end note] Class `locale` relies on this type as its interface to `istream`, so that it does not need to depend directly on `istream`.

```
operator>>(short& val);
```

- 2 The conversion occurs as if performed by the following code fragment (using the same notation as for the preceding code fragment):

```
using numget = num_get<charT, istreambuf_iterator<charT, traits>>;
iostate err = ios_base::goodbit;
long lval;
use_facet<numget>(loc).get(*this, 0, *this, err, lval);
if (lval < numeric_limits<short>::min()) {
 err |= ios_base::failbit;
 val = numeric_limits<short>::min();
} else if (numeric_limits<short>::max() < lval) {
 err |= ios_base::failbit;
 val = numeric_limits<short>::max();
} else
 val = static_cast<short>(lval);
setstate(err);
```

```
operator>>(int& val);
```

- 3 The conversion occurs as if performed by the following code fragment (using the same notation as for the preceding code fragment):

```
using numget = num_get<charT, istreambuf_iterator<charT, traits>>;
iostate err = ios_base::goodbit;
long lval;
use_facet<numget>(loc).get(*this, 0, *this, err, lval);
if (lval < numeric_limits<int>::min()) {
 err |= ios_base::failbit;
 val = numeric_limits<int>::min();
} else if (numeric_limits<int>::max() < lval) {
 err |= ios_base::failbit;
 val = numeric_limits<int>::max();
} else
 val = static_cast<int>(lval);
setstate(err);
```

### 30.7.4.2.3 `basic_istream::operator>>`

[istream.extractors]

```
basic_istream<charT, traits>&
```

```
operator>>(basic_istream<charT, traits>& (*pf)(basic_istream<charT, traits>&));
```

1 *Effects:* None. This extractor does not behave as a formatted input function (as described in 30.7.4.2.1).

2 *Returns:* pf(\*this).<sup>308</sup>

```
basic_istream<charT, traits>&
```

```
operator>>(basic_ios<charT, traits>& (*pf)(basic_ios<charT, traits>&));
```

3 *Effects:* Calls pf(\*this). This extractor does not behave as a formatted input function (as described in 30.7.4.2.1).

4 *Returns:* \*this.

```
basic_istream<charT, traits>& operator>>(ios_base& (*pf)(ios_base&));
```

5 *Effects:* Calls pf(\*this).<sup>309</sup> This extractor does not behave as a formatted input function (as described in 30.7.4.2.1).

6 *Returns:* \*this.

```
template<class charT, class traits>
```

```
basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>& in, charT* s);
```

```
template<class traits>
```

```
basic_istream<char, traits>& operator>>(basic_istream<char, traits>& in, unsigned char* s);
```

```
template<class traits>
```

```
basic_istream<char, traits>& operator>>(basic_istream<char, traits>& in, signed char* s);
```

7 *Effects:* Behaves like a formatted input member (as described in 30.7.4.2.1) of in. After a sentry object is constructed, operator>> extracts characters and stores them into successive locations of an array whose first element is designated by s. If width() is greater than zero, n is width(). Otherwise n is the number of elements of the largest array of char\_type that can store a terminating charT(). n is the maximum number of characters stored.

8 Characters are extracted and stored until any of the following occurs:

(8.1) — n-1 characters are stored;

(8.2) — end of file occurs on the input sequence;

(8.3) — letting ct be use\_facet<ctype<charT>>(in.getloc()), ct.is(ct.space, c) is true.

9 operator>> then stores a null byte (charT()) in the next position, which may be the first position if no characters were extracted. operator>> then calls width(0).

10 If the function extracted no characters, it calls setstate(failbit), which may throw ios\_base::failure (30.5.5.4).

11 *Returns:* in.

```
template<class charT, class traits>
```

```
basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>& in, charT& c);
```

```
template<class traits>
```

```
basic_istream<char, traits>& operator>>(basic_istream<char, traits>& in, unsigned char& c);
```

```
template<class traits>
```

```
basic_istream<char, traits>& operator>>(basic_istream<char, traits>& in, signed char& c);
```

12 *Effects:* Behaves like a formatted input member (as described in 30.7.4.2.1) of in. After a sentry object is constructed a character is extracted from in, if one is available, and stored in c. Otherwise, the function calls in.setstate(failbit).

308) See, for example, the function signature ws(basic\_istream&) (30.7.4.4).

309) See, for example, the function signature dec(ios\_base&) (30.5.6.3).

13 *Returns:* in.

```
basic_istream<charT, traits>& operator>>(basic_streambuf<charT, traits>* sb);
```

14 *Effects:* Behaves as an unformatted input function (30.7.4.3). If *sb* is null, calls `setstate(failbit)`, which may throw `ios_base::failure` (30.5.5.4). After a sentry object is constructed, extracts characters from *\*this* and inserts them in the output sequence controlled by *sb*. Characters are extracted and inserted until any of the following occurs:

(14.1) — end-of-file occurs on the input sequence;

(14.2) — inserting in the output sequence fails (in which case the character to be inserted is not extracted);

(14.3) — an exception occurs (in which case the exception is caught).

15 If the function inserts no characters, it calls `setstate(failbit)`, which may throw `ios_base::failure` (30.5.5.4). If it inserted no characters because it caught an exception thrown while extracting characters from *\*this* and `failbit` is on in `exceptions()` (30.5.5.4), then the caught exception is rethrown.

16 *Returns:* *\*this*.

### 30.7.4.3 Unformatted input functions

[istream.unformatted]

1 Each unformatted input function begins execution by constructing an object of class `sentry` with the default argument `noskipws` (second) argument `true`. If the `sentry` object returns `true`, when converted to a value of type `bool`, the function endeavors to obtain the requested input. Otherwise, if the `sentry` constructor exits by throwing an exception or if the `sentry` object returns `false`, when converted to a value of type `bool`, the function returns without attempting to obtain any input. In either case the number of extracted characters is set to 0; unformatted input functions taking a character array of nonzero size as an argument shall also store a null character (using `charT()`) in the first location of the array. If an exception is thrown during input then `ios::badbit` is turned on<sup>310</sup> in *\*this*'s error state. (Exceptions thrown from `basic_ios<>::clear()` are not caught or rethrown.) If `(exceptions() & badbit) != 0` then the exception is rethrown. It also counts the number of characters extracted. If no exception has been thrown it ends by storing the count in a member object and returning the value specified. In any event the `sentry` object is destroyed before leaving the unformatted input function.

```
streamsize gcount() const;
```

2 *Effects:* None. This member function does not behave as an unformatted input function (as described above).

3 *Returns:* The number of characters extracted by the last unformatted input member function called for the object.

```
int_type get();
```

4 *Effects:* Behaves as an unformatted input function (as described above). After constructing a `sentry` object, extracts a character *c*, if one is available. Otherwise, the function calls `setstate(failbit)`, which may throw `ios_base::failure` (30.5.5.4),

5 *Returns:* *c* if available, otherwise `traits::eof()`.

```
basic_istream<charT, traits>& get(char_type& c);
```

6 *Effects:* Behaves as an unformatted input function (as described above). After constructing a `sentry` object, extracts a character, if one is available, and assigns it to *c*.<sup>311</sup> Otherwise, the function calls `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4)).

310) This is done without causing an `ios::failure` to be thrown.

311) Note that this function is not overloaded on types `signed char` and `unsigned char`.

7 *Returns: \*this.*

```
basic_istream<charT, traits>& get(char_type* s, streamsize n, char_type delim);
```

8 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, extracts characters and stores them into successive locations of an array whose first element is designated by *s*.<sup>312</sup> Characters are extracted and stored until any of the following occurs:

- (8.1) — *n* is less than one or *n* - 1 characters are stored;
- (8.2) — end-of-file occurs on the input sequence (in which case the function calls `setstate(eofbit)`);
- (8.3) — `traits::eq(c, delim)` for the next available input character *c* (in which case *c* is not extracted).

9 If the function stores no characters, it calls `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4)). In any case, if *n* is greater than zero it then stores a null character into the next successive location of the array.

10 *Returns: \*this.*

```
basic_istream<charT, traits>& get(char_type* s, streamsize n);
```

11 *Effects:* Calls `get(s, n, widen('\n'))`.

12 *Returns:* Value returned by the call.

```
basic_istream<charT, traits>& get(basic_streambuf<char_type, traits>& sb, char_type delim);
```

13 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, extracts characters and inserts them in the output sequence controlled by *sb*. Characters are extracted and inserted until any of the following occurs:

- (13.1) — end-of-file occurs on the input sequence;
- (13.2) — inserting in the output sequence fails (in which case the character to be inserted is not extracted);
- (13.3) — `traits::eq(c, delim)` for the next available input character *c* (in which case *c* is not extracted);
- (13.4) — an exception occurs (in which case, the exception is caught but not rethrown).

14 If the function inserts no characters, it calls `setstate(failbit)`, which may throw `ios_base::failure` (30.5.5.4).

15 *Returns: \*this.*

```
basic_istream<charT, traits>& get(basic_streambuf<char_type, traits>& sb);
```

16 *Effects:* Calls `get(sb, widen('\n'))`.

17 *Returns:* Value returned by the call.

```
basic_istream<charT, traits>& getline(char_type* s, streamsize n, char_type delim);
```

18 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, extracts characters and stores them into successive locations of an array whose first element is designated by *s*.<sup>313</sup> Characters are extracted and stored until one of the following occurs:

1. end-of-file occurs on the input sequence (in which case the function calls `setstate(eofbit)`);
2. `traits::eq(c, delim)` for the next available input character *c* (in which case the input character is extracted but not stored);<sup>314</sup>
3. *n* is less than one or *n* - 1 characters are stored (in which case the function calls `setstate(`

312) Note that this function is not overloaded on types `signed char` and `unsigned char`.

313) Note that this function is not overloaded on types `signed char` and `unsigned char`.

314) Since the final input character is “extracted”, it is counted in the `gcount()`, even though it is not stored.

failbit)).

19 These conditions are tested in the order shown.<sup>315</sup>

20 If the function extracts no characters, it calls `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4)).<sup>316</sup>

21 In any case, if `n` is greater than zero, it then stores a null character (using `charT()`) into the next successive location of the array.

22 *Returns:* `*this`.

23 [*Example:*

```
#include <iostream>

int main() {
 using namespace std;
 const int line_buffer_size = 100;

 char buffer[line_buffer_size];
 int line_number = 0;
 while (cin.getline(buffer, line_buffer_size, '\n') || cin.gcount()) {
 int count = cin.gcount();
 if (cin.eof())
 cout << "Partial final line"; // cin.fail() is false
 else if (cin.fail()) {
 cout << "Partial long line";
 cin.clear(cin.rdstate() & ~ios_base::failbit);
 } else {
 count--; // Don't include newline in count
 cout << "Line " << ++line_number;
 }
 cout << " (" << count << " chars): " << buffer << endl;
 }
}
```

— end example]

`basic_istream<charT, traits>& getline(char_type* s, streamsize n);`

24 *Returns:* `getline(s, n, widen('\n'))`

`basic_istream<charT, traits>& ignore(streamsize n = 1, int_type delim = traits::eof());`

25 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, extracts characters and discards them. Characters are extracted until any of the following occurs:

- (25.1) — `n != numeric_limits<streamsize>::max()` (21.3.4) and `n` characters have been extracted so far
- (25.2) — end-of-file occurs on the input sequence (in which case the function calls `setstate eofbit`), which may throw `ios_base::failure` (30.5.5.4));
- (25.3) — `traits::eq_int_type(traits::to_int_type(c), delim)` for the next available input character `c` (in which case `c` is extracted).

315) This allows an input line which exactly fills the buffer, without setting `failbit`. This is different behavior than the historical AT&T implementation.

316) This implies an empty input line will not cause `failbit` to be set.

26 *Remarks:* The last condition will never occur if `traits::eq_int_type(delim, traits::eof())`.

27 *Returns:* `*this`.

`int_type peek();`

28 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, reads but does not extract the current input character.

29 *Returns:* `traits::eof()` if `good()` is `false`. Otherwise, returns `rdbuf()->sgetc()`.

`basic_istream<charT, traits>& read(char_type* s, streamsize n);`

30 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, if `!good()` calls `setstate(failbit)` which may throw an exception, and return. Otherwise extracts characters and stores them into successive locations of an array whose first element is designated by `s`.<sup>317</sup> Characters are extracted and stored until either of the following occurs:

(30.1) — `n` characters are stored;

(30.2) — end-of-file occurs on the input sequence (in which case the function calls `setstate(failbit | eofbit)`, which may throw `ios_base::failure` (30.5.5.4)).

31 *Returns:* `*this`.

`streamsize readsome(char_type* s, streamsize n);`

32 *Effects:* Behaves as an unformatted input function (as described above). After constructing a sentry object, if `!good()` calls `setstate(failbit)` which may throw an exception, and return. Otherwise extracts characters and stores them into successive locations of an array whose first element is designated by `s`. If `rdbuf()->in_avail() == -1`, calls `setstate(eofbit)` (which may throw `ios_base::failure` (30.5.5.4)), and extracts no characters;

(32.1) — If `rdbuf()->in_avail() == 0`, extracts no characters

(32.2) — If `rdbuf()->in_avail() > 0`, extracts `min(rdbuf()->in_avail(), n)`.

33 *Returns:* The number of characters extracted.

`basic_istream<charT, traits>& putback(char_type c);`

34 *Effects:* Behaves as an unformatted input function (as described above), except that the function first clears `eofbit`. After constructing a sentry object, if `!good()` calls `setstate(failbit)` which may throw an exception, and return. If `rdbuf()` is not null, calls `rdbuf()->sputbackc()`. If `rdbuf()` is null, or if `sputbackc()` returns `traits::eof()`, calls `setstate(badbit)` (which may throw `ios_base::failure` (30.5.5.4)). [ *Note:* This function extracts no characters, so the value returned by the next call to `gcount()` is 0. — *end note* ]

35 *Returns:* `*this`.

`basic_istream<charT, traits>& unget();`

36 *Effects:* Behaves as an unformatted input function (as described above), except that the function first clears `eofbit`. After constructing a sentry object, if `!good()` calls `setstate(failbit)` which may throw an exception, and return. If `rdbuf()` is not null, calls `rdbuf()->sungetc()`. If `rdbuf()` is null, or if `sungetc()` returns `traits::eof()`, calls `setstate(badbit)` (which may throw `ios_base::failure` (30.5.5.4)). [ *Note:* This function extracts no characters, so the value returned by the next call to `gcount()` is 0. — *end note* ]

37 *Returns:* `*this`.

317) Note that this function is not overloaded on types `signed char` and `unsigned char`.

```
int sync();
```

- 38 *Effects:* Behaves as an unformatted input function (as described above), except that it does not count the number of characters extracted and does not affect the value returned by subsequent calls to `gcount()`. After constructing a sentry object, if `rdbuf()` is a null pointer, returns `-1`. Otherwise, calls `rdbuf()->pubsync()` and, if that function returns `-1` calls `setstate(badbit)` (which may throw `ios_base::failure` (30.5.5.4), and returns `-1`. Otherwise, returns zero.

```
pos_type tellg();
```

- 39 *Effects:* Behaves as an unformatted input function (as described above), except that it does not count the number of characters extracted and does not affect the value returned by subsequent calls to `gcount()`.
- 40 *Returns:* After constructing a sentry object, if `fail() != false`, returns `pos_type(-1)` to indicate failure. Otherwise, returns `rdbuf()->pubseekoff(0, cur, in)`.

```
basic_istream<charT, traits>& seekg(pos_type pos);
```

- 41 *Effects:* Behaves as an unformatted input function (as described above), except that the function first clears `eofbit`, it does not count the number of characters extracted, and it does not affect the value returned by subsequent calls to `gcount()`. After constructing a sentry object, if `fail() != true`, executes `rdbuf()->pubseekpos(pos, ios_base::in)`. In case of failure, the function calls `setstate(failbit)` (which may throw `ios_base::failure`).
- 42 *Returns:* `*this`.

```
basic_istream<charT, traits>& seekg(off_type off, ios_base::seekdir dir);
```

- 43 *Effects:* Behaves as an unformatted input function (as described above), except that the function first clears `eofbit`, does not count the number of characters extracted, and does not affect the value returned by subsequent calls to `gcount()`. After constructing a sentry object, if `fail() != true`, executes `rdbuf()->pubseekoff(off, dir, ios_base::in)`. In case of failure, the function calls `setstate(failbit)` (which may throw `ios_base::failure`).
- 44 *Returns:* `*this`.

#### 30.7.4.4 Standard `basic_istream` manipulators

[istream.manip]

```
template <class charT, class traits>
```

```
 basic_istream<charT, traits>& ws(basic_istream<charT, traits>& is);
```

- 1 *Effects:* Behaves as an unformatted input function (30.7.4.3), except that it does not count the number of characters extracted and does not affect the value returned by subsequent calls to `is.gcount()`. After constructing a sentry object extracts characters as long as the next available character `c` is whitespace or until there are no more characters in the sequence. Whitespace characters are distinguished with the same criterion as used by `sentry::sentry` (30.7.4.1.3). If `ws` stops extracting characters because there are no more available it sets `eofbit`, but not `failbit`.
- 2 *Returns:* `is`.

#### 30.7.4.5 Rvalue stream extraction

[istream.rvalue]

```
template <class charT, class traits, class T>
```

```
 basic_istream<charT, traits>& operator>>(basic_istream<charT, traits>&& is, T&& x);
```

- 1 *Effects:* Equivalent to:
- ```
    is >> std::forward<T>(x);
    return is;
```

- ² *Remarks:* This function shall not participate in overload resolution unless the expression `is >> std::forward<T>(x)` is well-formed.

30.7.4.6 Class template `basic_iostream`

[iostreamclass]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_iostream
        : public basic_istream<charT, traits>,
          public basic_ostream<charT, traits> {
    public:
        using char_type      = charT;
        using int_type        = typename traits::int_type;
        using pos_type        = typename traits::pos_type;
        using off_type        = typename traits::off_type;
        using traits_type     = traits;

        // 30.7.4.6.1, constructor
        explicit basic_iostream(basic_streambuf<charT, traits>* sb);

        // 30.7.4.6.2, destructor
        virtual ~basic_iostream();

    protected:
        // 30.7.4.6.1, constructor
        basic_iostream(const basic_iostream& rhs) = delete;
        basic_iostream(basic_iostream&& rhs);

        // 30.7.4.6.3, assign and swap
        basic_iostream& operator=(const basic_iostream& rhs) = delete;
        basic_iostream& operator=(basic_iostream&& rhs);
        void swap(basic_iostream& rhs);
    };
}
```

- ¹ The class template `basic_iostream` inherits a number of functions that allow reading input and writing output to sequences controlled by a stream buffer.

30.7.4.6.1 `basic_iostream` constructors

[iostream.cons]

```
explicit basic_iostream(basic_streambuf<charT, traits>* sb);
```

- ¹ *Effects:* Constructs an object of class `basic_iostream`, initializing the base class subobjects with `basic_istream<charT, traits>(sb)` (30.7.4.1) and `basic_ostream<charT, traits>(sb)` (30.7.5.1).
- ² *Postconditions:* `rdbuf()` == `sb` and `gcount()` == 0.

```
basic_iostream(basic_iostream&& rhs);
```

- ³ *Effects:* Move constructs from the rvalue `rhs` by constructing the `basic_istream` base class with `move(rhs)`.

30.7.4.6.2 `basic_iostream` destructor

[iostream.dest]

```
virtual ~basic_iostream();
```

- ¹ *Effects:* Destroys an object of class `basic_iostream`.
- ² *Remarks:* Does not perform any operations on `rdbuf()`.

30.7.4.6.3 basic_ostream assign and swap

[iostream.assign]

```
basic_ostream& operator=(basic_ostream&& rhs);
```

1 *Effects:* As if by `swap(rhs)`.

```
void swap(basic_ostream& rhs);
```

2 *Effects:* Calls `basic_istream<charT, traits>::swap(rhs)`.

30.7.5 Output streams

[output.streams]

1 The header `<ostream>` defines a type and several function signatures that control output to a stream buffer along with a function template that inserts into stream rvalues.

30.7.5.1 Class template basic_ostream

[ostream]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_ostream : virtual public basic_ios<charT, traits> {
    public:
        // types (inherited from basic_ios (30.5.5)):
        using char_type    = charT;
        using int_type     = typename traits::int_type;
        using pos_type     = typename traits::pos_type;
        using off_type     = typename traits::off_type;
        using traits_type  = traits;

        // 30.7.5.1.1, constructor/destructor
        explicit basic_ostream(basic_streambuf<char_type, traits>* sb);
        virtual ~basic_ostream();

        // 30.7.5.1.3, prefix/suffix
        class sentry;

        // 30.7.5.2, formatted output
        basic_ostream<charT, traits>&
            operator<<(basic_ostream<charT, traits>& (*pf)(basic_ostream<charT, traits>&));
        basic_ostream<charT, traits>&
            operator<<(basic_ios<charT, traits>& (*pf)(basic_ios<charT, traits>&));
        basic_ostream<charT, traits>&
            operator<<(ios_base& (*pf)(ios_base&));

        basic_ostream<charT, traits>& operator<<(bool n);
        basic_ostream<charT, traits>& operator<<(short n);
        basic_ostream<charT, traits>& operator<<(unsigned short n);
        basic_ostream<charT, traits>& operator<<(int n);
        basic_ostream<charT, traits>& operator<<(unsigned int n);
        basic_ostream<charT, traits>& operator<<(long n);
        basic_ostream<charT, traits>& operator<<(unsigned long n);
        basic_ostream<charT, traits>& operator<<(long long n);
        basic_ostream<charT, traits>& operator<<(unsigned long long n);
        basic_ostream<charT, traits>& operator<<(float f);
        basic_ostream<charT, traits>& operator<<(double f);
        basic_ostream<charT, traits>& operator<<(long double f);

        basic_ostream<charT, traits>& operator<<(const void* p);
        basic_ostream<charT, traits>& operator<<(nullptr_t);
```

```

    basic_ostream<charT, traits>& operator<<(basic_streambuf<char_type, traits>* sb);

    // 30.7.5.3, unformatted output
    basic_ostream<charT, traits>& put(char_type c);
    basic_ostream<charT, traits>& write(const char_type* s, streamsize n);

    basic_ostream<charT, traits>& flush();

    // 30.7.5.1.4, seeks
    pos_type tellp();
    basic_ostream<charT, traits>& seekp(pos_type);
    basic_ostream<charT, traits>& seekp(off_type, ios_base::seekdir);

protected:
    // 30.7.5.1.1, copy/move constructor
    basic_ostream(const basic_ostream& rhs) = delete;
    basic_ostream(basic_ostream&& rhs);

    // 30.7.5.1.2, assign and swap
    basic_ostream& operator=(const basic_ostream& rhs) = delete;
    basic_ostream& operator=(basic_ostream&& rhs);
    void swap(basic_ostream& rhs);
};

// 30.7.5.2.4, character inserters
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, charT);
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, char);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, char);

template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, signed char);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, unsigned char);

template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, const charT*);
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, const char*);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const char*);

template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const signed char*);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const unsigned char*);
}

```

- ¹ The class template `basic_ostream` defines a number of member function signatures that assist in formatting and writing output to output sequences controlled by a stream buffer.
- ² Two groups of member function signatures share common properties: the *formatted output functions* (or *inserters*) and the *unformatted output functions*. Both groups of output functions generate (or *insert*) output *characters* by actions equivalent to calling `rddbuf()->sputc(int_type)`. They may use other public members

of `basic_ostream` except that they shall not invoke any virtual members of `rdbuf()` except `overflow()`, `xspn()`, and `sync()`.

- 3 If one of these called functions throws an exception, then unless explicitly noted otherwise the output function sets `badbit` in error state. If `badbit` is on in `exceptions()`, the output function rethrows the exception without completing its actions, otherwise it does not throw anything and treat as an error.

30.7.5.1.1 `basic_ostream` constructors [ostream.cons]

```
explicit basic_ostream(basic_streambuf<charT, traits>* sb);
```

- 1 *Effects:* Constructs an object of class `basic_ostream`, initializing the base class subobject with `basic_ios<charT, traits>::init(sb)` (30.5.5.2).

- 2 *Postconditions:* `rdbuf() == sb`.

```
basic_ostream(basic_ostream&& rhs);
```

- 3 *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by default constructing the base class and calling `basic_ios<charT, traits>::move(rhs)` to initialize the base class.

```
virtual ~basic_ostream();
```

- 4 *Effects:* Destroys an object of class `basic_ostream`.

- 5 *Remarks:* Does not perform any operations on `rdbuf()`.

30.7.5.1.2 Class `basic_ostream` assign and swap [ostream.assign]

```
basic_ostream& operator=(basic_ostream&& rhs);
```

- 1 *Effects:* As if by `swap(rhs)`.

- 2 *Returns:* `*this`.

```
void swap(basic_ostream& rhs);
```

- 3 *Effects:* Calls `basic_ios<charT, traits>::swap(rhs)`.

30.7.5.1.3 Class `basic_ostream::sentry` [ostream::sentry]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_ostream<charT, traits>::sentry {
        bool ok_; // exposition only
    public:
        explicit sentry(basic_ostream<charT, traits>& os);
        ~sentry();
        explicit operator bool() const { return ok_; }

        sentry(const sentry&) = delete;
        sentry& operator=(const sentry&) = delete;
    };
}
```

- 1 The class `sentry` defines a class that is responsible for doing exception safe prefix and suffix operations.

```
explicit sentry(basic_ostream<charT, traits>& os);
```

- 2 If `os.good()` is nonzero, prepares for formatted or unformatted output. If `os.tie()` is not a null pointer, calls `os.tie()->flush()`.³¹⁸

318) The call `os.tie()->flush()` does not necessarily occur if the function can determine that no synchronization is necessary.

- 3 If, after any preparation is completed, `os.good()` is `true`, `ok_ == true` otherwise, `ok_ == false`. During preparation, the constructor may call `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4))³¹⁹

`~sentry();`

- 4 If `(os.flags() & ios_base::unitbuf) && !uncaught_exceptions() && os.good()` is `true`, calls `os.rdbuf()->pubsync()`. If that function returns -1, sets `badbit` in `os.rdstate()` without propagating an exception.

`explicit operator bool() const;`

- 5 *Effects:* Returns `ok_`.

30.7.5.1.4 `basic_ostream` seek members

[ostream.seek]

- 1 Each seek member function begins execution by constructing an object of class `sentry`. It returns by destroying the `sentry` object.

`pos_type tellp();`

- 2 *Returns:* If `fail() != false`, returns `pos_type(-1)` to indicate failure. Otherwise, returns `rdbuf()->pubseekoff(0, cur, out)`.

`basic_ostream<charT, traits>& seekp(pos_type pos);`

- 3 *Effects:* If `fail() != true`, executes `rdbuf()->pubseekpos(pos, ios_base::out)`. In case of failure, the function calls `setstate(failbit)` (which may throw `ios_base::failure`).

- 4 *Returns:* `*this`.

`basic_ostream<charT, traits>& seekp(off_type off, ios_base::seekdir dir);`

- 5 *Effects:* If `fail() != true`, executes `rdbuf()->pubseekoff(off, dir, ios_base::out)`. In case of failure, the function calls `setstate(failbit)` (which may throw `ios_base::failure`).

- 6 *Returns:* `*this`.

30.7.5.2 Formatted output functions

[ostream.formatted]

30.7.5.2.1 Common requirements

[ostream.formatted.reqmts]

- 1 Each formatted output function begins execution by constructing an object of class `sentry`. If this object returns `true` when converted to a value of type `bool`, the function endeavors to generate the requested output. If the generation fails, then the formatted output function does `setstate(ios_base::failbit)`, which might throw an exception. If an exception is thrown during output, then `ios::badbit` is turned on³²⁰ in `*this`'s error state. If `(exceptions() & badbit) != 0` then the exception is rethrown. Whether or not an exception is thrown, the `sentry` object is destroyed before leaving the formatted output function. If no exception is thrown, the result of the formatted output function is `*this`.
- 2 The descriptions of the individual formatted output functions describe how they perform output and do not mention the `sentry` object.
- 3 If a formatted output function of a stream `os` determines padding, it does so as follows. Given a `charT` character sequence `seq` where `charT` is the character type of the stream, if the length of `seq` is less than `os.width()`, then enough copies of `os.fill()` are added to this sequence as necessary to pad to a width of `os.width()` characters. If `(os.flags() & ios_base::adjustfield) == ios_base::left` is `true`, the fill characters are placed after the character sequence; otherwise, they are placed before the character sequence.

319) The `sentry` constructor and destructor can also perform additional implementation-dependent operations.

320) without causing an `ios::failure` to be thrown.

30.7.5.2.2 Arithmetic inserters

[ostream.inserters.arithmetic]

```

operator<<(bool val);
operator<<(short val);
operator<<(unsigned short val);
operator<<(int val);
operator<<(unsigned int val);
operator<<(long val);
operator<<(unsigned long val);
operator<<(long long val);
operator<<(unsigned long long val);
operator<<(float val);
operator<<(double val);
operator<<(long double val);
operator<<(const void* val);

```

- ¹ *Effects:* The classes `num_get<>` and `num_put<>` handle locale-dependent numeric formatting and parsing. These inserter functions use the imbued `locale` value to perform numeric formatting. When `val` is of type `bool`, `long`, `unsigned long`, `long long`, `unsigned long long`, `double`, `long double`, or `const void*`, the formatting conversion occurs as if it performed the following code fragment:

```

bool failed = use_facet<
    num_put<charT, ostreambuf_iterator<charT, traits>>
    >(getloc()).put(*this, *this, fill(), val).failed();

```

When `val` is of type `short` the formatting conversion occurs as if it performed the following code fragment:

```

ios_base::fmtflags baseflags = ios_base::flags() & ios_base::basefield;
bool failed = use_facet<
    num_put<charT, ostreambuf_iterator<charT, traits>>
    >(getloc()).put(*this, *this, fill(),
        baseflags == ios_base::oct || baseflags == ios_base::hex
        ? static_cast<long>(static_cast<unsigned short>(val))
        : static_cast<long>(val)).failed();

```

When `val` is of type `int` the formatting conversion occurs as if it performed the following code fragment:

```

ios_base::fmtflags baseflags = ios_base::flags() & ios_base::basefield;
bool failed = use_facet<
    num_put<charT, ostreambuf_iterator<charT, traits>>
    >(getloc()).put(*this, *this, fill(),
        baseflags == ios_base::oct || baseflags == ios_base::hex
        ? static_cast<long>(static_cast<unsigned int>(val))
        : static_cast<long>(val)).failed();

```

When `val` is of type `unsigned short` or `unsigned int` the formatting conversion occurs as if it performed the following code fragment:

```

bool failed = use_facet<
    num_put<charT, ostreambuf_iterator<charT, traits>>
    >(getloc()).put(*this, *this, fill(),
        static_cast<unsigned long>(val)).failed();

```

When `val` is of type `float` the formatting conversion occurs as if it performed the following code fragment:

```

bool failed = use_facet<
    num_put<charT, ostreambuf_iterator<charT, traits>>

```

```
>(getloc()).put(*this, *this, fill(),
    static_cast<double>(val)).failed();
```

2 The first argument provides an object of the `ostreambuf_iterator<>` class which is an iterator for class `basic_ostream<>`. It bypasses `ostreams` and uses `streambufs` directly. Class `locale` relies on these types as its interface to `iostreams`, since for flexibility it has been abstracted away from direct dependence on `ostream`. The second parameter is a reference to the base class subobject of type `ios_base`. It provides formatting specifications such as field width, and a locale from which to obtain other facets. If `failed` is `true` then does `setstate(badbit)`, which may throw an exception, and returns.

3 *Returns:* `*this`.

30.7.5.2.3 `basic_ostream::operator<<` [ostream.inserters]

```
basic_ostream<charT, traits>&
    operator<<(basic_ostream<charT, traits>& (*pf)(basic_ostream<charT, traits>&));
```

1 *Effects:* None. Does not behave as a formatted output function (as described in 30.7.5.2.1).

2 *Returns:* `pf(*this)`.³²¹

```
basic_ostream<charT, traits>&
    operator<<(basic_ios<charT, traits>& (*pf)(basic_ios<charT, traits>&));
```

3 *Effects:* Calls `pf(*this)`. This inserter does not behave as a formatted output function (as described in 30.7.5.2.1).

4 *Returns:* `*this`.³²²

```
basic_ostream<charT, traits>& operator<<(ios_base& (*pf)(ios_base&));
```

5 *Effects:* Calls `pf(*this)`. This inserter does not behave as a formatted output function (as described in 30.7.5.2.1).

6 *Returns:* `*this`.

```
basic_ostream<charT, traits>& operator<<(basic_streambuf<charT, traits>* sb);
```

7 *Effects:* Behaves as an unformatted output function (30.7.5.3). After the sentry object is constructed, if `sb` is null calls `setstate(badbit)` (which may throw `ios_base::failure`).

8 Gets characters from `sb` and inserts them in `*this`. Characters are read from `sb` and inserted until any of the following occurs:

- (8.1) — end-of-file occurs on the input sequence;
- (8.2) — inserting in the output sequence fails (in which case the character to be inserted is not extracted);
- (8.3) — an exception occurs while getting a character from `sb`.

9 If the function inserts no characters, it calls `setstate(failbit)` (which may throw `ios_base::failure` (30.5.5.4)). If an exception was thrown while extracting a character, the function sets `failbit` in error state, and if `failbit` is on in `exceptions()` the caught exception is rethrown.

10 *Returns:* `*this`.

```
basic_ostream<charT, traits>& operator<<(nullptr_t);
```

11 *Effects:* Equivalent to:

```
return *this << s;
```

321) See, for example, the function signature `endl(basic_ostream&)` (30.7.5.4).

322) See, for example, the function signature `dec(ios_base&)` (30.5.6.3).

where *s* is an implementation-defined NTCTS (20.3.16).

30.7.5.2.4 Character inserter function templates

[ostream.inserters.character]

```
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>& out, charT c);
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>& out, char c);
// specialization
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out, char c);
// signed and unsigned
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out, signed char c);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out, unsigned char c);
```

¹ *Effects:* Behaves as a formatted output function (30.7.5.2.1) of *out*. Constructs a character sequence *seq*. If *c* has type *char* and the character type of the stream is not *char*, then *seq* consists of *out.widen(c)*; otherwise *seq* consists of *c*. Determines padding for *seq* as described in 30.7.5.2.1. Inserts *seq* into *out*. Calls *os.width(0)*.

² *Returns:* *out*.

```
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>& out, const charT* s);
template<class charT, class traits>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>& out, const char* s);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out, const char* s);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out, const signed char* s);
template<class traits>
    basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>& out,
                                         const unsigned char* s);
```

³ *Requires:* *s* shall not be a null pointer.

⁴ *Effects:* Behaves like a formatted inserter (as described in 30.7.5.2.1) of *out*. Creates a character sequence *seq* of *n* characters starting at *s*, each widened using *out.widen()* (30.5.5.3), where *n* is the number that would be computed as if by:

- (4.1) — *traits::length(s)* for the overload where the first argument is of type *basic_ostream<charT, traits>&* and the second is of type *const charT**, and also for the overload where the first argument is of type *basic_ostream<char, traits>&* and the second is of type *const char**,
- (4.2) — *char_traits<char>::length(s)* for the overload where the first argument is of type *basic_ostream<charT, traits>&* and the second is of type *const char**,
- (4.3) — *traits::length(reinterpret_cast<const char*>(s))* for the other two overloads.

Determines padding for *seq* as described in 30.7.5.2.1. Inserts *seq* into *out*. Calls *width(0)*.

⁵ *Returns:* *out*.

30.7.5.3 Unformatted output functions

[ostream.unformatted]

¹ Each unformatted output function begins execution by constructing an object of class *sentry*. If this object returns *true*, while converting to a value of type *bool*, the function endeavors to generate the requested

output. If an exception is thrown during output, then `ios::badbit` is turned on³²³ in `*this`'s error state. If `(exceptions() & badbit) != 0` then the exception is rethrown. In any case, the unformatted output function ends by destroying the sentry object, then, if no exception was thrown, returning the value specified for the unformatted output function.

```
basic_ostream<charT, traits>& put(char_type c);
```

2 *Effects:* Behaves as an unformatted output function (as described above). After constructing a sentry object, inserts the character `c`, if possible.³²⁴

3 Otherwise, calls `setstate(badbit)` (which may throw `ios_base::failure` (30.5.5.4)).

4 *Returns:* `*this`.

```
basic_ostream& write(const char_type* s, streamsize n);
```

5 *Effects:* Behaves as an unformatted output function (as described above). After constructing a sentry object, obtains characters to insert from successive locations of an array whose first element is designated by `s`.³²⁵ Characters are inserted until either of the following occurs:

(5.1) — `n` characters are inserted;

(5.2) — inserting in the output sequence fails (in which case the function calls `setstate(badbit)`, which may throw `ios_base::failure` (30.5.5.4)).

6 *Returns:* `*this`.

```
basic_ostream& flush();
```

7 *Effects:* Behaves as an unformatted output function (as described above). If `rdbuf()` is not a null pointer, constructs a sentry object. If this object returns `true` when converted to a value of type `bool` the function calls `rdbuf()->pubsync()`. If that function returns -1 calls `setstate(badbit)` (which may throw `ios_base::failure` (30.5.5.4)). Otherwise, if the sentry object returns `false`, does nothing.

8 *Returns:* `*this`.

30.7.5.4 Standard `basic_ostream` manipulators

[ostream.manip]

```
template <class charT, class traits>
    basic_ostream<charT, traits>& endl(basic_ostream<charT, traits>& os);
```

1 *Effects:* Calls `os.put(os.widen('\n'))`, then `os.flush()`.

2 *Returns:* `os`.

```
template <class charT, class traits>
    basic_ostream<charT, traits>& ends(basic_ostream<charT, traits>& os);
```

3 *Effects:* Inserts a null character into the output sequence: calls `os.put(charT())`.

4 *Returns:* `os`.

```
template <class charT, class traits>
    basic_ostream<charT, traits>& flush(basic_ostream<charT, traits>& os);
```

5 *Effects:* Calls `os.flush()`.

6 *Returns:* `os`.

30.7.5.5 Rvalue stream insertion

[ostream.rvalue]

323) without causing an `ios::failure` to be thrown.

324) Note that this function is not overloaded on types `signed char` and `unsigned char`.

325) Note that this function is not overloaded on types `signed char` and `unsigned char`.


```
template <class charT, class traits, class T>
    basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&& os, const T& x);
```

- 1 *Effects:* As if by: `os << x;`
- 2 *Returns:* `os`.
- 3 *Remarks:* This function shall not participate in overload resolution unless the expression `os << x` is well-formed.

30.7.6 Standard manipulators [std.manip]

- 1 The header `<iomanip>` defines several functions that support extractors and inserters that alter information maintained by class `ios_base` and its derived classes.

```
unspecified resetiosflags(ios_base::fmtflags mask);
```

- 2 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << resetiosflags(mask)` behaves as if it called `f(out, mask)`, or if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> resetiosflags(mask)` behaves as if it called `f(in, mask)`, where the function `f` is defined as:³²⁶

```
void f(ios_base& str, ios_base::fmtflags mask) {
    // reset specified flags
    str.setf(ios_base::fmtflags(0), mask);
}
```

The expression `out << resetiosflags(mask)` shall have type `basic_ostream<charT, traits>&` and value `out`. The expression `in >> resetiosflags(mask)` shall have type `basic_istream<charT, traits>&` and value `in`.

```
unspecified setiosflags(ios_base::fmtflags mask);
```

- 3 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << setiosflags(mask)` behaves as if it called `f(out, mask)`, or if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> setiosflags(mask)` behaves as if it called `f(in, mask)`, where the function `f` is defined as:

```
void f(ios_base& str, ios_base::fmtflags mask) {
    // set specified flags
    str.setf(mask);
}
```

The expression `out << setiosflags(mask)` shall have type `basic_ostream<charT, traits>&` and value `out`. The expression `in >> setiosflags(mask)` shall have type `basic_istream<charT, traits>&` and value `in`.

```
unspecified setbase(int base);
```

- 4 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << setbase(base)` behaves as if it called `f(out, base)`, or if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> setbase(base)` behaves as if it called `f(in, base)`, where the function `f` is defined as:

```
void f(ios_base& str, int base) {
    // set basefield
    str.setf(base == 8 ? ios_base::oct :
```

³²⁶ The expression `cin >> resetiosflags(ios_base::skipws)` clears `ios_base::skipws` in the format flags stored in the `basic_istream<charT, traits>` object `cin` (the same as `cin >> noskipws`), and the expression `cout << resetiosflags(ios_base::showbase)` clears `ios_base::showbase` in the format flags stored in the `basic_ostream<charT, traits>` object `cout` (the same as `cout << noshowbase`).

```

        base == 10 ? ios_base::dec :
        base == 16 ? ios_base::hex :
        ios_base::fmtflags(0), ios_base::basefield);
    }

```

The expression `out << setbase(base)` shall have type `basic_ostream<charT, traits>&` and value `out`. The expression `in >> setbase(base)` shall have type `basic_istream<charT, traits>&` and value `in`.

unspecified `setfill(char_type c);`

- 5 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` and `c` has type `charT` then the expression `out << setfill(c)` behaves as if it called `f(out, c)`, where the function `f` is defined as:

```

template<class charT, class traits>
void f(basic_ios<charT, traits>& str, charT c) {
    // set fill character
    str.fill(c);
}

```

The expression `out << setfill(c)` shall have type `basic_ostream<charT, traits>&` and value `out`.

unspecified `setprecision(int n);`

- 6 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << setprecision(n)` behaves as if it called `f(out, n)`, or if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> setprecision(n)` behaves as if it called `f(in, n)`, where the function `f` is defined as:

```

void f(basic_ios<charT, traits>& str, int n) {
    // set precision
    str.precision(n);
}

```

The expression `out << setprecision(n)` shall have type `basic_ostream<charT, traits>&` and value `out`. The expression `in >> setprecision(n)` shall have type `basic_istream<charT, traits>&` and value `in`.

unspecified `setw(int n);`

- 7 *Returns:* An object of unspecified type such that if `out` is an instance of `basic_ostream<charT, traits>` then the expression `out << setw(n)` behaves as if it called `f(out, n)`, or if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> setw(n)` behaves as if it called `f(in, n)`, where the function `f` is defined as:

```

void f(basic_ios<charT, traits>& str, int n) {
    // set width
    str.width(n);
}

```

The expression `out << setw(n)` shall have type `basic_ostream<charT, traits>&` and value `out`. The expression `in >> setw(n)` shall have type `basic_istream<charT, traits>&` and value `in`.

30.7.7 Extended manipulators [ext.manip]

- 1 The header `<iomanip>` defines several functions that support extractors and inserters that allow for the parsing and formatting of sequences and values for money and time.

```
template <class moneyT> unspecified get_money(moneyT& mon, bool intl = false);
```

2 *Requires:* The type `moneyT` shall be either `long double` or a specialization of the `basic_string` template (Clause 24).

3 *Effects:* The expression `in >> get_money(mon, intl)` described below behaves as a formatted input function (30.7.4.2.1).

4 *Returns:* An object of unspecified type such that if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> get_money(mon, intl)` behaves as if it called `f(in, mon, intl)`, where the function `f` is defined as:

```
template <class charT, class traits, class moneyT>
void f(basic_ios<charT, traits>& str, moneyT& mon, bool intl) {
    using Iter      = istreambuf_iterator<charT, traits>;
    using MoneyGet = money_get<charT, Iter>;

    ios_base::iostate err = ios_base::goodbit;
    const MoneyGet& mg = use_facet<MoneyGet>(str.getloc());

    mg.get(Iter(str.rdbuf()), Iter(), intl, str, err, mon);

    if (ios_base::goodbit != err)
        str.setstate(err);
}
```

The expression `in >> get_money(mon, intl)` shall have type `basic_istream<charT, traits>&` and value `in`.

```
template <class moneyT> unspecified put_money(const moneyT& mon, bool intl = false);
```

5 *Requires:* The type `moneyT` shall be either `long double` or a specialization of the `basic_string` template (Clause 24).

6 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << put_money(mon, intl)` behaves as a formatted output function (30.7.5.2.1) that calls `f(out, mon, intl)`, where the function `f` is defined as:

```
template <class charT, class traits, class moneyT>
void f(basic_ios<charT, traits>& str, const moneyT& mon, bool intl) {
    using Iter      = ostreambuf_iterator<charT, traits>;
    using MoneyPut = money_put<charT, Iter>;

    const MoneyPut& mp = use_facet<MoneyPut>(str.getloc());
    const Iter end = mp.put(Iter(str.rdbuf()), intl, str, str.fill(), mon);

    if (end.failed())
        str.setstate(ios::badbit);
}
```

The expression `out << put_money(mon, intl)` shall have type `basic_ostream<charT, traits>&` and value `out`.

```
template <class charT> unspecified get_time(struct tm* tmb, const charT* fmt);
```

7 *Requires:* The argument `tmb` shall be a valid pointer to an object of type `struct tm`. The argument `fmt` shall be a valid pointer to an array of objects of type `charT` with `char_traits<charT>::length(fmt)` elements.

8 *Returns:* An object of unspecified type such that if `in` is an object of type `basic_istream<charT, traits>` then the expression `in >> get_time(tmb, fmt)` behaves as if it called `f(in, tmb, fmt)`, where the function `f` is defined as:

```

template <class charT, class traits>
void f(basic_ios<charT, traits>& str, struct tm* tmb, const charT* fmt) {
    using Iter    = istreambuf_iterator<charT, traits>;
    using TimeGet = time_get<charT, Iter>;

    ios_base::iostate err = ios_base::goodbit;
    const TimeGet& tg = use_facet<TimeGet>(str.getloc());

    tg.get(Iter(str.rdbuf()), Iter(), str, err, tmb,
        fmt, fmt + traits::length(fmt));

    if (err != ios_base::goodbit)
        str.setstate(err);
}

```

The expression in `>> get_time(tmb, fmt)` shall have type `basic_istream<charT, traits>&` and value `in`.

```

template <class charT> unspecified put_time(const struct tm* tmb, const charT* fmt);

```

9 *Requires:* The argument `tmb` shall be a valid pointer to an object of type `struct tm`, and the argument `fmt` shall be a valid pointer to an array of objects of type `charT` with `char_traits<charT>::length(fmt)` elements.

10 *Returns:* An object of unspecified type such that if `out` is an object of type `basic_ostream<charT, traits>` then the expression `out << put_time(tmb, fmt)` behaves as if it called `f(out, tmb, fmt)`, where the function `f` is defined as:

```

template <class charT, class traits>
void f(basic_ios<charT, traits>& str, const struct tm* tmb, const charT* fmt) {
    using Iter    = ostreambuf_iterator<charT, traits>;
    using TimePut = time_put<charT, Iter>;

    const TimePut& tp = use_facet<TimePut>(str.getloc());
    const Iter end = tp.put(Iter(str.rdbuf()), str, str.fill(), tmb,
        fmt, fmt + traits::length(fmt));

    if (end.failed())
        str.setstate(ios_base::badbit);
}

```

The expression `out << put_time(tmb, fmt)` shall have type `basic_ostream<charT, traits>&` and value `out`.

30.7.8 Quoted manipulators

[quoted.manip]

1 [*Note:* Quoted manipulators provide string insertion and extraction of quoted strings (for example, XML and CSV formats). Quoted manipulators are useful in ensuring that the content of a string with embedded spaces remains unchanged if inserted and then extracted via stream I/O. — *end note*]

```

template <class charT>
unspecified quoted(const charT* s, charT delim = charT('"'), charT escape = charT('\\'));
template <class charT, class traits, class Allocator>
unspecified quoted(const basic_string<charT, traits, Allocator>& s,
    charT delim = charT('"'), charT escape = charT('\\'));
template <class charT, class traits>
unspecified quoted(basic_string_view<charT, traits> s,
    charT delim = charT('"'), charT escape = charT('\\'));

```

2 *Returns:* An object of unspecified type such that if `out` is an instance of `basic_ostream` with member type `char_type` the same as `charT` and with member type `traits_type`, which in the second and third forms is the same as `traits`, then the expression `out << quoted(s, delim, escape)` behaves as a formatted output function (30.7.5.2.1) of `out`. This forms a character sequence `seq`, initially consisting of the following elements:

- (2.1) — `delim`.
- (2.2) — Each character in `s`. If the character to be output is equal to `escape` or `delim`, as determined by `traits_type::eq`, first output `escape`.
- (2.3) — `delim`.

Let `x` be the number of elements initially in `seq`. Then padding is determined for `seq` as described in 30.7.5.2.1, `seq` is inserted as if by calling `out.rdbuf()->sputn(seq, n)`, where `n` is the larger of `out.width()` and `x`, and `out.width(0)` is called. The expression `out << quoted(s, delim, escape)` shall have type `basic_ostream<charT, traits>&` and value `out`.

```
template <class charT, class traits, class Allocator>
    unspecified quoted(basic_string<charT, traits, Allocator>& s,
                      charT delim = charT(' '), charT escape = charT('\\'));
```

3 *Returns:* An object of unspecified type such that:

- (3.1) — If `in` is an instance of `basic_istream` with member types `char_type` and `traits_type` the same as `charT` and `traits`, respectively, then the expression `in >> quoted(s, delim, escape)` behaves as if it extracts the following characters from `in` using `operator>>(basic_istream<charT, traits>&, charT&)` (30.7.4.2.3) which may throw `ios_base::failure` (30.5.3.1.1):
 - (3.1.1) — If the first character extracted is equal to `delim`, as determined by `traits_type::eq`, then:
 - (3.1.1.1) — Turn off the `skipws` flag.
 - (3.1.1.2) — `s.clear()`
 - (3.1.1.3) — Until an unescaped `delim` character is reached or `!in`, extract characters from `in` and append them to `s`, except that if an `escape` is reached, ignore it and append the next character to `s`.
 - (3.1.1.4) — Discard the final `delim` character.
 - (3.1.1.5) — Restore the `skipws` flag to its original value.
 - (3.1.2) — Otherwise, `in >> s`.
- (3.2) — If `out` is an instance of `basic_ostream` with member types `char_type` and `traits_type` the same as `charT` and `traits`, respectively, then the expression `out << quoted(s, delim, escape)` behaves as specified for the `const basic_string<charT, traits, Allocator>&` overload of the `quoted` function.

The expression `in >> quoted(s, delim, escape)` shall have type `basic_istream<charT, traits>&` and value `in`. The expression `out << quoted(s, delim, escape)` shall have type `basic_ostream<charT, traits>&` and value `out`.

30.8 String-based streams

[string.streams]

30.8.1 Header <sstream> synopsis

[sstream.syn]

```
namespace std {
    template <class charT, class traits = char_traits<charT>,
              class Allocator = allocator<charT>>
        class basic_stringbuf;
```

```

using stringbuf = basic_stringbuf<char>;
using wstringbuf = basic_stringbuf<wchar_t>;

template <class charT, class traits = char_traits<charT>,
          class Allocator = allocator<charT>>
    class basic_istreamstream;

using istringstream = basic_istreamstream<char>;
using wistringstream = basic_istreamstream<wchar_t>;

template <class charT, class traits = char_traits<charT>,
          class Allocator = allocator<charT>>
    class basic_ostreamstream;
using ostreamstream = basic_ostreamstream<char>;
using wostreamstream = basic_ostreamstream<wchar_t>;

template <class charT, class traits = char_traits<charT>,
          class Allocator = allocator<charT>>
    class basic_stringstream;
using stringstream = basic_stringstream<char>;
using wstringstream = basic_stringstream<wchar_t>;
}

```

- ¹ The header <sstream> defines four class templates and eight types that associate stream buffers with objects of class basic_string, as described in 24.3.

30.8.2 Class template basic_stringbuf

[stringbuf]

```

namespace std {
    template <class charT, class traits = char_traits<charT>,
              class Allocator = allocator<charT>>
    class basic_stringbuf : public basic_streambuf<charT, traits> {
    public:
        using char_type      = charT;
        using int_type       = typename traits::int_type;
        using pos_type       = typename traits::pos_type;
        using off_type       = typename traits::off_type;
        using traits_type    = traits;
        using allocator_type = Allocator;

        // 30.8.2.1, constructors
        explicit basic_stringbuf(
            ios_base::openmode which = ios_base::in | ios_base::out);
        explicit basic_stringbuf(
            const basic_string<charT, traits, Allocator>& str,
            ios_base::openmode which = ios_base::in | ios_base::out);
        basic_stringbuf(const basic_stringbuf& rhs) = delete;
        basic_stringbuf(basic_stringbuf&& rhs);

        // 30.8.2.2, assign and swap
        basic_stringbuf& operator=(const basic_stringbuf& rhs) = delete;
        basic_stringbuf& operator=(basic_stringbuf&& rhs);
        void swap(basic_stringbuf& rhs);

        // 30.8.2.3, get and set
        basic_string<charT, traits, Allocator> str() const;
        void str(const basic_string<charT, traits, Allocator>& s);
    };
}

```

```

protected:
    // 30.8.2.4, overridden virtual functions
    int_type underflow() override;
    int_type pbackfail(int_type c = traits::eof()) override;
    int_type overflow (int_type c = traits::eof()) override;
    basic_streambuf<charT, traits>* setbuf(charT*, streamsize) override;

    pos_type seekoff(off_type off, ios_base::seekdir way,
                     ios_base::openmode which
                     = ios_base::in | ios_base::out) override;
    pos_type seekpos(pos_type sp,
                     ios_base::openmode which
                     = ios_base::in | ios_base::out) override;

private:
    ios_base::openmode mode; // exposition only
};

template <class charT, class traits, class Allocator>
void swap(basic_stringbuf<charT, traits, Allocator>& x,
          basic_stringbuf<charT, traits, Allocator>& y);
}

```

- ¹ The class `basic_stringbuf` is derived from `basic_streambuf` to associate possibly the input sequence and possibly the output sequence with a sequence of arbitrary *characters*. The sequence can be initialized from, or made available as, an object of class `basic_string`.
- ² For the sake of exposition, the maintained data is presented here as:
- (2.1) — `ios_base::openmode mode`, has `in` set if the input sequence can be read, and `out` set if the output sequence can be written.

30.8.2.1 `basic_stringbuf` constructors

[stringbuf.cons]

```

explicit basic_stringbuf(
    ios_base::openmode which = ios_base::in | ios_base::out);

```

- ¹ *Effects:* Constructs an object of class `basic_stringbuf`, initializing the base class with `basic_streambuf()` (30.6.3.1), and initializing `mode` with `which`.
- ² *Postconditions:* `str() == ""`.

```

explicit basic_stringbuf(
    const basic_string<charT, traits, Allocator>& s,
    ios_base::openmode which = ios_base::in | ios_base::out);

```

- ³ *Effects:* Constructs an object of class `basic_stringbuf`, initializing the base class with `basic_streambuf()` (30.6.3.1), and initializing `mode` with `which`. Then calls `str(s)`.

```

basic_stringbuf(basic_stringbuf&& rhs);

```

- ⁴ *Effects:* Move constructs from the rvalue `rhs`. It is implementation-defined whether the sequence pointers in `*this` (`eback()`, `gptr()`, `egptr()`, `pbase()`, `pptr()`, `epptr()`) obtain the values which `rhs` had. Whether they do or not, `*this` and `rhs` reference separate buffers (if any at all) after the construction. The `openmode`, `locale` and any other state of `rhs` is also copied.
- ⁵ *Postconditions:* Let `rhs_p` refer to the state of `rhs` just prior to this construction and let `rhs_a` refer to the state of `rhs` just after this construction.

```

(5.1)      — str() == rhs_p.str()
(5.2)      — gptr() - eback() == rhs_p.gptr() - rhs_p.eback()
(5.3)      — egptr() - eback() == rhs_p.egptr() - rhs_p.eback()
(5.4)      — pptr() - pbase() == rhs_p.pptr() - rhs_p.pbase()
(5.5)      — ep_ptr() - pbase() == rhs_p.ep_ptr() - rhs_p.pbase()
(5.6)      — if (eback()) eback() != rhs_a.eback()
(5.7)      — if (gp_ptr()) gp_ptr() != rhs_a.gp_ptr()
(5.8)      — if (eg_ptr()) eg_ptr() != rhs_a.eg_ptr()
(5.9)      — if (pbase()) pbase() != rhs_a.pbase()
(5.10)     — if (pptr()) pptr() != rhs_a.pptr()
(5.11)     — if (ep_ptr()) ep_ptr() != rhs_a.ep_ptr()

```

30.8.2.2 Assign and swap

[stringbuf.assign]

```
basic_stringbuf& operator=(basic_stringbuf&& rhs);
```

1 *Effects:* After the move assignment **this* has the observable state it would have had if it had been move constructed from *rhs* (see 30.8.2.1).

2 *Returns:* **this*.

```
void swap(basic_stringbuf& rhs);
```

3 *Effects:* Exchanges the state of **this* and *rhs*.

```
template <class charT, class traits, class Allocator>
void swap(basic_stringbuf<charT, traits, Allocator>& x,
          basic_stringbuf<charT, traits, Allocator>& y);
```

4 *Effects:* As if by *x.swap(y)*.

30.8.2.3 Member functions

[stringbuf.members]

```
basic_string<charT, traits, Allocator> str() const;
```

1 *Returns:* A *basic_string* object whose content is equal to the *basic_stringbuf* underlying character sequence. If the *basic_stringbuf* was created only in input mode, the resultant *basic_string* contains the character sequence in the range *[eback(), eg_ptr())*. If the *basic_stringbuf* was created with *which & ios_base::out* being nonzero then the resultant *basic_string* contains the character sequence in the range *[pbase(), high_mark)*, where *high_mark* represents the position one past the highest initialized character in the buffer. Characters can be initialized by writing to the stream, by constructing the *basic_stringbuf* with a *basic_string*, or by calling the *str(basic_string)* member function. In the case of calling the *str(basic_string)* member function, all characters initialized prior to the call are now considered uninitialized (except for those characters re-initialized by the new *basic_string*). Otherwise the *basic_stringbuf* has been created in neither input nor output mode and a zero length *basic_string* is returned.

```
void str(const basic_string<charT, traits, Allocator>& s);
```

2 *Effects:* Copies the content of *s* into the *basic_stringbuf* underlying character sequence and initializes the input and output sequences according to *mode*.

3 *Postconditions:* If *mode & ios_base::out* is nonzero, *pbase()* points to the first underlying character and *ep_ptr() >= pbase() + s.size()* holds; in addition, if *mode & ios_base::ate* is nonzero, *pptr()*

`== pbase() + s.size()` holds, otherwise `pptr() == pbase()` is true. If `mode & ios_base::in` is nonzero, `eback()` points to the first underlying character, and both `gptr() == eback()` and `egptr() == eback() + s.size()` hold.

30.8.2.4 Overridden virtual functions

[stringbuf.virtuals]

`int_type underflow() override;`

- 1 *Returns:* If the input sequence has a read position available, returns `traits::to_int_type(*gptr())`. Otherwise, returns `traits::eof()`. Any character in the underlying buffer which has been initialized is considered to be part of the input sequence.

`int_type pbackfail(int_type c = traits::eof()) override;`

- 2 *Effects:* Puts back the character designated by `c` to the input sequence, if possible, in one of three ways:
- (2.1) — If `traits::eq_int_type(c, traits::eof())` returns false and if the input sequence has a putback position available, and if `traits::eq(to_char_type(c), gptr()[-1])` returns true, assigns `gptr() - 1` to `gptr()`.
Returns: `c`.
- (2.2) — If `traits::eq_int_type(c, traits::eof())` returns false and if the input sequence has a putback position available, and if `mode & ios_base::out` is nonzero, assigns `c` to `*--gptr()`.
Returns: `c`.
- (2.3) — If `traits::eq_int_type(c, traits::eof())` returns true and if the input sequence has a putback position available, assigns `gptr() - 1` to `gptr()`.
Returns: `traits::not_eof(c)`.
- 3 *Returns:* `traits::eof()` to indicate failure.
- 4 *Remarks:* If the function can succeed in more than one of these ways, it is unspecified which way is chosen.

`int_type overflow(int_type c = traits::eof()) override;`

- 5 *Effects:* Appends the character designated by `c` to the output sequence, if possible, in one of two ways:
- (5.1) — If `traits::eq_int_type(c, traits::eof())` returns false and if either the output sequence has a write position available or the function makes a write position available (as described below), the function calls `sputc(c)`.
Signals success by returning `c`.
- (5.2) — If `traits::eq_int_type(c, traits::eof())` returns true, there is no character to append.
Signals success by returning a value other than `traits::eof()`.
- 6 *Remarks:* The function can alter the number of write positions available as a result of any call.
- 7 *Returns:* `traits::eof()` to indicate failure.
- 8 The function can make a write position available only if `(mode & ios_base::out) != 0`. To make a write position available, the function reallocates (or initially allocates) an array object with a sufficient number of elements to hold the current array object (if any), plus at least one additional write position. If `(mode & ios_base::in) != 0`, the function alters the read end pointer `egptr()` to point just past the new write position.

`pos_type seekoff(off_type off, ios_base::seekdir way,
ios_base::openmode which
= ios_base::in | ios_base::out) override;`

- 9 *Effects:* Alters the stream position within one of the controlled sequences, if possible, as indicated in Table 115.

Table 115 — seekoff positioning

Conditions	Result
(which & ios_base::in) == ios_-, base::in	positions the input sequence
(which & ios_base::out) == ios_-, base::out	positions the output sequence
(which & (ios_base::in ios_base::out)) == (ios_base::in ios_base::out)) and way == either ios_base::beg or ios_base::end	positions both the input and the output sequences
Otherwise	the positioning operation fails.

- 10 For a sequence to be positioned, if its next pointer (either `gptr()` or `pptr()`) is a null pointer and the new offset `newoff` is nonzero, the positioning operation fails. Otherwise, the function determines `newoff` as indicated in Table 116.

Table 116 — newoff values

Condition	newoff Value
way == ios_base::beg	0
way == ios_base::cur	the next pointer minus the beginning pointer (<code>xnext - xbeg</code>).
way == ios_base::end	the high mark pointer minus the beginning pointer (<code>high_mark - xbeg</code>).

- 11 If (`newoff + off`) < 0, or if `newoff + off` refers to an uninitialized character (30.8.2.3), the positioning operation fails. Otherwise, the function assigns `xbeg + newoff + off` to the next pointer `xnext`.
- 12 *Returns:* `pos_type(newoff)`, constructed from the resultant offset `newoff` (of type `off_type`), that stores the resultant stream position, if possible. If the positioning operation fails, or if the constructed object cannot represent the resultant stream position, the return value is `pos_type(off_type(-1))`.

```
pos_type seekpos(pos_type sp,
                 ios_base::openmode which
                 = ios_base::in | ios_base::out) override;
```

- 13 *Effects:* Equivalent to `seekoff(off_type(sp), ios_base::beg, which)`.
- 14 *Returns:* `sp` to indicate success, or `pos_type(off_type(-1))` to indicate failure.

```
basic_streambuf<charT, traits>* setbuf(charT* s, streamsize n);
```

- 15 *Effects:* implementation-defined, except that `setbuf(0, 0)` has no effect.
- 16 *Returns:* `this`.

30.8.3 Class template basic_istream

[istream]

```

namespace std {
    template <class charT, class traits = char_traits<charT>,
              class Allocator = allocator<charT>>
    class basic_istream : public basic_istream<charT, traits> {
    public:
        using char_type      = charT;
        using int_type        = typename traits::int_type;
        using pos_type        = typename traits::pos_type;
        using off_type        = typename traits::off_type;
        using traits_type     = traits;
        using allocator_type  = Allocator;

        // 30.8.3.1, constructors
        explicit basic_istream(
            ios_base::openmode which = ios_base::in);
        explicit basic_istream(
            const basic_string<charT, traits, Allocator>& str,
            ios_base::openmode which = ios_base::in);
        basic_istream(const basic_istream& rhs) = delete;
        basic_istream(basic_istream&& rhs);

        // 30.8.3.2, assign and swap
        basic_istream& operator=(const basic_istream& rhs) = delete;
        basic_istream& operator=(basic_istream&& rhs);
        void swap(basic_istream& rhs);

        // 30.8.3.3, members
        basic_stringbuf<charT, traits, Allocator>* rdbuf() const;

        basic_string<charT, traits, Allocator> str() const;
        void str(const basic_string<charT, traits, Allocator>& s);
    private:
        basic_stringbuf<charT, traits, Allocator> sb; // exposition only
    };

    template <class charT, class traits, class Allocator>
        void swap(basic_istream<charT, traits, Allocator>& x,
                  basic_istream<charT, traits, Allocator>& y);
}

```

- ¹ The class `basic_istream<charT, traits, Allocator>` supports reading objects of class `basic_string<charT, traits, Allocator>`. It uses a `basic_stringbuf<charT, traits, Allocator>` object to control the associated storage. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the `stringbuf` object.

30.8.3.1 basic_istream constructors

[istream.cons]

```
explicit basic_istream(ios_base::openmode which = ios_base::in);
```

- ¹ *Effects:* Constructs an object of class `basic_istream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(which | ios_base::in)` (30.8.2.1).

```
explicit basic_istream(
    const basic_string<charT, traits, Allocator>& str,
```

```
ios_base::openmode which = ios_base::in);
```

- 2 *Effects:* Constructs an object of class `basic_istream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(str, which | ios_base::in)` (30.8.2.1).

```
basic_istream(basic_istream&& rhs);
```

- 3 *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_stringbuf`. Next `basic_istream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_stringbuf`.

30.8.3.2 Assign and swap

[istream.assign]

```
basic_istream& operator=(basic_istream&& rhs);
```

- 1 *Effects:* Move assigns the base and members of `*this` from the base and corresponding members of `rhs`.

- 2 *Returns:* `*this`.

```
void swap(basic_istream& rhs);
```

- 3 *Effects:* Exchanges the state of `*this` and `rhs` by calling `basic_istream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```
template <class charT, class traits, class Allocator>
void swap(basic_istream<charT, traits, Allocator>& x,
         basic_istream<charT, traits, Allocator>& y);
```

- 4 *Effects:* As if by `x.swap(y)`.

30.8.3.3 Member functions

[istream.members]

```
basic_stringbuf<charT, traits, Allocator>* rdbuf() const;
```

- 1 *Returns:* `const_cast<basic_stringbuf<charT, traits, Allocator>*>(&sb)`.

```
basic_string<charT, traits, Allocator> str() const;
```

- 2 *Returns:* `rdbuf()->str()`.

```
void str(const basic_string<charT, traits, Allocator>& s);
```

- 3 *Effects:* Calls `rdbuf()->str(s)`.

30.8.4 Class template `basic_ostringstream`

[ostream]

```
namespace std {
    template <class charT, class traits = char_traits<charT>,
              class Allocator = allocator<charT>>
    class basic_ostringstream : public basic_ostream<charT, traits> {
    public:
        using char_type      = charT;
        using int_type       = typename traits::int_type;
        using pos_type       = typename traits::pos_type;
        using off_type       = typename traits::off_type;
        using traits_type    = traits;
        using allocator_type = Allocator;

        // 30.8.4.1, constructors
        explicit basic_ostringstream(
```

```

        ios_base::openmode which = ios_base::out);
explicit basic_ostringstream(
    const basic_string<charT, traits, Allocator>& str,
    ios_base::openmode which = ios_base::out);
basic_ostringstream(const basic_ostringstream& rhs) = delete;
basic_ostringstream(basic_ostringstream&& rhs);

// 30.8.4.2, assign and swap
basic_ostringstream& operator=(const basic_ostringstream& rhs) = delete;
basic_ostringstream& operator=(basic_ostringstream&& rhs);
void swap(basic_ostringstream& rhs);

// 30.8.4.3, members
basic_stringbuf<charT, traits, Allocator>* rdbuf() const;

basic_string<charT, traits, Allocator> str() const;
void str(const basic_string<charT, traits, Allocator>& s);
private:
    basic_stringbuf<charT, traits, Allocator> sb; // exposition only
};

template <class charT, class traits, class Allocator>
    void swap(basic_ostringstream<charT, traits, Allocator>& x,
              basic_ostringstream<charT, traits, Allocator>& y);
}

```

- ¹ The class `basic_ostringstream<charT, traits, Allocator>` supports writing objects of class `basic_string<charT, traits, Allocator>`. It uses a `basic_stringbuf` object to control the associated storage. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the `stringbuf` object.

30.8.4.1 `basic_ostringstream` constructors

[`ostreamstream.cons`]

```

explicit basic_ostringstream(
    ios_base::openmode which = ios_base::out);

```

- ¹ *Effects:* Constructs an object of class `basic_ostringstream`, initializing the base class with `basic_ostream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(which | ios_base::out)` (30.8.2.1).

```

explicit basic_ostringstream(
    const basic_string<charT, traits, Allocator>& str,
    ios_base::openmode which = ios_base::out);

```

- ² *Effects:* Constructs an object of class `basic_ostringstream<charT, traits>`, initializing the base class with `basic_ostream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(str, which | ios_base::out)` (30.8.2.1).

```

basic_ostringstream(basic_ostringstream&& rhs);

```

- ³ *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_stringbuf`. Next `basic_ostream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_stringbuf`.

30.8.4.2 Assign and swap

[`ostreamstream.assign`]

```

basic_ostringstream& operator=(basic_ostringstream&& rhs);

```

1 *Effects:* Move assigns the base and members of **this* from the base and corresponding members of *rhs*.

2 *Returns:* **this*.

```
void swap(basic_ostringstream& rhs);
```

3 *Effects:* Exchanges the state of **this* and *rhs* by calling `basic_ostream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```
template <class charT, class traits, class Allocator>
    void swap(basic_ostringstream<charT, traits, Allocator>& x,
              basic_ostringstream<charT, traits, Allocator>& y);
```

4 *Effects:* As if by `x.swap(y)`.

30.8.4.3 Member functions

[ostringstream.members]

```
basic_stringbuf<charT, traits, Allocator>* rdbuf() const;
```

1 *Returns:* `const_cast<basic_stringbuf<charT, traits, Allocator>*>(&sb)`.

```
basic_string<charT, traits, Allocator> str() const;
```

2 *Returns:* `rdbuf()->str()`.

```
void str(const basic_string<charT, traits, Allocator>& s);
```

3 *Effects:* Calls `rdbuf()->str(s)`.

30.8.5 Class template `basic_stringstream`

[stringstream]

```
namespace std {
    template <class charT, class traits = char_traits<charT>,
              class Allocator = allocator<charT>>
    class basic_stringstream : public basic_istream<charT, traits> {
    public:
        using char_type      = charT;
        using int_type       = typename traits::int_type;
        using pos_type       = typename traits::pos_type;
        using off_type       = typename traits::off_type;
        using traits_type    = traits;
        using allocator_type = Allocator;

        // 30.8.5.1, constructors
        explicit basic_stringstream(
            ios_base::openmode which = ios_base::out | ios_base::in);
        explicit basic_stringstream(
            const basic_string<charT, traits, Allocator>& str,
            ios_base::openmode which = ios_base::out | ios_base::in);
        basic_stringstream(const basic_stringstream& rhs) = delete;
        basic_stringstream(basic_stringstream&& rhs);

        // 30.8.5.2, assign and swap
        basic_stringstream& operator=(const basic_stringstream& rhs) = delete;
        basic_stringstream& operator=(basic_stringstream&& rhs);
        void swap(basic_stringstream& rhs);

        // 30.8.5.3, members
        basic_stringbuf<charT, traits, Allocator>* rdbuf() const;
```

```

    basic_string<charT, traits, Allocator> str() const;
    void str(const basic_string<charT, traits, Allocator>& str);

private:
    basic_stringbuf<charT, traits> sb; // exposition only
};

template <class charT, class traits, class Allocator>
    void swap(basic_stringstream<charT, traits, Allocator>& x,
              basic_stringstream<charT, traits, Allocator>& y);
}

```

- ¹ The class template `basic_stringstream<charT, traits>` supports reading and writing from objects of class `basic_string<charT, traits, Allocator>`. It uses a `basic_stringbuf<charT, traits, Allocator>` object to control the associated sequence. For the sake of exposition, the maintained data is presented here as

(1.1) — `sb`, the `stringbuf` object.

30.8.5.1 `basic_stringstream` constructors

[`stringstream.cons`]

```

explicit basic_stringstream(
    ios_base::openmode which = ios_base::out | ios_base::in);

```

- ¹ *Effects:* Constructs an object of class `basic_stringstream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(which)`.

```

explicit basic_stringstream(
    const basic_string<charT, traits, Allocator>& str,
    ios_base::openmode which = ios_base::out | ios_base::in);

```

- ² *Effects:* Constructs an object of class `basic_stringstream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_stringbuf<charT, traits, Allocator>(str, which)`.

```

basic_stringstream(basic_stringstream&& rhs);

```

- ³ *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_stringbuf`. Next `basic_istream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_stringbuf`.

30.8.5.2 Assign and swap

[`stringstream.assign`]

```

basic_stringstream& operator=(basic_stringstream&& rhs);

```

- ¹ *Effects:* Move assigns the base and members of `*this` from the base and corresponding members of `rhs`.

- ² *Returns:* `*this`.

```

void swap(basic_stringstream& rhs);

```

- ³ *Effects:* Exchanges the state of `*this` and `rhs` by calling `basic_istream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```

template <class charT, class traits, class Allocator>
    void swap(basic_stringstream<charT, traits, Allocator>& x,
              basic_stringstream<charT, traits, Allocator>& y);

```

- ⁴ *Effects:* As if by `x.swap(y)`.

30.8.5.3 Member functions

[stringstream.members]

```
basic_stringbuf<charT, traits, Allocator>* rdbuf() const;
```

¹ *Returns:* `const_cast<basic_stringbuf<charT, traits, Allocator>*>(&sb)`

```
basic_string<charT, traits, Allocator> str() const;
```

² *Returns:* `rdbuf()->str()`.

```
void str(const basic_string<charT, traits, Allocator>& str);
```

³ *Effects:* Calls `rdbuf()->str(str)`.

30.9 File-based streams

[file.streams]

30.9.1 Header <fstream> synopsis

[fstream.syn]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
        class basic_filebuf;
    using filebuf = basic_filebuf<char>;
    using wfilebuf = basic_filebuf<wchar_t>;

    template <class charT, class traits = char_traits<charT>>
        class basic_ifstream;
    using ifstream = basic_ifstream<char>;
    using wifstream = basic_ifstream<wchar_t>;

    template <class charT, class traits = char_traits<charT>>
        class basic_ofstream;
    using ofstream = basic_ofstream<char>;
    using wofstream = basic_ofstream<wchar_t>;

    template <class charT, class traits = char_traits<charT>>
        class basic_fstream;
    using fstream = basic_fstream<char>;
    using wfstream = basic_fstream<wchar_t>;
}
```

¹ The header <fstream> defines four class templates and eight types that associate stream buffers with files and assist reading and writing files.

² [Note: The class template `basic_filebuf` treats a file as a source or sink of bytes. In an environment that uses a large character set, the file typically holds multibyte character sequences and the `basic_filebuf` object converts those multibyte sequences into wide character sequences. — end note]

³ In this subclause, member functions taking arguments of `const filesystem::path::value_type*` are only be provided on systems where `filesystem::path::value_type` (30.10.8) is not `char`. [Note: These functions enable class `path` support for systems with a wide native path character type, such as `wchar_t`. — end note]

30.9.2 Class template `basic_filebuf`

[filebuf]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
        class basic_filebuf : public basic_streambuf<charT, traits> {
    public:
        using char_type = charT;
        using int_type = typename traits::int_type;
        using pos_type = typename traits::pos_type;
```



```

using off_type    = typename traits::off_type;
using traits_type = traits;

// 30.9.2.1, constructors/destructor
basic_filebuf();
basic_filebuf(const basic_filebuf& rhs) = delete;
basic_filebuf(basic_filebuf&& rhs);
virtual ~basic_filebuf();

// 30.9.2.2, assign and swap
basic_filebuf& operator=(const basic_filebuf& rhs) = delete;
basic_filebuf& operator=(basic_filebuf&& rhs);
void swap(basic_filebuf& rhs);

// 30.9.2.3, members
bool is_open() const;
basic_filebuf* open(const char* s, ios_base::openmode mode);
basic_filebuf* open(const filesystem::path::value_type* s,
                    ios_base::openmode mode); // wide systems only; see 30.9.1
basic_filebuf* open(const string& s,
                    ios_base::openmode mode);
basic_filebuf* open(const filesystem::path& s,
                    ios_base::openmode mode);
basic_filebuf* close();

protected:
// 30.9.2.4, overridden virtual functions
streamsize showmanyc() override;
int_type underflow() override;
int_type uflow() override;
int_type pbackfail(int_type c = traits::eof()) override;
int_type overflow (int_type c = traits::eof()) override;

basic_streambuf<charT, traits>* setbuf(char_type* s,
                                     streamsize n) override;
pos_type seekoff(off_type off, ios_base::seekdir way,
                 ios_base::openmode which
                 = ios_base::in | ios_base::out) override;
pos_type seekpos(pos_type sp,
                 ios_base::openmode which
                 = ios_base::in | ios_base::out) override;
int      sync() override;
void     imbue(const locale& loc) override;
};

template <class charT, class traits>
void swap(basic_filebuf<charT, traits>& x,
          basic_filebuf<charT, traits>& y);
}

```

¹ The class `basic_filebuf<charT, traits>` associates both the input sequence and the output sequence with a file.

² The restrictions on reading and writing a sequence controlled by an object of class `basic_filebuf<charT, traits>` are the same as for reading and writing with the C standard library `FILES`.

3 In particular:

- (3.1) — If the file is not open for reading the input sequence cannot be read.
 - (3.2) — If the file is not open for writing the output sequence cannot be written.
 - (3.3) — A joint file position is maintained for both the input sequence and the output sequence.
- 4 An instance of `basic_filebuf` behaves as described in 30.9.2 provided `traits::pos_type` is `fpos<traits::state_type>`. Otherwise the behavior is undefined.
- 5 In order to support file I/O and multibyte/wide character conversion, conversions are performed using members of a facet, referred to as `a_codecvt` in following sections, obtained as if by

```
const codecvt<charT, char, typename traits::state_type>& a_codecvt =
    use_facet<codecvt<charT, char, typename traits::state_type>>(getloc());
```

30.9.2.1 `basic_filebuf` constructors

[filebuf.cons]

```
basic_filebuf();
```

1 *Effects:* Constructs an object of class `basic_filebuf<charT, traits>`, initializing the base class with `basic_streambuf<charT, traits>()` (30.6.3.1).

2 *Postconditions:* `is_open() == false`.

```
basic_filebuf(basic_filebuf&& rhs);
```

3 *Effects:* Move constructs from the rvalue `rhs`. It is implementation-defined whether the sequence pointers in `*this` (`eback()`, `gptr()`, `egptr()`, `pbase()`, `pptr()`, `epptr()`) obtain the values which `rhs` had. Whether they do or not, `*this` and `rhs` reference separate buffers (if any at all) after the construction. Additionally `*this` references the file which `rhs` did before the construction, and `rhs` references no file after the construction. The openmode, locale and any other state of `rhs` is also copied.

4 *Postconditions:* Let `rhs_p` refer to the state of `rhs` just prior to this construction and let `rhs_a` refer to the state of `rhs` just after this construction.

- (4.1) — `is_open() == rhs_p.is_open()`
- (4.2) — `rhs_a.is_open() == false`
- (4.3) — `gptr() - eback() == rhs_p.gptr() - rhs_p.eback()`
- (4.4) — `egptr() - eback() == rhs_p.egptr() - rhs_p.eback()`
- (4.5) — `pptr() - pbase() == rhs_p.pptr() - rhs_p.pbase()`
- (4.6) — `epptr() - pbase() == rhs_p.epptr() - rhs_p.pbase()`
- (4.7) — `if (eback()) eback() != rhs_a.eback()`
- (4.8) — `if (gptr()) gptr() != rhs_a.gptr()`
- (4.9) — `if (egptr()) egptr() != rhs_a.egptr()`
- (4.10) — `if (pbase()) pbase() != rhs_a.pbase()`
- (4.11) — `if (pptr()) pptr() != rhs_a.pptr()`
- (4.12) — `if (epptr()) epptr() != rhs_a.epptr()`

```
virtual ~basic_filebuf();
```

5 *Effects:* Destroys an object of class `basic_filebuf<charT, traits>`. Calls `close()`. If an exception occurs during the destruction of the object, including the call to `close()`, the exception is caught but not rethrown (see 20.5.5.12).

30.9.2.2 Assign and swap

[filebuf.assign]

```
basic_filebuf& operator=(basic_filebuf&& rhs);
```

1 *Effects:* Calls `close()` then move assigns from `rhs`. After the move assignment `*this` has the observable state it would have had if it had been move constructed from `rhs` (see 30.9.2.1).

2 *Returns:* `*this`.

```
void swap(basic_filebuf& rhs);
```

3 *Effects:* Exchanges the state of `*this` and `rhs`.

```
template <class charT, class traits>
    void swap(basic_filebuf<charT, traits>& x,
              basic_filebuf<charT, traits>& y);
```

4 *Effects:* As if by `x.swap(y)`.

30.9.2.3 Member functions

[filebuf.members]

```
bool is_open() const;
```

1 *Returns:* `true` if a previous call to `open` succeeded (returned a non-null value) and there has been no intervening call to `close`.

```
basic_filebuf* open(const char* s, ios_base::openmode mode);
basic_filebuf* open(const filesystem::path::value_type* s,
                    ios_base::openmode mode); // wide systems only; see 30.9.1
```

2 *Effects:* If `is_open() != false`, returns a null pointer. Otherwise, initializes the `filebuf` as required. It then opens a file, if possible, whose name is the NTBS `s` (as if by calling `fopen(s, modstr)`). The NTBS `modstr` is determined from `mode & ~ios_base::ate` as indicated in Table 117. If `mode` is not some combination of flags shown in the table then the open fails.

3 If the open operation succeeds and `(mode & ios_base::ate) != 0`, positions the file to the end (as if by calling `fseek(file, 0, SEEK_END)`).³²⁷

4 If the repositioning operation fails, calls `close()` and returns a null pointer to indicate failure.

5 *Returns:* `this` if successful, a null pointer otherwise.

```
basic_filebuf* open(const string& s, ios_base::openmode mode);
basic_filebuf* open(const filesystem::path& s, ios_base::openmode mode);
```

6 *Returns:* `open(s.c_str(), mode)`;

```
basic_filebuf* close();
```

7 *Effects:* If `is_open() == false`, returns a null pointer. If a put area exists, calls `overflow(traits::eof())` to flush characters. If the last virtual member function called on `*this` (between `underflow`, `overflow`, `seekoff`, and `seekpos`) was `overflow` then calls `a_codecvt.unshift` (possibly several times) to determine a termination sequence, inserts those characters and calls `overflow(traits::eof())` again. Finally, regardless of whether any of the preceding calls fails or throws an exception, the function closes the file (as if by calling `fclose(file)`). If any of the calls made by the function, including `fclose`, fails, `close` fails by returning a null pointer. If one of these calls throws an exception, the exception is caught and rethrown after closing the file.

8 *Returns:* `this` on success, a null pointer otherwise.

³²⁷ The macro `SEEK_END` is defined, and the function signatures `fopen(const char*, const char*)` and `fseek(FILE*, long, int)` are declared, in `<cstdio>` (30.11.1).

Table 117 — File open modes

ios_base flag combination					stdio equivalent
binary	in	out	trunc	app	
		+			"w"
		+		+	"a"
				+	"a"
		+	+		"w"
	+				"r"
	+	+			"r+"
	+	+	+		"w+"
	+	+		+	"a+"
	+			+	"a+"
+		+			"wb"
+		+		+	"ab"
+				+	"ab"
+		+	+		"wb"
+	+				"rb"
+	+	+			"r+b"
+	+	+	+		"w+b"
+	+	+		+	"a+b"
+	+			+	"a+b"

⁹ *Postconditions:* `is_open() == false`.

30.9.2.4 Overridden virtual functions

[filebuf.virtuals]

`streamsize showmanyc()` override;

¹ *Effects:* Behaves the same as `basic_streambuf::showmanyc()` (30.6.3.4).

² *Remarks:* An implementation might well provide an overriding definition for this function signature if it can determine that more characters can be read from the input sequence.

`int_type underflow()` override;

³ *Effects:* Behaves according to the description of `basic_streambuf<charT, traits>::underflow()`, with the specialization that a sequence of characters is read from the input sequence as if by reading from the associated file into an internal buffer (`extern_buf`) and then as if by doing:

```
char  extern_buf[XSIZE];
char* extern_end;
charT intern_buf[ISIZE];
charT* intern_end;
codecvt_base::result r =
    a_codecvt.in(state, extern_buf, extern_buf+XSIZE, extern_end,
                intern_buf, intern_buf+ISIZE, intern_end);
```

This shall be done in such a way that the class can recover the position (`fpos_t`) corresponding to each character between `intern_buf` and `intern_end`. If the value of `r` indicates that `a_codecvt.in()` ran out of space in `intern_buf`, retry with a larger `intern_buf`.

`int_type uflow()` override;

- 4 *Effects:* Behaves according to the description of `basic_streambuf<charT, traits>::uflow()`, with the specialization that a sequence of characters is read from the input with the same method as used by `underflow`.

```
int_type pbackfail(int_type c = traits::eof()) override;
```

- 5 *Effects:* Puts back the character designated by `c` to the input sequence, if possible, in one of three ways:
- (5.1) — If `traits::eq_int_type(c, traits::eof())` returns `false` and if the function makes a putback position available and if `traits::eq(to_char_type(c), gptr()[-1])` returns `true`, decrements the next pointer for the input sequence, `gptr()`.
Returns: `c`.
 - (5.2) — If `traits::eq_int_type(c, traits::eof())` returns `false` and if the function makes a putback position available and if the function is permitted to assign to the putback position, decrements the next pointer for the input sequence, and stores `c` there.
Returns: `c`.
 - (5.3) — If `traits::eq_int_type(c, traits::eof())` returns `true`, and if either the input sequence has a putback position available or the function makes a putback position available, decrements the next pointer for the input sequence, `gptr()`.
Returns: `traits::not_eof(c)`.

6 *Returns:* `traits::eof()` to indicate failure.

7 *Remarks:* If `is_open() == false`, the function always fails.

8 The function does not put back a character directly to the input sequence.

9 If the function can succeed in more than one of these ways, it is unspecified which way is chosen. The function can alter the number of putback positions available as a result of any call.

```
int_type overflow(int_type c = traits::eof()) override;
```

- 10 *Effects:* Behaves according to the description of `basic_streambuf<charT, traits>::overflow(c)`, except that the behavior of “consuming characters” is performed by first converting as if by:

```
charT* b = pbase();
charT* p = pptr();
charT* end;
char xbuf[XSIZE];
char* xbuf_end;
codecvt_base::result r =
    a_codecvt.out(state, b, p, end, xbuf, xbuf+XSIZE, xbuf_end);
```

and then

- (10.1) — If `r == codecvt_base::error` then fail.
- (10.2) — If `r == codecvt_base::noconv` then output characters from `b` up to (and not including) `p`.
- (10.3) — If `r == codecvt_base::partial` then output to the file characters from `xbuf` up to `xbuf_end`, and repeat using characters from `end` to `p`. If output fails, fail (without repeating).
- (10.4) — Otherwise output from `xbuf` to `xbuf_end`, and fail if output fails. At this point if `b != p` and `b == end` (`xbuf` isn't large enough) then increase `XSIZE` and repeat from the beginning.

- 11 *Returns:* `traits::not_eof(c)` to indicate success, and `traits::eof()` to indicate failure. If `is_open() == false`, the function always fails.

```
basic_streambuf* setbuf(char_type* s, streamsize n) override;
```

- 12 *Effects:* If `setbuf(0, 0)` is called on a stream before any I/O has occurred on that stream, the stream becomes unbuffered. Otherwise the results are implementation-defined. “Unbuffered” means that `pbase()` and `pptr()` always return null and output to the file should appear as soon as possible.

```
pos_type seekoff(off_type off, ios_base::seekdir way,
                ios_base::openmode which
                = ios_base::in | ios_base::out) override;
```

- 13 *Effects:* Let `width` denote `a_codecvt.encoding()`. If `is_open() == false`, or `off != 0 && width <= 0`, then the positioning operation fails. Otherwise, if `way != basic_ios::cur` or `off != 0`, and if the last operation was output, then update the output sequence and write any unshift sequence. Next, seek to the new position: if `width > 0`, call `fseek(file, width * off, whence)`, otherwise call `fseek(file, 0, whence)`.

- 14 *Remarks:* “The last operation was output” means either the last virtual operation was overflow or the put buffer is non-empty. “Write any unshift sequence” means, if `width` is less than zero then call `a_codecvt.unshift(state, xbuf, xbuf+XSIZE, xbuf_end)` and output the resulting unshift sequence. The function determines one of three values for the argument `whence`, of type `int`, as indicated in Table 118.

Table 118 — `seekoff` effects

way Value	stdio Equivalent
<code>basic_ios::beg</code>	<code>SEEK_SET</code>
<code>basic_ios::cur</code>	<code>SEEK_CUR</code>
<code>basic_ios::end</code>	<code>SEEK_END</code>

- 15 *Returns:* A newly constructed `pos_type` object that stores the resultant stream position, if possible. If the positioning operation fails, or if the object cannot represent the resultant stream position, returns `pos_type(off_type(-1))`.

```
pos_type seekpos(pos_type sp,
                ios_base::openmode which
                = ios_base::in | ios_base::out) override;
```

- 16 Alters the file position, if possible, to correspond to the position stored in `sp` (as described below). Altering the file position performs as follows:

1. if `(om & ios_base::out) != 0`, then update the output sequence and write any unshift sequence;
2. set the file position to `sp` as if by a call to `fsetpos`;
3. if `(om & ios_base::in) != 0`, then update the input sequence;

where `om` is the open mode passed to the last call to `open()`. The operation fails if `is_open()` returns `false`.

- 17 If `sp` is an invalid stream position, or if the function positions neither sequence, the positioning operation fails. If `sp` has not been obtained by a previous successful call to one of the positioning functions (`seekoff` or `seekpos`) on the same file the effects are undefined.

- 18 *Returns:* `sp` on success. Otherwise returns `pos_type(off_type(-1))`.

```
int sync() override;
```

- 19 *Effects:* If a put area exists, calls `filebuf::overflow` to write the characters to the file, then flushes the file as if by calling `fflush(file)`. If a get area exists, the effect is implementation-defined.

```
void imbue(const locale& loc) override;
```

20 *Requires:* If the file is not positioned at its beginning and the encoding of the current locale as determined by `a_codecvt.encoding()` is state-dependent (25.4.1.4.2) then that facet is the same as the corresponding facet of `loc`.

21 *Effects:* Causes characters inserted or extracted after this call to be converted according to `loc` until another call of `imbue`.

22 *Remarks:* This may require reversion of previously converted characters. This in turn may require the implementation to be able to reconstruct the original contents of the file.

30.9.3 Class template `basic_ifstream`

[`ifstream`]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_ifstream : public basic_istream<charT, traits> {
    public:
        using char_type    = charT;
        using int_type      = typename traits::int_type;
        using pos_type      = typename traits::pos_type;
        using off_type      = typename traits::off_type;
        using traits_type   = traits;

        // 30.9.3.1, constructors
        basic_ifstream();
        explicit basic_ifstream(const char* s,
                               ios_base::openmode mode = ios_base::in);
        explicit basic_ifstream(const filesystem::path::value_type* s,
                               ios_base::openmode mode = ios_base::in); // wide systems only; see 30.9.1
        explicit basic_ifstream(const string& s,
                               ios_base::openmode mode = ios_base::in);
        explicit basic_ifstream(const filesystem::path& s,
                               ios_base::openmode mode = ios_base::in);
        basic_ifstream(const basic_ifstream& rhs) = delete;
        basic_ifstream(basic_ifstream&& rhs);

        // 30.9.3.2, assign and swap
        basic_ifstream& operator=(const basic_ifstream& rhs) = delete;
        basic_ifstream& operator=(basic_ifstream&& rhs);
        void swap(basic_ifstream& rhs);

        // 30.9.3.3, members
        basic_filebuf<charT, traits>* rdbuf() const;

        bool is_open() const;
        void open(const char* s, ios_base::openmode mode = ios_base::in);
        void open(const filesystem::path::value_type* s,
                  ios_base::openmode mode = ios_base::in); // wide systems only; see 30.9.1
        void open(const string& s, ios_base::openmode mode = ios_base::in);
        void open(const filesystem::path& s, ios_base::openmode mode = ios_base::in);
        void close();
    private:
        basic_filebuf<charT, traits> sb; // exposition only
    };

    template <class charT, class traits>
```

```

        void swap(basic_ifstream<charT, traits>& x,
                  basic_ifstream<charT, traits>& y);
    }

```

- ¹ The class `basic_ifstream<charT, traits>` supports reading from named files. It uses a `basic_filebuf<charT, traits>` object to control the associated sequence. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the filebuf object.

30.9.3.1 `basic_ifstream` constructors

[`ifstream.cons`]

```
basic_ifstream();
```

- ¹ *Effects:* Constructs an object of class `basic_ifstream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()` (30.7.4.1.1, 30.9.2.1).

```
explicit basic_ifstream(const char* s,
                       ios_base::openmode mode = ios_base::in);
explicit basic_ifstream(const filesystem::path::value_type* s,
                       ios_base::openmode mode = ios_base::in); // wide systems only; see 30.9.1
```

- ² *Effects:* Constructs an object of class `basic_ifstream`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()` (30.7.4.1.1, 30.9.2.1), then calls `rdbuf()->open(s, mode | ios_base::in)`. If that function returns a null pointer, calls `setstate(failbit)`.

```
explicit basic_ifstream(const string& s,
                       ios_base::openmode mode = ios_base::in);
explicit basic_ifstream(const filesystem::path& s,
                       ios_base::openmode mode = ios_base::in);
```

- ³ *Effects:* The same as `basic_ifstream(s.c_str(), mode)`.

```
basic_ifstream(basic_ifstream&& rhs);
```

- ⁴ *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_filebuf`. Next `basic_istream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_filebuf`.

30.9.3.2 Assign and swap

[`ifstream.assign`]

```
basic_ifstream& operator=(basic_ifstream&& rhs);
```

- ¹ *Effects:* Move assigns the base and members of `*this` from the base and corresponding members of `rhs`.

- ² *Returns:* `*this`.

```
void swap(basic_ifstream& rhs);
```

- ³ *Effects:* Exchanges the state of `*this` and `rhs` by calling `basic_istream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```
template <class charT, class traits>
void swap(basic_ifstream<charT, traits>& x,
          basic_ifstream<charT, traits>& y);
```

- ⁴ *Effects:* As if by `x.swap(y)`.

30.9.3.3 Member functions**[ifstream.members]**

```

basic_filebuf<charT, traits>* rdbuf() const;
1     Returns: const_cast<basic_filebuf<charT, traits>*>(&sb).

bool is_open() const;
2     Returns: rdbuf()->is_open().

void open(const char* s, ios_base::openmode mode = ios_base::in);
void open(const filesystem::path::value_type* s,
          ios_base::openmode mode = ios_base::in); // wide systems only; see 30.9.1
3     Effects: Calls rdbuf()->open(s, mode | ios_base::in). If that function does not return a null
        pointer calls clear(), otherwise calls setstate(failbit) (which may throw ios_base::failure)
        (30.5.5.4).

void open(const string& s, ios_base::openmode mode = ios_base::in);
void open(const filesystem::path& s, ios_base::openmode mode = ios_base::in);
4     Effects: Calls open(s.c_str(), mode).

void close();
5     Effects: Calls rdbuf()->close() and, if that function returns a null pointer, calls setstate(failbit)
        (which may throw ios_base::failure) (30.5.5.4).

```

30.9.4 Class template basic_ofstream**[ofstream]**

```

namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_ofstream : public basic_ostream<charT, traits> {
    public:
        using char_type    = charT;
        using int_type      = typename traits::int_type;
        using pos_type      = typename traits::pos_type;
        using off_type      = typename traits::off_type;
        using traits_type   = traits;

        // 30.9.4.1, constructors
        basic_ofstream();
        explicit basic_ofstream(const char* s,
                               ios_base::openmode mode = ios_base::out);
        explicit basic_ofstream(const filesystem::path::value_type* s,
                               ios_base::openmode mode = ios_base::out); // wide systems only; see 30.9.1
        explicit basic_ofstream(const string& s,
                               ios_base::openmode mode = ios_base::out);
        explicit basic_ofstream(const filesystem::path& s,
                               ios_base::openmode mode = ios_base::out);
        basic_ofstream(const basic_ofstream& rhs) = delete;
        basic_ofstream(basic_ofstream&& rhs);

        // 30.9.4.2, assign and swap
        basic_ofstream& operator=(const basic_ofstream& rhs) = delete;
        basic_ofstream& operator=(basic_ofstream&& rhs);
        void swap(basic_ofstream& rhs);

        // 30.9.4.3, members

```

```

    basic_filebuf<charT, traits>* rdbuf() const;

    bool is_open() const;
    void open(const char* s, ios_base::openmode mode = ios_base::out);
    void open(const filesystem::path::value_type* s,
              ios_base::openmode mode = ios_base::out); // wide systems only; see 30.9.1
    void open(const string& s, ios_base::openmode mode = ios_base::out);
    void open(const filesystem::path& s, ios_base::openmode mode = ios_base::out);
    void close();
private:
    basic_filebuf<charT, traits> sb; // exposition only
};

template <class charT, class traits>
    void swap(basic_ofstream<charT, traits>& x,
              basic_ofstream<charT, traits>& y);
}

```

- ¹ The class `basic_ofstream<charT, traits>` supports writing to named files. It uses a `basic_filebuf<charT, traits>` object to control the associated sequence. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the filebuf object.

30.9.4.1 `basic_ofstream` constructors

[ofstream.cons]

```
basic_ofstream();
```

- ¹ *Effects:* Constructs an object of class `basic_ofstream<charT, traits>`, initializing the base class with `basic_ostream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()` (30.7.5.1.1, 30.9.2.1).

```

explicit basic_ofstream(const char* s,
                       ios_base::openmode mode = ios_base::out);
explicit basic_ofstream(const filesystem::path::value_type* s,
                       ios_base::openmode mode = ios_base::out); // wide systems only; see 30.9.1

```

- ² *Effects:* Constructs an object of class `basic_ofstream<charT, traits>`, initializing the base class with `basic_ostream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()` (30.7.5.1.1, 30.9.2.1), then calls `rdbuf()->open(s, mode | ios_base::out)`. If that function returns a null pointer, calls `setstate(failbit)`.

```

explicit basic_ofstream(const string& s,
                       ios_base::openmode mode = ios_base::out);
explicit basic_ofstream(const filesystem::path& s,
                       ios_base::openmode mode = ios_base::out);

```

- ³ *Effects:* The same as `basic_ofstream(s.c_str(), mode)`.

```
basic_ofstream(basic_ofstream&& rhs);
```

- ⁴ *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_filebuf`. Next `basic_ostream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_filebuf`.

30.9.4.2 Assign and swap

[ofstream.assign]

```
basic_ofstream& operator=(basic_ofstream&& rhs);
```

1 *Effects:* Move assigns the base and members of **this* from the base and corresponding members of *rhs*.

2 *Returns:* **this*.

```
void swap(basic_ofstream& rhs);
```

3 *Effects:* Exchanges the state of **this* and *rhs* by calling `basic_ofstream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```
template <class charT, class traits>
    void swap(basic_ofstream<charT, traits>& x,
              basic_ofstream<charT, traits>& y);
```

4 *Effects:* As if by `x.swap(y)`.

30.9.4.3 Member functions

[ofstream.members]

```
basic_filebuf<charT, traits>* rdbuf() const;
```

1 *Returns:* `const_cast<basic_filebuf<charT, traits>*>(&sb)`.

```
bool is_open() const;
```

2 *Returns:* `rdbuf()->is_open()`.

```
void open(const char* s, ios_base::openmode mode = ios_base::out);
```

```
void open(const filesystem::path::value_type* s,
          ios_base::openmode mode = ios_base::out); // wide systems only; see 30.9.1
```

3 *Effects:* Calls `rdbuf()->open(s, mode | ios_base::out)`. If that function does not return a null pointer calls `clear()`, otherwise calls `setstate(failbit)` (which may throw `ios_base::failure`) (30.5.5.4).

```
void close();
```

4 *Effects:* Calls `rdbuf()->close()` and, if that function fails (returns a null pointer), calls `setstate(failbit)` (which may throw `ios_base::failure`) (30.5.5.4).

```
void open(const string& s, ios_base::openmode mode = ios_base::out);
```

```
void open(const filesystem::path& s, ios_base::openmode mode = ios_base::out);
```

5 *Effects:* Calls `open(s.c_str(), mode)`.

30.9.5 Class template `basic_fstream`

[fstream]

```
namespace std {
    template <class charT, class traits = char_traits<charT>>
    class basic_fstream : public basic_iostream<charT, traits> {
    public:
        using char_type    = charT;
        using int_type      = typename traits::int_type;
        using pos_type      = typename traits::pos_type;
        using off_type      = typename traits::off_type;
        using traits_type    = traits;

        // 30.9.5.1, constructors
        basic_fstream();
        explicit basic_fstream(
            const char* s,
            ios_base::openmode mode = ios_base::in | ios_base::out);
```

```

explicit basic_fstream(
    const std::filesystem::path::value_type* s,
    ios_base::openmode mode = ios_base::in|ios_base::out); // wide systems only; see 30.9.1
explicit basic_fstream(
    const string& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
explicit basic_fstream(
    const filesystem::path& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
basic_fstream(const basic_fstream& rhs) = delete;
basic_fstream(basic_fstream&& rhs);

// 30.9.5.2, assign and swap
basic_fstream& operator=(const basic_fstream& rhs) = delete;
basic_fstream& operator=(basic_fstream&& rhs);
void swap(basic_fstream& rhs);

// 30.9.5.3, members
basic_filebuf<charT, traits>* rdbuf() const;
bool is_open() const;
void open(
    const char* s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
void open(
    const std::filesystem::path::value_type* s,
    ios_base::openmode mode = ios_base::in|ios_base::out); // wide systems only; see 30.9.1
void open(
    const string& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
void open(
    const filesystem::path& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
void close();

private:
    basic_filebuf<charT, traits> sb; // exposition only
};

template <class charT, class traits>
void swap(basic_fstream<charT, traits>& x,
          basic_fstream<charT, traits>& y);
}

```

- ¹ The class template `basic_fstream<charT, traits>` supports reading and writing from named files. It uses a `basic_filebuf<charT, traits>` object to control the associated sequences. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the `basic_filebuf` object.

30.9.5.1 basic_fstream constructors

[fstream.cons]

```
basic_fstream();
```

- ¹ *Effects:* Constructs an object of class `basic_fstream<charT, traits>`, initializing the base class with `basic_iostream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()`.

```
explicit basic_fstream(
```

```

    const char* s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
explicit basic_fstream(
    const filesystem::path::value_type* s,
    ios_base::openmode mode = ios_base::in | ios_base::out); // wide systems only; see 30.9.1

```

- 2 *Effects:* Constructs an object of class `basic_fstream<charT, traits>`, initializing the base class with `basic_istream(&sb)` and initializing `sb` with `basic_filebuf<charT, traits>()`. Then calls `rdbuf()->open(s, mode)`. If that function returns a null pointer, calls `setstate(failbit)`.

```

explicit basic_fstream(
    const string& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
explicit basic_fstream(
    const filesystem::path& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);

```

- 3 *Effects:* The same as `basic_fstream(s.c_str(), mode)`.

```
basic_fstream(basic_fstream&& rhs);
```

- 4 *Effects:* Move constructs from the rvalue `rhs`. This is accomplished by move constructing the base class, and the contained `basic_filebuf`. Next `basic_istream<charT, traits>::set_rdbuf(&sb)` is called to install the contained `basic_filebuf`.

30.9.5.2 Assign and swap

[fstream.assign]

```
basic_fstream& operator=(basic_fstream&& rhs);
```

- 1 *Effects:* Move assigns the base and members of `*this` from the base and corresponding members of `rhs`.

- 2 *Returns:* `*this`.

```
void swap(basic_fstream& rhs);
```

- 3 *Effects:* Exchanges the state of `*this` and `rhs` by calling `basic_istream<charT, traits>::swap(rhs)` and `sb.swap(rhs.sb)`.

```

template <class charT, class traits>
void swap(basic_fstream<charT, traits>& x,
          basic_fstream<charT, traits>& y);

```

- 4 *Effects:* As if by `x.swap(y)`.

30.9.5.3 Member functions

[fstream.members]

```
basic_filebuf<charT, traits>* rdbuf() const;
```

- 1 *Returns:* `const_cast<basic_filebuf<charT, traits>*>(&sb)`.

```
bool is_open() const;
```

- 2 *Returns:* `rdbuf()->is_open()`.

```

void open(
    const char* s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
void open(
    const filesystem::path::value_type* s,
    ios_base::openmode mode = ios_base::in | ios_base::out); // wide systems only; see 30.9.1

```

- ³ *Effects:* Calls `rdbuf()->open(s, mode)`. If that function does not return a null pointer calls `clear()`, otherwise calls `setstate(failbit)` (which may throw `ios_base::failure`) (30.5.5.4).

```
void open(
    const string& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
void open(
    const filesystem::path& s,
    ios_base::openmode mode = ios_base::in | ios_base::out);
```

- ⁴ *Effects:* Calls `open(s.c_str(), mode)`.

```
void close();
```

- ⁵ *Effects:* Calls `rdbuf()->close()` and, if that function returns a null pointer, calls `setstate(failbit)` (which may throw `ios_base::failure`) (30.5.5.4).

30.10 File systems [filesystems]

30.10.1 General [fs.general]

- ¹ This subclause describes operations on file systems and their components, such as paths, regular files, and directories.

30.10.2 Conformance [fs.conformance]

- ¹ Conformance is specified in terms of behavior. Ideal behavior is not always implementable, so the conformance subclauses take that into account.

30.10.2.1 POSIX conformance [fs.conform.9945]

- ¹ Some behavior is specified by reference to POSIX (30.10.3). How such behavior is actually implemented is unspecified. [*Note:* This constitutes an “as if” rule allowing implementations to call native operating system or other APIs. — *end note*]
- ² Implementations are encouraged to provide such behavior as it is defined by POSIX. Implementations shall document any behavior that differs from the behavior defined by POSIX. Implementations that do not support exact POSIX behavior are encouraged to provide behavior as close to POSIX behavior as is reasonable given the limitations of actual operating systems and file systems. If an implementation cannot provide any reasonable behavior, the implementation shall report an error as specified in 30.10.7. [*Note:* This allows users to rely on an exception being thrown or an error code being set when an implementation cannot provide any reasonable behavior. — *end note*]
- ³ Implementations are not required to provide behavior that is not supported by a particular file system. [*Example:* The FAT file system used by some memory cards, camera memory, and floppy disks does not support hard links, symlinks, and many other features of more capable file systems, so implementations are not required to support those features on the FAT file system but instead are required to report an error as described above. — *end example*]

30.10.2.2 Operating system dependent behavior conformance [fs.conform.os]

- ¹ Some behavior is specified as being operating system dependent (30.10.4.12). The operating system an implementation is dependent upon is implementation-defined.
- ² It is permissible for an implementation to be dependent upon an operating system emulator rather than the actual underlying operating system.

30.10.2.3 File system race behavior [fs.race.behavior]

- ¹ Behavior is undefined if calls to functions provided by this subclause introduce a file system race (30.10.4.5).

- ² If the possibility of a file system race would make it unreliable for a program to test for a precondition before calling a function described herein, *Requires:* is not specified for the function. [*Note:* As a design practice, preconditions are not specified when it is unreasonable for a program to detect them prior to calling the function. — *end note*]

30.10.3 Normative references [fs.norm.ref]

- ¹ This subclause mentions commercially available operating systems for purposes of exposition. ³²⁸

30.10.4 Terms and definitions [fs.definitions]

30.10.4.1 [fs.def.absolute.path]

absolute path

A path that unambiguously identifies the location of a file without reference to an additional starting location. The elements of a path that determine if it is absolute are operating system dependent.

30.10.4.2 [fs.def.directory]

directory

A file within a file system that acts as a container of directory entries that contain information about other files, possibly including other directory files.

30.10.4.3 [fs.def.file]

file

An object within a file system that holds user or system data. Files can be written to, or read from, or both. A file has certain attributes, including type. File types include regular files and directories. Other types of files, such as symbolic links (30.10.4.19), may be supported by the implementation.

30.10.4.4 [fs.def.filesystem]

file system

A collection of files and their attributes.

30.10.4.5 [fs.def.race]

file system race

The condition that occurs when multiple threads, processes, or computers interleave access and modification of the same object within a file system.

30.10.4.6 [fs.def.filename]

filename

The name of a file. Filenames *dot* and *dot-dot*, consisting solely of one and two period characters respectively, have special meaning. The following characteristics of filenames are operating system dependent:

- The permitted characters. [*Example:* Some operating systems prohibit the ASCII control characters (0x00 – 0x1F) in filenames. — *end example*]
- The maximum permitted length.
- Filenames that are not permitted.
- Filenames that have special meaning.
- Case awareness and sensitivity during path resolution.
- Special rules that may apply to file types other than regular files, such as directories.

³²⁸) POSIX® is a registered trademark of The IEEE. Windows® is a registered trademark of Microsoft Corporation. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO or IEC of these products.

30.10.4.7 [fs.def.hardlink] hard link

A link (30.10.4.8) to an existing file. Some file systems support multiple hard links to a file. If the last hard link to a file is removed, the file itself is removed. [*Note*: A hard link can be thought of as a shared-ownership smart pointer to a file. — *end note*]

30.10.4.8 [fs.def.link] link

An object that associates a filename with a file. Several links can associate names with the same file.

30.10.4.9 [fs.def.native.encode] native encoding

For narrow character strings, the operating system dependent current encoding for pathnames (30.10.4.16). For wide character strings, the implementation-defined execution wide-character set encoding (5.3).

30.10.4.10 [fs.def.native] native pathname format

The operating system dependent pathname format accepted by the host operating system.

30.10.4.11 [fs.def.normal.form] normal form

A path in normal form is said to be *normalized*. The process of obtaining a normalized path from a path that is not in normal form is called *normalization*.

Normalization of a generic format pathname means:

1. If the path is empty, stop.
2. Replace each slash character in the *root-name* with a *preferred-separator*.
3. Replace each *directory-separator* with a *preferred-separator*. [*Note*: The generic pathname grammar (30.10.8.1) defines *directory-separator* as one or more slashes and *preferred-separators*. — *end note*]
4. Remove each *dot* filename and any immediately following *directory-separator*.
5. As long as any appear, remove a non-*dot-dot* filename immediately followed by a *directory-separator* and a *dot-dot* filename, along with any immediately following *directory-separator*.
6. If there is a *root-directory*, remove all *dot-dot* filenames and any *directory-separators* immediately following them. [*Note*: These *dot-dot* filenames attempt to refer to nonexistent parent directories. — *end note*]
7. If the last filename is *dot-dot*, remove any trailing *directory-separator*.
8. If the path is empty, add a *dot*.

30.10.4.12 [fs.def.osdep] operating system dependent behavior

Behavior that is dependent upon the behavior and characteristics of an operating system. See 30.10.2.2.

30.10.4.13 [fs.def.parent] parent directory

⟨of a directory⟩ the directory that both contains a directory entry for the given directory and is represented by the filename *dot-dot* in the given directory.

30.10.4.14 [fs.def.parent.other] parent directory

⟨of other types of files⟩ a directory containing a directory entry for the file under discussion.

30.10.4.15 [fs.def.path] path

A sequence of elements that identify the location of a file within a filesystem. The elements are the *root-name_{opt}*, *root-directory_{opt}*, and an optional sequence of filenames. The maximum number of elements in the sequence is operating system dependent.

30.10.4.16 [fs.def.pathname] pathname

A character string that represents the name of a path. Pathnames are formatted according to the generic pathname format grammar (30.10.8.1) or an operating system dependent native pathname format.

30.10.4.17 [fs.def.pathres] pathname resolution

Pathname resolution is the operating system dependent mechanism for resolving a pathname to a particular file in a file hierarchy. There may be multiple pathnames that resolve to the same file. [*Example:* POSIX specifies the mechanism in section 4.11, Pathname resolution. — *end example*]

30.10.4.18 [fs.def.rel.path] relative path

A path that is not absolute, and as such, only unambiguously identifies the location of a file when resolved (30.10.4.17) relative to an implied starting location. The elements of a path that determine if it is relative are operating system dependent. [*Note:* Pathnames “.” and “..” are relative paths. — *end note*]

30.10.4.19 [fs.def.symlink] symbolic link

A type of file with the property that when the file is encountered during pathname resolution, a string stored by the file is used to modify the pathname resolution. [*Note:* Symbolic links are often called symlinks. A symbolic link can be thought of as a raw pointer to a file. If the file pointed to does not exist, the symbolic link is said to be a “dangling” symbolic link. — *end note*]

30.10.5 Requirements [fs.req]

- ¹ Throughout this subclause, `char`, `wchar_t`, `char16_t`, and `char32_t` are collectively called *encoded character types*.
- ² Functions with template parameters named `EcharT` shall not participate in overload resolution unless `EcharT` is one of the encoded character types.
- ³ Template parameters named `InputIterator` shall meet the input iterator requirements (27.2.3) and shall have a value type that is one of the encoded character types.
- ⁴ [*Note:* Use of an encoded character type implies an associated character set and encoding. Since `signed char` and `unsigned char` have no implied character set and encoding, they are not included as permitted types. — *end note*]
- ⁵ Template parameters named `Allocator` shall meet the Allocator requirements (20.5.3.5).

30.10.5.1 Namespaces and headers [fs.req.namespace]

- ¹ Unless otherwise specified, references to entities described in this subclause are assumed to be qualified with `::std::filesystem::`.

30.10.6 Header `<filesystem>` synopsis [fs.filesystem.syn]

```
namespace std::filesystem {
    // 30.10.8, paths
    class path;
```

```

// 30.10.8.6, path non-member functions
void swap(path& lhs, path& rhs) noexcept;
size_t hash_value(const path& p) noexcept;

bool operator==(const path& lhs, const path& rhs) noexcept;
bool operator!=(const path& lhs, const path& rhs) noexcept;
bool operator<(const path& lhs, const path& rhs) noexcept;
bool operator<=(const path& lhs, const path& rhs) noexcept;
bool operator>(const path& lhs, const path& rhs) noexcept;
bool operator>=(const path& lhs, const path& rhs) noexcept;

path operator/ (const path& lhs, const path& rhs);

// 30.10.8.6.1, path inserter and extractor
template <class charT, class traits>
    basic_ostream<charT, traits>&
        operator<<(basic_ostream<charT, traits>& os, const path& p);
template <class charT, class traits>
    basic_istream<charT, traits>&
        operator>>(basic_istream<charT, traits>& is, path& p);

// 30.10.8.6.2, path factory functions
template <class Source>
    path u8path(const Source& source);
template <class InputIterator>
    path u8path(InputIterator first, InputIterator last);

// 30.10.9, filesystem errors
class filesystem_error;

// 30.10.12, directory entries
class directory_entry;

// 30.10.13, directory iterators
class directory_iterator;

// 30.10.13.2, range access for directory iterators
directory_iterator begin(directory_iterator iter) noexcept;
directory_iterator end(const directory_iterator&) noexcept;

// 30.10.14, recursive directory iterators
class recursive_directory_iterator;

// 30.10.14.2, range access for recursive directory iterators
recursive_directory_iterator begin(recursive_directory_iterator iter) noexcept;
recursive_directory_iterator end(const recursive_directory_iterator&) noexcept;

// 30.10.11, file status
class file_status;

struct space_info {
    uintmax_t capacity;
    uintmax_t free;
    uintmax_t available;
};

```

```

// 30.10.10, enumerations
enum class file_type;
enum class perms;
enum class perm_options;
enum class copy_options;
enum class directory_options;

using file_time_type = chrono::time_point<trivial_clock>;

// 30.10.15, filesystem operations
path absolute(const path& p, const path& base = current_path());

path canonical(const path& p, const path& base = current_path());
path canonical(const path& p, error_code& ec);
path canonical(const path& p, const path& base, error_code& ec);

void copy(const path& from, const path& to);
void copy(const path& from, const path& to, error_code& ec) noexcept;
void copy(const path& from, const path& to, copy_options options);
void copy(const path& from, const path& to, copy_options options,
          error_code& ec) noexcept;

bool copy_file(const path& from, const path& to);
bool copy_file(const path& from, const path& to, error_code& ec) noexcept;
bool copy_file(const path& from, const path& to, copy_options option);
bool copy_file(const path& from, const path& to, copy_options option,
               error_code& ec) noexcept;

void copy_symlink(const path& existing_symlink, const path& new_symlink);
void copy_symlink(const path& existing_symlink, const path& new_symlink,
                  error_code& ec) noexcept;

bool create_directories(const path& p);
bool create_directories(const path& p, error_code& ec) noexcept;

bool create_directory(const path& p);
bool create_directory(const path& p, error_code& ec) noexcept;

bool create_directory(const path& p, const path& attributes);
bool create_directory(const path& p, const path& attributes,
                     error_code& ec) noexcept;

void create_directory_symlink(const path& to, const path& new_symlink);
void create_directory_symlink(const path& to, const path& new_symlink,
                              error_code& ec) noexcept;

void create_hard_link(const path& to, const path& new_hard_link);
void create_hard_link(const path& to, const path& new_hard_link,
                      error_code& ec) noexcept;

void create_symlink(const path& to, const path& new_symlink);
void create_symlink(const path& to, const path& new_symlink,
                    error_code& ec) noexcept;

```

```
path current_path();
path current_path(error_code& ec);
void current_path(const path& p);
void current_path(const path& p, error_code& ec) noexcept;

bool exists(file_status s) noexcept;
bool exists(const path& p);
bool exists(const path& p, error_code& ec) noexcept;

bool equivalent(const path& p1, const path& p2);
bool equivalent(const path& p1, const path& p2, error_code& ec) noexcept;

uintmax_t file_size(const path& p);
uintmax_t file_size(const path& p, error_code& ec) noexcept;

uintmax_t hard_link_count(const path& p);
uintmax_t hard_link_count(const path& p, error_code& ec) noexcept;

bool is_block_file(file_status s) noexcept;
bool is_block_file(const path& p);
bool is_block_file(const path& p, error_code& ec) noexcept;

bool is_character_file(file_status s) noexcept;
bool is_character_file(const path& p);
bool is_character_file(const path& p, error_code& ec) noexcept;

bool is_directory(file_status s) noexcept;
bool is_directory(const path& p);
bool is_directory(const path& p, error_code& ec) noexcept;

bool is_empty(const path& p);
bool is_empty(const path& p, error_code& ec) noexcept;

bool is_fifo(file_status s) noexcept;
bool is_fifo(const path& p);
bool is_fifo(const path& p, error_code& ec) noexcept;

bool is_other(file_status s) noexcept;
bool is_other(const path& p);
bool is_other(const path& p, error_code& ec) noexcept;

bool is_regular_file(file_status s) noexcept;
bool is_regular_file(const path& p);
bool is_regular_file(const path& p, error_code& ec) noexcept;

bool is_socket(file_status s) noexcept;
bool is_socket(const path& p);
bool is_socket(const path& p, error_code& ec) noexcept;

bool is_symlink(file_status s) noexcept;
bool is_symlink(const path& p);
bool is_symlink(const path& p, error_code& ec) noexcept;

file_time_type last_write_time(const path& p);
file_time_type last_write_time(const path& p, error_code& ec) noexcept;
```

```

void last_write_time(const path& p, file_time_type new_time);
void last_write_time(const path& p, file_time_type new_time,
                    error_code& ec) noexcept;

void permissions(const path& p, perms prms, perm_options opts=perm_options::replace);
void permissions(const path& p, perms prms, error_code& ec) noexcept;
void permissions(const path& p, perms prms, perm_options opts, error_code& ec);

path proximate(const path& p, error_code& ec);
path proximate(const path& p, const path& base = current_path());
path proximate(const path& p, const path& base, error_code& ec);

path read_symlink(const path& p);
path read_symlink(const path& p, error_code& ec);

path relative(const path& p, error_code& ec);
path relative(const path& p, const path& base = current_path());
path relative(const path& p, const path& base, error_code& ec);

bool remove(const path& p);
bool remove(const path& p, error_code& ec) noexcept;

uintmax_t remove_all(const path& p);
uintmax_t remove_all(const path& p, error_code& ec) noexcept;

void rename(const path& from, const path& to);
void rename(const path& from, const path& to, error_code& ec) noexcept;

void resize_file(const path& p, uintmax_t size);
void resize_file(const path& p, uintmax_t size, error_code& ec) noexcept;

space_info space(const path& p);
space_info space(const path& p, error_code& ec) noexcept;

file_status status(const path& p);
file_status status(const path& p, error_code& ec) noexcept;

bool status_known(file_status s) noexcept;

file_status symlink_status(const path& p);
file_status symlink_status(const path& p, error_code& ec) noexcept;

path temp_directory_path();
path temp_directory_path(error_code& ec);

path weakly_canonical(const path& p);
path weakly_canonical(const path& p, error_code& ec);
}

```

- ¹ *trivial-clock* is an implementation-defined type that satisfies the TrivialClock requirements (23.17.3) and that is capable of representing and measuring file time values. Implementations should ensure that the resolution and range of `file_time_type` reflect the operating system dependent resolution and range of file

time values.

30.10.7 Error reporting

[fs.err.report]

- ¹ Filesystem library functions often provide two overloads, one that throws an exception to report file system errors, and another that sets an `error_code`. [Note: This supports two common use cases:
 - (1.1) — Uses where file system errors are truly exceptional and indicate a serious failure. Throwing an exception is an appropriate response.
 - (1.2) — Uses where file system errors are routine and do not necessarily represent failure. Returning an error code is the most appropriate response. This allows application specific error handling, including simply ignoring the error.
 — end note]
- ² Functions not having an argument of type `error_code&` handle errors as follows, unless otherwise specified:
 - (2.1) — When a call by the implementation to an operating system or other underlying API results in an error that prevents the function from meeting its specifications, an exception of type `filesystem_error` shall be thrown. For functions with a single path argument, that argument shall be passed to the `filesystem_error` constructor with a single path argument. For functions with two path arguments, the first of these arguments shall be passed to the `filesystem_error` constructor as the `path1` argument, and the second shall be passed as the `path2` argument. The `filesystem_error` constructor's `error_code` argument is set as appropriate for the specific operating system dependent error.
 - (2.2) — Failure to allocate storage is reported by throwing an exception as described in 20.5.5.12.
 - (2.3) — Destructors throw nothing.
- ³ Functions having an argument of type `error_code&` handle errors as follows, unless otherwise specified:
 - (3.1) — If a call by the implementation to an operating system or other underlying API results in an error that prevents the function from meeting its specifications, the `error_code&` argument is set as appropriate for the specific operating system dependent error. Otherwise, `clear()` is called on the `error_code&` argument.

30.10.8 Class path

[fs.class.path]

- ¹ An object of class `path` represents a path (30.10.4.15) and contains a pathname (30.10.4.16). Such an object is concerned only with the lexical and syntactic aspects of a path. The path does not necessarily exist in external storage, and the pathname is not necessarily valid for the current operating system or for a particular file system.
- ² [Note: Class `path` is used to support the differences between the string types used by different operating systems to represent pathnames, and to perform conversions between encodings when necessary. — end note]

```
namespace std::filesystem {
    class path {
    public:
        using value_type = see below;
        using string_type = basic_string<value_type>;
        static constexpr value_type preferred_separator = see below;

        // 30.10.10.1, enumeration format
        enum format;

        // 30.10.8.4.1, constructors and destructor
        path() noexcept;
```

```

path(const path& p);
path(path&& p) noexcept;
path(string_type&& source, format fmt = auto_format);
template <class Source>
    path(const Source& source, format fmt = auto_format);
template <class InputIterator>
    path(InputIterator first, InputIterator last, format fmt = auto_format);
template <class Source>
    path(const Source& source, const locale& loc, format fmt = auto_format);
template <class InputIterator>
    path(InputIterator first, InputIterator last, const locale& loc, format fmt = auto_format);
~path();

// 30.10.8.4.2, assignments
path& operator=(const path& p);
path& operator=(path&& p) noexcept;
path& operator=(string_type&& source);
path& assign(string_type&& source);
template <class Source>
    path& operator=(const Source& source);
template <class Source>
    path& assign(const Source& source)
template <class InputIterator>
    path& assign(InputIterator first, InputIterator last);

// 30.10.8.4.3, appends
path& operator+=(const path& p);
template <class Source>
    path& operator+=(const Source& source);
template <class Source>
    path& append(const Source& source);
template <class InputIterator>
    path& append(InputIterator first, InputIterator last);

// 30.10.8.4.4, concatenation
path& operator+=(const path& x);
path& operator+=(const string_type& x);
path& operator+=(basic_string_view<value_type> x);
path& operator+=(const value_type* x);
path& operator+=(value_type x);
template <class Source>
    path& operator+=(const Source& x);
template <class EcharT>
    path& operator+=(EcharT x);
template <class Source>
    path& concat(const Source& x);
template <class InputIterator>
    path& concat(InputIterator first, InputIterator last);

// 30.10.8.4.5, modifiers
void clear() noexcept;
path& make_preferred();
path& remove_filename();
path& replace_filename(const path& replacement);
path& replace_extension(const path& replacement = path());

```

```

void swap(path& rhs) noexcept;

// 30.10.8.4.6, native format observers
const string_type& native() const noexcept;
const value_type* c_str() const noexcept;
operator string_type() const;

template <class EcharT, class traits = char_traits<EcharT>,
          class Allocator = allocator<EcharT>>
    basic_string<EcharT, traits, Allocator>
        string(const Allocator& a = Allocator()) const;
std::string      string() const;
std::wstring     wstring() const;
std::string      u8string() const;
std::u16string   u16string() const;
std::u32string   u32string() const;

// 30.10.8.4.7, generic format observers
template <class EcharT, class traits = char_traits<EcharT>,
          class Allocator = allocator<EcharT>>
    basic_string<EcharT, traits, Allocator>
        generic_string(const Allocator& a = Allocator()) const;
std::string      generic_string() const;
std::wstring     generic_wstring() const;
std::string      generic_u8string() const;
std::u16string   generic_u16string() const;
std::u32string   generic_u32string() const;

// 30.10.8.4.8, compare
int compare(const path& p) const noexcept;
int compare(const string_type& s) const;
int compare(basic_string_view<value_type> s) const;
int compare(const value_type* s) const;

// 30.10.8.4.9, decomposition
path root_name() const;
path root_directory() const;
path root_path() const;
path relative_path() const;
path parent_path() const;
path filename() const;
path stem() const;
path extension() const;

// 30.10.8.4.10, query
bool empty() const noexcept;
bool has_root_name() const;
bool has_root_directory() const;
bool has_root_path() const;
bool has_relative_path() const;
bool has_parent_path() const;
bool has_filename() const;
bool has_stem() const;
bool has_extension() const;
bool is_absolute() const;

```



```

    bool is_relative() const;

    // 30.10.8.4.11, generation
    path lexically_normal() const;
    path lexically_relative(const path& base) const;
    path lexically_proximate(const path& base) const;

    // 30.10.8.5, iterators
    class iterator;
    using const_iterator = iterator;

    iterator begin() const;
    iterator end() const;
};
}

```

- ³ `value_type` is a typedef for the operating system dependent encoded character type used to represent pathnames.
- ⁴ The value of the `preferred_separator` member is the operating system dependent *preferred-separator* character (30.10.8.1).
- ⁵ [Example: For POSIX-based operating systems, `value_type` is `char` and `preferred_separator` is the slash character ('/'). For Windows-based operating systems, `value_type` is `wchar_t` and `preferred_separator` is the backslash character (L'\\'). — end example]

30.10.8.1 Generic pathname format

[fs.path.generic]

pathname:

root-name_{opt} root-directory_{opt} relative-path

root-name:

operating system dependent sequences of characters
implementation-defined sequences of characters

root-directory:

directory-separator

relative-path:

filename
filename directory-separator relative-path
an empty path

filename:

non-empty sequence of characters other than *directory-separator* characters

directory-separator:

preferred-separator directory-separator_{opt}
fallback-separator directory-separator_{opt}

preferred-separator:

operating system dependent directory separator character

fallback-separator:

/, if *preferred-separator* is not /

- ¹ [Note: Operating systems often place restrictions on the characters that may be used in a *filename*. For wide portability, users may wish to limit *filename* characters to the POSIX Portable Filename Character Set:

```

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
a b c d e f g h i j k l m n o p q r s t u v w x y z
0 1 2 3 4 5 6 7 8 9 . _ - — end note]

```

- ² Except in a *root-name*, multiple successive *directory-separator* characters are considered to be the same as one *directory-separator* character.
- ³ The filename *dot* (30.10.4.6) is treated as a reference to the current directory. The filename *dot-dot* (30.10.4.6) is treated as a reference to the parent directory. What the filename *dot-dot* refers to relative to *root-directory* is implementation-defined. Specific filenames may have special meanings for a particular operating system.
- ⁴ A *root-name* identifies the starting location for pathname resolution (30.10.4.17). If there are no operating system dependent *root-names*, at least one implementation-defined *root-name* is required. [Note: Many operating systems define a name beginning with two *directory-separator* characters as a *root-name* that identifies network or other resource locations. Some operating systems define a single letter followed by a colon as a drive specifier – a *root-name* identifying a specific device such as a disk drive. — end note]
- ⁵ If a *root-name* is otherwise ambiguous, the possibility with the longest sequence of characters is chosen. [Note: On a POSIX-like operating system, it is impossible to have a *root-name* and a *relative-path* without an intervening *root-directory* element. — end note]

30.10.8.2 path conversions

[fs.path.cvt]

30.10.8.2.1 path argument format conversions

[fs.path.fmt.cvt]

- ¹ [Note: The format conversions described in this section are not applied on POSIX-based operating systems because on these systems:
 - (1.1) — The generic format is acceptable as a native path.
 - (1.2) — There is no need to distinguish between native format and generic format in function arguments.
 - (1.3) — Paths for regular files and paths for directories share the same syntax.
 — end note]
- ² Several functions are defined to accept *detected-format* arguments, which are character sequences. A detected-format argument represents a path using either a pathname in the generic format (30.10.8.1) or a pathname in the native format (30.10.4.10). Such an argument is taken to be in the generic format if and only if it matches the generic format and is not acceptable to the operating system as a native path.
- ³ [Note: Some operating systems may have no unambiguous way to distinguish between native format and generic format arguments. This is by design as it simplifies use for operating systems that do not require disambiguation. An implementation for an operating system where disambiguation is required is permitted to distinguish between the formats. — end note]
- ⁴ Pathnames are converted as needed between the generic and native formats in an operating-system-dependent manner. Let $G(n)$ and $N(g)$ in a mathematical sense be the implementation's functions that convert native-to-generic and generic-to-native formats respectively. If $g=G(n)$ for some n , then $G(N(g))=g$; if $n=N(g)$ for some g , then $N(G(n))=n$. [Note: Neither G nor N need be invertible. — end note]
- ⁵ If the native format requires paths for regular files to be formatted differently from paths for directories, the path shall be treated as a directory path if its last element is a *directory-separator*, otherwise it shall be treated as a path to a regular file.
- ⁶ [Note: A path stores a native format pathname (30.10.8.4.6) and acts as if it also stores a generic format pathname, related as given below. The implementation may generate the generic format pathname based on the native format pathname (and possibly other information) when requested. — end note]
- ⁷ When a path is constructed from or is assigned a single representation separate from any path, the other representation is selected by the appropriate conversion function (G or N).
- ⁸ When the (new) value p of one representation of a path is derived from the representation of that or another path, a value q is chosen for the other representation. The value q converts to p (by G or N as appropriate) if any such value does so; q is otherwise unspecified. [Note: If q is the result of converting any path at all, it

is the result of converting *p*. — *end note*]

30.10.8.2.2 path type and encoding conversions

[fs.path.type.cvt]

- ¹ For member function arguments that take character sequences representing paths and for member functions returning strings, value type and encoding conversion is performed if the value type of the argument or return value differs from `path::value_type`. For the argument or return value, the method of conversion and the encoding to be converted to is determined by its value type:
 - (1.1) — `char`: The encoding is the native narrow encoding (30.10.4.9). The method of conversion, if any, is operating system dependent. [*Note*: For POSIX-based operating systems `path::value_type` is `char` so no conversion from `char` value type arguments or to `char` value type return values is performed. For Windows-based operating systems, the native narrow encoding is determined by calling a Windows API function. — *end note*] [*Note*: This results in behavior identical to other C and C++ standard library functions that perform file operations using narrow character strings to identify paths. Changing this behavior would be surprising and error prone. — *end note*]
 - (1.2) — `wchar_t`: The encoding is the native wide encoding (30.10.4.9). The method of conversion is unspecified. [*Note*: For Windows-based operating systems `path::value_type` is `wchar_t` so no conversion from `wchar_t` value type arguments or to `wchar_t` value type return values is performed. — *end note*]
 - (1.3) — `char16_t`: The encoding is UTF-16. The method of conversion is unspecified.
 - (1.4) — `char32_t`: The encoding is UTF-32. The method of conversion is unspecified.
- ² If the encoding being converted to has no representation for source characters, the resulting converted characters, if any, are unspecified. Implementations should not modify member function arguments if already of type `path::value_type`.

30.10.8.3 path requirements

[fs.path.req]

- ¹ In addition to the requirements (30.10.5), function template parameters named `Source` shall be one of:
 - (1.1) — `basic_string<EcharT, traits, Allocator>`. A function argument `const Source& source` shall have an effective range `[source.begin(), source.end())`.
 - (1.2) — `basic_string_view<EcharT, traits>`. A function argument `const Source& source` shall have an effective range `[source.begin(), source.end())`.
 - (1.3) — A type meeting the input iterator requirements that iterates over a NTCTS. The value type shall be an encoded character type. A function argument `const Source& source` shall have an effective range `[source, end)` where `end` is the first iterator value with an element value equal to `iterator_traits<Source>::value_type()`.
 - (1.4) — A character array that after array-to-pointer decay results in a pointer to the start of a NTCTS. The value type shall be an encoded character type. A function argument `const Source& source` shall have an effective range `[source, end)` where `end` is the first iterator value with an element value equal to `iterator_traits<decay_t<Source>>::value_type()`.
- ² Functions taking template parameters named `Source` shall not participate in overload resolution unless either
 - (2.1) — `Source` is a specialization of `basic_string` or `basic_string_view`, or
 - (2.2) — the *qualified-id* `iterator_traits<decay_t<Source>>::value_type` is valid and denotes a possibly `const` encoded character type (17.8.2).
- ³ [*Note*: See path conversions (30.10.8.2) for how the value types above and their encodings convert to `path::value_type` and its encoding. — *end note*]
- ⁴ Arguments of type `Source` shall not be null pointers.

30.10.8.4 path members

[fs.path.member]

30.10.8.4.1 path constructors

[fs.path.construct]

```
path() noexcept;
```

1 *Effects:* Constructs an object of class `path`.

2 *Postconditions:* `empty() == true`.

```
path(const path& p);
```

```
path(path&& p) noexcept;
```

3 *Effects:* Constructs an object of class `path` having the same pathname in the native and generic formats, respectively, as the original value of `p`. In the second form, `p` is left in a valid but unspecified state.

```
path(string_type&& source, format fmt = auto_format);
```

4 *Effects:* Constructs an object of class `path` for which the pathname in the detected-format of `source` has the original value of `source` (30.10.8.2.1), converting format if required (30.10.8.2.1). `source` is left in a valid but unspecified state.

```
template <class Source>
```

```
path(const Source& source, format fmt = auto_format);
```

```
template <class InputIterator>
```

```
path(InputIterator first, InputIterator last, format fmt = auto_format);
```

5 *Effects:* Let `s` be the effective range of `source` (30.10.8.3) or the range `[first, last)`, with the encoding converted if required (30.10.8.2). Finds the detected-format of `s` (30.10.8.2.1) and constructs an object of class `path` for which the pathname in that format is `s`.

```
template <class Source>
```

```
path(const Source& source, const locale& loc, format fmt = auto_format);
```

```
template <class InputIterator>
```

```
path(InputIterator first, InputIterator last, const locale& loc, format fmt = auto_format);
```

6 *Requires:* The value type of `Source` and `InputIterator` is `char`.

7 *Effects:* Let `s` be the effective range of `source` or the range `[first, last)`, after converting the encoding as follows:

(7.1) — If `value_type` is `wchar_t`, converts to the native wide encoding (30.10.4.9) using the `codecvt<wchar_t, char, mbstate_t>` facet of `loc`.

(7.2) — Otherwise a conversion is performed using the `codecvt<wchar_t, char, mbstate_t>` facet of `loc`, and then a second conversion to the current narrow encoding.

8 Finds the detected-format of `s` (30.10.8.2.1) and constructs an object of class `path` for which the pathname in that format is `s`.

[*Example:* A string is to be read from a database that is encoded in ISO/IEC 8859-1, and used to create a directory:

```
namespace fs = std::filesystem;
std::string latin1_string = read_latin1_data();
codecvt_8859_1<wchar_t> latin1_facet;
std::locale latin1_locale(std::locale(), latin1_facet);
fs::create_directory(fs::path(latin1_string, latin1_locale));
```

For POSIX-based operating systems, the path is constructed by first using `latin1_facet` to convert ISO/IEC 8859-1 encoded `latin1_string` to a wide character string in the native wide encoding (30.10.4.9). The resulting wide string is then converted to a narrow character pathname string in the current native narrow encoding. If the native wide encoding is UTF-16 or UTF-32, and the current

native narrow encoding is UTF-8, all of the characters in the ISO/IEC 8859-1 character set will be converted to their Unicode representation, but for other native narrow encodings some characters may have no representation.

For Windows-based operating systems, the path is constructed by using `latin1_facet` to convert ISO/IEC 8859-1 encoded `latin1_string` to a UTF-16 encoded wide character pathname string. All of the characters in the ISO/IEC 8859-1 character set will be converted to their Unicode representation.

— *end example*]

30.10.8.4.2 path assignments

[`fs.path.assign`]

```
path& operator=(const path& p);
```

1 *Effects:* If `*this` and `p` are the same object, has no effect. Otherwise, sets both respective pathnames of `*this` to the respective pathnames of `p`.

2 *Returns:* `*this`.

```
path& operator=(path&& p) noexcept;
```

3 *Effects:* If `*this` and `p` are the same object, has no effect. Otherwise, sets both respective pathnames of `*this` to the respective pathnames of `p`. `p` is left in a valid but unspecified state. [*Note:* A valid implementation is `swap(p)`. — *end note*]

4 *Returns:* `*this`.

```
path& operator=(string_type&& source);
path& assign(string_type&& source);
```

5 *Effects:* Sets the pathname in the detected-format of `source` to the original value of `source`. `source` is left in a valid but unspecified state.

6 *Returns:* `*this`.

```
template <class Source>
    path& operator=(const Source& source);
template <class Source>
    path& assign(const Source& source);
template <class InputIterator>
    path& assign(InputIterator first, InputIterator last);
```

7 *Effects:* Let `s` be the effective range of `source` (30.10.8.3) or the range `[first, last)`, with the encoding converted if required (30.10.8.2). Finds the detected-format of `s` (30.10.8.2.1) and sets the pathname in that format to `s`.

8 *Returns:* `*this`.

30.10.8.4.3 path appends

[`fs.path.append`]

1 The append operations use `operator/=` to denote their semantic effect of appending *preferred-separator* when needed.

```
path& operator/=(const path& p);
```

2 *Effects:* If `p.is_absolute() || (p.has_root_name() && p.root_name() != root_name())`, then `operator=(p)`.

3 Otherwise, modifies `*this` as if by these steps:

- (3.1) — If `p.has_root_directory()`, then removes any root directory and relative path from the generic format pathname. Otherwise, if `!has_root_directory() && is_absolute()` is true or if `has_filename()` is true, then appends `path::preferred_separator` to the generic format pathname.

- (3.2) — Then appends the native format pathname of `p`, omitting any *root-name* from its generic format pathname, to the native format pathname.

4 [*Example:* Even if `//host` is interpreted as a *root-name*, both of the paths `path("//host")/"foo"` and `path("//host/")/"foo"` equal `"//host/foo"`.

Expression examples:

```
// On POSIX,
path("foo") / "";      // yields "foo/"
path("foo") / "/bar";  // yields "/bar"
// On Windows, backslashes replace slashes in the above yields
```

```
// On Windows,
path("foo") / "c:/bar"; // yields "c:/bar"
path("foo") / "c:.";    // yields "c:."
path("c:") / "";       // yields "c:."
path("c:foo") / "/bar"; // yields "c:/bar"
path("c:foo") / "c:bar"; // yields "c:foo/bar"
```

— *end example*]

5 *Returns:* `*this`.

```
template <class Source>
    path& operator+=(const Source& source);
template <class Source>
    path& append(const Source& source);
```

6 *Effects:* Equivalent to: `return operator+=(path(source));`

```
template <class InputIterator>
    path& append(InputIterator first, InputIterator last);
```

7 *Effects:* Equivalent to: `return operator+=(path(first, last));`

30.10.8.4.4 path concatenation

[`fs.path.concat`]

```
path& operator+=(const path& x);
path& operator+=(const string_type& x);
path& operator+=(basic_string_view<value_type> x);
path& operator+=(const value_type* x);
path& operator+=(value_type x);
template <class Source>
    path& operator+=(const Source& x);
template <class EcharT>
    path& operator+=(EcharT x);
template <class Source>
    path& concat(const Source& x);
```

1 *Effects:* Appends `path(x).native()` to the pathname in the native format. [*Note:* This directly manipulates the value of `native()` and may not be portable between operating systems. — *end note*]

2 *Returns:* `*this`.

```
template <class InputIterator>
    path& concat(InputIterator first, InputIterator last);
```

3 *Effects:* Equivalent to `return *this += path(first, last).`

30.10.8.4.5 path modifiers

[`fs.path.modifiers`]

```
void clear() noexcept;
```

```
1      Postconditions: empty() == true.
```

```
path& make_preferred();
```

```
2      Effects: Each directory-separator of the pathname in the generic format is converted to preferred-separator.
```

```
3      Returns: *this.
```

```
4      [ Example:
```

```
        path p("foo/bar");
        std::cout << p << '\n';
        p.make_preferred();
        std::cout << p << '\n';
```

On an operating system where *preferred-separator* is a slash, the output is:

```
"foo/bar"
"foo/bar"
```

On an operating system where *preferred-separator* is a backslash, the output is:

```
"foo/bar"
"foo\bar"
```

— *end example*]

```
path& remove_filename();
```

```
5      Postconditions: !has_filename().
```

```
6      Effects: Remove the generic format pathname of filename() from the generic format pathname.
```

```
7      Returns: *this.
```

```
8      [ Example:
```

```
        path("foo/bar").remove_filename(); // yields "foo/"
        path("foo/").remove_filename();    // yields "foo/"
        path("/foo").remove_filename();    // yields "/"
        path("/").remove_filename();       // yields "/"
```

— *end example*]

```
path& replace_filename(const path& replacement);
```

```
9      Effects: Equivalent to:
```

```
        remove_filename();
        operator/=(replacement);
```

```
10     Returns: *this.
```

```
11     [ Example:
```

```
        path("/foo").replace_filename("bar"); // yields "/bar" on POSIX
        path("/").replace_filename("bar");    // yields "/bar" on POSIX
```

— *end example*]

```
path& replace_extension(const path& replacement = path());
```

```
12     Effects:
```

(12.1) — Any existing `extension()` (30.10.8.4.9) is removed from the pathname in the generic format, then

(12.2) — If `replacement` is not empty and does not begin with a dot character, a dot character is appended to the pathname in the generic format, then

(12.3) — `operator+=(replacement);`.

13 *Returns:* `*this`.

`void swap(path& rhs) noexcept;`

14 *Effects:* Swaps the contents (in all formats) of the two paths.

15 *Complexity:* Constant time.

30.10.8.4.6 path native format observers [fs.path.native.obs]

1 The string returned by all native format observers is in the native pathname format (30.10.4.10).

`const string_type& native() const noexcept;`

2 *Returns:* The pathname in the native format.

`const value_type* c_str() const noexcept;`

3 *Returns:* Equivalent to `native().c_str()`.

`operator string_type() const;`

4 *Returns:* `native()`.

5 [*Note:* Conversion to `string_type` is provided so that an object of class `path` can be given as an argument to existing standard library file stream constructors and open functions. — *end note*]

```
template <class EcharT, class traits = char_traits<EcharT>,
         class Allocator = allocator<EcharT>>
    basic_string<EcharT, traits, Allocator>
    string(const Allocator& a = Allocator()) const;
```

6 *Returns:* `native()`.

7 *Remarks:* All memory allocation, including for the return value, shall be performed by `a`. Conversion, if any, is specified by 30.10.8.2.

```
std::string string() const;
std::wstring wstring() const;
std::string u8string() const;
std::u16string u16string() const;
std::u32string u32string() const;
```

8 *Returns:* `pathstring`.

9 *Remarks:* Conversion, if any, is performed as specified by 30.10.8.2. The encoding of the string returned by `u8string()` is always UTF-8.

30.10.8.4.7 path generic format observers [fs.path.generic.obs]

1 Generic format observer functions return strings formatted according to the generic pathname format (30.10.8.1). A single slash (`'/'`) character is used as the *directory-separator*.

2 [*Example:* On an operating system that uses backslash as its *preferred-separator*,

```
path("foo\\bar").generic_string()
returns "foo/bar". — end example ]
```

```
template <class EcharT, class traits = char_traits<EcharT>,
         class Allocator = allocator<EcharT>>
```



```
basic_string<EcharT, traits, Allocator>
generic_string(const Allocator& a = Allocator()) const;
```

3 *Returns:* The pathname in the generic format.

4 *Remarks:* All memory allocation, including for the return value, shall be performed by *a*. Conversion, if any, is specified by 30.10.8.2.

```
std::string generic_string() const;
std::wstring generic_wstring() const;
std::string generic_u8string() const;
std::u16string generic_u16string() const;
std::u32string generic_u32string() const;
```

5 *Returns:* The pathname in the generic format.

6 *Remarks:* Conversion, if any, is specified by 30.10.8.2. The encoding of the string returned by `generic_u8string()` is always UTF-8.

30.10.8.4.8 path compare

[fs.path.compare]

```
int compare(const path& p) const noexcept;
```

1 *Returns:*

- (1.1) — A value less than 0, if `native()` for the elements of `*this` are lexicographically less than `native()` for the elements of `p`; otherwise,
- (1.2) — a value greater than 0, if `native()` for the elements of `*this` are lexicographically greater than `native()` for the elements of `p`; otherwise,
- (1.3) — 0.

2 *Remarks:* The elements are determined as if by iteration over the half-open range `[begin(), end())` for `*this` and `p`.

```
int compare(const string_type& s) const
int compare(basic_string_view<value_type> s) const;
```

3 *Returns:* `compare(path(s))`.

```
int compare(const value_type* s) const
```

4 *Returns:* `compare(path(s))`.

30.10.8.4.9 path decomposition

[fs.path.decompose]

```
path root_name() const;
```

1 *Returns:* *root-name*, if the pathname in the generic format includes *root-name*, otherwise `path()`.

```
path root_directory() const;
```

2 *Returns:* *root-directory*, if the pathname in the generic format includes *root-directory*, otherwise `path()`.

```
path root_path() const;
```

3 *Returns:* `root_name() / root_directory()`.

```
path relative_path() const;
```

4 *Returns:* A `path` composed from the pathname in the generic format, if `!empty()`, beginning with the first *filename* after *root-path*. Otherwise, `path()`.

```
path parent_path() const;
```

5 *Returns:* `*this` if `!has_relative_path()`, otherwise a path whose generic format pathname is the longest prefix of the generic format pathname of `*this` that produces one fewer element in its iteration.

`path filename() const;`

6 *Returns:* `relative_path().empty() ? path() : *--end()`.

7 [*Example:*

```
path("/foo/bar.txt").filename(); // yields "bar.txt"
path("/foo/bar").filename();     // yields "bar"
path("/foo/bar/").filename();    // yields ""
path("/").filename();            // yields ""
path("//host").filename();       // yields ""
path(".").filename();            // yields "."
path("..").filename();           // yields ".."
```

— *end example*]

`path stem() const;`

8 *Returns:* Let `f` be the generic format pathname of `filename()`. Returns a path whose pathname in the generic format is

(8.1) — `f`, if it contains no periods other than a leading period or consists solely of one or two periods;

(8.2) — otherwise, the prefix of `f` ending before its last period.

9 [*Example:*

```
std::cout << path("/foo/bar.txt").stem(); // outputs "bar"
path p = "foo.bar.baz.tar";
for (; !p.extension().empty(); p = p.stem())
    std::cout << p.extension() << '\n';
// outputs: .tar
// .baz
// .bar
```

— *end example*]

`path extension() const;`

10 *Returns:* a path whose pathname in the generic format is the suffix of `filename()` not included in `stem()`.

11 [*Example:*

```
path("/foo/bar.txt").extension(); // yields ".txt" and stem() is "bar"
path("/foo/bar").extension();     // yields "" and stem() is "bar"
path("/foo/.profile").extension(); // yields "" and stem() is ".profile"
path(".bar").extension();         // yields "" and stem() is ".bar"
path("..bar").extension();        // yields ".bar" and stem() is "."
```

— *end example*]

12 [*Note:* The period is included in the return value so that it is possible to distinguish between no extension and an empty extension. — *end note*]

13 [*Note:* On non-POSIX operating systems, for a path `p`, it may not be the case that `p.stem() + p.extension() == p.filename()`, even though the generic format pathnames are the same. — *end note*]

30.10.8.4.10 path query

[`fs.path.query`]

```

bool empty() const noexcept;
1     Returns: true if the pathname in the generic format is empty, else false.

bool has_root_path() const;
2     Returns: !root_path().empty().

bool has_root_name() const;
3     Returns: !root_name().empty().

bool has_root_directory() const;
4     Returns: !root_directory().empty().

bool has_relative_path() const;
5     Returns: !relative_path().empty().

bool has_parent_path() const;
6     Returns: !parent_path().empty().

bool has_filename() const;
7     Returns: !filename().empty().

bool has_stem() const;
8     Returns: !stem().empty().

bool has_extension() const;
9     Returns: !extension().empty().

bool is_absolute() const;
10    Returns: true if the pathname in the native format contains an absolute path (30.10.4.1), else false.
11    [Example: path("/").is_absolute() is true for POSIX-based operating systems, and false for
    Windows-based operating systems. — end example]

bool is_relative() const;
12    Returns: !is_absolute().

```

30.10.8.4.11 path generation

[fs.path.gen]

```

path lexically_normal() const;
1     Returns: A path whose pathname in the generic format is the normal form (30.10.4.11) of the pathname
    in the generic format of *this.
2     [Example:
        assert(path("foo/./bar/..").lexically_normal() == "foo/");
        assert(path("foo/.////bar/..").lexically_normal() == "foo/");
        The above assertions will succeed. On Windows, the returned path's directory-separator characters will
        be backslashes rather than slashes, but that does not affect path equality. — end example]

path lexically_relative(const path& base) const;
3     Returns: *this made relative to base. Does not resolve (30.10.4.17) symlinks. Does not first
    normalize (30.10.4.11) *this or base.

```

4 *Effects:* If `root_name() != base.root_name()` is true or `is_absolute() != base.is_absolute()` is true or `!has_root_directory() && base.has_root_directory()` is true, returns `path()`. Determines the first mismatched element of `*this` and `base` as if by:

```
    auto [a, b] = mismatch(begin(), end(), base.begin(), base.end());
```

Then,

- (4.1) — if `a == end()` and `b == base.end()`, returns `path(".")`; otherwise
- (4.2) — let `n` be the number of *filename* elements in `[b, base.end())` that are not *dot* or *dot-dot* minus the number that are *dot-dot*. If `n < 0`, returns `path()`; otherwise
- (4.3) — returns an object of class `path` that is default-constructed, followed by
- (4.3.1) — application of `operator/=(path(".."))` `n` times, and then
- (4.3.2) — application of `operator/=(path("."))` for each element in `[a, end())`.

5 [*Example:*

```
    assert(path("/a/d").lexically_relative("/a/b/c") == "../d");
    assert(path("/a/b/c").lexically_relative("/a/d") == "../b/c");
    assert(path("a/b/c").lexically_relative("a") == "b/c");
    assert(path("a/b/c").lexically_relative("a/b/c/x/y") == "../..");
    assert(path("a/b/c").lexically_relative("a/b/c") == ".");
    assert(path("a/b").lexically_relative("c/d") == "../a/b");
```

The above assertions will succeed. On Windows, the returned path's *directory-separator* characters will be backslashes rather than slashes, but that does not affect `path` equality. — *end example*]

6 [*Note:* If symlink following semantics are desired, use the operational function `relative()`. — *end note*]

7 [*Note:* If normalization (30.10.4.11) is needed to ensure consistent matching of elements, apply `lexically_normal()` to `*this`, `base`, or both. — *end note*]

```
path lexically_proximate(const path& base) const;
```

8 *Returns:* If the value of `lexically_relative(base)` is not an empty path, return it. Otherwise return `*this`.

9 [*Note:* If symlink following semantics are desired, use the operational function `proximate()`. — *end note*]

10 [*Note:* If normalization (30.10.4.11) is needed to ensure consistent matching of elements, apply `lexically_normal()` to `*this`, `base`, or both. — *end note*]

30.10.8.5 path iterators

[**fs.path.itr**]

1 Path iterators iterate over the elements of the pathname in the generic format (30.10.8.1).

2 A `path::iterator` is a constant iterator satisfying all the requirements of a bidirectional iterator (27.2.6) except that, for dereferenceable iterators `a` and `b` of type `path::iterator` with `a == b`, there is no requirement that `*a` and `*b` are bound to the same object. Its `value_type` is `path`.

3 Calling any non-const member function of a `path` object invalidates all iterators referring to elements of that object.

4 For the elements of the pathname in the generic format, the forward traversal order is as follows:

- (4.1) — The *root-name* element, if present.
- (4.2) — The *root-directory* element, if present. [*Note:* The generic format is required to ensure lexicographical comparison works correctly. — *end note*]

- (4.3) — Each successive *filename* element, if present.
- (4.4) — An empty element, if a trailing non-root *directory-separator* is present.
- 5 The backward traversal order is the reverse of forward traversal.

```
iterator begin() const;
```

- 6 *Returns:* An iterator for the first present element in the traversal list above. If no elements are present, the end iterator.

```
iterator end() const;
```

- 7 *Returns:* The end iterator.

30.10.8.6 path non-member functions

[fs.path.nonmember]

```
void swap(path& lhs, path& rhs) noexcept;
```

- 1 *Effects:* Equivalent to: `lhs.swap(rhs);`

```
size_t hash_value (const path& p) noexcept;
```

- 2 *Returns:* A hash value for the path `p`. If for two paths, `p1 == p2` then `hash_value(p1) == hash_value(p2)`.

```
bool operator< (const path& lhs, const path& rhs) noexcept;
```

- 3 *Returns:* `lhs.compare(rhs) < 0`.

```
bool operator<=(const path& lhs, const path& rhs) noexcept;
```

- 4 *Returns:* `!(rhs < lhs)`.

```
bool operator> (const path& lhs, const path& rhs) noexcept;
```

- 5 *Returns:* `rhs < lhs`.

```
bool operator>=(const path& lhs, const path& rhs) noexcept;
```

- 6 *Returns:* `!(lhs < rhs)`.

```
bool operator==(const path& lhs, const path& rhs) noexcept;
```

- 7 *Returns:* `!(lhs < rhs) && !(rhs < lhs)`.

- 8 [*Note:* Path equality and path equivalence have different semantics.

- (8.1) — Equality is determined by the `path` non-member `operator==`, which considers the two path's lexical representations only. [*Example:* `path("foo") == "bar"` is never `true`. — *end example*]

- (8.2) — Equivalence is determined by the `equivalent()` non-member function, which determines if two paths resolve (30.10.4.17) to the same file system entity. [*Example:* `equivalent("foo", "bar")` will be `true` when both paths resolve to the same file. — *end example*]

Programmers wishing to determine if two paths are “the same” must decide if “the same” means “the same representation” or “resolve to the same actual file”, and choose the appropriate function accordingly. — *end note*]

```
bool operator!=(const path& lhs, const path& rhs) noexcept;
```

- 9 *Returns:* `!(lhs == rhs)`.

```
path operator/ (const path& lhs, const path& rhs);
```

- 10 *Effects:* Equivalent to: `return path(lhs) /= rhs;`

30.10.8.6.1 path inserter and extractor**[fs.path.io]**

```
template <class charT, class traits>
    basic_ostream<charT, traits>&
        operator<<(basic_ostream<charT, traits>& os, const path& p);
```

1 *Effects:* Equivalent to: `os << quoted(p.string<charT, traits>());` [*Note:* The quoted function is described in 30.7.8. — *end note*]

2 *Returns:* `os`.

```
template <class charT, class traits>
    basic_istream<charT, traits>&
        operator>>(basic_istream<charT, traits>& is, path& p);
```

3 *Effects:* Equivalent to:

```
        basic_string<charT, traits> tmp;
        is >> quoted(tmp);
        p = tmp;
```

4 *Returns:* `is`.

30.10.8.6.2 path factory functions**[fs.path.factory]**

```
template <class Source>
    path u8path(const Source& source);
template <class InputIterator>
    path u8path(InputIterator first, InputIterator last);
```

1 *Requires:* The source and `[first, last)` sequences are UTF-8 encoded. The value type of `Source` and `InputIterator` is `char`.

2 *Returns:*

(2.1) — If `value_type` is `char` and the current native narrow encoding (30.10.4.9) is UTF-8, return `path(source)` or `path(first, last)`; otherwise,

(2.2) — if `value_type` is `wchar_t` and the native wide encoding is UTF-16, or if `value_type` is `char16_t` or `char32_t`, convert `source` or `[first, last)` to a temporary, `tmp`, of type `string_type` and return `path(tmp)`; otherwise,

(2.3) — convert `source` or `[first, last)` to a temporary, `tmp`, of type `u32string` and return `path(tmp)`.

3 *Remarks:* Argument format conversion (30.10.8.2.1) applies to the arguments for these functions. How Unicode encoding conversions are performed is unspecified.

4 [*Example:* A string is to be read from a database that is encoded in UTF-8, and used to create a directory using the native encoding for filenames:

```
    namespace fs = std::filesystem;
    std::string utf8_string = read_utf8_data();
    fs::create_directory(fs::u8path(utf8_string));
```

For POSIX-based operating systems with the native narrow encoding set to UTF-8, no encoding or type conversion occurs.

For POSIX-based operating systems with the native narrow encoding not set to UTF-8, a conversion to UTF-32 occurs, followed by a conversion to the current native narrow encoding. Some Unicode characters may have no native character set representation.

For Windows-based operating systems a conversion from UTF-8 to UTF-16 occurs. — *end example*]

30.10.9 Class filesystem_error**[fs.class.filesystem_error]**

```

namespace std::filesystem {
    class filesystem_error : public system_error {
    public:
        filesystem_error(const string& what_arg, error_code ec);
        filesystem_error(const string& what_arg,
                        const path& p1, error_code ec);
        filesystem_error(const string& what_arg,
                        const path& p1, const path& p2, error_code ec);

        const path& path1() const noexcept;
        const path& path2() const noexcept;
        const char* what() const noexcept override;
    };
}

```

- ¹ The class `filesystem_error` defines the type of objects thrown as exceptions to report file system errors from functions described in this subclause.

30.10.9.1 `filesystem_error` members [`filesystem_error.members`]

- ¹ Constructors are provided that store zero, one, or two paths associated with an error.

```
filesystem_error(const string& what_arg, error_code ec);
```

- ² *Postconditions:* The postconditions of this function are indicated in Table 119.

Table 119 — `filesystem_error(const string&, error_code)` effects

Expression	Value
<code>runtime_error::what()</code>	<code>what_arg.c_str()</code>
<code>code()</code>	<code>ec</code>
<code>path1().empty()</code>	<code>true</code>
<code>path2().empty()</code>	<code>true</code>

```
filesystem_error(const string& what_arg, const path& p1, error_code ec);
```

- ³ *Postconditions:* The postconditions of this function are indicated in Table 120.

Table 120 — `filesystem_error(const string&, const path&, error_code)` effects

Expression	Value
<code>runtime_error::what()</code>	<code>what_arg.c_str()</code>
<code>code()</code>	<code>ec</code>
<code>path1()</code>	Reference to stored copy of <code>p1</code>
<code>path2().empty()</code>	<code>true</code>

```
filesystem_error(const string& what_arg, const path& p1, const path& p2, error_code ec);
```

- ⁴ *Postconditions:* The postconditions of this function are indicated in Table 121.

```
const path& path1() const noexcept;
```

- ⁵ *Returns:* A reference to the copy of `p1` stored by the constructor, or, if none, an empty path.

```
const path& path2() const noexcept;
```

Table 121 — `filesystem_error(const string&, const path&, const path&, error_code)` effects

Expression	Value
<code>runtime_error::what()</code>	<code>what_arg.c_str()</code>
<code>code()</code>	<code>ec</code>
<code>path1()</code>	Reference to stored copy of <code>p1</code>
<code>path2()</code>	Reference to stored copy of <code>p2</code>

⁶ *Returns:* A reference to the copy of `p2` stored by the constructor, or, if none, an empty path.

`const char* what() const noexcept override;`

⁷ *Returns:* A string containing `runtime_error::what()`. The exact format is unspecified. Implementations are encouraged but not required to include `path1.native_string()` if not empty, `path2.native_string()` if not empty, and `system_error::what()` strings in the returned string.

30.10.10 Enumerations

[fs.enum]

30.10.10.1 Enum `path::format`

[fs.enum.path.format]

¹ This enum specifies constants used to identify the format of the character sequence, with the meanings listed in Table 122.

Table 122 — Enum `path::format`

Name	Meaning
<code>native_format</code>	The native pathname format.
<code>generic_format</code>	The generic pathname format.
<code>auto_format</code>	The interpretation of the format of the character sequence is implementation-defined. The implementation may inspect the content of the character sequence to determine the format. [<i>Note:</i> For POSIX-based systems, native and generic formats are equivalent and the character sequence should always be interpreted in the same way. — <i>end note</i>]

30.10.10.2 Enum class `file_type`

[fs.enum.file_type]

¹ This enum class specifies constants used to identify file types, with the meanings listed in Table 123.

30.10.10.3 Enum class `copy_options`

[fs.enum.copy.opts]

¹ The `enum class` type `copy_options` is a bitmask type (20.4.2.1.4) that specifies bitmask constants used to control the semantics of copy operations. The constants are specified in option groups with the meanings listed in Table 124. Constant `none` is shown in each option group for purposes of exposition; implementations shall provide only a single definition.

30.10.10.4 Enum class `perms`

[fs.enum.perms]

¹ The `enum class` type `perms` is a bitmask type (20.4.2.1.4) that specifies bitmask constants used to identify file permissions, with the meanings listed in Table 125.

Table 123 — Enum class `file_type`

Constant	Meaning
<code>none</code>	The type of the file has not been determined or an error occurred while trying to determine the type.
<code>not_found</code>	Pseudo-type indicating the file was not found. [<i>Note: The file not being found is not considered an error while determining the type of a file. — end note</i>]
<code>regular</code>	Regular file
<code>directory</code>	Directory file
<code>symlink</code>	Symbolic link file
<code>block</code>	Block special file
<code>character</code>	Character special file
<code>fifo</code>	FIFO or pipe file
<code>socket</code>	Socket file
<i>implementation-defined</i>	Implementations that support file systems having file types in addition to the above <code>file_type</code> types shall supply implementation-defined <code>file_type</code> constants to separately identify each of those additional file types
<code>unknown</code>	The file exists but the type could not be determined

Table 124 — Enum class `copy_options`

Option group controlling <code>copy_file</code> function effects for existing target files	
Constant	Meaning
<code>none</code>	(Default) Error; file already exists.
<code>skip_existing</code>	Do not overwrite existing file, do not report an error.
<code>overwrite_existing</code>	Overwrite the existing file.
<code>update_existing</code>	Overwrite the existing file if it is older than the replacement file.
Option group controlling copy function effects for sub-directories	
Constant	Meaning
<code>none</code>	(Default) Do not copy sub-directories.
<code>recursive</code>	Recursively copy sub-directories and their contents.
Option group controlling copy function effects for symbolic links	
Constant	Meaning
<code>none</code>	(Default) Follow symbolic links.
<code>copy_symlinks</code>	Copy symbolic links as symbolic links rather than copying the files that they point to.
<code>skip_symlinks</code>	Ignore symbolic links.
Option group controlling copy function effects for choosing the form of copying	
Constant	Meaning
<code>none</code>	(Default) Copy content.
<code>directories_only</code>	Copy directory structure only, do not copy non-directory files.
<code>create_symlinks</code>	Make symbolic links instead of copies of files. The source path shall be an absolute path unless the destination path is in the current directory.
<code>create_hard_links</code>	Make hard links instead of copies of files.

Table 125 — Enum class `perms`

Name	Value (octal)	POSIX macro	Definition or notes
<code>none</code>	0		There are no permissions set for the file.
<code>owner_read</code>	0400	<code>S_IRUSR</code>	Read permission, owner
<code>owner_write</code>	0200	<code>S_IWUSR</code>	Write permission, owner
<code>owner_exec</code>	0100	<code>S_IXUSR</code>	Execute/search permission, owner
<code>owner_all</code>	0700	<code>S_IRWXU</code>	Read, write, execute/search by owner; <code>owner_read owner_write owner_exec</code>
<code>group_read</code>	040	<code>S_IRGRP</code>	Read permission, group
<code>group_write</code>	020	<code>S_IWGRP</code>	Write permission, group
<code>group_exec</code>	010	<code>S_IXGRP</code>	Execute/search permission, group
<code>group_all</code>	070	<code>S_IRWXG</code>	Read, write, execute/search by group; <code>group_read group_write group_exec</code>
<code>others_read</code>	04	<code>S_IROTH</code>	Read permission, others
<code>others_write</code>	02	<code>S_IWOTH</code>	Write permission, others
<code>others_exec</code>	01	<code>S_IXOTH</code>	Execute/search permission, others
<code>others_all</code>	07	<code>S_IRWXO</code>	Read, write, execute/search by others; <code>others_read others_write others_exec</code>
<code>all</code>	0777		<code>owner_all group_all others_all</code>
<code>set_uid</code>	04000	<code>S_ISUID</code>	Set-user-ID on execution
<code>set_gid</code>	02000	<code>S_ISGID</code>	Set-group-ID on execution
<code>sticky_bit</code>	01000	<code>S_ISVTX</code>	Operating system dependent.
<code>mask</code>	07777		<code>all set_uid set_gid sticky_bit</code>
<code>unknown</code>	0xFFFF		The permissions are not known, such as when a <code>file_status</code> object is created without specifying the permissions

30.10.10.5 Enum class `perm_options`

[fs.enum.perm.opts]

- ¹ The `enum class` type `perm_options` is a bitmask type (20.4.2.1.4) that specifies bitmask constants used to control the semantics of permissions operations, with the meanings listed in Table 126. The bitmask constants are bitmask elements. In Table 126 `perm` denotes a value of type `perms` passed to `permissions`.

Table 126 — Enum class `perm_options`

Name	Meaning
<code>replace</code>	<code>permissions</code> shall replace the file's permission bits with <code>perm</code>
<code>add</code>	<code>permissions</code> shall replace the file's permission bits with the bitwise OR of <code>perm</code> and the file's current permission bits.
<code>remove</code>	<code>permissions</code> shall replace the file's permission bits with the bitwise AND of the complement of <code>perm</code> and the file's current permission bits.
<code>nofollow</code>	<code>permissions</code> shall change the permissions of a symbolic link itself rather than the permissions of the file the link resolves to.

30.10.10.6 Enum class `directory_options`**[fs.enum.dir.opts]**

- ¹ The enum class type `directory_options` is a bitmask type (20.4.2.1.4) that specifies bitmask constants used to identify directory traversal options, with the meanings listed in Table 127.

Table 127 — Enum class `directory_options`

Name	Meaning
<code>none</code>	(Default) Skip directory symlinks, permission denied is an error.
<code>follow_directory_symlink</code>	Follow rather than skip directory symlinks.
<code>skip_permission_denied</code>	Skip directories that would otherwise result in permission denied.

30.10.11 Class `file_status`**[fs.class.file_status]**

```

namespace std::filesystem {
    class file_status {
    public:
        // 30.10.11.1, constructors and destructor
        file_status() noexcept : file_status(file_type::none) {}
        explicit file_status(file_type ft,
                           perms prms = perms::unknown) noexcept;
        file_status(const file_status&) noexcept = default;
        file_status(file_status&&) noexcept = default;
        ~file_status();

        // assignments:
        file_status& operator=(const file_status&) noexcept = default;
        file_status& operator=(file_status&&) noexcept = default;

        // 30.10.11.3, modifiers
        void type(file_type ft) noexcept;
        void permissions(perms prms) noexcept;

        // 30.10.11.2, observers
        file_type type() const noexcept;
        perms permissions() const noexcept;
    };
}

```

- ¹ An object of type `file_status` stores information about the type and permissions of a file.

30.10.11.1 `file_status` constructors**[fs.file_status.cons]**

```
explicit file_status(file_type ft, perms prms = perms::unknown) noexcept;
```

- ¹ *Postconditions:* `type() == ft` and `permissions() == prms`.

30.10.11.2 `file_status` observers**[fs.file_status.obs]**

```
file_type type() const noexcept;
```

- ¹ *Returns:* The value of `type()` specified by the postconditions of the most recent call to a constructor, `operator=`, or `type(file_type)` function.

```
perms permissions() const noexcept;
```

- 2 *Returns:* The value of `permissions()` specified by the postconditions of the most recent call to a constructor, `operator=`, or `permissions(perms)` function.

30.10.11.3 `file_status` modifiers [fs.file_status.mods]

`void type(file_type ft) noexcept;`

- 1 *Postconditions:* `type() == ft`.

`void permissions(perms prms) noexcept;`

- 2 *Postconditions:* `permissions() == prms`.

30.10.12 Class `directory_entry` [fs.class.directory_entry]

```
namespace std::filesystem {
    class directory_entry {
    public:
        // 30.10.12.1, constructors and destructor
        directory_entry() noexcept = default;
        directory_entry(const directory_entry&) = default;
        directory_entry(directory_entry&&) noexcept = default;
        explicit directory_entry(const path& p);
        directory_entry(const path& p, error_code& ec);
        ~directory_entry();

        // assignments:
        directory_entry& operator=(const directory_entry&) = default;
        directory_entry& operator=(directory_entry&&) noexcept = default;

        // 30.10.12.2, modifiers
        void assign(const path& p);
        void assign(const path& p, error_code& ec);
        void replace_filename(const path& p);
        void replace_filename(const path& p, error_code& ec);
        void refresh();
        void refresh(error_code& ec) noexcept;

        // 30.10.12.3, observers
        const path& path() const noexcept;
        operator const path&() const noexcept;
        bool exists() const;
        bool exists(error_code& ec) const noexcept;
        bool is_block_file() const;
        bool is_block_file(error_code& ec) const noexcept;
        bool is_character_file() const;
        bool is_character_file(error_code& ec) const noexcept;
        bool is_directory() const;
        bool is_directory(error_code& ec) const noexcept;
        bool is_fifo() const;
        bool is_fifo(error_code& ec) const noexcept;
        bool is_other() const;
        bool is_other(error_code& ec) const noexcept;
        bool is_regular_file() const;
        bool is_regular_file(error_code& ec) const noexcept;
        bool is_socket() const;
        bool is_socket(error_code& ec) const noexcept;
```

```

    bool is_symlink() const;
    bool is_symlink(error_code& ec) const noexcept;
    uintmax_t file_size() const;
    uintmax_t file_size(error_code& ec) const noexcept;
    uintmax_t hard_link_count() const;
    uintmax_t hard_link_count(error_code& ec) const noexcept;
    file_time_type last_write_time() const;
    file_time_type last_write_time(error_code& ec) const noexcept;
    file_status status() const;
    file_status status(error_code& ec) const noexcept;
    file_status symlink_status() const;
    file_status symlink_status(error_code& ec) const noexcept;

    bool operator< (const directory_entry& rhs) const noexcept;
    bool operator==(const directory_entry& rhs) const noexcept;
    bool operator!=(const directory_entry& rhs) const noexcept;
    bool operator<=(const directory_entry& rhs) const noexcept;
    bool operator> (const directory_entry& rhs) const noexcept;
    bool operator>=(const directory_entry& rhs) const noexcept;

private:
    path pathobject;                // exposition only
    friend class directory_iterator; // exposition only
};
}

```

- ¹ A `directory_entry` object stores a `path` object and may store additional objects for file attributes such as hard link count, status, symlink status, file size, and last write time.
- ² Implementations are encouraged to store such additional file attributes during directory iteration if their values are available and storing the values would allow the implementation to eliminate file system accesses by `directory_entry` observer functions (30.10.15). Such stored file attribute values are said to be *cached*.
- ³ [Note: For purposes of exposition, class `directory_iterator` (30.10.13) is shown above as a friend of class `directory_entry`. Friendship allows the `directory_iterator` implementation to cache already available attribute values directly into a `directory_entry` object without the cost of an unneeded call to `refresh()`. — end note]

- ⁴ [Example:

```

    using namespace std::filesystem;

    // use possibly cached last write time to minimize disk accesses
    for (auto&& x : directory_iterator("."))
    {
        std::cout << x.path() << " " << x.last_write_time() << std::endl;
    }

    // call refresh() to refresh a stale cache
    for (auto&& x : directory_iterator("."))
    {
        lengthy_function(x.path()); // cache becomes stale
        x.refresh();
        std::cout << x.path() << " " << x.last_write_time() << std::endl;
    }
}

```

On implementations that do not cache the last write time, both loops will result in a potentially expensive call to the `std::filesystem::last_write_time` function. On implementations that do cache the last write

time, the first loop will use the cached value and so will not result in a potentially expensive call to the `std::filesystem::last_write_time` function. The code is portable to any implementation, regardless of whether or not it employs caching. — *end example*]

30.10.12.1 directory_entry constructors

[fs.dir.entry.cons]

```
explicit directory_entry(const path& p);
directory_entry(const path& p, error_code& ec);
```

- 1 *Effects:* Constructs an object of type `directory_entry`, then `refresh()` or `refresh(ec)`, respectively.
- 2 *Postconditions:* `path() == p` if no error occurs, otherwise `path() == std::filesystem::path()`.
- 3 *Throws:* As specified in 30.10.7.

30.10.12.2 directory_entry modifiers

[fs.dir.entry.mods]

```
void assign(const path& p);
void assign(const path& p, error_code& ec);
```

- 1 *Effects:* Equivalent to `pathobject = p`, then `refresh()` or `refresh(ec)`, respectively. If an error occurs, the values of any cached attributes are unspecified.
- 2 *Throws:* As specified in 30.10.7.

```
void replace_filename(const path& p);
void replace_filename(const path& p, error_code& ec);
```

- 3 *Effects:* Equivalent to `pathobject.replace_filename(p)`, then `refresh()` or `refresh(ec)`, respectively. If an error occurs, the values of any cached attributes are unspecified.
- Throws:* As specified in 30.10.7.

```
void refresh();
void refresh(error_code& ec) noexcept;
```

- 4 *Effects:* Stores the current values of any cached attributes of the file `p` resolves to. If an error occurs, an error is reported (30.10.7) and the values of any cached attributes are unspecified.
- 5 *Throws:* As specified in 30.10.7.
- 6 [*Note:* Implementations of `directory_iterator` (30.10.13) are prohibited from directly or indirectly calling the `refresh` function since it must access the external file system, and the objective of caching is to avoid unnecessary file system accesses. — *end note*]

30.10.12.3 directory_entry observers

[fs.dir.entry.obs]

- 1 Unqualified function names in the *Returns:* elements of the `directory_entry` observers described below refer to members of the `std::filesystem` namespace.

```
const path& path() const noexcept;
operator const path&() const noexcept;
```

- 2 *Returns:* `pathobject`.

```
bool exists() const;
bool exists(error_code& ec) const noexcept;
```

- 3 *Returns:* `exists(this->status())` or `exists(this->status(), ec)`, respectively.
- 4 *Throws:* As specified in 30.10.7.

```
bool is_block_file() const;
bool is_block_file(error_code& ec) const noexcept;
```

5 *Returns:* `is_block_file(this->status())` or `is_block_file(this->status(), ec)`, respectively.

6 *Throws:* As specified in 30.10.7.

```
bool is_character_file() const;
bool is_character_file(error_code& ec) const noexcept;
```

7 *Returns:* `is_character_file(this->status())` or `is_character_file(this->status(), ec)`, respectively.

8 *Throws:* As specified in 30.10.7.

```
bool is_directory() const;
bool is_directory(error_code& ec) const noexcept;
```

9 *Returns:* `is_directory(this->status())` or `is_directory(this->status(), ec)`, respectively.

10 *Throws:* As specified in 30.10.7.

```
bool is_fifo() const;
bool is_fifo(error_code& ec) const noexcept;
```

11 *Returns:* `is_fifo(this->status())` or `is_fifo(this->status(), ec)`, respectively.

12 *Throws:* As specified in 30.10.7.

```
bool is_other() const;
bool is_other(error_code& ec) const noexcept;
```

13 *Returns:* `is_other(this->status())` or `is_other(this->status(), ec)`, respectively.

14 *Throws:* As specified in 30.10.7.

```
bool is_regular_file() const;
bool is_regular_file(error_code& ec) const noexcept;
```

15 *Returns:* `is_regular_file(this->status())` or `is_regular_file(this->status(), ec)`, respectively.

16 *Throws:* As specified in 30.10.7.

```
bool is_socket() const;
bool is_socket(error_code& ec) const noexcept;
```

17 *Returns:* `is_socket(this->status())` or `is_socket(this->status(), ec)`, respectively.

18 *Throws:* As specified in 30.10.7.

```
bool is_symlink() const;
bool is_symlink(error_code& ec) const noexcept;
```

19 *Returns:* `is_symlink(this->symlink_status())` or `is_symlink(this->symlink_status(), ec)`, respectively.

20 *Throws:* As specified in 30.10.7.

```
uintmax_t file_size() const;
uintmax_t file_size(error_code& ec) const noexcept;
```

21 *Returns:* If cached, the file size attribute value. Otherwise, `file_size(path())` or `file_size(path(), ec)`, respectively.

22 *Throws:* As specified in 30.10.7.

```
uintmax_t hard_link_count() const;
```

```
uintmax_t hard_link_count(error_code& ec) const noexcept;
```

23 *Returns:* If cached, the hard link count attribute value. Otherwise, `hard_link_count(path())` or `hard_link_count(path(), ec)`, respectively.

24 *Throws:* As specified in 30.10.7.

```
file_time_type last_write_time() const;
```

```
file_time_type last_write_time(error_code& ec) const noexcept;
```

25 *Returns:* If cached, the last write time attribute value. Otherwise, `last_write_time(path())` or `last_write_time(path(), ec)`, respectively.

26 *Throws:* As specified in 30.10.7.

```
file_status status() const;
```

```
file_status status(error_code& ec) const noexcept;
```

27 *Returns:* If cached, the status attribute value. Otherwise, `status(path())` or `status(path(), ec)`, respectively.

28 *Throws:* As specified in 30.10.7.

```
file_status symlink_status() const;
```

```
file_status symlink_status(error_code& ec) const noexcept;
```

29 *Returns:* If cached, the symlink status attribute value. Otherwise, `symlink_status(path())` or `symlink_status(path(), ec)`, respectively.

30 *Throws:* As specified in 30.10.7.

```
bool operator==(const directory_entry& rhs) const noexcept;
```

31 *Returns:* `pathobject == rhs.pathobject`.

```
bool operator!=(const directory_entry& rhs) const noexcept;
```

32 *Returns:* `pathobject != rhs.pathobject`.

```
bool operator< (const directory_entry& rhs) const noexcept;
```

33 *Returns:* `pathobject < rhs.pathobject`.

```
bool operator<=(const directory_entry& rhs) const noexcept;
```

34 *Returns:* `pathobject <= rhs.pathobject`.

```
bool operator> (const directory_entry& rhs) const noexcept;
```

35 *Returns:* `pathobject > rhs.pathobject`.

```
bool operator>=(const directory_entry& rhs) const noexcept;
```

36 *Returns:* `pathobject >= rhs.pathobject`.

30.10.13 Class `directory_iterator`

[`fs.class.directory_iterator`]

¹ An object of type `directory_iterator` provides an iterator for a sequence of `directory_entry` elements representing the path and any cached attribute values (30.10.12) for each file in a directory or in an implementation-defined directory-like file type. [*Note:* For iteration into sub-directories, see class `recursive_directory_iterator` (30.10.14). — *end note*]

```
namespace std::filesystem {
    class directory_iterator {
    public:
```



```

using iterator_category = input_iterator_tag;
using value_type         = directory_entry;
using difference_type     = ptrdiff_t;
using pointer            = const directory_entry*;
using reference           = const directory_entry&;

// 30.10.13.1, member functions
directory_iterator() noexcept;
explicit directory_iterator(const path& p);
directory_iterator(const path& p, directory_options options);
directory_iterator(const path& p, error_code& ec) noexcept;
directory_iterator(const path& p, directory_options options,
                  error_code& ec) noexcept;
directory_iterator(const directory_iterator& rhs);
directory_iterator(directory_iterator&& rhs) noexcept;
~directory_iterator();

directory_iterator& operator=(const directory_iterator& rhs);
directory_iterator& operator=(directory_iterator&& rhs) noexcept;

const directory_entry& operator*() const;
const directory_entry* operator->() const;
directory_iterator& operator++();
directory_iterator& increment(error_code& ec) noexcept;

// other members as required by 27.2.3, input iterators
};
}

```

- 2 `directory_iterator` satisfies the requirements of an input iterator (27.2.3).
- 3 If an iterator of type `directory_iterator` reports an error or is advanced past the last directory element, that iterator shall become equal to the end iterator value. The `directory_iterator` default constructor shall create an iterator equal to the end iterator value, and this shall be the only valid iterator for the end condition.
- 4 The end iterator is not dereferenceable.
- 5 Two end iterators are always equal. An end iterator shall not be equal to a non-end iterator.
- 6 The result of calling the `path()` member of the `directory_entry` object obtained by dereferencing a `directory_iterator` is a reference to a `path` object composed of the directory argument from which the iterator was constructed with filename of the directory entry appended as if by `operator/`.
- 7 Directory iteration shall not yield directory entries for the current (*dot*) and parent (*dot-dot*) directories.
- 8 The order of directory entries obtained by dereferencing successive increments of a `directory_iterator` is unspecified.
- 9 Constructors and non-const `directory_iterator` member functions store the values of any cached attributes (30.10.12) in the `directory_entry` element returned by `operator*`. `directory_iterator` member functions shall not directly or indirectly call any `directory_entry refresh` function. [Note: The exact mechanism for storing cached attribute values is not exposed to users. For exposition, class `directory_iterator` is shown in 30.10.12 as a friend of class `directory_entry`. — end note]
- 10 [Note: Programs performing directory iteration may wish to test if the path obtained by dereferencing a directory iterator actually exists. It could be a symbolic link to a non-existent file. Programs recursively walking directory trees for purposes of removing and renaming entries may wish to avoid following symbolic links. — end note]

- 11 [*Note*: If a file is removed from or added to a directory after the construction of a `directory_iterator` for the directory, it is unspecified whether or not subsequently incrementing the iterator will ever result in an iterator referencing the removed or added directory entry. See POSIX `readdir_r`. — *end note*]

30.10.13.1 `directory_iterator` members

[fs.dir.itr.members]

`directory_iterator()` noexcept;

- 1 *Effects*: Constructs the end iterator.

`explicit directory_iterator(const path& p);`

`directory_iterator(const path& p, directory_options options);`

`directory_iterator(const path& p, error_code& ec) noexcept;`

`directory_iterator(const path& p, directory_options options, error_code& ec) noexcept;`

- 2 *Effects*: For the directory that `p` resolves to, constructs an iterator for the first element in a sequence of `directory_entry` elements representing the files in the directory, if any; otherwise the end iterator. However, if

(`options & directory_options::skip_permission_denied`) != `directory_options::none`

and construction encounters an error indicating that permission to access `p` is denied, constructs the end iterator and does not report an error.

- 3 *Throws*: As specified in 30.10.7.

- 4 [*Note*: To iterate over the current directory, use `directory_iterator(".")` rather than `directory_iterator("")`. — *end note*]

`directory_iterator(const directory_iterator& rhs);`

`directory_iterator(directory_iterator&& rhs) noexcept;`

- 5 *Effects*: Constructs an object of class `directory_iterator`.

- 6 *Postconditions*: `*this` has the original value of `rhs`.

`directory_iterator& operator=(const directory_iterator& rhs);`

`directory_iterator& operator=(directory_iterator&& rhs) noexcept;`

- 7 *Effects*: If `*this` and `rhs` are the same object, the member has no effect.

- 8 *Postconditions*: `*this` has the original value of `rhs`.

- 9 *Returns*: `*this`.

`directory_iterator& operator++();`

`directory_iterator& increment(error_code& ec) noexcept;`

- 10 *Effects*: As specified for the prefix increment operation of Input iterators (27.2.3).

- 11 *Returns*: `*this`.

- 12 *Throws*: As specified in 30.10.7.

30.10.13.2 `directory_iterator` non-member functions

[fs.dir.itr.nonmembers]

- 1 These functions enable range access for `directory_iterator`.

`directory_iterator begin(directory_iterator iter) noexcept;`

- 2 *Returns*: `iter`.

`directory_iterator end(const directory_iterator&) noexcept;`

- 3 *Returns*: `directory_iterator()`.

30.10.14 Class recursive_directory_iterator**[fs.class.rec.dir.itr]**

- ¹ An object of type `recursive_directory_iterator` provides an iterator for a sequence of `directory_entry` elements representing the files in a directory or in an implementation-defined directory-like file type, and its sub-directories.

```

namespace std::filesystem {
    class recursive_directory_iterator {
    public:
        using iterator_category = input_iterator_tag;
        using value_type        = directory_entry;
        using difference_type    = ptrdiff_t;
        using pointer            = const directory_entry*;
        using reference          = const directory_entry&;

        // 30.10.14.1, constructors and destructor
        recursive_directory_iterator() noexcept;
        explicit recursive_directory_iterator(const path& p);
        recursive_directory_iterator(const path& p, directory_options options);
        recursive_directory_iterator(const path& p, directory_options options,
                                     error_code& ec) noexcept;
        recursive_directory_iterator(const path& p, error_code& ec) noexcept;
        recursive_directory_iterator(const recursive_directory_iterator& rhs);
        recursive_directory_iterator(recursive_directory_iterator&& rhs) noexcept;
        ~recursive_directory_iterator();

        // 30.10.14.1, observers
        directory_options options() const;
        int               depth() const;
        bool              recursion_pending() const;

        const directory_entry& operator*() const;
        const directory_entry* operator->() const;

        // 30.10.14.1, modifiers
        recursive_directory_iterator&
            operator=(const recursive_directory_iterator& rhs);
        recursive_directory_iterator&
            operator=(recursive_directory_iterator&& rhs) noexcept;

        recursive_directory_iterator& operator++();
        recursive_directory_iterator& increment(error_code& ec) noexcept;

        void pop();
        void pop(error_code& ec);
        void disable_recursion_pending();

        // other members as required by 27.2.3, input iterators
    };
}

```

- ² Calling `options`, `depth`, `recursion_pending`, `pop` or `disable_recursion_pending` on an iterator that is not dereferenceable results in undefined behavior.
- ³ The behavior of a `recursive_directory_iterator` is the same as a `directory_iterator` unless otherwise specified.

- 4 [*Note*: If the directory structure being iterated over contains cycles then the end iterator may be unreachable.
— *end note*]

30.10.14.1 recursive_directory_iterator members [fs.rec.dir.itr.members]

recursive_directory_iterator() noexcept;

- 1 *Effects*: Constructs the end iterator.

```
explicit recursive_directory_iterator(const path& p);
recursive_directory_iterator(const path& p, directory_options options);
recursive_directory_iterator(const path& p, directory_options options, error_code& ec) noexcept;
recursive_directory_iterator(const path& p, error_code& ec) noexcept;
```

- 2 *Effects*: Constructs a iterator representing the first entry in the directory *p* resolves to, if any; otherwise, the end iterator. However, if

(options & directory_options::skip_permission_denied) != directory_options::none
and construction encounters an error indicating that permission to access *p* is denied, constructs the end iterator and does not report an error.

- 3 *Postconditions*: options() == options for the signatures with a directory_options argument, otherwise options() == directory_options::none.

- 4 *Throws*: As specified in 30.10.7.

- 5 [*Note*: To iterate over the current directory, use recursive_directory_iterator(".") rather than recursive_directory_iterator(""). — *end note*]

- 6 [*Note*: By default, recursive_directory_iterator does not follow directory symlinks. To follow directory symlinks, specify options as directory_options::follow_directory_symlink — *end note*]

recursive_directory_iterator(const recursive_directory_iterator& rhs);

- 7 *Effects*: Constructs an object of class recursive_directory_iterator.

- 8 *Postconditions*:

- (8.1) — options() == rhs.options()
- (8.2) — depth() == rhs.depth()
- (8.3) — recursion_pending() == rhs.recursion_pending()

recursive_directory_iterator(recursive_directory_iterator&& rhs) noexcept;

- 9 *Effects*: Constructs an object of class recursive_directory_iterator.

- 10 *Postconditions*: options(), depth(), and recursion_pending() have the values that rhs.options(), rhs.depth(), and rhs.recursion_pending(), respectively, had before the function call.

recursive_directory_iterator& operator=(const recursive_directory_iterator& rhs);

- 11 *Effects*: If *this and rhs are the same object, the member has no effect.

- 12 *Postconditions*:

- (12.1) — options() == rhs.options()
- (12.2) — depth() == rhs.depth()
- (12.3) — recursion_pending() == rhs.recursion_pending()

- 13 *Returns*: *this.

recursive_directory_iterator& operator=(recursive_directory_iterator&& rhs) noexcept;

14 *Effects:* If `*this` and `rhs` are the same object, the member has no effect.

15 *Postconditions:* `options()`, `depth()`, and `recursion_pending()` have the values that `rhs.options()`, `rhs.depth()`, and `rhs.recursion_pending()`, respectively, had before the function call.

16 *Returns:* `*this`.

`directory_options options() const;`

17 *Returns:* The value of the argument passed to the constructor for the `options` parameter, if present, otherwise `directory_options::none`.

18 *Throws:* Nothing.

`int depth() const;`

19 *Returns:* The current depth of the directory tree being traversed. [*Note:* The initial directory is depth 0, its immediate subdirectories are depth 1, and so forth. — *end note*]

20 *Throws:* Nothing.

`bool recursion_pending() const;`

21 *Returns:* `true` if `disable_recursion_pending()` has not been called subsequent to the prior construction or increment operation, otherwise `false`.

22 *Throws:* Nothing.

`recursive_directory_iterator& operator++();`
`recursive_directory_iterator& increment(error_code& ec) noexcept;`

23 *Effects:* As specified for the prefix increment operation of Input iterators (27.2.3), except that:

(23.1) — If there are no more entries at the current depth, then if `depth() != 0` iteration over the parent directory resumes; otherwise `*this = recursive_directory_iterator()`.

(23.2) — Otherwise if

`recursion_pending() && is_directory((*this)->status()) &&`
`(!is_symlink((*this)->symlink_status()) ||`
`(options() & directory_options::follow_directory_symlink) != directory_options::none)`
 then either directory `(*this)->path()` is recursively iterated into or, if

`(options() & directory_options::skip_permission_denied) != directory_options::none`
 and an error occurs indicating that permission to access directory `(*this)->path()` is denied,
 then directory `(*this)->path()` is treated as an empty directory and no error is reported.

24 *Returns:* `*this`.

25 *Throws:* As specified in 30.10.7.

`void pop();`
`void pop(error_code& ec);`

26 *Effects:* If `depth() == 0`, set `*this` to `recursive_directory_iterator()`. Otherwise, cease iteration of the directory currently being iterated over, and continue iteration over the parent directory.

27 *Throws:* As specified in 30.10.7.

`void disable_recursion_pending();`

28 *Postconditions:* `recursion_pending() == false`.

29 [*Note:* `disable_recursion_pending()` is used to prevent unwanted recursion into a directory. — *end note*]

30.10.14.2 recursive_directory_iterator non-member functions [fs.rec.dir.itr.nonmembers]

¹ These functions enable use of `recursive_directory_iterator` with range-based for statements.

```
recursive_directory_iterator begin(recursive_directory_iterator iter) noexcept;
```

² *Returns:* `iter`.

```
recursive_directory_iterator end(const recursive_directory_iterator&) noexcept;
```

³ *Returns:* `recursive_directory_iterator()`.

30.10.15 Filesystem operation functions [fs.op.funcs]

¹ Filesystem operation functions query or modify files, including directories, in external storage.

² [*Note:* Because hardware failures, network failures, file system races (30.10.4.5), and many other kinds of errors occur frequently in file system operations, users should be aware that any filesystem operation function, no matter how apparently innocuous, may encounter an error; see 30.10.7. — *end note*]

30.10.15.1 Absolute [fs.op.absolute]

```
path absolute(const path& p);
path absolute(const path& p, error_code& ec);
```

¹ *Effects:* Composes an absolute path referencing the same file system location as `p` according to the operating system (30.10.2.2).

² *Returns:* The composed path. The signature with argument `ec` returns `path()` if an error occurs.

³ [*Note:* For the returned path, `rp.is_absolute()` is `true` unless an error occurs. — *end note*]

⁴ *Throws:* As specified in 30.10.7.

⁵ [*Note:* To resolve symlinks, or perform other sanitization which might require queries to secondary storage, such as hard disks, consider `canonical` (30.10.15.2). — *end note*]

⁶ [*Note:* Implementations are strongly encouraged to not query secondary storage, and not consider `!exists(p)` an error. — *end note*]

⁷ [*Example:* For POSIX-based operating systems, `absolute(p)` is simply `current_path()/p`. For Windows-based operating systems, `absolute` might have the same semantics as `GetFullPathNameW`. — *end example*]

30.10.15.2 Canonical [fs.op.canonical]

```
path canonical(const path& p, const path& base = current_path());
path canonical(const path& p, error_code& ec);
path canonical(const path& p, const path& base, error_code& ec);
```

¹ *Effects:* Converts `p`, which must exist, to an absolute path that has no symbolic link, *dot*, or *dot-dot* elements in its pathname in the generic format.

² *Returns:* A path that refers to the same file system object as `absolute(p, base)`. For the overload without a `base` argument, `base` is `current_path()`. Signatures with argument `ec` return `path()` if an error occurs.

³ *Throws:* As specified in 30.10.7.

⁴ *Remarks:* `!exists(p)` is an error.

30.10.15.3 Copy [fs.op.copy]

```
void copy(const path& from, const path& to);
```

1 *Effects:* Equivalent to `copy(from, to, copy_options::none)`.

```
void copy(const path& from, const path& to, error_code& ec) noexcept;
```

2 *Effects:* Equivalent to `copy(from, to, copy_options::none, ec)`.

```
void copy(const path& from, const path& to, copy_options options);
void copy(const path& from, const path& to, copy_options options,
          error_code& ec) noexcept;
```

3 *Requires:* At most one element from each option group (30.10.10.3) is set in `options`.

4 *Effects:* Before the first use of `f` and `t`:

- (4.1) — If


```
(options & copy_options::create_symlinks) != copy_options::none ||
(options & copy_options::skip_symlinks) != copy_options::none
```

 then `auto f = symlink_status(from)` and if needed `auto t = symlink_status(to)`.
- (4.2) — Otherwise, if


```
(options & copy_options::copy_symlinks) != copy_options::none
```

 then `auto f = symlink_status(from)` and if needed `auto t = status(to)`.
- (4.3) — Otherwise, `auto f = status(from)` and if needed `auto t = status(to)`.

Effects are then as follows:

- (4.4) — If `f.type()` or `t.type()` is an implementation-defined file type (30.10.10.2), then the effects are implementation-defined.
- (4.5) — Otherwise, an error is reported as specified in 30.10.7 if:
 - (4.5.1) — `!exists(f)`, or
 - (4.5.2) — `equivalent(from, to)`, or
 - (4.5.3) — `is_other(f) || is_other(t)`, or
 - (4.5.4) — `is_directory(f) && is_regular_file(t)`.
- (4.6) — Otherwise, if `is_symlink(f)`, then:
 - (4.6.1) — If `(options & copy_options::skip_symlinks) != copy_options::none` then return.
 - (4.6.2) — Otherwise if


```
!exists(t) && (options & copy_options::copy_symlinks) != copy_options::none
```

 then `copy_symlink(from, to)`.
 - (4.6.3) — Otherwise report an error as specified in 30.10.7.
- (4.7) — Otherwise, if `is_regular_file(f)`, then:
 - (4.7.1) — If `(options & copy_options::directories_only) != copy_options::none`, then return.
 - (4.7.2) — Otherwise, if `(options & copy_options::create_symlinks) != copy_options::none`, then create a symbolic link to the source file.
 - (4.7.3) — Otherwise, if `(options & copy_options::create_hard_links) != copy_options::none`, then create a hard link to the source file.
 - (4.7.4) — Otherwise, if `is_directory(t)`, then `copy_file(from, to/from.filename(), options)`.
 - (4.7.5) — Otherwise, `copy_file(from, to, options)`.
 - (4.8) — Otherwise, if

- ```

 is_directory(f) &&
 ((options & copy_options::recursive) != copy_options::none ||
 options == copy_options::none)
 then:
(4.8.1) — If !exists(t), then create_directory(to, from).
(4.8.2) — Then, iterate over the files in from, as if by
 for (const directory_entry& x : directory_iterator(from))
 copy(x.path(), to/x.path().filename(), options | copy_options::unspecified)
(4.9) — Otherwise, for the signature with argument ec, ec.clear().
(4.10) — Otherwise, no effects.
5 Throws: As specified in 30.10.7.
6 Remarks: For the signature with argument ec, any library functions called by the implementation shall
 have an error_code argument if applicable.
7 [Example: Given this directory structure:

```

```

 /dir1
 file1
 file2
 dir2
 file3

```

Calling `copy("/dir1", "/dir3")` would result in:

```

 /dir1
 file1
 file2
 dir2
 file3
 /dir3
 file1
 file2

```

Alternatively, calling `copy("/dir1", "/dir3", copy_options::recursive)` would result in:

```

 /dir1
 file1
 file2
 dir2
 file3
 /dir3
 file1
 file2
 dir2
 file3

```

— *end example*]

#### 30.10.15.4 Copy file

[fs.op.copy\_file]

```

bool copy_file(const path& from, const path& to);
bool copy_file(const path& from, const path& to, error_code& ec) noexcept;

```

- 1     *Returns:* `copy_file(from, to, copy_options::none)` or  
       `copy_file(from, to, copy_options::none, ec)`, respectively.
- 2     *Throws:* As specified in 30.10.7.



```
bool copy_file(const path& from, const path& to, copy_options options);
bool copy_file(const path& from, const path& to, copy_options options,
 error_code& ec) noexcept;
```

3 *Requires:* At most one element from each option group (30.10.10.3) is set in `options`.

4 *Effects:* As follows:

- (4.1) — Report a file already exists error as specified in 30.10.7 if:
    - (4.1.1) — `!is_regular_file(from)`, or
    - (4.1.2) — `exists(to)` and `!is_regular_file(to)`, or
    - (4.1.3) — `exists(to)` and `equivalent(from, to)`, or
    - (4.1.4) — `exists(to)` and
      - `(options & (copy_options::skip_existing |`  
`copy_options::overwrite_existing |`  
`copy_options::update_existing)) == copy_options::none`
  - (4.2) — Otherwise, copy the contents and attributes of the file `from` resolves to, to the file `to` resolves to, if:
    - (4.2.1) — `!exists(to)`, or
    - (4.2.2) — `(options & copy_options::overwrite_existing) != copy_options::none`, or
    - (4.2.3) — `(options & copy_options::update_existing) != copy_options::none` and `from` is more recent than `to`, determined as if by use of the `last_write_time` function (30.10.15.25).
  - (4.3) — Otherwise, no effects.
- 5 *Returns:* `true` if the `from` file was copied, otherwise `false`. The signature with argument `ec` returns `false` if an error occurs.
- 6 *Throws:* As specified in 30.10.7.
- 7 *Complexity:* At most one direct or indirect invocation of `status(to)`.

### 30.10.15.5 Copy symlink

[fs.op.copy\_symlink]

```
void copy_symlink(const path& existing_symlink, const path& new_symlink);
void copy_symlink(const path& existing_symlink, const path& new_symlink,
 error_code& ec) noexcept;
```

- 1 *Effects:* Equivalent to *function*(`read_symlink(existing_symlink)`, `new_symlink`) or *function*(`read_symlink(existing_symlink, ec)`, `new_symlink, ec`), respectively, where in each case *function* is `create_symlink` or `create_directory_symlink` as appropriate.
- 2 *Throws:* As specified in 30.10.7.

### 30.10.15.6 Create directories

[fs.op.create\_directories]

```
bool create_directories(const path& p);
bool create_directories(const path& p, error_code& ec) noexcept;
```

- 1 *Effects:* Establishes the postcondition by calling `create_directory()` for any element of `p` that does not exist.
- 2 *Postconditions:* `is_directory(p)`.
- 3 *Returns:* `true` if a new directory was created, otherwise `false`. The signature with argument `ec` returns `false` if an error occurs.
- 4 *Throws:* As specified in 30.10.7.

5 *Complexity:*  $\mathcal{O}(n)$  where  $n$  is the number of elements of  $p$  that do not exist.

### 30.10.15.7 Create directory

[fs.op.create\_directory]

```
bool create_directory(const path& p);
bool create_directory(const path& p, error_code& ec) noexcept;
```

1 *Effects:* Establishes the postcondition by attempting to create the directory  $p$  resolves to, as if by POSIX `mkdir()` with a second argument of `static_cast<int>(perms::all)`. Creation failure because  $p$  resolves to an existing directory shall not be treated as an error.

2 *Postconditions:* `is_directory(p)`.

3 *Returns:* `true` if a new directory was created, otherwise `false`. The signature with argument `ec` returns `false` if an error occurs.

4 *Throws:* As specified in 30.10.7.

```
bool create_directory(const path& p, const path& existing_p);
bool create_directory(const path& p, const path& existing_p, error_code& ec) noexcept;
```

5 *Effects:* Establishes the postcondition by attempting to create the directory  $p$  resolves to, with attributes copied from directory `existing_p`. The set of attributes copied is operating system dependent. Creation failure because  $p$  resolves to an existing directory shall not be treated as an error. [Note: For POSIX-based operating systems, the attributes are those copied by native API `stat(existing_p.c_str(), &attributes_stat)` followed by `mkdir(p.c_str(), attributes_stat.st_mode)`. For Windows-based operating systems, the attributes are those copied by native API `CreateDirectoryExW(existing_p.c_str(), p.c_str(), 0)`. — end note]

6 *Postconditions:* `is_directory(p)`.

7 *Returns:* `true` if a new directory was created, otherwise `false`. The signature with argument `ec` returns `false` if an error occurs.

8 *Throws:* As specified in 30.10.7.

### 30.10.15.8 Create directory symlink

[fs.op.create\_dir\_symlink]

```
void create_directory_symlink(const path& to, const path& new_symlink);
void create_directory_symlink(const path& to, const path& new_symlink,
 error_code& ec) noexcept;
```

1 *Effects:* Establishes the postcondition, as if by POSIX `symlink()`.

2 *Postconditions:* `new_symlink` resolves to a symbolic link file that contains an unspecified representation of `to`.

3 *Throws:* As specified in 30.10.7.

4 [Note: Some operating systems require symlink creation to identify that the link is to a directory. Portable code should use `create_directory_symlink()` to create directory symlinks rather than `create_symlink()` — end note]

5 [Note: Some operating systems do not support symbolic links at all or support them only for regular files. Some file systems (such as the FAT file system) do not support symbolic links regardless of the operating system. — end note]

### 30.10.15.9 Create hard link

[fs.op.create\_hard\_lk]

```
void create_hard_link(const path& to, const path& new_hard_link);
void create_hard_link(const path& to, const path& new_hard_link,
 error_code& ec) noexcept;
```

1 *Effects:* Establishes the postcondition, as if by POSIX `link()`.

2 *Postconditions:*

(2.1) — `exists(to) && exists(new_hard_link) && equivalent(to, new_hard_link)`

(2.2) — The contents of the file or directory `to` resolves to are unchanged.

3 *Throws:* As specified in 30.10.7.

4 [ *Note:* Some operating systems do not support hard links at all or support them only for regular files. Some file systems (such as the FAT file system) do not support hard links regardless of the operating system. Some file systems limit the number of links per file. — *end note* ]

### 30.10.15.10 Create symlink

[fs.op.create\_symlink]

```
void create_symlink(const path& to, const path& new_symlink);
void create_symlink(const path& to, const path& new_symlink,
 error_code& ec) noexcept;
```

1 *Effects:* Establishes the postcondition, as if by POSIX `symlink()`.

2 *Postconditions:* `new_symlink` resolves to a symbolic link file that contains an unspecified representation of `to`.

3 *Throws:* As specified in 30.10.7.

4 [ *Note:* Some operating systems do not support symbolic links at all or support them only for regular files. Some file systems (such as the FAT file system) do not support symbolic links regardless of the operating system. — *end note* ]

### 30.10.15.11 Current path

[fs.op.current\_path]

```
path current_path();
path current_path(error_code& ec);
```

1 *Returns:* The absolute path of the current working directory, whose pathname in the native format is obtained as if by POSIX `getcwd()`. The signature with argument `ec` returns `path()` if an error occurs.

2 *Throws:* As specified in 30.10.7.

3 *Remarks:* The current working directory is the directory, associated with the process, that is used as the starting location in pathname resolution for relative paths.

4 [ *Note:* The `current_path()` name was chosen to emphasize that the returned value is a path, not just a single directory name. — *end note* ]

5 [ *Note:* The current path as returned by many operating systems is a dangerous global variable. It may be changed unexpectedly by a third-party or system library functions, or by another thread. — *end note* ]

```
void current_path(const path& p);
void current_path(const path& p, error_code& ec) noexcept;
```

6 *Effects:* Establishes the postcondition, as if by POSIX `chdir()`.

7 *Postconditions:* `equivalent(p, current_path())`.

8 *Throws:* As specified in 30.10.7.

9 [ *Note:* The current path for many operating systems is a dangerous global state. It may be changed unexpectedly by a third-party or system library functions, or by another thread. — *end note* ]

### 30.10.15.12 Equivalent

[fs.op.equivalent]

```
bool equivalent(const path& p1, const path& p2);
bool equivalent(const path& p1, const path& p2, error_code& ec) noexcept;
```

- 1 Let `s1` and `s2` be `file_status`s, determined as if by `status(p1)` and `status(p2)`, respectively.
- 2 *Effects:* Determines `s1` and `s2`. If `(!exists(s1) && !exists(s2)) || (is_other(s1) && is_other(s2))` an error is reported (30.10.7).
- 3 *Returns:* `true`, if `s1 == s2` and `p1` and `p2` resolve to the same file system entity, else `false`. The signature with argument `ec` returns `false` if an error occurs.
- 4 Two paths are considered to resolve to the same file system entity if two candidate entities reside on the same device at the same location. This is determined as if by the values of the POSIX `stat` structure, obtained as if by `stat()` for the two paths, having equal `st_dev` values and equal `st_ino` values.
- 5 *Throws:* As specified in 30.10.7.

### 30.10.15.13 Exists

[fs.op.exists]

```
bool exists(file_status s) noexcept;
```

- 1 *Returns:* `status_known(s) && s.type() != file_type::not_found`.

```
bool exists(const path& p);
bool exists(const path& p, error_code& ec) noexcept;
```

- 2 Let `s` be a `file_status`, determined as if by `status(p)` or `status(p, ec)`, respectively.
- 3 *Effects:* The signature with argument `ec` calls `ec.clear()` if `status_known(s)`.
- 4 *Returns:* `exists(s)`.
- 5 *Throws:* As specified in 30.10.7.

### 30.10.15.14 File size

[fs.op.file\_size]

```
uintmax_t file_size(const path& p);
uintmax_t file_size(const path& p, error_code& ec) noexcept;
```

- 1 *Returns:*
    - (1.1) — If `!exists(p)` an error is reported (30.10.7).
    - (1.2) — Otherwise, if `is_regular_file(p)`, the size in bytes of the file `p` resolves to, determined as if by the value of the POSIX `stat` structure member `st_size` obtained as if by POSIX `stat()`.
    - (1.3) — Otherwise, the result is implementation-defined.
- The signature with argument `ec` returns `static_cast<uintmax_t>(-1)` if an error occurs.
- 2 *Throws:* As specified in 30.10.7.

### 30.10.15.15 Hard link count

[fs.op.hard\_lk\_ct]

```
uintmax_t hard_link_count(const path& p);
uintmax_t hard_link_count(const path& p, error_code& ec) noexcept;
```

- 1 *Returns:* The number of hard links for `p`. The signature with argument `ec` returns `static_cast<uintmax_t>(-1)` if an error occurs.
- 2 *Throws:* As specified in 30.10.7.

### 30.10.15.16 Is block file

[fs.op.is\_block\_file]

```
bool is_block_file(file_status s) noexcept;
```

- 1 *Returns:* `s.type() == file_type::block`.

```
bool is_block_file(const path& p);
bool is_block_file(const path& p, error_code& ec) noexcept;
```

2 *Returns:* `is_block_file(status(p))` or `is_block_file(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3 *Throws:* As specified in 30.10.7.

### 30.10.15.17 Is character file [fs.op.is\_char\_file]

```
bool is_character_file(file_status s) noexcept;
```

1 *Returns:* `s.type() == file_type::character`.

```
bool is_character_file(const path& p);
bool is_character_file(const path& p, error_code& ec) noexcept;
```

2 *Returns:* `is_character_file(status(p))` or `is_character_file(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3 *Throws:* As specified in 30.10.7.

### 30.10.15.18 Is directory [fs.op.is\_directory]

```
bool is_directory(file_status s) noexcept;
```

1 *Returns:* `s.type() == file_type::directory`.

```
bool is_directory(const path& p);
bool is_directory(const path& p, error_code& ec) noexcept;
```

2 *Returns:* `is_directory(status(p))` or `is_directory(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3 *Throws:* As specified in 30.10.7.

### 30.10.15.19 Is empty [fs.op.is\_empty]

```
bool is_empty(const path& p);
bool is_empty(const path& p, error_code& ec) noexcept;
```

1 *Effects:*

- (1.1) — Determine `file_status s`, as if by `status(p)` or `status(p, ec)`, respectively.
- (1.2) — For the signature with argument `ec`, return `false` if an error occurred.
- (1.3) — Otherwise, if `is_directory(s)`:
  - (1.3.1) — Create a variable `itr`, as if by `directory_iterator itr(p)` or `directory_iterator itr(p, ec)`, respectively.
  - (1.3.2) — For the signature with argument `ec`, return `false` if an error occurred.
  - (1.3.3) — Otherwise, return `itr == directory_iterator()`.
- (1.4) — Otherwise:
  - (1.4.1) — Determine `uintmax_t sz`, as if by `file_size(p)` or `file_size(p, ec)`, respectively.
  - (1.4.2) — For the signature with argument `ec`, return `false` if an error occurred.
  - (1.4.3) — Otherwise, return `sz == 0`.

2 *Throws:* As specified in 30.10.7.

### 30.10.15.20 Is fifo [fs.op.is\_fifo]

```
bool is_fifo(file_status s) noexcept;
```

1     *Returns:* `s.type() == file_type::fifo`.

```
bool is_fifo(const path& p);
```

```
bool is_fifo(const path& p, error_code& ec) noexcept;
```

2     *Returns:* `is_fifo(status(p))` or `is_fifo(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3     *Throws:* As specified in 30.10.7.

### 30.10.15.21 Is other

[fs.op.is\_\_other]

```
bool is_other(file_status s) noexcept;
```

1     *Returns:* `exists(s) && !is_regular_file(s) && !is_directory(s) && !is_symlink(s)`.

```
bool is_other(const path& p);
```

```
bool is_other(const path& p, error_code& ec) noexcept;
```

2     *Returns:* `is_other(status(p))` or `is_other(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3     *Throws:* As specified in 30.10.7.

### 30.10.15.22 Is regular file

[fs.op.is\_\_regular\_file]

```
bool is_regular_file(file_status s) noexcept;
```

1     *Returns:* `s.type() == file_type::regular`.

```
bool is_regular_file(const path& p);
```

2     *Returns:* `is_regular_file(status(p))`.

3     *Throws:* `filesystem_error` if `status(p)` would throw `filesystem_error`.

```
bool is_regular_file(const path& p, error_code& ec) noexcept;
```

4     *Effects:* Sets `ec` as if by `status(p, ec)`. [Note: `file_type::none`, `file_type::not_found` and `file_type::unknown` cases set `ec` to error values. To distinguish between cases, call the `status` function directly. — end note]

5     *Returns:* `is_regular_file(status(p, ec))`. Returns `false` if an error occurs.

### 30.10.15.23 Is socket

[fs.op.is\_\_socket]

```
bool is_socket(file_status s) noexcept;
```

1     *Returns:* `s.type() == file_type::socket`.

```
bool is_socket(const path& p);
```

```
bool is_socket(const path& p, error_code& ec) noexcept;
```

2     *Returns:* `is_socket(status(p))` or `is_socket(status(p, ec))`, respectively. The signature with argument `ec` returns `false` if an error occurs.

3     *Throws:* As specified in 30.10.7.

### 30.10.15.24 Is symlink

[fs.op.is\_\_symlink]

```
bool is_symlink(file_status s) noexcept;
```

1     *Returns:* `s.type() == file_type::symlink`.

```
bool is_symlink(const path& p);
bool is_symlink(const path& p, error_code& ec) noexcept;
```

2 *Returns:* `is_symlink(symlink_status(p))` or `is_symlink(symlink_status(p, ec))`, respectively.  
The signature with argument `ec` returns `false` if an error occurs.

3 *Throws:* As specified in 30.10.7.

### 30.10.15.25 Last write time [fs.op.last\_write\_time]

```
file_time_type last_write_time(const path& p);
file_time_type last_write_time(const path& p, error_code& ec) noexcept;
```

1 *Returns:* The time of last data modification of `p`, determined as if by the value of the POSIX `stat` structure member `st_mtime` obtained as if by POSIX `stat()`. The signature with argument `ec` returns `file_time_type::min()` if an error occurs.

2 *Throws:* As specified in 30.10.7.

```
void last_write_time(const path& p, file_time_type new_time);
void last_write_time(const path& p, file_time_type new_time,
 error_code& ec) noexcept;
```

3 *Effects:* Sets the time of last data modification of the file resolved to by `p` to `new_time`, as if by POSIX `futimens()`.

4 *Throws:* As specified in 30.10.7.

5 [ *Note:* A postcondition of `last_write_time(p) == new_time` is not specified since it might not hold for file systems with coarse time granularity. — *end note* ]

### 30.10.15.26 Permissions [fs.op.permissions]

```
void permissions(const path& p, perms prms, perm_options opts=perm_options::replace);
void permissions(const path& p, perms prms, error_code& ec) noexcept;
void permissions(const path& p, perms prms, perm_options opts, error_code& ec);
```

1 *Requires:* Exactly one of the `perm_options` constants `replace`, `add`, or `remove` is present in `opts`.

2 *Remarks:* The second signature behaves as if it had an additional parameter `perm_options opts` with an argument of `perm_options::replace`.

3 *Effects:* Applies the action specified by `opts` to the file `p` resolves to, or to file `p` itself if `p` is a symbolic link and `perm_options::nofollow` is set in `opts`. The action is applied as if by POSIX `fchmodat()`.

4 [ *Note:* Conceptually permissions are viewed as bits, but the actual implementation may use some other mechanism. — *end note* ]

5 *Throws:* As specified in 30.10.7.

### 30.10.15.27 Proximate [fs.op.proximate]

```
path proximate(const path& p, error_code& ec);
```

1 *Returns:* `proximate(p, current_path(), ec)`.

2 *Throws:* As specified in 30.10.7.

```
path proximate(const path& p, const path& base = current_path());
path proximate(const path& p, const path& base, error_code& ec);
```

3 *Returns:* For the first form:

```
 weakly_canonical(p).lexically_proximate(weakly_canonical(base));
```

For the second form:

```
weakly_canonical(p, ec).lexically_proximate(weakly_canonical(base, ec));
```

or `path()` at the first error occurrence, if any.

4 *Throws:* As specified in 30.10.7.

### 30.10.15.28 Read symlink

[fs.op.read\_symlink]

```
path read_symlink(const path& p);
path read_symlink(const path& p, error_code& ec);
```

1 *Returns:* If `p` resolves to a symbolic link, a `path` object containing the contents of that symbolic link. The signature with argument `ec` returns `path()` if an error occurs.

2 *Throws:* As specified in 30.10.7. [ *Note:* It is an error if `p` does not resolve to a symbolic link. — end note ]

### 30.10.15.29 Relative

[fs.op.relative]

```
path relative(const path& p, error_code& ec);
```

1 *Returns:* `relative(p, current_path(), ec)`.

2 *Throws:* As specified in 30.10.7.

```
path relative(const path& p, const path& base = current_path());
path relative(const path& p, const path& base, error_code& ec);
```

3 *Returns:* For the first form:

```
weakly_canonical(p).lexically_relative(weakly_canonical(base));
```

For the second form:

```
weakly_canonical(p, ec).lexically_relative(weakly_canonical(base, ec));
```

or `path()` at the first error occurrence, if any.

4 *Throws:* As specified in 30.10.7.

### 30.10.15.30 Remove

[fs.op.remove]

```
bool remove(const path& p);
bool remove(const path& p, error_code& ec) noexcept;
```

1 *Effects:* If `exists(symlink_status(p, ec))`, the file `p` is removed as if by POSIX `remove()`. [ *Note:* A symbolic link is itself removed, rather than the file it resolves to. — end note ]

2 *Postconditions:* `!exists(symlink_status(p))`.

3 *Returns:* `false` if `p` did not exist, otherwise `true`. The signature with argument `ec` returns `false` if an error occurs.

4 *Throws:* As specified in 30.10.7.

### 30.10.15.31 Remove all

[fs.op.remove\_all]

```
uintmax_t remove_all(const path& p);
uintmax_t remove_all(const path& p, error_code& ec) noexcept;
```

1 *Effects:* Recursively deletes the contents of `p` if it exists, then deletes file `p` itself, as if by POSIX `remove()`. [ *Note:* A symbolic link is itself removed, rather than the file it resolves to. — end note ]

2 *Postconditions:* `!exists(symlink_status(p))`.



3 *Returns:* The number of files removed. The signature with argument `ec` returns `static_cast<uintmax_t>(-1)` if an error occurs.

4 *Throws:* As specified in 30.10.7.

### 30.10.15.32 Rename

[fs.op.rename]

```
void rename(const path& old_p, const path& new_p);
void rename(const path& old_p, const path& new_p, error_code& ec) noexcept;
```

1 *Effects:* Renames `old_p` to `new_p`, as if by POSIX `rename()`.

[ *Note:*

- (1.1) — If `old_p` and `new_p` resolve to the same existing file, no action is taken.
- (1.2) — Otherwise, the rename may include the following effects:
  - (1.2.1) — if `new_p` resolves to an existing non-directory file, `new_p` is removed; otherwise,
  - (1.2.2) — if `new_p` resolves to an existing directory, `new_p` is removed if empty on POSIX compliant operating systems but may be an error on other operating systems.

A symbolic link is itself renamed, rather than the file it resolves to. — *end note*]

2 *Throws:* As specified in 30.10.7.

### 30.10.15.33 Resize file

[fs.op.resize\_file]

```
void resize_file(const path& p, uintmax_t new_size);
void resize_file(const path& p, uintmax_t new_size, error_code& ec) noexcept;
```

1 *Postconditions:* `file_size(p) == new_size`.

2 *Throws:* As specified in 30.10.7.

3 *Remarks:* Achieves its postconditions as if by POSIX `truncate()`.

### 30.10.15.34 Space

[fs.op.space]

```
space_info space(const path& p);
space_info space(const path& p, error_code& ec) noexcept;
```

1 *Returns:* An object of type `space_info`. The value of the `space_info` object is determined as if by using POSIX `statvfs` to obtain a POSIX `struct statvfs`, and then multiplying its `f_blocks`, `f_bfree`, and `f_bavail` members by its `f_frsize` member, and assigning the results to the `capacity`, `free`, and `available` members respectively. Any members for which the value cannot be determined shall be set to `static_cast<uintmax_t>(-1)`. For the signature with argument `ec`, all members are set to `static_cast<uintmax_t>(-1)` if an error occurs.

2 *Throws:* As specified in 30.10.7.

3 *Remarks:* The value of member `space_info::available` is operating system dependent. [ *Note:* `available` may be less than `free`. — *end note* ]

### 30.10.15.35 Status

[fs.op.status]

```
file_status status(const path& p);
```

1 *Effects:* As if:

```
error_code ec;
file_status result = status(p, ec);
if (result.type() == file_type::none)
 throw filesystem_error(implementation-supplied-message, p, ec);
```

return result;

2 Returns: See above.

3 Throws: filesystem\_error. [Note: result values of file\_status(file\_type::not\_found) and file\_status(file\_type::unknown) are not considered failures and do not cause an exception to be thrown. — end note]

file\_status status(const path& p, error\_code& ec) noexcept;

4 Effects: If possible, determines the attributes of the file `p` resolves to, as if by using POSIX `stat()` to obtain a POSIX `struct stat`. If, during attribute determination, the underlying file system API reports an error, sets `ec` to indicate the specific error reported. Otherwise, `ec.clear()`. [Note: This allows users to inspect the specifics of underlying API errors even when the value returned by `status()` is not `file_status(file_type::none)`. — end note]

5 Let `prms` denote the result of `(m & perms::mask)`, where `m` is determined as if by converting the `st_mode` member of the obtained `struct stat` to the type `perms`.

6 Returns:

(6.1) — If `ec != error_code()`:

(6.1.1) — If the specific error indicates that `p` cannot be resolved because some element of the path does not exist, returns `file_status(file_type::not_found)`.

(6.1.2) — Otherwise, if the specific error indicates that `p` can be resolved but the attributes cannot be determined, returns `file_status(file_type::unknown)`.

(6.1.3) — Otherwise, returns `file_status(file_type::none)`.

[Note: These semantics distinguish between `p` being known not to exist, `p` existing but not being able to determine its attributes, and there being an error that prevents even knowing if `p` exists. These distinctions are important to some use cases. — end note]

(6.2) — Otherwise,

(6.2.1) — If the attributes indicate a regular file, as if by POSIX `S_ISREG`, returns `file_status(file_type::regular, prms)`. [Note: `file_type::regular` implies appropriate `<fstream>` operations would succeed, assuming no hardware, permission, access, or file system race errors. Lack of `file_type::regular` does not necessarily imply `<fstream>` operations would fail on a directory. — end note]

(6.2.2) — Otherwise, if the attributes indicate a directory, as if by POSIX `S_ISDIR`, returns `file_status(file_type::directory, prms)`. [Note: `file_type::directory` implies that calling `directory_iterator(p)` would succeed. — end note]

(6.2.3) — Otherwise, if the attributes indicate a block special file, as if by POSIX `S_ISBLK`, returns `file_status(file_type::block, prms)`.

(6.2.4) — Otherwise, if the attributes indicate a character special file, as if by POSIX `S_ISCHR`, returns `file_status(file_type::character, prms)`.

(6.2.5) — Otherwise, if the attributes indicate a fifo or pipe file, as if by POSIX `S_ISFIFO`, returns `file_status(file_type::fifo, prms)`.

(6.2.6) — Otherwise, if the attributes indicate a socket, as if by POSIX `S_ISSOCK`, returns `file_status(file_type::socket, prms)`.

(6.2.7) — Otherwise, if the attributes indicate an implementation-defined file type (30.10.10.2), returns `file_status(file_type::A, prms)`, where `A` is the constant for the implementation-defined file type.

(6.2.8) — Otherwise, returns `file_status(file_type::unknown, prms)`.

7 *Remarks:* If a symbolic link is encountered during pathname resolution, pathname resolution continues using the contents of the symbolic link.

### 30.10.15.36 Status known [fs.op.status\_known]

```
bool status_known(file_status s) noexcept;
```

1 *Returns:* `s.type() != file_type::none`.

### 30.10.15.37 Symlink status [fs.op.symlink\_status]

```
file_status symlink_status(const path& p);
file_status symlink_status(const path& p, error_code& ec) noexcept;
```

1 *Effects:* Same as `status()`, above, except that the attributes of `p` are determined as if by using POSIX `lstat()` to obtain a POSIX `struct stat`.

2 Let `prms` denote the result of `(m & perms::mask)`, where `m` is determined as if by converting the `st_mode` member of the obtained `struct stat` to the type `perms`.

3 *Returns:* Same as `status()`, above, except that if the attributes indicate a symbolic link, as if by POSIX `S_ISLNK`, returns `file_status(file_type::symlink, prms)`. The signature with argument `ec` returns `file_status(file_type::none)` if an error occurs.

4 *Remarks:* Pathname resolution terminates if `p` names a symbolic link.

5 *Throws:* As specified in 30.10.7.

### 30.10.15.38 Temporary directory path [fs.op.temp\_dir\_path]

```
path temp_directory_path();
path temp_directory_path(error_code& ec);
```

1 *Returns:* An unspecified directory path suitable for temporary files. An error shall be reported if `!exists(p) || !is_directory(p)`, where `p` is the path to be returned. The signature with argument `ec` returns `path()` if an error occurs.

2 *Throws:* As specified in 30.10.7.

3 [*Example:* For POSIX-based operating systems, an implementation might return the path supplied by the first environment variable found in the list `TMPDIR`, `TMP`, `TEMP`, `TEMPDIR`, or if none of these are found, `"/tmp"`.

For Windows-based operating systems, an implementation might return the path reported by the Windows `GetTempPath` API function. — *end example*]

### 30.10.15.39 Weakly canonical [fs.op.weakly\_canonical]

```
path weakly_canonical(const path& p);
path weakly_canonical(const path& p, error_code& ec);
```

1 *Returns:* `p` with symlinks resolved and the result normalized (30.10.4.11).

2 *Effects:* Using `status(p)` or `status(p, ec)`, respectively, to determine existence, return a path composed by `operator/=` from the result of calling `canonical()` without a `base` argument and with a path argument composed of the leading elements of `p` that exist, if any, followed by the elements of `p` that do not exist, if any. For the first form, `canonical()` is called without an `error_code` argument. For the second form, `canonical()` is called with `ec` as an `error_code` argument, and `path()` is returned at the first error occurrence, if any.

3 *Postconditions:* The returned path is in normal form (30.10.4.11).

- 4 *Remarks:* Implementations are encouraged to avoid unnecessary normalization such as when `canonical` has already been called on the entirety of `p`.
- 5 *Throws:* As specified in 30.10.7.

## 30.11 C library files

[c.files]

### 30.11.1 Header `<stdio>` synopsis

[stdio.syn]

```

namespace std {
 using size_t = see 21.2.4;
 using FILE = see below;
 using fpos_t = see below;
}

#define NULL see 21.2.3
#define _IOFBF see below
#define _IOLBF see below
#define _IONBF see below
#define BUFSIZ see below
#define EOF see below
#define FOPEN_MAX see below
#define FILENAME_MAX see below
#define L_tmpnam see below
#define SEEK_CUR see below
#define SEEK_END see below
#define SEEK_SET see below
#define TMP_MAX see below
#define stderr see below
#define stdin see below
#define stdout see below

namespace std {
 int remove(const char* filename);
 int rename(const char* old, const char* new);
 FILE* tmpfile();
 char* tmpnam(char* s);
 int fclose(FILE* stream);
 int fflush(FILE* stream);
 FILE* fopen(const char* filename, const char* mode);
 FILE* freopen(const char* filename, const char* mode, FILE* stream);
 void setbuf(FILE* stream, char* buf);
 int setvbuf(FILE* stream, char* buf, int mode, size_t size);
 int fprintf(FILE* stream, const char* format, ...);
 int fscanf(FILE* stream, const char* format, ...);
 int printf(const char* format, ...);
 int scanf(const char* format, ...);
 int snprintf(char* s, size_t n, const char* format, ...);
 int sprintf(char* s, const char* format, ...);
 int sscanf(const char* s, const char* format, ...);
 int vfprintf(FILE* stream, const char* format, va_list arg);
 int vfscanf(FILE* stream, const char* format, va_list arg);
 int vprintf(const char* format, va_list arg);
 int vscanf(const char* format, va_list arg);
 int vsnprintf(char* s, size_t n, const char* format, va_list arg);
 int vsprintf(char* s, const char* format, va_list arg);
 int vsscanf(const char* s, const char* format, va_list arg);

```

```

int fgetc(FILE* stream);
char* fgets(char* s, int n, FILE* stream);
int fputc(int c, FILE* stream);
int fputs(const char* s, FILE* stream);
int getc(FILE* stream);
int getchar();
int putc(int c, FILE* stream);
int putchar(int c);
int puts(const char* s);
int ungetc(int c, FILE* stream);
size_t fread(void* ptr, size_t size, size_t nmemb, FILE* stream);
size_t fwrite(const void* ptr, size_t size, size_t nmemb, FILE* stream);
int fgetpos(FILE* stream, fpos_t* pos);
int fseek(FILE* stream, long int offset, int whence);
int fsetpos(FILE* stream, const fpos_t* pos);
long int ftell(FILE* stream);
void rewind(FILE* stream);
void clearerr(FILE* stream);
int feof(FILE* stream);
int ferror(FILE* stream);
void perror(const char* s);
}

```

- <sup>1</sup> The contents and meaning of the header `<cstdio>` are the same as the C standard library header `<stdio.h>`.
- <sup>2</sup> Calls to the function `tmpnam` with an argument that is a null pointer value may introduce a data race ([20.5.5.9](#)) with other calls to `tmpnam` with an argument that is a null pointer value.

SEE ALSO: ISO C 7.21.

### 30.11.2 Header `<cinttypes>` synopsis

[`cinttypes.syn`]

```

#include <cstdint> // see 21.4.1

namespace std {
 using imaxdiv_t = see below;

 intmax_t imaxabs(intmax_t j);
 imaxdiv_t imaxdiv(intmax_t numer, intmax_t denom);
 intmax_t strtoumax(const char* nptr, char** endptr, int base);
 uintmax_t strtoumax(const char* nptr, char** endptr, int base);
 intmax_t wcstoumax(const wchar_t* nptr, wchar_t** endptr, int base);
 uintmax_t wcstoumax(const wchar_t* nptr, wchar_t** endptr, int base);

 intmax_t abs(intmax_t); // optional, see below
 imaxdiv_t div(intmax_t, intmax_t); // optional, see below
}

#define PRIdN see below
#define PRIiN see below
#define PRIdN see below
#define PRIuN see below
#define PRIxN see below
#define PRIxN see below
#define SCNdN see below
#define SCNiN see below
#define SCNoN see below
#define SCNuN see below

```

```

#define SCNxN see below
#define PRIdLEASTN see below
#define PRIiLEASTN see below
#define PRIoLEASTN see below
#define PRIuLEASTN see below
#define PRIxLEASTN see below
#define PRIXLEASTN see below
#define SCNdLEASTN see below
#define SCNiLEASTN see below
#define SCNoLEASTN see below
#define SCNuLEASTN see below
#define SCNxLEASTN see below
#define PRIdFASTN see below
#define PRIiFASTN see below
#define PRIoFASTN see below
#define PRIuFASTN see below
#define PRIxFASTN see below
#define PRIXFASTN see below
#define SCNdFASTN see below
#define SCNiFASTN see below
#define SCNoFASTN see below
#define SCNuFASTN see below
#define SCNxFASTN see below
#define PRIdMAX see below
#define PRIiMAX see below
#define PRIoMAX see below
#define PRIuMAX see below
#define PRIxMAX see below
#define PRIXMAX see below
#define SCNdMAX see below
#define SCNiMAX see below
#define SCNoMAX see below
#define SCNuMAX see below
#define SCNxMAX see below
#define PRIdPTR see below
#define PRIiPTR see below
#define PRIoPTR see below
#define PRIuPTR see below
#define PRIxPTR see below
#define PRIXPTR see below
#define SCNdPTR see below
#define SCNiPTR see below
#define SCNoPTR see below
#define SCNuPTR see below
#define SCNxPTR see below

```

<sup>1</sup> The contents and meaning of the header `<inttypes>` are the same as the C standard library header `<inttypes.h>`, with the following changes:

- (1.1) — The header `<inttypes>` includes the header `<cstdint>` instead of `<stdint.h>`, and
- (1.2) — if and only if the type `intmax_t` designates an extended integer type (6.9.1), the following function signatures are added:

```

intmax_t abs(intmax_t);
imaxdiv_t div(intmax_t, intmax_t);

```

which shall have the same semantics as the function signatures `intmax_t imaxabs(intmax_t)` and

`imaxdiv_t imaxdiv(intmax_t, intmax_t)`, respectively.

SEE ALSO: ISO C 7.8.

# 31 Regular expressions library [re]

## 31.1 General [re.general]

- <sup>1</sup> This Clause describes components that C++ programs may use to perform operations involving regular expression matching and searching.
- <sup>2</sup> The following subclauses describe a basic regular expression class template and its traits that can handle char-like (24.1) template arguments, two specializations of this class template that handle sequences of `char` and `wchar_t`, a class template that holds the result of a regular expression match, a series of algorithms that allow a character sequence to be operated upon by a regular expression, and two iterator types for enumerating regular expression matches, as described in Table 128.

Table 128 — Regular expressions library summary

| Subclause                                        | Header(s)                  |
|--------------------------------------------------|----------------------------|
| <a href="#">31.2</a> Definitions                 |                            |
| <a href="#">31.3</a> Requirements                |                            |
| <a href="#">31.5</a> Constants                   |                            |
| <a href="#">31.6</a> Exception type              |                            |
| <a href="#">31.7</a> Traits                      |                            |
| <a href="#">31.8</a> Regular expression template | <code>&lt;regex&gt;</code> |
| <a href="#">31.9</a> Submatches                  |                            |
| <a href="#">31.10</a> Match results              |                            |
| <a href="#">31.11</a> Algorithms                 |                            |
| <a href="#">31.12</a> Iterators                  |                            |
| <a href="#">31.13</a> Grammar                    |                            |

## 31.2 Definitions [re.def]

- <sup>1</sup> The following definitions shall apply to this Clause:

### 31.2.0.1 [defns.regex.collating.element]

#### collating element

a sequence of one or more characters within the current locale that collate as if they were a single character.

### 31.2.0.2 [defns.regex.finite.state.machine]

#### finite state machine

an unspecified data structure that is used to represent a regular expression, and which permits efficient matches against the regular expression to be obtained.

### 31.2.0.3 [defns.regex.format.specifier]

#### format specifier

a sequence of one or more characters that is to be replaced with some part of a regular expression match.

### 31.2.0.4 [defns.regex.matched]

#### matched

a sequence of zero or more characters is matched by a regular expression when the characters in the sequence correspond to a sequence of characters defined by the pattern.



**31.2.0.5**

[defns.regex.primary.equivalence.class]

**primary equivalence class**

a set of one or more characters which share the same primary sort key: that is the sort key weighting that depends only upon character shape, and not accents, case, or locale specific tailorings.

**31.2.0.6**

[defns.regex.regular.expression]

**regular expression**

a pattern that selects specific strings from a set of character strings.

**31.2.0.7**

[defns.regex.subexpression]

**sub-expression**

a subset of a regular expression that has been marked by parenthesis.

**31.3 Requirements**

[re.req]

- <sup>1</sup> This subclause defines requirements on classes representing regular expression traits. [ *Note*: The class template `regex_traits`, defined in Clause 31.7, satisfies these requirements. — *end note* ]
- <sup>2</sup> The class template `basic_regex`, defined in Clause 31.8, needs a set of related types and functions to complete the definition of its semantics. These types and functions are provided as a set of member *typedef-names* and functions in the template parameter `traits` used by the `basic_regex` class template. This subclause defines the semantics of these members.
- <sup>3</sup> To specialize class template `basic_regex` for a character container `CharT` and its related regular expression traits class `Traits`, use `basic_regex<CharT, Traits>`.
- <sup>4</sup> In Table 129 `X` denotes a traits class defining types and functions for the character container type `charT`; `u` is an object of type `X`; `v` is an object of type `const X`; `p` is a value of type `const charT*`; `I1` and `I2` are input iterators (27.2.3); `F1` and `F2` are forward iterators (27.2.5); `c` is a value of type `const charT`; `s` is an object of type `X::string_type`; `cs` is an object of type `const X::string_type`; `b` is a value of type `bool`; `I` is a value of type `int`; `cl` is an object of type `X::char_class_type`, and `loc` is an object of type `X::locale_type`.

Table 129 — Regular expression traits class requirements

| Expression                      | Return type                            | Assertion/note pre-/post-condition                                                                                                                                        |
|---------------------------------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>X::char_type</code>       | <code>charT</code>                     | The character container type used in the implementation of class template <code>basic_regex</code> .                                                                      |
| <code>X::string_type</code>     | <code>basic_string&lt;charT&gt;</code> |                                                                                                                                                                           |
| <code>X::locale_type</code>     | A copy constructible type              | A type that represents the locale used by the traits class.                                                                                                               |
| <code>X::char_class_type</code> | A bitmask type (20.4.2.1.4).           | A bitmask type representing a particular character classification.                                                                                                        |
| <code>X::length(p)</code>       | <code>size_t</code>                    | Yields the smallest <code>i</code> such that <code>p[i] == 0</code> . Complexity is linear in <code>i</code> .                                                            |
| <code>v.translate(c)</code>     | <code>X::char_type</code>              | Returns a character such that for any character <code>d</code> that is to be considered equivalent to <code>c</code> then <code>v.translate(c) == v.translate(d)</code> . |

Table 129 — Regular expression traits class requirements (continued)

| Expression                                 | Return type                     | Assertion/note pre-/post-condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------------------|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>v.translate_nocase(c)</code>         | <code>X::char_type</code>       | For all characters <code>C</code> that are to be considered equivalent to <code>c</code> when comparisons are to be performed without regard to case, then <code>v.translate_nocase(c) == v.translate_nocase(C)</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>v.transform(F1, F2)</code>           | <code>X::string_type</code>     | Returns a sort key for the character sequence designated by the iterator range <code>[F1, F2)</code> such that if the character sequence <code>[G1, G2)</code> sorts before the character sequence <code>[H1, H2)</code> then <code>v.transform(G1, G2) &lt; v.transform(H1, H2)</code> .                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>v.transform_primary(F1, F2)</code>   | <code>X::string_type</code>     | Returns a sort key for the character sequence designated by the iterator range <code>[F1, F2)</code> such that if the character sequence <code>[G1, G2)</code> sorts before the character sequence <code>[H1, H2)</code> when character case is not considered then <code>v.transform_primary(G1, G2) &lt; v.transform_primary(H1, H2)</code> .                                                                                                                                                                                                                                                                                                                                              |
| <code>v.lookup_collatename(F1, F2)</code>  | <code>X::string_type</code>     | Returns a sequence of characters that represents the collating element consisting of the character sequence designated by the iterator range <code>[F1, F2)</code> . Returns an empty string if the character sequence is not a valid collating element.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>v.lookup_classname(F1, F2, b)</code> | <code>X::char_class_type</code> | Converts the character sequence designated by the iterator range <code>[F1, F2)</code> into a value of a bitmask type that can subsequently be passed to <code>isctype</code> . Values returned from <code>lookup_classname</code> can be bitwise or'ed together; the resulting value represents membership in either of the corresponding character classes. If <code>b</code> is <code>true</code> , the returned bitmask is suitable for matching characters without regard to their case. Returns 0 if the character sequence is not the name of a character class recognized by <code>X</code> . The value returned shall be independent of the case of the characters in the sequence. |
| <code>v.isctype(c, cl)</code>              | <code>bool</code>               | Returns <code>true</code> if character <code>c</code> is a member of one of the character classes designated by <code>cl</code> , <code>false</code> otherwise.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>v.value(c, I)</code>                 | <code>int</code>                | Returns the value represented by the digit <code>c</code> in base <code>I</code> if the character <code>c</code> is a valid digit in base <code>I</code> ; otherwise returns <code>-1</code> . [Note: The value of <code>I</code> will only be 8, 10, or 16. — end note]                                                                                                                                                                                                                                                                                                                                                                                                                     |

Table 129 — Regular expression traits class requirements (continued)

| Expression                | Return type                 | Assertion/note pre-/post-condition                                                                                    |
|---------------------------|-----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <code>u.imbue(loc)</code> | <code>X::locale_type</code> | Imbues <code>u</code> with the locale <code>loc</code> and returns the previous locale used by <code>u</code> if any. |
| <code>v.getloc()</code>   | <code>X::locale_type</code> | Returns the current locale used by <code>v</code> , if any.                                                           |

<sup>5</sup> [ *Note:* Class template `regex_traits` satisfies the requirements for a regular expression traits class when it is specialized for `char` or `wchar_t`. This class template is described in the header `<regex>`, and is described in Clause 31.7. — *end note* ]

### 31.4 Header `<regex>` synopsis

[re.syn]

```
#include <initializer_list>

namespace std {
 // 31.5, regex constants
 namespace regex_constants {
 using syntax_option_type = T1;
 using match_flag_type = T2;
 using error_type = T3;
 }

 // 31.6, class regex_error
 class regex_error;

 // 31.7, class template regex_traits
 template <class charT> struct regex_traits;

 // 31.8, class template basic_regex
 template <class charT, class traits = regex_traits<charT>> class basic_regex;

 using regex = basic_regex<char>;
 using wregex = basic_regex<wchar_t>;

 // 31.8.6, basic_regex swap
 template <class charT, class traits>
 void swap(basic_regex<charT, traits>& e1, basic_regex<charT, traits>& e2);

 // 31.9, class template sub_match
 template <class BidirectionalIterator>
 class sub_match;

 using csub_match = sub_match<const char*>;
 using wsub_match = sub_match<const wchar_t*>;
 using ssub_match = sub_match<string::const_iterator>;
 using wssub_match = sub_match<wstring::const_iterator>;

 // 31.9.2, sub_match non-member operators
 template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
 template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
```

```

template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator>(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);

template <class BiIter, class ST, class SA>
 bool operator==(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter, class ST, class SA>
 bool operator!=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter, class ST, class SA>
 bool operator<(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter, class ST, class SA>
 bool operator>(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter, class ST, class SA>
 bool operator>=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter, class ST, class SA>
 bool operator<=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);

template <class BiIter, class ST, class SA>
 bool operator==(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
template <class BiIter, class ST, class SA>
 bool operator!=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
template <class BiIter, class ST, class SA>
 bool operator<(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
template <class BiIter, class ST, class SA>
 bool operator>(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
template <class BiIter, class ST, class SA>
 bool operator>=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
template <class BiIter, class ST, class SA>

```

```

 bool operator<=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);

template <class BiIter>
 bool operator==(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator!=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator<(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator>(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator>=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator<=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);

template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
template <class BiIter>
 bool operator>(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);

template <class BiIter>
 bool operator==(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator!=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator<(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator>(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>

```

```

 bool operator>=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
template <class BiIter>
 bool operator<=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);

template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
template <class BiIter>
 bool operator>(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);

template <class charT, class ST, class BiIter>
 basic_ostream<charT, ST>&
 operator<<(basic_ostream<charT, ST>& os, const sub_match<BiIter>& m);

// 31.10, class template match_results
template <class BidirectionalIterator,
 class Allocator = allocator<sub_match<BidirectionalIterator>>>
 class match_results;

using cmatch = match_results<const char*>;
using wcmatch = match_results<const wchar_t*>;
using smatch = match_results<string::const_iterator>;
using wsmatch = match_results<wstring::const_iterator>;

// match_results comparisons
template <class BidirectionalIterator, class Allocator>
 bool operator==(const match_results<BidirectionalIterator, Allocator>& m1,
 const match_results<BidirectionalIterator, Allocator>& m2);
template <class BidirectionalIterator, class Allocator>
 bool operator!=(const match_results<BidirectionalIterator, Allocator>& m1,
 const match_results<BidirectionalIterator, Allocator>& m2);

// 31.10.7, match_results swap
template <class BidirectionalIterator, class Allocator>
 void swap(match_results<BidirectionalIterator, Allocator>& m1,
 match_results<BidirectionalIterator, Allocator>& m2);

// 31.11.2, function template regex_match
template <class BidirectionalIterator, class Allocator, class charT, class traits>
 bool regex_match(BidirectionalIterator first, BidirectionalIterator last,

```

```

 match_results<BidirectionalIterator, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class BidirectionalIterator, class charT, class traits>
 bool regex_match(BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class charT, class Allocator, class traits>
 bool regex_match(const charT* str, match_results<const charT*, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class ST, class SA, class Allocator, class charT, class traits>
 bool regex_match(const basic_string<charT, ST, SA>& s,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class ST, class SA, class Allocator, class charT, class traits>
 bool regex_match(const basic_string<charT, ST, SA>&&,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>&,
 const basic_regex<charT, traits>&,
 regex_constants::match_flag_type = regex_constants::match_default) = delete;
template <class charT, class traits>
 bool regex_match(const charT* str,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class ST, class SA, class charT, class traits>
 bool regex_match(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);

// 31.11.3, function template regex_search
template <class BidirectionalIterator, class Allocator, class charT, class traits>
 bool regex_search(BidirectionalIterator first, BidirectionalIterator last,
 match_results<BidirectionalIterator, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class BidirectionalIterator, class charT, class traits>
 bool regex_search(BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class charT, class Allocator, class traits>
 bool regex_search(const charT* str,
 match_results<const charT*, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class charT, class traits>
 bool regex_search(const charT* str,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class ST, class SA, class charT, class traits>
 bool regex_search(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);

```

```

template <class ST, class SA, class Allocator, class charT, class traits>
 bool regex_search(const basic_string<charT, ST, SA>& s,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class ST, class SA, class Allocator, class charT, class traits>
 bool regex_search(const basic_string<charT, ST, SA>&&,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>&,
 const basic_regex<charT, traits>&,
 regex_constants::match_flag_type
 = regex_constants::match_default) = delete;

// 31.11.4, function template regex_replace
template <class OutputIterator, class BidirectionalIterator,
 class traits, class charT, class ST, class SA>
 OutputIterator
 regex_replace(OutputIterator out,
 BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class OutputIterator, class BidirectionalIterator, class traits, class charT>
 OutputIterator
 regex_replace(OutputIterator out,
 BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class traits, class charT, class ST, class SA, class FST, class FSA>
 basic_string<charT, ST, SA>
 regex_replace(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, FST, FSA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class traits, class charT, class ST, class SA>
 basic_string<charT, ST, SA>
 regex_replace(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class traits, class charT, class ST, class SA>
 basic_string<charT>
 regex_replace(const charT* s,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class traits, class charT>
 basic_string<charT>
 regex_replace(const charT* s,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);

```



```

// 31.12.1, class template regex_iterator
template <class BidirectionalIterator,
 class charT = typename iterator_traits<BidirectionalIterator>::value_type,
 class traits = regex_traits<charT>>
 class regex_iterator;

using cregex_iterator = regex_iterator<const char*>;
using wcregex_iterator = regex_iterator<const wchar_t*>;
using sregex_iterator = regex_iterator<string::const_iterator>;
using wsregex_iterator = regex_iterator<wstring::const_iterator>;

// 31.12.2, class template regex_token_iterator
template <class BidirectionalIterator,
 class charT = typename iterator_traits<BidirectionalIterator>::value_type,
 class traits = regex_traits<charT>>
 class regex_token_iterator;

using cregex_token_iterator = regex_token_iterator<const char*>;
using wcregex_token_iterator = regex_token_iterator<const wchar_t*>;
using sregex_token_iterator = regex_token_iterator<string::const_iterator>;
using wsregex_token_iterator = regex_token_iterator<wstring::const_iterator>;

namespace pmr {
 template <class BidirectionalIterator>
 using match_results =
 std::match_results<BidirectionalIterator,
 polymorphic_allocator<sub_match<BidirectionalIterator>>>;

 using cmatch = match_results<const char*>;
 using wcmatch = match_results<const wchar_t*>;
 using smatch = match_results<string::const_iterator>;
 using wsmatch = match_results<wstring::const_iterator>;
}
}

```

### 31.5 Namespace `std::regex_constants` [re.const]

- <sup>1</sup> The namespace `std::regex_constants` holds symbolic constants used by the regular expression library. This namespace provides three types, `syntax_option_type`, `match_flag_type`, and `error_type`, along with several constants of these types.

#### 31.5.1 Bitmask type `syntax_option_type` [re.synopt]

```

namespace std::regex_constants {
 using syntax_option_type = T1;
 inline constexpr syntax_option_type icafe = unspecified;
 inline constexpr syntax_option_type nosubs = unspecified;
 inline constexpr syntax_option_type optimize = unspecified;
 inline constexpr syntax_option_type collate = unspecified;
 inline constexpr syntax_option_type ECMAScript = unspecified;
 inline constexpr syntax_option_type basic = unspecified;
 inline constexpr syntax_option_type extended = unspecified;
 inline constexpr syntax_option_type awk = unspecified;
 inline constexpr syntax_option_type grep = unspecified;
 inline constexpr syntax_option_type egrep = unspecified;
 inline constexpr syntax_option_type multiline = unspecified;
}

```

- <sup>1</sup> The type `syntax_option_type` is an implementation-defined bitmask type (20.4.2.1.4). Setting its elements has the effects listed in Table 130. A valid value of type `syntax_option_type` shall have at most one of the grammar elements `ECMAScript`, `basic`, `extended`, `awk`, `grep`, `egrep`, `set`. If no grammar element is set, the default grammar is `ECMAScript`.

Table 130 — `syntax_option_type` effects

| Element                 | Effect(s) if set                                                                                                                                                                                                                                                          |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>icase</code>      | Specifies that matching of regular expressions against a character container sequence shall be performed without regard to case.                                                                                                                                          |
| <code>nosubs</code>     | Specifies that no sub-expressions shall be considered to be marked, so that when a regular expression is matched against a character container sequence, no sub-expression matches shall be stored in the supplied <code>match_results</code> structure.                  |
| <code>optimize</code>   | Specifies that the regular expression engine should pay more attention to the speed with which regular expressions are matched, and less to the speed with which regular expression objects are constructed. Otherwise it has no detectable effect on the program output. |
| <code>collate</code>    | Specifies that character ranges of the form "[a-b]" shall be locale sensitive.                                                                                                                                                                                            |
| <code>ECMAScript</code> | Specifies that the grammar recognized by the regular expression engine shall be that used by ECMAScript in ECMA-262, as modified in 31.13.                                                                                                                                |
| <code>basic</code>      | Specifies that the grammar recognized by the regular expression engine shall be that used by basic regular expressions in POSIX, Base Definitions and Headers, Section 9, Regular Expressions.                                                                            |
| <code>extended</code>   | Specifies that the grammar recognized by the regular expression engine shall be that used by extended regular expressions in POSIX, Base Definitions and Headers, Section 9, Regular Expressions.                                                                         |
| <code>awk</code>        | Specifies that the grammar recognized by the regular expression engine shall be that used by the utility <code>awk</code> in POSIX.                                                                                                                                       |
| <code>grep</code>       | Specifies that the grammar recognized by the regular expression engine shall be that used by the utility <code>grep</code> in POSIX.                                                                                                                                      |
| <code>egrep</code>      | Specifies that the grammar recognized by the regular expression engine shall be that used by the utility <code>grep</code> when given the <code>-E</code> option in POSIX.                                                                                                |
| <code>multiline</code>  | Specifies that <code>^</code> shall match the beginning of a line and <code>\$</code> shall match the end of a line, if the <code>ECMAScript</code> engine is selected.                                                                                                   |

### 31.5.2 Bitmask type `match_flag_type`

[`re.matchflag`]

```
namespace std::regex_constants {
 using match_flag_type = T2;
 inline constexpr match_flag_type match_default = {};
 inline constexpr match_flag_type match_not_bol = unspecified;
 inline constexpr match_flag_type match_not_eol = unspecified;
 inline constexpr match_flag_type match_not_bow = unspecified;
 inline constexpr match_flag_type match_not_eow = unspecified;
 inline constexpr match_flag_type match_any = unspecified;
 inline constexpr match_flag_type match_not_null = unspecified;
 inline constexpr match_flag_type match_continuous = unspecified;
 inline constexpr match_flag_type match_prev_avail = unspecified;
 inline constexpr match_flag_type format_default = {};
```

```

inline constexpr match_flag_type format_sed = unspecified;
inline constexpr match_flag_type format_no_copy = unspecified;
inline constexpr match_flag_type format_first_only = unspecified;
}

```

- <sup>1</sup> The type `match_flag_type` is an implementation-defined bitmask type (20.4.2.1.4). The constants of that type, except for `match_default` and `format_default`, are bitmask elements. The `match_default` and `format_default` constants are empty bitmasks. Matching a regular expression against a sequence of characters `[first, last)` proceeds according to the rules of the grammar specified for the regular expression object, modified according to the effects listed in Table 131 for any bitmask elements set.

Table 131 — `regex_constants::match_flag_type` effects when obtaining a match against a character container sequence `[first, last)`.

| Element                        | Effect(s) if set                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>match_not_bol</code>     | The first character in the sequence <code>[first, last)</code> shall be treated as though it is not at the beginning of a line, so the character <code>^</code> in the regular expression shall not match <code>[first, first)</code> .                                                                                                                                                                                                                                                   |
| <code>match_not_eol</code>     | The last character in the sequence <code>[first, last)</code> shall be treated as though it is not at the end of a line, so the character <code>"\$"</code> in the regular expression shall not match <code>[last, last)</code> .                                                                                                                                                                                                                                                         |
| <code>match_not_bow</code>     | The expression <code>"\\b"</code> shall not match the sub-sequence <code>[first, first)</code> .                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>match_not_eow</code>     | The expression <code>"\\b"</code> shall not match the sub-sequence <code>[last, last)</code> .                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>match_any</code>         | If more than one match is possible then any match is an acceptable result.                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>match_not_null</code>    | The expression shall not match an empty sequence.                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>match_continuous</code>  | The expression shall only match a sub-sequence that begins at <code>first</code> .                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>match_prev_avail</code>  | <code>--first</code> is a valid iterator position. When this flag is set the flags <code>match_not_bol</code> and <code>match_not_bow</code> shall be ignored by the regular expression algorithms (31.11) and iterators (31.12).                                                                                                                                                                                                                                                         |
| <code>format_default</code>    | When a regular expression match is to be replaced by a new string, the new string shall be constructed using the rules used by the ECMAScript replace function in ECMA-262, part 15.5.4.11 <code>String.prototype.replace</code> . In addition, during search and replace operations all non-overlapping occurrences of the regular expression shall be located and replaced, and sections of the input that did not match the expression shall be copied unchanged to the output string. |
| <code>format_sed</code>        | When a regular expression match is to be replaced by a new string, the new string shall be constructed using the rules used by the <code>sed</code> utility in POSIX.                                                                                                                                                                                                                                                                                                                     |
| <code>format_no_copy</code>    | During a search and replace operation, sections of the character container sequence being searched that do not match the regular expression shall not be copied to the output string.                                                                                                                                                                                                                                                                                                     |
| <code>format_first_only</code> | When specified during a search and replace operation, only the first occurrence of the regular expression shall be replaced.                                                                                                                                                                                                                                                                                                                                                              |

### 31.5.3 Implementation-defined error\_type

[re.err]

```

namespace std::regex_constants {
 using error_type = T3;
 inline constexpr error_type error_collate = unspecified;
 inline constexpr error_type error_ctype = unspecified;
 inline constexpr error_type error_escape = unspecified;
}

```

```

inline constexpr error_type error_backref = unspecified;
inline constexpr error_type error_brack = unspecified;
inline constexpr error_type error_paren = unspecified;
inline constexpr error_type error_brace = unspecified;
inline constexpr error_type error_badbrace = unspecified;
inline constexpr error_type error_range = unspecified;
inline constexpr error_type error_space = unspecified;
inline constexpr error_type error_badrepeat = unspecified;
inline constexpr error_type error_complexity = unspecified;
inline constexpr error_type error_stack = unspecified;
}

```

- <sup>1</sup> The type `error_type` is an implementation-defined enumerated type (20.4.2.1.3). Values of type `error_type` represent the error conditions described in Table 132:

Table 132 — `error_type` values in the C locale

| Value                         | Error condition                                                                                                         |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <code>error_collate</code>    | The expression contained an invalid collating element name.                                                             |
| <code>error_ctype</code>      | The expression contained an invalid character class name.                                                               |
| <code>error_escape</code>     | The expression contained an invalid escaped character, or a trailing escape.                                            |
| <code>error_backref</code>    | The expression contained an invalid back reference.                                                                     |
| <code>error_brack</code>      | The expression contained mismatched [ and ].                                                                            |
| <code>error_paren</code>      | The expression contained mismatched ( and ).                                                                            |
| <code>error_brace</code>      | The expression contained mismatched { and }                                                                             |
| <code>error_badbrace</code>   | The expression contained an invalid range in a {} expression.                                                           |
| <code>error_range</code>      | The expression contained an invalid character range, such as [b-a] in most encodings.                                   |
| <code>error_space</code>      | There was insufficient memory to convert the expression into a finite state machine.                                    |
| <code>error_badrepeat</code>  | One of *?+{ was not preceded by a valid regular expression.                                                             |
| <code>error_complexity</code> | The complexity of an attempted match against a regular expression exceeded a pre-set level.                             |
| <code>error_stack</code>      | There was insufficient memory to determine whether the regular expression could match the specified character sequence. |

### 31.6 Class `regex_error`

[re.badexp]

```

class regex_error : public runtime_error {
public:
 explicit regex_error(regex_constants::error_type ecode);
 regex_constants::error_type code() const;
};

```

- <sup>1</sup> The class `regex_error` defines the type of objects thrown as exceptions to report errors from the regular expression library.

```
regex_error(regex_constants::error_type ecode);
```

- <sup>2</sup> *Effects:* Constructs an object of class `regex_error`.

- <sup>3</sup> *Postconditions:* `ecode == code()`.

```
regex_constants::error_type code() const;
```

- <sup>4</sup> *Returns:* The error code that was passed to the constructor.

31.7 Class template `regex_traits`

[re.traits]

```

namespace std {
 template <class charT>
 struct regex_traits {
 using char_type = charT;
 using string_type = basic_string<char_type>;
 using locale_type = locale;
 using char_class_type = bitmask_type;

 regex_traits();
 static size_t length(const char_type* p);
 charT translate(charT c) const;
 charT translate_nocase(charT c) const;
 template <class ForwardIterator>
 string_type transform(ForwardIterator first, ForwardIterator last) const;
 template <class ForwardIterator>
 string_type transform_primary(
 ForwardIterator first, ForwardIterator last) const;
 template <class ForwardIterator>
 string_type lookup_collatename(
 ForwardIterator first, ForwardIterator last) const;
 template <class ForwardIterator>
 char_class_type lookup_classname(
 ForwardIterator first, ForwardIterator last, bool icase = false) const;
 bool isctype(charT c, char_class_type f) const;
 int value(charT ch, int radix) const;
 locale_type imbue(locale_type l);
 locale_type getloc() const;
 };
};

```

- <sup>1</sup> The specializations `regex_traits<char>` and `regex_traits<wchar_t>` shall be valid and shall satisfy the requirements for a regular expression traits class (31.3).

```
using char_class_type = bitmask_type;
```

- <sup>2</sup> The type `char_class_type` is used to represent a character classification and is capable of holding an implementation specific set returned by `lookup_classname`.

```
static size_t length(const char_type* p);
```

- <sup>3</sup> *Returns:* `char_traits<charT>::length(p)`.

```
charT translate(charT c) const;
```

- <sup>4</sup> *Returns:* `c`.

```
charT translate_nocase(charT c) const;
```

- <sup>5</sup> *Returns:* `use_facet<ctype<charT>>(getloc()).tolower(c)`.

```
template <class ForwardIterator>
 string_type transform(ForwardIterator first, ForwardIterator last) const;
```

- <sup>6</sup> *Effects:* As if by:

```

 string_type str(first, last);
 return use_facet<collate<charT>>(
 getloc()).transform(&*str.begin(), &*str.begin() + str.length());

```

```
template <class ForwardIterator>
 string_type transform_primary(ForwardIterator first, ForwardIterator last) const;
```

7     *Effects:* If

```
 typeid(use_facet<collate<charT>>) == typeid(collate_byname<charT>)
```

and the form of the sort key returned by `collate_byname<charT>::transform(first, last)` is known and can be converted into a primary sort key then returns that key, otherwise returns an empty string.

```
template <class ForwardIterator>
 string_type lookup_collatename(ForwardIterator first, ForwardIterator last) const;
```

8     *Returns:* a sequence of one or more characters that represents the collating element consisting of the character sequence designated by the iterator range `[first, last)`. Returns an empty string if the character sequence is not a valid collating element.

```
template <class ForwardIterator>
 char_class_type lookup_classname(
 ForwardIterator first, ForwardIterator last, bool icase = false) const;
```

9     *Returns:* an unspecified value that represents the character classification named by the character sequence designated by the iterator range `[first, last)`. If the parameter `icase` is `true` then the returned mask identifies the character classification without regard to the case of the characters being matched, otherwise it does honor the case of the characters being matched.<sup>329</sup> The value returned shall be independent of the case of the characters in the character sequence. If the name is not recognized then returns `char_class_type()`.

10    *Remarks:* For `regex_traits<char>`, at least the narrow character names in Table 133 shall be recognized. For `regex_traits<wchar_t>`, at least the wide character names in Table 133 shall be recognized.

```
bool isctype(charT c, char_class_type f) const;
```

11    *Effects:* Determines if the character `c` is a member of the character classification represented by `f`.

12    *Returns:* Given the following function declaration:

```
 // for exposition only
```

```
 template<class C>
 ctype_base::mask convert(typename regex_traits<C>::char_class_type f);
```

that returns a value in which each `ctype_base::mask` value corresponding to a value in `f` named in Table 133 is set, then the result is determined as if by:

```
 ctype_base::mask m = convert<charT>(f);
 const ctype<charT>& ct = use_facet<ctype<charT>>(getloc());
 if (ct.is(m, c)) {
 return true;
 } else if (c == ct.widen('_')) {
 charT w[1] = { ct.widen('w') };
 char_class_type x = lookup_classname(w, w+1);
 return (f&x) == x;
 } else {
 return false;
 }
```

[ *Example:*

---

329) For example, if the parameter `icase` is `true` then `[[:lower:]]` is the same as `[[:alpha:]]`.

```

 regex_traits<char> t;
 string d("d");
 string u("upper");
 regex_traits<char>::char_class_type f;
 f = t.lookup_classname(d.begin(), d.end());
 f |= t.lookup_classname(u.begin(), u.end());
 ctype_base::mask m = convert<char>(f); // m == ctype_base::digit|ctype_base::upper

```

— end example] [Example:

```

 regex_traits<char> t;
 string w("w");
 regex_traits<char>::char_class_type f;
 f = t.lookup_classname(w.begin(), w.end());
 t.isctype('A', f); // returns true
 t.isctype('_', f); // returns true
 t.isctype(' ', f); // returns false

```

— end example]

```
int value(charT ch, int radix) const;
```

13 *Requires:* The value of **radix** shall be 8, 10, or 16.

14 *Returns:* the value represented by the digit **ch** in base **radix** if the character **ch** is a valid digit in base **radix**; otherwise returns -1.

```
locale_type imbue(locale_type loc);
```

15 *Effects:* Imbues **this** with a copy of the locale **loc**. [Note: Calling **imbue** with a different locale than the one currently in use invalidates all cached data held by **\*this**. — end note]

16 *Returns:* if no locale has been previously imbued then a copy of the global locale in effect at the time of construction of **\*this**, otherwise a copy of the last argument passed to **imbue**.

17 *Postconditions:* **getloc() == loc**.

```
locale_type getloc() const;
```

18 *Returns:* if no locale has been imbued then a copy of the global locale in effect at the time of construction of **\*this**, otherwise a copy of the last argument passed to **imbue**.

### 31.8 Class template **basic\_regex** [re.regex]

1 For a char-like type **charT**, specializations of class template **basic\_regex** represent regular expressions constructed from character sequences of **charT** characters. In the rest of 31.8, **charT** denotes a given char-like type. Storage for a regular expression is allocated and freed as necessary by the member functions of class **basic\_regex**.

2 Objects of type specialization of **basic\_regex** are responsible for converting the sequence of **charT** objects to an internal representation. It is not specified what form this representation takes, nor how it is accessed by algorithms that operate on regular expressions. [Note: Implementations will typically declare some function templates as friends of **basic\_regex** to achieve this — end note]

3 The functions described in this Clause report errors by throwing exceptions of type **regex\_error**.

```

namespace std {
 template <class charT, class traits = regex_traits<charT>>
 class basic_regex {
 public:
 // types:
 using value_type = charT;

```

Table 133 — Character class names and corresponding ctype masks

| Narrow character name | Wide character name | Corresponding ctype_base::mask value |
|-----------------------|---------------------|--------------------------------------|
| "alnum"               | L"alnum"            | ctype_base::alnum                    |
| "alpha"               | L"alpha"            | ctype_base::alpha                    |
| "blank"               | L"blank"            | ctype_base::blank                    |
| "cntrl"               | L"cntrl"            | ctype_base::cntrl                    |
| "digit"               | L"digit"            | ctype_base::digit                    |
| "d"                   | L"d"                | ctype_base::digit                    |
| "graph"               | L"graph"            | ctype_base::graph                    |
| "lower"               | L"lower"            | ctype_base::lower                    |
| "print"               | L"print"            | ctype_base::print                    |
| "punct"               | L"punct"            | ctype_base::punct                    |
| "space"               | L"space"            | ctype_base::space                    |
| "s"                   | L"s"                | ctype_base::space                    |
| "upper"               | L"upper"            | ctype_base::upper                    |
| "w"                   | L"w"                | ctype_base::alnum                    |
| "xdigit"              | L"xdigit"           | ctype_base::xdigit                   |

```

using traits_type = traits;
using string_type = typename traits::string_type;
using flag_type = regex_constants::syntax_option_type;
using locale_type = typename traits::locale_type;

// 31.8.1, constants
static constexpr regex_constants::syntax_option_type
 icalse = regex_constants::icalse;
static constexpr regex_constants::syntax_option_type
 nosubs = regex_constants::nosubs;
static constexpr regex_constants::syntax_option_type
 optimize = regex_constants::optimize;
static constexpr regex_constants::syntax_option_type
 collate = regex_constants::collate;
static constexpr regex_constants::syntax_option_type
 ECMAScript = regex_constants::ECMAScript;
static constexpr regex_constants::syntax_option_type
 basic = regex_constants::basic;
static constexpr regex_constants::syntax_option_type
 extended = regex_constants::extended;
static constexpr regex_constants::syntax_option_type
 awk = regex_constants::awk;
static constexpr regex_constants::syntax_option_type
 grep = regex_constants::grep;
static constexpr regex_constants::syntax_option_type
 egrep = regex_constants::egrep;
static constexpr regex_constants::syntax_option_type
 multiline = regex_constants::multiline;

// 31.8.2, construct/copy/destroy
basic_regex();
explicit basic_regex(const charT* p, flag_type f = regex_constants::ECMAScript);

```



```

basic_regex(const charT* p, size_t len, flag_type f = regex_constants::ECMAScript);
basic_regex(const basic_regex&);
basic_regex(basic_regex&&) noexcept;
template <class ST, class SA>
 explicit basic_regex(const basic_string<charT, ST, SA>& p,
 flag_type f = regex_constants::ECMAScript);
template <class ForwardIterator>
 basic_regex(ForwardIterator first, ForwardIterator last,
 flag_type f = regex_constants::ECMAScript);
basic_regex(initializer_list<charT>, flag_type = regex_constants::ECMAScript);

~basic_regex();

basic_regex& operator=(const basic_regex&);
basic_regex& operator=(basic_regex&&) noexcept;
basic_regex& operator=(const charT* ptr);
basic_regex& operator=(initializer_list<charT> il);
template <class ST, class SA>
 basic_regex& operator=(const basic_string<charT, ST, SA>& p);

// 31.8.3, assign
basic_regex& assign(const basic_regex& that);
basic_regex& assign(basic_regex&& that) noexcept;
basic_regex& assign(const charT* ptr, flag_type f = regex_constants::ECMAScript);
basic_regex& assign(const charT* p, size_t len, flag_type f);
template <class string_traits, class A>
 basic_regex& assign(const basic_string<charT, string_traits, A>& s,
 flag_type f = regex_constants::ECMAScript);
template <class InputIterator>
 basic_regex& assign(InputIterator first, InputIterator last,
 flag_type f = regex_constants::ECMAScript);
basic_regex& assign(initializer_list<charT>,
 flag_type = regex_constants::ECMAScript);

// 31.8.4, const operations
unsigned mark_count() const;
flag_type flags() const;

// 31.8.5, locale
locale_type imbue(locale_type loc);
locale_type getloc() const;

// 31.8.6, swap
void swap(basic_regex&);
};

template<class ForwardIterator>
 basic_regex(ForwardIterator, ForwardIterator,
 regex_constants::syntax_option_type = regex_constants::ECMAScript)
 -> basic_regex<typename iterator_traits<ForwardIterator>::value_type>;
}

```

### 31.8.1 basic\_regex constants

[re.regex.const]

```

static constexpr regex_constants::syntax_option_type icaase = regex_constants::icaase;
static constexpr regex_constants::syntax_option_type nosubs = regex_constants::nosubs;

```

```

static constexpr regex_constants::syntax_option_type optimize = regex_constants::optimize;
static constexpr regex_constants::syntax_option_type collate = regex_constants::collate;
static constexpr regex_constants::syntax_option_type ECMAScript = regex_constants::ECMAScript;
static constexpr regex_constants::syntax_option_type basic = regex_constants::basic;
static constexpr regex_constants::syntax_option_type extended = regex_constants::extended;
static constexpr regex_constants::syntax_option_type awk = regex_constants::awk;
static constexpr regex_constants::syntax_option_type grep = regex_constants::grep;
static constexpr regex_constants::syntax_option_type egrep = regex_constants::egrep;
static constexpr regex_constants::syntax_option_type multiline = regex_constants::multiline;

```

<sup>1</sup> The static constant members are provided as synonyms for the constants declared in namespace `regex_constants`.

### 31.8.2 basic\_regex constructors

[re.regex.construct]

```
basic_regex();
```

<sup>1</sup> *Effects:* Constructs an object of class `basic_regex` that does not match any character sequence.

```
explicit basic_regex(const charT* p, flag_type f = regex_constants::ECMAScript);
```

<sup>2</sup> *Requires:* `p` shall not be a null pointer.

<sup>3</sup> *Throws:* `regex_error` if `p` is not a valid regular expression.

<sup>4</sup> *Effects:* Constructs an object of class `basic_regex`; the object's internal finite state machine is constructed from the regular expression contained in the array of `charT` of length `char_traits<charT>::length(p)` whose first element is designated by `p`, and interpreted according to the flags `f`.

<sup>5</sup> *Postconditions:* `flags()` returns `f`. `mark_count()` returns the number of marked sub-expressions within the expression.

```
basic_regex(const charT* p, size_t len, flag_type f);
```

<sup>6</sup> *Requires:* `p` shall not be a null pointer.

<sup>7</sup> *Throws:* `regex_error` if `p` is not a valid regular expression.

<sup>8</sup> *Effects:* Constructs an object of class `basic_regex`; the object's internal finite state machine is constructed from the regular expression contained in the sequence of characters `[p, p+len)`, and interpreted according the flags specified in `f`.

<sup>9</sup> *Postconditions:* `flags()` returns `f`. `mark_count()` returns the number of marked sub-expressions within the expression.

```
basic_regex(const basic_regex& e);
```

<sup>10</sup> *Effects:* Constructs an object of class `basic_regex` as a copy of the object `e`.

<sup>11</sup> *Postconditions:* `flags()` and `mark_count()` return `e.flags()` and `e.mark_count()`, respectively.

```
basic_regex(basic_regex&& e) noexcept;
```

<sup>12</sup> *Effects:* Move constructs an object of class `basic_regex` from `e`.

<sup>13</sup> *Postconditions:* `flags()` and `mark_count()` return the values that `e.flags()` and `e.mark_count()`, respectively, had before construction. `e` is in a valid state with unspecified value.

```

template <class ST, class SA>
explicit basic_regex(const basic_string<charT, ST, SA>& s,
 flag_type f = regex_constants::ECMAScript);

```

<sup>14</sup> *Throws:* `regex_error` if `s` is not a valid regular expression.

15 *Effects:* Constructs an object of class `basic_regex`; the object's internal finite state machine is constructed from the regular expression contained in the string `s`, and interpreted according to the flags specified in `f`.

16 *Postconditions:* `flags()` returns `f`. `mark_count()` returns the number of marked sub-expressions within the expression.

```
template <class ForwardIterator>
 basic_regex(ForwardIterator first, ForwardIterator last,
 flag_type f = regex_constants::ECMAScript);
```

17 *Throws:* `regex_error` if the sequence `[first, last)` is not a valid regular expression.

18 *Effects:* Constructs an object of class `basic_regex`; the object's internal finite state machine is constructed from the regular expression contained in the sequence of characters `[first, last)`, and interpreted according to the flags specified in `f`.

19 *Postconditions:* `flags()` returns `f`. `mark_count()` returns the number of marked sub-expressions within the expression.

```
basic_regex(initializer_list<charT> il, flag_type f = regex_constants::ECMAScript);
```

20 *Effects:* Same as `basic_regex(il.begin(), il.end(), f)`.

### 31.8.3 `basic_regex` assign

[re.regex.assign]

```
basic_regex& operator=(const basic_regex& e);
```

1 *Effects:* Copies `e` into `*this` and returns `*this`.

2 *Postconditions:* `flags()` and `mark_count()` return `e.flags()` and `e.mark_count()`, respectively.

```
basic_regex& operator=(basic_regex&& e) noexcept;
```

3 *Effects:* Move assigns from `e` into `*this` and returns `*this`.

4 *Postconditions:* `flags()` and `mark_count()` return the values that `e.flags()` and `e.mark_count()`, respectively, had before assignment. `e` is in a valid state with unspecified value.

```
basic_regex& operator=(const charT* ptr);
```

5 *Requires:* `ptr` shall not be a null pointer.

6 *Effects:* Returns `assign(ptr)`.

```
basic_regex& operator=(initializer_list<charT> il);
```

7 *Effects:* Returns `assign(il.begin(), il.end())`.

```
template <class ST, class SA>
 basic_regex& operator=(const basic_string<charT, ST, SA>& p);
```

8 *Effects:* Returns `assign(p)`.

```
basic_regex& assign(const basic_regex& that);
```

9 *Effects:* Equivalent to `*this = that`.

10 *Returns:* `*this`.

```
basic_regex& assign(basic_regex&& that) noexcept;
```

11 *Effects:* Equivalent to `*this = std::move(that)`.

12 *Returns:* `*this`.

```
basic_regex& assign(const charT* ptr, flag_type f = regex_constants::ECMAScript);
```

13     *Returns:* assign(string\_type(ptr), f).

```
basic_regex& assign(const charT* ptr, size_t len, flag_type f = regex_constants::ECMAScript);
```

14     *Returns:* assign(string\_type(ptr, len), f).

```
template <class string_traits, class A>
 basic_regex& assign(const basic_string<charT, string_traits, A>& s,
 flag_type f = regex_constants::ECMAScript);
```

15     *Throws:* regex\_error if s is not a valid regular expression.

16     *Returns:* \*this.

17     *Effects:* Assigns the regular expression contained in the string s, interpreted according the flags specified in f. If an exception is thrown, \*this is unchanged.

18     *Postconditions:* If no exception is thrown, flags() returns f and mark\_count() returns the number of marked sub-expressions within the expression.

```
template <class InputIterator>
 basic_regex& assign(InputIterator first, InputIterator last,
 flag_type f = regex_constants::ECMAScript);
```

19     *Requires:* The type InputIterator shall satisfy the requirements for an Input Iterator (27.2.3).

20     *Returns:* assign(string\_type(first, last), f).

```
basic_regex& assign(initializer_list<charT> il,
 flag_type f = regex_constants::ECMAScript);
```

21     *Effects:* Same as assign(il.begin(), il.end(), f).

22     *Returns:* \*this.

### 31.8.4 basic\_regex constant operations

[re.regex.operations]

```
unsigned mark_count() const;
```

1     *Effects:* Returns the number of marked sub-expressions within the regular expression.

```
flag_type flags() const;
```

2     *Effects:* Returns a copy of the regular expression syntax flags that were passed to the object's constructor or to the last call to assign.

### 31.8.5 basic\_regex locale

[re.regex.locale]

```
locale_type imbue(locale_type loc);
```

1     *Effects:* Returns the result of traits\_inst.imbue(loc) where traits\_inst is a (default-initialized) instance of the template type argument traits stored within the object. After a call to imbue the basic\_regex object does not match any character sequence.

```
locale_type getloc() const;
```

2     *Effects:* Returns the result of traits\_inst.getloc() where traits\_inst is a (default-initialized) instance of the template parameter traits stored within the object.

### 31.8.6 basic\_regex swap

[re.regex.swap]

```
void swap(basic_regex& e);
```

- 1 *Effects:* Swaps the contents of the two regular expressions.
- 2 *Postconditions:* `*this` contains the regular expression that was in `e`, `e` contains the regular expression that was in `*this`.
- 3 *Complexity:* Constant time.

### 31.8.7 `basic_regex` non-member functions [re.regex.nonmemb]

#### 31.8.7.1 `basic_regex` non-member swap [re.regex.nmswap]

```
template <class charT, class traits>
 void swap(basic_regex<charT, traits>& lhs, basic_regex<charT, traits>& rhs);
```

- 1 *Effects:* Calls `lhs.swap(rhs)`.

### 31.9 Class template `sub_match` [re.submatch]

- 1 Class template `sub_match` denotes the sequence of characters matched by a particular marked sub-expression.

```
namespace std {
 template <class BidirectionalIterator>
 class sub_match : public pair<BidirectionalIterator, BidirectionalIterator> {
 public:
 using value_type =
 typename iterator_traits<BidirectionalIterator>::value_type;
 using difference_type =
 typename iterator_traits<BidirectionalIterator>::difference_type;
 using iterator = BidirectionalIterator;
 using string_type = basic_string<value_type>;

 bool matched;

 constexpr sub_match();

 difference_type length() const;
 operator string_type() const;
 string_type str() const;

 int compare(const sub_match& s) const;
 int compare(const string_type& s) const;
 int compare(const value_type* s) const;
 };
}
```

#### 31.9.1 `sub_match` members [re.submatch.members]

```
constexpr sub_match();
```

- 1 *Effects:* Value-initializes the `pair` base class subobject and the member `matched`.

```
difference_type length() const;
```

- 2 *Returns:* `matched ? distance(first, second) : 0`.

```
operator string_type() const;
```

- 3 *Returns:* `matched ? string_type(first, second) : string_type()`.

```
string_type str() const;
```

- 4 *Returns:* `matched ? string_type(first, second) : string_type()`.

```

int compare(const sub_match& s) const;
5 Returns: str().compare(s.str()).

int compare(const string_type& s) const;
6 Returns: str().compare(s).

int compare(const value_type* s) const;
7 Returns: str().compare(s).

```

### 31.9.2 sub\_match non-member operators

[re.submatch.op]

```

template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
1 Returns: lhs.compare(rhs) == 0.

template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
2 Returns: lhs.compare(rhs) != 0.

template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
3 Returns: lhs.compare(rhs) < 0.

template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
4 Returns: lhs.compare(rhs) <= 0.

template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
5 Returns: lhs.compare(rhs) >= 0.

template <class BiIter>
 bool operator>(const sub_match<BiIter>& lhs, const sub_match<BiIter>& rhs);
6 Returns: lhs.compare(rhs) > 0.

template <class BiIter, class ST, class SA>
 bool operator==(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
7 Returns:
 rhs.compare(typename sub_match<BiIter>::string_type(lhs.data(), lhs.size())) == 0

template <class BiIter, class ST, class SA>
 bool operator!=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
8 Returns: !(lhs == rhs).

template <class BiIter, class ST, class SA>
 bool operator<(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);

```

```

9 Returns:
 rhs.compare(typename sub_match<BiIter>::string_type(lhs.data(), lhs.size())) > 0

template <class BiIter, class ST, class SA>
 bool operator>(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
10 Returns: rhs < lhs.

template <class BiIter, class ST, class SA>
 bool operator>=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
11 Returns: !(lhs < rhs).

template <class BiIter, class ST, class SA>
 bool operator<=(
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& lhs,
 const sub_match<BiIter>& rhs);
12 Returns: !(rhs < lhs).

template <class BiIter, class ST, class SA>
 bool operator==(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
13 Returns:
 lhs.compare(typename sub_match<BiIter>::string_type(rhs.data(), rhs.size())) == 0

template <class BiIter, class ST, class SA>
 bool operator!=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
14 Returns: !(lhs == rhs).

template <class BiIter, class ST, class SA>
 bool operator<(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
15 Returns:
 lhs.compare(typename sub_match<BiIter>::string_type(rhs.data(), rhs.size())) < 0

template <class BiIter, class ST, class SA>
 bool operator>(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
16 Returns: rhs < lhs.

template <class BiIter, class ST, class SA>
 bool operator>=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
17 Returns: !(lhs < rhs).

```

```

template <class BiIter, class ST, class SA>
 bool operator<=(
 const sub_match<BiIter>& lhs,
 const basic_string<typename iterator_traits<BiIter>::value_type, ST, SA>& rhs);
18 Returns: !(rhs < lhs).

template <class BiIter>
 bool operator==(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
19 Returns: rhs.compare(lhs) == 0.

template <class BiIter>
 bool operator!=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
20 Returns: !(lhs == rhs).

template <class BiIter>
 bool operator<(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
21 Returns: rhs.compare(lhs) > 0.

template <class BiIter>
 bool operator>(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
22 Returns: rhs < lhs.

template <class BiIter>
 bool operator>=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
23 Returns: !(lhs < rhs).

template <class BiIter>
 bool operator<=(const typename iterator_traits<BiIter>::value_type* lhs,
 const sub_match<BiIter>& rhs);
24 Returns: !(rhs < lhs).

template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
25 Returns: lhs.compare(rhs) == 0.

template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
26 Returns: !(lhs == rhs).

template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
27 Returns: lhs.compare(rhs) < 0.

template <class BiIter>

```



```

 bool operator>(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
28 Returns: rhs < lhs.

template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
29 Returns: !(lhs < rhs).

template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type* rhs);
30 Returns: !(rhs < lhs).

template <class BiIter>
 bool operator==(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
31 Returns: rhs.compare(typename sub_match<BiIter>::string_type(1, lhs)) == 0.

template <class BiIter>
 bool operator!=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
32 Returns: !(lhs == rhs).

template <class BiIter>
 bool operator<(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
33 Returns: rhs.compare(typename sub_match<BiIter>::string_type(1, lhs)) > 0.

template <class BiIter>
 bool operator>(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
34 Returns: rhs < lhs.

template <class BiIter>
 bool operator>=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
35 Returns: !(lhs < rhs).

template <class BiIter>
 bool operator<=(const typename iterator_traits<BiIter>::value_type& lhs,
 const sub_match<BiIter>& rhs);
36 Returns: !(rhs < lhs).

template <class BiIter>
 bool operator==(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
37 Returns: lhs.compare(typename sub_match<BiIter>::string_type(1, rhs)) == 0.

template <class BiIter>
 bool operator!=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);

```

```

38 Returns: !(lhs == rhs).

template <class BiIter>
 bool operator<(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
39 Returns: lhs.compare(typename sub_match<BiIter>::string_type(1, rhs)) < 0.

template <class BiIter>
 bool operator>(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
40 Returns: rhs < lhs.

template <class BiIter>
 bool operator>=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
41 Returns: !(lhs < rhs).

template <class BiIter>
 bool operator<=(const sub_match<BiIter>& lhs,
 const typename iterator_traits<BiIter>::value_type& rhs);
42 Returns: !(rhs < lhs).

template <class charT, class ST, class BiIter>
 basic_ostream<charT, ST>&
 operator<<(basic_ostream<charT, ST>& os, const sub_match<BiIter>& m);
43 Returns: os << m.str().

```

### 31.10 Class template `match_results`

[re.results]

- 1 Class template `match_results` denotes a collection of character sequences representing the result of a regular expression match. Storage for the collection is allocated and freed as necessary by the member functions of class template `match_results`.
- 2 The class template `match_results` satisfies the requirements of an allocator-aware container and of a sequence container (26.2.1, 26.2.3) except that only operations defined for const-qualified sequence containers are supported and that the semantics of comparison functions are different from those required for a container.
- 3 A default-constructed `match_results` object has no fully established result state. A match result is *ready* when, as a consequence of a completed regular expression match modifying such an object, its result state becomes fully established. The effects of calling most member functions from a `match_results` object that is not ready are undefined.
- 4 The `sub_match` object stored at index 0 represents sub-expression 0, i.e., the whole match. In this case the `sub_match` member `matched` is always `true`. The `sub_match` object stored at index `n` denotes what matched the marked sub-expression `n` within the matched expression. If the sub-expression `n` participated in a regular expression match then the `sub_match` member `matched` evaluates to `true`, and members `first` and `second` denote the range of characters [`first`, `second`) which formed that match. Otherwise `matched` is `false`, and members `first` and `second` point to the end of the sequence that was searched. [ *Note*: The `sub_match` objects representing different sub-expressions that did not participate in a regular expression match need not be distinct. — *end note* ]

```

namespace std {
 template <class BidirectionalIterator,
 class Allocator = allocator<sub_match<BidirectionalIterator>>>
 class match_results {

```

```

public:
 using value_type = sub_match<BidirectionalIterator>;
 using const_reference = const value_type&;
 using reference = value_type&;
 using const_iterator = implementation-defined;
 using iterator = const_iterator;
 using difference_type =
 typename iterator_traits<BidirectionalIterator>::difference_type;
 using size_type = typename allocator_traits<Allocator>::size_type;
 using allocator_type = Allocator;
 using char_type =
 typename iterator_traits<BidirectionalIterator>::value_type;
 using string_type = basic_string<char_type>;

 // 31.10.1, construct/copy/destroy
 explicit match_results(const Allocator& a = Allocator());
 match_results(const match_results& m);
 match_results(match_results&& m) noexcept;
 match_results& operator=(const match_results& m);
 match_results& operator=(match_results&& m);
 ~match_results();

 // 31.10.2, state
 bool ready() const;

 // 31.10.3, size
 size_type size() const;
 size_type max_size() const;
 bool empty() const;

 // 31.10.4, element access
 difference_type length(size_type sub = 0) const;
 difference_type position(size_type sub = 0) const;
 string_type str(size_type sub = 0) const;
 const_reference operator[](size_type n) const;

 const_reference prefix() const;
 const_reference suffix() const;
 const_iterator begin() const;
 const_iterator end() const;
 const_iterator cbegin() const;
 const_iterator cend() const;

 // 31.10.5, format
 template <class OutputIter>
 OutputIter
 format(OutputIter out,
 const char_type* fmt_first, const char_type* fmt_last,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
 template <class OutputIter, class ST, class SA>
 OutputIter
 format(OutputIter out,
 const basic_string<char_type, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
 template <class ST, class SA>

```

```

 basic_string<char_type, ST, SA>
 format(const basic_string<char_type, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
string_type
 format(const char_type* fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;

 // 31.10.6, allocator
 allocator_type get_allocator() const;

 // 31.10.7, swap
 void swap(match_results& that);
};
}

```

### 31.10.1 match\_results constructors

[re.results.const]

- <sup>1</sup> In all `match_results` constructors, a copy of the `Allocator` argument shall be used for any memory allocation performed by the constructor or member functions during the lifetime of the object.

```
match_results(const Allocator& a = Allocator());
```

- <sup>2</sup> *Effects:* Constructs an object of class `match_results`.

- <sup>3</sup> *Postconditions:* `ready()` returns `false`. `size()` returns 0.

```
match_results(const match_results& m);
```

- <sup>4</sup> *Effects:* Constructs an object of class `match_results`, as a copy of `m`.

```
match_results(match_results&& m) noexcept;
```

- <sup>5</sup> *Effects:* Move constructs an object of class `match_results` from `m` satisfying the same postconditions as Table 134. Additionally, the stored `Allocator` value is move constructed from `m.get_allocator()`.

- <sup>6</sup> *Throws:* Nothing.

```
match_results& operator=(const match_results& m);
```

- <sup>7</sup> *Effects:* Assigns `m` to `*this`. The postconditions of this function are indicated in Table 134.

```
match_results& operator=(match_results&& m);
```

- <sup>8</sup> *Effects:* Move-assigns `m` to `*this`. The postconditions of this function are indicated in Table 134.

Table 134 — `match_results` assignment operator effects

| Element                  | Value                                                                    |
|--------------------------|--------------------------------------------------------------------------|
| <code>ready()</code>     | <code>m.ready()</code>                                                   |
| <code>size()</code>      | <code>m.size()</code>                                                    |
| <code>str(n)</code>      | <code>m.str(n)</code> for all integers <code>n &lt; m.size()</code>      |
| <code>prefix()</code>    | <code>m.prefix()</code>                                                  |
| <code>suffix()</code>    | <code>m.suffix()</code>                                                  |
| <code>(*this)[n]</code>  | <code>m[n]</code> for all integers <code>n &lt; m.size()</code>          |
| <code>length(n)</code>   | <code>m.length(n)</code> for all integers <code>n &lt; m.size()</code>   |
| <code>position(n)</code> | <code>m.position(n)</code> for all integers <code>n &lt; m.size()</code> |

### 31.10.2 match\_results state

[re.results.state]

`bool ready() const;`

1 *Returns:* `true` if `*this` has a fully established result state, otherwise `false`.

### 31.10.3 `match_results` size [`re.results.size`]

`size_type size() const;`

1 *Returns:* One plus the number of marked sub-expressions in the regular expression that was matched if `*this` represents the result of a successful match. Otherwise returns 0. [*Note:* The state of a `match_results` object can be modified only by passing that object to `regex_match` or `regex_search`. Sections 31.11.2 and 31.11.3 specify the effects of those algorithms on their `match_results` arguments. — *end note*]

`size_type max_size() const;`

2 *Returns:* The maximum number of `sub_match` elements that can be stored in `*this`.

`bool empty() const;`

3 *Returns:* `size() == 0`.

### 31.10.4 `match_results` element access [`re.results.acc`]

`difference_type length(size_type sub = 0) const;`

1 *Requires:* `ready() == true`.

2 *Returns:* `(*this)[sub].length()`.

`difference_type position(size_type sub = 0) const;`

3 *Requires:* `ready() == true`.

4 *Returns:* The distance from the start of the target sequence to `(*this)[sub].first`.

`string_type str(size_type sub = 0) const;`

5 *Requires:* `ready() == true`.

6 *Returns:* `string_type((*this)[sub])`.

`const_reference operator[](size_type n) const;`

7 *Requires:* `ready() == true`.

8 *Returns:* A reference to the `sub_match` object representing the character sequence that matched marked sub-expression `n`. If `n == 0` then returns a reference to a `sub_match` object representing the character sequence that matched the whole regular expression. If `n >= size()` then returns a `sub_match` object representing an unmatched sub-expression.

`const_reference prefix() const;`

9 *Requires:* `ready() == true`.

10 *Returns:* A reference to the `sub_match` object representing the character sequence from the start of the string being matched/searched to the start of the match found.

`const_reference suffix() const;`

11 *Requires:* `ready() == true`.

12 *Returns:* A reference to the `sub_match` object representing the character sequence from the end of the match found to the end of the string being matched/searched.

```
const_iterator begin() const;
const_iterator cbegin() const;
```

13 *Returns:* A starting iterator that enumerates over all the sub-expressions stored in *\*this*.

```
const_iterator end() const;
const_iterator cend() const;
```

14 *Returns:* A terminating iterator that enumerates over all the sub-expressions stored in *\*this*.

### 31.10.5 match\_results formatting

[re.results.form]

```
template <class OutputIter>
```

```
OutputIter format(
 OutputIter out,
 const char_type* fmt_first, const char_type* fmt_last,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
```

1 *Requires:* `ready() == true` and `OutputIter` shall satisfy the requirements for an Output Iterator (27.2.4).

2 *Effects:* Copies the character sequence `[fmt_first, fmt_last)` to `OutputIter out`. Replaces each format specifier or escape sequence in the copied range with either the character(s) it represents or the sequence of characters within *\*this* to which it refers. The bitmasks specified in `flags` determine which format specifiers and escape sequences are recognized.

3 *Returns:* `out`.

```
template <class OutputIter, class ST, class SA>
```

```
OutputIter format(
 OutputIter out,
 const basic_string<char_type, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
```

4 *Effects:* Equivalent to:

```
return format(out, fmt.data(), fmt.data() + fmt.size(), flags);
```

```
template <class ST, class SA>
```

```
basic_string<char_type, ST, SA> format(
 const basic_string<char_type, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
```

5 *Requires:* `ready() == true`.

6 *Effects:* Constructs an empty string result of type `basic_string<char_type, ST, SA>` and calls:

```
format(back_inserter(result), fmt, flags);
```

7 *Returns:* `result`.

```
string_type format(
```

```
 const char_type* fmt,
 regex_constants::match_flag_type flags = regex_constants::format_default) const;
```

8 *Requires:* `ready() == true`.

9 *Effects:* Constructs an empty string result of type `string_type` and calls:

```
format(back_inserter(result), fmt, fmt + char_traits<char_type>::length(fmt), flags);
```

10 *Returns:* `result`.

### 31.10.6 match\_results allocator

[re.results.all]

```
allocator_type get_allocator() const;
```

- 1 *Returns:* A copy of the Allocator that was passed to the object's constructor or, if that allocator has been replaced, a copy of the most recent replacement.

### 31.10.7 match\_results swap [re.results.swap]

```
void swap(match_results& that);
```

- 1 *Effects:* Swaps the contents of the two sequences.
- 2 *Postconditions:* *\*this* contains the sequence of matched sub-expressions that were in *that*, *that* contains the sequence of matched sub-expressions that were in *\*this*.
- 3 *Complexity:* Constant time.

```
template <class BidirectionalIterator, class Allocator>
void swap(match_results<BidirectionalIterator, Allocator>& m1,
 match_results<BidirectionalIterator, Allocator>& m2);
```

- 4 *Effects:* As if by *m1.swap(m2)*.

### 31.10.8 match\_results non-member functions [re.results.nonmember]

```
template <class BidirectionalIterator, class Allocator>
bool operator==(const match_results<BidirectionalIterator, Allocator>& m1,
 const match_results<BidirectionalIterator, Allocator>& m2);
```

- 1 *Returns:* true if neither match result is ready, false if one match result is ready and the other is not. If both match results are ready, returns true only if:

- (1.1) — *m1.empty()* && *m2.empty()*, or
- (1.2) — *!m1.empty()* && *!m2.empty()*, and the following conditions are satisfied:
  - (1.2.1) — *m1.prefix()* == *m2.prefix()*,
  - (1.2.2) — *m1.size()* == *m2.size()* && *equal(m1.begin(), m1.end(), m2.begin(), m2.end())*, and
  - (1.2.3) — *m1.suffix()* == *m2.suffix()*.

[ *Note:* The algorithm *equal* is defined in Clause 28. — end note ]

```
template <class BidirectionalIterator, class Allocator>
bool operator!=(const match_results<BidirectionalIterator, Allocator>& m1,
 const match_results<BidirectionalIterator, Allocator>& m2);
```

- 2 *Returns:* *!(m1 == m2)*.

## 31.11 Regular expression algorithms [re.alg]

### 31.11.1 Exceptions [re.except]

- 1 The algorithms described in this subclause may throw an exception of type `regex_error`. If such an exception *e* is thrown, *e.code()* shall return either `regex_constants::error_complexity` or `regex_constants::error_stack`.

### 31.11.2 regex\_match [re.alg.match]

```
template <class BidirectionalIterator, class Allocator, class charT, class traits>
bool regex_match(BidirectionalIterator first, BidirectionalIterator last,
 match_results<BidirectionalIterator, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

<sup>1</sup> *Requires:* The type `BidirectionalIterator` shall satisfy the requirements of a Bidirectional Iterator (27.2.6).

<sup>2</sup> *Effects:* Determines whether there is a match between the regular expression `e`, and all of the character sequence `[first, last)`. The parameter `flags` is used to control how the expression is matched against the character sequence. When determining if there is a match, only potential matches that match the entire character sequence are considered. Returns `true` if such a match exists, `false` otherwise. [Example:

```
std::regex re("Get|GetValue");
std::cmatch m;
regex_search("GetValue", m, re); // returns true, and m[0] contains "Get"
regex_match("GetValue", m, re); // returns true, and m[0] contains "GetValue"
regex_search("GetValues", m, re); // returns true, and m[0] contains "Get"
regex_match("GetValues", m, re); // returns false
```

— end example]

<sup>3</sup> *Postconditions:* `m.ready() == true` in all cases. If the function returns `false`, then the effect on parameter `m` is unspecified except that `m.size()` returns 0 and `m.empty()` returns `true`. Otherwise the effects on parameter `m` are given in Table 135.

Table 135 — Effects of `regex_match` algorithm

| Element                         | Value                                                                                                                                                                                                                   |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>m.size()</code>           | <code>1 + e.mark_count()</code>                                                                                                                                                                                         |
| <code>m.empty()</code>          | <code>false</code>                                                                                                                                                                                                      |
| <code>m.prefix().first</code>   | <code>first</code>                                                                                                                                                                                                      |
| <code>m.prefix().second</code>  | <code>first</code>                                                                                                                                                                                                      |
| <code>m.prefix().matched</code> | <code>false</code>                                                                                                                                                                                                      |
| <code>m.suffix().first</code>   | <code>last</code>                                                                                                                                                                                                       |
| <code>m.suffix().second</code>  | <code>last</code>                                                                                                                                                                                                       |
| <code>m.suffix().matched</code> | <code>false</code>                                                                                                                                                                                                      |
| <code>m[0].first</code>         | <code>first</code>                                                                                                                                                                                                      |
| <code>m[0].second</code>        | <code>last</code>                                                                                                                                                                                                       |
| <code>m[0].matched</code>       | <code>true</code>                                                                                                                                                                                                       |
| <code>m[n].first</code>         | For all integers $0 < n < m.size()$ , the start of the sequence that matched sub-expression <code>n</code> . Alternatively, if sub-expression <code>n</code> did not participate in the match, then <code>last</code> . |
| <code>m[n].second</code>        | For all integers $0 < n < m.size()$ , the end of the sequence that matched sub-expression <code>n</code> . Alternatively, if sub-expression <code>n</code> did not participate in the match, then <code>last</code> .   |
| <code>m[n].matched</code>       | For all integers $0 < n < m.size()$ , <code>true</code> if sub-expression <code>n</code> participated in the match, <code>false</code> otherwise.                                                                       |

```
template <class BidirectionalIterator, class charT, class traits>
bool regex_match(BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

<sup>4</sup> *Effects:* Behaves “as if” by constructing an instance of `match_results<BidirectionalIterator>`



what, and then returning the result of `regex_match(first, last, what, e, flags)`.

```
template <class charT, class Allocator, class traits>
bool regex_match(const charT* str,
 match_results<const charT*, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

5 *Returns:* `regex_match(str, str + char_traits<charT>::length(str), m, e, flags)`.

```
template <class ST, class SA, class Allocator, class charT, class traits>
bool regex_match(const basic_string<charT, ST, SA>& s,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

6 *Returns:* `regex_match(s.begin(), s.end(), m, e, flags)`.

```
template <class charT, class traits>
bool regex_match(const charT* str,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

7 *Returns:* `regex_match(str, str + char_traits<charT>::length(str), e, flags)`

```
template <class ST, class SA, class charT, class traits>
bool regex_match(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

8 *Returns:* `regex_match(s.begin(), s.end(), e, flags)`.

### 31.11.3 regex\_search

[re.alg.search]

```
template <class BidirectionalIterator, class Allocator, class charT, class traits>
bool regex_search(BidirectionalIterator first, BidirectionalIterator last,
 match_results<BidirectionalIterator, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

1 *Requires:* Type `BidirectionalIterator` shall satisfy the requirements of a Bidirectional Iterator (27.2.6).

2 *Effects:* Determines whether there is some sub-sequence within `[first, last)` that matches the regular expression `e`. The parameter `flags` is used to control how the expression is matched against the character sequence. Returns `true` if such a sequence exists, `false` otherwise.

3 *Postconditions:* `m.ready() == true` in all cases. If the function returns `false`, then the effect on parameter `m` is unspecified except that `m.size()` returns 0 and `m.empty()` returns `true`. Otherwise the effects on parameter `m` are given in Table 136.

Table 136 — Effects of `regex_search` algorithm

| Element                        | Value                           |
|--------------------------------|---------------------------------|
| <code>m.size()</code>          | <code>1 + e.mark_count()</code> |
| <code>m.empty()</code>         | <code>false</code>              |
| <code>m.prefix().first</code>  | <code>first</code>              |
| <code>m.prefix().second</code> | <code>m[0].first</code>         |

Table 136 — Effects of `regex_search` algorithm (continued)

| Element                         | Value                                                                                                                                                                                                                   |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>m.prefix().matched</code> | <code>m.prefix().first != m.prefix().second</code>                                                                                                                                                                      |
| <code>m.suffix().first</code>   | <code>m[0].second</code>                                                                                                                                                                                                |
| <code>m.suffix().second</code>  | <code>last</code>                                                                                                                                                                                                       |
| <code>m.suffix().matched</code> | <code>m.suffix().first != m.suffix().second</code>                                                                                                                                                                      |
| <code>m[0].first</code>         | The start of the sequence of characters that matched the regular expression                                                                                                                                             |
| <code>m[0].second</code>        | The end of the sequence of characters that matched the regular expression                                                                                                                                               |
| <code>m[0].matched</code>       | <code>true</code>                                                                                                                                                                                                       |
| <code>m[n].first</code>         | For all integers $0 < n < m.size()$ , the start of the sequence that matched sub-expression <code>n</code> . Alternatively, if sub-expression <code>n</code> did not participate in the match, then <code>last</code> . |
| <code>m[n].second</code>        | For all integers $0 < n < m.size()$ , the end of the sequence that matched sub-expression <code>n</code> . Alternatively, if sub-expression <code>n</code> did not participate in the match, then <code>last</code> .   |
| <code>m[n].matched</code>       | For all integers $0 < n < m.size()$ , <code>true</code> if sub-expression <code>n</code> participated in the match, <code>false</code> otherwise.                                                                       |

```
template <class charT, class Allocator, class traits>
bool regex_search(const charT* str, match_results<const charT*, Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

4     *Returns:* `regex_search(str, str + char_traits<charT>::length(str), m, e, flags)`.

```
template <class ST, class SA, class Allocator, class charT, class traits>
bool regex_search(const basic_string<charT, ST, SA>& s,
 match_results<typename basic_string<charT, ST, SA>::const_iterator,
 Allocator>& m,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

5     *Returns:* `regex_search(s.begin(), s.end(), m, e, flags)`.

```
template <class BidirectionalIterator, class charT, class traits>
bool regex_search(BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

6     *Effects:* Behaves “as if” by constructing an object what of type `match_results<BidirectionalIterator>` and returning `regex_search(first, last, what, e, flags)`.

```
template <class charT, class traits>
bool regex_search(const charT* str,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

7     *Returns:* `regex_search(str, str + char_traits<charT>::length(str), e, flags)`.

```
template <class ST, class SA, class charT, class traits>
```

```
bool regex_search(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

8 *Returns:* `regex_search(s.begin(), s.end(), e, flags)`.

### 31.11.4 regex\_replace

[re.alg.replace]

```
template <class OutputIterator, class BidirectionalIterator,
 class traits, class charT, class ST, class SA>
OutputIterator
regex_replace(OutputIterator out,
 BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class OutputIterator, class BidirectionalIterator, class traits, class charT>
OutputIterator
regex_replace(OutputIterator out,
 BidirectionalIterator first, BidirectionalIterator last,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

1 *Effects:* Constructs a `regex_iterator` object `i` as if by

```
regex_iterator<BidirectionalIterator, charT, traits> i(first, last, e, flags)
```

and uses `i` to enumerate through all of the matches `m` of type `match_results<BidirectionalIterator>` that occur within the sequence `[first, last)`. If no such matches are found and `!(flags & regex_constants::format_no_copy)`, then calls

```
out = copy(first, last, out)
```

If any matches are found then, for each such match:

(1.1) — If `!(flags & regex_constants::format_no_copy)`, calls

```
out = copy(m.prefix().first, m.prefix().second, out)
```

(1.2) — Then calls

```
out = m.format(out, fmt, flags)
```

for the first form of the function and

```
out = m.format(out, fmt, fmt + char_traits<charT>::length(fmt), flags)
```

for the second.

Finally, if such a match is found and `!(flags & regex_constants::format_no_copy)`, calls

```
out = copy(last_m.suffix().first, last_m.suffix().second, out)
```

where `last_m` is a copy of the last match found. If `flags & regex_constants::format_first_only` is nonzero, then only the first match found is replaced.

2 *Returns:* `out`.

```
template <class traits, class charT, class ST, class SA, class FST, class FSA>
basic_string<charT, ST, SA>
regex_replace(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, FST, FSA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
```

```

template <class traits, class charT, class ST, class SA>
 basic_string<charT, ST, SA>
 regex_replace(const basic_string<charT, ST, SA>& s,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
3 Effects: Constructs an empty string result of type basic_string<charT, ST, SA> and calls:
 regex_replace(back_inserter(result), s.begin(), s.end(), e, fmt, flags);
4 Returns: result.

template <class traits, class charT, class ST, class SA>
 basic_string<charT>
 regex_replace(const charT* s,
 const basic_regex<charT, traits>& e,
 const basic_string<charT, ST, SA>& fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
template <class traits, class charT>
 basic_string<charT>
 regex_replace(const charT* s,
 const basic_regex<charT, traits>& e,
 const charT* fmt,
 regex_constants::match_flag_type flags = regex_constants::match_default);
5 Effects: Constructs an empty string result of type basic_string<charT> and calls:
 regex_replace(back_inserter(result), s, s + char_traits<charT>::length(s), e, fmt, flags);
6 Returns: result.

```

## 31.12 Regular expression iterators

[re.iter]

### 31.12.1 Class template `regex_iterator`

[re.regiter]

- 1 The class template `regex_iterator` is an iterator adaptor. It represents a new view of an existing iterator sequence, by enumerating all the occurrences of a regular expression within that sequence. A `regex_iterator` uses `regex_search` to find successive regular expression matches within the sequence from which it was constructed. After the iterator is constructed, and every time `operator++` is used, the iterator finds and stores a value of `match_results<BidirectionalIterator>`. If the end of the sequence is reached (`regex_search` returns `false`), the iterator becomes equal to the end-of-sequence iterator value. The default constructor constructs an end-of-sequence iterator object, which is the only legitimate iterator to be used for the end condition. The result of `operator*` on an end-of-sequence iterator is not defined. For any other iterator value a `const match_results<BidirectionalIterator>&` is returned. The result of `operator->` on an end-of-sequence iterator is not defined. For any other iterator value a `const match_results<BidirectionalIterator>*` is returned. It is impossible to store things into `regex_iterators`. Two end-of-sequence iterators are always equal. An end-of-sequence iterator is not equal to a non-end-of-sequence iterator. Two non-end-of-sequence iterators are equal when they are constructed from the same arguments.

```

namespace std {
 template <class BidirectionalIterator,
 class charT = typename iterator_traits<BidirectionalIterator>::value_type,
 class traits = regex_traits<charT>>
 class regex_iterator {
 public:
 using regex_type = basic_regex<charT, traits>;
 using iterator_category = forward_iterator_tag;
 using value_type = match_results<BidirectionalIterator>;

```

```

using difference_type = ptrdiff_t;
using pointer = const value_type*;
using reference = const value_type&;

regex_iterator();
regex_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 regex_constants::match_flag_type m = regex_constants::match_default);
regex_iterator(BidirectionalIterator, BidirectionalIterator,
 const regex_type&,
 regex_constants::match_flag_type = regex_constants::match_default) = delete;
regex_iterator(const regex_iterator&);
regex_iterator& operator=(const regex_iterator&);
bool operator==(const regex_iterator&) const;
bool operator!=(const regex_iterator&) const;
const value_type& operator*() const;
const value_type* operator->() const;
regex_iterator& operator++();
regex_iterator operator++(int);

private:
 BidirectionalIterator begin; // exposition only
 BidirectionalIterator end; // exposition only
 const regex_type* prenex; // exposition only
 regex_constants::match_flag_type flags; // exposition only
 match_results<BidirectionalIterator> match; // exposition only
};
}

```

- <sup>2</sup> An object of type `regex_iterator` that is not an end-of-sequence iterator holds a *zero-length match* if `match[0].matched == true` and `match[0].first == match[0].second`. [Note: For example, this can occur when the part of the regular expression that matched consists only of an assertion (such as `'^'`, `'$'`, `'\b'`, `'\B'`). — end note]

#### 31.12.1.1 `regex_iterator` constructors

[re.regiter.cnstr]

```
regex_iterator();
```

- <sup>1</sup> *Effects:* Constructs an end-of-sequence iterator.

```

regex_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 regex_constants::match_flag_type m = regex_constants::match_default);

```

- <sup>2</sup> *Effects:* Initializes `begin` and `end` to `a` and `b`, respectively, sets `pregex` to `&re`, sets `flags` to `m`, then calls `regex_search(begin, end, match, *pregex, flags)`. If this call returns `false` the constructor sets `*this` to the end-of-sequence iterator.

#### 31.12.1.2 `regex_iterator` comparisons

[re.regiter.comp]

```
bool operator==(const regex_iterator& right) const;
```

- <sup>1</sup> *Returns:* `true` if `*this` and `right` are both end-of-sequence iterators or if the following conditions all hold:

- (1.1) — `begin == right.begin`,  
 (1.2) — `end == right.end`,

```

(1.3) — pregex == right.pregex,
(1.4) — flags == right.flags, and
(1.5) — match[0] == right.match[0];
 otherwise false.

```

```
bool operator!=(const regex_iterator& right) const;
```

```
2 Returns: !(*this == right).
```

### 31.12.1.3 regex\_iterator indirection [re.regiter.deref]

```
const value_type& operator*() const;
```

```
1 Returns: match.
```

```
const value_type* operator->() const;
```

```
2 Returns: &match.
```

### 31.12.1.4 regex\_iterator increment [re.regiter.incr]

```
regex_iterator& operator++();
```

```
1 Effects: Constructs a local variable start of type BidirectionalIterator and initializes it with the
 value of match[0].second.
```

```
2 If the iterator holds a zero-length match and start == end the operator sets *this to the end-of-
 sequence iterator and returns *this.
```

```
3 Otherwise, if the iterator holds a zero-length match, the operator calls:
```

```
 regex_search(start, end, match, *pregex,
 flags | regex_constants::match_not_null | regex_constants::match_continuous)
```

If the call returns **true** the operator returns **\*this**. Otherwise the operator increments **start** and continues as if the most recent match was not a zero-length match.

```
4 If the most recent match was not a zero-length match, the operator sets flags to flags | regex_
constants::match_prev_avail and calls regex_search(start, end, match, *pregex, flags). If
 the call returns false the iterator sets *this to the end-of-sequence iterator. The iterator then returns
*this.
```

```
5 In all cases in which the call to regex_search returns true, match.prefix().first shall be equal to
 the previous value of match[0].second, and for each index i in the half-open range [0, match.size())
 for which match[i].matched is true, match.position(i) shall return distance(begin, match[i].
first).
```

```
6 [Note: This means that match.position(i) gives the offset from the beginning of the target sequence,
 which is often not the same as the offset from the sequence passed in the call to regex_search. — end
 note]
```

```
7 It is unspecified how the implementation makes these adjustments.
```

```
8 [Note: This means that a compiler may call an implementation-specific search function, in which case
 a user-defined specialization of regex_search will not be called. — end note]
```

```
regex_iterator operator++(int);
```

```
9 Effects: As if by:
```

```
 regex_iterator tmp = *this;
 ++(*this);
```

```
return tmp;
```

### 31.12.2 Class template `regex_token_iterator`

[re.tokiter]

- <sup>1</sup> The class template `regex_token_iterator` is an iterator adaptor; that is to say it represents a new view of an existing iterator sequence, by enumerating all the occurrences of a regular expression within that sequence, and presenting one or more sub-expressions for each match found. Each position enumerated by the iterator is a `sub_match` class template instance that represents what matched a particular sub-expression within the regular expression.
- <sup>2</sup> When class `regex_token_iterator` is used to enumerate a single sub-expression with index -1 the iterator performs field splitting: that is to say it enumerates one sub-expression for each section of the character container sequence that does not match the regular expression specified.
- <sup>3</sup> After it is constructed, the iterator finds and stores a value `regex_iterator<BidirectionalIterator>` `position` and sets the internal count `N` to zero. It also maintains a sequence `subs` which contains a list of the sub-expressions which will be enumerated. Every time `operator++` is used the count `N` is incremented; if `N` exceeds or equals `subs.size()`, then the iterator increments member `position` and sets count `N` to zero.
- <sup>4</sup> If the end of sequence is reached (`position` is equal to the end of sequence iterator), the iterator becomes equal to the end-of-sequence iterator value, unless the sub-expression being enumerated has index -1, in which case the iterator enumerates one last sub-expression that contains all the characters from the end of the last regular expression match to the end of the input sequence being enumerated, provided that this would not be an empty sub-expression.
- <sup>5</sup> The default constructor constructs an end-of-sequence iterator object, which is the only legitimate iterator to be used for the end condition. The result of `operator*` on an end-of-sequence iterator is not defined. For any other iterator value a `const sub_match<BidirectionalIterator>&` is returned. The result of `operator->` on an end-of-sequence iterator is not defined. For any other iterator value a `const sub_match<BidirectionalIterator>*` is returned.
- <sup>6</sup> It is impossible to store things into `regex_token_iterators`. Two end-of-sequence iterators are always equal. An end-of-sequence iterator is not equal to a non-end-of-sequence iterator. Two non-end-of-sequence iterators are equal when they are constructed from the same arguments.

```
namespace std {
 template <class BidirectionalIterator,
 class charT = typename iterator_traits<BidirectionalIterator>::value_type,
 class traits = regex_traits<charT>>
 class regex_token_iterator {
 public:
 using regex_type = basic_regex<charT, traits>;
 using iterator_category = forward_iterator_tag;
 using value_type = sub_match<BidirectionalIterator>;
 using difference_type = ptrdiff_t;
 using pointer = const value_type*;
 using reference = const value_type&;

 regex_token_iterator();
 regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 int submatch = 0,
 regex_constants::match_flag_type m =
 regex_constants::match_default);
 regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 const vector<int>& submatches,
```

```

 regex_constants::match_flag_type m =
 regex_constants::match_default);
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 initializer_list<int> submatches,
 regex_constants::match_flag_type m =
 regex_constants::match_default);

template <size_t N>
 regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 const int (&submatches)[N],
 regex_constants::match_flag_type m =
 regex_constants::match_default);
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type&& re,
 int submatch = 0,
 regex_constants::match_flag_type m =
 regex_constants::match_default) = delete;
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type&& re,
 const vector<int>& submatches,
 regex_constants::match_flag_type m =
 regex_constants::match_default) = delete;
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type&& re,
 initializer_list<int> submatches,
 regex_constants::match_flag_type m =
 regex_constants::match_default) = delete;

template <size_t N>
 regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type&& re,
 const int (&submatches)[N],
 regex_constants::match_flag_type m =
 regex_constants::match_default) = delete;

regex_token_iterator(const regex_token_iterator&);
regex_token_iterator& operator=(const regex_token_iterator&);
bool operator==(const regex_token_iterator&) const;
bool operator!=(const regex_token_iterator&) const;
const value_type& operator*() const;
const value_type* operator->() const;
regex_token_iterator& operator++();
regex_token_iterator operator++(int);

private:
 using position_iterator =
 regex_iterator<BidirectionalIterator, charT, traits>; // exposition only
 position_iterator position; // exposition only
 const value_type* result; // exposition only
 value_type suffix; // exposition only
 size_t N; // exposition only
 vector<int> subs; // exposition only
};
}

```

<sup>7</sup> A *suffix iterator* is a `regex_token_iterator` object that points to a final sequence of characters at the end



of the target sequence. In a suffix iterator the member `result` holds a pointer to the data member `suffix`, the value of the member `suffix.match` is `true`, `suffix.first` points to the beginning of the final sequence, and `suffix.second` points to the end of the final sequence.

<sup>8</sup> [ *Note:* For a suffix iterator, data member `suffix.first` is the same as the end of the last match found, and `suffix.second` is the same as the end of the target sequence — *end note* ]

<sup>9</sup> The *current match* is `(*position).prefix()` if `subs[N] == -1`, or `(*position)[subs[N]]` for any other value of `subs[N]`.

### 31.12.2.1 `regex_token_iterator` constructors

[`re.tokiter.cnstr`]

```
regex_token_iterator();
```

<sup>1</sup> *Effects:* Constructs the end-of-sequence iterator.

```
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 int submatch = 0,
 regex_constants::match_flag_type m = regex_constants::match_default);
```

```
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 const vector<int>& submatches,
 regex_constants::match_flag_type m = regex_constants::match_default);
```

```
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 initializer_list<int> submatches,
 regex_constants::match_flag_type m = regex_constants::match_default);
```

```
template <size_t N>
regex_token_iterator(BidirectionalIterator a, BidirectionalIterator b,
 const regex_type& re,
 const int (&submatches)[N],
 regex_constants::match_flag_type m = regex_constants::match_default);
```

<sup>2</sup> *Requires:* Each of the initialization values of `submatches` shall be  $\geq -1$ .

<sup>3</sup> *Effects:* The first constructor initializes the member `subs` to hold the single value `submatch`. The second constructor initializes the member `subs` to hold a copy of the argument `submatches`. The third and fourth constructors initialize the member `subs` to hold a copy of the sequence of integer values pointed to by the iterator range `[submatches.begin(), submatches.end())` and `[&submatches, &submatches + N)`, respectively.

<sup>4</sup> Each constructor then sets `N` to 0, and `position` to `position_iterator(a, b, re, m)`. If `position` is not an end-of-sequence iterator the constructor sets `result` to the address of the current match. Otherwise if any of the values stored in `subs` is equal to -1 the constructor sets `*this` to a suffix iterator that points to the range `[a, b)`, otherwise the constructor sets `*this` to an end-of-sequence iterator.

### 31.12.2.2 `regex_token_iterator` comparisons

[`re.tokiter.comp`]

```
bool operator==(const regex_token_iterator& right) const;
```

<sup>1</sup> *Returns:* `true` if `*this` and `right` are both end-of-sequence iterators, or if `*this` and `right` are both suffix iterators and `suffix == right.suffix`; otherwise returns `false` if `*this` or `right` is an end-of-sequence iterator or a suffix iterator. Otherwise returns `true` if `position == right.position`, `N == right.N`, and `subs == right.subs`. Otherwise returns `false`.

```
bool operator!=(const regex_token_iterator& right) const;
```

2 *Returns:* `!(*this == right)`.

### 31.12.2.3 `regex_token_iterator` indirection

[re.tokiter.deref]

```
const value_type& operator*() const;
```

1 *Returns:* `*result`.

```
const value_type* operator->() const;
```

2 *Returns:* `result`.

### 31.12.2.4 `regex_token_iterator` increment

[re.tokiter.incr]

```
regex_token_iterator& operator++();
```

1 *Effects:* Constructs a local variable `prev` of type `position_iterator`, initialized with the value of `position`.

2 If `*this` is a suffix iterator, sets `*this` to an end-of-sequence iterator.

3 Otherwise, if `N + 1 < subs.size()`, increments `N` and sets `result` to the address of the current match.

4 Otherwise, sets `N` to 0 and increments `position`. If `position` is not an end-of-sequence iterator the operator sets `result` to the address of the current match.

5 Otherwise, if any of the values stored in `subs` is equal to -1 and `prev->suffix().length()` is not 0 the operator sets `*this` to a suffix iterator that points to the range `[prev->suffix().first, prev->suffix().second)`.

6 Otherwise, sets `*this` to an end-of-sequence iterator.

7 *Returns:* `*this`

```
regex_token_iterator& operator++(int);
```

8 *Effects:* Constructs a copy `tmp` of `*this`, then calls `++(*this)`.

9 *Returns:* `tmp`.

## 31.13 Modified ECMAScript regular expression grammar

[re.grammar]

1 The regular expression grammar recognized by `basic_regex` objects constructed with the ECMAScript flag is that specified by ECMA-262, except as specified below.

2 Objects of type specialization of `basic_regex` store within themselves a default-constructed instance of their `traits` template parameter, henceforth referred to as `traits_inst`. This `traits_inst` object is used to support localization of the regular expression; `basic_regex` member functions shall not call any locale dependent C or C++ API, including the formatted string input functions. Instead they shall call the appropriate traits member function to achieve the required effect.

3 The following productions within the ECMAScript grammar are modified as follows:

```
ClassAtom ::
```

```
-
```

```
ClassAtomNoDash
```

```
ClassAtomExClass
```

```
ClassAtomCollatingElement
```

```
ClassAtomEquivalence
```

```
IdentityEscape ::
```

```
SourceCharacter but not c
```

- 4 The following new productions are then added:

```

ClassAtomExClass ::
 [: ClassName :]

ClassAtomCollatingElement ::
 [. ClassName .]

ClassAtomEquivalence ::
 [= ClassName =]

ClassName ::
 ClassNameCharacter
 ClassNameCharacter ClassName

ClassNameCharacter ::
 SourceCharacter but not one of "." "=" ":"

```

- 5 The productions `ClassAtomExClass`, `ClassAtomCollatingElement` and `ClassAtomEquivalence` provide functionality equivalent to that of the same features in regular expressions in POSIX.
- 6 The regular expression grammar may be modified by any `regex_constants::syntax_option_type` flags specified when constructing an object of type specialization of `basic_regex` according to the rules in Table 130.
- 7 A `ClassName` production, when used in `ClassAtomExClass`, is not valid if `traits_inst.lookup_classname` returns zero for that name. The names recognized as valid `ClassNames` are determined by the type of the traits class, but at least the following names shall be recognized: `alnum`, `alpha`, `blank`, `cntrl`, `digit`, `graph`, `lower`, `print`, `punct`, `space`, `upper`, `xdigit`, `d`, `s`, `w`. In addition the following expressions shall be equivalent:
- ```

\d and [[:digit:]]

\D and [^[:digit:]]

\s and [[:space:]]

\S and [^[:space:]]

\w and [_[:alnum:]]

\W and [^_[:alnum:]]

```
- 8 A `ClassName` production when used in a `ClassAtomCollatingElement` production is not valid if the value returned by `traits_inst.lookup_collatename` for that name is an empty string.
- 9 The results from multiple calls to `traits_inst.lookup_classname` can be bitwise OR'ed together and subsequently passed to `traits_inst.isctype`.
- 10 A `ClassName` production when used in a `ClassAtomEquivalence` production is not valid if the value returned by `traits_inst.lookup_collatename` for that name is an empty string or if the value returned by `traits_inst.transform_primary` for the result of the call to `traits_inst.lookup_collatename` is an empty string.
- 11 When the sequence of characters being transformed to a finite state machine contains an invalid class name the translator shall throw an exception object of type `regex_error`.
- 12 If the *CV* of a *UnicodeEscapeSequence* is greater than the largest value that can be held in an object of type `charT` the translator shall throw an exception object of type `regex_error`. [*Note*: This means that values of the form "uxxxx" that do not fit in a character are invalid. — *end note*]

- ¹³ Where the regular expression grammar requires the conversion of a sequence of characters to an integral value, this is accomplished by calling `traits_inst.value`.
- ¹⁴ The behavior of the internal finite state machine representation when used to match a sequence of characters is as described in ECMA-262. The behavior is modified according to any `match_flag_type` flags (31.5.2) specified when using the regular expression object in one of the regular expression algorithms (31.11). The behavior is also localized by interaction with the traits class template parameter as follows:
- (14.1) — During matching of a regular expression finite state machine against a sequence of characters, two characters `c` and `d` are compared using the following rules:
 - (14.1.1) — if `(flags() & regex_constants::icase)` the two characters are equal if `traits_inst.translate_nocase(c) == traits_inst.translate_nocase(d)`;
 - (14.1.2) — otherwise, if `flags() & regex_constants::collate` the two characters are equal if `traits_inst.translate(c) == traits_inst.translate(d)`;
 - (14.1.3) — otherwise, the two characters are equal if `c == d`.
 - (14.2) — During matching of a regular expression finite state machine against a sequence of characters, comparison of a collating element range `c1-c2` against a character `c` is conducted as follows: if `flags() & regex_constants::collate` is false then the character `c` is matched if `c1 <= c && c <= c2`, otherwise `c` is matched in accordance with the following algorithm:


```

string_type str1 = string_type(1,
    flags() & icase ?
        traits_inst.translate_nocase(c1) : traits_inst.translate(c1);
string_type str2 = string_type(1,
    flags() & icase ?
        traits_inst.translate_nocase(c2) : traits_inst.translate(c2);
string_type str = string_type(1,
    flags() & icase ?
        traits_inst.translate_nocase(c) : traits_inst.translate(c);
return traits_inst.transform(str1.begin(), str1.end())
    <= traits_inst.transform(str.begin(), str.end())
    && traits_inst.transform(str.begin(), str.end())
    <= traits_inst.transform(str2.begin(), str2.end());
      
```
 - (14.3) — During matching of a regular expression finite state machine against a sequence of characters, testing whether a collating element is a member of a primary equivalence class is conducted by first converting the collating element and the equivalence class to sort keys using `traits::transform_primary`, and then comparing the sort keys for equality.
 - (14.4) — During matching of a regular expression finite state machine against a sequence of characters, a character `c` is a member of a character class designated by an iterator range `[first, last)` if `traits_inst.isctype(c, traits_inst.lookup_classname(first, last, flags() & icase))` is true.

32 Atomic operations library [atomics]

32.1 General [atomics.general]

- ¹ This Clause describes components for fine-grained atomic access. This access is provided via operations on atomic objects.
- ² The following subclauses describe atomics requirements and components for types and operations, as summarized below.

Table 137 — Atomics library summary

Subclause	Header(s)
32.4 Order and Consistency	
32.5 Lock-free Property	
32.6 Atomic Types	<atomic>
32.6.1 Operations on Atomic Types	
32.8 Flag Type and Operations	
32.9 Fences	

32.2 Header <atomic> synopsis [atomics.syn]

```

namespace std {
    // 32.4, order and consistency
    enum memory_order;
    template <class T>
        T kill_dependency(T y) noexcept;

    // 32.5, lock-free property
    #define ATOMIC_BOOL_LOCK_FREE unspecified
    #define ATOMIC_CHAR_LOCK_FREE unspecified
    #define ATOMIC_CHAR16_T_LOCK_FREE unspecified
    #define ATOMIC_CHAR32_T_LOCK_FREE unspecified
    #define ATOMIC_WCHAR_T_LOCK_FREE unspecified
    #define ATOMIC_SHORT_LOCK_FREE unspecified
    #define ATOMIC_INT_LOCK_FREE unspecified
    #define ATOMIC_LONG_LOCK_FREE unspecified
    #define ATOMIC_LLONG_LOCK_FREE unspecified
    #define ATOMIC_POINTER_LOCK_FREE unspecified

    // 32.6, atomic
    template<class T> struct atomic;
    // 32.6.3, partial specialization for pointers
    template<class T> struct atomic<T*>;

    // 32.7, non-member functions
    template<class T>
        bool atomic_is_lock_free(const volatile atomic<T*>) noexcept;
    template<class T>
        bool atomic_is_lock_free(const atomic<T*>) noexcept;
    template<class T>

```

```

    void atomic_init(volatile atomic<T>*, typename atomic<T>::value_type) noexcept;
template<class T>
    void atomic_init(atomic<T>*, typename atomic<T>::value_type) noexcept;
template<class T>
    void atomic_store(volatile atomic<T>*, typename atomic<T>::value_type) noexcept;
template<class T>
    void atomic_store(atomic<T>*, typename atomic<T>::value_type) noexcept;
template<class T>
    void atomic_store_explicit(volatile atomic<T>*, typename atomic<T>::value_type,
                               memory_order) noexcept;
template<class T>
    void atomic_store_explicit(atomic<T>*, typename atomic<T>::value_type,
                               memory_order) noexcept;
template<class T>
    T atomic_load(const volatile atomic<T>*) noexcept;
template<class T>
    T atomic_load(const atomic<T>*) noexcept;
template<class T>
    T atomic_load_explicit(const volatile atomic<T>*, memory_order) noexcept;
template<class T>
    T atomic_load_explicit(const atomic<T>*, memory_order) noexcept;
template<class T>
    T atomic_exchange(volatile atomic<T>*, T) noexcept;
template<class T>
    T atomic_exchange(atomic<T>*, typename atomic<T>::value_type) noexcept;
template<class T>
    T atomic_exchange_explicit(volatile atomic<T>*, typename atomic<T>::value_type,
                               memory_order) noexcept;
template<class T>
    T atomic_exchange_explicit(atomic<T>*, typename atomic<T>::value_type,
                               memory_order) noexcept;
template<class T>
    bool atomic_compare_exchange_weak(volatile atomic<T>*,
                                      typename atomic<T>::value_type*,
                                      typename atomic<T>::value_type) noexcept;
template<class T>
    bool atomic_compare_exchange_weak(atomic<T>*,
                                      typename atomic<T>::value_type*,
                                      typename atomic<T>::value_type) noexcept;
template<class T>
    bool atomic_compare_exchange_strong(volatile atomic<T>*,
                                       typename atomic<T>::value_type*,
                                       typename atomic<T>::value_type) noexcept;
template<class T>
    bool atomic_compare_exchange_strong(atomic<T>*,
                                       typename atomic<T>::value_type*,
                                       typename atomic<T>::value_type) noexcept;
template<class T>
    bool atomic_compare_exchange_weak_explicit(volatile atomic<T>*,
                                               typename atomic<T>::value_type*,
                                               typename atomic<T>::value_type,
                                               memory_order, memory_order) noexcept;
template<class T>
    bool atomic_compare_exchange_weak_explicit(atomic<T>*,
                                               typename atomic<T>::value_type*,

```

```

                                typename atomic<T>::value_type,
                                memory_order, memory_order) noexcept;

template<class T>
    bool atomic_compare_exchange_strong_explicit(volatile atomic<T>*,
                                                typename atomic<T>::value_type*,
                                                typename atomic<T>::value_type,
                                                memory_order, memory_order) noexcept;

template<class T>
    bool atomic_compare_exchange_strong_explicit(atomic<T>*,
                                                typename atomic<T>::value_type*,
                                                typename atomic<T>::value_type,
                                                memory_order, memory_order) noexcept;

template <class T>
    T atomic_fetch_add(volatile atomic<T>*, typename atomic<T>::difference_type) noexcept;
template <class T>
    T atomic_fetch_add(atomic<T>*, typename atomic<T>::difference_type) noexcept;
template <class T>
    T atomic_fetch_add_explicit(volatile atomic<T>*, typename atomic<T>::difference_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_add_explicit(atomic<T>*, typename atomic<T>::difference_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_sub(volatile atomic<T>*, typename atomic<T>::difference_type) noexcept;
template <class T>
    T atomic_fetch_sub(atomic<T>*, typename atomic<T>::difference_type) noexcept;
template <class T>
    T atomic_fetch_sub_explicit(volatile atomic<T>*, typename atomic<T>::difference_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_sub_explicit(atomic<T>*, typename atomic<T>::difference_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_and(volatile atomic<T>*, typename atomic<T>::value_type) noexcept;
template <class T>
    T atomic_fetch_and(atomic<T>*, typename atomic<T>::value_type) noexcept;
template <class T>
    T atomic_fetch_and_explicit(volatile atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_and_explicit(atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_or(volatile atomic<T>*, typename atomic<T>::value_type) noexcept;
template <class T>
    T atomic_fetch_or(atomic<T>*, typename atomic<T>::value_type) noexcept;
template <class T>
    T atomic_fetch_or_explicit(volatile atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_or_explicit(atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_xor(volatile atomic<T>*, typename atomic<T>::value_type) noexcept;

```

```

template <class T>
    T atomic_fetch_xor(atomic<T>*, typename atomic<T>::value_type) noexcept;
template <class T>
    T atomic_fetch_xor_explicit(volatile atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;
template <class T>
    T atomic_fetch_xor_explicit(atomic<T>*, typename atomic<T>::value_type,
                                memory_order) noexcept;

// 32.6.1, initialization
#define ATOMIC_VAR_INIT(value) see below

// 32.3, type aliases
using atomic_bool      = atomic<bool>;
using atomic_char      = atomic<char>;
using atomic_schar     = atomic<signed char>;
using atomic_uchar     = atomic<unsigned char>;
using atomic_short     = atomic<short>;
using atomic_ushort    = atomic<unsigned short>;
using atomic_int       = atomic<int>;
using atomic_uint      = atomic<unsigned int>;
using atomic_long      = atomic<long>;
using atomic_ulong     = atomic<unsigned long>;
using atomic_llong     = atomic<long long>;
using atomic_ullong    = atomic<unsigned long long>;
using atomic_char16_t  = atomic<char16_t>;
using atomic_char32_t  = atomic<char32_t>;
using atomic_wchar_t   = atomic<wchar_t>;

using atomic_int8_t    = atomic<int8_t>;
using atomic_uint8_t   = atomic<uint8_t>;
using atomic_int16_t   = atomic<int16_t>;
using atomic_uint16_t  = atomic<uint16_t>;
using atomic_int32_t   = atomic<int32_t>;
using atomic_uint32_t  = atomic<uint32_t>;
using atomic_int64_t   = atomic<int64_t>;
using atomic_uint64_t  = atomic<uint64_t>;

using atomic_int_least8_t  = atomic<int_least8_t>;
using atomic_uint_least8_t = atomic<uint_least8_t>;
using atomic_int_least16_t = atomic<int_least16_t>;
using atomic_uint_least16_t = atomic<uint_least16_t>;
using atomic_int_least32_t = atomic<int_least32_t>;
using atomic_uint_least32_t = atomic<uint_least32_t>;
using atomic_int_least64_t = atomic<int_least64_t>;
using atomic_uint_least64_t = atomic<uint_least64_t>;

using atomic_int_fast8_t   = atomic<int_fast8_t>;
using atomic_uint_fast8_t  = atomic<uint_fast8_t>;
using atomic_int_fast16_t  = atomic<int_fast16_t>;
using atomic_uint_fast16_t = atomic<uint_fast16_t>;
using atomic_int_fast32_t  = atomic<int_fast32_t>;
using atomic_uint_fast32_t = atomic<uint_fast32_t>;
using atomic_int_fast64_t  = atomic<int_fast64_t>;
using atomic_uint_fast64_t = atomic<uint_fast64_t>;

```



```

using atomic_intptr_t      = atomic<intptr_t>;
using atomic_uintptr_t     = atomic<uintptr_t>;
using atomic_size_t        = atomic<size_t>;
using atomic_ptrdiff_t     = atomic<ptrdiff_t>;
using atomic_intmax_t      = atomic<intmax_t>;
using atomic_uintmax_t     = atomic<uintmax_t>;

// 32.8, flag type and operations
struct atomic_flag;
bool atomic_flag_test_and_set(volatile atomic_flag*) noexcept;
bool atomic_flag_test_and_set(atomic_flag*) noexcept;
bool atomic_flag_test_and_set_explicit(volatile atomic_flag*, memory_order) noexcept;
bool atomic_flag_test_and_set_explicit(atomic_flag*, memory_order) noexcept;
void atomic_flag_clear(volatile atomic_flag*) noexcept;
void atomic_flag_clear(atomic_flag*) noexcept;
void atomic_flag_clear_explicit(volatile atomic_flag*, memory_order) noexcept;
void atomic_flag_clear_explicit(atomic_flag*, memory_order) noexcept;
#define ATOMIC_FLAG_INIT see below

// 32.9, fences
extern "C" void atomic_thread_fence(memory_order) noexcept;
extern "C" void atomic_signal_fence(memory_order) noexcept;
}

```

32.3 Type aliases [atomics.alias]

- ¹ The type aliases `atomic_intN_t`, `atomic_uintN_t`, `atomic_intptr_t`, and `atomic_uintptr_t` are defined if and only if `intN_t`, `uintN_t`, `intptr_t`, and `uintptr_t` are defined, respectively.

32.4 Order and consistency [atomics.order]

```

namespace std {
    enum memory_order {
        memory_order_relaxed, memory_order_consume, memory_order_acquire,
        memory_order_release, memory_order_acq_rel, memory_order_seq_cst
    };
}

```

- ¹ The enumeration `memory_order` specifies the detailed regular (non-atomic) memory synchronization order as defined in 4.7 and may provide for operation ordering. Its enumerated values and their meanings are as follows:
- (1.1) — `memory_order_relaxed`: no operation orders memory.
 - (1.2) — `memory_order_release`, `memory_order_acq_rel`, and `memory_order_seq_cst`: a store operation performs a release operation on the affected memory location.
 - (1.3) — `memory_order_consume`: a load operation performs a consume operation on the affected memory location. [*Note*: Prefer `memory_order_acquire`, which provides stronger guarantees than `memory_order_consume`. Implementations have found it infeasible to provide performance better than that of `memory_order_acquire`. Specification revisions are under consideration. — *end note*]
 - (1.4) — `memory_order_acquire`, `memory_order_acq_rel`, and `memory_order_seq_cst`: a load operation performs an acquire operation on the affected memory location.

[*Note*: Atomic operations specifying `memory_order_relaxed` are relaxed with respect to memory ordering. Implementations must still guarantee that any given atomic access to a particular atomic object be indivisible with respect to all other atomic accesses to that object. — *end note*]

- ² An atomic operation *A* that performs a release operation on an atomic object *M* synchronizes with an atomic operation *B* that performs an acquire operation on *M* and takes its value from any side effect in the release sequence headed by *A*.
- ³ There shall be a single total order *S* on all `memory_order_seq_cst` operations, consistent with the “happens before” order and modification orders for all affected locations, such that each `memory_order_seq_cst` operation *B* that loads a value from an atomic object *M* observes one of the following values:
- (3.1) — the result of the last modification *A* of *M* that precedes *B* in *S*, if it exists, or
 - (3.2) — if *A* exists, the result of some modification of *M* that is not `memory_order_seq_cst` and that does not happen before *A*, or
 - (3.3) — if *A* does not exist, the result of some modification of *M* that is not `memory_order_seq_cst`.
- [*Note:* Although it is not explicitly required that *S* include locks, it can always be extended to an order that does include lock and unlock operations, since the ordering between those is already included in the “happens before” ordering. — *end note*]
- ⁴ For an atomic operation *B* that reads the value of an atomic object *M*, if there is a `memory_order_seq_cst` fence *X* sequenced before *B*, then *B* observes either the last `memory_order_seq_cst` modification of *M* preceding *X* in the total order *S* or a later modification of *M* in its modification order.
- ⁵ For atomic operations *A* and *B* on an atomic object *M*, where *A* modifies *M* and *B* takes its value, if there is a `memory_order_seq_cst` fence *X* such that *A* is sequenced before *X* and *B* follows *X* in *S*, then *B* observes either the effects of *A* or a later modification of *M* in its modification order.
- ⁶ For atomic operations *A* and *B* on an atomic object *M*, where *A* modifies *M* and *B* takes its value, if there are `memory_order_seq_cst` fences *X* and *Y* such that *A* is sequenced before *X*, *Y* is sequenced before *B*, and *X* precedes *Y* in *S*, then *B* observes either the effects of *A* or a later modification of *M* in its modification order.
- ⁷ For atomic modifications *A* and *B* of an atomic object *M*, *B* occurs later than *A* in the modification order of *M* if:
- (7.1) — there is a `memory_order_seq_cst` fence *X* such that *A* is sequenced before *X*, and *X* precedes *B* in *S*,
or
 - (7.2) — there is a `memory_order_seq_cst` fence *Y* such that *Y* is sequenced before *B*, and *A* precedes *Y* in *S*,
or
 - (7.3) — there are `memory_order_seq_cst` fences *X* and *Y* such that *A* is sequenced before *X*, *Y* is sequenced before *B*, and *X* precedes *Y* in *S*.
- ⁸ [*Note:* `memory_order_seq_cst` ensures sequential consistency only for a program that is free of data races and uses exclusively `memory_order_seq_cst` operations. Any use of weaker ordering will invalidate this guarantee unless extreme care is used. In particular, `memory_order_seq_cst` fences ensure a total order only for the fences themselves. Fences cannot, in general, be used to restore sequential consistency for atomic operations with weaker ordering specifications. — *end note*]
- ⁹ Implementations should ensure that no “out-of-thin-air” values are computed that circularly depend on their own computation.

[*Note:* For example, with *x* and *y* initially zero,

```
// Thread 1:
r1 = y.load(memory_order_relaxed);
x.store(r1, memory_order_relaxed);

// Thread 2:
r2 = x.load(memory_order_relaxed);
y.store(r2, memory_order_relaxed);
```

should not produce `r1 == r2 == 42`, since the store of 42 to `y` is only possible if the store to `x` stores 42, which circularly depends on the store to `y` storing 42. Note that without this restriction, such an execution is possible. — *end note*]

- 10 [*Note*: The recommendation similarly disallows `r1 == r2 == 42` in the following example, with `x` and `y` again initially zero:

```
// Thread 1:
r1 = x.load(memory_order_relaxed);
if (r1 == 42) y.store(42, memory_order_relaxed);

// Thread 2:
r2 = y.load(memory_order_relaxed);
if (r2 == 42) x.store(42, memory_order_relaxed);

— end note]
```

- 11 Atomic read-modify-write operations shall always read the last value (in the modification order) written before the write associated with the read-modify-write operation.
- 12 Implementations should make atomic stores visible to atomic loads within a reasonable amount of time.

```
template <class T>
T kill_dependency(T y) noexcept;
```

- 13 *Effects*: The argument does not carry a dependency to the return value (4.7).

- 14 *Returns*: `y`.

32.5 Lock-free property

[**atomics.lockfree**]

```
#define ATOMIC_BOOL_LOCK_FREE unspecified
#define ATOMIC_CHAR_LOCK_FREE unspecified
#define ATOMIC_CHAR16_T_LOCK_FREE unspecified
#define ATOMIC_CHAR32_T_LOCK_FREE unspecified
#define ATOMIC_WCHAR_T_LOCK_FREE unspecified
#define ATOMIC_SHORT_LOCK_FREE unspecified
#define ATOMIC_INT_LOCK_FREE unspecified
#define ATOMIC_LONG_LOCK_FREE unspecified
#define ATOMIC_LLONG_LOCK_FREE unspecified
#define ATOMIC_POINTER_LOCK_FREE unspecified
```

- 1 The `ATOMIC_..._LOCK_FREE` macros indicate the lock-free property of the corresponding atomic types, with the signed and unsigned variants grouped together. The properties also apply to the corresponding (partial) specializations of the `atomic` template. A value of 0 indicates that the types are never lock-free. A value of 1 indicates that the types are sometimes lock-free. A value of 2 indicates that the types are always lock-free.
- 2 The function `atomic_is_lock_free` (32.6.1) indicates whether the object is lock-free. In any given program execution, the result of the lock-free query shall be consistent for all pointers of the same type.
- 3 Atomic operations that are not lock-free are considered to potentially block (4.7.2).
- 4 [*Note*: Operations that are lock-free should also be address-free. That is, atomic operations on the same memory location via two different addresses will communicate atomically. The implementation should not depend on any per-process state. This restriction enables communication by memory that is mapped into a process more than once and by memory that is shared between two processes. — *end note*]

32.6 Class template `atomic`

[**atomics.types.generic**]

```
namespace std {
    template <class T> struct atomic {
        using value_type = T;
        static constexpr bool is_always_lock_free = implementation-defined;
```

```

bool is_lock_free() const volatile noexcept;
bool is_lock_free() const noexcept;
void store(T, memory_order = memory_order_seq_cst) volatile noexcept;
void store(T, memory_order = memory_order_seq_cst) noexcept;
T load(memory_order = memory_order_seq_cst) const volatile noexcept;
T load(memory_order = memory_order_seq_cst) const noexcept;
operator T() const volatile noexcept;
operator T() const noexcept;
T exchange(T, memory_order = memory_order_seq_cst) volatile noexcept;
T exchange(T, memory_order = memory_order_seq_cst) noexcept;
bool compare_exchange_weak(T&, T, memory_order, memory_order) volatile noexcept;
bool compare_exchange_weak(T&, T, memory_order, memory_order) noexcept;
bool compare_exchange_strong(T&, T, memory_order, memory_order) volatile noexcept;
bool compare_exchange_strong(T&, T, memory_order, memory_order) noexcept;
bool compare_exchange_weak(T&, T, memory_order = memory_order_seq_cst) volatile noexcept;
bool compare_exchange_weak(T&, T, memory_order = memory_order_seq_cst) noexcept;
bool compare_exchange_strong(T&, T, memory_order = memory_order_seq_cst) volatile noexcept;
bool compare_exchange_strong(T&, T, memory_order = memory_order_seq_cst) noexcept;

atomic() noexcept = default;
constexpr atomic(T) noexcept;
atomic(const atomic&) = delete;
atomic& operator=(const atomic&) = delete;
atomic& operator=(const atomic&) volatile = delete;
T operator=(T) volatile noexcept;
T operator=(T) noexcept;
};
}

```

- 1 The template argument for T shall be trivially copyable (6.9). [Note: Type arguments that are not also statically initializable may be difficult to use. — end note]
- 2 The specialization `atomic<bool>` is a standard-layout struct.
- 3 [Note: The representation of an atomic specialization need not have the same size as its corresponding argument type. Specializations should have the same size whenever possible, as this reduces the effort required to port existing code. — end note]

32.6.1 Operations on atomic types

[atomics.types.operations]

- 1 [Note: Many operations are volatile-qualified. The “volatile as device register” semantics have not changed in the standard. This qualification means that volatility is preserved when applying these operations to volatile objects. It does not mean that operations on non-volatile objects become volatile. — end note]

```
atomic() noexcept = default;
```

- 2 *Effects:* Leaves the atomic object in an uninitialized state. [Note: These semantics ensure compatibility with C. — end note]

```
constexpr atomic(T desired) noexcept;
```

- 3 *Effects:* Initializes the object with the value `desired`. Initialization is not an atomic operation (4.7). [Note: It is possible to have an access to an atomic object A race with its construction, for example by communicating the address of the just-constructed object A to another thread via `memory_order_relaxed` operations on a suitable atomic pointer variable, and then immediately accessing A in the receiving thread. This results in undefined behavior. — end note]

```
#define ATOMIC_VAR_INIT(value) see below
```

- 4 The macro expands to a token sequence suitable for constant initialization of an atomic variable of static storage duration of a type that is initialization-compatible with `value`. [*Note*: This operation may need to initialize locks. — *end note*] Concurrent access to the variable being initialized, even via an atomic operation, constitutes a data race. [*Example*:

```
    atomic<int> v = ATOMIC_VAR_INIT(5);
    — end example]
```

```
static constexpr bool is_always_lock_free = implementation-defined;
```

- 5 The static data member `is_always_lock_free` is `true` if the atomic type's operations are always lock-free, and `false` otherwise. [*Note*: The value of `is_always_lock_free` is consistent with the value of the corresponding `ATOMIC_..._LOCK_FREE` macro, if defined. — *end note*]

```
bool is_lock_free() const volatile noexcept;
bool is_lock_free() const noexcept;
```

- 6 *Returns*: `true` if the object's operations are lock-free, `false` otherwise. [*Note*: The return value of the `is_lock_free` member function is consistent with the value of `is_always_lock_free` for the same type. — *end note*]

```
void store(T desired, memory_order order = memory_order_seq_cst) volatile noexcept;
void store(T desired, memory_order order = memory_order_seq_cst) noexcept;
```

- 7 *Requires*: The `order` argument shall not be `memory_order_consume`, `memory_order_acquire`, nor `memory_order_acq_rel`.

- 8 *Effects*: Atomically replaces the value pointed to by `this` with the value of `desired`. Memory is affected according to the value of `order`.

```
T operator=(T desired) volatile noexcept;
T operator=(T desired) noexcept;
```

- 9 *Effects*: Equivalent to: `store(desired)`.

- 10 *Returns*: `desired`.

```
T load(memory_order order = memory_order_seq_cst) const volatile noexcept;
T load(memory_order order = memory_order_seq_cst) const noexcept;
```

- 11 *Requires*: The `order` argument shall not be `memory_order_release` nor `memory_order_acq_rel`.

- 12 *Effects*: Memory is affected according to the value of `order`.

- 13 *Returns*: Atomically returns the value pointed to by `this`.

```
operator T() const volatile noexcept;
operator T() const noexcept;
```

- 14 *Effects*: Equivalent to: `return load()`;

```
T exchange(T desired, memory_order order = memory_order_seq_cst) volatile noexcept;
T exchange(T desired, memory_order order = memory_order_seq_cst) noexcept;
```

- 15 *Effects*: Atomically replaces the value pointed to by `this` with `desired`. Memory is affected according to the value of `order`. These operations are atomic read-modify-write operations (4.7).

- 16 *Returns*: Atomically returns the value pointed to by `this` immediately before the effects.

```
bool compare_exchange_weak(T& expected, T desired,
                           memory_order success, memory_order failure) volatile noexcept;
bool compare_exchange_weak(T& expected, T desired,
```

```

        memory_order success, memory_order failure) noexcept;
bool compare_exchange_strong(T& expected, T desired,
        memory_order success, memory_order failure) volatile noexcept;
bool compare_exchange_strong(T& expected, T desired,
        memory_order success, memory_order failure) noexcept;
bool compare_exchange_weak(T& expected, T desired,
        memory_order order = memory_order_seq_cst) volatile noexcept;
bool compare_exchange_weak(T& expected, T desired,
        memory_order order = memory_order_seq_cst) noexcept;
bool compare_exchange_strong(T& expected, T desired,
        memory_order order = memory_order_seq_cst) volatile noexcept;
bool compare_exchange_strong(T& expected, T desired,
        memory_order order = memory_order_seq_cst) noexcept;

```

17 *Requires:* The failure argument shall not be `memory_order_release` nor `memory_order_acq_rel`.

18 *Effects:* Retrieves the value in `expected`. It then atomically compares the contents of the memory pointed to by `this` for equality with that previously retrieved from `expected`, and if true, replaces the contents of the memory pointed to by `this` with that in `desired`. If and only if the comparison is true, memory is affected according to the value of `success`, and if the comparison is false, memory is affected according to the value of `failure`. When only one `memory_order` argument is supplied, the value of `success` is `order`, and the value of `failure` is `order` except that a value of `memory_order_acq_rel` shall be replaced by the value `memory_order_acquire` and a value of `memory_order_release` shall be replaced by the value `memory_order_relaxed`. If and only if the comparison is false then, after the atomic operation, the contents of the memory in `expected` are replaced by the value read from the memory pointed to by `this` during the atomic comparison. If the operation returns `true`, these operations are atomic read-modify-write operations (4.7) on the memory pointed to by `this`. Otherwise, these operations are atomic load operations on that memory.

19 *Returns:* The result of the comparison.

20 [*Note:* For example, the effect of `compare_exchange_strong` is

```

    if (memcmp(this, &expected, sizeof(*this)) == 0)
        memcpy(this, &desired, sizeof(*this));
    else
        memcpy(expected, this, sizeof(*this));

```

— *end note*] [*Example:* The expected use of the compare-and-exchange operations is as follows. The compare-and-exchange operations will update `expected` when another iteration of the loop is needed.

```

    expected = current.load();
    do {
        desired = function(expected);
    } while (!current.compare_exchange_weak(expected, desired));

```

— *end example*] [*Example:* Because the expected value is updated only on failure, code releasing the memory containing the `expected` value on success will work. E.g. list head insertion will act atomically and would not introduce a data race in the following code:

```

    do {
        p->next = head; // make new list node point to the current head
    } while (!head.compare_exchange_weak(p->next, p)); // try to insert

```

— *end example*]

21 Implementations should ensure that weak compare-and-exchange operations do not consistently return `false` unless either the atomic object has value different from `expected` or there are concurrent

modifications to the atomic object.

- 22 *Remarks:* A weak compare-and-exchange operation may fail spuriously. That is, even when the contents of memory referred to by `expected` and `this` are equal, it may return `false` and store back to `expected` the same memory contents that were originally there. [*Note:* This spurious failure enables implementation of compare-and-exchange on a broader class of machines, e.g., load-locked store-conditional machines. A consequence of spurious failure is that nearly all uses of weak compare-and-exchange will be in a loop.

When a compare-and-exchange is in a loop, the weak version will yield better performance on some platforms. When a weak compare-and-exchange would require a loop and a strong one would not, the strong one is preferable. — *end note*]

- 23 [*Note:* The `memcpy` and `memcmp` semantics of the compare-and-exchange operations may result in failed comparisons for values that compare equal with `operator==` if the underlying type has padding bits, trap bits, or alternate representations of the same value. Thus, `compare_exchange_strong` should be used with extreme care. On the other hand, `compare_exchange_weak` should converge rapidly. — *end note*]

32.6.2 Specializations for integers

[`atomics.types.int`]

- ¹ There are specializations of the atomic template for the integral types `char`, `signed char`, `unsigned char`, `short`, `unsigned short`, `int`, `unsigned int`, `long`, `unsigned long`, `long long`, `unsigned long long`, `char16_t`, `char32_t`, `wchar_t`, and any other types needed by the typedefs in the header `<stdint>`. For each such integral type *integral*, the specialization `atomic<integral>` provides additional atomic operations appropriate to integral types. [*Note:* For the specialization `atomic<bool>`, see 32.6. — *end note*]

```
namespace std {
    template <> struct atomic<integral> {
        using value_type = integral;
        using difference_type = value_type;
        static constexpr bool is_always_lock_free = implementation-defined;
        bool is_lock_free() const volatile noexcept;
        bool is_lock_free() const noexcept;
        void store(integral, memory_order = memory_order_seq_cst) volatile noexcept;
        void store(integral, memory_order = memory_order_seq_cst) noexcept;
        integral load(memory_order = memory_order_seq_cst) const volatile noexcept;
        integral load(memory_order = memory_order_seq_cst) const noexcept;
        operator integral() const volatile noexcept;
        operator integral() const noexcept;
        integral exchange(integral, memory_order = memory_order_seq_cst) volatile noexcept;
        integral exchange(integral, memory_order = memory_order_seq_cst) noexcept;
        bool compare_exchange_weak(integral&, integral,
                                   memory_order, memory_order) volatile noexcept;
        bool compare_exchange_weak(integral&, integral,
                                   memory_order, memory_order) noexcept;
        bool compare_exchange_strong(integral&, integral,
                                     memory_order, memory_order) volatile noexcept;
        bool compare_exchange_strong(integral&, integral,
                                     memory_order, memory_order) noexcept;
        bool compare_exchange_weak(integral&, integral,
                                   memory_order = memory_order_seq_cst) volatile noexcept;
        bool compare_exchange_weak(integral&, integral,
                                   memory_order = memory_order_seq_cst) noexcept;
        bool compare_exchange_strong(integral&, integral,
                                     memory_order = memory_order_seq_cst) volatile noexcept;
        bool compare_exchange_strong(integral&, integral,
```

```

        memory_order = memory_order_seq_cst) noexcept;
    integral fetch_add(integral, memory_order = memory_order_seq_cst) volatile noexcept;
    integral fetch_add(integral, memory_order = memory_order_seq_cst) noexcept;
    integral fetch_sub(integral, memory_order = memory_order_seq_cst) volatile noexcept;
    integral fetch_sub(integral, memory_order = memory_order_seq_cst) noexcept;
    integral fetch_and(integral, memory_order = memory_order_seq_cst) volatile noexcept;
    integral fetch_and(integral, memory_order = memory_order_seq_cst) noexcept;
    integral fetch_or(integral, memory_order = memory_order_seq_cst) volatile noexcept;
    integral fetch_or(integral, memory_order = memory_order_seq_cst) noexcept;
    integral fetch_xor(integral, memory_order = memory_order_seq_cst) volatile noexcept;
    integral fetch_xor(integral, memory_order = memory_order_seq_cst) noexcept;

    atomic() noexcept = default;
    constexpr atomic(integral) noexcept;
    atomic(const atomic&) = delete;
    atomic& operator=(const atomic&) = delete;
    atomic& operator=(const atomic&) volatile = delete;
    integral operator=(integral) volatile noexcept;
    integral operator=(integral) noexcept;

    integral operator++(int) volatile noexcept;
    integral operator++(int) noexcept;
    integral operator--(int) volatile noexcept;
    integral operator--(int) noexcept;
    integral operator++() volatile noexcept;
    integral operator++() noexcept;
    integral operator--() volatile noexcept;
    integral operator--() noexcept;
    integral operator+=(integral) volatile noexcept;
    integral operator+=(integral) noexcept;
    integral operator-=(integral) volatile noexcept;
    integral operator-=(integral) noexcept;
    integral operator&=(integral) volatile noexcept;
    integral operator&=(integral) noexcept;
    integral operator|=(integral) volatile noexcept;
    integral operator|=(integral) noexcept;
    integral operator^=(integral) volatile noexcept;
    integral operator^=(integral) noexcept;
};
}

```

- ² The atomic integral specializations are standard-layout structs. They each have a trivial default constructor and a trivial destructor.
- ³ Descriptions are provided below only for members that differ from the primary template.
- ⁴ The following operations perform arithmetic computations. The key, operator, and computation correspondence is:

Table 138 — Atomic arithmetic computations

key	Op	Computation	key	Op	Computation
add	+	addition	sub	-	subtraction
or		bitwise inclusive or	xor	^	bitwise exclusive or
and	&	bitwise and			

T fetch_key(T operand, memory_order order = memory_order_seq_cst) volatile noexcept;

T fetch_key(T operand, memory_order order = memory_order_seq_cst) noexcept;

- 5 *Effects:* Atomically replaces the value pointed to by **this** with the result of the computation applied to the value pointed to by **this** and the given **operand**. Memory is affected according to the value of **order**. These operations are atomic read-modify-write operations (4.7).

- 6 *Returns:* Atomically, the value pointed to by **this** immediately before the effects.

- 7 *Remarks:* For signed integer types, arithmetic is defined to use two's complement representation. There are no undefined results.

T operator op=(T operand) volatile noexcept;

T operator op=(T operand) noexcept;

- 8 *Effects:* Equivalent to: return fetch_key(operand) op operand;

32.6.3 Partial specialization for pointers

[atomics.types.pointer]

```
namespace std {
    template <class T> struct atomic<T*> {
        using value_type = T*;
        using difference_type = ptrdiff_t;
        static constexpr bool is_always_lock_free = implementation-defined;
        bool is_lock_free() const volatile noexcept;
        bool is_lock_free() const noexcept;
        void store(T*, memory_order = memory_order_seq_cst) volatile noexcept;
        void store(T*, memory_order = memory_order_seq_cst) noexcept;
        T* load(memory_order = memory_order_seq_cst) const volatile noexcept;
        T* load(memory_order = memory_order_seq_cst) const noexcept;
        operator T*() const volatile noexcept;
        operator T*() const noexcept;
        T* exchange(T*, memory_order = memory_order_seq_cst) volatile noexcept;
        T* exchange(T*, memory_order = memory_order_seq_cst) noexcept;
        bool compare_exchange_weak(T*&, T*, memory_order, memory_order) volatile noexcept;
        bool compare_exchange_weak(T*&, T*, memory_order, memory_order) noexcept;
        bool compare_exchange_strong(T*&, T*, memory_order, memory_order) volatile noexcept;
        bool compare_exchange_strong(T*&, T*, memory_order, memory_order) noexcept;
        bool compare_exchange_weak(T*&, T*, memory_order = memory_order_seq_cst) volatile noexcept;
        bool compare_exchange_weak(T*&, T*, memory_order = memory_order_seq_cst) noexcept;
        bool compare_exchange_strong(T*&, T*, memory_order = memory_order_seq_cst) volatile noexcept;
        bool compare_exchange_strong(T*&, T*, memory_order = memory_order_seq_cst) noexcept;
        T* fetch_add(ptrdiff_t, memory_order = memory_order_seq_cst) volatile noexcept;
        T* fetch_add(ptrdiff_t, memory_order = memory_order_seq_cst) noexcept;
        T* fetch_sub(ptrdiff_t, memory_order = memory_order_seq_cst) volatile noexcept;
        T* fetch_sub(ptrdiff_t, memory_order = memory_order_seq_cst) noexcept;

        atomic() noexcept = default;
        constexpr atomic(T*) noexcept;
        atomic(const atomic&) = delete;
        atomic& operator=(const atomic&) = delete;
        atomic& operator=(const atomic&) volatile = delete;
        T* operator=(T*) volatile noexcept;
        T* operator=(T*) noexcept;

        T* operator++(int) volatile noexcept;
        T* operator++(int) noexcept;
        T* operator--(int) volatile noexcept;
```

```

    T* operator--(int) noexcept;
    T* operator++() volatile noexcept;
    T* operator++() noexcept;
    T* operator--() volatile noexcept;
    T* operator--() noexcept;
    T* operator+=(ptrdiff_t) volatile noexcept;
    T* operator+=(ptrdiff_t) noexcept;
    T* operator--(ptrdiff_t) volatile noexcept;
    T* operator--(ptrdiff_t) noexcept;
};
}

```

- 1 There is a partial specialization of the `atomic` class template for pointers. Specializations of this partial specialization are standard-layout structs. They each have a trivial default constructor and a trivial destructor.
- 2 Descriptions are provided below only for members that differ from the primary template.
- 3 The following operations perform pointer arithmetic. The key, operator, and computation correspondence is:

Table 139 — Atomic pointer computations

Key	Op	Computation	Key	Op	Computation
add	+	addition	sub	-	subtraction

```

T* fetch_key(ptrdiff_t operand, memory_order order = memory_order_seq_cst) volatile noexcept;
T* fetch_key(ptrdiff_t operand, memory_order order = memory_order_seq_cst) noexcept;

```

- 4 *Requires:* T shall be an object type, otherwise the program is ill-formed. [*Note:* Pointer arithmetic on `void*` or function pointers is ill-formed. — *end note*]
- 5 *Effects:* Atomically replaces the value pointed to by `this` with the result of the computation applied to the value pointed to by `this` and the given `operand`. Memory is affected according to the value of `order`. These operations are atomic read-modify-write operations (4.7).
- 6 *Returns:* Atomically, the value pointed to by `this` immediately before the effects.
- 7 *Remarks:* The result may be an undefined address, but the operations otherwise have no undefined behavior.

```

T* operator op=(ptrdiff_t operand) volatile noexcept;
T* operator op=(ptrdiff_t operand) noexcept;

```

- 8 *Effects:* Equivalent to: `return fetch_key(operand) op operand;`

32.6.4 Member operators common to integers and pointers to objects [atomics.types.memop]

```

T operator++(int) volatile noexcept;
T operator++(int) noexcept;

```

Effects: Equivalent to: `return fetch_add(1);`

```

T operator--(int) volatile noexcept;
T operator--(int) noexcept;

```

Effects: Equivalent to: `return fetch_sub(1);`

```

T operator++() volatile noexcept;
T operator++() noexcept;

```

¹ *Effects:* Equivalent to: `return fetch_add(1) + 1;`

`T operator--() volatile noexcept;`

`T operator--() noexcept;`

² *Effects:* Equivalent to: `return fetch_sub(1) - 1;`

32.7 Non-member functions

[atomics.nonmembers]

¹ A non-member function template whose name matches the pattern `atomic_f` or the pattern `atomic_f_` followed by `explicit` invokes the member function `f`, with the value of the first parameter as the object expression and the values of the remaining parameters (if any) as the arguments of the member function call, in order. An argument for a parameter of type `atomic<T>::value_type*` is dereferenced when passed to the member function call. If no such member function exists, the program is ill-formed.

```
template<class T>
```

```
void atomic_init(volatile atomic<T>* object, typename atomic<T>::value_type desired) noexcept;
```

```
template<class T>
```

```
void atomic_init(atomic<T>* object, typename atomic<T>::value_type desired) noexcept;
```

² *Effects:* Non-atomically initializes `*object` with value `desired`. This function shall only be applied to objects that have been default constructed, and then only once. [Note: These semantics ensure compatibility with C. — end note] [Note: Concurrent access from another thread, even via an atomic operation, constitutes a data race. — end note]

³ [Note: The non-member functions enable programmers to write code that can be compiled as either C or C++, for example in a shared header file. — end note]

32.8 Flag type and operations

[atomics.flag]

```
namespace std {
```

```
struct atomic_flag {
```

```
bool test_and_set(memory_order = memory_order_seq_cst) volatile noexcept;
```

```
bool test_and_set(memory_order = memory_order_seq_cst) noexcept;
```

```
void clear(memory_order = memory_order_seq_cst) volatile noexcept;
```

```
void clear(memory_order = memory_order_seq_cst) noexcept;
```

```
atomic_flag() noexcept = default;
```

```
atomic_flag(const atomic_flag&) = delete;
```

```
atomic_flag& operator=(const atomic_flag&) = delete;
```

```
atomic_flag& operator=(const atomic_flag&) volatile = delete;
```

```
};
```

```
bool atomic_flag_test_and_set(volatile atomic_flag*) noexcept;
```

```
bool atomic_flag_test_and_set(atomic_flag*) noexcept;
```

```
bool atomic_flag_test_and_set_explicit(volatile atomic_flag*, memory_order) noexcept;
```

```
bool atomic_flag_test_and_set_explicit(atomic_flag*, memory_order) noexcept;
```

```
void atomic_flag_clear(volatile atomic_flag*) noexcept;
```

```
void atomic_flag_clear(atomic_flag*) noexcept;
```

```
void atomic_flag_clear_explicit(volatile atomic_flag*, memory_order) noexcept;
```

```
void atomic_flag_clear_explicit(atomic_flag*, memory_order) noexcept;
```

```
#define ATOMIC_FLAG_INIT see below
```

```
}
```

¹ The `atomic_flag` type provides the classic test-and-set functionality. It has two states, set and clear.

² Operations on an object of type `atomic_flag` shall be lock-free. [Note: Hence the operations should also be address-free. — end note]

- 3 The `atomic_flag` type is a standard-layout struct. It has a trivial default constructor and a trivial destructor.
- 4 The macro `ATOMIC_FLAG_INIT` shall be defined in such a way that it can be used to initialize an object of type `atomic_flag` to the clear state. The macro can be used in the form:

```
atomic_flag guard = ATOMIC_FLAG_INIT;
```

It is unspecified whether the macro can be used in other initialization contexts. For a complete static-duration object, that initialization shall be static. Unless initialized with `ATOMIC_FLAG_INIT`, it is unspecified whether an `atomic_flag` object has an initial state of set or clear.

```
bool atomic_flag_test_and_set(volatile atomic_flag* object) noexcept;
bool atomic_flag_test_and_set(atomic_flag* object) noexcept;
bool atomic_flag_test_and_set_explicit(volatile atomic_flag* object, memory_order order) noexcept;
bool atomic_flag_test_and_set_explicit(atomic_flag* object, memory_order order) noexcept;
bool atomic_flag::test_and_set(memory_order order = memory_order_seq_cst) volatile noexcept;
bool atomic_flag::test_and_set(memory_order order = memory_order_seq_cst) noexcept;
```

- 5 *Effects:* Atomically sets the value pointed to by `object` or by `this` to `true`. Memory is affected according to the value of `order`. These operations are atomic read-modify-write operations (4.7).
- 6 *Returns:* Atomically, the value of the object immediately before the effects.

```
void atomic_flag_clear(volatile atomic_flag* object) noexcept;
void atomic_flag_clear(atomic_flag* object) noexcept;
void atomic_flag_clear_explicit(volatile atomic_flag* object, memory_order order) noexcept;
void atomic_flag_clear_explicit(atomic_flag* object, memory_order order) noexcept;
void atomic_flag::clear(memory_order order = memory_order_seq_cst) volatile noexcept;
void atomic_flag::clear(memory_order order = memory_order_seq_cst) noexcept;
```

- 7 *Requires:* The `order` argument shall not be `memory_order_consume`, `memory_order_acquire`, nor `memory_order_acq_rel`.
- 8 *Effects:* Atomically sets the value pointed to by `object` or by `this` to `false`. Memory is affected according to the value of `order`.

32.9 Fences

[atomics.fences]

- 1 This section introduces synchronization primitives called *fences*. Fences can have acquire semantics, release semantics, or both. A fence with acquire semantics is called an *acquire fence*. A fence with release semantics is called a *release fence*.
- 2 A release fence *A* synchronizes with an acquire fence *B* if there exist atomic operations *X* and *Y*, both operating on some atomic object *M*, such that *A* is sequenced before *X*, *X* modifies *M*, *Y* is sequenced before *B*, and *Y* reads the value written by *X* or a value written by any side effect in the hypothetical release sequence *X* would head if it were a release operation.
- 3 A release fence *A* synchronizes with an atomic operation *B* that performs an acquire operation on an atomic object *M* if there exists an atomic operation *X* such that *A* is sequenced before *X*, *X* modifies *M*, and *B* reads the value written by *X* or a value written by any side effect in the hypothetical release sequence *X* would head if it were a release operation.
- 4 An atomic operation *A* that is a release operation on an atomic object *M* synchronizes with an acquire fence *B* if there exists some atomic operation *X* on *M* such that *X* is sequenced before *B* and reads the value written by *A* or a value written by any side effect in the release sequence headed by *A*.

```
extern "C" void atomic_thread_fence(memory_order order) noexcept;
```

- 5 *Effects:* Depending on the value of `order`, this operation:
- (5.1) — has no effects, if `order == memory_order_relaxed`;

- (5.2) — is an acquire fence, if `order == memory_order_acquire || order == memory_order_consume`;
- (5.3) — is a release fence, if `order == memory_order_release`;
- (5.4) — is both an acquire fence and a release fence, if `order == memory_order_acq_rel`;
- (5.5) — is a sequentially consistent acquire and release fence, if `order == memory_order_seq_cst`.

```
extern "C" void atomic_signal_fence(memory_order order) noexcept;
```

- 6 *Effects:* Equivalent to `atomic_thread_fence(order)`, except that the resulting ordering constraints are established only between a thread and a signal handler executed in the same thread.
- 7 [*Note:* `atomic_signal_fence` can be used to specify the order in which actions performed by the thread become visible to the signal handler. Compiler optimizations and reorderings of loads and stores are inhibited in the same way as with `atomic_thread_fence`, but the hardware fence instructions that `atomic_thread_fence` would have inserted are not emitted. — *end note*]

33 Thread support library

[thread]

33.1 General

[thread.general]

- ¹ The following subclauses describe components to create and manage threads (4.7), perform mutual exclusion, and communicate conditions and values between threads, as summarized in Table 140.

Table 140 — Thread support library summary

Subclause	Header(s)
33.2 Requirements	
33.3 Threads	<thread>
33.4 Mutual exclusion	<mutex> <shared_mutex>
33.5 Condition variables	<condition_variable>
33.6 Futures	<future>

33.2 Requirements

[thread.req]

33.2.1 Template parameter names

[thread.req.paramname]

- ¹ Throughout this Clause, the names of template parameters are used to express type requirements. If a template parameter is named **Predicate**, **operator()** applied to the template argument shall return a value that is convertible to **bool**.

33.2.2 Exceptions

[thread.req.exception]

- ¹ Some functions described in this Clause are specified to throw exceptions of type **system_error** (22.5.7). Such exceptions shall be thrown if any of the function's error conditions is detected or a call to an operating system or other underlying API results in an error that prevents the library function from meeting its specifications. Failure to allocate storage shall be reported as described in 20.5.5.12.

[*Example:* Consider a function in this clause that is specified to throw exceptions of type **system_error** and specifies error conditions that include **operation_not_permitted** for a thread that does not have the privilege to perform the operation. Assume that, during the execution of this function, an **errno** of **EPERM** is reported by a POSIX API call used by the implementation. Since POSIX specifies an **errno** of **EPERM** when “the caller does not have the privilege to perform the operation”, the implementation maps **EPERM** to an **error_condition** of **operation_not_permitted** (22.5) and an exception of type **system_error** is thrown. — *end example*]

- ² The **error_code** reported by such an exception's **code()** member function shall compare equal to one of the conditions specified in the function's error condition element.

33.2.3 Native handles

[thread.req.native]

- ¹ Several classes described in this Clause have members **native_handle_type** and **native_handle**. The presence of these members and their semantics is implementation-defined. [*Note:* These members allow implementations to provide access to implementation details. Their names are specified to facilitate portable compile-time detection. Actual use of these members is inherently non-portable. — *end note*]

33.2.4 Timing specifications

[thread.req.timing]

- ¹ Several functions described in this Clause take an argument to specify a timeout. These timeouts are specified as either a `duration` or a `time_point` type as specified in 23.17.
- ² Implementations necessarily have some delay in returning from a timeout. Any overhead in interrupt response, function return, and scheduling induces a “quality of implementation” delay, expressed as duration D_i . Ideally, this delay would be zero. Further, any contention for processor and memory resources induces a “quality of management” delay, expressed as duration D_m . The delay durations may vary from timeout to timeout, but in all cases shorter is better.
- ³ The member functions whose names end in `_for` take an argument that specifies a duration. These functions produce relative timeouts. Implementations should use a steady clock to measure time for these functions.³³⁰ Given a duration argument D_t , the real-time duration of the timeout is $D_t + D_i + D_m$.
- ⁴ The member functions whose names end in `_until` take an argument that specifies a time point. These functions produce absolute timeouts. Implementations should use the clock specified in the time point to measure time for these functions. Given a clock time point argument C_t , the clock time point of the return from timeout should be $C_t + D_i + D_m$ when the clock is not adjusted during the timeout. If the clock is adjusted to the time C_a during the timeout, the behavior should be as follows:
 - (4.1) — if $C_a > C_t$, the waiting function should wake as soon as possible, i.e. $C_a + D_i + D_m$, since the timeout is already satisfied. [Note: This specification may result in the total duration of the wait decreasing when measured against a steady clock. — end note]
 - (4.2) — if $C_a \leq C_t$, the waiting function should not time out until `Clock::now()` returns a time $C_n \geq C_t$, i.e. waking at $C_t + D_i + D_m$. [Note: When the clock is adjusted backwards, this specification may result in the total duration of the wait increasing when measured against a steady clock. When the clock is adjusted forwards, this specification may result in the total duration of the wait decreasing when measured against a steady clock. — end note]

An implementation shall return from such a timeout at any point from the time specified above to the time it would return from a steady-clock relative timeout on the difference between C_t and the time point of the call to the `_until` function. [Note: Implementations should decrease the duration of the wait when the clock is adjusted forwards. — end note]

- ⁵ [Note: If the clock is not synchronized with a steady clock, e.g., a CPU time clock, these timeouts might not provide useful functionality. — end note]
- ⁶ The resolution of timing provided by an implementation depends on both operating system and hardware. The finest resolution provided by an implementation is called the *native resolution*.
- ⁷ Implementation-provided clocks that are used for these functions shall meet the `TrivialClock` requirements (23.17.3).
- ⁸ A function that takes an argument which specifies a timeout will throw if, during its execution, a clock, time point, or time duration throws an exception. Such exceptions are referred to as *timeout-related exceptions*. [Note: Instantiations of clock, time point and duration types supplied by the implementation as specified in 23.17.7 do not throw exceptions. — end note]

33.2.5 Requirements for Lockable types

[thread.req.lockable]

33.2.5.1 In general

[thread.req.lockable.general]

- ¹ An *execution agent* is an entity such as a thread that may perform work in parallel with other execution agents. [Note: Implementations or users may introduce other kinds of agents such as processes or thread-pool

³³⁰) All implementations for which standard time units are meaningful must necessarily have a steady clock within their hardware implementation.

tasks. — *end note*] The calling agent is determined by context, e.g. the calling thread that contains the call, and so on.

- ² [*Note*: Some lockable objects are “agent oblivious” in that they work for any execution agent model because they do not determine or store the agent’s ID (e.g., an ordinary spin lock). — *end note*]
- ³ The standard library templates `unique_lock` (33.4.4.3), `shared_lock` (33.4.4.4), `scoped_lock` (33.4.4.2), `lock_guard` (33.4.4.1), `lock`, `try_lock` (33.4.5), and `condition_variable_any` (33.5.4) all operate on user-supplied lockable objects. The `BasicLockable` requirements, the `Lockable` requirements, and the `TimedLockable` requirements list the requirements imposed by these library types in order to acquire or release ownership of a lock by a given execution agent. [*Note*: The nature of any lock ownership and any synchronization it may entail are not part of these requirements. — *end note*]

33.2.5.2 BasicLockable requirements

[thread.req.lockable.basic]

- ¹ A type `L` meets the `BasicLockable` requirements if the following expressions are well-formed and have the specified semantics (`m` denotes a value of type `L`).

`m.lock()`

- ² *Effects*: Blocks until a lock can be acquired for the current execution agent. If an exception is thrown then a lock shall not have been acquired for the current execution agent.

`m.unlock()`

- ³ *Requires*: The current execution agent shall hold a lock on `m`.
- ⁴ *Effects*: Releases a lock on `m` held by the current execution agent.
- ⁵ *Throws*: Nothing.

33.2.5.3 Lockable requirements

[thread.req.lockable.req]

- ¹ A type `L` meets the `Lockable` requirements if it meets the `BasicLockable` requirements and the following expressions are well-formed and have the specified semantics (`m` denotes a value of type `L`).

`m.try_lock()`

- ² *Effects*: Attempts to acquire a lock for the current execution agent without blocking. If an exception is thrown then a lock shall not have been acquired for the current execution agent.
- ³ *Return type*: `bool`.
- ⁴ *Returns*: `true` if the lock was acquired, `false` otherwise.

33.2.5.4 TimedLockable requirements

[thread.req.lockable.timed]

- ¹ A type `L` meets the `TimedLockable` requirements if it meets the `Lockable` requirements and the following expressions are well-formed and have the specified semantics (`m` denotes a value of type `L`, `rel_time` denotes a value of an instantiation of `duration` (23.17.5), and `abs_time` denotes a value of an instantiation of `time_point` (23.17.6)).

`m.try_lock_for(rel_time)`

- ² *Effects*: Attempts to acquire a lock for the current execution agent within the relative timeout (33.2.4) specified by `rel_time`. The function shall not return within the timeout specified by `rel_time` unless it has obtained a lock on `m` for the current execution agent. If an exception is thrown then a lock shall not have been acquired for the current execution agent.
- ³ *Return type*: `bool`.
- ⁴ *Returns*: `true` if the lock was acquired, `false` otherwise.


```
m.try_lock_until(abs_time)
```

- 5 *Effects:* Attempts to acquire a lock for the current execution agent before the absolute timeout (33.2.4) specified by `abs_time`. The function shall not return before the timeout specified by `abs_time` unless it has obtained a lock on `m` for the current execution agent. If an exception is thrown then a lock shall not have been acquired for the current execution agent.

6 *Return type:* `bool`.

7 *Returns:* `true` if the lock was acquired, `false` otherwise.

33.2.6 `decay_copy`

[thread.decaycopy]

- 1 In several places in this Clause the operation *DECAY_COPY*(`x`) is used. All such uses mean call the function `decay_copy(x)` and use the result, where `decay_copy` is defined as follows:

```
template <class T> decay_t<T> decay_copy(T&& v)
{ return std::forward<T>(v); }
```

33.3 Threads

[thread.threads]

- 1 33.3 describes components that can be used to create and manage threads. [*Note:* These threads are intended to map one-to-one with operating system threads. — *end note*]

33.3.1 Header `<thread>` synopsis

[thread.syn]

```
namespace std {
    class thread;

    void swap(thread& x, thread& y) noexcept;

    namespace this_thread {
        thread::id get_id() noexcept;

        void yield() noexcept;
        template <class Clock, class Duration>
            void sleep_until(const chrono::time_point<Clock, Duration>& abs_time);
        template <class Rep, class Period>
            void sleep_for(const chrono::duration<Rep, Period>& rel_time);
    }
}
```

33.3.2 Class `thread`

[thread.thread.class]

- 1 The class `thread` provides a mechanism to create a new thread of execution, to join with a thread (i.e., wait for a thread to complete), and to perform other operations that manage and query the state of a thread. A `thread` object uniquely represents a particular thread of execution. That representation may be transferred to other `thread` objects in such a way that no two `thread` objects simultaneously represent the same thread of execution. A thread of execution is *detached* when no `thread` object represents that thread. Objects of class `thread` can be in a state that does not represent a thread of execution. [*Note:* A `thread` object does not represent a thread of execution after default construction, after being moved from, or after a successful call to `detach` or `join`. — *end note*]

```
namespace std {
    class thread {
    public:
        // types:
        class id;
        using native_handle_type = implementation-defined; // See 33.2.3
```

```

// construct/copy/destroy:
thread() noexcept;
template <class F, class... Args> explicit thread(F&& f, Args&&... args);
~thread();
thread(const thread&) = delete;
thread(thread&&) noexcept;
thread& operator=(const thread&) = delete;
thread& operator=(thread&&) noexcept;

// members:
void swap(thread&) noexcept;
bool joinable() const noexcept;
void join();
void detach();
id get_id() const noexcept;
native_handle_type native_handle(); // See 33.2.3

// static members:
static unsigned hardware_concurrency() noexcept;
};
}

```

33.3.2.1 Class `thread::id`

[thread.thread.id]

```

namespace std {
    class thread::id {
    public:
        id() noexcept;

        bool operator==(thread::id x, thread::id y) noexcept;
        bool operator!=(thread::id x, thread::id y) noexcept;
        bool operator<(thread::id x, thread::id y) noexcept;
        bool operator<=(thread::id x, thread::id y) noexcept;
        bool operator>(thread::id x, thread::id y) noexcept;
        bool operator>=(thread::id x, thread::id y) noexcept;

        template<class charT, class traits>
            basic_ostream<charT, traits>&
                operator<< (basic_ostream<charT, traits>& out, thread::id id);

        // Hash support
        template <class T> struct hash;
        template <> struct hash<thread::id>;
    }
}

```

- ¹ An object of type `thread::id` provides a unique identifier for each thread of execution and a single distinct value for all `thread` objects that do not represent a thread of execution (33.3.2). Each thread of execution has an associated `thread::id` object that is not equal to the `thread::id` object of any other thread of execution and that is not equal to the `thread::id` object of any `thread` object that does not represent threads of execution.
- ² `thread::id` shall be a trivially copyable class (Clause 12). The library may reuse the value of a `thread::id` of a terminated thread that can no longer be joined.
- ³ [Note: Relational operators allow `thread::id` objects to be used as keys in associative containers. — end note]

`id() noexcept;`

4 *Effects:* Constructs an object of type `id`.

5 *Postconditions:* The constructed object does not represent a thread of execution.

`bool operator==(thread::id x, thread::id y) noexcept;`

6 *Returns:* `true` only if `x` and `y` represent the same thread of execution or neither `x` nor `y` represents a thread of execution.

`bool operator!=(thread::id x, thread::id y) noexcept;`

7 *Returns:* `!(x == y)`

`bool operator<(thread::id x, thread::id y) noexcept;`

8 *Returns:* A value such that `operator<` is a total ordering as described in 28.7.

`bool operator<=(thread::id x, thread::id y) noexcept;`

9 *Returns:* `!(y < x)`.

`bool operator>(thread::id x, thread::id y) noexcept;`

10 *Returns:* `y < x`.

`bool operator>=(thread::id x, thread::id y) noexcept;`

11 *Returns:* `!(x < y)`.

`template<class charT, class traits>`

`basic_ostream<charT, traits>&`

`operator<< (basic_ostream<charT, traits>& out, thread::id id);`

12 *Effects:* Inserts an unspecified text representation of `id` into `out`. For two objects of type `thread::id` `x` and `y`, if `x == y` the `thread::id` objects shall have the same text representation and if `x != y` the `thread::id` objects shall have distinct text representations.

13 *Returns:* `out`.

`template <> struct hash<thread::id>;`

14 The specialization is enabled (23.14.15).

33.3.2.2 thread constructors

[thread.thread.constr]

`thread() noexcept;`

1 *Effects:* Constructs a `thread` object that does not represent a thread of execution.

2 *Postconditions:* `get_id() == id()`.

`template <class F, class... Args> explicit thread(F&& f, Args&&... args);`

3 *Requires:* `F` and each `Ti` in `Args` shall satisfy the `MoveConstructible` requirements. `INVOKE(DECAY_COPY(std::forward<F>(f)), DECAY_COPY(std::forward<Args>(args))...)` (23.14.3) shall be a valid expression.

4 *Remarks:* This constructor shall not participate in overload resolution if `decay_t<F>` is the same type as `std::thread`.

5 *Effects:* Constructs an object of type `thread`. The new thread of execution executes `INVOKE(DECAY_COPY(std::forward<F>(f)), DECAY_COPY(std::forward<Args>(args))...)` with the calls to `DECAY_COPY` being evaluated in the constructing thread. Any return value from this invocation

is ignored. [*Note:* This implies that any exceptions not thrown from the invocation of the copy of `f` will be thrown in the constructing thread, not the new thread. — *end note*] If the invocation of `INVOKE(DECAY_COPY(std::forward<F>(f)), DECAY_COPY(std::forward<Args>(args))...)` terminates with an uncaught exception, `terminate` shall be called.

6 *Synchronization:* The completion of the invocation of the constructor synchronizes with the beginning of the invocation of the copy of `f`.

7 *Postconditions:* `get_id() != id()`. `*this` represents the newly started thread.

8 *Throws:* `system_error` if unable to start the new thread.

9 *Error conditions:*

- (9.1) — `resource_unavailable_try_again` — the system lacked the necessary resources to create another thread, or the system-imposed limit on the number of threads in a process would be exceeded.

`thread(thread&& x) noexcept;`

10 *Effects:* Constructs an object of type `thread` from `x`, and sets `x` to a default constructed state.

11 *Postconditions:* `x.get_id() == id()` and `get_id()` returns the value of `x.get_id()` prior to the start of construction.

33.3.2.3 thread destructor

[`thread.thread.destr`]

`~thread();`

1 If `joinable()`, calls `terminate()`. Otherwise, has no effects. [*Note:* Either implicitly detaching or joining a `joinable()` thread in its destructor could result in difficult to debug correctness (for detach) or performance (for join) bugs encountered only when an exception is thrown. Thus the programmer must ensure that the destructor is never executed while the thread is still joinable. — *end note*]

33.3.2.4 thread assignment

[`thread.thread.assign`]

`thread& operator=(thread&& x) noexcept;`

1 *Effects:* If `joinable()`, calls `terminate()`. Otherwise, assigns the state of `x` to `*this` and sets `x` to a default constructed state.

2 *Postconditions:* `x.get_id() == id()` and `get_id()` returns the value of `x.get_id()` prior to the assignment.

3 *Returns:* `*this`.

33.3.2.5 thread members

[`thread.thread.member`]

`void swap(thread& x) noexcept;`

1 *Effects:* Swaps the state of `*this` and `x`.

`bool joinable() const noexcept;`

2 *Returns:* `get_id() != id()`.

`void join();`

3 *Effects:* Blocks until the thread represented by `*this` has completed.

4 *Synchronization:* The completion of the thread represented by `*this` synchronizes with (4.7) the corresponding successful `join()` return. [*Note:* Operations on `*this` are not synchronized. — *end note*]

5 *Postconditions:* The thread represented by `*this` has completed. `get_id() == id()`.

6 *Throws:* `system_error` when an exception is required (33.2.2).

7 *Error conditions:*

(7.1) — `resource_deadlock_would_occur` — if deadlock is detected or `get_id() == this_thread::get_id()`.

(7.2) — `no_such_process` — if the thread is not valid.

(7.3) — `invalid_argument` — if the thread is not joinable.

`void detach();`

8 *Effects:* The thread represented by `*this` continues execution without the calling thread blocking. When `detach()` returns, `*this` no longer represents the possibly continuing thread of execution. When the thread previously represented by `*this` ends execution, the implementation shall release any owned resources.

9 *Postconditions:* `get_id() == id()`.

10 *Throws:* `system_error` when an exception is required (33.2.2).

11 *Error conditions:*

(11.1) — `no_such_process` — if the thread is not valid.

(11.2) — `invalid_argument` — if the thread is not joinable.

`id get_id() const noexcept;`

12 *Returns:* A default constructed `id` object if `*this` does not represent a thread, otherwise `this_thread::get_id()` for the thread of execution represented by `*this`.

33.3.2.6 thread static members

[`thread.thread.static`]

`unsigned hardware_concurrency() noexcept;`

1 *Returns:* The number of hardware thread contexts. [*Note:* This value should only be considered to be a hint. — *end note*] If this value is not computable or well defined an implementation should return 0.

33.3.2.7 thread specialized algorithms

[`thread.thread.algorithm`]

`void swap(thread& x, thread& y) noexcept;`

1 *Effects:* As if by `x.swap(y)`.

33.3.3 Namespace `this_thread`

[`thread.thread.this`]

```
namespace std::this_thread {
    thread::id get_id() noexcept;
```

```
    void yield() noexcept;
```

```
    template <class Clock, class Duration>
```

```
        void sleep_until(const chrono::time_point<Clock, Duration>& abs_time);
```

```
    template <class Rep, class Period>
```

```
        void sleep_for(const chrono::duration<Rep, Period>& rel_time);
```

```
}
```

`thread::id this_thread::get_id() noexcept;`

1 *Returns:* An object of type `thread::id` that uniquely identifies the current thread of execution. No other thread of execution shall have this id and this thread of execution shall always have this id. The object returned shall not compare equal to a default constructed `thread::id`.

```
void this_thread::yield() noexcept;
```

2 *Effects:* Offers the implementation the opportunity to reschedule.

3 *Synchronization:* None.

```
template <class Clock, class Duration>
```

```
void sleep_until(const chrono::time_point<Clock, Duration>& abs_time);
```

4 *Effects:* Blocks the calling thread for the absolute timeout (33.2.4) specified by `abs_time`.

5 *Synchronization:* None.

6 *Throws:* Timeout-related exceptions (33.2.4).

```
template <class Rep, class Period>
```

```
void sleep_for(const chrono::duration<Rep, Period>& rel_time);
```

7 *Effects:* Blocks the calling thread for the relative timeout (33.2.4) specified by `rel_time`.

8 *Synchronization:* None.

9 *Throws:* Timeout-related exceptions (33.2.4).

33.4 Mutual exclusion

[thread.mutex]

1 This section provides mechanisms for mutual exclusion: mutexes, locks, and call once. These mechanisms ease the production of race-free programs (4.7).

33.4.1 Header <mutex> synopsis

[mutex.syn]

```
namespace std {
    class mutex;
    class recursive_mutex;
    class timed_mutex;
    class recursive_timed_mutex;

    struct defer_lock_t { explicit defer_lock_t() = default; };
    struct try_to_lock_t { explicit try_to_lock_t() = default; };
    struct adopt_lock_t { explicit adopt_lock_t() = default; };

    inline constexpr defer_lock_t defer_lock { };
    inline constexpr try_to_lock_t try_to_lock { };
    inline constexpr adopt_lock_t adopt_lock { };

    template <class Mutex> class lock_guard;
    template <class... MutexTypes> class scoped_lock;
    template <class Mutex> class unique_lock;

    template <class Mutex>
        void swap(unique_lock<Mutex>& x, unique_lock<Mutex>& y) noexcept;

    template <class L1, class L2, class... L3> int try_lock(L1&, L2&, L3&...);
    template <class L1, class L2, class... L3> void lock(L1&, L2&, L3&...);

    struct once_flag;

    template<class Callable, class... Args>
        void call_once(once_flag& flag, Callable&& func, Args&&... args);
}
```

33.4.2 Header <shared_mutex> synopsis

[shared_mutex.syn]

```

namespace std {
    class shared_mutex;
    class shared_timed_mutex;
    template <class Mutex> class shared_lock;
    template <class Mutex>
        void swap(shared_lock<Mutex>& x, shared_lock<Mutex>& y) noexcept;
}

```

33.4.3 Mutex requirements

[thread.mutex.requirements]

33.4.3.1 In general

[thread.mutex.requirements.general]

- ¹ A mutex object facilitates protection against data races and allows safe synchronization of data between execution agents (33.2.5). An execution agent *owns* a mutex from the time it successfully calls one of the lock functions until it calls unlock. Mutexes can be either recursive or non-recursive, and can grant simultaneous ownership to one or many execution agents. Both recursive and non-recursive mutexes are supplied.

33.4.3.2 Mutex types

[thread.mutex.requirements.mutex]

- ¹ The *mutex types* are the standard library types `mutex`, `recursive_mutex`, `timed_mutex`, `recursive_timed_mutex`, `shared_mutex`, and `shared_timed_mutex`. They shall meet the requirements set out in this section. In this description, `m` denotes an object of a mutex type.
- ² The mutex types shall meet the Lockable requirements (33.2.5.3).
- ³ The mutex types shall be `DefaultConstructible` and `Destructible`. If initialization of an object of a mutex type fails, an exception of type `system_error` shall be thrown. The mutex types shall not be copyable or movable.
- ⁴ The error conditions for error codes, if any, reported by member functions of the mutex types shall be:
- (4.1) — `resource_unavailable_try_again` — if any native handle type manipulated is not available.
 - (4.2) — `operation_not_permitted` — if the thread does not have the privilege to perform the operation.
 - (4.3) — `invalid_argument` — if any native handle type manipulated as part of mutex construction is incorrect.
- ⁵ The implementation shall provide lock and unlock operations, as described below. For purposes of determining the existence of a data race, these behave as atomic operations (4.7). The lock and unlock operations on a single mutex shall appear to occur in a single total order. [*Note*: This can be viewed as the modification order (4.7) of the mutex. — *end note*] [*Note*: Construction and destruction of an object of a mutex type need not be thread-safe; other synchronization should be used to ensure that mutex objects are initialized and visible to other threads. — *end note*]
- ⁶ The expression `m.lock()` shall be well-formed and have the following semantics:
- ⁷ *Requires*: If `m` is of type `mutex`, `timed_mutex`, `shared_mutex`, or `shared_timed_mutex`, the calling thread does not own the mutex.
 - ⁸ *Effects*: Blocks the calling thread until ownership of the mutex can be obtained for the calling thread.
 - ⁹ *Postconditions*: The calling thread owns the mutex.
 - ¹⁰ *Return type*: `void`.
 - ¹¹ *Synchronization*: Prior `unlock()` operations on the same object shall *synchronize with* (4.7) this operation.
 - ¹² *Throws*: `system_error` when an exception is required (33.2.2).
 - ¹³ *Error conditions*:
- (13.1) — `operation_not_permitted` — if the thread does not have the privilege to perform the operation.

(13.2) — `resource_deadlock_would_occur` — if the implementation detects that a deadlock would occur.

14 The expression `m.try_lock()` shall be well-formed and have the following semantics:

15 *Requires:* If `m` is of type `mutex`, `timed_mutex`, `shared_mutex`, or `shared_timed_mutex`, the calling thread does not own the mutex.

16 *Effects:* Attempts to obtain ownership of the mutex for the calling thread without blocking. If ownership is not obtained, there is no effect and `try_lock()` immediately returns. An implementation may fail to obtain the lock even if it is not held by any other thread. [*Note:* This spurious failure is normally uncommon, but allows interesting implementations based on a simple compare and exchange (Clause 32). — *end note*] An implementation should ensure that `try_lock()` does not consistently return `false` in the absence of contending mutex acquisitions.

17 *Return type:* `bool`.

18 *Returns:* `true` if ownership of the mutex was obtained for the calling thread, otherwise `false`.

19 *Synchronization:* If `try_lock()` returns `true`, prior `unlock()` operations on the same object *synchronize with* (4.7) this operation. [*Note:* Since `lock()` does not synchronize with a failed subsequent `try_lock()`, the visibility rules are weak enough that little would be known about the state after a failure, even in the absence of spurious failures. — *end note*]

20 *Throws:* Nothing.

21 The expression `m.unlock()` shall be well-formed and have the following semantics:

22 *Requires:* The calling thread shall own the mutex.

23 *Effects:* Releases the calling thread's ownership of the mutex.

24 *Return type:* `void`.

25 *Synchronization:* This operation synchronizes with (4.7) subsequent lock operations that obtain ownership on the same object.

26 *Throws:* Nothing.

33.4.3.2.1 Class `mutex`

[`thread.mutex.class`]

```
namespace std {
    class mutex {
    public:
        constexpr mutex() noexcept;
        ~mutex();

        mutex(const mutex&) = delete;
        mutex& operator=(const mutex&) = delete;

        void lock();
        bool try_lock();
        void unlock();

        using native_handle_type = implementation-defined; // See 33.2.3
        native_handle_type native_handle(); // See 33.2.3
    };
}
```

1 The class `mutex` provides a non-recursive mutex with exclusive ownership semantics. If one thread owns a mutex object, attempts by another thread to acquire ownership of that object will fail (for `try_lock()`) or block (for `lock()`) until the owning thread has released ownership with a call to `unlock()`.

2 [*Note:* After a thread A has called `unlock()`, releasing a mutex, it is possible for another thread B to lock

the same mutex, observe that it is no longer in use, unlock it, and destroy it, before thread A appears to have returned from its unlock call. Implementations are required to handle such scenarios correctly, as long as thread A doesn't access the mutex after the unlock call returns. These cases typically occur when a reference-counted object contains a mutex that is used to protect the reference count. — *end note*]

- 3 The class `mutex` shall satisfy all of the mutex requirements (33.4.3). It shall be a standard-layout class (Clause 12).
- 4 [*Note*: A program may deadlock if the thread that owns a `mutex` object calls `lock()` on that object. If the implementation can detect the deadlock, a `resource_deadlock_would_occur` error condition may be observed. — *end note*]
- 5 The behavior of a program is undefined if it destroys a `mutex` object owned by any thread or a thread terminates while owning a `mutex` object.

33.4.3.2.2 Class `recursive_mutex`

[`thread.mutex.recursive`]

```
namespace std {
    class recursive_mutex {
    public:
        recursive_mutex();
        ~recursive_mutex();

        recursive_mutex(const recursive_mutex&) = delete;
        recursive_mutex& operator=(const recursive_mutex&) = delete;

        void lock();
        bool try_lock() noexcept;
        void unlock();

        using native_handle_type = implementation-defined; // See 33.2.3
        native_handle_type native_handle(); // See 33.2.3
    };
}
```

- 1 The class `recursive_mutex` provides a recursive mutex with exclusive ownership semantics. If one thread owns a `recursive_mutex` object, attempts by another thread to acquire ownership of that object will fail (for `try_lock()`) or block (for `lock()`) until the first thread has completely released ownership.
- 2 The class `recursive_mutex` shall satisfy all of the mutex requirements (33.4.3). It shall be a standard-layout class (Clause 12).
- 3 A thread that owns a `recursive_mutex` object may acquire additional levels of ownership by calling `lock()` or `try_lock()` on that object. It is unspecified how many levels of ownership may be acquired by a single thread. If a thread has already acquired the maximum level of ownership for a `recursive_mutex` object, additional calls to `try_lock()` shall fail, and additional calls to `lock()` shall throw an exception of type `system_error`. A thread shall call `unlock()` once for each level of ownership acquired by calls to `lock()` and `try_lock()`. Only when all levels of ownership have been released may ownership be acquired by another thread.
- 4 The behavior of a program is undefined if:
 - (4.1) — it destroys a `recursive_mutex` object owned by any thread or
 - (4.2) — a thread terminates while owning a `recursive_mutex` object.

33.4.3.3 Timed mutex types

[`thread.timedmutex.requirements`]

- 1 The *timed mutex types* are the standard library types `timed_mutex`, `recursive_timed_mutex`, and `shared_timed_mutex`. They shall meet the requirements set out below. In this description, `m` denotes an object of a

mutex type, `rel_time` denotes an object of an instantiation of `duration` (23.17.5), and `abs_time` denotes an object of an instantiation of `time_point` (23.17.6).

2 The timed mutex types shall meet the `TimedLockable` requirements (33.2.5.4).

3 The expression `m.try_lock_for(rel_time)` shall be well-formed and have the following semantics:

4 *Requires:* If `m` is of type `timed_mutex` or `shared_timed_mutex`, the calling thread does not own the mutex.

5 *Effects:* The function attempts to obtain ownership of the mutex within the relative timeout (33.2.4) specified by `rel_time`. If the time specified by `rel_time` is less than or equal to `rel_time.zero()`, the function attempts to obtain ownership without blocking (as if by calling `try_lock()`). The function shall return within the timeout specified by `rel_time` only if it has obtained ownership of the mutex object. [*Note:* As with `try_lock()`, there is no guarantee that ownership will be obtained if the lock is available, but implementations are expected to make a strong effort to do so. — *end note*]

6 *Return type:* `bool`.

7 *Returns:* `true` if ownership was obtained, otherwise `false`.

8 *Synchronization:* If `try_lock_for()` returns `true`, prior `unlock()` operations on the same object synchronize with (4.7) this operation.

9 *Throws:* Timeout-related exceptions (33.2.4).

10 The expression `m.try_lock_until(abs_time)` shall be well-formed and have the following semantics:

11 *Requires:* If `m` is of type `timed_mutex` or `shared_timed_mutex`, the calling thread does not own the mutex.

12 *Effects:* The function attempts to obtain ownership of the mutex. If `abs_time` has already passed, the function attempts to obtain ownership without blocking (as if by calling `try_lock()`). The function shall return before the absolute timeout (33.2.4) specified by `abs_time` only if it has obtained ownership of the mutex object. [*Note:* As with `try_lock()`, there is no guarantee that ownership will be obtained if the lock is available, but implementations are expected to make a strong effort to do so. — *end note*]

13 *Return type:* `bool`.

14 *Returns:* `true` if ownership was obtained, otherwise `false`.

15 *Synchronization:* If `try_lock_until()` returns `true`, prior `unlock()` operations on the same object synchronize with (4.7) this operation.

16 *Throws:* Timeout-related exceptions (33.2.4).

33.4.3.3.1 Class `timed_mutex`

[`thread.timedmutex.class`]

```
namespace std {
    class timed_mutex {
    public:
        timed_mutex();
        ~timed_mutex();

        timed_mutex(const timed_mutex&) = delete;
        timed_mutex& operator=(const timed_mutex&) = delete;

        void lock(); // blocking
        bool try_lock();
        template <class Rep, class Period>
            bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
        template <class Clock, class Duration>
```

```

        bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);
        void unlock();

        using native_handle_type = implementation-defined; // See 33.2.3
        native_handle_type native_handle(); // See 33.2.3
    };
}

```

- ¹ The class `timed_mutex` provides a non-recursive mutex with exclusive ownership semantics. If one thread owns a `timed_mutex` object, attempts by another thread to acquire ownership of that object will fail (for `try_lock()`) or block (for `lock()`, `try_lock_for()`, and `try_lock_until()`) until the owning thread has released ownership with a call to `unlock()` or the call to `try_lock_for()` or `try_lock_until()` times out (having failed to obtain ownership).
- ² The class `timed_mutex` shall satisfy all of the timed mutex requirements (33.4.3.3). It shall be a standard-layout class (Clause 12).
- ³ The behavior of a program is undefined if:
 - (3.1) — it destroys a `timed_mutex` object owned by any thread,
 - (3.2) — a thread that owns a `timed_mutex` object calls `lock()`, `try_lock()`, `try_lock_for()`, or `try_lock_until()` on that object, or
 - (3.3) — a thread terminates while owning a `timed_mutex` object.

33.4.3.3.2 Class `recursive_timed_mutex`

[thread.timedmutex.recursive]

```

namespace std {
    class recursive_timed_mutex {
    public:
        recursive_timed_mutex();
        ~recursive_timed_mutex();

        recursive_timed_mutex(const recursive_timed_mutex&) = delete;
        recursive_timed_mutex& operator=(const recursive_timed_mutex&) = delete;

        void lock(); // blocking
        bool try_lock() noexcept;
        template <class Rep, class Period>
            bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
        template <class Clock, class Duration>
            bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);
        void unlock();

        using native_handle_type = implementation-defined; // See 33.2.3
        native_handle_type native_handle(); // See 33.2.3
    };
}

```

- ¹ The class `recursive_timed_mutex` provides a recursive mutex with exclusive ownership semantics. If one thread owns a `recursive_timed_mutex` object, attempts by another thread to acquire ownership of that object will fail (for `try_lock()`) or block (for `lock()`, `try_lock_for()`, and `try_lock_until()`) until the owning thread has completely released ownership or the call to `try_lock_for()` or `try_lock_until()` times out (having failed to obtain ownership).
- ² The class `recursive_timed_mutex` shall satisfy all of the timed mutex requirements (33.4.3.3). It shall be a standard-layout class (Clause 12).
- ³ A thread that owns a `recursive_timed_mutex` object may acquire additional levels of ownership by calling

`lock()`, `try_lock()`, `try_lock_for()`, or `try_lock_until()` on that object. It is unspecified how many levels of ownership may be acquired by a single thread. If a thread has already acquired the maximum level of ownership for a `recursive_timed_mutex` object, additional calls to `try_lock()`, `try_lock_for()`, or `try_lock_until()` shall fail, and additional calls to `lock()` shall throw an exception of type `system_error`. A thread shall call `unlock()` once for each level of ownership acquired by calls to `lock()`, `try_lock()`, `try_lock_for()`, and `try_lock_until()`. Only when all levels of ownership have been released may ownership of the object be acquired by another thread.

4 The behavior of a program is undefined if:

- (4.1) — it destroys a `recursive_timed_mutex` object owned by any thread, or
- (4.2) — a thread terminates while owning a `recursive_timed_mutex` object.

33.4.3.4 Shared mutex types

[`thread.sharedmutex.requirements`]

1 The standard library types `shared_mutex` and `shared_timed_mutex` are *shared mutex types*. Shared mutex types shall meet the requirements of mutex types (33.4.3.2), and additionally shall meet the requirements set out below. In this description, `m` denotes an object of a shared mutex type.

2 In addition to the exclusive lock ownership mode specified in 33.4.3.2, shared mutex types provide a *shared lock* ownership mode. Multiple execution agents can simultaneously hold a shared lock ownership of a shared mutex type. But no execution agent shall hold a shared lock while another execution agent holds an exclusive lock on the same shared mutex type, and vice-versa. The maximum number of execution agents which can share a shared lock on a single shared mutex type is unspecified, but shall be at least 10000. If more than the maximum number of execution agents attempt to obtain a shared lock, the excess execution agents shall block until the number of shared locks are reduced below the maximum amount by other execution agents releasing their shared lock.

3 The expression `m.lock_shared()` shall be well-formed and have the following semantics:

4 *Requires:* The calling thread has no ownership of the mutex.

5 *Effects:* Blocks the calling thread until shared ownership of the mutex can be obtained for the calling thread. If an exception is thrown then a shared lock shall not have been acquired for the current thread.

6 *Postconditions:* The calling thread has a shared lock on the mutex.

7 *Return type:* `void`.

8 *Synchronization:* Prior `unlock()` operations on the same object shall synchronize with (4.7) this operation.

9 *Throws:* `system_error` when an exception is required (33.2.2).

10 *Error conditions:*

- (10.1) — `operation_not_permitted` — if the thread does not have the privilege to perform the operation.
- (10.2) — `resource_deadlock_would_occur` — if the implementation detects that a deadlock would occur.

11 The expression `m.unlock_shared()` shall be well-formed and have the following semantics:

12 *Requires:* The calling thread shall hold a shared lock on the mutex.

13 *Effects:* Releases a shared lock on the mutex held by the calling thread.

14 *Return type:* `void`.

15 *Synchronization:* This operation synchronizes with (4.7) subsequent `lock()` operations that obtain ownership on the same object.

16 *Throws:* Nothing.

17 The expression `m.try_lock_shared()` shall be well-formed and have the following semantics:

- 18 *Requires:* The calling thread has no ownership of the mutex.
- 19 *Effects:* Attempts to obtain shared ownership of the mutex for the calling thread without blocking. If shared ownership is not obtained, there is no effect and `try_lock_shared()` immediately returns. An implementation may fail to obtain the lock even if it is not held by any other thread.
- 20 *Return type:* `bool`.
- 21 *Returns:* `true` if the shared ownership lock was acquired, `false` otherwise.
- 22 *Synchronization:* If `try_lock_shared()` returns `true`, prior `unlock()` operations on the same object synchronize with (4.7) this operation.
- 23 *Throws:* Nothing.

33.4.3.4.1 Class `shared_mutex`

[`thread.sharedmutex.class`]

```
namespace std {
    class shared_mutex {
    public:
        shared_mutex();
        ~shared_mutex();

        shared_mutex(const shared_mutex&) = delete;
        shared_mutex& operator=(const shared_mutex&) = delete;

        // Exclusive ownership
        void lock(); // blocking
        bool try_lock();
        void unlock();

        // Shared ownership
        void lock_shared(); // blocking
        bool try_lock_shared();
        void unlock_shared();

        using native_handle_type = implementation-defined; // See 33.2.3
        native_handle_type native_handle(); // See 33.2.3
    };
}
```

- 1 The class `shared_mutex` provides a non-recursive mutex with shared ownership semantics.
- 2 The class `shared_mutex` shall satisfy all of the shared mutex requirements (33.4.3.4). It shall be a standard-layout class (Clause 12).
- 3 The behavior of a program is undefined if:
- (3.1) — it destroys a `shared_mutex` object owned by any thread,
 - (3.2) — a thread attempts to recursively gain any ownership of a `shared_mutex`, or
 - (3.3) — a thread terminates while possessing any ownership of a `shared_mutex`.
- 4 `shared_mutex` may be a synonym for `shared_timed_mutex`.

33.4.3.5 Shared timed mutex types

[`thread.sharedtimedmutex.requirements`]

- 1 The standard library type `shared_timed_mutex` is a *shared timed mutex type*. Shared timed mutex types shall meet the requirements of timed mutex types (33.4.3.3), shared mutex types (33.4.3.4), and additionally shall meet the requirements set out below. In this description, `m` denotes an object of a shared timed mutex type, `rel_type` denotes an object of an instantiation of `duration` (23.17.5), and `abs_time` denotes an object

of an instantiation of `time_point` (23.17.6).

2 The expression `m.try_lock_shared_for(rel_time)` shall be well-formed and have the following semantics:

3 *Requires:* The calling thread has no ownership of the mutex.

4 *Effects:* Attempts to obtain shared lock ownership for the calling thread within the relative timeout (33.2.4) specified by `rel_time`. If the time specified by `rel_time` is less than or equal to `rel_time.zero()`, the function attempts to obtain ownership without blocking (as if by calling `try_lock_shared()`). The function shall return within the timeout specified by `rel_time` only if it has obtained shared ownership of the mutex object. [*Note:* As with `try_lock()`, there is no guarantee that ownership will be obtained if the lock is available, but implementations are expected to make a strong effort to do so. — *end note*] If an exception is thrown then a shared lock shall not have been acquired for the current thread.

5 *Return type:* `bool`.

6 *Returns:* `true` if the shared lock was acquired, `false` otherwise.

7 *Synchronization:* If `try_lock_shared_for()` returns `true`, prior `unlock()` operations on the same object synchronize with (4.7) this operation.

8 *Throws:* Timeout-related exceptions (33.2.4).

9 The expression `m.try_lock_shared_until(abs_time)` shall be well-formed and have the following semantics:

10 *Requires:* The calling thread has no ownership of the mutex.

11 *Effects:* The function attempts to obtain shared ownership of the mutex. If `abs_time` has already passed, the function attempts to obtain shared ownership without blocking (as if by calling `try_lock_shared()`). The function shall return before the absolute timeout (33.2.4) specified by `abs_time` only if it has obtained shared ownership of the mutex object. [*Note:* As with `try_lock()`, there is no guarantee that ownership will be obtained if the lock is available, but implementations are expected to make a strong effort to do so. — *end note*] If an exception is thrown then a shared lock shall not have been acquired for the current thread.

12 *Return type:* `bool`.

13 *Returns:* `true` if the shared lock was acquired, `false` otherwise.

14 *Synchronization:* If `try_lock_shared_until()` returns `true`, prior `unlock()` operations on the same object synchronize with (4.7) this operation.

15 *Throws:* Timeout-related exceptions (33.2.4).

33.4.3.5.1 Class `shared_timed_mutex`

[`thread.sharedtimedmutex.class`]

```
namespace std {
    class shared_timed_mutex {
    public:
        shared_timed_mutex();
        ~shared_timed_mutex();

        shared_timed_mutex(const shared_timed_mutex&) = delete;
        shared_timed_mutex& operator=(const shared_timed_mutex&) = delete;

        // Exclusive ownership
        void lock(); // blocking
        bool try_lock();
        template <class Rep, class Period>
            bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
        template <class Clock, class Duration>
```

```

    bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);
    void unlock();

    // Shared ownership
    void lock_shared(); // blocking
    bool try_lock_shared();
    template <class Rep, class Period>
        bool
            try_lock_shared_for(const chrono::duration<Rep, Period>& rel_time);
    template <class Clock, class Duration>
        bool
            try_lock_shared_until(const chrono::time_point<Clock, Duration>& abs_time);
    void unlock_shared();
};
}

```

- ¹ The class `shared_timed_mutex` provides a non-recursive mutex with shared ownership semantics.
- ² The class `shared_timed_mutex` shall satisfy all of the shared timed mutex requirements (33.4.3.5). It shall be a standard-layout class (Clause 12).
- ³ The behavior of a program is undefined if:
 - (3.1) — it destroys a `shared_timed_mutex` object owned by any thread,
 - (3.2) — a thread attempts to recursively gain any ownership of a `shared_timed_mutex`, or
 - (3.3) — a thread terminates while possessing any ownership of a `shared_timed_mutex`.

33.4.4 Locks

[thread.lock]

- ¹ A *lock* is an object that holds a reference to a lockable object and may unlock the lockable object during the lock's destruction (such as when leaving block scope). An execution agent may use a lock to aid in managing ownership of a lockable object in an exception safe manner. A lock is said to *own* a lockable object if it is currently managing the ownership of that lockable object for an execution agent. A lock does not manage the lifetime of the lockable object it references. [*Note*: Locks are intended to ease the burden of unlocking the lockable object under both normal and exceptional circumstances. — *end note*]
- ² Some lock constructors take tag types which describe what should be done with the lockable object during the lock's construction.

```

namespace std {
    struct defer_lock_t { }; // do not acquire ownership of the mutex
    struct try_to_lock_t { }; // try to acquire ownership of the mutex
                                // without blocking
    struct adopt_lock_t { }; // assume the calling thread has already
                                // obtained mutex ownership and manage it

    inline constexpr defer_lock_t defer_lock { };
    inline constexpr try_to_lock_t try_to_lock { };
    inline constexpr adopt_lock_t adopt_lock { };
}

```

33.4.4.1 Class template `lock_guard`

[thread.lock.guard]

```

namespace std {
    template <class Mutex>
    class lock_guard {
    public:
        using mutex_type = Mutex;
    };
}

```

```

    explicit lock_guard(mutex_type& m);
    lock_guard(mutex_type& m, adopt_lock_t);
    ~lock_guard();

    lock_guard(const lock_guard&) = delete;
    lock_guard& operator=(const lock_guard&) = delete;

private:
    mutex_type& pm; // exposition only
};

template<class Mutex> lock_guard(lock_guard<Mutex>) -> lock_guard<Mutex>;
}

```

- ¹ An object of type `lock_guard` controls the ownership of a lockable object within a scope. A `lock_guard` object maintains ownership of a lockable object throughout the `lock_guard` object's lifetime (6.8). The behavior of a program is undefined if the lockable object referenced by `pm` does not exist for the entire lifetime of the `lock_guard` object. The supplied `Mutex` type shall meet the `BasicLockable` requirements (33.2.5.2).

```
explicit lock_guard(mutex_type& m);
```

- ² *Requires:* If `mutex_type` is not a recursive mutex, the calling thread does not own the mutex `m`.
³ *Effects:* As if by `m.lock()`.
⁴ *Postconditions:* `&pm == &m`

```
lock_guard(mutex_type& m, adopt_lock_t);
```

- ⁵ *Requires:* The calling thread owns the mutex `m`.
⁶ *Postconditions:* `&pm == &m`
⁷ *Throws:* Nothing.

```
~lock_guard();
```

- ⁸ *Effects:* As if by `pm.unlock()`.

33.4.4.2 Class template `scoped_lock`

[thread.lock.scoped]

```

namespace std {
    template <class... MutexTypes>
    class scoped_lock {
    public:
        using mutex_type = Mutex; // If MutexTypes... consists of the single type Mutex

        explicit scoped_lock(MutexTypes&... m);
        explicit scoped_lock(MutexTypes&... m, adopt_lock_t);
        ~scoped_lock();

        scoped_lock(const scoped_lock&) = delete;
        scoped_lock& operator=(const scoped_lock&) = delete;

    private:
        tuple<MutexTypes&...> pm; // exposition only
    };

    template<class... MutexTypes>

```



```

        scoped_lock(scoped_lock<MutexTypes...>) -> scoped_lock<MutexTypes...>;
    }

```

- ¹ An object of type `scoped_lock` controls the ownership of lockable objects within a scope. A `scoped_lock` object maintains ownership of lockable objects throughout the `scoped_lock` object's lifetime (6.8). The behavior of a program is undefined if the lockable objects referenced by `pm` do not exist for the entire lifetime of the `scoped_lock` object. When `sizeof...(MutexTypes)` is 1, the supplied `Mutex` type shall meet the `BasicLockable` requirements (33.2.5.2). Otherwise, each of the mutex types shall meet the `Lockable` requirements (33.2.5.3).

```
explicit scoped_lock(MutexTypes&... m);
```

- ² *Requires:* If a `MutexTypes` type is not a recursive mutex, the calling thread does not own the corresponding mutex element of `m`.
- ³ *Effects:* Initializes `pm` with `tie(m...)`. Then if `sizeof...(MutexTypes)` is 0, no effects. Otherwise if `sizeof...(MutexTypes)` is 1, then `m.lock()`. Otherwise, `lock(m...)`.

```
explicit scoped_lock(MutexTypes&... m, adopt_lock_t);
```

- ⁴ *Requires:* The calling thread owns all the mutexes in `m`.
- ⁵ *Effects:* Initializes `pm` with `tie(m...)`.
- ⁶ *Throws:* Nothing.

```
~scoped_lock();
```

- ⁷ *Effects:* For all `i` in `[0, sizeof...(MutexTypes))`, `get<i>(pm).unlock()`.

33.4.4.3 Class template `unique_lock`

[thread.lock.unique]

```

namespace std {
    template <class Mutex>
    class unique_lock {
    public:
        using mutex_type = Mutex;

        // 33.4.4.3.1, construct/copy/destroy
        unique_lock() noexcept;
        explicit unique_lock(mutex_type& m);
        unique_lock(mutex_type& m, defer_lock_t) noexcept;
        unique_lock(mutex_type& m, try_to_lock_t);
        unique_lock(mutex_type& m, adopt_lock_t);
        template <class Clock, class Duration>
            unique_lock(mutex_type& m, const chrono::time_point<Clock, Duration>& abs_time);
        template <class Rep, class Period>
            unique_lock(mutex_type& m, const chrono::duration<Rep, Period>& rel_time);
        ~unique_lock();

        unique_lock(const unique_lock&) = delete;
        unique_lock& operator=(const unique_lock&) = delete;

        unique_lock(unique_lock&& u) noexcept;
        unique_lock& operator=(unique_lock&& u);

        // 33.4.4.3.2, locking
        void lock();
        bool try_lock();

```

```

template <class Rep, class Period>
    bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
template <class Clock, class Duration>
    bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);

void unlock();

// 33.4.4.3.3, modifiers
void swap(unique_lock& u) noexcept;
mutex_type* release() noexcept;

// 33.4.4.3.4, observers
bool owns_lock() const noexcept;
explicit operator bool () const noexcept;
mutex_type* mutex() const noexcept;

private:
    mutex_type* pm; // exposition only
    bool owns;      // exposition only
};

template<class Mutex> unique_lock(unique_lock<Mutex>) -> unique_lock<Mutex>;

template <class Mutex>
    void swap(unique_lock<Mutex>& x, unique_lock<Mutex>& y) noexcept;
}

```

- ¹ An object of type `unique_lock` controls the ownership of a lockable object within a scope. Ownership of the lockable object may be acquired at construction or after construction, and may be transferred, after acquisition, to another `unique_lock` object. Objects of type `unique_lock` are not copyable but are movable. The behavior of a program is undefined if the contained pointer `pm` is not null and the lockable object pointed to by `pm` does not exist for the entire remaining lifetime (6.8) of the `unique_lock` object. The supplied `Mutex` type shall meet the `BasicLockable` requirements (33.2.5.2).
- ² [*Note:* `unique_lock<Mutex>` meets the `BasicLockable` requirements. If `Mutex` meets the `Lockable` requirements (33.2.5.3), `unique_lock<Mutex>` also meets the `Lockable` requirements; if `Mutex` meets the `TimedLockable` requirements (33.2.5.4), `unique_lock<Mutex>` also meets the `TimedLockable` requirements. — end note]

33.4.4.3.1 `unique_lock` constructors, destructor, and assignment [thread.lock.unique.cons]

```
unique_lock() noexcept;
```

- ¹ *Effects:* Constructs an object of type `unique_lock`.

- ² *Postconditions:* `pm == 0` and `owns == false`.

```
explicit unique_lock(mutex_type& m);
```

- ³ *Requires:* If `mutex_type` is not a recursive mutex the calling thread does not own the mutex.

- ⁴ *Effects:* Constructs an object of type `unique_lock` and calls `m.lock()`.

- ⁵ *Postconditions:* `pm == addressof(m)` and `owns == true`.

```
unique_lock(mutex_type& m, defer_lock_t) noexcept;
```

- ⁶ *Effects:* Constructs an object of type `unique_lock`.

- ⁷ *Postconditions:* `pm == addressof(m)` and `owns == false`.

```
unique_lock(mutex_type& m, try_to_lock_t);
```

8 *Requires:* The supplied `Mutex` type shall meet the `Lockable` requirements (33.2.5.3). If `mutex_type` is not a recursive mutex the calling thread does not own the mutex.

9 *Effects:* Constructs an object of type `unique_lock` and calls `m.try_lock()`.

10 *Postconditions:* `pm == addressof(m)` and `owns == res`, where `res` is the value returned by the call to `m.try_lock()`.

```
unique_lock(mutex_type& m, adopt_lock_t);
```

11 *Requires:* The calling thread owns the mutex.

12 *Effects:* Constructs an object of type `unique_lock`.

13 *Postconditions:* `pm == addressof(m)` and `owns == true`.

14 *Throws:* Nothing.

```
template <class Clock, class Duration>
```

```
unique_lock(mutex_type& m, const chrono::time_point<Clock, Duration>& abs_time);
```

15 *Requires:* If `mutex_type` is not a recursive mutex the calling thread does not own the mutex. The supplied `Mutex` type shall meet the `TimedLockable` requirements (33.2.5.4).

16 *Effects:* Constructs an object of type `unique_lock` and calls `m.try_lock_until(abs_time)`.

17 *Postconditions:* `pm == addressof(m)` and `owns == res`, where `res` is the value returned by the call to `m.try_lock_until(abs_time)`.

```
template <class Rep, class Period>
```

```
unique_lock(mutex_type& m, const chrono::duration<Rep, Period>& rel_time);
```

18 *Requires:* If `mutex_type` is not a recursive mutex the calling thread does not own the mutex. The supplied `Mutex` type shall meet the `TimedLockable` requirements (33.2.5.4).

19 *Effects:* Constructs an object of type `unique_lock` and calls `m.try_lock_for(rel_time)`.

20 *Postconditions:* `pm == addressof(m)` and `owns == res`, where `res` is the value returned by the call to `m.try_lock_for(rel_time)`.

```
unique_lock(unique_lock&& u) noexcept;
```

21 *Postconditions:* `pm == u_p.pm` and `owns == u_p.owns` (where `u_p` is the state of `u` just prior to this construction), `u.pm == 0` and `u.owns == false`.

```
unique_lock& operator=(unique_lock&& u);
```

22 *Effects:* If `owns` calls `pm->unlock()`.

23 *Postconditions:* `pm == u_p.pm` and `owns == u_p.owns` (where `u_p` is the state of `u` just prior to this construction), `u.pm == 0` and `u.owns == false`.

24 [*Note:* With a recursive mutex it is possible for both `*this` and `u` to own the same mutex before the assignment. In this case, `*this` will own the mutex after the assignment and `u` will not. — *end note*]

25 *Throws:* Nothing.

```
~unique_lock();
```

26 *Effects:* If `owns` calls `pm->unlock()`.

33.4.4.3.2 unique_lock locking

[thread.lock.unique.locking]

```
void lock();
```

1 *Effects:* As if by `pm->lock()`.

2 *Postconditions:* `owns == true`.

3 *Throws:* Any exception thrown by `pm->lock()`. `system_error` when an exception is required (33.2.2).

4 *Error conditions:*

(4.1) — `operation_not_permitted` — if `pm` is `nullptr`.

(4.2) — `resource_deadlock_would_occur` — if on entry `owns` is `true`.

`bool try_lock();`

5 *Requires:* The supplied `Mutex` shall meet the `Lockable` requirements (33.2.5.3).

6 *Effects:* As if by `pm->try_lock()`.

7 *Returns:* The value returned by the call to `try_lock()`.

8 *Postconditions:* `owns == res`, where `res` is the value returned by the call to `try_lock()`.

9 *Throws:* Any exception thrown by `pm->try_lock()`. `system_error` when an exception is required (33.2.2).

10 *Error conditions:*

(10.1) — `operation_not_permitted` — if `pm` is `nullptr`.

(10.2) — `resource_deadlock_would_occur` — if on entry `owns` is `true`.

`template <class Clock, class Duration>`
 `bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);`

11 *Requires:* The supplied `Mutex` type shall meet the `TimedLockable` requirements (33.2.5.4).

12 *Effects:* As if by `pm->try_lock_until(abs_time)`.

13 *Returns:* The value returned by the call to `try_lock_until(abs_time)`.

14 *Postconditions:* `owns == res`, where `res` is the value returned by the call to `try_lock_until(abs_time)`.

15 *Throws:* Any exception thrown by `pm->try_lock_until()`. `system_error` when an exception is required (33.2.2).

16 *Error conditions:*

(16.1) — `operation_not_permitted` — if `pm` is `nullptr`.

(16.2) — `resource_deadlock_would_occur` — if on entry `owns` is `true`.

`template <class Rep, class Period>`
 `bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);`

17 *Requires:* The supplied `Mutex` type shall meet the `TimedLockable` requirements (33.2.5.4).

18 *Effects:* As if by `pm->try_lock_for(rel_time)`.

19 *Returns:* The value returned by the call to `try_lock_for(rel_time)`.

20 *Postconditions:* `owns == res`, where `res` is the value returned by the call to `try_lock_for(rel_time)`.

21 *Throws:* Any exception thrown by `pm->try_lock_for()`. `system_error` when an exception is required (33.2.2).

22 *Error conditions:*

(22.1) — `operation_not_permitted` — if `pm` is `nullptr`.

(22.2) — `resource_deadlock_would_occur` — if on entry `owns` is `true`.

`void unlock();`

23 *Effects:* As if by `pm->unlock()`.

24 *Postconditions:* `owns == false`.

25 *Throws:* `system_error` when an exception is required (33.2.2).

26 *Error conditions:*

(26.1) — `operation_not_permitted` — if on entry `owns` is `false`.

33.4.4.3.3 `unique_lock` modifiers

[thread.lock.unique.mod]

`void swap(unique_lock& u) noexcept;`

1 *Effects:* Swaps the data members of `*this` and `u`.

`mutex_type* release() noexcept;`

2 *Returns:* The previous value of `pm`.

3 *Postconditions:* `pm == 0` and `owns == false`.

`template <class Mutex>`

`void swap(unique_lock<Mutex>& x, unique_lock<Mutex>& y) noexcept;`

4 *Effects:* As if by `x.swap(y)`.

33.4.4.3.4 `unique_lock` observers

[thread.lock.unique.obs]

`bool owns_lock() const noexcept;`

1 *Returns:* `owns`.

`explicit operator bool() const noexcept;`

2 *Returns:* `owns`.

`mutex_type *mutex() const noexcept;`

3 *Returns:* `pm`.

33.4.4.4 Class template `shared_lock`

[thread.lock.shared]

`namespace std {`

`template <class Mutex>`

`class shared_lock {`

`public:`

`using mutex_type = Mutex;`

// 33.4.4.4.1, construct/copy/destroy

`shared_lock() noexcept;`

`explicit shared_lock(mutex_type& m); // blocking`

`shared_lock(mutex_type& m, defer_lock_t) noexcept;`

`shared_lock(mutex_type& m, try_to_lock_t);`

`shared_lock(mutex_type& m, adopt_lock_t);`

`template <class Clock, class Duration>`

`shared_lock(mutex_type& m,`

`const chrono::time_point<Clock, Duration>& abs_time);`

`template <class Rep, class Period>`

`shared_lock(mutex_type& m,`

```

        const chrono::duration<Rep, Period>& rel_time);
~shared_lock();

shared_lock(const shared_lock&) = delete;
shared_lock& operator=(const shared_lock&) = delete;

shared_lock(shared_lock&& u) noexcept;
shared_lock& operator=(shared_lock&& u) noexcept;

// 33.4.4.4.2, locking
void lock(); // blocking
bool try_lock();
template <class Rep, class Period>
    bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
template <class Clock, class Duration>
    bool try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);
void unlock();

// 33.4.4.4.3, modifiers
void swap(shared_lock& u) noexcept;
mutex_type* release() noexcept;

// 33.4.4.4.4, observers
bool owns_lock() const noexcept;
explicit operator bool () const noexcept;
mutex_type* mutex() const noexcept;

private:
    mutex_type* pm; // exposition only
    bool owns;      // exposition only
};

template<class Mutex> shared_lock(shared_lock<Mutex>) -> shared_lock<Mutex>;

template <class Mutex>
    void swap(shared_lock<Mutex>& x, shared_lock<Mutex>& y) noexcept;
}

```

- ¹ An object of type `shared_lock` controls the shared ownership of a lockable object within a scope. Shared ownership of the lockable object may be acquired at construction or after construction, and may be transferred, after acquisition, to another `shared_lock` object. Objects of type `shared_lock` are not copyable but are movable. The behavior of a program is undefined if the contained pointer `pm` is not null and the lockable object pointed to by `pm` does not exist for the entire remaining lifetime (6.8) of the `shared_lock` object. The supplied `Mutex` type shall meet the shared mutex requirements (33.4.3.5).

- ² [*Note:* `shared_lock<Mutex>` meets the `TimedLockable` requirements (33.2.5.4). — *end note*]

33.4.4.4.1 `shared_lock` constructors, destructor, and assignment [thread.lock.shared.cons]

```
shared_lock() noexcept;
```

- ¹ *Effects:* Constructs an object of type `shared_lock`.

- ² *Postconditions:* `pm == nullptr` and `owns == false`.

```
explicit shared_lock(mutex_type& m);
```

- ³ *Requires:* The calling thread does not own the mutex for any ownership mode.

4 *Effects:* Constructs an object of type `shared_lock` and calls `m.lock_shared()`.

5 *Postconditions:* `pm == addressof(m)` and `owns == true`.

`shared_lock(mutex_type& m, defer_lock_t) noexcept;`

6 *Effects:* Constructs an object of type `shared_lock`.

7 *Postconditions:* `pm == addressof(m)` and `owns == false`.

`shared_lock(mutex_type& m, try_to_lock_t);`

8 *Requires:* The calling thread does not own the mutex for any ownership mode.

9 *Effects:* Constructs an object of type `shared_lock` and calls `m.try_lock_shared()`.

10 *Postconditions:* `pm == addressof(m)` and `owns == res` where `res` is the value returned by the call to `m.try_lock_shared()`.

`shared_lock(mutex_type& m, adopt_lock_t);`

11 *Requires:* The calling thread has shared ownership of the mutex.

12 *Effects:* Constructs an object of type `shared_lock`.

13 *Postconditions:* `pm == addressof(m)` and `owns == true`.

`template <class Clock, class Duration>`
 `shared_lock(mutex_type& m,`
 `const chrono::time_point<Clock, Duration>& abs_time);`

14 *Requires:* The calling thread does not own the mutex for any ownership mode.

15 *Effects:* Constructs an object of type `shared_lock` and calls `m.try_lock_shared_until(abs_time)`.

16 *Postconditions:* `pm == addressof(m)` and `owns == res` where `res` is the value returned by the call to `m.try_lock_shared_until(abs_time)`.

`template <class Rep, class Period>`
 `shared_lock(mutex_type& m,`
 `const chrono::duration<Rep, Period>& rel_time);`

17 *Requires:* The calling thread does not own the mutex for any ownership mode.

18 *Effects:* Constructs an object of type `shared_lock` and calls `m.try_lock_shared_for(rel_time)`.

19 *Postconditions:* `pm == addressof(m)` and `owns == res` where `res` is the value returned by the call to `m.try_lock_shared_for(rel_time)`.

`~shared_lock();`

20 *Effects:* If `owns` calls `pm->unlock_shared()`.

`shared_lock(shared_lock&& sl) noexcept;`

21 *Postconditions:* `pm == sl.p.pm` and `owns == sl.p.owns` (where `sl_p` is the state of `sl` just prior to this construction), `sl.pm == nullptr` and `sl.owns == false`.

`shared_lock& operator=(shared_lock&& sl) noexcept;`

22 *Effects:* If `owns` calls `pm->unlock_shared()`.

23 *Postconditions:* `pm == sl.p.pm` and `owns == sl.p.owns` (where `sl_p` is the state of `sl` just prior to this assignment), `sl.pm == nullptr` and `sl.owns == false`.

33.4.4.4.2 `shared_lock` locking

[thread.lock.shared.locking]

```

void lock();
1      Effects: As if by pm->lock_shared().
2      Postconditions: owns == true.
3      Throws: Any exception thrown by pm->lock_shared(). system_error when an exception is re-
        quired (33.2.2).
4      Error conditions:
(4.1)    — operation_not_permitted — if pm is nullptr.
(4.2)    — resource_deadlock_would_occur — if on entry owns is true.

bool try_lock();
5      Effects: As if by pm->try_lock_shared().
6      Returns: The value returned by the call to pm->try_lock_shared().
7      Postconditions: owns == res, where res is the value returned by the call to pm->try_lock_shared().
8      Throws: Any exception thrown by pm->try_lock_shared(). system_error when an exception is
        required (33.2.2).
9      Error conditions:
(9.1)    — operation_not_permitted — if pm is nullptr.
(9.2)    — resource_deadlock_would_occur — if on entry owns is true.

template <class Clock, class Duration>
    bool
    try_lock_until(const chrono::time_point<Clock, Duration>& abs_time);
10     Effects: As if by pm->try_lock_shared_until(abs_time).
11     Returns: The value returned by the call to pm->try_lock_shared_until(abs_time).
12     Postconditions: owns == res, where res is the value returned by the call to pm->try_lock_shared_-
        until(abs_time).
13     Throws: Any exception thrown by pm->try_lock_shared_until(abs_time). system_error when an
        exception is required (33.2.2).
14     Error conditions:
(14.1)   — operation_not_permitted — if pm is nullptr.
(14.2)   — resource_deadlock_would_occur — if on entry owns is true.

template <class Rep, class Period>
    bool try_lock_for(const chrono::duration<Rep, Period>& rel_time);
15     Effects: As if by pm->try_lock_shared_for(rel_time).
16     Returns: The value returned by the call to pm->try_lock_shared_for(rel_time).
17     Postconditions: owns == res, where res is the value returned by the call to pm->try_lock_shared_-
        for(rel_time).
18     Throws: Any exception thrown by pm->try_lock_shared_for(rel_time). system_error when an
        exception is required (33.2.2).
19     Error conditions:
(19.1)   — operation_not_permitted — if pm is nullptr.

```


(19.2) — resource_deadlock_would_occur — if on entry owns is true.

void unlock();

20 *Effects:* As if by pm->unlock_shared().

21 *Postconditions:* owns == false.

22 *Throws:* system_error when an exception is required (33.2.2).

23 *Error conditions:*

(23.1) — operation_not_permitted — if on entry owns is false.

33.4.4.4.3 shared_lock modifiers

[thread.lock.shared.mod]

void swap(shared_lock& sl) noexcept;

1 *Effects:* Swaps the data members of *this and sl.

mutex_type* release() noexcept;

2 *Returns:* The previous value of pm.

3 *Postconditions:* pm == nullptr and owns == false.

template <class Mutex>

void swap(shared_lock<Mutex>& x, shared_lock<Mutex>& y) noexcept;

4 *Effects:* As if by x.swap(y).

33.4.4.4.4 shared_lock observers

[thread.lock.shared.obs]

bool owns_lock() const noexcept;

1 *Returns:* owns.

explicit operator bool() const noexcept;

2 *Returns:* owns.

mutex_type* mutex() const noexcept;

3 *Returns:* pm.

33.4.5 Generic locking algorithms

[thread.lock.algorithm]

template <class L1, class L2, class... L3> int try_lock(L1&, L2&, L3&...);

1 *Requires:* Each template parameter type shall meet the Lockable requirements. [*Note:* The unique_lock class template meets these requirements when suitably instantiated. — end note]

2 *Effects:* Calls try_lock() for each argument in order beginning with the first until all arguments have been processed or a call to try_lock() fails, either by returning false or by throwing an exception. If a call to try_lock() fails, unlock() shall be called for all prior arguments and there shall be no further calls to try_lock().

3 *Returns:* -1 if all calls to try_lock() returned true, otherwise a zero-based index value that indicates the argument for which try_lock() returned false.

template <class L1, class L2, class... L3> void lock(L1&, L2&, L3&...);

4 *Requires:* Each template parameter type shall meet the Lockable requirements, [*Note:* The unique_lock class template meets these requirements when suitably instantiated. — end note]

- 5 *Effects:* All arguments are locked via a sequence of calls to `lock()`, `try_lock()`, or `unlock()` on each argument. The sequence of calls shall not result in deadlock, but is otherwise unspecified. [*Note:* A deadlock avoidance algorithm such as try-and-back-off must be used, but the specific algorithm is not specified to avoid over-constraining implementations. — *end note*] If a call to `lock()` or `try_lock()` throws an exception, `unlock()` shall be called for any argument that had been locked by a call to `lock()` or `try_lock()`.

33.4.6 Call once

[thread.once]

33.4.6.1 Struct `once_flag`

[thread.once.onceflag]

```
namespace std {
    struct once_flag {
        constexpr once_flag() noexcept;

        once_flag(const once_flag&) = delete;
        once_flag& operator=(const once_flag&) = delete;
    };
}
```

- 1 The class `once_flag` is an opaque data structure that `call_once` uses to initialize data without causing a data race or deadlock.

```
constexpr once_flag() noexcept;
```

- 2 *Effects:* Constructs an object of type `once_flag`.
- 3 *Synchronization:* The construction of a `once_flag` object is not synchronized.
- 4 *Postconditions:* The object's internal state is set to indicate to an invocation of `call_once` with the object as its initial argument that no function has been called.

33.4.6.2 Function `call_once`

[thread.once.callonce]

```
template<class Callable, class... Args>
void call_once(once_flag& flag, Callable&& func, Args&&... args);
```

- 1 *Requires:*
- `INVOKE(std::forward<Callable>(func), std::forward<Args>(args)...) (see 23.14.3)` shall be a valid expression.
- 2 *Effects:* An execution of `call_once` that does not call its `func` is a *passive* execution. An execution of `call_once` that calls its `func` is an *active* execution. An active execution shall call `INVOKE(std::forward<Callable>(func), std::forward<Args>(args)...) (see 23.14.3)`. If such a call to `func` throws an exception the execution is *exceptional*, otherwise it is *returning*. An exceptional execution shall propagate the exception to the caller of `call_once`. Among all executions of `call_once` for any given `once_flag`: at most one shall be a returning execution; if there is a returning execution, it shall be the last active execution; and there are passive executions only if there is a returning execution. [*Note:* Passive executions allow other threads to reliably observe the results produced by the earlier returning execution. — *end note*]
- 3 *Synchronization:* For any given `once_flag`: all active executions occur in a total order; completion of an active execution synchronizes with (4.7) the start of the next one in this total order; and the returning execution synchronizes with the return from all passive executions.
- 4 *Throws:* `system_error` when an exception is required (33.2.2), or any exception thrown by `func`.
- 5 [*Example:*
- `// global flag, regular function`

```

void init();
std::once_flag flag;

void f() {
    std::call_once(flag, init);
}

// function static flag, function object
struct initializer {
    void operator()();
};

void g() {
    static std::once_flag flag2;
    std::call_once(flag2, initializer());
}

// object flag, member function
class information {
    std::once_flag verified;
    void verifier();
public:
    void verify() { std::call_once(verified, &information::verifier, *this); }
};
— end example]

```

33.5 Condition variables

[thread.condition]

- ¹ Condition variables provide synchronization primitives used to block a thread until notified by some other thread that some condition is met or until a system time is reached. Class `condition_variable` provides a condition variable that can only wait on an object of type `unique_lock<mutex>`, allowing maximum efficiency on some platforms. Class `condition_variable_any` provides a general condition variable that can wait on objects of user-supplied lock types.
- ² Condition variables permit concurrent invocation of the `wait`, `wait_for`, `wait_until`, `notify_one` and `notify_all` member functions.
- ³ The execution of `notify_one` and `notify_all` shall be atomic. The execution of `wait`, `wait_for`, and `wait_until` shall be performed in three atomic parts:
 1. the release of the mutex and entry into the waiting state;
 2. the unblocking of the wait; and
 3. the reacquisition of the lock.
- ⁴ The implementation shall behave as if all executions of `notify_one`, `notify_all`, and each part of the `wait`, `wait_for`, and `wait_until` executions are executed in a single unspecified total order consistent with the "happens before" order.
- ⁵ Condition variable construction and destruction need not be synchronized.

33.5.1 Header `<condition_variable>` synopsis

[condition_variable.syn]

```

namespace std {
    class condition_variable;
    class condition_variable_any;

    void notify_all_at_thread_exit(condition_variable& cond, unique_lock<mutex> lk);

```

```
enum class cv_status { no_timeout, timeout };
}
```

33.5.2 Non-member functions

[thread.condition.nonmember]

```
void notify_all_at_thread_exit(condition_variable& cond, unique_lock<mutex> lk);
```

- 1 *Requires:* lk is locked by the calling thread and either
 - (1.1) — no other thread is waiting on cond, or
 - (1.2) — lk.mutex() returns the same value for each of the lock arguments supplied by all concurrently waiting (via wait, wait_for, or wait_until) threads.
- 2 *Effects:* Transfers ownership of the lock associated with lk into internal storage and schedules cond to be notified when the current thread exits, after all objects of thread storage duration associated with the current thread have been destroyed. This notification shall be as if:


```
lk.unlock();
cond.notify_all();
```
- 3 *Synchronization:* The implied lk.unlock() call is sequenced after the destruction of all objects with thread storage duration associated with the current thread.
- 4 [*Note:* The supplied lock will be held until the thread exits, and care must be taken to ensure that this does not cause deadlock due to lock ordering issues. After calling notify_all_at_thread_exit it is recommended that the thread should be exited as soon as possible, and that no blocking or time-consuming tasks are run on that thread. — end note]
- 5 [*Note:* It is the user's responsibility to ensure that waiting threads do not erroneously assume that the thread has finished if they experience spurious wakeups. This typically requires that the condition being waited for is satisfied while holding the lock on lk, and that this lock is not released and reacquired prior to calling notify_all_at_thread_exit. — end note]

33.5.3 Class condition_variable

[thread.condition.condvar]

```
namespace std {
class condition_variable {
public:

condition_variable();
~condition_variable();

condition_variable(const condition_variable&) = delete;
condition_variable& operator=(const condition_variable&) = delete;

void notify_one() noexcept;
void notify_all() noexcept;
void wait(unique_lock<mutex>& lock);
template <class Predicate>
void wait(unique_lock<mutex>& lock, Predicate pred);
template <class Clock, class Duration>
cv_status wait_until(unique_lock<mutex>& lock,
                    const chrono::time_point<Clock, Duration>& abs_time);
template <class Clock, class Duration, class Predicate>
bool wait_until(unique_lock<mutex>& lock,
                const chrono::time_point<Clock, Duration>& abs_time,
                Predicate pred);
```

```

template <class Rep, class Period>
    cv_status wait_for(unique_lock<mutex>& lock,
                      const chrono::duration<Rep, Period>& rel_time);
template <class Rep, class Period, class Predicate>
    bool wait_for(unique_lock<mutex>& lock,
                  const chrono::duration<Rep, Period>& rel_time,
                  Predicate pred);

using native_handle_type = implementation-defined; // See 33.2.3
native_handle_type native_handle();                // See 33.2.3
};
}

```

- 1 The class `condition_variable` shall be a standard-layout class (Clause 12).

```
condition_variable();
```

- 2 *Effects:* Constructs an object of type `condition_variable`.

- 3 *Throws:* `system_error` when an exception is required (33.2.2).

- 4 *Error conditions:*

- (4.1) — `resource_unavailable_try_again` — if some non-memory resource limitation prevents initialization.

```
~condition_variable();
```

- 5 *Requires:* There shall be no thread blocked on `*this`. [*Note:* That is, all threads shall have been notified; they may subsequently block on the lock specified in the wait. This relaxes the usual rules, which would have required all wait calls to happen before destruction. Only the notification to unblock the wait must happen before destruction. The user must take care to ensure that no threads wait on `*this` once the destructor has been started, especially when the waiting threads are calling the wait functions in a loop or using the overloads of `wait`, `wait_for`, or `wait_until` that take a predicate. — *end note*]

- 6 *Effects:* Destroys the object.

```
void notify_one() noexcept;
```

- 7 *Effects:* If any threads are blocked waiting for `*this`, unblocks one of those threads.

```
void notify_all() noexcept;
```

- 8 *Effects:* Unblocks all threads that are blocked waiting for `*this`.

```
void wait(unique_lock<mutex>& lock);
```

- 9 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

- (9.1) — no other thread is waiting on this `condition_variable` object or

- (9.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

- 10 *Effects:*

- (10.1) — Atomically calls `lock.unlock()` and blocks on `*this`.

- (10.2) — When unblocked, calls `lock.lock()` (possibly blocking on the lock), then returns.

- (10.3) — The function will unblock when signaled by a call to `notify_one()` or a call to `notify_all()`, or spuriously.

11 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

12 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.

13 *Throws:* Nothing.

```
template <class Predicate>
void wait(unique_lock<mutex>& lock, Predicate pred);
```

14 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

(14.1) — no other thread is waiting on this `condition_variable` object or

(14.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

15 *Effects:* Equivalent to:

```
while (!pred())
    wait(lock);
```

16 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

17 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.

18 *Throws:* Any exception thrown by `pred`.

```
template <class Clock, class Duration>
cv_status wait_until(unique_lock<mutex>& lock,
                    const chrono::time_point<Clock, Duration>& abs_time);
```

19 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

(19.1) — no other thread is waiting on this `condition_variable` object or

(19.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

20 *Effects:*

(20.1) — Atomically calls `lock.unlock()` and blocks on `*this`.

(20.2) — When unblocked, calls `lock.lock()` (possibly blocking on the lock), then returns.

(20.3) — The function will unblock when signaled by a call to `notify_one()`, a call to `notify_all()`, expiration of the absolute timeout (33.2.4) specified by `abs_time`, or spuriously.

(20.4) — If the function exits via an exception, `lock.lock()` shall be called prior to exiting the function.

21 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

22 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.

23 *Returns:* `cv_status::timeout` if the absolute timeout (33.2.4) specified by `abs_time` expired, otherwise `cv_status::no_timeout`.

24 *Throws:* Timeout-related exceptions (33.2.4).

```
template <class Rep, class Period>
cv_status wait_for(unique_lock<mutex>& lock,
                  const chrono::duration<Rep, Period>& rel_time);
```

25 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

(25.1) — no other thread is waiting on this `condition_variable` object or

(25.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

26 *Effects:* Equivalent to:

```
    return wait_until(lock, chrono::steady_clock::now() + rel_time);
```

27 *Returns:* `cv_status::timeout` if the relative timeout (33.2.4) specified by `rel_time` expired, otherwise `cv_status::no_timeout`.

28 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

29 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.

30 *Throws:* Timeout-related exceptions (33.2.4).

```
template <class Clock, class Duration, class Predicate>
bool wait_until(unique_lock<mutex>& lock,
               const chrono::time_point<Clock, Duration>& abs_time,
               Predicate pred);
```

31 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

(31.1) — no other thread is waiting on this `condition_variable` object or

(31.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

32 *Effects:* Equivalent to:

```
    while (!pred())
        if (wait_until(lock, abs_time) == cv_status::timeout)
            return pred();
    return true;
```

33 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

34 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.

35 [*Note:* The returned value indicates whether the predicate evaluated to `true` regardless of whether the timeout was triggered. — *end note*]

36 *Throws:* Timeout-related exceptions (33.2.4) or any exception thrown by `pred`.

```
template <class Rep, class Period, class Predicate>
bool wait_for(unique_lock<mutex>& lock,
             const chrono::duration<Rep, Period>& rel_time,
             Predicate pred);
```

37 *Requires:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread, and either

(37.1) — no other thread is waiting on this `condition_variable` object or

(37.2) — `lock.mutex()` returns the same value for each of the `lock` arguments supplied by all concurrently waiting (via `wait`, `wait_for`, or `wait_until`) threads.

38 *Effects:* Equivalent to:

```
    return wait_until(lock, chrono::steady_clock::now() + rel_time, std::move(pred));
```

39 [*Note:* There is no blocking if `pred()` is initially `true`, even if the timeout has already expired. — *end note*]

40 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:*

This can happen if the re-locking of the mutex throws an exception. — *end note*

- 41 *Postconditions:* `lock.owns_lock()` is `true` and `lock.mutex()` is locked by the calling thread.
- 42 [*Note:* The returned value indicates whether the predicate evaluates to `true` regardless of whether the timeout was triggered. — *end note*]
- 43 *Throws:* Timeout-related exceptions (33.2.4) or any exception thrown by `pred`.

33.5.4 Class `condition_variable_any` [thread.condition.condvarany]

- ¹ A `Lock` type shall meet the `BasicLockable` requirements (33.2.5.2). [*Note:* All of the standard mutex types meet this requirement. If a `Lock` type other than one of the standard mutex types or a `unique_lock` wrapper for a standard mutex type is used with `condition_variable_any`, the user must ensure that any necessary synchronization is in place with respect to the predicate associated with the `condition_variable_any` instance. — *end note*]

```
namespace std {
    class condition_variable_any {
    public:
        condition_variable_any();
        ~condition_variable_any();

        condition_variable_any(const condition_variable_any&) = delete;
        condition_variable_any& operator=(const condition_variable_any&) = delete;

        void notify_one() noexcept;
        void notify_all() noexcept;
        template <class Lock>
            void wait(Lock& lock);
        template <class Lock, class Predicate>
            void wait(Lock& lock, Predicate pred);

        template <class Lock, class Clock, class Duration>
            cv_status wait_until(Lock& lock, const chrono::time_point<Clock, Duration>& abs_time);
        template <class Lock, class Clock, class Duration, class Predicate>
            bool wait_until(Lock& lock, const chrono::time_point<Clock, Duration>& abs_time,
                Predicate pred);
        template <class Lock, class Rep, class Period>
            cv_status wait_for(Lock& lock, const chrono::duration<Rep, Period>& rel_time);
        template <class Lock, class Rep, class Period, class Predicate>
            bool wait_for(Lock& lock, const chrono::duration<Rep, Period>& rel_time,
                Predicate pred);
    };
}
```

`condition_variable_any();`

- 2 *Effects:* Constructs an object of type `condition_variable_any`.
- 3 *Throws:* `bad_alloc` or `system_error` when an exception is required (33.2.2).
- 4 *Error conditions:*
- (4.1) — `resource_unavailable_try_again` — if some non-memory resource limitation prevents initialization.
- (4.2) — `operation_not_permitted` — if the thread does not have the privilege to perform the operation.

`~condition_variable_any();`

5 *Requires:* There shall be no thread blocked on `*this`. [*Note:* That is, all threads shall have been notified; they may subsequently block on the lock specified in the wait. This relaxes the usual rules, which would have required all wait calls to happen before destruction. Only the notification to unblock the wait must happen before destruction. The user must take care to ensure that no threads wait on `*this` once the destructor has been started, especially when the waiting threads are calling the wait functions in a loop or using the overloads of `wait`, `wait_for`, or `wait_until` that take a predicate. — *end note*]

6 *Effects:* Destroys the object.

```
void notify_one() noexcept;
```

7 *Effects:* If any threads are blocked waiting for `*this`, unblocks one of those threads.

```
void notify_all() noexcept;
```

8 *Effects:* Unblocks all threads that are blocked waiting for `*this`.

```
template <class Lock>
    void wait(Lock& lock);
```

9 [*Note:* If any of the `wait` functions exits via an exception, it is unspecified whether the `Lock` is held. One can use a `Lock` type that allows to query that, such as the `unique_lock` wrapper. — *end note*]

10 *Effects:*

(10.1) — Atomically calls `lock.unlock()` and blocks on `*this`.

(10.2) — When unblocked, calls `lock.lock()` (possibly blocking on the lock) and returns.

(10.3) — The function will unblock when signaled by a call to `notify_one()`, a call to `notify_all()`, or spuriously.

11 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

12 *Postconditions:* `lock` is locked by the calling thread.

13 *Throws:* Nothing.

```
template <class Lock, class Predicate>
    void wait(Lock& lock, Predicate pred);
```

14 *Effects:* Equivalent to:

```
while (!pred())
    wait(lock);
```

```
template <class Lock, class Clock, class Duration>
    cv_status wait_until(Lock& lock, const chrono::time_point<Clock, Duration>& abs_time);
```

15 *Effects:*

(15.1) — Atomically calls `lock.unlock()` and blocks on `*this`.

(15.2) — When unblocked, calls `lock.lock()` (possibly blocking on the lock) and returns.

(15.3) — The function will unblock when signaled by a call to `notify_one()`, a call to `notify_all()`, expiration of the absolute timeout (33.2.4) specified by `abs_time`, or spuriously.

(15.4) — If the function exits via an exception, `lock.lock()` shall be called prior to exiting the function.

16 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

17 *Postconditions:* `lock` is locked by the calling thread.

18 *Returns:* `cv_status::timeout` if the absolute timeout (33.2.4) specified by `abs_time` expired, otherwise `cv_status::no_timeout`.

19 *Throws:* Timeout-related exceptions (33.2.4).

```
template <class Lock, class Rep, class Period>
    cv_status wait_for(Lock& lock, const chrono::duration<Rep, Period>& rel_time);
```

20 *Effects:* Equivalent to:

```
    return wait_until(lock, chrono::steady_clock::now() + rel_time);
```

21 *Returns:* `cv_status::timeout` if the relative timeout (33.2.4) specified by `rel_time` expired, otherwise `cv_status::no_timeout`.

22 *Remarks:* If the function fails to meet the postcondition, `terminate()` shall be called (18.5.1). [*Note:* This can happen if the re-locking of the mutex throws an exception. — *end note*]

23 *Postconditions:* `lock` is locked by the calling thread.

24 *Throws:* Timeout-related exceptions (33.2.4).

```
template <class Lock, class Clock, class Duration, class Predicate>
    bool wait_until(Lock& lock, const chrono::time_point<Clock, Duration>& abs_time, Predicate pred);
```

25 *Effects:* Equivalent to:

```
    while (!pred())
        if (wait_until(lock, abs_time) == cv_status::timeout)
            return pred();
    return true;
```

26 [*Note:* There is no blocking if `pred()` is initially `true`, or if the timeout has already expired. — *end note*]

27 [*Note:* The returned value indicates whether the predicate evaluates to `true` regardless of whether the timeout was triggered. — *end note*]

```
template <class Lock, class Rep, class Period, class Predicate>
    bool wait_for(Lock& lock, const chrono::duration<Rep, Period>& rel_time, Predicate pred);
```

28 *Effects:* Equivalent to:

```
    return wait_until(lock, chrono::steady_clock::now() + rel_time, std::move(pred));
```

33.6 Futures

[futures]

33.6.1 Overview

[futures.overview]

1 33.6 describes components that a C++ program can use to retrieve in one thread the result (value or exception) from a function that has run in the same thread or another thread. [*Note:* These components are not restricted to multi-threaded programs but can be useful in single-threaded programs as well. — *end note*]

33.6.2 Header <future> synopsis

[future.syn]

```
namespace std {
    enum class future_errc {
        broken_promise = implementation-defined,
        future_already_retrieved = implementation-defined,
        promise_already_satisfied = implementation-defined,
        no_state = implementation-defined
    };

    enum class launch : unspecified {
```

```

    async = unspecified,
    deferred = unspecified,
    implementation-defined
};

enum class future_status {
    ready,
    timeout,
    deferred
};

template <> struct is_error_code_enum<future_errc> : public true_type { };
error_code make_error_code(future_errc e) noexcept;
error_condition make_error_condition(future_errc e) noexcept;

const error_category& future_category() noexcept;

class future_error;

template <class R> class promise;
template <class R> class promise<R&>;
template <> class promise<void>;

template <class R>
    void swap(promise<R>& x, promise<R>& y) noexcept;

template <class R, class Alloc>
    struct uses_allocator<promise<R>, Alloc>;

template <class R> class future;
template <class R> class future<R&>;
template <> class future<void>;

template <class R> class shared_future;
template <class R> class shared_future<R&>;
template <> class shared_future<void>;

template <class> class packaged_task;    // not defined
template <class R, class... ArgTypes>
    class packaged_task<R(ArgTypes...)>;

template <class R, class... ArgTypes>
    void swap(packaged_task<R(ArgTypes...)>&, packaged_task<R(ArgTypes...)>&) noexcept;

template <class R, class Alloc>
    struct uses_allocator<packaged_task<R>, Alloc>;

template <class F, class... Args>
    future<invoke_result_t<decay_t<F>, decay_t<Args>...>>
    async(F&& f, Args&&... args);
template <class F, class... Args>
    future<invoke_result_t<decay_t<F>, decay_t<Args>...>>
    async(launch_policy, F&& f, Args&&... args);
}

```

¹ The enum type `launch` is a bitmask type (20.4.2.1.4) with elements `launch::async` and `launch::deferred`. [*Note:* Implementations can provide bitmasks to specify restrictions on task interaction by functions launched by `async()` applicable to a corresponding subset of available launch policies. Implementations can extend the behavior of the first overload of `async()` by adding their extensions to the launch policy under the “as if” rule. — *end note*]

² The enum values of `future_errc` are distinct and not zero.

33.6.3 Error handling

[`futures.errors`]

```
const error_category& future_category() noexcept;
```

¹ *Returns:* A reference to an object of a type derived from class `error_category`.

² The object's `default_error_condition` and equivalent virtual functions shall behave as specified for the class `error_category`. The object's `name` virtual function shall return a pointer to the string “future”.

```
error_code make_error_code(future_errc e) noexcept;
```

³ *Returns:* `error_code(static_cast<int>(e), future_category())`.

```
error_condition make_error_condition(future_errc e) noexcept;
```

⁴ *Returns:* `error_condition(static_cast<int>(e), future_category())`.

33.6.4 Class `future_error`

[`futures.future__error`]

```
namespace std {
    class future_error : public logic_error {
    public:
        explicit future_error(future_errc e);

        const error_code& code() const noexcept;
        const char* what() const noexcept;
    private:
        error_code ec_; // exposition only
    };
}
```

```
explicit future_error(future_errc e);
```

¹ *Effects:* Constructs an object of class `future_error` and initializes `ec_` with `make_error_code(e)`.

```
const error_code& code() const noexcept;
```

² *Returns:* `ec_`.

```
const char* what() const noexcept;
```

³ *Returns:* An NTBS incorporating `code().message()`.

33.6.5 Shared state

[`futures.state`]

¹ Many of the classes introduced in this subclause use some state to communicate results. This *shared state* consists of some state information and some (possibly not yet evaluated) *result*, which can be a (possibly void) value or an exception. [*Note:* Futures, promises, and tasks defined in this clause reference such shared state. — *end note*]

² [*Note:* The result can be any kind of object including a function to compute that result, as used by `async` when policy is `launch::deferred`. — *end note*]

- ³ An *asynchronous return object* is an object that reads results from a shared state. A *waiting function* of an asynchronous return object is one that potentially blocks to wait for the shared state to be made ready. If a waiting function can return before the state is made ready because of a timeout (33.2.5), then it is a *timed waiting function*, otherwise it is a *non-timed waiting function*.
- ⁴ An *asynchronous provider* is an object that provides a result to a shared state. The result of a shared state is set by respective functions on the asynchronous provider. [*Note*: Such as promises or tasks. — *end note*] The means of setting the result of a shared state is specified in the description of those classes and functions that create such a state object.
- ⁵ When an asynchronous return object or an asynchronous provider is said to release its shared state, it means:
- (5.1) — if the return object or provider holds the last reference to its shared state, the shared state is destroyed; and
 - (5.2) — the return object or provider gives up its reference to its shared state; and
 - (5.3) — these actions will not block for the shared state to become ready, except that it may block if all of the following are true: the shared state was created by a call to `std::async`, the shared state is not yet ready, and this was the last reference to the shared state.
- ⁶ When an asynchronous provider is said to make its shared state ready, it means:
- (6.1) — first, the provider marks its shared state as ready; and
 - (6.2) — second, the provider unblocks any execution agents waiting for its shared state to become ready.
- ⁷ When an asynchronous provider is said to abandon its shared state, it means:
- (7.1) — first, if that state is not ready, the provider
 - (7.1.1) — stores an exception object of type `future_error` with an error condition of `broken_promise` within its shared state; and then
 - (7.1.2) — makes its shared state ready;
 - (7.2) — second, the provider releases its shared state.
- ⁸ A shared state is *ready* only if it holds a value or an exception ready for retrieval. Waiting for a shared state to become ready may invoke code to compute the result on the waiting thread if so specified in the description of the class or function that creates the state object.
- ⁹ Calls to functions that successfully set the stored result of a shared state synchronize with (4.7) calls to functions successfully detecting the ready state resulting from that setting. The storage of the result (whether normal or exceptional) into the shared state synchronizes with (4.7) the successful return from a call to a waiting function on the shared state.
- ¹⁰ Some functions (e.g., `promise::set_value_at_thread_exit`) delay making the shared state ready until the calling thread exits. The destruction of each of that thread's objects with thread storage duration (6.7.2) is sequenced before making that shared state ready.
- ¹¹ Access to the result of the same shared state may conflict (4.7). [*Note*: This explicitly specifies that the result of the shared state is visible in the objects that reference this state in the sense of data race avoidance (20.5.5.9). For example, concurrent accesses through references returned by `shared_future::get()` (33.6.8) must either use read-only operations or provide additional synchronization. — *end note*]

33.6.6 Class template `promise`

[`futures.promise`]

```
namespace std {
    template <class R>
    class promise {
    public:
        promise();
```

```

template <class Allocator>
    promise(allocator_arg_t, const Allocator& a);
promise(promise&& rhs) noexcept;
promise(const promise& rhs) = delete;
~promise();

// assignment
promise& operator=(promise&& rhs) noexcept;
promise& operator=(const promise& rhs) = delete;
void swap(promise& other) noexcept;

// retrieving the result
future<R> get_future();

// setting the result
void set_value(see below);
void set_exception(exception_ptr p);

// setting the result with deferred notification
void set_value_at_thread_exit(see below);
void set_exception_at_thread_exit(exception_ptr p);
};
template <class R>
    void swap(promise<R>& x, promise<R>& y) noexcept;
template <class R, class Alloc>
    struct uses_allocator<promise<R>, Alloc>;
}

```

- ¹ The implementation shall provide the template `promise` and two specializations, `promise<R>` and `promise<void>`. These differ only in the argument type of the member functions `set_value` and `set_value_at_thread_exit`, as set out in their descriptions, below.
- ² The `set_value`, `set_exception`, `set_value_at_thread_exit`, and `set_exception_at_thread_exit` member functions behave as though they acquire a single mutex associated with the promise object while updating the promise object.

```

template <class R, class Alloc>
    struct uses_allocator<promise<R>, Alloc>
        : true_type { };

```

- ³ *Requires:* `Alloc` shall be an `Allocator` (20.5.3.5).

```

promise();
template <class Allocator>
    promise(allocator_arg_t, const Allocator& a);

```

- ⁴ *Effects:* constructs a `promise` object and a shared state. The second constructor uses the allocator `a` to allocate memory for the shared state.

```

promise(promise&& rhs) noexcept;

```

- ⁵ *Effects:* constructs a new `promise` object and transfers ownership of the shared state of `rhs` (if any) to the newly-constructed object.
- ⁶ *Postconditions:* `rhs` has no shared state.

```

~promise();

```

- ⁷ *Effects:* Abandons any shared state (33.6.5).

```

promise& operator=(promise&& rhs) noexcept;
8      Effects: Abandons any shared state (33.6.5) and then as if promise(std::move(rhs)).swap(*this).
9      Returns: *this.

void swap(promise& other) noexcept;
10     Effects: Exchanges the shared state of *this and other.
11     Postconditions: *this has the shared state (if any) that other had prior to the call to swap. other
        has the shared state (if any) that *this had prior to the call to swap.

future<R> get_future();
12     Returns: A future<R> object with the same shared state as *this.
13     Throws: future_error if *this has no shared state or if get_future has already been called on a
        promise with the same shared state as *this.
14     Error conditions:
(14.1) — future_already_retrieved if get_future has already been called on a promise with the same
        shared state as *this.
(14.2) — no_state if *this has no shared state.

void promise::set_value(const R& r);
void promise::set_value(R&& r);
void promise<R&>::set_value(R& r);
void promise<void>::set_value();
15     Effects: Atomically stores the value r in the shared state and makes that state ready (33.6.5).
16     Throws:
(16.1) — future_error if its shared state already has a stored value or exception, or
(16.2) — for the first version, any exception thrown by the constructor selected to copy an object of R, or
(16.3) — for the second version, any exception thrown by the constructor selected to move an object of R.
17     Error conditions:
(17.1) — promise_already_satisfied if its shared state already has a stored value or exception.
(17.2) — no_state if *this has no shared state.

void set_exception(exception_ptr p);
18     Requires: p is not null.
19     Effects: Atomically stores the exception pointer p in the shared state and makes that state ready (33.6.5).
20     Throws: future_error if its shared state already has a stored value or exception.
21     Error conditions:
(21.1) — promise_already_satisfied if its shared state already has a stored value or exception.
(21.2) — no_state if *this has no shared state.

void promise::set_value_at_thread_exit(const R& r);
void promise::set_value_at_thread_exit(R&& r);
void promise<R&>::set_value_at_thread_exit(R& r);
void promise<void>::set_value_at_thread_exit();
22     Effects: Stores the value r in the shared state without making that state ready immediately. Schedules

```

that state to be made ready when the current thread exits, after all objects of thread storage duration associated with the current thread have been destroyed.

23 *Throws:*

- (23.1) — **future_error** if its shared state already has a stored value or exception, or
- (23.2) — for the first version, any exception thrown by the constructor selected to copy an object of **R**, or
- (23.3) — for the second version, any exception thrown by the constructor selected to move an object of **R**.

24 *Error conditions:*

- (24.1) — **promise_already_satisfied** if its shared state already has a stored value or exception.
- (24.2) — **no_state** if ***this** has no shared state.

```
void set_exception_at_thread_exit(exception_ptr p);
```

25 *Requires:* **p** is not null.

26 *Effects:* Stores the exception pointer **p** in the shared state without making that state ready immediately. Schedules that state to be made ready when the current thread exits, after all objects of thread storage duration associated with the current thread have been destroyed.

27 *Throws:* **future_error** if an error condition occurs.

28 *Error conditions:*

- (28.1) — **promise_already_satisfied** if its shared state already has a stored value or exception.
- (28.2) — **no_state** if ***this** has no shared state.

```
template <class R>
void swap(promise<R>& x, promise<R>& y) noexcept;
```

29 *Effects:* As if by **x.swap(y)**.

33.6.7 Class template future

[**futures.unique_future**]

1 The class template **future** defines a type for asynchronous return objects which do not share their shared state with other asynchronous return objects. A default-constructed **future** object has no shared state. A **future** object with shared state can be created by functions on asynchronous providers (33.6.5) or by the move constructor and shares its shared state with the original asynchronous provider. The result (value or exception) of a **future** object can be set by calling a respective function on an object that shares the same shared state.

2 [Note: Member functions of **future** do not synchronize with themselves or with member functions of **shared_future**. — end note]

3 The effect of calling any member function other than the destructor, the move-assignment operator, **share**, or **valid** on a **future** object for which **valid() == false** is undefined. [Note: It is valid to move from a **future** object for which **valid() == false**. — end note] [Note: Implementations are encouraged to detect this case and throw an object of type **future_error** with an error condition of **future_errc::no_state**. — end note]

```
namespace std {
    template <class R>
    class future {
    public:
        future() noexcept;
        future(future&&) noexcept;
        future(const future& rhs) = delete;
        ~future();
```



```

future& operator=(const future& rhs) = delete;
future& operator=(future&&) noexcept;
shared_future<R> share() noexcept;

// retrieving the value
see below get();

// functions to check state
bool valid() const noexcept;

void wait() const;
template <class Rep, class Period>
    future_status wait_for(const chrono::duration<Rep, Period>& rel_time) const;
template <class Clock, class Duration>
    future_status wait_until(const chrono::time_point<Clock, Duration>& abs_time) const;
};
}

```

- 4 The implementation shall provide the template `future` and two specializations, `future<R>` and `future<void>`. These differ only in the return type and return value of the member function `get`, as set out in its description, below.

```
future() noexcept;
```

- 5 *Effects:* Constructs an *empty* `future` object that does not refer to a shared state.

- 6 *Postconditions:* `valid() == false`.

```
future(future&& rhs) noexcept;
```

- 7 *Effects:* Move constructs a `future` object that refers to the shared state that was originally referred to by `rhs` (if any).

- 8 *Postconditions:*

- (8.1) — `valid()` returns the same value as `rhs.valid()` prior to the constructor invocation.

- (8.2) — `rhs.valid() == false`.

```
~future();
```

- 9 *Effects:*

- (9.1) — Releases any shared state (33.6.5);

- (9.2) — destroys `*this`.

```
future& operator=(future&& rhs) noexcept;
```

- 10 *Effects:*

- (10.1) — Releases any shared state (33.6.5).

- (10.2) — move assigns the contents of `rhs` to `*this`.

- 11 *Postconditions:*

- (11.1) — `valid()` returns the same value as `rhs.valid()` prior to the assignment.

- (11.2) — `rhs.valid() == false`.

```
shared_future<R> share() noexcept;
```

- 12 *Returns:* `shared_future<R>(std::move(*this))`.

13 *Postconditions:* `valid() == false`.

```
R future::get();
R& future<R&>::get();
void future<void>::get();
```

14 [*Note:* As described above, the template and its two required specializations differ only in the return type and return value of the member function `get`. — *end note*]

15 *Effects:*

(15.1) — `wait()`s until the shared state is ready, then retrieves the value stored in the shared state;

(15.2) — releases any shared state (33.6.5).

16 *Returns:*

(16.1) — `future::get()` returns the value `v` stored in the object's shared state as `std::move(v)`.

(16.2) — `future<R&>::get()` returns the reference stored as value in the object's shared state.

(16.3) — `future<void>::get()` returns nothing.

17 *Throws:* the stored exception, if an exception was stored in the shared state.

18 *Postconditions:* `valid() == false`.

```
bool valid() const noexcept;
```

19 *Returns:* `true` only if `*this` refers to a shared state.

```
void wait() const;
```

20 *Effects:* Blocks until the shared state is ready.

```
template <class Rep, class Period>
future_status wait_for(const chrono::duration<Rep, Period>& rel_time) const;
```

21 *Effects:* None if the shared state contains a deferred function (33.6.9), otherwise blocks until the shared state is ready or until the relative timeout (33.2.4) specified by `rel_time` has expired.

22 *Returns:*

(22.1) — `future_status::deferred` if the shared state contains a deferred function.

(22.2) — `future_status::ready` if the shared state is ready.

(22.3) — `future_status::timeout` if the function is returning because the relative timeout (33.2.4) specified by `rel_time` has expired.

23 *Throws:* timeout-related exceptions (33.2.4).

```
template <class Clock, class Duration>
future_status wait_until(const chrono::time_point<Clock, Duration>& abs_time) const;
```

24 *Effects:* None if the shared state contains a deferred function (33.6.9), otherwise blocks until the shared state is ready or until the absolute timeout (33.2.4) specified by `abs_time` has expired.

25 *Returns:*

(25.1) — `future_status::deferred` if the shared state contains a deferred function.

(25.2) — `future_status::ready` if the shared state is ready.

(25.3) — `future_status::timeout` if the function is returning because the absolute timeout (33.2.4) specified by `abs_time` has expired.

26 *Throws:* timeout-related exceptions (33.2.4).

33.6.8 Class template `shared_future` [`futures.shared_future`]

- ¹ The class template `shared_future` defines a type for asynchronous return objects which may share their shared state with other asynchronous return objects. A default-constructed `shared_future` object has no shared state. A `shared_future` object with shared state can be created by conversion from a `future` object and shares its shared state with the original asynchronous provider (33.6.5) of the shared state. The result (value or exception) of a `shared_future` object can be set by calling a respective function on an object that shares the same shared state.
- ² [*Note:* Member functions of `shared_future` do not synchronize with themselves, but they synchronize with the shared state. — *end note*]
- ³ The effect of calling any member function other than the destructor, the move-assignment operator, the copy-assignment operator, or `valid()` on a `shared_future` object for which `valid() == false` is undefined. [*Note:* It is valid to copy or move from a `shared_future` object for which `valid()` is `false`. — *end note*]
[*Note:* Implementations are encouraged to detect this case and throw an object of type `future_error` with an error condition of `future_errc::no_state`. — *end note*]

```
namespace std {
    template <class R>
    class shared_future {
    public:
        shared_future() noexcept;
        shared_future(const shared_future& rhs) noexcept;
        shared_future(future<R>&&) noexcept;
        shared_future(shared_future&& rhs) noexcept;
        ~shared_future();
        shared_future& operator=(const shared_future& rhs) noexcept;
        shared_future& operator=(shared_future&& rhs) noexcept;

        // retrieving the value
        see below get() const;

        // functions to check state
        bool valid() const noexcept;

        void wait() const;
        template <class Rep, class Period>
            future_status wait_for(const chrono::duration<Rep, Period>& rel_time) const;
        template <class Clock, class Duration>
            future_status wait_until(const chrono::time_point<Clock, Duration>& abs_time) const;
    };
}
```

- ⁴ The implementation shall provide the template `shared_future` and two specializations, `shared_future<R&>` and `shared_future<void>`. These differ only in the return type and return value of the member function `get`, as set out in its description, below.

```
shared_future() noexcept;
```

- ⁵ *Effects:* Constructs an *empty* `shared_future` object that does not refer to a shared state.

- ⁶ *Postconditions:* `valid() == false`.

```
shared_future(const shared_future& rhs) noexcept;
```

- ⁷ *Effects:* Constructs a `shared_future` object that refers to the same shared state as `rhs` (if any).

- ⁸ *Postconditions:* `valid()` returns the same value as `rhs.valid()`.

```
shared_future(future<R>&& rhs) noexcept;
shared_future(shared_future&& rhs) noexcept;
```

9 *Effects:* Move constructs a `shared_future` object that refers to the shared state that was originally referred to by `rhs` (if any).

10 *Postconditions:*

(10.1) — `valid()` returns the same value as `rhs.valid()` returned prior to the constructor invocation.

(10.2) — `rhs.valid() == false`.

```
~shared_future();
```

11 *Effects:*

(11.1) — Releases any shared state (33.6.5);

(11.2) — destroys `*this`.

```
shared_future& operator=(shared_future&& rhs) noexcept;
```

12 *Effects:*

(12.1) — Releases any shared state (33.6.5);

(12.2) — move assigns the contents of `rhs` to `*this`.

13 *Postconditions:*

(13.1) — `valid()` returns the same value as `rhs.valid()` returned prior to the assignment.

(13.2) — `rhs.valid() == false`.

```
shared_future& operator=(const shared_future& rhs) noexcept;
```

14 *Effects:*

(14.1) — Releases any shared state (33.6.5);

(14.2) — assigns the contents of `rhs` to `*this`. [*Note:* As a result, `*this` refers to the same shared state as `rhs` (if any). — *end note*]

15 *Postconditions:* `valid() == rhs.valid()`.

```
const R& shared_future::get() const;
R& shared_future<R&>::get() const;
void shared_future<void>::get() const;
```

16 [*Note:* As described above, the template and its two required specializations differ only in the return type and return value of the member function `get`. — *end note*]

17 [*Note:* Access to a value object stored in the shared state is unsynchronized, so programmers should apply only those operations on `R` that do not introduce a data race (4.7). — *end note*]

18 *Effects:* `wait()`s until the shared state is ready, then retrieves the value stored in the shared state.

19 *Returns:*

(19.1) — `shared_future::get()` returns a `const` reference to the value stored in the object's shared state. [*Note:* Access through that reference after the shared state has been destroyed produces undefined behavior; this can be avoided by not storing the reference in any storage with a greater lifetime than the `shared_future` object that returned the reference. — *end note*]

(19.2) — `shared_future<R&>::get()` returns the reference stored as value in the object's shared state.

(19.3) — `shared_future<void>::get()` returns nothing.

20 *Throws:* the stored exception, if an exception was stored in the shared state.

```
bool valid() const noexcept;
```

21 *Returns:* `true` only if `*this` refers to a shared state.

```
void wait() const;
```

22 *Effects:* Blocks until the shared state is ready.

```
template <class Rep, class Period>
    future_status wait_for(const chrono::duration<Rep, Period>& rel_time) const;
```

23 *Effects:* None if the shared state contains a deferred function (33.6.9), otherwise blocks until the shared state is ready or until the relative timeout (33.2.4) specified by `rel_time` has expired.

24 *Returns:*

(24.1) — `future_status::deferred` if the shared state contains a deferred function.

(24.2) — `future_status::ready` if the shared state is ready.

(24.3) — `future_status::timeout` if the function is returning because the relative timeout (33.2.4) specified by `rel_time` has expired.

25 *Throws:* timeout-related exceptions (33.2.4).

```
template <class Clock, class Duration>
    future_status wait_until(const chrono::time_point<Clock, Duration>& abs_time) const;
```

26 *Effects:* None if the shared state contains a deferred function (33.6.9), otherwise blocks until the shared state is ready or until the absolute timeout (33.2.4) specified by `abs_time` has expired.

27 *Returns:*

(27.1) — `future_status::deferred` if the shared state contains a deferred function.

(27.2) — `future_status::ready` if the shared state is ready.

(27.3) — `future_status::timeout` if the function is returning because the absolute timeout (33.2.4) specified by `abs_time` has expired.

28 *Throws:* timeout-related exceptions (33.2.4).

33.6.9 Function template `async` [futures.async]

1 The function template `async` provides a mechanism to launch a function potentially in a new thread and provides the result of the function in a `future` object with which it shares a shared state.

```
template <class F, class... Args>
    future<invoke_result_t<decay_t<F>, decay_t<Args>...>>
        async(F&& f, Args&&... args);
template <class F, class... Args>
    future<invoke_result_t<decay_t<F>, decay_t<Args>...>>
        async(launch_policy, F&& f, Args&&... args);
```

2 *Requires:* `F` and each `Ti` in `Args` shall satisfy the `MoveConstructible` requirements, and

```
    INVOKE(DECAY_COPY(std::forward<F>(f)),
           DECAY_COPY(std::forward<Args>(args))...)    // see 23.14.3, 33.3.2.2
```

shall be a valid expression.

3 *Effects:* The first function behaves the same as a call to the second function with a `policy` argument of `launch::async` | `launch::deferred` and the same arguments for `F` and `Args`. The second function creates a shared state that is associated with the returned `future` object. The further behavior of

the second function depends on the `policy` argument as follows (if more than one of these conditions applies, the implementation may choose any of the corresponding policies):

- (3.1) — If `launch::async` is set in `policy`, calls `INVOKE(DECAY_COPY(std::forward<F>(f)), DECAY_COPY(std::forward<Args>(args))...)` (23.14.3, 33.3.2.2) as if in a new thread of execution represented by a `thread` object with the calls to `DECAY_COPY()` being evaluated in the thread that called `async`. Any return value is stored as the result in the shared state. Any exception propagated from the execution of `INVOKE(DECAY_COPY(std::forward<F>(f)), DECAY_COPY(std::forward<Args>(args))...)` is stored as the exceptional result in the shared state. The `thread` object is stored in the shared state and affects the behavior of any asynchronous return objects that reference that state.
 - (3.2) — If `launch::deferred` is set in `policy`, stores `DECAY_COPY(std::forward<F>(f))` and `DECAY_COPY(std::forward<Args>(args))...` in the shared state. These copies of `f` and `args` constitute a *deferred function*. Invocation of the deferred function evaluates `INVOKE(std::move(g), std::move(xyz))` where `g` is the stored value of `DECAY_COPY(std::forward<F>(f))` and `xyz` is the stored copy of `DECAY_COPY(std::forward<Args>(args))...`. Any return value is stored as the result in the shared state. Any exception propagated from the execution of the deferred function is stored as the exceptional result in the shared state. The shared state is not made ready until the function has completed. The first call to a non-timed waiting function (33.6.5) on an asynchronous return object referring to this shared state shall invoke the deferred function in the thread that called the waiting function. Once evaluation of `INVOKE(std::move(g), std::move(xyz))` begins, the function is no longer considered deferred. [*Note:* If this policy is specified together with other policies, such as when using a `policy` value of `launch::async` | `launch::deferred`, implementations should defer invocation or the selection of the policy when no more concurrency can be effectively exploited. — *end note*]
 - (3.3) — If no value is set in the launch policy, or a value is set that is neither specified in this International Standard nor by the implementation, the behavior is undefined.
- 4 *Returns:* An object of type `future<invoke_result_t<decay_t<F>, decay_t<Args>...>>` that refers to the shared state created by this call to `async`. [*Note:* If a future obtained from `async` is moved outside the local scope, other code that uses the future must be aware that the future's destructor may block for the shared state to become ready. — *end note*]
- 5 *Synchronization:* Regardless of the provided `policy` argument,
- (5.1) — the invocation of `async` synchronizes with (4.7) the invocation of `f`. [*Note:* This statement applies even when the corresponding `future` object is moved to another thread. — *end note*]; and
 - (5.2) — the completion of the function `f` is sequenced before (4.7) the shared state is made ready. [*Note:* `f` might not be called at all, so its completion might never happen. — *end note*]
- If the implementation chooses the `launch::async` policy,
- (5.3) — a call to a waiting function on an asynchronous return object that shares the shared state created by this `async` call shall block until the associated thread has completed, as if joined, or else time out (33.3.2.5);
 - (5.4) — the associated thread completion synchronizes with (4.7) the return from the first function that successfully detects the ready status of the shared state or with the return from the last function that releases the shared state, whichever happens first.
- 6 *Throws:* `system_error` if `policy == launch::async` and the implementation is unable to start a new thread, or `std::bad_alloc` if memory for the internal data structures could not be allocated.
- 7 *Error conditions:*
- (7.1) — `resource_unavailable_try_again` — if `policy == launch::async` and the system is unable

to start a new thread.

⁸ [Example:

```
int work1(int value);
int work2(int value);
int work(int value) {
    auto handle = std::async([=]{ return work2(value); });
    int tmp = work1(value);
    return tmp + handle.get();    // #1
}
```

[Note: Line #1 might not result in concurrency because the `async` call uses the default policy, which may use `launch::deferred`, in which case the lambda might not be invoked until the `get()` call; in that case, `work1` and `work2` are called on the same thread and there is no concurrency. — end note] — end example]

33.6.10 Class template `packaged_task`

[`futures.task`]

- ¹ The class template `packaged_task` defines a type for wrapping a function or callable object so that the return value of the function or callable object is stored in a future when it is invoked.
- ² When the `packaged_task` object is invoked, its stored task is invoked and the result (whether normal or exceptional) stored in the shared state. Any futures that share the shared state will then be able to access the stored result.

```
namespace std {
    template<class> class packaged_task; // not defined

    template<class R, class... ArgTypes>
    class packaged_task<R(ArgTypes...)> {
    public:
        // construction and destruction
        packaged_task() noexcept;
        template <class F>
            explicit packaged_task(F&& f);
        ~packaged_task();

        // no copy
        packaged_task(const packaged_task&) = delete;
        packaged_task& operator=(const packaged_task&) = delete;

        // move support
        packaged_task(packaged_task&& rhs) noexcept;
        packaged_task& operator=(packaged_task&& rhs) noexcept;
        void swap(packaged_task& other) noexcept;

        bool valid() const noexcept;

        // result retrieval
        future<R> get_future();

        // execution
        void operator()(ArgTypes... );
        void make_ready_at_thread_exit(ArgTypes...);

        void reset();
    };
    template <class R, class... ArgTypes>
```

```

    void swap(packaged_task<R(ArgTypes...)>& x, packaged_task<R(ArgTypes...)>& y) noexcept;
    template <class R, class Alloc>
        struct uses_allocator<packaged_task<R>, Alloc>;
}

```

33.6.10.1 packaged_task member functions

[futures.task.members]

```
packaged_task() noexcept;
```

- 1 *Effects:* Constructs a `packaged_task` object with no shared state and no stored task.

```

template <class F>
    packaged_task(F&& f);

```

- 2 *Requires:* `INVOKE<R>(f, t1, t2, ..., tN)`, where `t1`, `t2`, ..., `tN` are values of the corresponding types in `ArgTypes...`, shall be a valid expression. Invoking a copy of `f` shall behave the same as invoking `f`.

- 3 *Remarks:* This constructor shall not participate in overload resolution if `decay_t<F>` is the same type as `packaged_task<R(ArgTypes...)>`.

- 4 *Effects:* Constructs a new `packaged_task` object with a shared state and initializes the object's stored task with `std::forward<F>(f)`.

- 5 *Throws:*

- (5.1) — Any exceptions thrown by the copy or move constructor of `f`.
- (5.2) — For the first version, `bad_alloc` if memory for the internal data structures could not be allocated.
- (5.3) — For the second version, any exceptions thrown by `allocator_traits<Allocator>::template rebind_traits<unspecified>::allocate`.

```
packaged_task(packaged_task&& rhs) noexcept;
```

- 6 *Effects:* Constructs a new `packaged_task` object and transfers ownership of `rhs`'s shared state to `*this`, leaving `rhs` with no shared state. Moves the stored task from `rhs` to `*this`.

- 7 *Postconditions:* `rhs` has no shared state.

```
packaged_task& operator=(packaged_task&& rhs) noexcept;
```

- 8 *Effects:*

- (8.1) — Releases any shared state (33.6.5);
- (8.2) — calls `packaged_task(std::move(rhs)).swap(*this)`.

```
~packaged_task();
```

- 9 *Effects:* Abandons any shared state (33.6.5).

```
void swap(packaged_task& other) noexcept;
```

- 10 *Effects:* Exchanges the shared states and stored tasks of `*this` and `other`.

- 11 *Postconditions:* `*this` has the same shared state and stored task (if any) as `other` prior to the call to `swap`. `other` has the same shared state and stored task (if any) as `*this` prior to the call to `swap`.

```
bool valid() const noexcept;
```

- 12 *Returns:* `true` only if `*this` has a shared state.

```
future<R> get_future();
```

- 13 *Returns:* A `future` object that shares the same shared state as `*this`.

- 14 *Throws:* a `future_error` object if an error occurs.
- 15 *Error conditions:*
- (15.1) — `future_already_retrieved` if `get_future` has already been called on a `packaged_task` object with the same shared state as `*this`.
- (15.2) — `no_state` if `*this` has no shared state.
- `void operator()(ArgTypes... args);`
- 16 *Effects:* As if by `INVOKE<R>(f, t1, t2, ..., tN)`, where `f` is the stored task of `*this` and `t1, t2, ..., tN` are the values in `args...`. If the task returns normally, the return value is stored as the asynchronous result in the shared state of `*this`, otherwise the exception thrown by the task is stored. The shared state of `*this` is made ready, and any threads blocked in a function waiting for the shared state of `*this` to become ready are unblocked.
- 17 *Throws:* a `future_error` exception object if there is no shared state or the stored task has already been invoked.
- 18 *Error conditions:*
- (18.1) — `promise_already_satisfied` if the stored task has already been invoked.
- (18.2) — `no_state` if `*this` has no shared state.
- `void make_ready_at_thread_exit(ArgTypes... args);`
- 19 *Effects:* As if by `INVOKE<R>(f, t1, t2, ..., tN)`, where `f` is the stored task and `t1, t2, ..., tN` are the values in `args...`. If the task returns normally, the return value is stored as the asynchronous result in the shared state of `*this`, otherwise the exception thrown by the task is stored. In either case, this shall be done without making that state ready (33.6.5) immediately. Schedules the shared state to be made ready when the current thread exits, after all objects of thread storage duration associated with the current thread have been destroyed.
- 20 *Throws:* `future_error` if an error condition occurs.
- 21 *Error conditions:*
- (21.1) — `promise_already_satisfied` if the stored task has already been invoked.
- (21.2) — `no_state` if `*this` has no shared state.
- `void reset();`
- 22 *Effects:* As if `*this = packaged_task(std::move(f))`, where `f` is the task stored in `*this`. [*Note:* This constructs a new shared state for `*this`. The old state is abandoned (33.6.5). — *end note*]
- 23 *Throws:*
- (23.1) — `bad_alloc` if memory for the new shared state could not be allocated.
- (23.2) — any exception thrown by the move constructor of the task stored in the shared state.
- (23.3) — `future_error` with an error condition of `no_state` if `*this` has no shared state.

33.6.10.2 packaged_task globals

[`futures.task.nonmembers`]

```
template <class R, class... ArgTypes>
    void swap(packaged_task<R(ArgTypes...)>& x, packaged_task<R(ArgTypes...)>& y) noexcept;
```

1 *Effects:* As if by `x.swap(y)`.

```
template <class R, class Alloc>
    struct uses_allocator<packaged_task<R>, Alloc>
```

```
: true_type { };
```

² *Requires:* Alloc shall be an Allocator ([20.5.3.5](#)).

Annex A (informative)

Grammar summary

[gram]

- ¹ This summary of C++ grammar is intended to be an aid to comprehension. It is not an exact statement of the language. In particular, the grammar described here accepts a superset of valid C++ constructs. Disambiguation rules (9.8, 10.1, 13.2) must be applied to distinguish expressions from declarations. Further, access control, ambiguity, and type rules must be used to weed out syntactically valid but meaningless constructs.

A.1 Keywords

[gram.key]

- ¹ New context-dependent keywords are introduced into a program by `typedef` (10.1.3), `namespace` (10.3.1), `class` (Clause 12), `enumeration` (10.2), and `template` (Clause 17) declarations.

typedef-name:
identifier

namespace-name:
identifier
namespace-alias

namespace-alias:
identifier

class-name:
identifier
simple-template-id

enum-name:
identifier

template-name:
identifier

Note that a *typedef-name* naming a class is also a *class-name* (12.1).

A.2 Lexical conventions

[gram.lex]

hex-quad:
hexadecimal-digit hexadecimal-digit hexadecimal-digit hexadecimal-digit

universal-character-name:
 \u *hex-quad*
 \U *hex-quad hex-quad*

preprocessing-token:
header-name
identifier
pp-number
character-literal
user-defined-character-literal
string-literal
user-defined-string-literal
preprocessing-op-or-punc
 each non-white-space character that cannot be one of the above

token:

- identifier*
- keyword*
- literal*
- operator*
- punctuator*

header-name:

- < h-char-sequence >*
- " q-char-sequence "*

h-char-sequence:

- h-char*
- h-char-sequence h-char*

h-char:

- any member of the source character set except new-line and *>*

q-char-sequence:

- q-char*
- q-char-sequence q-char*

q-char:

- any member of the source character set except new-line and *"*

pp-number:

- digit*
- . digit*
- pp-number digit*
- pp-number identifier-nondigit*
- pp-number ' digit*
- pp-number ' nondigit*
- pp-number e sign*
- pp-number E sign*
- pp-number p sign*
- pp-number P sign*
- pp-number .*

identifier:

- identifier-nondigit*
- identifier identifier-nondigit*
- identifier digit*

identifier-nondigit:

- nondigit*
- universal-character-name*

nondigit: one of

- a b c d e f g h i j k l m*
- n o p q r s t u v w x y z*
- A B C D E F G H I J K L M*
- N O P Q R S T U V W X Y Z _*

digit: one of

- 0 1 2 3 4 5 6 7 8 9*

preprocessing-op-or-punc: one of

{	}	[	]	#	##	(	)		
<:	>:	<%	%>	%:	%::	;	:	...	
new	delete	?	::	.	.*				
+	-	*	/	%	^	&		~	
!	=	<	>	+=	-=	*=	/=	%=	
^=	&=	=	<<	>>	>>=	<<=	==	!=	
<=	>=	&&		++	--	,	->*	->	
and	and_eq	bitand	bitor	compl	not	not_eq			
or	or_eq	xor	xor_eq						

literal:

integer-literal
character-literal
floating-literal
string-literal
boolean-literal
pointer-literal
user-defined-literal

integer-literal:

binary-literal integer-suffix_{opt}
octal-literal integer-suffix_{opt}
decimal-literal integer-suffix_{opt}
hexadecimal-literal integer-suffix_{opt}

binary-literal:

0b *binary-digit*
0B *binary-digit*
binary-literal ' _{opt} *binary-digit*

octal-literal:

0
octal-literal ' _{opt} *octal-digit*

decimal-literal:

nonzero-digit
decimal-literal ' _{opt} *digit*

hexadecimal-literal:

hexadecimal-prefix hexadecimal-digit-sequence

binary-digit:

0
1

octal-digit: one of

0 1 2 3 4 5 6 7

nonzero-digit: one of

1 2 3 4 5 6 7 8 9

hexadecimal-prefix: one of

0x 0X

hexadecimal-digit-sequence:

hexadecimal-digit
hexadecimal-digit-sequence ' _{opt} *hexadecimal-digit*

hexadecimal-digit: one of
 0 1 2 3 4 5 6 7 8 9
 a b c d e f
 A B C D E F

integer-suffix:
unsigned-suffix long-suffix_{opt}
unsigned-suffix long-long-suffix_{opt}
long-suffix unsigned-suffix_{opt}
long-long-suffix unsigned-suffix_{opt}

unsigned-suffix: one of
 u U

long-suffix: one of
 l L

long-long-suffix: one of
 ll LL

character-literal:
encoding-prefix_{opt} ' c-char-sequence '

encoding-prefix: one of
 u8 u U L

c-char-sequence:
c-char
c-char-sequence c-char

c-char:
 any member of the source character set except
 the single-quote ' , backslash \ , or new-line character
escape-sequence
universal-character-name

escape-sequence:
simple-escape-sequence
octal-escape-sequence
hexadecimal-escape-sequence

simple-escape-sequence: one of
 \ ' \ " \ ? \ \
 \ a \ b \ f \ n \ r \ t \ v

octal-escape-sequence:
 \ octal-digit
 \ octal-digit octal-digit
 \ octal-digit octal-digit octal-digit

hexadecimal-escape-sequence:
 \ x hexadecimal-digit
 hexadecimal-escape-sequence hexadecimal-digit

floating-literal:
decimal-floating-literal
hexadecimal-floating-literal

decimal-floating-literal:
fractional-constant exponent-part_{opt} floating-suffix_{opt}
digit-sequence exponent-part floating-suffix_{opt}

hexadecimal-floating-literal:

hexadecimal-prefix hexadecimal-fractional-constant binary-exponent-part floating-suffix_{opt}
hexadecimal-prefix hexadecimal-digit-sequence binary-exponent-part floating-suffix_{opt}

fractional-constant:

digit-sequence_{opt} . digit-sequence
digit-sequence .

hexadecimal-fractional-constant:

hexadecimal-digit-sequence_{opt} . hexadecimal-digit-sequence
hexadecimal-digit-sequence .

exponent-part:

e sign_{opt} digit-sequence
E sign_{opt} digit-sequence

binary-exponent-part:

p sign_{opt} digit-sequence
P sign_{opt} digit-sequence

sign: one of

+ -

digit-sequence:

digit
digit-sequence ' _{opt} digit

floating-suffix: one of

f l F L

string-literal:

encoding-prefix_{opt} " s-char-sequence_{opt} "
encoding-prefix_{opt} R raw-string

s-char-sequence:

s-char
s-char-sequence s-char

s-char:

any member of the source character set except
 the double-quote *"*, backslash **, or new-line character
escape-sequence
universal-character-name

raw-string:

" d-char-sequence_{opt} (r-char-sequence_{opt}) d-char-sequence_{opt} "

r-char-sequence:

r-char
r-char-sequence r-char

r-char:

any member of the source character set, except
 a right parenthesis *)* followed by the initial *d-char-sequence*
 (which may be empty) followed by a double quote *"*.

d-char-sequence:

d-char
d-char-sequence d-char

d-char:

any member of the basic source character set except:
 space, the left parenthesis (, the right parenthesis), the backslash \,
 and the control characters representing horizontal tab,
 vertical tab, form feed, and newline.

boolean-literal:

false
true

pointer-literal:

nullptr

user-defined-literal:

user-defined-integer-literal
user-defined-floating-literal
user-defined-string-literal
user-defined-character-literal

user-defined-integer-literal:

decimal-literal ud-suffix
octal-literal ud-suffix
hexadecimal-literal ud-suffix
binary-literal ud-suffix

user-defined-floating-literal:

fractional-constant exponent-part_{opt} ud-suffix
digit-sequence exponent-part ud-suffix
hexadecimal-prefix hexadecimal-fractional-constant binary-exponent-part ud-suffix
hexadecimal-prefix hexadecimal-digit-sequence binary-exponent-part ud-suffix

user-defined-string-literal:

string-literal ud-suffix

user-defined-character-literal:

character-literal ud-suffix

ud-suffix:

identifier

A.3 Basic concepts

[gram.basic]

translation-unit:

declaration-seq_{opt}

A.4 Expressions

[gram.expr]

primary-expression:

literal
this
 (*expression*)
id-expression
lambda-expression
fold-expression

id-expression:

unqualified-id
qualified-id

unqualified-id:

- identifier*
- operator-function-id*
- conversion-function-id*
- literal-operator-id*
- ~ class-name*
- ~ decltype-specifier*
- template-id*

qualified-id:

- nested-name-specifier* **template**_{opt} *unqualified-id*

nested-name-specifier:

- ::**
- type-name* **::**
- namespace-name* **::**
- decltype-specifier* **::**
- nested-name-specifier* *identifier* **::**
- nested-name-specifier* **template**_{opt} *simple-template-id* **::**

lambda-expression:

- lambda-introducer* *lambda-declarator*_{opt} *compound-statement*

lambda-introducer:

- [*lambda-capture*_{opt}]

lambda-declarator:

- (*parameter-declaration-clause*) *decl-specifier-seq*_{opt}
- noexcept-specifier*_{opt} *attribute-specifier-seq*_{opt} *trailing-return-type*_{opt}

lambda-capture:

- capture-default*
- capture-list*
- capture-default* , *capture-list*

capture-default:

- &**
- =**

capture-list:

- capture* ..._{opt}
- capture-list* , *capture* ..._{opt}

capture:

- simple-capture*
- init-capture*

simple-capture:

- identifier*
- &** *identifier*
- this**
- * this**

init-capture:

- identifier* *initializer*
- &** *identifier* *initializer*

fold-expression:

- (*cast-expression* *fold-operator* ...)
- (... *fold-operator* *cast-expression*)
- (*cast-expression* *fold-operator* ... *fold-operator* *cast-expression*)

fold-operator: one of

```

+   -   *   /   %   ^   &   |   <<   >>
+=  -=  *=  /=  %=  ^=  &=  |=  <<=  >>=  =
==  !=  <   >   <=  >=  &&  ||   ,   .*   ->*

```

postfix-expression:

```

primary-expression
postfix-expression [ expr-or-braced-init-list ]
postfix-expression ( expression-listopt )
simple-type-specifier ( expression-listopt )
typename-specifier ( expression-listopt )
simple-type-specifier braced-init-list
typename-specifier braced-init-list
postfix-expression . templateopt id-expression
postfix-expression -> templateopt id-expression
postfix-expression . pseudo-destructor-name
postfix-expression -> pseudo-destructor-name
postfix-expression ++
postfix-expression --
dynamic_cast < type-id > ( expression )
static_cast < type-id > ( expression )
reinterpret_cast < type-id > ( expression )
const_cast < type-id > ( expression )
typeid ( expression )
typeid ( type-id )

```

expression-list:

initializer-list

pseudo-destructor-name:

```

nested-name-specifieropt type-name :: ~ type-name
nested-name-specifier template simple-template-id :: ~ type-name
~ type-name
~ decltype-specifier

```

unary-expression:

```

postfix-expression
++ cast-expression
-- cast-expression
unary-operator cast-expression
sizeof unary-expression
sizeof ( type-id )
sizeof ... ( identifier )
alignof ( type-id )
noexcept-expression
new-expression
delete-expression

```

unary-operator: one of

```
* & + - ! ~
```

new-expression:

```

::opt new new-placementopt new-type-id new-initializeropt
::opt new new-placementopt ( type-id ) new-initializeropt

```

new-placement:

```
( expression-list )
```

new-type-id:

```
type-specifier-seq new-declaratoropt
```

new-declarator:

- ptr-operator new-declarator_{opt}*
- noptr-new-declarator*

noptr-new-declarator:

- [*expression*] *attribute-specifier-seq_{opt}*
- noptr-new-declarator* [*constant-expression*] *attribute-specifier-seq_{opt}*

new-initializer:

- (*expression-list_{opt}*)
- braced-init-list*

delete-expression:

- ::_{opt} **delete** *cast-expression*
- ::_{opt} **delete** [] *cast-expression*

noexcept-expression:

- noexcept** (*expression*)

cast-expression:

- unary-expression*
- (*type-id*) *cast-expression*

pm-expression:

- cast-expression*
- pm-expression* .* *cast-expression*
- pm-expression* ->* *cast-expression*

multiplicative-expression:

- pm-expression*
- multiplicative-expression* * *pm-expression*
- multiplicative-expression* / *pm-expression*
- multiplicative-expression* % *pm-expression*

additive-expression:

- multiplicative-expression*
- additive-expression* + *multiplicative-expression*
- additive-expression* - *multiplicative-expression*

shift-expression:

- additive-expression*
- shift-expression* << *additive-expression*
- shift-expression* >> *additive-expression*

relational-expression:

- shift-expression*
- relational-expression* < *shift-expression*
- relational-expression* > *shift-expression*
- relational-expression* <= *shift-expression*
- relational-expression* >= *shift-expression*

equality-expression:

- relational-expression*
- equality-expression* == *relational-expression*
- equality-expression* != *relational-expression*

and-expression:

- equality-expression*
- and-expression* & *equality-expression*

exclusive-or-expression:

- and-expression*
- exclusive-or-expression* ^ *and-expression*

inclusive-or-expression:
exclusive-or-expression
inclusive-or-expression | *exclusive-or-expression*

logical-and-expression:
inclusive-or-expression
logical-and-expression && *inclusive-or-expression*

logical-or-expression:
logical-and-expression
logical-or-expression || *logical-and-expression*

conditional-expression:
logical-or-expression
logical-or-expression ? *expression* : *assignment-expression*

throw-expression:
throw *assignment-expression*_{opt}

assignment-expression:
conditional-expression
logical-or-expression *assignment-operator* *initializer-clause*
throw-expression

assignment-operator: one of
 = * = / = % = + = - = > = < = & = ^ = | =

expression:
assignment-expression
expression , *assignment-expression*

constant-expression:
conditional-expression

A.5 Statements

[gram.stmt]

statement:
labeled-statement
*attribute-specifier-seq*_{opt} *expression-statement*
*attribute-specifier-seq*_{opt} *compound-statement*
*attribute-specifier-seq*_{opt} *selection-statement*
*attribute-specifier-seq*_{opt} *iteration-statement*
*attribute-specifier-seq*_{opt} *jump-statement*
declaration-statement
*attribute-specifier-seq*_{opt} *try-block*

init-statement:
expression-statement
simple-declaration

condition:
expression
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *declarator* *brace-or-equal-initializer*

labeled-statement:
*attribute-specifier-seq*_{opt} *identifier* : *statement*
*attribute-specifier-seq*_{opt} **case** *constant-expression* : *statement*
*attribute-specifier-seq*_{opt} **default** : *statement*

expression-statement:
*expression*_{opt} ;

compound-statement:
 { *statement-seq*_{opt} }

statement-seq:
statement
statement-seq statement

selection-statement:
if **constexpr**_{opt} (*init-statement*_{opt} *condition*) *statement*
if **constexpr**_{opt} (*init-statement*_{opt} *condition*) *statement* **else** *statement*
switch (*init-statement*_{opt} *condition*) *statement*

iteration-statement:
while (*condition*) *statement*
do *statement* **while** (*expression*) ;
for (*init-statement* *condition*_{opt} ; *expression*_{opt}) *statement*
for (*for-range-declaration* : *for-range-initializer*) *statement*

for-range-declaration:
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *declarator*
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *ref-qualifier*_{opt} [*identifier-list*]

for-range-initializer:
expr-or-braced-init-list

jump-statement:
break ;
continue ;
return *expr-or-braced-init-list*_{opt} ;
goto *identifier* ;

declaration-statement:
block-declaration

A.6 Declarations

[gram.dcl]

declaration-seq:
declaration
declaration-seq declaration

declaration:
block-declaration
nodeclspec-function-declaration
function-definition
template-declaration
deduction-guide
explicit-instantiation
explicit-specialization
linkage-specification
namespace-definition
empty-declaration
attribute-declaration

block-declaration:
simple-declaration
asm-definition
namespace-alias-definition
using-declaration
using-directive
static_assert-declaration
alias-declaration
opaque-enum-declaration

```

nodeclspec-function-declaration:
    attribute-specifier-seqopt declarator ;

alias-declaration:
    using identifier attribute-specifier-seqopt = defining-type-id ;

simple-declaration:
    decl-specifier-seq init-declarator-listopt ;
    attribute-specifier-seq decl-specifier-seq init-declarator-list ;
    attribute-specifier-seqopt decl-specifier-seq ref-qualifieropt [ identifier-list ] initializer ;

static_assert-declaration:
    static_assert ( constant-expression ) ;
    static_assert ( constant-expression , string-literal ) ;

empty-declaration:
    ;

attribute-declaration:
    attribute-specifier-seq ;

decl-specifier:
    storage-class-specifier
    defining-type-specifier
    function-specifier
    friend
    typedef
    constexpr
    inline

decl-specifier-seq:
    decl-specifier attribute-specifier-seqopt
    decl-specifier decl-specifier-seq

storage-class-specifier:
    static
    thread_local
    extern
    mutable

function-specifier:
    virtual
    explicit

typedef-name:
    identifier

type-specifier:
    simple-type-specifier
    elaborated-type-specifier
    typename-specifier
    cv-qualifier

type-specifier-seq:
    type-specifier attribute-specifier-seqopt
    type-specifier type-specifier-seq

defining-type-specifier:
    type-specifier
    class-specifier
    enum-specifier

```

defining-type-specifier-seq:
defining-type-specifier *attribute-specifier-seq*_{opt}
defining-type-specifier *defining-type-specifier-seq*

simple-type-specifier:
*nested-name-specifier*_{opt} *type-name*
nested-name-specifier **template** *simple-template-id*
*nested-name-specifier*_{opt} *template-name*
char
char16_t
char32_t
wchar_t
bool
short
int
long
signed
unsigned
float
double
void
auto
decltype-specifier

type-name:
class-name
enum-name
typedef-name
simple-template-id

decltype-specifier:
decltype (*expression*)
decltype (**auto**)

elaborated-type-specifier:
class-key *attribute-specifier-seq*_{opt} *nested-name-specifier*_{opt} *identifier*
class-key *simple-template-id*
class-key *nested-name-specifier* **template**_{opt} *simple-template-id*
enum *nested-name-specifier*_{opt} *identifier*

enum-name:
identifier

enum-specifier:
enum-head { *enumerator-list*_{opt} }
enum-head { *enumerator-list* , }

enum-head:
enum-key *attribute-specifier-seq*_{opt} *enum-head-name*_{opt} *enum-base*_{opt}

enum-head-name:
*nested-name-specifier*_{opt} *identifier*

opaque-enum-declaration:
enum-key *attribute-specifier-seq*_{opt} *nested-name-specifier*_{opt} *identifier* *enum-base*_{opt} ;

enum-key:
enum
enum class
enum struct

```

enum-base:
    : type-specifier-seq

enumerator-list:
    enumerator-definition
    enumerator-list , enumerator-definition

enumerator-definition:
    enumerator
    enumerator = constant-expression

enumerator:
    identifier attribute-specifier-seqopt

namespace-name:
    identifier
    namespace-alias

namespace-definition:
    named-namespace-definition
    unnamed-namespace-definition
    nested-namespace-definition

named-namespace-definition:
    inlineopt namespace attribute-specifier-seqopt identifier { namespace-body }

unnamed-namespace-definition:
    inlineopt namespace attribute-specifier-seqopt { namespace-body }

nested-namespace-definition:
    namespace enclosing-namespace-specifier :: identifier { namespace-body }

enclosing-namespace-specifier:
    identifier
    enclosing-namespace-specifier :: identifier

namespace-body:
    declaration-seqopt

namespace-alias:
    identifier

namespace-alias-definition:
    namespace identifier = qualified-namespace-specifier ;

qualified-namespace-specifier:
    nested-name-specifieropt namespace-name

using-declaration:
    using using-declarator-list ;

using-declarator-list:
    using-declarator ...opt
    using-declarator-list , using-declarator ...opt

using-declarator:
    typenameopt nested-name-specifier unqualified-id

using-directive:
    attribute-specifier-seqopt using namespace nested-name-specifieropt namespace-name ;

asm-definition:
    attribute-specifier-seqopt asm ( string-literal ) ;

linkage-specification:
    extern string-literal { declaration-seqopt }
    extern string-literal declaration

```


attribute-specifier-seq:
*attribute-specifier-seq*_{opt} *attribute-specifier*

attribute-specifier:
 [[*attribute-using-prefix*_{opt} *attribute-list*]]
alignment-specifier

alignment-specifier:
alignas (*type-id* ..._{opt})
alignas (*constant-expression* ..._{opt})

attribute-using-prefix:
using *attribute-namespace* :

attribute-list:
*attribute*_{opt}
attribute-list , *attribute*_{opt}
attribute ...
attribute-list , *attribute* ...

attribute:
attribute-token *attribute-argument-clause*_{opt}

attribute-token:
identifier
attribute-scoped-token

attribute-scoped-token:
attribute-namespace :: *identifier*

attribute-namespace:
identifier

attribute-argument-clause:
 (*balanced-token-seq*_{opt})

balanced-token-seq:
balanced-token
balanced-token-seq *balanced-token*

balanced-token:
 (*balanced-token-seq*_{opt})
 [*balanced-token-seq*_{opt}]
 { *balanced-token-seq*_{opt} }
 any *token* other than a parenthesis, a bracket, or a brace

A.7 Declarators

[gram.decl]

init-declarator-list:
init-declarator
init-declarator-list , *init-declarator*

init-declarator:
declarator *initializer*_{opt}

declarator:
ptr-declarator
noptr-declarator *parameters-and-qualifiers* *trailing-return-type*

ptr-declarator:
noptr-declarator
ptr-operator *ptr-declarator*

noptr-declarator:

declarator-id *attribute-specifier-seq_{opt}*
noptr-declarator *parameters-and-qualifiers*
noptr-declarator [*constant-expression_{opt}*] *attribute-specifier-seq_{opt}*
(*ptr-declarator*)

parameters-and-qualifiers:

(*parameter-declaration-clause*) *cv-qualifier-seq_{opt}*
ref-qualifier_{opt} *noexcept-specifier_{opt}* *attribute-specifier-seq_{opt}*

trailing-return-type:

-> *type-id*

ptr-operator:

* *attribute-specifier-seq_{opt}* *cv-qualifier-seq_{opt}*
& *attribute-specifier-seq_{opt}*
&& *attribute-specifier-seq_{opt}*
nested-name-specifier * *attribute-specifier-seq_{opt}* *cv-qualifier-seq_{opt}*

cv-qualifier-seq:

cv-qualifier *cv-qualifier-seq_{opt}*

cv-qualifier:

const
volatile

ref-qualifier:

&
&&

declarator-id:

..._{opt} *id-expression*

type-id:

type-specifier-seq *abstract-declarator_{opt}*

defining-type-id:

defining-type-specifier-seq *abstract-declarator_{opt}*

abstract-declarator:

ptr-abstract-declarator
noptr-abstract-declarator_{opt} *parameters-and-qualifiers* *trailing-return-type*
abstract-pack-declarator

ptr-abstract-declarator:

noptr-abstract-declarator
ptr-operator *ptr-abstract-declarator_{opt}*

noptr-abstract-declarator:

noptr-abstract-declarator_{opt} *parameters-and-qualifiers*
noptr-abstract-declarator_{opt} [*constant-expression_{opt}*] *attribute-specifier-seq_{opt}*
(*ptr-abstract-declarator*)

abstract-pack-declarator:

noptr-abstract-pack-declarator
ptr-operator *abstract-pack-declarator*

noptr-abstract-pack-declarator:

noptr-abstract-pack-declarator *parameters-and-qualifiers*
noptr-abstract-pack-declarator [*constant-expression_{opt}*] *attribute-specifier-seq_{opt}*
...

parameter-declaration-clause:
*parameter-declaration-list*_{opt} ... *opt*
parameter-declaration-list , ...

parameter-declaration-list:
parameter-declaration
parameter-declaration-list , *parameter-declaration*

parameter-declaration:
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *declarator*
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *declarator* = *initializer-clause*
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *abstract-declarator*_{opt}
*attribute-specifier-seq*_{opt} *decl-specifier-seq* *abstract-declarator*_{opt} = *initializer-clause*

function-definition:
*attribute-specifier-seq*_{opt} *decl-specifier-seq*_{opt} *declarator* *virt-specifier-seq*_{opt} *function-body*

function-body:
*ctor-initializer*_{opt} *compound-statement*
function-try-block
= **default** ;
= **delete** ;

initializer:
brace-or-equal-initializer
(*expression-list*)

brace-or-equal-initializer:
= *initializer-clause*
braced-init-list

initializer-clause:
assignment-expression
braced-init-list

initializer-list:
initializer-clause ... *opt*
initializer-list , *initializer-clause* ... *opt*

braced-init-list:
{ *initializer-list* , *opt* }
{ }

expr-or-braced-init-list:
expression
braced-init-list

A.8 Classes

[gram.class]

class-name:
identifier
simple-template-id

class-specifier:
class-head { *member-specification*_{opt} }

class-head:
class-key *attribute-specifier-seq*_{opt} *class-head-name* *class-virt-specifier*_{opt} *base-clause*_{opt}
class-key *attribute-specifier-seq*_{opt} *base-clause*_{opt}

class-head-name:
*nested-name-specifier*_{opt} *class-name*

```

class-virt-specifier:
    final

class-key:
    class
    struct
    union

member-specification:
    member-declaration member-specificationopt
    access-specifier : member-specificationopt

member-declaration:
    attribute-specifier-seqopt decl-specifier-seqopt member-declarator-listopt ;
    function-definition
    using-declaration
    static_assert-declaration
    template-declaration
    deduction-guide
    alias-declaration
    empty-declaration

member-declarator-list:
    member-declarator
    member-declarator-list , member-declarator

member-declarator:
    declarator virt-specifier-seqopt pure-specifieropt
    declarator brace-or-equal-initializeropt
    identifieropt attribute-specifier-seqopt : constant-expression

virt-specifier-seq:
    virt-specifier
    virt-specifier-seq virt-specifier

virt-specifier:
    override
    final

pure-specifier:
    = 0

```

A.9 Derived classes

[gram.derived]

```

base-clause:
    : base-specifier-list

base-specifier-list:
    base-specifier ...opt
    base-specifier-list , base-specifier ...opt

base-specifier:
    attribute-specifier-seqopt class-or-decltype
    attribute-specifier-seqopt virtual access-specifieropt class-or-decltype
    attribute-specifier-seqopt access-specifier virtualopt class-or-decltype

class-or-decltype:
    nested-name-specifieropt class-name
    nested-name-specifier template simple-template-id
    decltype-specifier

```

access-specifier:
private
protected
public

A.10 Special member functions

[gram.special]

conversion-function-id:
operator *conversion-type-id*

conversion-type-id:
type-specifier-seq *conversion-declarator*_{opt}

conversion-declarator:
ptr-operator *conversion-declarator*_{opt}

ctor-initializer:
 : *mem-initializer-list*

mem-initializer-list:
mem-initializer ..._{opt}
mem-initializer-list , *mem-initializer* ..._{opt}

mem-initializer:
mem-initializer-id (*expression-list*_{opt})
mem-initializer-id *braced-init-list*

mem-initializer-id:
class-or-decltype
identifier

A.11 Overloading

[gram.over]

operator-function-id:
operator *operator*

operator: one of

new	delete	new[]	delete[]						
+	-	*	/	%	^	&		~	
!	=	<	>	+=	--	*=	/=	%=	
^=	&=	=	<<	>>	>>=	<<=	==	!=	
<=	>=	&&		++	--	,	->*	->	
()	[]								

literal-operator-id:
operator *string-literal* *identifier*
operator *user-defined-string-literal*

A.12 Templates

[gram.temp]

template-declaration:
template < *template-parameter-list* > *declaration*

template-parameter-list:
template-parameter
template-parameter-list , *template-parameter*

template-parameter:
type-parameter
parameter-declaration

type-parameter:

```

    type-parameter-key ...opt identifieropt
    type-parameter-key identifieropt = type-id
    template < template-parameter-list > type-parameter-key ...opt identifieropt
    template < template-parameter-list > type-parameter-key identifieropt = id-expression

```

type-parameter-key:

```

    class
    typename

```

simple-template-id:

```

    template-name < template-argument-listopt >

```

template-id:

```

    simple-template-id
    operator-function-id < template-argument-listopt >
    literal-operator-id < template-argument-listopt >

```

template-name:

```

    identifier

```

template-argument-list:

```

    template-argument ...opt
    template-argument-list , template-argument ...opt

```

template-argument:

```

    constant-expression
    type-id
    id-expression

```

typename-specifier:

```

    typename nested-name-specifier identifier
    typename nested-name-specifier templateopt simple-template-id

```

explicit-instantiation:

```

    externopt template declaration

```

explicit-specialization:

```

    template < > declaration

```

deduction-guide:

```

    explicitopt template-name ( parameter-declaration-clause ) -> simple-template-id ;

```

A.13 Exception handling

[gram.except]

try-block:

```

    try compound-statement handler-seq

```

function-try-block:

```

    try ctor-initializeropt compound-statement handler-seq

```

handler-seq:

```

    handler handler-seqopt

```

handler:

```

    catch ( exception-declaration ) compound-statement

```

exception-declaration:

```

    attribute-specifier-seqopt type-specifier-seq declarator
    attribute-specifier-seqopt type-specifier-seq abstract-declaratoropt
    ...

```

```

noexcept-specifier:
    noexcept ( constant-expression )
    noexcept
    throw ( )

```

A.14 Preprocessing directives

[gram.cpp]

```

preprocessing-file:
    groupopt

group:
    group-part
    group group-part

group-part:
    control-line
    if-section
    text-line
    # conditionally-supported-directive

control-line:
    # include      pp-tokens new-line
    # define       identifier replacement-list new-line
    # define       identifier lparen identifier-listopt ) replacement-list new-line
    # define       identifier lparen ... ) replacement-list new-line
    # define       identifier lparen identifier-list , ... ) replacement-list new-line
    # undef        identifier new-line
    # line         pp-tokens new-line
    # error        pp-tokensopt new-line
    # pragma       pp-tokensopt new-line
    # new-line

if-section:
    if-group elif-groupsopt else-groupopt endif-line

if-group:
    # if           constant-expression new-line groupopt
    # ifdef        identifier new-line groupopt
    # ifndef       identifier new-line groupopt

elif-groups:
    elif-group
    elif-groups elif-group

elif-group:
    # elif         constant-expression new-line groupopt

else-group:
    # else         new-line groupopt

endif-line:
    # endif        new-line

text-line:
    pp-tokensopt new-line

conditionally-supported-directive:
    pp-tokens new-line

lparen:
    a ( character not immediately preceded by white-space

```

identifier-list:
 identifier
 identifier-list , *identifier*

replacement-list:
 *pp-tokens*_{opt}

pp-tokens:
 preprocessing-token
 pp-tokens *preprocessing-token*

new-line:
 the new-line character

defined-macro-expression:
 defined *identifier*
 defined (*identifier*)

h-preprocessing-token:
 any *preprocessing-token* other than >

h-pp-tokens:
 h-preprocessing-token
 h-pp-tokens *h-preprocessing-token*

has-include-expression:
 __has_include (< *h-char-sequence* >)
 __has_include (" *q-char-sequence* ")
 __has_include (*string-literal*)
 __has_include (< *h-pp-tokens* >)

Annex B (informative)

Implementation quantities [implimits]

- ¹ Because computers are finite, C++ implementations are inevitably limited in the size of the programs they can successfully process. Every implementation shall document those limitations where known. This documentation may cite fixed limits where they exist, say how to compute variable limits as a function of available resources, or say that fixed limits do not exist or are unknown.
 - ² The limits may constrain quantities that include those described below or others. The bracketed number following each quantity is recommended as the minimum for that quantity. However, these quantities are only guidelines and do not determine compliance.
- (2.1) — Nesting levels of compound statements, iteration control structures, and selection control structures [256].
 - (2.2) — Nesting levels of conditional inclusion [256].
 - (2.3) — Pointer, array, and function declarators (in any combination) modifying a class, arithmetic, or incomplete type in a declaration [256].
 - (2.4) — Nesting levels of parenthesized expressions within a full-expression [256].
 - (2.5) — Number of characters in an internal identifier or macro name [1 024].
 - (2.6) — Number of characters in an external identifier [1 024].
 - (2.7) — External identifiers in one translation unit [65 536].
 - (2.8) — Identifiers with block scope declared in one block [1 024].
 - (2.9) — Structured bindings introduced in one declaration [256].
 - (2.10) — Macro identifiers simultaneously defined in one translation unit [65 536].
 - (2.11) — Parameters in one function definition [256].
 - (2.12) — Arguments in one function call [256].
 - (2.13) — Parameters in one macro definition [256].
 - (2.14) — Arguments in one macro invocation [256].
 - (2.15) — Characters in one logical source line [65 536].
 - (2.16) — Characters in a string literal (after concatenation) [65 536].
 - (2.17) — Size of an object [262 144].
 - (2.18) — Nesting levels for `#include` files [256].
 - (2.19) — Case labels for a `switch` statement (excluding those for any nested `switch` statements) [16 384].
 - (2.20) — Data members in a single class [16 384].
 - (2.21) — Lambda-captures in one *lambda-expression* [256].
 - (2.22) — Enumeration constants in a single enumeration [4 096].
 - (2.23) — Levels of nested class definitions in a single *member-specification* [256].
 - (2.24) — Functions registered by `atexit()` [32].
 - (2.25) — Functions registered by `at_quick_exit()` [32].

- (2.26) — Direct and indirect base classes [16 384].
- (2.27) — Direct base classes for a single class [1 024].
- (2.28) — Members declared in a single class [4 096].
- (2.29) — Final overriding virtual functions in a class, accessible or not [16 384].
- (2.30) — Direct and indirect virtual bases of a class [1 024].
- (2.31) — Static members of a class [1 024].
- (2.32) — Friend declarations in a class [4 096].
- (2.33) — Access control declarations in a class [4 096].
- (2.34) — Member initializers in a constructor definition [6 144].
- (2.35) — *initializer-clauses* in one *braced-init-list* [16 384].
- (2.36) — Scope qualifications of one identifier [256].
- (2.37) — Nested external specifications [1 024].
- (2.38) — Recursive constexpr function invocations [512].
- (2.39) — Full-expressions evaluated within a core constant expression [1 048 576].
- (2.40) — Template arguments in a template declaration [1 024].
- (2.41) — Recursively nested template instantiations, including substitution during template argument deduction (17.8.2) [1 024].
- (2.42) — Handlers per try block [256].
- (2.43) — Number of placeholders (23.14.11.4) [10].

Annex C (informative)

Compatibility

[diff]

C.1 C++ and ISO C

[diff.iso]

- ¹ This subclause lists the differences between C++ and ISO C, by the chapters of this document.

C.1.1 Clause 5: lexical conventions

[diff.lex]

5.11

Change: New Keywords

New keywords are added to C++; see 5.11.

Rationale: These keywords were added in order to implement the new semantics of C++.

Effect on original feature: Change to semantics of well-defined feature. Any ISO C programs that used any of these keywords as identifiers are not valid C++ programs.

Difficulty of converting: Syntactic transformation. Converting one specific program is easy. Converting a large collection of related programs takes more work.

How widely used: Common.

5.13.3

Change: Type of character literal is changed from `int` to `char`.

Rationale: This is needed for improved overloaded function argument type matching. For example:

```
int function( int i );
int function( char c );

function( 'x' );
```

It is preferable that this call match the second version of function rather than the first.

Effect on original feature: Change to semantics of well-defined feature. ISO C programs which depend on

```
sizeof('x') == sizeof(int)
```

will not work the same as C++ programs.

Difficulty of converting: Simple.

How widely used: Programs which depend upon `sizeof('x')` are probably rare.

Subclause 5.13.5:

Change: String literals made `const`.

The type of a string literal is changed from “array of `char`” to “array of `const char`”. The type of a `char16_t` string literal is changed from “array of *some-integer-type*” to “array of `const char16_t`”. The type of a `char32_t` string literal is changed from “array of *some-integer-type*” to “array of `const char32_t`”. The type of a wide string literal is changed from “array of `wchar_t`” to “array of `const wchar_t`”.

Rationale: This avoids calling an inappropriate overloaded function, which might expect to be able to modify its argument.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Syntactic transformation. The fix is to add a cast:

```
char* p = "abc";           // valid in C, invalid in C++
void f(char*) {
    char* p = (char*)"abc"; // OK: cast added
    f(p);
    f((char*)"def");        // OK: cast added
```

```

}
```

How widely used: Programs that have a legitimate reason to treat string literals as pointers to potentially modifiable memory are probably rare.

C.1.2 Clause 6: basic concepts

[diff.basic]

6.1

Change: C++ does not have “tentative definitions” as in C.

E.g., at file scope,

```

int i;
int i;
```

is valid in C, invalid in C++. This makes it impossible to define mutually referential file-local static objects, if initializers are restricted to the syntactic forms of C. For example,

```

struct X { int i; struct X* next; };

static struct X a;
static struct X b = { 0, &a };
static struct X a = { 1, &b };
```

Rationale: This avoids having different initialization rules for fundamental types and user-defined types.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. In C++, the initializer for one of a set of mutually-referential file-local static objects must invoke a function call to achieve the initialization.

How widely used: Seldom.

6.3

Change: A `struct` is a scope in C++, not in C.

Rationale: Class scope is crucial to C++, and a `struct` is a class.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: C programs use `struct` extremely frequently, but the change is only noticeable when `struct`, enumeration, or enumerator names are referred to outside the `struct`. The latter is probably rare.

6.5 [also 10.1.7]

Change: A name of file scope that is explicitly declared `const`, and not explicitly declared `extern`, has internal linkage, while in C it would have external linkage.

Rationale: Because `const` objects may be used as values during translation in C++, this feature urges programmers to provide an explicit initializer for each `const` object. This feature allows the user to put `const` objects in source files that are included in more than one translation unit.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: Seldom.

6.6.1

Change: The `main` function cannot be called recursively and cannot have its address taken.

Rationale: The `main` function may require special actions.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Trivial: create an intermediary function such as `mymain(argc, argv)`.

How widely used: Seldom.

6.9

Change: C allows “compatible types” in several places, C++ does not.

For example, otherwise-identical **struct** types with different tag names are “compatible” in C but are distinctly different types in C++.

Rationale: Stricter type checking is essential for C++.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. The “typesafe linkage” mechanism will find many, but not all, of such problems. Those problems not found by typesafe linkage will continue to function properly, according to the “layout compatibility rules” of this International Standard.

How widely used: Common.

C.1.3 Clause 7: standard conversions

[diff.conv]

7.11

Change: Converting `void*` to a pointer-to-object type requires casting.

```
char a[10];
void* b=a;
void foo() {
    char* c=b;
}
```

ISO C will accept this usage of pointer to void being assigned to a pointer to object type. C++ will not.

Rationale: C++ tries harder than C to enforce compile-time type safety.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Could be automated. Violations will be diagnosed by the C++ translator. The fix is to add a cast. For example:

```
char* c = (char*) b;
```

How widely used: This is fairly widely used but it is good programming practice to add the cast when assigning pointer-to-void to pointer-to-object. Some ISO C translators will give a warning if the cast is not used.

C.1.4 Clause 8: expressions

[diff.expr]

8.2.2

Change: Implicit declaration of functions is not allowed.

Rationale: The type-safe nature of C++.

Effect on original feature: Deletion of semantically well-defined feature. Note: the original feature was labeled as “obsolescent” in ISO C.

Difficulty of converting: Syntactic transformation. Facilities for producing explicit function declarations are fairly widespread commercially.

How widely used: Common.

8.2.6, 8.3.2

Change: Decrement operator is not allowed with `bool` operand.

Rationale: Feature with surprising semantics.

Effect on original feature: A valid ISO C expression utilizing the decrement operator on a `bool` lvalue (for instance, via the C typedef in `<stdbool.h>`) is ill-formed in this International Standard.

8.3.3, 8.4

Change: Types must be defined in declarations, not in expressions.

In C, a `sizeof` expression or cast expression may define a new type. For example,

```
p = (void*)(struct x {int i;} *)0;
```

defines a new type, `struct x`.

Rationale: This prohibition helps to clarify the location of definitions in the source code.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation.

How widely used: Seldom.

8.16, 8.18, 8.19

Change: The result of a conditional expression, an assignment expression, or a comma expression may be an lvalue.

Rationale: C++ is an object-oriented language, placing relatively more emphasis on lvalues. For example, functions may return lvalues.

Effect on original feature: Change to semantics of well-defined feature. Some C expressions that implicitly rely on lvalue-to-rvalue conversions will yield different results. For example,

```
char arr[100];
sizeof(0, arr)
```

yields 100 in C++ and `sizeof(char*)` in C.

Difficulty of converting: Programs must add explicit casts to the appropriate rvalue.

How widely used: Rare.

C.1.5 Clause 9: statements

[diff.stat]

9.4.2, 9.6.4

Change: It is now invalid to jump past a declaration with explicit or implicit initializer (except across entire block not entered).

Rationale: Constructors used in initializers may allocate resources which need to be de-allocated upon leaving the block. Allowing jump past initializers would require complicated runtime determination of allocation. Furthermore, any use of the uninitialized object could be a disaster. With this simple compile-time rule, C++ assures that if an initialized variable is in scope, then it has assuredly been initialized.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: Seldom.

9.6.3

Change: It is now invalid to return (explicitly or implicitly) from a function which is declared to return a value without actually returning a value.

Rationale: The caller and callee may assume fairly elaborate return-value mechanisms for the return of class objects. If some flow paths execute a return without specifying any value, the implementation must embody many more complications. Besides, promising to return a value of a given type, and then not returning such a value, has always been recognized to be a questionable practice, tolerated only because very-old C had no distinction between void functions and int functions.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. Add an appropriate return value to the source code, such as zero.

How widely used: Seldom. For several years, many existing C implementations have produced warnings in this case.

C.1.6 Clause 10: declarations

[diff.dcl]

10.1.1

Change: In C++, the `static` or `extern` specifiers can only be applied to names of objects or functions. Using these specifiers with type declarations is illegal in C++. In C, these specifiers are ignored when used on type declarations.

Example:

```
static struct S {           // valid C, invalid in C++
    int i;
```

```
};
```

Rationale: Storage class specifiers don't have any meaning when associated with a type. In C++, class members can be declared with the **static** storage class specifier. Allowing storage class specifiers on type declarations could render the code confusing for users.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation.

How widely used: Seldom.

10.1.1

Change: In C++, **register** is not a storage class specifier.

Rationale: The storage class specifier had no effect in C++.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation.

How widely used: Common.

10.1.3

Change: A C++ typedef name must be different from any class type name declared in the same scope (except if the typedef is a synonym of the class name with the same name). In C, a typedef name and a struct tag name declared in the same scope can have the same name (because they have different name spaces).

Example:

```
typedef struct name1 { /* ... */ } name1;           // valid C and C++
struct name { /* ... */ };
typedef int name;                                   // valid C, invalid C++
```

Rationale: For ease of use, C++ doesn't require that a type name be prefixed with the keywords **class**, **struct** or **union** when used in object declarations or type casts.

Example:

```
class name { /* ... */ };
name i;                                           // i has type class name
```

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. One of the 2 types has to be renamed.

How widely used: Seldom.

10.1.7 [see also 6.5]

Change: **const** objects must be initialized in C++ but can be left uninitialized in C.

Rationale: A **const** object cannot be assigned to so it must be initialized to hold a useful value.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: Seldom.

10.1.7

Change: Banning implicit **int**.

In C++ a *decl-specifier-seq* must contain a *type-specifier*, unless it is followed by a declarator for a constructor, a destructor, or a conversion function. In the following example, the left-hand column presents valid C; the right-hand column presents equivalent C++:

<code>void f(const parm);</code>	<code>void f(const int parm);</code>
<code>const n = 3;</code>	<code>const int n = 3;</code>
<code>main()</code>	<code>int main()</code>
<code>/* ... */</code>	<code>/* ... */</code>

Rationale: In C++, implicit int creates several opportunities for ambiguity between expressions involving function-like casts and declarations. Explicit declaration is increasingly considered to be proper style. Liaison with WG14 (C) indicated support for (at least) deprecating implicit int in the next revision of C.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation. Could be automated.

How widely used: Common.

10.1.7.4

Change: The keyword `auto` cannot be used as a storage class specifier.

```
void f() {
    auto int x;    // valid C, invalid C++
}
```

Rationale: Allowing the use of `auto` to deduce the type of a variable from its initializer results in undesired interpretations of `auto` as a storage class specifier in certain contexts.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation.

How widely used: Rare.

10.2

Change: C++ objects of enumeration type can only be assigned values of the same enumeration type. In C, objects of enumeration type can be assigned values of any integral type.

Example:

```
enum color { red, blue, green };
enum color c = 1;    // valid C, invalid C++
```

Rationale: The type-safe nature of C++.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation. (The type error produced by the assignment can be automatically corrected by applying an explicit cast.)

How widely used: Common.

10.2

Change: In C++, the type of an enumerator is its enumeration. In C, the type of an enumerator is `int`.

Example:

```
enum e { A };
sizeof(A) == sizeof(int)    // in C
sizeof(A) == sizeof(e)     // in C++
/* and sizeof(int) is not necessarily equal to sizeof(e) */
```

Rationale: In C++, an enumeration is a distinct type.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: Seldom. The only time this affects existing C code is when the size of an enumerator is taken. Taking the size of an enumerator is not a common C coding practice.

C.1.7 Clause 11: declarators

[diff.decl]

11.3.5

Change: In C++, a function declared with an empty parameter list takes no arguments. In C, an empty

parameter list means that the number and type of the function arguments are unknown.

Example:

```
int f();           // means int f(void) in C++
                  // int f( unknown ) in C
```

Rationale: This is to avoid erroneous function calls (i.e., function calls with the wrong number or type of arguments).

Effect on original feature: Change to semantics of well-defined feature. This feature was marked as “obsolescent” in C.

Difficulty of converting: Syntactic transformation. The function declarations using C incomplete declaration style must be completed to become full prototype declarations. A program may need to be updated further if different calls to the same (non-prototype) function have different numbers of arguments or if the type of corresponding arguments differed.

How widely used: Common.

11.3.5 [see 8.3.3]

Change: In C++, types may not be defined in return or parameter types. In C, these type definitions are allowed.

Example:

```
void f( struct S { int a; } arg ) {} // valid C, invalid C++
enum E { A, B, C } f() {}          // valid C, invalid C++
```

Rationale: When comparing types in different translation units, C++ relies on name equivalence when C relies on structural equivalence. Regarding parameter types: since the type defined in a parameter list would be in the scope of the function, the only legal calls in C++ would be from within the function itself.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. The type definitions must be moved to file scope, or in header files.

How widely used: Seldom. This style of type definition is seen as poor coding style.

11.4

Change: In C++, the syntax for function definition excludes the “old-style” C function. In C, “old-style” syntax is allowed, but deprecated as “obsolescent”.

Rationale: Prototypes are essential to type safety.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Syntactic transformation.

How widely used: Common in old programs, but already known to be obsolescent.

11.6.2

Change: In C++, when initializing an array of character with a string, the number of characters in the string (including the terminating ‘\0’) must not exceed the number of elements in the array. In C, an array can be initialized with a string even if the array is not large enough to contain the string-terminating ‘\0’.

Example:

```
char array[4] = "abcd"; // valid C, invalid C++
```

Rationale: When these non-terminated arrays are manipulated by standard string functions, there is potential for major catastrophe.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. The arrays must be declared one element bigger to contain the string terminating ‘\0’.

How widely used: Seldom. This style of array initialization is seen as poor coding style.

C.1.8 Clause 12: classes

[diff.class]

12.1 [see also 10.1.3]

Change: In C++, a class declaration introduces the class name into the scope where it is declared and hides any object, function or other declaration of that name in an enclosing scope. In C, an inner scope declaration of a struct tag name never hides the name of an object or function in an outer scope.

Example:

```
int x[99];
void f() {
    struct x { int a; };
    sizeof(x); /* size of the array in C */
    /* size of the struct in C++ */
}
```

Rationale: This is one of the few incompatibilities between C and C++ that can be attributed to the new C++ name space definition where a name can be declared as a type and as a non-type in a single scope causing the non-type name to hide the type name and requiring that the keywords **class**, **struct**, **union** or **enum** be used to refer to the type name. This new name space definition provides important notational conveniences to C++ programmers and helps making the use of the user-defined types as similar as possible to the use of fundamental types. The advantages of the new name space definition were judged to outweigh by far the incompatibility with C described above.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation. If the hidden name that needs to be accessed is at global scope, the `::` C++ operator can be used. If the hidden name is at block scope, either the type or the struct tag has to be renamed.

How widely used: Seldom.

12.2.4

Change: Bit-fields of type plain **int** are signed.

Rationale: Leaving the choice of signedness to implementations could lead to inconsistent definitions of template specializations. For consistency, the implementation freedom was eliminated for non-dependent types, too.

Effect on original feature: The choice is implementation-defined in C, but not so in C++.

Difficulty of converting: Syntactic transformation.

How widely used: Seldom.

12.2.5

Change: In C++, the name of a nested class is local to its enclosing class. In C the name of the nested class belongs to the same scope as the name of the outermost enclosing class.

Example:

```
struct X {
    struct Y { /* ... */ } y;
};
struct Y yy;                // valid C, invalid C++
```

Rationale: C++ classes have member functions which require that classes establish scopes. The C rule would leave classes as an incomplete scope mechanism which would prevent C++ programmers from maintaining locality within a class. A coherent set of scope rules for C++ based on the C rule would be very complicated and C++ programmers would be unable to predict reliably the meanings of nontrivial examples involving

nested or local functions.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation. To make the struct type name visible in the scope of the enclosing struct, the struct tag could be declared in the scope of the enclosing struct, before the enclosing struct is defined. Example:

```
struct Y;                                // struct Y and struct X are at the same scope
struct X {
    struct Y { /* ... */ } y;
};
```

All the definitions of C struct types enclosed in other struct definitions and accessed outside the scope of the enclosing struct could be exported to the scope of the enclosing struct. Note: this is a consequence of the difference in scope rules, which is documented in 6.3.

How widely used: Seldom.

12.2.6

Change: In C++, a typedef name may not be redeclared in a class definition after being used in that definition.

Example:

```
typedef int I;
struct S {
    I i;
    int I;           // valid C, invalid C++
};
```

Rationale: When classes become complicated, allowing such a redefinition after the type has been used can create confusion for C++ programmers as to what the meaning of I really is.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. Either the type or the struct member has to be renamed.

How widely used: Seldom.

C.1.9 Clause 15: special member functions

[diff.special]

15.8

Change: Copying volatile objects.

The implicitly-declared copy constructor and implicitly-declared copy assignment operator cannot make a copy of a volatile lvalue. For example, the following is valid in ISO C:

```
struct X { int i; };
volatile struct X x1 = {0};
struct X x2 = x1;           // invalid C++
struct X x3;
x3 = x1;                   // also invalid C++
```

Rationale: Several alternatives were debated at length. Changing the parameter to `volatile const X&` would greatly complicate the generation of efficient code for class objects. Discussion of providing two alternative signatures for these implicitly-defined operations raised unanswered concerns about creating ambiguities and complicating the rules that specify the formation of these operators according to the bases and members.

Effect on original feature: Deletion of semantically well-defined feature.

Difficulty of converting: Semantic transformation. If volatile semantics are required for the copy, a

user-declared constructor or assignment must be provided. If non-volatile semantics are required, an explicit `const_cast` can be used.

How widely used: Seldom.

C.1.10 Clause 19: preprocessing directives

[diff.cpp]

19.8

Change: Whether `__STDC__` is defined and if so, what its value is, are implementation-defined.

Rationale: C++ is not identical to ISO C. Mandating that `__STDC__` be defined would require that translators make an incorrect claim. Each implementation must choose the behavior that will be most useful to its marketplace.

Effect on original feature: Change to semantics of well-defined feature.

Difficulty of converting: Semantic transformation.

How widely used: Programs and headers that reference `__STDC__` are quite common.

C.2 C++ and ISO C++ 2003

[diff.cpp03]

- ¹ This subclause lists the differences between C++ and ISO C++ 2003 (ISO/IEC 14882:2003, *Programming Language — C++*), by the chapters of this document.

C.2.1 Clause 5: lexical conventions

[diff.cpp03.lex]

5.4

Change: New kinds of string literals.

Rationale: Required for new features.

Effect on original feature: Valid C++ 2003 code may fail to compile or produce different results in this International Standard. Specifically, macros named `R`, `u8`, `u8R`, `u`, `uR`, `U`, `UR`, or `LR` will not be expanded when adjacent to a string literal but will be interpreted as part of the string literal. For example,

```
#define u8 "abc"
const char* s = u8"def";           // Previously "abcdef", now "def"
```

5.4

Change: User-defined literal string support.

Rationale: Required for new features.

Effect on original feature: Valid C++ 2003 code may fail to compile or produce different results in this International Standard, as the following example illustrates.

```
#define _x "there"
"hello"_x           // #1
```

Previously, `#1` would have consisted of two separate preprocessing tokens and the macro `_x` would have been expanded. In this International Standard, `#1` consists of a single preprocessing token, so the macro is not expanded.

5.11

Change: New keywords.

Rationale: Required for new features.

Effect on original feature: Added to Table 5, the following identifiers are new keywords: `alignas`, `alignof`, `char16_t`, `char32_t`, `constexpr`, `decltype`, `noexcept`, `nullptr`, `static_assert`, and `thread_local`. Valid C++ 2003 code using these identifiers is invalid in this International Standard.

5.13.2

Change: Type of integer literals.

Rationale: C99 compatibility.

Effect on original feature: Certain integer literals larger than can be represented by `long` could change from an unsigned integer type to `signed long long`.

C.2.2 Clause 7: standard conversions

[diff.cpp03.conv]

7.11**Change:** Only literals are integer null pointer constants.**Rationale:** Removing surprising interactions with templates and constant expressions.**Effect on original feature:** Valid C++ 2003 code may fail to compile or produce different results in this International Standard, as the following example illustrates:

```

void f(void *); // #1
void f(...);    // #2
template<int N> void g() {
    f(0*N);      // calls #2; used to call #1
}

```

C.2.3 Clause 8: expressions

[diff.cpp03.expr]

8.6**Change:** Specify rounding for results of integer / and %.**Rationale:** Increase portability, C99 compatibility.**Effect on original feature:** Valid C++ 2003 code that uses integer division rounds the result toward 0 or toward negative infinity, whereas this International Standard always rounds the result toward 0.**8.14****Change:** && is valid in a *type-name*.**Rationale:** Required for new features.**Effect on original feature:** Valid C++ 2003 code may fail to compile or produce different results in this International Standard, as the following example illustrates:

```

bool b1 = new int && false; // previously false, now ill-formed
struct S { operator int(); };
bool b2 = &S::operator int && false; // previously false, now ill-formed

```

C.2.4 Clause 10: declarations

[diff.cpp03.dcl.dcl]

10.1**Change:** Remove `auto` as a storage class specifier.**Rationale:** New feature.**Effect on original feature:** Valid C++ 2003 code that uses the keyword `auto` as a storage class specifier may be invalid in this International Standard. In this International Standard, `auto` indicates that the type of a variable is to be deduced from its initializer expression.**C.2.5 Clause 11: declarators**

[diff.cpp03.dcl.decl]

11.6.4**Change:** Narrowing restrictions in aggregate initializers.**Rationale:** Catches bugs.**Effect on original feature:** Valid C++ 2003 code may fail to compile in this International Standard. For example, the following code is valid in C++ 2003 but invalid in this International Standard because `double` to `int` is a narrowing conversion:

```

int x[] = { 2.0 };

```

C.2.6 Clause 15: special member functions

[diff.cpp03.special]

15.1, 15.4, 15.8**Change:** Implicitly-declared special member functions are defined as deleted when the implicit definition would have been ill-formed.**Rationale:** Improves template argument deduction failure.

Effect on original feature: A valid C++ 2003 program that uses one of these special member functions in a context where the definition is not required (e.g., in an expression that is not potentially evaluated) becomes ill-formed.

15.4 (destructors)

Change: User-declared destructors have an implicit exception specification.

Rationale: Clarification of destructor requirements.

Effect on original feature: Valid C++ 2003 code may execute differently in this International Standard. In particular, destructors that throw exceptions will call `std::terminate` (without calling `std::unexpected`) if their exception specification is non-throwing.

C.2.7 Clause 17: templates

[diff.cpp03.temp]

17.1

Change: Remove `export`.

Rationale: No implementation consensus.

Effect on original feature: A valid C++ 2003 declaration containing `export` is ill-formed in this International Standard.

17.3

Change: Remove whitespace requirement for nested closing template right angle brackets.

Rationale: Considered a persistent but minor annoyance. Template aliases representing non-class types would exacerbate whitespace issues.

Effect on original feature: Change to semantics of well-defined expression. A valid C++ 2003 expression containing a right angle bracket (“>”) followed immediately by another right angle bracket may now be treated as closing two templates. For example, the following code is valid in C++ 2003 because “>>” is a right-shift operator, but invalid in this International Standard because “>>” closes two templates.

```
template <class T> struct X { };
template <int N> struct Y { };
X< Y< 1 >> 2 > > x;
```

17.6.4.2

Change: Allow dependent calls of functions with internal linkage.

Rationale: Overly constrained, simplify overload resolution rules.

Effect on original feature: A valid C++ 2003 program could get a different result than this International Standard.

C.2.8 Clause 20: library introduction

[diff.cpp03.library]

20 – 33

Change: New reserved identifiers.

Rationale: Required by new features.

Effect on original feature: Valid C++ 2003 code that uses any identifiers added to the C++ standard library by this International Standard may fail to compile or produce different results in this International Standard. A comprehensive list of identifiers used by the C++ standard library can be found in the Index of Library Names in this International Standard.

20.5.1.2

Change: New headers.

Rationale: New functionality.

Effect on original feature: The following C++ headers are new: `<array>`, `<atomic>`, `<chrono>`, `<codecvt>`, `<condition_variable>`, `<forward_list>`, `<future>`, `<initializer_list>`, `<mutex>`, `<random>`, `<ratio>`, `<regex>`, `<scoped_allocator>`, `<system_error>`, `<thread>`, `<tuple>`, `<typeindex>`, `<type_traits>`, `<unordered_map>`, and `<unordered_set>`. In addition the following C compatibility headers are new:

<complex>, <cfenv>, <cstdint>, <cstdlib>, <stdbool>, <stdint>, <tgmath>, and <uchar>. Valid C++ 2003 code that #includes headers with these names may be invalid in this International Standard.

20.5.3.2

Effect on original feature: Function `swap` moved to a different header

Rationale: Remove dependency on <algorithm> for `swap`.

Effect on original feature: Valid C++ 2003 code that has been compiled expecting `swap` to be in <algorithm> may have to instead include <utility>.

20.5.4.2.2

Change: New reserved namespace.

Rationale: New functionality.

Effect on original feature: The global namespace `posix` is now reserved for standardization. Valid C++ 2003 code that uses a top-level namespace `posix` may be invalid in this International Standard.

20.5.5.3

Change: Additional restrictions on macro names.

Rationale: Avoid hard to diagnose or non-portable constructs.

Effect on original feature: Names of attribute identifiers may not be used as macro names. Valid C++ 2003 code that defines `override`, `final`, `carries_dependency`, or `noreturn` as macros is invalid in this International Standard.

C.2.9 Clause 21: language support library [diff.cpp03.language.support]

21.6.2.1

Change: Linking `new` and `delete` operators.

Rationale: The two throwing single-object signatures of `operator new` and `operator delete` are now specified to form the base functionality for the other operators. This clarifies that replacing just these two signatures changes others, even if they are not explicitly changed.

Effect on original feature: Valid C++ 2003 code that replaces global `new` or `delete` operators may execute differently in this International Standard. For example, the following program should write "custom deallocation" twice, once for the single-object `delete` and once for the array `delete`.

```
#include <stdio>
#include <stdlib>
#include <new>

void* operator new(std::size_t size) throw(std::bad_alloc) {
    return std::malloc(size);
}

void operator delete(void* ptr) throw() {
    std::puts("custom deallocation");
    std::free(ptr);
}

int main() {
    int* i = new int;
    delete i;                // single-object delete
    int* a = new int[3];
    delete [] a;             // array delete
}
```

21.6.2.1

Change: `operator new` may throw exceptions other than `std::bad_alloc`.

Rationale: Consistent application of `noexcept`.

Effect on original feature: Valid C++ 2003 code that assumes that global operator `new` only throws `std::bad_alloc` may execute differently in this International Standard.

C.2.10 Clause 22: diagnostics library [diff.cpp03.diagnostics]

22.4

Change: Thread-local error numbers.

Rationale: Support for new thread facilities.

Effect on original feature: Valid but implementation-specific C++ 2003 code that relies on `errno` being the same across threads may change behavior in this International Standard.

C.2.11 Clause 23: general utilities library [diff.cpp03.utilities]

23.10.4

Change: Minimal support for garbage-collected regions.

Rationale: Required by new feature.

Effect on original feature: Valid C++ 2003 code, compiled without traceable pointer support, that interacts with newer C++ code using regions declared reachable may have different runtime behavior.

23.14.5, 23.14.6, 23.14.7, 23.14.8, 23.14.9, D.8.3

Change: Standard function object types no longer derived from `std::unary_function` or `std::binary_function`.

Rationale: Superseded by new feature; `unary_function` and `binary_function` are no longer defined.

Effect on original feature: Valid C++ 2003 code that depends on function object types being derived from `unary_function` or `binary_function` may fail to compile in this International Standard.

C.2.12 Clause 24: strings library [diff.cpp03.strings]

24.3

Change: `basic_string` requirements no longer allow reference-counted strings.

Rationale: Invalidation is subtly different with reference-counted strings. This change regularizes behavior for this International Standard.

Effect on original feature: Valid C++ 2003 code may execute differently in this International Standard.

24.3.2.1

Change: Loosen `basic_string` invalidation rules.

Rationale: Allow small-string optimization.

Effect on original feature: Valid C++ 2003 code may execute differently in this International Standard. Some `const` member functions, such as `data` and `c_str`, no longer invalidate iterators.

C.2.13 Clause 26: containers library [diff.cpp03.containers]

26.2

Change: Complexity of `size()` member functions now constant.

Rationale: Lack of specification of complexity of `size()` resulted in divergent implementations with inconsistent performance characteristics.

Effect on original feature: Some container implementations that conform to C++ 2003 may not conform to the specified `size()` requirements in this International Standard. Adjusting containers such as `std::list` to the stricter requirements may require incompatible changes.

26.2

Change: Requirements change: relaxation.

Rationale: Clarification.

Effect on original feature: Valid C++ 2003 code that attempts to meet the specified container requirements may now be over-specified. Code that attempted to be portable across containers may need to be adjusted as follows:

- not all containers provide `size()`; use `empty()` instead of `size() == 0`;
- not all containers are empty after construction (`array`);
- not all containers have constant complexity for `swap()` (`array`).

26.2

Change: Requirements change: default constructible.

Rationale: Clarification of container requirements.

Effect on original feature: Valid C++ 2003 code that attempts to explicitly instantiate a container using a user-defined type with no default constructor may fail to compile.

26.2.3, 26.2.6

Change: Signature changes: from `void` return types.

Rationale: Old signature threw away useful information that may be expensive to recalculate.

Effect on original feature: The following member functions have changed:

- `erase(iter)` for `set`, `multiset`, `map`, `multimap`
- `erase(begin, end)` for `set`, `multiset`, `map`, `multimap`
- `insert(pos, num, val)` for `vector`, `deque`, `list`, `forward_list`
- `insert(pos, beg, end)` for `vector`, `deque`, `list`, `forward_list`

Valid C++ 2003 code that relies on these functions returning `void` (e.g., code that creates a pointer to member function that points to one of these functions) will fail to compile with this International Standard.

26.2.3, 26.2.6

Change: Signature changes: from `iterator` to `const_iterator` parameters.

Rationale: Overspecification.

Effect on original feature: The signatures of the following member functions changed from taking an `iterator` to taking a `const_iterator`:

- `insert(iter, val)` for `vector`, `deque`, `list`, `set`, `multiset`, `map`, `multimap`
- `insert(pos, beg, end)` for `vector`, `deque`, `list`, `forward_list`
- `erase(begin, end)` for `set`, `multiset`, `map`, `multimap`
- all forms of `list::splice`
- all forms of `list::merge`

Valid C++ 2003 code that uses these functions may fail to compile with this International Standard.

26.2.3, 26.2.6

Change: Signature changes: `resize`.

Rationale: Performance, compatibility with move semantics.

Effect on original feature: For `vector`, `deque`, and `list` the fill value passed to `resize` is now passed by reference instead of by value, and an additional overload of `resize` has been added. Valid C++ 2003 code that uses this function may fail to compile with this International Standard.

C.2.14 Clause 28: algorithms library

[diff.cpp03.algorithms]

28.1

Change: Result state of inputs after application of some algorithms.

Rationale: Required by new feature.

Effect on original feature: A valid C++ 2003 program may detect that an object with a valid but unspecified state has a different valid but unspecified state with this International Standard. For example, `std::remove` and `std::remove_if` may leave the tail of the input sequence with a different set of values than previously.

C.2.15 Clause 29: numerics library**[diff.cpp03.numerics]****29.5****Change:** Specified representation of complex numbers.**Rationale:** Compatibility with C99.**Effect on original feature:** Valid C++ 2003 code that uses implementation-specific knowledge about the binary representation of the required template specializations of `std::complex` may not be compatible with this International Standard.**C.2.16 Clause 30: input/output library****[diff.cpp03.input.output]****30.7.4.1.3, 30.7.5.1.3, 30.5.5.4****Change:** Specify use of `explicit` in existing boolean conversion functions.**Rationale:** Clarify intentions, avoid workarounds.**Effect on original feature:** Valid C++ 2003 code that relies on implicit boolean conversions will fail to compile with this International Standard. Such conversions occur in the following conditions:

- passing a value to a function that takes an argument of type `bool`;
- using `operator==` to compare to `false` or `true`;
- returning a value from a function with a return type of `bool`;
- initializing members of type `bool` via aggregate initialization;
- initializing a `const bool&` which would bind to a temporary.

30.5.3.1.1**Change:** Change base class of `std::ios_base::failure`.**Rationale:** More detailed error messages.**Effect on original feature:** `std::ios_base::failure` is no longer derived directly from `std::exception`, but is now derived from `std::system_error`, which in turn is derived from `std::runtime_error`. Valid C++ 2003 code that assumes that `std::ios_base::failure` is derived directly from `std::exception` may execute differently in this International Standard.**30.5.3****Change:** Flag types in `std::ios_base` are now bitmasks with values defined as constexpr static members.**Rationale:** Required for new features.**Effect on original feature:** Valid C++ 2003 code that relies on `std::ios_base` flag types being represented as `std::bitset` or as an integer type may fail to compile with this International Standard. For example:

```
#include <iostream>

int main() {
    int flag = std::ios_base::hex;
    std::cout.setf(flag);           // error: setf does not take argument of type int
}
```

C.3 C++ and ISO C++ 2011**[diff.cpp11]**

- ¹ This subclause lists the differences between C++ and ISO C++ 2011 (ISO/IEC 14882:2011, *Programming Languages — C++*), by the chapters of this document.

C.3.1 Clause 5: lexical conventions**[diff.cpp11.lex]****5.9****Change:** *pp-number* can contain one or more single quotes.**Rationale:** Necessary to enable single quotes as digit separators.**Effect on original feature:** Valid C++ 2011 code may fail to compile or may change meaning in this International Standard. For example, the following code is valid both in C++ 2011 and in this International

Standard, but the macro invocation produces different outcomes because the single quotes delimit a character literal in C++ 2011, whereas they are digit separators in this International Standard:

```
#define M(x, ...) __VA_ARGS__
int x[2] = { M(1'2,3'4, 5) };
// int x[2] = { 5 };           — C++ 2011
// int x[2] = { 3'4, 5 };     — this International Standard
```

C.3.2 Clause 6: basic concepts

[diff.cpp11.basic]

6.7.4.2

Change: New usual (non-placement) deallocator.

Rationale: Required for sized deallocation.

Effect on original feature: Valid C++ 2011 code could declare a global placement allocation function and deallocation function as follows:

```
void* operator new(std::size_t, std::size_t);
void operator delete(void*, std::size_t) noexcept;
```

In this International Standard, however, the declaration of `operator delete` might match a predefined usual (non-placement) `operator delete` (6.7.4). If so, the program is ill-formed, as it was for class member allocation functions and deallocation functions (8.3.4).

C.3.3 Clause 8: expressions

[diff.cpp11.expr]

8.16

Change: A conditional expression with a throw expression as its second or third operand keeps the type and value category of the other operand.

Rationale: Formerly mandated conversions (lvalue-to-rvalue (7.1), array-to-pointer (7.2), and function-to-pointer (7.3) standard conversions), especially the creation of the temporary due to lvalue-to-rvalue conversion, were considered gratuitous and surprising.

Effect on original feature: Valid C++ 2011 code that relies on the conversions may behave differently in this International Standard:

```
struct S {
    int x = 1;
    void mf() { x = 2; }
};
int f(bool cond) {
    S s;
    (cond ? s : throw 0).mf();
    return s.x;
}
```

In C++ 2011, `f(true)` returns 1. In this International Standard, it returns 2.

```
sizeof(true ? "" : throw 0)
```

In C++ 2011, the expression yields `sizeof(const char*)`. In this International Standard, it yields `sizeof(const char[1])`.

C.3.4 Clause 10: declarations

[diff.cpp11.dcl.dcl]

10.1.5

Change: `constexpr` non-static member functions are not implicitly `const` member functions.

Rationale: Necessary to allow `constexpr` member functions to mutate the object.

Effect on original feature: Valid C++ 2011 code may fail to compile in this International Standard. For example, the following code is valid in C++ 2011 but invalid in this International Standard because it declares the same member function twice with different return types:

```
struct S {
    constexpr const int &f();
    int &f();
};
```

C.3.5 Clause 11: declarators

[diff.cpp11.dcl.decl]

11.6.1

Change: Classes with default member initializers can be aggregates.

Rationale: Necessary to allow default member initializers to be used by aggregate initialization.

Effect on original feature: Valid C++ 2011 code may fail to compile or may change meaning in this International Standard.

```
struct S { // Aggregate in C++ 2014 onwards.
    int m = 1;
};
struct X {
    operator int();
    operator S();
};
X a{};
S b{a}; // uses copy constructor in C++ 2011,
        // performs aggregate initialization in this International Standard
```

C.3.6 Clause 20: library introduction

[diff.cpp11.library]

20.5.1.2

Change: New header.

Rationale: New functionality.

Effect on original feature: The C++ header `<shared_mutex>` is new. Valid C++ 2011 code that `#includes` a header with that name may be invalid in this International Standard.

C.3.7 Clause 30: input/output library

[diff.cpp11.input.output]

30.11

Change: `gets` is not defined.

Rationale: Use of `gets` is considered dangerous.

Effect on original feature: Valid C++ 2011 code that uses the `gets` function may fail to compile in this International Standard.

C.4 C++ and ISO C++ 2014

[diff.cpp14]

- ¹ This subclause lists the differences between C++ and ISO C++ 2014 (ISO/IEC 14882:2014, *Programming Language — C++*), by the chapters of this document.

C.4.1 Clause 5: lexical conventions

[diff.cpp14.lex]

5.2

Change: Removal of trigraph support as a required feature.

Rationale: Prevents accidental uses of trigraphs in non-raw string literals and comments.

Effect on original feature: Valid C++ 2014 code that uses trigraphs may not be valid or may have different semantics in this International Standard. Implementations may choose to translate trigraphs as specified in C++ 2014 if they appear outside of a raw string literal, as part of the implementation-defined mapping from physical source file characters to the basic source character set.

5.9

Change: *pp-number* can contain *p sign* and *P sign*.

Rationale: Necessary to enable hexadecimal floating literals.

Effect on original feature: Valid C++ 2014 code may fail to compile or produce different results in this International Standard. Specifically, character sequences like `0p+0` and `0e1_p+0` are three separate tokens each in C++ 2014, but one single token in this International Standard.

```
#define F(a) b ## a
int b0p = F(0p+0); // ill-formed; equivalent to "int b0p = b0p + 0;" in C++ 2014
```

C.4.2 Clause 8: expressions

[diff.cpp14.expr]

8.2.6, 8.3.2

Change: Remove increment operator with `bool` operand.

Rationale: Obsolete feature with occasionally surprising semantics.

Effect on original feature: A valid C++ 2014 expression utilizing the increment operator on a `bool` lvalue is ill-formed in this International Standard. Note that this might occur when the lvalue has a type given by a template parameter.

8.3.4, 8.3.5

Change: Dynamic allocation mechanism for over-aligned types.

Rationale: Simplify use of over-aligned types.

Effect on original feature: In C++ 2014 code that uses a *new-expression* to allocate an object with an over-aligned class type, where that class has no allocation functions of its own, `::operator new(std::size_t)` is used to allocate the memory. In this International Standard, `::operator new(std::size_t, std::align_val_t)` is used instead.

C.4.3 Clause 10: declarations

[diff.cpp14.dcl.dcl]

10.1.1

Change: Removal of `register storage-class-specifier`.

Rationale: Enable repurposing of deprecated keyword in future revisions of this International Standard.

Effect on original feature: A valid C++ 2014 declaration utilizing the `register storage-class-specifier` is ill-formed in this International Standard. The specifier can simply be removed to retain the original meaning.

10.1.7.4

Change: auto deduction from *braced-init-list*.

Rationale: More intuitive deduction behavior.

Effect on original feature: Valid C++ 2014 code may fail to compile or may change meaning in this International Standard. For example:

```
auto x1{1}; // was std::initializer_list<int>, now int
auto x2{1, 2}; // was std::initializer_list<int>, now ill-formed
```

C.4.4 Clause 11: declarators

[diff.cpp14.decl]

11.3.5

Change: Make exception specifications be part of the type system.

Rationale: Improve type-safety.

Effect on original feature: Valid C++ 2014 code may fail to compile or change meaning in this International Standard:

```
void g1() noexcept;
void g2();
template<class T> int f(T *, T *);
int x = f(g1, g2); // ill-formed; previously well-formed
```

11.6.1

Change: Definition of an aggregate is extended to apply to user-defined types with base classes.

Rationale: To increase convenience of aggregate initialization.

Effect on original feature: Valid C++ 2014 code may fail to compile or produce different results in this International Standard; initialization from an empty initializer list will perform aggregate initialization instead of invoking a default constructor for the affected types:

```
struct derived;
struct base {
    friend struct derived;
private:
    base();
};
struct derived : base {};

derived d1{};           // Error. The code was well-formed before.
derived d2;             // still OK
```

C.4.5 Clause 15: special member functions

[diff.cpp14.special]

15.6.3

Change: Inheriting a constructor no longer injects a constructor into the derived class.

Rationale: Better interaction with other language features.

Effect on original feature: Valid C++ 2014 code that uses inheriting constructors may not be valid or may have different semantics. A *using-declaration* that names a constructor now makes the corresponding base class constructors visible to initializations of the derived class rather than declaring additional derived class constructors.

```
struct A {
    template<typename T> A(T, typename T::type = 0);
    A(int);
};
struct B : A {
    using A::A;
    B(int);
};
B b(42L); // now calls B(int), used to call B<long>(long),
          // which called A(int) due to substitution failure
          // in A<long>(long).
```

C.4.6 Clause 17: templates

[diff.cpp14.temp]

17.8.2.5

Change: Allowance to deduce from the type of a non-type template argument.

Rationale: In combination with the ability to declare non-type template arguments with placeholder types, allows partial specializations to decompose from the type deduced for the non-type template argument.

Effect on original feature: Valid C++ 2014 code may fail to compile or produce different results in this International Standard:

```
template <int N> struct A;
template <typename T, T N> int foo(A<N> *) = delete;
void foo(void *);
void bar(A<0> *p) {
    foo(p); // ill-formed; previously well-formed
}
```

C.4.7 Clause 18: exception handling

[diff.cpp14.except]

18.4

Change: Remove dynamic exception specifications.

Rationale: Dynamic exception specifications were a deprecated feature that was complex and brittle in use. They interacted badly with the type system, which became a more significant issue in this International Standard where (non-dynamic) exception specifications are part of the function type.

Effect on original feature: A valid C++ 2014 function declaration, member function declaration, function pointer declaration, or function reference declaration, if it has a potentially throwing dynamic exception specification, will be rejected as ill-formed in this International Standard. Violating a non-throwing dynamic exception specification will call `terminate` rather than `unexpected` and might not perform stack unwinding prior to such a call.

C.4.8 Clause 20: library introduction

[diff.cpp14.library]

20.5.4.2.3

Change: New reserved namespaces.

Rationale: Reserve namespaces for future revisions of the standard library that might otherwise be incompatible with existing programs.

Effect on original feature: The global namespaces `std` followed by an arbitrary sequence of digits is reserved for future standardization. Valid C++ 2014 code that uses such a top-level namespace, e.g., `std2`, may be invalid in this International Standard.

C.4.9 Clause 23: general utilities library

[diff.cpp14.utilities]

23.14.13

Change: Constructors taking allocators removed.

Rationale: No implementation consensus.

Effect on original feature: Valid C++ 2014 code may fail to compile or may change meaning in this International Standard. Specifically, constructing a `std::function` with an allocator is ill-formed and uses-allocator construction will not pass an allocator to `std::function` constructors in this International Standard.

23.11.2.2

Change: Different constraint on conversions from `unique_ptr`.

Rationale: Adding array support to `shared_ptr`, via the syntax `shared_ptr<T[]>` and `shared_ptr<T[N]>`.

Effect on original feature: Valid C++ 2014 code may fail to compile or may change meaning in this International Standard. For example:

```
#include <memory>
std::unique_ptr<int[]> arr(new int[1]);
std::shared_ptr<int> ptr(std::move(arr)); // error: int(*)[] is not compatible with int*
```

C.4.10 Clause 24: strings library

[diff.cpp14.string]

24.3.2

Change: Non-const `.data()` member added.

Rationale: The lack of a non-const `.data()` differed from the similar member of `std::vector`. This change regularizes behavior for this International Standard.

Effect on original feature: Overloaded functions which have differing code paths for `char*` and `const char*` arguments will execute differently when called with a non-const string's `.data()` member in this International Standard.

```
int f(char *) = delete;
int f(const char *);
string s;
int x = f(s.data()); // ill-formed; previously well-formed
```

C.4.11 Clause 26: containers library**[diff.cpp14.containers]****26.2.6****Change:** Requirements change:**Rationale:** Increase portability, clarification of associative container requirements.**Effect on original feature:** Valid C++ 2014 code that attempts to use associative containers having a comparison object with non-const function call operator may fail to compile in this International Standard:

```
#include <set>

struct compare
{
    bool operator()(int a, int b)
    {
        return a < b;
    }
};

int main() {
    const std::set<int, compare> s;
    s.find(0);
}
```

C.4.12 Annex D: compatibility features**[diff.cpp14.depr]****Change:** The class templates `auto_ptr`, `unary_function`, and `binary_function`, the function templates `random_shuffle`, and the function templates (and their return types) `ptr_fun`, `mem_fun`, `mem_fun_ref`, `bind1st`, and `bind2nd` are not defined.**Rationale:** Superseded by new features.**Effect on original feature:** Valid C++ 2014 code that uses these class templates and function templates may fail to compile in this International Standard.**Change:** Remove old iostreams members [depr.ios.members].**Rationale:** Redundant feature for compatibility with pre-standard code has served its time.**Effect on original feature:** A valid C++ 2014 program using these identifiers may be ill-formed in this International Standard.**C.5 C standard library****[diff.library]**

- ¹ This subclause summarizes the explicit changes in headers, definitions, declarations, or behavior between the C standard library in the C standard and the parts of the C++ standard library that were included from the C standard library.

C.5.1 Modifications to headers**[diff.mods.to.headers]**

- ¹ For compatibility with the C standard library, the C++ standard library provides the C headers enumerated in D.5, but their use is deprecated in C++.
- ² There are no C++ headers for the C headers `<stdatomic.h>`, `<stdnoreturn.h>`, and `<threads.h>`, nor are the C headers themselves part of C++.
- ³ The C++ headers `<ccomplex>` (D.4.1) and `<ctgmath>` (D.4.4), as well as their corresponding C headers `<complex.h>` and `<tgmath.h>`, do not contain any of the content from the C standard library and instead merely include other headers from the C++ standard library.

- ⁴ The headers `<ciso646>`, `<cstdlibalign>` (D.4.2), and `<cstdlibbool>` (D.4.3) are meaningless in C++. Use of the C++ headers `<ccomplex>`, `<cstdlibalign>`, `<cstdlibbool>`, and `<ctgmath>` is deprecated (D.5).

C.5.2 Modifications to definitions [diff.mods.to.definitions]

C.5.2.1 Types `char16_t` and `char32_t` [diff.char16]

- ¹ The types `char16_t` and `char32_t` are distinct types rather than typedefs to existing integral types. The tokens `char16_t` and `char32_t` are keywords in this International Standard (5.11). They do not appear as macro names defined in `<cuchar>` (24.5.5).

C.5.2.2 Type `wchar_t` [diff.wchar.t]

- ¹ The type `wchar_t` is a distinct type rather than a typedef to an existing integral type. The token `wchar_t` is a keyword in this International Standard (5.11). It does not appear as a type name defined in any of `<cstdlibdef>` (21.2.1), `<cstdliblib>` (21.2.2), or `<cwchar>` (24.5.4).

C.5.2.3 Header `<assert.h>` [diff.header.assert.h]

- ¹ The token `static_assert` is a keyword in this International Standard (5.11). It does not appear as a macro name defined in `<cassert>` (22.3.1).

C.5.2.4 Header `<iso646.h>` [diff.header.iso646.h]

- ¹ The tokens `and`, `and_eq`, `bitand`, `bitor`, `compl`, `not_eq`, `not`, `or`, `or_eq`, `xor`, and `xor_eq` are keywords in this International Standard (5.11). They do not appear as macro names defined in `<ciso646>`.

C.5.2.5 Header `<stdalign.h>` [diff.header.stdalign.h]

- ¹ The token `alignas` is a keyword in this International Standard (5.11). It does not appear as a macro name defined in `<cstdlibalign>` (D.4.2).

C.5.2.6 Header `<stdbool.h>` [diff.header.stdbool.h]

- ¹ The tokens `bool`, `true`, and `false` are keywords in this International Standard (5.11). They do not appear as macro names defined in `<cstdlibbool>` (D.4.3).

C.5.2.7 Macro `NULL` [diff.null]

- ¹ The macro `NULL`, defined in any of `<locale>` (25.5), `<cstdlibdef>` (21.2.1), `<cstdio>` (30.11.1), `<cstdliblib>` (21.2.2), `<cstring>` (24.5.3), `<ctime>` (23.17.8), or `<cwchar>` (24.5.4), is an implementation-defined C++ null pointer constant in this International Standard (21.2).

C.5.3 Modifications to declarations [diff.mods.to.declarations]

- ¹ Header `<cstring>` (24.5.3): The following functions have different declarations:

- (1.1) — `strchr`
- (1.2) — `strpbrk`
- (1.3) — `strrchr`
- (1.4) — `strstr`
- (1.5) — `memchr`

Subclause 24.5.3 describes the changes.

- ² Header `<cwchar>` (24.5.4): The following functions have different declarations:

- (2.1) — `wcschr`
- (2.2) — `wcspbrk`
- (2.3) — `wcsrchr`

(2.4) — `wcsstr`

(2.5) — `wmemchr`

Subclause 24.5.4 describes the changes.

- ³ Header `<cstddef>` (21.2.1) declares the name `nullptr_t` in addition to the names declared in `<stddef.h>` in the C standard library.

C.5.4 Modifications to behavior [diff.mods.to.behavior]

- ¹ Header `<cstdlib>` (21.2.2): The following functions have different behavior:

(1.1) — `atexit`

(1.2) — `exit`

(1.3) — `abort`

Subclause 21.5 describes the changes.

- ² Header `<csetjmp>` (21.10.2): The following functions have different behavior:

(2.1) — `longjmp`

Subclause 21.10.2 describes the changes.

C.5.4.1 Macro `offsetof(type, member-designator)` [diff.offsetof]

- ¹ The macro `offsetof`, defined in `<cstddef>` (21.2.1), accepts a restricted set of *type* arguments in this International Standard. Subclause 21.2.4 describes the change.

C.5.4.2 Memory allocation functions [diff.malloc]

- ¹ The functions `aligned_alloc`, `calloc`, `malloc`, and `realloc` are restricted in this International Standard. Subclause 23.10.11 describes the changes.

Annex D (normative)

Compatibility features

[depr]

- ¹ This Clause describes features of the C++ Standard that are specified for compatibility with existing implementations.
- ² These are deprecated features, where *deprecated* is defined as: Normative for the current edition of this International Standard, but having been identified as a candidate for removal from future revisions. An implementation may declare library names and entities described in this section with the **deprecated** attribute (10.6.4).

D.1 Redclaration of **static constexpr** data members [depr.static_constexpr]

- ¹ For compatibility with prior C++ International Standards, a **constexpr** static data member may be redundantly redeclared outside the class with no initializer. This usage is deprecated. [*Example*:

```
struct A {
    static constexpr int n = 5; // definition (declaration in C++ 2014)
};

constexpr int A::n; // redundant declaration (definition in C++ 2014)
— end example]
```

D.2 Implicit declaration of copy functions [depr.impldec]

- ¹ The implicit definition of a copy constructor as defaulted is deprecated if the class has a user-declared copy assignment operator or a user-declared destructor. The implicit definition of a copy assignment operator as defaulted is deprecated if the class has a user-declared copy constructor or a user-declared destructor (15.4, 15.8). In a future revision of this International Standard, these implicit definitions could become deleted (11.4).

D.3 Deprecated exception specifications [depr.except.spec]

- ¹ The *noexcept-specifier* **throw()** is deprecated.

D.4 C++ standard library headers [depr.cpp.headers]

- ¹ For compatibility with prior C++ International Standards, the C++ standard library provides headers **<complex>** (D.4.1), **<cstdalign>** (D.4.2), **<cstdbool>** (D.4.3), and **<ctgmath>** (D.4.4). The use of these headers is deprecated.

D.4.1 Header **<complex>** synopsis [depr.ccomplex.syn]

```
#include <complex>
```

- ¹ The header **<complex>** behaves as if it simply includes the header **<complex>** (29.5.1).

D.4.2 Header **<cstdalign>** synopsis [depr.cstdalign.syn]

```
#define __alignas_is_defined 1
```

- ¹ The contents of the header **<cstdalign>** are the same as the C standard library header **<stdalign.h>**, with the following changes: The header **<cstdalign>** and the header **<stdalign.h>** shall not define a macro named **alignas**.

SEE ALSO: ISO C 7.15.

D.4.3 Header <stdbool> synopsis

[depr.cstdbool.syn]

```
#define __bool_true_false_are_defined 1
```

- ¹ The contents of the header <stdbool> are the same as the C standard library header <stdbool.h>, with the following changes: The header <stdbool> and the header <stdbool.h> shall not define macros named `bool`, `true`, or `false`.

SEE ALSO: ISO C 7.18.

D.4.4 Header <ctgmath> synopsis

[depr.ctgmath.syn]

```
#include <complex>
#include <cmath>
```

- ¹ The header <ctgmath> simply includes the headers <complex> (29.5.1) and <cmath> (29.9.1).
- ² [*Note:* The overloads provided in C by type-generic macros are already provided in <complex> and <cmath> by “sufficient” additional overloads. — *end note*]

D.5 C standard library headers

[depr.c.headers]

- ¹ For compatibility with the C standard library, the C++ standard library provides the *C headers* shown in Table 141.

Table 141 — C headers

<assert.h>	<inttypes.h>	<signal.h>	<stdio.h>	<wchar.h>
<complex.h>	<iso646.h>	<stdalign.h>	<stdlib.h>	<wctype.h>
<ctype.h>	<limits.h>	<stdarg.h>	<string.h>	
<errno.h>	<locale.h>	<stdbool.h>	<tgmath.h>	
<fenv.h>	<math.h>	<stddef.h>	<time.h>	
<float.h>	<setjmp.h>	<stdint.h>	<uchar.h>	

- ² The header <complex.h> behaves as if it simply includes the header <ccomplex>. The header <tgmath.h> behaves as if it simply includes the header <ctgmath>.
- ³ Every other C header, each of which has a name of the form `name.h`, behaves as if each name placed in the standard library namespace by the corresponding *cname* header is placed within the global namespace scope, except for the functions described in 29.9.5, the declaration of `std::byte` (21.2.1), and the functions and function templates described in 21.2.5. It is unspecified whether these names are first declared or defined within namespace scope (6.3.6) of the namespace `std` and are then injected into the global namespace scope by explicit *using-declarations* (10.3.3).
- ⁴ [*Example:* The header <cstdlib> assuredly provides its declarations and definitions within the namespace `std`. It may also provide these names within the global namespace. The header <stdlib.h> assuredly provides the same declarations and definitions within the global namespace, much as in the C Standard. It may also provide these names within the namespace `std`. — *end example*]

D.6 char* streams

[depr.str.strstreams]

- ¹ The header <strstream> defines three types that associate stream buffers with character array objects and assist reading and writing such objects.

D.6.1 Class strstreambuf

[depr.strstreambuf]

```
namespace std {
    class strstreambuf : public basic_streambuf<char> {
```

```

public:
    explicit strstreambuf(streamsize alsize_arg = 0);
    strstreambuf(void* (*palloc_arg)(size_t), void (*pfree_arg)(void*));
    strstreambuf(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
    strstreambuf(const char* gnext_arg, streamsize n);

    strstreambuf(signed char* gnext_arg, streamsize n,
        signed char* pbeg_arg = 0);
    strstreambuf(const signed char* gnext_arg, streamsize n);
    strstreambuf(unsigned char* gnext_arg, streamsize n,
        unsigned char* pbeg_arg = 0);
    strstreambuf(const unsigned char* gnext_arg, streamsize n);

    virtual ~strstreambuf();

    void freeze(bool freezefl = true);
    char* str();
    int pcount();

protected:
    int_type overflow(int_type c = EOF) override;
    int_type pbackfail(int_type c = EOF) override;
    int_type underflow() override;
    pos_type seekoff(off_type off, ios_base::seekdir way,
        ios_base::openmode which
        = ios_base::in | ios_base::out) override;
    pos_type seekpos(pos_type sp,
        ios_base::openmode which
        = ios_base::in | ios_base::out) override;
    streambuf* setbuf(char* s, streamsize n) override;

private:
    using strstate = T1;           // exposition only
    static const strstate allocated; // exposition only
    static const strstate constant; // exposition only
    static const strstate dynamic;  // exposition only
    static const strstate frozen;   // exposition only
    strstate strmode;               // exposition only
    streamsize alsize;              // exposition only
    void* (*palloc)(size_t);        // exposition only
    void (*pfree)(void*);           // exposition only
};
}

```

¹ The class `strstreambuf` associates the input sequence, and possibly the output sequence, with an object of some *character* array type, whose elements store arbitrary values. The array object has several attributes.

² [*Note:* For the sake of exposition, these are represented as elements of a bitmask type (indicated here as `T1`) called `strstate`. The elements are:

- (2.1) — `allocated`, set when a dynamic array object has been allocated, and hence should be freed by the destructor for the `strstreambuf` object;
- (2.2) — `constant`, set when the array object has `const` elements, so the output sequence cannot be written;
- (2.3) — `dynamic`, set when the array object is allocated (or reallocated) as necessary to hold a character sequence that can change in length;

- (2.4) — **frozen**, set when the program has requested that the array object not be altered, reallocated, or freed.
— *end note*]

3 [*Note*: For the sake of exposition, the maintained data is presented here as:

- (3.1) — **strstate** **strmode**, the attributes of the array object associated with the **strstreambuf** object;
 (3.2) — **int** **alsize**, the suggested minimum size for a dynamic array object;
 (3.3) — **void*** (***palloc**)(**size_t**), points to the function to call to allocate a dynamic array object;
 (3.4) — **void** (***pfree**)(**void***), points to the function to call to free a dynamic array object.
 — *end note*]

- 4 Each object of class **strstreambuf** has a *seekable area*, delimited by the pointers **seeklow** and **seekhigh**. If **gnext** is a null pointer, the seekable area is undefined. Otherwise, **seeklow** equals **gbeg** and **seekhigh** is either **pend**, if **pend** is not a null pointer, or **gend**.

D.6.1.1 **strstreambuf** constructors

[depr.strstreambuf.cons]

```
explicit strstreambuf(streamsize alsize_arg = 0);
```

- 1 *Effects*: Constructs an object of class **strstreambuf**, initializing the base class with **streambuf**(). The postconditions of this function are indicated in Table 142.

Table 142 — **strstreambuf**(**streamsize**) effects

Element	Value
strmode	dynamic
alsize	alsize_arg
palloc	a null pointer
pfree	a null pointer

```
strstreambuf(void* (*palloc_arg)(size_t), void (*pfree_arg)(void*));
```

- 2 *Effects*: Constructs an object of class **strstreambuf**, initializing the base class with **streambuf**(). The postconditions of this function are indicated in Table 143.

Table 143 — **strstreambuf**(**void*** (*) (**size_t**), **void** (*) (**void***)) effects

Element	Value
strmode	dynamic
alsize	an unspecified value
palloc	palloc_arg
pfree	pfree_arg

```
strstreambuf(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
strstreambuf(signed char* gnext_arg, streamsize n,
             signed char* pbeg_arg = 0);
strstreambuf(unsigned char* gnext_arg, streamsize n,
             unsigned char* pbeg_arg = 0);
```

- 3 *Effects*: Constructs an object of class **strstreambuf**, initializing the base class with **streambuf**(). The postconditions of this function are indicated in Table 144.

Table 144 — `strstreambuf(charT*, streamsize, charT*)` effects

Element	Value
<code>strmode</code>	0
<code>alsize</code>	an unspecified value
<code>palloc</code>	a null pointer
<code>pfree</code>	a null pointer

4 `gnext_arg` shall point to the first element of an array object whose number of elements `N` is determined as follows:

(4.1) — If `n > 0`, `N` is `n`.

(4.2) — If `n == 0`, `N` is `std::strlen(gnext_arg)`.

(4.3) — If `n < 0`, `N` is `INT_MAX`.³³¹

5 If `pbeg_arg` is a null pointer, the function executes:

```
setg(gnext_arg, gnext_arg, gnext_arg + N);
```

6 Otherwise, the function executes:

```
setg(gnext_arg, gnext_arg, pbeg_arg);
setp(pbeg_arg, pbeg_arg + N);
```

```
strstreambuf(const char* gnext_arg, streamsize n);
strstreambuf(const signed char* gnext_arg, streamsize n);
strstreambuf(const unsigned char* gnext_arg, streamsize n);
```

7 *Effects:* Behaves the same as `strstreambuf((char*)gnext_arg,n)`, except that the constructor also sets constant in `strmode`.

```
virtual ~strstreambuf();
```

8 *Effects:* Destroys an object of class `strstreambuf`. The function frees the dynamically allocated array object only if `(strmode & allocated) != 0` and `(strmode & frozen) == 0`. (D.6.1.3 describes how a dynamically allocated array object is freed.)

D.6.1.2 Member functions

[depr.strstreambuf.members]

```
void freeze(bool freezefl = true);
```

1 *Effects:* If `strmode & dynamic` is nonzero, alters the freeze status of the dynamic array object as follows:

(1.1) — If `freezefl` is `true`, the function sets `frozen` in `strmode`.

(1.2) — Otherwise, it clears `frozen` in `strmode`.

```
char* str();
```

2 *Effects:* Calls `freeze()`, then returns the beginning pointer for the input sequence, `gbeg`.

3 *Remarks:* The return value can be a null pointer.

```
int pcount() const;
```

³³¹) The function signature `strlen(const char*)` is declared in `<cstring>` (24.5.3). The macro `INT_MAX` is defined in `<climits>` (21.3.5).

- 4 *Effects:* If the next pointer for the output sequence, `pnext`, is a null pointer, returns zero. Otherwise, returns the current effective length of the array object as the next pointer minus the beginning pointer for the output sequence, `pnext - pbeg`.

D.6.1.3 `strstreambuf` overridden virtual functions

[depr.strstreambuf.virtuals]

`int_type overflow(int_type c = EOF) override;`

- 1 *Effects:* Appends the character designated by `c` to the output sequence, if possible, in one of two ways:
- (1.1) — If `c != EOF` and if either the output sequence has a write position available or the function makes a write position available (as described below), assigns `c` to `*pnext++`.
Returns `(unsigned char)c`.
- (1.2) — If `c == EOF`, there is no character to append.
Returns a value other than `EOF`.
- 2 Returns `EOF` to indicate failure.
- 3 *Remarks:* The function can alter the number of write positions available as a result of any call.
- 4 To make a write position available, the function reallocates (or initially allocates) an array object with a sufficient number of elements `n` to hold the current array object (if any), plus at least one additional write position. How many additional write positions are made available is otherwise unspecified.³³² If `palloc` is not a null pointer, the function calls `(*palloc)(n)` to allocate the new dynamic array object. Otherwise, it evaluates the expression `new charT[n]`. In either case, if the allocation fails, the function returns `EOF`. Otherwise, it sets `allocated` in `strmode`.
- 5 To free a previously existing dynamic array object whose first element address is `p`: If `pfree` is not a null pointer, the function calls `(*pfree)(p)`. Otherwise, it evaluates the expression `delete[]p`.
- 6 If `(strmode & dynamic) == 0`, or if `(strmode & frozen) != 0`, the function cannot extend the array (reallocate it with greater length) to make a write position available.

`int_type pbackfail(int_type c = EOF) override;`

- 7 Puts back the character designated by `c` to the input sequence, if possible, in one of three ways:
- (7.1) — If `c != EOF`, if the input sequence has a putback position available, and if `(char)c == gnext[-1]`, assigns `gnext - 1` to `gnext`.
Returns `c`.
- (7.2) — If `c != EOF`, if the input sequence has a putback position available, and if `strmode & constant` is zero, assigns `c` to `*--gnext`.
Returns `c`.
- (7.3) — If `c == EOF` and if the input sequence has a putback position available, assigns `gnext - 1` to `gnext`.
Returns a value other than `EOF`.
- 8 Returns `EOF` to indicate failure.
- 9 *Remarks:* If the function can succeed in more than one of these ways, it is unspecified which way is chosen. The function can alter the number of putback positions available as a result of any call.

`int_type underflow() override;`

³³²) An implementation should consider `alsize` in making this decision.

10 *Effects:* Reads a character from the *input sequence*, if possible, without moving the stream position past it, as follows:

(10.1) — If the input sequence has a read position available, the function signals success by returning `(unsigned char)*gnext`.

(10.2) — Otherwise, if the current write next pointer `pnext` is not a null pointer and is greater than the current read end pointer `gend`, makes a *read position* available by assigning to `gend` a value greater than `gnext` and no greater than `pnext`.

Returns `(unsigned char)*gnext`.

11 Returns EOF to indicate failure.

12 *Remarks:* The function can alter the number of read positions available as a result of any call.

`pos_type seekoff(off_type off, seekdir way, openmode which = in | out) override;`

13 *Effects:* Alters the stream position within one of the controlled sequences, if possible, as indicated in Table 145.

Table 145 — `seekoff` positioning

Conditions	Result
<code>(which & ios::in) != 0</code>	positions the input sequence
<code>(which & ios::out) != 0</code>	positions the output sequence
<code>(which & (ios::in ios::out)) == (ios::in ios::out)</code> and <code>way == either ios::beg or ios::end</code>	positions both the input and the output sequences
Otherwise	the positioning operation fails.

14 For a sequence to be positioned, if its next pointer is a null pointer, the positioning operation fails. Otherwise, the function determines `newoff` as indicated in Table 146.

Table 146 — `newoff` values

Condition	<code>newoff</code> Value
<code>way == ios::beg</code>	0
<code>way == ios::cur</code>	the next pointer minus the beginning pointer (<code>xnext - xbeg</code>).
<code>way == ios::end</code>	<code>seekhigh</code> minus the beginning pointer (<code>seekhigh - xbeg</code>).

15 If `(newoff + off) < (seeklow - xbeg)` or `(seekhigh - xbeg) < (newoff + off)`, the positioning operation fails. Otherwise, the function assigns `xbeg + newoff + off` to the next pointer `xnext`.

16 *Returns:* `pos_type(newoff)`, constructed from the resultant offset `newoff` (of type `off_type`), that stores the resultant stream position, if possible. If the positioning operation fails, or if the constructed object cannot represent the resultant stream position, the return value is `pos_type(off_type(-1))`.

`pos_type seekpos(pos_type sp, ios_base::openmode which
= ios_base::in | ios_base::out) override;`

- 17 *Effects:* Alters the stream position within one of the controlled sequences, if possible, to correspond to the stream position stored in `sp` (as described below).
- (17.1) — If `(which & ios::in) != 0`, positions the input sequence.
- (17.2) — If `(which & ios::out) != 0`, positions the output sequence.
- (17.3) — If the function positions neither sequence, the positioning operation fails.
- 18 For a sequence to be positioned, if its next pointer is a null pointer, the positioning operation fails. Otherwise, the function determines `newoff` from `sp.offset()`:
- (18.1) — If `newoff` is an invalid stream position, has a negative value, or has a value greater than `(seekhigh - seeklow)`, the positioning operation fails
- (18.2) — Otherwise, the function adds `newoff` to the beginning pointer `xbeg` and stores the result in the next pointer `xnext`.
- 19 *Returns:* `pos_type(newoff)`, constructed from the resultant offset `newoff` (of type `off_type`), that stores the resultant stream position, if possible. If the positioning operation fails, or if the constructed object cannot represent the resultant stream position, the return value is `pos_type(off_type(-1))`.
- `streambuf<char>* setbuf(char* s, streamsize n)` override;
- 20 *Effects:* Implementation defined, except that `setbuf(0, 0)` has no effect.

D.6.2 Class `istream`

[depr.istream]

```
namespace std {
    class istream : public basic_istream<char> {
    public:
        explicit istream(const char* s);
        explicit istream(char* s);
        istream(const char* s, streamsize n);
        istream(char* s, streamsize n);
        virtual ~istream();

        strstreambuf* rdbuf() const;
        char* str();
    private:
        strstreambuf sb; // exposition only
    };
}
```

- 1 The class `istream` supports the reading of objects of class `strstreambuf`. It supplies a `strstreambuf` object to control the associated array object. For the sake of exposition, the maintained data is presented here as:
- (1.1) — `sb`, the `strstreambuf` object.

D.6.2.1 `istream` constructors

[depr.istream.cons]

```
explicit istream(const char* s);
explicit istream(char* s);
```

- 1 *Effects:* Constructs an object of class `istream`, initializing the base class with `istream(&sb)` and initializing `sb` with `strstreambuf(s,0)`. `s` shall designate the first element of an NTBS.

```
istream(const char* s, streamsize n);
istream(char* s, streamsize n);
```

- 2 *Effects:* Constructs an object of class `istream`, initializing the base class with `istream(&sb)` and initializing `sb` with `strstreambuf(s,n)`. `s` shall designate the first element of an array whose length is `n` elements, and `n` shall be greater than zero.

D.6.2.2 Member functions

[depr.istream.members]

```
strstreambuf* rdbuf() const;
```

- 1 *Returns:* `const_cast<strstreambuf*>(&sb)`.

```
char* str();
```

- 2 *Returns:* `rdbuf()->str()`.

D.6.3 Class `ostream`

[depr.ostream]

```
namespace std {
    class ostream : public basic_ostream<char> {
    public:
        ostream();
        ostream(char* s, int n, ios_base::openmode mode = ios_base::out);
        virtual ~ostream();

        strstreambuf* rdbuf() const;
        void freeze(bool freezefl = true);
        char* str();
        int pcount() const;
    private:
        strstreambuf sb; // exposition only
    };
}
```

- 1 The class `ostream` supports the writing of objects of class `strstreambuf`. It supplies a `strstreambuf` object to control the associated array object. For the sake of exposition, the maintained data is presented here as:

- (1.1) — `sb`, the `strstreambuf` object.

D.6.3.1 `ostream` constructors

[depr.ostream.cons]

```
ostream();
```

- 1 *Effects:* Constructs an object of class `ostream`, initializing the base class with `ostream(&sb)` and initializing `sb` with `strstreambuf()`.

```
ostream(char* s, int n, ios_base::openmode mode = ios_base::out);
```

- 2 *Effects:* Constructs an object of class `ostream`, initializing the base class with `ostream(&sb)`, and initializing `sb` with one of two constructors:

- (2.1) — If `(mode & app) == 0`, then `s` shall designate the first element of an array of `n` elements.

The constructor is `strstreambuf(s, n, s)`.

- (2.2) — If `(mode & app) != 0`, then `s` shall designate the first element of an array of `n` elements that contains an NTBS whose first element is designated by `s`. The constructor is `strstreambuf(s, n, s + std::strlen(s))`.³³³

D.6.3.2 Member functions

[depr.ostream.members]

333) The function signature `strlen(const char*)` is declared in `<cstring>` (24.5.3).

```

    strstreambuf* rdbuf() const;
1    Returns: (strstreambuf*)&sb.

    void freeze(bool freezefl = true);
2    Effects: Calls rdbuf()->freeze(freezefl).

    char* str();
3    Returns: rdbuf()->str().

    int pcount() const;
4    Returns: rdbuf()->pcount().

```

D.6.4 Class strstream

[depr.strstream]

```

namespace std {
    class strstream
        : public basic_istream<char> {
    public:
        // Types
        using char_type = char;
        using int_type = char_traits<char>::int_type;
        using pos_type = char_traits<char>::pos_type;
        using off_type = char_traits<char>::off_type;

        // constructors/destructor
        strstream();
        strstream(char* s, int n,
            ios_base::openmode mode = ios_base::in|ios_base::out);
        virtual ~strstream();

        // Members:
        strstreambuf* rdbuf() const;
        void freeze(bool freezefl = true);
        int pcount() const;
        char* str();

    private:
        strstreambuf sb; // exposition only
    };
}

```

1 The class `strstream` supports reading and writing from objects of class `strstreambuf`. It supplies a `strstreambuf` object to control the associated array object. For the sake of exposition, the maintained data is presented here as:

(1.1) — `sb`, the `strstreambuf` object.

D.6.4.1 strstream constructors

[depr.strstream.cons]

```

strstream();
1    Effects: Constructs an object of class strstream, initializing the base class with istream(&sb).

strstream(char* s, int n,
    ios_base::openmode mode = ios_base::in|ios_base::out);

```

² *Effects:* Constructs an object of class `stringstream`, initializing the base class with `iostream(&sb)` and initializing `sb` with one of the two constructors:

- (2.1) — If `(mode & app) == 0`, then `s` shall designate the first element of an array of `n` elements. The constructor is `stringstreambuf(s,n,s)`.
- (2.2) — If `(mode & app) != 0`, then `s` shall designate the first element of an array of `n` elements that contains an NTBS whose first element is designated by `s`. The constructor is `stringstreambuf(s,n,s + std::strlen(s))`.

D.6.4.2 `stringstream` destructor

[depr stringstream.dest]

```
virtual ~stringstream();
```

¹ *Effects:* Destroys an object of class `stringstream`.

D.6.4.3 `stringstream` operations

[depr stringstream.oper]

```
stringstreambuf* rdbuf() const;
```

¹ *Returns:* `&sb`.

```
void freeze(bool freezefl = true);
```

² *Effects:* Calls `rdbuf()->freeze(freezefl)`.

```
char* str();
```

³ *Returns:* `rdbuf()->str()`.

```
int pcount() const;
```

⁴ *Returns:* `rdbuf()->pcount()`.

D.7 `uncaught_exception`

[depr.uncaught]

¹ The header `<exception>` has the following addition:

```
namespace std {
    bool uncaught_exception() noexcept;
}
```

```
bool uncaught_exception() noexcept;
```

² *Returns:* `uncaught_exceptions() > 0`.

D.8 Old adaptable function bindings

[depr.func.adaptor.binding]

D.8.1 Weak result types

[depr.weak.result_type]

¹ A call wrapper (23.14.2) may have a *weak result type*. If it does, the type of its member type `result_type` is based on the type `T` of the wrapper's target object:

- (1.1) — if `T` is a pointer to function type, `result_type` shall be a synonym for the return type of `T`;
- (1.2) — if `T` is a pointer to member function, `result_type` shall be a synonym for the return type of `T`;
- (1.3) — if `T` is a class type and the *qualified-id* `T::result_type` is valid and denotes a type (17.8.2), then `result_type` shall be a synonym for `T::result_type`;
- (1.4) — otherwise `result_type` shall not be defined.

D.8.2 Typedefs to support function binders

[depr.func.adaptor.typedefs]

¹ To enable old function adaptors to manipulate function objects that take one or two arguments, many of the function objects in this International Standard correspondingly provide *typedef-names* `argument_type` and

result_type for function objects that take one argument and first_argument_type, second_argument_type, and result_type for function objects that take two arguments.

- ² The following member names are defined in addition to names specified in Clause 23.14:

```
namespace std {
    template<class T> struct owner_less<shared_ptr<T>> {
        using result_type      = bool;
        using first_argument_type = shared_ptr<T>;
        using second_argument_type = shared_ptr<T>;
    };

    template<class T> struct owner_less<weak_ptr<T>> {
        using result_type      = bool;
        using first_argument_type = weak_ptr<T>;
        using second_argument_type = weak_ptr<T>;
    };

    template <class T> class reference_wrapper {
    public :
        using result_type      = see below; // not always defined
        using argument_type    = see below; // not always defined
        using first_argument_type = see below; // not always defined
        using second_argument_type = see below; // not always defined
    };

    template <class T> struct plus {
        using first_argument_type = T;
        using second_argument_type = T;
        using result_type      = T;
    };

    template <class T> struct minus {
        using first_argument_type = T;
        using second_argument_type = T;
        using result_type      = T;
    };

    template <class T> struct multiplies {
        using first_argument_type = T;
        using second_argument_type = T;
        using result_type      = T;
    };

    template <class T> struct divides {
        using first_argument_type = T;
        using second_argument_type = T;
        using result_type      = T;
    };

    template <class T> struct modulus {
        using first_argument_type = T;
        using second_argument_type = T;
        using result_type      = T;
    };
};
```

```
template <class T> struct negate {
    using argument_type = T;
    using result_type   = T;
};

template <class T> struct equal_to {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct not_equal_to {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct greater {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct less {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct greater_equal {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct less_equal {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct logical_and {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct logical_or {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type          = bool;
};

template <class T> struct logical_not {
    using argument_type = T;
};
```

```

    using result_type    = bool;
};

template <class T> struct bit_and {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type         = T;
};

template <class T> struct bit_or {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type         = T;
};

template <class T> struct bit_xor {
    using first_argument_type  = T;
    using second_argument_type = T;
    using result_type         = T;
};

template <class T> struct bit_not {
    using argument_type = T;
    using result_type   = T;
};

template<class R, class T1>
class function<R(T1)> {
public:
    using argument_type = T1;
};

template<class R, class T1, class T2>
class function<R(T1, T2)> {
public:
    using first_argument_type  = T1;
    using second_argument_type = T2;
};
}

```

- ³ `reference_wrapper<T>` has a weak result type (D.8.1). If `T` is a function type, `result_type` shall be a synonym for the return type of `T`.
- ⁴ The template specialization `reference_wrapper<T>` shall define a nested type named `argument_type` as a synonym for `T1` only if the type `T` is any of the following:
- (4.1) — a function type or a pointer to function type taking one argument of type `T1`
 - (4.2) — a pointer to member function `R T0::f() cv` (where *cv* represents the member function's cv-qualifiers); the type `T1` is *cv* `T0*`
 - (4.3) — a class type where the *qualified-id* `T::argument_type` is valid and denotes a type (17.8.2); the type `T1` is `T::argument_type`.
- ⁵ The template instantiation `reference_wrapper<T>` shall define two nested types named `first_argument_type` and `second_argument_type` as synonyms for `T1` and `T2`, respectively, only if the type `T` is any of the following:

- (5.1) — a function type or a pointer to function type taking two arguments of types T1 and T2
 - (5.2) — a pointer to member function `R T0::f(T2) cv` (where *cv* represents the member function's cv-qualifiers); the type T1 is *cv* T0*
 - (5.3) — a class type where the *qualified-ids* `T::first_argument_type` and `T::second_argument_type` are both valid and both denote types (17.8.2); the type T1 is `T::first_argument_type` and the type T2 is `T::second_argument_type`.
- 6 All enabled specializations `hash<Key>` of `hash` (23.14.15) provide two nested types, `result_type` and `argument_type`, which shall be synonyms for `size_t` and `Key`, respectively.
 - 7 The forwarding call wrapper `g` returned by a call to `bind(f, bound_args...)` (23.14.11.3) shall have a weak result type (D.8.1).
 - 8 The forwarding call wrapper `g` returned by a call to `bind<R>(f, bound_args...)` (23.14.11.3) shall have a nested type `result_type` defined as a synonym for `R`.
 - 9 The simple call wrapper returned from a call to `mem_fn(pm)` shall have a nested type `result_type` that is a synonym for the return type of `pm` when `pm` is a pointer to member function.
 - 10 The simple call wrapper returned from a call to `mem_fn(pm)` shall define two nested types named `argument_type` and `result_type` as synonyms for *cv* T* and `Ret`, respectively, when `pm` is a pointer to member function with cv-qualifier *cv* and taking no arguments, where `Ret` is `pm`'s return type.
 - 11 The simple call wrapper returned from a call to `mem_fn(pm)` shall define three nested types named `first_argument_type`, `second_argument_type`, and `result_type` as synonyms for *cv* T*, T1, and `Ret`, respectively, when `pm` is a pointer to member function with cv-qualifier *cv* and taking one argument of type T1, where `Ret` is `pm`'s return type.
 - 12 The following member names are defined in addition to names specified in Clause 26:

```
namespace std {
    template <class Key, class T, class Compare, class Allocator>
    class map<Key, T, Compare, Allocator>::value_compare {
    public:
        using result_type          = bool;
        using first_argument_type  = value_type;
        using second_argument_type = value_type;
    };

    template <class Key, class T, class Compare, class Allocator>
    class multimap<Key, T, Compare, Allocator>::value_compare {
    public:
        using result_type          = bool;
        using first_argument_type  = value_type;
        using second_argument_type = value_type;
    };
}
```

D.8.3 Negators

[depr.negators]

- 1 The header `<functional>` has the following additions:

```
namespace std {
    template <class Predicate> class unary_negate;
    template <class Predicate>
        constexpr unary_negate<Predicate> not1(const Predicate&);
    template <class Predicate> class binary_negate;
    template <class Predicate>
```

```
constexpr binary_negate<Predicate> not2(const Predicate&);
}
```

- ² Negators `not1` and `not2` take a unary and a binary predicate, respectively, and return their logical negations (8.3.1).

```
template <class Predicate>
class unary_negate {
public:
    constexpr explicit unary_negate(const Predicate& pred);
    constexpr bool operator()(const typename Predicate::argument_type& x) const;
    using argument_type = typename Predicate::argument_type;
    using result_type    = bool;
};
```

```
constexpr bool operator()(const typename Predicate::argument_type& x) const;
```

- ³ *Returns:* `!pred(x)`.

```
template <class Predicate>
constexpr unary_negate<Predicate> not1(const Predicate& pred);
```

- ⁴ *Returns:* `unary_negate<Predicate>(pred)`.

```
template <class Predicate>
class binary_negate {
public:
    constexpr explicit binary_negate(const Predicate& pred);
    constexpr bool operator()(const typename Predicate::first_argument_type& x,
                              const typename Predicate::second_argument_type& y) const;
    using first_argument_type = typename Predicate::first_argument_type;
    using second_argument_type = typename Predicate::second_argument_type;
    using result_type         = bool;
};
```

```
constexpr bool operator()(const typename Predicate::first_argument_type& x,
                          const typename Predicate::second_argument_type& y) const;
```

- ⁵ *Returns:* `!pred(x,y)`.

```
template <class Predicate>
constexpr binary_negate<Predicate> not2(const Predicate& pred);
```

- ⁶ *Returns:* `binary_negate<Predicate>(pred)`.

D.9 The default allocator

[depr.default.allocator]

- ¹ The following members and explicit class template specialization are defined in addition to those specified in 23.10.9:

```
namespace std {
    // specialize for void:
    template <> class allocator<void> {
    public:
        using value_type    = void;
        using pointer       = void*;
        using const_pointer = const void*;
        // reference-to-void members are impossible.

        template <class U> struct rebind { using other = allocator<U>; };
    };
}
```

```

};

template <class T> class allocator {
public:
    using size_type      = size_t;
    using difference_type = ptrdiff_t;
    using pointer        = T*;
    using const_pointer   = const T*;
    using reference       = T&;
    using const_reference = const T&;
    template <class U> struct rebind { using other = allocator<U>; };

    T* address(T& x) const noexcept;
    const T* address(const T& x) const noexcept;

    T* allocate(size_t n, const void* hint);

    template<class U, class... Args>
        void construct(U* p, Args&&... args);
    template <class U>
        void destroy(U* p);

    size_t max_size() const noexcept;
};
}

```

```

T* address(T& x) const noexcept;
const T* address(const T& x) const noexcept;

```

2 *Returns:* `addressof(x)`.

```

T* allocate(size_t n, const void* hint);

```

3 *Returns:* A pointer to the initial element of an array of storage of size `n * sizeof(T)`, aligned appropriately for objects of type `T`. It is implementation-defined whether over-aligned types are supported (6.11).

4 *Remarks:* The storage is obtained by calling `::operator new(std::size_t)` (21.6.2), but it is unspecified when or how often this function is called.

5 *Throws:* `bad_alloc` if the storage cannot be obtained.

```

template <class U, class... Args>
    void construct(U* p, Args&&... args);

```

6 *Effects:* As if by: `::new((void *)p) U(std::forward<Args>(args)...) ;`

```

template <class U>
    void destroy(U* p);

```

7 *Effects:* As if by `p->~U()`.

```

size_t max_size() const noexcept;

```

8 *Returns:* The largest value `N` for which the call `allocate(N, 0)` might succeed.

D.10 Raw storage iterator

[depr.storage.iterator]

1 The header `<memory>` has the following addition:

```

namespace std {

```

```

template <class OutputIterator, class T>
class raw_storage_iterator {
public:
    using iterator_category = output_iterator_tag;
    using value_type        = void;
    using difference_type    = void;
    using pointer            = void;
    using reference          = void;

    explicit raw_storage_iterator(OutputIterator x);

    raw_storage_iterator& operator*();
    raw_storage_iterator& operator=(const T& element);
    raw_storage_iterator& operator=(T&& element);
    raw_storage_iterator& operator++();
    raw_storage_iterator operator++(int);
    OutputIterator base() const;
};
}

```

- ² `raw_storage_iterator` is provided to enable algorithms to store their results into uninitialized memory. The template parameter `OutputIterator` is required to have its `operator*` return an object for which `operator&` is defined and returns a pointer to `T`, and is also required to satisfy the requirements of an output iterator (27.2.4).

```
explicit raw_storage_iterator(OutputIterator x);
```

- ³ *Effects:* Initializes the iterator to point to the same value to which `x` points.

```
raw_storage_iterator& operator*();
```

- ⁴ *Returns:* `*this`

```
raw_storage_iterator& operator=(const T& element);
```

- ⁵ *Requires:* `T` shall be CopyConstructible.

- ⁶ *Effects:* Constructs a value from `element` at the location to which the iterator points.

- ⁷ *Returns:* A reference to the iterator.

```
raw_storage_iterator& operator=(T&& element);
```

- ⁸ *Requires:* `T` shall be MoveConstructible.

- ⁹ *Effects:* Constructs a value from `std::move(element)` at the location to which the iterator points.

- ¹⁰ *Returns:* A reference to the iterator.

```
raw_storage_iterator& operator++();
```

- ¹¹ *Effects:* Pre-increment: advances the iterator and returns a reference to the updated iterator.

```
raw_storage_iterator operator++(int);
```

- ¹² *Effects:* Post-increment: advances the iterator and returns the old value of the iterator.

```
OutputIterator base() const;
```

- ¹³ *Returns:* An iterator of type `OutputIterator` that points to the same value as `*this` points to.

D.11 Temporary buffers**[depr.temporary.buffer]**

- 1 The header `<memory>` has the following additions:

```
namespace std {
    template <class T>
        pair<T*, ptrdiff_t> get_temporary_buffer(ptrdiff_t n) noexcept;
    template <class T>
        void return_temporary_buffer(T* p);
}
```

```
template <class T>
    pair<T*, ptrdiff_t> get_temporary_buffer(ptrdiff_t n) noexcept;
```

- 2 *Effects:* Obtains a pointer to uninitialized, contiguous storage for N adjacent objects of type T , for some non-negative number N . It is implementation-defined whether over-aligned types are supported (6.11).
- 3 *Remarks:* Calling `get_temporary_buffer` with a positive number n is a non-binding request to return storage for n objects of type T . In this case, an implementation is permitted to return instead storage for a non-negative number N of such objects, where $N \neq n$ (including $N == 0$). [Note: The request is non-binding to allow latitude for implementation-specific optimizations of its memory management. — end note]
- 4 *Returns:* If $n \leq 0$ or if no storage could be obtained, returns a pair P such that $P.first$ is a null pointer value and $P.second == 0$; otherwise returns a pair P such that $P.first$ refers to the address of the uninitialized storage and $P.second$ refers to its capacity N (in the units of `sizeof(T)`).

```
template <class T> void return_temporary_buffer(T* p);
```

- 5 *Effects:* Deallocates the storage referenced by p .
- 6 *Requires:* p shall be a pointer value returned by an earlier call to `get_temporary_buffer` that has not been invalidated by an intervening call to `return_temporary_buffer(T*)`.
- 7 *Throws:* Nothing.

D.12 Deprecated type traits**[depr.meta.types]**

- 1 The header `<type_traits>` has the following addition:

```
namespace std {
    template <class T> struct is_literal_type;

    template <class T> constexpr bool is_literal_type_v = is_literal_type<T>::value;

    template <class> struct result_of; // not defined
    template <class Fn, class... ArgTypes> struct result_of<Fn(ArgTypes...)>;

    template <class T> using result_of_t = typename result_of<T>::type;
}
```

- 2 *Requires:* For `is_literal_type`, `remove_all_extents_t<T>` shall be a complete type or *cv* void. For `result_of<Fn(ArgTypes...)>`, Fn and all types in the parameter pack `ArgTypes` shall be complete types, *cv* void, or arrays of unknown bound.
- 3 `is_literal_type<T>` is a `UnaryTypeTrait` (23.15.1) with a base characteristic of `true_type` if T is a literal type (6.9), and `false_type` otherwise. The partial specialization `result_of<Fn(ArgTypes...)>` is a `TransformationTrait` whose member typedef `type` is defined if and only if `invoke_result<Fn, ArgTypes...>::type` is defined. If `type` is defined, it names the same type as `invoke_result_t<Fn, ArgTypes...>`.

- ⁴ The behavior of a program that adds specializations for `is_literal_type` or `is_literal_type_v` is undefined.

D.13 Deprecated iterator primitives

[depr.iterator.primitives]

D.13.1 Basic iterator

[depr.iterator.basic]

- ¹ The header `<iterator>` has the following addition:

```
namespace std {
    template<class Category, class T, class Distance = ptrdiff_t,
            class Pointer = T*, class Reference = T&>
    struct iterator {
        using iterator_category = Category;
        using value_type        = T;
        using difference_type    = Distance;
        using pointer            = Pointer;
        using reference          = Reference;
    };
}
```

- ² The `iterator` template may be used as a base class to ease the definition of required types for new iterators.
- ³ [*Note:* If the new iterator type is a class template, then these aliases will not be visible from within the iterator class's template definition, but only to callers of that class. — *end note*]
- ⁴ [*Example:* If a C++ program wants to define a bidirectional iterator for some data structure containing `double` and such that it works on a large memory model of the implementation, it can do so with:

```
class MyIterator :
    public iterator<bidirectional_iterator_tag, double, long, T*, T&> {
    // code implementing ++, etc.
};
```

— *end example*]

D.14 Deprecated shared_ptr observers

[depr.util.smartptr.shared.obs]

- ¹ The following member is defined in addition to those members specified in 23.11.2.2:

```
namespace std {
    template<class T> class shared_ptr {
    public:
        bool unique() const noexcept;
    };
}
```

```
bool unique() const noexcept;
```

- ² *Returns:* `use_count() == 1`.

D.15 Deprecated standard code conversion facets

[depr.locale.stdcvt]

- ¹ The header `<codecvt>` provides code conversion facets for various character encodings.

D.15.1 Header `<codecvt>` synopsis

[depr.codecvt.syn]

```
namespace std {
    enum codecvt_mode {
        consume_header = 4,
        generate_header = 2,
        little_endian = 1
    };
}
```

```

};

template <class Elem, unsigned long Maxcode = 0x10ffff, codecvt_mode Mode = (codecvt_mode)0>
class codecvt_utf8 : public codecvt<Elem, char, mbstate_t> {
public:
    explicit codecvt_utf8(size_t refs = 0);
    ~codecvt_utf8();
};

template <class Elem, unsigned long Maxcode = 0x10ffff, codecvt_mode Mode = (codecvt_mode)0>
class codecvt_utf16 : public codecvt<Elem, char, mbstate_t> {
public:
    explicit codecvt_utf16(size_t refs = 0);
    ~codecvt_utf16();
};

template <class Elem, unsigned long Maxcode = 0x10ffff, codecvt_mode Mode = (codecvt_mode)0>
class codecvt_utf8_utf16 : public codecvt<Elem, char, mbstate_t> {
public:
    explicit codecvt_utf8_utf16(size_t refs = 0);
    ~codecvt_utf8_utf16();
};
}

```

D.15.2 Requirements

[depr.locale.stdcvt.req]

- ¹ For each of the three code conversion facets `codecvt_utf8`, `codecvt_utf16`, and `codecvt_utf8_utf16`:
 - (1.1) — `Elem` is the wide-character type, such as `wchar_t`, `char16_t`, or `char32_t`.
 - (1.2) — `Maxcode` is the largest wide-character code that the facet will read or write without reporting a conversion error.
 - (1.3) — If (`Mode & consume_header`), the facet shall consume an initial header sequence, if present, when reading a multibyte sequence to determine the endianness of the subsequent multibyte sequence to be read.
 - (1.4) — If (`Mode & generate_header`), the facet shall generate an initial header sequence when writing a multibyte sequence to advertise the endianness of the subsequent multibyte sequence to be written.
 - (1.5) — If (`Mode & little_endian`), the facet shall generate a multibyte sequence in little-endian order, as opposed to the default big-endian order.
- ² For the facet `codecvt_utf8`:
 - (2.1) — The facet shall convert between UTF-8 multibyte sequences and UCS2 or UCS4 (depending on the size of `Elem`) within the program.
 - (2.2) — Endianness shall not affect how multibyte sequences are read or written.
 - (2.3) — The multibyte sequences may be written as either a text or a binary file.
- ³ For the facet `codecvt_utf16`:
 - (3.1) — The facet shall convert between UTF-16 multibyte sequences and UCS2 or UCS4 (depending on the size of `Elem`) within the program.
 - (3.2) — Multibyte sequences shall be read or written according to the `Mode` flag, as set out above.
 - (3.3) — The multibyte sequences may be written only as a binary file. Attempting to write to a text file produces undefined behavior.
- ⁴ For the facet `codecvt_utf8_utf16`:

- (4.1) — The facet shall convert between UTF-8 multibyte sequences and UTF-16 (one or two 16-bit codes) within the program.
- (4.2) — Endianness shall not affect how multibyte sequences are read or written.
- (4.3) — The multibyte sequences may be written as either a text or a binary file.

SEE ALSO: ISO/IEC 10646-1:1993.

D.16 Deprecated convenience conversion interfaces

[depr.conversions]

- ¹ The header `<locale>` has the following additions:

```
namespace std {
    template <class Codecvt, class Elem = wchar_t,
              class Wide_alloc = allocator<Elem>,
              class Byte_alloc = allocator<char>>
        class wstring_convert;

    template <class Codecvt, class Elem = wchar_t,
              class Tr = char_traits<Elem>>
        class wbuffer_convert;
}
```

D.16.1 Class template `wstring_convert`

[depr.conversions.string]

- ¹ Class template `wstring_convert` performs conversions between a wide string and a byte string. It lets you specify a code conversion facet (like class template `codecvt`) to perform the conversions, without affecting any streams or locales. [*Example:* If you want to use the code conversion facet `codecvt_utf8` to output to `cout` a UTF-8 multibyte sequence corresponding to a wide string, but you don't want to alter the locale for `cout`, you can write something like:

```
wstring_convert<std::codecvt_utf8<wchar_t>> myconv;
std::string mbstring = myconv.to_bytes(L"Hello\n");
std::cout << mbstring;
```

— *end example*]

```
namespace std {
    template <class Codecvt, class Elem = wchar_t,
              class Wide_alloc = allocator<Elem>,
              class Byte_alloc = allocator<char>>
        class wstring_convert {
        public:
            using byte_string = basic_string<char, char_traits<char>, Byte_alloc>;
            using wide_string = basic_string<Elem, char_traits<Elem>, Wide_alloc>;
            using state_type = typename Codecvt::state_type;
            using int_type = typename wide_string::traits_type::int_type;

            explicit wstring_convert(Codecvt* pcvt = new Codecvt);
            wstring_convert(Codecvt* pcvt, state_type state);
            explicit wstring_convert(const byte_string& byte_err,
                                    const wide_string& wide_err = wide_string());
            ~wstring_convert();

            wstring_convert(const wstring_convert&) = delete;
            wstring_convert& operator=(const wstring_convert&) = delete;

            wide_string from_bytes(char byte);
            wide_string from_bytes(const char* ptr);
```



```

    wide_string from_bytes(const byte_string& str);
    wide_string from_bytes(const char* first, const char* last);

    byte_string to_bytes(Elem wchar);
    byte_string to_bytes(const Elem* wptr);
    byte_string to_bytes(const wide_string& wstr);
    byte_string to_bytes(const Elem* first, const Elem* last);

    size_t converted() const noexcept;
    state_type state() const;

private:
    byte_string byte_err_string; // exposition only
    wide_string wide_err_string; // exposition only
    Codecvt* cvtptr;             // exposition only
    state_type cvtstate;         // exposition only
    size_t cvtcount;             // exposition only
};

```

- 2 The class template describes an object that controls conversions between wide string objects of class `basic_string<Elem, char_traits<Elem>, Wide_alloc>` and byte string objects of class `basic_string<char, char_traits<char>, Byte_alloc>`. The class template defines the types `wide_string` and `byte_string` as synonyms for these two types. Conversion between a sequence of `Elem` values (stored in a `wide_string` object) and multibyte sequences (stored in a `byte_string` object) is performed by an object of class `Codecvt`, which meets the requirements of the standard code-conversion facet `codecvt<Elem, char, mbstate_t>`.

- 3 An object of this class template stores:

- (3.1) — `byte_err_string` — a byte string to display on errors
- (3.2) — `wide_err_string` — a wide string to display on errors
- (3.3) — `cvtptr` — a pointer to the allocated conversion object (which is freed when the `wstring_convert` object is destroyed)
- (3.4) — `cvtstate` — a conversion state object
- (3.5) — `cvtcount` — a conversion count

```
using byte_string = basic_string<char, char_traits<char>, Byte_alloc>;
```

- 4 The type shall be a synonym for `basic_string<char, char_traits<char>, Byte_alloc>`.

```
size_t converted() const noexcept;
```

- 5 *Returns:* `cvtcount`.

```

wide_string from_bytes(char byte);
wide_string from_bytes(const char* ptr);
wide_string from_bytes(const byte_string& str);
wide_string from_bytes(const char* first, const char* last);

```

- 6 *Effects:* The first member function shall convert the single-element sequence `byte` to a wide string. The second member function shall convert the null-terminated sequence beginning at `ptr` to a wide string. The third member function shall convert the sequence stored in `str` to a wide string. The fourth member function shall convert the sequence defined by the range `[first, last)` to a wide string.

- 7 In all cases:

- (7.1) — If the `cvtstate` object was not constructed with an explicit value, it shall be set to its default value

(the initial conversion state) before the conversion begins. Otherwise it shall be left unchanged.

(7.2) — The number of input elements successfully converted shall be stored in `cvtcount`.

8 *Returns:* If no conversion error occurs, the member function shall return the converted wide string. Otherwise, if the object was constructed with a wide-error string, the member function shall return the wide-error string. Otherwise, the member function throws an object of class `range_error`.

```
using int_type = typename wide_string::traits_type::int_type;
```

9 The type shall be a synonym for `wide_string::traits_type::int_type`.

```
state_type state() const;
```

10 returns `cvtstate`.

```
using state_type = typename Codecvt::state_type;
```

11 The type shall be a synonym for `Codecvt::state_type`.

```
byte_string to_bytes(Elem wchar);
byte_string to_bytes(const Elem* wptr);
byte_string to_bytes(const wide_string& wstr);
byte_string to_bytes(const Elem* first, const Elem* last);
```

12 *Effects:* The first member function shall convert the single-element sequence `wchar` to a byte string. The second member function shall convert the null-terminated sequence beginning at `wptr` to a byte string. The third member function shall convert the sequence stored in `wstr` to a byte string. The fourth member function shall convert the sequence defined by the range `[first, last)` to a byte string.

13 In all cases:

(13.1) — If the `cvtstate` object was not constructed with an explicit value, it shall be set to its default value (the initial conversion state) before the conversion begins. Otherwise it shall be left unchanged.

(13.2) — The number of input elements successfully converted shall be stored in `cvtcount`.

14 *Returns:* If no conversion error occurs, the member function shall return the converted byte string. Otherwise, if the object was constructed with a byte-error string, the member function shall return the byte-error string. Otherwise, the member function shall throw an object of class `range_error`.

```
using wide_string = basic_string<Elem, char_traits<Elem>, Wide_alloc>;
```

15 The type shall be a synonym for `basic_string<Elem, char_traits<Elem>, Wide_alloc>`.

```
explicit wstring_convert(Codecvt* pcvt = new Codecvt);
wstring_convert(Codecvt* pcvt, state_type state);
explicit wstring_convert(const byte_string& byte_err,
    const wide_string& wide_err = wide_string());
```

16 *Requires:* For the first and second constructors, `pcvt != nullptr`.

17 *Effects:* The first constructor shall store `pcvt` in `cvtptr` and default values in `cvtstate`, `byte_err_string`, and `wide_err_string`. The second constructor shall store `pcvt` in `cvtptr`, `state` in `cvtstate`, and default values in `byte_err_string` and `wide_err_string`; moreover the stored state shall be retained between calls to `from_bytes` and `to_bytes`. The third constructor shall store `new Codecvt` in `cvtptr`, `state_type()` in `cvtstate`, `byte_err` in `byte_err_string`, and `wide_err` in `wide_err_string`.

```
~wstring_convert();
```

18 *Effects:* The destructor shall delete `cvtptr`.

D.16.2 Class template `wbuffer_convert` [depr.conversions.buffer]

- ¹ Class template `wbuffer_convert` looks like a wide stream buffer, but performs all its I/O through an underlying byte stream buffer that you specify when you construct it. Like class template `wstring_convert`, it lets you specify a code conversion facet to perform the conversions, without affecting any streams or locales.

```
namespace std {
    template <class Codecvt, class Elem = wchar_t, class Tr = char_traits<Elem>>
        class wbuffer_convert : public basic_streambuf<Elem, Tr> {
        public:
            using state_type = typename Codecvt::state_type;

            explicit wbuffer_convert(streambuf* bytebuf = 0,
                                    Codecvt* pcvt = new Codecvt,
                                    state_type state = state_type());

            ~wbuffer_convert();

            wbuffer_convert(const wbuffer_convert&) = delete;
            wbuffer_convert& operator=(const wbuffer_convert&) = delete;

            streambuf* rdbuf() const;
            streambuf* rdbuf(streambuf* bytebuf);

            state_type state() const;

        private:
            streambuf* bufptr;           // exposition only
            Codecvt* cvtptr;             // exposition only
            state_type cvtstate;         // exposition only
        };
    }
```

- ² The class template describes a stream buffer that controls the transmission of elements of type `Elem`, whose character traits are described by the class `Tr`, to and from a byte stream buffer of type `streambuf`. Conversion between a sequence of `Elem` values and multibyte sequences is performed by an object of class `Codecvt`, which shall meet the requirements of the standard code-conversion facet `codecvt<Elem, char, mbstate_t>`.

- ³ An object of this class template stores:

- (3.1) — `bufptr` — a pointer to its underlying byte stream buffer
- (3.2) — `cvtptr` — a pointer to the allocated conversion object (which is freed when the `wbuffer_convert` object is destroyed)
- (3.3) — `cvtstate` — a conversion state object

```
state_type state() const;
```

- ⁴ *Returns:* `cvtstate`.

```
streambuf* rdbuf() const;
```

- ⁵ *Returns:* `bufptr`.

```
streambuf* rdbuf(streambuf* bytebuf);
```

- ⁶ *Effects:* Stores `bytebuf` in `bufptr`.

- ⁷ *Returns:* The previous value of `bufptr`.

```
using state_type = typename Codecvt::state_type;
```

8 The type shall be a synonym for `Codecvt::state_type`.

```
explicit wbuffer_convert(  
    streambuf* bytebuf = 0,  
    Codecvt* pcvt = new Codecvt,  
    state_type state = state_type());
```

9 *Requires:* `pcvt != nullptr`.

10 *Effects:* The constructor constructs a stream buffer object, initializes `bufptr` to `bytebuf`, initializes `cvtptr` to `pcvt`, and initializes `cvtstate` to `state`.

```
~wbuffer_convert();
```

11 *Effects:* The destructor shall delete `cvtptr`.

Cross references

This annex lists each section label and the corresponding section number and page number, in alphabetical order by label.

accumulate (29.8.2)	1130	alg.unique (28.6.9)	1027
adjacent.difference (29.8.11)	1137	algorithm.stable (20.5.5.7)	475
adjustfield.manip (30.5.6.2)	1178	algorithm.syn (28.2)	989
alg.adjacent.find (28.5.8)	1015	algorithms (28)	989
alg.all_of (28.5.1)	1012	algorithms.general (28.1)	989
alg.any_of (28.5.2)	1012	algorithms.parallel (28.4)	1009
alg.binary.search (28.7.3)	1034	algorithms.parallel.defns (28.4.1)	1009
alg.c.library (28.8)	1049	algorithms.parallel.exceptions (28.4.4)	1011
alg.clamp (28.7.9)	1047	algorithms.parallel.exec (28.4.3)	1009
alg.copy (28.6.1)	1020	algorithms.parallel.overloads (28.4.5)	1011
alg.count (28.5.9)	1016	algorithms.parallel.user (28.4.2)	1009
alg.equal (28.5.11)	1017	algorithms.requirements (28.3)	1008
alg.fill (28.6.6)	1025	alloc.errors (21.6.3)	500
alg.find (28.5.5)	1013	allocator.adaptor (23.13)	646
alg.find.end (28.5.6)	1014	allocator.adaptor.cnstr (23.13.3)	649
alg.find.first.of (28.5.7)	1015	allocator.adaptor.members (23.13.4)	650
alg.foreach (28.5.4)	1012	allocator.adaptor.syn (23.13.1)	646
alg.generate (28.6.7)	1025	allocator.adaptor.types (23.13.2)	649
alg.heap.operations (28.7.7)	1043	allocator.globals (23.10.9.2)	606
alg.is_permutation (28.5.12)	1018	allocator.members (23.10.9.1)	605
alg.lex.comparison (28.7.10)	1048	allocator.requirements (20.5.3.5)	463
alg.merge (28.7.5)	1038	allocator.requirements.completeness (20.5.3.5.1)	469
alg.min.max (28.7.8)	1045	allocator.tag (23.10.6)	602
alg.modifying.operations (28.6)	1020	allocator.traits (23.10.8)	602
alg.move (28.6.2)	1021	allocator.traits.members (23.10.8.2)	604
alg.none_of (28.5.3)	1012	allocator.traits.types (23.10.8.1)	603
alg.nonmodifying (28.5)	1012	allocator.uses (23.10.7)	602
alg.nth.element (28.7.2)	1034	allocator.uses.construction (23.10.7.2)	602
alg.partitions (28.7.4)	1036	allocator.uses.trait (23.10.7.1)	602
alg.permutation.generators (28.7.11)	1048	alt.headers (20.5.4.4)	471
alg.random.sample (28.6.12)	1029	any (23.8)	582
alg.random.shuffle (28.6.13)	1030	any.assign (23.8.3.2)	585
alg.remove (28.6.8)	1025	any.bad_any_cast (23.8.2)	582
alg.replace (28.6.5)	1023	any.class (23.8.3)	583
alg.reverse (28.6.10)	1028	any.cons (23.8.3.1)	583
alg.rotate (28.6.11)	1028	any.modifiers (23.8.3.3)	585
alg.search (28.5.13)	1019	any.nonmembers (23.8.4)	586
alg.set.operations (28.7.6)	1039	any.observers (23.8.3.4)	586
alg.sort (28.7.1)	1031	any.synop (23.8.1)	582
alg.sorting (28.7)	1030	arithmetic.operations (23.14.6)	658
alg.swap (28.6.3)	1022	arithmetic.operations.divides (23.14.6.4)	659
alg.transform (28.6.4)	1023		

- arithmetic.operations.minus (23.14.6.2) 658
- arithmetic.operations.modulus (23.14.6.5) 659
- arithmetic.operations.multiplies (23.14.6.3) 658
- arithmetic.operations.negate (23.14.6.6) 659
- arithmetic.operations.plus (23.14.6.1) 658
- array (26.3.7) 871
- array.cons (26.3.7.2) 873
- array.data (26.3.7.5) 873
- array.fill (26.3.7.6) 873
- array.overview (26.3.7.1) 871
- array.size (26.3.7.4) 873
- array.special (26.3.7.3) 873
- array.swap (26.3.7.7) 873
- array.syn (26.3.2) 868
- array.tuple (26.3.7.9) 874
- array.zero (26.3.7.8) 873
- assertions (22.3) 517
- assertions.assert (22.3.2) 517
- associative (26.4) 900
- associative.general (26.4.1) 900
- associative.map.syn (26.4.2) 900
- associative.reqmts (26.2.6) 845
- associative.reqmts.except (26.2.6.1) 856
- associative.set.syn (26.4.3) 901
- atomics (32) 1342
- atomics.alias (32.3) 1346
- atomics.fences (32.9) 1357
- atomics.flag (32.8) 1356
- atomics.general (32.1) 1342
- atomics.lockfree (32.5) 1348
- atomics.nonmembers (32.7) 1356
- atomics.order (32.4) 1346
- atomics.syn (32.2) 1342
- atomics.types.generic (32.6) 1348
- atomics.types.int (32.6.2) 1352
- atomics.types.memop (32.6.4) 1355
- atomics.types.operations (32.6.1) 1349
- atomics.types.pointer (32.6.3) 1354
- back.insert.iter.cons (27.5.2.2.1) 973
- back.insert.iter.op* (27.5.2.2.3) 973
- back.insert.iter.op++ (27.5.2.2.4) 973
- back.insert.iter.op= (27.5.2.2.2) 973
- back.insert.iter.ops (27.5.2.2) 973
- back.insert.iterator (27.5.2.1) 972
- back.inserter (27.5.2.2.5) 973
- bad.alloc (21.6.3.1) 500
- bad.cast (21.7.3) 503
- bad.exception (21.8.3) 506
- bad.typeid (21.7.4) 504
- basefield.manip (30.5.6.3) 1178
- basic (6) 39
- basic.align (6.11) 84
- basic.compound (6.9.2) 81
- basic.def (6.1) 39
- basic.def.odr (6.2) 41
- basic.fundamental (6.9.1) 79
- basic.funscope (6.3.5) 47
- basic.ios.cons (30.5.5.2) 1173
- basic.ios.members (30.5.5.3) 1174
- basic.life (6.8) 74
- basic.link (6.5) 63
- basic.lookup (6.4) 50
- basic.lookup.argdep (6.4.2) 54
- basic.lookup.classref (6.4.5) 62
- basic.lookup.elab (6.4.4) 61
- basic.lookup.qual (6.4.3) 56
- basic.lookup.udir (6.4.6) 63
- basic.lookup.unqual (6.4.1) 50
- basic.lval (6.10) 83
- basic.namespace (10.3) 178
- basic.scope (6.3) 44
- basic.scope.block (6.3.3) 46
- basic.scope.class (6.3.7) 48
- basic.scope.declarative (6.3.1) 44
- basic.scope.enum (6.3.8) 49
- basic.scope.hiding (6.3.10) 50
- basic.scope.namespace (6.3.6) 47
- basic.scope.pdecl (6.3.2) 45
- basic.scope.proto (6.3.4) 47
- basic.scope.temp (6.3.9) 49
- basic.start (6.6) 66
- basic.start.dynamic (6.6.3) 67
- basic.start.main (6.6.1) 66
- basic.start.static (6.6.2) 67
- basic.start.term (6.6.4) 69
- basic.stc (6.7) 70
- basic.stc.auto (6.7.3) 71
- basic.stc.dynamic (6.7.4) 71
- basic.stc.dynamic.allocation (6.7.4.1) 71
- basic.stc.dynamic.deallocation (6.7.4.2) 72
- basic.stc.dynamic.safety (6.7.4.3) 73
- basic.stc.inherit (6.7.5) 74
- basic.stc.static (6.7.1) 70
- basic.stc.thread (6.7.2) 70
- basic.string (24.3.2) 736
- basic.string.hash (24.3.5) 766
- basic.string.literals (24.3.6) 766
- basic.type.qualifier (6.9.3) 82
- basic.types (6.9) 77
- bidirectional.iterators (27.2.6) 960
- binary.search (28.7.3.4) 1036

bitmask.types (20.4.2.1.4)	454	class.access.spec (14.1)	270
bitset (23.9)	587	class.access.virt (14.5)	278
bitset.cons (23.9.2.1)	589	class.base.init (15.6.2)	294
bitset.hash (23.9.3)	593	class.bit (12.2.4)	249
bitset.members (23.9.2.2)	590	class.cdtor (15.7)	300
bitset.operators (23.9.4)	593	class.conv (15.3)	285
bitset.syn (23.9.1)	587	class.conv.ctor (15.3.1)	286
bitwise.operations (23.14.9)	663	class.conv.fct (15.3.2)	287
bitwise.operations.and (23.14.9.1)	663	class.copy (15.8)	303
bitwise.operations.not (23.14.9.4)	664	class.copy.assign (15.8.2)	305
bitwise.operations.or (23.14.9.2)	664	class.copy.ctor (15.8.1)	303
bitwise.operations.xor (23.14.9.3)	664	class.copy.elision (15.8.3)	308
byte.strings (20.4.2.1.5.1)	455	class.ctor (15.1)	280
c.files (30.11)	1293	class.derived (13)	256
c.locales (25.5)	829	class.dtor (15.4)	288
c.malloc (23.10.11)	608	class.expl.init (15.6.1)	293
c.math (29.9)	1139	class.free (15.5)	291
c.math.abs (29.9.2)	1149	class.friend (14.3)	274
c.math.fpclass (29.9.4)	1150	class.gslic (29.7.6)	1119
c.math.hypot3 (29.9.3)	1150	class.gslic.overview (29.7.6.1)	1119
c.math.rand (29.6.9)	1105	class.inhctor.init (15.6.3)	299
c.mb.wcs (24.5.6)	780	class.init (15.6)	293
c.strings (24.5)	776	class.local (12.4)	254
cassert.syn (22.3.1)	517	class.mem (12.2)	241
category.collate (25.4.4)	811	class.member.lookup (13.2)	259
category.ctype (25.4.1)	791	class.mfct (12.2.1)	245
category.messages (25.4.7)	824	class.mfct.non-static (12.2.2)	246
category.monetary (25.4.6)	819	class.mi (13.1)	257
category.numeric (25.4.2)	801	class.name (12.1)	239
category.time (25.4.5)	813	class.nest (12.2.5)	250
cctype.syn (24.5.1)	776	class.nested.type (12.2.6)	251
cerrno.syn (22.4.1)	517	class.paths (14.6)	278
cfenv (29.4)	1051	class.protected (14.4)	277
cfenv.syn (29.4.1)	1051	class.qual (6.4.3.1)	57
cfloat.syn (21.3.6)	491	class.slice (29.7.4)	1118
char.traits (24.2)	726	class.slice.overview (29.7.4.1)	1118
char.traits.require (24.2.1)	726	class.static (12.2.3)	247
char.traits.specializations (24.2.3)	728	class.static.data (12.2.3.2)	248
char.traits.specializations.char (24.2.3.1)	729	class.static.mfct (12.2.3.1)	248
char.traits.specializations.char16_t (24.2.3.2)	729	class.temporary (15.2)	283
char.traits.specializations.char32_t (24.2.3.3)	730	class.this (12.2.2.1)	247
char.traits.specializations.wchar_t (24.2.3.4)	731	class.union (12.3)	251
char.traits.typedefs (24.2.2)	728	class.union.anon (12.3.1)	253
character.seq (20.4.2.1.5)	455	class.virtual (13.3)	262
cinttypes.syn (30.11.2)	1294	classification (25.3.3.1)	790
class (12)	237	climits.syn (21.3.5)	491
class.abstract (13.4)	266	clocale.syn (25.5.1)	829
class.access (14)	269	cmath.syn (29.9.1)	1139
class.access.base (14.2)	271	cmplx.over (29.5.9)	1061
class.access.nest (14.7)	278	comparisons (23.14.7)	660
		comparisons.equal_to (23.14.7.1)	660

- comparisons.greater (23.14.7.3) 661
- comparisons.greater_equal (23.14.7.5) 661
- comparisons.less (23.14.7.4) 661
- comparisons.less_equal (23.14.7.6) 662
- comparisons.not_equal_to (23.14.7.2) 660
- complex (29.5.2) 1054
- complex.literals (29.5.10) 1061
- complex.member.ops (29.5.5) 1057
- complex.members (29.5.4) 1056
- complex.numbers (29.5) 1052
- complex.ops (29.5.6) 1058
- complex.special (29.5.3) 1055
- complex.syn (29.5.1) 1053
- complex.transcendentals (29.5.8) 1059
- complex.value.ops (29.5.7) 1059
- compliance (20.5.1.3) 458
- condition_variable.syn (33.5.1) 1388
- conforming (20.5.5) 473
- conforming.overview (20.5.5.1) 473
- cons.slice (29.7.4.2) 1118
- constexpr.functions (20.5.5.6) 475
- constraints (20.5.4) 469
- constraints.overview (20.5.4.1) 469
- container.adaptors (26.6) 945
- container.adaptors.general (26.6.1) 945
- container.insert.return (26.2.5) 845
- container.node (26.2.4) 842
- container.node.cons (26.2.4.2) 844
- container.node.dtor (26.2.4.3) 844
- container.node.modifiers (26.2.4.5) 845
- container.node.observers (26.2.4.4) 844
- container.node.overview (26.2.4.1) 842
- container.requirements (26.2) 830
- container.requirements.dataraces (26.2.2) 837
- container.requirements.general (26.2.1) 830
- containers (26) 830
- containers.general (26.1) 830
- contents (20.5.1.1) 456
- conv (7) 86
- conv.array (7.2) 87
- conv.bool (7.14) 91
- conv.double (7.9) 90
- conv.fctptr (7.13) 91
- conv.fpint (7.10) 90
- conv.fpprom (7.7) 89
- conv.func (7.3) 88
- conv.integral (7.8) 89
- conv.lval (7.1) 87
- conv.mem (7.12) 90
- conv.prom (7.6) 89
- conv.ptr (7.11) 90
- conv.qual (7.5) 88
- conv.rank (7.15) 91
- conv.rval (7.4) 88
- conventions (20.4.2) 453
- conversions (25.3.3.2) 791
- conversions.character (25.3.3.2.1) 791
- cpp (19) 434
- cpp.concat (19.3.3) 440
- cpp.cond (19.1) 435
- cpp.error (19.5) 444
- cpp.include (19.2) 437
- cpp.line (19.4) 443
- cpp.null (19.7) 444
- cpp.pragma (19.6) 444
- cpp.pragma.op (19.9) 446
- cpp.predefined (19.8) 444
- cpp.replace (19.3) 438
- cpp.rescan (19.3.4) 441
- cpp.scope (19.3.5) 441
- cpp.stringize (19.3.2) 440
- cpp.subst (19.3.1) 440
- csetjmp.syn (21.10.2) 511
- csignal.syn (21.10.3) 511
- cstdarg.syn (21.10.1) 510
- cstddef.syn (21.2.1) 478
- cstdint (21.4) 492
- cstdint.syn (21.4.1) 492
- cstdio.syn (30.11.1) 1293
- cstdlib.syn (21.2.2) 479
- cstring.syn (24.5.3) 777
- ctime.syn (23.17.8) 721
- cuchar.syn (24.5.5) 780
- cwchar.syn (24.5.4) 778
- cwctype.syn (24.5.2) 777
- dcl.align (10.6.2) 196
- dcl.ambig.res (11.2) 203
- dcl.array (11.3.4) 208
- dcl.asm (10.4) 191
- dcl.attr (10.6) 194
- dcl.attr.depend (10.6.3) 197
- dcl.attr.deprecated (10.6.4) 198
- dcl.attr.fallthrough (10.6.5) 198
- dcl.attr.grammar (10.6.1) 194
- dcl.attr.nodiscard (10.6.7) 199
- dcl.attr.noreturn (10.6.8) 200
- dcl.attr.unused (10.6.6) 199
- dcl.constexpr (10.1.5) 161
- dcl.dcl (10) 155
- dcl.decl (11) 201
- dcl.enum (10.2) 174

dcl.fct (11.3.5)	210	defns.direct-non-list-init (20.3.10)	449
dcl.fct.def (11.4)	216	defns.dynamic.type (3.9)	3
dcl.fct.def.default (11.4.2)	217	defns.dynamic.type.prvalue (3.10)	4
dcl.fct.def.delete (11.4.3)	218	defns.handler (20.3.11)	449
dcl.fct.def.general (11.4.1)	216	defns.ill.formed (3.11)	4
dcl.fct.default (11.3.6)	213	defns.impl.defined (3.12)	4
dcl.fct.spec (10.1.2)	159	defns.impl.limits (3.13)	4
dcl.friend (10.1.4)	161	defns.iostream.templates (20.3.12)	449
dcl.init (11.6)	220	defns.locale.specific (3.14)	4
dcl.init.aggr (11.6.1)	224	defns.modifier (20.3.13)	449
dcl.init.list (11.6.4)	231	defns.move.assign (20.3.14)	449
dcl.init.ref (11.6.3)	228	defns.move.constr (20.3.15)	449
dcl.init.string (11.6.2)	228	defns.multibyte (3.15)	4
dcl.inline (10.1.6)	164	defns.ntcts (20.3.16)	449
dcl.link (10.5)	191	defns.observer (20.3.17)	449
dcl.meaning (11.3)	204	defns.parameter (3.16)	4
dcl.mptr (11.3.3)	207	defns.parameter.macro (3.17)	4
dcl.name (11.1)	202	defns.parameter.templ (3.18)	4
dcl.ptr (11.3.1)	205	defns.referenceable (20.3.18)	450
dcl.ref (11.3.2)	206	defns.regex.collating.element (31.2.0.1)	1297
dcl.spec (10.1)	157	defns.regex.finite.state.machine (31.2.0.2)	1297
dcl.spec.auto (10.1.7.4)	170	defns.regex.format.specifier (31.2.0.3)	1297
dcl.stc (10.1.1)	157	defns.regex.matched (31.2.0.4)	1297
dcl.struct.bind (11.5)	219	defns.regex.primary.equivalence.class (31.2.0.5)	1297
dcl.type (10.1.7)	165		
dcl.type.auto.deduct (10.1.7.4.1)	173	defns.regex.regular.expression (31.2.0.6)	1298
dcl.type.class.deduct (10.1.7.5)	174	defns.regex.subexpression (31.2.0.7)	1298
dcl.type.cv (10.1.7.1)	166	defns.replacement (20.3.19)	450
dcl.type.elab (10.1.7.3)	170	defns.repositional.stream (20.3.20)	450
dcl.type.simple (10.1.7.2)	167	defns.required.behavior (20.3.21)	450
dcl.typedef (10.1.3)	160	defns.reserved.function (20.3.22)	450
declval (23.2.7)	536	defns.signature (3.19)	4
default allocator (23.10.9)	605	defns.signature.member (3.22)	5
definitions (20.3)	448	defns.signature.member.spec (3.24)	5
defns.access (3.1)	3	defns.signature.member.templ (3.23)	5
defns.arbitrary.stream (20.3.1)	448	defns.signature.spec (3.21)	5
defns.argument (3.2)	3	defns.signature.templ (3.20)	4
defns.argument.macro (3.3)	3	defns.stable (20.3.23)	450
defns.argument.templ (3.5)	3	defns.static.type (3.25)	5
defns.argument.throw (3.4)	3	defns.traits (20.3.24)	450
defns.block (3.6)	3	defns.unblock (3.26)	5
defns.character (20.3.2)	448	defns.undefined (3.27)	5
defns.character.container (20.3.3)	448	defns.unspecified (3.28)	5
defns.comparison (20.3.4)	448	defns.valid (20.3.25)	450
defns.component (20.3.5)	448	defns.well.formed (3.29)	5
defns.cond.suppr (3.7)	3	denorm.style (21.3.3.2)	484
defns.const.subexpr (20.3.6)	448	depr (D)	1460
defns.deadlock (20.3.7)	449	depr.c.headers (D.5)	1461
defns.default.behavior.func (20.3.9)	449	depr.ccomplex.syn (D.4.1)	1460
defns.default.behavior.impl (20.3.8)	449	depr.codecvr.syn (D.15.1)	1479
defns.diagnostic (3.8)	3	depr.conversions (D.16)	1481

depr.conversions.buffer (D.16.2)	1484	diff.basic (C.1.2)	1437
depr.conversions.string (D.16.1)	1481	diff.char16 (C.5.2.1)	1458
depr.cpp.headers (D.4)	1460	diff.class (C.1.8)	1443
depr.cstdalign.syn (D.4.2)	1460	diff.conv (C.1.3)	1438
depr.cstdbool.syn (D.4.3)	1461	diff.cpp (C.1.10)	1445
depr.ctgmath.syn (D.4.4)	1461	diff.cpp03 (C.2)	1445
depr.default allocator (D.9)	1475	diff.cpp03.algorithms (C.2.14)	1450
depr.except.spec (D.3)	1460	diff.cpp03.containers (C.2.13)	1449
depr.func.adaptor.binding (D.8)	1470	diff.cpp03.conv (C.2.2)	1446
depr.func.adaptor.typedefs (D.8.2)	1470	diff.cpp03.dcl.dcl (C.2.4)	1446
depr.impldec (D.2)	1460	diff.cpp03.dcl.decl (C.2.5)	1446
depr.istrstream (D.6.2)	1467	diff.cpp03.diagnostics (C.2.10)	1449
depr.istrstream.cons (D.6.2.1)	1467	diff.cpp03.expr (C.2.3)	1446
depr.istrstream.members (D.6.2.2)	1468	diff.cpp03.input.output (C.2.16)	1451
depr.iterator.basic (D.13.1)	1479	diff.cpp03.language.support (C.2.9)	1448
depr.iterator.primitives (D.13)	1479	diff.cpp03.lex (C.2.1)	1445
depr.locale.stdcv (D.15)	1479	diff.cpp03.library (C.2.8)	1447
depr.locale.stdcv.req (D.15.2)	1480	diff.cpp03.numerics (C.2.15)	1451
depr.meta.types (D.12)	1478	diff.cpp03.special (C.2.6)	1446
depr.negators (D.8.3)	1474	diff.cpp03.strings (C.2.12)	1449
depr.ostrstream (D.6.3)	1468	diff.cpp03.temp (C.2.7)	1447
depr.ostrstream.cons (D.6.3.1)	1468	diff.cpp03.utilities (C.2.11)	1449
depr.ostrstream.members (D.6.3.2)	1468	diff.cpp11 (C.3)	1451
depr.static_constexpr (D.1)	1460	diff.cpp11.basic (C.3.2)	1452
depr.storage.iterator (D.10)	1476	diff.cpp11.dcl.dcl (C.3.4)	1452
depr.str.strstreams (D.6)	1461	diff.cpp11.dcl.decl (C.3.5)	1453
depr.strstream (D.6.4)	1469	diff.cpp11.expr (C.3.3)	1452
depr.strstream.cons (D.6.4.1)	1469	diff.cpp11.input.output (C.3.7)	1453
depr.strstream.dest (D.6.4.2)	1470	diff.cpp11.lex (C.3.1)	1451
depr.strstream.oper (D.6.4.3)	1470	diff.cpp11.library (C.3.6)	1453
depr.strstreambuf (D.6.1)	1461	diff.cpp14 (C.4)	1453
depr.strstreambuf.cons (D.6.1.1)	1463	diff.cpp14.containers (C.4.11)	1457
depr.strstreambuf.members (D.6.1.2)	1464	diff.cpp14.dcl.dcl (C.4.3)	1454
depr.strstreambuf.virtuals (D.6.1.3)	1465	diff.cpp14.decl (C.4.4)	1454
depr.temporary.buffer (D.11)	1478	diff.cpp14.depr (C.4.12)	1457
depr.uncaught (D.7)	1470	diff.cpp14.except (C.4.7)	1455
depr.util.smartptr.shared.obs (D.14)	1479	diff.cpp14.expr (C.4.2)	1454
depr.weak.result_type (D.8.1)	1470	diff.cpp14.lex (C.4.1)	1453
deque (26.3.8)	874	diff.cpp14.library (C.4.8)	1456
deque.capacity (26.3.8.3)	877	diff.cpp14.special (C.4.5)	1455
deque.cons (26.3.8.2)	876	diff.cpp14.string (C.4.10)	1456
deque.modifiers (26.3.8.4)	877	diff.cpp14.temp (C.4.6)	1455
deque.overview (26.3.8.1)	874	diff.cpp14.utilities (C.4.9)	1456
deque.special (26.3.8.5)	878	diff.dcl (C.1.6)	1439
deque.syn (26.3.3)	869	diff.decl (C.1.7)	1441
derivation (20.5.5.11)	476	diff.expr (C.1.4)	1438
derived.classes (20.5.4.5)	471	diff.header.assert.h (C.5.2.3)	1458
description (20.4)	451	diff.header.iso646.h (C.5.2.4)	1458
diagnostics (22)	513	diff.header.stdalign.h (C.5.2.5)	1458
diagnostics.general (22.1)	513	diff.header.stdbool.h (C.5.2.6)	1458
diff (C)	1436	diff.iso (C.1)	1436

- diff.lex (C.1.1) 1436
- diff.library (C.5) 1457
- diff.malloc (C.5.4.2) 1459
- diff.mods.to.behavior (C.5.4) 1459
- diff.mods.to.declarations (C.5.3) 1458
- diff.mods.to.definitions (C.5.2) 1458
- diff.mods.to.headers (C.5.1) 1457
- diff.null (C.5.2.7) 1458
- diff.offsetof (C.5.4.1) 1459
- diff.special (C.1.9) 1444
- diff.stat (C.1.5) 1439
- diff.wchar.t (C.5.2.2) 1458
- domain.error (22.2.3) 514
- enumerated.types (20.4.2.1.3) 453
- equal.range (28.7.3.3) 1035
- errno (22.4) 517
- error.reporting (30.5.6.5) 1179
- except (18) 424
- except.ctor (18.2) 427
- except.handle (18.3) 427
- except.nested (21.8.7) 508
- except.spec (18.4) 429
- except.special (18.5) 432
- except.terminate (18.5.1) 432
- except.throw (18.1) 425
- except.uncaught (18.5.2) 433
- exception (21.8.2) 505
- exception.syn (21.8.1) 504
- exception.terminate (21.8.4) 506
- exclusive.scan (29.8.7) 1133
- execpol (23.19) 723
- execpol.general (23.19.1) 723
- execpol.objects (23.19.7) 725
- execpol.par (23.19.5) 724
- execpol.parunseq (23.19.6) 724
- execpol.seq (23.19.4) 724
- execpol.type (23.19.3) 724
- execution.syn (23.19.2) 723
- expos.only.types (20.4.2.1.2) 453
- expr (8) 93
- expr.add (8.7) 131
- expr.alignof (8.3.6) 129
- expr.ass (8.18) 138
- expr.bit.and (8.11) 135
- expr.call (8.2.2) 109
- expr.cast (8.4) 129
- expr.comma (8.19) 139
- expr.cond (8.16) 136
- expr.const (8.20) 139
- expr.const.cast (8.2.11) 119
- expr.delete (8.3.5) 127
- expr.dynamic.cast (8.2.7) 113
- expr.eq (8.10) 133
- expr.log.and (8.14) 135
- expr.log.or (8.15) 135
- expr.mptr.oper (8.5) 130
- expr.mul (8.6) 131
- expr.new (8.3.4) 122
- expr.or (8.13) 135
- expr.post (8.2) 108
- expr.post.incr (8.2.6) 113
- expr.pre.incr (8.3.2) 121
- expr.prim (8.1) 96
- expr.prim.fold (8.1.6) 108
- expr.prim.id (8.1.4) 97
- expr.prim.id.qual (8.1.4.2) 98
- expr.prim.id.unqual (8.1.4.1) 97
- expr.prim.lambda (8.1.5) 98
- expr.prim.lambda.capture (8.1.5.2) 103
- expr.prim.lambda.closure (8.1.5.1) 99
- expr.prim.literal (8.1.1) 96
- expr.prim.paren (8.1.3) 97
- expr.prim.this (8.1.2) 96
- expr.pseudo (8.2.4) 112
- expr.ref (8.2.5) 112
- expr.reinterpret.cast (8.2.10) 117
- expr.rel (8.9) 133
- expr.shift (8.8) 132
- expr.sizeof (8.3.3) 121
- expr.static.cast (8.2.9) 115
- expr.sub (8.2.1) 109
- expr.throw (8.17) 137
- expr.type.conv (8.2.3) 111
- expr.typeid (8.2.8) 114
- expr.unary (8.3) 120
- expr.unary.noexcept (8.3.7) 129
- expr.unary.op (8.3.1) 120
- expr.xor (8.12) 135
- ext.manip (30.7.7) 1211
- extern.names (20.5.4.3.3) 471
- extern.types (20.5.4.3.4) 471
- facet ctype.char.dtor (25.4.1.3.1) 796
- facet ctype.char.members (25.4.1.3.2) 796
- facet ctype.char.statics (25.4.1.3.3) 797
- facet ctype.char.virtuals (25.4.1.3.4) 797
- facet ctype.special (25.4.1.3) 795
- facet.num.get.members (25.4.2.1.1) 803
- facet.num.get.virtuals (25.4.2.1.2) 803
- facet.num.put.members (25.4.2.2.1) 806
- facet.num.put.virtuals (25.4.2.2.2) 807

facet.numpunct (25.4.3)	809	fs.def.hardlink (30.10.4.7)	1240
facet.numpunct.members (25.4.3.1.1)	810	fs.def.link (30.10.4.8)	1241
facet.numpunct.virtuals (25.4.3.1.2)	811	fs.def.native (30.10.4.10)	1241
facets.examples (25.4.8)	826	fs.def.native.encode (30.10.4.9)	1241
file.streams (30.9)	1225	fs.def.normal.form (30.10.4.11)	1241
filebuf (30.9.2)	1225	fs.def.osdep (30.10.4.12)	1241
filebuf.assign (30.9.2.2)	1228	fs.def.parent (30.10.4.13)	1241
filebuf.cons (30.9.2.1)	1227	fs.def.parent.other (30.10.4.14)	1241
filebuf.members (30.9.2.3)	1228	fs.def.path (30.10.4.15)	1241
filebuf.virtuals (30.9.2.4)	1229	fs.def.pathname (30.10.4.16)	1242
filesystem_error.members (30.10.9.1)	1264	fs.def.pathres (30.10.4.17)	1242
filesystems (30.10)	1239	fs.def.race (30.10.4.5)	1240
floatfield.manip (30.5.6.4)	1178	fs.def.rel.path (30.10.4.18)	1242
fntflags.manip (30.5.6.1)	1177	fs.def.symlink (30.10.4.19)	1242
fntflags.state (30.5.3.2)	1168	fs.definitions (30.10.4)	1240
forward (23.2.5)	535	fs.dir.entry.cons (30.10.12.1)	1271
forward.iterators (27.2.5)	959	fs.dir.entry.mods (30.10.12.2)	1271
forward_list.syn (26.3.4)	870	fs.dir.entry.obs (30.10.12.3)	1271
forwardlist (26.3.9)	878	fs.dir.itr.members (30.10.13.1)	1275
forwardlist.access (26.3.9.4)	882	fs.dir.itr.nonmembers (30.10.13.2)	1275
forwardlist.cons (26.3.9.2)	881	fs.enum (30.10.10)	1265
forwardlist.iter (26.3.9.3)	882	fs.enum.copy.opts (30.10.10.3)	1265
forwardlist.modifiers (26.3.9.5)	882	fs.enum.dir.opts (30.10.10.6)	1268
forwardlist.ops (26.3.9.6)	884	fs.enum.file_type (30.10.10.2)	1265
forwardlist.overview (26.3.9.1)	878	fs.enum.path.format (30.10.10.1)	1265
forwardlist.spec (26.3.9.7)	886	fs.enum.perm.opts (30.10.10.5)	1267
fp.style (21.3.3)	483	fs.enum.perms (30.10.10.4)	1265
fpos (30.5.4)	1171	fs.err.report (30.10.7)	1247
fpos.members (30.5.4.1)	1171	fs.file_status.cons (30.10.11.1)	1268
fpos.operations (30.5.4.2)	1171	fs.file_status.mods (30.10.11.3)	1269
front.insert.iter.cons (27.5.2.4.1)	974	fs.file_status.obs (30.10.11.2)	1268
front.insert.iter.op* (27.5.2.4.3)	974	fs.filesystem.syn (30.10.6)	1242
front.insert.iter.op++ (27.5.2.4.4)	974	fs.general (30.10.1)	1239
front.insert.iter.op= (27.5.2.4.2)	974	fs.norm.ref (30.10.3)	1240
front.insert.iter.ops (27.5.2.4)	974	fs.op.absolute (30.10.15.1)	1279
front.insert.iterator (27.5.2.3)	973	fs.op.canonical (30.10.15.2)	1279
front.inserter (27.5.2.4.5)	974	fs.op.copy (30.10.15.3)	1279
fs.class.directory_entry (30.10.12)	1269	fs.op.copy_file (30.10.15.4)	1281
fs.class.directory_iterator (30.10.13)	1273	fs.op.copy_symlink (30.10.15.5)	1282
fs.class.file_status (30.10.11)	1268	fs.op.create_dir_symlk (30.10.15.8)	1283
fs.class.filesystem_error (30.10.9)	1263	fs.op.create_directories (30.10.15.6)	1282
fs.class.path (30.10.8)	1247	fs.op.create_directory (30.10.15.7)	1283
fs.class.rec.dir.itr (30.10.14)	1276	fs.op.create_hard_lk (30.10.15.9)	1283
fs.conform.9945 (30.10.2.1)	1239	fs.op.create_symlink (30.10.15.10)	1284
fs.conform.os (30.10.2.2)	1239	fs.op.current_path (30.10.15.11)	1284
fs.conformance (30.10.2)	1239	fs.op.equivalent (30.10.15.12)	1284
fs.def.absolute.path (30.10.4.1)	1240	fs.op.exists (30.10.15.13)	1285
fs.def.directory (30.10.4.2)	1240	fs.op.file_size (30.10.15.14)	1285
fs.def.file (30.10.4.3)	1240	fs.op.funcs (30.10.15)	1279
fs.def.filename (30.10.4.6)	1240	fs.op.hard_lk_ct (30.10.15.15)	1285
fs.def.filesystem (30.10.4.4)	1240	fs.op.is_block_file (30.10.15.16)	1285

fs.op.is_char_file (30.10.15.17)	1286	fstream.cons (30.9.5.1)	1237
fs.op.is_directory (30.10.15.18)	1286	fstream.members (30.9.5.3)	1238
fs.op.is_empty (30.10.15.19)	1286	fstream.syn (30.9.1)	1225
fs.op.is_fifo (30.10.15.20)	1286	func.bind (23.14.11)	666
fs.op.is_other (30.10.15.21)	1287	func.bind.bind (23.14.11.3)	667
fs.op.is_regular_file (30.10.15.22)	1287	func.bind.isbind (23.14.11.1)	666
fs.op.is_socket (30.10.15.23)	1287	func.bind.isplace (23.14.11.2)	666
fs.op.is_symlink (30.10.15.24)	1287	func.bind.place (23.14.11.4)	668
fs.op.last_write_time (30.10.15.25)	1288	func.def (23.14.2)	655
fs.op.permissions (30.10.15.26)	1288	func.invoke (23.14.4)	656
fs.op.proximate (30.10.15.27)	1288	func.memfn (23.14.12)	668
fs.op.read_symlink (30.10.15.28)	1289	func.not_fn (23.14.10)	665
fs.op.relative (30.10.15.29)	1289	func.require (23.14.3)	655
fs.op.remove (30.10.15.30)	1289	func.search (23.14.14)	673
fs.op.remove_all (30.10.15.31)	1289	func.search.bm (23.14.14.2)	674
fs.op.rename (30.10.15.32)	1290	func.search.bmh (23.14.14.3)	675
fs.op.resize_file (30.10.15.33)	1290	func.search.default (23.14.14.1)	673
fs.op.space (30.10.15.34)	1290	func.wrap (23.14.13)	668
fs.op.status (30.10.15.35)	1290	func.wrap.badcall (23.14.13.1)	668
fs.op.status_known (30.10.15.36)	1292	func.wrap.badcall.const (23.14.13.1.1)	669
fs.op.symlink_status (30.10.15.37)	1292	func.wrap.func (23.14.13.2)	669
fs.op.temp_dir_path (30.10.15.38)	1292	func.wrap.func.alg (23.14.13.2.7)	672
fs.op.weakly_canonical (30.10.15.39)	1292	func.wrap.func.cap (23.14.13.2.3)	672
fs.path.append (30.10.8.4.3)	1254	func.wrap.func.con (23.14.13.2.1)	670
fs.path.assign (30.10.8.4.2)	1254	func.wrap.func.inv (23.14.13.2.4)	672
fs.path.compare (30.10.8.4.8)	1258	func.wrap.func.mod (23.14.13.2.2)	672
fs.path.concat (30.10.8.4.4)	1255	func.wrap.func.nullptr (23.14.13.2.6)	672
fs.path.construct (30.10.8.4.1)	1253	func.wrap.func.targ (23.14.13.2.5)	672
fs.path.cvt (30.10.8.2)	1251	function.objects (23.14)	652
fs.path.decompose (30.10.8.4.9)	1258	functional.syn (23.14.1)	653
fs.path.factory (30.10.8.6.2)	1263	functions.within.classes (20.4.2.2)	455
fs.path.fmt.cvt (30.10.8.2.1)	1251	future.syn (33.6.2)	1395
fs.path.gen (30.10.8.4.11)	1260	futures (33.6)	1395
fs.path.generic (30.10.8.1)	1250	futures.async (33.6.9)	1406
fs.path.generic.obs (30.10.8.4.7)	1257	futures.errors (33.6.3)	1397
fs.path.io (30.10.8.6.1)	1263	futures.future_error (33.6.4)	1397
fs.path.itr (30.10.8.5)	1261	futures.overview (33.6.1)	1395
fs.path.member (30.10.8.4)	1253	futures.promise (33.6.6)	1398
fs.path.modifiers (30.10.8.4.5)	1255	futures.shared_future (33.6.8)	1404
fs.path.native.obs (30.10.8.4.6)	1257	futures.state (33.6.5)	1397
fs.path.nonmember (30.10.8.6)	1262	futures.task (33.6.10)	1408
fs.path.query (30.10.8.4.10)	1259	futures.task.members (33.6.10.1)	1409
fs.path.req (30.10.8.3)	1252	futures.task.nonmembers (33.6.10.2)	1410
fs.path.type.cvt (30.10.8.2.2)	1252	futures.unique_future (33.6.7)	1401
fs.race.behavior (30.10.2.3)	1239		
fs.rec.dir.itr.members (30.10.14.1)	1277	get.new.handler (21.6.3.5)	501
fs.rec.dir.itr.nonmembers (30.10.14.2)	1279	get.terminate (21.8.4.3)	506
fs.req (30.10.5)	1242	global.functions (20.5.5.4)	474
fs.req.namespace (30.10.5.1)	1242	gram (A)	1412
fstream (30.9.5)	1236	gram.basic (A.3)	1417
fstream.assign (30.9.5.2)	1238	gram.class (A.8)	1428

gram.cpp (A.14) 1432
 gram.dcl (A.6) 1422
 gram.decl (A.7) 1426
 gram.derived (A.9) 1429
 gram.except (A.13) 1431
 gram.expr (A.4) 1417
 gram.key (A.1) 1412
 gram.lex (A.2) 1412
 gram.over (A.11) 1430
 gram.special (A.10) 1430
 gram.stmt (A.5) 1421
 gram.temp (A.12) 1430
 gslice.access (29.7.6.3) 1121
 gslice.array.assign (29.7.7.2) 1122
 gslice.array.comp.assign (29.7.7.3) 1122
 gslice.array.fill (29.7.7.4) 1122
 gslice.cons (29.7.6.2) 1121

 handler.functions (20.5.4.7) 472
 hardware.interference (21.6.5) 502
 hash.requirements (20.5.3.4) 463
 headers (20.5.1.2) 456

 ifstream (30.9.3) 1232
 ifstream.assign (30.9.3.2) 1233
 ifstream.cons (30.9.3.1) 1233
 ifstream.members (30.9.3.3) 1234
 implimits (B) 1434
 includes (28.7.6.1) 1040
 inclusive.scan (29.8.8) 1134
 indirect.array.assign (29.7.9.2) 1124
 indirect.array.comp.assign (29.7.9.3) 1124
 indirect.array.fill (29.7.9.4) 1125
 initializer_list.syn (21.9.1) 509
 inner.product (29.8.4) 1131
 input.iterators (27.2.3) 957
 input.output (30) 1157
 input.output.general (30.1) 1157
 input.streams (30.7.4) 1190
 insert.iter.cons (27.5.2.6.1) 975
 insert.iter.op* (27.5.2.6.3) 975
 insert.iter.op++ (27.5.2.6.4) 976
 insert.iter.op= (27.5.2.6.2) 975
 insert.iter.ops (27.5.2.6) 975
 insert.iterator (27.5.2.5) 975
 insert.iterators (27.5.2) 972
 inserter (27.5.2.6.5) 976
 intro (4) 7
 intro.ack (4.8) 20
 intro.compliance (4.1) 7
 intro.defs (3) 3

 intro.execution (4.6) 11
 intro.memory (4.4) 8
 intro.multithread (4.7) 15
 intro.object (4.5) 9
 intro.progress (4.7.2) 19
 intro.races (4.7.1) 15
 intro.refs (2) 2
 intro.scope (1) 1
 intro.structure (4.2) 8
 intseq (23.3) 538
 intseq.general (23.3.1) 538
 intseq.intseq (23.3.2) 538
 intseq.make (23.3.3) 539
 invalid.argument (22.2.4) 514
 iomanip.syn (30.7.3) 1189
 ios (30.5.5) 1172
 ios.base (30.5.3) 1163
 ios.base.callback (30.5.3.6) 1170
 ios.base.cons (30.5.3.7) 1171
 ios.base.locales (30.5.3.3) 1169
 ios.base.storage (30.5.3.5) 1170
 ios.members.static (30.5.3.4) 1169
 ios.overview (30.5.5.1) 1172
 ios.syn (30.5.1) 1162
 ios.types (30.5.3.1) 1166
 ios::failure (30.5.3.1.1) 1166
 ios::fmtflags (30.5.3.1.2) 1166
 ios::Init (30.5.3.1.6) 1168
 ios::iostate (30.5.3.1.3) 1166
 ios::openmode (30.5.3.1.4) 1166
 ios::seekdir (30.5.3.1.5) 1166
 iosfwd.syn (30.3.1) 1158
 iostate.flags (30.5.5.4) 1176
 ostream.assign (30.7.4.6.3) 1202
 ostream.cons (30.7.4.6.1) 1201
 ostream.dest (30.7.4.6.2) 1201
 ostream.format (30.7) 1188
 ostream.forward (30.3) 1158
 ostream.forward.overview (30.3.2) 1160
 ostream.limits.imbue (30.2.1) 1158
 ostream.objects (30.4) 1160
 ostream.objects.overview (30.4.2) 1161
 ostream.syn (30.4.1) 1160
 ostreamclass (30.7.4.6) 1201
 iostreams.base (30.5) 1162
 iostreams.limits.pos (30.2.2) 1158
 iostreams.requirements (30.2) 1158
 iostreams.threadafety (30.2.3) 1158
 is.heap (28.7.7.5) 1044
 is.sorted (28.7.1.5) 1033
 istream (30.7.4.1) 1190

- istream.assign (30.7.4.1.2) 1192
- istream.cons (30.7.4.1.1) 1192
- istream.extractors (30.7.4.2.3) 1194
- istream.formatted (30.7.4.2) 1193
- istream.formatted.arithmetic (30.7.4.2.2) 1193
- istream.formatted.reqmts (30.7.4.2.1) 1193
- istream.iterator (27.6.1) 980
- istream.iterator.cons (27.6.1.1) 981
- istream.iterator.ops (27.6.1.2) 981
- istream.manip (30.7.4.4) 1200
- istream.rvalue (30.7.4.5) 1200
- istream.syn (30.7.1) 1188
- istream.unformatted (30.7.4.3) 1196
- istream::sentry (30.7.4.1.3) 1192
- istreambuf.iterator (27.6.3) 983
- istreambuf.iterator.cons (27.6.3.2) 985
- istreambuf.iterator.ops (27.6.3.3) 985
- istreambuf.iterator.proxy (27.6.3.1) 984
- istringstream (30.8.3) 1220
- istringstream.assign (30.8.3.2) 1221
- istringstream.cons (30.8.3.1) 1220
- istringstream.members (30.8.3.3) 1221
- iterator.container (27.8) 988
- iterator.iterators (27.2.2) 956
- iterator.operations (27.4.3) 967
- iterator.primitives (27.4) 964
- iterator.range (27.7) 987
- iterator.requirements (27.2) 955
- iterator.requirements.general (27.2.1) 955
- iterator.synopsis (27.3) 961
- iterator.traits (27.4.1) 964
- iterators (27) 955
- iterators.general (27.1) 955

- language.support (21) 478
- length.error (22.2.5) 514
- lex (5) 22
- lex.bool (5.13.6) 36
- lex.ccon (5.13.3) 31
- lex.charset (5.3) 23
- lex.comment (5.7) 26
- lex.digraph (5.5) 25
- lex.ext (5.13.8) 37
- lex.fcon (5.13.4) 33
- lex.header (5.8) 26
- lex.icon (5.13.2) 29
- lex.key (5.11) 28
- lex.literal (5.13) 29
- lex.literal.kinds (5.13.1) 29
- lex.name (5.10) 27
- lex.nullptr (5.13.7) 37
- lex.operators (5.12) 29
- lex.phases (5.2) 22
- lex.ppnumber (5.9) 26
- lex.pptoken (5.4) 24
- lex.separate (5.1) 22
- lex.string (5.13.5) 34
- lex.token (5.6) 25
- lib.types.movedfrom (20.5.5.15) 477
- library (20) 447
- library.c (20.2) 448
- library.general (20.1) 447
- limits.syn (21.3.2) 483
- list (26.3.10) 886
- list.capacity (26.3.10.3) 889
- list.cons (26.3.10.2) 889
- list.modifiers (26.3.10.4) 890
- list.ops (26.3.10.5) 890
- list.overview (26.3.10.1) 886
- list.special (26.3.10.6) 892
- list.syn (26.3.5) 870
- locale (25.3.1) 784
- locale.categories (25.4) 791
- locale.category (25.3.1.1.1) 785
- locale.codecvt (25.4.1.4) 797
- locale.codecvt.byname (25.4.1.5) 801
- locale.codecvt.members (25.4.1.4.1) 798
- locale.codecvt.virtuals (25.4.1.4.2) 799
- locale.collate (25.4.4.1) 811
- locale.collate.byname (25.4.4.2) 813
- locale.collate.members (25.4.4.1.1) 812
- locale.collate.virtuals (25.4.4.1.2) 812
- locale.cons (25.3.1.2) 788
- locale.convenience (25.3.3) 790
- locale.ctype (25.4.1.1) 791
- locale.ctype.byname (25.4.1.2) 794
- locale.ctype.members (25.4.1.1.1) 792
- locale.ctype.virtuals (25.4.1.1.2) 793
- locale.facet (25.3.1.1.2) 786
- locale.global.templates (25.3.2) 790
- locale.id (25.3.1.1.3) 788
- locale.members (25.3.1.3) 789
- locale.messages (25.4.7.1) 824
- locale.messages.byname (25.4.7.2) 826
- locale.messages.members (25.4.7.1.1) 825
- locale.messages.virtuals (25.4.7.1.2) 825
- locale.money.get (25.4.6.1) 819
- locale.money.get.members (25.4.6.1.1) 819
- locale.money.get.virtuals (25.4.6.1.2) 819
- locale.money.put (25.4.6.2) 820
- locale.money.put.members (25.4.6.2.1) 821
- locale.money.put.virtuals (25.4.6.2.2) 821

locale.money_punct (25.4.6.3)	822	mem.res.monotonic.buffer.mem (23.12.6.2)	646
locale.money_punct.byname (25.4.6.4)	824	mem.res.pool (23.12.5)	641
locale.money_punct.members (25.4.6.3.1)	823	mem.res.pool.ctor (23.12.5.3)	643
locale.money_punct.virtuals (25.4.6.3.2)	823	mem.res.pool.mem (23.12.5.4)	644
locale.nm.put (25.4.2.2)	806	mem.res.pool.options (23.12.5.2)	643
locale.num.get (25.4.2.1)	802	mem.res.pool.overview (23.12.5.1)	641
locale.numpunct (25.4.3.1)	809	mem.res.private (23.12.2.2)	637
locale.numpunct.byname (25.4.3.2)	811	mem.res.public (23.12.2.1)	636
locale.operators (25.3.1.4)	789	mem.res.syn (23.12.1)	635
locale.statics (25.3.1.5)	790	member.functions (20.5.5.5)	474
locale.syn (25.2)	782	memory (23.10)	594
locale.time.get (25.4.5.1)	813	memory.general (23.10.1)	594
locale.time.get.byname (25.4.5.2)	817	memory.syn (23.10.2)	594
locale.time.get.members (25.4.5.1.1)	814	meta (23.15)	676
locale.time.get.virtuals (25.4.5.1.2)	815	meta.help (23.15.3)	684
locale.time.put (25.4.5.3)	817	meta.logical (23.15.8)	701
locale.time.put.byname (25.4.5.4)	818	meta.rel (23.15.6)	694
locale.time.put.members (25.4.5.3.1)	818	meta.rqmts (23.15.1)	676
locale.time.put.virtuals (25.4.5.3.2)	818	meta.trans (23.15.7)	695
locale.types (25.3.1.1)	785	meta.trans.arr (23.15.7.4)	698
locales (25.3)	784	meta.trans.cv (23.15.7.1)	695
localization (25)	782	meta.trans.other (23.15.7.6)	699
localization.general (25.1)	782	meta.trans.ptr (23.15.7.5)	698
logic.error (22.2.2)	513	meta.trans.ref (23.15.7.2)	696
logical.operations (23.14.8)	662	meta.trans.sign (23.15.7.3)	696
logical.operations.and (23.14.8.1)	662	meta.type.synop (23.15.2)	677
logical.operations.not (23.14.8.3)	663	meta.unary (23.15.4)	684
logical.operations.or (23.14.8.2)	663	meta.unary.cat (23.15.4.1)	684
lower.bound (28.7.3.1)	1034	meta.unary.comp (23.15.4.2)	685
		meta.unary.prop (23.15.4.3)	685
macro.names (20.5.4.3.2)	471	meta.unary.prop.query (23.15.5)	693
make.heap (28.7.7.3)	1044	mismatch (28.5.10)	1016
map (26.4.4)	903	move.iter.nonmember (27.5.3.3.14)	980
map.access (26.4.4.3)	907	move.iter.op.+ (27.5.3.3.8)	979
map.cons (26.4.4.2)	907	move.iter.op.+= (27.5.3.3.9)	979
map.modifiers (26.4.4.4)	907	move.iter.op.- (27.5.3.3.10)	979
map.overview (26.4.4.1)	903	move.iter.op.-= (27.5.3.3.11)	979
map.special (26.4.4.5)	909	move.iter.op.comp (27.5.3.3.13)	979
mask.array.assign (29.7.8.2)	1123	move.iter.op.const (27.5.3.3.1)	977
mask.array.comp.assign (29.7.8.3)	1123	move.iter.op.conv (27.5.3.3.3)	978
mask.array.fill (29.7.8.4)	1123	move.iter.op.decr (27.5.3.3.7)	978
mem.poly allocator.class (23.12.3)	637	move.iter.op.incr (27.5.3.3.6)	978
mem.poly allocator.ctor (23.12.3.1)	638	move.iter.op.index (27.5.3.3.12)	979
mem.poly allocator.eq (23.12.3.3)	640	move.iter.op.ref (27.5.3.3.5)	978
mem.poly allocator.mem (23.12.3.2)	639	move.iter.op.star (27.5.3.3.4)	978
mem.res (23.12)	635	move.iter.op.= (27.5.3.3.2)	978
mem.res.class (23.12.2)	636	move.iter.ops (27.5.3.3)	977
mem.res.eq (23.12.2.3)	637	move.iter.requirements (27.5.3.2)	977
mem.res.global (23.12.4)	641	move.iterator (27.5.3.1)	976
mem.res.monotonic.buffer (23.12.6)	644	move.iterators (27.5.3)	976
mem.res.monotonic.buffer.ctor (23.12.6.1)	645	multibyte.strings (20.4.2.1.5.2)	455

- multimap (26.4.5) 909
- multimap.cons (26.4.5.2) 913
- multimap.modifiers (26.4.5.3) 913
- multimap.overview (26.4.5.1) 909
- multimap.special (26.4.5.4) 913
- multiset (26.4.7) 917
- multiset.cons (26.4.7.2) 921
- multiset.overview (26.4.7.1) 917
- multiset.special (26.4.7.3) 921
- mutex.syn (33.4.1) 1367

- namespace.alias (10.3.2) 182
- namespace.constraints (20.5.4.2) 469
- namespace.def (10.3.1) 178
- namespace.future (20.5.4.2.3) 470
- namespace.memdef (10.3.1.2) 180
- namespace.posix (20.5.4.2.2) 469
- namespace.qual (6.4.3.2) 58
- namespace.std (20.5.4.2.1) 469
- namespace.udecl (10.3.3) 182
- namespace.udir (10.3.4) 188
- namespace.unnamed (10.3.1.1) 180
- narrow.stream.objects (30.4.3) 1161
- new.badlength (21.6.3.2) 500
- new.delete (21.6.2) 495
- new.delete.array (21.6.2.2) 497
- new.delete.dataraces (21.6.2.4) 500
- new.delete.placement (21.6.2.3) 499
- new.delete.single (21.6.2.1) 495
- new.handler (21.6.3.3) 501
- new.syn (21.6.1) 494
- nullablepointer.requirements (20.5.3.3) 463
- numarray (29.7) 1105
- numeric.iota (29.8.12) 1139
- numeric.limits (21.3.4) 484
- numeric.limits.members (21.3.4.1) 485
- numeric.ops (29.8) 1125
- numeric.ops.gcd (29.8.13) 1139
- numeric.ops.lcm (29.8.14) 1139
- numeric.ops.overview (29.8.1) 1125
- numeric.requirements (29.3) 1050
- numeric.special (21.3.4.2) 489
- numerics (29) 1050
- numerics.defns (29.2) 1050
- numerics.general (29.1) 1050

- objects.within.classes (20.4.2.3) 456
- ofstream (30.9.4) 1234
- ofstream.assign (30.9.4.2) 1235
- ofstream.cons (30.9.4.1) 1235
- ofstream.members (30.9.4.3) 1236

- operators (23.2.2) 534
- optional (23.6) 554
- optional.assign (23.6.3.3) 559
- optional.bad.access (23.6.5) 565
- optional.comp_with_t (23.6.8) 567
- optional.ctor (23.6.3.1) 557
- optional.dtor (23.6.3.2) 559
- optional.general (23.6.1) 554
- optional.hash (23.6.10) 568
- optional.mod (23.6.3.6) 565
- optional.nullopts (23.6.7) 566
- optional.nullopt (23.6.4) 565
- optional.observe (23.6.3.5) 563
- optional.optional (23.6.3) 556
- optional.relops (23.6.6) 565
- optional.specalg (23.6.9) 568
- optional.swap (23.6.3.4) 563
- optional.syn (23.6.2) 554
- organization (20.5.1) 456
- ostream (30.7.5.1) 1202
- ostream.assign (30.7.5.1.2) 1204
- ostream.cons (30.7.5.1.1) 1204
- ostream.formatted (30.7.5.2) 1205
- ostream.formatted.reqmts (30.7.5.2.1) 1205
- ostream.inserters (30.7.5.2.3) 1207
- ostream.inserters.arithmetic (30.7.5.2.2) 1206
- ostream.inserters.character (30.7.5.2.4) 1208
- ostream.iterator (27.6.2) 982
- ostream.iterator.cons.des (27.6.2.1) 983
- ostream.iterator.ops (27.6.2.2) 983
- ostream.manip (30.7.5.4) 1209
- ostream.rvalue (30.7.5.5) 1209
- ostream.seek (30.7.5.1.4) 1205
- ostream.syn (30.7.2) 1189
- ostream.unformatted (30.7.5.3) 1208
- ostream::sentry (30.7.5.1.3) 1204
- ostreambuf.iter.cons (27.6.4.1) 986
- ostreambuf.iter.ops (27.6.4.2) 986
- ostreambuf.iterator (27.6.4) 985
- ostreamstring (30.8.4) 1221
- ostreamstring.assign (30.8.4.2) 1222
- ostreamstring.cons (30.8.4.1) 1222
- ostreamstring.members (30.8.4.3) 1223
- out.of.range (22.2.6) 515
- output.iterators (27.2.4) 958
- output.streams (30.7.5) 1202
- over (16) 311
- over.ass (16.5.3) 338
- over.best.ics (16.3.3.1) 326
- over.binary (16.5.2) 337
- over.built (16.6) 341

- over.call (16.5.4) 338
- over.call.func (16.3.1.1.1) 317
- over.call.object (16.3.1.1.2) 317
- over.dcl (16.2) 313
- over.ics.ellipsis (16.3.3.1.3) 329
- over.ics.list (16.3.3.1.5) 330
- over.ics.rank (16.3.3.2) 332
- over.ics.ref (16.3.3.1.4) 329
- over.ics.scs (16.3.3.1.1) 328
- over.ics.user (16.3.3.1.2) 328
- over.inc (16.5.7) 339
- over.literal (16.5.8) 340
- over.load (16.1) 311
- over.match (16.3) 314
- over.match.best (16.3.3) 324
- over.match.call (16.3.1.1) 316
- over.match.class.deduct (16.3.1.8) 322
- over.match.conv (16.3.1.5) 321
- over.match.copy (16.3.1.4) 321
- over.match.ctor (16.3.1.3) 321
- over.match.funcs (16.3.1) 315
- over.match.list (16.3.1.7) 322
- over.match.oper (16.3.1.2) 318
- over.match.ref (16.3.1.6) 322
- over.match.viable (16.3.2) 323
- over.oper (16.5) 336
- over.over (16.4) 335
- over.ref (16.5.6) 339
- over.sub (16.5.5) 338
- over.unary (16.5.1) 337
- overflow.error (22.2.9) 516

- pair.astuple (23.4.4) 542
- pair.pieces (23.4.5) 543
- pairs (23.4) 539
- pairs.general (23.4.1) 539
- pairs.pair (23.4.2) 539
- pairs.spec (23.4.3) 541
- partial.sort (28.7.1.3) 1032
- partial.sort.copy (28.7.1.4) 1032
- partial.sum (29.8.6) 1133
- pointer.traits (23.10.3) 599
- pointer.traits.functions (23.10.3.2) 600
- pointer.traits.types (23.10.3.1) 600
- pop.heap (28.7.7.2) 1043
- predef.iterators (27.5) 967
- priority.queue (26.6.5) 949
- priqueue.cons (26.6.5.1) 950
- priqueue.cons.alloc (26.6.5.2) 951
- priqueue.members (26.6.5.3) 951
- priqueue.special (26.6.5.4) 952

- propagation (21.8.6) 507
- protection.within.classes (20.5.5.10) 475
- ptr.align (23.10.5) 601
- ptr.laundry (21.6.4) 501
- push.heap (28.7.7.1) 1043

- queue (26.6.4) 947
- queue.cons (26.6.4.2) 948
- queue.cons.alloc (26.6.4.3) 948
- queue.defn (26.6.4.1) 947
- queue.ops (26.6.4.4) 948
- queue.special (26.6.4.5) 949
- queue.syn (26.6.2) 946
- quoted.manip (30.7.8) 1213

- rand (29.6) 1062
- rand.adapt (29.6.4) 1077
- rand.adapt.disc (29.6.4.2) 1078
- rand.adapt.general (29.6.4.1) 1077
- rand.adapt.ibits (29.6.4.3) 1079
- rand.adapt.shuf (29.6.4.4) 1080
- rand.device (29.6.6) 1082
- rand.dist (29.6.8) 1085
- rand.dist.bern (29.6.8.3) 1087
- rand.dist.bern.bernoulli (29.6.8.3.1) 1087
- rand.dist.bern.bin (29.6.8.3.2) 1088
- rand.dist.bern.geo (29.6.8.3.3) 1089
- rand.dist.bern.negbin (29.6.8.3.4) 1090
- rand.dist.general (29.6.8.1) 1085
- rand.dist.norm (29.6.8.5) 1095
- rand.dist.norm.cauchy (29.6.8.5.4) 1097
- rand.dist.norm.chisq (29.6.8.5.3) 1096
- rand.dist.norm.f (29.6.8.5.5) 1098
- rand.dist.norm.lognormal (29.6.8.5.2) 1096
- rand.dist.norm.normal (29.6.8.5.1) 1095
- rand.dist.norm.t (29.6.8.5.6) 1099
- rand.dist.pois (29.6.8.4) 1091
- rand.dist.pois.exp (29.6.8.4.2) 1091
- rand.dist.pois.extreme (29.6.8.4.5) 1094
- rand.dist.pois.gamma (29.6.8.4.3) 1092
- rand.dist.pois.poisson (29.6.8.4.1) 1091
- rand.dist.pois.weibull (29.6.8.4.4) 1093
- rand.dist.samp (29.6.8.6) 1100
- rand.dist.samp.discrete (29.6.8.6.1) 1100
- rand.dist.samp.pconst (29.6.8.6.2) 1101
- rand.dist.samp.plinear (29.6.8.6.3) 1103
- rand.dist.uni (29.6.8.2) 1086
- rand.dist.uni.int (29.6.8.2.1) 1086
- rand.dist.uni.real (29.6.8.2.2) 1086
- rand.eng (29.6.3) 1073
- rand.eng.lcong (29.6.3.1) 1074

rand.eng.mers (29.6.3.2)	1075	re.req (31.3)	1298
rand.eng.sub (29.6.3.3)	1076	re.results (31.10)	1323
rand.predef (29.6.5)	1081	re.results.acc (31.10.4)	1326
rand.req (29.6.1)	1062	re.results.all (31.10.6)	1327
rand.req.adapt (29.6.1.5)	1067	re.results.const (31.10.1)	1325
rand.req.dist (29.6.1.6)	1068	re.results.form (31.10.5)	1327
rand.req.eng (29.6.1.4)	1065	re.results.nonmember (31.10.8)	1328
rand.req.genl (29.6.1.1)	1062	re.results.size (31.10.3)	1326
rand.req.seedseq (29.6.1.2)	1063	re.results.state (31.10.2)	1325
rand.req.urng (29.6.1.3)	1064	re.results.swap (31.10.7)	1328
rand.synopsis (29.6.2)	1071	re.submatch (31.9)	1318
rand.util (29.6.7)	1083	re.submatch.members (31.9.1)	1318
rand.util.canonical (29.6.7.2)	1085	re.submatch.op (31.9.2)	1319
rand.util.seedseq (29.6.7.1)	1083	re.syn (31.4)	1300
random.access.iterators (27.2.7)	960	re.synopt (31.5.1)	1306
range.error (22.2.8)	516	re.tokiter (31.12.2)	1336
ratio (23.16)	702	re.tokiter.cnstr (31.12.2.1)	1338
ratio.arithmetic (23.16.4)	704	re.tokiter.comp (31.12.2.2)	1338
ratio.comparison (23.16.5)	704	re.tokiter.deref (31.12.2.3)	1339
ratio.general (23.16.1)	702	re.tokiter.incr (31.12.2.4)	1339
ratio.ratio (23.16.3)	703	re.traits (31.7)	1310
ratio.si (23.16.6)	705	reduce (29.8.3)	1130
ratio.syn (23.16.2)	702	reentrancy (20.5.5.8)	475
re (31)	1297	refwrap (23.14.5)	656
re.alg (31.11)	1328	refwrap.access (23.14.5.3)	657
re.alg.match (31.11.2)	1328	refwrap.assign (23.14.5.2)	657
re.alg.replace (31.11.4)	1332	refwrap.const (23.14.5.1)	657
re.alg.search (31.11.3)	1330	refwrap.helpers (23.14.5.5)	657
re.badexp (31.6)	1309	refwrap.invoke (23.14.5.4)	657
re.const (31.5)	1306	replacement.functions (20.5.4.6)	471
re.def (31.2)	1297	requirements (20.5)	456
re.err (31.5.3)	1308	res.on.arguments (20.5.4.9)	473
re.except (31.11.1)	1328	res.on.data.races (20.5.5.9)	475
re.general (31.1)	1297	res.on.exception.handling (20.5.5.12)	476
re.grammar (31.13)	1339	res.on.functions (20.5.4.8)	472
re.iter (31.12)	1333	res.on.headers (20.5.5.2)	474
re.matchflag (31.5.2)	1307	res.on.macro.definitions (20.5.5.3)	474
re.regex (31.8)	1312	res.on.objects (20.5.4.10)	473
re.regex.assign (31.8.3)	1316	res.on.pointer.storage (20.5.5.13)	476
re.regex.const (31.8.1)	1314	res.on.required (20.5.4.11)	473
re.regex.construct (31.8.2)	1315	reserved.names (20.5.4.3)	470
re.regex.locale (31.8.5)	1317	reverse.iter.cons (27.5.1.3.1)	969
re.regex.nmswap (31.8.7.1)	1318	reverse.iter.conv (27.5.1.3.3)	969
re.regex.nonmemb (31.8.7)	1318	reverse.iter.make (27.5.1.3.21)	972
re.regex.operations (31.8.4)	1317	reverse.iter.op!= (27.5.1.3.15)	971
re.regex.swap (31.8.6)	1317	reverse.iter.op+ (27.5.1.3.8)	970
re.regiter (31.12.1)	1333	reverse.iter.op++ (27.5.1.3.6)	970
re.regiter.cnstr (31.12.1.1)	1334	reverse.iter.op+= (27.5.1.3.9)	970
re.regiter.comp (31.12.1.2)	1334	reverse.iter.op- (27.5.1.3.10)	970
re.regiter.deref (31.12.1.3)	1335	reverse.iter.op-= (27.5.1.3.11)	970
re.regiter.incr (31.12.1.4)	1335	reverse.iter.op-- (27.5.1.3.7)	970

reverse.iter.op.star (27.5.1.3.4)	969	sf.cmath.sph_bessel (29.9.5.19)	1155
reverse.iter.op< (27.5.1.3.14)	971	sf.cmath.sph_legendre (29.9.5.20)	1155
reverse.iter.op<= (27.5.1.3.18)	971	sf.cmath.sph_neumann (29.9.5.21)	1156
reverse.iter.op= (27.5.1.3.2)	969	shared_mutex.syn (33.4.2)	1368
reverse.iter.op== (27.5.1.3.13)	971	slice.access (29.7.4.3)	1118
reverse.iter.op> (27.5.1.3.16)	971	slice.arr.assign (29.7.5.2)	1119
reverse.iter.op>= (27.5.1.3.17)	971	slice.arr.comp.assign (29.7.5.3)	1119
reverse.iter.opdiff (27.5.1.3.19)	972	slice.arr.fill (29.7.5.4)	1119
reverse.iter.opindex (27.5.1.3.12)	971	smartptr (23.11)	609
reverse.iter.opref (27.5.1.3.5)	970	sort (28.7.1.1)	1031
reverse.iter.ops (27.5.1.3)	969	sort.heap (28.7.7.4)	1044
reverse.iter.opsum (27.5.1.3.20)	972	special (15)	280
reverse.iter.requirements (27.5.1.2)	969	specialized.addressof (23.10.10.1)	606
reverse.iterator (27.5.1.1)	967	specialized.algorithms (23.10.10)	606
reverse.iterators (27.5.1)	967	specialized.destroy (23.10.10.7)	608
round.style (21.3.3.1)	483	sstream.syn (30.8.1)	1214
runtime.error (22.2.7)	515	stable.sort (28.7.1.2)	1031
		stack (26.6.6)	952
scoped.adaptor.operators (23.13.5)	652	stack.cons (26.6.6.2)	953
sequence.reqmts (26.2.3)	837	stack.cons.alloc (26.6.6.3)	953
sequences (26.3)	868	stack.defn (26.6.6.1)	952
sequences.general (26.3.1)	868	stack.ops (26.6.6.4)	954
set (26.4.6)	913	stack.special (26.6.6.5)	954
set.cons (26.4.6.2)	917	stack.syn (26.6.3)	946
set.difference (28.7.6.4)	1041	std.exceptions (22.2)	513
set.intersection (28.7.6.3)	1041	std.ios.manip (30.5.6)	1177
set.new.handler (21.6.3.4)	501	std.iterator.tags (27.4.2)	966
set.overview (26.4.6.1)	913	std.manip (30.7.6)	1210
set.special (26.4.6.3)	917	stdexcept.syn (22.2.1)	513
set.symmetric.difference (28.7.6.5)	1042	stmt.ambig (9.8)	152
set.terminate (21.8.4.2)	506	stmt.block (9.3)	145
set.union (28.7.6.2)	1040	stmt.break (9.6.1)	151
sf.cmath (29.9.5)	1150	stmt.cont (9.6.2)	151
sf.cmath.assoc_laguerre (29.9.5.1)	1150	stmt.dcl (9.7)	152
sf.cmath.assoc_legendre (29.9.5.2)	1151	stmt.do (9.5.2)	149
sf.cmath.beta (29.9.5.3)	1151	stmt.expr (9.2)	145
sf.cmath.comp_ellint_1 (29.9.5.4)	1151	stmt.for (9.5.3)	149
sf.cmath.comp_ellint_2 (29.9.5.5)	1151	stmt.goto (9.6.4)	151
sf.cmath.comp_ellint_3 (29.9.5.6)	1152	stmt.if (9.4.1)	146
sf.cmath.cyl_bessel_i (29.9.5.7)	1152	stmt.iter (9.5)	147
sf.cmath.cyl_bessel_j (29.9.5.8)	1152	stmt.jump (9.6)	150
sf.cmath.cyl_bessel_k (29.9.5.9)	1152	stmt.label (9.1)	145
sf.cmath.cyl_neumann (29.9.5.10)	1153	stmt.ranged (9.5.4)	150
sf.cmath.ellint_1 (29.9.5.11)	1153	stmt.return (9.6.3)	151
sf.cmath.ellint_2 (29.9.5.12)	1153	stmt.select (9.4)	145
sf.cmath.ellint_3 (29.9.5.13)	1154	stmt.stmt (9)	144
sf.cmath.expint (29.9.5.14)	1154	stmt.switch (9.4.2)	147
sf.cmath.hermite (29.9.5.15)	1154	stmt.while (9.5.1)	148
sf.cmath.laguerre (29.9.5.16)	1154	stream.buffers (30.6)	1179
sf.cmath.legendre (29.9.5.17)	1155	stream.iterators (27.6)	980
sf.cmath.riemann_zeta (29.9.5.18)	1155	stream.types (30.5.2)	1163

streambuf (30.6.3)	1180	string.require (24.3.2.1)	741
streambuf.assign (30.6.3.3.1)	1184	string.rfind (24.3.2.7.3)	756
streambuf.buffer (30.6.3.2.2)	1183	string.special (24.3.3.8)	763
streambuf.cons (30.6.3.1)	1182	string.streams (30.8)	1214
streambuf.get.area (30.6.3.3.2)	1184	string.substr (24.3.2.7.8)	758
streambuf.locales (30.6.3.2.1)	1182	string.swap (24.3.2.6.8)	755
streambuf.members (30.6.3.2)	1182	string.syn (24.3.1)	732
streambuf.protected (30.6.3.3)	1184	string.view (24.4)	766
streambuf.pub.get (30.6.3.2.3)	1183	string.view.access (24.4.2.4)	771
streambuf.pub.pback (30.6.3.2.4)	1183	string.view.capacity (24.4.2.3)	771
streambuf.pub.put (30.6.3.2.5)	1184	string.view.comparison (24.4.3)	774
streambuf.put.area (30.6.3.3.3)	1185	string.view.cons (24.4.2.1)	770
streambuf.reqts (30.6.2)	1179	string.view.find (24.4.2.7)	773
streambuf.syn (30.6.1)	1179	string.view.hash (24.4.5)	776
streambuf.virt.buffer (30.6.3.4.2)	1185	string.view.io (24.4.4)	776
streambuf.virt.get (30.6.3.4.3)	1186	string.view.iterators (24.4.2.2)	770
streambuf.virt.locales (30.6.3.4.1)	1185	string.view.literals (24.4.6)	776
streambuf.virt.pback (30.6.3.4.4)	1187	string.view.modifiers (24.4.2.5)	772
streambuf.virt.put (30.6.3.4.5)	1187	string.view.ops (24.4.2.6)	772
streambuf.virtuals (30.6.3.4)	1185	string.view.synop (24.4.1)	767
string.access (24.3.2.5)	747	string.view.template (24.4.2)	768
string.accessors (24.3.2.7.1)	755	stringbuf (30.8.2)	1215
string.append (24.3.2.6.2)	748	stringbuf.assign (30.8.2.2)	1217
string.assign (24.3.2.6.3)	749	stringbuf.cons (30.8.2.1)	1216
string.capacity (24.3.2.4)	746	stringbuf.members (30.8.2.3)	1217
string.classes (24.3)	732	stringbuf.virtuals (30.8.2.4)	1218
string.compare (24.3.2.7.9)	758	strings (24)	726
string.cons (24.3.2.2)	741	strings.general (24.1)	726
string.conversions (24.3.4)	764	stringstream (30.8.5)	1223
string.copy (24.3.2.6.7)	754	stringstream.assign (30.8.5.2)	1224
string.erase (24.3.2.6.5)	752	stringstream.cons (30.8.5.1)	1224
string.find (24.3.2.7.2)	755	stringstream.members (30.8.5.3)	1225
string.find.first.not.of (24.3.2.7.6)	757	structure (20.4.1)	451
string.find.first.of (24.3.2.7.4)	756	structure.elements (20.4.1.1)	451
string.find.last.not.of (24.3.2.7.7)	758	structure.requirements (20.4.1.3)	451
string.find.last.of (24.3.2.7.5)	757	structure.see.also (20.4.1.5)	453
string.insert (24.3.2.6.4)	750	structure.specifications (20.4.1.4)	452
string.io (24.3.3.9)	763	structure.summary (20.4.1.2)	451
string.iterators (24.3.2.3)	745	support.dynamic (21.6)	494
string.modifiers (24.3.2.6)	747	support.exception (21.8)	504
string.nonmembers (24.3.3)	759	support.general (21.1)	478
string.op!= (24.3.3.3)	761	support.initlist (21.9)	509
string.op+ (24.3.3.1)	759	support.initlist.access (21.9.3)	510
string.op+= (24.3.2.6.1)	747	support.initlist.cons (21.9.2)	509
string.op< (24.3.3.4)	762	support.initlist.range (21.9.4)	510
string.op<= (24.3.3.6)	762	support.limits (21.3)	483
string.op> (24.3.3.5)	762	support.limits.general (21.3.1)	483
string.op>= (24.3.3.7)	762	support.rtti (21.7)	502
string.operator== (24.3.3.2)	761	support.runtime (21.10)	510
string.ops (24.3.2.7)	755	support.signal (21.10.4)	511
string.replace (24.3.2.6.6)	752	support.start.term (21.5)	493

- support.types (21.2) 478
- support.types.byteops (21.2.5) 481
- support.types.layout (21.2.4) 481
- support.types.nullptr (21.2.3) 481
- swappable.requirements (20.5.3.2) 461
- syntax (4.3) 8
- syserr (22.5) 519
- syserr.compare (22.5.5) 527
- syserr.errcat (22.5.2) 522
- syserr.errcat.derived (22.5.2.4) 523
- syserr.errcat.nonvirtuals (22.5.2.3) 522
- syserr.errcat.objects (22.5.2.5) 523
- syserr.errcat.overview (22.5.2.1) 522
- syserr.errcat.virtuals (22.5.2.2) 522
- syserr.errcode (22.5.3) 524
- syserr.errcode.constructors (22.5.3.2) 524
- syserr.errcode.modifiers (22.5.3.3) 525
- syserr.errcode.nonmembers (22.5.3.5) 525
- syserr.errcode.observers (22.5.3.4) 525
- syserr.errcode.overview (22.5.3.1) 524
- syserr.errcondition (22.5.4) 526
- syserr.errcondition.constructors (22.5.4.2) 526
- syserr.errcondition.modifiers (22.5.4.3) 526
- syserr.errcondition.nonmembers (22.5.4.5) 527
- syserr.errcondition.observers (22.5.4.4) 527
- syserr.errcondition.overview (22.5.4.1) 526
- syserr.hash (22.5.6) 528
- syserr.syserr (22.5.7) 528
- syserr.syserr.members (22.5.7.2) 528
- syserr.syserr.overview (22.5.7.1) 528
- system_error.syn (22.5.1) 519
- temp (17) 344
- temp.alias (17.5.7) 374
- temp.arg (17.3) 350
- temp.arg.explicit (17.8.1) 402
- temp.arg.nontype (17.3.2) 353
- temp.arg.template (17.3.3) 354
- temp.arg.type (17.3.1) 352
- temp.class (17.5.1) 357
- temp.class.order (17.5.5.2) 368
- temp.class.spec (17.5.5) 366
- temp.class.spec.match (17.5.5.1) 367
- temp.class.spec.mfunc (17.5.5.3) 369
- temp.decls (17.5) 357
- temp.deduct (17.8.2) 405
- temp.deduct.call (17.8.2.1) 409
- temp.deduct.conv (17.8.2.3) 412
- temp.deduct.decl (17.8.2.6) 421
- temp.deduct.funcaddr (17.8.2.2) 412
- temp.deduct.guide (17.9) 423
- temp.deduct.partial (17.8.2.4) 413
- temp.deduct.type (17.8.2.5) 415
- temp.dep (17.6.2) 381
- temp.dep.candidate (17.6.4.2) 389
- temp.dep.constexpr (17.6.2.3) 387
- temp.dep.expr (17.6.2.2) 385
- temp.dep.res (17.6.4) 388
- temp.dep.temp (17.6.2.4) 387
- temp.dep.type (17.6.2.1) 382
- temp.expl.spec (17.7.3) 397
- temp.explicit (17.7.2) 394
- temp.fct (17.5.6) 370
- temp.fct.spec (17.8) 402
- temp.friend (17.5.4) 364
- temp.func.order (17.5.6.2) 372
- temp.inject (17.6.5) 389
- temp.inst (17.7.1) 391
- temp.local (17.6.1) 379
- temp.mem (17.5.2) 359
- temp.mem.class (17.5.1.2) 358
- temp.mem.enum (17.5.1.4) 359
- temp.mem.func (17.5.1.1) 358
- temp.names (17.2) 349
- temp.nondep (17.6.3) 388
- temp.over (17.8.3) 422
- temp.over.link (17.5.6.1) 370
- temp.param (17.1) 345
- temp.point (17.6.4.1) 388
- temp.res (17.6) 375
- temp.spec (17.7) 390
- temp.static (17.5.1.3) 359
- temp.type (17.4) 356
- temp.variadic (17.5.3) 361
- template.bitset (23.9.2) 588
- template.gslice.array (29.7.7) 1121
- template.gslice.array.overview (29.7.7.1) 1121
- template.indirect.array (29.7.9) 1124
- template.indirect.array.overview (29.7.9.1) 1124
- template.mask.array (29.7.8) 1122
- template.mask.array.overview (29.7.8.1) 1122
- template.slice.array (29.7.5) 1118
- template.slice.array.overview (29.7.5.1) 1118
- template.valarray (29.7.2) 1108
- template.valarray.overview (29.7.2.1) 1108
- terminate (21.8.4.4) 507
- terminate.handler (21.8.4.1) 506
- thread (33) 1359
- thread.condition (33.5) 1388
- thread.condition.condvar (33.5.3) 1389
- thread.condition.condvarany (33.5.4) 1393
- thread.condition.nonmember (33.5.2) 1389

- thread.decaycopy (33.2.6) 1362
- thread.general (33.1) 1359
- thread.lock (33.4.4) 1376
- thread.lock.algorithm (33.4.5) 1386
- thread.lock.guard (33.4.4.1) 1376
- thread.lock.scoped (33.4.4.2) 1377
- thread.lock.shared (33.4.4.4) 1382
- thread.lock.shared.cons (33.4.4.4.1) 1383
- thread.lock.shared.locking (33.4.4.4.2) 1384
- thread.lock.shared.mod (33.4.4.4.3) 1386
- thread.lock.shared.obs (33.4.4.4.4) 1386
- thread.lock.unique (33.4.4.3) 1378
- thread.lock.unique.cons (33.4.4.3.1) 1379
- thread.lock.unique.locking (33.4.4.3.2) 1380
- thread.lock.unique.mod (33.4.4.3.3) 1382
- thread.lock.unique.obs (33.4.4.3.4) 1382
- thread.mutex (33.4) 1367
- thread.mutex.class (33.4.3.2.1) 1369
- thread.mutex.recursive (33.4.3.2.2) 1370
- thread.mutex.requirements (33.4.3) 1368
- thread.mutex.requirements.general (33.4.3.1) 1368
- thread.mutex.requirements.mutex (33.4.3.2) 1368
- thread.once (33.4.6) 1387
- thread.once.callonce (33.4.6.2) 1387
- thread.once.onceflag (33.4.6.1) 1387
- thread.req (33.2) 1359
- thread.req.exception (33.2.2) 1359
- thread.req.lockable (33.2.5) 1360
- thread.req.lockable.basic (33.2.5.2) 1361
- thread.req.lockable.general (33.2.5.1) 1360
- thread.req.lockable.req (33.2.5.3) 1361
- thread.req.lockable.timed (33.2.5.4) 1361
- thread.req.native (33.2.3) 1359
- thread.req.paramname (33.2.1) 1359
- thread.req.timing (33.2.4) 1360
- thread.sharedmutex.class (33.4.3.4.1) 1374
- thread.sharedmutex.requirements (33.4.3.4) 1373
- thread.sharedtimedmutex.class (33.4.3.5.1) 1375
- thread.sharedtimedmutex.requirements (33.4.3.5) 1374
- thread.syn (33.3.1) 1362
- thread.thread.algorithm (33.3.2.7) 1366
- thread.thread.assign (33.3.2.4) 1365
- thread.thread.class (33.3.2) 1362
- thread.thread.constr (33.3.2.2) 1364
- thread.thread.destr (33.3.2.3) 1365
- thread.thread.id (33.3.2.1) 1363
- thread.thread.member (33.3.2.5) 1365
- thread.thread.static (33.3.2.6) 1366
- thread.thread.this (33.3.3) 1366
- thread.threads (33.3) 1362
- thread.timedmutex.class (33.4.3.3.1) 1371
- thread.timedmutex.recursive (33.4.3.3.2) 1372
- thread.timedmutex.requirements (33.4.3.3) 1370
- time (23.17) 705
- time.clock (23.17.7) 720
- time.clock.hires (23.17.7.3) 721
- time.clock.req (23.17.3) 708
- time.clock.steady (23.17.7.2) 721
- time.clock.system (23.17.7.1) 720
- time.duration (23.17.5) 710
- time.duration.alg (23.17.5.9) 717
- time.duration.arithmetic (23.17.5.3) 712
- time.duration.cast (23.17.5.7) 715
- time.duration.comparisons (23.17.5.6) 715
- time.duration.cons (23.17.5.1) 712
- time.duration.literals (23.17.5.8) 716
- time.duration.nonmember (23.17.5.5) 713
- time.duration.observer (23.17.5.2) 712
- time.duration.special (23.17.5.4) 713
- time.general (23.17.1) 705
- time.point (23.17.6) 717
- time.point.arithmetic (23.17.6.3) 718
- time.point.cast (23.17.6.7) 719
- time.point.comparisons (23.17.6.6) 719
- time.point.cons (23.17.6.1) 718
- time.point.nonmember (23.17.6.5) 718
- time.point.observer (23.17.6.2) 718
- time.point.special (23.17.6.4) 718
- time.syn (23.17.2) 705
- time.traits (23.17.4) 709
- time.traits.duration_values (23.17.4.2) 709
- time.traits.is_fp (23.17.4.1) 709
- time.traits.specializations (23.17.4.3) 710
- transform.exclusive.scan (29.8.9) 1135
- transform.inclusive.scan (29.8.10) 1136
- transform.reduce (29.8.5) 1131
- tuple (23.5) 543
- tuple.apply (23.5.3.5) 551
- tuple.assign (23.5.3.2) 549
- tuple.cnstr (23.5.3.1) 546
- tuple.creation (23.5.3.4) 550
- tuple.elem (23.5.3.7) 552
- tuple.general (23.5.1) 543
- tuple.helper (23.5.3.6) 551
- tuple.rel (23.5.3.8) 553
- tuple.special (23.5.3.10) 554
- tuple.swap (23.5.3.3) 550
- tuple.syn (23.5.2) 543
- tuple.traits (23.5.3.9) 554
- tuple.tuple (23.5.3) 545

- type.descriptions (20.4.2.1) 453
- type.descriptions.general (20.4.2.1.1) 453
- type.index (23.18) 722
- type.index.hash (23.18.4) 723
- type.index.members (23.18.3) 722
- type.index.overview (23.18.2) 722
- type.index.synopsis (23.18.1) 722
- type.info (21.7.2) 503
- typeinfo.syn (21.7.1) 502
- uncaught.exceptions (21.8.5) 507
- underflow.error (22.2.10) 516
- uninitialized.construct.default (23.10.10.2) 606
- uninitialized.construct.value (23.10.10.3) 606
- uninitialized.copy (23.10.10.4) 607
- uninitialized.fill (23.10.10.6) 608
- uninitialized.move (23.10.10.5) 607
- unique.ptr (23.11.1) 609
- unique.ptr.create (23.11.1.4) 618
- unique.ptr.dltr (23.11.1.1) 610
- unique.ptr.dltr.dflt (23.11.1.1.2) 611
- unique.ptr.dltr.dflt1 (23.11.1.1.3) 611
- unique.ptr.dltr.general (23.11.1.1.1) 610
- unique.ptr.runtime (23.11.1.3) 616
- unique.ptr.runtime.asgn (23.11.1.3.2) 617
- unique.ptr.runtime.ctor (23.11.1.3.1) 617
- unique.ptr.runtime.modifiers (23.11.1.3.4) 618
- unique.ptr.runtime.observers (23.11.1.3.3) 618
- unique.ptr.single (23.11.1.2) 611
- unique.ptr.single.asgn (23.11.1.2.3) 614
- unique.ptr.single.ctor (23.11.1.2.1) 612
- unique.ptr.single.dtor (23.11.1.2.2) 614
- unique.ptr.single.modifiers (23.11.1.2.5) 615
- unique.ptr.single.observers (23.11.1.2.4) 615
- unique.ptr.special (23.11.1.5) 618
- unord (26.5) 921
- unord.general (26.5.1) 921
- unord.hash (23.14.15) 676
- unord.map (26.5.4) 924
- unord.map.cnstr (26.5.4.2) 928
- unord.map.elem (26.5.4.3) 929
- unord.map.modifiers (26.5.4.4) 929
- unord.map.overview (26.5.4.1) 924
- unord.map.swap (26.5.4.5) 930
- unord.map.syn (26.5.2) 921
- unord.multimap (26.5.5) 931
- unord.multimap.cnstr (26.5.5.2) 935
- unord.multimap.modifiers (26.5.5.3) 935
- unord.multimap.overview (26.5.5.1) 931
- unord.multimap.swap (26.5.5.4) 936
- unord.multiset (26.5.7) 941
- unord.multiset.cnstr (26.5.7.2) 945
- unord.multiset.overview (26.5.7.1) 941
- unord.multiset.swap (26.5.7.3) 945
- unord.req (26.2.7) 856
- unord.req.except (26.2.7.1) 868
- unord.set (26.5.6) 936
- unord.set.cnstr (26.5.6.2) 940
- unord.set.overview (26.5.6.1) 936
- unord.set.swap (26.5.6.3) 940
- unord.set.syn (26.5.3) 922
- upper.bound (28.7.3.2) 1035
- using (20.5.2) 458
- using.headers (20.5.2.2) 459
- using.linkage (20.5.2.3) 459
- using.overview (20.5.2.1) 458
- usrlit.suffix (20.5.4.3.5) 471
- util.dynamic.safety (23.10.4) 600
- util.smartptr (23.11.2) 620
- util.smartptr.enab (23.11.2.5) 633
- util.smartptr.getdeleter (23.11.2.2.10) 629
- util.smartptr.hash (23.11.2.7) 635
- util.smartptr.ownerless (23.11.2.4) 632
- util.smartptr.shared (23.11.2.2) 620
- util.smartptr.shared.assign (23.11.2.2.3) 625
- util.smartptr.shared.atomic (23.11.2.6) 633
- util.smartptr.shared.cast (23.11.2.2.9) 628
- util.smartptr.shared.cmp (23.11.2.2.7) 627
- util.smartptr.shared.const (23.11.2.2.1) 623
- util.smartptr.shared.create (23.11.2.2.6) 627
- util.smartptr.shared.dest (23.11.2.2.2) 625
- util.smartptr.shared.io (23.11.2.2.11) 629
- util.smartptr.shared.mod (23.11.2.2.4) 625
- util.smartptr.shared.obs (23.11.2.2.5) 626
- util.smartptr.shared.spec (23.11.2.2.8) 628
- util.smartptr.weak (23.11.2.3) 629
- util.smartptr.weak.assign (23.11.2.3.3) 631
- util.smartptr.weak.bad (23.11.2.1) 620
- util.smartptr.weak.const (23.11.2.3.1) 630
- util.smartptr.weak.dest (23.11.2.3.2) 631
- util.smartptr.weak.mod (23.11.2.3.4) 631
- util.smartptr.weak.obs (23.11.2.3.5) 631
- util.smartptr.weak.spec (23.11.2.3.6) 632
- utilities (23) 530
- utilities.general (23.1) 530
- utility (23.2) 530
- utility.arg.requirements (20.5.3.1) 460
- utility.as_const (23.2.6) 536
- utility.exchange (23.2.4) 535
- utility.from.chars (23.2.9) 537
- utility.requirements (20.5.3) 459
- utility.swap (23.2.3) 534

[utility.syn \(23.2.1\)](#) 530
[utility.to.chars \(23.2.8\)](#) 536

[valarray.access \(29.7.2.4\)](#) 1111
[valarray.assign \(29.7.2.3\)](#) 1110
[valarray.binary \(29.7.3.1\)](#) 1115
[valarray.cassign \(29.7.2.7\)](#) 1113
[valarray.comparison \(29.7.3.2\)](#) 1116
[valarray.cons \(29.7.2.2\)](#) 1109
[valarray.members \(29.7.2.8\)](#) 1114
[valarray.nonmembers \(29.7.3\)](#) 1115
[valarray.range \(29.7.10\)](#) 1125
[valarray.special \(29.7.3.4\)](#) 1117
[valarray.sub \(29.7.2.5\)](#) 1111
[valarray.syn \(29.7.1\)](#) 1105
[valarray.transcend \(29.7.3.3\)](#) 1117
[valarray.unary \(29.7.2.6\)](#) 1113
[value.error.codes \(20.5.5.14\)](#) 476
[variant \(23.7\)](#) 569
[variant.assign \(23.7.3.3\)](#) 575
[variant.bad.access \(23.7.11\)](#) 581
[variant.ctor \(23.7.3.1\)](#) 572
[variant.dtor \(23.7.3.2\)](#) 575
[variant.general \(23.7.1\)](#) 569
[variant.get \(23.7.5\)](#) 578
[variant.hash \(23.7.12\)](#) 581
[variant.helper \(23.7.4\)](#) 578
[variant.mod \(23.7.3.4\)](#) 576
[variant.monostate \(23.7.8\)](#) 581
[variant.monostate.relops \(23.7.9\)](#) 581
[variant.relops \(23.7.6\)](#) 579
[variant.specalg \(23.7.10\)](#) 581
[variant.status \(23.7.3.5\)](#) 577
[variant.swap \(23.7.3.6\)](#) 577
[variant.syn \(23.7.2\)](#) 569
[variant.traits \(23.7.13\)](#) 582
[variant.variant \(23.7.3\)](#) 571
[variant.visit \(23.7.7\)](#) 580
[vector \(26.3.11\)](#) 892
[vector.bool \(26.3.12\)](#) 897
[vector.capacity \(26.3.11.3\)](#) 895
[vector.cons \(26.3.11.2\)](#) 895
[vector.data \(26.3.11.4\)](#) 897
[vector.modifiers \(26.3.11.5\)](#) 897
[vector.overview \(26.3.11.1\)](#) 892
[vector.special \(26.3.11.6\)](#) 897
[vector.syn \(26.3.6\)](#) 871

[wide.stream.objects \(30.4.4\)](#) 1162

[zombie.names \(20.5.4.3.1\)](#) 470

Cross references from ISO C++ 2014

All section labels from ISO C++ 2014 (ISO/IEC 14882:2014, *Programming Language — C++*) are present in this document, with the exceptions described below.

atomics.types.operations.arith <i>see</i>	depr.lib.binders <i>removed</i>
atomics.types.int	depr.member.pointer.adaptors <i>removed</i>
atomics.types.operations.general <i>see</i>	depr.register <i>removed</i>
atomics.types.operations	
atomics.types.operations.pointer <i>see</i>	except.unexpected <i>removed</i>
atomics.types.pointer	exception.unexpected <i>removed</i>
atomics.types.operations.req <i>see</i>	expr.prim.general <i>see</i> expr.prim
atomics.types.operations	
atomics.types.operations.templ <i>see</i>	fstreams <i>see</i> fstream.syn
atomics.types.operations	
auto.ptr <i>removed</i>	get.unexpected <i>removed</i>
auto.ptr.cons <i>removed</i>	global.names <i>see</i> lex.name
auto.ptr.conv <i>removed</i>	
auto.ptr.members <i>removed</i>	
	iostream.format.overview <i>see</i> istream.syn ,
basic.start.init <i>see</i> basic.start.static ,	ostream.syn , iomanip.syn
basic.start.dynamic	iostreams.base.overview <i>see</i> ios.syn
bind <i>see</i> func.bind	istream::extractors <i>see</i> istream.extractors
	istreambuf.iterator::equal <i>see</i>
c.limits <i>see</i> climits.syn	istreambuf.iterator.ops
ccmplx <i>see</i> depr.ccomplex.syn	istreambuf.iterator::op!= <i>see</i>
charname <i>see</i> lex.name	istreambuf.iterator.ops
charname.allowed <i>see</i> Table 2	istreambuf.iterator::op* <i>see</i>
charname.disallowed <i>see</i> Table 3	istreambuf.iterator.ops
class.inhctor <i>see</i> class.inhctor.init ,	istreambuf.iterator::op++ <i>see</i>
namespace.udecl	istreambuf.iterator.ops
conversions.buffer <i>see</i> depr.conversions.buffer	istreambuf.iterator::op== <i>see</i>
conversions.string <i>see</i> depr.conversions.string	istreambuf.iterator.ops
	istreambuf.iterator::proxy <i>see</i>
date.time <i>see</i> ctime.syn	istreambuf.iterator.proxy
defs.additional <i>see</i> definitions	iterator.basic <i>see</i> depr.iterator.basic
depr.adaptors <i>removed</i>	
depr.alg.random.shuffle <i>removed</i>	lex.trigraph <i>removed</i>
depr.auto.ptr <i>removed</i>	limits <i>see</i> support.limits
depr.base <i>removed</i>	limits.numeric <i>see</i> support.limits.general ,
depr.function.objects <i>removed</i>	limits.syn
depr.function.pointer.adaptors <i>removed</i>	locale.stdcvrt <i>see</i> depr.locale.stdcvrt
depr.incr.bool <i>removed</i>	
depr.ios.members <i>removed</i>	negators <i>see</i> depr.negators
depr.lib.bind.1st <i>removed</i>	
depr.lib.bind.2nd <i>removed</i>	set.unexpected <i>removed</i>
depr.lib.binder.1st <i>removed</i>	storage.iterator <i>see</i> depr.storage.iterator
depr.lib.binder.2nd <i>removed</i>	stream.buffers.overview <i>see</i> streambuf.syn
	string.streams.overview <i>see</i> sstream.syn

`string::append` *see* [string.append](#)
`string::assign` *see* [string.assign](#)
`string::compare` *see* [string.compare](#)
`string::copy` *see* [string.copy](#)
`string::erase` *see* [string.erase](#)
`string::find` *see* [string.find](#)
`string::find.first.not.of` *see* [string.find.first.not.of](#)
`string::find.first.of` *see* [string.find.first.of](#)
`string::find.last.not.of` *see* [string.find.last.not.of](#)
`string::find.last.of` *see* [string.find.last.of](#)
`string::insert` *see* [string.insert](#)
`string::op!=` *see* [string.op!=](#)
`string::op+` *see* [string.op+](#)
`string::op+=` *see* [string.op+=](#)
`string::op<` *see* [string.op<](#)
`string::op<=` *see* [string.op<=](#)
`string::op>` *see* [string.op>](#)
`string::op>=` *see* [string.op>=](#)
`string::operator==` *see* [string.operator==](#)
`string::replace` *see* [string.replace](#)
`string::rfind` *see* [string.rfind](#)
`string::substr` *see* [string.substr](#)
`string::swap` *see* [string.swap](#)

`temporary.buffer` *see* [depr.temporary.buffer](#)

`uncaught` *see* [depr.uncaught](#)
`unexpected` *removed*
`unexpected.handler` *removed*
`uninitialized.fill.n` *see* [uninitialized.fill](#)
`util.smartptr.weakptr` *see* [util.smartptr.weak.bad](#)

Index

- !, *see* operator, logical negation
- !=, *see* operator, inequality
- (), *see* operator, function call, *see* declarator, function
- *, *see* operator, indirection, *see* operator, multiplication, *see* declarator, pointer
- +, *see* operator, unary plus, *see* operator, addition
- ++, *see* operator, increment
- ,, *see* operator, comma
- , *see* operator, unary minus, *see* operator, subtraction
- >, *see* operator, class member access
- >*, *see* operator, pointer to member
- , *see* operator, decrement
- ., *see* operator, class member access
- .*, *see* operator, pointer to member
- ..., *see* ellipsis
- /, *see* operator, division
- :
 - bit-field declaration, 249
 - label specifier, 145
- ::, *see* operator, scope resolution
- ::*, *see* declarator, pointer to member
- <, *see* operator, less than
 - template and, 348, 349
- <<, *see* operator, left shift
- <=, *see* operator, less than or equal to
- =, *see* assignment operator
- ==, *see* operator, equality
- >, *see* operator, greater than
- >=, *see* operator, greater than or equal to
- >>, *see* operator, right shift
- ?:, *see* operator, conditional expression
- [], *see* operator, subscripting, *see* declarator, array
- # operator, 439, 440
- ## operator, 440
- #define, 439
- #elif, 436
- #else, 437
- #endif, 437
- #error, *see* preprocessing directives, error
- #if, 436, 474
- #ifdef, 437
- #ifndef, 437
- #include, 437, 459
- #line, *see* preprocessing directives, line control
- #pragma, *see* preprocessing directives, pragma
- #undef, 441, 471
- %, *see* operator, remainder
- &, *see* operator, address-of, *see* operator, bitwise
 - AND, *see* declarator, reference
- &&, *see* operator, logical AND
- ^, *see* operator, bitwise exclusive OR
- \, *see* backslash character
- { }
 - block statement, 145
 - class declaration, 237
 - class definition, 237
 - enum declaration, 174
 - initializer list, 224
- _, *see* character, underscore
- __cplusplus, 444
- __DATE__, 444
- __FILE__, 444
- __has_include, 436
- __LINE__, 445
- __STDCPP_DEFAULT_NEW_ALIGNMENT__, 445
- __STDCPP_STRICT_POINTER_SAFETY__, 445
- __STDCPP_THREADS__, 445
- __STDC_HOSTED__, 445
- __STDC_ISO_10646__, 445
- __STDC_MB_MIGHT_NEQ_WC__, 445
- __STDC_VERSION__, 445
- __STDC__, 445
- __TIME__, 445
- __VA_ARGS__, 439
- |, *see* operator, bitwise inclusive OR
- ||, *see* operator, logical OR
- ~, *see* operator, ones' complement, *see* destructor
- 0, *see also* zero, null
 - null character, *see* character, null
 - string terminator, 36
- abort, 70, 151
- abstract-declarator, 202, 1427
- abstract-pack-declarator, 202, 1427
- access, 3
- access control, 269–279
 - anonymous union, 253

- base class, 271
- base class member, 256
- class member, 112
- default, 269
- default argument, 270
- friend function, 274
- member function and, 280
- member name, 269
- multiple access, 278
- nested class, 278
- overload resolution and, 260
- overloading and, 314
- private**, 269
- protected**, 269, 277
- public**, 269
- union** default member, 238
- using-declaration and, 187
- virtual function, 278
- access specifier, 270, 271
- access-specifier*, 256, 1430
- active
 - union member, 251
- addition operator, *see* operator, addition
- additive-expression*, 131, 1420
- address, 81, 134
- aggregate, 224
 - elements, 224
- aggregate initialization, 224
- algorithm
 - stable, 450, 475
- <algorithm>**, 989
- alias
 - namespace, 182
- alias template, 374
- alias-declaration*, 155, 1423
- alignment, 84
 - extended, 85
 - fundamental, 85
 - new-extended, 85
 - stricter, 85
 - stronger, 85
 - weaker, 85
- alignment requirement
 - implementation-defined, 84
- alignment-specifier*, 194, 1426
- allocation
 - alignment storage, 125
 - implementation-defined bit-field, 249
 - unspecified, 243
- allocation functions, 71
- alternative token, *see* token, alternative
- ambiguity
 - base class member, 259
 - class conversion, 261
 - declaration type, 157
 - declaration versus cast, 203
 - declaration versus expression, 152
 - function declaration, 222
 - member access, 259
 - overloaded function, 314
 - parentheses and, 123
- Amendment 1, 471
- and-expression*, 135, 1420
- anonymous union, 253
- anonymous union object, 253
- <any>**, 582
- appertain, 195
- argc**, 66
- argument, 3, 473, 474, 515
 - access checking and default, 270
 - binding of default, 214
 - evaluation of default, 214, 215
 - example of default, 213, 214
 - function call expression, 3
 - function-like macro, 3
 - overloaded operator and default, 337
 - reference, 111
 - scope of default, 215
 - template, 350
 - template instantiation, 3
 - throw expression, 3
 - type checking of default, 214
- argument and name hiding
 - default, 215
- argument and virtual function
 - default, 216
- argument list
 - empty, 210
 - variable, 210
- argument passing, 111
 - reference and, 229
- argument substitution, *see* macro, argument substitution
- argument type
 - unknown, 210
- argv**, 66
- arithmetic
 - pointer, 132
 - unsigned**, 80
- array
 - bound, 208
 - const**, 82

- delete, 127
- handler of type, 427
- multidimensional, 209
- new, 123
- overloading and pointer versus, 312
- parameter of type, 211
- sizeof, 122
- storage of, 209
- template parameter of type, 347
- <array>, 868
- array
 - as aggregate, 871
 - contiguous storage, 871
 - initialization, 871, 873
 - tuple interface to, 874
 - zero sized, 873
- array size
 - default, 209
- arrow operator, *see* operator, class member access
- as-if rule, 11
- asm
 - implementation-defined, 191
- asm-definition*, 191, 1425
- assembler, 191
- <assert.h>, 459, 517
- assignment
 - and lvalue, 138
 - conversion by, 138
 - copy, *see* assignment operator, copy
 - move, *see* assignment operator, move, 449
 - reference, 229
- assignment operator
 - copy, 280, 305–308
 - hidden, 307
 - implicitly declared, 306
 - implicitly defined, 307
 - inaccessible, 303
 - non-trivial, 307
 - trivial, 307
 - virtual bases and, 308
 - move, 280, 305–308
 - hidden, 307
 - implicitly declared, 306
 - implicitly defined, 307
 - inaccessible, 303
 - non-trivial, 307
 - trivial, 307
 - overloaded, 338
- assignment-expression*, 138, 1421
- assignment-operator*, 138, 1421
- associative containers
 - exception safety, 856
 - requirements, 856
 - unordered, *see* unordered associative containers
- asynchronous provider, 1398
- asynchronous return object, 1398
- at least as specialized as, *see* more specialized
- atexit, 69
- <atomic>, 1342
- atomic operations, *see* operation, atomic
- attribute, 194–198
 - alignment, 196
 - carries dependency, 197
 - deprecated, 198
 - fallthrough, 198
 - maybe unused, 199
 - nodiscard, 199
 - noreturn, 200
 - syntax and semantics, 194
- attribute*, 194, 1426
- attribute-argument-clause*, 195, 1426
- attribute-declaration*, 155, 1423
- attribute-list*, 194, 1426
- attribute-namespace*, 195, 1426
- attribute-scoped-token*, 195, 1426
- attribute-specifier*, 194, 1426
- attribute-specifier-seq*, 194, 1426
- attribute-token*, 195, 1426
- attribute-using-prefix*, 194, 1426
- automatic storage duration, 71
- awk, 1307
- backslash character, 32
- bad_alloc, 126
- bad_cast, 114
- bad_typeid, 115
- balanced-token*, 195, 1426
- balanced-token-seq*, 195, 1426
- base characteristic, 676
- base class, 256, 257
 - dependent, 383
 - direct, 256
 - indirect, 256
 - non-virtual, 258
 - overloading and, 313
 - private, 271
 - protected, 271
 - public, 271
 - virtual, 258
- base class subobject, 9
- base-clause*, 256, 1429

- base-specifier*, 256, 1429
- base-specifier-list*, 256, 1429
- begin**
 - unordered associative containers, 866
- behavior**
 - conditionally-supported, 3, 7
 - default, 449, 453
 - implementation-defined, 4, 11
 - locale-specific, 4
 - observable, 11, 12
 - on receipt of signal, 15
 - required, 450, 453
 - undefined, 5, 7, 11, 983
 - unspecified, 5, 11
- Ben**, 314
- Bernoulli distributions**, 1087–1090
- bernoulli_distribution**
 - discrete probability function, 1087
- Bessel functions**
 - I_ν , 1152
 - J_ν , 1152
 - K_ν , 1152
 - N_ν , 1153
 - j_n , 1155
 - n_n , 1156
- beta functions B**, 1151
- binary fold**, 108
- binary left fold**, 108
- binary operator**
 - interpretation of, 337
 - overloaded, 337
- binary right fold**, 108
- binary-digit*, 29, 1414
- binary-exponent-part*, 33, 1416
- binary-literal*, 29, 1414
- BinaryTypeTrait**, 677
- bind directly**, 231
- binding**
 - reference, 229
- binomial_distribution**
 - discrete probability function, 1088
- bit-field**, 249
 - address of, 250
 - alignment of, 249
 - implementation-defined alignment of, 249
 - implementation-defined sign of, 1443
 - type of, 250
 - unnamed, 249
 - zero width of, 249
- bitmask**
 - empty, 454
- <bitset>**, 587
- block**, 3
 - initialization in, 152
- block scope**, 46
- block statement**, *see* statement, compound
- block structure**, 152
- block with forward progress guarantee delegation**, 20
- block-declaration*, 155, 1422
- body**
 - function, 216
- Bond**
 - James Bond, 105
- Boolean**, 250
- Boolean literal**, 36
- boolean literal**, *see* literal, boolean
- Boolean type**, 80
- boolean-literal*, 36, 1417
- bound arguments**, 668
- bound**, of array, 208
- brace-or-equal-initializer*, 220, 1428
- braced-init-list*, 220, 1428
- brains**
 - names that want to eat your, 470
- bucket**
 - unordered associative containers, 866
- bucket_count**
 - unordered associative containers, 866
- bucket_size**
 - unordered associative containers, 866
- buckets**, 857
- byte**, 8, 121
- C**
 - linkage to, 192
 - standard, 1
 - standard library, 2
- c-char*, 31, 1415
- c-char-sequence*, 31, 1415
- call**
 - operator function, 337
 - pseudo destructor, 112
- call signature**, 655
- call wrapper**, 655, 656
 - forwarding, 656
 - simple, 656
 - type, 655
- callable object**, 655
- callable type**, 655, 670
- capture**
 - implicit, 104

- capture*, 103, 1418
- capture-default*, 103, 1418
- capture-list*, 103, 1418
- captured, 105
 - by copy, 106
 - by reference, 106
- carries a dependency, 16
- carry
 - `subtract_with_carry_engine`, 1076
- `<cassert>`, 459, 517, 829
- cast
 - base class, 117
 - const, 119, 129
 - derived class, 117
 - dynamic, 113, 504
 - construction and, 302
 - destruction and, 302
 - integer to pointer, 118
 - lvalue, 115, 117
 - pointer to integer, 117
 - pointer-to-function, 118
 - pointer-to-member, 117, 118
 - reference, 115, 118
 - reinterpret, 117, 129
 - integer to pointer, 118
 - lvalue, 117
 - pointer to integer, 117
 - pointer-to-function, 118
 - pointer-to-member, 118
 - reference, 118
 - static, 115, 129
 - lvalue, 115
 - reference, 115
 - undefined pointer-to-function, 118
- cast-expression*, 129, 1420
- casting, 111
- casting away constness, 119
- `catch`, 424
- cats
 - interfering with canines, 502
- `cauchy_distribution`
 - probability density function, 1097
- `cbegin`
 - unordered associative containers, 867
- `<ccomplex>`, 1457
- `<cctype>`, 776
- `cend`
 - unordered associative containers, 867
- `<cerrno>`, 471, 517
- `<cfenv>`, 1051
- char
 - implementation-defined sign of, 79
- char-like object, 726
- char-like type, 726
- `char16_t`, *see* type, `char16_t`
- `char16_t` character, 32
- `char32_t`, *see* type, `char32_t`
- `char32_t` character, 32
- `char_class_type`
 - regular expression traits, 1298
- character, 448
 - decimal-point, 455
 - multibyte, 4
 - null, 24
 - signed, 79
 - source file, 22
 - underscore, 28
 - in identifier, 28
- character literal, *see* literal, character
- character set, 23–24
 - basic execution, 8, 24
 - basic source, 22, 23
 - execution, 24
- character string, 35
- character string literal, 440
- character-literal*, 31, 1415
- checking
 - point of error, 376
 - syntax, 376
- `chi_squared_distribution`
 - probability density function, 1096
- `<chrono>`, 705
- chunks, 641
- `<cinttypes>`, 1294, 1295
- class, 81, 237–251
 - abstract, 266
 - associated, 54
 - base, 471, 476
 - cast to incomplete, 130
 - constructor and abstract, 267
 - definition, 41
 - derived, 476
 - linkage of, 64
 - linkage specification, 192
 - local, *see* local class
 - member function, *see* member function, class
 - nested, *see* nested class
 - pointer to abstract, 267
 - polymorphic, 262
 - scope of enumerator, 177
 - standard-layout, 238
 - trivial, 238

- trivially copyable, 238
- union-like, 254
- unnamed, 161
- variant member of, 254
- class name
 - elaborated, 170, 240, 241
 - point of declaration, 241
 - scope of, 240
 - typedef**, 161, 241
- class object
 - assignment to, 138
 - member, 243
 - sizeof**, 121
- class object copy, *see* constructor, copy
- class object initialization, *see* constructor
- class-head*, 237, 1428
- class-head-name*, 237, 1428
- class-key*, 237, 1429
- class-name*, 237, 1428
- class-or-decltype*, 256, 1429
- class-specifier*, 237, 1428
- class-virt-specifier*, 237, 1429
- clear**
 - unordered associative containers, 865
- <climits>**, 1464
- <locale>**, 455
- closure object, 99
- closure type, 99
- <cmath>**, 1139, 1149
- <codecvt>**, 1479
- collating element, 1297
- comma operator, *see* operator, comma
- comment, 24, 26
 - /* */*, 26
 - //*, 26
- common initial sequence, 244
- comparison
 - pointer, 134
 - pointer to function, 134
 - undefined pointer, 132
- compatible with
 - shared_ptr**, 623
- compilation
 - separate, 22
- compiler control line, *see* preprocessing directives
- complete object, 9
- complete object of, 10
- completely defined, 242
- <complex>**, 1052, 1053
- <complex.h>**, 1457
- component, 448
- composite pointer type, 95
- compound-statement*, 145, 1421
- concatenation
 - macro argument, *see* **##** operator
 - string, 36
- concurrent forward progress guarantees, 19
- condition*, 144, 1421
- conditions*
 - rules for, 144
- <condition_variable>**, 1388
- conditional-expression
 - throw-expression in, 136
- conditional-expression*, 136, 1421
- conditionally-supported behavior, *see* behavior,
 - conditionally-supported
- conditionally-supported-directive*, 435, 1432
- conflict, 15
- conformance requirements, 7, 11
 - class templates, 7
 - classes, 7
 - general, 7
 - library, 7
 - method of description, 7
- consistency
 - linkage, 158
 - linkage specification, 193
 - type declaration, 66
- const**, 82
 - cast away, 119
 - constructor and, 247, 281
 - destructor and, 247, 289
 - linkage of, 63
 - overloading and, 313
- const-object**
 - undefined change to, 166
- const-default-constructible**, 221
- const-qualified**, 82
- const-volatile-qualified**, 82
- const_cast**, *see* cast, const
- const_local_iterator**, 858
 - unordered associative containers, 858
- constant, 29, 96
 - enumeration, 175
 - null pointer, 90
- constant expression, 139
 - permitted result of, 142
- constant initialization, 67
- constant initializer, 67
- constant iterator, 955
- constant subexpression, 449
- constant-expression*, 139, 1421

- constexpr function, 162
- constexpr if, 146
- constituent expression, 12
- construction, 300–303
 - dynamic cast and, 302
 - member access, 300
 - move, 449
 - pointer to member or base, 301
 - typeid** operator, 302
 - virtual function call, 301
- constructor, 280
 - address of, 282
 - array of class objects and, 293
 - converting, 286
 - copy, 280, 284, 303–305, 455
 - elision, 308
 - implicitly declared, 304
 - implicitly defined, 305
 - inaccessible, 303
 - nontrivial, 305
 - trivial, 305
 - default, 280, 281
 - non-trivial, 281
 - trivial, 281
 - exception handling, *see* exception handling,
 - constructors and destructors
 - explicit call, 282
 - implicitly called, 282
 - implicitly defined, 282
 - inheritance of, 281
 - move, 280, 303–305
 - elision, 308
 - implicitly declared, 304
 - implicitly defined, 305
 - inaccessible, 303
 - non-trivial, 305
 - trivial, 305
 - non-trivial, 281
 - random number distribution requirement, 1069
 - random number engine requirement, 1065
 - union**, 252
- constructor, conversion by, *see* conversion,
 - user-defined
- contained value
 - any**, 583
 - optional**, 557
 - variant**, 572
- container
 - contiguous, 834
- contains a value
 - optional**, 557
- context
 - non-deduced, 415
- contextually converted constant expression of type
 - bool**, *see* conversion, contextual
- contextually converted to **bool**, *see* conversion,
 - contextual
- contextually implicitly converted, 86
- contiguous container, 834
- contiguous iterators, 956
- continue**
 - and handler, 424
 - and try block, 424
- control line, *see* preprocessing directives
- control-line*, 434, 1432
- conventions, 453
 - lexical, 22–38
- conversion
 - argument, 210
 - array-to-pointer, 87
 - bool**, 90
 - boolean, 91
 - class, 285
 - contextual, 86
 - contextual to **bool**, 86
 - contextual to constant expression of type
 - bool**, 142
 - deduced return type of user-defined, 288
 - derived-to-base, 327
 - floating to integral, 90
 - floating-point, 90
 - function pointer, 91
 - function-to-pointer, 88
 - implementation-defined pointer integer, 117, 118
 - implicit, 86, 285
 - implicit user-defined, 285
 - inheritance of user-defined, 288
 - integer rank, 91
 - integral, 89
 - integral to floating, 90
 - lvalue-to-rvalue, 87, 1439
 - narrowing, 235
 - overload resolution and, 324
 - overload resolution and pointer, 336
 - pointer, 90
 - pointer to member, 90
 - void***, 91
 - qualification, 88–89
 - return type, 151
 - standard, 86–92

- temporary materialization, 88
- to signed, 90
- to unsigned, 89
- type of, 287
- user-defined, 285–287
- usual arithmetic, 94
- virtual user-defined, 288
- conversion explicit type, *see* casting
- conversion function, *see* conversion, user-defined, 287
- conversion rank, 328
- conversion-declarator*, 287, 1430
- conversion-function-id*, 287, 1430
- conversion-type-id*, 287, 1430
- copy
 - class object, *see* constructor, copy, *see* assignment operator, copy
- copy constructor
 - random number engine requirement, 1065
- copy deduction candidate, 322
- copy elision, *see* constructor, copy, elision
- copy-initialization, 223
- copy-list-initialization, 231
- CopyInsertable into X, 835
- count
 - unordered associative containers, 866
- `<csetjmp>`, 471, 510, 511
- `<csignal>`, 510, 511
- `<cstdarg>`, 210, 471, 510
- `<cstdbool>`, 510
- `<cstddef>`, 122, 132
- `<stdint>`, 492
- `<stdio>`, 1161, 1162, 1228, 1293, 1294
- `<stdlib>`, 70, 458, 479, 493, 510, 608, 780, 1049, 1105, 1149, 1461
- `<string>`, 455, 777, 1464, 1468
- `<tgmath>`, 1457
- `<time>`, 510, 721, 722, 783
- ctor-initializer*, 294, 1430
- `<ctype.h>`, 777
- `<cuchar>`, 471, 780
- current instantiation, 382
 - dependent member of the, 384
 - member of the, 383
- currently handled exception, *see* exception
 - handling, currently handled exception
- cv-decomposition, 88
- cv-qualification signature, 88
- cv-qualifier, 82
 - top-level, 82
- cv-qualifier*, 202, 1427
- cv-qualifier-seq*, 202, 1427
- `<cwchar>`, 471, 778, 780
- `<cwctype>`, 471, 777
- d-char*, 34, 1417
- d-char-sequence*, 34, 1416
- DAG
 - multiple inheritance, 259
 - non-virtual base class, 259
 - virtual base class, 259
- data member, *see* member, 242
 - static, 242
- data race, 18
- deadlock, 449
- deallocation function
 - usual, 72
- deallocation functions, 71
- decay
 - array, *see* conversion, array to pointer
 - function, *see* conversion, function to pointer
- DECAY_COPY*, 1362
- decimal-floating-literal*, 33, 1415
- decimal-literal*, 29, 1414
- decl-specifier*, 157, 1423
- decl-specifier-seq*, 157, 1423
- declaration, 39, 155–198
 - array, 208
 - asm, 191
 - bit-field, 249
 - class name, 40
 - constant pointer, 205
 - default argument, 213–216
 - definition versus, 39
 - ellipsis in function, 111, 210
 - enumerator point of, 46
 - extern, 40
 - extern reference, 229
 - forward, 159
 - forward class, 240
 - function, 39, 210
 - local class, 254
 - member, 241
 - multiple, 66
 - name, 39
 - opaque enum, 40
 - overloaded, 311
 - overloaded name and friend, 275
 - parameter, 40, 210
 - parentheses in, 203, 205
 - pointer, 205
 - reference, 206

- static member, 40
- storage class, 157
- structured binding, *see* structured binding
 - declaration
- type, 204
- typedef, 40
- typedef as type, 160
- declaration*, 155, 1422
- declaration hiding, *see* name hiding
- declaration-seq*, 155, 1422
- declaration-statement*, 152, 1422
- declarative region, 44
- declarator, 40, 156, 201–236
 - array, 208
 - function, 210–213
 - meaning of, 204–216
 - multidimensional array, 209
 - pointer, 205
 - pointer to member, 207
 - reference, 206
- declarator*, 201, 1426
- declarator-id*, 202, 1427
- decltype-specifier*, 167, 1424
- decrement operator
 - overloaded, *see* overloading, decrement
 - operator
- deduction
 - class template argument, 423
 - class template arguments, 111, 167, 174, 322
 - placeholder type, 173
- deduction-guide*, 423, 1431
- default access control, *see* access control, default
- default argument
 - overload resolution and, 323
- default argument instantiation, 394
- default constructor, *see* constructor, default
 - random number distribution requirement, 1069
 - seed sequence requirement, 1063
- default initializers
 - overloading and, 313
- default member initializer, 243
- default memory resource pointer, 641
- default-initialization, 221
- default-inserted, 835
- defaulted, 218
- `DefaultInsertable` into `X`, 835
- deferred function, 1407
- defined**, 435
- defined-macro-expression*, 435, 1433
- defining-type-id*, 202, 1427
- defining-type-specifier*, 165, 1423
- defining-type-specifier-seq*, 165, 1424
- definition, 39
 - alternate, 471
 - class, 237, 242
 - class name as type, 239
 - constructor, 216
 - declaration as, 157
 - function, 216–219
 - deleted, 218
 - explicitly-defaulted, 217
 - local class, 254
 - member function, 245
 - namespace, 178
 - nested class, 250
 - pure virtual function, 267
 - scope of class, 240
 - static member, 248
 - virtual function, 265
- definitions, 3–6
- delete**, 71, 127, 291
 - array, 127
 - destructor and, 128, 290
 - object, 127
 - operator**
 - replaceable, 472
 - overloading and, 72
 - type of, 292
 - undefined, 127
- delete-expression*, 127, 1420
- deleter, 609
- denormalized value, *see* number, subnormal
- dependency-ordered before, 16
- dependent base class, *see* base class, dependent
- dependent member of the current instantiation,
 - see* current instantiation, dependent
 - member of the
- dependent name, *see* name, dependent
- `<deque>`, 869
- dereferencing, *see also* indirection
- derivation, *see* inheritance
- derived class, 256–268
 - most, *see* most derived class
- derived object
 - most, *see* most derived object
- destruction, 300–303
 - dynamic cast and, 302
 - member access, 300
 - pointer to member or base, 301
 - `typeid` operator, 302
 - virtual function call, 301

- destructor, [288](#), [455](#)
 - default, [289](#)
 - exception handling, *see* exception handling,
 - constructors and destructors
 - explicit call, [290](#)
 - implicit call, [289](#)
 - implicitly defined, [289](#)
 - non-trivial, [289](#)
 - program termination and, [289](#)
 - pure virtual, [289](#)
 - union, [252](#)
 - virtual, [289](#)
- diagnosable rules, [7](#)
- diagnostic message, *see* message, diagnostic
- digit*, [27](#), [1413](#)
- digit-sequence*, [33](#), [1416](#)
- digraph, *see* token, alternative, [25](#)
- direct member, [242](#)
- direct-initialization, [223](#)
- direct-list-initialization, [231](#)
- direct-non-list-initialization, [449](#)
- directed acyclic graph, *see* DAG
- directive, preprocessing, *see* preprocessing
 - directives
- directory-separator*, [1250](#)
- discard
 - random number engine requirement, [1066](#)
- discard_block_engine
 - generation algorithm, [1078](#)
 - state, [1078](#)
 - textual representation, [1079](#)
 - transition algorithm, [1078](#)
- discarded statement, [146](#)
- discarded-value expression, [94](#)
- discrete probability function
 - bernoulli_distribution, [1087](#)
 - binomial_distribution, [1088](#)
 - discrete_distribution, [1100](#)
 - geometric_distribution, [1089](#)
 - negative_binomial_distribution, [1090](#)
 - poisson_distribution, [1091](#)
 - uniform_int_distribution, [1086](#)
- discrete_distribution
 - discrete probability function, [1100](#)
 - weights, [1100](#)
- distribution, *see* random number distribution
- dogs
 - obliviousness to interference, [502](#)
- domain error, [1150](#)
- dominance
 - virtual base class, [261](#)
- dot operator, *see* operator, class member access
- dynamic binding, *see* virtual function
- dynamic initialization, [67](#)
- dynamic type, *see* type, dynamic
- dynamic_cast, *see* cast, dynamic
- E (complete elliptic integrals), [1151](#)
- E (incomplete elliptic integrals), [1153](#)
- ECMA-262, [2](#)
- ECMAScript, [1307](#), [1339](#)
- egrep, [1307](#)
- Ei (exponential integrals), [1154](#)
- elaborated type specifier, *see* class name,
 - elaborated
- elaborated-type-specifier*, [170](#), [1424](#)
- element access functions, [1009](#)
- elif-group*, [434](#), [1432](#)
- elif-groups*, [434](#), [1432](#)
- elision
 - copy, *see* constructor, copy, elision
 - copy constructor, *see* constructor, copy,
 - elision
 - move constructor, *see* constructor, move,
 - elision
- ellipsis
 - conversion sequence, [111](#), [329](#)
 - overload resolution and, [323](#)
- elliptic integrals
 - complete Π , [1152](#)
 - complete E, [1151](#)
 - complete K, [1151](#)
 - incomplete Π , [1154](#)
 - incomplete E, [1153](#)
 - incomplete F, [1153](#)
- else-group*, [434](#), [1432](#)
- EmplaceConstructible into X from args, [835](#)
- empty future object, [1402](#)
- empty shared_future object, [1404](#)
- empty-declaration*, [155](#), [1423](#)
- enclosing-namespace-specifier*, [178](#), [1425](#)
- encoded character type, [1242](#)
- encoding
 - multibyte, [36](#)
- encoding-prefix*, [31](#), [1415](#)
- end
 - unordered associative containers, [866](#)
- end-of-file, [594](#)
- endif-line*, [435](#), [1432](#)
- engine, *see* random number engine
- engine adaptor, *see* random number engine
 - adaptor

- engines with predefined parameters
 - `default_random_engine`, 1082
 - `knuth_b`, 1082
 - `minstd_rand`, 1081
 - `minstd_rand0`, 1081
 - `mt19937`, 1081
 - `mt19937_64`, 1081
 - `ranlux24`, 1081
 - `ranlux24_base`, 1081
 - `ranlux48`, 1082
 - `ranlux48_base`, 1081
- entity, 39
 - templated, 345
- `enum`, 81
 - overloading and, 312
 - type of, 174, 176
 - underlying type, *see* type, underlying
- enum name
 - `typedef`, 161
- enum-base*, 175, 1425
- enum-head*, 174, 1424
- enum-head-name*, 174, 1424
- enum-key*, 175, 1424
- enum-name*, 174, 1424
- enum-specifier*, 174, 1424
- enumeration, 174, 175
 - linkage of, 64
 - scoped, 175
 - unscoped, 175
- enumeration scope, 49
- enumeration type
 - conversion to, 116
 - `static_cast`
 - conversion to, 116
- enumerator
 - definition, 41
 - value of, 175
- enumerator*, 175, 1425
- enumerator-definition*, 175, 1425
- enumerator-list*, 175, 1425
- environment
 - program, 66
- epoch, 708
- `equal_range`
 - unordered associative containers, 866
- equality-expression*, 133, 1420
- equivalence
 - template type, 356
 - type, 160, 239
- equivalent
 - expression, *see* expression, equivalent
- function template, *see* template, function, equivalent
- functionally
 - expression, *see* expression, functionally equivalent
 - function template, *see* template, function, functionally equivalent
- equivalent parameter declarations, 312
 - overloading and, 312
- equivalent-key group, 856
- equivalently-valued, 468
- Erasable from X, 835
- `erase`
 - unordered associative containers, 865
- `<errno.h>`, 517
- escape character, *see* backslash character
- escape sequence
 - undefined, 32
- escape-sequence*, 31, 1415
- Eulerian integral of the first kind, *see* `beta`
- evaluation, 14
 - order of argument, 110
 - signal-safe, 511
 - unspecified order of, 14, 68
 - unspecified order of argument, 110
 - unspecified order of function call, 110
- example
 - array, 209
 - class definition, 243
 - `const`, 205
 - constant pointer, 205
 - constructor, 282
 - constructor and initialization, 293
 - declaration, 40, 212
 - declarator, 203
 - definition, 40
 - `delete`, 292
 - derived class, 256
 - destructor and `delete`, 292
 - ellipsis, 210
 - enumeration, 176
 - explicit destructor call, 290
 - explicit qualification, 260
 - friend, 240
 - friend function, 274
 - function declaration, 211
 - function definition, 216
 - linkage consistency, 158
 - local class, 254
 - member function, 246, 274
 - nested class, 250

- nested class definition, 251, 278
- nested class forward declaration, 251
- nested type name, 251
- pointer to member, 207
- pure virtual function, 267
- scope of `delete`, 292
- scope resolution operator, 260
- static member, 248
- subscripting, 209
- type name, 203
- `typedef`, 160
- unnamed parameter, 216
- variable parameter list, 210
- virtual function, 264, 265
- exception
 - arithmetic, 93
 - undefined arithmetic, 93
- `<exception>`, 504, 1470
- exception handling, 424–433
 - constructors and destructors, 427
 - currently handled exception, 428
 - exception object, 426
 - constructor, 426
 - destructor, 426
 - function try block, 425
 - `goto`, 424
 - handler, 424, 426–429, 476
 - array in, 427
 - incomplete type in, 427
 - match, 427–429
 - pointer to function in, 427
 - rvalue reference in, 427
 - memory, 426
 - nearest handler, 426
 - rethrow, 137, 426
 - rethrowing, 426
 - `switch`, 424
 - `terminate` called, 137, 426, 430
 - throwing, 137, 425, 426
 - try block, 424
- exception object, *see* exception handling, exception object
- exception specification, 429–432
 - `noexcept`
 - constant expression and, 429
 - non-throwing, 429
 - potentially-throwing, 429
 - virtual function and, 430
- exception-declaration*, 424, 1431
- exclusive-or-expression*, 135, 1420
- `<execution>`, 723
- execution agent, 1360
- execution policy, 723
- execution step, 19
- `exit`, 66, 69, 151
- explicit type conversion, *see* casting
- explicit-instantiation*, 394, 1431
- explicit-specialization*, 397, 1431
- explicitly captured, 103
- exponent-part*, 33, 1416
- exponential integrals Ei , 1154
- `exponential_distribution`
 - probability density function, 1091
- expr-or-braced-init-list*, 220, 1428
- expression, 93–143
 - additive operators, 131
 - `alignof`, 129
 - assignment and compound assignment, 138
 - bitwise AND, 135
 - bitwise exclusive OR, 135
 - bitwise inclusive OR, 135
 - cast, 111, 129–130
 - class member access, 112
 - comma, 139
 - conditional operator, 136
 - const cast, 119
 - constant, 139, 142
 - converted constant, 141
 - core constant, 139
 - decrement, 113, 121
 - `delete`, 127
 - dynamic cast, 113
 - equality operators, 133
 - equivalent, 371
 - fold, 108
 - function call, 109
 - functionally equivalent, 371
 - increment, 113, 121
 - integral constant, 141
 - lambda, 98–108
 - left-shift-operator, 132
 - logical AND, 135
 - logical OR, 135
 - multiplicative operators, 131
 - `new`, 122
 - `noexcept`, 129
 - order of evaluation of, 12
 - parenthesized, 97
 - pointer to member constant, 120
 - pointer-to-member, 130
 - postfix, 108–120
 - primary, 96–108

- pseudo-destructor call, 112
- reference, 93
- reinterpret cast, 117
- relational operators, 133
- right-shift-operator, 132
- rvalue reference, 93
- sizeof, 121
- static cast, 115
- throw, 137
- type identification, 114
- type-dependent, 381
- unary, 120–129
- unary operator, 120
- value-dependent, 381
- expression*, 139, 1421
- expression-list*, 109, 1419
- expression-statement*, 145, 1421
- extend, *see* namespace, extend
- extended alignment, 85
- extended integer type, 80
- extended signed integer type, 79
- extended unsigned integer type, 80
- extern, 157
 - linkage of, 158
- extern "C", 459, 471
- extern "C++", 459, 471
- external linkage, 63
- extreme_value_distribution
 - probability density function, 1094
- F (incomplete elliptic integrals), 1153
- facet, 787
- fallback-separator*, 1250
- file attributes, 1270
 - cached, 1270
- file, source, *see* source file
- filename*, 1250
- <filesystem>, 1242
- final override, 262
- find
 - unordered associative containers, 866
- finite state machine, 1297
- fisher_f_distribution
 - probability density function, 1098
- floating literal, *see* literal, floating
- floating-literal*, 33, 1415
- floating-point literal, *see* literal, floating
- floating-point type, 80
 - implementation-defined, 80
- floating-suffix*, 34, 1416
- fold
 - binary, 108
 - unary, 108
- fold-expression*, 108, 1418
- fold-operator*, 108, 1419
- for
 - scope of declaration in, 149
- for-range-declaration*, 148, 1422
- for-range-initializer*, 148, 1422
- format specifier, 1297
- forward progress guarantees
 - concurrent, 19
 - delegation of, 20
 - parallel, 20
 - weakly parallel, 20
- <forward_list>, 870
- forwarding call wrapper, 656
- forwarding reference, 410
- fractional-constant*, 33, 1416
- free store, *see also* new, delete, 291
- freestanding implementation, 7
- friend
 - virtual and, 265
 - access specifier and, 276
 - class access and, 274
 - inheritance and, 276
 - local class and, 276
 - template and, 364
- friend function
 - access and, 274
 - inline, 275
 - linkage of, 275
 - member function and, 274
 - nested class, 251
- <fstream>, 1225
- full-expression, 13
- function, *see also* friend function; member
 - function; inline function; virtual function
 - allocation, 71, 123
 - comparison, 448
 - conversion, 287
 - deallocation, 72, 291
 - definition, 41
 - global, 471, 474
 - handler, 449
 - handler of type, 427
 - linkage specification overloaded, 193
 - modifier, 449
 - observer, 450
 - operator, 336
 - overload resolution and, 315
 - overloading and pointer versus, 312

- parameter of type, 211
- pointer to member, 131
- replacement, 450
- reserved, 450
- template parameter of type, 347
- viable, 315
- virtual function call, 110
- virtual member, 471
- function argument, *see* argument
- function call, 111
 - recursive, 111
 - undefined, 118
- function call operator
 - overloaded, 338
- function object, 652
 - binders, 666–668
 - mem_fn, 668
 - reference_wrapper, 656
 - type, 652
 - wrapper, 668–672
- function parameter, *see* parameter
- function parameter pack, 361
- function pointer type, 81
- function prototype, 47
- function return, *see* **return**
- function return type, *see* return type
- function try block, *see* exception handling,
 - function try block
- function, overloaded, *see* overloading
- function, virtual, *see* virtual function
- function-body*, 216, 1428
- function-definition*, 216, 1428
- function-like macro, *see* macro, function-like
- function-specifier*, 159, 1423
- function-try-block*, 424, 1431
- <functional>**, 653, 1474
- functionally equivalent
 - expression, *see* expression, functionally equivalent
 - function template, *see* template, function, functionally equivalent
- functions
 - candidate, 389
- fundamental alignment, 85
- fundamental type
 - destructor and, 291
- fundamental type conversion, *see* conversion,
 - user-defined
- future
 - shared state, 1397
- <future>**, 1395
- gamma_distribution**
 - probability density function, 1092
- generate**
 - seed sequence requirement, 1064
- generated destructor, *see* destructor, default
- generation algorithm
 - discard_block_engine, 1078
 - independent_bits_engine, 1079
 - linear_congruential_engine, 1074
 - mersenne_twister_engine, 1075
 - shuffle_order_engine, 1080
 - subtract_with_carry_engine, 1076
- generic lambda
 - definition of, 171
- geometric_distribution**
 - discrete probability function, 1089
- global, 48
- global namespace, 48
- global namespace scope, 48
- global scope, 48
- glvalue, 83
- goto**
 - and handler, 424
 - and try block, 424
 - initialization and, 152
- grammar, 1412
 - regular expression, 1339
- grep**, 1307
- group*, 434, 1432
- group-part*, 434, 1432
- H_n (Hermite polynomials), 1154
- h-char*, 26, 1413
- h-char-sequence*, 26, 1413
- h-pp-tokens*, 436, 1433
- h-preprocessing-token*, 435, 1433
- handler, *see* exception handling, handler
- handler*, 424, 1431
- handler-seq*, 424, 1431
- happens after, 17
- happens before, 17
- has-include-expression*, 436, 1433
- hash**
 - instantiation restrictions, 676
- hash code, 857
- hash function, 856
- hash tables, *see* unordered associative containers
- hash_function**
 - unordered associative containers, 860
- hasher**
 - unordered associative containers, 857

- header
 - C, 471, 474, 1461
 - C library, 459
 - C++ library, 457
 - name, 26
- header-name*, 26, 1413
- headers
 - C library, 1461
- Hermite polynomials H_n , 1154
- hex-quad*, 23, 1412
- hexadecimal-digit*, 30, 1415
- hexadecimal-digit-sequence*, 30, 1414
- hexadecimal-escape-sequence*, 31, 1415
- hexadecimal-floating-literal*, 33, 1416
- hexadecimal-fractional-constant*, 33, 1416
- hexadecimal-literal*, 29, 1414
- hexadecimal-prefix*, 30, 1414
- hiding, *see* name hiding
- high-order bit, 8
- hosted implementation, 7
- I_ν (Bessell functions), 1152
- id
 - qualified, 98
- id-expression, 97
- id-expression*, 97, 1417
- identifier, 27–28, 97, 156
- identifier*, 27, 1413
- identifier label, 145
- identifier-list*, 435, 1433
- identifier-nondigit*, 27, 1413
- if-group*, 434, 1432
- if-section*, 434, 1432
- ill-formed program, *see* program, ill-formed
- immediate subexpression, 12
- implementation
 - freestanding, 458
 - hosted, 458
- implementation limits, *see* limits, implementation
- implementation-defined behavior, *see* behavior,
 - implementation-defined
- implementation-dependent, 1193
- implementation-generated, 41
- implicit capture
 - definition of, 104
- implicit conversion, *see* conversion, implicit
- implicit object parameter, 315
- implicitly-declared default constructor, *see*
 - constructor, default, 281
- implied object argument, 315
 - implicit conversion sequences, 316
 - non-static member function and, 316
- inclusion
 - conditional, *see* preprocessing directive,
 - conditional inclusion
 - source file, *see* preprocessing directives,
 - source-file inclusion
- inclusive-or-expression*, 135, 1421
- incomplete, 132
- increment operator
 - overloaded, *see* overloading, increment
 - operator
- independent_bits_engine**
 - generation algorithm, 1079
 - state, 1079
 - textual representation, 1080
 - transition algorithm, 1079
- indeterminate value, 222
- indeterminately sequenced, 14
- indirection, 120
- inheritance, 256
 - using-declaration* and, 183
- init-capture*, 103, 1418
- init-declarator*, 201, 1426
- init-declarator-list*, 201, 1426
- init-statement*, 144, 1421
- initialization, 67, 220–236
 - aggregate, 224
 - array, 224
 - array of class objects, 228, 293
 - automatic, 152
 - automatic object, 220
 - base class, 294, 295
 - by inherited constructor, 299
 - character array, 228
 - class member, 222
 - class object, *see also* constructor, 224,
 - 293–300
 - const**, 166, 224
 - const member, 296
 - constant, 67
 - constructor and, 293
 - copy, 223
 - default, 221
 - default constructor and, 293
 - definition and, 157
 - direct, 223
 - dynamic, 67
 - dynamic block-scope, 152
 - dynamic non-local, 67
 - explicit, 293
 - jump past, 152

- list-initialization, 231–236
- local **static**, 152
- local **thread_local**, 152
- member, 294
- member function call during, 298
- member object, 295
- non-vacuous, 74
- order of, 67, 257
- order of base class, 297
- order of member, 297
- order of virtual base class, 297
- overloaded assignment and, 293
- parameter, 110
- reference, 207, 228
- reference member, 296
- runtime, 67
- static and thread, 67
- static member, 248
- static** object, 67, 220, 221
- union**, 228, 253
- virtual base class, 305
- zero-initialization, 221
- initializer
 - base class, 216
 - member, 216
 - pack expansion, 298
 - scope of member, 297
 - temporary and declarator, 284
- initializer*, 220, 1428
- initializer-clause*, 220, 1428
- initializer-list*, 220, 1428
- initializer-list constructor, 232
 - seed sequence requirement, 1063
- <initializer_list>**, 509
- initializing declaration, 224
- injected-class-name*, 237
- inline, 474
- inline**
 - linkage of, 63
- inline function, 164
- insert**
 - unordered associative containers, 862
- instantiation
 - explicit, 394
 - point of, 388
 - template implicit, 391
- instantiation units, 23
- integer literal, *see* literal, integer
- integer representation, 73
- integer type, 80
- integer-literal*, 29, 1414
- integer-suffix*, 30, 1415
- integral type, 80
 - implementation-defined **sizeof**, 79
- inter-thread happens before, 16
- internal linkage, 63
- interval boundaries
 - piecewise_constant_distribution**, 1101
 - piecewise_linear_distribution**, 1103
- <inttypes.h>**, 1295
- invalid pointer value, 81
- invocation
 - macro, 439
- <iomanip>**, 1189
- <ios>**, 1162
- <iosfwd>**, 1158
- <iostream>**, 1160
- isctype**
 - regular expression traits, 1299
- <istream>**, 1188
- iteration-statement*, 148, 151, 1422
- <iterator>**, 961, 1479
- j_n (spherical Bessel functions), 1155
- J_ν (Bessell functions), 1152
- Jessie, 286
- jump-statement*, 150, 1422
- K (complete elliptic integrals), 1151
- K_ν (Bessell functions), 1152
- key_eq**
 - unordered associative containers, 861
- key_equal**
 - unordered associative containers, 858
- key_type**
 - unordered associative containers, 857
- keyword, 28, 1412
- L_n (Laguerre polynomials), 1154
- L_n^m (associated Laguerre polynomials), 1150
- label, 151
 - case**, 145, 147
 - default**, 145, 147
 - scope of, 47, 145
- labeled-statement*, 145, 1421
- Laguerre polynomials
 - L_n , 1154
 - L_n^m , 1150
- lambda-capture*, 103, 1418
- lambda-declarator*, 98, 1418
- lambda-expression*, 98, 1418
- lambda-introducer*, 98, 167, 1418

- lattice, *see* DAG, subobject
- layout
 - bit-field, 249
 - class object, 243, 257
- layout-compatible, 79
 - class, 244
 - enumeration, 176
- layout-compatible type, 79
- left shift
 - undefined, 132
- left shift operator, *see* operator, left shift
- Legendre functions Y_ℓ^m , 1155
- Legendre polynomials
 - P_ℓ , 1155
 - P_ℓ^m , 1151
- lexical conventions, *see* conventions, lexical
- LIA-1, 2
- library
 - C standard, 448, 455, 457, 459, 1457, 1461
 - C++ standard, 447, 471, 473, 476
- library clauses, 8
- lifetime, 74
- limits
 - implementation, 4
- <limits>, 483
- line splicing, 22
- linear_congruential_engine
 - generation algorithm, 1074
 - modulus, 1074
 - state, 1074
 - textual representation, 1074
 - transition algorithm, 1074
- linkage, 39, 63–66
 - const and, 63
 - external, 63, 459, 471
 - implementation-defined object, 194
 - inline and, 63
 - internal, 63
 - no, 63, 65
 - static and, 63
- linkage specification, *see* specification, linkage
- linkage-specification, 191, 192, 1425
- <list>, 870
- list-initialization, 231
- literal, 29–38, 96
 - base of integer, 30
 - binary, 30
 - boolean, 36
 - char16_t, 32
 - char32_t, 32
 - character, 31, 32
 - char16_t, 32
 - char32_t, 32
 - ordinary, 32
 - UTF-8, 32
 - wide, 32
- constant, 29
- decimal, 30
- decimal floating, 34
- double, 34
- float, 34
- floating, 33, 34
- hexadecimal, 30
- hexadecimal floating, 34
- implementation-defined value of char, 32
- integer, 29, 30
- long, 30
- long double, 34
- multicharacter, 32
 - implementation-defined value of, 32
- narrow-character, 32
- octal, 30
- pointer, 37
- string, 34, 35
 - char16_t, 35
 - char32_t, 35
 - narrow, 35
 - raw, 24, 35
 - type of, 35
 - undefined change to, 36
 - UTF-8, 35
 - wide, 35
- type of character, 32
- type of floating-point, 34
- type of integer, 30
- unsigned, 30
- user-defined, 37
- literal, 29, 1414
- literal type, 78
- literal-operator-id, 340, 1430
- living dead
 - name of, 470
- load_factor
 - unordered associative containers, 867
- local class, 254
 - friend, 276
 - member function in, 245
 - scope of, 254
- local lambda expression, 103
- local scope, *see* block scope
- local variable, 46
 - destruction of, 151, 152

- `local_iterator`, 858
 - unordered associative containers, 858
- locale, 1297, 1298, 1300, 1307
- `<locale>`, 782, 784
- locale-specific behavior, *see* behavior,
 - locale-specific
- `<locale.h>`, 829
- lock-free execution, 19
- logical-and-expression*, 135, 1421
- logical-or-expression*, 135, 1421
- `lognormal_distribution`
 - probability density function, 1096
- `long`
 - `typedef` and, 157
- long-long-suffix*, 30, 1415
- long-suffix*, 30, 1415
- lookup
 - argument-dependent, 54
 - class member, 57, 62
 - elaborated type specifier, 61–62
 - member name, 259
 - name, 39, 50–63
 - namespace aliases and, 63
 - namespace member, 58
 - qualified name, 56–61
 - template name, 375
 - unqualified name, 50
 - using-directives and, 63
- `lookup_classname`
 - regular expression traits, 1299, 1341
- `lookup_collatename`
 - regular expression traits, 1299
- low-order bit, 8
- lowercase, 455
- lparen*, 435, 1432
- `lvalue`, 83, 1439
- `lvalue` reference, 81, 206
- Lvalue-Callable, 670
- macro
 - argument substitution, 440
 - function-like, 439
 - arguments, 439, 440
 - masking, 474
 - name, 439
 - object-like, 438, 439
 - pragma operator, 446
 - predefined, 444
 - replacement, 438–443
 - replacement list, 438, 439
 - rescanning and replacement, 441
 - scope of definition, 441
- `main` function, 66–67
 - implementation-defined linkage of, 66
 - implementation-defined parameters to, 66
 - parameters to, 66
 - return from, 67, 69
- make progress
 - thread, 19
- `<map>`, 900
- `match_results`
 - as sequence, 1323
- matched, 1297
- mathematical special functions, 1150–1156
- `max`
 - random number distribution requirement, 1069
 - uniform random bit generator requirement, 1064
- `max_bucket_count`
 - unordered associative containers, 866
- `max_load_factor`
 - unordered associative containers, 867
- mean
 - `normal_distribution`, 1095
 - `poisson_distribution`, 1091
- mem-initializer*, 294, 1430
- mem-initializer-id*, 294, 1430
- mem-initializer-list*, 294, 1430
- member
 - class `static`, 70
 - default initializer, 243
 - enumerator, 177
 - static, 242, 247
 - template and `static`, 359
- member access operator
 - overloaded, 339
- member data
 - static, 248
- member function, 242
 - call undefined, 246
 - class, 245
 - `const`, 247
 - constructor and, 282
 - destructor and, 289
 - friend, 275
 - inline, 245
 - local class, 254
 - nested class, 278
 - non-static, 246
 - overload resolution and, 315
 - static, 242, 248

- `this`, 247
- `union`, 252
- `volatile`, 247
- member names, 47
- member of an unknown specialization, 384
- member of the current instantiation, *see* current instantiation, member of the
- member pointer to, *see* pointer to member
- member subobject, 9
- member-declaration*, 241, 1429
- member-declarator*, 241, 1429
- member-declarator-list*, 241, 1429
- member-specification*, 241, 1429
- members, 47
- `<memory>`, 594, 1476, 1478
- memory location, 8
- memory management, *see also* `new`, `delete`
- memory model, 8–9
- `<memory_resource>`, 635
- `mersenne_twister_engine`
 - generation algorithm, 1075
 - state, 1075
 - textual representation, 1076
 - transition algorithm, 1075
- message
 - diagnostic, 3, 7
- `min`
 - random number distribution requirement, 1069
 - uniform random bit generator requirement, 1064
- modifiable, 84
- modification order, 16
- more cv-qualified, 82
- more specialized, 368, 414
 - class template, 368
 - function template, 414
- most derived class, 10
- most derived object, 10
 - bit-field, 10
 - zero size subobject, 10
- move
 - class object, *see* constructor, `move`, *see* assignment operator, `move`
- `MoveInsertable` into X, 835
- multi-pass guarantee, 959
- multibyte character, *see* character, multibyte
- multicharacter literal, *see* literal, multicharacter
- `multiline`, 1307
- multiple inheritance, 256, 257
 - `virtual` and, 265
- multiple threads, *see* threads, multiple
- multiplicative-expression*, 131, 1420
- `mutable`, 157
- mutable iterator, 955
- `<mutex>`, 1367
- mutex types, 1368
- n_n (spherical Neumann functions), 1156
- N_ν (Neumann functions), 1153
- name, 27, 39, 97
 - address of cv-qualified, 120
 - dependent, 381, 388
 - elaborated
 - `enum`, 170
 - global, 48
 - length of, 27
 - macro, *see* macro, name
 - point of declaration, 45
 - predefined macro, *see* macro, predefined
 - qualified, 56
 - reserved, 470
 - same, 39
 - scope of, 44
 - unqualified, 50
 - zombie, 470
- name class, *see* class name
- name hiding, 45, 50, 98, 152
 - class definition, 240
 - function, 314
 - overloading versus, 314
 - user-defined conversion and, 286
 - using-declaration and, 186
- name space
 - label, 145
- named-namespace-definition*, 178, 1425
- namespace, 456, 1461
 - alias, 182
 - associated, 54
 - definition, 178
 - extend, 178
 - global, 28
 - member definition, 180
 - unnamed, 180
- namespace-alias*, 182, 1425
- namespace-alias-definition*, 182, 1425
- namespace-body*, 178, 1425
- namespace-definition*, 178, 1425
- namespace-name*, 178, 1425
- namespaces, 178–191
- NaN, 1150
- narrowing conversion, 235

- NDEBUG, 459
- needed
 - exception specification, 431
- negative_binomial_distribution
 - discrete probability function, 1090
- nested class, 250
 - local class, 254
 - scope of, 250
- nested within, 10
- nested-name-specifier, 98, 1418
- nested-namespace-definition, 178, 1425
- Neumann functions
 - N_ν , 1153
 - n_n , 1156
- <new>, 494
- new, 71, 122, 123
 - array of class objects and, 126
 - constructor and, 126
 - default constructor and, 126
 - exception and, 126
 - initialization and, 126
 - operator
 - replaceable, 471, 472
 - scoping and, 122
 - storage allocation, 122
 - type of, 291
 - unspecified constructor and, 126
 - unspecified order of evaluation, 126
- new-declarator, 122, 1420
- new-expression, 122, 1419
- new-expression
 - placement, 125
- new-extended alignment, 85
- new-initializer, 122, 1420
- new-line, 435, 1433
- new-placement, 122, 1419
- new-type-id, 122, 1419
- new_handler, 72
- no linkage, 63
- nodeclspec-function-declaration, 155, 1423
- noexcept-expression, 129, 1420
- noexcept-specifier, 429, 1432
- non-initialization odr-use, *see* odr-use,
 - non-initialization
- non-static data member, 242
- non-static member, 242
- non-static member function, 242
- non-throwing exception specification, 429
- nondigit, 27, 1413
- nonzero-digit, 30, 1414
- noptr-abstract-declarator, 202, 1427
- noptr-abstract-pack-declarator, 203, 1427
- noptr-declarator, 202, 1427
- noptr-new-declarator, 122, 1420
- normal distributions, 1095–1100
- normal_distribution
 - mean, 1095
 - probability density function, 1095
 - standard deviation, 1095
- normative references, *see* references, normative
- notation
 - syntax, 8
- NTBS, 455, 1228, 1467, 1468
 - static, 455
- NTCTS, 449
- NTMBS, 455
 - static, 455
- null character, *see* character, null
- null pointer value, 81
- null statement, 145
- null wide character, *see* wide-character, null
- number
 - hex, 32
 - octal, 32
 - preprocessing, 26–27
 - subnormal, 484, 485, 487, 488
- <numeric>, 1125
- numeric_limits, 483
 - specializations for arithmetic types, 80
- object, *see also* object model, 9, 39
 - byte copying and, 77
 - complete, 9
 - const, 82
 - const volatile, 82
 - definition, 41
 - delete, 127
 - destructor and placement of, 290
 - destructor static, 69
 - linkage specification, 194
 - local static, 70
 - nested within, 10
 - providing storage for, 10
 - unnamed, 282
 - volatile, 82
- object class, *see also* class object
- object expression, 112
- object lifetime, 74–77
- object model, 9–11
- object pointer type, 81
- object representation, 77
- object temporary, *see* temporary

- object type, 78
 - incompletely-defined, 78
- object, exception, *see* exception handling,
 - exception object
- object-like macro, *see* macro, object-like
- observable behavior, *see* behavior, observable
- octal-digit*, 30, 1414
- octal-escape-sequence*, 31, 1415
- octal-literal*, 29, 1414
- odr-use
 - non-initialization, 68
- odr-used, 42
- one-definition rule, 41–44
- opaque-enum-declaration*, 174, 1424
- operation
 - atomic, 15–20
- operator, 29, 337
 - `*=`, 138
 - `+=`, 121, 138
 - `-=`, 138
 - `/=`, 138
 - `<<=`, 138
 - `>>=`, 138
 - `%=`, 138
 - `&=`, 138
 - `^=`, 138
 - `|=`, 138
 - addition, 131
 - additive, 131
 - address-of, 120
 - assignment, 138, 455
 - bitwise, 135
 - bitwise AND, 135
 - bitwise exclusive OR, 135
 - bitwise inclusive OR, 135
 - cast, 120, 202
 - class member access, 112
 - comma, 139
 - conditional expression, 136
 - copy assignment, *see* assignment operator,
 - copy
 - decrement, 113, 120, 121
 - division, 131
 - equality, 133
 - function call, 109, 337
 - greater than, 133
 - greater than or equal to, 133
 - increment, 113, 120, 121
 - indirection, 120
 - inequality, 133
 - left shift, 132
 - less than, 133
 - less than or equal to, 133
 - logical AND, 135
 - logical negation, 120, 121
 - logical OR, 135
 - move assignment, *see* assignment operator,
 - move
 - multiplication, 131
 - multiplicative, 131
 - ones' complement, 120, 121
 - overloaded, 93, 336
 - pointer to member, 130
 - pragma, *see* macro, pragma operator
 - precedence of, 12
 - relational, 133
 - remainder, 131
 - right shift, 132
 - scope resolution, 56, 98, 124, 245, 256, 266
 - side effects and comma, 139
 - side effects and logical AND, 135
 - side effects and logical OR, 136
 - `sizeof`, 120, 121
 - subscripting, 109, 337
 - subtraction, 131
 - unary, 120
 - unary minus, 120, 121
 - unary plus, 120, 121
- operator*, 336, 1430
- operator delete**, *see also* delete, 124, 128, 291
- operator new**, *see also* new, 124
- operator overloading, *see* overloading, operator
- operator use
 - scope resolution, 248
- operator!=**
 - random number distribution requirement, 1070
 - random number engine requirement, 1066
- operator()**
 - random number distribution requirement, 1069
 - random number engine requirement, 1066
 - uniform random bit generator requirement, 1064
- operator-function-id*, 336, 1430
- operator<<**
 - random number distribution requirement, 1070
 - random number engine requirement, 1066
- operator==**
 - random number distribution requirement, 1070

- random number engine requirement, 1066
- `operator>>`
 - random number distribution requirement, 1070
 - random number engine requirement, 1067
- operators
 - built-in, 93
- optimization of temporary, *see* temporary,
 - elimination of
- `<optional>`, 554
- optional object, 554
- order of evaluation in expression, *see* expression,
 - order of evaluation of
- order of execution
 - base class constructor, 282
 - base class destructor, 289
 - constructor and `static` objects, 294
 - constructor and array, 293
 - destructor, 289
 - destructor and array, 289
 - member constructor, 282
 - member destructor, 289
- ordering
 - function template partial, *see* template,
 - function, partial ordering
- ordinary character literal, 32
- ordinary string literal, 35
- `<ostream>`, 1189
- over-aligned type, *see* type, over-aligned
- overflow, 93
 - undefined, 93
- overloaded function, *see* overloading
 - address of, 121, 335
- overloaded operator, *see* overloading, operator
 - inheritance of, 337
- overloading, 211, 240, 311–343, 370
 - access control and, 314
 - address of overloaded function, 335
 - argument lists, 315–323
 - array versus pointer, 312
 - assignment operator, 338
 - binary operator, 337
 - built-in operators and, 341
 - candidate functions, 315–323
 - declaration matching, 313
 - declarations, 311
 - example of, 311
 - function call operator, 338
 - function versus pointer, 312
 - member access operator, 339
 - operator, 336–341
 - prohibited, 311
 - resolution, 314–335
 - best viable function, 324–337
 - contexts, 314
 - function call syntax, 316–318
 - function template, 422
 - implicit conversions and, 326–335
 - initialization, 321, 322
 - operators, 318
 - scoping ambiguity, 260
 - template, 372
 - template name, 375
 - viable functions, 323–337
 - subscripting operator, 338
 - unary operator, 337
 - user-defined literal, 340
 - using directive and, 190
 - using-declaration and, 187
- overloads
 - floating-point, 1061
- overrider
 - final, 262
- own, 609
- P_ℓ (Legendre polynomials), 1155
- P_ℓ^m (associated Legendre polynomials), 1151
- pack expansion, 361
 - pattern, 361
- `pair`
 - tuple interface to, 539
- parallel algorithm, 1009
- parallel forward progress guarantees, 20
- `param`
 - random number distribution requirement, 1069
 - seed sequence requirement, 1064
- `param_type`
 - random number distribution requirement, 1069
- parameter, 4
 - catch clause, 4
 - function, 4
 - function-like macro, 4
 - reference, 206
 - scope of, 47
 - template, 4, 40
 - `void`, 210
- parameter declaration, 40
- parameter list
 - variable, 111, 210
- parameter pack, 361

- unexpanded, 362
- parameter-declaration*, 210, 1428
- parameter-declaration-clause*, 210, 1428
- parameter-declaration-list*, 210, 1428
- parameter-type-list, 211
- parameterized type, *see* template
- parameters
 - macro, 439
- parameters-and-qualifiers*, 202, 1427
- path equality, 1262
- pathname*, 1250
- pattern, *see* pack expansion, pattern
- period, 455
- phases of translation, *see* translation, phases
- Π (complete elliptic integrals), 1152
- Π (incomplete elliptic integrals), 1154
- piecewise construction, 541
- piecewise_constant_distribution*
 - interval boundaries, 1101
 - probability density function, 1101
 - weights, 1101
- piecewise_linear_distribution*
 - interval boundaries, 1103
 - probability density function, 1103
 - weights at boundaries, 1103
- placeholder type deduction, 173
- placement *new-expression*, 125
- placement syntax
 - new**, 125
- plain lock-free atomic operation, 511
- pm-expression*, 130, 1420
- POD class, 239
- POD struct, 239
- POD union, 239
- point, 81
- point of declaration, 45
- pointer, *see also* **void***
 - composite pointer type, 95
 - integer representation of safely-derived, 73
 - safely-derived, 73–74
 - to traceable object, 73, 476
 - zero, 90
- pointer literal, *see* literal, pointer
- pointer past the end of, 81
- pointer to, 81
- pointer to member, 81, 130
- pointer-interconvertible, 82
- pointer-literal*, 37, 1417
- Poisson distributions, 1091–1095
- poisson_distribution*
 - discrete probability function, 1091
 - mean, 1091
- pool resource classes, 641
- pools, 641
- population, 1029
- POSIX, 2
 - extended regular expressions, 1307
 - regular expressions, 1307
- postfix ++ and --
 - overloading, 339
- postfix ++, 113
- postfix --, 113
- postfix-expression*, 109, 1419
- potential results, 41
- potential scope, 44
- potentially concurrent, 18
- potentially evaluated, 41
- potentially-throwing
 - exception specification, 429
 - expression, 430
- pp-number*, 26, 1413
- pp-tokens*, 435, 1433
- precedence of operator, *see* operator, precedence
 - of
- preferred-separator*, 1250
- prefix
 - L, 32, 35
 - R, 35
 - U, 32, 35
 - u, 32, 35
 - u8, 32, 35
- prefix ++ and --
 - overloading, 339
- prefix ++, 121
- prefix --, 121
- preprocessing directive, 434
 - conditional inclusion, 435
- preprocessing directives, 434–446
 - error, 444
 - header inclusion, 437
 - line control, 443
 - macro replacement, *see* macro, replacement
 - null, 444
 - pragma, 444
 - source-file inclusion, 437
- preprocessing-file*, 434, 1432
- preprocessing-op-or-punc*, 29, 1414
- preprocessing-token*, 24, 1412
- primary class template, *see* template, primary
- primary equivalence class, 1297
- primary-expression*, 96, 1417
- private**, *see* access control, **private**

- probability density function
 - cauchy_distribution, 1097
 - chi_squared_distribution, 1096
 - exponential_distribution, 1091
 - extreme_value_distribution, 1094
 - fisher_f_distribution, 1098
 - gamma_distribution, 1092
 - lognormal_distribution, 1096
 - normal_distribution, 1095
 - piecewise_constant_distribution, 1101
 - piecewise_linear_distribution, 1103
 - student_t_distribution, 1099
 - uniform_real_distribution, 1086
 - weibull_distribution, 1093
- program, 63
 - ill-formed, 4
 - start, 66–69
 - termination, 69–70
 - well-formed, 5, 11
- program execution, 11–15
 - abstract machine, 11
 - as-if rule, *see* as-if rule
- promoted arithmetic type, 341
- promoted integral type, 341
- promotion
 - bool to int, 89
 - default argument promotion, 111
 - floating-point, 89
 - integral, 89
- protected**, *see* access control, **protected**
- protection, *see* access control, 475
- provides storage, 10
- prvalue, 83
- pseudo-destructor-name, 112
- pseudo-destructor-name*, 109, 1419
- ptr-abstract-declarator*, 202, 1427
- ptr-declarator*, 201, 1426
- ptr-operator*, 202, 1427
- ptrdiff_t, 132
 - implementation-defined type of, 132
- public**, *see* access control, **public**
- punctuator, 29
- pure-specifier*, 242, 1429
- q-char*, 26, 1413
- q-char-sequence*, 26, 1413
- qualification
 - explicit, 56
- qualified-id*, 98, 1418
- qualified-namespacespecifier*, 182, 1425
- <queue>**, 946
- r-char*, 34, 1416
- r-char-sequence*, 34, 1416
- <random>**, 1071–1073
- random number distribution
 - bernoulli_distribution, 1087
 - binomial_distribution, 1088
 - cauchy_distribution, 1097
 - chi_squared_distribution, 1096
 - discrete_distribution, 1100
 - exponential_distribution, 1091
 - extreme_value_distribution, 1094
 - fisher_f_distribution, 1098
 - gamma_distribution, 1092
 - geometric_distribution, 1089
 - lognormal_distribution, 1096
 - negative_binomial_distribution, 1090
 - normal_distribution, 1095
 - piecewise_constant_distribution, 1101
 - piecewise_linear_distribution, 1103
 - poisson_distribution, 1091
 - requirements, 1068–1071
 - student_t_distribution, 1099
 - uniform_int_distribution, 1086
 - uniform_real_distribution, 1086
 - weibull_distribution, 1093
- random number distributions
 - Bernoulli, 1087–1090
 - normal, 1095–1100
 - Poisson, 1091–1095
 - sampling, 1100–1105
 - uniform, 1086–1087
- random number engine
 - linear_congruential_engine, 1074
 - mersenne_twister_engine, 1075
 - requirements, 1065–1067
 - subtract_with_carry_engine, 1076
 - with predefined parameters, 1081–1082
- random number engine adaptor
 - discard_block_engine, 1078
 - independent_bits_engine, 1079
 - shuffle_order_engine, 1080
 - with predefined parameters, 1081–1082
- random number generation, 1062–1105
 - distributions, 1085–1105
 - engines, 1073–1081
 - predefined engines and adaptors, 1081–1082
 - requirements, 1062–1071
 - synopsis, 1071–1073
 - utilities, 1083–1085
- random number generator, *see* uniform random bit generator

- random_device
 - implementation leeway, 1082
- <ratio>, 702
- raw string literal, 35
- raw-string*, 34, 1416
- reaching scope, 103
- ready, 1323, 1398
- redefinition
 - typedef, 160
- ref-qualifier*, 202, 1427
- reference, 81
 - assignment to, 138
 - call by, 111
 - forwarding, 410
 - lvalue, 81
 - null, 207
 - rvalue, 81
 - sizeof, 121
- reference collapsing, 207
- reference-compatible, 229
- reference-related, 229
- references
 - normative, 2
- regex_iterator
 - end-of-sequence, 1334
- regex_token_iterator
 - end-of-sequence, 1336
- regex_traits
 - specializations, 1310
- region
 - declarative, 39, 44
- register storage class, 1454
- regular expression, 1297–1341
 - grammar, 1339
 - matched, 1297
 - requirements, 1298
- regular expression traits, 1339
 - char_class_type, 1298
 - isctype, 1299
 - lookup_classname, 1299, 1341
 - lookup_collatename, 1299
 - requirements, 1298, 1310
 - transform, 1299, 1341
 - transform_primary, 1299, 1341
 - translate, 1298, 1341
 - translate_nocase, 1299, 1341
- rehash
 - unordered associative containers, 867
- reinterpret_cast, *see* cast, reinterpret
- relational-expression*, 133, 1420
- relative-path*, 1250
- relaxed pointer safety, 73
- release sequence, 16
- remainder operator, *see* operator, remainder
- replacement
 - macro, *see* macro, replacement
- replacement-list*, 435, 1433
- representation
 - object, 77
 - value, 77
- represents the address, 81
- requirements, 451
 - Allocator, 463
 - container, 830, 857, 871, 873, 1323
 - not required for unordered associated containers, 856
 - CopyAssignable, 460
 - CopyConstructible, 460
 - DefaultConstructible, 460
 - Destructible, 460
 - EqualityComparable, 460
 - Hash, 463
 - iterator, 955
 - LessThanComparable, 460
 - MoveAssignable, 460
 - MoveConstructible, 460
 - NullablePointer, 463
 - numeric type, 1050
 - random number distribution, 1068–1071
 - random number engine, 1065–1067
 - regular expression traits, 1298, 1310
 - seed sequence, 1063–1064
 - sequence, 1323
 - uniform random bit generator, 1064–1065
 - unordered associative container, 857
- rescanning and replacement, *see* macro, rescanning and replacement
- reserved identifier, 28
- reset, 609
- reset
 - random number distribution requirement, 1069
- resolution, *see* overloading, resolution
- restriction, 473, 474, 476
 - address of bit-field, 250
 - anonymous union, 253
 - bit-field, 250
 - constructor, 281, 282
 - destructor, 289
 - extern, 158
 - local class, 254
 - operator overloading, 337

- overloading, 337
- pointer to bit-field, 250
- reference, 207
- static**, 158
- static member local class, 255
- union**, 252
- result
 - glvalue, 84
 - prvalue, 84
- result object, 84
- result_type**
 - entity characterization based on, 1062
 - random number distribution requirement, 1069
 - seed sequence requirement, 1063
 - uniform random bit generator requirement, 1064
- rethrow, *see* exception handling, rethrow
- return**, 150, 151
 - and handler, 424
 - and try block, 424
 - constructor and, 151
 - reference and, 229
- return statement**, *see* **return**
- return type, 211
 - covariant, 264
 - overloading and, 311
- right shift
 - implementation-defined, 133
- right shift operator, *see* operator, right shift
- root-directory*, 1250
- root-name*, 1250
- rounding, 90
- rvalue, 83
 - lvalue conversion to, *see* conversion, lvalue to rvalue, 1439
- rvalue reference, 81, 206
- s-char*, 34, 1416
- s-char-sequence*, 34, 1416
- safely-derived pointer, 73
 - integer representation, 73
- sample, 1029
- sampling distributions, 1100–1105
- scalar type, 78
- scope, 1, 39, 44–50, 156
 - anonymous **union** at namespace, 253
 - block, 46
 - class, 48
 - declarations and, 44–46
 - destructor and exit from, 151
 - enumeration, 49
 - exception declaration, 47
 - function, 47
 - function prototype, 47
 - global, 48
 - global namespace, 48
 - iteration-statement*, 148
 - macro definition, *see* macro, scope of definition
 - name lookup and, 50–63
 - namespace, 47
 - overloading and, 313
 - potential, 44
 - selection-statement*, 145
 - template parameter, 49
 - scope name hiding and, 50
 - scope resolution operator, *see* operator, scope resolution
 - <scoped_allocator>**, 646
 - seed**
 - random number engine requirement, 1065, 1066
 - seed sequence, 1063
 - requirements, 1063–1064
 - selection-statement*, 145, 1422
 - semantics
 - class member, 112
 - separate compilation, *see* compilation, separate
 - separate translation, *see* compilation, separate
 - sequence
 - ambiguous conversion, 327
 - implicit conversion, 326
 - standard conversion, 86
 - sequence constructor
 - seed sequence requirement, 1063
 - sequenced after, 14
 - sequenced before, 14
 - sequencing operator, *see* operator, comma
 - <set>**, 901
 - <setjmp.h>**, 511
 - setlocale**, 455
 - shared lock, 1373
 - shared mutex types, 1373
 - shared state, *see* future, shared state
 - shared timed mutex type, 1374
 - <shared_mutex>**, 1368
 - shift operator
 - left, *see* operator, left shift
 - right, *see* operator, right shift
 - shift-expression*, 132, 1420
 - short**

- typedef and, 157
- shuffle_order_engine
 - generation algorithm, 1080
 - state, 1080
 - textual representation, 1081
 - transition algorithm, 1080
- side effects, 11, 14, 16–18, 135, 136, 145, 284, 296, 308, 441, 475
- visible, 17
- sign*, 33, 1416
- signal, 15
- signal-safe
 - _Exit, 493
 - abort, 493
 - evaluation, *see* evaluation, signal-safe
 - forward, 535
 - initializer_list functions, 509
 - memcpy, 778
 - memmove, 778
 - move, 535
 - move_if_noexcept, 535
 - numeric_limits members, 485
 - quick_exit, 494
 - signal, 512
 - type traits, 676
- <signal.h>, 511
- signature, 4, 5
- signed
 - typedef and, 157
- signed integer representation
 - ones' complement, 80, 121, 176
 - signed magnitude, 80, 176
 - two's complement, 80, 89, 176, 703, 1354
- signed integer type, 79
- significand, 34
- similar types, 88
- simple call wrapper, 656
- simple-capture*, 103, 1418
- simple-declaration*, 155, 1423
- simple-escape-sequence*, 31, 1415
- simple-template-id*, 349, 1431
- simple-type-specifier*, 167, 1424
- size
 - seed sequence requirement, 1064
- size_t, 122
- smart pointers, 620–635
- source file, 22, 459, 471
- source file character, *see* character, source file
- space
 - white, 24
- special member function, *see* constructor, *see* destructor, *see* assignment operator
- specialization
 - class template, 350
 - class template partial, 366
 - template, 390
 - template explicit, 397
- specification
 - linkage, 191–194
 - extern, 191
 - implementation-defined, 192
 - nesting, 192
 - template argument, 402
- specifications
 - C standard library exception, 476
 - C++, 476
- specifier, 157–174
 - constexpr, 161
 - constructor, 162, 163
 - function, 162
 - cv-qualifier, 166
 - declaration, 157
 - explicit, 159
 - friend, 161, 475
 - function, 159
 - inline, 164
 - static, 158
 - storage class, 157
 - type, *see* type specifier
 - typedef, 160
 - virtual, 159
- specifier access, *see* access specifier
- spherical harmonics Y_ℓ^m , 1155
- <sstream>, 1214
- stable algorithm, 450, 475
- <stack>, 946
- stack unwinding, 427
- standard
 - structure of, 8
- standard deviation
 - normal_distribution, 1095
- standard integer type, 80
- standard signed integer type, 79
- standard unsigned integer type, 79
- standard-layout class, 238
- standard-layout struct, 239
- standard-layout types, 78
- standard-layout union, 239
- start
 - program, 67
- startup

- program, 459, 472
- state, 583
 - discard_block_engine, 1078
 - independent_bits_engine, 1079
 - linear_congruential_engine, 1074
 - mersenne_twister_engine, 1075
 - shuffle_order_engine, 1080
 - subtract_with_carry_engine, 1076
- statement, 144–154
 - continue in for, 149
 - break, 150, 151
 - compound, 145
 - continue, 150, 151
 - declaration, 152
 - declaration in for, 149
 - declaration in if, 144
 - declaration in switch, 144, 147
 - declaration in while, 148
 - do, 147, 149
 - empty, 145
 - expression, 145
 - fallthrough, 198
 - for, 147, 149
 - goto, 145, 150, 151
 - if, 145, 146
 - iteration, 147–150
 - jump, 150
 - labeled, 145
 - null, 145
 - range based for, 150
 - selection, 145–147
 - switch, 145, 147, 151
 - while, 147, 148
- statement, 144, 1421
- statement-seq, 145, 1422
- static, 157
 - destruction of local, 152
 - linkage of, 63, 158
 - overloading and, 311
- static data member, 242
- static initialization, 67
- static member, 242
- static member function, 242
- static storage duration, 70
- static type, *see* type, static
- static_assert, 156
- static_assert
 - not macro, 517
- static_assert-declaration, 155, 1423
- static_cast, *see* cast, static
- <stdarg.h>, 510
- <stdatomic.h>, 457, 1457
- <stddef.h>, 32, 35
- <stdexcept>, 513
- <stdio.h>, 1294
- <stdlib.h>, 1461
- <stdnoreturn.h>, 457, 1457
- storage class, 39
- storage duration, 70–74
 - automatic, 70, 71
 - class member, 74
 - dynamic, 70–74, 122
 - local object, 71
 - static, 70
 - thread, 70
- storage management, *see* new, delete
- storage-class-specifier, 158, 1423
- stream
 - arbitrary-positional, 448
 - repositional, 450
- <streambuf>, 1179
- strict pointer safety, 73
- string
 - distinct, 36
 - null-terminated byte, 455
 - null-terminated character type, 449
 - null-terminated multibyte, 455
 - sizeof, 36
 - type of, 35
- <string>, 732
- string literal, *see* literal, string
- string-literal, 34, 1416
- <string.h>, 778
- <string_view>, 767
- stringize, *see* # operator
- strongly happens before, 17
- <strstream>, 1461
- struct
 - standard-layout, 239
- struct
 - class versus, 238
- structure, 238
- structure tag, *see* class name
- structured binding, 219
- structured binding declaration, 156, 219
- student_t_distribution
 - probability density function, 1099
- sub-expression, 1298
- subexpression, 13
- subnormal number, *see* number, subnormal
- subobject, *see also* object model, 9
- subscripting operator

- overloaded, 338
- subsequence rule
 - overloading, 332
- subtract_with_carry_engine**
 - carry, 1076
 - generation algorithm, 1076
 - state, 1076
 - textual representation, 1077
 - transition algorithm, 1076
- subtraction
 - implementation-defined pointer, 132
- subtraction operator, *see* operator, subtraction
- suffix
 - E, 34
 - e, 34
 - F, 34
 - f, 34
 - L, 30, 34
 - l, 30, 34
 - P, 34
 - p, 34
 - U, 30
 - u, 30
- summary
 - compatibility with ISO C, 1436
 - compatibility with ISO C++ 2003, 1445
 - compatibility with ISO C++ 2011, 1451
 - compatibility with ISO C++ 2014, 1453
 - syntax, 1412
- swappable, 462
- swappable with, 461
- switch**
 - and handler, 424
 - and try block, 424
- synchronize with, 16
- synonym, 182
 - type name as, 160
- syntax
 - class member, 112
- <system_error>**, 519
- target object, 655
- template, 344–423
 - class, 357
 - definition of, 344
 - function, 402
 - equivalent, 371
 - functionally equivalent, 371
 - partial ordering, 372
 - member function, 358
 - primary, 366
 - static data member, 344
 - variable, 344
- template**, 344
- template instantiation, 390
- template name
 - linkage of, 345
- template parameter, 40
- template parameter pack, 361
- template parameter scope, 49
- template-argument*, 349, 1431
 - default, 347
- template-argument-list*, 349, 1431
- template-declaration*, 344, 1430
- template-id*, 349, 1431
- template-name*, 349, 1431
- template-parameter*, 345, 1430
- template-parameter-list*, 344, 1430
- templated entity, 345
- temporary, 283
 - constructor for, 284
 - destruction of, 284
 - destructor for, 284
 - elimination of, 283, 308
 - implementation-defined generation of, 283
 - order of destruction of, 284
- terminate**, 432
 - called, 137, 426, 430, 432
- termination
 - program, 66, 67, 70
- terminology
 - pointer, 81
- text-line*, 435, 1432
- textual representation
 - discard_block_engine**, 1079
 - independent_bits_engine**, 1080
 - shuffle_order_engine**, 1081
 - subtract_with_carry_engine**, 1077
- <tgmath.h>**, 1457
- this**, 96, 247
 - type of, 247
- this** pointer, *see* **this**
- thread, 15
- <thread>**, 1362
- thread of execution, 15
- thread storage duration, 70
- thread_local**, 157
- threads
 - multiple, 15–20
- <threads.h>**, 457, 1457
- throw**, 137
- throw-expression*, 137, 1421

- throwing, *see* exception handling, throwing
- `<time.h>`, 722
- timed mutex types, 1370
- token, 25–26
 - alternative, 25
 - preprocessing, 24–25
- token*, 25, 1413
- traceable pointer object, 73, 476
- trailing-return-type*, 202, 1427
- traits, 450
- transfer ownership, 609
- transform**
 - regular expression traits, 1299, 1341
- transform_primary**
 - regular expression traits, 1299, 1340, 1341
- TransformationTrait, 677
- transition algorithm
 - `discard_block_engine`, 1078
 - `independent_bits_engine`, 1079
 - `linear_congruential_engine`, 1074
 - `mersenne_twister_engine`, 1075
 - `shuffle_order_engine`, 1080
 - `subtract_with_carry_engine`, 1076
- translate**
 - regular expression traits, 1298, 1341
- translate_nocase**
 - regular expression traits, 1299, 1341
- translation
 - phases, 22–23
 - separate, *see* compilation, separate
- translation unit, 22, 63
 - name and, 39
- translation-unit*, 63, 1417
- trigraph sequence, 1453
- trivial class, 238
- trivial class type, 126
- trivial type, 126
- trivial types, 78
- trivially copyable class, 238
- trivially copyable types, 78
- truncation, 90
- try**, 424
- try block, *see* exception handling, try block
- try-block*, 424, 1431
- `<tuple>`, 543
- tuple**
 - and **pair**, 539
- type, 39, 77–83
 - allocated, 122
 - arithmetic, 80
 - promoted, 341
- array, 81
- bitmask, 454
- Boolean, 79
- char**, 79
- `char16_t`, 32, 35, 80, 92
- `char32_t`, 32, 35, 80, 92
- character, 79
- character container, 448
- class and, 237
- compound, 81
- const**, 165
- cv-combined, 95
- cv-unqualified, 82
- destination, 223
- double**, 80
- dynamic, 3, 4
- enumerated, 81, 453, 454
- example of incomplete, 78
- extended integer, 80
- extended signed integer, 79
- extended unsigned integer, 79
- float**, 80
- floating-point, 79
- function, 81, 210, 211
- fundamental, 79
- implementation-defined **sizeof**, 79
- incomplete, 41, 42, 46, 78, 87, 109–113, 120–122, 128, 138, 256
- incompletely-defined object, 77
- int**, 79
- integral, 79
 - promoted, 341
- long**, 79
- long double**, 80
- long long**, 79
- narrow character, 79
- over-aligned, 85
- POD, 78
- pointer, 81
- polymorphic, 262
- referenceable, 450
- short**, 79
- signed char**, 79
- signed integer, 79
- similar, *see* similar types
- standard integer, 80
- standard signed integer, 79
- standard unsigned integer, 79
- static, 5
- trivially copyable, 77
- underlying

- char16_t, 80, 89
 - char32_t, 80, 89
 - enumeration, 89, 176
 - wchar_t, 80, 89
- unsigned, 79
- unsigned char, 79
- unsigned int, 79
- unsigned integer, 79
- unsigned long, 79
- unsigned long long, 79
- unsigned short, 79
- void, 80
- volatile, 165
- wchar_t, 32, 35, 80, 92
- type checking
 - argument, 111
- type conversion, explicit, *see* casting
- type generator, *see* template
- type name, 202
 - nested, 251
 - scope of, 251
- type pun, 118
- type specifier
 - auto, 167, 170
 - bool, 167
 - char, 167
 - char16_t, 167
 - char32_t, 167
 - const, 166
 - decltype, 167, 168
 - double, 167
 - elaborated, 61, 170
 - enum, 170
 - float, 167
 - int, 167
 - long, 167
 - short, 167
 - signed, 167
 - simple, 167
 - unsigned, 167
 - void, 167
 - volatile, 166, 167
 - wchar_t, 167
- type-id*, 202, 1427
- type-name*, 167, 1424
- type-parameter*, 345, 1431
- type-parameter-key*, 345, 1431
- type-specifier*, 165, 1423
- type-specifier-seq*, 165, 1423
- type_info, 114
- <type_traits>, 677, 1478
- typedef
 - function, 212
- typedef
 - overloading and, 312
- typedef-name*, 160, 1423
- typeid, 114
 - construction and, 302
 - destruction and, 302
- <typeindex>, 722
- <typeinfo>, 502
- typename, 170
- typename-specifier*, 375, 1431
- types
 - implementation-defined, 453
- <uchar.h>, 780
- ud-suffix*, 37, 1417
- unary fold, 108
- unary left fold, 108
- unary operator
 - interpretation of, 337
 - overloaded, 337
- unary right fold, 108
- unary-expression*, 120, 1419
- unary-operator*, 120, 1419
- UnaryTypeTrait, 676
- unlock, 5
- undefined, 450, 470, 471, 473, 1116, 1121, 1124, 1125, 1172
- undefined behavior, *see* behavior, undefined
- underlying type, *see* type, underlying
- unevaluated operand, 94
- Unicode required set, 445
- uniform distributions, 1086–1087
- uniform random bit generator
 - requirements, 1064–1065
- uniform_int_distribution
 - discrete probability function, 1086
- uniform_real_distribution
 - probability density function, 1086
- union
 - standard-layout, 239
- union, 81, 251
 - class versus, 238
 - anonymous, 253
 - global anonymous, 253
- union-like class, 254
- unique pointer, 609
- unit
 - translation, 459, 471
- universal character name, 22

- universal-character-name*, 23, 1412
- unnamed bit-field, 249
- unnamed-namespace-definition*, 178, 1425
- unordered associative containers, 857
 - begin*, 866
 - bucket*, 866
 - bucket_count*, 866
 - bucket_size*, 866
 - cbegin*, 867
 - cend*, 867
 - clear*, 865
 - complexity, 856
 - const_local_iterator*, 858
 - count*, 866
 - end*, 866
 - equal_range*, 866
 - equality function, 856
 - equivalent keys, 856, 857, 931, 941
 - erase*, 865
 - exception safety, 868
 - find*, 866
 - hash function, 856
 - hash_function*, 860
 - hasher*, 857
 - insert*, 862
 - iterator invalidation, 868
 - iterators, 868
 - key_eq*, 861
 - key_equal*, 858
 - key_type*, 857
 - lack of comparison functions, 856
 - load_factor*, 867
 - local_iterator*, 858
 - max_bucket_count*, 866
 - max_load_factor*, 867
 - rehash*, 867
 - requirements, 856, 857, 868
 - unique keys, 856, 857, 924, 936
- <unordered_map>*, 921
- unordered_map*
 - element access, 929
 - unique keys, 924
- unordered_multimap*
 - equivalent keys, 931
- unordered_multiset*
 - equivalent keys, 941
- <unordered_set>*, 922
- unordered_set*
 - unique keys, 936
- unqualified-id*, 97, 1418
- unsequenced, 14
- unsigned
 - typedef* and, 157
 - unsigned integer type, 80
 - unsigned-suffix*, 30, 1415
 - unspecified, 496, 497, 503, 1032, 1218, 1463, 1465
 - unspecified behavior, *see* behavior, unspecified
 - unwinding
 - stack, 427
 - uppercase, 28, 455
 - upstream, 645
 - upstream allocator, 642
 - user-defined literal, *see* literal, user-defined
 - overloaded, 340
 - user-defined-character-literal*, 37, 1417
 - user-defined-floating-literal*, 37, 1417
 - user-defined-integer-literal*, 37, 1417
 - user-defined-literal*, 37, 1417
 - user-defined-string-literal*, 37, 1417
 - user-provided, 218
 - uses-allocator construction, 602
 - using-declaration, 182–188
 - using-declaration*, 182, 1425
 - using-declarator*, 182, 1425
 - using-declarator-list*, 182, 1425
 - using-directive, 188–191
 - using-directive*, 188, 1425
 - usual arithmetic conversions, *see* conversion, usual
 - arithmetic
 - usual deallocation function, 72
 - UTF-8 character literal, 32
 - UTF-8 string literal, 35
 - <utility>*, 530
 - <valarray>*, 1105
 - valid, 44
 - valid but unspecified state, 450
 - value, 77
 - call by, 111
 - denormalized, *see* number, subnormal
 - indeterminate, 222
 - null member pointer, 90
 - null pointer, 90
 - undefined unrepresentable integral, 90
 - value category, 83
 - value computation, 14–15, 18, 113, 126, 135, 136, 138, 139, 284
 - value representation, 77
 - value-initialization, 221
 - variable, 39
 - indeterminate uninitialized, 221
 - variable template

- definition of, 344
- <variant>, 569
- variant member, 254
- <vector>, 871
- vectorization-unsafe, 1011
- virt-specifier*, 242, 1429
- virt-specifier-seq*, 242, 1429
- virtual base class, *see* base class, virtual
- virtual function, 262–266
 - pure, 266, 267
- virtual function call, 266
 - constructor and, 301
 - destructor and, 301
 - undefined pure, 267
- visibility, 50
- visible, 50
- void*
 - type, 82
- void&, 206
- volatile, 82
 - constructor and, 247, 281
 - destructor and, 247, 289
 - implementation-defined, 167
 - overloading and, 313
- volatile-qualified, 82
- waiting function, 1398
- <wchar.h>, 780
- wchar_t, *see* type, wchar_t
- <wctype.h>, 777
- weak result type, 1470
- weakly parallel forward progress guarantees, 20
- weibull_distribution
 - probability density function, 1093
- weights
 - discrete_distribution, 1100
 - piecewise_constant_distribution, 1101
- weights at boundaries
 - piecewise_linear_distribution, 1103
- well-formed program, *see* program, well-formed
- white space, 25
- wide string literal, 35
- wide-character, 32
 - null, 24
- wide-character literal, 32
- wide-character set
 - basic execution, 24
 - execution, 24
- writable, 955
- X(X&), *see* constructor, copy
- xvalue, 83
- Y_ℓ^m (spherical associated Legendre functions), 1155
- zero
 - division by undefined, 93
 - remainder undefined, 93
 - undefined division by, 131
- zero-initialization, 221
- zeta functions ζ , 1155

Index of grammar productions

The first page number for each entry is the page in the general text where the grammar production is defined. The second page number is the corresponding page in the Grammar summary (Annex A).

- abstract-declarator*, 202, 1427
- abstract-pack-declarator*, 202, 1427
- access-specifier*, 256, 1430
- additive-expression*, 131, 1420
- alias-declaration*, 155, 1423
- alignment-specifier*, 194, 1426
- and-expression*, 135, 1420
- asm-definition*, 191, 1425
- assignment-expression*, 138, 1421
- assignment-operator*, 138, 1421
- attribute*, 194, 1426
- attribute-argument-clause*, 195, 1426
- attribute-declaration*, 155, 1423
- attribute-list*, 194, 1426
- attribute-namespace*, 195, 1426
- attribute-scoped-token*, 195, 1426
- attribute-specifier*, 194, 1426
- attribute-specifier-seq*, 194, 1426
- attribute-token*, 195, 1426
- attribute-using-prefix*, 194, 1426

- balanced-token*, 195, 1426
- balanced-token-seq*, 195, 1426
- base-clause*, 256, 1429
- base-specifier*, 256, 1429
- base-specifier-list*, 256, 1429
- binary-digit*, 29, 1414
- binary-exponent-part*, 33, 1416
- binary-literal*, 29, 1414
- block-declaration*, 155, 1422
- boolean-literal*, 36, 1417
- brace-or-equal-initializer*, 220, 1428
- braced-init-list*, 220, 1428

- c-char*, 31, 1415
- c-char-sequence*, 31, 1415
- capture*, 103, 1418
- capture-default*, 103, 1418
- capture-list*, 103, 1418
- cast-expression*, 129, 1420
- character-literal*, 31, 1415
- class-head*, 237, 1428
- class-head-name*, 237, 1428

- class-key*, 237, 1429
- class-name*, 237, 1428
- class-or-decltype*, 256, 1429
- class-specifier*, 237, 1428
- class-virt-specifier*, 237, 1429
- compound-statement*, 145, 1421
- condition*, 144, 1421
- conditional-expression*, 136, 1421
- conditionally-supported-directive*, 435, 1432
- constant-expression*, 139, 1421
- control-line*, 434, 1432
- conversion-declarator*, 287, 1430
- conversion-function-id*, 287, 1430
- conversion-type-id*, 287, 1430
- ctor-initializer*, 294, 1430
- cv-qualifier*, 202, 1427
- cv-qualifier-seq*, 202, 1427

- d-char*, 34, 1417
- d-char-sequence*, 34, 1416
- decimal-floating-literal*, 33, 1415
- decimal-literal*, 29, 1414
- decl-specifier*, 157, 1423
- decl-specifier-seq*, 157, 1423
- declaration*, 155, 1422
- declaration-seq*, 155, 1422
- declaration-statement*, 152, 1422
- declarator*, 201, 1426
- declarator-id*, 202, 1427
- decltype-specifier*, 167, 1424
- deduction-guide*, 423, 1431
- defined-macro-expression*, 435, 1433
- defining-type-id*, 202, 1427
- defining-type-specifier*, 165, 1423
- defining-type-specifier-seq*, 165, 1424
- delete-expression*, 127, 1420
- digit*, 27, 1413
- digit-sequence*, 33, 1416
- directory-separator*, 1250

- elaborated-type-specifier*, 170, 1424
- elif-group*, 434, 1432
- elif-groups*, 434, 1432

else-group, 434, 1432
empty-declaration, 155, 1423
enclosing-namespace-specifier, 178, 1425
encoding-prefix, 31, 1415
endif-line, 435, 1432
enum-base, 175, 1425
enum-head, 174, 1424
enum-head-name, 174, 1424
enum-key, 175, 1424
enum-name, 174, 1424
enum-specifier, 174, 1424
enumerator, 175, 1425
enumerator-definition, 175, 1425
enumerator-list, 175, 1425
equality-expression, 133, 1420
escape-sequence, 31, 1415
exception-declaration, 424, 1431
exclusive-or-expression, 135, 1420
explicit-instantiation, 394, 1431
explicit-specialization, 397, 1431
exponent-part, 33, 1416
expr-or-braced-init-list, 220, 1428
expression, 139, 1421
expression-list, 109, 1419
expression-statement, 145, 1421

fallback-separator, 1250
filename, 1250
floating-literal, 33, 1415
floating-suffix, 34, 1416
fold-expression, 108, 1418
fold-operator, 108, 1419
for-range-declaration, 148, 1422
for-range-initializer, 148, 1422
fractional-constant, 33, 1416
function-body, 216, 1428
function-definition, 216, 1428
function-specifier, 159, 1423
function-try-block, 424, 1431

group, 434, 1432
group-part, 434, 1432

h-char, 26, 1413
h-char-sequence, 26, 1413
h-pp-tokens, 436, 1433
h-preprocessing-token, 435, 1433
handler, 424, 1431
handler-seq, 424, 1431
has-include-expression, 436, 1433
header-name, 26, 1413

hex-quad, 23, 1412
hexadecimal-digit, 30, 1415
hexadecimal-digit-sequence, 30, 1414
hexadecimal-escape-sequence, 31, 1415
hexadecimal-floating-literal, 33, 1416
hexadecimal-fractional-constant, 33, 1416
hexadecimal-literal, 29, 1414
hexadecimal-prefix, 30, 1414

id-expression, 97, 1417
identifier, 27, 1413
identifier-list, 435, 1433
identifier-nondigit, 27, 1413
if-group, 434, 1432
if-section, 434, 1432
inclusive-or-expression, 135, 1421
init-capture, 103, 1418
init-declarator, 201, 1426
init-declarator-list, 201, 1426
init-statement, 144, 1421
initializer, 220, 1428
initializer-clause, 220, 1428
initializer-list, 220, 1428
integer-literal, 29, 1414
integer-suffix, 30, 1415
iteration-statement, 148, 1422

jump-statement, 150, 1422

labeled-statement, 145, 1421
lambda-capture, 103, 1418
lambda-declarator, 98, 1418
lambda-expression, 98, 1418
lambda-introducer, 98, 1418
linkage-specification, 192, 1425
literal, 29, 1414
literal-operator-id, 340, 1430
logical-and-expression, 135, 1421
logical-or-expression, 135, 1421
long-long-suffix, 30, 1415
long-suffix, 30, 1415
lparen, 435, 1432

mem-initializer, 294, 1430
mem-initializer-id, 294, 1430
mem-initializer-list, 294, 1430
member-declaration, 241, 1429
member-declarator, 241, 1429
member-declarator-list, 241, 1429
member-specification, 241, 1429
multiplicative-expression, 131, 1420

named-namespace-definition, 178, 1425
namespace-alias, 182, 1425
namespace-alias-definition, 182, 1425
namespace-body, 178, 1425
namespace-definition, 178, 1425
namespace-name, 178, 1425
nested-name-specifier, 98, 1418
nested-namespace-definition, 178, 1425
new-declarator, 122, 1420
new-expression, 122, 1419
new-initializer, 122, 1420
new-line, 435, 1433
new-placement, 122, 1419
new-type-id, 122, 1419
nodeclspec-function-declaration, 155, 1423
noexcept-expression, 129, 1420
noexcept-specifier, 429, 1432
nondigit, 27, 1413
nonzero-digit, 30, 1414
noPtr-abstract-declarator, 202, 1427
noPtr-abstract-pack-declarator, 203, 1427
noPtr-declarator, 202, 1427
noPtr-new-declarator, 122, 1420

octal-digit, 30, 1414
octal-escape-sequence, 31, 1415
octal-literal, 29, 1414
opaque-enum-declaration, 174, 1424
operator, 336, 1430
operator-function-id, 336, 1430

parameter-declaration, 210, 1428
parameter-declaration-clause, 210, 1428
parameter-declaration-list, 210, 1428
parameters-and-qualifiers, 202, 1427
pathname, 1250
pm-expression, 130, 1420
pointer-literal, 37, 1417
postfix-expression, 109, 1419
pp-number, 26, 1413
pp-tokens, 435, 1433
preferred-separator, 1250
preprocessing-file, 434, 1432
preprocessing-op-or-punc, 29, 1414
preprocessing-token, 24, 1412
primary-expression, 96, 1417
pseudo-destructor-name, 109, 1419
Ptr-abstract-declarator, 202, 1427
Ptr-declarator, 201, 1426
Ptr-operator, 202, 1427
pure-specifier, 242, 1429

q-char, 26, 1413
q-char-sequence, 26, 1413
qualified-id, 98, 1418
qualified-namespace-specifier, 182, 1425

r-char, 34, 1416
r-char-sequence, 34, 1416
raw-string, 34, 1416
ref-qualifier, 202, 1427
relational-expression, 133, 1420
relative-path, 1250
replacement-list, 435, 1433
root-directory, 1250
root-name, 1250

s-char, 34, 1416
s-char-sequence, 34, 1416
selection-statement, 145, 1422
shift-expression, 132, 1420
sign, 33, 1416
simple-capture, 103, 1418
simple-declaration, 155, 1423
simple-escape-sequence, 31, 1415
simple-template-id, 349, 1431
simple-type-specifier, 167, 1424
statement, 144, 1421
statement-seq, 145, 1422
static_assert-declaration, 155, 1423
storage-class-specifier, 158, 1423
string-literal, 34, 1416

template-argument, 349, 1431
template-argument-list, 349, 1431
template-declaration, 344, 1430
template-id, 349, 1431
template-name, 349, 1431
template-parameter, 345, 1430
template-parameter-list, 344, 1430
text-line, 435, 1432
throw-expression, 137, 1421
token, 25, 1413
trailing-return-type, 202, 1427
translation-unit, 63, 1417
try-block, 424, 1431
type-id, 202, 1427
type-name, 167, 1424
type-parameter, 345, 1431
type-parameter-key, 345, 1431
type-specifier, 165, 1423
type-specifier-seq, 165, 1423
typedef-name, 160, 1423

typename-specifier, 375, 1431

ud-suffix, 37, 1417

unary-expression, 120, 1419

unary-operator, 120, 1419

universal-character-name, 23, 1412

unnamed-namespace-definition, 178, 1425

unqualified-id, 97, 1418

unsigned-suffix, 30, 1415

user-defined-character-literal, 37, 1417

user-defined-floating-literal, 37, 1417

user-defined-integer-literal, 37, 1417

user-defined-literal, 37, 1417

user-defined-string-literal, 37, 1417

using-declaration, 182, 1425

using-declarator, 182, 1425

using-declarator-list, 182, 1425

using-directive, 188, 1425

virt-specifier, 242, 1429

virt-specifier-seq, 242, 1429

Index of library names

_Exit, 479, 493
 _IOFBF, 1293
 _IOLBF, 1293
 _IONBF, 1293
 __alignas_is_defined, 1460
 __bool_true_false_are_defined, 510, 1461
 _1, 668
 a
 cauchy_distribution, 1098
 extreme_value_distribution, 1094
 uniform_int_distribution, 1086
 uniform_real_distribution, 1087
 weibull_distribution, 1094
 abort, 70, 151, 458, 479, 493, 501, 506
 abs, 479, 1139, 1149, 1294
 complex, 1059
 duration, 717
 valarray, 1117
 absolute, 1279
 accumulate, 1130
 acos, 1139
 complex, 1059
 valarray, 1117
 acosf, 1139
 acosh, 1139
 complex, 1060
 acoshf, 1139
 acoshl, 1139
 acosl, 1139
 add_const, 696
 add_cv, 696
 add_lvalue_reference, 696
 add_pointer, 698
 add_rvalue_reference, 696
 add_volatile, 696
 address
 allocator, 1476
 addressof, 606
 adjacent_difference, 1137
 adjacent_find, 1015
 adopt_lock, 1376
 adopt_lock_t, 1376
 advance, 967
 <algorithm>, 989
 align, 601
 align_val_t, 494
 aligned_alloc, 479, 608, 1459
 aligned_storage, 699, 700
 aligned_union, 699
 alignment_of, 693
 all
 bitset, 592
 all_of, 1012
 allocate
 allocator, 605, 1476
 allocator_traits, 604
 memory_resource, 636
 polymorphic_allocator, 639
 scoped_allocator_adaptor, 650
 allocate_shared, 627
 allocator, 605, 1475
 address, 1476
 allocate, 605, 1476
 construct, 1476
 deallocate, 605
 destroy, 1476
 max_size, 1476
 operator!=, 606
 operator==, 606
 allocator_arg, 602
 allocator_arg_t, 602
 allocator_traits, 603
 allocate, 604
 const_pointer, 603
 const_void_pointer, 603
 construct, 604
 deallocate, 604
 destroy, 604
 difference_type, 604
 is_always_equal, 604
 max_size, 605
 pointer, 603
 propagate_on_container_copy_ -
 assignment,
 604
 propagate_on_container_move_ -
 assignment,
 604
 propagate_on_container_swap, 604

```

    rebind_alloc, 604
    select_on_container_copy_construction,
        605
    size_type, 604
    void_pointer, 603
alpha
    gamma_distribution, 1093
always_noconv
    codecvt, 799
<any>, 582
any
    constructor, 583, 584
    destructor, 584
    emplace, 585
    has_value, 586
    operator=, 585
    reset, 586
    swap, 586
    type, 586
any (member)
    bitset, 592
any_cast, 586, 587
any_of, 1012
append
    basic_string, 748, 749
    path, 1255
apply, 551
    valarray, 1115
arg, 1061
    complex, 1059
argument_type
    bit_not, 1471
    function, 1471
    hash, 1474
    logical_not, 1471
    mem_fn, 1474
    negate, 1471
    reference_wrapper, 1473
    unary_negate, 1475
<array>, 868
array, 871, 872, 874
    begin, 872
    data, 873
    end, 872
    fill, 873
    get, 874
    max_size, 872
    size, 872, 873
    swap, 873
as_const, 536
asctime, 721
    asin, 1139
        complex, 1060
        valarray, 1117
    asinf, 1139
    asinh, 1139
        complex, 1060
    asinhf, 1139
    asinhl, 1139
    asinl, 1139
    assert, 517
    <assert.h>, 459, 517, 1458
    assign
        basic_regex, 1316, 1317
        basic_string, 749, 750
        directory_entry, 1271
        error_code, 525
        error_condition, 526
        path, 1254
    assoc_laguerre, 1150
    assoc_laguerref, 1150
    assoc_laguerrel, 1150
    assoc_legendre, 1151
    assoc_legendref, 1151
    assoc_legendrel, 1151
    async, 1406
    at
        basic_string, 747
        basic_string_view, 771
        map, 907
        unordered_map, 929
    at_quick_exit, 479, 494
    atan, 1139
        complex, 1060
        valarray, 1117
    atan2, 1139
        valarray, 1117
    atan2f, 1139
    atan2l, 1139
    atanf, 1139
    atanh, 1139
        complex, 1060
    atanhf, 1139
    atanhhl, 1139
    atanl, 1139
    atexit, 69, 458, 479, 493
    atof, 479
    atoi, 479
    atol, 479
    atoll, 479
    <atomic>, 1342
    atomic, 1348, 1349

```

```

compare_exchange_strong, 1350
compare_exchange_weak, 1350
constructor, 1349
exchange, 1350
is_always_lock_free, 1350
is_lock_free, 1350
load, 1350
operator type, 1350
operator=, 1350
store, 1350
atomic<integral>, 1352
    compare_exchange_strong, 1350
    compare_exchange_weak, 1350
    constructor, 1349
    exchange, 1350
    fetch_add, 1353
    fetch_and, 1353
    fetch_or, 1353
    fetch_sub, 1353
    fetch_xor, 1353
    is_always_lock_free, 1350
    is_lock_free, 1350
    load, 1350
    operator integral, 1350
    operator++, 1355
    operator+=, 1354
    operator-=, 1354
    operator--, 1355, 1356
    operator=, 1350
    operator&=, 1354
    operator^=, 1354
    operator|=, 1354
    store, 1350
atomic<T*>, 1354, 1355
    compare_exchange_strong, 1350
    compare_exchange_weak, 1350
    constructor, 1349
    exchange, 1350
    fetch_add, 1355
    fetch_sub, 1355
    is_always_lock_free, 1350
    is_lock_free, 1350
    load, 1350
    operator T*, 1350
    operator++, 1355
    operator+=, 1354, 1355
    operator-=, 1354, 1355
    operator--, 1355, 1356
    operator=, 1350
    store, 1350
atomic_bool, 1346
    ATOMIC_BOOL_LOCK_FREE, 1348
    atomic_char, 1346
    atomic_char16_t, 1346
    ATOMIC_CHAR16_T_LOCK_FREE, 1348
    atomic_char32_t, 1346
    ATOMIC_CHAR32_T_LOCK_FREE, 1348
    ATOMIC_CHAR_LOCK_FREE, 1348
    atomic_compare_exchange_strong, 1350
        shared_ptr, 635
    atomic_compare_exchange_strong_explicit,
        1350
        shared_ptr, 635
    atomic_compare_exchange_weak, 1350
        shared_ptr, 635
    atomic_compare_exchange_weak_explicit,
        1350
        shared_ptr, 635
    atomic_exchange, 1350
        shared_ptr, 634
    atomic_exchange_explicit, 1350
        shared_ptr, 634
    atomic_fetch_add, 1353, 1355
    atomic_fetch_add_explicit, 1353, 1355
    atomic_fetch_and, 1353
    atomic_fetch_and_explicit, 1353
    atomic_fetch_or, 1353
    atomic_fetch_or_explicit, 1353
    atomic_fetch_sub, 1353, 1355
    atomic_fetch_sub_explicit, 1353, 1355
    atomic_fetch_xor, 1353
    atomic_fetch_xor_explicit, 1353
    atomic_flag
        clear, 1357
        test_and_set, 1357
    atomic_flag_clear, 1357
    atomic_flag_clear_explicit, 1357
    atomic_flag_test_and_set, 1357
    atomic_flag_test_and_set_explicit, 1357
    atomic_init, 1356
    atomic_int, 1346
    atomic_int16_t, 1346
    atomic_int32_t, 1346
    atomic_int64_t, 1346
    atomic_int8_t, 1346
    atomic_int_fast16_t, 1346
    atomic_int_fast32_t, 1346
    atomic_int_fast64_t, 1346
    atomic_int_fast8_t, 1346
    atomic_int_least16_t, 1346
    atomic_int_least32_t, 1346
    atomic_int_least64_t, 1346

```

atomic_int_least8_t, 1346
 ATOMIC_INT_LOCK_FREE, 1348
 atomic_intmax_t, 1346
 atomic_intptr_t, 1346
 atomic_is_lock_free, 1350
 shared_ptr, 634
 atomic_llong, 1346
 ATOMIC_LLONG_LOCK_FREE, 1348
 atomic_load, 1350
 shared_ptr, 634
 atomic_load_explicit, 1350
 shared_ptr, 634
 atomic_long, 1346
 ATOMIC_LONG_LOCK_FREE, 1348
 ATOMIC_POINTER_LOCK_FREE, 1348
 atomic_ptrdiff_t, 1346
 atomic_schar, 1346
 atomic_short, 1346
 ATOMIC_SHORT_LOCK_FREE, 1348
 atomic_signal_fence, 1358
 atomic_size_t, 1346
 atomic_store, 1350
 shared_ptr, 634
 atomic_store_explicit, 1350
 shared_ptr, 634
 atomic_thread_fence, 1357
 atomic_uchar, 1346
 atomic_uint, 1346
 atomic_uint16_t, 1346
 atomic_uint32_t, 1346
 atomic_uint64_t, 1346
 atomic_uint8_t, 1346
 atomic_uint_fast16_t, 1346
 atomic_uint_fast32_t, 1346
 atomic_uint_fast64_t, 1346
 atomic_uint_fast8_t, 1346
 atomic_uint_least16_t, 1346
 atomic_uint_least32_t, 1346
 atomic_uint_least64_t, 1346
 atomic_uint_least8_t, 1346
 atomic_uintmax_t, 1346
 atomic_uintptr_t, 1346
 atomic_ullong, 1346
 atomic_ulong, 1346
 atomic_ushort, 1346
 ATOMIC_VAR_INIT, 1349
 atomic_wchar_t, 1346
 ATOMIC_WCHAR_T_LOCK_FREE, 1348
 auto_ptr
 zombie, 470

b
 cauchy_distribution, 1098
 extreme_value_distribution, 1095
 uniform_int_distribution, 1086
 uniform_real_distribution, 1087
 weibull_distribution, 1094
 back
 basic_string, 747
 basic_string_view, 771
 back_insert_iterator, 972
 constructor, 973
 operator*, 973
 operator++, 973
 operator=, 973
 back_inserter, 973
 bad
 basic_ios, 1176
 bad_alloc, 126, 496, 500, 501
 constructor, 500
 operator=, 500
 what, 500
 bad_any_access
 what, 582
 bad_any_cast, 582
 bad_array_new_length, 500
 constructor, 501
 what, 501
 bad_cast, 114, 502, 503
 constructor, 504
 operator=, 504
 what, 504
 bad_exception, 506
 constructor, 506
 operator=, 506
 what, 506
 bad_function_call, 668
 constructor, 669
 what, 669
 bad_optional_access
 constructor, 565
 what, 565
 bad_typeid, 115, 502, 504
 constructor, 504
 operator=, 504
 what, 504
 bad_variant_access, 581
 constructor, 581
 what, 581
 bad_weak_ptr, 620
 constructor, 620
 what, 620

```

base
    move_iterator, 978
    raw_storage_iterator, 1477
    reverse_iterator, 969
basic_filebuf, 1158, 1225
    close, 1228
    constructor, 1227
    destructor, 1227
    imbue, 1231
    is_open, 1228
    open, 1228
    operator=, 1228
    overflow, 1230
    pbackfail, 1230
    seekoff, 1231
    seekpos, 1231
    setbuf, 1230
    showmanyc, 1229
    swap, 1228
    sync, 1231
    uflow, 1229
    underflow, 1229
basic_filebuf<char>, 1225
basic_filebuf<wchar_t>, 1225
basic_fstream, 1158, 1236
    close, 1239
    constructor, 1237, 1238
    is_open, 1238
    open, 1238, 1239
    operator=, 1238
    rdbuf, 1238
    swap, 1238
basic_fstream<char>, 1225
basic_fstream<wchar_t>, 1225
basic_ifstream, 1158, 1232
    close, 1234
    constructor, 1233
    is_open, 1234
    open, 1234
    operator=, 1233
    rdbuf, 1234
    swap, 1233
basic_ifstream<char>, 1225
basic_ifstream<wchar_t>, 1225
basic_ios, 1158, 1172
    bad, 1176
    clear, 1176
    constructor, 1173
    copyfmt, 1175
    destructor, 1173
    eof, 1176
    exceptions, 1176
    fail, 1176
    fill, 1174, 1175
    good, 1176
    imbue, 1174
    init, 1173, 1192
    move, 1175
    narrow, 1174
    operator bool, 1176
    operator!, 1176
    rdbuf, 1174
    rdstate, 1176
    set_rdbuf, 1176
    setstate, 1176
    swap, 1175
    tie, 1174
    widen, 1174
basic_ios<char>, 1163
basic_ios<wchar_t>, 1163
basic_iostream, 1201
    constructor, 1201
    destructor, 1201
    operator=, 1202
    swap, 1202
basic_istream, 1158, 1190
    constructor, 1192
    destructor, 1192
    gcount, 1196
    get, 1196, 1197
    getline, 1197, 1198
    ignore, 1198
    operator=, 1192
    operator>>, 1193–1196, 1200
    peek, 1199
    putback, 1199
    read, 1199
    readsome, 1199
    seekg, 1200
    swap, 1192
    sync, 1200
    tellg, 1200
    unget, 1199
basic_istream::sentry, 1192
    constructor, 1192
    destructor, 1193
    operator bool, 1193
basic_istream<char>, 1189
basic_istream<wchar_t>, 1189
basic_istreambuf_iterator, 1158
basic_istreamstream, 1158, 1220
    constructor, 1220, 1221

```

```

    operator=, 1221
    rdbuf, 1221
    str, 1221
    swap, 1221
basic_istream<char>, 1214
basic_istream<wchar_t>, 1214
basic_ofstream, 1158, 1234
    close, 1236
    constructor, 1235
    is_open, 1236
    open, 1236
    operator=, 1235
    rdbuf, 1236
    swap, 1236
basic_ofstream<char>, 1225
basic_ofstream<wchar_t>, 1225
basic_ostream, 1158, 1202, 1323
    constructor, 1204
    destructor, 1204
    flush, 1209
    init, 1204
    operator<<, 1206–1209
    operator=, 1204
    put, 1209
    seekp, 1205
    swap, 1204
    tellp, 1205
    write, 1209
basic_ostream::sentry, 1204
    constructor, 1204
    destructor, 1205
    operator bool, 1205
basic_ostream<char>, 1189
basic_ostream<wchar_t>, 1189
basic_ostreambuf_iterator, 1158
basic_ostringstream, 1158, 1221
    constructor, 1222
    operator=, 1222
    rdbuf, 1223
    str, 1223
    swap, 1223
basic_ostringstream<char>, 1214
basic_ostringstream<wchar_t>, 1214
basic_regex, 1300, 1312, 1339
    assign, 1316, 1317
    constants, 1314, 1315
    constructor, 1315, 1316
    flag_type, 1317
    getloc, 1317
    imbue, 1317
    mark_count, 1317
    operator=, 1316
    swap, 1317, 1318
basic_streambuf, 1158, 1180
    constructor, 1182
    destructor, 1182
    eback, 1184
    egptr, 1184
    ep_ptr, 1185
    gbump, 1184
    getloc, 1183
    gp_ptr, 1184
    imbue, 1185
    in_avail, 1183
    operator=, 1184
    overflow, 1188
    pbackfail, 1187
    pbase, 1185
    pbump, 1185
    pptr, 1185
    pubimbue, 1182
    pubseekoff, 1183
    pubseekpos, 1183
    pubsetbuf, 1183
    pubsync, 1183
    sbumpc, 1183
    seekoff, 1185
    seekpos, 1185
    setbuf, 1185, 1219
    setg, 1185
    setp, 1185
    sgetc, 1183
    sgetn, 1183
    showmanyc, 1186
    snextc, 1183
    sputbackc, 1183
    sputc, 1184
    sputn, 1184
    sungetc, 1184
    swap, 1184
    sync, 1186
    uflow, 1187
    underflow, 1186
    xsgetn, 1186
    xspn, 1187
basic_streambuf<char>, 1179
basic_streambuf<wchar_t>, 1179
basic_string, 736, 759, 1215
    append, 748, 749
    assign, 749, 750
    at, 747
    back, 747

```

```

begin, 745
c_str, 755
capacity, 746
cbegin, 745
cend, 745
clear, 746
compare, 758, 759
constructor, 741–744
copy, 754
crbegin, 745
crend, 745
data, 755
empty, 747
end, 745
erase, 752
find, 755, 756
find_first_not_of, 757
find_first_of, 756, 757
find_last_not_of, 758
find_last_of, 757
front, 747
get_allocator, 755
getline, 763, 764
insert, 750–752
length, 746
max_size, 746
operator basic_string_view, 755
operator!=, 761
operator+, 759–761
operator+=, 747, 748
operator<, 762
operator<<, 763
operator<=, 762
operator=, 744, 745
operator==, 761
operator>, 762
operator>=, 762, 763
operator>>, 763
operator[], 747
pop_back, 752
push_back, 749
rbegin, 745
rend, 745
replace, 752–754
reserve, 746
resize, 746
rfind, 756
shrink_to_fit, 746
size, 746
substr, 758
swap, 755, 763

basic_string_view, 768
    at, 771
    back, 771
    begin, 770
    cbegin, 770
    cend, 770
    compare, 772, 773
    const_iterator, 770
    constructor, 770
    copy, 772
    crbegin, 771
    crend, 771
    data, 771
    empty, 771
    end, 770
    find, 773
    find_first_not_of, 774
    find_first_of, 774
    find_last_not_of, 774
    find_last_of, 774
    front, 771
    length, 771
    max_size, 771
    operator!=, 775
    operator<, 775
    operator<<, 776
    operator<=, 776
    operator==, 775
    operator>, 775
    operator>=, 776
    operator[], 771
    rbegin, 771
    remove_prefix, 772
    remove_suffix, 772
    rend, 771
    rfind, 773
    size, 771
    substr, 772
    swap, 772

basic_stringbuf, 1158, 1215
    constructor, 1216
    operator=, 1217
    overflow, 1218
    pbackfail, 1218
    seekoff, 1218
    seekpos, 1219
    str, 1217
    swap, 1217
    underflow, 1218
basic_stringbuf<char>, 1214
basic_stringbuf<wchar_t>, 1214

```

basic_stringstream, 1158, 1223
 constructor, 1224
 operator=, 1224
 rdbuf, 1225
 str, 1225
 swap, 1224
 basic_stringstream<char>, 1214
 basic_stringstream<wchar_t>, 1214
 before
 type_info, 503
 before_begin
 forward_list, 882
 begin, 509
 array, 872
 basic_string, 745
 basic_string_view, 770
 directory_iterator, 1275
 initializer_list, 510
 match_results, 1326
 path, 1262
 recursive_directory_iterator, 1279
 valarray, 1125
 begin(C&), 987
 begin(initializer_list<E>), 510
 begin(T (&)[N]), 987
 bernoulli_distribution, 1087
 constructor, 1088
 p, 1088
 beta, 1151
 gamma_distribution, 1093
 betaf, 1151
 betal, 1151
 bidirectional_iterator_tag, 966
 binary_function
 zombie, 470
 binary_negate, 1474, 1475
 first_argument_type, 1475
 operator(), 1475
 result_type, 1475
 second_argument_type, 1475
 binary_search, 1036
 bind, 667–668
 weak result type, 1474
 bind1st
 zombie, 470
 bind2nd
 zombie, 470
 binder1st
 zombie, 470
 binder2nd
 zombie, 470
 binomial_distribution, 1088
 constructor, 1089
 p, 1089
 t, 1089
 bit_and, 663
 first_argument_type, 1471
 operator(), 663
 result_type, 1471
 second_argument_type, 1471
 bit_and<>, 664
 operator(), 664
 bit_not
 argument_type, 1471
 operator(), 665
 result_type, 1471
 bit_not<>, 665
 operator(), 665
 bit_or, 664
 first_argument_type, 1471
 operator(), 664
 result_type, 1471
 second_argument_type, 1471
 bit_or<>, 664
 operator(), 664
 bit_xor, 664
 first_argument_type, 1471
 operator(), 664
 result_type, 1471
 second_argument_type, 1471
 bit_xor<>, 664
 operator(), 664
 <bitset>, 587
 bitset, 587, 588
 all, 592
 any, 592
 constructor, 589, 590
 count, 592
 flip, 591, 592
 none, 593
 operator!=, 592
 operator<<, 593, 594
 operator<<=, 591
 operator==, 592
 operator>>, 593
 operator>>=, 591
 operator[], 593
 operator&, 593
 operator&=, 590
 operator^, 593
 operator^=, 591
 operator~, 591


```

    operator|, 593
    operator|=, 590
    reset, 591
    set, 591
    size, 592
    test, 592
    to_string, 592
    to_ullong, 592
    to_ulong, 592
bool_constant, 684
boolalpha, 1177
boyer_moore_horspool_searcher, 675
    constructor, 675
    operator(), 675
boyer_moore_searcher, 674
    constructor, 674
    operator(), 674
bsearch, 479, 1049
btowc, 778
BUFSIZ, 1293
byte, 478
    operator<<, 481
    operator<=, 481
    operator>>, 482
    operator>=, 482
    operator&, 482
    operator&=, 482
    operator~, 482
    operator^=, 482
    operator~, 482
    operator|, 482
    operator|=, 482
    to_integer, 482
byte_string
    wstring_convert, 1482

c16rtomb, 780
c32rtomb, 780
c_str
    basic_string, 755
    path, 1257
cacos
    complex, 1059
cacosh
    complex, 1060
call_once, 1387
calloc, 479, 608, 1459
canonical, 1279
capacity
    basic_string, 746
    vector, 895

casin
    complex, 1060
c sinh
    complex, 1060
<cassert>, 459, 517, 829, 1458
catan
    complex, 1060
catanh
    complex, 1060
category
    error_code, 525
    error_condition, 527
    locale, 785
cauchy_distribution, 1097
    a, 1098
    b, 1098
    constructor, 1098
cbefore_begin
    forward_list, 882
cbegin
    basic_string, 745
    basic_string_view, 770
cbegin(const C&), 987
cbrt, 1139
cbrtf, 1139
cbrtl, 1139
<ccomplex>, 1460
<cctype>, 776
ceil, 1139
    duration, 716
    time_point, 720
ceilf, 1139
ceilL, 1139
cend
    basic_string, 745
    basic_string_view, 770
cend(const C&), 987
cerr, 1161
<cerrno>, 471, 517
<cfenv>, 1051
CHAR_BIT, 491
char_class_type
    regex_traits, 1310
CHAR_MAX, 491
CHAR_MIN, 491
char_traits, 728–731
    char_type, 728
    int_type, 728
    off_type, 728
    pos_type, 728
    state_type, 728

```

char_type
 char_traits, 728
 chars_format, 533
 fixed, 533
 general, 533
 hex, 533
 scientific, 533
 chi_squared_distribution, 1096
 constructor, 1097
 n, 1097
 <chrono>, 705
 chrono, 705
 cin, 1161
 <cinatypes>, 1294, 1295
 <ciso646>, 1458
 clamp, 1047
 classic
 locale, 790
 classic_table
 ctype<char>, 797
 clear
 atomic_flag, 1357
 basic_ios, 1176
 basic_string, 746
 error_code, 525
 error_condition, 527
 forward_list, 884
 path, 1255
 clearerr, 1293
 <climits>, 1464
 <locale>, 455, 1458
 clock, 721
 clock_t, 721
 CLOCKS_PER_SEC, 721
 clog, 1161
 close
 basic_filebuf, 1228
 basic_fstream, 1239
 basic_ifstream, 1234
 basic_ofstream, 1236
 messages, 825
 <cmath>, 1139, 1149
 code
 future_error, 1397
 system_error, 529
 <codecvt>, 1479
 codecvt, 797
 always_noconv, 799
 do_always_noconv, 801
 do_encoding, 801
 do_in, 799
 do_length, 801
 do_max_length, 801
 do_out, 799
 do_unshift, 800
 encoding, 799
 in, 799
 length, 799
 max_length, 799
 out, 798
 unshift, 799
 codecvt_byname, 801
 codecvt_mode, 1479
 codecvt_utf16, 1479, 1480
 codecvt_utf8, 1479, 1480
 codecvt_utf8_utf16, 1479, 1480
 collate, 811
 compare, 812
 do_compare, 812
 do_hash, 812
 do_transform, 812
 hash, 812
 transform, 812
 collate_byname, 813
 combine
 locale, 789
 common_type, 700, 710, 713, 714
 comp_ellint_1, 1151
 comp_ellint_1f, 1151
 comp_ellint_1l, 1151
 comp_ellint_2, 1151
 comp_ellint_2f, 1151
 comp_ellint_2l, 1151
 comp_ellint_3, 1152
 comp_ellint_3f, 1152
 comp_ellint_3l, 1152
 compare
 basic_string, 758, 759
 basic_string_view, 772, 773
 collate, 812
 path, 1258
 sub_match, 1319
 compare_exchange_strong
 atomic, 1350
 atomic<integral>, 1350
 atomic<T*>, 1350
 compare_exchange_weak
 atomic, 1350
 atomic<integral>, 1350
 atomic<T*>, 1350
 complex
 literals, 1061

<complex>, 1052, 1053
 complex, 1054
 constructor, 1056
 imag, 1057
 operator!=, 1058
 operator""i, 1061
 operator""if, 1062
 operator""il, 1061
 operator*, 1058
 operator*=, 1057
 operator+, 1058
 operator+=, 1057
 operator-, 1058
 operator-=, 1057
 operator/, 1058
 operator/=: 1057
 operator<<, 1059
 operator==, 1058
 operator>>, 1058
 real, 1056, 1057
 concat
 path, 1255
 <condition_variable>, 1388
 condition_variable, 1389
 constructor, 1390
 destructor, 1390
 notify_all, 1390
 notify_one, 1390
 wait, 1390, 1391
 wait_for, 1391, 1392
 wait_until, 1391, 1392
 condition_variable_any, 1393
 constructor, 1393
 destructor, 1393
 notify_all, 1394
 notify_one, 1394
 wait, 1394
 wait_for, 1395
 wait_until, 1394, 1395
 conj, 1061
 complex, 1059
 conjunction, 701
 const_iterator
 basic_string_view, 770
 const_mem_fun1_ref_t
 zombie, 470
 const_mem_fun1_t
 zombie, 470
 const_mem_fun_ref_t
 zombie, 470
 const_mem_fun_t
 zombie, 470
 const_pointer
 allocator_traits, 603
 const_pointer_cast
 shared_ptr, 629
 const_void_pointer
 allocator_traits, 603
 construct
 allocator, 1476
 allocator_traits, 604
 polymorphic_allocator, 639, 640
 scoped_allocator_adaptor, 650–652
 converted
 wstring_convert, 1482
 copy, 1020
 basic_string, 754
 basic_string_view, 772
 path, 1279, 1280
 copy_backward, 1021
 copy_file, 1281, 1282
 copy_if, 1021
 copy_n, 1021
 copy_options, 1265
 copy_symlink, 1282
 copyfmt
 basic_ios, 1175
 copysign, 1139
 copysignf, 1139
 copysignl, 1139
 cos, 1139
 complex, 1060
 valarray, 1117
 cosf, 1139
 cosh, 1139
 complex, 1060
 valarray, 1117
 coshf, 1139
 coshl, 1139
 cosl, 1139
 count, 1016
 bitset, 592
 duration, 712
 count_if, 1016
 cout, 1161
 crbegin
 basic_string, 745
 basic_string_view, 771
 crbegin(const C& c), 987
 create_directories, 1282
 create_directory, 1283
 create_directory_symlink, 1283

```

create_hard_link, 1283
create_symlink, 1284
cref
    reference_wrapper, 657
crend
    basic_string, 745
    basic_string_view, 771
crend(const C& c), 987
<csetjmp>, 471, 510, 511, 1459
cshift
    valarray, 1115
<csignal>, 510, 511
<cstdalign>, 1458, 1460
<cstdarg>, 471, 510
<cstdbool>, 510, 1458, 1461
<cstddef>, 1458, 1459
<cstdint>, 492
<cstdio>, 1161, 1162, 1228, 1294, 1458
<cstdlib>, 458, 479, 510, 780, 1049, 1105, 1149,
    1458, 1459, 1461
<cstring>, 455, 777, 1458, 1464, 1468
<ctgmath>, 1461
<ctime>, 510, 721, 722, 783, 1458
ctime, 721
ctype, 791
    do_is, 793
    do_narrow, 794
    do_scan_not, 793
    do_tolower, 793
    do_toupper, 793
    do_widen, 794
    is, 792
    narrow, 793
    scan_is, 792
    scan_not, 792
    tolower, 793
    toupper, 793
    widen, 793
<ctype.h>, 777
ctype<char>, 795
    classic_table, 797
    constructor, 796
    ctype<char>, 796
    destructor, 796
    do_narrow, 797
    do_tolower, 797
    do_toupper, 797
    do_widen, 797
    is, 796
    narrow, 797
    scan_is, 796
    scan_not, 796
    table, 797
    tolower, 796
    toupper, 796
    widen, 796
ctype_base, 791
    do_scan_is, 793
ctype_byname, 794
<cuchar>, 471, 780, 1458
curr_symbol
    moneypunct, 823
current_exception, 507
current_path, 1284
cv_status, 1388
<cwchar>, 471, 778, 780, 1458
<cwctype>, 471, 777
cyl_bessel_i, 1152
cyl_bessel_if, 1152
cyl_bessel_il, 1152
cyl_bessel_j, 1152
cyl_bessel_jf, 1152
cyl_bessel_jl, 1152
cyl_bessel_k, 1152
cyl_bessel_kf, 1152
cyl_bessel_kl, 1152
cyl_neumann, 1153
cyl_neumannf, 1153
cyl_neumannl, 1153
data
    array, 873
    basic_string, 755
    basic_string_view, 771
    vector, 897
data(C& c), 988
data(initializer_list<E>), 988
data(T (&array)[N]), 988
date_order
    time_get, 814
DBL_DECIMAL_DIG, 491
DBL_DIG, 491
DBL_EPSILON, 491
DBL_HAS_SUBNORM, 491
DBL_MANT_DIG, 491
DBL_MAX, 491
DBL_MAX_10_EXP, 491
DBL_MAX_EXP, 491
DBL_MIN, 491
DBL_MIN_10_EXP, 491
DBL_MIN_EXP, 491
DBL_TRUE_MIN, 491

```

deallocate
 allocator, 605
 allocator_traits, 604
 memory_resource, 637
 polymorphic_allocator, 639
 scoped_allocator_adaptor, 650
 dec, 1178, 1207
 decay, 699
 DECAY_COPY, 1362
 DECIMAL_DIG, 491
 decimal_point
 moneypunct, 823
 numpunct, 810
 declare_no_pointers, 601
 declare_reachable, 600
 declval, 536
 default_delete
 constructor, 611
 operator(), 611
 default_error_condition
 error_category, 522, 523
 error_code, 525
 default_random_engine, 1082
 default_searcher, 673
 constructor, 673
 operator(), 673
 defaultfloat, 1179
 defer_lock, 1376
 defer_lock_t, 1376
 delete
 operator, 472, 496–499, 609
 denorm_absent, 484
 denorm_indeterminate, 484
 denorm_min
 numeric_limits, 488
 denorm_present, 484
 densities
 piecewise_constant_distribution, 1103
 piecewise_linear_distribution, 1104
 depth
 recursive_directory_iterator, 1278
 <deque>, 869
 deque, 874
 constructor, 876, 877
 shrink_to_fit, 877
 swap, 878
 destroy, 608
 allocator, 1476
 allocator_traits, 604
 polymorphic_allocator, 640
 scoped_allocator_adaptor, 652
 destroy_at, 608
 destroy_n, 608
 detach
 thread, 1366
 difference_type
 allocator_traits, 604
 pointer_traits, 600
 difftime, 721
 digits
 numeric_limits, 485
 digits10
 numeric_limits, 486
 directory_entry, 1269
 assign, 1271
 constructor, 1271
 exists, 1271
 file_size, 1272
 hard_link_count, 1272
 is_block_file, 1271
 is_character_file, 1272
 is_directory, 1272
 is_fifo, 1272
 is_other, 1272
 is_regular_file, 1272
 is_socket, 1272
 is_symlink, 1272
 last_write_time, 1273
 operator const path&, 1271
 operator!=, 1273
 operator<, 1273
 operator<=, 1273
 operator==, 1273
 operator>, 1273
 operator>=, 1273
 path, 1271
 refresh, 1271
 replace_filename, 1271
 status, 1273
 symlink_status, 1273
 directory_iterator, 1273
 constructor, 1275
 increment, 1275
 operator++, 1275
 operator=, 1275
 directory_options, 1268
 disable_recursion_pending
 recursive_directory_iterator, 1278
 discard_block_engine, 1078
 constructor, 1079
 discrete_distribution, 1100
 constructor, 1100, 1101

probabilities, 1101
 disjunction, 702
 distance, 967
 div, 479, 1294
 div_t, 479
 divides, 659
 first_argument_type, 1471
 operator(), 659
 result_type, 1471
 second_argument_type, 1471
 divides<>, 659
 operator(), 659
 do_allocate
 memory_resource, 637
 monotonic_buffer_resource, 646
 synchronized_pool_resource, 644
 unsynchronized_pool_resource, 644
 do_always_noconv
 codecvt, 801
 do_close
 message, 825
 do_compare
 collate, 812
 do_curr_symbol
 moneypunct, 824
 do_date_order
 time_get, 815
 do_deallocate
 memory_resource, 637
 monotonic_buffer_resource, 646
 synchronized_pool_resource, 644
 unsynchronized_pool_resource, 644
 do_decimal_point
 moneypunct, 823
 numpunct, 811
 do_encoding
 codecvt, 801
 do_falsename
 numpunct, 811
 do_frac_digits
 moneypunct, 824
 do_get
 messages, 825
 money_get, 819
 num_get, 803, 805
 time_get, 816
 do_get_date
 time_get, 816
 do_get_monthname
 time_get, 816
 do_get_time
 time_get, 815
 do_get_weekday
 time_get, 816
 do_get_year
 time_get, 816
 do_grouping
 moneypunct, 823
 numpunct, 811
 do_hash
 collate, 812
 do_in
 codecvt, 799
 do_is
 ctype, 793
 do_is_equal
 memory_resource, 637
 monotonic_buffer_resource, 646
 synchronized_pool_resource, 644
 unsynchronized_pool_resource, 644
 do_length
 codecvt, 801
 do_max_length
 codecvt, 801
 do_narrow, 797
 ctype, 794
 ctype<char>, 797
 do_neg_format
 moneypunct, 824
 do_negative_sign
 moneypunct, 824
 do_open
 messages, 825
 do_out
 codecvt, 799
 do_pos_format
 moneypunct, 824
 do_positive_sign
 moneypunct, 824
 do_put
 money_put, 821
 num_put, 807, 809
 time_put, 818
 do_scan_is
 ctype_base, 793
 do_scan_not
 ctype, 793
 do_thousands_sep
 moneypunct, 823
 numpunct, 811
 do_tolower
 ctype, 793

```

    ctype<char>, 797
do_toupper
    ctype, 793
    ctype<char>, 797
do_transform
    collate, 812
do_truename
    numpunct, 811
do_unshift
    codecvt, 800
do_widen, 797
    ctype, 794
    ctype<char>, 797
domain_error, 513, 514
    constructor, 514
double_t, 1139
duration, 710
    abs, 717
    ceil, 716
    constructor, 712
    count, 712
    duration_cast, 715
    floor, 716
    max, 713
    min, 713
    operator!=, 715
    operator""h, 716
    operator""min, 716
    operator""ms, 717
    operator""ns, 717
    operator""s, 717
    operator""us, 717
    operator*, 714
    operator==, 713
    operator+, 712, 718, 719
    operator++, 712, 713
    operator+=, 713
    operator-, 712, 719
    operator-=, 713
    operator--, 713
    operator/, 714
    operator/=: 713
    operator<, 715
    operator<=: 715
    operator==, 715
    operator>, 715
    operator>=: 715
    operator%, 714
    operator%=: 713
    round, 716
    zero, 713
    duration_cast, 715
    duration_values, 709
        max, 710
        min, 710
        zero, 710
dynamic_pointer_cast
    shared_ptr, 628

E2BIG, 517
EACCES, 517
EADDRINUSE, 517
EADDRNOTAVAIL, 517
EAFNOSUPPORT, 517
EAGAIN, 517
EALREADY, 517
eback
    basic_streambuf, 1184
EBADF, 517
EBADMSG, 517
EBUSY, 517
ec
    from_chars_result, 533
    to_chars_result, 533
ECANCELED, 517
ECHILD, 517
ECONNABORTED, 517
ECONNREFUSED, 517
ECONNRESET, 517
EDEADLK, 517
EDESTADDRREQ, 517
EDOM, 517
EEXIST, 517
EFAULT, 517
EFBIG, 517
egptr
    basic_streambuf, 1184
EHOSTUNREACH, 517
EIDRM, 517
EILSEQ, 517
EINPROGRESS, 517
EINTR, 517
EINVAL, 517
EIO, 517
EISCONN, 517
EISDIR, 517
element_type
    pointer_traits, 600
ellint_1, 1153
ellint_1f, 1153
ellint_1l, 1153
ellint_2, 1153

```

ellint_2f, 1153
 ellint_2l, 1153
 ellint_3, 1154
 ellint_3f, 1154
 ellint_3l, 1154
 ELOOP, 517
 EMFILE, 517
 EMLINK, 517
 emplace
 any, 585
 deque, 877
 optional, 563
 priority_queue, 952
 variant, 576, 577
 emplace_after
 forward_list, 883
 emplace_front
 forward_list, 882
 empty, 966
 basic_string, 747
 basic_string_view, 771
 match_results, 1326
 path, 1259
 empty(C& c), 988
 empty(initializer_list<E>), 988
 empty(T (&array)[N]), 988
 EMSGSIZE, 517
 enable_if, 699
 enable_shared_from_this, 633
 constructor, 633
 operator=, 633
 shared_from_this, 633
 weak_from_this, 633
 ENAMETOOLONG, 517
 encoding
 codecvt, 799
 end, 509
 array, 872
 basic_string, 745
 basic_string_view, 770
 directory_iterator, 1275
 initializer_list, 510
 match_results, 1327
 path, 1262
 recursive_directory_iterator, 1279
 valarray, 1125
 end(C&), 987
 end(initializer_list<E>), 510
 end(T (&)[N]), 987
 endl, 1207, 1209
 ends, 1209
 ENETDOWN, 517
 ENETRESET, 517
 ENETUNREACH, 517
 ENFILE, 517
 ENOBUFS, 517
 ENODATA, 517
 ENODEV, 517
 ENOENT, 517
 ENOEXEC, 517
 ENOLCK, 517
 ENOLINK, 517
 ENOMEM, 517
 ENOMSG, 517
 ENOPROTOOPT, 517
 ENOSPC, 517
 ENOSR, 517
 ENOSTR, 517
 ENOSYS, 517
 ENOTCONN, 517
 ENOTDIR, 517
 ENOTEMPTY, 517
 ENOTRECOVERABLE, 517
 ENOTSOCK, 517
 ENOTSUP, 517
 ENOTTY, 517
 entropy
 random_device, 1083
 ENXIO, 517
 EOF, 1293
 eof
 basic_ios, 1176
 EOPNOTSUPP, 517
 EOVERFLOW, 517
 EOWNERDEAD, 517
 EPERM, 517
 EPIPE, 517
 ep_ptr
 basic_streambuf, 1185
 EPROTO, 517
 EPROTONOSUPPORT, 517
 EPROTOTYPE, 517
 epsilon
 numeric_limits, 486
 eq
 char_traits, 755–758
 equal, 1017
 istreambuf_iterator, 985
 equal_range, 1035
 equal_to, 660
 first_argument_type, 1471
 operator(), 660

- result_type, 1471
- second_argument_type, 1471
- equal_to<>, 660
 - operator(), 660
- equivalent, 1284
 - error_category, 522, 523
- ERANGE, 517
- erase
 - basic_string, 752
 - deque, 878
 - list, 890
 - vector, 897
- erase_after
 - forward_list, 883
- erased
 - forward_list, 883
- erf, 1139
- erfc, 1139
- erfcf, 1139
- erfcl, 1139
- erff, 1139
- erfl, 1139
- EROFS, 517
- errc, 519
 - make_error_code, 525
 - make_error_condition, 527
- errno, 517
- <errno.h>, 517
- error_category, 519, 522
 - constructor, 522
 - default_error_condition, 522, 523
 - destructor, 522
 - equivalent, 522, 523
 - message, 522
 - name, 522, 523
 - operator!=, 523
 - operator<, 523
 - operator==, 523
- error_code, 519, 524
 - assign, 525
 - category, 525
 - clear, 525
 - constructor, 524
 - default_error_condition, 525
 - message, 525
 - operator bool, 525
 - operator!=, 528
 - operator<, 527
 - operator<<, 525
 - operator=, 525
 - operator==, 527
- value, 525
- error_condition, 519, 526
 - assign, 526
 - category, 527
 - clear, 527
 - constructor, 526
 - message, 527
 - operator bool, 527
 - operator!=, 528
 - operator<, 527
 - operator=, 527
 - operator==, 527, 528
 - value, 527
- error_type, 1308, 1309
- ESPIPE, 517
- ESRCH, 517
- ETIME, 517
- ETIMEDOUT, 517
- ETXTBSY, 517
- EWOULDBLOCK, 517
- <exception>, 504, 1470
- exception, 505
 - constructor, 505
 - destructor, 505
 - operator=, 505
 - what, 505
- exception_ptr, 507
- exceptions
 - basic_ios, 1176
- exchange, 535
 - atomic, 1350
 - atomic<integral>, 1350
 - atomic<T*>, 1350
- exclusive_scan, 1133, 1134
- EXDEV, 517
- <execution>, 723
- execution
 - par, 725
 - par_unseq, 725
 - seq, 725
- execution::parallel_policy, 724
- execution::parallel_unsequenced_policy, 724
- execution::sequenced_policy, 724
- exists, 1285
 - directory_entry, 1271
- exit, 66, 69, 151, 458, 479, 493, 501
- EXIT_FAILURE, 479
- EXIT_SUCCESS, 479
- exp, 1139
 - complex, 1060

- valarray, 1117
- exp2, 1139
- exp2f, 1139
- exp2l, 1139
- expf, 1139
- expint, 1154
- expintf, 1154
- expintl, 1154
- expired
 - weak_ptr, 631
- expl, 1139
- expm1, 1139
- expm1f, 1139
- expm1l, 1139
- exponential_distribution, 1091
 - constructor, 1092
 - lambda, 1092
- extension
 - path, 1259
- extent, 693
- extreme_value_distribution, 1094
 - a, 1094
 - b, 1095
 - constructor, 1094
- fabs, 1139
- fabsf, 1139
- fabsl, 1139
- facet
 - locale, 786
- fail
 - basic_ios, 1176
- failed
 - ostreambuf_iterator, 986
- false_type, 684
- falsename
 - numpunct, 810
- fclose, 1228, 1293
- fdim, 1139
- fdimf, 1139
- fdiml, 1139
- FE_ALL_EXCEPT, 1051
- FE_DFL_ENV, 1051
- FE_DIVBYZERO, 1051
- FE_DOWNWARD, 1051
- FE_INEXACT, 1051
- FE_INVALID, 1051
- FE_OVERFLOW, 1051
- FE_TONEAREST, 1051
- FE_TOWARDZERO, 1051
- FE_UNDERFLOW, 1051
- FE_UPWARD, 1051
- feclearexcept, 1051
- fegetenv, 1051
- fegetexceptflag, 1051
- fegetround, 1051
- feholdexcept, 1051
- fenv_t, 1051
- feof, 1293
- feraiseexcept, 1051
- ferror, 1293
- fesetenv, 1051
- fesetexceptflag, 1051
- fesetround, 1051
- fetch_add
 - atomic<integral>, 1353
 - atomic<T*>, 1355
- fetch_and
 - atomic<integral>, 1353
- fetch_or
 - atomic<integral>, 1353
- fetch_sub
 - atomic<integral>, 1353
 - atomic<T*>, 1355
- fetch_xor
 - atomic<integral>, 1353
- fetestexcept, 1051
- feupdateenv, 1051
- fexcept_t, 1051
- fflush, 1293
- fgetc, 1293
- fgetpos, 1293
- fgets, 1293
- fgetwc, 778
- fgetws, 778
- FILE, 1293
- file_size, 1285
 - directory_entry, 1272
- file_status, 1268
 - constructor, 1268
 - permissions, 1268, 1269
 - type, 1268, 1269
- file_type, 1265
- filebuf, 1158, 1225
- filename
 - path, 1259
- FILENAME_MAX, 1293
- <filesystem>, 1242
- filesystem_error, 1263
 - constructor, 1264
 - path1, 1264
 - path2, 1264

- what, 1265
- fill, 1025
 - array, 873
 - basic_ios, 1174, 1175
- fill_n, 1025
- find, 1013
 - basic_string, 755, 756
 - basic_string_view, 773
- find_end, 1014
- find_first_not_of
 - basic_string, 757
 - basic_string_view, 774
- find_first_of, 1015
 - basic_string, 756, 757
 - basic_string_view, 774
- find_if, 1013
- find_if_not, 1013
- find_last_not_of
 - basic_string, 758
 - basic_string_view, 774
- find_last_of
 - basic_string, 757
 - basic_string_view, 774
- first_argument_type
 - binary_negate, 1475
 - bit_and, 1471
 - bit_or, 1471
 - bit_xor, 1471
 - divides, 1471
 - equal_to, 1471
 - function, 1471
 - greater, 1471
 - greater_equal, 1471
 - less, 1471
 - less_equal, 1471
 - logical_and, 1471
 - logical_or, 1471
 - map::value_compare, 1474
 - mem_fn, 1474
 - minus, 1471
 - modulus, 1471
 - multimap::value_compare, 1474
 - multiplies, 1471
 - not_equal_to, 1471
 - owner_less, 1471
 - plus, 1471
 - reference_wrapper, 1473
- fisher_f_distribution, 1098
 - constructor, 1099
 - m, 1099
 - n, 1099
- fixed, 1178
- fixed
 - chars_format, 533
- flag_type
 - basic_regex, 1317
- flags
 - ios_base, 791, 1168
- flip
 - bitset, 591, 592
 - vector<bool>, 900
- float_denorm_style, 483, 484
 - numeric_limits, 487
- float_round_style, 483
- float_t, 1139
- floor, 1139
 - duration, 716
 - time_point, 720
- floorf, 1139
- floorl, 1139
- FLT_DECIMAL_DIG, 491
- FLT_DIG, 491
- FLT_EPSILON, 491
- FLT_EVAL_METHOD, 491
- FLT_HAS_SUBNORM, 491
- FLT_MANT_DIG, 491
- FLT_MAX, 491
- FLT_MAX_10_EXP, 491
- FLT_MAX_EXP, 491
- FLT_MIN, 491
- FLT_MIN_10_EXP, 491
- FLT_MIN_EXP, 491
- FLT_RADIX, 491
- FLT_ROUNDS, 491
- FLT_TRUE_MIN, 491
- flush, 1168, 1192, 1204, 1209
 - basic_ostream, 1209
- fma, 1139
- fmaf, 1139
- fmal, 1139
- fmax, 1139
- fmaxf, 1139
- fmaxl, 1139
- fmin, 1139
- fminf, 1139
- fminl, 1139
- fmod, 1139
- fmodf, 1139
- fmodl, 1139
- fmtflags
 - ios_base, 1166, 1210
- fopen, 1228, 1293

FOPEN_MAX, 1293
 for_each, 1012, 1013
 for_each_n, 1013
 format
 match_results, 1327
 format_default, 1307, 1308
 format_first_only, 1307, 1308, 1332
 format_no_copy, 1307, 1308, 1332
 format_sed, 1307, 1308
 forward, 535
 forward_as_tuple, 550
 forward_iterator_tag, 966
 <forward_list>, 870
 forward_list
 before_begin, 882
 cbefore_begin, 882
 clear, 884
 constructor, 881, 882
 emplace_after, 883
 emplace_front, 882
 erase_after, 883
 erased, 883
 front, 882
 insert_after, 882, 883
 merge, 885
 pop, 882
 push_front, 882
 remove, 884
 remove_if, 884
 resize, 883
 reverse, 885
 sort, 885
 splice_after, 884
 swap, 886
 unique, 885
 FP_FAST_FMA, 1139
 FP_FAST_FMAF, 1139
 FP_FAST_FMAL, 1139
 FP_ILOGB0, 1139
 FP_ILOGBNAN, 1139
 FP_INFINITE, 1139
 FP_NAN, 1139
 FP_NORMAL, 1139
 FP_SUBNORMAL, 1139
 FP_ZERO, 1139
 fpclassify, 1139
 fpos, 1163, 1171
 state, 1171
 fpos_t, 1293
 fprintf, 1293
 fputc, 1293
 fputs, 1293
 fputwc, 778
 fputws, 778
 frac_digits
 moneypunct, 823
 fread, 1293
 free, 479, 609
 freeze
 ostrstream, 1469
 strstream, 1470
 strstreambuf, 1464
 freopen, 1293
 frexp, 1139
 frexpf, 1139
 frexpl, 1139
 from_bytes
 wstring_convert, 1482
 from_chars, 538
 from_chars_result, 533
 ec, 533
 ptr, 533
 from_time_t
 system_clock, 721
 front
 basic_string, 747
 basic_string_view, 771
 forward_list, 882
 front_insert_iterator, 973
 constructor, 974
 operator*, 974
 operator++, 974
 operator=, 974
 front_inserter, 974
 fscanf, 1293
 fseek, 1228, 1293
 fsetpos, 1293
 <fstream>, 1225
 fstream, 1158, 1225
 ftell, 1293
 function, 669
 argument_type, 1471
 constructor, 670
 destructor, 672
 first_argument_type, 1471
 invocation, 672
 operator bool, 672
 operator!=, 672
 operator(), 672
 operator=, 671
 operator==, 672
 result_type, 1471

- second_argument_type, 1471
- swap, 672
- target, 672
- target_type, 672
- <functional>, 653, 1474
- <future>, 1395
- future, 1401
 - constructor, 1402
 - get, 1403
 - operator=, 1402
 - share, 1402
 - valid, 1403
 - wait, 1403
 - wait_for, 1403
 - wait_until, 1403
- future_category, 1397
- future_errc, 1395
 - make_error_code, 1397
 - make_error_condition, 1397
- future_error, 1397
 - code, 1397
 - constructor, 1397
 - what, 1397
- fwide, 778
- fwprintf, 778
- fwrite, 1293
- fwscanf, 778
- gamma_distribution, 1092
 - alpha, 1093
 - beta, 1093
 - constructor, 1093
- gbump
 - basic_streambuf, 1184
- gcd, 1139
- gcount
 - basic_istream, 1196
- general
 - chars_format, 533
- GENERALIZED_NONCOMMUTATIVE_SUM, 1050
- GENERALIZED_SUM, 1050
- generate, 1025
 - seed_seq, 1084
- generate_canonical, 1085
- generate_n, 1025
- generic_category, 522, 523
- generic_string
 - path, 1257, 1258
- generic_u16string
 - path, 1258
- generic_u32string
 - path, 1258
- generic_u8string
 - path, 1258
- generic_wstring
 - path, 1258
- geometric_distribution, 1089
 - constructor, 1089
 - p, 1090
- get
 - array, 874
 - basic_istream, 1196, 1197
 - future, 1403
 - messages, 825
 - money_get, 819
 - num_get, 803
 - pair, 542, 543
 - reference_wrapper, 657
 - shared_future, 1405
 - shared_ptr, 626
 - time_get, 815
 - tuple, 552, 553
 - unique_ptr, 615
 - variant, 578, 579
- get_allocator
 - basic_string, 755
 - match_results, 1327
- get_date
 - time_get, 814
- get_default_resource, 641
- get_deleter
 - shared_ptr, 629
 - unique_ptr, 615
- get_future
 - packaged_task, 1409
 - promise, 1400
- get_id
 - this_thread, 1366
 - thread, 1366
- get_if, 579
- get_money, 1211
- get_monthname
 - time_get, 814
- get_new_handler, 472, 501
- get_pointer_safety, 601
- get_temporary_buffer, 1478
- get_terminate, 472, 506
- get_time, 1212
 - time_get, 814
- get_unexpected
 - zombie, 470
- get_weekday

```

    time_get, 814
get_year
    time_get, 814
getc, 1293
getchar, 1293
getenv, 479, 510
getline
    basic_istream, 1197, 1198
    basic_string, 763, 764
getloc, 1312
    basic_regex, 1317
    basic_streambuf, 1183
    ios_base, 1169
getwc, 778
getwchar, 778
global
    locale, 790
gmtime, 721
good
    basic_ios, 1176
gptr
    basic_streambuf, 1184
greater, 661
    first_argument_type, 1471
    operator(), 661
    result_type, 1471
    second_argument_type, 1471
greater<>, 661
    operator(), 661
greater_equal, 661
    first_argument_type, 1471
    operator(), 662
    result_type, 1471
    second_argument_type, 1471
greater_equal<>, 662
    operator(), 662
grouping
    moneypunct, 823
    numpunct, 810
gslice, 1119
    constructor, 1121
    size, 1121
    start, 1121
    stride, 1121
gslice_array, 1121, 1122
    operator*=, 1122
    operator+=, 1122
    operator-=, 1122
    operator/=: 1122
    operator<<=: 1122
    operator=, 1122
    operator>>=: 1122
    operator%=: 1122
    operator&=: 1122
    operator^=: 1122
    operator|=, 1122
hard_link_count, 1285
    directory_entry, 1272
hardware_concurrency
    thread, 1366
hardware_constructive_interference_size,
    502
hardware_destructive_interference_size,
    502
has_denorm_loss
    numeric_limits, 487
has_extension
    path, 1260
has_facet
    locale, 790
has_filename
    path, 1260
has_infinity
    numeric_limits, 487
has_parent_path
    path, 1260
has_quiet_NaN
    numeric_limits, 487
has_relative_path
    path, 1260
has_root_directory
    path, 1260
has_root_name
    path, 1260
has_root_path
    path, 1260
has_signaling_NaN
    numeric_limits, 487
has_stem
    path, 1260
has_unique_object_representations, 692, 693
has_value
    any, 586
    optional, 564
has_virtual_destructor, 692
hash, 676
    argument_type, 1474
    collate, 812
    error_code, 528
    monostate, 581
    optional, 568

```

- result_type, 1474
- shared_ptr, 635
- string, 766
- string_view, 776
- thread::id, 1364
- type_index, 723
- u16string, 766
- u16string_view, 776
- u32string, 766
- u32string_view, 776
- unique_ptr, 635
- variant, 581
- wstring, 766
- wstring_view, 776
- hash_code, 593
 - type_index, 723
 - type_info, 503
- hash_value
 - path, 1262
- hermite, 1154
- hermitef, 1154
- hermitel, 1154
- hex, 1178
- hex
 - chars_format, 533
- hexfloat, 1179
- high_resolution_clock, 721
- holds_alternative, 578
- HUGE_VAL, 1139
- HUGE_VALF, 1139
- HUGE_VALL, 1139
- hypot, 1139
 - 3-argument form, 1150
- hypotf, 1139
- hypotl, 1139
- id
 - locale, 788
- ifstream, 1158, 1225
- ignore, 550
 - basic_istream, 1198
- ilogb, 1139
- ilogbf, 1139
- ilogbl, 1139
- imag, 1061
 - complex, 1057, 1059
- imaxabs, 1294
- imaxdiv, 1294
- imaxdiv_t, 1294
- imbue, 1312
 - basic_filebuf, 1231
- basic_ios, 1174
- basic_regex, 1317
- basic_streambuf, 1185
- ios_base, 1169
- in
 - codecvt, 799
- in_avail
 - basic_streambuf, 1183
- includes, 1040
- inclusive_scan, 1134, 1135
- increment
 - directory_iterator, 1275
 - recursive_directory_iterator, 1278
- independent_bits_engine, 1079
- index
 - variant, 577
- index_sequence, 531
- index_sequence_for, 531
- indirect_array, 1124
 - operator*=, 1124
 - operator+=, 1124
 - operator-=, 1124
 - operator/=: 1124
 - operator<<=: 1124
 - operator=: 1124, 1125
 - operator>>=: 1124
 - operator[], 1124
 - operator%=: 1124
 - operator&=: 1124
 - operator^=: 1124
 - operator|=, 1124
- INFINITY, 1139
- infinity
 - numeric_limits, 487
- init
 - basic_ios, 1173, 1192
 - basic_ostream, 1204
- <initializer_list>, 509
- initializer_list, 509
 - begin, 510
 - constructor, 509
 - end, 510
 - size, 510
- inner_allocator
 - scoped_allocator_adaptor, 650
- inner_allocator_type
 - scoped_allocator_adaptor, 649
- inner_product, 1131
- inplace_merge, 1039
- input_iterator_tag, 966
- insert

```

    basic_string, 750–752
    deque, 877
    list, 890
    map, 907
    multimap, 913
    unordered_map, 929
    unordered_multimap, 935
    vector, 897
insert_after
    forward_list, 882, 883
insert_iterator, 975
    constructor, 975
    operator*, 975
    operator++, 976
    operator=, 975
insert_or_assign
    map, 908
    unordered_map, 930
insertter, 976
int16_t, 492
int32_t, 492
int64_t, 492
int8_t, 492
int_fast16_t, 492
int_fast32_t, 492
int_fast64_t, 492
int_fast8_t, 492
int_least16_t, 492
int_least32_t, 492
int_least64_t, 492
int_least8_t, 492
INT_MAX, 491
INT_MIN, 491
int_type
    char_traits, 728
    wstring_convert, 1483
integer_sequence, 538
integral_constant, 684
internal, 1178
intervals
    piecewise_constant_distribution, 1103
    piecewise_linear_distribution, 1104
intmax_t, 492
intptr_t, 492
<inttypes.h>, 1295
invalid_argument, 513, 514, 589, 590
    constructor, 514
INVOKE, 655, 656
invoke, 656
io_errc, 1162
    make_error_code, 1179
    make_error_condition, 1179
<iomanip>, 1189
<ios>, 1162
ios, 1158, 1163
ios_base, 1163
    constructor, 1171
    destructor, 1171
    failure, 1166
    flags, 1168
    fmtflags, 1166
    getloc, 1169
    imbue, 1169
    Init, 1168
    iostate, 1166
    iword, 1170
    openmode, 1166
    precision, 1169
    pword, 1170
    register_callback, 1170
    seekdir, 1166
    setf, 1168
    sync_with_stdio, 1169
    unsetf, 1169
    width, 1169
    xalloc, 1170
ios_base::failure, 1166
    constructor, 1166
ios_base::Init, 1168
    constructor, 1168
    destructor, 1168
<iosfwd>, 1158
iostate
    ios_base, 1166
<iostream>, 1160
iostream_category, 1179
iota, 1139
is
    ctype, 792
    ctype<char>, 796
is_absolute
    path, 1260
is_abstract, 686
is_aggregate_signed
    class, 686
is_always_equal
    allocator_traits, 604
    scoped_allocator_adaptor, 649
is_always_lock_free
    atomic, 1350
    atomic<integral>, 1350
    atomic<T*>, 1350

```


is_arithmetic, 685
 is_array, 684
 is_assignable, 688
 is_base_of, 694
 is_bind_expression, 666
 is_block_file, 1285, 1286
 directory_entry, 1271
 is_bounded
 numeric_limits, 488
 is_character_file, 1286
 directory_entry, 1272
 is_class, 685
 is_compound, 685
 is_const, 686
 is_constructible, 687, 692
 is_convertible, 694, 695
 is_copy_assignable, 688
 is_copy_constructible, 687
 is_default_constructible, 687
 is_destructible, 689
 is_directory, 1286
 directory_entry, 1272
 is_empty
 class, 686
 function, 1286
 is_enum, 685
 is_equal
 memory_resource, 637
 is_error_code_enum, 519
 is_error_condition_enum, 519
 is_exact
 numeric_limits, 486
 is_execution_policy, 724
 is_fifo, 1286, 1287
 directory_entry, 1272
 is_final, 686
 is_floating_point, 684
 is_function, 685
 is_fundamental, 685
 is_heap, 1044
 is_heap_until, 1045
 is_iec559
 numeric_limits, 488
 is_integer
 numeric_limits, 486
 is_integral, 684
 is_invocable, 694
 is_invocable_r, 694
 is_literal_type, 1478
 is_lock_free
 atomic, 1350
 atomic<integral>, 1350
 atomic<T*>, 1350
 is_lvalue_reference, 684
 is_member_function_pointer, 685
 is_member_object_pointer, 685
 is_member_pointer, 685
 is_modulo
 numeric_limits, 488
 is_move_assignable, 688
 is_move_constructible, 687
 is_nothrow_assignable, 691
 is_nothrow_constructible, 691
 is_nothrow_copy_assignable, 691
 is_nothrow_copy_constructible, 691
 is_nothrow_default_constructible, 691
 is_nothrow_destructible, 692
 is_nothrow_invocable, 694
 is_nothrow_invocable_r, 694
 is_nothrow_move_assignable, 691
 is_nothrow_move_constructible, 691
 is_nothrow_swappable, 691
 is_nothrow_swappable_with, 691
 is_null_pointer, 684
 is_object, 685
 is_open
 basic_filebuf, 1228
 basic_fstream, 1238
 basic_ifstream, 1234
 basic_ofstream, 1236
 is_other, 1287
 directory_entry, 1272
 is_partitioned, 1036
 is_permutation, 1018
 is_placeholder, 666
 is_pod, 686
 is_pointer, 684
 is_polymorphic, 686
 is_reference, 685
 is_regular_file, 1287
 directory_entry, 1272
 is_relative
 path, 1260
 is_rvalue_reference, 684
 is_scalar, 685
 is_signed
 class, 687
 numeric_limits, 486
 is_socket, 1287
 directory_entry, 1272
 is_sorted, 1033
 is_sorted_until, 1033

is_standard_layout, 686
 is_swappable, 689
 is_swappable_with, 689
 is_symlink, 1287
 directory_entry, 1272
 is_trivial, 686
 is_trivially_assignable, 690
 is_trivially_constructible, 690
 is_trivially_copy_assignable, 690
 is_trivially_copy_constructible, 690
 is_trivially_copyable, 686
 is_trivially_default_constructible, 690
 is_trivially_destructible, 690
 is_trivially_move_assignable, 690
 is_trivially_move_constructible, 690
 is_union, 685
 is_unsigned, 687
 is_void, 684
 is_volatile, 686
 isalnum, 776, 790
 isalpha, 776, 790
 isblank, 776, 790
 iscntrl, 776, 790
 isctype
 regex_traits, 1311
 regular expression traits, 1340
 isdigit, 776, 790
 isfinite, 1139
 isgraph, 776, 790
 isgreater, 1139
 isgreaterequal, 1139
 isinf, 1139
 isless, 1139
 islessequal, 1139
 islessgreater, 1139
 islower, 776, 790
 isnan, 1139
 isnormal, 1139
 <iso646.h>, 1458
 isprint, 776, 790
 ispunct, 776, 790
 isspace, 776, 790
 <istream>, 1188
 istream, 1158, 1189
 istream_iterator, 980
 constructor, 981
 destructor, 981
 operator!=, 982
 operator*, 981
 operator++, 982
 operator->, 982
 operator==, 982
 istreambuf_iterator, 983
 constructor, 985
 equal, 985
 operator!=, 985
 operator*, 985
 operator++, 985
 operator==, 985
 istringstream, 1158, 1214
 istrstream, 1467
 constructor, 1467
 rdbuf, 1468
 str, 1468
 isunordered, 1139
 isupper, 776, 790
 iswalnum, 777
 iswalpha, 777
 iswblank, 777
 iswcntrl, 777
 iswctype, 777
 iswdigit, 777
 iswgraph, 777
 iswlower, 777
 iswprint, 777
 iswpunct, 777
 iswspace, 777
 iswupper, 777
 iswxdigit, 777
 isxdigit, 776, 790
 iter_swap, 1023
 <iterator>, 961, 1479
 iterator, 1470, 1479
 iterator_traits, 964
 iword
 ios_base, 1170

 jmp_buf, 511
 join
 thread, 1365
 joinable
 thread, 1365

 k
 negative_binomial_distribution, 1090
 kill_dependency, 1348
 knuth_b, 1082

 L_tmpnam, 1293
 labs, 479
 laguerre, 1154
 laguerref, 1154

laguerrel, 1154
 lambda
 exponential_distribution, 1092
 last_write_time, 1288
 directory_entry, 1273
 launder, 501
 LC_ALL, 829
 LC_COLLATE, 829
 LC_CTYPE, 829
 LC_MONETARY, 829
 LC_NUMERIC, 829
 LC_TIME, 829
 lcm, 1139
 lconv, 829
 LDBL_DECIMAL_DIG, 491
 LDBL_DIG, 491
 LDBL_EPSILON, 491
 LDBL_HAS_SUBNORM, 491
 LDBL_MANT_DIG, 491
 LDBL_MAX, 491
 LDBL_MAX_10_EXP, 491
 LDBL_MAX_EXP, 491
 LDBL_MIN, 491
 LDBL_MIN_10_EXP, 491
 LDBL_MIN_EXP, 491
 LDBL_TRUE_MIN, 491
 ldexp, 1139
 ldexpf, 1139
 ldexpl, 1139
 ldiv, 479
 ldiv_t, 479
 left, 1178
 legendre, 1155
 legendref, 1155
 legendrel, 1155
 length
 basic_string, 746
 basic_string_view, 771
 char_traits, 745
 codecvt, 799
 match_results, 1326
 regex_traits, 1310
 sub_match, 1318
 length_error, 513, 514, 736
 constructor, 515
 less, 661
 first_argument_type, 1471
 operator(), 661
 result_type, 1471
 second_argument_type, 1471
 less<>, 661
 operator(), 661
 less_equal, 662
 first_argument_type, 1471
 operator(), 662
 result_type, 1471
 second_argument_type, 1471
 less_equal<>, 662
 operator(), 662
 lexically_normal
 path, 1260
 lexically_proximate
 path, 1261
 lexically_relative
 path, 1260
 lexicographical_compare, 1048
 lgamma, 1139
 lgammaf, 1139
 lgammal, 1139
 <limits>, 483
 linear_congruential_engine, 1074
 constructor, 1074
 <list>, 870
 list, 886
 constructor, 889
 splice, 891
 swap, 892
 literals
 complex, 1061
 labs, 479
 lldiv, 479
 lldiv_t, 479
 LLONG_MAX, 491
 LLONG_MIN, 491
 llrint, 1139
 llrintf, 1139
 llrintl, 1139
 llround, 1139
 llroundf, 1139
 llroundl, 1139
 load
 atomic, 1350
 atomic<integral>, 1350
 atomic<T*>, 1350
 <locale>, 782, 784
 locale, 1312, 1317, 1339
 category, 785
 classic, 790
 combine, 789
 constructor, 788, 789
 destructor, 789
 facet, 786

```

    global, 790
    has_facet, 790
    id, 788
    name, 789
    operator!=, 789
    operator(), 789
    operator=, 789
    operator==, 789
    use_facet, 790
<locale.h>, 829
localeconv, 829
localtime, 721
lock, 1386
    shared_lock, 1384
    unique_lock, 1380
    weak_ptr, 631
lock_guard, 1376
    constructor, 1377
    destructor, 1377
log, 1139
    complex, 1060
    valarray, 1117
log10, 1139
    complex, 1060
    valarray, 1117
log10f, 1139
log10l, 1139
log1p, 1139
log1pf, 1139
log1pl, 1139
log2, 1139
log2f, 1139
log2l, 1139
logb, 1139
logbf, 1139
logbl, 1139
logf, 1139
logic_error, 513
    constructor, 514
logical_and, 662
    first_argument_type, 1471
    operator(), 662
    result_type, 1471
    second_argument_type, 1471
logical_and<>, 662
    operator(), 663
logical_not, 663
    argument_type, 1471
    operator(), 663
    result_type, 1471
logical_not<>, 663
    operator(), 663
logical_or, 663
    first_argument_type, 1471
    operator(), 663
    result_type, 1471
    second_argument_type, 1471
logical_or<>, 663
    operator(), 663
logl, 1139
lognormal_distribution, 1096
    constructor, 1096
    m, 1096
    s, 1096
LONG_MAX, 491
LONG_MIN, 491
longjmp, 511
lookup_classname
    regex_traits, 1311
    regular expression traits, 1340
lookup_collatename
    regex_traits, 1311
    regular expression traits, 1340
lower_bound, 1034
lowest
    numeric_limits, 485
lrint, 1139
lrintf, 1139
lrintl, 1139
lround, 1139
lroundf, 1139
lroundl, 1139

m
    fisher_f_distribution, 1099
    lognormal_distribution, 1096
make_any, 586
make_error_code
    errc, 525
    future_errc, 1397
    io_errc, 1179
make_error_condition
    errc, 527
    future_errc, 1397
    io_errc, 1179
make_exception_ptr, 508
make_from_tuple, 551
make_heap, 1044
make_index_sequence, 531
make_integer_sequence, 539
make_move_iterator, 980
make_optional, 568

```

make_pair, 542
 make_preferred
 path, 1256
 make_ready_at_thread_exit
 packaged_task, 1410
 make_reverse_iterator, 972
 make_shared, 627
 make_signed, 697
 make_tuple, 550
 make_unique, 618
 make_unsigned, 697
 malloc, 479, 608, 1459
 <map>, 900
 map, 903
 constructor, 907
 insert, 907
 insert_or_assign, 908
 operator<, 907
 operator==, 907
 swap, 909
 try_emplace, 908
 map::value_compare
 first_argument_type, 1474
 result_type, 1474
 second_argument_type, 1474
 mark_count
 basic_regex, 1317
 mask_array, 1122
 operator==, 1123
 operator+=, 1123
 operator-=, 1123
 operator/=: 1123
 operator<=, 1123
 operator=, 1123
 operator>=, 1123
 operator[], 1123
 operator%=: 1123
 operator&=: 1123
 operator^=: 1123
 operator|=, 1123
 match_any, 1307, 1308
 match_continuous, 1307, 1308, 1335
 match_default, 1307
 match_flag_type, 1307, 1308, 1341
 match_not_bol, 1307, 1308
 match_not_bow, 1307, 1308
 match_not_eol, 1307, 1308
 match_not_eow, 1307, 1308
 match_not_null, 1307, 1308, 1335
 match_prev_avail, 1307, 1308, 1335
 match_results, 1323, 1333, 1336
 begin, 1326
 constructor, 1325
 empty, 1326
 end, 1327
 format, 1327
 get_allocator, 1327
 length, 1326
 matched, 1323
 max_size, 1326
 operator!=, 1328
 operator=, 1325
 operator==, 1328
 operator[], 1326
 position, 1326
 prefix, 1326
 ready, 1325
 size, 1326
 str, 1326
 suffix, 1326
 swap, 1328
 MATH_ERREXCEPT, 1139
 math_errhandling, 1139
 MATH_ERRNO, 1139
 max, 1045, 1046
 duration, 713
 duration_values, 710
 numeric_limits, 485
 time_point, 718
 valarray, 1114
 max_align_t, 478, 481
 max_digits10
 numeric_limits, 486
 max_element, 1047
 max_exponent
 numeric_limits, 487
 max_exponent10
 numeric_limits, 487
 max_length
 codecvt, 799
 max_size
 allocator, 1476
 allocator_traits, 605
 array, 872
 basic_string, 746
 basic_string_view, 771
 match_results, 1326
 scoped_allocator_adaptor, 650
 MB_CUR_MAX, 479
 MB_LEN_MAX, 491
 mblen, 479, 780
 mbrlen, 778, 780

mbrstowcs, 780
 mbrtoc16, 780
 mbrtoc32, 780
 mbrtowc, 778, 780
 mbsinit, 778, 780
 mbsrtowcs, 778
 mbstate_t, 778, 780
 mbstowcs, 479, 780
 mbtowc, 479, 780
 mean
 normal_distribution, 1095
 poisson_distribution, 1091
 student_t_distribution, 1100
 mem_fn, 668
 argument_type, 1474
 first_argument_type, 1474
 result_type, 1474
 second_argument_type, 1474
 mem_fun
 zombie, 470
 mem_fun1_ref_t
 zombie, 470
 mem_fun1_t
 zombie, 470
 mem_fun_ref
 zombie, 470
 mem_fun_ref_t
 zombie, 470
 mem_fun_t
 zombie, 470
 memchr, 777
 memcmp, 777
 memcpy, 777
 memmove, 777
 <memory>, 594, 1476, 1478
 <memory_resource>, 635
 memory_resource, 636
 allocate, 636
 deallocate, 637
 destructor, 636
 do_allocate, 637
 do_deallocate, 637
 do_is_equal, 637
 is_equal, 637
 operator!=, 637
 operator==, 637
 memset, 777
 merge, 1038
 forward_list, 885
 list, 891
 mersenne_twister_engine, 1075
 constructor, 1076
 message
 do_close, 825
 error_category, 522
 error_code, 525
 error_condition, 527
 messages, 824
 close, 825
 do_get, 825
 do_open, 825
 get, 825
 open, 825
 messages_byname, 826
 min, 1045
 duration, 713
 duration_values, 710
 numeric_limits, 485
 time_point, 718
 valarray, 1114
 min_element, 1046
 min_exponent
 numeric_limits, 486
 min_exponent10
 numeric_limits, 486
 minmax, 1046
 minmax_element, 1047
 minstd_rand, 1081
 minstd_rand0, 1081
 minus, 658
 first_argument_type, 1471
 operator(), 658
 result_type, 1471
 second_argument_type, 1471
 minus<>, 658
 operator(), 658
 mismatch, 1016
 mktime, 721
 modf, 1139
 modff, 1139
 modfl, 1139
 modulus, 659
 first_argument_type, 1471
 operator(), 659
 result_type, 1471
 second_argument_type, 1471
 modulus<>, 659
 operator(), 659
 money_get, 819
 do_get, 819
 get, 819
 money_put, 820

```

do_put, 821
put, 821
moneypunct, 822
    curr_symbol, 823
    decimal_point, 823
    do_curr_symbol, 824
    do_decimal_point, 823
    do_frac_digits, 824
    do_grouping, 823
    do_neg_format, 824
    do_negative_sign, 824
    do_pos_format, 824
    do_positive_sign, 824
    do_thousands_sep, 823
    frac_digits, 823
    grouping, 823
    negative_sign, 823
    positive_sign, 823
    thousands_sep, 823
moneypunct_byname, 824
monostate, 581
monotonic_buffer_resource, 645
    constructor, 645, 646
    destructor, 646
    do_allocate, 646
    do_deallocate, 646
    do_is_equal, 646
    release, 646
    upstream_resource, 646
move
    algorithm, 1021, 1022
    basic_ios, 1175
    function, 535
move_backward, 1022
move_if_noexcept, 536
move_iterator, 976
    base, 978
    constructor, 977, 978
    operator!=, 979
    operator*, 978
    operator+, 979, 980
    operator++, 978
    operator+=, 979
    operator-, 979, 980
    operator-=, 979
    operator->, 978
    operator--, 978
    operator<, 979
    operator<=, 979
    operator=, 978
    operator==, 979
    operator>, 979
    operator>=, 979
    operator[], 979
mt19937, 1081
mt19937_64, 1081
multimap, 909
    constructor, 913
    insert, 913
    operator<, 913
    operator==, 913
    swap, 913
multimap::value_compare
    first_argument_type, 1474
    result_type, 1474
    second_argument_type, 1474
multiplies, 658
    first_argument_type, 1471
    operator(), 658
    result_type, 1471
    second_argument_type, 1471
multiplies<>, 658
    operator(), 659
multiset, 917
    constructor, 921
    operator<, 921
    operator==, 921
    swap, 921
<mutex>, 1367
mutex, 1369
    shared_lock, 1386
    unique_lock, 1382
n
    chi_squared_distribution, 1097
    fisher_f_distribution, 1099
name
    error_category, 522, 523
    locale, 789
    type_index, 723
    type_info, 503
NAN, 1139
nan, 1139
nanf, 1139
nanl, 1139
narrow
    basic_ios, 1174
    ctype, 793
    ctype<char>, 797
native
    path, 1257
NDEBUG, 459

```

```

nearbyint, 1139
nearbyintf, 1139
nearbyintl, 1139
negate, 659
    argument_type, 1471
    operator(), 660
    result_type, 1471
negate<>, 660
    operator(), 660
negation, 702
negative_binomial_distribution, 1090
    constructor, 1090
    k, 1090
    p, 1090
negative_sign
    moneypunct, 823
nested_exception, 508
    constructor, 508
    nested_ptr, 508
    rethrow_if_nested, 509
    rethrow_nested, 508
    throw_with_nested, 508
nested_ptr
    nested_exception, 508
<new>, 494
new
    operator, 471, 472, 495–499, 609
new_delete_resource, 641
new_handler, 501
next, 967
next_permutation, 1048
nextafter, 1139
nextafterf, 1139
nextafterl, 1139
nexttoward, 1139
nexttowardf, 1139
nexttowardl, 1139
noboolalpha, 1177
none
    bitset, 593
none_of, 1012
norm, 1061
    complex, 1059
normal_distribution, 1095
    constructor, 1095
    mean, 1095
    stddev, 1095
noshowbase, 1177
noshowpoint, 1177
noshowpos, 1177
noskipws, 1177
not1, 1474, 1475
not2, 1474, 1475
not_equal_to, 660
    first_argument_type, 1471
    operator(), 660
    result_type, 1471
    second_argument_type, 1471
not_equal_to<>, 661
    operator(), 661
not_fn, 665
nothrow, 494
nothrow_t, 494
notify_all
    condition_variable, 1390
    condition_variable_any, 1394
notify_all_at_thread_exit, 1389
notify_one
    condition_variable, 1390
    condition_variable_any, 1394
nounitbuf, 1178
nouppercase, 1178
nth_element, 1034
NULL, 478, 479, 481, 721, 778, 829, 1293
null_memory_resource, 641
nullopt, 565
nullopt_t, 565
nullptr_t, 478, 481
num_get, 802
    do_get, 803, 805
    get, 803
num_put, 806
    do_put, 807, 809
    put, 806
<numeric>, 1125
numeric_limits, 483, 484
    denorm_min, 488
    digits, 485
    digits10, 486
    epsilon, 486
    float_denorm_style, 487
    has_denorm_loss, 487
    has_infinity, 487
    has_quiet_NaN, 487
    has_signaling_NaN, 487
    infinity, 487
    is_bounded, 488
    is_exact, 486
    is_iec559, 488
    is_integer, 486
    is_modulo, 488
    is_signed, 486

```


lowest, 485
 max, 485
 max_digits10, 486
 max_exponent, 487
 max_exponent10, 487
 min, 485
 min_exponent, 486
 min_exponent10, 486
 quiet_NaN, 488
 radix, 486
 round_error, 486
 round_style, 489
 signaling_NaN, 488
 tinyness_before, 488
 traps, 488
 numeric_limits<bool>, 490
 numpunct, 809
 decimal_point, 810
 do_decimal_point, 811
 do_falsename, 811
 do_grouping, 811
 do_thousands_sep, 811
 do_truename, 811
 falsename, 810
 grouping, 810
 thousands_sep, 810
 truename, 810
 numpunct_byname, 811

 oct, 1178
 off_type
 char_traits, 728
 offsetof, 478, 481, 1459
 ofstream, 1158, 1225
 once_flag, 1387
 open
 basic_filebuf, 1228
 basic_fstream, 1238, 1239
 basic_ifstream, 1234
 basic_ofstream, 1236
 messages, 825
 openmode
 ios_base, 1166
 operator *integral*
 atomic<*integral*>, 1350
 operator *type*
 atomic, 1350
 operator basic_string
 sub_match, 1318
 operator basic_string_view
 basic_string, 755

 operator bool
 basic_ios, 1176
 basic_istream::sentry, 1193
 basic_ostream::sentry, 1205
 error_code, 525
 error_condition, 527
 function, 672
 optional, 564
 shared_lock, 1386
 shared_ptr, 626
 unique_lock, 1382
 unique_ptr, 615
 operator const path&
 directory_entry, 1271
 operator string_type
 path, 1257
 operator T*
 atomic<T*>, 1350
 operator T&
 reference_wrapper, 657
 operator!
 basic_ios, 1176
 valarray, 1113
 operator!=, 534
 allocator, 606
 basic_string, 761
 basic_string_view, 775
 bitset, 592
 complex, 1058
 directory_entry, 1273
 duration, 715
 error_category, 523
 error_code, 528
 error_condition, 528
 function, 672
 istream_iterator, 982
 istreambuf_iterator, 985
 locale, 789
 match_results, 1328
 memory_resource, 637
 monostate, 581
 move_iterator, 979
 optional, 566, 567
 pair, 542
 path, 1262
 polymorphic_allocator, 641
 queue, 949
 regex_iterator, 1335
 regex_token_iterator, 1338
 reverse_iterator, 971
 scoped_allocator_adaptor, 652

```

    shared_ptr, 628
    stack, 954
    sub_match, 1319–1322
    thread::id, 1364
    time_point, 719
    tuple, 554
    type_index, 723
    type_info, 503
    unique_ptr, 618, 619
    valarray, 1116
    variant, 579
operator""h
    duration, 716
operator""i
    complex, 1061
operator""if
    complex, 1062
operator""il
    complex, 1061
operator""min
    duration, 716
operator""ms
    duration, 717
operator""ns
    duration, 717
operator""s
    duration, 717
    string, 766
    u16string, 766
    u32string, 766
    wstring, 766
operator""sv
    string_view, 776
    u16string_view, 776
    u32string_view, 776
    wstring_view, 776
operator""us
    duration, 717
operator()
    binary_negate, 1475
    bit_and, 663
    bit_and<>, 664
    bit_not, 665
    bit_not<>, 665
    bit_or, 664
    bit_or<>, 664
    bit_xor, 664
    bit_xor<>, 664
    boyer_moore_horspool_searcher, 675
    boyer_moore_searcher, 674
    default_delete, 611
    default_searcher, 673
    divides, 659
    divides<>, 659
    equal_to, 660
    equal_to<>, 660
    function, 672
    greater, 661
    greater<>, 661
    greater_equal, 662
    greater_equal<>, 662
    less, 661
    less<>, 661
    less_equal, 662
    less_equal<>, 662
    locale, 789
    logical_and, 662
    logical_and<>, 663
    logical_not, 663
    logical_not<>, 663
    logical_or, 663
    logical_or<>, 663
    minus, 658
    minus<>, 658
    modulus, 659
    modulus<>, 659
    multiplies, 658
    multiplies<>, 659
    negate, 660
    negate<>, 660
    not_equal_to, 660
    not_equal_to<>, 661
    owner_less, 632
    packaged_task, 1410
    plus, 658
    plus<>, 658
    random_device, 1083
    reference_wrapper, 657
    unary_negate, 1475
operator*
    back_insert_iterator, 973
    complex, 1058
    duration, 714
    front_insert_iterator, 974
    insert_iterator, 975
    istream_iterator, 981
    istreambuf_iterator, 985
    move_iterator, 978
    optional, 563, 564
    ostream_iterator, 983
    ostreambuf_iterator, 986
    raw_storage_iterator, 1477

```

```

    regex_iterator, 1335
    regex_token_iterator, 1339
    reverse_iterator, 969
    shared_ptr, 626
    unique_ptr, 615
    valarray, 1115, 1116
operator*=
    complex, 1057
    duration, 713
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator+
    basic_string, 759–761
    complex, 1058
    duration, 712, 718, 719
    move_iterator, 979, 980
    reverse_iterator, 970, 972
    time_point, 718, 719
    valarray, 1113, 1115, 1116
operator++
    atomic<integral>, 1355
    atomic<T*>, 1355
    back_insert_iterator, 973
    directory_iterator, 1275
    duration, 712, 713
    front_insert_iterator, 974
    insert_iterator, 976
    istream_iterator, 982
    istreambuf_iterator, 985
    move_iterator, 978
    ostream_iterator, 983
    ostreambuf_iterator, 986
    raw_storage_iterator, 1477
    recursive_directory_iterator, 1278
    regex_iterator, 1335
    regex_token_iterator, 1339
    reverse_iterator, 970
operator+=
    atomic<integral>, 1354
    atomic<T*>, 1354, 1355
    basic_string, 747, 748
    complex, 1057
    duration, 713
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    move_iterator, 979
    path, 1255
    reverse_iterator, 970
    slice_array, 1119
    time_point, 718
    valarray, 1113, 1114
operator--
    atomic<integral>, 1355, 1356
    atomic<T*>, 1355, 1356
    duration, 713
    move_iterator, 978
    reverse_iterator, 970
operator/
    complex, 1058
    duration, 714
    path, 1262
    valarray, 1115, 1116
operator/=
    complex, 1057
    duration, 713
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    path, 1254, 1255

```

```

    slice_array, 1119
    valarray, 1113, 1114
operator<
    basic_string, 762
    basic_string_view, 775
    directory_entry, 1273
    duration, 715
    error_category, 523
    error_code, 527
    error_condition, 527
    monostate, 581
    move_iterator, 979
    optional, 566, 567
    pair, 541
    path, 1262
    queue, 949
    reverse_iterator, 971
    shared_ptr, 627, 628
    stack, 954
    sub_match, 1319, 1321–1323
    thread::id, 1364
    time_point, 719
    tuple, 553
    type_index, 723
    unique_ptr, 619
    valarray, 1116
    variant, 580
operator<<
    basic_ostream, 1206–1209
    basic_string, 763
    basic_string_view, 776
    bitset, 593, 594
    byte, 481
    complex, 1059
    error_code, 525
    path, 1263
    shared_ptr, 629
    sub_match, 1323
    thread::id, 1364
    valarray, 1115, 1116
operator<<=
    bitset, 591
    byte, 481
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator<=, 534
    basic_string, 762
    basic_string_view, 776
    directory_entry, 1273
    duration, 715
    monostate, 581
    move_iterator, 979
    optional, 566–568
    pair, 542
    path, 1262
    queue, 949
    reverse_iterator, 971
    shared_ptr, 628
    stack, 954
    sub_match, 1319–1323
    thread::id, 1364
    time_point, 719
    tuple, 554
    type_index, 723
    unique_ptr, 619, 620
    valarray, 1116
    variant, 580
operator=
    any, 585
    atomic, 1350
    atomic<integral>, 1350
    atomic<T*>, 1350
    back_insert_iterator, 973
    bad_alloc, 500
    bad_cast, 504
    bad_exception, 506
    bad_typeid, 504
    basic_filebuf, 1228
    basic_fstream, 1238
    basic_ifstream, 1233
    basic_iostream, 1202
    basic_istream, 1192
    basic_istreamstream, 1221
    basic_ofstream, 1235
    basic_ostream, 1204
    basic_ostreamstream, 1222
    basic_regex, 1316
    basic_streambuf, 1184
    basic_string, 744, 745
    basic_stringbuf, 1217
    basic_stringstream, 1224
    directory_iterator, 1275
    enable_shared_from_this, 633
    error_code, 525
    error_condition, 527
    exception, 505
    front_insert_iterator, 974
    function, 671
    future, 1402

```

gslice_array, 1122
 indirect_array, 1124, 1125
 insert_iterator, 975
 locale, 789
 mask_array, 1123
 match_results, 1325
 move_iterator, 978
 optional, 559–562
 ostream_iterator, 983
 ostreambuf_iterator, 986
 packaged_task, 1409
 pair, 541
 path, 1254
 promise, 1399
 raw_storage_iterator, 1477
 recursive_directory_iterator, 1277
 reference_wrapper, 657
 reverse_iterator, 969
 shared_future, 1405
 shared_lock, 1384
 shared_ptr, 625
 slice_array, 1119
 thread, 1365
 tuple, 549
 unique_lock, 1380
 unique_ptr, 614, 615, 617
 valarray, 1110, 1111
 variant, 575
 weak_ptr, 631
 operator==
 allocator, 606
 basic_string, 761
 basic_string_view, 775
 bitset, 592
 complex, 1058
 directory_entry, 1273
 duration, 715
 error_category, 523
 error_code, 527
 error_condition, 527, 528
 function, 672
 istream_iterator, 982
 istreambuf_iterator, 985
 locale, 789
 match_results, 1328
 memory_resource, 637
 monostate, 581
 move_iterator, 979
 optional, 565–567
 pair, 541
 path, 1262
 polymorphic_allocator, 640
 queue, 948
 regex_iterator, 1334
 regex_token_iterator, 1336, 1338
 reverse_iterator, 971
 scoped_allocator_adaptor, 652
 shared_ptr, 627
 stack, 954
 sub_match, 1319–1322
 thread::id, 1364
 time_point, 719
 tuple, 553
 type_index, 722
 type_info, 503
 unique_ptr, 618, 619
 valarray, 1116
 variant, 579
 operator>, 534
 basic_string, 762
 basic_string_view, 775
 directory_entry, 1273
 duration, 715
 monostate, 581
 move_iterator, 979
 optional, 566–568
 pair, 542
 path, 1262
 queue, 949
 reverse_iterator, 971
 shared_ptr, 628
 stack, 954
 sub_match, 1319–1323
 thread::id, 1364
 time_point, 719
 tuple, 554
 type_index, 723
 unique_ptr, 619
 valarray, 1116
 variant, 580
 operator>=, 534
 basic_string, 762, 763
 basic_string_view, 776
 directory_entry, 1273
 duration, 715
 monostate, 581
 move_iterator, 979
 optional, 566–568
 pair, 542
 path, 1262
 queue, 949
 reverse_iterator, 971

```

    shared_ptr, 628
    stack, 954
    sub_match, 1319–1323
    thread::id, 1364
    time_point, 719
    tuple, 554
    type_index, 723
    unique_ptr, 619, 620
    valarray, 1116
    variant, 580
operator>>
    basic_istream, 1193–1196, 1200
    basic_string, 763
    bitset, 593
    byte, 482
    complex, 1058
    path, 1263
    valarray, 1115, 1116
operator>>=
    bitset, 591
    byte, 482
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator[]
    basic_string, 747
    basic_string_view, 771
    bitset, 593
    indirect_array, 1124
    map, 907
    mask_array, 1123
    match_results, 1326
    move_iterator, 979
    reverse_iterator, 971
    shared_ptr, 626
    unique_ptr, 618
    unordered_map, 929
    valarray, 1111–1113
operator%
    duration, 714
    valarray, 1115, 1116
operator%=
    duration, 713
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator&
    bitset, 593
    byte, 482
    valarray, 1115, 1116
operator&=
    atomic<integral>, 1354
    bitset, 590
    byte, 482
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator&&
    valarray, 1116
operator^
    bitset, 593
    byte, 482
    valarray, 1115, 1116
operator^=
    atomic<integral>, 1354
    bitset, 591
    byte, 482
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator~
    bitset, 591
    byte, 482
    valarray, 1113
operator|
    bitset, 593
    byte, 482
    valarray, 1115, 1116
operator|=
    atomic<integral>, 1354
    bitset, 590
    byte, 482
    gslice_array, 1122
    indirect_array, 1124
    mask_array, 1123
    slice_array, 1119
    valarray, 1113, 1114
operator||
    valarray, 1116
<optional>, 554
optional, 556
    constructor, 557–559
    destructor, 559
    emplace, 563

```

- has_value, 564
- operator bool, 564
- operator!=, 566, 567
- operator*, 563, 564
- operator->, 563
- operator<, 566, 567
- operator<=, 566–568
- operator=, 559–562
- operator==, 565–567
- operator>, 566–568
- operator>=, 566–568
- reset, 565
- swap, 563
- value, 564
- value_or, 565
- options
 - recursive_directory_iterator, 1278
 - synchronized_pool_resource, 644
 - unsynchronized_pool_resource, 644
- <ostream>, 1189
- ostream, 1158, 1189
- ostream_iterator, 982
 - constructor, 983
 - destructor, 983
 - operator*, 983
 - operator++, 983
 - operator=, 983
- ostreambuf_iterator, 985
 - constructor, 986
 - failed, 986
 - operator*, 986
 - operator++, 986
 - operator=, 986
- ostringstream, 1158, 1214
- ostrstream, 1468
 - constructor, 1468
 - freeze, 1469
 - pcount, 1469
 - rdbuf, 1468
 - str, 1469
- out
 - codecvt, 798
- out_of_range, 513, 515, 589–592, 736
 - constructor, 515
- outer_allocator
 - scoped_allocator_adaptor, 650
- output_iterator_tag, 966
- overflow
 - basic_filebuf, 1230
 - basic_streambuf, 1188
 - basic_stringbuf, 1218
 - strstreambuf, 1465
- overflow_error, 513, 516, 589, 592
 - constructor, 516
- owner_before
 - shared_ptr, 626
 - weak_ptr, 631
- owner_less, 632
 - first_argument_type, 1471
 - operator(), 632
 - result_type, 1471
 - second_argument_type, 1471
- owns_lock
 - shared_lock, 1386
 - unique_lock, 1382
- p
 - bernoulli_distribution, 1088
 - binomial_distribution, 1089
 - geometric_distribution, 1090
 - negative_binomial_distribution, 1090
- packaged_task, 1408
 - constructor, 1409
 - destructor, 1409
 - get_future, 1409
 - make_ready_at_thread_exit, 1410
 - operator(), 1410
 - operator=, 1409
 - reset, 1410
 - swap, 1409, 1410
 - valid, 1409
- pair, 539, 548, 549
 - constructor, 540
 - get, 542, 543
 - operator!=, 542
 - operator<, 541
 - operator<=, 542
 - operator=, 541
 - operator==, 541
 - operator>, 542
 - operator>=, 542
 - swap, 541
- par, 725
- par_unseq, 725
- param
 - seed_seq, 1085
- parent_path
 - path, 1258
- partial_sort, 1032
- partial_sort_copy, 1032
- partial_sum, 1133
- partition, 1036

partition_copy, 1037
 partition_point, 1038
 path, 1247
 append, 1255
 assign, 1254
 begin, 1262
 c_str, 1257
 clear, 1255
 compare, 1258
 concat, 1255
 constructor, 1253
 directory_entry, 1271
 empty, 1259
 end, 1262
 extension, 1259
 filename, 1259
 generic_string, 1257, 1258
 generic_u16string, 1258
 generic_u32string, 1258
 generic_u8string, 1258
 generic_wstring, 1258
 has_extension, 1260
 has_filename, 1260
 has_parent_path, 1260
 has_relative_path, 1260
 has_root_directory, 1260
 has_root_name, 1260
 has_root_path, 1260
 has_stem, 1260
 is_absolute, 1260
 is_relative, 1260
 iterator, 1261
 lexically_normal, 1260
 lexically_proximate, 1261
 lexically_relative, 1260
 make_preferred, 1256
 native, 1257
 operator string_type, 1257
 operator!=, 1262
 operator+=, 1255
 operator/, 1262
 operator/=: 1254, 1255
 operator<, 1262
 operator<<, 1263
 operator<=: 1262
 operator=: 1254
 operator==, 1262
 operator>, 1262
 operator>=: 1262
 operator>>, 1263
 parent_path, 1258
 preferred_separator, 1250
 relative_path, 1258
 remove_filename, 1256
 replace_extension, 1256
 replace_filename, 1256
 root_directory, 1258
 root_name, 1258
 root_path, 1258
 stem, 1259
 string, 1257
 swap, 1257
 u16string, 1257
 u32string, 1257
 u8string, 1257
 value_type, 1250
 wstring, 1257
 path1
 filesystem_error, 1264
 path2
 filesystem_error, 1264
 pbackfail
 basic_filebuf, 1230
 basic_streambuf, 1187
 basic_stringbuf, 1218
 strstreambuf, 1465
 pbase
 basic_streambuf, 1185
 pbump
 basic_streambuf, 1185
 pcount
 ostrstream, 1469
 strstream, 1470
 strstreambuf, 1464
 peek
 basic_istream, 1199
 perm_options, 1267
 permissions, 1288
 file_status, 1268, 1269
 perms, 1265
 perror, 1293
 piecewise_constant_distribution, 1101
 constructor, 1102
 densities, 1103
 intervals, 1103
 piecewise_construct, 543
 piecewise_construct_t, 543
 piecewise_linear_distribution, 1103
 constructor, 1104
 densities, 1104
 intervals, 1104
 placeholders, 668

plus, 658
 first_argument_type, 1471
 operator(), 658
 result_type, 1471
 second_argument_type, 1471
 plus<>, 658
 operator(), 658
 pointer
 allocator_traits, 603
 pointer_to
 pointer_traits, 600
 pointer_to_binary_function
 zombie, 470
 pointer_to_unary_function
 zombie, 470
 pointer_traits, 599
 difference_type, 600
 element_type, 600
 pointer_to, 600
 rebind, 600
 poisson_distribution, 1091
 constructor, 1091
 mean, 1091
 polar
 complex, 1059
 polymorphic_allocator, 637
 allocate, 639
 construct, 639, 640
 constructor, 638
 deallocate, 639
 destroy, 640
 operator!=, 641
 operator==, 640
 resource, 640
 select_on_container_copy_construction, 640
 pool_options, 642
 largest_required_pool_block, 643
 max_blocks_per_chunk, 643
 pop
 forward_list, 882
 priority_queue, 952
 recursive_directory_iterator, 1278
 pop_back
 basic_string, 752
 pop_heap, 1043
 pos_type
 char_traits, 728
 position
 match_results, 1326
 positive_sign
 moneypunct, 823
 pow, 1061, 1139
 complex, 1060
 valarray, 1117
 powf, 1139
 powl, 1139
 pptr
 basic_streambuf, 1185
 precision
 ios_base, 791, 1169
 preferred_separator
 path, 1250
 prefix
 match_results, 1326
 prev, 967
 prev_permutation, 1049
 PRIdFASTN, 1294
 PRIdLEASTN, 1294
 PRIdMAX, 1294
 PRIdN, 1294
 PRIdPTR, 1294
 PRIiFASTN, 1294
 PRIiLEASTN, 1294
 PRIiMAX, 1294
 PRIiN, 1294
 PRIiPTR, 1294
 printf, 1293
 PRIOFASTN, 1294
 PRIOLEASTN, 1294
 PRIOMAX, 1294
 PRION, 1294
 PRIOPTR, 1294
 priority_queue, 949
 constructor, 950, 951
 emplace, 952
 swap, 952
 PRIuFASTN, 1294
 PRIuLEASTN, 1294
 PRIuMAX, 1294
 PRIuN, 1294
 PRIuPTR, 1294
 PRIfASTN, 1294
 PRIfLEASTN, 1294
 PRIfMAX, 1294
 PRIfN, 1294
 PRIfPTR, 1294
 PRIfxFASTN, 1294
 PRIfxLEASTN, 1294
 PRIfxMAX, 1294
 PRIfxN, 1294
 PRIfxPTR, 1294
 PRIfxPTR, 1294

probabilities
 discrete_distribution, 1101
 proj
 complex, 1059
 promise, 1398
 constructor, 1399
 destructor, 1399
 get_future, 1400
 operator=, 1399
 set_exception, 1400
 set_exception_at_thread_exit, 1401
 set_value, 1400
 set_value_at_thread_exit, 1400
 swap, 1400, 1401
 propagate_on_container_copy_assignment
 allocator_traits, 604
 scoped_allocator_adaptor, 649
 propagate_on_container_move_assignment
 allocator_traits, 604
 scoped_allocator_adaptor, 649
 propagate_on_container_swap
 allocator_traits, 604
 scoped_allocator_adaptor, 649
 proximate, 1288
 proxy
 istreambuf_iterator, 984
 ptr
 from_chars_result, 533
 to_chars_result, 533
 ptr_fun
 zombie, 470
 ptrdiff_t, 478
 pubimbue
 basic_streambuf, 1182
 pubseekoff
 basic_streambuf, 1183
 pubseekpos
 basic_streambuf, 1183
 pubsetbuf
 basic_streambuf, 1183
 pubsync
 basic_streambuf, 1183
 push
 priority_queue, 951, 952
 push_back
 basic_string, 749
 deque, 877
 push_front
 deque, 877
 forward_list, 882
 push_heap, 1043
 put
 basic_ostream, 1209
 money_put, 821
 num_put, 806
 time_put, 818
 put_money, 1212
 put_time, 1213
 putback
 basic_istream, 1199
 putc, 1293
 putchar, 1293
 putenv, 510
 puts, 1293
 putwc, 778
 putwchar, 778
 pword
 ios_base, 1170
 qsort, 479, 1049
 <queue>, 946
 queue, 947
 swap, 949
 quick_exit, 479, 494
 quiet_NaN
 numeric_limits, 488
 quoted, 1213, 1214
 radix
 numeric_limits, 486
 raise, 511
 rand, 479, 1105
 discouraged, 1105
 RAND_MAX, 479
 <random>, 1071–1073
 random_access_iterator_tag, 966
 random_device, 1082
 constructor, 1082
 entropy, 1083
 operator(), 1083
 random_shuffle
 zombie, 470
 range_error, 513, 516
 constructor, 516
 rank, 693
 ranlux24, 1081
 ranlux24_base, 1081
 ranlux48, 1082
 ranlux48_base, 1081
 <ratio>, 702
 ratio, 702, 703
 ratio_equal, 704

ratio_greater, 705
 ratio_greater_equal, 705
 ratio_less, 704
 ratio_less_equal, 705
 ratio_not_equal, 704
 raw_storage_iterator, 1476
 base, 1477
 constructor, 1477
 operator*, 1477
 operator++, 1477
 operator=, 1477
 rbegin
 basic_string, 745
 basic_string_view, 771
 rbegin(C&), 987
 rbegin(initializer_list<E>), 987
 rbegin(T (&array)[N]), 987
 rdbuf
 basic_fstream, 1238
 basic_ifstream, 1234
 basic_ios, 1174
 basic_istream, 1221
 basic_ofstream, 1236
 basic_ostringstream, 1223
 basic_stringstream, 1225
 istream, 1468
 ostream, 1468
 stringstream, 1470
 wbuffer_convert, 1484
 rdstate
 basic_ios, 1176
 read
 basic_istream, 1199
 read_symlink, 1289
 readsome
 basic_istream, 1199
 ready
 match_results, 1325
 real, 1061
 complex, 1056, 1057, 1059
 realloc, 479, 608, 1459
 rebind
 pointer_traits, 600
 rebind_alloc
 allocator_traits, 604
 recursion_pending
 recursive_directory_iterator, 1278
 recursive_directory_iterator, 1276
 constructor, 1277
 depth, 1278
 disable_recursion_pending, 1278
 increment, 1278
 operator++, 1278
 operator=, 1277
 options, 1278
 pop, 1278
 recursion_pending, 1278
 recursive_mutex, 1370
 recursive_timed_mutex, 1372
 reduce, 1130
 ref
 reference_wrapper, 657
 reference_wrapper, 656
 argument_type, 1473
 constructor, 657
 cref, 657
 first_argument_type, 1473
 get, 657
 operator T&, 657
 operator(), 657
 operator=, 657
 ref, 657
 second_argument_type, 1473
 weak result type, 1473
 refresh
 directory_entry, 1271
 <regex>, 1300
 regex, 1300
 regex_constants, 1306
 error_type, 1308, 1309
 match_flag_type, 1307
 syntax_option_type, 1306
 regex_error, 1309, 1312, 1340
 constructor, 1309
 regex_iterator, 1333
 constructor, 1334
 increment, 1335
 operator!=, 1335
 operator*, 1335
 operator++, 1335
 operator->, 1335
 operator==, 1334
 regex_match, 1328–1330
 regex_replace, 1332, 1333
 regex_search, 1330, 1331
 regex_token_iterator, 1336
 constructor, 1338
 end-of-sequence, 1336
 operator!=, 1338
 operator*, 1339
 operator++, 1339
 operator->, 1339

```

    operator==, 1336, 1338
regex_traits, 1310
    char_class_type, 1310
    isctype, 1311
    length, 1310
    lookup_classname, 1311
    lookup_collatename, 1311
    transform, 1310
    transform_primary, 1310
    translate, 1310
    translate_nocase, 1310
    value, 1312
register_callback
    ios_base, 1170
regular expression traits
    isctype, 1340
    lookup_classname, 1340
    lookup_collatename, 1340
    transform_primary, 1340
reinterpret_pointer_cast
    shared_ptr, 629
rel_ops, 530
relative, 1289
relative_path
    path, 1258
release
    monotonic_buffer_resource, 646
    shared_lock, 1386
    synchronized_pool_resource, 644
    unique_lock, 1382
    unique_ptr, 615
    unsynchronized_pool_resource, 644
remainder, 1139
remainderf, 1139
remainderl, 1139
remove, 1025, 1293
    forward_list, 884
    list, 891
    path, 1289
remove_all, 1289
remove_all_extents, 698
remove_const, 695
remove_copy, 1026
remove_copy_if, 1026
remove_cv, 696
remove_extent, 698
remove_filename
    path, 1256
remove_if, 1025
    forward_list, 884
remove_pointer, 698
remove_prefix
    basic_string_view, 772
remove_reference, 696
remove_suffix
    basic_string_view, 772
remove_volatile, 696
remquo, 1139
remquof, 1139
remquol, 1139
rename, 1290, 1293
rend
    basic_string, 745
    basic_string_view, 771
rend(C&), 987
rend(initializer_list<E>), 987
rend(T (&array)[N]), 987
rep
    system_clock, 720
replace, 1023
    basic_string, 752–754
replace_copy, 1024
replace_copy_if, 1024
replace_extension
    path, 1256
replace_filename
    directory_entry, 1271
    path, 1256
replace_if, 1023
reserve
    basic_string, 746
    vector, 896
reset
    any, 586
    bitset, 591
    optional, 565
    packaged_task, 1410
    shared_ptr, 625, 626
    unique_ptr, 615, 618
    weak_ptr, 631
resetiosflags, 1210
resize
    basic_string, 746
    deque, 877
    forward_list, 883
    list, 889
    valarray, 1115
    vector, 896
resize_file, 1290
resource
    polymorphic_allocator, 640
result_type

```

- binary_negate, 1475
- bit_and, 1471
- bit_not, 1471
- bit_or, 1471
- bit_xor, 1471
- divides, 1471
- equal_to, 1471
- function, 1471
- greater, 1471
- greater_equal, 1471
- hash, 1474
- less, 1471
- less_equal, 1471
- logical_and, 1471
- logical_not, 1471
- logical_or, 1471
- map::value_compare, 1474
- mem_fn, 1474
- minus, 1471
- modulus, 1471
- multimap::value_compare, 1474
- multiplies, 1471
- negate, 1471
- not_equal_to, 1471
- owner_less, 1471
- plus, 1471
- unary_negate, 1475
- rethrow_exception, 508
- rethrow_if_nested
 - nested_exception, 509
- rethrow_nested
 - nested_exception, 508
- return_temporary_buffer, 1478
- reverse, 1028
 - forward_list, 885
 - list, 892
- reverse_copy, 1028
- reverse_iterator, 967
 - base, 969
 - constructor, 969
 - make_reverse_iterator non-member
 - function, 972
 - operator!=, 971
 - operator*, 969
 - operator+, 970, 972
 - operator++, 970
 - operator+=, 970
 - operator-, 970, 972
 - operator-=, 970
 - operator->, 970
 - operator--, 970
 - operator<, 971
 - operator<=, 971
 - operator=, 969
 - operator==, 971
 - operator>, 971
 - operator>=, 971
 - operator[], 971
- rewind, 1293
- rfind
 - basic_string, 756
 - basic_string_view, 773
- riemann_zeta, 1155
- riemann_zetaf, 1155
- riemann_zetal, 1155
- right, 1178
- rint, 1139
- rintf, 1139
- rintl, 1139
- root_directory
 - path, 1258
- root_name
 - path, 1258
- root_path
 - path, 1258
- rotate, 1028
- rotate_copy, 1029
- round, 1139
 - duration, 716
 - time_point, 720
- round_error
 - numeric_limits, 486
- round_indeterminate, 483
- round_style
 - numeric_limits, 489
- round_to_nearest, 483
- round_toward_infinity, 484
- round_toward_neg_infinity, 484
- round_toward_zero, 483
- roundf, 1139
- roundl, 1139
- runtime_error, 513, 515
 - constructor, 515, 516
- s
 - lognormal_distribution, 1096
- sample, 1029
- sbumpc
 - basic_streambuf, 1183
- scalbln, 1139
- scalblnf, 1139
- scalblnl, 1139

```

scalbn, 1139
scalbnf, 1139
scalbnl, 1139
scan_is
    ctype, 792
    ctype<char>, 796
scan_not
    ctype, 792
    ctype<char>, 796
scanf, 1293
SCHAR_MAX, 491
SCHAR_MIN, 491
scientific, 1179
scientific
    chars_format, 533
SCNdFASTN, 1294
SCNdLEASTN, 1294
SCNdMAX, 1294
SCNdN, 1294
SCNdPTR, 1294
SCNiFASTN, 1294
SCNiLEASTN, 1294
SCNiMAX, 1294
SCNiN, 1294
SCNiPTR, 1294
SCNoFASTN, 1294
SCNoLEASTN, 1294
SCNoMAX, 1294
SCNoN, 1294
SCNoPTR, 1294
SCNuFASTN, 1294
SCNuLEASTN, 1294
SCNuMAX, 1294
SCNuN, 1294
SCNuPTR, 1294
SCNxFASTN, 1294
SCNxLEASTN, 1294
SCNxMAX, 1294
SCNxN, 1294
SCNxPTR, 1294
<scoped_allocator>, 646
scoped_allocator_adaptor, 647
    allocate, 650
    construct, 650–652
    constructor, 649
    deallocate, 650
    destroy, 652
    inner_allocator, 650
    inner_allocator_type, 649
    is_always_equal, 649
    max_size, 650
    operator!=, 652
    operator==, 652
    outer_allocator, 650
    propagate_on_container_copy_
        assignment,
        649
    propagate_on_container_move_
        assignment,
        649
    propagate_on_container_swap, 649
    select_on_container_copy_construction,
        652
scoped_lock, 1377
    constructor, 1378
    destructor, 1378
search, 1019, 1020
search_n, 1019
second_argument_type
    binary_negate, 1475
    bit_and, 1471
    bit_or, 1471
    bit_xor, 1471
    divides, 1471
    equal_to, 1471
    function, 1471
    greater, 1471
    greater_equal, 1471
    less, 1471
    less_equal, 1471
    logical_and, 1471
    logical_or, 1471
    map::value_compare, 1474
    mem_fn, 1474
    minus, 1471
    modulus, 1471
    multimap::value_compare, 1474
    multiplies, 1471
    not_equal_to, 1471
    owner_less, 1471
    plus, 1471
    reference_wrapper, 1473
seed_seq, 1083
    constructor, 1083, 1084
    generate, 1084
    param, 1085
    size, 1084
SEEK_CUR, 1293
SEEK_END, 1293
SEEK_SET, 1293
seekdir
    ios_base, 1166

```

```

seekg
    basic_istream, 1200
seekoff
    basic_filebuf, 1231
    basic_streambuf, 1185
    basic_stringbuf, 1218
    strstreambuf, 1466
seekp
    basic_ostream, 1205
seekpos
    basic_filebuf, 1231
    basic_streambuf, 1185
    basic_stringbuf, 1219
    strstreambuf, 1466
select_on_container_copy_construction
    allocator_traits, 605
    polymorphic_allocator, 640
    scoped_allocator_adaptor, 652
sentry
    basic_istream, 1192
    basic_ostream, 1204
    constructor, 1192
    destructor, 1193
seq, 725
<set>, 901
set, 913
    constructor, 917
    operator<, 917
    operator==, 917
    swap, 917
set (member)
    bitset, 591
set_default_resource, 641
set_difference, 1041
set_exception
    promise, 1400
set_exception_at_thread_exit
    promise, 1401
set_intersection, 1041
set_new_handler, 472, 501
set_rdbuf
    basic_ios, 1176
set_symmetric_difference, 1042
set_terminate, 472, 506
set_unexpected
    zombie, 470
set_union, 1040
set_value
    promise, 1400
set_value_at_thread_exit
    promise, 1400

setbase, 1210
setbuf, 1293
    basic_filebuf, 1230
    basic_streambuf, 1185, 1219
    strstreambuf, 1467
setenv, 510
setf
    ios_base, 1168
setfill, 1211
setg
    basic_streambuf, 1185
setiosflags, 1210
setjmp, 471, 511
<setjmp.h>, 511
setlocale, 455, 829
setp
    basic_streambuf, 1185
setprecision, 1211
setstate
    basic_ios, 1176
setvbuf, 1293
setw, 1211
sgetc
    basic_streambuf, 1183
sgetn
    basic_streambuf, 1183
share
    future, 1402
shared_from_this
    enable_shared_from_this, 633
shared_future, 1404
    constructor, 1404
    destructor, 1405
    get, 1405
    operator=, 1405
    valid, 1406
    wait, 1406
    wait_for, 1406
    wait_until, 1406
shared_lock, 1382
    constructor, 1383, 1384
    destructor, 1384
    lock, 1384
    mutex, 1386
    operator bool, 1386
    operator=, 1384
    owns_lock, 1386
    release, 1386
    swap, 1386
    try_lock, 1385
    try_lock_for, 1385

```

```

    try_lock_until, 1385
    unlock, 1386
<shared_mutex>, 1368
shared_mutex, 1374
shared_ptr, 620, 633, 1479
    atomic_compare_exchange_strong, 635
    atomic_compare_exchange_strong_
        explicit,
        635
    atomic_compare_exchange_weak, 635
    atomic_compare_exchange_weak_explicit,
        635
    atomic_exchange, 634
    atomic_exchange_explicit, 634
    atomic_is_lock_free, 634
    atomic_load, 634
    atomic_load_explicit, 634
    atomic_store, 634
    atomic_store_explicit, 634
    const_pointer_cast, 629
    constructor, 623, 624
    destructor, 625
    dynamic_pointer_cast, 628
    get, 626
    get_deleter, 629
    operator bool, 626
    operator !=, 628
    operator *, 626
    operator -, 626
    operator <, 627, 628
    operator <=, 629
    operator <=, 628
    operator =, 625
    operator ==, 627
    operator >, 628
    operator >=, 628
    operator [], 626
    owner_before, 626
    reinterpret_pointer_cast, 629
    reset, 625, 626
    static_pointer_cast, 628
    swap, 625, 628
    unique, 1479
    use_count, 626
shared_timed_mutex, 1375
shift
    valarray, 1115
showbase, 1177
showmanyc
    basic_filebuf, 1229
    basic_streambuf, 1186, 1229
    showpoint, 1177
    showpos, 1177
    shrink_to_fit
        basic_string, 746
        deque, 877
        vector, 896
    SHRT_MAX, 491
    SHRT_MIN, 491
    shuffle, 1030
    shuffle_order_engine, 1080
        constructor, 1081
    sig_atomic_t, 511
    SIG_DFL, 511
    SIG_ERR, 511
    SIG_IGN, 511
    SIGABRT, 511
    SIGFPE, 511
    SIGILL, 511
    SIGINT, 511
    signal, 511
    <signal.h>, 511
    signaling_NaN
        numeric_limits, 488
    signbit, 1139
    SIGSEGV, 511
    SIGTERM, 511
    sin, 1139
        complex, 1060
        valarray, 1117
    sinf, 1139
    sinh, 1139
        complex, 1061
        valarray, 1117
    sinhlf, 1139
    sinhl, 1139
    sinl, 1139
    size
        array, 872, 873
        basic_string, 746
        basic_string_view, 771
        bitset, 592
        gslslice, 1121
        initializer_list, 510
        match_results, 1326
        seed_seq, 1084
        slice, 1118
        valarray, 1114
    size(C& c), 988
    size(T (&array)[N]), 988
    size_t, 122, 478, 479, 721, 777, 778, 780, 1293
    size_type

```


- allocator_traits, 604
- skipws, 1177
- sleep_for
 - this_thread, 1367
- sleep_until
 - this_thread, 1367
- slice, 1118
 - constructor, 1118
 - size, 1118
 - start, 1118
 - stride, 1118
- slice_array, 1118
 - operator*, 1119
 - operator+=, 1119
 - operator-=, 1119
 - operator/=: 1119
 - operator<=, 1119
 - operator=, 1119
 - operator>=, 1119
 - operator%=: 1119
 - operator&=: 1119
 - operator^=: 1119
 - operator|=, 1119
- snnextc
 - basic_streambuf, 1183
- snprintf, 1293
- sort, 1031
 - forward_list, 885
 - list, 892
- sort_heap, 1044
- space, 1290
- sph_bessel, 1155
- sph_besself, 1155
- sph_bessell, 1155
- sph_legendre, 1155
- sph_legendref, 1155
- sph_legendrel, 1155
- sph_neumann, 1156
- sph_neumannf, 1156
- sph_neumannl, 1156
- splice
 - list, 890, 891
- splice_after
 - forward_list, 884
- sprintf, 1293
- sputbackc
 - basic_streambuf, 1183
- sputc
 - basic_streambuf, 1184
- sputn
 - basic_streambuf, 1184
- sqrt, 1139
 - complex, 1061
 - valarray, 1117
- sqrtrf, 1139
- sqrtrl, 1139
- srand, 479, 1105
- sscanf, 1293
- <sstream>, 1214
- stable_partition, 1037
- stable_sort, 1031
- <stack>, 946
- stack, 952
 - constructor, 953, 954
 - swap, 954
- start
 - gslice, 1121
 - slice, 1118
- state
 - fpos, 1171
 - wbuffer_convert, 1484
 - wstring_convert, 1483
- state_type
 - char_traits, 728
 - wbuffer_convert, 1484
 - wstring_convert, 1483
- static_pointer_cast
 - shared_ptr, 628
- status, 1290, 1291
 - directory_entry, 1273
- status_known, 1292
- <stdalign.h>, 1458, 1460
- <stdarg.h>, 510
- <stdbool.h>, 1458, 1461
- stddev
 - normal_distribution, 1095
- stderr, 1293
- <stdexcept>, 513
- stdin, 1293
- <stdio.h>, 1294
- <stdlib.h>, 1461
- stdout, 1293
- steady_clock, 721
- stem
 - path, 1259
- stod, 764, 765
- stof, 764, 765
- stoi, 764, 765
- stol, 764, 765
- stold, 764, 765
- stoll, 764, 765
- store

```

    atomic, 1350
    atomic<integral>, 1350
    atomic<T*>, 1350
stoul, 764, 765
stoull, 764, 765
str
    basic_istream, 1221
    basic_ostringstream, 1223
    basic_stringbuf, 1217
    basic_stringstream, 1225
    istream, 1468
    match_results, 1326
    ostream, 1469
    strstream, 1470
    stringstream, 1464
    sub_match, 1318
strcat, 777
strchr, 777
strcmp, 777
strcoll, 777
strcpy, 777
strcspn, 777
<streambuf>, 1179
streambuf, 1158, 1179
streamoff, 1163, 1171
streamsize, 1163
strerror, 777
strftime, 721, 818
stride
    gslice, 1121
    slice, 1118
<string>, 732
string
    operator"s, 766
    path, 1257
<string.h>, 778
<string_view>, 767
string_view
    operator"sv, 776
stringbuf, 1158, 1214
stringstream, 1158, 1214
strlen, 777, 1464, 1468
strncat, 777
strncmp, 777
strncpy, 777
strpbrk, 777
strrchr, 777
strspn, 777
strstr, 777
<strstream>, 1461
strstream, 1469
    constructor, 1469
    destructor, 1470
    freeze, 1470
    pcount, 1470
    rdbuf, 1470
    str, 1470
stringstream, 1461
    constructor, 1463, 1464
    destructor, 1464
    freeze, 1464
    overflow, 1465
    pbackfail, 1465
    pcount, 1464
    seekoff, 1466
    seekpos, 1466
    setbuf, 1467
    str, 1464
    underflow, 1465
strtod, 479
strtof, 479
strtoimax, 1294
strtok, 777
strtol, 479
strtold, 479
strtoll, 479
strtoul, 479
strtoull, 479
strtoumax, 1294
strxfrm, 777
student_t_distribution, 1099
    constructor, 1099
    mean, 1100
sub_match, 1318
    compare, 1319
    constructor, 1318
    length, 1318
    operator basic_string, 1318
    operator!=, 1319–1322
    operator<, 1319–1323
    operator<<, 1323
    operator<=, 1319–1323
    operator==, 1319–1322
    operator>, 1319–1323
    operator>=, 1319–1323
    str, 1318
substr
    basic_string, 758
    basic_string_view, 772
subtract_with_carry_engine, 1076
    constructor, 1077
suffix

```

match_results, 1326
 sum
 valarray, 1114
 sungetc
 basic_streambuf, 1184
 swap, 534, 554
 any, 586
 array, 873
 basic_filebuf, 1228
 basic_fstream, 1238
 basic_ifstream, 1233
 basic_ios, 1175
 basic_iostream, 1202
 basic_istream, 1192
 basic_istreamstream, 1221
 basic_ofstream, 1236
 basic_ostream, 1204
 basic_ostreamstream, 1223
 basic_regex, 1317, 1318
 basic_streambuf, 1184
 basic_string, 755, 763
 basic_string_view, 772
 basic_stringbuf, 1217
 basic_stringstream, 1224
 deque, 878
 forward_list, 886
 function, 672
 list, 892
 map, 909
 match_results, 1328
 multimap, 913
 multiset, 921
 optional, 563, 568
 packaged_task, 1409, 1410
 pair, 541, 542
 path, 1257, 1262
 priority_queue, 952
 promise, 1400, 1401
 queue, 949
 set, 917
 shared_lock, 1386
 shared_ptr, 625, 628
 stack, 954
 thread, 1365, 1366
 tuple, 550
 unique_lock, 1382
 unique_ptr, 615
 unordered_map, 930
 unordered_multimap, 936
 unordered_multiset, 945
 unordered_set, 940
 valarray, 1114, 1117
 variant, 577, 581
 vector, 896, 897
 vector<bool>, 900
 weak_ptr, 631, 632
 swap(unique_ptr&, unique_ptr&), 618
 swap_ranges, 1022
 swprintf, 778
 swscanf, 778
 symlink_status, 1292
 directory_entry, 1273
 sync
 basic_filebuf, 1231
 basic_istream, 1200
 basic_streambuf, 1186
 sync_with_stdio
 ios_base, 1169
 synchronized_pool_resource, 642
 constructor, 643
 destructor, 644
 do_allocate, 644
 do_deallocate, 644
 do_is_equal, 644
 options, 644
 release, 644
 upstream_resource, 644
 syntax_option_type, 1306, 1307
 awk, 1307
 basic, 1307
 collate, 1307, 1341
 ECMAScript, 1307
 egrep, 1307
 extended, 1307
 grep, 1307
 icase, 1307
 multiline, 1307
 nosubs, 1307
 optimize, 1307
 system, 479, 510
 system_category, 522, 523
 system_clock, 720
 from_time_t, 721
 rep, 720
 to_time_t, 720
 <system_error>, 519
 system_error, 519, 528
 code, 529
 constructor, 528, 529
 what, 529
 t

```

    binomial_distribution, 1089
table
    ctype<char>, 797
tan, 1139
    complex, 1061
    valarray, 1117
tanf, 1139
tanh, 1139
    complex, 1061
    valarray, 1117
tanhf, 1139
tanhf, 1139
tanl, 1139
target
    function, 672
target_type
    function, 672
tellg
    basic_istream, 1200
tellp
    basic_ostream, 1205
temp_directory_path, 1292
terminate, 493, 494, 506, 507
terminate_handler, 472, 506
test
    bitset, 592
test_and_set
    atomic_flag, 1357
tgamma, 1139
tgammaf, 1139
tgammal, 1139
this_thread
    get_id, 1366
    sleep_for, 1367
    sleep_until, 1367
    yield, 1366
thousands_sep
    moneypunct, 823
    numpunct, 810
<thread>, 1362
thread, 1362
    constructor, 1364, 1365
    destructor, 1365
    detach, 1366
    get_id, 1366
    hardware_concurrency, 1366
    id, 1363
    join, 1365
    joinable, 1365
    operator=, 1365
    swap, 1365, 1366
    thread::id, 1363
        constructor, 1363
        operator!=, 1364
        operator<, 1364
        operator<<, 1364
        operator<=, 1364
        operator==, 1364
        operator>, 1364
        operator>=, 1364
throw_with_nested
    nested_exception, 508
tie, 550
    basic_ios, 1174
time, 721
<time.h>, 722
time_get, 813
    date_order, 814
    do_date_order, 815
    do_get, 816
    do_get_date, 816
    do_get_monthname, 816
    do_get_time, 815
    do_get_weekday, 816
    do_get_year, 816
    get, 815
    get_date, 814
    get_monthname, 814
    get_time, 814
    get_weekday, 814
    get_year, 814
time_get_byname, 817
time_point, 717
    ceil, 720
    constructor, 718
    floor, 720
    max, 718
    min, 718
    operator!=, 719
    operator+, 718, 719
    operator+=, 718
    operator-, 719
    operator-=, 718
    operator<, 719
    operator<=, 719
    operator==, 719
    operator>, 719
    operator>=, 719
    round, 720
    time_point_cast, 719
    time_since_epoch, 718
time_point_cast, 719

```

time_put, 817
 do_put, 818
 put, 818
 time_put_byname, 818
 time_since_epoch
 time_point, 718
 time_t, 721
 TIME_UTC, 721
 timed_mutex, 1371
 timespec, 721
 timespec_get, 721
 tinyness_before
 numeric_limits, 488
 tm, 721, 778
 TMP_MAX, 1293
 tmpfile, 1293
 tmpnam, 1293
 to_bytes
 wstring_convert, 1483
 to_chars, 537
 to_chars_result, 533
 ec, 533
 ptr, 533
 to_integer
 byte, 482
 to_string, 765
 bitset, 592
 to_time_t
 system_clock, 720
 to_ullong
 bitset, 592
 to_ulong
 bitset, 592
 to_wstring, 766
 tolower, 776, 791
 ctype, 793
 ctype<char>, 796
 toupper, 776, 791
 ctype, 793
 ctype<char>, 796
 towctrans, 777
 tolower, 777
 towupper, 777
 transform, 1023
 collate, 812
 regex_traits, 1310
 transform_exclusive_scan, 1135
 transform_inclusive_scan, 1136
 transform_primary
 regex_traits, 1310
 transform_reduce, 1131, 1132
 translate
 regex_traits, 1310
 translate_nocase
 regex_traits, 1310
 traps
 numeric_limits, 488
 treat_as_floating_point, 709
 true_type, 684
 truename
 numpunct, 810
 trunc, 1139
 truncf, 1139
 trunc1, 1139
 try_emplace
 map, 908
 unordered_map, 929, 930
 try_lock, 1386
 shared_lock, 1385
 unique_lock, 1381
 try_lock_for
 shared_lock, 1385
 unique_lock, 1381
 try_lock_until
 shared_lock, 1385
 unique_lock, 1381
 try_to_lock, 1376
 try_to_lock_t, 1376
 <tuple>, 543
 tuple, 543, 545, 874
 constructor, 547, 548
 forward_as_tuple, 550
 get, 552, 553
 make_tuple, 550
 operator!=, 554
 operator<, 553
 operator<=, 554
 operator=, 549
 operator==, 553
 operator>, 554
 operator>=, 554
 swap, 550
 tie, 550
 tuple_cat, 550
 tuple_element, 542, 552, 874
 tuple_size, 542, 551, 552, 874
 in general, 551
 type
 any, 586
 file_status, 1268, 1269
 type_index, 722
 constructor, 722

- hash_code, 723
- name, 723
- operator!=, 723
- operator<, 723
- operator<=, 723
- operator==, 722
- operator>, 723
- operator>=, 723
- type_info, 114, 502, 503
 - before, 503
 - hash_code, 503
 - name, 503
 - operator!=, 503
 - operator==, 503
- <type_traits>, 677, 1478
- <typeindex>, 722
- <typeinfo>, 502
- u16string
 - operator"s, 766
 - path, 1257
- u16string_view
 - operator"sv, 776
- u32string
 - operator"s, 766
 - path, 1257
- u32string_view
 - operator"sv, 776
- u8path, 1263
- u8string
 - path, 1257
- <uchar.h>, 780
- UCHAR_MAX, 491
- uflow
 - basic_filebuf, 1229
 - basic_streambuf, 1187
- uint16_t, 492
- uint32_t, 492
- uint64_t, 492
- uint8_t, 492
- uint_fast16_t, 492
- uint_fast32_t, 492
- uint_fast64_t, 492
- uint_fast8_t, 492
- uint_least16_t, 492
- uint_least32_t, 492
- uint_least64_t, 492
- uint_least8_t, 492
- UINT_MAX, 491
- uintmax_t, 492
- uintptr_t, 492
- ULLONG_MAX, 491
- ULONG_MAX, 491
- unary_function
 - zombie, 470
- unary_negate, 1474, 1475
 - argument_type, 1475
 - operator(), 1475
 - result_type, 1475
- uncaught_exception, 1470
- uncaught_exceptions, 433, 507
- undecclare_no_pointers, 601
- undecclare_reachable, 600
- underflow
 - basic_filebuf, 1229
 - basic_streambuf, 1186
 - basic_stringbuf, 1218
 - strstreambuf, 1465
- underflow_error, 513, 516
 - constructor, 517
- underlying_type, 699
- unexpected
 - zombie, 470
- unexpected_handler
 - zombie, 471
- unget
 - basic_istream, 1199
- ungetc, 1293
- ungetwc, 778
- uniform_int_distribution, 1086
 - a, 1086
 - b, 1086
 - constructor, 1086
- uniform_real_distribution, 1086
 - a, 1087
 - b, 1087
 - constructor, 1087
- uninitialized_copy, 607
- uninitialized_copy_n, 607
- uninitialized_default_construct, 606
- uninitialized_default_construct_n, 606
- uninitialized_fill, 608
- uninitialized_fill_n, 608
- uninitialized_move, 607
- uninitialized_move_n, 607
- uninitialized_value_construct, 606
- uninitialized_value_construct_n, 607
- unique, 1027
 - forward_list, 885
 - list, 891
 - shared_ptr, 1479
- unique_copy, 1027

- unique_lock, 1378
 - constructor, 1379, 1380
 - destructor, 1380
 - lock, 1380
 - mutex, 1382
 - operator bool, 1382
 - operator=, 1380
 - owns_lock, 1382
 - release, 1382
 - swap, 1382
 - try_lock, 1381
 - try_lock_for, 1381
 - try_lock_until, 1381
 - unlock, 1382
- unique_ptr, 611, 616, 624
 - constructor, 612–614, 617
 - destructor, 614
 - get, 615
 - get_deleter, 615
 - operator bool, 615
 - operator!=, 618, 619
 - operator*, 615
 - operator->, 615
 - operator<, 619
 - operator<=, 619, 620
 - operator=, 614, 615, 617
 - operator==, 618, 619
 - operator>, 619
 - operator>=, 619, 620
 - operator[], 618
 - release, 615
 - reset, 615, 618
 - swap, 615
- unitbuf, 1178
- unlock
 - shared_lock, 1386
 - unique_lock, 1382
- <unordered_map>, 921
- unordered_map, 921, 924
 - at, 929
 - constructor, 928
 - insert, 929
 - insert_or_assign, 930
 - operator[], 929
 - swap, 930
 - try_emplace, 929, 930
- unordered_multimap, 921, 931
 - constructor, 935
 - insert, 935
 - swap, 936
- unordered_multiset, 922, 941
 - constructor, 945
 - swap, 945
- <unordered_set>, 922
- unordered_set, 922, 936
 - constructor, 940
 - swap, 940
- unsetf
 - ios_base, 1169
- unshift
 - codecvt, 799
- unsynchronized_pool_resource, 642
 - constructor, 643
 - destructor, 644
 - do_allocate, 644
 - do_deallocate, 644
 - do_is_equal, 644
 - options, 644
 - release, 644
 - upstream_resource, 644
- upper_bound, 1035
- uppercase, 1177
- upstream_resource
 - monotonic_buffer_resource, 646
 - synchronized_pool_resource, 644
 - unsynchronized_pool_resource, 644
- use_count
 - shared_ptr, 626
 - weak_ptr, 631
- use_facet
 - locale, 790
- uses_allocator, 602
 - packaged_task, 1410
 - promise, 1399
 - variant, 582
- uses_allocator<tuple>, 554
- USHRT_MAX, 491
- <utility>, 530
- va_arg, 510
- va_copy, 510
- va_end, 471, 510
- va_list, 471, 510
- va_start, 510
- <valarray>, 1105
- valarray, 1108, 1122
 - apply, 1115
 - constructor, 1109, 1110
 - cshift, 1115
 - destructor, 1110
 - max, 1114
 - min, 1114

```

operator!, 1113
operator!=, 1116
operator*, 1115, 1116
operator==, 1113, 1114
operator+, 1113, 1115, 1116
operator+=, 1113, 1114
operator-, 1113, 1115, 1116
operator-=, 1113, 1114
operator/, 1115, 1116
operator/=: 1113, 1114
operator<, 1116
operator<<, 1115, 1116
operator<=, 1113, 1114
operator<=: 1116
operator=, 1110, 1111
operator==, 1116
operator>, 1116
operator>=: 1116
operator>>, 1115, 1116
operator>>=: 1113, 1114
operator[], 1111–1113
operator%, 1115, 1116
operator%=: 1113, 1114
operator&, 1115, 1116
operator&=: 1113, 1114
operator&&, 1116
operator~, 1115, 1116
operator^=: 1113, 1114
operator~, 1113
operator|, 1115, 1116
operator|=, 1113, 1114
operator||, 1116
resize, 1115
shift, 1115
size, 1114
sum, 1114
swap, 1114, 1117
valid
    future, 1403
    packaged_task, 1409
    shared_future, 1406
value
    error_code, 525
    error_condition, 527
    optional, 564
    regex_traits, 1312
value_or
    optional, 565
value_type
    path, 1250
valueless_by_exception
    variant, 577
<variant>, 569
variant, 571
    constructor, 572–574
    destructor, 575
    emplace, 576, 577
    get, 578, 579
    get_if, 579
    holds_alternative, 578
    index, 577
    operator!=, 579
    operator<, 580
    operator<=: 580
    operator=, 575
    operator==, 579
    operator>, 580
    operator>=: 580
    swap, 577
    valueless_by_exception, 577
    visit, 580
variant_alternative, 578
variant_size, 578
<vector>, 871
vector, 892
    constructor, 895
    operator<, 895
    operator==, 895
    swap, 897
vector<bool>, 897
    flip, 900
    swap, 900
vfprintf, 1293
vfscanf, 1293
vfwprintf, 778
vfwscanf, 778
visit, 580
void_pointer
    allocator_traits, 603
vprintf, 1293
vscanf, 1293
vsprintf, 1293
vsprintf, 1293
vsscanf, 1293
vswprintf, 778
vswscanf, 778
vwprintf, 778
vwscanf, 778
wait
    condition_variable, 1390, 1391
    condition_variable_any, 1394

```


future, 1403
 shared_future, 1406
 wait_for
 condition_variable, 1391, 1392
 condition_variable_any, 1395
 future, 1403
 shared_future, 1406
 wait_until
 condition_variable, 1391, 1392
 condition_variable_any, 1394, 1395
 future, 1403
 shared_future, 1406
 wbuffer_convert, 1484
 constructor, 1485
 destructor, 1485
 rdbuf, 1484
 state, 1484
 state_type, 1484
 wcerr, 1162
 <wchar.h>, 780
 WCHAR_MAX, 778
 WCHAR_MIN, 778
 wcin, 1162
 wclog, 1162
 wcout, 1162
 wcrstombs, 780
 wctomb, 778, 780
 wcscat, 778
 wcschr, 778
 wcscmp, 778
 wcscoll, 778
 wcsncpy, 778
 wcscspn, 778
 wcsftime, 778
 wcslen, 778
 wcsncat, 778
 wcsncmp, 778
 wcsncpy, 778
 wcsrchr, 778
 wcsrtombs, 778
 wcssp, 778
 wcsstr, 778
 wcstod, 778
 wcstof, 778
 wcstoimax, 1294
 wcstok, 778
 wcstol, 778
 wcstold, 778
 wcstoll, 778
 wcstombs, 479, 780
 wcstoul, 778
 wcstoull, 778
 wcstoumax, 1294
 wcsxfrm, 778
 wctob, 778
 wctomb, 479, 780
 wctrans, 777
 wctrans_t, 777
 wctype, 777
 <wctype.h>, 777
 wctype_t, 777
 weak_from_this
 enable_shared_from_this, 633
 weak_ptr, 624, 629, 633
 constructor, 630, 631
 destructor, 631
 expired, 631
 lock, 631
 operator=, 631
 owner_before, 631
 reset, 631
 swap, 631, 632
 use_count, 631
 weakly_canonical, 1292
 weibull_distribution, 1093
 a, 1094
 b, 1094
 constructor, 1094
 WEOF, 777, 778
 wfilebuf, 1158, 1225
 wfstream, 1158, 1225
 what
 bad_alloc, 500
 bad_any_access, 582
 bad_array_new_length, 501
 bad_cast, 504
 bad_exception, 506
 bad_function_call, 669
 bad_optional_access, 565
 bad_typeid, 504
 bad_variant_access, 581
 bad_weak_ptr, 620
 exception, 505
 filesystem_error, 1265
 future_error, 1397
 system_error, 529
 wide_string
 wstring_convert, 1483
 widen
 basic_ios, 1174
 ctype, 793

```

        ctype<char>, 796
width
    ios_base, 791, 1169
wifstream, 1158, 1225
wint_t, 777, 778
wios, 1163
wistream, 1158, 1189
wistreamstream, 1158, 1214
wmemchr, 778
wmemcmp, 778
wmemcpy, 778
wmemmove, 778
wmemset, 778
wofstream, 1158, 1225
wostream, 1158, 1189
wostringstream, 1158, 1214
wprintf, 778
wregex, 1300
write
    basic_ostream, 1209
ws, 1195, 1200
wscanf, 778
wstreambuf, 1158, 1179
wstring
    operator"s, 766
    path, 1257
wstring_convert, 1481
    byte_string, 1482
    constructor, 1483
    converted, 1482
    destructor, 1483
    from_bytes, 1482
    int_type, 1483
    state, 1483
    state_type, 1483
    to_bytes, 1483
    wide_string, 1483
wstring_view
    operator"sv, 776
wstringbuf, 1158, 1214
wstringstream, 1158, 1214

xalloc
    ios_base, 1170
xsgetn
    basic_streambuf, 1186
xspn
    basic_streambuf, 1187

yield
    this_thread, 1366

```

```

zero
    duration, 713
    duration_values, 710

```

Index of implementation-defined behavior

The entries in this section are rough descriptions; exact specifications are at the indicated page in the general text.

`#pragma`, 444

additional execution policies supported by parallel algorithms, 724, 1011

additional `file_type` enumerators for file systems supporting additional types of file, 1266

additional formats for `time_get::do_get_date`, 816

additional supported forms of preprocessing directive, 435

algorithms for producing the standard random number distributions, 1085

alignment, 84

alignment additional values, 85

alignment of bit-fields within a class object, 249

allocation of bit-fields within a class object, 249

any use of an invalid pointer other than to perform indirection or deallocate, 70

argument values to construct `basic_ios::failure`, 1176

assignability of placeholder objects, 668

behavior of `iostream` classes when `traits::pos_type` is not `streampos` or when `traits::off_type` is not `streamoff`, 1158

behavior of non-standard attributes, 195

bits in a byte, 8

choice of larger or smaller value of floating literal, 34

concatenation of some types of string literals, 36

conversions between pointers and integers, 118

converting characters from source character set to execution character set, 23

converting function pointer to object pointer and vice versa, 118

default configuration of a pool, 644

default `next_buffer_size` for a `monotonic_buffer_resource`, 646

default number of buckets in `unordered_map`, 928, 929

default number of buckets in

`unordered_multimap`, 935

default number of buckets in

`unordered_multiset`, 945

default number of buckets in `unordered_set`, 940

defining `main` in freestanding environment, 66

definition and meaning of `__STDC__`, 445, 1445

definition and meaning of `__STDC_VERSION__`, 445

definition of `NULL`, 481, 1458

derived type for `typeid`, 114

diagnostic message, 3

dynamic initialization of static inline variables before `main`, 69

dynamic initialization of static variables before `main`, 68

dynamic initialization of thread-local variables before entry, 69

effect of calling associated Laguerre polynomials with `n` $\geq$ 128 or `m` $\geq$ 128, 1150

effect of calling associated Legendre polynomials with `l` $\geq$ 128, 1151

effect of calling `basic_filebuf::setbuf` with nonzero arguments, 1231

effect of calling `basic_filebuf::sync` when a get area exists, 1231

effect of calling `basic_streambuf::setbuf` with nonzero arguments, 1219

effect of calling cylindrical Bessel functions of the first kind with `nu` $\geq$ 128, 1152

effect of calling cylindrical Neumann functions with `nu` $\geq$ 128, 1153

effect of calling Hermite polynomials with `n` $\geq$ 128, 1154

effect of calling `ios_base::sync_with_stdio` after any input or output operation on standard streams, 1169

effect of calling irregular modified cylindrical Bessel functions with `nu` $\geq$ 128, 1153

effect of calling Laguerre polynomials with `n` $\geq$ 128, 1154

- effect of calling Legendre polynomials with `l >= 128`, 1155
- effect of calling regular modified cylindrical Bessel functions with `nu >= 128`, 1152
- effect of calling spherical associated Legendre functions with `l >= 128`, 1156
- effect of calling spherical Bessel functions with `n >= 128`, 1155
- effect of calling spherical Neumann functions with `n >= 128`, 1156
- effect of `filesystem::copy`, 1280
- effect on C locale of calling `locale::global`, 790
- encoding of universal character name not in execution character set, 32
- `error_category` for errors originating outside the operating system, 476
- exception type when `random_device` constructor fails, 1083
- exception type when `random_device::operator()` fails, 1083
- exception type when `shared_ptr` constructor fails, 623, 624
- exceptions thrown by standard library functions that have a potentially-throwing exception specification, 476
- execution character set and execution wide-character set, 24
- exit status, 494
- extended signed integer types, 79
- file type of the file argument of `filesystem::status`, 1291
- formatted character sequence generated by `time_put::do_put` in C locale, 818
- forward progress guarantees for implicit threads of parallel algorithms (if not defined for `thread`), 1010
- growth factor for `monotonic_buffer_resource`, 646
- headers for freestanding implementation, 458
- how `random_device::operator()` generates values, 1083
- interactive device, 12
- interpretation of the path character sequence with format `path::auto_format`, 1265
- largest supported value to configure the largest allocation satisfied directly by a pool, 643
- largest supported value to configure the maximum number of blocks to replenish a pool, 643
- linkage of `main`, 66
- linkage of names from C standard library, 459
- linkage of objects between C++ and other languages, 194
- locale names, 788
- lvalue-to-rvalue conversion of an invalid pointer value, 87
- manner of search for included source file, 438
- mapping from name to catalog when calling `messages::do_open`, 825
- mapping from physical source file characters to basic source character set, 23, 1453
- mapping header name to header or external source file, 26
- mapping of pointer to integer, 117
- mapping physical source file characters to basic source character set, 22
- mapping to message when calling `messages::do_get`, 825
- maximum depth of recursive template instantiations, 394
- maximum size of an allocated object, 123, 501
- meaning of `'`, `\`, `/*`, or `//` in a *q-char-sequence* or an *h-char-sequence*, 26
- meaning of `asm` declaration, 191
- meaning of attribute declaration, 156
- meaning of *dot-dot* in *root-directory*, 1251
- negative value of character literal in preprocessor, 437
- nesting limit for `#include` directives, 438
- NTCTS in `basic_ostream<charT, traits>& operator<<(nullptr_t)`, 1208
- number of placeholders for bind expressions, 654, 668
- number of threads in a program under a freestanding implementation, 15
- numeric values of character literals in `#if` directives, 437
- operating system on which implementation depends, 1239
- parameters to `main`, 66
- passing argument of class type through ellipsis, 111
- physical source file characters, 22
- presence and meaning of `native_handle_type` and `native_handle`, 1359

- range defined for character literals, 32
- rank of extended signed integer type, 92
- representation of `char`, 79
- required libraries for freestanding implementation, 7
- resource limits on a message catalog, 826
- result of `filesystem::file_size`, 1285
- result of inexact floating-point conversion, 90
- result of right shift of negative value, 133
- return value of `bad_alloc::what`, 500
- return value of `bad_any_access::what`, 583
- return value of `bad_array_new_length::what`, 501
- return value of `bad_cast::what`, 504
- return value of `bad_exception::what`, 506
- return value of `bad_function_call::what`, 669
- return value of `bad_optional_access::what`, 565
- return value of `bad_typeid::what`, 504
- return value of `bad_variant_access::what`, 581
- return value of `bad_weak_ptr::what`, 620
- return value of `char_traits<char16_t>::eof`, 730
- return value of `char_traits<char32_t>::eof`, 731
- return value of `exception::what`, 506
- return value of `type_info::name()`, 503
- search locations for `"` header, 438
- search locations for `<>` header, 437
- semantics and default value of `token` parameter to `random_device` constructor, 1082
- semantics of an access through a volatile glvalue, 167
- semantics of linkage specification on templates, 345
- semantics of linkage specifiers, 192
- semantics of non-standard escape sequences, 32
- semantics of parallel algorithms invoked with implementation-defined execution policies, 1011
- sequence of places searched for a header, 437
- set of character types that `istream`s templates can be instantiated for, 786, 1158
- signedness of `char`, 79, 167
- `sizeof` applied to fundamental types other than `char`, `signed char`, and `unsigned char`, 121
- stack unwinding before call to `std::terminate()`, 429, 432
- start-up and termination in freestanding environment, 66
- string resulting from `__func__`, 217
- support for extended alignment, 700
- support for extended alignments, 85
- support for over-aligned types, 1476, 1478
- supported multibyte character encoding rules, 729, 731
- supported *root-names* in addition to any operating system dependent *root-names*, 1250, 1251
- text of `__DATE__` when date of translation is not available, 444
- text of `__TIME__` when time of translation is not available, 445
- threads and program points at which deferred dynamic initialization is performed, 68, 69
- type of a directory-like file, 1273, 1276
- type of `array::const_iterator`, 872
- type of `array::iterator`, 872
- type of `basic_string::const_iterator`, 736
- type of `basic_string::iterator`, 736
- type of `basic_string_view::const_iterator`, 768, 770
- type of `default_random_engine`, 1082
- type of `deque::const_iterator`, 874
- type of `deque::iterator`, 874
- type of `filesystem` trivial clock, 1246
- type of `forward_list::const_iterator`, 879
- type of `forward_list::iterator`, 879
- type of `list::const_iterator`, 886
- type of `list::iterator`, 886
- type of `map::const_iterator`, 903
- type of `map::iterator`, 903
- type of `multimap::const_iterator`, 909
- type of `multimap::iterator`, 909
- type of `multiset::const_iterator`, 918
- type of `multiset::iterator`, 918
- type of `ptrdiff_t`, 132, 481
- type of `regex_constants::error_type`, 1309
- type of `regex_constants::match_flag_type`, 1308
- type of `set::const_iterator`, 914
- type of `set::iterator`, 914
- type of `size_t`, 481
- type of `streamoff`, 729
- type of `streampos`, 729
- type of `syntax_option_type`, 1307
- type of `u16streampos`, 730

type of `u32streampos`, [731](#)
 type of `unordered_map::const_iterator`, [924](#)
 type of `unordered_map::const_local_iterator`,
 [924](#)
 type of `unordered_map::iterator`, [924](#)
 type of `unordered_map::local_iterator`, [924](#)
 type of `unordered_multimap::const_iterator`,
 [931](#)
 type of `unordered_multimap::const_local_iterator`,
 [931](#)
 type of `unordered_multimap::iterator`, [931](#)
 type of `unordered_multimap::local_iterator`,
 [931](#)
 type of `unordered_multiset::const_iterator`,
 [941](#)
 type of `unordered_multiset::const_local_iterator`,
 [941](#)
 type of `unordered_multiset::iterator`, [941](#)
 type of `unordered_multiset::local_iterator`,
 [941](#)
 type of `unordered_set::const_iterator`, [936](#)
 type of `unordered_set::const_local_iterator`,
 [936](#)
 type of `unordered_set::iterator`, [936](#)
 type of `unordered_set::local_iterator`, [936](#)
 type of `vector::const_iterator`, [893](#)
 type of `vector::iterator`, [893](#)
 type of `vector<bool>::const_iterator`, [898](#)
 type of `vector<bool>::iterator`, [898](#)
 type of `wstreampos`, [731](#)

 underlying type for enumeration, [176](#)

 value of bit-field that cannot represent
 assigned value, [138](#)
 incremented value, [113](#)
 initializer, [224](#)
 value of character literal outside range of
 corresponding type, [32](#)
 value of `ctype<char>::table_size`, [796](#)
 value of multicharacter literal, [32](#)
 value of `pow(0,0)`, [1060](#)
 value of result of inexact integer to floating-point
 conversion, [90](#)
 value of result of unsigned to signed conversion, [90](#)
 value of wide-character literal containing multiple
 characters, [32](#)

value of wide-character literal with single c-char
 that is not in execution wide-character
 set, [32](#)
 value representation of floating-point types, [80](#)
 value representation of pointer types, [81](#)
 values of a trivially copyable type, [77](#)
 values of various `ATOMIC_..._LOCK_FREE` macros,
 [1348](#)

 whether `<cfenv>` functions can be used to manage
 floating-point status, [1052](#)
 whether a given `atomic` type's operations are
 always lock free, [1348](#), [1350](#), [1352](#), [1354](#)
 whether an implementation has relaxed or strict
 pointer safety, [74](#)
 whether functions from Annex K of the C
 standard library are declared when C++
 headers are included, [458](#)
 whether `get_pointer_safety` returns
 `pointer_safety::relaxed` or
 `pointer_safety::preferred` if the
 implementation has relaxed pointer
 safety, [601](#)
 whether locale object is global or per-thread, [785](#)
 whether `pragma FENV_ACCESS` is supported, [1052](#)
 whether `rand` may introduce a data race, [1105](#)
 whether sequence pointers are copied by
 `basic_filebuf` move constructor, [1227](#)
 whether sequence pointers are copied by
 `basic_stringbuf` move constructor,
 [1216](#)
 whether source of translation units must be
 available to locate template definitions,
 [23](#)
 whether stack is unwound before calling
 `std::terminate()` when a `noexcept`
 specification is violated, [432](#)
 whether the lifetime of a parameter ends when the
 callee returns or at the end of the
 enclosing full-expression, [110](#)
 whether the thread that executes `main` and the
 threads created by `std::thread` provide
 concurrent forward progress guarantees,
 [20](#)
 whether `time_get::do_get_year` accepts
 two-digit year numbers, [816](#)
 whether values are rounded or truncated to the
 required precision when converting
 between `time_t` values and `time_point`
 objects, [721](#)
 whether `variant` supports over-aligned types, [572](#)

which functions in the C++ standard library may
be recursively reentered, [475](#)
which scalar types have unique object
representations, [693](#)