

Introduction to Computer Networks

Flooding (§5.2.3)




David Wetherall (djw@uw.edu)

Professor of Computer Science & Engineering



UNIVERSITY *of* WASHINGTON

Topic

- How to broadcast a message to all nodes in the network with flooding
 - Simple mechanism, but inefficient




Flooding

- Rule used at each node:
 -  Sends an incoming message on to all other neighbors
 -  Remember the message so that it is only flood once
- Inefficient because one node may receive multiple copies of message


Flooding (2)

- Consider a flood from A; first reaches B via AB, E via AE




Flooding (3)

- Next B floods BC, BE, BF, BG, and E floods EB, EC, ED, EF




Flooding (4)

- C floods CD, CH; D floods DC; F floods FG; G floods GF



Flooding (5)


- H has no-one to flood ... and we're done



Flooding Details

- Remember message (to stop flood) using source and sequence number
 - So next message (with higher sequence number) will go through
- To make flooding reliable, use ARQ
 - So receiver acknowledges, and sender resends if needed

END



© 2013 D. Wetherall

Slide material from: TANENBAUM, ANDREW S.; WETHERALL, DAVID J., COMPUTER NETWORKS, 5th Edition, © 2011.
Electronically reproduced by permission of Pearson Education, Inc., Upper Saddle River, New Jersey