

**Classe 95** has an eye-catching, futuristic design and is made from tough materials, such as stainless steel and aluminium, so it's packed with character.

Shock-absorbing side panels guarantee a sturdy machine that's practical to use. Available with 2, 3 and 4 groups



The soft-touch button control makes starting and stopping the machine while dispensing extremely effortless and easy.



Classe 9S is fitted with side bumpers that absorb any knocks or bumps. Functionality and an incredibly sturdy design are the distinctive hallmarks of the new Classe 9S.



The YouSteam manual steam control heats and froths milk. The extremely easy to use ergonomic steam wand guarantees perfect milk foam of the finest quality every time, so you can serve an impeccable cappuccino (on demand).



Classe 9S has an ergonomic lighting system in the work area to make the barista's job easier plus chrome group covers and all the distinctive stylish accessories from the Rancilio range.

Stunning lights on the steel side

panels and the floating front panel

accentuate the design, lending the machine a strikingly elegant yet

bold and trendy look.







Classe 95 - 3 groups - front view



Classe 95 - 3 groups - rear view



Classe 95 - 2 groups - side view

# Classe 95

# SS

# **Technical Features**

independent heat exchangers
electric heating
built-in volumetric pump
pump pressure gauge
boiler pressure gauge
electronic water level control
boiler pressure control with pressurestat
230 V brew heads
low-voltage dispensing controls (24 V)
LED lights illuminate the work area plus stylish lateral lighting

# Standard features, accessories

**STANDARD FEATURES:** 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 hot water dispenser, coffee tamper, measuring scoop and cleaning discs, levelling feet

ACCESSORIES: DP automatic or manual water softener, MD dosing grinder

#### Materials

aluminium and stainless steel body

#### **Technical Data**

#### 2 GROUPS

dimensions (w×D×H)		weight	boiler
29.5×21.3×20.6 in (750×540×523 mm)		145.5 lb (66 kg)	11 I (2.4 gal <sub>uk</sub> )
boiler power	voltage		frequency
3,200 W (120 V) - 4,300 W	120 V / 220-240 V / 380-415 V (3N)		50/60 Hz

## 3 GROUPS

dimensions (wxDxH)	mm)	<b>weight</b>	<b>boiler</b>
39.0×21.3×20.6 in (990×540×523		174.2 lb (79 kg)	16 I (3.5 gal <sub>uk</sub> )
<b>boiler power</b>	<b>voltage</b>	415 V (3N)	frequency
6,000 W	220-240 V / 380-		50/60 Hz

### 4 GROUPS

dimensions (wърън) 48.3×21.3×20.6 in (1230×540×523 mm)		<b>weight</b> 211.6 lb (96 kg)	boiler 22 I (4.8 gal <sub>uk</sub> )
boiler power	voltage	voltage	
6,000 W	220-240 V / 38	220-240 V / 380-415 V (3N)	

## Standard

















Ergonomic work surface



### On demand















