

8S

RANCILIO

coffeeing the World



CLASSE 8 S


Formal purism

The semi-automatic control of this version makes it an extremely simple machine to use and reliable in all situations.

1 C-LEVER (Rancilio Patent) The new steam valve with a special control knob and ergonomic design is complete with open-stay and open-close functions. The valve has a very short travel distance, and is operated by rotating it just 25°. Turning it upwards, it opens and remains in this position. Turned downwards, it automatically closes when released. Rapidity, precision and ergonomics: maximum user comfort for daily tasks.

2 GRID SYSTEM To make cleaning and maintenance easier, Rancilio has equipped all its products with a revolutionary work surface. Support grids come in a scratchproof polymer, with an efficient liquid collection system that keeps the work surface clean and protects cups against unsightly marks left by drops of coffee. The grids can be removed for washing in a dishwasher. Rancilio quality also means attention to details.

3 SPACE SAVER (Optional) Extended sides can be easily removed for space saving needs.



www.rancilio.com

Technical Features

independent heat exchangers

electric heating

incorporated volumetric pump

boiler pressure gauge

automatic water level control

boiler pressure control with pressure stat

200 V – 240 V dispensing controls

housing in stainless steel

Endowments, accessories

ENDOWMENTS: 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 hot water dispenser programmable for dosage time, coffee tamper, measuring scoop and washing disks, foot extensions.

ACCESSORIES: DP automatic or manual water softener, MD dosing grinder, interchangeable sides.

Colors

stainless steel

Technical Data

1 GROUP

dimensions (wxdxh)	weight	boiler (lt)	Hz
27.1(22.4)* x 19.6 x 19.2 inches	116.8 Lb	5	50/60
boiler power	voltage		
3200 W (120V) - 3000W	120 / 220-240 / 380-415 3N		

2 GROUPS

dimensions (wxdxh)	weight	boiler (lt)	Hz
33.4(28.7)* x 19.6 x 19.2 inches	167.5 Lb	11	50/60
boiler power	voltage		
3200 W (120V) - 6000W	120 / 220-240 / 380-415 3N		

3 GROUPS

dimensions (wxdxh)	weight	boiler (lt)	Hz
42.9(38.1)* x 19.6 x 19.2 inches	207.2 Lb	16	50/60
boiler power	voltage		
6000 W	220-240 / 380-415 3N		

4 GROUPS

dimensions (wxdxh)	weight	boiler (lt)	Hz
52.3(47.6)* x 19.6 x 19.2 inches	246.9 Lb	22	50/60
boiler power	voltage		
6000 W	220-240 / 380-415 3N		

*Without side extensions, decrease the total width by 5"

Standard



Ergonomic steam control

On demand



Pod and Capsule Adaptor

